Learning decouples accuracy and reaction time for rapid decisions in a transitive inference task

Abbreviated Title: Diffusion modeling of rapid decisions in transitive inference

Fabian Munoz[1,2], Greg Jensen[3], Maxwell Shinn[4], Yelda Alkan[1,2], John D. Murray[5], Herbert S. Terrace[6], Vincent P. Ferrera[*,1,2,7,8]

1. Department of Neuroscience, Columbia University Medical Center, New York, NY, 10032,

2. Zuckerman Mind Brain Behavior Institute, Columbia University, New York, NY, 10027

3. Reed College, Portland, OR, 97202

4. UCL Queen Square Institute of Neurology, University College London, London WC1E 6BT, UK

5. Department of Psychology, Dartmouth University, Hanover, NH 03755

6. Department of Psychology, Columbia University, New York, NY 10027

7. Department of Psychiatry, Columbia University Medical Center, New York, NY, 10032

8. Kavli Institute for Brain Sciences, Columbia University, New York, NY, 10027

*Corresponding author email address: vpf3@cumc.columbia.edu

Keywords: sequential sampling, drift-diffusion model, drift rate, collapsing boundary, leak

Abstract

The accumulation of evidence over time formalized in the drift diffusion model (DDM), has become one of the most prevalent models of deliberative decision-making. To better understand the role of latent variables during a serial learning task, in which decisions were made rapidly and did not show typical accuracy and response time patterns, we fit behavioral data with a DDM using PyDDM (Shinn et al., 2020). We trained macaque monkeys (N = 3) on a transitive inference transfer task in which they learned the implied order in a ranked list of 7 novel pictures in each behavioral session, indicating their choices by making saccadic eye movements. They reliably learned each new list order within 200-300 trials with asymptotic accuracy of around 80-90% correct. Their responses showed a symbolic distance effect, with 60% accuracy for adjacent list items and 90% accuracy for the largest symbolic distance. Although performance accuracy improved with learning and symbolic distance, reaction times were nearly constant. Nevertheless, accuracy and reaction time were well fit by the generalized drift-diffusion model. The fits were achieved by simultaneously increasing both the evidence accumulation rate and a collapsing bound to capture the shape of the reaction time distributions. These results indicate that decision-making during learning and transfer in a TI task may be characterized by a "variable collapsing bound" DDM.

Introduction

Perceptual decision-making is often characterized as a process of deliberative evidence accumulation. Such models provide a bridge linking behavior to neurophysiology. A well-studied neuro-computational paradigm for decision-making is the drift-diffusion model (DDM, Ratcliff 1978), which derives from the statistical theory of sequential sampling (Wald, 1945). Drift-diffusion models a process that repeatedly samples the relative likelihood of each decision alternative until sufficient evidence supports making a choice with a given level of accuracy. These models therefore provide an explanatory framework for the frequently observed empirical relationship between performance accuracy and reaction time.

For many two-alternative choice tasks in nonhuman primates (NHP), in which response times often extend to a full second or longer, it is usually found that response times are inversely correlated with stimulus strength for both dynamic (Roitman & Shadlen 2002) and static stimuli (Ratcliff et al., 2003). These response times also correspond to the temporal evolution of neural activity in the parietal (Roitman & Shadlen 2002), prefrontal cortex (Kim & Shadlen 1999, Kiani et al., 2014), and in the superior colliculus (Jun et al., 2021). The relationship between behavioral and neural dynamics has been central to the development of computational models of perceptual decision-making.

There is a growing recognition that decision processes occur on multiple time scales (Murray et al., 2014, Soltani et al., 2021), including continuous decisions (Yoo et al., 2021). Rapid decisions are of particular interest due to their importance in natural environments where decisions are made under considerable time pressure and survival is often at

65   stake. Some studies have reported behavioral evidence of oculomotor decisions with average

66   response times in the range of 200-300 msec and neural activity in FEF differentiating target

67   location in that time frame (Cohen et al., 2010; Stanford et al., 2010; Shankar et al 2011)

68   Transitive inference (TI) tests the ability to learn and generalize about relationships that

obey the law of transitivity (that is, if A>B and B>C, then it follows that A>C). In the

current study, monkeys performed a TI task in which, in each behavioral session, they learned

the implicit order in a novel set of images during pairwise presentations. While accuracy

improved with learning, choice reaction times remained constant and short, even though

monkeys were under little time pressure. This behavior is distinct from other perceptual tasks

where reaction times tend to decrease with increasing accuracy. TI also differs from other

perceptual tasks in that variations in accuracy are not directly related to the physical properties

of the stimulus but to variables implicit to the task demands. For example, "symbolic distance"

is the difference between the implicit ranks of items (so, given an order ABC, the pair AB has a

symbolic distance of 1, whereas AC has a distance of 2), and is a strong predictor of response

accuracy. The differences between the TI task and other perceptual tasks led us to ask if the

DDM framework was compatible with behavior (accuracy and reaction times) measured during

TI learning, and thus whether rapid decisions share common characteristics and mechanisms

with more deliberative decision processes.

83   We tested this by fitting the data with a generalized drift diffusion model using PyDDM

84   (Shinn et al. 2020). The results suggest that both the rate of evidence accumulation (drift rate)

85   and the amount of accumulated evidence needed to initiate a response (boundary position) vary

86 with learning and with symbolic distance. These results contrast with most other tasks which

87 can be fit by varying drift rate while accumulating evidence to a constant boundary.

Methods

Subjects

Subjects were three male rhesus macaques (F, H, and L), 13-14 years old and weighing

8-10 kg at time of experiment. The research was conducted in accordance with U.S. Department

of Health and Human Services (National Institutes of Health) guidelines for the care and use of

laboratory animals and was approved by the Institutional Animal Care and Use Committee at

Columbia University and the New York State Psychiatric Institute. Monkeys were prepared for

experiments by surgical implantation of a post for head restraint and a recording chamber to

give access to prefrontal cortex. All surgery was performed under general anesthesia (isoflurane

1-3%) and aseptic conditions. Subjects had prior experience performing transitive inference tasks

(Jensen et al. 2015).

Visual Stimuli and Eye Movements

The subjects were seated in an upright primate chair during the experiment and

responded to visual stimuli by making saccadic eye movements. Stimuli were generated and

controlled by a CRS VSG2/3F video frame buffer and displayed on a CRT monitor with a

resolution of 1280 x 1024 pixels at 60 Hz. Viewing distance was 60 cm.

Visual stimuli consisted of 140-by-130 pixel color photographs (7° by 8° visual angle) and

small squares that served as fixation and eye movement targets. To control the retinal position

of visual stimuli, monkeys were required to maintain fixation while the stimuli were presented.

The fixation point was a small red square (0.5° visual angle).

Eye position was recorded using a monocular scleral search coil (CNC Engineering,

Seattle WA) and digitized at a rate of 1 kHz (Judge et al. 1980). Subjects expressed choices by

making eye movements from the central fixation point to peripheral target stimuli. Eye velocity

was computed offline by convolving eye position with a digital filter. The filter was constructed

by taking the first derivative of a temporal Gaussian, $G(t)$, such that $\frac{dG}{dt} = -k \cdot t \cdot exp\left(\frac{t^2}{\tau^2}\right)$,

where $\tau = 8$ msec and k is a constant that sets the filter gain to 1.0. This filter does not

introduce a time shift between the position input and velocity output, but adds temporal

uncertainty to the velocity estimates. Horizontal and vertical eye velocities ($h'(t)$ and $v'(t)$,

respectively) were combined to estimate radial eye speed $r'(t)$ using the formula $r'(t) =$

$\sqrt{h'(t)^2 + v'(t)^2}$.

Transitive Inference Task

Prior to the beginning of each behavioral session, a set of 7 photographs never before

presented to the subjects was selected from a database of over 2500 images. A different set of

images was used for each behavioral session. These stimuli were randomly assigned a unique

rank, indicated by the letters A thru G, to create an ordered list (**Fig. 1A**). No explicit

information about stimulus rank was presented to the subjects. That is, the rank assigned to

each stimulus was never displayed, nor was there any information about serial order conveyed

by the spatial or temporal presentation of the stimuli.

Figure 1. **Transitive Inference Transfer Task.** This task tests subjects' ability to learn the implied serial order of a set of images from pairwise presentations. **A.** Set of 7 randomly selected images arranged in an ordered list (A>B>C>D>E>F>G). A novel set of images was used for each behavioral session. **B.** Choice trials with spatial position counterbalanced. **C.** Adjacent pairs used for the training phase of the session **D.** All pairs used for the transfer phase.

On each trial (**Fig. 1B**), the subject first fixated a small target in the center of the

screen. Following a random delay (0.4 sec to 1.2 sec, positively skewed with a mean of 0.5 sec),

the fixation point was extinguished, and two stimuli appeared equidistant from the center of the

screen in opposite directions. To receive a reward, subjects had to select the stimulus with the

lower rank by making a saccadic eye movement to the selected stimulus within 1.5 sec of

stimulus onset and fixating for a random interval (0.4 to 0.6 sec, uniformly distributed). When

this interval elapsed, auditory feedback was delivered indicating that the response was either

correct (high tone, 880 Hz) and would be rewarded, or was incorrect (low tone, 440 Hz). To

receive the reward on correct trials, subjects had to maintain fixation for another interval (0.35

to 0.65 sec, uniformly distributed), after which the screen went dark and fluid rewards (juice or

water drops) were delivered through a sipper tube.

In the training phase of the task, adjacent pairs of stimuli were presented. Each pair

comprised two stimuli whose ordinal positions were adjacent in the list (A/B, B/C, C/D, etc,

Fig. 1C). To receive a reward, the subject was required to make a saccadic eye movement to

the stimulus with the lower rank (e.g. A from A/B). For a 7-item list, there are 6 adjacent

pairs. With positional counterbalancing, this resulted in training blocks that were 12 trials in

length. This phase lasted up to 20 blocks (i.e. 240 trials in total).

In the testing phase of the task, all possible combinations of the 7 items were presented

(**Fig. 1D**). The subjects were still required to saccade to the lower ranking stimulus. This

phase tested the subjects' ability to transfer knowledge about the list order gained during the

adjacent pairs phase to novel, non-adjacent pairs. For a 7-item list, there are 21 possible pairs

(6 adjacent, 15 non-adjacent). With counterbalancing of the stimulus positions, this resulted in

blocks of 42 trials. This phase generally lasted for 5-10 blocks (240-420 trials).

Each pair of stimuli could be identified in terms of the ranks of the individual stimuli

they included. Pairs could be also described in terms of "symbolic distance," a metric that is

calculated by taking the difference between the individual stimulus ranks (D'Amato & Colombo

1990). For example, since the pair B/C consists of items that are adjacent in the list (i.e. ranks

2 and 3, respectively), the symbolic distance is 1, while the pair A/G (ranks 1 and 7) has a

symbolic distance of 6.

Figure 2. DDM Simulations. Top: Standard model with constant bound and no leak. Left: red traces represent weaker signal strengths, blue is stronger signal. Center: reaction time histograms for correct (green) and error (red) trials for a single, moderate signal strength. Right: Accuracy (percent correct) and reaction time as a function of signal strength. **Middle:** Standard model with leak. **Bottom:** Collapsing bound model

Generalized Drift Diffusion Modeling (GDDM)

Behavioral data were fit to a Generalized DDM using the PyDDM toolbox (Shinn et al.,

2020).   We used several different approaches to understand the effect of each variable in the

GDDM model. In all approaches, the data to be fit were reaction time and accuracy segregated

by symbolic distance or trial block. The two conditions (symbolic distance or trial block) were

fit separately. Parameters were estimated for each NHP subject individually.

In the first, "standard," approach, a simple version of the GDDM was implemented with

four parameters: drift rate (rate of evidence accumulation), boundary level (amount of

accumulated evidence required for a decision), noise (instantaneous variability in drift rate), and

non-decision time. The time evolution of the decision variable, x (accumulated evidence), is

given by:

Eqn 1. $dx = [drift * condition] * dt + dW$

"*Drift*" is the drift rate parameter. "*Condition*" is either symbolic distance or trial block,

depending on how the data are segregated, and is coded as an integer; [1…,6] for symbolic

distance or [1,…,8] for trial block. "*W*" is the momentary noise represented as a Weiner process

with standard deviation = 1. We fixed the noise parameters to $mu = 0$ and $sigma = 1.0$ to

avoid redundancy with the boundary height parameter as scaling noise variability is equivalent

to scaling the boundary height. The time resolution (dt) was 10 msec and the overall duration

was 1.0 sec.

In this approach, the fitting algorithm searched for a single set of parameters (drift,

bound, and non-decision time) that fit the data within each condition. All parameters except for

noise were allowed to vary freely within a wide range (**Table 1**). The actual drift rate is the

product of the scalar drift parameter and the condition index, and therefore varied linearly with

condition. The boundary was constant both in time, and over conditions (symbolic distance or

trial block). The same parameter ranges were used for all NHP and all conditions.

In the standard approach, there was no loss of evidence over time. However, evidence

integration can be imperfect. Thus, in a second, "leaky integration" approach, imperfect

integration was modeled by adding a leak term to the standard model:

Eqn 2. $\qquad\qquad dx = [drift * condition + leak * x] * dt + dW$

"*Leak*" is a constant that multiplies accumulated evidence (x) at each moment. If the leak term

is negative, the evidence tends to decay exponentially toward zero. When the leak is positive, it

acts like a gain factor that causes the evidence to increase exponentially (unstable integration).

In the two approaches above, the decision boundary was constant over the time when

evidence was being accumulated. To test the effect of allowing the boundary to change over

time, a "collapsing bound" approach was tested. In this approach, the bound collapsed

exponentially as a function of time. This introduced a sixth parameter, tau, the collapse rate.

In this approach, the equation for momentary evidence is the same as **Eqn 1**, but the time-

dependence of the boundary is given by:

Eqn 3. $\qquad\qquad bound = B_0 * exp(-t/tau)$

Where B_0 is the initial boundary level at $t = 0$. This model was tested both with a leak

parameter (using **Eqn 1** for evidence accumulation) and without a leak (using **Eqn 2**).

To understand how each model parameter affects performance, simulations of the

standard, leaky integration, and collapsing bound models are shown in **Fig 2**. The left panel

illustrates the time evolution of accumulated evidence for range of drift rates (signal strength).

The center panel shows the reaction time histograms for correct and error trials. The right

panel shows accuracy and reaction time. Non-decision time was set to zero in all simulations.

For the standard model (**Fig 2**, top row), low signal strength is associated with chance

performance accuracy and long reaction times. The addition of a positive leak term (**Fig 2**,

middle row) restricts the range of reaction times by speeding up evidence accumulation, but also

reduces accuracy for moderate signal strengths. The collapsing bound model (**Fig 2**, bottom

row) performs similarly to the leaky integration model but is more effective in reducing long

reaction times and produces more symmetric reaction time distributions.

Table 1. PyDDM parameter ranges.						
Range	**Drift**	**Boundary**	**Noise**	**Leak** **(if present)**	**Tau**	**Non-** **decision**
Standard model						
min	0.0	0.1	1.0	0	-	50 msec
max	10.0	10.0	1.0	100	-	400 msec
Collapsing bound model						
min	0.0	0.3	1.0	-5.0	0.01	50 msec
max	5.0	3.0	1.0	5.0	10	400 msec

Results

Behavioral Performance

Behavioral performance was quantified in terms of accuracy (percent correct) and

response time (time from stimulus onset until choice saccade onset). A total of 273 behavioral

sessions were recorded (F: 85, H: 98, L: 90). Each session started with a novel set of pictures

that were arranged into a list by assigning a rank order to each picture (**Fig. 1A**). The ranking

was initially unknown to the subject but was learned over the course of the session.

Reaction times (RT) as a function of trial number for all sessions completed by NHP H

are shown in **Fig. 3A**. The three phases of the task are color coded (single target trials in gray,

adjacent pairs in blue, all pairs in magenta). There is an abrupt shift in the RT distribution

(**Fig. 3B**) at the transition from single stimuli (median RT 192 msec) to stimulus pairs (median

RT 270 to 275 msec). Adjacent-pair (training phase) and all-pair (testing phase) trials were

grouped into blocks of 50 consecutive trials to obtain robust estimates of RT (**Fig. 3A**). The

shape and median value of the RT distributions remained constant across trial blocks. The

distributions were also similar in shape for correct (**Fig 3B** solid lines) and incorrect (dashed

lines) trials, and for adjacent (**Fig. 3B,** blue lines) and non-adjacent pairs (magenta lines).

The effect of learning on accuracy and RT for this NHP is shown in **Fig. 3C**. During

adjacent pair training, logistic regression showed a significant effect of trial number on accuracy

for all NHPs (F: $p = 0.03$, df = 15,206; H: $p < 0.0001$, df = 16,012; L: $p < 0.0001$, df = 6658).

Figure 3. **Behavioral Performance on TI transfer task. A.** Reaction time vs trial number for NHP H. The colors represent the three task phases (blue – presentation of single items, cyan – adjacent pairs, red – all pairs). **B.** Reaction time histograms. Colors as in A. For choice trials, solid lines are correct responses and dashed lines are incorrect. **C.** Accuracy (green) and reaction time (gray/black) during learning. **D.** Accuracy (red) and reaction time (grey/black) as a function of symbolic distance.

Logistic regression coefficients for accuracy versus trial number were similar for all NHP (0.096

for NHP F, 0.07 for NHP H, 0.11 for NHP L). The effect of trial number on RT, as assessed by

linear regression, was also significant ($p < 0.0001$ for all NHPs). However, the slope of the

regression was shallow, amounting to an increase of $5 - 7$ msec for every 100 trials.

During all-pairs testing, the relationship between trial number and accuracy remained

significant ($p < 0.0001$ for all NHP) and the RT trend turned slightly negative (-0.5 msec per

100 trials) and was significant for 2 NHP ($p < 0.002$). However, this change was negative for

one NHP (H: decrease of 1.6 ms/400 trials), and positive for the other (L: increase of 4 ms/400

trials).

Symbolic distance (SD, the difference in rank between the two stimuli in a pair) had a

strong effect on accuracy (**Fig. 3D**). Logistic regression coefficients for SD were consistent

across NHP (0.35 for NHP F, 0.28 NHP H, 0.22 for NHP L). There was a small but significant

reduction in RT as SD increased for both NHPs (F: slope = -1.5 msec, $p < 0.0001$; H: -2.9 msec,

$p < 0.0001$; L: -0.33 msec, $p = 0.02$). The results overall indicate a strong effect of trial number

and SD on performance accuracy, but little effect on RTs.

Speed-accuracy trade-off

Although there was not a clear relationship between accuracy and choice reaction time

when data were combined over sessions, a more fine-grained analysis might reveal subtler

relationships. We therefore calculated the residual accuracy and average reaction time in each

block of 50 consecutive trials during the adjacent-pair training and all-pairs testing phases of the

task. "Residual" is here defined as the accuracy or average reaction time within each block of

50 trials normalized by subtracting the averages of each of those measures calculated over all

choice trials for the entire session. By accounting for the session-to-session variability, this

produced an estimate of the change in accuracy per unit change in reaction time that could be

combined across sessions.

Figs. 4A,B,C show an improvement in accuracy with lengthening reaction times during

the training phase of the task (first 250 choice trials of each session) for all three NHP. Each

data point represents a single 50-trial block from one session. There was an average increase in

performance ranging from 0.24 to 0.43 percent correct for every additional millisecond of

reaction time. The correlation between accuracy and RT was significant for each NHP. During

Figure 4. Speed-accuracy trade-off. A,B,C. Improvement in accuracy v. increase in RT during training phase for each NHP. 'm' is the linear regression slope, 'r²' is the coefficient of determination, 'p' is the significance of the correlation (Pearson), and 'n' is the number of 50-trial blocks per session times the number of sessions. The color gradient indicates trial blocks that were earlier in training (red) vs. later (blue). **D,E,F.** All-pairs testing phase.

260 the subsequent testing phase (the first 250 trials after end of training)(**Fig. 4 D,E,F**), no

261 significant relationship was found.

Figure 5. Speed-accuracy trade-off for trials grouped by symbolic distance. A,B,C.
Decrement in accuracy v. increase in RT during testing phase for each NHP. 'm' is the linear regression
slope, 'r²' is the coefficient of determination, 'p' is the significance of the correlation (Pearson), and 'n' is
the number of symbolic distances times the number of sessions. The color gradient indicates smaller
(green) vs. larger (magenta) symbolic distances.

During the all-pairs testing phase, it is also possible to sort trials into six groups by

symbolic distance (SD), rather than trial block. When this was done, a significant negative

relationship was found between the change in accuracy and increasing reaction time (**Fig. 5**

A,B,C); trials with larger SD had higher accuracy and shorter RTs.

PyDDM Results

Choice reaction times during the TI transfer task were generally under 300 msec even

though subjects were allowed up to 1500 msec after stimulus onset to respond by making a

saccadic eye movement to the target or distractor. Choice RTs averaged only 35 msec longer

than simple RTs for NHP F (215 vs. 180 msec median RT), 85 msec for NHP H (275 vs. 190

msec), and 30 msec for NHP L (211 vs. 181 msec). RTs remained nearly constant despite learning-

related improvements in accuracy. RTs were also constant across symbolic distance despite large

differences in accuracy. Drift diffusion models (DDMs) with constant bounds and variable drift

rate typically show increases in accuracy that are accompanied by shorter reaction times. As the

current results did not show this pattern, they raise the question of whether DDMs can fit the

behavior exhibited by NHP during the transitive inference task and thus shed light on how

decisions are made during TI learning.

Figure 6. Drift Diffusion model fits for symbolic distance. Data from all sessions for NHP L
segregated by symbolic distance (SD). Green dots are reaction time distributions for correct trials, red dots
for error trials. Vertical red and green lines indicate the median RT for each distribution. Green and red
curves are fits for correct and error trials, respectively, using the standard model. The correlation between
the fits and the data are shown in red and green text. Blue and magenta curves and text are fits obtained
with the leaky integration model. Black and grey curves and text are fits obtained with the collapsing
bound model.

278   To test this, we first fit a generalized DDM with four parameters (drift rate, noise,

279   boundary, and non-decision time, see Methods) to the current behavioral data using the

Table 2. PyDDM fitted parameters for each model, NHP, and condition. For "condition," SD is symbolic distance, TB is trial block. Model 1 is the standard model with constant bound and no leak. Model 2 is the standard model with leak. Model 3 is the collapsing bound model with no leak. Model 4 is the collapsing bound with leak. BIC is Bayesian information criterion. VAC is variance accounted for (r^2).

NHP - Condition	Model	Drift	Bound	Noise	Leak	Tau	Non-decision	BIC	VAC
NHP F - SD	1	0.68	0.30	1.0	-	-	152 msec	-73232	0.78
NHP F - SD	2	0.99	9.0	1.0	43.1	-	105 msec	-85582	0.96
NHP F - SD	3	0.55	0.58	1.0	-	0.15	122 msec	-83621	0.93
NHP F - SD	4	0.50	0.58	1.0	-4.9	0.14	118 msec	-83706	0.93
NHP H - SD	1	0.61	0.35	1.0	-	-	184 msec	-39867	0.75
NHP H - SD	2	0.83	8.6	1.0	29.8	-	116 msec	-52508	0.96
NHP H - SD	3	0.50	0.88	1.0	-	0.15	126 msec	-48531	0.91
NHP H - SD	4	0.45	0.92	1.0	-4.7	0.15	110 msec	-48737	0.92
NHP L - SD	1	0.57	0.30	1.0	-	-	154 msec	-103034	0.73
NHP L - SD	2	0.93	8.2	1.0	69.4	-	133 msec	-120970	0.97
NHP L - SD	3	0.47	0.46	1.0	-	0.15	137 msec	-118035	0.92
NHP L - SD	4	0.47	0.47	1.0	-3.9	0.10	140 msec	-118598	0.93
NHP F - TB	1	0.29	0.30	1.0	-	-	151 msec	-54357	0.79
NHP F - TB	2	0.41	9.9	1.0	44.5	-	100 msec	-64415	0.96
NHP F - TB	3	0.25	0.65	1.0	-	0.15	116 msec	-57016	0.95
NHP F - TB	4	0.50	0.58	1.0	-4.9	0.14	118 msec	-83706	0.95
NHP H - TB	1	0.27	0.35	1.0	-	-	187 msec	-34058	0.74
NHP H - TB	2	0.36	9.5	1.0	28.6	-	105 msec	-45301	0.96
NHP H - TB	3	0.23	0.99	1.0	-	0.15	125 msec	-38285	0.91
NHP H - TB	4	0.21	0.92	1.0	-4.8	0.15	107 msec	-38316	0.91
NHP L - TB	1	0.28	0.25	1.0	-	-	156 msec	-76581	0.73
NHP L - TB	2	0.46	8.2	1.0	71.2	-	133 msec	-90833	0.96
NHP L - TB	3	0.22	0.86	1.0	-	0.10	116 msec	-80666	0.93
NHP L - TB	4	0.24	0.54	1.0	-3.7	0.10	132 msec	-80857	0.93

PyDDM package (Shinn et al. 2020). An example of the PyDDM fits for data segregated by SD

and outcome (green = correct, red = error) for NHP L are shown in **Fig. 6** (the fits for all NHP

are shown in supplemental **Figs. S1** and **S2**). The fits for the standard model are shown as the

green and red curves. These fits were relatively poor and this was confirmed by the variance

accounted for by the standard model (VAC, measured by r^2), which was generally less than

80%. The fitted parameter values are shown in **Table 2**.

To estimate the effect of within-session learning on model fits, the data were grouped

into 8 blocks of 50 consecutive trials spanning the first 400 trials of paired presentations during

which accuracy improved from chance levels to roughly 80% correct. The variance accounted

for (r^2) was generally < 80% for each trial block condition for all NHP (**Fig S2**). These results

indicate that a DDM with constant bounds and no leak term provided a poor fit to data in

which accuracy improves across conditions while RTs remain relatively constant. We next

explore the role of the different model parameters by testing variants of the standard DDM.

<u>Effect of Drift Rate.</u> The drift term captures whether the rate of evidence accumulation

is sensitive to the stimulus conditions, as indexed by symbolic distance, or stage of learning, as

indexed by trial block. The fitted parameters indicate an increased rate of evidence

accumulation (drift rate) as a function of both SD and trial block (TB). This is expected as

drift rate has a strong effect on accuracy. The drift rate estimates were similar across NHP.

However, there was a factor of 2 difference between conditions, most likely due to the fact that

performance accuracy reached higher asymptotic levels as a function of symbolic distance (**Fig.**

3D) than it did for trial block (**Fig. 3C**).

<u>Effect of Leak.</u> The leak term modulates the rate of evidence accumulation in

proportion to the amount of evidence accumulated at any given time. It can be thought of as a

gain control that dampens or enhances the effect of drift rate and has a more powerful effect as

more evidence is accumulated. Adding a leak term to the standard model improved the fits, as

shown by the blue and magenta curves (**Fig. 6**). These fits were substantially better than the

standard non-leaky model, resulting in VACs in the range of 88% to 97%. The Bayesian

Information Criterion (BIC) scores were also better (**Table 2**).

The leak term either slows or accelerates the rate of evidence accumulation depending on

its sign. For the standard model, the fitted leak term was positive, indicating unstable

integration. The magnitude of the leak term was also several times larger than any other fitted

parameter.

Effect of Boundary. The initial boundary level sets the amount of accumulated evidence

needed to render a decision, whereas the collapse rate tests if that amount of evidence is stable

over time. The collapsing bound model with no leak provided fits that were as good as the

standard (constant bound) model with leaky integration, as measured by VAC and BIC.

Adding a leak term to the collapsing bound model improved the fits but only by a small amount

(**Table 2**). When a leak term is included in the collapsing bound model, the fitted values were

negative, indicating true leaky integration (loss of evidence over time). This contrasts with the

 function of the leak parameter in the constant bound model, which was positive, indicative of

 unstable integration.

Figure 7. Effect of drift rate vs. leak and boundary. A-D: Accuracy (circles) and model fits (lines) for 3 NHP (**A**). Drift rate varies as a function of symbolic distance (**B**), while leak (**C**) and boundary are fixed. **E-H**. Accuracy and model fits (**E**) where drift rate (**F**) was fixed and leak (**G**) and boundary (**H**) were allowed to vary.

While leaky integration and collapsing bounds affect the shape of the RT distributions,

they cannot fully account for performance accuracy when drift rate is held constant. To

demonstrate, we compared constant-bound models with 5-parameters (drift rate, leak,

boundary, non-decision time, noise) in which either the drift rate was allowed to vary with

symbolic distance and the leak and boundary were constant (**Fig. 7 A-D**), or the drift rate was

fixed at a moderate value and the leak and boundary were allowed to vary (**Fig 7. E-H**).

Allowing drift rate to vary linearly with SD yielded reasonable fits to the data (**Fig. 7A**) when

leak (**Fig. 7C**) and boundary (**Fig. 7D**) were constant across SD. When drift rate was fixed

(**Fig. 7F**), the fits did not match the change in performance accuracy (**Fig. 7E**), even though

leak (**Fig. 7G**) and boundary (**Fig. 7H**) were allowed to vary over a range 10x greater than

that afforded to drift rate.

Effect of Non-decision Time. All NHP had non-decision times that were similar across

conditions. However, there were differences among the NHP. Non-decision times for NHP F

and L were on average 30-32 msec shorter than NHP H. It is of interest that the simple RTs

for NHP F and L had the same average (181 msec), while H had the longest simple RTs at 192

msec suggesting that simple RTs may be related to non-decision time.

Speed-accuracy trade-off. The modeling approaches considered so far have been

evaluated on the basis of their ability to fit average accuracy and reaction time data. We have

not yet considered the relationship between residual accuracy and reaction time (i.e. the speed-

accuracy trade-off) as shown in **Figs. 4** and **5**. The striking feature of these trade-offs is that

they have positive slope as a function of trial block during training and negative slope as a

function of symbolic distance during testing.

The standard DDM tends to produce a negative relationship between accuracy and

reaction time as indicated in **Fig. 2.** One way to turn this into a positive relationship is to

have a variable boundary. If the boundary height increases with signal strength, then accuracy

and reaction time can increase together. The relationship between boundary position and signal

strength that leads to increasing reaction times can be calculated analytically (Bogacz et al

2006, 2008). These calculations reveal that accuracy is related to the product of drift rate and

boundary position, while reaction time is more closely related to their ratio. **Fig. 8A** illustrates

Figure 8. Variable collapsing bound model. A. Initial boundary position increases with signal strength during training. **B.** Positive correlation between residual reaction time and accuracy. **C.** Initial boundary position stabilizes after training. **D.** Negative relationship between reaction time and accuracy during testing.

350   a "variable collapsing bound model" in which an increasing initial boundary position leads to

351   reaction times that increase with signal strength (**Fig. 8B**). When the initial boundary position

352   is fixed (**Fig. 8C**), reaction time decreases with signal strength leading to a negative

353   relationship between accuracy and reaction time (**Fig. 8D**).

Figure 9. Variable collapsing bound fitted to training and testing data. A. Initial boundary position fit independently for each training block for all 3 NHP. Solid symbols are parameters for a model with a leak term. Dashed lines are quadratic fits to these data. Open symbols and dotted lines are parameters and quadratic fits to a model without a leak term. **B.** Initial boundary position fit to each symbolic distance. Same conventions as **A**.

In the collapsing bound model, initial boundary position was constant across trial blocks.

We tested a version of the collapsing bound model in which initial boundary position was free to

vary in each trial block. In this case, the fitted initial boundary position tended to increase

during training for all 3 NHP (**Fig. 9A**). This was true whether there was a leak term included

in the model or not. When each symbolic distance was fit (**Fig. 9B**), the initial bound position

decreased when the leak term was included. Without the leak term, the bound position was

constant across symbolic distance.

Discussion

The transitive inference (TI) paradigm tests subjects' ability to learn the implied serial order of a set of pictorial stimuli without any explicit spatial or temporal cues. This is accomplished by presenting pairs of images drawn from a rank-ordered list of images and rewarding subjects for choosing the item that has the lower rank. When presented with a novel set of images, NHP subjects initially respond at chance levels, and then performance improves over the first 200-300 trials of training. Little is known about the mechanisms that underlie decision-making during TI learning. This can be assessed by analyzing performance accuracy and reaction time in the context of evidence accumulation models. In the current study, the improvement in performance was accompanied by a very modest reduction in response time. Choice reaction times were generally under 300 msec, and only 30 to 85 msec longer than simple reaction times.

Response accuracy also depended on the symbolic distance between each pair of images. Larger symbolic distances were associated with higher accuracy. However, there was only a small effect of symbolic distance on reaction time, consistent with a previous report from our lab (Munoz et al., 2020).

These results contrast with many studies of decision making (Roitman & Shadlen 2002, Ratcliff et al., 2003, Kim & Shadlen 1999, Kiani et al., 2014, Jun et al., 2021) in which choice RTs tend to be much longer (500-1000 msec), suggestive of a more deliberative decision process. Choice RTs in other studies have also been found to be inversely related to accuracy. This pattern of anti-covarying accuracy and RT has been taken as strong evidence for gradual

evidence accumulation as predicted by sequential sampling frameworks such as the drift

diffusion model.

The drift diffusion model allows for multiple modes of operation. The constant bound

mode is illustrated in **Fig. 2,** top row. This is perhaps the most common mode reported in

studies that provide support for evidence accumulation in decision-making. This mode can

result in extremely long reaction times when evidence is weak and accumulation is mostly

stochastic. If evidence is accumulating slowly, then there may be no advantage to a lengthy

accumulation period as the gain in performance will be small or non-existent. On the other

hand, when evidence is accumulating rapidly, increasing the boundary by a small amount may

increase performance dramatically with little additional time cost.

An alternative regime is one with a positive "leak" term (**Fig. 2,** middle row). When

this term is positive, it acts like a gain factor, resulting in unstable integration. To fit the

current data with a fixed bound, PyDDM found that a large gain term was needed. Thus,

evidence accumulation was dominated by the gain factor rather than by the drift rate. The

need for such a large gain factor calls into question the plausibility of a model with constant

bounds but highly unstable integration.

Another alternative is to allow the evidence boundary to collapse exponentially over time

(**Fig. 2**, bottom row). This approach also reduces long reaction times and makes the reaction

time histograms more symmetrical, which is in accord with the data. The collapsing bound

approach provided fits that were comparable to the constant bound with leak model. When a

leak term was added to the collapsing bound, the fitted leak was negative, indicating true leaky

integration. The fits were improved only slightly over the collapsing, no leak condition. Thus,

the collapsing bound model can fit the current data with or without a leak term. The collapsing

bound model provided excellent fits to the current data and seems the most plausible of the

various approaches compare in this study.

A closer look at the relationship between accuracy and reaction time (**Figs. 4 and 5**)

revealed a weak but significant positive correlation during the training phase of the task. In the

DDM, speed-accuracy trade-offs reflect the interplay of drift rate and boundary position. When

changes in accuracy are driven by changes in drift rate, increasing drift rate leads to higher

accuracy and shorter reaction times. When changes in accuracy are driven by changes in the

boundary, the opposite pattern can be seen – increasing the bound height leads to higher

accuracy and longer reaction time. It is therefore possible that, during learning, increases in

drift rate are accompanied by adjustments of the boundary height that allow subjects to gain

accuracy by increasing response time.

These observations led us to consider a hybrid "variable collapsing bound" model (**Fig.**

8). In the hybrid model, the collapsing boundary gradually increases during the training phase

of the task (**Fig. 8A**), leading to a positive correlation between accuracy and reaction time

(**Fig. 8B**). The boundary stabilizes during the testing phase (after learning) (**Fig. 8C**), giving

rise to a negative relationship between accuracy and reaction time (**Fig. 8D**), as seen in the

behavioral data when accuracy and reaction time are sorted by symbolic distance (**Fig. 5.**)

Conclusion

The drift diffusion model is often fit to data where accuracy and reaction time vary inversely. However, this class of model has the flexibility to characterize results that are less typical. Here, we show that it can be applied to a learning task where reaction times are nearly constant despite gains in accuracy. Accuracy improves through learning, in which case an exponentially collapsing boundary can be slowly adjusted as performance improves, in effect, gradually increasing the amount of evidence required as evidence begins to accumulate more rapidly with learning. Accuracy can also improve with internally computed variables, such as symbolic distance. Here, the collapsing boundary reduces changes in reaction time as accuracy improves. In both scenarios, decision-making is made more efficient, compared to the constant bound model, by taking advantage of an increasing rate of evidence accumulation during learning to increase accuracy with little cost in reaction time. When evidence is accumulating slowly, a collapsing boundary reduces the total amount of evidence required as little accuracy is gained by increasing the integration time.

Data availability

The datasets generated and/or analyzed during the current study are available from the corresponding author on request.

Competing interests

446 The authors declare they have no competing interests.

Acknowledgements

449 This study was supported by NIH R01-MH111703 (VPF and HST).

Author Contributions

452 The study was designed by FM, GJ, YA, VPF, and HST. Data were collected by FM and YA.

453 Data were analyzed by FM, GJ, MS, JDM and VPF. The manuscript was written by FM, GJ,

454 MS, and VPF.

456 Supplemental Figures

Figure S1. Drift Diffusion model fit for symbolic distance. Data from all sessions for all NHP segregated by trial block. Green dots are reaction time distributions for correct trials, red dots for error trials. Vertical lines indicate the median RT for each distribution. Green and red curves are PyDDM fits for the constant bound model. Blue and magenta curves are fits for the constant bound with leak model. Black and grey curves are fits for the collapsing bound model.

Figure S2. Drift Diffusion model fit for trial block. Data from all sessions for all NHP segregated by trial block. Green dots are reaction time distributions for correct trials, red dots for error trials. Vertical lines indicate the median RT for each distribution. Green and red curves are PyDDM fits for the constant bound model. Blue and magenta curves are fits for the constant bound with leak model. Black and grey curves are fits for the collapsing bound model.

References

1. Bogacz R, Brown E, Moehlis J, Holmes P, Cohen JD. The physics of optimal decision making: a formal analysis of models of performance in two-alternative forced-choice tasks. Psychol Rev. 2006 Oct;113(4):700-65. doi: 10.1037/0033-295X.113.4.700. PMID: 17014301.

2. Bogacz R, Wagenmakers E-J, Forstmann BU, Nieuwenhuis S (2008) The neural basis of the speed-accuracy trade-off. Trends in Neurosciences. 33(1):10-16

3. Cohen JY, Crowder EA, Heitz RP, Subraveti CR, Thompson KG, Woodman GF, Schall JD. Cooperation and competition among frontal eye field neurons during visual target selection. J Neurosci. 2010 Mar 3;30(9):3227-38. doi:

4.   Jensen G, Muñoz F, Alkan Y, Ferrera VP, Terrace HS. Implicit value updating explains

transitive inference performance: the betasort model. *PLOS Computational Biology*, *11*, e1004523.

(2015).

5.   Judge SJ, Richmond BJ, Chu FC. Implantation of magnetic search coils for measurement of eye

position: an improved method. *Vision Research*, *20*, 535-538. (1980).

6.   Jun EJ, Bautista AR, Nunez MD, Allen DC, Tak JH, Alvarez E, Basso MA. Causal role for the

primate superior colliculus in the computation of evidence for perceptual decisions. Nat Neurosci.

2021 Aug;24(8):1121-1131. doi: 10.1038/s41593-021-00878-6. Epub 2021 Jun 28. PMID: 34183869;

PMCID: PMC8338902.

7.   Kiani R, Cueva CJ, Reppas JB, Newsome WT. Dynamics of neural population responses in

prefrontal cortex indicate changes of mind on single trials. Curr Biol. 2014 Jul 7;24(13):1542-7.

doi: 10.1016/j.cub.2014.05.049. Epub 2014 Jun 19. PMID: 24954050; PMCID: PMC4191655.

8.   Kim JN, Shadlen MN. Neural correlates of a decision in the dorsolateral prefrontal cortex of the

macaque. Nat Neurosci. 1999 Feb;2(2):176-85. doi: 10.1038/5739. PMID: 10195203.

9.   Munoz, F., Jensen, G., Kennedy, B.C. *et al.* Learned Representation of Implied Serial Order in

Posterior Parietal Cortex. *Sci Rep* **10**, 9386 (2020). https://doi.org/10.1038/s41598-020-65838-9

10. Murray, J., Bernacchia, A., Freedman, D., Romo R, Wallis JD, Cai X, Padoa-Schioppa C,

Pasternak T, Seo H, Lee D, Wang X-J. A hierarchy of intrinsic timescales across primate

cortex. Nat Neurosci 17, 1661–1663 (2014). https://doi.org/10.1038/nn.3862

11. Ratcliff, R. (1978). A theory of memory retrieval. *Psychological Review, 85*(2), 59–

108. https://doi.org/10.1037/0033-295X.85.2.59

12. Ratcliff R, Cherian A, Segraves M. A comparison of macaque behavior and superior colliculus

neuronal activity to predictions from models of two-choice decisions. J Neurophysiol. 2003

Sep;90(3):1392-407. doi: 10.1152/jn.01049.2002. Epub 2003 May 21. PMID: 12761282.

13. Roitman JD, Shadlen MN. Response of neurons in the lateral intraparietal area during a

combined visual discrimination reaction time task. J Neurosci. 2002 Nov 1;22(21):9475-89. doi:

10.1523/JNEUROSCI.22-21-09475.2002. PMID: 12417672; PMCID: PMC6758024.

14. Shankar S, Massoglia DP, Zhu D, Costello MG, Stanford TR, Salinas E. Tracking the temporal

evolution of a perceptual judgment using a compelled-response task. J Neurosci. 2011 Jun

8;31(23):8406-21. doi: 10.1523/JNEUROSCI.1419-11.2011. PMID: 21653845; PMCID:

PMC3134312.

15. Maxwell Shinn, Norman H Lam, John D Murray (2020) A flexible framework for simulating and

fitting generalized drift-diffusion models eLife 9:e56938

16. Soltani A, Murray JD, Seo H, Lee D. Timescales of Cognition in the Brain. Curr Opin Behav Sci.

2021 Oct;41:30-37. doi: 10.1016/j.cobeha.2021.03.003. Epub 2021 Mar 31. PMID: 34026949;

PMCID: PMC8136243.

17. Stanford, T., Shankar, S., Massoglia, D. *et al.* Perceptual decision making in less than 30

milliseconds. *Nat Neurosci* **13**, 379–385 (2010). https://doi.org/10.1038/nn.2485

18. Wald A (1945) Sequential tests of statistical hypotheses. Ann Math Statist. 16(2):117-186. Doi:

10.l1214/aoms/1177731118

19. Yoo SBM, Hayden BY, Pearson JM. Continuous decisions. Philos Trans R Soc Lond B Biol Sci.

2021 Mar;376(1819):20190664. doi: 10.1098/rstb.2019.0664. Epub 2021 Jan 11. PMID: 33423634;

PMCID: PMC7815426.