A common algorithm for confidence judgements across visual, auditory and

audio-visual decisions

Rebecca K West[1*], Natasha Matthews[1], Jason B Mattingley[1,2,3], & David K Sewell[1]

[1] School of Psychology, University of Queensland, Australia

[2] Queensland Brain Institute, University of Queensland, Australia

[3] Canadian Institute for Advanced Research, Canada

*Corresponding Author

E-mail: rebeca.west1@uq.net.au

Abstract

Most studies investigating the computational basis of decision confidence have focused on simple visual perceptual tasks, leaving open questions about how confidence is formed in decisions involving other sensory modalities or those requiring the integration of information across modalities. To address these gaps, we used computational modelling to analyse confidence judgements in perceptual decisions involving visual, auditory, and audio-visual stimuli. Drawing on research into visual confidence, we adapted models from the literature to evaluate their fit to our data, comparing three popular classes: unscaled evidence strength, scaled evidence strength, and Bayesian models. Our results show that the scaled evidence strength models consistently outperformed the other model classes across all tasks and could also be used to predict behaviour in the audio-visual task from the unidimensional auditory and visual model fits. These findings suggest that confidence judgements across different perceptual decisions rely on a shared algorithm that dynamically accounts for both sensory uncertainty and evidence strength, without the computation of posterior probabilities. Additionally, we investigated the algorithms used for multidimensional (audio-visual) confidence judgements specifically, showing that participants integrated both the visual and auditory dimensions of the stimulus, rather than relying solely on the most informative modality, and used a modality-independent measure of sensory uncertainty to adjust their confidence. Overall, our findings provide evidence for a common algorithm underlying confidence judgements across modalities and demonstrate the broad applicability of the scaled evidence strength algorithm, even in tasks requiring the integration of distinct sensory information.

Introduction

Human perceptual decisions are often accompanied by a level of confidence

that reflects the accuracy of the decision (Boldt et al., 2017; Kepecs et al., 2008).

This ability to accurately monitor and evaluate one's decision-making processes,

referred to as *metacognition*, plays a crucial role in humans' capacity to make

adaptive decisions. It prompts individuals to seek more information before

committing to a choice (Desender et al., 2018), decide when to stop deliberating in a

difficult decision (van den Berg et al., 2016), or anticipate effort or uncertainty in an

upcoming decision (Boldt et al., 2019). Given the pivotal role that metacognitive

judgements play in adaptive decision-making, one crucial goal for cognitive science

has been to understand the psychological processes involved in generating such

judgements.

Investigating the mechanisms that underpin metacognitive judgements,

however, requires considering how these computations are shaped by the sensory

modalities involved. For instance, forming confidence about the colour of a traffic

light relies solely on visual information, confidence in whether a phone is ringing

relies on auditory input, and confidence in whether a pineapple is ripe requires

integrating information about its colour, smell, and texture (de Gardelle et al., 2016).

Most previous studies investigating confidence judgements, however, focused on

simple visual perceptual decisions only (Adler & Ma, 2018; Aitchison et al., 2015;

Denison et al., 2018; Hangya et al., 2016; Li & Ma, 2020; Lisi et al., 2021; Locke et

al., 2022; Navajas et al., 2017; Sanders et al., 2016).

To bridge this significant gap in our understanding about the formation of

confidence across sensory modalities, our previous work utilised computational

modelling to explore the psychological algorithms underlying confidence judgements

across different perceptual domains (West et al., 2023). Specifically, we investigated

whether the algorithms underlying confidence judgements were the same across

vision and audition. Participants completed two versions of a categorisation task with

visual and auditory stimuli, where they categorised each stimulus based on a

perceptual feature (orientation or frequency) and then reported their confidence in

that decision. In both modalities, we varied evidence strength (i.e., the strength of the

evidence for a particular category) and sensory uncertainty (i.e. the amount of noise

or uncertainty in the sensory signal). This allowed us to keep the decision context the

same but vary the modality of presentation, isolating any similarities (*modality-independent* processes) or differences (*modality-specific* processes) in the algorithms used to generate confidence. In order to quantify the algorithms used for confidence, we evaluated the performance of several classes of existing models which mathematically formalise the mapping of evidence strength and sensory uncertainty to confidence in different ways. We found that a single class of models, in which confidence is derived from a subjective assessment of the strength of the evidence for a particular choice, scaled by an estimate of sensory uncertainty, provided the best account of confidence for both visual and auditory decisions. Comparing the 'settings' (or parameters) of this process across modalities however, revealed that the algorithm was tuned differently in each modality. That is, we found evidence for a modality-general scaled evidence strength algorithm that was tuned specifically in each modality (Lehmann et al., 2022; Masset et al., 2020; Mazancieux et al., 2020; Morales et al., 2018; Rouault et al., 2018).

While our recent work (West et al., 2023) has expanded our understanding of the algorithms that underlie confidence judgements in distinct sensory modalities, many everyday decisions require the integration of information from multiple senses. The psychological computations supporting metacognitive judgements in multidimensional contexts, however, remain under-researched and poorly understood. To address this gap, the current study explored both how participants make metacognitive judgements for multidimensional perceptual decisions and how the algorithms used for multidimensional decisions compare with those used in unidimensional contexts-those involving a single sensory modality.

In exploring the processes involved in multidimensional decision-making, we can build on substantial research that has investigated how individuals combine information from different senses, such as vision and audition, to form a unified perceptual representation. Specifically, cue combination research has explored whether perceptual judgements are formed by combining inputs from different senses in a weighted manner (integration perspective) or if they are based on a maximal input approach (selection perspective), where the brain selects only the dominant sensory input. Numerous studies have shown that individuals combine information from multiple sensory modalities by weighting inputs based on their reliability, which is often referred to as optimal integration or Bayesian cue integration. According to weighted integration models, sensory input from different

modalities is not treated equally; instead more reliable (less noisy) information is
given greater weight when integrating cues (Ernst & Banks, 2002; McGurk &
MacDonald, 1967). Other studies suggest that, in certain situations, rather than
combining cues, people rely predominantly on the most informative or salient
sensory modality (Posner et al., 1976; Welch & Warren, 1980). For example, under
conditions of uncertainty or conflict, perceptual judgements often favour the most
easily processed modality (Posner et al., 1976; Welch & Warren, 1980).

The same question of how sensory input is combined across modalities also
applies to confidence judgements. Specifically, it is not known whether confidence is
based on a weighted integration of information from different senses, or if it follows a
selection-based approach, where confidence reflects input from the most informative
or salient modality only. Recent findings from Gao et al. (2023) support the weighted
integration perspective, showing that participants combined auditory and visual
motion cues based on their reliability. In Gao et al.'s multisensory task, participants
were instructed to judge the direction of an auditory motion cue and ignore a
simultaneously presented visual motion cue. Despite these instructions, they found
that participants' judgements and confidence were influenced by both the direction
and reliability of the visual cue. This effect was captured by a computational model
which assumed that the cognitive processes involved in confidence judgements are
the same as those used in lower-level stages of perception. These findings also align
with the results of Faivre et al. (2018) who used computational modelling to
demonstrate that confidence in an audio-visual task could be predicted by an
integrated representation of auditory and visual signals. Specifically, Faivre and
colleagues (2018) modelled confidence as the probability of being correct, showing
that participants' perceived probability of correctness depended on the integration of
sensory inputs from both visual and auditory modalities.

Building on these studies, here we also investigated how confidence
judgements operate in multidimensional contexts by using a task in which stimulus
information provided in different modalities was explicitly task relevant (Gao et al.,
2023), and by expanding the range of models used to investigate confidence beyond
purely probabilistic frameworks (Faivre et al., 2018). This approach enabled us to
compare multiple potential algorithms for generating confidence, offering a more
nuanced comparison between the integration-based and selection-based
perspectives. Moreover, by using an expanded modelling framework, we were able

to explore potential biases in integration as well as more directly investigate the role of prior knowledge in confidence judgements, providing deeper insight into the cognitive processes underlying multidimensional confidence formation.

A second, related question that we addressed in this study was whether the algorithms used for confidence judgements differ between unidimensional stimuli, such as a purely visual or auditory stimulus, and multidimensional stimuli, such as an audio-visual stimulus. A modality-general framework suggests that the same computational processes apply across both uni- and multidimensional contexts, where a single algorithm is tuned to the specific decision context. However, one alternative view posits that integrating information from multiple senses may require a distinct computational strategy, possibly leading multidimensional decisions to rely on optimal or near-optimal, Bayesian-like algorithms. That is, while simpler heuristic strategies may be sufficient for unidimensional contexts (Adler & Ma, 2018; West et al., 2023), a more statistically optimal approach could be better suited for multidimensional contexts. Bayesian algorithms assume the computation of a probability metric which automatically resolves any 'translation issues' when combining (or comparing) sensory input from different modalities. Moreover, given the multidimensional nature of real-world experiences, along with the richer feedback opportunities they provide, optimal integration strategies may be more finely tuned for scenarios involving multiple sensory inputs. To assess whether a unified computational framework can account for both unidimensional and multidimensional judgements, we included unidimensional visual and auditory and multidimensional audio-visual decisions in our study.

To characterise and compare the computational processes used for metacognitive judgements in visual, auditory and audio-visual decisions, we use the same modelling framework as in our previous work (West et al., 2023). Specifically, we considered different theoretical models of decision confidence – Bayesian models and non-Bayesian evidence strength-based models – and evaluated their performance across the different types of perceptual decisions (see **Figure 1**). We provide a brief overview of the different model classes below.

According to *Bayesian models*, observers optimally combine knowledge about the statistical structure of a task (the "prior") with the present sensory input (the "likelihood") to compute a posterior probability distribution over possible states of a stimulus (Drugowitsch et al., 2014; Hangya et al., 2016; Kepecs & Mainen, 2012;

Meyniel et al., 2015; Pouget et al., 2016). The posterior probability distribution thus
represents every possible outcome and its associated probability. Bayesian models
stipulate that the observer uses the posterior probability distribution to guide both
their choice and confidence. For example, one possible strategy posits that an
observer's confidence increases with the posterior probability of the chosen
outcome. In experimental paradigms where numerical confidence ratings are used, a
set of criteria can map posterior probabilities to each level of the confidence rating
scale. In the example of judging the ripeness of a pineapple, a Bayesian observer
would eat the pineapple where $p(ripe \mid pineapple)$ is above 0.5, with higher
probabilities indicating greater confidence in the decision. Another method for
mapping posterior probability to confidence is to use the log posterior probability
ratio, $\log\left(\frac{p(ripe \mid pineapple)}{p(not\ ripe \mid pineapple)}\right)$, which is unbounded and allows for greater
differences in confidence at different levels of sensory uncertainty (Adler & Ma, 2018;
Locke et al., 2022).

Unscaled evidence strength models posit that confidence depends entirely on
the strength of the evidence for a particular decision outcome. These models
assume that the observer uses the attribute value of the stimulus to directly quantify
evidence strength, with confidence increasing as evidence becomes stronger. For
example, in this framework, the more saturated the yellow colour of a pineapple, the
more confident the person is that it's ripe. The relationship between evidence
strength and confidence can also be quantified numerically by setting criteria based
on evidence strength. Unlike Bayesian models and scaled evidence strength models
(described below), unscaled evidence strength models do not explicitly account for
sensory uncertainty in the computation of confidence, focusing instead on the direct
relationship between attribute value and confidence.

Scaled evidence strength models posit that confidence depends on both the
strength of the evidence and the amount of sensory uncertainty associated with the
decision. According to scaled evidence strength models, sensory uncertainty is used
to scale evidence strength such that under conditions of high uncertainty, greater
evidence strength is required to produce the same level of confidence as under
conditions of low sensory uncertainty. For example, these models suggest that a
person would feel less confident about the ripeness of a pineapple whose colour is
highly variable relative to one where there is low variability in colour, even though the

average 'yellowness' of the two pineapples is the same. For numerical confidence ratings, a point estimate of sensory uncertainty can be used to scale the criteria used to delineate continuous evidence strength (Adler & Ma, 2018; Denison et al., 2018; West et al., 2023). Although both scaled evidence strength and Bayesian models consider evidence strength and sensory uncertainty as important for confidence, scaled evidence strength models do not rely on probabilistic inference. Because scaled evidence strength models do not involve the computation of a probability metric, they are considered less computationally complex, and arguably, a more feasible explanation of human cognition (Sanborn et al., 2010; Sanborn & Chater, 2016; Stewart et al., 2006).

The Current Study

The aim of the current study was to differentiate between these different theoretical accounts and use computational models to characterise the computations involved in confidence for visual, auditory and audio-visual decisions. Specifically, one key focus of our analyses was to investigate whether the same computational algorithms governed confidence judgements across all three types of decisions. To address this question, we evaluated the performance of the different model classes and tested whether a single class consistently fit the data across tasks. We also examined the generalisability of the models by determining how well predictions from the unidimensional tasks (visual and auditory) align with observed behaviour in the audio-visual task. A second key focus of our analyses was to understand how participants integrate sensory information from multiple modalities when making multidimensional confidence judgements. To characterise the algorithms supporting these judgements, we systematically explored different assumptions regarding how sensory inputs are combined across modalities within each model class.

 Figure 1

 Choice and Confidence Criteria Across Models

229
Note. **(A**) Illustration of category structures for unidimensional task and **(B)**
multidimensional task. For the unscaled evidence strength models (top row), the
choice and confidence criteria do not change as a function of sensory noise for both
the **(C)** unidimensional and **(D)** multidimensional tasks. For the scaled evidence
strength models and Bayesian models (middle and bottom rows, respectively), the
choice and confidence criteria change as a function of sensory uncertainty/noise.

Method

Overview

Participants completed 3 categorisation tasks: (1) a visual categorisation task, (2) an auditory categorisation task and (3) an audio-visual categorisation task. In each task, participants made a two-alternative forced choice category decision (Category 1 or Category 2), followed by a 4-point confidence rating, ranging from low confidence (1) to high confidence (4). Category membership was determined by an attribute of the stimulus: orientation for visual stimuli (drifting Gabor patches), frequency for auditory stimuli (pure tones) and both orientation and frequency for the audio-visual stimuli (drifting Gabor patches with simultaneously presented pure tones). A normal distribution of the relevant stimulus attribute defined each category where the category distributions had the same mean and different standard deviations. Sensory uncertainty also varied with stimuli presented at 4 different intensities. In the visual tasks, intensity depended on the contrast of the Gabor patch (3.3%, 5%, 6.7%, 13.5%). In the auditory tasks, intensity depended on the loudness of the tone (equivalent of -3 dB SPL, 4 dB SPL, 10.5 dB SPL, 17 dB SPL for a 1 kHz pure tone). In the audio-visual task, both contrast (3.3%, 4.2%, 5.3%, 6.7%) and loudness (equivalent of -3 dB SPL, 2 dB SPL, 6 dB SPL, 10.5 dB SPL for a 1 kHz pure tone) varied together. The intensity levels were chosen to achieve a similar range of performance across all tasks based on pilot data.

 Figure 2

 Experimental Task

258
259 *Note.* **(A)** Category distribution for auditory (left), visual (middle) and audio-visual
260 (right) task. **(B)** Trial structure for testing trials. **(C)** Levels of stimulus intensity.

Participants

Participants were recruited from the University of Queensland's research
participation scheme and were reimbursed for their time ($20 per hour in cash or gift
cards). Inclusion criteria required normal (or corrected-to-normal) vision and normal
hearing, both assessed by self-report. After exclusions (see the Results section for
details), the final sample comprised of 10 participants.

Categorisation Task

As shown in **Figure 2A**, the categories were defined by normal distributions
which had the same mean and different standard deviations. In the visual modality,
larger rotations clockwise or counter clockwise relative to horizontal were more likely
to be sampled from category 2 (   ) whereas smaller rotations
relative to horizontal were more likely to be sampled from category 1 (
). In the auditory modality, lower and higher frequency tones were more

likely to be sampled from category 2 ($\mu_{cat2} = 2700\ Hz, \sigma_{cat2} = 500\ Hz$), whereas
intermediate frequency tones were more likely to be sampled from category 1
($\mu_{cat1} = 2700\ Hz,\ \sigma_{cat1} = 125\ Hz$). In the audio-visual task, the categories were
defined by bivariate normal distributions with the same means and standard
deviations as in the visual and auditory versions of the tasks
($\mu_{cat1} = [0°, 2700\ Hz]\ ;\ \sigma_{cat1} = [3°, 125\ Hz];\ \mu_{cat2} = [0°, 2700\ Hz]; \sigma_{cat2} =$
$[12°, 500\ Hz]$). To maximise correct responses in each task, the ideal observer would
use the points where the category distributions intersect, reporting that stimulus
values contained within the intervals were sampled from category 1 and stimulus
values outside the intervals were sampled from category 2 (see dotted lines in
Figure 2A).

Stimuli

Visual Stimuli

The visual stimuli were a drifting Gabors which had a spatial frequency of 0.5
cycles per degrees of visual angle (*dva*), a speed of 6 cycles per second, a Gaussian
envelope with a standard deviation of 1.2 *dva*, and a randomized starting phase.

Auditory Stimuli

The auditory stimuli were pure tones of varying frequency (including 5ms
linear onset and offset amplitude ramps to eliminate onset and offset clicks). Stimuli
were synthesized with an ASIO4ALL sound driver with a sampling rate of 28 kHz.
Tones were matched for loudness according to the International Standard ISO
226:2003: Acoustics- Normal Equal-Loudness-Level-Contours (International
Standardization Organisation, 2003) and extensive piloting was undertaken to select
intensity levels. Auditory stimuli were presented in stereo via headphones
(Sennheiser HD 202).

Audio-Visual Stimuli

The audio-visual stimuli were simultaneously presented Gabors and tones,
the parameters of which were the same as described above.

Procedure

All participants completed all combinations of tasks in 3 separate testing
sessions (i.e., visual task, auditory task, audio-visual task). The order of the visual
and auditory tasks was counterbalanced across participants and all participants
completed the audio-visual task in the final session.

Participants were seated in a dark room, at a viewing distance of 57 cm from
the screen, and their head was stabilised with a chinrest. Stimuli were presented on
a gamma-corrected 60 Hz 1920-by-1080 display. The computer display (ASUS
VG248QE Monitor) was connected to a Dell Precision T1700, calibrated with a
ColorCal MKII (Cambridge Research Systems). Stimuli were generated and
presented using custom code and the Psychophysics Toolbox extensions (Brainard,
1997; Pelli, 1997) for MATLAB.

In each session, participants received instructions for that session's task
which included an explanation about how the stimuli were generated from the
relevant category distributions. To further illustrate these distributions, participants
were then shown 36 stimuli that were randomly sampled from category 1, followed
by category 2. They then completed the category training and testing (detailed
below). Each session took approximately 1 hour.

Testing

At the start of each trial, a fixation cross was presented centrally for 1 s. The
fixation cross was then extinguished, and a stimulus was presented (either a visual,
auditory or audio-visual stimulus depending on session; all 50 ms in duration).
Immediately after the offset of the stimulus, participants were able to respond
category 1 or category 2 by pressing a button (F or J keys) with their left or right
index finger, respectively. Participants were then prompted to make a confidence
judgement for their chosen category with text that read 'Confidence?' presented
centrally. Participants used the 1- 4 number keys to indicate their confidence. The
inter-trial interval was 1 s, after which the fixation cross reappeared.

Within a testing block, an equal number of stimuli were shown from each
category and intensity level (i.e., 15 trials per cell of the design). Stimulus attributes
were sampled randomly from the relevant category distribution. Participants
completed 6 testing blocks per session (120 trials per block, a total of 720 trials per
session). The order of both category and intensity level was randomised within a
block.

At the end of each block, participants were required to take at least a 30 s
break. During the break, they were shown the percentage of trials that they had
correctly categorised in the most recent block. Participants were also shown a list of
the top 10 block scores (across all participants, indicated by initials) for the task they
had just completed. This was intended to motivate participants to score highly. We
did not provide trial-by-trial feedback during testing to ensure that confidence
judgements reflected participants' subjective evaluations of uncertainty rather than
being influenced by external correction signals.

Training

The trial procedure in training blocks was the same as in testing blocks,
except that trial-to-trial feedback was given, only the highest intensity level was used
for stimulus presentation and participants were not required to make confidence
judgements. For the trial-to-trial feedback, the word "correct" in green or "incorrect" in
red was displayed for 1.1 s after participants made their response. Participants
completed 2 training blocks (120 trials per block, in total 240 trials) per session.
Training was intended to further familiarise participants with the generating category
distributions.

353   **Model Specification**

To model responses, we assumed that on each trial, *t*, observers perceived a
sensory signal, *x*. Observers transformed that sensory signal into a *decision variable*,
the computation of which differed across model classes. To make a discrete
category-confidence response, we assumed that observers compared the decision
variable to a set of *criteria*. In the following sections, we describe our stimulus
standardisation procedure, our assumptions about the sensory signals, decision
variable, decision criteria and then describe the model fitting procedure.

Standardisation of Stimulus Values

362   To compare stimulus values and model parameters across modalities, we
363 standardised all stimulus values before fitting models. To standardise stimulus
364 values, we subtracted the mean and divided by the standard deviation of all
365 presented stimulus values in each modality such that:

$$Z = \frac{s - \bar{x}_{[M]}}{sd_{[M]}}$$

1)

where *Z* is the standardised stimulus value; *s* is the true stimulus value in its
original perceptual units (degrees or hertz); $\bar{x}$ is the mean of all presented stimulus
values for a given modality *M* (visual or auditory) and *sd* is the standard deviation of
the same set of stimulus values. For the audio-visual task, stimulus values were
standardised separately within each modality. This standardisation process was
consistent with the idea that participants built up a reliable internal representation of
the categories during training such that they understood the relative frequencies of
different stimulus values within each category distribution.

The Sensory Distribution

In all models, we assumed that the observer's perception of the stimulus, *x*,
was a noisy measurement of the true stimulus presented on trial *t* (see **Figure 3A**).
We modelled this noisy internal measurement using a Gaussian distribution, referred
to as the *sensory distribution*. The sensory distribution was centred on the true
stimulus attribute, s_t, with a standard deviation that depended on the intensity of the
stimulus, σ_I. σ was estimated separately at each stimulus intensity level, subject to
the constraint that it decreased monotonically as intensity increased. That is, we
assumed that greater stimulus intensity was associated with less sensory noise and
thus, smaller values of σ (see **Figure 3A**). Below we describe the derivation of *x* and

σ for both the unidimensional (visual, auditory) and multidimensional (audio-visual)

stimuli.

Unidimensional Stimuli

387   On a given trial, the sensory distribution for the unidimensional stimuli, x_{uni},

388   was defined as:

$$x_{uni} \sim N(s, \sigma_I^2)$$

2)

389   where N denotes the normal density function, s is the true stimulus attribute,

390   and σ is the estimated standard deviation of the distribution, given the stimulus

391   intensity level, *I.*

Multidimensional Stimuli

393   For the multidimensional stimuli, the sensory signal comprised two

394   dimensions, one for each modality. The sensory distribution was thus described by a

395   bivariate Gaussian distribution:

$$x_{bi} \sim N(\boldsymbol{\mu}, \Sigma)$$

3)

396   where N denotes the normal density function, $\boldsymbol{\mu}$ denotes a vector of stimulus

397   attributes and Σ a covariance matrix. Specifically, the vector of stimulus attributes on

398   a given trial was described by:

$$\boldsymbol{\mu} = \begin{pmatrix} s_V \\ s_A \end{pmatrix}$$

4)

399   where s_V was the stimulus attribute for the visual dimension and s_A was the

400   stimulus attribute for the auditory dimension. The covariance matrix was described

401   by:

$$\Sigma = \begin{bmatrix} \sigma^2_{V[I]} & 0 \\ 0 & \sigma^2_{A[I]} \end{bmatrix}$$

5)

where $\sigma_{V[I]}$ was the estimated standard deviation of the visual dimension, $\sigma_{A[I]}$

was the estimated standard deviation of the auditory dimension, given the stimulus

intensity level, *I*. We tested two different assumptions about σ: either that σ differed

across the stimulus dimensions, referred to as the *different noise* variant, or that σ

was the same across the stimulus dimensions, referred to as the *same noise* variant.

Same Noise. For the *same noise* model variants, we assumed that sensory

noise was the same across the two stimulus dimensions such that:

$$\sigma_{V[I]} = \sigma_{A[I]}$$

6)

where σ_V was the estimated amount of sensory noise in the visual dimension,

σ_A was the estimated amount of sensory noise in the auditory dimension, and *I*

indexed the stimulus intensity level (see top right panel of **Figure 3B**).

Different Noise. For the *different noise* variants, we assumed that sensory

noise differed across the two stimulus dimensions such that

$\sigma_{V[I]} \neq \sigma_{A[I]}$, where σ_V was the estimated amount of sensory noise in the visual

dimension, σ_A was the estimated amount of sensory noise in the auditory dimension

and *I* indexed the stimulus intensity level (see bottom left panel of **Figure 3B**). Under

the different noise assumption, we estimated σ separately for each stimulus

dimension and intensity level, constrained by monotonicity within each domain.

Figure 3

Sensory Signals

421
Note. **(A)** For the unidimensional stimuli, the observers' internal representation of the
stimulus was approximated with a Gaussian distribution centred on the true stimulus
attribute with a standard deviation, , that depended on the intensity level of the
stimulus. **(B)** The observer's internal representation of the multidimensional stimuli
was approximated with a bivariate Gaussian distribution. Sensory signals in each
dimension, and , were combined into a single measure, . Top right quadrant
shows unbiased integration of dimensions with the same amount of sensory noise
across dimensions. Bottom left quadrant shows unbiased integration with different
amounts of sensory noise in each dimension. Samples were taken from the shaded
region and each combination of values was transformed into a single measure **(C)**
Black data points show unbiased integration of stimulus attributes across
dimensions, orange data points show an auditory bias and blue data points show a
visual bias for 4 different audio-visual stimuli (shapes).

Transformation of Bivariate Sensory Distribution. For ease of exposition,

we transformed the bivariate sensory distribution, , into a univariate Gaussian

distribution defined by:

7)

where denotes the normal density function, denotes the mean and the

standard deviation of the resulting univariate distribution. We calculated as the

Euclidian distance of a set of multidimensional stimulus coordinates, $[x_V, x_A]$, from

the centre of the standardised stimulus space, [0,0] (henceforth referred to as the

origin). We tested two different assumptions about the computation of l: either that

the observer attended to both dimensions of the stimulus (*integration* model variants)

or that the observer attended to only a single dimension of the stimulus (*max* model

variants).

Integration Variants. For the integration model variants, we assumed that

the observer attended to both dimensions of the stimulus to make their decision. We

therefore computed a weighted combination of the sensory signals received from

each dimension such that:

$$l = \sqrt{w_V({x_V}^2) + (1 - w_V)({x_A}^2)} \qquad \text{8)}$$

where w_V was the weight for the visual stimulus dimension, x_V was the

perceived stimulus value for the visual dimension and x_A was the perceived stimulus

value for the auditory dimension. See **Figure 3C** where orange data points show

integration with an auditory bias (where $w_V < 0.5$) and blue data points show

integration with a visual bias (where $w_V > 0.5$). The weights were constrained to be

non-negative and bounded on the interval [0, 1] such that $w_V + w_A = 1$.

Max Variants. For the max model variants, we assumed that the observer

attended to a single dimension of the stimulus only and thus, the computation of l

depended on a single value from the set of stimulus coordinates $[x_V, x_A]$. The

"selected" dimension was determined by which value was the most informative about

the generating category. The informativeness of the generating category was

referred to as *category diagnosticity* and reflected the probability density of the

presented stimulus value for the most probable category distribution, normalised by

the total probability density of the stimulus for both category distributions:

$$CD = \frac{\max\left(\varphi(s_n; \mu_1, \sigma_1), \varphi(s_n; \mu_2, \sigma_2)\right)}{\sum_{C=1}^{2} N(s; \mu_C, \sigma_C)} \qquad \text{9)}$$

464   where φ denoted the normal density function, μ_1 and μ_2 were the means of

465   the generating category 1 and category 2 distributions and σ_1 and σ_2 were the

466   standard deviations of the generating category 1 and category 2 distributions. *C*

467   denoted the category and s_t was the stimulus attribute on trial *t*. The distance, l, was

468   then calculated as the absolute value of the selected dimension:

$$l = |x_V| \; if \; CD(s_V) > \; CD(s_A)$$
$$l = |x_A| \; if \; CD(s_V) < \; CD(s_A) \qquad \qquad \text{10)}$$

The computation of l for the max models was thus consistent with the

integration models because the result was equivalent to a distance measure

involving only a single term.

Same Noise and Different Noise Variants. The standard deviation of x_{comb},

σ_{AV}, depended on the model variant, specifically the same noise or different noise

assumption *and* the integration or max assumption. Under the same noise

assumption:

$$\sigma_{AV[I]} = \; \sigma_{V[I]} = \; \sigma_{A[I]} \qquad \qquad \text{11)}$$

where σ_V was the estimated standard deviation of the visual dimension of x_{bi},

σ_A was the estimated standard deviation of the auditory dimension of x_{bi}, and I

indexed the stimulus intensity level.

Under the *integration different noise* assumption, we calculated a weighted

combination of the standard deviations of each dimension of the bivariate sensory

distribution x_{bi}:

$$\sigma_{AV[I]} = \; \sqrt{w_V \, \sigma_{V[I]}^2 + (1 - \; w_V) \, \sigma_{A[I]}^2} \qquad \qquad \text{12)}$$

where w_V was the estimated weight for the visual dimension of the stimulus

(as in Equation 8), σ_V was the estimated standard deviation of the visual dimension

of x_{bi}, σ_A was the estimated standard deviation of the auditory dimension of x_{bi}, and I

indexed the stimulus intensity level. Using Equation 12 to combine the estimates of σ

across modalities meant that the resulting value of σ_{AV} was of the same magnitude

as σ_V and σ_A. Under the *max different noise* assumption,

$$\sigma_{AV[I]} = \begin{cases} \sigma_{V[I]} \; if \; CD(s_V) > \; CD(s_A) \\ \sigma_{A[I]} \; if \; CD(s_V) < \; CD(s_A) \end{cases} \qquad \text{13)}$$

where $CD(s_V)$ was the category diagnosticity of the visual dimension of the

stimulus and $CD(s_A)$ was the category diagnosticity of the auditory dimension of the

stimulus (see Equation 9).

Decision Variable

In all models, we assumed that the observer transformed the sensory signal

into a *decision variable* which was then compared with a set of criteria. We tested

different assumptions about the computation of the decision variable which
quantified different theoretical models about the choice and confidence generation
process. We categorised these theoretical models into three broad classes: (1) the
unscaled evidence strength models, (2) the scaled evidence strength models and (3)
the Bayesian models. One of the distinguishing factors among candidate classes
concerned whether the decision variable was represented in *psychological space*
(unscaled evidence strength and scaled evidence strength; discussed in more detail
below) or *probability space* (Bayesian; discussed in more detail below).

For models that represented the decision variable in *psychological space*, the
decision variable was assumed to be in the same psychological units as the sensory
signals. For these models, we therefore use *x* to denote both the sensory signal and
the decision variable. For models that represented the decision variable in *probability*
space, we assumed that the sensory signal was transformed into a probability metric
which was then compared with choice and confidence criteria in the same probability
units. For these models we use *d* to denote the decision variable and distinguish it
from the sensory signal.

To illustrate the difference between the computation of a decision variable
which is represented in psychological space or probability space: for a non-Bayesian
model with category-confidence criteria in psychological space, a Category 2
Confidence 1 response might be made for any visual stimulus perceived as having
an orientation between 0 and 5 degrees (or 0 and 0.6 in standardised stimulus units).
For a Bayesian model, where the criteria were in probability space, the same
Category 2 Confidence 1 response might be made for any visual stimulus perceived
as having a log posterior probability ratio between 0 and 0.5.

Non-Bayesian Models

519   As described above, for the non-Bayesian models, the sensory distribution
520 and the decision variable distribution were represented in the same psychological
521 space. This meant that *the sensory distributions* (x_{uni} and x_{comb} for the
522 unidimensional and multidimensional stimuli respectively) *were equivalent to the*
523 *decision variable distributions*.

Bayesian Models

Consistent with Bayesian decision theory, for the Bayesian models we
assumed that the observer combined prior knowledge of the generating category

distributions with observed stimulus information to form posterior beliefs about
category membership. For all Bayesian models, therefore, we assumed that the
observer transformed the sensory signal into a log posterior probability ratio, *d*, to
make a decision. The log posterior probability ratio represented the (log) ratio of
posterior beliefs about category membership, such that $d = log\frac{p(C=1\,|\,x)}{p(C=2\,|\,x)}$ where *x*
represented the perceived value of the stimulus on a given trial. When the log
posterior probability ratio was positive, there was greater evidence for category 1.
For the Bayesian models, we assumed that category and confidence reports
depended on the sensory signal *x* only via *d.* Following Adler and Ma (2018), we
used the following derivation of *d:*

$$d = \frac{1}{2}log\frac{\sigma^2 + \sigma_2^2}{\sigma^2 + \sigma_1^2} - \frac{\sigma_2^2 - \sigma_1^2}{2(\sigma^2 + \sigma_1^2)(\sigma^2 + \sigma_2^2)}x^2 + log\frac{p(C=1)}{p(C=2)} \qquad 14)$$

where σ_1 was the standard deviation of the category 1 distribution, σ_2 was the
standard deviation of the category 2 distribution and σ was the fitted value of sensory
noise, approximating the amount of sensory uncertainty in the observer's internal
representation of the stimulus. Because we sampled equally from each category, we
assumed that *p(C*=1)=*p(C*=2)=0.5 such that $log\frac{p(C=1)}{p(C=2)}$ was 0 in Equation 14.

Log Posterior Probability Ratio with Free Category Distribution
Parameters. The log posterior probability ratio model described above assumes that
the observer knows the true values of the standard deviations of the category
distributions σ_1 and σ_2 in Equation 14. We also tested a version of the model in
which the observer had imperfect knowledge of the parameters of the generating
category distributions. In this model, we estimated the values of σ_1 and σ_2 as free
parameters.

Figure 4

Choice and Confidence Criteria Across Unidimensional and Multidimensional Tasks

Note. In the unidimensional task (top panel), 7 symmetrical criteria partitioned the range of the decision variable into discrete category and confidence response regions (top left panel; see legend at the bottom for corresponding responses). The sensory distribution was compared against the choice and confidence criteria to calculate a response probability (top right panel). In the multidimensional task, 7 circular criteria partitioned the response regions (bottom left panel) and were compared against the bivariate sensory distribution (bottom right panel).

Choice and Confidence Criteria

As described above, in all models we assumed that the decision variable was compared with a set of criteria. The criteria partitioned the range of the decision variable into discrete category and confidence response regions so that if the decision variable fell within a defined region, response *r* was given (see

Figure 4). Given four confidence levels for each of the two categories, this
yielded eight response regions, $r \in \{1, 2, 3, ..., 8\}$, each corresponding to a unique
category and confidence combination. The choice and confidence criteria were
positioned in the same units as the decision variable and required different
assumptions across the different theoretical model classes. These assumptions are
described below for the non-Bayesian models, where the decision variable was
measured in psychological space, and Bayesian models, where the decision variable
was measured in probability space.

Non-Bayesian Choice and Confidence Criteria

The non-Bayesian models constituted models from both the scaled evidence
strength and unscaled evidence strength class. For all these models, we refer to the
position of the criteria in psychological space as *b*. To define the eight response
regions across the range of psychological space, we used seven criteria. We
assumed that each criterion increased monotonically across successive criteria such
that higher confidence response regions were aligned with more extreme category
evidence (see

Figure 4). We also assumed that the criteria were positioned symmetrically

around the means of the category distributions. We refer to this centre point as b_0.

We assumed the criteria were symmetrical in this task because two measurements

that are equidistant from the middle of the category structure but on opposite sides of

b_0 should logically have the same confidence associated with them. Due to

symmetry, confidence regions on equidistant but opposite sides of b_0 were treated

as equivalent by the model. The criteria were ordered such that:

$$-b_7 < -b_6 < -b_5 < -b_4 < -b_3 < -b_2 < -b_1 < b_0 < b_1 < b_2 <$$
$$b_3 < b_4 < b_5 < b_6 < b_7. \qquad \text{15)}$$

587   The symmetrical criteria $-b_4$ and b_4 divided the stimulus range into two

588   different category response regions such that:

$$if \ |x| \begin{cases} < b_4, respond \ category \ 1 \\ > b_4, respond \ category \ 2 \end{cases} \qquad \text{16)}$$

589   To make a confidence response, we assumed that the observer used 4

590   symmetrical criteria for each category: b_1- b_4 for category 1 responses and b_4 -

591   b_7 for category 2 responses. See

592   **Figure 4A** to see how the criteria aligned with category evidence. Thus, the
593   observer used a decision rule such that:

$$if\ |x| \begin{cases} < b_1, respond\ confidence\ 4 \\ > b_1\ and\ < b_2, respond\ confidence\ 3 \\ > b_2\ and\ < b_3, respond\ confidence\ 2 \\ > b_3\ and\ < b_4, respond\ confidence\ 1 \\ > b_4\ and\ < b_5, respond\ confidence\ 1 \\ > b_5\ and\ < b_6, respond\ confidence\ 2 \\ > b_6\ and\ < b_7, respond\ confidence\ 3 \\ \quad > b_7, \quad respond\ confidence\ 4 \end{cases} \qquad 17)$$

For the unscaled evidence strength models and the scaled evidence strength
models, we made different assumptions about how *b* varies as a function of sensory
uncertainty.

Unscaled Evidence Strength Model. In the unscaled evidence strength
model, the choice and confidence criteria were not dependent on (estimated) values
of sensory uncertainty (σ) and therefore occupied fixed positions across intensity
levels. The position of each criterion in psychological space was described by a free
parameter, *k*. The resulting criteria in psychological space were given by:

$$b_r = k_r$$

18)

602   **Scaled Evidence Strength Model.** In the scaled evidence strength model,
603   the positions of the choice and confidence criteria were functions of σ. Each criterion
604   depended on 4 free parameters: *k*, *m, z* and σ. *k* represented the base position of
605   each criterion which was offset by $m\sigma^z$, where *m* was also estimated separately for
606   each criterion. The resulting criteria in psychological space were given by:

$$b_r(\sigma) = k_r + m_r\sigma^z$$

19)

We constrained *z* to be greater than 1. Previous research has also considered
different scaling rules (Adler & Ma, 2018; Locke et al., 2022; West et al., 2023), for
example where criteria are estimated as linear or quadratic functions of σ. We chose
not to investigate these variants directly here to reduce the number of models for
model comparison and importantly, our chosen evidence strength model contained
both linear and quadratic scaling as special cases.

Bayesian Choice and Confidence Criteria

For the Bayesian models, we assumed that the observer chose a response by

comparing *d,* the log posterior probability ratio for a given stimulus (see Equation

14), with a set of choice and confidence criteria $k = (k_1, k_2 \dots k_7)$ that partitioned *d*

space into eight response regions, each representing a unique category and

confidence combination. The positions of the choice and confidence criteria for the

Bayesian models, therefore, were free parameters in *d* units. We assumed that each

criterion increased monotonically across successive criteria such that higher

confidence response regions aligned with greater absolute values of *d* (

Figure 4D). Thus, the choice and confidence criteria were ordered such that:

$$k_1 < k_2 < k_3 < k_4 < k_5 < k_6 < k_7$$

20)

623   k_4 divided the stimulus range into two different category response regions such that

$$if \ d \begin{cases} < k_4, respond \ category \ 1 \\ > k_4, respond \ category \ 2 \end{cases}$$

21)

624   For confidence response, the observer used a decision rule such that:

$$if \ d \begin{cases} < k_1, respond \ confidence \ 4 \\ > k_1 \ and \ < k_2, respond \ confidence \ 3 \\ > k_2 \ and \ < k_3, respond \ confidence \ 2 \\ > k_3 \ and \ < k_4, respond \ confidence \ 1 \\ > k_4 \ and \ < k_5, respond \ confidence \ 1 \\ > k_5 \ and \ < k_6, respond \ confidence \ 2 \\ > k_6 \ and \ < k_7, respond \ confidence \ 3 \\ > k_7, \ \ \ \ \ respond \ confidence \ 4 \end{cases}$$

22)

Fitting the Models to Data

Model parameters were estimated for each participant using maximum
likelihood estimation. Below we first describe the process for estimating the
parameters of the bivariate sensory distribution and then describe the process for
calculating the likelihood of a given response, *r*, for a model with parameters θ. We
describe this process separately for the non-Bayesian and Bayesian models, as they
required different transformations.

Bivariate Sensory Distribution

To estimate the parameters of the bivariate sensory distribution, we sampled
10 evenly spaced values from the 5[th] to 95[th] percentile of the cumulative density
distribution for each dimension of the sensory distribution. We generated all possible
combinations of these sampled values (see shaded region of bottom left panel of
Figure 3B) and transformed each combination into the relevant univariate decision
variable, x_{comb}, given the model variant assumptions (integration vs. max and
different noise vs. same noise). See above for detailed descriptions for each set of
assumptions. For each univariate Gaussian decision variable, we computed a
likelihood (described below) which was then multiplied by the normalised joint
density of the sample, given the bivariate sensory distribution, x_{bi}.

Likelihood Calculation: Non-Bayesian Models

For the non-Bayesian models, the decision variable distributions, x_{uni} and

x_{comb}, were in the same psychological units as the choice and confidence criteria, *b*,
and thus, could be compared directly. For each trial, we therefore determined the
predicted response probability for a chosen combination of category and confidence
level by computing the probability mass of the sensory distribution between adjacent
criteria, given the participant's response on that trial, r_t (cf. Luce, 1959; see Fig 3D).
This quantity was defined as:

$$\int_{-b_{r_t}}^{-b_{t-1}} N(x;\ s_t, \sigma_t^2)\, dx\ +\ \int_{b_{r_t-1}}^{b_{r_t}} N(x;\ s_t, \sigma_t^2)\, dx$$

23)

651   Where $b_0 = 0, b_8 = \infty$ and $- b_8 = -\infty$.

Likelihood Calculation: Bayesian Models

In the Bayesian models, the choice and confidence criteria were positioned in
probability space (log posterior probability ratio units) and thus, the sensory
distribution and criteria could not be compared directly. We, therefore, transformed
the choice and confidence criteria into psychological space by using the relevant
value of *d* as the left-hand side of Equation 14 and solved for *x*. Solving Equation 14
for *x* requires calculating the square root of *d*, which is undefined for negative values.
We therefore used the absolute value of *d* to solve Equation 14 for *x* and applied the
appropriate sign to the result to arrive at a final standardised value for *x*. Where the
category distribution parameters were estimated as free parameters, we used the
estimated values in place of the true standard deviations (σ_1 and σ_2). The resulting
choice and confidence criteria in psychological space were then compared with the
decision variable distribution, described below.

Unidimensional Stimuli. After transforming the choice and confidence
criteria in *d* space to psychological space using Equation 14, we computed the
probability mass of the sensory distribution between adjacent criteria using Equation
23.

Multidimensional Stimuli. In order to transform the choice and confidence
criteria into psychological space we used the value of *d* as the left-hand side of
Equation 14 to solve for *x*. For the integration variants, we did this separately for
each stimulus dimension such that we used the estimated value of σ and the
standard deviations of the generating category distribution (σ_1 and σ_2) for each
dimension. This gave us a "threshold" value in psychological space for each stimulus
dimension, referred to as y_V and y_A. These values were then converted into a

combined distance metric, b_{comb}, according to:

$$b_{comb} = \sqrt{y_V^2 + y_A^2}$$

24)

b_{comb}, therefore, represented a criterion in psychological space calculated as a
combination of the "threshold" values for each stimulus dimension. The criteria were
unweighted, as the weighting was applied to the stimulus values directly (see
Equation 8). For the max variants, we converted the estimated choice and
confidence criteria into psychological space, see Equation 14, for the selected
stimulus dimension only, see Equation 10.

Log Likelihood of the Dataset

To obtain the log likelihood of the dataset, we computed the sum of the log
probability for every trial t, where T is the total number of trials.

$$\log p(data \mid \theta) = \sum_{t=1}^{T} \log p(r_t \mid \theta) = \sum_{t=1}^{T} \log p_{\theta}(r_t \mid s_{t,}, \sigma_t)$$

25)

686 **Model Selection**

687   To compare candidate models, we used Akaike information criterion (*AIC*)
688   and Bayesian information criterion (*BIC*) for model selection. For a single participant,
689   *AIC* is defined as:

$$AIC = 2K - 2\log(L)$$

26)

690   where *K* is the number of model parameters and $\log(L)$ is the log likelihood of
691   the dataset. To evaluate the performance of each model across all participants, we
692   summed the *AIC* values across the *N* participants,

$$AIC_{sum} = \sum_{N=1}^{N} AIC_N$$

27)

693   To compare the relative support for each model, we also calculated Akaike
694   weights (Wagenmakers & Farrell, 2004). First, for each model M_m, where $m = $
695     $1, 2, \ldots, J$, we computed the difference in *AIC* relative to the best candidate model
696   (the model with the lowest *AIC* value):

$$\Delta_m(AIC) = AIC_m - \min(AIC)$$

28)

697   Next, we calculated the Akaike weight for each model as:

$$wAIC_m = \frac{exp\left\{-\frac{1}{2}\Delta_m(AIC)\right\}}{\sum_{k=1}^{K} exp\left\{-\frac{1}{2}\Delta_k(AIC)\right\}}$$

29)

698   The Akaike weights can be interpreted as the probability that a particular
699   model is the best model in the set of candidate models, given the data and specified
700   models (Wagenmakers & Farrell, 2004).
701   For a single participant, *BIC* is defined as:

$$BIC = -2\log(L) + K\log(T)$$

30)

where *K* is the number of model parameters, $\log(L)$ is the log likelihood of the
dataset and *T* is the number of trials in the dataset. Because *BIC* is sensitive to the
total sample size used to compute the likelihood, calculating the summed *BIC* for
each model requires that the sample size accounts for the total number of trials
across all participants. We therefore summed the likelihood terms across
participants, *N*, and added to that the total number of free parameters across
participants, *kN*, multiplied by the logarithm of the total number of trials across
participants, *tN*:

$$BIC_{sum} = \sum_{N=1}^{N} -2\log(L_N) + kN\log(tN)$$

31)

Parameter and Model Recovery

We performed both parameter and model recovery for our core models. In the

case of parameter recovery, we simulated data using known parameter values, fit

the models to the simulated data, and then checked the correlation between the true

generating parameters and the parameters estimated during the fitting procedure.

For model recovery, we simulated datasets from each model and fit all models to

these datasets. We then evaluated the probability that the model used to generate

the data was correctly identified as the best-fitting model based on a specific model

selection metric (*AIC* or *BIC*). Model recovery was conducted at two levels: individual

model variants (see **Figure 5A**) and broader model classes (see **Figure 5B**).

Evaluating model recovery at the model class level allowed us to determine how well

the core theoretical assumptions distinguishing different groups of models aligned

with the data (West et al., 2023). For both the parameter and model recovery, we

used parameter values that were similar to the range of values obtained through

fitting participant data. Further, to match our empirical dataset, we performed the

parameter and model recovery with simulated datasets consisting of 10 'participants'

and 720 trials per participant.

As shown in **Table S 3 – Table S 5** and **Figure S 3 – Figure S 5**, parameters

generally exhibited strong recovery across models, with the vast majority of

correlation coefficients exceeding $r > 0.75$ (White et al., 2018). However, there were

some exceptions: noise parameters (σ) in the unscaled evidence strength and

Bayesian models showed poorer recovery ($r < 0.5$) under different noise and

integration assumptions. The poorer recovery could have stemmed from using a

restricted range of parameter values when simulating data. For the unscaled

evidence strength and Bayesian models in particular, small changes in the noise

parameters often resulted in minimal changes to the model's predictions of category

and confidence responses, making parameter recovery in these cases more difficult.

This issue would have likely been more pronounced as the number of parameters in

the model increased (as in the different noise and integration assumptions).

As shown in **Figure 5B**, model class recovery was robust overall. This was

particularly true when using *AIC* for model selection (see **Figure S 6B),** which aligns

with findings from our previous work (West et al., 2023). For the bidimensional
models, recovery was also strong across assumptions (see **Figure 5A**), though the
integration models with the same noise assumption were slightly over-selected. This
is likely because we simulated with similar noise values across modalities, so the
additional four parameters in the different noise models did not improve the model's
fit sufficiently to outweigh the penalty for added complexity. Using *AIC* for model
selection also led to better recovery for the bidimensional models (see **Figure S 6A**).

Figure 5

Model Recovery

Note. Numbers and colours denote the probability that the data generated with
model X (y-axis) are best fit by model Y (x-axis). Confusability matrix for **(A)** all
model variants and **(B)** model classes using *AIC* for model selection. U.E.S refers to
the unscaled evidence strength model class. S.E.S refers to the scaled evidence
strength model class. Bayes. refers to the Bayesian model class. Int. refers to the
integration assumption. Diff. and same refers to the assumption about the noise
parameters across modalities.

Results

Participant Exclusion

To ensure that participants understood the task and the underlying category
distributions, we excluded data from participants whose categorisation accuracy was
not significantly above chance (50%) in the highest intensity condition (see **Figure S
1**), using a binomial test of significance. This test was applied to each task and
modality separately and included testing trials only (see **Table S 1**). We considered a

category response as correct if it was the most probable generating category, given
the stimulus attribute/s and category distributions for that task. One participant was
excluded using this criterion.

768 Confirming the Effect of Stimulus Manipulations: Model Free
769 GLMMs

Although our primary theoretical interest was in the model-based analysis of
the data, we first checked that our chosen stimulus manipulations had the intended
effects on category and confidence responses across tasks. As described below, we
fit generalised linear mixed models (GLMMs) to predict category and confidence
responses from the relevant stimulus features for each task. Because the expected
pattern of responses was not linear across stimulus attributes, we had to transform
the raw stimulus attributes to fit the GLMMs. To determine the effect of the stimulus
manipulations on category responses, we transformed stimulus attributes to
'evidence for category 2'.

779 *Confirming that the stimulus manipulations affected category*
780 *responses*

781 For each task, we computed the evidence for category 2 by evaluating the
782 probability density of the presented stimulus attribute for the category 2 distribution,
783 normalised by the total probability density for both category distributions for that
784 stimulus attribute,

$$E(C = 2) = \frac{N(x; \mu_2, \sigma_2)}{\sum_{t=1}^{2} N(x; \mu_t, \sigma_t)} \qquad \text{32)}$$

where N denotes the normal density function. The result indicated 'evidence
for category 2' for each stimulus attribute, which could range from 0.2 (stimulus was
highly likely to be from category 1) to 1 (stimulus could be from category 2 only). The
evidence value never reaches 0 because the category 1 distribution falls entirely
within the range of the category 2 distribution (see **Figure 2A**).

We fit linear mixed models using a logistic link function to predict category
response (1 or 2) from stimulus intensity and evidence for category 2, for each task
and modality. The models included an intercept term, intensity, evidence and the
interaction term between intensity and evidence as random effects. For each
regression analysis, we report the odds ratio for the fixed effect and 95% confidence
intervals in **Table 1**. As this analysis was intended to provide a descriptive summary

of the effect of the stimulus manipulations on responses across tasks, as opposed to

a hypothesis testing exercise, we report other statistical metrics and follow-ups in

Table S 2.

As expected, stimulus values that indicated increasing evidence for category

2 were positively predictive of category 2 responses in the visual (OR_{visual} = 2.55,

95% CI [2.05-3.16], p < .001), auditory ($OR_{auditory}$ = 2.33, 95% CI [1.61-3.39], p = <

.001), and audio-visual tasks ($OR_{audio-visual}$ = 3.38, 95% CI [2.58-4.42], p < .001).

Increasing stimulus intensity was also positively predictive of category 2 responses

for the visual (OR_{visual} = 1.48, 95% CI [1.14-1.93], p = .004) and auditory tasks

($OR_{auditory}$ = 1.46 [1.13-1.88], p = .004) but not the audio-visual task ($OR_{audio-visual}$ =

1.14, 95% CI [0.92-1.42], p = .223). These main effects were qualified by significant

two-way interactions between category 2 evidence and intensity, for the visual

(OR_{visual} = 1.73, 95% CI [1.57-1.90], p = < .001), auditory ($OR_{auditory}$ = 1.52, 95% CI

[1.33-1.73], p < .001) and audio-visual tasks ($OR_{audio-visual}$ = 1.25, 95% CI [1.15-1.37],

p < .001). As illustrated in **Figure 6A**, the effect of increasing category 2 evidence on

category 2 responses was strongest for the highest intensity stimuli and decreased

with stimulus intensity (see **Table S 2** for follow up tests).

These findings demonstrate that participants understood the category

distributions across modalities. Specifically, where there was an increase in the

relative probability that a stimulus was sampled from category 2, participants were

more likely to report that that stimulus had been sampled from category 2. The effect

of category 2 evidence was modulated by stimulus intensity, specifically, contrast for

the visual tasks and loudness for the auditory tasks, such that as the intensity of the

stimulus was reduced, category responses were more random and less influenced

by the category distributions. This effect was observed across tasks and confirmed

that the chosen stimulus manipulations had the intended effect on participants'

category responses. Because we were interested in quantifying the computations

underlying metacognitive judgements across modalities, this analysis also provided

evidence for similarities in the perceptual task requirements, allowing us to isolate

any differences in metacognition itself (Lehmann et al., 2022).

Figure 6

Model Free GLMMs

Note. **(A)** Predictions from a *GLMM* on category responses showed that the proportion of category 2 responses increased as a function of evidence for category 2 across the visual, auditory and audio-visual tasks (columns). The strength of this relationship was modulated by stimulus intensity (colours). **(B)** Predictions from a *GLMM* on confidence responses showed that across all tasks (columns), confidence increased as category diagnosticity, the relative evidence for the most probable category, increased. The strength of this relationship was modulated by stimulus intensity (colours).

Confirming that the Stimulus Manipulations Affected Confidence

To compare the effect of the stimulus manipulations on confidence across the different tasks we transformed stimulus values to 'category diagnosticity' using Equation 9 prior to fitting the GLMMs. The result indicated category diagnosticity for each stimulus value, which could range from 0.5 (both categories are equally likely) to 1 (stimulus could be from the most probable category only). We fit linear mixed models to predict confidence from stimulus intensity and category diagnosticity for each modality. The models included an intercept term, intensity, diagnosticity and the interaction term between intensity and diagnosticity as random effects. For each regression analysis, we report the regression coefficient for the fixed effect and 95% confidence intervals in **Table 1**.

Increasing category diagnosticity was predictive of increasing confidence in the visual ($\quad$ = 0.08, 95% CI [0.05-0.12], *p* < .001) and audio-visual tasks

($\beta_{audio-visual}$= 0.08, 95% CI [0.02-0.15], p = 0.10), but not the auditory task ($\beta_{auditory}$

= 0.09, 95% CI [-0.01-0.18], p = .066). Increasing stimulus intensity was predictive of

increasing confidence in the visual (β_{visual} = 0.51, 95% CI [0.31-0.70], p < .001),

auditory ($\beta_{auditory}$ = 0.50, 95% CI [0.30-0.70], p < .001) and audio-visual tasks

($\beta_{audio-visual}$ = 0.24, 95% CI [0.12-0.36], p < .001). We also observed significant

two-way interactions between category diagnosticity and intensity in the visual

(β_{visual} = 0.06, 95% CI [0.02-0.09], p = .002) and audio-visual task ($\beta_{audio-visual}$=

0.03, 95% CI [0.00-0.06], p = 0.024), but not the auditory task ($\beta_{auditory}$= 0.03, 95%

CI [-0.02-0.08], p = .211). For the visual and audio-visual task, increasing category

diagnosticity was associated with increasing confidence but the strength of this effect

was modulated by stimulus intensity. As illustrated in **Figure 6B**, the effect of

increasing category diagnosticity was strongest for the highest intensity stimuli and

decreased with lower stimulus intensities (see **Table S 2** for follow up tests).

These results indicate that as the relative evidence for a given category

increased, participants' confidence in their chosen category increased, especially for

the visual and audio-visual tasks. Taken with the results of the category GLMMs,

showing that participants' category responses corresponded with the most probable

category given the value of the stimulus, these findings suggest that participants

understood the category distributions and used them to guide their confidence

responses. The effect of the category distributions on confidence was modulated by

stimulus intensity, such that as the intensity of the stimulus decreased, confidence

responses were uniformly low. In the auditory task, changes in confidence were

driven primarily by changes in stimulus intensity and not category diagnosticity.

Table 1

Model-Free GLMMs for Category and Confidence Responses

Predictor		Tasks		
		Visual	Auditory	Audio-Visual
		Category		
Intercept	Odds Ratio	0.50*	0.59*	0.44**
	CI_{lower}	0.34	0.38	0.32
	CI_{upper}	0.74	0.93	0.61
Stimulus Intensity	Odds Ratio	1.48*	1.46*	1.14
	CI_{lower}	1.14	1.13	0.92
	CI_{upper}	1.93	1.88	1.42
Evidence for Category 2	Odds Ratio	2.55**	2.33**	3.38**
	CI_{lower}	2.05	1.61	2.58
	CI_{upper}	3.16	3.39	4.42
Intensity × Evidence	Odds Ratio	1.73**	1.52**	1.25**
	CI_{lower}	1.57	1.33	1.15
	CI_{upper}	1.90	1.73	1.37
		Confidence		
Intercept	β	2.51**	2.24**	2.51**
	CI_{lower}	2.14	1.97	2.11
	CI_{upper}	2.88	2.51	2.92
Stimulus Intensity	β	0.51**	0.50**	0.24**
	CI_{lower}	0.31	0.30	0.12
	CI_{upper}	0.70	0.70	0.36
Category Diagnosticity	β	0.08**	0.09	0.08*
	CI_{lower}	0.05	-0.01	0.02
	CI_{upper}	0.12	0.18	0.15
Intensity × Diagnosticity	β	0.06*	0.03	0.03*
	CI_{lower}	0.02	-0.02	0.00
	CI_{upper}	0.09	0.08	0.06

Note. CI terms refer to 95% confidence intervals calculated using the profile
likelihood method. Significance values are obtained using the Satterthwaite
approximation to calculate the degrees of freedom for the t-distribution based on the
estimated variance-covariance matrix of the model parameters (Lüdecke, 2022). For
category GLMMs (top section), we report the odds ratio (exponentiated coefficient
estimate) for ease of interpretation. The odds ratio represents the change in odds of
the outcome for a one-unit change in the predictor variable. For confidence GLMMs
(bottom section), we report standardised regression coefficients.
*$p < 0.05$, **$p < 0.001$

Computational Modelling

The GLMMs showed that our chosen stimulus manipulations had the intended

effects on category and confidence responses across modalities. We next sought to

characterise the algorithms underlying the category and confidence judgements

using computational modelling. We evaluated the performance of popular confidence

models from three classes: 1) unscaled evidence strength models, 2) scaled

evidence strength models and 3) Bayesian models. To assess the similarity in the

underlying algorithms, we first sought to determine whether a single class of models

provided the best account of responses across tasks. In the sections that follow, we

briefly re-describe the assumptions of each model class and then describe its

performance across tasks.

Performance of Model Classes

Unscaled Evidence Strength Model

According to the unscaled evidence strength account, confidence reports

depend on the distance between the sensory measurement and the category

decision criterion (*evidence strength*) only. These models do not independently

quantify *sensory uncertainty* as a core part of the decision process. Specifically, for

the unscaled evidence strength model, we assumed that the observer compares

their internal representation of a stimulus to a set of choice and confidence criteria

that do not change with stimulus intensity.

As a result of the fixed choice and confidence criteria, the model predictions

remain unchanged across intensity levels, as shown in **Figure 7A**. On the contrary,

the empirical confidence ratings clearly change as a function of stimulus intensity,

leading to a poor fit of the model to data across tasks. In line with this qualitatively

poor fit, the unscaled evidence strength model performed worst in terms of summed

AIC and *BIC* (see **Figure 7A**) and was selected as the best fitting class for only a

single participant in the auditory and audio-visual task and for no participants in the

visual task (see **Figure 9A**). These findings suggests that a model in which

confidence depends only on the strength of the evidence, and not on the amount of

sensory uncertainty in the representation of the stimulus, fails to accurately account

for the cognitive processes involved in perceptual metacognition.

    Figure 7

917   *Model Predictions Across Classes for Each Task*

918
Note. Columns show task modalities. Solid lines show model fit, where each row
represents a different model class, and data points show empirical data. Triangles
data points are from highest intensity level and circles are from the lowest intensity
level. Colours show proportions of category responses. For the audio-visual task, the
predictions from best performing model in each class is shown. Errors bars show
1*SEM*.

Scaled Evidence Strength Models

According to the scaled evidence strength account, confidence reports
depend on the distance between the observer's internal representation of the
stimulus and sensory uncertainty dependent choice and confidence criteria. We
estimated values of k and m for each response criterion, which allowed the effect of
sensory noise on the positioning of the criteria to differ across response options ($k_r +$
m_r). This meant that the criteria associated with low confidence regions could
expand under high sensory noise, while the corresponding high confidence regions
could contract (and vice versa for low sensory noise). We also estimated an
exponent on the measurement noise term, z, which was constant across criteria. The
exponent allowed for the effect of   on the choice and confidence criteria to change

as a function of σ.

As shown in **Figure 7B**, the scaled evidence strength model was able to
capture the empirical data well, where for the low intensity stimuli (those associated
with higher sensory noise), confidence ratings remained uniformly low across
stimulus values. For higher intensity stimuli (those associated with lower sensory
noise), the criteria shifted so that higher confidence ratings were given for stimulus
values associated with greater evidence strength (stimulus values with greater
category diagnosticity) and lower confidence ratings were given for stimulus values
associated with less evidence strength (stimulus values with lower category
diagnosticity).

As shown in **Figure 8**, the scaled evidence strength models had the lowest
summed *AIC* and *BIC* scores and they outperformed the alternative models for the
majority of individual participants (see **Figure 9A**), especially for the unidimensional
tasks. Specifically, the unscaled evidence strength models provided the best account
for 8 out of the 10 participants in the auditory task and 9 out of 10 the participants in
the visual task. We found that for the multidimensional task, the best performing
model class was more heterogenous but that on average, the scaled evidence
strength models still outperformed the other models, selected as the best performing
class for 7 out of the 10 participants. The overall performance of the scaled evidence
strength class suggests that observers consider sensory uncertainty when
generating a confidence report, unlike the unscaled evidence strength models, but
they do not do so in a way that is consistent with Bayesian inference (discussed in
more detail below).

Figure 8

Summed AIC and BIC Across Participants For Each Model Class

Note. The scaled evidence strength class had the lowest summed scores across the
visual (left panel), auditory (middle panel) and audio-visual (right panel) tasks.

Bayesian Models

According to Bayesian models of confidence, observers optimally combine
sensory information with prior knowledge to form a posterior belief about the nature
of the stimulus. In our task, we assumed that participants use the generating
category distributions to calculate a log posterior ratio, ——— which they
compare with choice-confidence criteria in the same measurement units. The
Bayesian models have fewer parameters than the scaled evidence strength models
because the choice and confidence criteria have the same positions in probability
space but the estimated values of sensory noise at each intensity level allow these
criteria to shift in perceptual space. That is, the amount of uncertainty associated
with the sensory observation causes the associated response regions to expand or
contract.

As shown in **Figure 7C**, the Bayesian models are not sufficiently flexible to
capture the empirical confidence data. Specifically, while the model predictions are
able to capture the empirical changes in responses as a function of stimulus values,
where greater evidence strength is associated with greater confidence, the
predictions show systematic deviations from the data across intensity levels. In
particular, the Bayesian models consistently over-estimate confidence for stimuli of
lower intensity and under-estimate confidence for stimuli of greater intensity. In terms
of model selection, we found that the Bayesian models were selected by a single
participant in the auditory and visual tasks and by 2 participants in the audio-visual
task (see **Figure 9**). In terms of summed *AIC* and *BIC*, the Bayesian models were
out-performed by the scaled evidence strength models (see **Figure 8**). The Bayesian
models performed poorly even when we allowed for additional flexibility in the model

by estimating participants' prior knowledge of the generating category parameters,
instantiating a subjective prior, rather than assuming they represent the true
parameters veridically. Overall, these findings suggest that participants do not
generate confidence reports in a way that is consistent with a Bayesian formalisation
in any of our tasks.

Figure 9

Akaike Weights Across Participants

Note. **(A)** Weights were calculated using the best-performing models in each class
for each participant. Darker colours show larger weights, demonstrating the superior
performance of the scaled evidence strength models across all tasks **(B)** Weights
were calculated across all possible combinations of assumptions and model classes
for the multidimensional task. Assumptions for model classes (Bayesian, scaled
evidence strength and unscaled evidence strength), the combination of stimulus
dimensions (integration or max) and sensory noise (same or different) are shown in
different columns. Darker colours show larger weights, demonstrating the superior
performance of the scaled evidence strength models with the integration and same
noise assumption.

Predicting Multidimensional Behaviour from Unidimensional

Behaviour

For the majority of cases, the scaled evidence strength models provided the
best account of choice and confidence across modalities, consistent with the results
from previous research using the same model classes (Adler & Ma, 2018; Denison et
al., 2018; West et al., 2023). Given the similarities in the type of algorithm used
across modalities, we wanted to investigate how well the confidence process
generalised by investigating how well behaviour in the unidimensional tasks (visual
and auditory) could predict behaviour in the multidimensional (audio-visual) task. To
this end, we used the estimated parameters from each participant's unidimensional
model fits to predict their category and confidence responses to multidimensional
stimuli. We did this using the model parameters from the scaled evidence strength
model, because it provided the best fit across participants. We combined the
parameters using the integration and different noise assumptions, as they
consistently outperformed the max models and included the same noise as a special
case.

Based on pilot data aimed at matching performance across tasks, we selected
a more compressed range of intensity levels for the multidimensional task, where the
second-highest intensity in the unidimensional tasks (level 3) corresponded to the
highest intensity in the multidimensional task (level 4). To generate predictions for
the multidimensional task, therefore, we estimated sensory noise parameters for the
intermediate audio-visual intensity levels (intensity 2 and intensity 3), which were not
tested in the unidimensional tasks. We fit an exponential function to the noise
parameters from the four unidimensional intensity levels and used this function to
predict noise values for the intermediate levels. The exponential function was chosen
for convenience, as it enforced monotonicity and required estimating only a single
parameter. We confirmed that it fit the data well (see **Figure S 2**). The tested
(intensity 1 and 4) and interpolated (intensity 2 and 3) noise parameters provided
noise estimates for each modality at the audio-visual intensity levels for each
participant. These were then combined using Equation 12 to calculate σ_{AV}.

We used the noise parameters to calculate choice and confidence criteria (*b*)
in each modality, applying the estimated *k*, *m* and *z* parameters (see Equation 19)
for each participant. These criteria were then transformed into a combined distance

metric using the equation $b_{AV} = \sqrt{(b_V{}^2) + (b_A{}^2)}$, yielding predicted criteria, b_{AV}, and

noise, σ_{AV}, parameters for each participant, directly estimated by the unidimensional

model parameters.

In the final step, we estimated an attentional weight   ) from the response
and stimulus data in the multidimensional task. This weight was applied to the visual
dimension, while the complementary weight   ) was applied to the auditory
dimension. By applying this weighting, we captured systematic biases in participants'
reliance on one stimulus dimension over the other. We then calculated the likelihood
of the dataset given the set of model parameters (see Equation 23). This model,
which generalises parameters from the unidimensional tasks to the multidimensional
task, is referred to as the *dimensionality-independent* model.

We found that with a single free parameter (the attentional weight), the
dimensionality-independent model predictions captured the empirical data from the
multidimensional task well (see **Figure 10**). The model did, however, underestimate
confidence for stimulus values associated with greater category diagnosticity (values
from the middle of the category 1 distribution and from the tails of the category 2
distribution), highlighting areas where confidence judgements may require further
refinement. Overall, however, the dimensionality-independent model demonstrated
strong predictive power across tasks, providing further evidence for the
generalisability of a single confidence algorithm across different types of perceptual
decisions.

Figure 10

Dimensionality-Independent Model Predictions

1062

Note. Model predictions from the dimensionality-independent model in which we
used the estimated parameters from the unidimensional (visual and auditory) model
fits to predict responses on the multidimensional (audio-visual) task. Solid lines show
model predictions and circular plotting symbols show empirical data from the audio-
visual task. Colours show proportion of category responses. Error bars show
SEM.

How is Sensory Information Combined Across Modalities?

Relatively little research has explored how confidence models perform in
tasks requiring the integration of information across sensory modalities. In this study,
therefore, we wanted to use our modelling approach to more comprehensively
characterise choice and confidence judgements in the audio-visual task. To do so,
we tested two key assumptions about the combination of sensory information across
modalities for each of the model classes, resulting in 4 variants for each core model
(i.e., a total of 16 models were fit to the audio-visual data across the 3 model
classes).

The first set of assumptions allowed us to investigate whether participants
attended to both dimensions of the multidimensional stimulus. In the 'integration'
models, we assumed that participants attended to both dimensions, while in the
'max' models, we assumed that they attended only to the most informative
dimension. We found that the integration models outperformed the max models in all
classes for every participant, confirming that confidence judgements relied on
combining auditory and visual input. However, participants did not appear to
integrate stimulus values across dimensions in an unbiased way. Parameter
estimates showed that all participants were biased towards the visual modality,
weighting the visual dimension of the stimulus more heavily in their confidence
judgement.

The second set of assumptions explored how participants represented
sensory noise. We implemented two model instantiations, one in which we estimated
noise values separately for each stimulus dimension (these estimates were later
combined across the two modalities) and the other in which we estimated a single
'modality-independent' sensory noise value. Models with a modality-independent
noise parameter performed better, suggesting participants rely on a generalised
noise estimate rather than combining noise from individual dimensions.

Together, these findings help elucidate how participants generate confidence
reports when integrating sensory information. We showed that confidence
judgements were based on both stimulus dimensions, instantiated in the model as a
weighted 'distance' measure. This combined measure, which provided a proxy for
evidence strength, was compared against choice and confidence criteria that were
adjusted based on a modality-independent noise estimate which varied with stimulus
intensity. As shown in **Figure 7B**, this model closely aligned with empirical data,
capturing response variation driven by stimulus values (evidence strength) and

intensity (measurement noise).

Discussion

Most previous studies of the computational basis of decision confidence have
relied on simple visual perceptual tasks, leaving unanswered how confidence is
formed in decisions involving other sensory modalities or those that require
integrating information across modalities. To address these questions, we used
computational modelling to analyse confidence judgements in perceptual decision-
making tasks involving visual, auditory and audio-visual stimuli. Our first set of
analyses investigated whether confidence judgements for such decisions are based
on the same underlying computational algorithms. Specifically, we compared the
performance of different classes of confidence models and evaluated whether the
same model class consistently fit data from all three tasks. We further tested the
generalisability of a single class of algorithms by examining how well predictions
generated from the unidimensional tasks (visual and auditory) aligned with empirical
data from the multidimensional (audio-visual) task. The second set of analyses
focused specifically on the multidimensional task, examining how participants
integrated sensory inputs from multiple modalities when making confidence
judgements. Within each model class, we tested different assumptions about the
integration process. In the sections that follow, we first discuss the model classes
and their performance across the different tasks, and then provide a more detailed
analysis of the modelling results from the multidimensional task.

A Theoretical Framework for Understanding Confidence Judgements: Comparing Model Classes

Building on an extensive body of research on the computational basis of
confidence in visual perceptual tasks (Adler & Ma, 2018; Aitchison et al., 2015;
Faivre et al., 2018; Locke et al., 2022; Navajas et al., 2017; Shekhar & Rahnev,
2024; West et al., 2023), we adapted models to evaluate how well they fit the data
from our visual, auditory and novel audio-visual categorisation tasks. Our model
classes instantiated different assumptions about how observers transform sensory
signals, whether unidimensional or multidimensional, into a choice and
corresponding confidence report. Within our general modelling framework, we
assumed that sensory input from the external world generates an internal response,

represented as a latent decision variable. The latent variable was modelled as a normal distribution, to capture the noise inherent in the sensory system itself. A key aspect of all our models, therefore, was the concept of *sensory uncertainty*, which refers to the variability (or noise) in the observer's internal representation of the stimulus. We assumed that this sensory uncertainty (characterised by the σ parameters) varied with stimulus intensity, with lower intensities leading to greater uncertainty. Sensory uncertainty also influenced the choice and confidence criteria, and different model classes handled this relationship in distinct ways.

For the non-Bayesian models, the decision variable was expressed in psychological units which were tied directly to the stimulus (e.g., a grating's orientation). The value of the stimulus itself, therefore, guided both category choice and confidence, with the choice-confidence criteria segmenting the possible values into discrete category and confidence response regions. We tested two types of non-Bayesian models: one which assumed fixed choice-confidence-criteria regardless of sensory uncertainty (unscaled evidence strength; Kepecs et al., 2008; Komura et al., 2013; Rahnev et al., 2011), and the other which assumed that the choice-confidence-criteria were adjusted based on the amount of sensory uncertainty in the decision variable (scaled evidence strength; Adler & Ma, 2018; Denison et al., 2018; Locke et al., 2022; West et al., 2023). In contrast, the Bayesian models approached sensory uncertainty by incorporating it into a probabilistic framework. These models used prior knowledge about the generating category distributions to compute a log posterior probability ratio. The magnitude of the log posterior probability ratio served as a choice and confidence metric, directly reflecting how sensory uncertainty impacts the perceived likelihood of a decision outcome.

Bayesian Class

We found that that Bayesian model class was outperformed across all tasks, both at the group level and for the majority of individual participants. Even after increasing their flexibility, by estimating participants' subjective prior knowledge rather than assuming they knew the true generating category parameters, the performance of the Bayesian models remained relatively poor. This consistently poor performance suggests that participants' confidence judgements in all our tasks are unlikely to rely on posterior probability computations, at least as represented by the models we tested. These findings align with previous research demonstrating the

limited applicability of Bayesian models to metacognitive decisions (Adler & Ma, 2018; Baranski & Petrusic, 1994; Locke et al., 2022; West et al., 2023). Notably, our results extend previous research by showing that confidence does not follow a strict Bayesian framework, even in multidimensional contexts where a modality-independent measurement system could theoretically resolve differences in how information from distinct sensory modalities is represented and integrated, resolving any 'translation issues'. The underperformance of the Bayesian models, even in tasks where integration may benefit from a unified measurement system, highlights the broader limitations of these models. Specifically, the rigid assumptions inherent to Bayesian inference may fail to account for the context-dependent nature of human confidence judgements.

Additionally, these findings suggest that the use of prior information in confidence judgements may be less straightforward than previously assumed. Rather than incorporating priors in a statistically optimal manner, individuals may employ them more heuristically, in ways that do not adhere to the strict probabilistic structure imposed by Bayesian models. This highlights the importance of future research exploring alternative modelling frameworks that incorporate prior knowledge in a more flexible and computationally efficient manner.

Unscaled Evidence Strength Class

In contrast to the Bayesian models, the unscaled evidence strength models instantiated the simplest view of metacognitive computations. In the unscaled evidence strength models, the decision variable, which was directly related to the stimulus itself, was compared to choice and confidence criteria that did not change as a function of sensory uncertainty. The unscaled evidence strength model performed worst on all tasks, except in a small number of individual cases (one participant in the auditory task and one participant in the audio-visual task). This finding aligns with previous studies that have documented poor performance of unscaled evidence strength models across unidimensional tasks performed in vision (Adler & Ma, 2018) and audition (West et al., 2023). The results from our study extend this understanding to multidimensional decisions, suggesting that even when observers must integrate stimulus information from distinct modalities, they rely on more sophisticated computations that factor in sensory uncertainty.

Scaled Evidence Strength Class

In the scaled evidence strength models, we assumed that the decision
variable was directly related to the value of the stimulus but that the choice and
confidence criteria were dynamically adjusted in response to sensory uncertainty.
This approach incorporated a scaling factor ($m\sigma^{z}$) that adjusted the criteria,
accommodating linear, quadratic and faster than quadratic relationships between
sensory uncertainty and criterion positioning. This flexibility allowed the model to
capture individual differences in how participants adapted to varying levels of noise.
The scaled evidence strength models outperformed all alternative models across
tasks, both for the majority of individual participants and for the group.

The scaled evidence strength framework allowed observers to integrate
sensory uncertainty into their confidence judgements, much like an 'optimal
observer,' but without the computational burden of posterior probability
computations. The success of the scaled evidence strength class aligns with
emerging evidence that confidence judgements rely on heuristic-like strategies that
approximate optimal behaviour (Adler & Ma, 2018; Aitchison et al., 2015; Denison et
al., 2018; West et al., 2023), extending these findings to decisions involving the
integration of multiple sources of information. The superior performance of this class
of models suggests that future studies may benefit from including models that
incorporate scaling mechanisms which allow confidence to dynamically adapt to
uncertainty, without relying on posterior probabilities.

A Shared Computational Basis for Confidence

The finding that the scaled evidence strength models outperformed the other
models across all tasks supports the idea that the same core algorithm governs
confidence judgements across modalities. We further investigated the
generalisability of the confidence process by testing whether behaviour in the
unidimensional tasks (visual and auditory) could predict behaviour in the
multidimensional (audio-visual) task using the scaled evidence strength algorithm.
Specifically, we used the parameters estimated from the unidimensional model fits
for each participant and estimated a single additional parameter to predict their
category and confidence responses to multidimensional stimuli. This approach,
referred to as the dimensionality-independent model, revealed that predictions
generated from the unidimensional tasks closely aligned with the observed data from
the audio-visual task. This finding reinforces the notion of a shared algorithmic basis

for confidence judgements across different types of perceptual decisions and aligns
with both our previous computational work (West et al., 2023) and other related
studies (Ais et al., 2016; Faivre et al., 2018; Fleck et al., 2006; Heereman et al.,
2015; Mazancieux et al., 2020; Morales et al., 2018; Pleskac & Busemeyer, 2010;
Rouault et al., 2018; Song et al., 2011) showing common mechanisms for
confidence judgements across modalities.

It is important to acknowledge, however, that our conclusions about a shared
algorithmic basis are limited by the scope of the models we tested. While we
included a range of models grounded in existing theoretical frameworks, it remains
possible that alternative models, either Bayesian or non-Bayesian, might account for
the data equally well or better. Nevertheless, the fact that the scaled evidence
strength algorithm outperformed other alternatives across all tasks, along with its
close fit to the data in each case, suggests that it captures a core feature of how
humans generate confidence judgements.

Looking ahead, future studies could explore the use of latent factor models to
gain deeper insights into the underlying shared computational mechanisms
(Schmiedek et al., 2007; Stevenson et al., 2024). In the context of our study, a latent
factor model could capture underlying cognitive constructs – such as modality-
independent confidence mechanisms – that operate across different sensory tasks.
Specifically, instead of modelling each task separately, a latent factor model could
account for both task-specific parameters and shared latent constructs that
generalise across tasks. By modelling both the latent cognitive constructs and task
parameters simultaneously, such models could provide insights into whether the
underlying confidence algorithm truly operates independently of the sensory modality
or if some modality-specific factors still play a role.

Metacognition Across Stimulus Dimensions: Comparing
Assumptions for Integrating Information Across Modalities

To the best of our knowledge, few studies have used computational modelling
to characterise the computations involved in metacognitive judgements when
integrating stimulus information across sensory modalities. Addressing this gap, we
developed a set of models to explore how people form confidence judgements when
integrating information from visual and auditory sources. In doing so, we examined
two assumptions about the confidence generation process.

The first set of assumptions quantified whether participants integrated both
stimulus dimensions or whether they relied on a single dimension only. In the
integration assumption, the decision variable was derived from a weighted
integration of both dimensions of the stimulus, whereas in the *max* assumption, it
relied solely on the dimension providing the strongest input. Our results showed
consistent evidence in favour of the integration assumption, with integration models
outperforming the max models across all classes and participants. This finding aligns
with prior research on perceptual decisions, which showed that people are able to
integrate information from different sensory modalities (Alais & Burr, 2004; Calvert et
al., 1998; Driver & Spence, 1998; Ernst & Banks, 2002; McGurk & MacDonald, 1967;
Shams et al., 2000; Stein & Meredith, 1993; Van Wassenhove et al., 2005).

This result also aligns with preliminary work that has investigated
metacognition for perceptual decisions involving multiple modalities (Faivre et al.,
2018; Gao et al., 2023). For example, Gao and colleagues (2023) demonstrated that
sensory cues are automatically integrated based on their reliability, even when
participants were instructed to disregard one of the modalities because it was task-
irrelevant. Our results build on those from Gao and colleagues (2023) by showing
that a reliability-weighted integration process also operates when both modalities are
explicitly task-relevant. This finding supports the idea that the integration process
reflects a broader, more fundamental principle of information processing.
Importantly, it shows that integration is not merely an artefact of a failure in selective
attention; rather, the brain appears to automatically combine information from all
available modalities, even if that information is not directly task-relevant.

Faivre and colleagues (2018) also explored confidence in audio-visual
decisions, demonstrating through computational modelling that confidence could be
predicted either from a bidimensional representation of an audio-visual signal or by
comparing unidimensional visual and auditory representations. Our approach
extends the work of Faivre and colleagues (2018) by considering a broader range of
theoretical model classes beyond modelling confidence as the probability of being
correct, an assumption that aligns most closely with our Bayesian models. This
broader modelling framework allowed us to investigate multiple possible algorithms
underlying confidence generation, providing deeper insight into how sensory
information is integrated at the metacognitive level.

Specifically, the weight parameter in our integration models also allowed us to

directly investigate whether participants systematically over-weighted one stimulus
dimension in their confidence judgement. All participants exhibited a bias toward the
visual modality. This over-reliance on visual information aligns with previous studies
suggesting that visual input tends to dominate multisensory integration (Alais & Burr,
2004; Colavita, 1974; Ernst & Banks, 2002; McGurk & MacDonald, 1967; Posner et
al., 1976; Rock & Victor, 1964; Welch & Warren, 1980). Importantly, our results
demonstrate that this visual dominance extends beyond perceptual judgements to
influence confidence judgements as well, reinforcing the idea that confidence reflects
the same biases present in perception. Further research could examine the relative
weighting of visual and auditory inputs more closely. One possible avenue would be
to implement dynamic models that update weighting on a trial-by-trial basis,
depending on stimulus characteristics. For example, the model could reflect a
baseline bias toward the visual modality that becomes less dominant when auditory
cues provide highly informative information. Another potential direction would involve
trying to experimentally manipulate the integration weights by instructing participants
to attend selectively to specific stimulus dimensions. This would allow future studies
to also explore whether these biases are modifiable through top-down attentional
control.

The second set of assumptions that we examined in our multidimensional
models was how participants estimated sensory uncertainty across modalities. We
tested two model variants to address this question: one in which sensory noise
values were estimated separately for each stimulus dimension and then combined
across modalities, and another in which a single modality-independent sensory noise
value was used across both dimensions. Our results indicated that participants
adjusted their choice and confidence criteria based on a single estimate of sensory
uncertainty, which varied systematically with the experimentally manipulated
intensity. However, this result should be interpreted cautiously, as our model
recovery analysis indicated a slight over-selection of models with the same noise
parameters across modalities, potentially biasing this conclusion (see **Figure 5**).

Despite this, we propose several possible interpretations to guide future
research. One is that the noise estimate in the multidimensional models may serve
as a general measure of uncertainty, rather than capturing low-level sensory noise
specific to each modality (e.g., noise which could be represented as variance in
neuron firing rates). From this perspective, participants may not require a fine-

grained noise estimate for each sensory input because a single general uncertainty measure suffices to regulate confidence across modalities. This interpretation aligns with other computational models of confidence including the weighted evidence and visibility (WEV) model (Rausch et al., 2018, 2021). The WEV model posits that individuals use visibility as a global signal shaping confidence judgements, regardless of the specific sensory modality contributing to the evidence. This visibility signal functions similarly to a global noise estimate, modulating the level of confidence placed in the accumulated evidence.

Alternatively, it is possible that our intensity manipulation was effective in matching the amount of sensory uncertainty across modalities, making a single noise estimate sufficient to capture the amount of low-level sensory noise in each modality. However, this explanation seems unlikely given the observed differences in categorisation performance at different intensity levels in the unidimensional tasks (see **Figure S 1**). An interesting direction for future research would be to vary intensity independently within each stimulus dimension, e.g., using high-intensity visual input combined with low-intensity auditory input. This approach would allow for a more nuanced investigation of whether participants can dynamically adjust their confidence judgements based on independent sensory noise levels across modalities.

Conclusions

In summary, our findings demonstrate that the scaled evidence strength models consistently outperformed the other model classes across all tasks and could be used to predict behaviour in the multidimensional task based on unidimensional data. These findings suggest that confidence judgements are governed by a shared algorithm that dynamically accounts for both sensory uncertainty and evidence strength, without relying on posterior probability computations. Additionally, we demonstrated that when making multidimensional confidence judgements, participants integrated visual and auditory information with a systematic bias toward the visual modality, and used a modality-independent measure of sensory uncertainty to modulate their confidence. Our results highlight the generalisability of the scaled evidence strength algorithm, even for tasks requiring integration across sensory modalities, and emphasise the limitations of Bayesian models in capturing the nuanced, context-dependent nature of human confidence judgements. These

1369   results open important avenues for future research, including the use of latent factor

1370   models to capture both shared and task-specific metacognitive constructs, exploring

1371   how sensory inputs are dynamically weighted for confidence, and investigating

1372   whether integration biases in confidence can be modulated through top-down

1373   attentional control.

References

Adler, W. T., & Ma, W. J. (2018). Comparing Bayesian and non-Bayesian accounts of human confidence reports. *PLOS Computational Biology*, *14*(11), e1006572. https://doi.org/10.1371/journal.pcbi.1006572

Ais, J., Zylberberg, A., Barttfeld, P., & Sigman, M. (2016). Individual consistency in the accuracy and distribution of confidence judgements. *Cognition*, *146*, 377–386. https://doi.org/10.1016/j.cognition.2015.10.006

Aitchison, L., Bang, D., Bahrami, B., & Latham, P. E. (2015). Doubly Bayesian Analysis of Confidence in Perceptual Decision-Making. *PLOS Computational Biology*, *11*(10), e1004519. https://doi.org/10.1371/journal.pcbi.1004519

Alais, D., & Burr, D. (2004). The Ventriloquist Effect Results from Near-Optimal Bimodal Integration. *Current Biology*, *14*(3), 257–262. https://doi.org/10.1016/j.cub.2004.01.029

Baranski, J. V., & Petrusic, W. M. (1994). The calibration and resolution of confidence in perceptual judgements. *Perception & Psychophysics*, *55*(4), 412–428. https://doi.org/10.3758/BF03205299

Boldt, A., de Gardelle, V., & Yeung, N. (2017). The impact of evidence reliability on sensitivity and bias in decision confidence. *Journal of Experimental Psychology: Human Perception and Performance*, *43*(8), 1520–1531. https://doi.org/10.1037/xhp0000404

Boldt, A., Schiffer, A.-M., Waszak, F., & Yeung, N. (2019). Confidence Predictions Affect Performance Confidence and Neural Preparation in Perceptual Decision Making. *Scientific Reports*, *9*(1), 4031. https://doi.org/10.1038/s41598-019-40681-9

Brainard, D. H. (1997). The Psychophysics Toolbox. *Spatial Vision*, *10*(4), 433–436. https://doi.org/10.1163/156856897X00357

Calvert, G. A., Brammer, M. J., & Iversen, S. D. (1998). Crossmodal identification. *Trends in Cognitive Sciences*, *2*(7), 247–253.

Colavita, F. B. (1974). Human sensory dominance. *Perception & Psychophysics*, *16*(2), 409–412. https://doi.org/10.3758/BF03203962

de Gardelle, V., Le Corre, F., & Mamassian, P. (2016). Confidence as a Common Currency between Vision and Audition. *PLOS ONE*, *11*(1), e0147901. https://doi.org/10.1371/journal.pone.0147901

Denison, R. N., Adler, W. T., Carrasco, M., & Ma, W. J. (2018). Humans incorporate attention-dependent uncertainty into perceptual decisions and confidence. *Proceedings of the National Academy of Sciences*, *115*(43), 11090–11095. https://doi.org/10.1073/pnas.1717720115

Desender, K., Boldt, A., & Yeung, N. (2018). Subjective Confidence Predicts Information Seeking in Decision Making. *Psychological Science*, *29*(5), 761–778. https://doi.org/10.1177/0956797617744771

Driver, J., & Spence, C. (1998). Crossmodal attention. *Current Opinion in Neurobiology*, *8*(2), 245–253.

Drugowitsch, J., Moreno-Bote, R., & Pouget, A. (2014). Relation between Belief and Performance in Perceptual Decision Making. *PLoS ONE*, *9*(5), e96511. https://doi.org/10.1371/journal.pone.0096511

Ernst, M. O., & Banks, M. S. (2002). Humans integrate visual and haptic information in a statistically optimal fashion. *Nature*, *415*(6870), 429–433. https://doi.org/10.1038/415429a

Faivre, N., Filevich, E., Solovey, G., Kühn, S., & Blanke, O. (2018). Behavioral, Modeling, and Electrophysiological Evidence for Supramodality in Human Metacognition. *Journal of Neuroscience*, *38*(2), 263–277. https://doi.org/10.1523/JNEUROSCI.0322-17.2017

Fleck, M. S., Daselaar, S. M., Dobbins, I. G., & Cabeza, R. (2006). Role of Prefrontal and Anterior Cingulate Regions in Decision-Making Processes Shared by Memory and Nonmemory Tasks. *Cerebral Cortex*, *16*(11), 1623–1630. https://doi.org/10.1093/cercor/bhj097

Gao, Y., Xue, K., Odegaard, B., & Rahnev, D. (2023). Common computations in automatic cue combination and metacognitive confidence reports. *bioRxiv*.

Hangya, B., Sanders, J. I., & Kepecs, A. (2016). A Mathematical Framework for Statistical Decision Confidence. *Neural Computation*, *28*(9), 1840–1858. https://doi.org/10.1162/NECO_a_00864

Heereman, J., Walter, H., & Heekeren, H. R. (2015). A task-independent neural representation of subjective certainty in visual perception. *Frontiers in Human Neuroscience*, *9*(551). https://doi.org/10.3389/fnhum.2015.00551

Kepecs, A., & Mainen, Z. F. (2012). A computational framework for the study of confidence in humans and animals. *Philosophical Transactions of the Royal Society B: Biological Sciences*, *367*(1594), 1322–1337. https://doi.org/10.1098/rstb.2012.0037

Kepecs, A., Uchida, N., Zariwala, H. A., & Mainen, Z. F. (2008). Neural correlates, computation and behavioural impact of decision confidence. *Nature*, *455*(7210), 227–231. https://doi.org/10.1038/nature07200

Komura, Y., Nikkuni, A., Hirashima, N., Uetake, T., & Miyamoto, A. (2013). Responses of pulvinar neurons reflect a subject's confidence in visual categorization. *Nature Neuroscience*, *16*(6), 749–755. https://doi.org/10.1038/nn.3393

Lehmann, M., Hagen, J., & Ettinger, U. (2022). Unity and diversity of metacognition. *Journal of Experimental Psychology: General*, *151*(10), 2396–2417. https://doi.org/10.1037/xge0001197

Li, H.-H., & Ma, W. J. (2020). Confidence reports in decision-making with multiple alternatives violate the Bayesian confidence hypothesis. *Nature Communications*, *11*(1), 2004. https://doi.org/10.1038/s41467-020-15581-6

Lisi, M., Mongillo, G., Milne, G., Dekker, T., & Gorea, A. (2021). Discrete confidence levels revealed by sequential decisions. *Nature Human Behaviour*, *5*(2), 273–280. https://doi.org/10.1038/s41562-020-00953-1

Locke, S. M., Landy, M. S., & Mamassian, P. (2022). Suprathreshold perceptual decisions constrain models of confidence. *PLOS Computational Biology*, *18*(7), e1010318. https://doi.org/10.1371/journal.pcbi.1010318

Lüdecke, D. (2022). *_sjPlot: Data Visualization for   Statistics in Social Science_. R package version 2.8.12* [Computer software]. <https://CRAN.R-project.org/package=sjPlot>

Masset, P., Ott, T., Lak, A., Hirokawa, J., & Kepecs, A. (2020). Behavior- and Modality-General Representation of Confidence in Orbitofrontal Cortex. *Cell*, *182*(1), 112-126.e18. https://doi.org/10.1016/j.cell.2020.05.022

Mazancieux, A., Fleming, S. M., Souchay, C., & Moulin, C. J. A. (2020). Is there a G factor for metacognition? Correlations in retrospective metacognitive sensitivity across tasks. *Journal of Experimental Psychology: General*, *149*(9), 1788–1799. https://doi.org/10.1037/xge0000746

McGurk, H., & MacDonald, J. (1967). Hearing lips and seeing voices. *Nature*, *264*, 746–748. https://doi.org/10.1038/264746a0

Meyniel, F., Sigman, M., & Mainen, Z. F. (2015). Confidence as Bayesian Probability: From Neural Origins to Behavior. *Neuron*, *88*(1), 78–92. https://doi.org/10.1016/j.neuron.2015.09.039

Morales, J., Lau, H., & Fleming, S. M. (2018). Domain-General and Domain-Specific Patterns of Activity Supporting Metacognition in Human Prefrontal Cortex. *The Journal of Neuroscience*, *38*(14), 3534–3546. https://doi.org/10.1523/JNEUROSCI.2360-17.2018

Navajas, J., Hindocha, C., Foda, H., Keramati, M., Latham, P. E., & Bahrami, B. (2017). The idiosyncratic nature of confidence. *Nature Human Behaviour*, *1*(11), 810–818. https://doi.org/10.1038/s41562-017-0215-1

Pelli, D. G. (1997). The VideoToolbox software for visual psychophysics: Transforming numbers into movies. *Spatial Vision*, *10*(4), 437–442. https://doi.org/10.1163/156856897X00366

Pleskac, T. J., & Busemeyer, J. R. (2010). Two-stage dynamic signal detection: A theory of choice, decision time, and confidence. *Psychological Review*, *117*(3), 864–901. https://doi.org/10.1037/a0019737

Posner, M. I., Nissen, M. J., & Klein, R. M. (1976). Visual dominance: An information-processing account of its origins and significance. *Psychological Review*, *83*(2), 157–171. https://doi.org/10.1037/0033-295X.83.2.157

Pouget, A., Drugowitsch, J., & Kepecs, A. (2016). Confidence and certainty: Distinct probabilistic quantities for different goals. *Nature Neuroscience*, *19*(3), 366–374. https://doi.org/10.1038/nn.4240

Rahnev, D., Maniscalco, B., Graves, T., Huang, E., de Lange, F. P., & Lau, H. (2011). Attention induces conservative subjective biases in visual perception. *Nature Neuroscience*, *14*(12), 1513–1515. https://doi.org/10.1038/nn.2948

Rausch, M., Hellmann, S., & Zehetleitner, M. (2018). Confidence in masked orientation judgements is informed by both evidence and visibility. *Attention, Perception, & Psychophysics*, *80*(1), 134–154. https://doi.org/10.3758/s13414-017-1431-5

Rausch, M., Hellmann, S., & Zehetleitner, M. (2021). Modelling visibility judgements using models of decision confidence. *Attention, Perception, & Psychophysics*, *83*(8), 3311–3336. https://doi.org/10.3758/s13414-021-02284-3

Rock, I., & Victor, J. (1964). Vision and Touch: An Experimentally Created Conflict between the Two Senses. *Science*, *143*(3606), 594–596. https://doi.org/10.1126/science.143.3606.594

Rouault, M., McWilliams, A., Allen, M. G., & Fleming, S. M. (2018). Human Metacognition Across Domains: Insights from Individual Differences and Neuroimaging. *Personality Neuroscience*, *1*, e17. https://doi.org/10.1017/pen.2018.16

Sanborn, A. N., & Chater, N. (2016). Bayesian Brains without Probabilities. *Trends in Cognitive Sciences*, *20*(12), 883–893. https://doi.org/10.1016/j.tics.2016.10.003

Sanborn, A. N., Griffiths, T. L., & Navarro, D. J. (2010). Rational approximations to rational models: Alternative algorithms for category learning. *Psychological Review*, *117*(4), 1144–1167. https://doi.org/10.1037/a0020511

Sanders, J. I., Hangya, B., & Kepecs, A. (2016). Signatures of a Statistical Computation in the Human Sense of Confidence. *Neuron*, *90*(3), 499–506. https://doi.org/10.1016/j.neuron.2016.03.025

Schmiedek, F., Oberauer, K., Wilhelm, O., Süß, H.-M., & Wittmann, W. W. (2007). Individual differences in components of reaction time distributions and their relations to working memory and intelligence. *Journal of Experimental Psychology: General*, *136*(3), 414–429. https://doi.org/10.1037/0096-3445.136.3.414

Shams, L., Kamitani, Y., & Shimojo, S. (2000). What you see is what you hear. *Nature*, *408*(6814), 788–788. https://doi.org/10.1038/35048669

Shekhar, M., & Rahnev, D. (2024). How do humans give confidence? A comprehensive comparison of process models of perceptual metacognition. *Journal of Experimental Psychology: General*, *153*(3), 656–688. https://doi.org/10.1037/xge0001524

Song, C., Kanai, R., Fleming, S. M., Weil, R. S., Schwarzkopf, D. S., & Rees, G. (2011). Relating inter-individual differences in metacognitive performance on different perceptual tasks. *Consciousness and Cognition*, *20*(4), 1787–1792. https://doi.org/10.1016/j.concog.2010.12.011

Stein, B. E., & Meredith, M. A. (1993). *The Merging of the Senses*. MIT Press.

Stevenson, N., Innes, R. J., Boag, R. J., Miletić, S., Isherwood, S. J. S., Trutti, A. C., Heathcote, A., & Forstmann, B. U. (2024). Joint Modelling of Latent Cognitive Mechanisms Shared Across Decision-Making Domains. *Computational Brain & Behavior*, *7*(1), 1–22. https://doi.org/10.1007/s42113-023-00192-3

Stewart, N., Chater, N., & Brown, G. D. A. (2006). Decision by sampling. *Cognitive Psychology*, *53*(1), 1–26. https://doi.org/10.1016/j.cogpsych.2005.10.003

van den Berg, R., Anandalingam, K., Zylberberg, A., Kiani, R., Shadlen, M. N., & Wolpert, D. M. (2016). A common mechanism underlies changes of mind

about decisions and confidence. *eLife*, *5*, e12192. https://doi.org/10.7554/eLife.12192

Van Wassenhove, V., Grant, K. W., & Poeppel, D. (2005). Visual speech speeds up the neural processing of auditory speech. *Proceedings of the National Academy of Sciences*, *102*(4), 1181–1186. https://doi.org/10.1073/pnas.0408949102

Wagenmakers, E.-J., & Farrell, S. (2004). AIC model selection using Akaike weights. *Psychonomic Bulletin & Review*, *11*(1), 192–196. https://doi.org/10.3758/BF03206482

Welch, R. B., & Warren, D. H. (1980). Immediate Perceptual Response to Intersensory Discrepancy. *Psychological Bulletin*, *88*(3), 638–667.

West, R. K., Harrison, W. J., Matthews, N., Mattingley, J. B., & Sewell, D. K. (2023). Modality independent or modality specific? Common computations underlie confidence judgements in visual and auditory decisions. *PLOS Computational Biology*, *19*(7), e1011245. https://doi.org/10.1371/journal.pcbi.1011245

White, C. N., Servant, M., & Logan, G. D. (2018). Testing the validity of conflict drift-diffusion models for use in estimating cognitive processes: A parameter-recovery study. *Psychonomic Bulletin & Review*, *25*(1), 286–301. https://doi.org/10.3758/s13423-017-1271-2