A common algorithm for confidence judgements across visual, auditory and

audio-visual decisions

Rebecca K West[1*], Natasha Matthews[1], Jason B Mattingley[1,2,3], & David K Sewell[1]

[1] School of Psychology, University of Queensland, Australia

[2] Queensland Brain Institute, University of Queensland, Australia

[3] Canadian Institute for Advanced Research, Canada

*Corresponding Author

E-mail: rebeca.west1@uq.net.au

Abstract

Most studies investigating the computational basis of decision confidence have focused on simple visual perceptual tasks, leaving open questions about how confidence is formed in decisions involving other sensory modalities or those requiring the integration of information across modalities. To address these gaps, we used computational modelling to analyse confidence judgements in perceptual decisions involving visual, auditory, and audio-visual stimuli. Drawing on research into visual confidence, we adapted models from the literature to evaluate their fit to our data, comparing three popular classes: unscaled evidence strength, scaled evidence strength, and Bayesian models. Our results show that the scaled evidence strength models consistently outperformed the other model classes across all tasks and could also be used to predict behaviour in the audio-visual task from the unidimensional auditory and visual model fits. These findings suggest that confidence judgements across different perceptual decisions rely on a shared algorithm that dynamically accounts for both sensory uncertainty and evidence strength, without the computation of posterior probabilities. Additionally, we investigated the algorithms used for multidimensional (audio-visual) confidence judgements specifically, showing that participants integrated both the visual and auditory dimensions of the stimulus, rather than relying solely on the most informative modality, and used a modality-independent measure of sensory uncertainty to adjust their confidence. Overall, our findings provide evidence for a common algorithm underlying confidence judgements across modalities and demonstrate the broad applicability of the scaled evidence strength algorithm, even in tasks requiring the integration of distinct sensory information.

Introduction

Human perceptual decisions are often accompanied by a level of confidence that reflects the accuracy of the decision (Boldt et al., 2017; Kepecs et al., 2008). This ability to accurately monitor and evaluate one's decision-making processes, referred to as *metacognition*, plays a crucial role in humans' capacity to make adaptive decisions. It prompts individuals to seek more information before committing to a choice (Desender et al., 2018), decide when to stop deliberating in a difficult decision (van den Berg et al., 2016), or anticipate effort or uncertainty in an upcoming decision (Boldt et al., 2019). Given the pivotal role that metacognitive judgements play in adaptive decision-making, one crucial goal for cognitive science has been to understand the psychological processes involved in generating such judgements.

Investigating the mechanisms that underpin metacognitive judgements, however, requires considering how these computations are shaped by the sensory modalities involved. For instance, forming confidence about the colour of a traffic light relies solely on visual information, confidence in whether a phone is ringing relies on auditory input, and confidence in whether a pineapple is ripe requires integrating information about its colour, smell, and texture (de Gardelle et al., 2016). Most previous studies investigating confidence judgements, however, focused on simple visual perceptual decisions only (Adler & Ma, 2018; Aitchison et al., 2015; Denison et al., 2018; Hangya et al., 2016; Li & Ma, 2020; Lisi et al., 2021; Locke et al., 2022; Navajas et al., 2017; Sanders et al., 2016).

To bridge this significant gap in our understanding about the formation of confidence across sensory modalities, our previous work utilised computational modelling to explore the psychological algorithms underlying confidence judgements across different perceptual domains (West et al., 2023). Specifically, we investigated whether the algorithms underlying confidence judgements were the same across vision and audition. Participants completed two versions of a categorisation task with visual and auditory stimuli, where they categorised each stimulus based on a perceptual feature (orientation or frequency) and then reported their confidence in that decision. In both modalities, we varied evidence strength (i.e., the strength of the evidence for a particular category) and sensory uncertainty (i.e. the amount of noise or uncertainty in the sensory signal). This allowed us to keep the decision context the same but vary the modality of presentation, isolating any similarities (*modality-*

independent processes) or differences (*modality-specific* processes) in the algorithms
used to generate confidence. In order to quantify the algorithms used for confidence,
we evaluated the performance of several classes of existing models which
mathematically formalise the mapping of evidence strength and sensory uncertainty
to confidence in different ways. We found that a single class of models, in which
confidence is derived from a subjective assessment of the strength of the evidence for
a particular choice, scaled by an estimate of sensory uncertainty, provided the best
account of confidence for both visual and auditory decisions. Comparing the 'settings'
(or parameters) of this process across modalities however, revealed that the algorithm
was tuned differently in each modality. That is, we found evidence for a modality-
general scaled evidence strength algorithm that was tuned specifically in each
modality (Lehmann et al., 2022; Masset et al., 2020; Mazancieux et al., 2020; Morales
et al., 2018; Rouault et al., 2018).

While our recent work (West et al., 2023) has expanded our understanding of
the algorithms that underlie confidence judgements in distinct sensory modalities,
many everyday decisions require the integration of information from multiple senses.
The psychological computations supporting metacognitive judgements in
multidimensional contexts, however, remain under-researched and poorly
understood. To address this gap, the current study explored both how participants
make metacognitive judgements for multidimensional perceptual decisions and how
the algorithms used for multidimensional decisions compare with those used in
unidimensional contexts-those involving a single sensory modality.

In exploring the processes involved in multidimensional decision-making, we
can build on substantial research that has investigated how individuals combine
information from different senses, such as vision and audition, to form a unified
perceptual representation. Specifically, cue combination research has explored
whether perceptual judgements are formed by combining inputs from different senses
in a weighted manner (integration perspective) or if they are based on a maximal input
approach (selection perspective), where the brain selects only the dominant sensory
input. Numerous studies have shown that individuals combine information from
multiple sensory modalities by weighting inputs based on their reliability, which is often
referred to as optimal integration or Bayesian cue integration. According to weighted
integration models, sensory input from different modalities is not treated equally;
instead more reliable (less noisy) information is given greater weight when integrating

cues (Ernst & Banks, 2002; McGurk & MacDonald, 1967). Other studies suggest that,

in certain situations, rather than combining cues, people rely predominantly on the

most informative or salient sensory modality (Posner et al., 1976; Welch & Warren,

1980). For example, under conditions of uncertainty or conflict, perceptual judgements

often favour the most easily processed modality (Posner et al., 1976; Welch & Warren,

1980).

The same question of how sensory input is combined across modalities also

applies to confidence judgements. Specifically, it is not known whether confidence is

based on a weighted integration of information from different senses, or if it follows a

selection-based approach, where confidence reflects input from the most informative

or salient modality only. Recent findings from Gao et al. (2023) support the weighted

integration perspective, showing that participants combined auditory and visual motion

cues based on their reliability. In Gao et al.'s multisensory task, participants were

instructed to judge the direction of an auditory motion cue and ignore a simultaneously

presented visual motion cue. Despite these instructions, they found that participants'

judgements and confidence were influenced by both the direction and reliability of the

visual cue. This effect was captured by a computational model which assumed that

the cognitive processes involved in confidence judgements are the same as those

used in lower-level stages of perception. These findings also align with the results of

Faivre et al. (2018) who used computational modelling to demonstrate that confidence

in an audio-visual task could be predicted by an integrated representation of auditory

and visual signals. Specifically, Faivre and colleagues (2018) modelled confidence as

the probability of being correct, showing that participants' perceived probability of

correctness depended on the integration of sensory inputs from both visual and

auditory modalities.

Building on these studies, here we also investigated how confidence

judgements operate in multidimensional contexts by using a task in which stimulus

information provided in different modalities was explicitly task relevant (Gao et al.,

2023), and by expanding the range of models used to investigate confidence beyond

purely probabilistic frameworks (Faivre et al., 2018). This approach enabled us to

compare multiple potential algorithms for generating confidence, offering a more

nuanced comparison between the integration-based and selection-based

perspectives. Moreover, by using an expanded modelling framework, we were able to

explore potential biases in integration as well as more directly investigate the role of

prior knowledge in confidence judgements, providing deeper insight into the cognitive

processes underlying multidimensional confidence formation.

A second, related question that we addressed in this study was whether the

algorithms used for confidence judgements differ between unidimensional stimuli,

such as a purely visual or auditory stimulus, and multidimensional stimuli, such as an

audio-visual stimulus. A modality-general framework suggests that the same

computational processes apply across both uni- and multidimensional contexts, where

a single algorithm is tuned to the specific decision context. However, one alternative

view posits that integrating information from multiple senses may require a distinct

computational strategy, possibly leading multidimensional decisions to rely on optimal

or near-optimal, Bayesian-like algorithms. That is, while simpler heuristic strategies

may be sufficient for unidimensional contexts (Adler & Ma, 2018; West et al., 2023), a

more statistically optimal approach could be better suited for multidimensional

contexts. Bayesian algorithms assume the computation of a probability metric which

automatically resolves any 'translation issues' when combining (or comparing) sensory

input from different modalities. Moreover, given the multidimensional nature of real-

world experiences, along with the richer feedback opportunities they provide, optimal

integration strategies may be more finely tuned for scenarios involving multiple

sensory inputs. To assess whether a unified computational framework can account for

both unidimensional and multidimensional judgements, we included unidimensional

visual and auditory and multidimensional audio-visual decisions in our study.

To characterise and compare the computational processes used for

metacognitive judgements in visual, auditory and audio-visual decisions, we use the

same modelling framework as in our previous work (West et al., 2023). Specifically,

we considered different theoretical models of decision confidence – Bayesian models

and non-Bayesian evidence strength-based models – and evaluated their

performance across the different types of perceptual decisions (see **Figure 1**). We

provide a brief overview of the different model classes below.

According to *Bayesian models*, observers optimally combine knowledge about

the statistical structure of a task (the "prior") with the present sensory input (the

"likelihood") to compute a posterior probability distribution over possible states of a

stimulus (Drugowitsch et al., 2014; Hangya et al., 2016; Kepecs & Mainen, 2012;

Meyniel et al., 2015; Pouget et al., 2016). The posterior probability distribution thus

represents every possible outcome and its associated probability. Bayesian models

stipulate that the observer uses the posterior probability distribution to guide both their

choice and confidence. For example, one possible strategy posits that an observer's

confidence increases with the posterior probability of the chosen outcome. In

experimental paradigms where numerical confidence ratings are used, a set of criteria

can map posterior probabilities to each level of the confidence rating scale. In the

example of judging the ripeness of a pineapple, a Bayesian observer would eat the

pineapple where $p(\textit{ripe} \mid \textit{pineapple})$ is above 0.5, with higher probabilities indicating

greater confidence in the decision. Another method for mapping posterior probability

to confidence is to use the log posterior probability ratio,

$\log\left(\frac{p(\textit{ripe} \mid \textit{pineapple})}{p(\textit{not ripe} \mid \textit{pineapple})}\right)$, which is unbounded and allows for greater differences in

confidence at different levels of sensory uncertainty (Adler & Ma, 2018; Locke et al.,

2022).

Unscaled evidence strength models posit that confidence depends entirely on

the strength of the evidence for a particular decision outcome. These models assume

that the observer uses the attribute value of the stimulus to directly quantify evidence

strength, with confidence increasing as evidence becomes stronger. For example, in

this framework, the more saturated the yellow colour of a pineapple, the more

confident the person is that it's ripe. The relationship between evidence strength and

confidence can also be quantified numerically by setting criteria based on evidence

strength. Unlike Bayesian models and scaled evidence strength models (described

below), unscaled evidence strength models do not explicitly account for sensory

uncertainty in the computation of confidence, focusing instead on the direct

relationship between attribute value and confidence.

Scaled evidence strength models posit that confidence depends on both the

strength of the evidence and the amount of sensory uncertainty associated with the

decision. According to scaled evidence strength models, sensory uncertainty is used

to scale evidence strength such that under conditions of high uncertainty, greater

evidence strength is required to produce the same level of confidence as under

conditions of low sensory uncertainty. For example, these models suggest that a

person would feel less confident about the ripeness of a pineapple whose colour is

highly variable relative to one where there is low variability in colour, even though the

average 'yellowness' of the two pineapples is the same. For numerical confidence

ratings, a point estimate of sensory uncertainty can be used to scale the criteria used

to delineate continuous evidence strength (Adler & Ma, 2018; Denison et al., 2018;
West et al., 2023). Although both scaled evidence strength and Bayesian models
consider evidence strength and sensory uncertainty as important for confidence,
scaled evidence strength models do not rely on probabilistic inference. Because
scaled evidence strength models do not involve the computation of a probability
metric, they are considered less computationally complex, and arguably, a more
feasible explanation of human cognition (Sanborn et al., 2010; Sanborn & Chater,
2016; Stewart et al., 2006).

The Current Study

The aim of the current study was to differentiate between these different
theoretical accounts and use computational models to characterise the computations
involved in confidence for visual, auditory and audio-visual decisions. Specifically, one
key focus of our analyses was to investigate whether the same computational
algorithms governed confidence judgements across all three types of decisions. To
address this question, we evaluated the performance of the different model classes
and tested whether a single class consistently fit the data across tasks. We also
examined the generalisability of the models by determining how well predictions from
the unidimensional tasks (visual and auditory) align with observed behaviour in the
audio-visual task. A second key focus of our analyses was to understand how
participants integrate sensory information from multiple modalities when making
multidimensional confidence judgements. To characterise the algorithms supporting
these judgements, we systematically explored different assumptions regarding how
sensory inputs are combined across modalities within each model class.

 Figure 1

Choice and Confidence Criteria Across Models

Note. **(A)** Illustration of category structures for unidimensional task and **(B)**
multidimensional task. For the unscaled evidence strength models (top row), the
choice and confidence criteria do not change as a function of sensory noise for both
the **(C)** unidimensional and **(D)** multidimensional tasks. For the scaled evidence
strength models and Bayesian models (middle and bottom rows, respectively), the
choice and confidence criteria change as a function of sensory uncertainty/noise.

Method

Overview

Participants completed 3 categorisation tasks: (1) a visual categorisation task, (2) an auditory categorisation task and (3) an audio-visual categorisation task. In each task, participants made a two-alternative forced choice category decision (Category 1 or Category 2), followed by a 4-point confidence rating, ranging from low confidence (1) to high confidence (4). Category membership was determined by an attribute of the stimulus: orientation for visual stimuli (drifting Gabor patches), frequency for auditory stimuli (pure tones) and both orientation and frequency for the audio-visual stimuli (drifting Gabor patches with simultaneously presented pure tones). A normal distribution of the relevant stimulus attribute defined each category where the category distributions had the same mean and different standard deviations. Sensory uncertainty also varied with stimuli presented at 4 different intensities. In the visual tasks, intensity depended on the contrast of the Gabor patch (3.3%, 5%, 6.7%, 13.5%). In the auditory tasks, intensity depended on the loudness of the tone (equivalent of -3 dB SPL, 4 dB SPL, 10.5 dB SPL, 17 dB SPL for a 1 kHz pure tone). In the audio-visual task, both contrast (3.3%, 4.2%, 5.3%, 6.7%) and loudness (equivalent of -3 dB SPL, 2 dB SPL, 6 dB SPL, 10.5 dB SPL for a 1 kHz pure tone) varied together. The intensity levels were chosen to achieve a similar range of performance across all tasks based on pilot data.

 Figure 2

254 *Experimental Task*

255
256 *Note.* **(A)** Category distribution for auditory (left), visual (middle) and audio-visual
257 (right) task. **(B)** Trial structure for testing trials. **(C)** Levels of stimulus intensity.

Participants

259   Participants were recruited from the University of Queensland's research
260 participation scheme and were reimbursed for their time ($20 per hour in cash or gift
261 cards). Inclusion criteria required normal (or corrected-to-normal) vision and normal
262 hearing, both assessed by self-report. After exclusions (see the Results section for
263 details), the final sample comprised of 10 participants.

Categorisation Task

As shown in **Figure 2A**, the categories were defined by normal distributions
which had the same mean and different standard deviations. In the visual modality,
larger rotations clockwise or counter clockwise relative to horizontal were more likely
to be sampled from category 2 ($\mu_{cat2} = 0°$, $\sigma_{cat2} = 12°$) whereas smaller rotations
relative to horizontal were more likely to be sampled from category 1 ($\mu_{cat1} = $
$0°, \sigma_{cat1} = 3°$). In the auditory modality, lower and higher frequency tones were more

likely to be sampled from category 2 ($\mu_{cat2} = 2700\,Hz, \sigma_{cat2} = 500\,Hz$), whereas

intermediate frequency tones were more likely to be sampled from category 1 ($\mu_{cat1} =$

$2700\,Hz$, $\sigma_{cat1} = 125\,Hz$). In the audio-visual task, the categories were defined by

bivariate normal distributions with the same means and standard deviations as in the

visual and auditory versions of the tasks ($\mu_{cat1} = [0°, 2700\,Hz]$; $\sigma_{cat1} =$

$[3°, 125\,Hz]$; $\mu_{cat2} = [0°, 2700\,Hz]$; $\sigma_{cat2} = [12°, 500\,Hz]$). To maximise correct

responses in each task, the ideal observer would use the points where the category

distributions intersect, reporting that stimulus values contained within the intervals

were sampled from category 1 and stimulus values outside the intervals were sampled

from category 2 (see dotted lines in **Figure 2A**).

Stimuli

Visual Stimuli

As in West et al. (2023), the visual stimuli were Gabor patches. Each Gabor

had a Gaussian envelope with a standard deviation of 1.2 degrees of visual angle

(dva), a spatial frequency of 0.5 cycles per dva and the starting phase was

randomised. The Gabors drifted with a speed of 6 cycles per second.

Auditory Stimuli

As in West et al. (2023), the auditory stimuli were pure tones presented in

stereo via headphones (Sennheiser HD 202). Each tone included a 5 ms linear onset

and offset ramp to avoid clicking artifacts. Tones were synthesised with a 28 kHz

sampling rate using an ASIO4ALL sound drive. Loudness was calibrated following the

International Standard ISO 226:2003: Acoustics- Normal Equal-Loudness-Level-

Contours (International Standardization Organisation, 2003), and final intensity levels

were selected through extensive pilot testing.

Audio-Visual Stimuli

The audio-visual stimuli were simultaneously presented Gabors and tones, the

parameters of which were the same as described above.

Procedure

All participants completed all combinations of tasks in 3 separate testing

sessions (i.e., visual task, auditory task, audio-visual task). The order of the visual and

auditory tasks was counterbalanced across participants and all participants completed

the audio-visual task in the final session.

Participants were seated in a dark room, at a viewing distance of 57 cm from

the screen, and their head was stabilised with a chinrest. Stimuli were presented on a
gamma-corrected 60 Hz 1920-by-1080 display. The computer display (ASUS
VG248QE Monitor) was connected to a Dell Precision T1700, calibrated with a
ColorCal MKII (Cambridge Research Systems). Stimuli were generated and presented
using custom code and the Psychophysics Toolbox extensions (Brainard, 1997; Pelli,
1997) for MATLAB.

In each session, participants received instructions for that session's task which
included an explanation about how the stimuli were generated from the relevant
category distributions. To further illustrate these distributions, participants were then
shown 36 stimuli that were randomly sampled from category 1, followed by category
2. They then completed the category training and testing (detailed below). Each
session took approximately 1 hour.

Testing

At the start of each trial, a fixation cross was presented centrally for 1 s. The
fixation cross was then extinguished, and a stimulus was presented (either a visual,
auditory or audio-visual stimulus depending on session; all 50 ms in duration).
Immediately after the offset of the stimulus, participants were able to respond category
1 or category 2 by pressing a button (F or J keys) with their left or right index finger,
respectively. Participants were then prompted to make a confidence judgement for
their chosen category with text that read 'Confidence?' presented centrally.
Participants used the 1- 4 number keys to indicate their confidence. The inter-trial
interval was 1 s, after which the fixation cross reappeared.

Within a testing block, an equal number of stimuli were shown from each
category and intensity level (i.e., 15 trials per cell of the design). Stimulus attributes
were sampled randomly from the relevant category distribution. Participants
completed 6 testing blocks per session (120 trials per block, a total of 720 trials per
session). The order of both category and intensity level was randomised within a block.

At the end of each block, participants were required to take at least a 30 s break.
During the break, they were shown the percentage of trials that they had correctly
categorised in the most recent block. Participants were also shown a list of the top 10
block scores (across all participants, indicated by initials) for the task they had just
completed. This was intended to motivate participants to score highly. We did not
provide trial-by-trial feedback during testing to ensure that confidence judgements

reflected participants' subjective evaluations of uncertainty rather than being
influenced by external correction signals.

Training

The trial procedure in training blocks was the same as in testing blocks, except
that trial-to-trial feedback was given, only the highest intensity level was used for
stimulus presentation and participants were not required to make confidence
judgements. For the trial-to-trial feedback, the word "correct" in green or "incorrect" in
red was displayed for 1.1 s after participants made their response. Participants
completed 2 training blocks (120 trials per block, in total 240 trials) per session.
Training was intended to further familiarise participants with the generating category
distributions.

Model Specification

To model responses, we assumed that on each trial, *t*, observers perceived a
sensory signal, *x*. Observers transformed that sensory signal into a *decision variable*,
the computation of which differed across model classes. To make a discrete category-
confidence response, we assumed that observers compared the decision variable to
a set of *criteria*. In the following sections, we describe our stimulus standardisation
procedure, our assumptions about the sensory signals, decision variable, decision
criteria and then describe the model fitting procedure.

Standardisation of Stimulus Values

357   To compare stimulus values and model parameters across modalities, we
358 standardised all stimulus values before fitting models. To standardise stimulus values,
359 we subtracted the mean and divided by the standard deviation of all presented
360 stimulus values in each modality such that:

$$Z = \frac{s - \bar{x}_{[M]}}{sd_{[M]}} \tag{1}$$

where Z is the standardised stimulus value; s is the true stimulus value in its
original perceptual units (degrees or hertz); $\bar{x}$ is the mean of all presented stimulus
values for a given modality M (visual or auditory) and sd is the standard deviation of
the same set of stimulus values. For the audio-visual task, stimulus values were
standardised separately within each modality. This standardisation process was
consistent with the idea that participants built up a reliable internal representation of
the categories during training such that they understood the relative frequencies of

different stimulus values within each category distribution.

The Sensory Distribution

In all models, we assumed that the observer's perception of the stimulus, *x*,

was a noisy measurement of the true stimulus presented on trial *t* (see **Figure 3A**).

We modelled this noisy internal measurement using a Gaussian distribution, referred

to as the *sensory distribution*. The sensory distribution was centred on the true

stimulus attribute, s_t, with a standard deviation that depended on the intensity of the

stimulus, σ_I. σ was estimated separately at each stimulus intensity level, subject to the

constraint that it decreased monotonically as intensity increased. That is, we assumed

that greater stimulus intensity was associated with less sensory noise and thus,

smaller values of σ (see **Figure 3A**). Below we describe the derivation of *x* and σ for

both the unidimensional (visual, auditory) and multidimensional (audio-visual) stimuli.

Unidimensional Stimuli

381   On a given trial, the sensory distribution for the unidimensional stimuli, x_{uni},

382   was defined as:

$$x_{uni} \sim N(s, \sigma_I^2) \tag{2}$$

383   where N denotes the normal density function, s is the true stimulus attribute,

384   and σ is the estimated standard deviation of the distribution, given the stimulus

385   intensity level, *I.*

Multidimensional Stimuli

387   For the multidimensional stimuli, the sensory signal comprised two dimensions,

388   one for each modality. The sensory distribution was thus described by a bivariate

389   Gaussian distribution:

$$x_{bi} \sim N(\boldsymbol{\mu}, \Sigma) \tag{3}$$

390   where N denotes the normal density function, $\boldsymbol{\mu}$ denotes a vector of stimulus

391   attributes and Σ a covariance matrix. Specifically, the vector of stimulus attributes on

392   a given trial was described by:

$$\boldsymbol{\mu} = \begin{pmatrix} s_V \\ s_A \end{pmatrix} \tag{4}$$

393   where s_V was the stimulus attribute for the visual dimension and s_A was the

394   stimulus attribute for the auditory dimension. The covariance matrix was described by:

$$\Sigma = \begin{bmatrix} \sigma_{V[I]}^2 & 0 \\ 0 & \sigma_{A[I]}^2 \end{bmatrix} \tag{5}$$

where $\sigma_{V[I]}$ was the estimated standard deviation of the visual dimension, $\sigma_{A[I]}$

was the estimated standard deviation of the auditory dimension, given the stimulus

intensity level, *I*. We tested two different assumptions about σ: either that σ differed

across the stimulus dimensions, referred to as the *different noise* variant, or that σ was

the same across the stimulus dimensions, referred to as the *same noise* variant.

Same Noise. For the *same noise* model variants, we assumed that sensory

noise was the same across the two stimulus dimensions such that:

$$\sigma_{V[I]} = \sigma_{A[I]} \tag{6}$$

where σ_V was the estimated amount of sensory noise in the visual dimension,

σ_A was the estimated amount of sensory noise in the auditory dimension, and *I* indexed

the stimulus intensity level (see top right panel of **Figure 3B**).

Different Noise. For the *different noise* variants, we assumed that sensory

noise   differed   across   the   two   stimulus   dimensions   such   that

$\sigma_{V[I]} \neq \sigma_{A[I]}$, where σ_V was the estimated amount of sensory noise in the visual

dimension, σ_A was the estimated amount of sensory noise in the auditory dimension

and *I* indexed the stimulus intensity level (see bottom left panel of **Figure 3B**). Under

the different noise assumption, we estimated σ separately for each stimulus dimension

and intensity level, constrained by monotonicity within each domain.

Figure 3

Sensory Signals

Note. **(A)** For the unidimensional stimuli, the observers' internal representation of the
stimulus was approximated with a Gaussian distribution centred on the true stimulus
attribute with a standard deviation, σ, that depended on the intensity level of the
stimulus. **(B)** The observer's internal representation of the multidimensional stimuli
was approximated with a bivariate Gaussian distribution. Sensory signals in each
dimension, x_A and x_V, were combined into a single measure, l. Top right quadrant
shows unbiased integration of dimensions with the same amount of sensory noise
across dimensions. Bottom left quadrant shows unbiased integration with different
amounts of sensory noise in each dimension. Samples were taken from the shaded
region and each combination of values was transformed into a single measure **(C)**
Black data points show unbiased integration of stimulus attributes across dimensions,
orange data points show an auditory bias and blue data points show a visual bias for
4 different audio-visual stimuli (shapes).

Transformation of Bivariate Sensory Distribution. For ease of exposition,

we transformed the bivariate sensory distribution, x_{bi}, into a univariate Gaussian

distribution defined by:

$$x_{comb} \sim N\left(l, \sigma^2_{AV[I]}\right) \tag{7}$$

where N denotes the normal density function, l denotes the mean and σ_{AV} the

standard deviation of the resulting univariate distribution. We calculated l as the

Euclidian distance of a set of multidimensional stimulus coordinates, $[x_V, x_A]$, from the

centre of the standardised stimulus space, [0,0] (henceforth referred to as the *origin*).

We tested two different assumptions about the computation of l: either that the

observer attended to both dimensions of the stimulus (*integration* model variants) or

that the observer attended to only a single dimension of the stimulus (*max* model

variants).

Integration Variants. For the integration model variants, we assumed that the

observer attended to both dimensions of the stimulus to make their decision. We

therefore computed a weighted combination of the sensory signals received from each

dimension such that:

$$l = \sqrt{w_V(x_V{}^2) + (1 - w_V)(x_A{}^2)} \qquad (8)$$

where w_V was the weight for the visual stimulus dimension, x_V was the

perceived stimulus value for the visual dimension and x_A was the perceived stimulus

value for the auditory dimension. See **Figure 3C** where orange data points show

integration with an auditory bias (where $w_V < 0.5$) and blue data points show

integration with a visual bias (where $w_V > 0.5$). The weights were constrained to be

non-negative and bounded on the interval [0, 1] such that $w_V + w_A = 1$.

Max Variants. For the max model variants, we assumed that the observer

attended to a single dimension of the stimulus only and thus, the computation of l

depended on a single value from the set of stimulus coordinates $[x_V, x_A]$. The "selected"

dimension was determined by which value was the most informative about the

generating category. The informativeness of the generating category was referred to

as *category diagnosticity* and reflected the probability density of the presented

stimulus value for the most probable category distribution, normalised by the total

probability density of the stimulus for both category distributions:

$$CD = \frac{\max\left(\varphi(s_n; \mu_1, \sigma_1), \varphi(s_n; \mu_2, \sigma_2)\right)}{\sum_{C=1}^{2} N(s; \mu_C, \sigma_C)} \qquad (9)$$

457   where φ denoted the normal density function, μ_1 and μ_2 were the means of the

458   generating category 1 and category 2 distributions and σ_1 and σ_2 were the standard

459   deviations of the generating category 1 and category 2 distributions. *C* denoted the

460   category and s_t was the stimulus attribute on trial *t*. The distance, l, was then

461   calculated as the absolute value of the selected dimension:

$$l = |x_V| \; if \; CD(s_V) > CD(s_A) \qquad (10)$$

$$l = |x_A| \ if \ CD(s_V) < \ CD(s_A)$$

The computation of l for the max models was thus consistent with the
integration models because the result was equivalent to a distance measure involving
only a single term.

Same Noise and Different Noise Variants. The standard deviation of x_{comb}, σ_{AV},
depended on the model variant, specifically the same noise or different noise
assumption *and* the integration or max assumption. Under the same noise
assumption:

$$\sigma_{AV[I]} = \ \sigma_{V[I]} = \ \sigma_{A[I]} \qquad (11)$$

where σ_V was the estimated standard deviation of the visual dimension of x_{bi},
σ_A was the estimated standard deviation of the auditory dimension of x_{bi}, and I indexed
the stimulus intensity level.

Under the *integration different noise* assumption, we calculated a weighted
combination of the standard deviations of each dimension of the bivariate sensory
distribution x_{bi}:

$$\sigma_{AV[I]} = \ \sqrt{w_V \ \sigma_{V[I]}^2 + (1 - \ w_V) \ \sigma_{A[I]}^2} \qquad (12)$$

where w_V was the estimated weight for the visual dimension of the stimulus (as
in Equation 8), σ_V was the estimated standard deviation of the visual dimension of x_{bi},
σ_A was the estimated standard deviation of the auditory dimension of x_{bi}, and I indexed
the stimulus intensity level. Using Equation 12 to combine the estimates of σ across
modalities meant that the resulting value of σ_{AV} was of the same magnitude as σ_V and
σ_A. Under the *max different noise* assumption,

$$\sigma_{AV[I]} = \begin{cases} \sigma_{V[I]} \ if \ CD(s_V) > \ CD(s_A) \\ \sigma_{A[I]} \ if \ CD(s_V) < \ CD(s_A) \end{cases} \qquad (13)$$

481   where $CD(s_V)$ was the category diagnosticity of the visual dimension of the
482   stimulus and $CD(s_A)$ was the category diagnosticity of the auditory dimension of the
483   stimulus (see Equation 9).

Decision Variable

In all models, we assumed that the observer transformed the sensory signal
into a *decision variable* which was then compared with a set of criteria. We tested
different assumptions about the computation of the decision variable which quantified
different theoretical models about the choice and confidence generation process. We

categorised these theoretical models into three broad classes: (1) the unscaled
evidence strength models, (2) the scaled evidence strength models and (3) the
Bayesian models. One of the distinguishing factors among candidate classes
concerned whether the decision variable was represented in *psychological space*
(unscaled evidence strength and scaled evidence strength; discussed in more detail
below) or *probability space* (Bayesian; discussed in more detail below).

For models that represented the decision variable in *psychological space*, the
decision variable was assumed to be in the same psychological units as the sensory
signals. For these models, we therefore use x to denote both the sensory signal and
the decision variable. For models that represented the decision variable in *probability*
space, we assumed that the sensory signal was transformed into a probability metric
which was then compared with choice and confidence criteria in the same probability
units. For these models we use d to denote the decision variable and distinguish it
from the sensory signal.

To illustrate the difference between the computation of a decision variable
which is represented in psychological space or probability space: for a non-Bayesian
model with category-confidence criteria in psychological space, a Category 2
Confidence 1 response might be made for any visual stimulus perceived as having an
orientation between 0 and 5 degrees (or 0 and 0.6 in standardised stimulus units). For
a Bayesian model, where the criteria were in probability space, the same Category 2
Confidence 1 response might be made for any visual stimulus perceived as having a
log posterior probability ratio between 0 and 0.5.

Non-Bayesian Models

512   As described above, for the non-Bayesian models, the sensory distribution and
513   the decision variable distribution were represented in the same psychological space.
514   This meant that *the sensory distributions* (x_{uni} and x_{comb} for the unidimensional and
515   multidimensional stimuli respectively) *were equivalent to the decision variable*
516   *distributions*.

Bayesian Models

518   Consistent with Bayesian decision theory, for the Bayesian models we
519   assumed that the observer combined prior knowledge of the generating category
520   distributions with observed stimulus information to form posterior beliefs about
521   category membership. For all Bayesian models, therefore, we assumed that the

observer transformed the sensory signal into a log posterior probability ratio, *d*, to make a decision. The log posterior probability ratio represented the (log) ratio of posterior beliefs about category membership, such that $d = log \frac{p(C=1 \mid x)}{p(C=2 \mid x)}$ where *x* represented the perceived value of the stimulus on a given trial. When the log posterior probability ratio was positive, there was greater evidence for category 1. For the Bayesian models, we assumed that category and confidence reports depended on the sensory signal *x* only via *d.* Following Adler and Ma (2018), we used the following derivation of *d:*

$$d = \frac{1}{2} log \frac{\sigma^2 + \sigma_2^2}{\sigma^2 + \sigma_1^2} - \frac{\sigma_2^2 - \sigma_1^2}{2(\sigma^2 + \sigma_1^2)(\sigma^2 + \sigma_2^2)} x^2 + log \frac{p(C=1)}{p(C=2)} \tag{14}$$

where σ_1 was the standard deviation of the category 1 distribution, σ_2 was the standard deviation of the category 2 distribution and σ was the fitted value of sensory noise, approximating the amount of sensory uncertainty in the observer's internal representation of the stimulus. Because we sampled equally from each category, we assumed that *p(C=1)=p(C=2)=*0.5 such that $log \frac{p(C=1)}{p(C=2)}$ was 0 in Equation 14.

Log Posterior Probability Ratio with Free Category Distribution Parameters. The log posterior probability ratio model described above assumes that the observer knows the true values of the standard deviations of the category distributions σ_1 and σ_2 in Equation 14. We also tested a version of the model in which the observer had imperfect knowledge of the parameters of the generating category distributions. In this model, we estimated the values of σ_1 and σ_2 as free parameters.

Choice and Confidence Criteria Across Unidimensional and Multidimensional Tasks

Note. In the unidimensional task (top panel), 7 symmetrical criteria partitioned the range of the decision variable into discrete category and confidence response regions (top left panel; see legend at the bottom for corresponding responses). The sensory distribution was compared against the choice and confidence criteria to calculate a response probability (top right panel). In the multidimensional task, 7 circular criteria partitioned the response regions (bottom left panel) and were compared against the bivariate sensory distribution (bottom right panel).

Choice and Confidence Criteria

As described above, in all models we assumed that the decision variable was compared with a set of criteria. The criteria partitioned the range of the decision variable into discrete category and confidence response regions so that if the decision variable fell within a defined region, response *r* was given (see **Figure 4**). Given four confidence levels for each of the two categories, this yielded eight response regions, $r \in \{1, 2, 3, ..., 8\}$, each corresponding to a unique category and confidence combination. The choice and confidence criteria were positioned in the same units as the decision variable and required different assumptions across the different theoretical model classes. These assumptions are described below for the non-Bayesian models, where the decision variable was measured in psychological space, and Bayesian models, where the decision variable was measured in probability space.

Non-Bayesian Choice and Confidence Criteria

The non-Bayesian models constituted models from both the scaled evidence strength and unscaled evidence strength class. For all these models, we refer to the position of the criteria in psychological space as *b*. To define the eight response regions across the range of psychological space, we used seven criteria. We assumed that each criterion increased monotonically across successive criteria such that higher confidence response regions were aligned with more extreme category evidence (see **Figure 4**). We also assumed that the criteria were positioned symmetrically around the means of the category distributions. We refer to this centre point as b_0. We assumed the criteria were symmetrical in this task because two measurements that are equidistant from the middle of the category structure but on opposite sides of b_0 should logically have the same confidence associated with them. Due to symmetry, confidence regions on equidistant but opposite sides of b_0 were treated as equivalent by the model. The criteria were ordered such that:

$$-b_7 < -b_6 < -b_5 < -b_4 < -b_3 < -b_2 < -b_1 < b_0 < b_1 <$$
$$b_2 < b_3 < b_4 < b_5 < b_6 < b_7. \tag{15}$$

The symmetrical criteria $-b_4$ and b_4 divided the stimulus range into two different category response regions such that:

$$if \ |x| \begin{cases} < b_4, respond \ category \ 1 \\ > b_4, respond \ category \ 2 \end{cases} \tag{16}$$

To make a confidence response, we assumed that the observer used 4 symmetrical criteria for each category: $b_1 - b_4$ for category 1 responses and $b_4 - b_7$ for category 2 responses. See **Figure 4A** to see how the criteria aligned with category evidence. Thus, the observer used a decision rule such that:

$$if \ |x| \begin{cases} < b_1, respond \ confidence \ 4 \\ > b_1 \ and < b_2, respond \ confidence \ 3 \\ > b_2 \ and < b_3, respond \ confidence \ 2 \\ > b_3 \ and < b_4, respond \ confidence \ 1 \\ > b_4 \ and < b_5, respond \ confidence \ 1 \\ > b_5 \ and < b_6, respond \ confidence \ 2 \\ > b_6 \ and < b_7, respond \ confidence \ 3 \\ > b_7, \quad respond \ confidence \ 4 \end{cases} \tag{17}$$

For the unscaled evidence strength models and the scaled evidence strength models, we made different assumptions about how *b* varies as a function of sensory uncertainty.

Unscaled Evidence Strength Model. In the unscaled evidence strength

587 model, the choice and confidence criteria were not dependent on (estimated) values
588 of sensory uncertainty (σ) and therefore occupied fixed positions across intensity
589 levels. The position of each criterion in psychological space was described by a free
590 parameter, k. The resulting criteria in psychological space were given by:

$$b_r = k_r \tag{18}$$

591 **Scaled Evidence Strength Model.** In the scaled evidence strength model, the
592 positions of the choice and confidence criteria were functions of σ. Each criterion
593 depended on 4 free parameters: k, m, z and σ. k represented the base position of each
594 criterion which was offset by $m\sigma^z$, where m was also estimated separately for each
595 criterion. The resulting criteria in psychological space were given by:

$$b_r(\sigma) = k_r + m_r \sigma^z \tag{19}$$

We constrained z to be greater than 1. Previous research has also considered
different scaling rules (Adler & Ma, 2018; Locke et al., 2022; West et al., 2023), for
example where criteria are estimated as linear or quadratic functions of σ. We chose
not to investigate these variants directly here to reduce the number of models for
model comparison and importantly, our chosen evidence strength model contained
both linear and quadratic scaling as special cases.

Bayesian Choice and Confidence Criteria

For the Bayesian models, we assumed that the observer chose a response by
comparing d, the log posterior probability ratio for a given stimulus (see Equation 14),
with a set of choice and confidence criteria $k = (k_1, k_2 \ldots k_7)$ that partitioned d space
into eight response regions, each representing a unique category and confidence
combination. The positions of the choice and confidence criteria for the Bayesian
models, therefore, were free parameters in d units. We assumed that each criterion
increased monotonically across successive criteria such that higher confidence
response regions aligned with greater absolute values of d (**Figure 4D**). Thus, the

choice and confidence criteria were ordered such that:

$$k_1 < k_2 < k_3 < k_4 < k_5 < k_6 < k_7 \qquad (20)$$

612   k_4 divided the stimulus range into two different category response regions such that

$$if\ d \begin{cases} < k_4, respond\ category\ 1 \\ > k_4, respond\ category\ 2 \end{cases} \qquad (21)$$

613   For confidence response, the observer used a decision rule such that:

$$if\ d \begin{cases} < k_1, respond\ confidence\ 4 \\ > k_1\ and\ < k_2, respond\ confidence\ 3 \\ > k_2\ and\ < k_3, respond\ confidence\ 2 \\ > k_3\ and\ < k_4, respond\ confidence\ 1 \\ > k_4\ and\ < k_5, respond\ confidence\ 1 \\ > k_5\ and\ < k_6, respond\ confidence\ 2 \\ > k_6\ and\ < k_7, respond\ confidence\ 3 \\ \ \ > k_7, \qquad respond\ confidence\ 4 \end{cases} \qquad (22)$$

Fitting the Models to Data

Model parameters were estimated for each participant using maximum
likelihood estimation. Below we first describe the process for estimating the
parameters of the bivariate sensory distribution and then describe the process for
calculating the likelihood of a given response, *r*, for a model with parameters θ. We
describe this process separately for the non-Bayesian and Bayesian models, as they
required different transformations.

Bivariate Sensory Distribution

To estimate the parameters of the bivariate sensory distribution, we sampled
10 evenly spaced values from the 5th to 95th percentile of the cumulative density
distribution for each dimension of the sensory distribution. We generated all possible
combinations of these sampled values (see shaded region of bottom left panel of
Figure 3B) and transformed each combination into the relevant univariate decision
variable, x_{comb}, given the model variant assumptions (integration vs. max and different
noise vs. same noise). See above for detailed descriptions for each set of
assumptions. For each univariate Gaussian decision variable, we computed a
likelihood (described below) which was then multiplied by the normalised joint density
of the sample, given the bivariate sensory distribution, x_{bi}.

Likelihood Calculation: Non-Bayesian Models

For the non-Bayesian models, the decision variable distributions, x_{uni} and

x_{comb}, were in the same psychological units as the choice and confidence criteria, *b*,

and thus, could be compared directly. For each trial, we therefore determined the

predicted response probability for a chosen combination of category and confidence

level by computing the probability mass of the sensory distribution between adjacent

criteria, given the participant's response on that trial, r_t (cf. Luce, 1959; see Fig 3D).

This quantity was defined as:

$$\int_{-b_{r_t}}^{-b_{t-1}} N(x;\ s_t, \sigma_t^2)\ dx\ +\int_{b_{r_{t-1}}}^{b_{r_t}} N(x;\ s_t, \sigma_t^2)\ dx \tag{23}$$

640   Where $b_0 = 0, b_8 = \infty$ and $-b_8 = -\infty$.

Likelihood Calculation: Bayesian Models

In the Bayesian models, the choice and confidence criteria were positioned in

probability space (log posterior probability ratio units) and thus, the sensory

distribution and criteria could not be compared directly. We, therefore, transformed the

choice and confidence criteria into psychological space by using the relevant value of

d as the left-hand side of Equation 14 and solved for *x*. Solving Equation 14 for *x*

requires calculating the square root of *d*, which is undefined for negative values. We

therefore used the absolute value of *d* to solve Equation 14 for *x* and applied the

appropriate sign to the result to arrive at a final standardised value for *x*. Where the

category distribution parameters were estimated as free parameters, we used the

estimated values in place of the true standard deviations (σ_1 and σ_2). The resulting

choice and confidence criteria in psychological space were then compared with the

decision variable distribution, described below.

Unidimensional Stimuli. After transforming the choice and confidence criteria

in *d* space to psychological space using Equation 14, we computed the probability

mass of the sensory distribution between adjacent criteria using Equation 23.

Multidimensional Stimuli. In order to transform the choice and confidence

criteria into psychological space we used the value of *d* as the left-hand side of

Equation 14 to solve for *x*. For the integration variants, we did this separately for each

stimulus dimension such that we used the estimated value of σ and the standard

deviations of the generating category distribution (σ_1 and σ_2) for each dimension. This

gave us a "threshold" value in psychological space for each stimulus dimension,

referred to as y_V and y_A. These values were then converted into a combined distance

metric, b_{comb}, according to:

$$b_{comb} = \sqrt{y_V^2 + y_A^2} \tag{24}$$

b_{comb}, therefore, represented a criterion in psychological space calculated as a combination of the "threshold" values for each stimulus dimension. The criteria were unweighted, as the weighting was applied to the stimulus values directly (see Equation 8). For the max variants, we converted the estimated choice and confidence criteria into psychological space, see Equation 14, for the selected stimulus dimension only, see Equation 10.

Log Likelihood of the Dataset

To obtain the log likelihood of the dataset, we computed the sum of the log probability for every trial t, where T is the total number of trials.

$$\log p(data \mid \theta) = \sum_{t=1}^{T} \log p(r_t \mid \theta) = \sum_{t=1}^{T} \log p_\theta(r_t \mid s_{t,}, \sigma_t) \tag{25}$$

Model Selection

To compare candidate models, we used Akaike information criterion (AIC) and Bayesian information criterion (BIC) for model selection. For a single participant, AIC is defined as:

$$AIC = 2K - 2\log(L) \tag{26}$$

where K is the number of model parameters and $\log(L)$ is the log likelihood of the dataset. To evaluate the performance of each model across all participants, we summed the AIC values across the N participants,

$$AIC_{sum} = \sum_{N=1}^{N} AIC_N \tag{27}$$

To compare the relative support for each model, we also calculated Akaike weights (Wagenmakers & Farrell, 2004). First, for each model M_m, where $m = 1, 2, \dots, J$, we computed the difference in AIC relative to the best candidate model (the model with the lowest AIC value):

$$\Delta_m(AIC) = AIC_m - \min(AIC) \tag{28}$$

Next, we calculated the Akaike weight for each model as:

$$wAIC_m = \frac{exp\left\{-\frac{1}{2}\Delta_m(AIC)\right\}}{\sum_{k=1}^{K} exp\left\{-\frac{1}{2}\Delta_k(AIC)\right\}} \tag{29}$$

The Akaike weights can be interpreted as the probability that a particular model is the best model in the set of candidate models, given the data and specified models (Wagenmakers & Farrell, 2004).

For a single participant, *BIC* is defined as:

$$BIC = -2\log(L) + K\log(T) \tag{30}$$

where K is the number of model parameters, $\log(L)$ is the log likelihood of the dataset and *T* is the number of trials in the dataset. Because *BIC* is sensitive to the total sample size used to compute the likelihood, calculating the summed *BIC* for each model requires that the sample size accounts for the total number of trials across all participants. We therefore summed the likelihood terms across participants, *N*, and added to that the total number of free parameters across participants, *kN*, multiplied by the logarithm of the total number of trials across participants, *tN*:

$$BIC_{sum} = \sum_{N=1}^{N} -2\log(L_N) + kN\log(tN) \tag{31}$$

Parameter and Model Recovery

We performed both parameter and model recovery for our core models. In the case of parameter recovery, we simulated data using known parameter values, fit the models to the simulated data, and then checked the correlation between the true generating parameters and the parameters estimated during the fitting procedure. For model recovery, we simulated datasets from each model and fit all models to these datasets. We then evaluated the probability that the model used to generate the data was correctly identified as the best-fitting model based on a specific model selection metric (*AIC* or *BIC*). Model recovery was conducted at two levels: individual model variants (see **Figure 5A**) and broader model classes (see **Figure 5B**). Evaluating model recovery at the model class level allowed us to determine how well the core theoretical assumptions distinguishing different groups of models aligned with the data (West et al., 2023). For both the parameter and model recovery, we used parameter values that were similar to the range of values obtained through fitting participant data. Further, to match our empirical dataset, we performed the parameter and model recovery with simulated datasets consisting of 10 'participants' and 720 trials per participant.

As shown in **Table S 3 – Table S 5** and **Figure S 3 – Figure S 5**, parameters generally exhibited strong recovery across models, with the vast majority of correlation

coefficients exceeding $r > 0.75$ (White et al., 2018). However, there were some exceptions: noise parameters (σ) in the unscaled evidence strength and Bayesian models showed poorer recovery ($r < 0.5$) under different noise and integration assumptions. The poorer recovery could have stemmed from using a restricted range of parameter values when simulating data. For the unscaled evidence strength and Bayesian models in particular, small changes in the noise parameters often resulted in minimal changes to the model's predictions of category and confidence responses, making parameter recovery in these cases more difficult. This issue would have likely been more pronounced as the number of parameters in the model increased (as in the different noise and integration assumptions).

As shown in **Figure 5B**, model class recovery was robust overall. This was particularly true when using *AIC* for model selection (see **Figure S 6B),** which aligns with findings from our previous work (West et al., 2023). For the bidimensional models, recovery was also strong across assumptions (see **Figure 5A**), though the integration models with the same noise assumption were slightly over-selected. This is likely because we simulated with similar noise values across modalities, so the additional four parameters in the different noise models did not improve the model's fit sufficiently to outweigh the penalty for added complexity. Using *AIC* for model selection also led to better recovery for the bidimensional models (see **Figure S 6A**).

Figure 5

Model Recovery

Note. Numbers and colours denote the probability that the data generated with model X (y-axis) are best fit by model Y (x-axis). Confusability matrix for **(A)** all model variants and **(B)** model classes using *AIC* for model selection. U.E.S refers to the unscaled evidence strength model class. S.E.S refers to the scaled evidence strength model class. Bayes. refers to the Bayesian model class. Int. refers to the integration assumption. Diff. and same refers to the assumption about the noise parameters across modalities.

Results

Participant Exclusion

Following the approach in West et al. (2023), we excluded one participant whose categorisation accuracy was not significantly above chance (50%) in the highest intensity condition, as determined by a binomial test of significance (see **Table S 1**).

Confirming the Effect of Stimulus Manipulations: Model Free GLMMs

Following the approach in West et al. (2023), we first verified that our stimulus manipulations had the desired effect on category and confidence responses across tasks. To do so, we used generalised linear mixed models (*GLMM*s) to predict category and confidence responses from the relevant stimulus features for each task. Since the expected relationships between stimulus attributes and responses were non-linear, we first transformed the raw stimulus attributes. For category responses,

759   this involved calculating a measure of 'evidence for category 2'.

Confirming that the stimulus manipulations affected category responses

762   For each task, we calculated evidence for category 2 by determining the
763   probability density of the presented stimulus attribute under the category 2 distribution,
764   normalised by the combined probability density across both category distributions:

$$E(C = 2) = \frac{N(s; \mu_2, \sigma_2)}{\sum_{C=1}^{2} N(s; \mu_C, \sigma_C)} \tag{32}$$

where s is the value of the stimulus, C is the category and N denotes the normal
density function. The result indicated 'evidence for category 2' for each stimulus
attribute, which could range from 0.2 (stimulus was highly likely to be from category 1)
to 1 (stimulus could be from category 2 only). The evidence value never reaches 0
because the category 1 distribution falls entirely within the range of the category 2
distribution (see **Figure 2A**).

We fit linear mixed models using a logistic link function to predict category
response (1 or 2) from stimulus intensity and evidence for category 2, for each task
and modality. The models included an intercept term, intensity, evidence and the
interaction term between intensity and evidence as random effects. For each
regression analysis, we report the odds ratio for the fixed effect and 95% confidence
intervals in **Table 1**. This analysis was conducted to descriptively assess the effects
of stimulus manipulations on responses across tasks so additional statistical details
and follow-ups are provided in **Table S 2**.

As expected, stimulus values that indicated increasing evidence for category 2
were positively predictive of category 2 responses in the visual (OR_{visual} = 2.55, 95%
CI [2.05-3.16], p < .001), auditory ($OR_{auditory}$ = 2.33, 95% CI [1.61-3.39], p = < .001),
and audio-visual tasks ($OR_{audio-visual}$ = 3.38, 95% CI [2.58-4.42], p < .001). Increasing
stimulus intensity was also positively predictive of category 2 responses for the visual
(OR_{visual} = 1.48, 95% CI [1.14-1.93], p = .004) and auditory tasks ($OR_{auditory}$ = 1.46
[1.13-1.88], p = .004) but not the audio-visual task ($OR_{audio-visual}$ = 1.14, 95% CI [0.92-
1.42], p = .223). These main effects were qualified by significant two-way interactions
between category 2 evidence and intensity, for the visual (OR_{visual} = 1.73, 95% CI
[1.57-1.90], p = < .001), auditory ($OR_{auditory}$ = 1.52, 95% CI [1.33-1.73], p < .001) and
audio-visual tasks ($OR_{audio-visual}$ = 1.25, 95% CI [1.15-1.37], p < .001). As illustrated in

Figure 6A, the effect of increasing category 2 evidence on category 2 responses was strongest for the highest intensity stimuli and decreased with stimulus intensity (see **Table S 2** for follow up tests).

These findings confirmed that participants understood the category distributions across modalities. Specifically, as the relative probability of a stimulus being sampled from category 2 increased, participants were more likely to categorise that stimulus as being sampled from category 2. The influence of category 2 evidence was modulated by stimulus intensity. At lower intensities, responses were more random and less guided by the category distributions. This pattern was consistent across tasks, confirming that the stimulus manipulations had the intended effect on category responses.

Figure 6

Model Free GLMMs

Note. **(A)** Predictions from a *GLMM* on category responses showed that the proportion of category 2 responses increased as a function of evidence for category 2 across the visual, auditory and audio-visual tasks (columns). The strength of this relationship was modulated by stimulus intensity (colours). **(B)** Predictions from a *GLMM* on confidence responses showed that across all tasks (columns), confidence increased as category diagnosticity, the relative evidence for the most probable category, increased. The strength of this relationship was modulated by stimulus intensity (colours).

Confirming that the Stimulus Manipulations Affected Confidence

To compare the effect of the stimulus manipulations on confidence across the different tasks we transformed stimulus values to 'category diagnosticity' using

Equation 9 prior to fitting the GLMMs. The result indicated category diagnosticity for

each stimulus value, which could range from 0.5 (both categories are equally likely) to

1 (stimulus could be from the most probable category only). We fit linear mixed models

to predict confidence from stimulus intensity and category diagnosticity for each

modality. The models included an intercept term, intensity, diagnosticity and the

interaction term between intensity and diagnosticity as random effects. For each

regression analysis, we report the regression coefficient for the fixed effect and 95%

confidence intervals in **Table 1**.

Increasing category diagnosticity was predictive of increasing confidence in the

visual (β_{visual}= 0.08, 95% CI [0.05-0.12], *p* < .001) and audio-visual tasks

($\beta_{audio-visual}$= 0.08, 95% CI [0.02-0.15], *p* = 0.10), but not the auditory task ($\beta_{auditory}$

= 0.09, 95% CI [-0.01-0.18], *p* = .066). Increasing stimulus intensity was predictive of

increasing confidence in the visual (β_{visual} = 0.51, 95% CI [0.31-0.70], *p* < .001),

auditory ($\beta_{auditory}$ = 0.50, 95% CI [0.30-0.70], *p* < .001) and audio-visual tasks

($\beta_{audio-visual}$ = 0.24, 95% CI [0.12-0.36], *p* < .001). We also observed significant two-

way interactions between category diagnosticity and intensity in the visual (β_{visual} =

0.06, 95% CI [0.02-0.09], *p* = .002) and audio-visual task ($\beta_{audio-visual}$= 0.03, 95% CI

[0.00-0.06], *p* = 0.024), but not the auditory task ($\beta_{auditory}$= 0.03, 95% CI [-0.02-0.08],

p = .211). For the visual and audio-visual task, increasing category diagnosticity was

associated with increasing confidence but the strength of this effect was modulated by

stimulus intensity. As illustrated in **Figure 6B**, the effect of increasing category

diagnosticity was strongest for the highest intensity stimuli and decreased with lower

stimulus intensities (see **Table S 2** for follow up tests).

These findings indicate that as the relative evidence for a given category

increased, participants' confidence in their chosen category increased, especially for

the visual and audio-visual tasks. When combined with the category GLMMs, which

showed that participants' category responses corresponded with the most probable

category, these results indicate that participants understood the category distributions

and used them to inform their confidence responses. The effect of the category

distributions on confidence was modulated by stimulus intensity, with lower stimulus

intensity leading to uniformly low confidence responses. In the auditory task, changes

in confidence were driven primarily by changes in stimulus intensity and not category

diagnosticity.

Table 1

Model-Free GLMMs for Category and Confidence Responses

Predictor		Tasks		
		Visual	Auditory	Audio-Visual
		Category		
Intercept	Odds Ratio	0.50*	0.59*	0.44**
	CI_{lower}	0.34	0.38	0.32
	CI_{upper}	0.74	0.93	0.61
Stimulus Intensity	Odds Ratio	1.48*	1.46*	1.14
	CI_{lower}	1.14	1.13	0.92
	CI_{upper}	1.93	1.88	1.42
Evidence for Category 2	Odds Ratio	2.55**	2.33**	3.38**
	CI_{lower}	2.05	1.61	2.58
	CI_{upper}	3.16	3.39	4.42
Intensity × Evidence	Odds Ratio	1.73**	1.52**	1.25**
	CI_{lower}	1.57	1.33	1.15
	CI_{upper}	1.90	1.73	1.37
		Confidence		
Intercept	β	2.51**	2.24**	2.51**
	CI_{lower}	2.14	1.97	2.11
	CI_{upper}	2.88	2.51	2.92
Stimulus Intensity	β	0.51**	0.50**	0.24**
	CI_{lower}	0.31	0.30	0.12
	CI_{upper}	0.70	0.70	0.36
Category Diagnosticity	β	0.08**	0.09	0.08*
	CI_{lower}	0.05	-0.01	0.02
	CI_{upper}	0.12	0.18	0.15
Intensity × Diagnosticity	β	0.06*	0.03	0.03*
	CI_{lower}	0.02	-0.02	0.00
	CI_{upper}	0.09	0.08	0.06

Note. CI terms refer to 95% confidence intervals calculated using the profile likelihood method. Significance values are obtained using the Satterthwaite approximation to calculate the degrees of freedom for the t-distribution based on the estimated variance-covariance matrix of the model parameters (Lüdecke, 2022). For category GLMMs (top section), we report the odds ratio (exponentiated coefficient estimate) for ease of interpretation. The odds ratio represents the change in odds of the outcome for a one-unit change in the predictor variable. For confidence GLMMs (bottom section), we report standardised regression coefficients.

*p < 0.05, **p < 0.001

Computational Modelling

The GLMMs confirmed that our chosen stimulus manipulations had the expected effects on category and confidence responses across modalities. To further explore the underlying computations driving these judgements, we used

computational modelling. We assessed the performance of confidence models from

three classes: 1) unscaled evidence strength models, 2) scaled evidence strength

models and 3) Bayesian models. To identify shared underlying algorithms, we first

tested whether a single class of models provided the best fit across modalities. In the

following sections, we briefly revisit the assumptions of each model class and describe

their performance across modalities.

Performance of Model Classes

Unscaled Evidence Strength Model

According to the unscaled evidence strength account, confidence reports

depend on the distance between the sensory measurement and the category decision

criterion (*evidence strength*) only. These models do not independently quantify

sensory uncertainty as a core part of the decision process. Specifically, for the

unscaled evidence strength model, we assumed that the observer compares their

internal representation of a stimulus to a set of choice and confidence criteria that do

not change with stimulus intensity.

As a result of the fixed choice and confidence criteria, the model predictions

remain unchanged across intensity levels, as shown in **Figure 7A**. On the contrary,

the empirical confidence ratings clearly change as a function of stimulus intensity,

leading to a poor fit of the model to data across tasks. In line with this qualitatively poor

fit, the unscaled evidence strength model performed worst in terms of summed *AIC*

and *BIC* (see **Figure 7A**) and was selected as the best fitting class for only a single

participant in the auditory and audio-visual task and for no participants in the visual

task (see **Figure 9A**). These findings suggests that a model in which confidence

depends only on the strength of the evidence, and not on the amount of sensory

uncertainty in the representation of the stimulus, fails to accurately account for the

cognitive processes involved in perceptual metacognition.

Model Predictions Across Classes for Each Task

Note. Columns show task modalities. Solid lines show model fit, where each row
represents a different model class, and data points show empirical data. Triangles
data points are from highest intensity level and circles are from the lowest intensity
level. Colours show proportions of category responses. For the audio-visual task, the
predictions from best performing model in each class is shown. Errors bars show $\pm$
1*SEM*.

Scaled Evidence Strength Models

According to the scaled evidence strength account, confidence reports depend
on the distance between the observer's internal representation of the stimulus and
sensory uncertainty dependent choice and confidence criteria. We estimated values
of *k* and *m* for each response criterion, which allowed the effect of sensory noise on
the positioning of the criteria to differ across response options ($k_r + m_r\sigma^z$). This meant
that the criteria associated with low confidence regions could expand under high
sensory noise, while the corresponding high confidence regions could contract (and
vice versa for low sensory noise). We also estimated an exponent on the
measurement noise term, *z*, which was constant across criteria. The exponent allowed
for the effect of σ on the choice and confidence criteria to change as a function of σ.

As shown in **Figure 7B**, the scaled evidence strength model was able to
capture the empirical data well, where for the low intensity stimuli (those associated
with higher sensory noise), confidence ratings remained uniformly low across stimulus
values. For higher intensity stimuli (those associated with lower sensory noise), the
criteria shifted so that higher confidence ratings were given for stimulus values
associated with greater evidence strength (stimulus values with greater category
diagnosticity) and lower confidence ratings were given for stimulus values associated
with less evidence strength (stimulus values with lower category diagnosticity).

As shown in **Figure 8**, the scaled evidence strength models had the lowest
summed *AIC* and *BIC* scores and they outperformed the alternative models for the
majority of individual participants (see **Figure 9A**), especially for the unidimensional
tasks. Specifically, the unscaled evidence strength models provided the best account
for 8 out of the 10 participants in the auditory task and 9 out of 10 the participants in
the visual task. We found that for the multidimensional task, the best performing model
class was more heterogenous but that on average, the scaled evidence strength
models still outperformed the other models, selected as the best performing class for
7 out of the 10 participants. The overall performance of the scaled evidence strength
class suggests that observers consider sensory uncertainty when generating a
confidence report, unlike the unscaled evidence strength models, but they do not do
so in a way that is consistent with Bayesian inference (discussed in more detail below).

Figure 8

Summed AIC and BIC Across Participants For Each Model Class

Note. The scaled evidence strength class had the lowest summed scores across the
visual (left panel), auditory (middle panel) and audio-visual (right panel) tasks.

Bayesian Models

According to Bayesian models of confidence, observers optimally combine sensory information with prior knowledge to form a posterior belief about the nature of the stimulus. In our task, we assumed that participants use the generating category distributions to calculate a log posterior ratio, $log \frac{p(C=1 \mid x)}{p(C=2 \mid x)}$ which they compare with choice-confidence criteria in the same measurement units. The Bayesian models have fewer parameters than the scaled evidence strength models because the choice and confidence criteria have the same positions in probability space but the estimated values of sensory noise at each intensity level allow these criteria to shift in perceptual space. That is, the amount of uncertainty associated with the sensory observation causes the associated response regions to expand or contract.

As shown in **Figure 7C**, the Bayesian models are not sufficiently flexible to capture the empirical confidence data. Specifically, while the model predictions are able to capture the empirical changes in responses as a function of stimulus values, where greater evidence strength is associated with greater confidence, the predictions show systematic deviations from the data across intensity levels. In particular, the Bayesian models consistently over-estimate confidence for stimuli of lower intensity and under-estimate confidence for stimuli of greater intensity. In terms of model selection, we found that the Bayesian models were selected by a single participant in the auditory and visual tasks and by 2 participants in the audio-visual task (see **Figure 9**). In terms of summed *AIC* and *BIC*, the Bayesian models were out-performed by the scaled evidence strength models (see **Figure 8**). The Bayesian models performed poorly even when we allowed for additional flexibility in the model by estimating participants' prior knowledge of the generating category parameters, instantiating a subjective prior, rather than assuming they represent the true parameters veridically. Overall, these findings suggest that participants do not generate confidence reports in a way that is consistent with a Bayesian formalisation in any of our tasks.

962   *Akaike Weights Across Participants*

963
Note. **(A)** Weights were calculated using the best-performing models in each class for
each participant. Darker colours show larger weights, demonstrating the superior
performance of the scaled evidence strength models across all tasks **(B)** Weights were
calculated across all possible combinations of assumptions and model classes for the
multidimensional task. Assumptions for model classes (Bayesian, scaled evidence
strength and unscaled evidence strength), the combination of stimulus dimensions
(integration or max) and sensory noise (same or different) are shown in different
columns. Darker colours show larger weights, demonstrating the superior
performance of the scaled evidence strength models with the integration and same
noise assumption.

Predicting Multidimensional Behaviour from Unidimensional

Behaviour

976   For the majority of cases, the scaled evidence strength models provided the

best account of choice and confidence across modalities, consistent with the results

from previous research using the same model classes (Adler & Ma, 2018; Denison et

al., 2018; West et al., 2023). Given the similarities in the type of algorithm used across

modalities, we wanted to investigate how well the confidence process generalised by

investigating how well behaviour in the unidimensional tasks (visual and auditory)

could predict behaviour in the multidimensional (audio-visual) task. To this end, we

used the estimated parameters from each participant's unidimensional model fits to

predict their category and confidence responses to multidimensional stimuli. We did

this using the model parameters from the scaled evidence strength model, because it

provided the best fit across participants. We combined the parameters using the

integration and different noise assumptions, as they consistently outperformed the

max models and included the same noise as a special case.

Based on pilot data aimed at matching performance across tasks, we selected

a more compressed range of intensity levels for the multidimensional task, where the

second-highest intensity in the unidimensional tasks (level 3) corresponded to the

highest intensity in the multidimensional task (level 4). To generate predictions for the

multidimensional task, therefore, we estimated sensory noise parameters for the

intermediate audio-visual intensity levels (intensity 2 and intensity 3), which were not

tested in the unidimensional tasks. We fit an exponential function to the noise

parameters from the four unidimensional intensity levels and used this function to

predict noise values for the intermediate levels. The exponential function was chosen

for convenience, as it enforced monotonicity and required estimating only a single

parameter. We confirmed that it fit the data well (see **Figure S 2**). The tested (intensity

1 and 4) and interpolated (intensity 2 and 3) noise parameters provided noise

estimates for each modality at the audio-visual intensity levels for each participant.

These were then combined using Equation 12 to calculate σ_{AV}.

We used the noise parameters to calculate choice and confidence criteria (*b*)

in each modality, applying the estimated *k*, *m* and *z* parameters (see Equation 19) for

each participant. These criteria were then transformed into a combined distance metric

using the equation $b_{AV} = \sqrt{(b_V{}^2) + (b_A{}^2)}$, yielding predicted criteria, b_{AV}, and noise,

σ_{AV}, parameters for each participant, directly estimated by the unidimensional model

parameters.

In the final step, we estimated an attentional weight (w_V) from the response

and stimulus data in the multidimensional task. This weight was applied to the visual

dimension, while the complementary weight ($1 - w_V$) was applied to the auditory

dimension. By applying this weighting, we captured systematic biases in participants'

reliance on one stimulus dimension over the other. We then calculated the likelihood

of the dataset given the set of model parameters (see Equation 23). This model, which

generalises parameters from the unidimensional tasks to the multidimensional task, is

referred to as the *dimensionality-independent* model.

We found that with a single free parameter (the attentional weight), the

dimensionality-independent model predictions captured the empirical data from the

multidimensional task well (see **Figure 10**). The model did, however, underestimate

confidence for stimulus values associated with greater category diagnosticity (values

from the middle of the category 1 distribution and from the tails of the category 2

distribution), highlighting areas where confidence judgements may require further

refinement. Overall, however, the dimensionality-independent model demonstrated

strong predictive power across tasks, providing further evidence for the generalisability

of a single confidence algorithm across different types of perceptual decisions.

Figure 10

Dimensionality-Independent Model Predictions

1028

Note. Model predictions from the dimensionality-independent model in which we used
the estimated parameters from the unidimensional (visual and auditory) model fits to
predict responses on the multidimensional (audio-visual) task. Solid lines show model
predictions and circular plotting symbols show empirical data from the audio-visual
task. Colours show proportion of category responses. Error bars show $\pm\, 1$ *SEM*.

How is Sensory Information Combined Across Modalities?

Relatively little research has explored how confidence models perform in tasks

requiring the integration of information across sensory modalities. In this study,

therefore, we wanted to use our modelling approach to more comprehensively

characterise choice and confidence judgements in the audio-visual task. To do so, we

tested two key assumptions about the combination of sensory information across

modalities for each of the model classes, resulting in 4 variants for each core model

(i.e., a total of 16 models were fit to the audio-visual data across the 3 model classes).

The first set of assumptions allowed us to investigate whether participants

attended to both dimensions of the multidimensional stimulus. In the 'integration'

models, we assumed that participants attended to both dimensions, while in the 'max'

models, we assumed that they attended only to the most informative dimension. We

found that the integration models outperformed the max models in all classes for every

participant, confirming that confidence judgements relied on combining auditory and

visual input. However, participants did not appear to integrate stimulus values across

dimensions in an unbiased way. Parameter estimates showed that all participants

were biased towards the visual modality, weighting the visual dimension of the

stimulus more heavily in their confidence judgement.

The second set of assumptions explored how participants represented sensory

noise. We implemented two model instantiations, one in which we estimated noise

values separately for each stimulus dimension (these estimates were later combined

across the two modalities) and the other in which we estimated a single 'modality-

independent' sensory noise value. Models with a modality-independent noise

parameter performed better, suggesting participants rely on a generalised noise

estimate rather than combining noise from individual dimensions.

Together, these findings help elucidate how participants generate confidence

reports when integrating sensory information. We showed that confidence judgements

were based on both stimulus dimensions, instantiated in the model as a weighted

'distance' measure. This combined measure, which provided a proxy for evidence

strength, was compared against choice and confidence criteria that were adjusted

based on a modality-independent noise estimate which varied with stimulus intensity.

As shown in **Figure 7B**, this model closely aligned with empirical data, capturing

response variation driven by stimulus values (evidence strength) and intensity

(measurement noise).

Discussion

Most previous studies of the computational basis of decision confidence have

relied on simple visual perceptual tasks, leaving unanswered how confidence is

formed in decisions involving other sensory modalities or those that require integrating

information across modalities. To address these questions, we used computational

modelling to analyse confidence judgements in perceptual decision-making tasks

involving visual, auditory and audio-visual stimuli. Our first set of analyses investigated

whether confidence judgements for such decisions are based on the same underlying computational algorithms. Specifically, we compared the performance of different classes of confidence models and evaluated whether the same model class consistently fit data from all three tasks. We further tested the generalisability of a single class of algorithms by examining how well predictions generated from the unidimensional tasks (visual and auditory) aligned with empirical data from the multidimensional (audio-visual) task. The second set of analyses focused specifically on the multidimensional task, examining how participants integrated sensory inputs from multiple modalities when making confidence judgements. Within each model class, we tested different assumptions about the integration process. In the sections that follow, we first discuss the model classes and their performance across the different tasks, and then provide a more detailed analysis of the modelling results from the multidimensional task.

A Theoretical Framework for Understanding Confidence Judgements: Comparing Model Classes

Building on an extensive body of research on the computational basis of confidence in visual perceptual tasks (Adler & Ma, 2018; Aitchison et al., 2015; Faivre et al., 2018; Locke et al., 2022; Navajas et al., 2017; Shekhar & Rahnev, 2024; West et al., 2023), we adapted models to evaluate how well they fit the data from our visual, auditory and novel audio-visual categorisation tasks. Our model classes instantiated different assumptions about how observers transform sensory signals, whether unidimensional or multidimensional, into a choice and corresponding confidence report. Within our general modelling framework, we assumed that sensory input from the external world generates an internal response, represented as a latent decision variable. The latent variable was modelled as a normal distribution, to capture the noise inherent in the sensory system itself. A key aspect of all our models, therefore, was the concept of *sensory uncertainty*, which refers to the variability (or noise) in the observer's internal representation of the stimulus. We assumed that this sensory uncertainty (characterised by the σ parameters) varied with stimulus intensity, with lower intensities leading to greater uncertainty. Sensory uncertainty also influenced the choice and confidence criteria, and different model classes handled this relationship in distinct ways.

For the non-Bayesian models, the decision variable was expressed in

psychological units which were tied directly to the stimulus (e.g., a grating's orientation). The value of the stimulus itself, therefore, guided both category choice and confidence, with the choice-confidence criteria segmenting the possible values into discrete category and confidence response regions. We tested two types of non-Bayesian models: one which assumed fixed choice-confidence-criteria regardless of sensory uncertainty (unscaled evidence strength; Kepecs et al., 2008; Komura et al., 2013; Rahnev et al., 2011), and the other which assumed that the choice-confidence-criteria were adjusted based on the amount of sensory uncertainty in the decision variable (scaled evidence strength; Adler & Ma, 2018; Denison et al., 2018; Locke et al., 2022; West et al., 2023). In contrast, the Bayesian models approached sensory uncertainty by incorporating it into a probabilistic framework. These models used prior knowledge about the generating category distributions to compute a log posterior probability ratio. The magnitude of the log posterior probability ratio served as a choice and confidence metric, directly reflecting how sensory uncertainty impacts the perceived likelihood of a decision outcome.

Bayesian Class

We found that that Bayesian model class was outperformed across all tasks, both at the group level and for the majority of individual participants. Even after increasing their flexibility, by estimating participants' subjective prior knowledge rather than assuming they knew the true generating category parameters, the performance of the Bayesian models remained relatively poor. This consistently poor performance suggests that participants' confidence judgements in all our tasks are unlikely to rely on posterior probability computations, at least as represented by the models we tested. These findings align with previous research demonstrating the limited applicability of Bayesian models to metacognitive decisions (Adler & Ma, 2018; Baranski & Petrusic, 1994; Locke et al., 2022; West et al., 2023). Notably, our results extend previous research by showing that confidence does not follow a strict Bayesian framework, even in multidimensional contexts where a modality-independent measurement system could theoretically resolve differences in how information from distinct sensory modalities is represented and integrated, resolving any 'translation issues'. The underperformance of the Bayesian models, even in tasks where integration may benefit from a unified measurement system, highlights the broader limitations of these models. Specifically, the rigid assumptions inherent to Bayesian inference may fail to

account for the context-dependent nature of human confidence judgements.

Additionally, these findings suggest that the use of prior information in

confidence judgements may be less straightforward than previously assumed. Rather

than incorporating priors in a statistically optimal manner, individuals may employ

them more heuristically, in ways that do not adhere to the strict probabilistic structure

imposed by Bayesian models. This highlights the importance of future research

exploring alternative modelling frameworks that incorporate prior knowledge in a more

flexible and computationally efficient manner.

Unscaled Evidence Strength Class

In contrast to the Bayesian models, the unscaled evidence strength models

instantiated the simplest view of metacognitive computations. In the unscaled

evidence strength models, the decision variable, which was directly related to the

stimulus itself, was compared to choice and confidence criteria that did not change as

a function of sensory uncertainty. The unscaled evidence strength model performed

worst on all tasks, except in a small number of individual cases (one participant in the

auditory task and one participant in the audio-visual task). This finding aligns with

previous studies that have documented poor performance of unscaled evidence

strength models across unidimensional tasks performed in vision (Adler & Ma, 2018)

and audition (West et al., 2023). The results from our study extend this understanding

to multidimensional decisions, suggesting that even when observers must integrate

stimulus information from distinct modalities, they rely on more sophisticated

computations that factor in sensory uncertainty.

Scaled Evidence Strength Class

In the scaled evidence strength models, we assumed that the decision variable

was directly related to the value of the stimulus but that the choice and confidence

criteria were dynamically adjusted in response to sensory uncertainty. This approach

incorporated a scaling factor ($m\sigma^z$) that adjusted the criteria, accommodating linear,

quadratic and faster than quadratic relationships between sensory uncertainty and

criterion positioning. This flexibility allowed the model to capture individual differences

in how participants adapted to varying levels of noise. The scaled evidence strength

models outperformed all alternative models across tasks, both for the majority of

individual participants and for the group.

The scaled evidence strength framework allowed observers to integrate

sensory uncertainty into their confidence judgements, much like an 'optimal observer,' but without the computational burden of posterior probability computations. The success of the scaled evidence strength class aligns with emerging evidence that confidence judgements rely on heuristic-like strategies that approximate optimal behaviour (Adler & Ma, 2018; Aitchison et al., 2015; Denison et al., 2018; West et al., 2023), extending these findings to decisions involving the integration of multiple sources of information. The superior performance of this class of models suggests that future studies may benefit from including models that incorporate scaling mechanisms which allow confidence to dynamically adapt to uncertainty, without relying on posterior probabilities.

A Shared Computational Basis for Confidence

The finding that the scaled evidence strength models outperformed the other models across all tasks supports the idea that the same core algorithm governs confidence judgements across modalities. We further investigated the generalisability of the confidence process by testing whether behaviour in the unidimensional tasks (visual and auditory) could predict behaviour in the multidimensional (audio-visual) task using the scaled evidence strength algorithm. Specifically, we used the parameters estimated from the unidimensional model fits for each participant and estimated a single additional parameter to predict their category and confidence responses to multidimensional stimuli. This approach, referred to as the dimensionality-independent model, revealed that predictions generated from the unidimensional tasks closely aligned with the observed data from the audio-visual task. This finding reinforces the notion of a shared algorithmic basis for confidence judgements across different types of perceptual decisions and aligns with both our previous computational work (West et al., 2023) and other related studies (Ais et al., 2016; Faivre et al., 2018; Fleck et al., 2006; Heereman et al., 2015; Mazancieux et al., 2020; Morales et al., 2018; Pleskac & Busemeyer, 2010; Rouault et al., 2018; Song et al., 2011) showing common mechanisms for confidence judgements across modalities.

It is important to acknowledge, however, that our conclusions about a shared algorithmic basis are limited by the scope of the models we tested. While we included a range of models grounded in existing theoretical frameworks, it remains possible that alternative models, either Bayesian or non-Bayesian, might account for the data

equally well or better. Nevertheless, the fact that the scaled evidence strength algorithm outperformed other alternatives across all tasks, along with its close fit to the data in each case, suggests that it captures a core feature of how humans generate confidence judgements.

Looking ahead, future studies could explore the use of latent factor models to gain deeper insights into the underlying shared computational mechanisms (Schmiedek et al., 2007; Stevenson et al., 2024). In the context of our study, a latent factor model could capture underlying cognitive constructs – such as modality-independent confidence mechanisms – that operate across different sensory tasks. Specifically, instead of modelling each task separately, a latent factor model could account for both task-specific parameters and shared latent constructs that generalise across tasks. By modelling both the latent cognitive constructs and task parameters simultaneously, such models could provide insights into whether the underlying confidence algorithm truly operates independently of the sensory modality or if some modality-specific factors still play a role.

Metacognition Across Stimulus Dimensions: Comparing Assumptions for Integrating Information Across Modalities

To the best of our knowledge, few studies have used computational modelling to characterise the computations involved in metacognitive judgements when integrating stimulus information across sensory modalities. Addressing this gap, we developed a set of models to explore how people form confidence judgements when integrating information from visual and auditory sources. In doing so, we examined two assumptions about the confidence generation process.

The first set of assumptions quantified whether participants integrated both stimulus dimensions or whether they relied on a single dimension only. In the *integration* assumption, the decision variable was derived from a weighted integration of both dimensions of the stimulus, whereas in the *max* assumption, it relied solely on the dimension providing the strongest input. Our results showed consistent evidence in favour of the integration assumption, with integration models outperforming the max models across all classes and participants. This finding aligns with prior research on perceptual decisions, which showed that people are able to integrate information from different sensory modalities (Alais & Burr, 2004; Calvert et al., 1998; Driver & Spence, 1998; Ernst & Banks, 2002; McGurk & MacDonald, 1967; Shams et al., 2000; Stein &

Meredith, 1993; Van Wassenhove et al., 2005).

This result also aligns with preliminary work that has investigated metacognition
for perceptual decisions involving multiple modalities (Faivre et al., 2018; Gao et al.,
2023). For example, Gao and colleagues (2023) demonstrated that sensory cues are
automatically integrated based on their reliability, even when participants were
instructed to disregard one of the modalities because it was task-irrelevant. Our results
build on those from Gao and colleagues (2023) by showing that a reliability-weighted
integration process also operates when both modalities are explicitly task-relevant.
This finding supports the idea that the integration process reflects a broader, more
fundamental principle of information processing. Importantly, it shows that integration
is not merely an artefact of a failure in selective attention; rather, the brain appears to
automatically combine information from all available modalities, even if that
information is not directly task-relevant.

Faivre and colleagues (2018) also explored confidence in audio-visual
decisions, demonstrating through computational modelling that confidence could be
predicted either from a bidimensional representation of an audio-visual signal or by
comparing unidimensional visual and auditory representations. Our approach extends
the work of Faivre and colleagues (2018) by considering a broader range of theoretical
model classes beyond modelling confidence as the probability of being correct, an
assumption that aligns most closely with our Bayesian models. This broader modelling
framework allowed us to investigate multiple possible algorithms underlying
confidence generation, providing deeper insight into how sensory information is
integrated at the metacognitive level.

Specifically, the weight parameter in our integration models also allowed us to
directly investigate whether participants systematically over-weighted one stimulus
dimension in their confidence judgement. All participants exhibited a bias toward the
visual modality. This over-reliance on visual information aligns with previous studies
suggesting that visual input tends to dominate multisensory integration (Alais & Burr,
2004; Colavita, 1974; Ernst & Banks, 2002; McGurk & MacDonald, 1967; Posner et
al., 1976; Rock & Victor, 1964; Welch & Warren, 1980). Importantly, our results
demonstrate that this visual dominance extends beyond perceptual judgements to
influence confidence judgements as well, reinforcing the idea that confidence reflects
the same biases present in perception. Further research could examine the relative
weighting of visual and auditory inputs more closely. One possible avenue would be

to implement dynamic models that update weighting on a trial-by-trial basis, depending
on stimulus characteristics. For example, the model could reflect a baseline bias
toward the visual modality that becomes less dominant when auditory cues provide
highly informative information. Another potential direction would involve trying to
experimentally manipulate the integration weights by instructing participants to attend
selectively to specific stimulus dimensions. This would allow future studies to also
explore whether these biases are modifiable through top-down attentional control.

The second set of assumptions that we examined in our multidimensional
models was how participants estimated sensory uncertainty across modalities. We
tested two model variants to address this question: one in which sensory noise values
were estimated separately for each stimulus dimension and then combined across
modalities, and another in which a single modality-independent sensory noise value
was used across both dimensions. Our results indicated that participants adjusted
their choice and confidence criteria based on a single estimate of sensory uncertainty,
which varied systematically with the experimentally manipulated intensity. However,
this result should be interpreted cautiously, as our model recovery analysis indicated
a slight over-selection of models with the same noise parameters across modalities,
potentially biasing this conclusion (see **Figure 5**).

Despite this, we propose several possible interpretations to guide future
research. One is that the noise estimate in the multidimensional models may serve as
a general measure of uncertainty, rather than capturing low-level sensory noise
specific to each modality (e.g., noise which could be represented as variance in neuron
firing rates). From this perspective, participants may not require a fine-grained noise
estimate for each sensory input because a single general uncertainty measure suffices
to regulate confidence across modalities. This interpretation aligns with other
computational models of confidence including the weighted evidence and visibility
(WEV) model (Rausch et al., 2018, 2021). The WEV model posits that individuals use
visibility as a global signal shaping confidence judgements, regardless of the specific
sensory modality contributing to the evidence. This visibility signal functions similarly
to a global noise estimate, modulating the level of confidence placed in the
accumulated evidence.

Alternatively, it is possible that our intensity manipulation was effective in
matching the amount of sensory uncertainty across modalities, making a single noise
estimate sufficient to capture the amount of low-level sensory noise in each modality.

However, this explanation seems unlikely given the observed differences in
categorisation performance at different intensity levels in the unidimensional tasks
(see **Figure S 1**). An interesting direction for future research would be to vary intensity
independently within each stimulus dimension, e.g., using high-intensity visual input
combined with low-intensity auditory input. This approach would allow for a more
nuanced investigation of whether participants can dynamically adjust their confidence
judgements based on independent sensory noise levels across modalities.

Conclusions

In summary, our findings demonstrate that the scaled evidence strength models
consistently outperformed the other model classes across all tasks and could be used
to predict behaviour in the multidimensional task based on unidimensional data. These
findings suggest that confidence judgements are governed by a shared algorithm that
dynamically accounts for both sensory uncertainty and evidence strength, without
relying on posterior probability computations. Additionally, we demonstrated that when
making multidimensional confidence judgements, participants integrated visual and
auditory information with a systematic bias toward the visual modality, and used a
modality-independent measure of sensory uncertainty to modulate their confidence.
Our results highlight the generalisability of the scaled evidence strength algorithm,
even for tasks requiring integration across sensory modalities, and emphasise the
limitations of Bayesian models in capturing the nuanced, context-dependent nature of
human confidence judgements. These results open important avenues for future
research, including the use of latent factor models to capture both shared and task-
specific metacognitive constructs, exploring how sensory inputs are dynamically
weighted for confidence, and investigating whether integration biases in confidence
can be modulated through top-down attentional control.

References

Adler, W. T., & Ma, W. J. (2018). Comparing Bayesian and non-Bayesian accounts of human confidence reports. *PLOS Computational Biology*, *14*(11), e1006572. https://doi.org/10.1371/journal.pcbi.1006572

Ais, J., Zylberberg, A., Barttfeld, P., & Sigman, M. (2016). Individual consistency in the accuracy and distribution of confidence judgements. *Cognition*, *146*, 377–386. https://doi.org/10.1016/j.cognition.2015.10.006

Aitchison, L., Bang, D., Bahrami, B., & Latham, P. E. (2015). Doubly Bayesian Analysis of Confidence in Perceptual Decision-Making. *PLOS Computational Biology*, *11*(10), e1004519. https://doi.org/10.1371/journal.pcbi.1004519

Alais, D., & Burr, D. (2004). The Ventriloquist Effect Results from Near-Optimal Bimodal Integration. *Current Biology*, *14*(3), 257–262. https://doi.org/10.1016/j.cub.2004.01.029

Baranski, J. V., & Petrusic, W. M. (1994). The calibration and resolution of confidence in perceptual judgements. *Perception & Psychophysics*, *55*(4), 412–428. https://doi.org/10.3758/BF03205299

Boldt, A., de Gardelle, V., & Yeung, N. (2017). The impact of evidence reliability on sensitivity and bias in decision confidence. *Journal of Experimental Psychology: Human Perception and Performance*, *43*(8), 1520–1531. https://doi.org/10.1037/xhp0000404

Boldt, A., Schiffer, A.-M., Waszak, F., & Yeung, N. (2019). Confidence Predictions Affect Performance Confidence and Neural Preparation in Perceptual Decision Making. *Scientific Reports*, *9*(1), 4031. https://doi.org/10.1038/s41598-019-40681-9

Brainard, D. H. (1997). The Psychophysics Toolbox. *Spatial Vision*, *10*(4), 433–436. https://doi.org/10.1163/156856897X00357

Calvert, G. A., Brammer, M. J., & Iversen, S. D. (1998). Crossmodal identification. *Trends in Cognitive Sciences*, *2*(7), 247–253.

Colavita, F. B. (1974). Human sensory dominance. *Perception & Psychophysics*, *16*(2), 409–412. https://doi.org/10.3758/BF03203962

de Gardelle, V., Le Corre, F., & Mamassian, P. (2016). Confidence as a Common Currency between Vision and Audition. *PLOS ONE*, *11*(1), e0147901. https://doi.org/10.1371/journal.pone.0147901

Denison, R. N., Adler, W. T., Carrasco, M., & Ma, W. J. (2018). Humans incorporate attention-dependent uncertainty into perceptual decisions and confidence. *Proceedings of the National Academy of Sciences*, *115*(43), 11090–11095. https://doi.org/10.1073/pnas.1717720115

Desender, K., Boldt, A., & Yeung, N. (2018). Subjective Confidence Predicts Information Seeking in Decision Making. *Psychological Science*, *29*(5), 761–778. https://doi.org/10.1177/0956797617744771

Driver, J., & Spence, C. (1998). Crossmodal attention. *Current Opinion in Neurobiology*, *8*(2), 245–253.

Drugowitsch, J., Moreno-Bote, R., & Pouget, A. (2014). Relation between Belief and Performance in Perceptual Decision Making. *PLoS ONE*, *9*(5), e96511. https://doi.org/10.1371/journal.pone.0096511

Ernst, M. O., & Banks, M. S. (2002). Humans integrate visual and haptic information in a statistically optimal fashion. *Nature*, *415*(6870), 429–433. https://doi.org/10.1038/415429a

Faivre, N., Filevich, E., Solovey, G., Kühn, S., & Blanke, O. (2018). Behavioral, Modeling, and Electrophysiological Evidence for Supramodality in Human Metacognition. *Journal of Neuroscience*, *38*(2), 263–277. https://doi.org/10.1523/JNEUROSCI.0322-17.2017

Fleck, M. S., Daselaar, S. M., Dobbins, I. G., & Cabeza, R. (2006). Role of Prefrontal and Anterior Cingulate Regions in Decision-Making Processes Shared by Memory and Nonmemory Tasks. *Cerebral Cortex*, *16*(11), 1623–1630. https://doi.org/10.1093/cercor/bhj097

Gao, Y., Xue, K., Odegaard, B., & Rahnev, D. (2023). Common computations in automatic cue combination and metacognitive confidence reports. *bioRxiv*.

Hangya, B., Sanders, J. I., & Kepecs, A. (2016). A Mathematical Framework for Statistical Decision Confidence. *Neural Computation*, *28*(9), 1840–1858. https://doi.org/10.1162/NECO_a_00864

Heereman, J., Walter, H., & Heekeren, H. R. (2015). A task-independent neural representation of subjective certainty in visual perception. *Frontiers in Human Neuroscience*, *9*(551). https://doi.org/10.3389/fnhum.2015.00551

Kepecs, A., & Mainen, Z. F. (2012). A computational framework for the study of confidence in humans and animals. *Philosophical Transactions of the Royal Society B: Biological Sciences*, *367*(1594), 1322–1337. https://doi.org/10.1098/rstb.2012.0037

Kepecs, A., Uchida, N., Zariwala, H. A., & Mainen, Z. F. (2008). Neural correlates, computation and behavioural impact of decision confidence. *Nature*, *455*(7210), 227–231. https://doi.org/10.1038/nature07200

Komura, Y., Nikkuni, A., Hirashima, N., Uetake, T., & Miyamoto, A. (2013). Responses of pulvinar neurons reflect a subject's confidence in visual categorization. *Nature Neuroscience*, *16*(6), 749–755. https://doi.org/10.1038/nn.3393

Lehmann, M., Hagen, J., & Ettinger, U. (2022). Unity and diversity of metacognition. *Journal of Experimental Psychology: General*, *151*(10), 2396–2417. https://doi.org/10.1037/xge0001197

Li, H.-H., & Ma, W. J. (2020). Confidence reports in decision-making with multiple alternatives violate the Bayesian confidence hypothesis. *Nature Communications*, *11*(1), 2004. https://doi.org/10.1038/s41467-020-15581-6

Lisi, M., Mongillo, G., Milne, G., Dekker, T., & Gorea, A. (2021). Discrete confidence levels revealed by sequential decisions. *Nature Human Behaviour*, *5*(2), 273–280. https://doi.org/10.1038/s41562-020-00953-1

Locke, S. M., Landy, M. S., & Mamassian, P. (2022). Suprathreshold perceptual decisions constrain models of confidence. *PLOS Computational Biology*, *18*(7), e1010318. https://doi.org/10.1371/journal.pcbi.1010318

Lüdecke, D. (2022). _sjPlot: Data Visualization for Statistics in Social Science_. R package version 2.8.12 [Computer software]. <https://CRAN.R-project.org/package=sjPlot>

Masset, P., Ott, T., Lak, A., Hirokawa, J., & Kepecs, A. (2020). Behavior- and Modality-General Representation of Confidence in Orbitofrontal Cortex. *Cell*, *182*(1), 112-126.e18. https://doi.org/10.1016/j.cell.2020.05.022

Mazancieux, A., Fleming, S. M., Souchay, C., & Moulin, C. J. A. (2020). Is there a G factor for metacognition? Correlations in retrospective metacognitive sensitivity across tasks. *Journal of Experimental Psychology: General*, *149*(9), 1788–1799. https://doi.org/10.1037/xge0000746

McGurk, H., & MacDonald, J. (1967). Hearing lips and seeing voices. *Nature*, *264*, 746–748. https://doi.org/10.1038/264746a0

Meyniel, F., Sigman, M., & Mainen, Z. F. (2015). Confidence as Bayesian Probability: From Neural Origins to Behavior. *Neuron*, *88*(1), 78–92. https://doi.org/10.1016/j.neuron.2015.09.039

Morales, J., Lau, H., & Fleming, S. M. (2018). Domain-General and Domain-Specific Patterns of Activity Supporting Metacognition in Human Prefrontal Cortex. *The Journal of Neuroscience*, *38*(14), 3534–3546. https://doi.org/10.1523/JNEUROSCI.2360-17.2018

Navajas, J., Hindocha, C., Foda, H., Keramati, M., Latham, P. E., & Bahrami, B. (2017). The idiosyncratic nature of confidence. *Nature Human Behaviour*, *1*(11), 810–818. https://doi.org/10.1038/s41562-017-0215-1

Pelli, D. G. (1997). The VideoToolbox software for visual psychophysics: Transforming numbers into movies. *Spatial Vision*, *10*(4), 437–442. https://doi.org/10.1163/156856897X00366

Pleskac, T. J., & Busemeyer, J. R. (2010). Two-stage dynamic signal detection: A theory of choice, decision time, and confidence. *Psychological Review*, *117*(3), 864–901. https://doi.org/10.1037/a0019737

Posner, M. I., Nissen, M. J., & Klein, R. M. (1976). Visual dominance: An information-processing account of its origins and significance. *Psychological Review*, *83*(2), 157–171. https://doi.org/10.1037/0033-295X.83.2.157

Pouget, A., Drugowitsch, J., & Kepecs, A. (2016). Confidence and certainty: Distinct probabilistic quantities for different goals. *Nature Neuroscience*, *19*(3), 366–374. https://doi.org/10.1038/nn.4240

Rahnev, D., Maniscalco, B., Graves, T., Huang, E., de Lange, F. P., & Lau, H. (2011). Attention induces conservative subjective biases in visual perception. *Nature Neuroscience*, *14*(12), 1513–1515. https://doi.org/10.1038/nn.2948

Rausch, M., Hellmann, S., & Zehetleitner, M. (2018). Confidence in masked orientation judgements is informed by both evidence and visibility. *Attention, Perception, & Psychophysics*, *80*(1), 134–154. https://doi.org/10.3758/s13414-017-1431-5

Rausch, M., Hellmann, S., & Zehetleitner, M. (2021). Modelling visibility judgements using models of decision confidence. *Attention, Perception, & Psychophysics*, *83*(8), 3311–3336. https://doi.org/10.3758/s13414-021-02284-3

Rock, I., & Victor, J. (1964). Vision and Touch: An Experimentally Created Conflict between the Two Senses. *Science*, *143*(3606), 594–596. https://doi.org/10.1126/science.143.3606.594

Rouault, M., McWilliams, A., Allen, M. G., & Fleming, S. M. (2018). Human Metacognition Across Domains: Insights from Individual Differences and Neuroimaging. *Personality Neuroscience*, *1*, e17. https://doi.org/10.1017/pen.2018.16

Sanborn, A. N., & Chater, N. (2016). Bayesian Brains without Probabilities. *Trends in Cognitive Sciences*, *20*(12), 883–893. https://doi.org/10.1016/j.tics.2016.10.003

Sanborn, A. N., Griffiths, T. L., & Navarro, D. J. (2010). Rational approximations to rational models: Alternative algorithms for category learning. *Psychological Review*, *117*(4), 1144–1167. https://doi.org/10.1037/a0020511

Sanders, J. I., Hangya, B., & Kepecs, A. (2016). Signatures of a Statistical Computation in the Human Sense of Confidence. *Neuron*, *90*(3), 499–506. https://doi.org/10.1016/j.neuron.2016.03.025

Schmiedek, F., Oberauer, K., Wilhelm, O., Süß, H.-M., & Wittmann, W. W. (2007). Individual differences in components of reaction time distributions and their relations to working memory and intelligence. *Journal of Experimental Psychology: General*, *136*(3), 414–429. https://doi.org/10.1037/0096-3445.136.3.414

Shams, L., Kamitani, Y., & Shimojo, S. (2000). What you see is what you hear. *Nature*, *408*(6814), 788–788. https://doi.org/10.1038/35048669

Shekhar, M., & Rahnev, D. (2024). How do humans give confidence? A comprehensive comparison of process models of perceptual metacognition. *Journal of Experimental Psychology: General*, *153*(3), 656–688. https://doi.org/10.1037/xge0001524

Song, C., Kanai, R., Fleming, S. M., Weil, R. S., Schwarzkopf, D. S., & Rees, G. (2011). Relating inter-individual differences in metacognitive performance on different perceptual tasks. *Consciousness and Cognition*, *20*(4), 1787–1792. https://doi.org/10.1016/j.concog.2010.12.011

Stein, B. E., & Meredith, M. A. (1993). *The Merging of the Senses*. MIT Press.

Stevenson, N., Innes, R. J., Boag, R. J., Miletić, S., Isherwood, S. J. S., Trutti, A. C., Heathcote, A., & Forstmann, B. U. (2024). Joint Modelling of Latent Cognitive Mechanisms Shared Across Decision-Making Domains. *Computational Brain & Behavior*, *7*(1), 1–22. https://doi.org/10.1007/s42113-023-00192-3

Stewart, N., Chater, N., & Brown, G. D. A. (2006). Decision by sampling. *Cognitive Psychology*, *53*(1), 1–26. https://doi.org/10.1016/j.cogpsych.2005.10.003

van den Berg, R., Anandalingam, K., Zylberberg, A., Kiani, R., Shadlen, M. N., & Wolpert, D. M. (2016). A common mechanism underlies changes of mind about decisions and confidence. *eLife*, *5*, e12192. https://doi.org/10.7554/eLife.12192

Van Wassenhove, V., Grant, K. W., & Poeppel, D. (2005). Visual speech speeds up the neural processing of auditory speech. *Proceedings of the National*

Academy of Sciences, *102*(4), 1181–1186. https://doi.org/10.1073/pnas.0408949102

Wagenmakers, E.-J., & Farrell, S. (2004). AIC model selection using Akaike weights. *Psychonomic Bulletin & Review*, *11*(1), 192–196. https://doi.org/10.3758/BF03206482

Welch, R. B., & Warren, D. H. (1980). Immediate Perceptual Response to Intersensory Discrepancy. *Psychological Bulletin*, *88*(3), 638–667.

West, R. K., Harrison, W. J., Matthews, N., Mattingley, J. B., & Sewell, D. K. (2023). Modality independent or modality specific? Common computations underlie confidence judgements in visual and auditory decisions. *PLOS Computational Biology*, *19*(7), e1011245. https://doi.org/10.1371/journal.pcbi.1011245

White, C. N., Servant, M., & Logan, G. D. (2018). Testing the validity of conflict drift-diffusion models for use in estimating cognitive processes: A parameter-recovery study. *Psychonomic Bulletin & Review*, *25*(1), 286–301. https://doi.org/10.3758/s13423-017-1271-2