Generalizable and scalable protein stability prediction with rewired protein generative models

Ziang Li[1] and Yunan Luo[1,*]

[1]School of Computational Science and Engineering, Georgia Institute of Technology
[*]Corresponding author: `yunan@gatech.edu`

Abstract

Predicting changes in protein thermostability caused by amino acid substitutions is essential for understanding human diseases and engineering proteins for practical applications. While recent protein generative models demonstrate impressive zero-shot performance in predicting various protein properties without task-specific training, their strong unsupervised prediction ability remains underexploited to improve protein stability prediction. We present SPURS, a deep learning framework that rewires and integrates two complementary protein generative models–a protein language model and an inverse folding model–and reprograms this unified framework for stability prediction through supervised fine-tuning on mega-scale thermostability data. SPURS delivers accurate, efficient, and scalable stability predictions with exceptional generalization to unseen proteins and mutations. Beyond stability prediction, SPURS enables broad applications in protein informatics, including zero-shot identification of functional residues, improved low-N protein fitness prediction, and systematic dissection of stability-pathogenicity for human diseases. Together, these capabilities establish SPURS as a versatile tool for advancing protein stability prediction and protein engineering at scale.

Introduction

Thermodynamic stability, often quantified by changes in Gibbs free energy (ΔG), is a fundamental property of proteins. Understanding protein stability is crucial for engineering robust proteins for industrial and therapeutic applications[1–3]. Although experimental techniques such as directed evolution have been successful in identifying stabilizing mutations, they require extensive experimental effort to screen numerous mutants, as stabilizing mutations are rare and the mutation exploration is often unguided. These constraints have driven the development of computational methods, particularly biophysical models and machine learning (ML) approaches[4], to predict stability changes ($\Delta\Delta G$) resulting from amino acid substitutions, offering cost-effective alternatives for engineering stabilized proteins.

While deep learning has revolutionized protein structure prediction through models like AlphaFold[5], no comparable transformative methods have emerged for protein stability prediction yet. This disparity stems primarily from data scarcity and the limitations of current computational models. Most current ML methods for stability prediction[6–14] are trained on relatively modest datasets[8,9,15–18], typically containing only hundreds to thousands of mutants across tens to hundreds of proteins. The mismatch between the limited data and the large demands of training data by modern ML models results in poor prediction generalization, particularly to unseen proteins or rare mutations. Although database consolidation efforts[16,19,20] have expanded data coverage, their inherent biases toward destabilizing variants, specific protein families, and experimental conditions continue to hinder progress in stability prediction, even as ML model complexity continues to grow.

Recent advances in mutagenesis experiments, such as complementary DNA (cDNA) proteolysis assays, offer new opportunities for ML-based protein stability prediction. A notable example is the mega-scale dataset (hereafter "Megascale" dataset) by Tsuboyama et al.[21], which provides over 770,000 $\Delta\Delta G$ measurements spanning all single and selected double amino acid variants across 479 diverse protein domains. This dataset, derived consistently from the same assay, represents an unprecedented resource for developing high-capacity ML models for protein stability prediction. However, fully realizing its potential requires ML models capable of capturing the underlying thermodynamic constraints driving protein folding and stability.

In parallel, protein generative models, including protein language models (pLMs)[22–25] and inverse-folding models (IFMs)[26,27], have recently emerged as "foundation models" for various ML tasks in protein informatics. Pre-trained to predict masked residue amino acids using context from unmasked residues (Fig. 1a), these models capture evolutionary patterns and biophysical constraints from vast natural protein sequence or 3D structure data. Studies have shown that these models can predict mutation effects in a zero-shot manner by calculating the log-likelihood ratios between mutants and wild-type proteins[28–30], correlating well with diverse protein fitness measures, including pathogenicity[31], binding affinity[32], and thermostability[30,33], even without task-specific supervised training.

These findings raise the natural expectation that combining pre-trained generative models with large-scale stability data through supervised training could yield improved stability prediction performance. However, recent studies reported that fine-tuning pLMs on the Megascale dataset often results in limited or even degraded performance compared to conventional ML models trained from scratch[34,35]. One explanation of this underperformance lies in the sheer size of pLMs with $\sim 10^9$ parameters, making them prone to overfitting[36] despite the availability of mega-scale training data. Moreover, pLMs operate solely on linear amino acid sequences, lacking structural context of 3D residue interactions that are crucial for modeling protein thermostability.

Addressing this limitation, recent efforts have explored structure-aware generative models like Protein-MPNN[26] and ESM-IF[37] for stability prediction via fine-tuning[38,39]. These models incorporated 3D structural information and have demonstrated improved generalization to unseen proteins, with some now recognized

as state-of-the-art among ML-based stability predictors[39,40]. However, IFMs like ProteinMPNN are intrinsically constrained by the quantity and diversity in their training data, which includes only experimentally determined structures (∼20k curated structures from the CATH database)–orders of magnitude fewer than the over 400M protein sequences in UniRef[41]. While other IFMs like ESM-IF incorporate AlphaFold2-predicted structures to expand training coverage, this approach remains constrained by the number of structures that can be predicted and the accuracy of the predictions, failing to capture full sequence diversity. Consequently, IFMs underutilize rich evolutionary information from large-scale sequence data, while pLMs lack explicit structural grounding. We hypothesize that integrating pre-trained pLMs and IFMs—trained on complementary modalities—could synergistically improve stability prediction by combining sequence-derived evolutionary priors with structure-based geometric features. However, fusing these models presents substantial challenges due to differences in their data modality, architectural design, and training scale.

In this work, we introduce SPURS (stability prediction using a rewired strategy), a deep learning framework that integrates sequence- and structure-based protein generative models for generalizable stability prediction (Fig. 1b). At the core of SPURS is a model rewiring strategy that implants a lightweight Adapter module[42,43] into a pLM (ESM[24]), enabling it to incorporate structure-informed features learned by an IFM (ProteinMPNN[26]) while preserving the pLM's evolutionary priors learned from large-scale sequence training (Fig. 1c). This design captures both IFM's features specific to structural stability alongside pLM's features supporting broad generalization. It also allows parameter-efficient fine-tuning, requiring updates to only a small fraction of trainable parameters to jointly model sequence and structure for $\Delta\Delta G$ prediction. Importantly, SPURS is highly scalable by design: it predicts $\Delta\Delta G$ values for all possible point mutations of a protein in a single forward pass of the neural network, in contrast to many prior methods that require separate evaluations per mutant. This scalability enabled us to perform large-scale stability predictions across the human proteome.

SPURS demonstrates strong generalization in protein stability prediction. We trained SPURS on the Megascale dataset and systematically benchmarked performance across 12 diverse datasets measuring thermostability ($\Delta\Delta G$) and melting temperature changes (ΔT_m). SPURS consistently outperformed state-of-the-art methods, achieving robust generalization to unseen mutations and proteins across datasets. In particular, SPURS excels at identifying stabilizing mutations, a persistent challenge for most existing methods due to the pronounced imbalance toward destabilizing variants in current stability datasets[44].

Beyond stability prediction, SPURS enables a range of compelling applications in protein biology (Fig. 1d). We show that, when paired with a pLM, SPURS can accurately identify functionally important residues involved in protein binding using only sequence input, without relying on binding structure information. We also demonstrate that SPURS's $\Delta\Delta G$ predictions serve as informative priors for guiding the prediction of protein variant fitness, enabling a simple yet effective regression model that enhances low-N fitness prediction. Finally, leveraging its scalability, we applied SPURS to the human proteome to dissect the role of stability loss in variant pathogenicity and uncover the distinct molecular mechanisms of different pathogenic mutations. Together, these capabilities position SPURS as a versatile method for protein stability modeling, with broad applications in structural biology, protein engineering, and functional genomics.

Results

SPURS: Thermostability prediction leveraging protein generative models

SPURS is a deep learning framework designed to predict changes in protein thermostability ($\Delta\Delta G$) resulting from amino acid substitutions (Fig. 1). Given a wild-type protein sequence, SPURS predicts $\Delta\Delta G$ for all possible point mutations or specified higher-order mutations. To inform these predictions, SPURS explicitly incorporates the 3D structure of the wild-type protein as additional input. Structure information is represented as atomic coordinates and abstracted into a graph with atoms as nodes and edges defined by spatial proximity (Methods). When an experimental structure is unavailable, SPURS employs AlphaFold[5] to predict the structure, ensuring broad applicability.

Figure 1: SPURS architecture. a-b, SPURS is a deep learning framework that rewires two pre-trained protein generative models (**a**) –a protein language model (ESM2) and an inverse folding model (ProteinMPNN)–to predict changes in protein thermostability ($\Delta\Delta G$) upon sequence mutations (**b**). **c**, The model takes as input a protein's wild-type sequence and structure (predicted by AlphaFold2 if the experimental structure is unavailable). Through neural network rewiring, SPURS integrates evolutionary priors from ESM2 and structural features from ProteinMPNN to learn structure-enhanced evolutionary features. These representations are passed to a prediction module that efficiently decodes $\Delta\Delta G$ predictions for all single mutations. The same features are reused by another decoder to predict epistatic effects of multiple mutations, enabling $\Delta\Delta G$ prediction for higher-order mutants. **d**, SPURS's performance is demonstrated in stability prediction and diverse applications in protein biology, including functional site identification, protein fitness prediction, and pathogenicity analysis. Abbreviations: Struct=Structure; Evo=Evolution.

At the core of SPURS is an effective integration of two pre-trained protein generative models (Fig. 1a): ESM2[24], a Transformer-based protein language model (pLM) trained on protein sequences, and Protein-MPNN[26], a graph neural network-based inverse-folding model (IFM) trained on protein structures. SPURS utilizes ProteinMPNN as a structure encoder to extract geometric features important for protein stability while leveraging sequence evolutionary priors learned by ESM to dissect mutation effects on stability (Methods).

Rather than treating these two models separately or integrating their outputs heuristically, SPURS employs Adapter[42,43], a lightweight neural network module, to rewire ProteinMPNN's structure-derived embeddings into ESM's sequence embeddings, learning structure-enhanced sequence representations in a parameter-efficient fashion (Fig. 1b-c; Methods). During training, only Adapter and ProteinMPNN parameters are updated, while ESM's parameters remain fixed. This integration strategy introduces only minimal architecture alterations to ESM and ProteinMPNN, preserving their rich evolutionary priors learned from pre-training while avoiding overfitting. This approach also makes SPURS highly data-efficient for fine-tuning, as it dramatically reduces trainable parameters by 98.5% compared to full ESM fine-tuning used in previous studies[35,39]. Although this work specifically uses ESM and ProteinMPNN, SPURS is a model-agnostic framework and can integrate other sequence- and structure-based generative models[25,37] for stability prediction.

SPURS offers significant scalability advantages through its algorithmic design. At the output layer, SPURS predicts $\Delta\Delta G$ for all possible point mutations for the input protein in a single forward pass of the neural network (Fig. 1c). This represents a major advancement over existing stability prediction methods[10,34,35,45,46], which typically require separate forward passes for each mutant sequence, resulting in computational cost of $\mathcal{O}(L \times 20)$ forward passes for a protein of length L. In contrast, SPURS transforms this one-mutant-per-pass approach to an all-mutants-per-pass paradigm. Rather than processing mutant sequences as input, SPURS conditions on wild-type sequence and structure to predict stability changes for all possible point substitutions simultaneously. This is achieved by learning per-residue latent representations and using a decoder shared across all residues to predict effects of substituting each residue with any of the 20 amino acids (Methods). This all-at-once inference paradigm reduces the required number of forward passes from $\mathcal{O}(L \times 20)$ to $\mathcal{O}(1)$, enabling efficient large-scale protein stability profiling. In our experiments, SPURS predicted $\Delta\Delta G$ for all single mutants across 118 full-length proteins from the ProteinGym benchmark[29] (mean length: 492 residues) in under 20 seconds on a single NVIDIA A40 GPU.

SPURS was trained on the Megascale dataset, comprising over 200,000 $\Delta\Delta G$ measurements for single amino acid substitutions across over 200 proteins. This unprecedented data size enables SPURS to learn generalizable representations for unseen proteins and mutations. Additionally, Megascale's dense mutational coverage–with each wild-type protein exhaustively mutagenized for all possible point mutations–enables SPURS to learn fine-grained, generalizable patterns across protein space and effectively capture the full $\Delta\Delta G$ landscape of $L \times 20$ possible substitutions.

We further extended SPURS to predict stability for higher-order mutants by modeling $\Delta\Delta G$ of a multi-mutation variant as the sum of individual mutation effects plus an epistatic term capturing non-additive interactions. SPURS reuses point-mutation predictions, inferred from a single forward pass, and employs an additional lightweight decoder network to predict epistatic effects (Methods). This extended SPURS framework was trained on all single- and double-mutation $\Delta\Delta G$ measurements from Megascale. This design captures complex combinatorial effects while maintaining efficiency. Together, SPURS provides a scalable, generalizable framework for stability prediction across both single and combinatorial mutation regimes.

SPURS enables accurate and generalizable protein stability prediction

To evaluate SPURS's performance in predicting protein stability changes upon mutations, we curated 12 datasets of stability measurements from published studies (Methods). These datasets vary in protein diversity and mutant coverage (Fig. 2a), collectively forming a comprehensive benchmark for assessing model accuracy and generalization. We first focused on the Megascale dataset[21], using the training, validation, and test splits (8:1:1 ratio) established in the ThermoMPNN study[38], comprising $\Delta\Delta G$ measurements for 272,721 single-substitution mutants across 298 proteins. To prevent information leakage, we removed from the training and

validation splits any sequences with $> 25\%$ sequence identity to those in the test split or other independent datasets (Methods). Throughout our experiments, SPURS was trained on this filtered Megascale training set.

We first compared SPURS to ThermoMPNN, the state-of-the-art ML model for stability prediction, on the Megascale test set covering 28,312 mutants across 28 proteins. SPURS outperformed ThermoMPNN in Spearman correlation (median 0.83 vs. 0.77, Mann-Whitney U test $P < 0.05$) in 24 out of 28 proteins (Fig. 2b) and remained comparable for the remaining four proteins. This improvement can be attributed to SPURS's effective integration of both sequence and structural priors from ESM and ProteinMPNN, in contrast to ThermoMPNN, which fine-tuned structure-based ProteinMPNN. Further, SPURS's rewiring strategy outperformed a straightforward integration approach that simply concatenates final-layer embeddings from ESM and ProteinMPNN across all test datasets (Fig. 2d), suggesting the consistent effectiveness of its integration.

Another ablation study, where we fine-tuned ESM and ProteinMPNN individually using multi-layer perceptrons (MLPs) on top of frozen ESM or ProteinMPNN layers, confirmed that fine-tuning either model alone led to performance drops compared to their integration in SPURS (Fig. 2c). Interestingly, even sequence likelihoods predicted by unsupervised ESM and ProteinMPNN exhibited a non-trivial Spearman correlation with $\Delta\Delta G$ measurements in Megascale (0.46 and 0.61, respectively). This observation is consistent with previous studies[30], suggesting that protein generative models, even without explicit training on stability data, capture evolutionary features predictive of stability. This forms the basis of our hypothesis and other works[35,38] that supervised fine-tuning of protein generative models improves stability prediction.

Next, we evaluated SPURS's generalizability using eight independent test sets from other studies[8,9,15,18,38,45,47]. We excluded sequences in the Megascale training and validation sets that had more than 25% sequence identity with these test sets. We additionally included six leading baselines (Supplementary Note B.1), including biophysical models (FoldX[48], Rosetta[49]) and ML methods (PROSTATA[10], RASP[34], Stability Oracle[50], ThermoNet[7], ThermoMPNN[38]). SPURS showed significantly higher (for 7/8 test sets) or comparable Spearman and Pearson correlations across all datasets compared to these baselines (Fig. 2e and Supplementary Tables 1, 2, and 3).

We also explored SPURS's ability to generalize to melting temperature (ΔT_m) prediction, another measure of protein stability. Even though SPURS was only trained on $\Delta\Delta G$ data, it demonstrated improved Spearman correlations on two ΔT_m datasets[45], S4346 and S571 (Fig. 2e), which highlights SPURS's broad capability to capture stability-related features beyond its training data.

To assess SPURS's ability to predict $\Delta\Delta G$ for higher-order mutants, we evaluated its performance on double-mutation data from the Megascale test set. SPURS outperformed DDGun[14] and MutateEverything[51], two competitive existing methods that support stability prediction for combinatorial mutations (Fig. 2f), even though advantages were given to MutateEverything as 13 of 20 proteins in our test set were included in its training set. In the comparison, we also included methods that only predict stability change for point mutations, including the fine-tuned ESM, ProteinMPNN, and ThermoMPNN, to predict for high-order mutants through additive effects of constituent individual mutations. Results showed that SPURS substantially outperformed these additive approaches (Fig. 2f), suggesting that multiple mutation effects on stability are not simply additive and that SPURS's modeling of epistatic effects is critical to achieving the performance gain.

Stabilizing mutations are of particular interest for protein engineering but are often rare and underrepresented in most datasets. As a result, many models tend to optimize prediction accuracy for overrepresented destabilizing variants, inflating apparent accuracy[50,52]. To assess robustness in this regime, we evaluated SPURS's ability to prioritize stabilizing mutations (defined as $\Delta\Delta G < -0.5$ kcal/mol[53]; $N=1{,}178$) from a much larger pool of destabilizing ones ($N=27{,}139$) in the Megascale test set. Across various prediction

Figure 2: SPURS achieves accurate prediction for protein stability. a, The numbers of proteins and mutants across the datasets used for training and evaluation. **b,** Performance comparison of SPURS and ThermoMPNN (a state-of-the-art deep learning-based stability model) on the Megascale test set. Each dot represents the Spearman correlation of SPURS and ThermoMPNN on a single protein test set. **c,** Performance comparison between SPURS and additional baseline methods on the Megascale test set ($n = 28$). ESM and ProteinMPNN are evaluated in a zero-shot setting using sequence likelihood differences between mutant and wild-type; FT-ESM and FT-ProteinMPNN denote fine-tuned (FT) versions of ESM and ProteinMPNN trained on the same Megascale training split as SPURS and ThermoMPNN. *: two-side Mann-Whitney U test P=0.003. **d,** Effectiveness of SPURS's rewiring strategy for integrating sequence- and structure-based protein generative models. SPURS was compared to a straightforward integration approach that directly concatenates the final-layer embeddings of ProteinMPNN and ESM ("Concatenation"). **e,** Performance of SPURS versus baseline methods across the Megascale test set and ten independent benchmarks. **f,** Performance for predicting $\Delta\Delta G$ of double-mutation mutants in the Megascale test set. Bar plots represent mean±s.d. of the performances on ten 80% bootstrapped subsets ($n = 10$) from all double mutants in the Megascale test split. DDGun-3D and DDGun-seq use structure and sequence features to predict $\Delta\Delta G$, respectively. FT-ESM, FT-ProteinMPNN, and ThermoMPNN are single-mutant predictors extended to predict for double mutants by simply adding the predicted $\Delta\Delta G$ of constituent individual mutations ("additive methods"); other methods directly support combinatorial predictions. **g,** Precision–recall comparison between SPURS and ThermoMPNN for identifying stabilizing mutations in the Megascale test set. **h,** Performance comparison on the Domainome dataset ($n = 522$). ESM1v (full) takes the full-length protein sequence as input, whereas ESM1v (domain) uses domain subsequences. Abbreviations: VEP = Variant effect predictors; rSASA = Relative solvent-accessible surface area. Box plots in **c** and **h** indicate the median (center line), 25th–75th percentiles (box), and whiskers represent data within 1.5× the interquartile range from the box.

thresholds, SPURS consistently outperformed ThermoMPNN in both precision and recall (Fig. 2g), indicating its effectiveness in identifying stabilizing mutations.

Finally, we applied SPURS to the recently released Human Domainome dataset[40], which quantifies the impact of human missense variants on protein stability using protein abundance in cells. This dataset contains 563,534 variants across 522 proteins, offering the largest diversity and coverage among our benchmarks (Fig. 2a). The original Domainome study reported that ThermoMPNN outperformed several other models for stability prediction, including general variant effect predictors (e.g., AlphaMissense[54] and EVE[31]), structural features (relative solvent accessibility), and dedicated stability predictors. We thus re-examined this evaluation and additionally compared SPURS with these reported methods. The result showed that SPURS significantly improved upon the best baseline, ThermoMPNN (correlation 0.54 vs. 0.49), further demonstrating SPURS's generalizability across large-scale variant effect landscapes of stability (Fig. 2h).

Taken together, our benchmark results demonstrate that SPURS achieved state-of-the-art performance for protein stability prediction, with superior generalizability and reduced bias compared to existing models.

SPURS identifies functionally important sites in proteins

Proteins perform diverse cellular functions, largely through interactions with other molecules. Identifying the residues responsible for these interactions is key to understanding molecular mechanisms and developing biomedical applications. Stability is just one biophysical property that contributes to protein function, while others, such as binding specificity and enzymatic activity, often trade off with stability during evolution[55]. Thus, the loss of function due to mutations can be attributed to either direct disruption of molecular interactions or structure destabilization that leads to reduced protein abundance. Mutations at protein binding interfaces, active sites, and allosteric sites frequently have larger effects on function than what stability changes alone can explain[21,56,57], making it complicated to deconvolve the effects of substitutions on intrinsic function from those on stability[57,58]. Recent experimental studies attempted to resolve this biophysical ambiguity by quantifying mutation effects on both protein binding and abundance, allowing comprehensive mapping of functional sites[56,59]. Inspired by this, we hypothesized that a similar strategy, combining SPURS's stability predictions with evolutionary fitness scores from pLMs, could help disentangle mutation effects on function and identify functional sites.

Specifically, we used SPURS to predict $\Delta\Delta G$ and ESM1v[28] to estimate the evolutionary fitness of a protein variant (Methods). Here, 'fitness' broadly refers to protein functions like binding affinity, catalytic activity, and more. ESM1v has been shown to be effective for zero-shot predictions of mutation effects on protein fitness[28]. We fit a sigmoid function to model the non-linear relationship between stability and fitness (Fig. 3a; Methods), following prior work that employed non-linear Boltzmann distribution to model the relationship between free energy changes caused by mutations in protein folding and those in protein binding[56,59–62]. A recent study showed that the residuals (fitting deviation) from the fitted sigmoid curve indicate whether mutations have larger or smaller effects on protein fitness than can be explained by changes in stability[40]. Our approach generalized their study by extending functional site identification beyond the restricted set of 500 protein domains with experimental stability data[40], scaling up to diverse, full-length proteins using SPURS's accurate stability predictions. We computed the fit residuals for all single mutations in a given protein (Fig. 3b) and defined a per-site function score by averaging residuals across all mutations at each site (Methods). Residues with high function scores are likely to be functionally important[40] (Fig. 3b,c).

We evaluated this approach for identifying function sites using 239 proteins from the Domainome dataset[40] with residue-level functional site annotations in the Conserved Domain Database (CDD)[63]. Among 14,434

Figure 3: SPURS accurately guides functional site annotation. a, ESM1v-predicted fitness scores and min-max normalized stability changes (-$\Delta\Delta G$) predicted by SPURS for the HMG-box domain (UniProt ID: P35716). A sigmoid function is fitted to model the relationship between fitness and normalized stability change. Color gradient represents SPURS's predicted function score. **b**, Heatmap depicting function scores of the HMG-box domain, with red letters indicating CDD-annotated DNA-binding sites. **c**, Structure of the HMG-box domain (PDB ID: 6T7C), where residues are colored based on SPURS's predicted function scores and DNA-binding sites are annotated. **d**, Distribution of SPURS's predicted function scores for functional sites annotated in CDD versus other sites across 239 human domains. **e**, SPURS's AUROC performance for functional site prediction across 239 human domains. **f**-**m**: The structures colored by SPURS's function scores for the six domains highlighted in **e**. Below each structure, a scatter plot shows the predicted function score for each residue, with CDD-annotated functional sites marked as ×. **f**, LIM domain in FHL1 (UniProt ID: Q13642; PDB ID: 1X63). **g**, SH3 domain in GRB2 (P62993, 1IO6). **h**, Alcohol dehydrogenase (P00327, 1QLH). **i**, Zoom-in view of the zinc ion around the catalytic center. **j**, SAM domain in CNKSR2 (Q8WXI2, 3BS5). **k**, MBD domain in MECP2 (P51608, 5BT2), **l**, PDZ domain in DLG3 (Q92796, 2FE5), **m**, PDZ domain in SCRIB (Q14160, 6XA7).

residues across these proteins, 3,516 were labeled as functional in CDD, while the rest were considered non-functional. SPURS's function score significantly distinguished functional from non-functional sites (Fig. 3d; t-test $P < 1 \times 10^{-150}$). At the individual protein level, SPURS achieved an average AUROC of 0.69 (Fig. 3e). Given that SPURS was not trained on functional site labels in contrast to previous supervised methods[64], these results demonstrated its strong unsupervised capability for identifying functional sites and scaling beyond with experimental stability data.

We further explored SPURS's predicted functional sites across seven protein domains that ranked high or mid in AUROC (Fig. 3e). These proteins were chosen to cover human domains that represent various sizes (56–97 residues), diverse structural folds, and different functions, including protein-protein interaction, DNA binding, ion interaction, and enzymatic activity. By mapping SPURS's function score onto their 3D structure, we found high-score regions significantly enriched for functional sites (Figs. 3f-m).

In the LIM domain, which contains two four-residue zinc fingers, SPURS assigned high scores exclusively to the zinc-coordinating residues (Fig.3f). Similarly, in the SH3 domain, SPURS accurately captured its critical peptide-binding sites (Figs. 3g). We extended this analysis to proteins not presented in Domainome, such as alcohol dehydrogenase (EC 1.1.1.1), a zinc-dependent enzyme. SPURS successfully identified its key zinc-binding residues (C46, H62, and C174) and a stabilizing residue (S48), which forms hydrogen bonds critical for the enzyme's structure (Fig. 3h-i)

Notably, despite being trained only on single-chain inputs, SPURS identified interaction interfaces and binding sites. For example, it highlighted SAM domain residues near the heterodimer interaction interface (Fig. 3j), even though its interacting partner's sequence or structure was not provided as input to SPURS. A similar observation was made for the MBD domain, where SPURS not only recovered DNA binding sites but also identified a β-turn located between two β-strands and close to the DNA helix (Fig. 3k). While this β-turn was not annotated by CDD as functional sites, it appeared to coordinate the protein-DNA binding, suggesting the potential of SPURS for discovering new functional sites.

SPURS also demonstrated consistency across different proteins harboring the same domain. For example, in two proteins with PDZ domains (Figs. 3l-m), SPURS assigned high function scores to several residues that occupy structurally corresponding positions in both proteins. A serine residue (S239 in Fig. 3l and S875 in Fig. 3m) consistently received the highest function score in both structures despite their different structural contexts. While SPURS prioritized consistent functional sites for both proteins, it also captured the context-dependent nature of binding and gave higher scores to residues involved in specific ligand interactions unique to each protein. In one case where the domain binds to a small glycerol molecule (Fig.3l), a lysine (K299) interacting with the molecule received a higher score than its counterpart in the other protein, while in the second case where the same domain binds to a peptide (Fig.3m), SPURS prioritized peptide-proximal residues (L872, H928). Importantly, the ligands were only shown for visualization and were not provided as input to SPURS. Nonetheless, SPURS was able to identify both conserved functional sites for the same domain across proteins and context-dependent sites specific to each protein's binding function.

These case studies illustrate SPURS's strong agreement with CDD annotations and its ability to identify both conserved and context-specific functional sites. Unlike previous methods that rely on docking structures[65] or supervised training[64], our approach is unsupervised, requiring only sequence input, with structural predictions generated by AlphaFold when needed. This approach alleviates data bottlenecks in functional site annotation, making it a powerful tool for applications like hotspot identification in protein engineering.

SPURS improves low-*N* protein fitness prediction

Having established SPURS's accuracy in predicting protein stability changes, we explored whether it could extend to enhancing the prediction of mutation effects on broader protein properties beyond stability. Many laboratory assays have been developed to measure various protein properties like binding affinity, expression, and solubility, often generally referred to as fitness. However, experimental techniques can only probe a tiny fraction of the exponentially large sequence space and screen their fitness, making it critical in protein engineering to develop ML models that generalize well from small-sized (low-*N*) fitness data to predict for unseen sequences[27,36,66].

Here, we aim to improve low-*N* fitness prediction models with SPURS. Proteins need to be structurally stable to perform functions. We thus hypothesized that SPURS's stability predictions could serve as informative priors for fitness prediction. We propose a simple yet effective approach that incorporates SPURS's $\Delta\Delta G$ prediction to improve protein fitness prediction. Our approach was inspired by a leading supervised low-*N* fitness prediction model called 'Augmented model'[27]. To predict the fitness of a protein variant, the Augmented model uses as input features the one-hot-encoded sequence and an evolutionary density score, which is the likelihood ratio between the mutant and the wild-type sequences predicted by pLMs like ESM or other sequence density models (e.g., DeepSequence[67] or EVE[31]), to train a Ridge regressor on fitness data (Fig. 4a). We extended the Augmented model by incorporating SPURS's $\Delta\Delta G$ predictions as an additional feature in the regressor (Fig. 4a; Methods), yielding an enhanced model denoted as 'SPURS-augmented ESM' when ESM is used as the sequence density model, or similarly if other models are used.

We compared SPURS-augmented models against a series of Augmented models, including Augmented-{ESM1b[22], EVMutation[68], Evotuned UniRep[69], DeepSequence[67]}, on the fitness data of 12 proteins from the original study[27]. Using 240 randomly sampled mutants for training and the rest for testing, SPURS-augmented models outperformed their counterparts for most proteins, with a 7% improvement in Spearman correlation (Fig. 4b). To further assess performance, we extended evaluation to the ProteinGym benchmark[29], which includes over 200 deep mutational scanning (DMS) datasets spanning various protein fitness metrics such as catalytic activity, binding affinity, stability, and organismal fitness. We excluded DMS datasets measuring stability, so as to test generalization beyond the property SPURS was trained on. Across the resulting 141 DMS datasets, SPURS-augmented DeepSequence model outperformed the original Augmented DeepSequence–the most competitive method reported[27]–in 115 (82%) cases, with an overall 15% improvement in Spearman correlation (Fig. 4c). Performance improvements were especially pronounced in datasets measuring expression (24.1%) and organismal fitness (16.5%) compared to activity (8.0%) and binding (12.6%) (Fig. 4d). These improvements were consistent across varying training set size *N* from as few as 48 to 240 variants, and up to 80% of the total sequences in a DMS dataset (Fig. 4e).

In summary, these results showed that the SPURS's $\Delta\Delta G$ predictions provide informative priors for protein fitness prediction, consistently enhancing leading low-*N* models across diverse DMS datasets and training data sizes. We note that our SPURS-augmented model itself is not intended to be a stand-alone, state-of-the-art predictor that outperforms a large volume of existing low-*N* models leveraging sophisticated deep learning models (e.g., pLMs)[27,36,66]. Instead, it serves as a simple yet effective enhancement that yields consistent performance gains when added to already-competitive models, highlighting SPURS's utility as a general-purpose stability prior for protein engineering tasks.

Figure 4: SPURS-augmented models enhances low-N protein fitness prediction. a, Architecture of the SPURS-augmented model. Compared to the original Augmented models [27], our approach adds SPURS's predicted stability change as an additional feature. **b**, Performance comparison between SPURS-augmented models (squares) and their corresponding Augmented models (dots) on 12 proteins benchmarked in Hsu et al. [27]. Aug=Augmented. **c**, Performances of SPURS-augmented DeepSequence and Augmented DeepSequence across 141 DMS datasets in ProteinGym, excluding stability-related sets and those with fewer than 96 variants. DMS dataset names on x-axis were abbreviated, with a mapping to their full names defined by ProteinGym provided in Supplementary Table 5. Results in **b-c** show the mean Spearman correlation over 20 repetitions of randomly sampled training sets. **d,** Relative Spearman correlation improvement of SPURS-augmented DeepSequence over Augmented DeepSequence, grouped by fitness categories from **c** (Activity, n = 42; Binding, n = 11; Expression, n = 18; OrganismalFitness, n = 70). **e,** Low-N prediction performance comparison between SPURS-augmented DeepSequence and Augmented DeepSequence across varying training set size N, from 48 variants up to 80% of each dataset. In **d-e**, plots show the mean±s.d. of the test performances of 20 repetitions of model training, with different random seeds used to randomly sample training data.

SPURS reveals contribution of stability to pathogenicity

The human proteome harbors millions of missense variants, where single amino acid substitutions may alter protein structure and function, contributing to genetic diseases[70–72]. While pathogenic variants may disrupt function through various molecular mechanisms such as perturbing interactions, the loss of function due to mutation effect on stability has been recognized as a major cause of disease[73–77]. Given SPURS's ability to predict protein stability changes ($\Delta\Delta G$) upon mutations, we sought to apply SPURS to examine the role of protein stability in pathogenicity.

We used SPURS to predict $\Delta\Delta G$ for all possible single amino acid substitutions in the human proteome (178,987,201 variants across 19,652 proteins). Among these, 696,736 variants spanning 16,997 proteins have clinical annotations from ClinVar[78] as either (likely) 'benign', (likely) 'pathogenic', or variants of uncertain significance (VUS). Additionally, we included 15,820 missense variants from gnomAD (allele frequency >0.05) as putative benign variants[40,79,80]. Our analysis revealed that pathogenic variants are more destabilizing, whereas most benign variants exhibit minimal stability changes (Fig. 5a). For example, 68% pathogenic variants (7,761/26,090) were destabilizing ($\Delta\Delta G > +0.5$ kcal/mol[30,53]), compared to only 19% of benign variants (9,497/50,763). These findings align with previous studies showing loss of stability as a key driver for loss of function for many disease variants[7,40,74,81].

To examine how structural context modulates the relationship between stability changes and pathogenicity, we stratified ClinVar variants by spatial locations and solvent exposure using AlphaFold2 predicted structures. First, we compared SPURS's $\Delta\Delta G$ predictions for mutations in folded regions versus intrinsically disordered regions (IDRs). In both groups, pathogenic variants were more destabilizing than benign ones (mean $\Delta\Delta G$ difference +0.86 kcal/mol and +0.40 kcal/mol for folded regions and IDRs, respectively), but the effect was stronger in folded regions (Fig. 5b), consistent with previously reported tolerance of IDRs to mutations[82]. While we recognize that AlphaFold2-predicted structures used in this analysis may not model IDRs accurately[83], recent studies on IDR conformation modeling may facilitate a better understanding of stability's role in pathogenicity in IDRs[84].

Within folded regions, we compared $\Delta\Delta G$ distributions for buried versus exposed residues (Fig. 5c). Again, pathogenic variants were more destabilizing than benign variants in both groups, but the difference was notably greater in buried positions than in exposed regions (mean $\Delta\Delta G = 1.47$ kcal/mol vs. $= 0.67$ kcal/mol). This observation, consistent with previous studies[85,86], suggests that pathogenic variants in buried residues primarily drive loss of function by reducing stability, whereas those at exposed sites likely disrupt function through alternative mechanisms, such as directly perturbing functional sites or intermolecular interactions[86].

Recognizing that the impact of stability on pathogenicity varies with residue exposure, we hypothesize that combining $\Delta\Delta G$ prediction with structural context could enhance the identification of pathogenic mutations. Using relative solvent-accessible surface area (rSASA) to quantify residue exposure (Methods), we found that pathogenic variants were enriched in regions with both high $\Delta\Delta G$ values and low rSASA scores (Fig. 5d), indicating that most pathogenic variants are located in buried residues and destabilize protein structure. Motivated by this, we developed an unsupervised predictor by linearly interpolating SPURS's predicted $\Delta\Delta G$ with rSASA with a weighting coefficient α to classify pathogenic and benign variants. Despite lacking supervised training on clinical variant annotations, this simple score achieved a maximum AUROC of 0.84 at $\alpha = 0.7$, outperforming models based on either feature alone (Fig. 5e). This result highlights the potential synergy between stability and structural context in explaining pathogenicity. Note that our goal here is not to outperform state-of-the-art variant effect predictors with an optimal value of α[54,87,88], but rather to

Figure 5: SPURS reveals the role of protein destabilization in variant pathogenicity. **a,** Distribution of SPURS-predicted stability change for ClinVar variants labeled as benign (including 'Benign' and 'Likely benign'), pathogenic (including 'Pathogenic' and 'Likely pathogenic'), and variants of uncertain significance (VUS). Common gnomAD variants (allele frequency >0.05) are included as putative benign variants for comparison. **b-c** Distribution of SPURS-predicted stability change for benign and pathogenic ClinVar missense mutations, categorized by (b) spatial locations—folded regions (n=31,463 benign, n=24,085 pathogenic) vs. intrinsically disordered regions (IDRs; n=19,207 benign, n=1,478 pathogenic)—and (c) solvent exposure—exposed residues (n=42,158 benign, n=10,419 pathogenic) vs. buried residues (n=8,512 benign, n=15,144 pathogenic). **d,** Joint distribution of SPURS-predicted $\Delta\Delta G$ and relative solvent-accessible surface area (rSASA) for ClinVar benign and pathogenic missense variants. Contour maps indicate the density of variants in the rSASA–$\Delta\Delta G$ space. **e,** AUROC for classifying ClinVar benign and pathogenic variants using a score that linearly interpolates SPURS-predicted $\Delta\Delta G$ and rSASA, defined as $\alpha \cdot \Delta\Delta G + (1-\alpha) \cdot$rSASA, with α as the interpolation coefficient. **f,** Comparison of SPURS-predicted $\Delta\Delta G$ values for gnomAD variants (n=15,820) and pathogenic ClinVar mutations in autosomal dominant (AD, n=6,722) and autosomal recessive (AR, n=5,603) genes. **g,** Gene-level enrichment of destabilizing or stabilizing cancer-associated missense mutations. $\Delta\Delta G$ difference for a gene is defined as the mean SPURS-predicted $\Delta\Delta G$ of observed COSMIC cancer mutations minus that of unobserved mutations in the same gene. A positive $\Delta\Delta G$ difference indicates selection for destabilizing mutations in the gene, whereas a negative difference suggests selection against destabilization. The horizontal dashed line represents the Bonferroni-corrected significance threshold ($P = 2.8 \times 10^{-6}$, two-side Mann-Whitney U test), corresponding to a pre-correction significance cutoff of 0.05. Box plots in **b**, **c**, and **f** indicate the median (center line), 25th–75th percentiles (box), and whiskers represent data within $1.5\times$ the interquartile range from the box.

demonstrate that integrating stability prediction and structural context yields a synergistic and effective classifier. Together, these results (Figs. 5a-e) reinforce prior studies[86,89] and highlight the importance of structural contexts in understanding variant pathogenicity.

Next, we investigated the mutation effects on stability in different modes of inheritance and disease mechanisms. Autosomal recessive (AR) diseases are strongly associated with loss-of-function mutations, whereas autosomal dominant (AD) diseases can arise from alternate molecular mechanisms, including gain-of-function mutations, dominant-negative effect, or protein aggregation[79,90], which may not always involve substantial stability loss. We collected 6,722 AR-associated genes and 5,603 AD-associated genes annotated in the OMIM databases[91] and applied SPURS to predict $\Delta\Delta G$ for the 12,325 pathogenic ClinVar variants covered by these genes. Consistent with previous findings[40,79], we found that pathogenic variants in AR genes were more destabilizing than those in AD genes or gnomAD variants (Fig. 5f; one-sided Mann-Whitney U test both $P < 10^{-50}$). This difference is partly explained by the spatial distribution of mutations: as shown in prior studies[92–95] and our analysis (Fig. 5c), pathogenic mutations are more frequent in buried residues, where they have stronger destabilizing effects. Interestingly, it has been observed that AR mutations are particularly enriched in buried regions compared to AD and gnomAD variants[79]. These findings highlighted the utility of SPURS with respect to disease mutations in understanding molecular mechanisms, implying that while stability loss is a major contributor to pathogenicity, a modest $\Delta\Delta G$ effect does not necessarily indicate benignity, as certain pathogenic mutations may act through alternative mechanisms.

Finally, we analyzed stability effects in cancer-associated mutations. Genes that harbor cancer-driving mutations are broadly categorized into oncogenes, which promote cell proliferation, and tumor suppressor genes (TSGs), which inhibit uncontrolled cell growth. Given that tumorigenesis is often driven by gain-of-function mutations in oncogenes and loss-of-function mutations in TSGs[96,97], we leveraged SPURS's $\Delta\Delta G$ predictions to examine the molecular mechanisms of cancer-associated mutations. We obtained 5,225,814 somatic missense mutations observed across various cancer types from the COSMIC Cancer Mutation Census (CMC) database[98,99] (Methods). Within each gene, we compared SPURS's predicted $\Delta\Delta G$ for cancer mutations cataloged in COSMIC with that for all other possible missense mutations in the same gene (Fig.5g), following prior work[97]. A gene with a positive $\Delta\Delta G$ difference indicates that there has been selection for structurally damaging mutations in that gene (right side of Fig. 5g). Notably, this category was enriched for well-known TSGs, including *TP53*, *PTEN*, and *VHL*, suggesting that mutations in these genes likely drive tumorigenesis through stability loss. Conversely, genes with negative $\Delta\Delta G$ difference (left side of Fig. 5g) were enriched for known oncogenes, such as *TERT*, *ACKR3*, *PIK3CA*, and *BCL2*. Several genes in this category, while not explicitly annotated in COSMIC, have literature support for tumorigenic roles, including *DSPP*[100] and *CLK2*[101]. These results suggested that oncogenic mutations tend to avoid destabilization, likely favoring gain-of-function effects or disrupting intermolecular interactions rather than affecting structure stability. Overall, our analysis recapitulated previous findings[96,97], highlighting that TSGs mutations often lead to destabilization and loss of function, while oncogene mutations tend to exhibit selection for gain-of-function effects, with modest perturbation on stability.

Taken together, these findings illustrate SPURS's capacity to discern the nuanced role of stability and structural context in variant pathogenicity, offering insights into the molecular mechanisms underlying human diseases.

Discussion

We presented SPURS, a deep learning framework for protein stability prediction. One notable advantage of SPURS is its strong generalizability across proteins, stability measures ($\Delta\Delta G$ or ΔT_m), and datasets from different studies. This generalizability stems from two key design choices. First, SPURS is trained on Megascale, a high-coverage dataset encompassing all single and selected double mutants across hundreds of diverse proteins. Equally important is the algorithmic design in SPURS's neural network architecture to fully harness the comprehensive stability measurements in Megascale. SPURS effectively integrates pre-trained sequence- and structure-based protein generative models (ESM2 and ProteinMPNN) through a neural network rewiring strategy, enabling them to be fine-tuned jointly for stability prediction in a data-efficient and scalable manner.

Our approach was motivated by previous findings that pre-trained protein generative models, when used in an unsupervised setting, already correlate well with experimentally measured $\Delta\Delta G$[28–30,33]. We thus reasoned that adapting these pre-trained models using stability-specific fine-tuning would lead to stronger stability models. SPURS's core innovation lies in the explicit integration of ESM2 and ProteinMPNN using a lightweight neural rewiring strategy. It integrates protein representations obtained from two different data modalities, fusing the structure embeddings that encode the geometric features important to protein stability with sequence embeddings that capture the evolutionary constraints in protein sequences. In addition, the resulting architecture is both expressive and parameter-efficient for fine-tuning while avoiding overfitting. While multimodal fusion has been well explored in fields such as vision-language modeling[102], and has recently inspired inverse folding studies[42,103,104], SPURS, to our knowledge, is the first to successfully integrate multi-modal protein generative models for stability prediction.

This study also addresses several limitations in prior stability prediction evaluations. First, in contrast to many previous studies that predominantly assessed models on random or in-distribution test splits, we systematically benchmarked SPURS on over ten independent datasets representing diverse proteins and various mutant coverage, where SPURS consistently outperformed state-of-the-art methods, highlighting its superior accuracy and generalizability. Furthermore, while most existing methods focus on single-mutation variants[105], we specifically evaluated SPURS's ability to predict stability effects of higher-order variants, which suggested that SPURS effectively models non-additive mutational effects, outperforming additive baselines and models explicitly trained to capture epistasis. Importantly, we also addressed a common pitfall in model evaluation: the overreliance on correlation-based metrics, which are biased toward destabilizing mutations due to their overrepresentation[50]. Instead, we reported classification-based performance in identifying stabilizing mutations–critical for protein engineering and design–where SPURS demonstrated higher precision and recall than leading method such as ThermoMPNN.

Another practical advantage of SPURS is its computational efficiency. By leveraging representation-sharing, it predicts $\Delta\Delta G$ for all single mutations of a protein in only one forward pass. For high-order mutations, only a lightweight epistasis decoder is used, incurring minimal additional cost. This enables proteome-scale stability analysis: for instance, SPURS can perform site-saturation mutagenesis for the human proteome (19,652 proteins) in just 30 minutes on a single GPU.

Beyond stability prediction, we demonstrated the versatility of SPURS in various analyses in structural biology, protein engineering, and functional genomics. We showcased broad applications in which SPURS's $\Delta\Delta G$ predictions were used to identify functional residues in proteins, enhance protein fitness prediction, and investigate the contribution of stability change to pathogenicity in human genetic diseases. These applications demonstrate that SPURS's superior accuracy, generalizability, and computational efficiency can serve as foundational capabilities to support diverse tasks in protein informatics.

Looking forward, we envision SPURS as a generalizable pre-trained model to predict stability changes for unseen proteins and mutations. With its state-of-the-art prediction accuracy, SPURS is a robust alternative to computationally expensive biophysical models for protein stability analysis. Since SPURS is trained on $\Delta\Delta G$ data, its predictions for other stability measures, such as melting temperature (ΔT_m), capture relative rankings rather than absolute values. A promising future direction is to exploit SPURS 's transferability to predict absolute magnitudes of other thermodynamic stability metrics, including ΔT_m or ΔG, through dataset-specific fine-tuning. SPURS's stability change predictions can also be combined with existing general variant effect predictors [31,54,106–108] and competitive models [109–111] in the Critical Assessment of Genome Interpretation (CAGI) [112] challenges to improve variant interpretation. SPURS also opens up exciting directions for protein engineering, either as a surrogate model for directed evolution or a reward model to guide generative AI models for designing stability-enhanced proteins. These broad applications establish SPURS as a versatile tool to enable faster and scalable analyses for characterizing protein stability and accelerating protein engineering for important applications in therapeutic design and synthetic biology.

Methods

Representations of input sequence and structure

SPURS takes as input a protein's wild-type sequence $\mathbf{x} = (x_1, \ldots, x_L)$, where L is the sequence length, $x_i \in \mathcal{A}$ denotes the amino acid at position i from the set $\mathcal{A}$ of 20 canonical amino acids, and predicts thermostability change ($\Delta\Delta G$) for all possible single-mutation variants and specified higher-order variants (Fig. 1). When available, SPURS also incorporates the wild-type protein's 3D structure. If no experimentally determined structure is accessible, SPURS uses AlphaFold2[5] to predict the structure. In our experiments, experimental structures were used when the original benchmark datasets (see 'Datasets') provided a Protein Data Bank (PDB) ID for the protein; otherwise, AlphaFold-predicted structures were used, following the practice of previous studies on stability prediction[29,38]. The structure source for each benchmark dataset is detailed in Supplementary Table 6.

SPURS integrates ProteinMPNN[26] as a structure encoder and ESM2[24] as both a sequence encoder and mutation effect predictor. ProteinMPNN is a message-passing neural network (MPNN)[113,114], a type of graph neural network, which learns representations from a 3D protein structure. Structure information is described as atomic coordinates $\mathcal{S} = \{\boldsymbol{c}_i \in \mathbb{R}^{N_b \times 3}\}_{i=1}^{L}$, where $\boldsymbol{c}_i$ contains the coordinates of N_b backbone atoms (e.g., C, C_α, O, and N atoms) for residue i. This structure is abstracted into a graph with atoms as nodes and edges formed by connecting each atom to its 48 nearest neighbors. This structure graph is passed through three encoder and three decoder layers in the MPNN to yield per-residue embeddings in $\mathbb{R}^{L \times 128}$. To improve representation learning, we replaced the autoregressive decoding in the original ProteinMPNN model with a masked decoding scheme (described below). We concatenated MPNN's output embedding with its internal residue embeddings ($\mathbb{R}^{L \times 128}$) learned based on the amino acid identity, resulting in combined embeddings $\boldsymbol{z}_m \in \mathbb{R}^{L \times 256}$, which were then up-sized by a linear layer to $\boldsymbol{z}_s \in \mathbb{R}^{L \times 1280}$, referred to as structure features. In parallel, ESM2, a 33-layer Transformer[115], encodes the protein sequence as a per-residue embedding $\boldsymbol{z}_e \in \mathbb{R}^{L \times 1280}$. Since ESM2 is pre-trained on massive natural sequence data, the output embeddings $\boldsymbol{z}_e$ capture evolutionary patterns of protein language, referred to as evolutionary features.

Model rewiring to learn structure-enhanced evolutionary features

To integrate the structure features $\boldsymbol{z}_s \in \mathbb{R}^{L \times 1280}$ captured by ProteinMPNN into the evolutionary features $\boldsymbol{z}_e \in \mathbb{R}^{L \times 1280}$ learned by ESM2, SPURS introduces a parameter-efficient rewiring mechanism based on Adapter layers[43], which has proven effective in fine-tuning large language models and for protein sequence design[42,116]. Injecting structure-derived context into the sequence-based representation, the Adapter creates structure-enhanced evolutionary features $\boldsymbol{z}_a \in \mathbb{R}^{L \times 1280}$ by cross-attention followed by residual learning and nonlinear transformation:

$$\boldsymbol{z}_a = \boldsymbol{W}_2 \cdot \text{GELU}(\boldsymbol{W}_1 \cdot (\text{MultiHead}(\boldsymbol{z}_e, \boldsymbol{z}_s, \boldsymbol{z}_s) + \boldsymbol{z}_e) + \boldsymbol{b}_1) + \boldsymbol{b}_2, \qquad (1)$$

where $\text{MultiHead}(Q, K, V)$ is the multi-head attention layer[115], with query Q, key K, and value V matrices. Here, we used $\boldsymbol{z}_e$ as the query and $\boldsymbol{z}_s$ as both key and value, allowing evolutionary features to attend to and create interactions with structural contexts. The attention output is added back to $\boldsymbol{z}_e$ through a residual connection[117], followed by a two-layer MLP parameterized by $\boldsymbol{W}_{\{1,2\}}$ and $\boldsymbol{b}_{\{1,2\}}$, with a GELU activation function[118], to produce the structure-enhanced evolutionary features $\boldsymbol{z}_a$. By learning to extract and integrate features from both structural and evolutionary contexts, SPURS is expected to provide more informed stability prediction with the enhanced feature $\boldsymbol{z}_a$. The Adapter is inserted after the 31st layer (out of 33 layers) of

ESM2, with the position selected via hyperparameter search on the validation set. After the Adapter, z_a is passed through the final layers of ESM2 and projected from $\mathbb{R}^{L \times 1280}$ to $\mathbb{R}^{L \times 128}$ via a linear layer. Finally, we concatenate this projected output with the earlier ProteinMPNN embeddings $z_m \in \mathbb{R}^{L \times 256}$ to obtain the final protein embedding $z_o \in \mathbb{R}^{L \times 384}$, reinforcing the structure prior while preserving the evolutionary context.

Building on prior work showing that Adapter-only fine-tuning can achieve comparable performance to fine-tuning the full Transformer model[42,43], we froze the ESM2 parameters (650 million parameters) and optimized only the Adapter and ProteinMPNN parameters (9.9 million parameters). This strategy (Fig. 1) reduced the number of trainable parameters by 98.5% compared to updating the full SPURS model, without compromising prediction accuracy.

Efficient stability prediction module

To predict the stability changes, the embedding z_o is passed to a multi-layer perceptron (MLP) $g : \mathbb{R}^{384} \to \mathbb{R}^{20}$, with each output dimension corresponds to one of the 20 amino acids (AAs). This MLP, shared across all L positions in the sequence, projects $z_o \in \mathbb{R}^{L \times 384}$ to a matrix $\phi = g(z_o) \in \mathbb{R}^{L \times 20}$. The element of this $L \times 20$ matrix ϕ is indexed by the sequence position and AA type, in which $\phi(i, a)$ represents a trainable weight that approximates the thermostability (ΔG) when the amino acid at residue i is of type a.

This matrix ϕ can be used to derive the change in ΔG (i.e., $\Delta\Delta G$) for a single mutation. Denote x^{WT} and x^{MT} as the wild-type sequence and its single-mutation variant resulting from the substitution $x_i^{\mathrm{WT}} \to x_i^{\mathrm{MT}}$ at position i. The stability change of x^{MT} with respect to x^{WT} is defined as

$$\Delta\Delta G(x^{\mathrm{MT}}|x^{\mathrm{WT}}) = \Delta G(x_i = x_i^{\mathrm{MT}}|x^{\mathrm{WT}}) - \Delta G(x_i = x_i^{\mathrm{WT}}|x^{\mathrm{WT}}). \tag{2}$$

In analogy, SPURS (denoted as f_θ parameterized by θ) predicts the $\Delta\Delta G$ for the variant x^{MT} with a substitution at residue i, conditioned on the protein's wild-type sequence x^{WT} and structure $\mathcal{S}^{\mathrm{WT}}$, as following:

$$f_\theta(x^{\mathrm{MT}}|x^{\mathrm{WT}}, \mathcal{S}^{\mathrm{WT}}; i) = \phi(i, x_i^{\mathrm{MT}}) - \phi(i, x_i^{\mathrm{WT}}). \tag{3}$$

This formulation enables efficient and scalable $\Delta\Delta G$ prediction: the matrix ϕ only needs to be computed once in a single forward pass of the neural network, and then can be reused efficiently to derive the $\Delta\Delta G$ for all single mutations using Eq. 3. In contrast, many existing methods use mutant sequences as input, which requires $\mathcal{O}(L \times 20)$ forward passes to predict $\Delta\Delta G$ for all $L \times 20$ single-mutation variants. By conditioning on the wild-type sequence and structure, SPURS predicts all single-mutation variants altogether in $\mathcal{O}(1)$ pass, significantly improving prediction efficiency. This approach, also adopted in recent studies[36,51], is well-suited for large-scale protein stability analysis.

SPURS was trained using a mean squared error (MSE) loss to minimize the difference between predicted and experimentally measured $\Delta\Delta G$ values. Each training data batch includes all mutants derived from a single wild-type sequence. Training was performed on an NVIDIA A40 GPU for a maximum of 200 epochs using the AdamW optimizer[119] with a learning rate of 0.0001. A plateau scheduler was used for adaptive learning rate adjustment, and early stopping was employed to prevent overfitting by terminating training once the validation performance was not improved for 30 epochs. Hyperparameters such as batch size, learning rate, and optimizer settings were selected using the Megascale validation set.

Extension to higher-order mutations

The prediction scheme described above for single mutations can be extended to higher-order variants. Given a mutant sequence $\boldsymbol{x}^{\mathrm{MT}}$ of length L that differ from the wild-type sequence $\boldsymbol{x}^{\mathrm{WT}}$ at multiple positions, we define the set of mutated positions as $\mathcal{M} = \{i | x_i^{\mathrm{MT}} \neq x_i^{\mathrm{WT}}; 1 \leq i \leq L\}$. The stability change induced by multiple mutations is often not simply the additive effects of individual point mutations due to epistatic interactions between residues. SPURS thus predicts the $\Delta\Delta G$ for $\boldsymbol{x}^{\mathrm{MT}}$ as

$$f_\theta(\boldsymbol{x}^{\mathrm{MT}} | \boldsymbol{x}^{\mathrm{WT}}, \mathcal{S}^{\mathrm{WT}}; \mathcal{M}) = \underbrace{\sum_{i \in \mathcal{M}} \left[\boldsymbol{\phi}(i, x_i^{\mathrm{MT}}) - \boldsymbol{\phi}(i, x_i^{\mathrm{WT}}) \right]}_{\text{individual effects}} + \underbrace{\epsilon(\boldsymbol{x}^{\mathrm{MT}}, \mathcal{M})}_{\text{epistatic effects}}, \tag{4}$$

where the first term aggregates individual mutation effects derived from previously computed matrix ϕ, and the epistatic effect ϵ among mutated residues is added to predict the overall $\Delta\Delta G$. The epistatic term ϵ is predicted by a dedicated MLP: $\epsilon(\boldsymbol{x}^{\mathrm{MT}}, \mathcal{M}) = g_\epsilon(\boldsymbol{z}_\mu^{\mathcal{M}})$, where g_ϵ is a four-layer MLP network with hidden dimensions 768, and $\boldsymbol{z}_\mu^{\mathcal{M}}$ is a latent mutation representation that encodes features of all mutations in $\mathcal{M}$. We factorized the representation $\boldsymbol{z}_\mu^{\mathcal{M}}$ into the representations of its compositional point mutations: $\boldsymbol{z}_\mu^{\mathcal{M}} = \sum_{i \in \mathcal{M}} \boldsymbol{z}_\mu^{(i)}$. The representation of a point mutation $\boldsymbol{z}_\mu^{(i)}$ is decomposed as the concatenation of a context-dependent feature and a context-independent feature: $\boldsymbol{z}_\mu^{(i)} = \left[\boldsymbol{z}_o^{(i)} \| \boldsymbol{e}_{\mathrm{AA}}(x_i^{\mathrm{MT}}) \right] \in \mathbb{R}^{512}$, where $\|$ is the vector concatenation, $\boldsymbol{z}_o^{(i)} \in \mathbb{R}^{384}$ is a context-dependent feature extracted from the i-th row of the aforementioned per-residue embedding matrix $\boldsymbol{z}_o \in \mathbb{R}^{L \times 384}$, whereas $\boldsymbol{e}_{\mathrm{AA}}(a) : \mathcal{A} \to \mathbb{R}^{128}$ is an embedding layer that maps an amino acid $a \in \mathcal{A}$ to a context-independent feature in $\mathbb{R}^{128}$. Intuitively, $\boldsymbol{z}_\mu^{(i)}$ captures the contextualized features of position i in the wild-type sequence, and $\boldsymbol{e}_{\mathrm{AA}}(x_i^{\mathrm{MT}})$ informs the mutated amino acid type.

The formulation in Eq. 4 allows efficient and scalable $\Delta\Delta G$ prediction for high-order mutations. Similar to the prediction of single-mutation variants, SPURS only requires one forward pass of the rewired ESM and ProteinMPNN networks to compute the per-residue embeddings $\boldsymbol{z}_o$ and matrix ϕ, which can be reused to infer $\Delta\Delta G$ for all possible single or higher-order variants. For each specific combination of mutations, SPURS only needs to run one additional forward pass on g_ϵ, adding only minimal computational overhead (less than 0.1% of the total parameters of ESM2 and ProteinMPNN).

To train this extended architecture of SPURS, we randomly initialized the parameters of g_ε and retained the weights of all other layers optimized from the training on Megascale single-mutation data. We then fine-tuned the entire model using 122,278 double-mutation variants from Megascale training set. Double-mutation variants from the Megascale validation set were used for hyperparameter tuning, and those in the test split were used to evaluate SPURS 's predictive performance on higher-order mutations (Fig. 2f).

Improved ProteinMPNN decoding for structural feature learning

ProteinMPNN was originally designed as an inverse folding model to generate sequences compatible with a given backbone structure. It uses an autoregressive (sequential) decoding scheme to generate each amino acid one at a time, conditioning on the input structure and already decoded residues: $p(x_i | \boldsymbol{x}_{<i}; \mathcal{S})$ where $\boldsymbol{x}_{<i} = x_1 \ldots x_{i-1}$. While this design aligns with ProteinMPNN's initial purpose, it inherently limits its ability to fully learn structural features for stability prediction in our work, as the model cannot access information from the entire sequence during decoding.

To overcome this limitation, we adopted a one-shot decoding strategy, allowing each residue in the sequence to access information from all other positions simultaneously: $p(x_i | \boldsymbol{x}_{-i}; \mathcal{S})$ where $\boldsymbol{x}_{-i}$ denotes the

full sequence excluding residue i, thereby providing richer sequence context and improving structure representation learning. To fully leverage the advantages of this new strategy, we fine-tuned the ProteinMPNN parameters jointly with the Adapter and prediction modules during SPURS's training, rather than keeping them fixed, allowing the model to better adapt to the refined decoding scheme and contribute more informative structure features for stability prediction.

Functional sites identification

For a given wild-type protein sequence, we used SPURS to predict $\Delta\Delta G$ and ESM1v[28] to predict the sequence likelihood change for all possible single-residue substitutions. The ESM-predicted sequence likelihood change, or delta log-likelihood (ΔLL), is defined as the difference in log-probability between a mutant and wild type residue at position i:

$$s_{\text{ESM}}(x_i = x_i^{\text{MT}}|\boldsymbol{x}^{\text{WT}}) = \log p_{\text{ESM}}(x_i = x_i^{\text{MT}}|\boldsymbol{x}^{\text{WT}}) - \log p_{\text{ESM}}(x_i = x_i^{\text{WT}}|\boldsymbol{x}^{\text{WT}}), \tag{5}$$

where $p_{\text{ESM}}(x_i = a|\boldsymbol{x})$ is the ESM-predicted probability of amino acid a occurring at position i, given the wild-type sequence $\boldsymbol{x}$ as context[28]. The score $s_{\text{ESM}}(x_i = x_i^{\text{MT}}|\boldsymbol{x}^{\text{WT}})$ can be interpreted as the relative evolutionary fitness of mutant $\boldsymbol{x}^{\text{MT}}$, which has been shown to be an effective zero-shot predictor of experimentally measured fitness data[28,29].

Inspired by prior studies modeling the relationship between the free energy changes due to mutations in protein folding and binding using a non-linear Boltzmann distribution[56,59–62], we applied a sigmoid function to fit the non-linear relationship between a mutant's stability change and evolutionary fitness. Specifically, we defined a stability change score $s_{\text{stab}}(x_i = x_i^{\text{MT}}|\boldsymbol{x}^{\text{WT}})$ as the negative SPURS-predicted $\Delta\Delta G$ (i.e., $-f_\theta(\cdot)$) and min-max normalized this score across all single-mutation variants, with the minimum set to the 0.1% percentile and the maximum to the 99.9% percentile. In this way, stabilizing mutations are assigned s_{stab} scores close to 1, while destabilizing ones approach 0.

Next, we fit a sigmoid function on the s_{stab} and s_{ESM} scores of all single-mutation variants for each protein:

$$\hat{s}_{\text{stab}}(x_i = x_i^{\text{MT}}|\boldsymbol{x}^{\text{WT}}) = \sigma\left(\frac{s_{\text{ESM}}(x_i = x_i^{\text{MT}}|\boldsymbol{x}^{\text{WT}}) - \mu}{\tau}\right), \tag{6}$$

where $\sigma(z) = 1/(1 + e^{-z})$ is the standard sigmoid function, μ and τ are learnable parameters controlling the sigmoid curve's shape (location and steepness), and $\hat{s}_{\text{stab}}$ is the sigmoid-fit values of s_{stab}. To prioritize fitting the low-stability variants, we weighted a variant by SPURS's $\Delta\Delta G$ prediction, following the Domainome study[40]:

$$w_i^{\text{MT}} = \max(s_{\text{stab}}) - \min(s_{\text{stab}}) - s_{\text{stab}}(x_i = x_i^{\text{MT}}|\boldsymbol{x}^{\text{WT}}) \tag{7}$$

The residue of the fit is defined as:

$$\epsilon(x_i = x_i^{\text{MT}}|\boldsymbol{x}^{\text{WT}}) = s_{\text{stab}}(x_i = x_i^{\text{MT}}|\boldsymbol{x}^{\text{WT}}) - \hat{s}_{\text{stab}}(x_i = x_i^{\text{MT}}|\boldsymbol{x}^{\text{WT}}), \tag{8}$$

which reflects how much the predicted stability deviates from what would be expected based on the predicted fitness alone. The Domainome study showed that these residuals may indicate mutations with larger or smaller effects on fitness than can be accounted for by changes in stability[40], suggesting stronger functional constraints at site i. We thus define a per-site importance score as the average residuals across the 20 AA

mutations at a site, referred to as function score:

$$s_{\text{func}}(i) = \frac{1}{|\mathcal{A}|} \sum_{a \in \mathcal{A}} \epsilon(x_i = a | \boldsymbol{x}^{\text{WT}}). \tag{9}$$

As shown in the Domainome study[40] and confirmed by our results (Fig. 3), a larger $s_{\text{func}}(i)$ value suggests that site i is more likely a functional site.

Enhanced protein fitness prediction with SPURS

To demonstrate that SPURS can enhance supervised prediction of general protein fitness, we used the "Augmented models" developed by Hsu et al.[27], a leading low-N fitness prediction method, as our base model. To predict the quantitative fitness value of a variant, Augmented models represent the input sequence as a concatenation of one-hot encoding of the amino acids in its sequence, resulting in a flattened vector of dimension $L \times |\mathcal{A}|$, where $\mathcal{A}$ is the set of 20 canonical amino acids. This vector is augmented to a $(L \times |\mathcal{A}| + 1)$-dimension feature vector by incorporating a scalar representing the input sequence's evolutionary plausibility (the delta log-likelihood score) predicted by a protein sequence generative model, such as a pLM (e.g., s_{ESM} in Eq. 5) or other sequence likelihood models (e.g., EVmutation[120], Evotuned UniRep[69], DeepSequence[67]). A Ridge regression model is then trained on these augmented features to predict experimental fitness measurements.

We extended this approach by incorporating the $\Delta\Delta G$ value predicted by SPURS as an additional input feature, resulting in a $(L \times |\mathcal{A}| + 2)$-dimensional feature vector. We refer to this enhanced model as the SPURS-augmented model. To benchmark performance, we followed the experimental design of Hsu et al.[27]. For each deep mutational scanning (DMS) dataset, we first set aside 20% randomly sampled variants as the test set. From the remaining variants, we sampled N mutants as the training set, where N was set to 48, 96, 144, 192, 240, or $N = 80\%$ of total sequences in a DMS dataset, following the setup from Hsu et al.[27]. For each value of N, we repeated the sampling and model training 20 times with different random seeds and reported the mean performance across repetitions as the final evaluation metric.

Analysis of stability effects on pathogenicity

We obtained the missense variants and their clinical annotations from the ClinVar database[78], following the processing protocol in Cagiada et al.[86]. In our analysis, we only included variants annotated as 'benign', 'likely benign', 'pathogenic', 'likely pathogenic', or 'variants of uncertain significance' (VUS). In our analysis, variants with 'benign' or 'likely benign' annotations were grouped as benign, and those with 'pathogenic' or 'likely pathogenic' annotations were grouped as pathogenic. We applied SPURS to predict $\Delta\Delta G$ for all possible missense mutations across the human proteome (19,652 proteins), and 696,736 variants from 16,997 proteins were successfully mapped to ClinVar annotations.

AlphaFold2 (AF2)-predicted structures of the mapped human proteins and their associated residue-level predicted Local Distance Difference Test (pLDDT) scores were retrieved from the AlphaFold Protein Structure Database[121]. Residues were categorized as folded if pLDDT > 50. Solvent exposure was estimated using relative solvent-accessible surface area (rSASA), defined as the SASA of a residue divided by its maximum SASA in a Gly-X-Gly tripeptide configuration. rSASA values were computed using the Biotite package[122] with normalization constants from Tien et al.[123]; residues with rSASA > 0.2 were considered exposed.

To jointly model the impact of structure and stability on pathogenicity, we interpolated $\Delta\Delta G$ and rSASA scores after clipping them to the 0.1st–99.9th percentile range to reduce the influence of outliers. These values were then min-max normalized to the [0,1] interval, preserving relative differences while ensuring

scale compatibility across the dataset.

The disease inheritance annotations (autosomal dominant [AD] or autosomal recessive [AR]) for genes were obtained from the OMIM database[91], following the approach of Gerasimavicius et al.[79]. We additionally included 15,820 gnomAD (v4.1) missense variants with allele frequency >0.05 as a reference set of putative benign variants. Cancer-associated mutations were collected from the Cancer Mutation Census dataset[99] (v99, GRCh38) in the COSMIC database[98]. For each gene, a $\Delta\Delta G$ difference score was computed as the mean predicted $\Delta\Delta G$ of observed cancer-associated mutations minus that of all remaining possible missense mutations in that gene. The significance of pairwise comparison was assessed using the Mann-Whitney U test, with Bonferroni correction for multiple testing. The threshold of the corrected P-value was defined as α/N, where $\alpha = 0.05$ is the commonly used significance level, and $N = 18,073$ is the number of genes considered.

Datasets

We used the training, validation, and test splits of the Megascale dataset created by Dieckhaus et al.[38], which ensured no sequences sharing $> 25\%$ identity across splits. For benchmarking, we additionally collected ten independent test sets, including Fireprot (HF)[18,38], Ssym-direct[47], Ssym-inverse[47], S669[9], S783[8], S2648[15], S461[124], S8754[45], S4346[45], S571[45]. Among these, four datasets (Fireprot, Ssym-direct, Ssym-inverse, and S669) were pre-filtered and provided by Dieckhaus et al.[38], while the remaining six datasets were obtained from Xu et al.[45]. Fireprot (HF) is a homology-free subset of the Fireprot dataset, curated to ensure that sequences share less than 25% identity with those in Megascale. We used experimentally solved structures from the PDB database to run SPURS and structure-based baseline methods if the representative structures of the wild-type proteins were provided by the original studies of these test sets; otherwise, AlphaFold2-predicted structures were used.

We first trained SPURS using single-mutation data in Megascale training and validation splits and evaluated it using the Megascale test split and the ten independent test sets (statistics provided in Supplementary Table 6). To prevent data leakage across evaluation sets, any training sequences with >25% sequence identity to sequences in the independent test sets were removed using MMseqs2[125]. To enable predictions for higher-order mutations, double-mutant variants from the Megascale training and validation splits (statistics provided in Supplementary Table 7) were incorporated into training for the extended model with the epistasis module g_ϵ. Double mutants in the Megascale test split were used to assess the performance of this extended model.

Functional site annotations for Domainome sequences were retrieved from the Conserved Domain Database (CDD) by parsing the National Center for Biotechnology Information (NCBI) protein entry page (e.g., `https://www.ncbi.nlm.nih.gov/protein/UNIPROT_ID/`, replacing "UNIPROT_ID" with the corresponding UniProt identifier). For the enzyme in Fig.3 (Alcohol dehydrogenase, Uniprot ID: P00327, PDB ID: 1QLH), functional site annotations were obtained from the Mechanism and Catalytic Site Atlas (M-CSA; `https://www.ebi.ac.uk/thornton-srv/m-csa/`). Experimental fitness measurements and baseline predictions for proteins in Fig.4 were taken from the ProteinGym benchmark[29] (`https://proteingym.org/`).

Data availability

Unless otherwise stated, all data supporting the results of this study can be found in the article, supplementary, and source data files. We used *esm2_t33_650M_UR50D* checkpoint of ESM2 (`https://dl.fbaipublicfiles.com/fair-esm/models/esm2_t33_650M_UR50D.pt`), *v_48_020* checkpoint of ProteinMPNN (`https://github.com/dauparas/ProteinMPNN/blob/main/vanilla_model_weights/v_48_020.pt`), and

esm1v_t33_650M_UR90S_1 checkpoint of ESM1v (`https://dl.fbaipublicfiles.com/fair-esm/model s/esm1v_t33_650M_UR90S_1.pt`). The Megascale dataset was downloaded from `https://zenodo.org /records/7844779`. Megascale split, Fireprot(HF), S669, Ssym-direct, and Ssym-inverse were downloaded from `https://github.com/Kuhlman-Lab/ThermoMPNN`. S783, S2648, S461, S8754, S4346 and S571 were downloaded from `https://github.com/Gonglab-THU/GeoStab`. Domainome data and the performance of baseline models were downloaded from `https://zenodo.org/records/11260616`. Clinvar annotations were collected from `https://ftp.ncbi.nlm.nih.gov/pub/clinvar/tab_delimited/`[86]. Cancer-associated mutations were obtained from the Cancer Mutation Census v99 (GRCh38) dataset, specifically the file `CancerMutationCensus_AllData_Tsv_v99_GRCh38`, available at `https://cancer.sanger.ac .uk/cosmic/download/cancer-mutation-census/v99/alldata-cmc`. Source Data are provided with this paper.

Code availability

SPURS was implemented in Python using the PyTorch (v1.12.0) library. The source code is available at `https://github.com/luo-group/SPURS`.

Acknowledgements

This work is supported in part by the National Institute of General Medical Sciences of the National Institutes of Health under award R35GM150890 (Y.L.). The authors acknowledge the computational resources provided by the Delta GPU Supercomputer at NCSA of UIUC through allocation CIS230097 (Y.L.) from the Advanced Cyberinfrastructure Coordination Ecosystem: Services & Support (ACCESS) program, which is supported by NSF grants #2138259, #2138286, #2138307, #2137603, and #2138296 (Y.L.), and the cloud computational resources provided by Microsoft Azure through the Cloud Hub program at GaTech IDEaS and the Microsoft Accelerate Foundation Models Research (AFMR) program (Y.L.).

Author contributions

Y.L. conceived and supervised the project. Z.L. developed the computational framework and performed the evaluation analyses. Y.L. and Z.L. wrote the manuscript.

Competing interests

The authors declare no competing interests.

References

[1] Mirfath Sultana Mesbahuddin, Aravindhan Ganesan, and Subha Kalyaanamoorthy. Engineering stable carbonic anhydrases for co2 capture: a critical review. *Protein Engineering, Design and Selection*, 34:gzab021, 2021.

[2] Shuke Wu, Radka Snajdrova, Jeffrey C Moore, Kai Baldenius, and Uwe T Bornscheuer. Biocatalysis: enzymatic synthesis for industrial applications. *Angewandte Chemie International Edition*, 60(1):88–119, 2021.

[3] Sisi Shan, Shitong Luo, Ziqing Yang, Junxian Hong, Yufeng Su, Fan Ding, Lili Fu, Chenyu Li, Peng Chen, Jianzhu Ma, et al. Deep learning guided optimization of human antibody against sars-cov-2 variants with broad neutralization. *Proceedings of the National Academy of Sciences*, 119(11):e2122954119, 2022.

[4] Brian Kuhlman and Philip Bradley. Advances in protein structure prediction and design. *Nature reviews molecular cell biology*, 20(11):681–697, 2019.

[5] John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with alphafold. *nature*, 596(7873):583–589, 2021.

[6] Lijun Quan, Qiang Lv, and Yang Zhang. Strum: structure-based prediction of protein stability changes upon single-point mutation. *Bioinformatics*, 32(19):2936–2946, 2016.

[7] Bian Li, Yucheng T Yang, John A Capra, and Mark B Gerstein. Predicting changes in protein thermodynamic stability upon point mutation with deep 3d convolutional neural networks. *PLoS computational biology*, 16(11):e1008291, 2020.

[8] Yuting Chen, Haoyu Lu, Ning Zhang, Zefeng Zhu, Shuqin Wang, and Minghui Li. Premps: Predicting the impact of missense mutations on protein stability. *PLoS computational biology*, 16(12):e1008543, 2020.

[9] Corrado Pancotti, Silvia Benevenuta, Giovanni Birolo, Virginia Alberini, Valeria Repetto, Tiziana Sanavia, Emidio Capriotti, and Piero Fariselli. Predicting protein stability changes upon single-point mutation: a thorough comparison of the available tools on a new dataset. *Briefings in Bioinformatics*, 23(2):bbab555, 2022.

[10] Dmitriy Umerenkov, Fedor Nikolaev, Tatiana I Shashkova, Pavel V Strashnov, Maria Sindeeva, Andrey Shevtsov, Nikita V Ivanisenko, and Olga L Kardymon. Prostata: a framework for protein stability assessment using transformers. *Bioinformatics*, 39(11):btad671, 2023.

[11] Gen Li, Sijie Yao, and Long Fan. Prostage: predicting effects of mutations on protein stability by using protein embeddings and graph convolutional networks. *Journal of Chemical Information and Modeling*, 64(2):340–347, 2024.

[12] S Benevenuta, C Pancotti, P Fariselli, G Birolo, and T Sanavia. An antisymmetric neural network to predict free energy changes in protein variants. *Journal of Physics D: Applied Physics*, 54(24):245403, 2021.

[13] Corrado Pancotti, Silvia Benevenuta, Valeria Repetto, Giovanni Birolo, Emidio Capriotti, Tiziana Sanavia, and Piero Fariselli. A deep-learning sequence-based method to predict protein stability changes upon genetic variations. *Genes*, 12(6):911, 2021.

[14] Ludovica Montanucci, Emidio Capriotti, Yotam Frank, Nir Ben-Tal, and Piero Fariselli. Ddgun: an untrained method for the prediction of protein stability changes upon single and multiple point variations. *BMC bioinformatics*, 20:1–10, 2019.

[15] Yves Dehouck, Aline Grosfils, Benjamin Folch, Dimitri Gilis, Philippe Bogaerts, and Marianne Rooman. Fast and accurate predictions of protein stability changes upon mutations using statistical potentials and neural networks: Popmusic-2.0. *Bioinformatics*, 25(19):2537–2543, 2009.

[16] Joicymara S Xavier, Thanh-Binh Nguyen, Malancha Karmarkar, Stephanie Portelli, Pâmela M Rezende, Joao PL Velloso, David B Ascher, and Douglas EV Pires. Thermomutdb: a thermodynamic database for missense mutations. *Nucleic acids research*, 49(D1):D475–D479, 2021.

[17] Rahul Nikam, A Kulandaisamy, K Harini, Divya Sharma, and M Michael Gromiha. Prothermdb: thermodynamic database for proteins and mutants revisited after 15 years. *Nucleic acids research*, 49(D1):D420–D424, 2021.

[18] Jan Stourac, Juraj Dubrava, Milos Musil, Jana Horackova, Jiri Damborsky, Stanislav Mazurenko, and David Bednar. Fireprotdb: database of manually curated protein stability data. *Nucleic acids research*, 49(D1):D319–D324, 2021.

[19] M Michael Gromiha, Jianghong An, Hidetoshi Kono, Motohisa Oobatake, Hatsuho Uedaira, Ponraj Prabakaran, and Akinori Sarai. Protherm, version 2.0: thermodynamic database for proteins and mutants. *Nucleic acids research*, 28(1):283–285, 2000.

[20] Connie Y Wang, Paul M Chang, Marie L Ary, Benjamin D Allen, Roberto A Chica, Stephen L Mayo, and Barry D Olafson. Protabank: A repository for protein design and engineering data. *Protein Science*, 27(6):1113–1124, 2018.

[21] Kotaro Tsuboyama, Justas Dauparas, Jonathan Chen, Elodie Laine, Yasser Mohseni Behbahani, Jonathan J Weinstein, Niall M Mangan, Sergey Ovchinnikov, and Gabriel J Rocklin. Mega-scale experimental analysis of protein folding stability in biology and design. *Nature*, 620(7973):434–444, 2023.

[22] Alexander Rives, Joshua Meier, Tom Sercu, Siddharth Goyal, Zeming Lin, Jason Liu, Demi Guo, Myle Ott, C Lawrence Zitnick, Jerry Ma, et al. Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. *Proceedings of the National Academy of Sciences*, 118(15):e2016239118, 2021.

[23] Ahmed Elnaggar, Michael Heinzinger, Christian Dallago, Ghalia Rehawi, Yu Wang, Llion Jones, Tom Gibbs, Tamas Feher, Christoph Angerer, Martin Steinegger, et al. Prottrans: Toward understanding the language of life through self-supervised learning. *IEEE transactions on pattern analysis and machine intelligence*, 44(10):7112–7127, 2021.

[24] Zeming Lin, Halil Akin, Roshan Rao, Brian Hie, Zhongkai Zhu, Wenting Lu, Allan dos Santos Costa, Maryam Fazel-Zarandi, Tom Sercu, Sal Candido, et al. Language models of protein sequences at the scale of evolution enable accurate structure prediction. *BioRxiv*, 2022:500902, 2022.

[25] Thomas Hayes, Roshan Rao, Halil Akin, Nicholas J Sofroniew, Deniz Oktay, Zeming Lin, Robert Verkuil, Vincent Q Tran, Jonathan Deaton, Marius Wiggert, et al. Simulating 500 million years of evolution with a language model. *Science*, page eads0018, 2025.

[26] Justas Dauparas, Ivan Anishchenko, Nathaniel Bennett, Hua Bai, Robert J Ragotte, Lukas F Milles, Basile IM Wicky, Alexis Courbet, Rob J de Haas, Neville Bethel, et al. Robust deep learning–based protein sequence design using proteinmpnn. *Science*, 378(6615):49–56, 2022.

[27] Chloe Hsu, Hunter Nisonoff, Clara Fannjiang, and Jennifer Listgarten. Learning protein fitness models from evolutionary and assay-labeled data. *Nature biotechnology*, 40(7):1114–1122, 2022.

[28] Joshua Meier, Roshan Rao, Robert Verkuil, Jason Liu, Tom Sercu, and Alex Rives. Language models enable zero-shot prediction of the effects of mutations on protein function. *Advances in neural information processing systems*, 34:29287–29303, 2021.

[29] Pascal Notin, Aaron W Kollasch, Daniel Ritter, Lood van Niekerk, Steffanie Paul, Hansen Spinner, Nathan Rollins, Ada Shaw, Ruben Weitzman, Jonathan Frazer, et al. Proteingym: Large-scale benchmarks for protein design and fitness prediction. *bioRxiv*, 2023.

[30] Shawn Reeves and Subha Kalyaanamoorthy. Zero-shot transfer of protein sequence likelihood models to thermostability prediction. *Nature Machine Intelligence*, 6(9):1063–1076, 2024.

[31] Jonathan Frazer, Pascal Notin, Mafalda Dias, Aidan Gomez, Joseph K Min, Kelly Brock, Yarin Gal, and Debora S Marks. Disease variant prediction with deep generative models of evolutionary data. *Nature*, 599(7883):91–95, 2021.

[32] Brian L Hie, Varun R Shanker, Duo Xu, Theodora UJ Bruun, Payton A Weidenbacher, Shaogeng Tang, Wesley Wu, John E Pak, and Peter S Kim. Efficient evolution of human antibodies from general protein language models. *Nature Biotechnology*, 42(2):275–283, 2024.

[33] Matteo Cagiada, Sergey Ovchinnikov, and Kresten Lindorff-Larsen. Predicting absolute protein folding stability using generative models. *Protein Science*, 34(1):e5233, 2025.

[34] Lasse M Blaabjerg, Maher M Kassem, Lydia L Good, Nicolas Jonsson, Matteo Cagiada, Kristoffer E Johansson, Wouter Boomsma, Amelie Stein, and Kresten Lindorff-Larsen. Rapid protein stability prediction using deep learning representations. *Elife*, 12:e82593, 2023.

[35] Simon KS Chu, Kush Narang, and Justin B Siegel. Protein stability prediction by fine-tuning a protein language model on a mega-scale dataset. *PLOS Computational Biology*, 20(7):e1012248, 2024.

[36] Junming Zhao, Chao Zhang, and Yunan Luo. Contrastive fitness learning: Reprogramming protein language models for low-n learning of protein fitness landscape. In *International Conference on Research in Computational Molecular Biology*, pages 470–474. Springer, 2024.

[37] Chloe Hsu, Robert Verkuil, Jason Liu, Zeming Lin, Brian Hie, Tom Sercu, Adam Lerer, and Alexander Rives. Learning inverse folding from millions of predicted structures. In *International conference on machine learning*, pages 8946–8970. PMLR, 2022.

[38] Henry Dieckhaus, Michael Brocidiacono, Nicholas Z Randolph, and Brian Kuhlman. Transfer learning to leverage larger datasets for improved prediction of protein stability changes. *Proceedings of the National Academy of Sciences*, 121(6):e2314853121, 2024.

[39] Talal Widatalla, Rafael Rafailov, and Brian Hie. Aligning protein generative models with experimental fitness via direct preference optimization. *bioRxiv*, pages 2024–05, 2024.

[40] Antoni Beltran, Xiang'er Jiang, Yue Shen, and Ben Lehner. Site-saturation mutagenesis of 500 human protein domains. *Nature*, pages 1–10, 2025.

[41] UniProt. Uniprot: the universal protein knowledgebase in 2021. *Nucleic acids research*, 49(D1):D480–D489, 2021.

[42] Zaixiang Zheng, Yifan Deng, Dongyu Xue, Yi Zhou, Fei Ye, and Quanquan Gu. Structure-informed language models are protein designers. In *International conference on machine learning*, pages 42317–42338. PMLR, 2023.

[43] Neil Houlsby, Andrei Giurgiu, Stanislaw Jastrzebski, Bruna Morrone, Quentin De Laroussilhe, Andrea Gesmundo, Mona Attariyan, and Sylvain Gelly. Parameter-efficient transfer learning for nlp. In *International conference on machine learning*, pages 2790–2799. PMLR, 2019.

[44] Tiziana Sanavia, Giovanni Birolo, Ludovica Montanucci, Paola Turina, Emidio Capriotti, and Piero Fariselli. Limitations and challenges in protein stability prediction upon genome variations: towards future applications in precision medicine. *Computational and structural biotechnology journal*, 18:1968–1979, 2020.

[45] Yunxin Xu, Di Liu, and Haipeng Gong. Improving the prediction of protein stability changes upon mutations by geometric learning and a pre-training strategy. *Nature Computational Science*, pages 1–11, 2024.

[46] Marina A Pak, Nikita V Dovidchenko, Satyarth Mishra Sharma, and Dmitry N Ivankov. New mega dataset combined with deep neural network makes a progress in predicting impact of mutation on protein stability. *BioRxiv*, pages 2022–12, 2023.

[47] Fabrizio Pucci, Katrien V Bernaerts, Jean Marc Kwasigroch, and Marianne Rooman. Quantification of biases in predictions of protein stability changes upon mutations. *Bioinformatics*, 34(21):3659–3665, 2018.

[48] Joost Schymkowitz, Jesper Borg, Francois Stricher, Robby Nys, Frederic Rousseau, and Luis Serrano. The foldx web server: an online force field. *Nucleic acids research*, 33(suppl_2):W382–W388, 2005.

[49] Rebecca F Alford, Andrew Leaver-Fay, Jeliazko R Jeliazkov, Matthew J O'Meara, Frank P DiMaio, Hahnbeom Park, Maxim V Shapovalov, P Douglas Renfrew, Vikram K Mulligan, Kalli Kappel, et al. The rosetta all-atom energy function for macromolecular modeling and design. *Journal of chemical theory and computation*, 13(6):3031–3048, 2017.

[50] Daniel J Diaz, Chengyue Gong, Jeffrey Ouyang-Zhang, James M Loy, Jordan Wells, David Yang, Andrew D Ellington, Alexandros G Dimakis, and Adam R Klivans. Stability oracle: a structure-based graph-transformer framework for identifying stabilizing mutations. *Nature Communications*, 15(1):6170, 2024.

[51] Jeffrey Ouyang-Zhang, Daniel Diaz, Adam Klivans, and Philipp Krähenbühl. Predicting a protein's stability under a million mutations. *Advances in Neural Information Processing Systems*, 36, 2024.

[52] Silvia Benevenuta, Giovanni Birolo, Tiziana Sanavia, Emidio Capriotti, and Piero Fariselli. Challenges in predicting stabilizing variations: An exploration. *Frontiers in Molecular Biosciences*, 9:1075570, 2023.

[53] Emidio Capriotti, Piero Fariselli, Ivan Rossi, and Rita Casadio. A three-state prediction of single point mutations on protein stability changes. *BMC bioinformatics*, 9:1–9, 2008.

[54] Jun Cheng, Guido Novati, Joshua Pan, Clare Bycroft, Akvilė Žemgulytė, Taylor Applebaum, Alexander Pritzel, Lai Hong Wong, Michal Zielinski, Tobias Sargeant, et al. Accurate proteome-wide missense variant effect prediction with alphamissense. *Science*, 381(6664):eadg7492, 2023.

[55] Nobuhiko Tokuriki and Dan S Tawfik. Stability effects of mutations and protein evolvability. *Current opinion in structural biology*, 19(5):596–604, 2009.

[56] Andre J Faure, Júlia Domingo, Jörn M Schmiedel, Cristina Hidalgo-Carcedo, Guillaume Diss, and Ben Lehner. Mapping the energetic and allosteric landscapes of protein binding domains. *Nature*, 604(7904):175–183, 2022.

[57] Magnus Haraldson Høie, Matteo Cagiada, Anders Haagen Beck Frederiksen, Amelie Stein, and Kresten Lindorff-Larsen. Predicting and interpreting large-scale mutagenesis data using analyses of protein stability and conservation. *Cell reports*, 38(2), 2022.

[58] Xianghua Li and Ben Lehner. Biophysical ambiguities prevent accurate genetic prediction. *Nature communications*, 11(1):4923, 2020.

[59] Chenchun Weng, Andre J Faure, Albert Escobedo, and Ben Lehner. The energetic and allosteric landscape for kras inhibition. *Nature*, 626(7999):643–652, 2024.

[60] Jakub Otwinowski. Biophysical inference of epistasis and the effects of mutations on protein stability and function. *Molecular biology and evolution*, 35(10):2345–2354, 2018.

[61] Andre J Faure, Aina Martí-Aranda, Cristina Hidalgo-Carcedo, Antoni Beltran, Jörn M Schmiedel, and Ben Lehner. The genetic architecture of protein stability. *Nature*, pages 1–9, 2024.

[62] Andre J Faure and Ben Lehner. Mochi: neural networks to fit interpretable models and quantify energies, energetic couplings, epistasis and allostery from deep mutational scanning data. *bioRxiv*, pages 2024–01, 2024.

[63] Jiyao Wang, Farideh Chitsaz, Myra K Derbyshire, Noreen R Gonzales, Marc Gwadz, Shennan Lu, Gabriele H Marchler, James S Song, Narmada Thanki, Roxanne A Yamashita, et al. The conserved domain database in 2023. *Nucleic Acids Research*, 51(D1):D384–D388, 2023.

[64] Matteo Cagiada, Sandro Bottaro, Søren Lindemose, Signe M Schenstrøm, Amelie Stein, Rasmus Hartmann-Petersen, and Kresten Lindorff-Larsen. Discovering functionally important sites in proteins. *Nature communications*, 14(1):4175, 2023.

[65] PC Agu, CA Afiukwa, OU Orji, EM Ezeh, IH Ofoke, CO Ogbu, EI Ugwuja, and PM Aja. Molecular docking as a tool for the discovery of molecular targets of nutraceuticals in diseases management. *Scientific Reports*, 13(1):13398, 2023.

[66] Surojit Biswas, Grigory Khimulya, Ethan C Alley, Kevin M Esvelt, and George M Church. Low-n protein engineering with data-efficient deep learning. *Nature methods*, 18(4):389–396, 2021.

[67] Adam J Riesselman, John B Ingraham, and Debora S Marks. Deep generative models of genetic variation capture the effects of mutations. *Nature methods*, 15(10):816–822, 2018.

[68] Thomas A Hopf, John B Ingraham, Frank J Poelwijk, Charlotta PI Schärfe, Michael Springer, Chris Sander, and Debora S Marks. Mutation effects predicted from sequence co-variation. *Nature biotechnology*, 35(2):128–135, 2017.

[69] Ethan C Alley, Grigory Khimulya, Surojit Biswas, Mohammed AlQuraishi, and George M Church. Unified rational protein engineering with sequence-based deep representation learning. *Nature methods*, 16(12):1315–1322, 2019.

[70] Konrad J Karczewski, Laurent C Francioli, Grace Tiao, Beryl B Cummings, Jessica Alföldi, Qingbo Wang, Ryan L Collins, Kristen M Laricchia, Andrea Ganna, Daniel P Birnbaum, et al. The mutational constraint spectrum quantified from variation in 141,456 humans. *Nature*, 581(7809):434–443, 2020.

[71] Peter D Stenson, Matthew Mort, Edward V Ball, Katy Evans, Matthew Hayden, Sally Heywood, Michelle Hussain, Andrew D Phillips, and David N Cooper. The human gene mutation database: towards a comprehensive repository of inherited mutation data for medical research, genetic diagnosis and next-generation sequencing studies. *Human genetics*, 136:665–677, 2017.

[72] Preeti Pandey, Sanjeev Ghimire, Bohua Wu, and Emil Alexov. On the linkage of thermodynamics and pathogenicity. *Current opinion in structural biology*, 80:102572, 2023.

[73] Zhen Wang and John Moult. Snps, protein structure, and disease. *Human mutation*, 17(4):263–270, 2001.

[74] Peng Yue, Zhaolong Li, and John Moult. Loss of protein structure stability as a major causative factor in monogenic disease. *Journal of molecular biology*, 353(2):459–473, 2005.

[75] Rita Casadio, Marco Vassura, Shalinee Tiwari, Piero Fariselli, and Pier Luigi Martelli. Correlating disease-related mutations to their effect on protein stability: A large-scale analysis of the human proteome. *Human mutation*, 32(10):1161–1170, 2011.

[76] Mu Gao, Hongyi Zhou, and Jeffrey Skolnick. Insights into disease-associated mutations in the human proteome through protein structural analysis. *Structure*, 23(7):1362–1369, 2015.

[77] Amelie Stein, Douglas M Fowler, Rasmus Hartmann-Petersen, and Kresten Lindorff-Larsen. Biophysical and mechanistic models for disease-causing protein variants. *Trends in biochemical sciences*, 44(7):575–588, 2019.

[78] Melissa J Landrum, Jennifer M Lee, George R Riley, Wonhee Jang, Wendy S Rubinstein, Deanna M Church, and Donna R Maglott. Clinvar: public archive of relationships among sequence variation and human phenotype. *Nucleic acids research*, 42(D1):D980–D985, 2014.

[79] Lukas Gerasimavicius, Benjamin J Livesey, and Joseph A Marsh. Loss-of-function, gain-of-function and dominant-negative mutations have profoundly different effects on protein structure. *Nature communications*, 13(1):3895, 2022.

[80] Sanna Gudmundsson, Moriel Singer-Berk, Nicholas A Watts, William Phu, Julia K Goodrich, Matthew Solomonson, Genome Aggregation Database Consortium, Heidi L Rehm, Daniel G MacArthur, and Anne O'Donnell-Luria. Variant interpretation using population databases: Lessons from gnomad. *Human mutation*, 43(8):1012–1030, 2022.

[81] Johanna Katarina Sofie Tiemann, Henrike Zschach, Kresten Lindorff-Larsen, and Amelie Stein. Interpreting the molecular mechanisms of disease variants in human transmembrane proteins. *Biophysical Journal*, 122(11):2176–2191, 2023.

[82] Shehab S Ahmed, Zaara T Rifat, Ruchi Lohia, Arthur J Campbell, A Keith Dunker, M Sohel Rahman, and Sumaiya Iqbal. Characterization of intrinsically disordered regions in proteins informed by human genetic diversity. *PLoS Computational Biology*, 18(3):e1009911, 2022.

[83] Kiersten M Ruff and Rohit V Pappu. Alphafold and implications for intrinsically disordered proteins. *Journal of molecular biology*, 433(20):167208, 2021.

[84] Giulio Tesei, Anna Ida Trolle, Nicolas Jonsson, Johannes Betz, Frederik E Knudsen, Francesco Pesce, Kristoffer E Johansson, and Kresten Lindorff-Larsen. Conformational ensembles of the human intrinsically disordered proteome. *Nature*, 626(8000):897–904, 2024.

[85] Castrense Savojardo, Matteo Manfredi, Pier Luigi Martelli, and Rita Casadio. Solvent accessibility of residues undergoing pathogenic variations in humans: from protein structures to protein sequences. *Frontiers in molecular biosciences*, 7:626363, 2021.

[86] Matteo Cagiada, Nicolas Jonsson, and Kresten Lindorff-Larsen. Decoding molecular mechanisms for loss of function variants in the human proteome. *bioRxiv*, pages 2024–05, 2024.

[87] Jing Zhang, Lisa Kinch, Panagiotis Katsonis, Olivier Lichtarge, Milind Jagota, Yun S Song, Yuanfei Sun, Yang Shen, Nurdan Kuru, Onur Dereli, et al. Assessing predictions on fitness effects of missense variants in hmbs in cagi6. *Human genetics*, pages 1–17, 2024.

[88] Gonzalo Benegas, Carlos Albors, Alan J Aw, Chengzhong Ye, and Yun S Song. A dna language model based on multispecies alignment predicts the effects of genome-wide variants. *Nature Biotechnology*, pages 1–6, 2025.

[89] Matteo Cagiada, Kristoffer E Johansson, Audrone Valanciute, Sofie V Nielsen, Rasmus Hartmann-Petersen, Jun J Yang, Douglas M Fowler, Amelie Stein, and Kresten Lindorff-Larsen. Understanding the origins of loss of protein function by analyzing the effects of thousands of variants on activity and abundance. *Molecular Biology and Evolution*, 38(8):3235–3246, 2021.

[90] Reiner A Veitia, Sandrine Caburet, and James A Birchler. Mechanisms of mendelian dominance. *Clinical Genetics*, 93(3):419–428, 2018.

[91] McKusick-Nathans Institute of Genetic Medicine, Johns Hopkins University. Online Mendelian Inheritance in Man, OMIM®, 2025. Available at `https://omim.org/`.

[92] Nobuhiko Tokuriki, Francois Stricher, Joost Schymkowitz, Luis Serrano, and Dan S Tawfik. The stability effects of protein mutations appear to be universally distributed. *Journal of molecular biology*, 369(5):1318–1332, 2007.

[93] Nidhi Sahni, Song Yi, Mikko Taipale, Juan I Fuxman Bass, Jasmin Coulombe-Huntington, Fan Yang, Jian Peng, Jochen Weile, Georgios I Karras, Yang Wang, et al. Widespread macromolecular interaction perturbations in human genetic disorders. *Cell*, 161(3):647–660, 2015.

[94] Harry C Jubb, Arun P Pandurangan, Meghan A Turner, Bernardo Ochoa-Montaño, Tom L Blundell, and David B Ascher. Mutations at protein-protein interfaces: Small changes over big surfaces have large impacts on human health. *Progress in biophysics and molecular biology*, 128:3–13, 2017.

[95] Benjamin J Livesey and Joseph A Marsh. The properties of human disease mutations at protein interfaces. *PLOS Computational Biology*, 18(2):e1009858, 2022.

[96] Emmanuel N Kontomanolis, Antonios Koutras, Athanasios Syllaios, Dimitrios Schizas, Aikaterini Mastoraki, Nikolaos Garmpis, Michail Diakosavvas, Kyveli Angelou, Georgios Tsatsaris, Athanasios Pagkalos, et al. Role of oncogenes and tumor-suppressor genes in carcinogenesis: a review. *Anticancer research*, 40(11):6009–6015, 2020.

[97] Diego Chillón-Pino, Mihaly Badonyi, Colin A Semple, and Joseph A Marsh. Protein structural context of cancer mutations reveals molecular mechanisms and candidate driver genes. *Cell Reports*, 43(11), 2024.

[98] John G Tate, Sally Bamford, Harry C Jubb, Zbyslaw Sondka, David M Beare, Nidhi Bindal, Harry Boutselakis, Charlotte G Cole, Celestino Creatore, Elisabeth Dawson, et al. Cosmic: the catalogue of somatic mutations in cancer. *Nucleic acids research*, 47(D1):D941–D947, 2019.

[99] Zbyslaw Sondka, Sally Bamford, Charlotte G Cole, Sari A Ward, Ian Dunham, and Simon A Forbes. The cosmic cancer gene census: describing genetic dysfunction across all human cancers. *Nature Reviews Cancer*, 18(11):696–705, 2018.

[100] Ioannis Gkouveris, Nikolaos G Nikitakis, Jaya Aseervatham, and Kalu UE Ogbureke. The tumorigenic role of dspp and its potential regulation of the unfolded protein response and er stress in oral cancer cells. *International Journal of Oncology*, 53(4):1743–1751, 2018.

[101] Taku Yoshida, Jee Hyun Kim, Kristopher Carver, Ying Su, Stanislawa Weremowicz, Laura Mulvey, Shoji Yamamoto, Cameron Brennan, Shenglin Mei, Henry Long, et al. Clk2 is an oncogenic kinase and splicing regulator in breast cancer. *Cancer research*, 75(7):1516–1526, 2015.

[102] Florian Bordes, Richard Yuanzhe Pang, Anurag Ajay, Alexander C Li, Adrien Bardes, Suzanne Petryk, Oscar Mañas, Zhiqiu Lin, Anas Mahmoud, Bargav Jayaraman, et al. An introduction to vision-language modeling. *arXiv preprint arXiv:2405.17247*, 2024.

[103] Jiezhong Qiu, Junde Xu, Jie Hu, Hanqun Cao, Liya Hou, Zijun Gao, Xinyi Zhou, Anni Li, Xiujuan Li, Bin Cui, et al. Instructplm: Aligning protein language models to follow protein structure instructions. *bioRxiv*, pages 2024–04, 2024.

[104] Jeffrey A Ruffolo, Aadyot Bhatnagar, Joel Beazer, Stephen Nayfach, Jordan Russ, Emily Hill, Riffat Hussain, Joseph Gallagher, and Ali Madani. Adapting protein language models for structure-conditioned design. *BioRxiv*, pages 2024–08, 2024.

[105] Henry Dieckhaus and Brian Kuhlman. Protein stability models fail to capture epistatic interactions of double point mutations. *Protein Science*, 34(1):e70003, 2025.

[106] Pauline C Ng and Steven Henikoff. Sift: Predicting amino acid changes that affect protein function. *Nucleic acids research*, 31(13):3812–3814, 2003.

[107] Martin Kircher, Daniela M Witten, Preti Jain, Brian J O'roak, Gregory M Cooper, and Jay Shendure. A general framework for estimating the relative pathogenicity of human genetic variants. *Nature genetics*, 46(3):310–315, 2014.

[108] Nilah M Ioannidis, Joseph H Rothstein, Vikas Pejaver, Sumit Middha, Shannon K McDonnell, Saurabh Baheti, Anthony Musolf, Qing Li, Emily Holzinger, Danielle Karyadi, et al. Revel: an ensemble method for predicting the pathogenicity of rare missense variants. *The American Journal of Human Genetics*, 99(4):877–885, 2016.

[109] Gen Li, Shailesh Kumar Panday, and Emil Alexov. Saafec-seq: a sequence-based method for predicting the effect of single point mutations on protein thermodynamic stability. *International journal of molecular sciences*, 22(2):606, 2021.

[110] Ivan Adzhubei, Daniel M Jordan, and Shamil R Sunyaev. Predicting functional effect of human missense mutations using polyphen-2. *Current protocols in human genetics*, 76(1):7–20, 2013.

[111] Vikas Pejaver, Jorge Urresti, Jose Lugo-Martinez, Kymberleigh A Pagel, Guan Ning Lin, Hyun-Jun Nam, Matthew Mort, David N Cooper, Jonathan Sebat, Lilia M Iakoucheva, et al. Inferring the molecular and phenotypic impact of amino acid variants with mutpred2. *Nature communications*, 11(1):5918, 2020.

[112] Cagi, the critical assessment of genome interpretation, establishes progress and prospects for computational genetic variant interpretation methods. *Genome biology*, 25(1):53, 2024.

[113] John Ingraham, Vikas Garg, Regina Barzilay, and Tommi Jaakkola. Generative models for graph-based protein design. *Advances in neural information processing systems*, 32, 2019.

[114] Bowen Jing, Stephan Eismann, Patricia Suriana, Raphael JL Townshend, and Ron Dror. Learning from protein structure with geometric vector perceptrons. *arXiv preprint arXiv:2009.01411*, 2020.

[115] A Vaswani. Attention is all you need. *Advances in Neural Information Processing Systems*, 2017.

[116] Ning Ding, Yujia Qin, Guang Yang, Fuchao Wei, Zonghan Yang, Yusheng Su, Shengding Hu, Yulin Chen, Chi-Min Chan, Weize Chen, et al. Parameter-efficient fine-tuning of large-scale pre-trained language models. *Nature Machine Intelligence*, 5(3):220–235, 2023.

[117] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[118] Dan Hendrycks and Kevin Gimpel. Gaussian error linear units (gelus). *arXiv preprint arXiv:1606.08415*, 2016.

[119] I Loshchilov. Decoupled weight decay regularization. *arXiv preprint arXiv:1711.05101*, 2017.

[120] Adam J Riesselman, John B Ingraham, and Debora S Marks. Deep generative models of genetic variation capture mutation effects. *arXiv preprint arXiv:1712.06527*, 2017.

[121] Kathryn Tunyasuvunakool, Jonas Adler, Zachary Wu, Tim Green, Michal Zielinski, Augustin Žídek, Alex Bridgland, Andrew Cowie, Clemens Meyer, Agata Laydon, et al. Highly accurate protein structure prediction for the human proteome. *Nature*, 596(7873):590–596, 2021.

[122] Patrick Kunzmann and Kay Hamacher. Biotite: a unifying open source computational biology framework in python. *BMC bioinformatics*, 19:1–8, 2018.

[123] Matthew Z Tien, Austin G Meyer, Dariya K Sydykova, Stephanie J Spielman, and Claus O Wilke. Maximum allowed solvent accessibilites of residues in proteins. *PloS one*, 8(11):e80635, 2013.

[124] Iván Martín Hernández, Yves Dehouck, Ugo Bastolla, José Ramón López-Blanco, and Pablo Chacón. Predicting protein stability changes upon mutation using a simple orientational potential. *Bioinformatics*, 39(1):btad011, 2023.

[125] Martin Steinegger and Johannes Söding. Mmseqs2 enables sensitive protein sequence searching for the analysis of massive data sets. *Nature biotechnology*, 35(11):1026–1028, 2017.

A Supplementary Tables

| | | Models | | | | | | |
		ESM	ProteinMPNN	FT-ESM	FT-ProteinMPNN	ThermoMPNN	ProteinMPNN+ESM	SPURS
Model Components	**ESM Encoder**	✓		✓			✓	✓
	ProteinMPNN Encoder		✓		✓	✓	✓	✓
	Finetuning			✓	✓	✓	✓	✓
	Rewiring							✓
Datasets	Megascale	0.33	0.41	0.64	0.70	0.72	0.72	**0.74**
	Fireprot (HF)	0.43	0.55	0.48	0.64	0.64	0.57	**0.67**
	Ssym-direct	0.36	0.58	0.43	0.71	0.71	0.60	**0.76**
	Ssym-inverse	0.38	0.38	0.28	0.63	0.59	0.45	**0.68**
	S669	0.37	0.43	0.46	0.46	0.44	0.45	**0.50**
	S461	0.29	0.50	0.65	0.60	0.61	0.65	**0.66**
	S783	0.30	0.52	0.59	0.69	0.70	0.64	**0.71**
	S8754	0.16	0.24	0.53	0.60	0.61	0.52	**0.64**
	S2648	0.18	0.31	0.53	0.65	0.65	0.61	**0.69**
	S571	0.27	0.43	0.40	0.42	0.39	0.39	**0.47**
	S4346	0.32	0.52	0.46	0.61	0.60	0.51	**0.64**
	Avg.	0.31	0.44	0.50	0.61	0.61	0.56	**0.65**

Supplementary Table 1: Spearman correlation of SPURS and baseline models on test sets. This table provides the raw correlation results underlying Fig. 2d. Fireprot (HF) denotes a homology-free subset of the Fireprot dataset, curated to ensure that sequences share less than 25% identity with those in Megascale, enabling rigorous evaluation of model generalization.

Dataset	Stability Oracle	PROSTATA	RASP	Rosetta	ThermoNet	SPURS
Megascale	-	0.59[1]	0.67[1]	0.56[1]	0.33[1]	**0.74**
Fireprot (HF)	-	0.55[1]	0.44[1]	0.52[1]	0.36[1]	**0.67**
Ssym-direct	0.68[2]	-	-	-	-	**0.76**
Ssym-inverse	0.68[2]	-	-	-	-	**0.68**
S669	0.50[2]	-	-	-	-	**0.50**

Supplementary Table 2: Spearman correlation of additional baseline models on test sets. Spearman correlation results for a group of additional baseline methods reported in Diaz et al.[2] and Dieckhaus et al.[1]. These results were also presented in Fig. 2d.

Dataset	ESM	ProteinMPNN	FT-ESM	FT-ProteinMPNN	ThermoMPNN	SPURS
Megascale	0.34	0.49	0.68	0.74	0.75	**0.78**
Fireprot (HF)	0.33	0.48	0.48	0.63	0.64	**0.66**
Ssym-direct	0.30	0.59	0.44	0.71	0.70	**0.74**
Ssym-inverse	0.27	0.42	0.28	0.60	0.58	**0.65**
S669	0.25	0.31	0.42	0.43	0.39	**0.46**
S461	0.32	0.38	**0.64**	0.58	0.58	**0.64**
S783	0.43	0.55	0.58	0.71	0.72	**0.73**
S8754	0.37	0.38	0.47	0.57	0.58	**0.60**
S2648	0.29	0.50	0.52	0.65	0.64	**0.67**
S571	0.18	0.22	0.36	0.31	0.25	**0.36**
S4346	0.27	0.43	0.44	0.54	0.53	**0.58**

Supplementary Table 3: Pearson correlation of SPURS and baseline models on test sets. Evaluation results following the same protocol as in Supplementary Table 1, using Pearson correlation as the performance metric to complement the Spearman results.

Model Name	Performance
DDGun-3D	0.36
DDGun-seq	0.33
ESM2 (Additive)	0.40
MPNN (Additive)	0.16
TheomMPNN (Additive)	0.45
SPURS (Additive)	0.52
MutateEverything	0.54
SPURS	0.59

Supplementary Table 4: Performance on double mutants in the Megascale test set. Evaluation of SPURS and baselines for predicting $\Delta\Delta G$ values of higher-order (double) mutations. "Additive" predict $\Delta\Delta G$ for high-order mutations by simply adding the predicted $\Delta\Delta G$ values for constituent individual mutations. Results correspond to Fig. 2f.

Abbreviation	ProteinGym Name	Abbreviation	ProteinGym Name
A0A192B1T2	A0A192B1T2_9HIV1_Haddox_2018	MTHR_HUMAN	MTHR_HUMAN_Weile_2021
A0A1I9GEU1	A0A1I9GEU1_NEIME_Kennouche_2019	NCAP_I34A1	NCAP_I34A1_Doud_2015
A0A247D711	A0A247D711_LISMN_Stadelmann_2021	NPC1_HUMAN	NPC1_HUMAN_Erwood_2022_HEK293T
A0A2Z5U3Z0	A0A2Z5U3Z0_9INFA_Doud_2016	NRAM_I33A0	NRAM_I33A0_Jiang_2016
A0A2Z5U3Z02	A0A2Z5U3Z0_9INFA_Wu_2014	NUD15_HUMAN	NUD15_HUMAN_Suiter_2020
A4D664	A4D664_9INFA_Soh_2019	OPSD_HUMAN	OPSD_HUMAN_Wan_2019
A4GRB6	A4GRB6_PSEAI_Chen_2020	OTC_HUMAN	OTC_HUMAN_Lo_2023
AACC1_PSEAI	AACC1_PSEAI_Dandage_2018	OXDA_RHOTO	OXDA_RHOTO_Vanella_2023_expression
ACE2_HUMAN	ACE2_HUMAN_Chan_2020	OXDA_RHOTO2	OXDA_RHOTO_Vanella_2023_activity
ADRB2_HUMAN	ADRB2_HUMAN_Jones_2020	P53_HUMAN	P53_HUMAN_Kotler_2018
AICDA_HUMAN	AICDA_HUMAN_Gajula_2014_3cycles	P53_HUMAN2	P53_HUMAN_Giacomelli_2018_WT_Nutlin
AMIE_PSEAE	AMIE_PSEAE_Wrenbeck_2017	P53_HUMAN3	P53_HUMAN_Giacomelli_2018_Null_Etoposide
ANCSZ_Hobbs	ANCSZ_Hobbs_2022	P53_HUMAN4	P53_HUMAN_Giacomelli_2018_Null_Nutlin
B2L11_HUMAN	B2L11_HUMAN_Dutta_2010_binding-Mcl-1	P84126	P84126_THETH_Chan_2017
BLAT_ECOLX	BLAT_ECOLX_Firnberg_2014	PABP_YEAST	PABP_YEAST_Melamed_2013
BLAT_ECOLX2	BLAT_ECOLX_Stiffler_2015	PAI1_HUMAN	PAI1_HUMAN_Huttinger_2021
BLAT_ECOLX3	BLAT_ECOLX_Jacquier_2013	PA_I34A1	PA_I34A1_Wu_2015
BLAT_ECOLX4	BLAT_ECOLX_Deng_2012	PHOT_CHLRE	PHOT_CHLRE_Chen_2023
BRCA1_HUMAN	BRCA1_HUMAN_Findlay_2018	POLG_DEN26	POLG_DEN26_Suphatrakul_2023
C6KNH7	C6KNH7_9INFA_Lee_2018	PPARG_HUMAN	PPARG_HUMAN_Majithia_2016
CALM1_HUMAN	CALM1_HUMAN_Weile_2017	PPM1D_HUMAN	PPM1D_HUMAN_Miller_2022
CAPSD_AAV2S	CAPSD_AAV2S_Sinai_2021	PRKN_HUMAN	PRKN_HUMAN_Clausen_2023
CAR11_HUMAN	CAR11_HUMAN_Meitlis_2020_lof	PTEN_HUMAN	PTEN_HUMAN_Mighell_2018
CAR11_HUMAN2	CAR11_HUMAN_Meitlis_2020_gof	PTEN_HUMAN2	PTEN_HUMAN_Matreyek_2021
CAS9_STRP1	CAS9_STRP1_Spencer_2017_positive	Q2N0S5	Q2N0S5_9HIV1_Haddox_2018
CASP3_HUMAN	CASP3_HUMAN_Roychowdhury_2020	Q53Z42	Q53Z42_HUMAN_McShan_2019_expression
CASP7_HUMAN	CASP7_HUMAN_Roychowdhury_2020	Q53Z422	Q53Z42_HUMAN_McShan_2019_binding-TAPBPR
CBS_HUMAN	CBS_HUMAN_Sun_2020	Q59976	Q59976_STRSQ_Romero_2015
CCDB_ECOLI	CCDB_ECOLI_Adkar_2012	Q6WV13	Q6WV13_9MAXI_Somermeyer_2022
CCDB_ECOLI2	CCDB_ECOLI_Tripathi_2016	Q837P4	Q837P4_ENTFA_Meier_2023
CCR5_HUMAN	CCR5_HUMAN_Gill_2023	Q837P5	Q837P5_ENTFA_Meier_2023
CD19_HUMAN	CD19_HUMAN_Klesmith_2019_FMC_singles	Q8WTC7	Q8WTC7_9CNID_Somermeyer_2022
CP2C9_HUMAN	CP2C9_HUMAN_Amorosi_2021_activity	R1AB_SARS2	R1AB_SARS2_Flynn_2022
CP2C9_HUMAN2	CP2C9_HUMAN_Amorosi_2021_abundance	RAF1_HUMAN	RAF1_HUMAN_Zinkus-Boltz_2019
D7PM05	D7PM05_CLYGR_Somermeyer_2022	RASH_HUMAN	RASH_HUMAN_Bandaru_2017
DLG4_HUMAN	DLG4_HUMAN_Faure_2021	RASK_HUMAN	RASK_HUMAN_Weng_2022_binding-DARPin_K55
DLG4_RAT	DLG4_RAT_McLaughlin_2012	RASK_HUMAN2	RASK_HUMAN_Weng_2022_abundance
DYR_ECOLI	DYR_ECOLI_Thompson_2019	RDRP_I33A0	RDRP_I33A0_Li_2023
DYR_ECOLI2	DYR_ECOLI_Nguyen_2023	REV_HV1H2	REV_HV1H2_Fernandes_2016
ENVZ_ECOLI	ENVZ_ECOLI_Ghose_2023	RL40A_YEAST	RL40A_YEAST_Roscoe_2013
ENV_HV1B9	ENV_HV1B9_DuenasDecamp_2016	RL40A_YEAST2	RL40A_YEAST_Roscoe_2014
ENV_HV1BR	ENV_HV1BR_Haddox_2016	RL40A_YEAST3	RL40A_YEAST_Mavor_2016
ERBB2_HUMAN	ERBB2_HUMAN_Elazar_2016	RNC_ECOLI	RNC_ECOLI_Weeks_2023
GAL4_YEAST	GAL4_YEAST_Kitzman_2015	RPC1_LAMBD	RPC1_LAMBD_Li_2019_low-expression
GDIA_HUMAN	GDIA_HUMAN_Silverstein_2021	RPC1_LAMBD2	RPC1_LAMBD_Li_2019_high-expression
GFP_AEQVI	GFP_AEQVI_Sarkisyan_2016	S22A1_HUMAN	S22A1_HUMAN_Yee_2023_abundance
GLPA_HUMAN	GLPA_HUMAN_Elazar_2016	S22A1_HUMAN2	S22A1_HUMAN_Yee_2023_activity
GRB2_HUMAN	GRB2_HUMAN_Faure_2021	SC6A4_HUMAN	SC6A4_HUMAN_Young_2021
HEM3_HUMAN	HEM3_HUMAN_Loggerenberg_2023	SERC_HUMAN	SERC_HUMAN_Xie_2023
HIS7_YEAST	HIS7_YEAST_Pokusaeva_2019	SHOC2_HUMAN	SHOC2_HUMAN_Kwon_2022
HMDH_HUMAN	HMDH_HUMAN_Jiang_2019	SPG1_STRSG	SPG1_STRSG_Olson_2014
HSP82_YEAST	HSP82_YEAST_Mishra_2016	SPIKE_SARS2	SPIKE_SARS2_Starr_2020_expression
HSP82_YEAST2	HSP82_YEAST_Flynn_2019	SPIKE_SARS22	SPIKE_SARS2_Starr_2020_binding
HSP82_YEAST3	HSP82_YEAST_Cote-Hammarlof_2020_growth-H2O2	SRC_HUMAN	SRC_HUMAN_Ahler_2019
HXK4_HUMAN	HXK4_HUMAN_Gersing_2022_activity	SRC_HUMAN2	SRC_HUMAN_Nguyen_2022
HXK4_HUMAN2	HXK4_HUMAN_Gersing_2023_abundance	SRC_HUMAN3	SRC_HUMAN_Chakraborty_2023_binding-DAS_25uM
I6TAH8	I6TAH8_I68A0_Doud_2015	SUMO1_HUMAN	SUMO1_HUMAN_Weile_2017
IF1_ECOLI	IF1_ECOLI_Kelsic_2016	SYUA_HUMAN	SYUA_HUMAN_Newberry_2020
KCNE1_HUMAN	KCNE1_HUMAN_Muhammad_2023_function	TADBP_HUMAN	TADBP_HUMAN_Bolognesi_2019
KCNE1_HUMAN2	KCNE1_HUMAN_Muhammad_2023_expression	TAT_HV1BR	TAT_HV1BR_Fernandes_2016
KCNH2_HUMAN	KCNH2_HUMAN_Kozek_2020	TPK1_HUMAN	TPK1_HUMAN_Weile_2017
KCNJ2_MOUSE	KCNJ2_MOUSE_Coyote-Maestas_2022_function	TPMT_HUMAN	TPMT_HUMAN_Matreyek_2018
KCNJ2_MOUSE2	KCNJ2_MOUSE_Coyote-Maestas_2022_surface	TPOR_HUMAN	TPOR_HUMAN_Bridgford_2020
KKA2_KLEPN	KKA2_KLEPN_Melnikov_2014	TRPC_SACS2	TRPC_SACS2_Chan_2017
LGK_LIPST	LGK_LIPST_Klesmith_2015	TRPC_THEMA	TRPC_THEMA_Chan_2017
LYAM1_HUMAN	LYAM1_HUMAN_Elazar_2016	UBC9_HUMAN	UBC9_HUMAN_Weile_2017
MET_HUMAN	MET_HUMAN_Estevam_2023	UBE4B_MOUSE	UBE4B_MOUSE_Starita_2013
MK01_HUMAN	MK01_HUMAN_Brenan_2016	VKOR1_HUMAN	VKOR1_HUMAN_Chiasson_2020_abundance
MLAC_ECOLI	MLAC_ECOLI_MacRae_2023	VKOR1_HUMAN2	VKOR1_HUMAN_Chiasson_2020_activity
MSH2_HUMAN	MSH2_HUMAN_Jia_2020	YAP1_HUMAN	YAP1_HUMAN_Araya_2012
MTH3_HAEAE	MTH3_HAEAE_RockahShmuel_2015		

Supplementary Table 5: Abbreviations for DMS datasets. Digit suffixes distinguish multiple DMS studies on the same protein.

Dataset	Number of mutants	Number of proteins	Structure
Megascale (training)	216,919	239	AF2
Filtered Megascale (training)	203,789	212	AF2
Megascale (validation)	27,481	31	AF2
Filtered Megascale (validation)	26,548	29	AF2
Megascale (test)	28,312	28	AF2
Fireprot (HF)	3,438	89	PDB
Ssym-direct	342	15	PDB
Ssym-inverse	342	342	PDB
S669	669	94	PDB
S461	461	48	PDB
S783	783	55	PDB
S8754	8,236	274	PDB
S2648	2,648	131	PDB
S4346	3,988	281	PDB
S571	571	37	PDB
Domainome	536,164	522	PDB

Supplementary Table 6: Summary statistics of single-mutation datasets used for training and evaluation. Number of proteins and total mutants per dataset. The "Structure" column denotes the source of structural data used in our experiments–AF2: AlphaFold2 predictions; PDB: experimentally solved structures available in the PDB database.

Dataset	Number of mutants	Number of proteins
Megascale (training)	122,278	116
Megascale (validation)	10,672	17
Megascale (test)	22,081	20

Supplementary Table 7: Summary of double-mutation variants in Megascale. The number of proteins and double-mutation variants included in the Megascale training, validation, and test splits used for training and evaluating SPURS's high-order mutation prediction module (Fig. 2f). The training/validation/test splits were obtained from the ThermoMPNN study[1].

B Supplementary Notes

B.1 Baseline Methods

We compared SPURS against several leading stability predictors, including biophysics and machine learning models. For some baselines, we reused evaluation results reported in the original publications or in Dieckhaus et al.[1], as noted below. It is worth noting that advantages were given to these baselines, as their training data are supersets of our filtered Megascale training set and may include proteins from the benchmark test sets used in our evaluation.

ThermoMPNN. Dieckhaus et al.[1] developed ThermoMPNN, a transfer learning framework based on the ProteinMPNN architecture, trained on the Megascale dataset. The model uses a lightweight attention layer and MLP to transform ProteinMPNN embeddings into stability scores. We adopted the official implementation from `https://github.com/Kuhlman-Lab/ThermoMPNN`. Following the original setup, we first trained ThermoMPNN on the full Megascale dataset and reproduced the authors' reported results on the Megascale test set, Fireprot (HF), and S669 benchmarks. For fair comparison, we then retrained the model using our filtered Megascale dataset and kept all original hyperparameters unchanged.

RASP. RASP, proposed by Blaabjerg et al.[3], is a stability prediction model pretrained on a structural representation learning task and subsequently fine-tuned on Rosetta-predicted $\Delta\Delta G$ values. We compared against the results reported by Dieckhaus et al.[1].

Stability Oracle. Stability Oracle is a structure-based $\Delta\Delta G$ predictor introduced by Diaz et al.[2], based on a graph transformer architecture. It models the local structural environment surrounding a mutation site and predicts position-specific $\Delta\Delta G$ values. The model was trained on a composite dataset that includes Megascale, FireProt, and other public sources. Since the authors did not release training code, we used the published results for comparison. Note that their training data used to train Stability Oracle partially overlaps with the test sets used in our evaluation, giving advantages to Stability Oracle compared to SPURS in the evaluation.

FoldX. FoldX[4] is a widely used physics-based method that estimates protein stability changes based on an empirical force field. Following standard protocols, we used the Repair and BuildModel steps to compute $\Delta\Delta G$ values. In cases where the wild-type sequence of a protein did not match the amino acid sequence in the associated PDB structure due to missing residues or inconsistent annotations, FoldX raised errors for these proteins due to the unresolved inconsistency in the input structure file and mutation list. We therefore excluded these cases, which comprised a small fraction of the test variants (2,168 out of 49,790; 4%) and had only a negligible impact on the overall evaluation of FoldX's performance.

ThermoNet. ThermoNet[5] is a structure-aware deep learning model that uses 3D convolutional neural networks on voxelized atomic neighborhoods to predict $\Delta\Delta G$. We used benchmark results reported by Dieckhaus et al.[1] for benchmarking.

PROSTATA. PROSTATA[6] is a machine learning model that applies transfer learning to a pre-trained protein language model (ESM-2). It encodes wild-type and mutant sequences separately and combines their transformer-derived embeddings using regression heads to predict $\Delta\Delta G$. Evaluation results were obtained from Dieckhaus et al.[1].

Rosetta. Rosetta[7] is a comprehensive physics-based modeling platform for protein structure and energetics. Stability predictions are computed using energy-based modeling of mutations. We used performance reported in Dieckhaus et al.[1] for comparison.

DDGun. DDGun[8] is a family of untrained methods for predicting protein stability changes upon mutation.

The sequence-based variant relies on multiple sequence alignments, while the structure-based version incorporates 3D structural features. We used the official implementation from `https://github.com/biofold/ddgun` to perform $\Delta\Delta G$ predictions.

MutateEverything. MutateEverything[9] is a parallel decoding framework for efficient $\Delta\Delta G$ prediction across all single and higher-order variants. The model fine-tunes an AlphaFold backbone with a lightweight MLP decoder on the Megascale dataset. We used the official implementation from `https://github.com/jozhang97/MutateEverything` to perform prediction for high-order mutation evaluations.

References

[1] Henry Dieckhaus, Michael Brocidiacono, Nicholas Z Randolph, and Brian Kuhlman. Transfer learning to leverage larger datasets for improved prediction of protein stability changes. *Proceedings of the National Academy of Sciences*, 121(6):e2314853121, 2024.

[2] Daniel J Diaz, Chengyue Gong, Jeffrey Ouyang-Zhang, James M Loy, Jordan Wells, David Yang, Andrew D Ellington, Alexandros G Dimakis, and Adam R Klivans. Stability oracle: a structure-based graph-transformer framework for identifying stabilizing mutations. *Nature Communications*, 15(1):6170, 2024.

[3] Lasse M Blaabjerg, Maher M Kassem, Lydia L Good, Nicolas Jonsson, Matteo Cagiada, Kristoffer E Johansson, Wouter Boomsma, Amelie Stein, and Kresten Lindorff-Larsen. Rapid protein stability prediction using deep learning representations. *Elife*, 12:e82593, 2023.

[4] Joost Schymkowitz, Jesper Borg, Francois Stricher, Robby Nys, Frederic Rousseau, and Luis Serrano. The foldx web server: an online force field. *Nucleic acids research*, 33(suppl_2):W382–W388, 2005.

[5] Bian Li, Yucheng T Yang, John A Capra, and Mark B Gerstein. Predicting changes in protein thermodynamic stability upon point mutation with deep 3d convolutional neural networks. *PLoS computational biology*, 16(11):e1008291, 2020.

[6] Dmitriy Umerenkov, Fedor Nikolaev, Tatiana I Shashkova, Pavel V Strashnov, Maria Sindeeva, Andrey Shevtsov, Nikita V Ivanisenko, and Olga L Kardymon. Prostata: a framework for protein stability assessment using transformers. *Bioinformatics*, 39(11):btad671, 2023.

[7] Rebecca F Alford, Andrew Leaver-Fay, Jeliazko R Jeliazkov, Matthew J O'Meara, Frank P DiMaio, Hahnbeom Park, Maxim V Shapovalov, P Douglas Renfrew, Vikram K Mulligan, Kalli Kappel, et al. The rosetta all-atom energy function for macromolecular modeling and design. *Journal of chemical theory and computation*, 13(6):3031–3048, 2017.

[8] Ludovica Montanucci, Emidio Capriotti, Yotam Frank, Nir Ben-Tal, and Piero Fariselli. Ddgun: an untrained method for the prediction of protein stability changes upon single and multiple point variations. *BMC bioinformatics*, 20:1–10, 2019.

[9] Jeffrey Ouyang-Zhang, Daniel Diaz, Adam Klivans, and Philipp Krähenbühl. Predicting a protein's stability under a million mutations. *Advances in Neural Information Processing Systems*, 36, 2024.