Effective connectivity between the medial temporal lobes and early visual cortex modulated by unrestricted viewing predicts memory retrieval and gaze reinstatement

Ladyka-Wojcik, N.[1]*, Liu, Z.-X.[2]*, & Ryan, J.D.[1,3,4]

[1]Rotman Research Institute, Baycrest Health Sciences, Toronto ON, Canada
[2]Department of Behavioral Sciences, University of Michigan-Dearborn, Dearborn MI, USA
[3]Department of Psychology, University of Toronto, Toronto ON, Canada
[4]Department of Psychiatry, University of Toronto, Toronto ON, Canada

*Indicates equal contribution

Correspondence concerning this article should be addressed to:

Natalia Ladyka-Wojcik
3560 Bathurst Street
Rotman Research Institute
Baycrest Health Sciences
Toronto, ON, CA M6A 2E1
Email: nladyka-wojcik@research.baycrest.org

1 Abstract

Memory and gaze behavior are intricately linked, guiding one another to extract

information and create mental representations of our environment for subsequent

retrieval. Recent findings from functional neuroimaging and computational modeling

suggest that reciprocal interactions between the extended hippocampal system and

visuo-oculomotor regions are functionally relevant for building these mental

representations during visual exploration. Yet, evidence for the directionality of

information flow during encoding within this reciprocal architecture in humans is limited.

In the current study, we used dynamic causal modeling (DCM) to give a non-invasive

account for the directional influences between these systems when new memories are

created. Here, we provide novel evidence demonstrating how unrestricted, naturalistic

visual exploration induces changes in this connectivity. Subsequent memory retrieval

performance was also predicted by the pattern of connectivity modulated by unrestricted

visual exploration, identifying the mechanism underlying a rich history of previous work

linking increased gaze behavior during encoding to later memory. Together, these

findings suggest that gaze behavior shapes the ways in which brain dynamics within

and between the hippocampal system and early visual cortex unfold during encoding in

humans. Importantly, these directional interactions support the building of coherent,

lasting mental representations.

Keywords: effective connectivity, encoding, gaze fixations, hippocampus,
neuroimaging, visual exploration

1 Introduction

What we encode in memory is intimately tied to where we look (Hannula et al., 2010; Ryan & Shen, 2020). Visual exploration allows us to accumulate salient information from our environment to build mental representations in support of memory retrieval (Liu et al., 2017; Loftus, 1972; Nikolaev et al., 2023; Sharot et al., 2008). During encoding, a greater number of gaze fixations—the discrete stops made by the eyes—predicts mnemonic performance (Damiano & Walther, 2019; Loftus, 1972). Conversely, when fixations are explicitly restricted, subsequent memory retrieval is impaired (Damiano & Walther, 2019; Henderson et al., 2005; Liu et al., 2020). Patterns of gaze fixations at encoding (i.e., scanpaths) are also spontaneously reproduced during retrieval in support of memory (Noton & Stark, 1971a, 1971b; for a review, see Wynn et al., 2019). Notably, where we move our eyes during encoding is not solely driven by bottom-up, exogenous features of space; visual exploration is also guided by top-down factors such as prior knowledge and memories of past experiences (Castelhano & Henderson, 2007; Ramey et al., 2020; Ryan et al., 2007). Eye movements increasingly anticipate upcoming stimulus locations over the course of learning which, paired with a shift in brain activity from representing previously viewed images to upcoming ones, predict later successful memory recall (Büchel et al., 2024; Huang et al., 2023). Thus, the neural architecture of the human brain must support the rapid exchange of information about mental representations and visual exploration, in service of cognition and behavior.

The hippocampal (HPC) memory and visuo-oculomotor control systems have been widely investigated for their respective roles in memory (Eichenbaum et al., 1994, 1996; Moscovitch et al., 2016) and gaze behavior (Robinson, 1986; Robinson & Optican, 1981). Recently, vast structural and functional connections between these systems have been identified in the human and nonhuman primate brain (e.g., Shen et al., 2016). Whereas early theoretical accounts positioned the HPC as the site at which already-parsed sensory information is bound into lasting representations in memory (Cohen & Eichenbaum, 1993), more recent accounts propose that connections between these systems might allow for eye movements themselves to be embedded into mnemonic representations (Katz et al., 2020; Ryan, 2024). Compelling evidence for this

notion comes from computational modeling, which has revealed numerous polysynaptic projections between these systems along which information may flow (Shen et al., 2016). Indeed, simulating stimulation to HPC subfields and the broader medial temporal lobes (MTL) resulted in propagating signals via multiple regions, including visual regions, that ultimately reached oculomotor control regions within the period of a gaze fixation (Ryan et al., 2020). Converging findings from electrophysiological recordings have identified neuronal responses in the HPC tuned to visual exploration in nonhuman primates (Hoffman et al., 2013; Jutras et al., 2013; Mao et al., 2021) and in humans (Katz et al., 2022). Moreover, amnesic cases with damage to the HPC system show selective deficits in their gaze patterns (Ryan et al., 2000; Warren et al., 2011) such as less organized viewing patterns relative to healthy individuals (Lucas et al., 2019). Together these findings speak to the existence of reciprocal connections between the HPC memory and visuo-oculomotor control systems, which could coordinate encoding-relevant viewing behavior towards previously seen and new locations (Knapen, 2021; Nikolaev et al., 2024; Ryan & Shen, 2020).

A question remains: how are the strength and directionality of connections between the HPC memory and visuo-oculomotor systems modified by viewing behavior during encoding? To this end, measures of effective connectivity offer the ability to model *directed influences* between these systems due to modulatory effects (Friston et al., 2003). Previous work by Tullo et al. (2023) found that perception of highly familiar scenes evokes bottom-up excitatory and top-down inhibitory effective connectivity between visual regions and subregions of the parahippocampal place area (PPA), a key area of the extended HPC memory system implicated in scene processing (Aguirre et al., 1996; Epstein et al., 1999; Epstein & Baker, 2019; Epstein & Kanwisher, 1998). This finding highlights plausible pathways between the HPC memory and visuo-oculomotor systems, but it is unknown if we should expect similar patterns of effective connectivity during encoding when new visuo-spatial information must be bound into mnemonic representations. Moreover, without manipulating visual behavior, we cannot discern whether gaze fixations directly modulate the strength and directionality of these pathways. Multi-modal approaches leveraging functional neuroimaging (i.e., fMRI) and simultaneous eye-tracking have provided arguably the strongest insights into this

question to date. Functional connectivity between the HPC, PPA, and early visual regions during the encoding of novel scenes was impeded when fixations were actively restricted compared to unrestricted, free, viewing (Liu et al., 2020). These effects were stronger for real-world scenes compared to scrambled color-tile images, for which there was relatively less information available for extraction, and the effects were also stronger for scenes that were subsequently remembered versus forgotten. A recent effective connectivity study supplies evidence consistent with this latter finding: successful encoding of novel scenes was associated with excitatory effective connectivity from the PPA to the HPC (Schott et al., 2023), although regions of the visuo-oculomotor system were not considered. At the level of the visuo-oculomotor system, functional activation in the occipital pole (OCP) has been tied to the formation and later reinstatement of gaze fixations made during *free*-viewing of novel scenes (Wynn et al., 2022). The authors also identified voxels in the HPC and PPA responsive to both subsequent memory strength and gaze reinstatement, suggesting that information about eye movements may be embedded into mnemonic representations. However, it is unknown whether effective engagement of the extended HPC and visuo-oculomotor systems differs based on subsequent memory and/or gaze reinstatement. In fact, to our knowledge, viewing behavior during encoding has not yet been considered in studies of effective connectivity between these systems.

In the present study, we used the data from Liu et al. (2020) to conduct Dynamic Causal Modeling (DCM), in order to probe the top-down and bottom-up modulatory nature of visual exploration during novel scene encoding in the healthy adult brain. Specifically, our main question of interest focused on how unrestricted, naturalistic visual exploration (i.e., *free*-viewing) during scene and scrambled image encoding could modulate the effective connectivity architecture between the HPC, PPA, and OCP, over-and-above restricted (i.e., *fixed-*) viewing. Briefly, DCM models the (1) underlying (i.e., average) effective connectivity within- and between-regions of interest (ROIs), (2) experimental modulation of within- (i.e, self-), forward, and backward connections of ROIs, and (3) the external input that stimulates the system. Here, we compared families of models with top-down, bottom-up, and bidirectional connections switched on or off, evaluating underlying and modulatory effects of *free*-viewing for scene and scrambled image

encoding. We predicted that the modulatory effects of unrestricted gaze fixations during encoding would be evidenced in strengthened excitatory connections from the early visual cortex towards the PPA for both scenes and scrambled images. This hypothesized architecture would facilitate bottom-up information flow accumulated through visual exploration, from the visuo-oculomotor system to the extended HPC memory system. During unrestricted viewing of scene images, when meaningful visuo-spatial information can be extracted to build mental representations for later retrieval, we hypothesized that this excitatory effect would propagate from the PPA towards the HPC. We also hypothesized a top-down, inhibitory modulatory effect of unrestricted viewing from the HPC to the PPA, thought to reflect suppression of mental representations from previously encoded images. Finally, we interrogated whether there were specific modulatory effects that predicted memory strength and/or similarity of gaze reinstatement during subsequent retrieval of scenes encoded under unrestricted viewing conditions. Importantly, we considered both self- and between-region modulatory effects, as both are integral to understanding the excitatory and inhibitory balance in the modeled architecture (see for e.g., Snyder et al., 2021). Our findings demonstrate how visual exploration dynamically modifies the connections between the extended HPC memory and visuo-oculomotor systems to support the rapid formation of scene representations in memory.

2 Materials and Methods

2.1 Participants

Our participants consisted of thirty-six young adults (22 females) aged 18-35 years ($M = 23.58$ years, $SD = 4.17$) from the University of Toronto and surrounding Toronto area (education: $M = 16.27$ years, $SD = 1.8$) reported in Liu et al. (2020). Participants had normal or corrected-to-normal vision (including color vision) and were screened for any neurological or psychological conditions. The study was approved by the Research Ethics Board at the Rotman Research Institute at Baycrest Health Sciences, and all participants provided written informed consent.

2.2 Stimuli

A comprehensive description of the stimuli used in this experiment is reported in Liu et

al. (2020). Briefly, stimuli consisted of twenty-four color scene images (500 x 500 pixels;

viewing angle: 7.95 x 7.95 degree) for each of 36 semantic scene categories (e.g.,

warehouse, movie theater, airport, etc.), for a total of 864 images. Images were either

obtained from a previous study by Park et al. (2015) or from Google Images using the

same semantic categories as the search term. Images in each semantic scene category

(8 images/category) were randomly assigned to either the *free*-viewing encoding

condition, the *fixed*-viewing encoding condition, or a retrieval task condition not reported

here (see Liu et al., 2020). The assignment of the images to these experimental

conditions was counterbalanced across participants, with low-level features such as

luminance equalized across conditions in MATLAB using the SHINE toolbox

(Willenbockel et al., 2010).

Next, the eight images for each scene category in the *free*- and *fixed*-viewing conditions

were randomly assigned to eight fMRI encoding runs, such that each run contained a

scene from each category shown under *free*- and *fixed*-viewing conditions. Finally,

images from two randomly selected fMRI runs were scrambled, using six levels of tile

sizes (i.e., 5, 10, 25, 50, 100, and 125 pixels) to resemble the clutter feature of the

scene images. The pixels within each tile were averaged to create two runs of

scrambled color-tile images.

Stimuli were presented with Experiment Builder (Eyelink 1000; SR Research) back

projected to a screen (projector resolution: 1024x768) and viewed with a mirror

mounted on the MRI head coil.

2.3 Procedure

Participants completed eight runs of the encoding task, with six runs containing scene

images and two runs containing scrambled images (Figure 1). Each run had 72 images,

studied under *free*-viewing instructions (i.e., 36 trials) or *fixed*-viewing instructions (i.e.,

36 trials). The order of the scene and scrambled image runs was randomized across

participants. Within an encoding trial, participants first saw a fixation cross ('+') for 1.72-
4.16 secs whose location was randomly determined within a radius of 100 pixels around
the center of the screen. The fixation cross was presented in either a green color
(indicating the subsequent trial image was in the *free*-viewing condition) or in a red color
(indicating the subsequent trial image was in the *fixed*-viewing condition). For the *free*-
viewing condition, participants were instructed to freely explore the scene or scrambled
image that followed with their eyes in order to encode as much information as possible.
For the *fixed*-viewing condition, participants were instead instructed to keep their eye
gaze at the location of the fixation cross for the duration of the presented scene or
scrambled image that followed. Each run was 500 seconds long, with 10 seconds and
12.4 seconds added to the start and end of the task, respectively. The trials from the
two viewing conditions (i.e., *free-* and *fixed*-viewing) were pseudo-randomized to obtain
an adequate design efficiency by choosing the design with the best efficiency from 1000
randomizations using MATLAB code by Spunt (2019). Please see Liu et al. (2020) for
further details about the encoding task procedure.

Figure 1. Visualization of experimental task procedure, adapted from Liu et al. (2020).
Participants were presented with either a green or red fixation cross within a radius of
100 pixels around the center of the screen at the start of each encoding trial. A green
fixation cross instructed participants to freely view the upcoming scene or scrambled
color-tile image (*free*-viewing condition). A red fixation cross instructed participants to
maintain fixation on the location of the cross during the presentation of the upcoming

scene or scrambled color-tile image (*fixed*-viewing condition). Participants were presented with 6 runs of scenes and 2 runs of scrambled color-tile images, the order of which was randomized for each participant.

2.4 Eye-tracking

During the encoding task, monocular eye movements (right pupil and corneal reflection) were recorded inside the scanner using the EyeLink 1000 MRI-compatible remote eye-tracker with a 1000 Hz sampling rate (SR Research LTD., Ottawa, Ontario, Canada). At the start of the experiment, calibration was performed using the built-in EyeLink 9-point calibration procedure, with drift correction used between trials when necessary to ensure good tracking accuracy.

EyeLink's default eye movement event parser was used to categorize fixations and saccades. Saccades were classified based on a velocity threshold of 30°/s and an acceleration threshold of 8000°/s (saccade onset threshold = 0.15°). Events not defined as saccades or blinks were classified as fixations. For each participant, the number of fixations made during the encoding task for each image was calculated and exported using EyeLink software Data Viewer.

2.5 MRI Data Acquisition

As specified in Liu et al. (2020), a 3T Siemens MRI scanner with a standard 32-channel head coil was used to acquire structural and functional MRI images. T1-weighted high-resolution MRI images for structural scans were obtained using a standard 3D MPRAGE (magnetization-prepared rapid acquisition gradient echo) pulse sequence (176 slices, FOV = 256 × 256 mm, 256 × 256 matrix, 1 mm isotropic resolution, TE/TR = 2.22/2000 ms, flip angle = 9°, and scan time = 280 s). For functional scans, BOLD signal was assessed using a T2*-weighted EPI acquisition protocol with TR = 2000 ms, TE = 27 ms, flip angle = 70 degrees, and FOV = 191 x 192 ms with 64 x 64 matrix (3 mm x 3 mm in-place resolution; slice thickness = 3.5 mm with no gap). A total of 250 volumes were acquired for the fMRI run, with the first 5 discarded to allow the magnetization to stabilize to a steady state. Both structural and functional images were

acquired in an oblique orientation 30° clockwise to the anterior–posterior commissure

axis.

2.6 fMRI Data Processing

The fMRI preprocessing procedure was previously reported in Liu et al. (2020); for

completeness, it is re-presented here. Functional images were processed using SPM12

(Statistical Parametric Mapping, Wellcome Trust Center for Neuroimaging, University

College London, UK; https://www.fil.ion.ucl.ac.uk/spm/software/spm12/; Version: 7771)

in MATLAB (The MathWorks, Natick, USA), starting with the standard SPM12

preprocessing procedure. To specify, slice timing was first corrected using sinc

interpolation with the reference slice set to the midpoint slice. Next, functional images

were aligned using a linear transformation, and for each participant functional image

parameters from the alignment procedure (along with global signal intensity) were

checked manually using the toolbox ART (http://www.nitrc.org/projects/artifact_detect/).

Anatomical images were co-registered to the aligned functional image and segmented

into white matter, gray matter, cerebrospinal fluid, skull, and soft tissues using SPM12's

default 6-tissue probability maps. Segmented images were then used to calculate the

transformation parameters mapping from the subjects' native space to the MNI template

space. The resulting transformation parameters were used to transform all functional

and structural images to the MNI template. The functional images were finally

resampled at 2 × 2 × 2 mm resolution and smoothed using a Gaussian kernel with an

FWHM of 6 mm. The first five fMRI volumes from each run were discarded to allow the

magnetization to stabilize to a steady state.

We then used SPM12 to conduct the first (i.e., subject) level whole brain voxel-wise

General Linear Model (GLM) analysis for subsequent time series extraction. We

included 4 conditions: all scene images, *free*-viewing scenes, all scrambled images, and

free-viewing scrambled images, separately convolved trials with duration = 4 s with the

canonical hemodynamic function (HRF). Motion parameters (6 from SPM realignment, 1

from ART processing), as well as outlier volumes, were added as regressors of no

interest. Default high-pass filter with cut-off of 128 secs was applied. The serial

correlation in fMRI time series in the restricted maximum-likelihood estimation of the

GLM was accounted for using a first-order autoregressive model AR(1).

Since we were interested in determining how effective connectivity changes as a result

of *free*-viewing over and above encoding under any viewing conditions, we constructed

a *t* contrast for all scene trials and a *t* contrast for only *free*-viewing trials of scenes,

averaged across all 6 scene runs. We did the same for the two runs of scrambled trials.

Finally, we added an effect of interest *F*-contrast with the 4 conditions to extract time

series for subsequent analyses of effective connectivity.

2.7 Time series extraction

Selecting ROIs for DCM analyses which show univariate contrast effects between

conditions of interest is strongly recommended, in order to ensure that the ROIs under

investigation are likely to play a role in the cognitive process targeted by the

independent variable manipulation (Stephan et al., 2010; Zeidman et al., 2019a). As

such, we used the significant group-level activation clusters to extract time series for the

DCM analysis, which were constrained to be within the boundaries of our ROIs.

Specifically, we focused on three *a priori* ROIs – the HPC, PPA, and OCP – based on

their involvement in scene encoding, visual exploration, and gaze reinstatement as

reported in Liu et al. (2020) and Wynn et al. (2022). Subject-specific anatomical masks

were generated for the HPC using FreeSurfer's recon-all function

(https://surfer.nmr.mgh.harvard.edu/; Fischl, 2012). The PPA was defined functionally

by contrasting the scene and scrambled image conditions, collapsing over the *free*- and

fixed-viewing conditions (Liu et al., 2020). For the OCP, we used peak activation

coordinates reported in Wynn et al. (2022) to identify the center of an 8-mm radius

spherical mask for each participant. Due to the increased complexity in interpretation

when including inter-hemispheric connections for DCM, in part because testing the full

model space would require additional nested models (Stephan et al., 2010; Stephan &

Friston, 2010; Zeidman et al., 2019b), we combined left and right hemisphere masks.

Using these bilateral masks, we separately extracted voxels for the scene and

scrambled image conditions that showed an effect of *free*-viewing ($p = .05$, no

corrections). Importantly, including voxels that show task modulation effects can

facilitate DCM analysis (Zeidman et al., 2019a). Therefore, when the number of voxels

was lower than 50 (i.e., too few voxels in the ROI) for a specific ROI of a participant, we

relaxed the threshold to 0.1, 0.5, or without using any threshold (i.e., threshold = 1) until

at least 50 voxels could be obtained for that ROI and that participant (see Table 1). The

average number of voxels (1 × 1 × 1 mm^3) for the PPA, HPC, and OCP are reported in

Table 1 below for both scene and scrambled image conditions.

Table 1. Averages and standard error of the mean (SE) for the number of voxels

included in each condition and ROI, with voxel threshold counts across participants.

ROIs	*Scene*					*Scrambled*				
	M_{voxels} (SE)	*Thresholds*				*M_{voxels} (SE)*	*Thresholds*			
		0.05	*0.1*	*0.5*	*1*		*0.05*	*0.1*	*0.5*	*1*
OCP	252.72 (24.53)	21	2	8	5	245.03 (26.32)	17	4	5	10
PPA	477.78 (28.54)	30	1	5	0	276.03 (31.14)	20	4	12	0
HPC	354.25 (55.05)	28	3	5	0	228.19 (32.51)	22	9	5	0

2.8 Dynamic causal modeling

DCM is a framework for specifying models of effective connectivity among brain

regions, estimating their parameters and testing hypotheses (Zeidman et al., 2019a).

Since DCM estimates region-specific hemodynamic responses and neural states

(Stephan & Friston, 2010), it is relatively resistant to issues related to HRF variations in

different brain regions (Friston et al., 2014; Stephan et al., 2007). This approach has

also been shown to have high scan-rescan reliability for fMRI (Schuyler et al., 2010).

We implemented DCM in SPM12. DCM presents an advantage over other measures of

effective connectivity such as structural equation modeling (C. Büchel & Friston, 1997;

McIntosh & Gonzalez-Lima, 1994) or Granger causality (Goebel et al., 2003) because it

not only provides a measure of endogenous effective connectivity between regions, but

also a measure of how these directed connections are modulated by task demands

(Stephan & Friston, 2010). In DCM, the state equations are causal in form – meaning

the rate of change in each region depends on the current state of the system (i.e.,

mechanistic effects; Chicarro & Ledberg, 2012). To be clear, by "mechanistic" here we

mean plausible neuronal mechanisms that underlie experimental measurements of

brain responses (Stephan et al., 2010). The resulting coupling parameters reflect

effective connectivity: the estimated influence that one region exerts over another under

different experimental conditions. When these parameters change across conditions,

we interpret this as modulation of connectivity by external inputs or task conditions.

Experimental paradigms that maximize the discriminability between the different models

are recommended for DCM (Daunizeau et al., 2011); our task design allowed us to

make discrete comparisons between two factors, each with two levels: image type (i.e.,

scene vs. scrambled color-tile images) and viewing instructions (*free*- vs. *fixed*-viewing).

The state equation for DCM is:

14
$$\dot{z} = (A + \Sigma u_j B^j)z + Cu$$

The intrinsic and baseline interactions between the neuronal states are endogenous

connections and quantified by *A* parameters. These interactions are mediated by

anatomical connections and are irrespective of task conditions (i.e., when the two

conditions are combined). The influences of the task conditions on connectivity between

ROIs are modulatory, and quantified by *B* parameters (i.e., connections altered on *free*-

viewing encoding trials over-and-above all encoding trials). In this study, we used a

mean-centered driving input so that the matrix *A* parameters represented an average

effective connectivity across experimental conditions and matrix *B* modulatory

parameters strengthen or weaken the average connectivity (Zeidman et al., 2019b). The

influences of driving inputs are quantified by *C* parameters (in this case, caused by all

encoding trials).

2.8.1 Individual-level DCM analysis

Our main question of interest asked how unrestricted viewing during scene and

scrambled image encoding modulated the effective connectivity architecture between

the HPC, PPA, and OCP. Due to the increased complexity in interpretation when

including inter-hemispheric connections for DCM (Stephan et al., 2010; Stephan &

Friston, 2010; Zeidman et al., 2019b), we averaged across hemispheres for all models.

Specifically, we configured the full model design with the HPC, PPA, and OCP to

include all self-connections in the *A*-matrix (Figure 2A). Self-connections determine the

excitatory/inhibitory balance within ROIs and provide a biologically-plausible mechanism

for changes in the ROI's activity through the interplay of interneurons and pyramidal

cells (Bastos et al., 2012). We also included reciprocal connections between the PPA

and OCP as well as between the PPA and HPC (Figure 2A) based on prior work

suggesting likely structural connections (Shen et al., 2016). These self-connections and

coupling parameters between ROIs were included in the modulatory *B*-matrix (Figure

2A), allowing us to examine our main research question, i.e., how unrestricted viewing

modulated these connections. For simplicity, we set the input (*C*-matrix) to enter the

earliest ROI in the visual stream (i.e., OCP). We conducted the first-level analysis by

specifying a DCM of the full model design for each subject then estimating the model

parameters, separately for the scene and scrambled encoding conditions. Finally, to

confirm that potential lateralization differences in scene encoding (see e.g., Silson et al.,

2019) would not be missed by averaging across hemispheres, we also modeled the *A*-

and *B*-matrices in the left and right hemispheres separately for the scene encoding

condition only.

Figure 2. Model design for dynamic causal modeling (DCM) showing self- and coupling

parameters for the hippocampus (HPC), parahippocampal place area (PPA) and

occipital pole (OCP). **(A)** Full model estimated using Parametric Bayes (PEB) approach including endogenous (i.e., *A*-matrix) connections shown with black arrows, modulatory (i.e., *B*-matrix) connections shown with green dots, and input (i.e., *C*-matrix) shown with a dotted green line. **(B)** Model space consisting of 7 "families" based on the directionality of modulatory connections, plus the null model (indicated by *), evaluated using Bayesian model selection at the family-wise level. The full model family is indicated by **.

2.8.2 Group-level DCM analysis

After specifying and estimating DCMs at the subject level, we used Parametric Empirical Bayes (PEB) analysis to evaluate group-level effects and between-subjects variability on parameters. PEB assumes that all subjects have the same basic architecture but differ in terms of the strength of connections within that model (Zeidman et al., 2019b).

For the *A*- and *C*-matrices, we then performed model comparison by running an automatic search with Bayesian Model Reduction (BMR). Here, parameters from the PEB model that do not contribute to model evidence are pruned (Penny et al., 2004, 2007). Finally, the parameters from the best reduced models were averaged using Bayesian Model Averaging (BMA) weighted by their evidence, which resulted in the winning models for scene and scrambled image encoding.

To test specific hypotheses about model parameters in the *B*-matrices, we first conducted Bayesian model comparison using a family-wise approach within a predefined model space (Penny et al., 2010; Figure 2B). Specifically, we investigated the effects of modulation by *free*-viewing for each of the two image encoding conditions by specifying a model space consisting of 7 "families" based on the directionality of connections: (1) bottom-up, (2) top-down, (3) bidirectional, (4) self-inhibitory, (5) bottom-up + self-inhibitory, (6) top-down + self-inhibitory, and (7) bidirectional + self-inhibitory. The model space consisted of 128 models, including the full model (in which all self- and between-ROI connections were turned on) and the null model (in which all self- and between-ROI connections were turned off). These models were assessed for evidence using Bayesian model selection at the family-wise level, selecting the family of models with the greatest posterior probability (Pp). Parameters from the winning family of

models were averaged using BMA, which resulted in the final winning models for *free-viewing* modulation of scene and scrambled image encoding.

In line with recommendations on reporting DCM results (see Stephan et al., 2010), here we focused on those parameters in the winning models with a posterior probability (Pp) equal to or greater than 95% (i.e., strong evidence; Kass & Raftery, 1995). Importantly, intrinsic (i.e., self-) connections are inhibitory by definition and are measured on a unitless log scale (Zeidman et al., 2019a) such that positive values reflect more self-inhibition and negative values reflect disinhibition (i.e., increased sensitivity to inputs). Coupling parameters (i.e., between-node connections) are measured in hertz, and so lend themselves to a simpler interpretation: if a connection is positive, then it is excitatory and if the connection is negative, then it is inhibitory.

To investigate the effect of meaningful content on modulatory effective connectivity strengths (Ep), we ran a 2x2 repeated measures ANOVA, specifying main effects and their interactions for image type (scene, scrambled) and DCM connection (OCP, PPA, HPC, OCP to PPA, HPC to PPA, PPA to OCP, PPA to HPC). The model was fit using the "aov_4" function in the *afex* package (Singmann et al., 2024) in R 4.4.2 (R Core Team, 2024). We used individual participants' parameters following PEB procedures, which had been updated using the group-level connection strengths as empirical priors. This facilitated the primary analysis focused on planned pairwise comparisons between scene and scrambled image types within each connection. These comparisons of interest were examined using the "contrast" function in the *emmeans* package (Lenth, 2021). All *p*-values were adjusted by controlling for False Discovery Rate (FDR).

2.8.3 Relationship with retrieval-related measures

In addition to assessing the group-level *B*-matrix modulatory results, we also investigated the relationship of the modulatory connections with two retrieval-related measures with each connection: (1) the average difference in subsequent memory retrieval strength between *free-* and *fixed*-viewing and (2) the average difference in gaze reinstatement similarity between *free-* and *fixed*-viewing. Here, we sought to answer how between-subject differences in recognition memory performance and

memory-related gaze reinstatement for scenes could be explained by the differences in

the excitability or inhibition of ROIs and their coupling parameters during encoding with

unrestricted viewing.

After the fMRI encoding task (see 2.3 Procedure above), participants were given a 60-

minute break before they began a retrieval task in a separate testing room. This post-

scan retrieval task is described in detail in Liu et al. (2020) and is summarized here. All

scene and scrambled images from the fMRI encoding task were tested in the retrieval

task, along with 288 images that were not used in the encoding task as lures (total

images = 864). These images were divided into 6 blocks. In each retrieval trial, a

fixation cross "+" was presented for 1.5 seconds and this cross was presented at the

same location as it was during the encoding task for previously viewed images. Then,

the retrieval image was presented on the screen for 4 seconds. Participants were given

3 seconds to indicate whether the image was "old" or "new" (i.e., previously viewed

during the fMRI task) using 4 keys on the keyboard: z (high confidence, old), x (low

confidence, old), n (high confidence, new) and m (low confidence, new). During the

retrieval task, participants' eye movements were recorded using the Eyelink II head

mounted infrared camera system (SR Research LTD., Ottawa, Ontario, Canada) at a

sampling rate of 500 Hz.

Subsequent memory retrieval strength was calculated as follows: participants'

responses were assigned 2 points to stimuli that were correctly recognized as

previously viewed with high confidence, 1 point to stimuli that were correctly recognized

with low confidence, 0 points to previously viewed stimuli that were incorrectly endorsed

as new with low confidence, and -1 point for previously viewed stimuli that were

incorrectly endorsed as new with high confidence. As described in further detail in Wynn

et al. (2022), the spatial overlap between gaze patterns elicited by the same participants

viewing the same images during encoding and retrieval was quantified into gaze

reinstatement scores. This was done by computing the Fisher *z*-transformed Pearson

correlation between the duration-weighted fixation density map for each image for each

participant during encoding and the corresponding density map for the same image

viewed by the same participant during retrieval (R *eyesim* package:

https://github.com/bbuchsbaum/eyesim; for further details regarding density map

computation, see Wynn et al., 2020). To account for idiosyncratic viewing tendencies

(e.g., participant's tendency to view each image from left to right) we also computed the

similarity between participant- and image-specific retrieval density maps and 50 other

randomly selected encoding density maps from the same participant in the same

condition, yielding an averaged single control score for each participant for each image.

The difference between these two gaze similarity scores reflects gaze reinstatement

similarity, i.e., spatial similarity between encoding and retrieval scanpaths for the same

participant viewing the same image, controlling for idiosyncratic viewing biases.

For each participant, we calculated the difference in the average (i.e., across all trials)

score for memory retrieval strength and gaze reinstatement similarity between *free-* and

fixed-viewing of scenes, which were subsequently mean-centered.

We applied canonical variate analysis (CVA) to model the effect of the modulatory self-

and between-region parameter strengths resulting from the DCM analysis against

memory strength and gaze reinstatement similarity (i.e., retrieval-related measures) with

unrestricted viewing for the scene condition only. In this way, we could assess whether

greater differences in memory performance and gaze reinstatement between *free-* and

fixed-viewing of scenes are associated with stronger modulatory effects during encoding

with unrestricted viewing. CVA allowed dimension reduction of the parameters in the

winning model for the *B*-matrix, so that we could investigate whether the behavioral

measures were associated with the first derived canonical variate. We assessed

canonical loadings (i.e., the correlation between each original variable and the canonical

variates) to determine how variables contribute to each respective canonical variate

while accounting for multicollinearity.

3 Results

For both scene and scrambled models, we found positive driving inputs (i.e., *C*-matrix)

to the OCP (scene: 0.638, $Pp \geq 99\%$; scrambled: 0.173, $Pp \geq 99\%$).

3.1 Endogenous effective connectivity

We first established the winning models of endogenous (i.e., *A*-matrix) effective connectivity for scene and scrambled image encoding using a BMA approach, the results of which can be seen in Figures 3A and 3B, respectively. For scene encoding, we found positive, intrinsic (i.e., self-) connections for all ROIs (HPC: 0.207; PPA: 0.407; OCP: 0.218, *all* Pp $\geq$ 99%). All between-ROI connections were also favored, except for the connection from the PPA to the HPC (Pp = 28%). Specifically, BMA revealed negative top-down coupling parameters from the HPC to PPA (-0.277, Pp $\geq$ 99%) and from the PPA to OCP (-0.657, Pp $\geq$ 99%). Finally, we also found positive, bottom-up connectivity from the OCP to PPA (0.747, Pp $\geq$ 99%). Follow-up analyses in each hemisphere separately revealed no differences in the pattern of endogenous effective connectivity for scene encoding, except for the self-connection of the left HPC, which did not reach the 95% Pp threshold.

For scrambled image encoding, self-connections were found to be negative (i.e., self-disinhibitory) for the PPA (-0.179, Pp = 98%) and positive (i.e., self-inhibitory) for the OCP (0.264, Pp $\geq$ 99%). Note that the HPC self-connection failed to reach the 95% Pp threshold, but was nonetheless highly probable (-0.156, Pp = 93%). We found positive coupling parameters from the HPC to PPA (0.247, Pp $\geq$ 99%) and vice versa (0.235, Pp $\geq$ 99%). BMA did not result in bottom-up connectivity from the OCP to the PPA (0.000, Pp = 15%), instead finding positive top-down coupling from the PPA to OCP (0.125, Pp = 98%).

Figure 3. *A*-matrix (i.e., endogenous) effective connectivity results from Bayesian Model
Averaging (BMA). (A) Scene image encoding model resulting from BMA. (B) Scrambled
image encoding model resulting from BMA. For (A) and (B) self-connections shown in
warm colors (i.e., yellow-red) are positive and reflect greater self-inhibition of the ROI,
whereas self-connections shown in cool colors (i.e., blue) are negative and reflect
greater disinhibition of the ROI. Between-node connections are shown in warm colors
(i.e., yellow-red) for positive coupling parameters, and in cool colors (i.e., blue) for
negative coupling parameters.

3.2 Modulatory connections

After establishing the winning models of endogenous connectivity for scene and
scrambled image encoding, we next assessed family-level evidence for modulatory (i.e.,
B-matrix) effects of *free*-viewing. The winning model family for scene encoding
modulated by *free*-viewing was the family that included self-connections and
bidirectional between-ROI connections (Pp $\geq$ 99%, indicated by ** in Figure 2B). We
found little or no evidence for any other model family for modulatory effects of *free*-
viewing on scene encoding. Likewise, the winning model family for scrambled image
encoding modulated by *free*-viewing also included bidirectional couplings and self-
connections (Pp $\geq$ 99%). We found weak evidence for scrambled image encoding
modulated by *free*-viewing of the top-down + self-inhibitory model family (Pp = 7%). This
is considered low evidence, so this family was not considered in subsequent BMA,
averaging only within the winning model family.

The averaged best candidate models within the winning family for the modulatory effect
of *free*-viewing on scene encoding included all self-connections and all between-ROI
connections, except for the connection from the PPA to the OCP (Figure 4A).
Specifically, we found negative, i.e., self-excitatory, modulation by *free*-viewing on the
OCP (-1.277, Pp $\geq$ 99%), the PPA (-0.744, Pp $\geq$ 99%) and the HPC (-0.867, Pp $\geq$ 99%).
Turning to the coupling parameters, we found a top-down, inhibitory effect of *free*-
viewing on scene encoding from the HPC to the PPA (-2.44, Pp $\geq$ 99%), which did not
extend from the PPA to the OCP (Pp = 21%). Additionally, there was a bottom-up,
positive modulatory effect (i.e., excitatory) of *free*-viewing extending from the OCP to
the PPA (0.346, Pp $\geq$ 99%), and from the PPA to the HPC (0.262, Pp $\geq$ 99%) for scene

encoding. Follow-up analyses in each hemisphere separately revealed no differences in

the pattern of modulatory effective connectivity for scene encoding.

For scrambled image encoding, the averaged best candidate models within the winning

family for the modulatory effect of *free*-viewing included all self-connections and two

between-ROI connections (Figure 4B). Specifically, we found negative (self-excitatory)

modulation by *free*-viewing on the OCP (-0.539, Pp $\geq$ 99%), the PPA (-2.003, Pp $\geq$

99%), and the HPC (-1.102, Pp $\geq$ 99%). Only two coupling parameters (i.e., between-

ROI connections) survived: a top-down, inhibitory effect of *free*-viewing on scrambled

image encoding from the HPC to the PPA (-1.100, Pp $\geq$ 99%), and a bottom-up,

excitatory modulatory effect from the OCP to the PPA (0.241, Pp > 95%).

Figure 4. *B*-matrix (i.e., modulatory effects) effective connectivity results from Bayesian
Model Averaging (BMA). Input (*C*-matrix) is shown with dashed arrows to the occipital
pole (OCP) in both models. (A) Scene image encoding modulated by *free*-viewing
resulting from BMA. (B) Scrambled image encoding modulated by *free*-viewing resulting
from BMA. For (A) and (B) self-connections shown in warm colors (i.e., yellow-red) are
positive and reflect greater self-inhibition of the ROI, whereas self-connections shown in
cool colors (i.e., blue) are negative and reflect greater disinhibition of the ROI. Between-
node connections and inputs are shown in warm colors (i.e., yellow-red) for positive
coupling parameters, and in cool colors (i.e., blue) for negative coupling parameters.

A 2x2 repeated measures ANOVA (image type by DCM connection) on modulatory

effective connectivity strength (Ep) found a main effect of image type ($F_{2.23,78.10}$ =

223.73, *p* < .001), which was qualified by an interaction with DCM connection ($F_{2.13,74.67}$

= 57.79, *p* < .001). Estimated marginal means were calculated for the effect of image

type across each level of DCM connection, summarized in Table 2. For self-

connections, Ep modulated by *free*-viewing was significantly more negative for scenes

compared to scrambled images in the OCP ($p < .001$), reflecting greater self-

disinhibition for scene images. In contrast, Ep modulated by *free*-viewing was

significantly less negative for scenes compared to scrambled images in the PPA ($p <$

$.001$) and in the HPC ($p < .01$), reflecting greater self-inhibition for scene images. For

the coupling parameter from the HPC to the PPA, Ep modulated by *free*-viewing was

significantly more negative (i.e., inhibitory) for scenes compared to scrambled images (p

$< .001$). Finally, Ep was significantly more positively modulated by *free*-viewing in the

coupling parameter from the PPA to the HPC for scenes compared to scrambled

images ($p < .05$). No other comparisons were significant (all ps $> .05$).

Table 2. Differences in estimated marginal means for the effect of image type by DCM
connection. (*indicates $p < .05$)

Contrast (Scene-Scrambled)	Estimate	t-ratio	p
OCP to OCP	-0.728	--4.893	<.001*
PPA to PPA	1.266	18.108	<.001*
HPC to HPC	0.162	3.423	.003*
OCP to PPA	0.105	1.078	.337
PPA to OCP	-0.021	-0.120	.905
PPA to HPC	0.128	2.712	.014*
HPC to PPA	-1.3855	-12.154	<.001*

3.3 Relationship with memory strength and gaze reinstatement

In addition to the average modulatory effect of *free*-viewing on encoding, we were

interested in quantifying the relationship of two retrieval-related measures (average

difference in subsequent memory strength and gaze reinstatement similarity for scenes

encoded in *free*- over *fixed*-viewing conditions) with each DCM modulatory connectivity

parameter. This analysis included modulatory parameters that reached Pp $\geq$ 95% in

BMA. We found that the canonical variate derived from the DCM connectivity

parameters correlated significantly with the canonical variate derived from the retrieval-

related measures [$r = 0.62$ (Pearson's correlation coefficient), $p < .001$], indicating that

38.4% of the shared variance was explained by the first canonical function. Canonical

loadings revealed that greater self-connectivity of the PPA ($r = 0.67$) and HPC ($r = 0.80$)

were the strongest contributors to the canonical variate, explaining 44.7% and 64.3% of

the variance, respectively. This was associated primarily with subsequent memory

strength ($r = 0.89$) but the canonical loading also revealed a moderate contribution of

gaze reinstatement similarity ($r = 0.34$). In other words, greater self-connectivity (i.e.,

less disinhibition, or less receptivity to input from the model) of the PPA and HPC was

significantly associated with greater subsequent memory strength and greater gaze

reinstatement similarity for *free-* compared to *fixed*-viewing of scenes. Importantly, even

when the endogenous (i.e., *A*-matrix) connectivity parameters that reached 95% Pp

were added to the model, greater modulatory self-connectivity of the PPA and HPC

continued to be the strongest contributors to the canonical variate – but not their

endogenous self-connections.

4 Discussion

Memory and gaze behavior are thought to be intricately linked (Ryan & Shen, 2020;

Yarbus, 1967), guiding one another in service of ongoing encoding and retrieval

processes. Thus, the neural architecture of the brain must support rapid, reciprocal

exchange of information between the extended HPC memory and visuo-oculomotor

control systems. Modeling of directed connections in the macaque brain has revealed

likely anatomical pathways from the HPC to visuo-oculomotor systems (Shen et al.,

2016) and also how these connections are functionally relevant to facilitating the flow of

information from the HPC about mnemonic representations to influence visuo-

oculomotor regions (Ryan et al., 2020). Convergent evidence from human neuroimaging

has demonstrated that these systems work together in service of building mental

representations of scenes for later retrieval (Liu et al., 2020) and that information about

patterns of gaze behavior at encoding may be embedded in these mental

representations to be recapitulated at retrieval (Wynn et al., 2022). Critically, however,

evidence for directionality of information flow in humans during encoding within this

reciprocal architecture is so far limited because measures of functional connectivity can

only reveal the degree to which component regions correlate over time. The current

study uses a measure of effective connectivity to provide a non-invasive account for the

directional influences between these systems when new memories are created, and—

for the first time—how unrestricted, naturalistic visual exploration induces changes in

this connectivity. Importantly, the current findings also suggest that this pattern of

effective connectivity modulated by unrestricted viewing predicts subsequent memory

retrieval performance, demonstrating a biologically-plausible model for the mechanism

underlying a rich history of findings starting with seminal work by Loftus (1972) linking

greater gaze fixations to better subsequent memory (Henderson et al., 2005; Liu et al.,

2017; Olsen et al., 2016). Altogether, these findings highlight how gaze behavior shapes

the ways in which brain dynamics within and between the extended HPC memory

system and visuo-oculomotor control system unfold during encoding in humans,

extending earlier neuroimaging findings focused on functional measures of connectivity

(Liu et al., 2020; Wynn et al., 2022).

The PPA is well-connected with regions of the visuo-oculomotor system to receive and

process incoming visuo-spatial information (Baldassano et al., 2013) and may reflect

maintained retinotopic organization along the visual stream (Huang & Sereno, 2013;

Silson et al., 2015). Importantly, prior functional connectivity analyses of the current

dataset revealed that unrestricted visual exploration – compared to when viewing is

restricted – enhances functional activation during scene encoding along the ventral

visual stream and into the PPA (Liu et al., 2020). Extending these findings, here we

show how excitatory effective (i.e., directional) connectivity from early visual cortex to

the PPA is enhanced by unrestricted visual exploration. Specifically, during scene

encoding, we found bottom-up, excitatory endogenous connectivity from the OCP to the

PPA and top-down, inhibitory connectivity from the PPA to the OCP across viewing

conditions. In line with our predictions, *free*-viewing further enhanced this bottom-up

connectivity and also disinhibited self-connections in both the PPA and OCP, thus

increasing the sensitivity of both regions to input coming from the rest of the network

(Bastos et al., 2012). Indeed, the OCP has been implicated in sampling informative

regions at encoding (Fehlmann et al., 2020) and in the formation of gaze scanpaths

(Wynn et al., 2022), suggesting that it may play a role in synchronizing visual

information across different gaze locations which are then integrated into a coherent

mental representation of space at the level of the PPA (Golomb et al., 2011). Increased

excitatory connectivity from early visual cortex to the PPA during *free*-viewing is also

consistent with an interpretation under predictive coding models (e.g., de-Wit et al.,

2010) which suggests that the brain actively anticipates upcoming sensory input rather

than passively registering it. Although we did not explicitly manipulate or measure

predictive errors in the current study, there is mounting evidence that the process of

prediction enhances encoding (Poskanzer et al., 2025), and unrestricted viewing in the

free-viewing condition may have allowed participants to test predictions about what

features should be present within the scenes. In contrast, the inhibitory endogenous

connection from PPA to OCP during scene encoding may represent a suppression of

top-down signal, reflecting a balancing mechanism to instead facilitate the positive,

bottom-up signal towards the extended HPC memory system (Zeidman et al., 2019b).

Alternatively, it could be argued that the pattern of effective connectivity between the

OCP and PPA simply reflects relative differences in attentional or working memory

demands induced by task instructions. However, prior work suggests that maintaining

central fixation (i.e., *fixed*-viewing) does not significantly increase these demands

(Armson et al., 2019), perhaps because participants still move their eyes, albeit with

fewer fixations and smaller saccade amplitudes, consistent with other work in the

literature (Damiano & Walther, 2019; Liu et al., 2020; Welke & Vessel, 2022). Moreover,

in examining the total viewing time that was directed to the scenes, we found that

participants spent as much, if not more, total viewing time looking at the scenes in the

fixed-viewing condition compared to the *free*-viewing condition. If participants had

differentially disengaged their attention from the *fixed*-viewing condition, we may have

expected to see more off-screen viewing behavior, resulting in a lower total duration of

viewing to the scenes. Instead, attentional engagement, operationalized as looking time,

remained comparable during fixed- and *free*-viewing, but the amount of information

extracted through gaze fixations differed.

Within the extended HPC memory system, *free*-viewing during scene encoding

increases connectivity between the PPA and HPC (Liu et al., 2020). Specifically, in line

with our hypotheses, we found that bottom-up modulatory excitatory connectivity driven

by input to the OCP extended to the PPA and ultimately to the HPC, facilitating the flow

of information accumulated during visual exploration into mental representations of

scenes. Neural states of the PPA have recently been tied to both low-level visual features and large-scale spatial locations (Oetringer et al., 2025), making it a prime candidate region for the transfer and processing of visual input towards coherent mental representations. Our results further characterized the modulatory effect of unrestricted viewing on this connective architecture by also identifying a disinhibitory response within the HPC and an inhibitory connection from the HPC to the PPA. One possibility is that increased disinhibition of the HPC, in response to excitatory input from the PPA, may reflect a novelty response to scenes that thereby signals to encode, rather than to strengthen, an existing representation. A similar result was reported by Schott et al. (2023), in which the authors reported self-disinhibition of the HPC in response to input from the PPA during novel scene encoding, and here we show that this input is carried from the early visual cortex in response to unrestricted gaze behavior. At the cellular level, there is evidence that disinhibitory interneurons in specific HPC subfields may contribute to spatial learning (e.g., Turi et al., 2019). Nonetheless, the role of inhibitory/disinhibitory dynamics in the HPC during complex cognitive processes, such as memory encoding, is still a nascent investigation (Tzilivaki et al., 2023). Importantly, self-disinhibition of the HPC and PPA modulated by *free*-viewing was actually weaker for scenes compared to scrambled images suggesting that in order to encode and organize meaningful content in mind, some degree of self-inhibition in these regions is necessary. In other words, relatively less self-disinhibition for scenes may reflect higher levels of internal processing, facilitating a transition from active learning to consolidation processes of existing representations in memory (Büchel et al., 2024). Furthermore, we found inhibitory connectivity during scene encoding modulated by *free*-viewing from the HPC to the PPA, which may support a pattern separation-like mechanism to distinguish between overlapping features of previously viewed scenes within the task (Kirwan & Stark, 2007; Yassa & Stark, 2011). This interpretation could be further interrogated in a future study by explicitly manipulating the visual similarity of trial-adjacent scenes. We would predict greater inhibition of HPC to PPA signal when highly similar scenes are presented together, thereby necessitating greater separation of overlapping features in memory. Altogether, the winning model of scene encoding modulated by *free*-viewing is consistent with the notion that visual exploration supports increased information

exchange between the visuo-oculomotor and extended HPC systems (Shen et al.,

2016; Ryan et al., 2020).

Although we found some similarities in how unrestricted viewing modulated encoding of

scenes and scrambled, color-tile images, there were two notable differences which

warrant closer investigation: (1) endogenous effective connectivity across viewing

conditions for scrambled image encoding was characterized by an excitatory connection

from the PPA to the OCP; and (2) modulatory effective connectivity by unrestricted

viewing did not extend to the HPC for scrambled image encoding. One potential

interpretation of the former finding is that the PPA sends top-down signals to early

visual cortex during scrambled image encoding based on prior knowledge and

expectations about the content of scenes. Indeed, prior work has demonstrated that the

PPA maintains functional responses to scrambled images of scenes (Coggan et al.,

2019; Watson et al., 2017), confirmed in analyses of univariate activation with the

current dataset (Liu et al., 2020). Additionally, in the absence of meaningful visual input,

we previously identified memory-related top-down, excitatory effective connectivity from

the PPA toward early visual cortex during scene construction (Ladyka-Wojcik et al.,

2021). The latter finding lends itself to a more straightforward explanation: excitatory

signals related to unrestricted viewing from the OPC towards the PPA did not extend to

the HPC for scrambled image encoding because there was insufficient relevant visuo-

spatial information to be extracted and bound into mental representations for later

retrieval (Olsen et al., 2012; Yonelinas, 2013). Importantly, this key difference between

scene and scrambled image encoding in the modulatory effect of *free*-viewing speaks to

questions regarding the type of information that is carried via gaze fixations and on

which the HPC operates (Hannula et al., 2010; Ryan, 2024; Voss et al., 2017). Effective

connectivity during encoding may only propagate from the visuo-oculomotor system to

the HPC when gaze behavior extracts meaningful information, such as the spatial and

temporal arrangements of scene features (e.g., Vericel et al., 2024). More broadly, the

visuo-oculomotor system seems to prioritize meaningful scene regions over bottom-up

visual salience, even during tasks for which meaning is irrelevant for behavioral

performance (Peacock et al., 2019). Since the scrambled images were matched to

scene images in terms of low-level features, but lacked coherent spatial structure, it is

likely that the OCP prioritized scene-relevant information that propagated through the

connective architecture from the PPA to the HPC for successful encoding. Looking

beyond the PPA, future studies could examine how effective connectivity of other nodes

within the extended HPC system is dynamically modulated by viewing behavior,

particularly in MTL regions, such as the entorhinal cortex, that are involved in spatial

processing (Fyhn et al., 2004; Killian et al., 2012; Witter & Moser, 2006).

Canonical variate analysis revealed a strong relationship in our data between retrieval-

related measures (i.e., memory strength and gaze reinstatement) and the effective

modulatory parameter resulting from DCM for the *free*-viewing of scenes. The finding of

such a relationship dovetails well with previous findings reported by Wynn et al. (2022)

in which overlapping subsequent memory and gaze reinstatement modulation effects

were found in the HPC memory system and in early visual cortex via cross-voxel brain

pattern similarity analysis. Importantly, this relationship suggests that eye movement

scanpaths at encoding not only facilitate the intake of visual information from our

environment, but also are themselves built into memory representations at the level of

the HPC system such that they can be leveraged to help with later retrieval. A closer

inspection of canonical loadings revealed strong positive contributions of modulatory

self-connections within the HPC and PPA (i.e., less disinhibition) – but not their

endogenous self-connections – towards predicting a greater difference in retrieval-

related performance with unrestricted viewing compared to restricted viewing. At the

cellular level, inhibition during encoding may prevent excessive, runaway outbursts of

postsynaptic activity (Kahan & Foltynie, 2013) and promote the consolidation and

storage of memories for later retrieval (Barron et al., 2017). For example, GABAergic

inhibitory interneurons in the HPC are thought to suppress irrelevant incoming activity to

allow for more refined mnemonic representations (Pelkey et al., 2017) and play a

fundamental role in further organizing these representations (McKenzie, 2018). In the

current study, it may be the case that participants who had less modulatory self-

disinhibition (i.e., greater self-inhibition) in these regions also showed greater

differences in memory and gaze reinstatement for *free*- over *fixed*-viewing because they

suppressed additional, irrelevant incoming visual information as they rapidly encoded

and organized mnemonic representations of meaningful information (Katz et al., 2022).

On the other hand, participants with greater self-disinhibition of the HPC and PPA in response to unrestricted viewing of scenes may show less of a representational shift from encoding incoming visual information about scenes towards consolidation (Büchel et al., 2024). In rodents, co-occurring signals in the HPC during periods of rest associated with replaying past experiences and simulating future actions are thought to help the animal transition towards memory-guided action (Diba & Buzsáki, 2007; Pastalkova et al., 2008) and activity spikes within the HPC may even represent a demarcation of event boundaries between contexts during learning (Bulkin et al., 2020). At a systems-level, however, our understanding as to how the interplay of excitatory and inhibitory activation in the HPC enables encoding and later retrieval still needs greater investigation (Takeuchi et al., 2014). Future work should look to emerging evidence in the rodent literature examining HPC inhibition using encoding paradigms (Topolnik & Tamboli, 2022).

One limitation inherent to DCM approaches for fMRI data is the need to average within- and across-trials due to low temporal resolution, thus restricting the number of data points used to estimate parameters (David et al., 2006, 2008). As such, future work to disentangle the relationship between self- and coupling parameters at encoding with subsequent memory retrieval may benefit from innovative trial-by-trial approaches to DCM, using event-related potentials (see e.g., Asadpour & Wong-Lin, 2025). Trial-by-trial approaches paired with DCM for magnetoencephalography (Kiebel et al., 2009) may be particularly well-suited to our experimental task design, as the relationship between neural dynamics and gaze fixations likely fluctuates within the period of a single trial (Katz et al., 2020).

Furthermore, it should be noted that because DCM analyses are restricted to *a priori* hypothesized ROIs (Stephan et al., 2010), there may be additional higher-level cortical regions contributing to the excitatory-inhibitory balance within the extended HPC memory system that explain the relationship with retrieval-related measures found here. In a similar vein, future investigations could also probe the dynamics of connectivity parameters within subregions of the HPC (Hainmueller et al., 2024; McKenzie, 2018) and along the posterior-anterior axis of the PPA (Baldassano et al., 2013; Watson &

Andrews, 2024), which may be associated with different aspects of subsequent mnemonic retrieval performance.

5 Conclusions

The neural architecture of the human brain must support the reciprocal exchange of information—including just-extracted information from visual exploration and previously stored mental representations—during encoding. In this study, we identified a biologically-plausible pathway in humans, dynamically modulated by gaze behavior, along which scene-relevant features can travel between the early visual cortex and the MTL. Active viewing enhances connections between these systems and predicts subsequent memory and replay of gaze patterns at retrieval. More broadly, our results demonstrate that the extended HPC memory and visuo-oculomotor control systems are intrinsically linked, and their directional interactions support the building of coherent, lasting mental representations.

Data and Code Availability

Analysis scripts and final results matrices are openly available on Open Science Framework (OSF) at https://doi.org/10.17605/OSF.IO/SEUQN. All processed data associated with reported results are available on request from the corresponding author (NLW). The original data is not publicly available due to ethics restrictions at the time of data collection.

Author Contributions

NLW: Conceptualization; Data curation; Formal analysis; Investigation; Methodology; Validation; Visualization; Writing – Original draft; Writing – Review.& editing. ZXL: Conceptualization; Data curation; Formal analysis; Investigation; Supervision; Methodology; Validation; Visualization; Writing – Original draft, Writing – Review & editing. JDR: Conceptualization; Funding acquisition, Project administration; Resources; Supervision; Writing – Original Draft; Writing – Review & editing.

Funding

This work was supported by funding from the Natural Sciences and Engineering Research Council of Canada to JDR (RGPIN-2018-06399), and the Canadian Institutes of Health Research awarded to JDR (MOP126003).

Declaration of Competing Interests

The authors declare no competing financial interest.

Acknowledgements

We would like to thank Arber Kacollja, Sarah Berger, Ling Li, Mandy Ding, Veena Sanmugananthan, Junghyun Nam, Mariam Aziz, and Jordana Wynn for their help at different stages of this research project.

References

Aguirre, G. K., Detre, J. A., Alsop, D. C., & D'Esposito, M. (1996). The Parahippocampus Subserves Topographical Learning in Man. *Cerebral Cortex*, *6*(6), 823–829. https://doi.org/10.1093/cercor/6.6.823

Armson, M. J., Ryan, J. D., & Levine, B. (2019). Maintaining fixation does not increase demands on working memory relative to free viewing. *PeerJ*, *7*, e6839. https://doi.org/10.7717/peerj.6839

Asadpour, A., & Wong-Lin, K. (2025). Effective connectivity predicts distributed neural coding of perceptual decision confidence, uncertainty, and speed. *Imaging Neuroscience*, *3*, imag_a_00441. https://doi.org/10.1162/imag_a_00441

Baldassano, C., Beck, D. M., & Fei-Fei, L. (2013). Differential connectivity within the Parahippocampal Place Area. *NeuroImage*, *75*, 228–237. https://doi.org/10.1016/j.neuroimage.2013.02.073

Barron, H. C., Vogels, T. P., Behrens, T. E., & Ramaswami, M. (2017). Inhibitory engrams in perception and memory. *Proceedings of the National Academy of Sciences*, *114*(26), 6666–6674. https://doi.org/10.1073/pnas.1701812114

Bastos, A. M., Usrey, W. M., Adams, R. A., Mangun, G. R., Fries, P., & Friston, K. J. (2012). Canonical Microcircuits for Predictive Coding. *Neuron*, *76*(4), 695–711. https://doi.org/10.1016/j.neuron.2012.10.038

Bates, D., Mächler, M., Bolker, B., & Walker, S. (2015). Fitting Linear Mixed-Effects Models Using lme4. *Journal of Statistical Software*, *67*(1), Article 1. https://doi.org/10.18637/jss.v067.i01

Büchel, C., & Friston, K. J. (1997). Modulation of connectivity in visual pathways by attention: Cortical interactions evaluated with structural equation modelling and fMRI. *Cerebral Cortex*, *7*(8), 768–778. https://doi.org/10.1093/cercor/7.8.768

Büchel, P. K., Klingspohr, J., Kehl, M. S., & Staresina, B. P. (2024). Brain and eye movement dynamics track the transition from learning to memory-guided action. *Current Biology*, *34*(21), 5054-5061.e4. https://doi.org/10.1016/j.cub.2024.09.063

Bulkin, D. A., Sinclair, D. G., Law, L. M., & Smith, D. M. (2020). Hippocampal state transitions at the boundaries between trial epochs. *Hippocampus*, *30*(6), 582–595. https://doi.org/10.1002/hipo.23180

Castelhano, M. S., & Henderson, J. M. (2007). Initial scene representations facilitate eye movement guidance in visual search. *Journal of Experimental Psychology: Human Perception and Performance*, *33*(4), 753–763. https://doi.org/10.1037/0096-1523.33.4.753

Chicharro, D., & Ledberg, A. (2012). Framework to study dynamic dependencies in networks of interacting processes. *Physical Review E—Statistical, Nonlinear, and Soft Matter Physics*, *86*(4), 041901. https://doi.org/10.1103/PhysRevE.86.041901

Coggan, D. D., Baker, D. H., & Andrews, T. J. (2019). Selectivity for mid-level properties of faces and places in the fusiform face area and parahippocampal place area. *European Journal of Neuroscience*, *49*(12), 1587–1596. https://doi.org/10.1111/ejn.14327

Cohen, N. J., & Eichenbaum, H. (1993). *Memory, amnesia, and the hippocampal system* (pp. xii, 330). The MIT Press.

Damiano, C., & Walther, D. B. (2019). Distinct roles of eye movements during memory encoding and retrieval. *Cognition*, *184*, 119–129. https://doi.org/10.1016/j.cognition.2018.12.014

Daunizeau, J., David, O., & Stephan, K. E. (2011). Dynamic causal modelling: A critical review of the biophysical and statistical foundations. *NeuroImage*, *58*(2), 312–322. https://doi.org/10.1016/j.neuroimage.2009.11.062

David, O., Guillemain, I., Saillet, S., Reyt, S., Deransart, C., Segebarth, C., & Depaulis, A. (2008). Identifying Neural Drivers with Functional MRI: An Electrophysiological Validation. *PLOS Biology*, *6*(12), e315. https://doi.org/10.1371/journal.pbio.0060315

David, O., Kiebel, S. J., Harrison, L. M., Mattout, J., Kilner, J. M., & Friston, K. J. (2006). Dynamic causal modeling of evoked responses in EEG and MEG. *NeuroImage*, *30*(4), 1255–1272. https://doi.org/10.1016/j.neuroimage.2005.10.045

De-Wit, L., Machilsen, B., & Putzeys, T. (2010). Predictive coding and the neural response to predictable stimuli. *Journal of Neuroscience*, *30*(26), 8702-8703. https://doi.org/10.1523/JNEUROSCI.2248-10.2010

Diba, K., & Buzsáki, G. (2007). Forward and reverse hippocampal place-cell sequences during ripples. *Nature Neuroscience*, *10*(10), 1241–1242. https://doi.org/10.1038/nn1961

Eichenbaum, H., Otto, T., & Cohen, N. J. (1994). Two functional components of the hippocampal memory system. *Behavioral and Brain Sciences*, *17*(3), 449–472. https://doi.org/10.1017/S0140525X00035391

Eichenbaum, H., Schoenbaum, G., Young, B., & Bunsey, M. (1996). Functional organization of the hippocampal memory system. *Proceedings of the National Academy of Sciences*, *93*(24), 13500–13507. https://doi.org/10.1073/pnas.93.24.13500

Epstein, R. A., & Baker, C. I. (2019). Scene Perception in the Human Brain. *Annual Review of Vision Science*, *5*, 373–397. https://doi.org/10.1146/annurev-vision-091718-014809

Epstein, R., Harris, A., Stanley, D., & Kanwisher, N. (1999). The Parahippocampal Place Area: Recognition, Navigation, or Encoding? *Neuron*, *23*(1), 115–125. https://doi.org/10.1016/S0896-6273(00)80758-8

Epstein, R., & Kanwisher, N. (1998). A cortical representation of the local visual environment. *Nature*, *392*(6676), 598–601. https://doi.org/10.1038/33402

Epstein, R. A., & Ward, E. J. (2010). How reliable are visual context effects in the parahippocampal place area?. *Cerebral Cortex*, *20*(2), 294-303. https://doi.org/10.1093/cercor/bhp099

Fehlmann, B., Coynel, D., Schicktanz, N., Milnik, A., Gschwind, L., Hofmann, P., Papassotiropoulos, A., & de Quervain, D. J.-F. (2020). Visual Exploration at Higher Fixation Frequency Increases Subsequent Memory Recall. *Cerebral Cortex Communications*, *1*(1), tgaa032. https://doi.org/10.1093/texcom/tgaa032

Fischl, B. (2012). FreeSurfer. *NeuroImage*, *62*(2), 774–781. https://doi.org/10.1016/j.neuroimage.2012.01.021

Friston, K. J., Harrison, L., & Penny, W. (2003). Dynamic causal modelling. *NeuroImage*, *19*(4), 1273–1302. https://doi.org/10.1016/s1053-8119(03)00202-7

Friston, K. J., Kahan, J., Biswal, B., & Razi, A. (2014). A DCM for resting state fMRI. *NeuroImage*, *94*, 396–407. https://doi.org/10.1016/j.neuroimage.2013.12.009

Fyhn, M., Molden, S., Witter, M. P., Moser, E. I., & Moser, M.-B. (2004). Spatial Representation in the Entorhinal Cortex. *Science*, *305*(5688), 1258–1264. https://doi.org/10.1126/science.1099901

Goebel, R., Roebroeck, A., Kim, D.-S., & Formisano, E. (2003). Investigating directed cortical interactions in time-resolved fMRI data using vector autoregressive modeling and Granger causality mapping. *Magnetic Resonance Imaging*, *21*(10), 1251–1261. https://doi.org/10.1016/j.mri.2003.08.026

Golomb, J. D., Albrecht, A. R., Park, S., & Chun, M. M. (2011). Eye Movements Help Link Different Views in Scene-Selective Cortex. *Cerebral Cortex*, *21*(9), 2094–2102. https://doi.org/10.1093/cercor/bhq292

Hainmueller, T., Cazala, A., Huang, L. W., & Bartos, M. (2024). Subfield-specific interneuron circuits govern the hippocampal response to novelty in male mice. *Nature Communications*, *15*, 714. https://doi.org/10.1038/s41467-024-44882-3

Hannula, D. E., Althoff, R. R., Warren, D. E., Riggs, L., Cohen, N. J., & Ryan, J. D. (2010). Worth a Glance: Using Eye Movements to Investigate the Cognitive Neuroscience of Memory. *Frontiers in Human Neuroscience*, *4*, 166. https://doi.org/10.3389/fnhum.2010.00166

Henderson, J. M., Williams, C. C., & Falk, R. J. (2005). Eye movements are functional during face learning. *Memory & Cognition*, *33*(1), 98–106. https://doi.org/10.3758/BF03195300

Hoffman, K. L., Dragan, M. C., Leonard, T. K., Micheli, C., Montefusco-Siegmund, R., & Valiante, T. A. (2013). Saccades during visual exploration align hippocampal 3–8 Hz rhythms in human and non-human primates. *Frontiers in Systems Neuroscience*, *7*. https://doi.org/10.3389/fnsys.2013.00043

Huang, J., Velarde, I., Ma, W. J., & Baldassano, C. (2023). Schema-based predictive eye movements support sequential memory encoding. *eLife*, *12*, e82599. https://doi.org/10.7554/eLife.82599

Huang, R.-S., & Sereno, M. I. (2013). Bottom-up Retinotopic Organization Supports Top-down Mental Imagery. *The Open Neuroimaging Journal*, *7*, 58–67. https://doi.org/10.2174/1874440001307010058

Jutras, M. J., Fries, P., & Buffalo, E. A. (2013). Oscillatory activity in the monkey hippocampus during visual exploration and memory formation. *Proceedings of the National Academy of Sciences of the United States of America*, *110*(32), 13144–13149. https://doi.org/10.1073/pnas.1302351110

Kahan, J., & Foltynie, T. (2013). Understanding DCM: ten simple rules for the clinician. *Neuroimage*, *83*, 542-549. https://doi.org/10.1016/j.neuroimage.2013.07.008

Kass, R. E., & Raftery, A. E. (1995). Bayes Factors. *Journal of the American Statistical Association*, *90*(430), 773–795. https://doi.org/10.2307/2291091

Katz, C. N., Patel, K., Talakoub, O., Groppe, D., Hoffman, K., & Valiante, T. A. (2020). Differential generation of saccade, fixation, and image-onset event-related potentials in the human mesial temporal lobe. *Cerebral Cortex*, *30*(10), 5502-5516. https://doi.org/10.1093/cercor/bhaa132

Katz, C. N., Schjetnan, A. G. P., Patel, K., Barkley, V., Hoffman, K. L., Kalia, S. K., Duncan, K. D., & Valiante, T. A. (2022). A corollary discharge mediates saccade-related inhibition of single units in mnemonic structures of the human brain. *Current Biology*, *32*(14), 3082-3094.e4. https://doi.org/10.1016/j.cub.2022.06.015

Kiebel S. J., Garrido M. I., Moran R., Chen C. C., Friston K. J. (2009). Dynamic causal modeling for EEG and MEG. *Human Brain Mapping*, *30*(6), 1866-76. https://doi.org/10.1002/hbm.20775.

Killian, N. J., Jutras, M. J., & Buffalo, E. A. (2012). A map of visual space in the primate entorhinal cortex. *Nature*, *491*(7426), Article 7426. https://doi.org/10.1038/nature11587

Kirwan, C. B., & Stark, C. E. L. (2007). Overcoming interference: An fMRI investigation of pattern separation in the medial temporal lobe. *Learning & Memory*, *14*(9), 625–633. https://doi.org/10.1101/lm.663507

Knapen, T. (2021). Topographic connectivity reveals task-dependent retinotopic processing throughout the human brain. *Proceedings of the National Academy of Sciences of the United States of America*, *118*(2), e2017032118. https://doi.org/10.1073/pnas.2017032118

Ladyka-Wojcik, N., Liu, Z.-X., & Ryan, J. D. (2022). Unrestricted eye movements strengthen causal connectivity from hippocampal to oculomotor regions during scene construction. *NeuroImage*, *260*(119497). https://doi.org/10.1101/2021.09.23.461606

Liu, Z.-X., Rosenbaum, R. S., & Ryan, J. D. (2020). Restricting Visual Exploration Directly Impedes Neural Activity, Functional Connectivity, and Memory. *Cerebral Cortex Communications*, *1*(tgaa054). https://doi.org/10.1093/texcom/tgaa054

Liu, Z.-X., Shen, K., Olsen, R. K., & Ryan, J. D. (2017). Visual Sampling Predicts Hippocampal Activity. *Journal of Neuroscience*, *37*(3), 599–609. https://doi.org/10.1523/JNEUROSCI.2610-16.2016

Loftus, G. R. (1972). Eye fixations and recognition memory for pictures. *Cognitive Psychology*, *3*(4), 525–551. https://doi.org/10.1016/0010-0285(72)90021-7

Lucas, H. D., Duff, M. C., & Cohen, N. J. (2019). The Hippocampus Promotes Effective Saccadic Information Gathering in Humans. *Journal of Cognitive Neuroscience*, *31*(2), 186–201. https://doi.org/10.1162/jocn_a_01336

Mao, D., Avila, E., Caziot, B., Laurens, J., Dickman, J. D., & Angelaki, D. E. (2021). Spatial modulation of hippocampal activity in freely moving macaques. *Neuron*, *109*(21), 3521-3534.e6. https://doi.org/10.1016/j.neuron.2021.09.032

McIntosh, A. R., & Gonzalez-Lima, F. (1994). Structural equation modeling and its application to network analysis in functional brain imaging. *Human Brain Mapping*, *2*(1–2), 2–22. https://doi.org/10.1002/hbm.460020104

McKenzie, S. (2018). Inhibition shapes the organization of hippocampal representations. *Hippocampus*, *28*(9), 659–671. https://doi.org/10.1002/hipo.22803

Moscovitch, M., Cabeza, R., Winocur, G., & Nadel, L. (2016). Episodic Memory and Beyond: The Hippocampus and Neocortex in Transformation. *Annual Review of Psychology*, *67*, 105–134. https://doi.org/10.1146/annurev-psych-113011-143733

Nikolaev, A. R., Bramão, I., Johansson, R., & Johansson, M. (2023). Episodic memory formation in unrestricted viewing. *NeuroImage*, *266*, 119821. https://doi.org/10.1016/j.neuroimage.2022.119821

Nikolaev, A. R., Meghanathan, R. N., & van Leeuwen, C. (2024). Refixation behavior in naturalistic viewing: Methods, mechanisms, and neural correlates. *Attention, Perception, & Psychophysics*. https://doi.org/10.3758/s13414-023-02836-9

Noton, D., & Stark, L. (1971a). Scanpaths in eye movements during pattern perception. *Science (New York, N.Y.)*, *171*(3968), 308–311. https://doi.org/10.1126/science.171.3968.308

Noton, D., & Stark, L. (1971b). Scanpaths in saccadic eye movements while viewing and recognizing patterns. *Vision Research*, *11*(9), 929-IN8. https://doi.org/10.1016/0042-6989(71)90213-6

Oetringer, D., Gözükara, D., Güçlü, U., & Geerligs, L. (2025). The neural basis of event segmentation: Stable features in the environment are reflected by neural states. Imaging Neuroscience, 3, imag_a_00432. https://doi.org/10.1162/imag_a_00432

Olsen, R. K., Moses, S. N., Riggs, L., & Ryan, J. D. (2012). The hippocampus supports multiple cognitive processes through relational binding and comparison. *Frontiers in Human Neuroscience*, *6*. https://doi.org/10.3389/fnhum.2012.00146

Olsen, R. K., Sebanayagam, V., Lee, Y., Moscovitch, M., Grady, C. L., Rosenbaum, R. S., & Ryan, J. D. (2016). The relationship between eye movements and subsequent recognition: Evidence from individual differences and amnesia. *Cortex*, *85*, 182–193. https://doi.org/10.1016/j.cortex.2016.10.007

Pastalkova, E., Itskov, V., Amarasingham, A., & Buzsáki, G. (2008). Internally Generated Cell Assembly Sequences in the Rat Hippocampus. *Science*, *321*(5894), 1322–1327. https://doi.org/10.1126/science.1159775

Pastalkova, E., Itskov, V., Amarasingham, A., & Buzsáki, G. (2008). Internally Generated Cell Assembly Sequences in the Rat Hippocampus. *Science*, *321*(5894), 1322–1327. https://doi.org/10.1126/science.1159775

Peacock, C. E., Hayes, T. R., & Henderson, J. M. (2019). Meaning guides attention during scene viewing, even when it is irrelevant. *Attention, Perception, & Psychophysics*, *81*, 20-34. https://doi.org/10.3758/s13414-018-1607-7

Pelkey, K. A., Chittajallu, R., Craig, M. T., Tricoire, L., Wester, J. C., & McBain, C. J. (2017). Hippocampal GABAergic Inhibitory Interneurons. *Physiological Reviews*, *97*(4), 1619–1747. https://doi.org/10.1152/physrev.00007.2017

Penny, W. D., Mattout, J., & Trujillo-Barreto, N. J. (2007). Bayesian Model Selection and Averaging. In *Statistical Parametric mapping: The analysis of functional brain images* (pp. 454–467). Academic Press, Ltd. https://research.manchester.ac.uk/en/publications/bayesian-model-selection-and-averaging

Penny, W. D., Stephan, K. E., Daunizeau, J., Rosa, M. J., Friston, K. J., Schofield, T. M., & Leff, A. P. (2010). Comparing Families of Dynamic Causal Models. *PLOS Computational Biology*, *6*(3), e1000709. https://doi.org/10.1371/journal.pcbi.1000709

Penny, W. D., Stephan, K. E., Mechelli, A., & Friston, K. J. (2004). Comparing dynamic causal models. *NeuroImage*, *22*(3), 1157–1172. https://doi.org/10.1016/j.neuroimage.2004.03.026

Poskanzer, C., Tarder-Stoll, H., Javid, R., Spolaore, E., & Aly, M. (2025). Successful prediction is associated with enhanced encoding. *PsyArXiv*. https://doi.org/10.31234/osf.io/scrxq_v2

Ramey, M. M., Yonelinas, A. P., & Henderson, J. M. (2020). Why do we retrace our visual steps? Semantic and episodic memory in gaze reinstatement. *Learning & Memory*, *27*(7), 275–283. https://doi.org/10.1101/lm.051227.119

Robinson, D. A. (1986). The systems approach to the oculomotor system. *Vision Research*, *26*(1), 91–99. https://doi.org/10.1016/0042-6989(86)90073-8

Robinson, D. A., & Optican, L. M. (1981). Adaptive Plasticity in the Oculomotor System. In H. Flohr & W. Precht (Eds.), *Lesion-Induced Neuronal Plasticity in Sensorimotor Systems* (pp. 295–304). Springer. https://doi.org/10.1007/978-3-642-68074-8_25

Ryan, J. D. (2024). Memory: Using the past to anticipate the future. *Current Biology*, *34*(23), R1177–R1179. https://doi.org/10.1016/j.cub.2024.10.056

Ryan, J. D., Althoff, R. R., Whitlow, S., & Cohen, N. J. (2000). Amnesia is a Deficit in Relational Memory. *Psychological Science*, *11*(6), 454–461. https://doi.org/10.1111/1467-9280.00288

Ryan, J. D., Hannula, D. E., & Cohen, N. J. (2007). The obligatory effects of memory on eye movements. *Memory*, *15*(5), 508–525. https://doi.org/10.1080/09658210701391022

Ryan, J. D., & Shen, K. (2020). The eyes are a window into memory. *Current Opinion in Behavioral Sciences*, *32*, 1–6. https://doi.org/10.1016/j.cobeha.2019.12.014

Ryan, J. D., Shen, K., Kacollja, A., Tian, H., Griffiths, J., Bezgin, G., & McIntosh, A. R. (2020). Modeling the influence of the hippocampal memory system on the oculomotor system. *Network Neuroscience*, *4*(1), 217–233. https://doi.org/10.1162/netn_a_00120

Schott, B. H., Soch, J., Kizilirmak, J. M., Schütze, H., Assmann, A., Maass, A., Ziegler, G., Sauvage, M., & Richter, A. (2023). Inhibitory temporo-parietal effective connectivity is associated with explicit memory performance in older adults. *iScience*, *26*(10). https://doi.org/10.1016/j.isci.2023.107765

Schuyler, B., Ollinger, J. M., Oakes, T. R., Johnstone, T., & Davidson, R. J. (2010). Dynamic Causal Modeling applied to fMRI data shows high reliability. *NeuroImage*, *49*(1), 603–611. https://doi.org/10.1016/j.neuroimage.2009.07.015

Sharot, T., Davidson, M. L., Carson, M. M., & Phelps, E. A. (2008). Eye Movements Predict Recollective Experience. *PLOS ONE*, *3*(8), e2884. https://doi.org/10.1371/journal.pone.0002884

Shen, K., Bezgin, G., Selvam, R., McIntosh, A. R., & Ryan, J. D. (2016). An Anatomical Interface between Memory and Oculomotor Systems. *Journal of Cognitive Neuroscience*, *28*(11), 1772–1783. https://doi.org/10.1162/jocn_a_01007

Silson, E. H., Chan, A. W.-Y., Reynolds, R. C., Kravitz, D. J., & Baker, C. I. (2015). A Retinotopic Basis for the Division of High-Level Scene Processing between Lateral and Ventral Human Occipitotemporal Cortex. *Journal of Neuroscience*, *35*(34), 11921–11935. https://doi.org/10.1523/JNEUROSCI.0137-15.2015

Snyder, A. D., Ma, L., Steinberg, J. L., Woisard, K., & Moeller, F. G. (2021). Dynamic causal modeling self-connectivity findings in the functional magnetic resonance imaging neuropsychiatric literature. *Frontiers in Neuroscience*, *15*, 636273. https://doi.org/10.3389/fnins.2021.636273

Spunt, B. (2019). *GUI-based MATLAB software for optimizing the design of fMRI tasks: Spunt/easy-optimize-x* [MATLAB]. https://github.com/spunt/easy-optimize-x

Stephan, K. E., & Friston, K. J. (2010). Analyzing effective connectivity with fMRI. *Wiley Interdisciplinary Reviews. Cognitive Science*, *1*(3), 446–459. https://doi.org/10.1002/wcs.58

Stephan, K. E., Harrison, L. M., Kiebel, S. J., David, O., Penny, W. D., & Friston, K. J. (2007). Dynamic causal models of neural system dynamics: Current state and future extensions. *Journal of Biosciences*, *32*(1), 129–144. https://doi.org/10.1007/s12038-007-0012-5

Stephan, K. E., Penny, W. D., Moran, R. J., den Ouden, H. E. M., Daunizeau, J., & Friston, K. J. (2010). Ten simple rules for dynamic causal modeling. *Neuroimage*, *49*(4), 3099–3109. https://doi.org/10.1016/j.neuroimage.2009.11.015

Takeuchi, T., Duszkiewicz, A. J., & Morris, R. G. M. (2014). The synaptic plasticity and memory hypothesis: Encoding, storage and persistence. *Philosophical Transactions of the Royal Society B: Biological Sciences*, *369*(1633), 20130288. https://doi.org/10.1098/rstb.2013.0288

Topolnik, L., & Tamboli, S. (2022). The role of inhibitory circuits in hippocampal memory processing. *Nature Reviews Neuroscience*, *23*(8), 476-492. https://doi.org/10.1038/s41583-022-00599-0

Tullo, M. G., Almgren, H., Van de Steen, F., Boccia, M., Bencivenga, F., & Galati, G. (2023). Preferential signal pathways during the perception and imagery of familiar scenes: An effective connectivity study. *Human Brain Mapping*, *44*(10), 3954–3971. https://doi.org/10.1002/hbm.26313

Turi, G. F., Li, W.-K., Chavlis, S., Pandi, I., O'Hare, J., Priestley, J. B., Grosmark, A. D., Liao, Z., Ladow, M., Zhang, J. F., Zemelman, B. V., Poirazi, P., & Losonczy, A. (2019). Vasoactive Intestinal Polypeptide-Expressing Interneurons in the Hippocampus Support Goal-Oriented Spatial Learning. *Neuron*, *101*(6), 1150-1165.e8. https://doi.org/10.1016/j.neuron.2019.01.009

Tzilivaki, A., Tukker, J. J., Maier, N., Poirazi, P., Sammons, R. P., & Schmitz, D. (2023). Hippocampal GABAergic interneurons and memory. *Neuron*, *111*(20), 3154–3175. https://doi.org/10.1016/j.neuron.2023.06.016

Vericel, M. E., Baraduc, P., Duhamel, J.-R., & Wirth, S. (2024). Organizing space through saccades and fixations between primate posterior parietal cortex and hippocampus. *Nature Communications*, *15*(1), 10448. https://doi.org/10.1038/s41467-024-54736-7

Voss, J. L., Bridge, D. J., Cohen, N. J., & Walker, J. A. (2017). A Closer Look at the Hippocampus and Memory. *Trends in Cognitive Sciences*, *21*(8), 577–588. https://doi.org/10.1016/j.tics.2017.05.008

Warren, D. E., Duff, M. C., Tranel, D., & Cohen, N. J. (2011). Observing degradation of visual representations over short intervals when medial temporal lobe is damaged. *Journal of Cognitive Neuroscience*, *23*(12), 3862–3873. https://doi.org/10.1162/jocn_a_00089

Watson, D. M., & Andrews, T. J. (2024). Mapping the functional and structural connectivity of the scene network. *Human Brain Mapping*, *45*(3), e26628. https://doi.org/10.1002/hbm.26628

Watson, D. M., Hartley, T., & Andrews, T. J. (2017). Patterns of response to scrambled scenes reveal the importance of visual properties in the organization of scene-selective cortex. *Cortex*, *92*, 162–174. https://doi.org/10.1016/j.cortex.2017.04.011

Welke, D., & Vessel, E. A. (2022). Naturalistic viewing conditions can increase task engagement and aesthetic preference but have only minimal impact on EEG quality. *NeuroImage*, *256*, 119218. https://doi.org/10.1016/j.neuroimage.2022.119218

Willenbockel, V., Sadr, J., Fiset, D., Horne, G. O., Gosselin, F., & Tanaka, J. W. (2010). Controlling low-level image properties: The SHINE toolbox. *Behavior Research Methods*, *42*(3), 671–684. https://doi.org/10.3758/BRM.42.3.671

Witter, M. P., & Moser, E. I. (2006). Spatial representation and the architecture of the entorhinal cortex. *Trends in Neurosciences*, *29*(12), 671–678. https://doi.org/10.1016/j.tins.2006.10.003

Wynn, J. S., Liu, Z.-X., & Ryan, J. D. (2022). Neural Correlates of Subsequent Memory-Related Gaze Reinstatement. *Journal of Cognitive Neuroscience*, *34*(9), 1547–1562. https://doi.org/10.1162/jocn_a_01761

Wynn, J. S., Ryan, J. D., & Buchsbaum, B. R. (2020). Eye movements support behavioral pattern completion. *Proceedings of the National Academy of Sciences*, *117*(11), 6246–6254. https://doi.org/10.1073/pnas.1917586117

Wynn, J. S., Shen, K., & Ryan, J. D. (2019). Eye Movements Actively Reinstate Spatiotemporal Mnemonic Content. *Vision*, *3*(2), Article 2. https://doi.org/10.3390/vision3020021

Yarbus, A. L. (1967). *Eye Movements and Vision*. Springer US. https://doi.org/10.1007/978-1-4899-5379-7

Yassa, M. A., & Stark, C. E. L. (2011). Pattern separation in the hippocampus. *Trends in Neurosciences*, *34*(10), 515–525. https://doi.org/10.1016/j.tins.2011.06.006

Yonelinas, A. P. (2013). The hippocampus supports high-resolution binding in the service of perception, working memory and long-term memory. *Behavioural Brain Research*, *254*, 34–44. https://doi.org/10.1016/j.bbr.2013.05.030

Zeidman, P., Jafarian, A., Corbin, N., Seghier, M. L., Razi, A., Price, C. J., & Friston, K. J. (2019). A guide to group effective connectivity analysis, part 1: First level analysis with DCM for fMRI. *NeuroImage*, *200*, 174–190. https://doi.org/10.1016/j.neuroimage.2019.06.031

Zeidman, P., Jafarian, A., Seghier, M. L., Litvak, V., Cagnan, H., Price, C. J., & Friston, K. J. (2019). A guide to group effective connectivity analysis, part 2: Second level analysis with PEB. *NeuroImage*, *200*, 12–25. https://doi.org/10.1016/j.neuroimage.2019.06.032