1   **Boosting Hyperalignment Performance with Age-specific Templates**

2   **Yuqi Zhang**
3   Dartmouth College

4   **Maria Ida Gobbini**
5   University of Bologna

6   **James V. Haxby***
7   Dartmouth College

8   **Ma Feilong***
9   Dartmouth College
10   University of South Carolina

11   *: These authors contributed equally.

12   **Abstract**

Hyperalignment aligns individual brain activity and functional connectivity patterns to a common,
high-dimensional   model   space,   resolving   idiosyncrasies   in   functional–anatomical
correspondence and revealing shared information encoded in fine-grained spatial patterns. Given
that the brain undergoes significant developmental and functional changes over the lifespan, it
is likely that certain features in brain functional organization are more prominent in certain age
groups than others. In this study, we examined whether age-specific functional templates, as
compared to a canonical template, could enhance alignment accuracy across diverse age groups.
We used the Cambridge Centre for Ageing and Neuroscience (Cam-CAN) dataset (18 to 87 yo) to
build age-specific templates and tested their performance for analyzing data in young and old
brains in both the Cam-CAN dataset and the Dallas Lifespan Brain Study (DLBS) dataset (20 to 90
yo). We found the congruent age-specific template outperforms the incongruent template for
various analyses, including inter-subject correlation of hyperaligned connectivity profiles and
predicting individualized connectomes and brain responses to the movie using the template. The
results are consistent across both datasets. This work enhances our understanding of age-
related differences in brain function, highlights the benefits of creating age-specific templates to
refine hyperalignment model performance, and may contribute to the development of age-
sensitive diagnostic tools and interventions for neurological disorders.
30
31   **Keywords:** fMRI, hyperalignment, brain aging, individual differences, functional connectivity

32   **Introduction**

Information encoded in the cortex can be decoded from fine-grained patterns of cortical activity via
multivariate pattern analysis of fMRI data (Haxby et al., 2001, 2014). However, there is considerable
variability across individual brains when encoding the same information (Cox & Savoy, 2003). Traditional
approaches to brain alignment often fail to capture the fine-grained functional correspondence between
brains due to topographic variability. Hyperalignment is a computational approach for modeling how the
brain encodes shared information across individuals, despite individual variability in cortical topographies

(Haxby et al., 2011, 2020). Hyperalignment can be trained using either brain responses (Haxby et al.,
2011; Guntupalli et al., 2016) or functional connectivity (Guntupalli et al., 2018), and it captures both
shared coarse- and fine-scale information encoded in the brain. This approach also enhances the
reliability of individual differences by affording analysis of differences in the fine-grained structure of the
functional connectome (Feilong et al., 2018, 2021).
44
Given that the brain undergoes substantial developmental, structural, and functional changes across the
lifespan, brain functional organization may demonstrate age-specific features that are not prominent in
other age groups. These age-related variations can impact the alignment of neural data across
individuals. Consequently, the performance of hyperalignment models in human connectomics may be
significantly influenced by the age of the individuals used to build the templates. In this study, we
investigate whether the incorporation of age-specific templates enhances the performance of
hyperalignment models. Examining this aspect could not only improve hyperalignment accuracy across
diverse age groups but also inform age-sensitive intervention strategies. Individual differences in the
brain arise from both aging and neurological diseases and brain injuries. This knowledge also could open
new pathways for creating more effective diagnostic tools for neurological disorders (Anderson et al.,
2021, 2024).
56
We investigated this problem by developing age-specific hyperalignment templates using the Cambridge
Centre for Ageing and Neuroscience (Cam-CAN) dataset and evaluating their performance with three
indices: (a) inter-subject correlation (ISC) of connectomes, (b) prediction accuracy of individualized
connectomes, and (c) prediction accuracy of individualized brain responses to the movie. Across all three
analyses, we found consistent advantages of congruent age-specific templates (i.e., those constructed
using data from the same age group) over incongruent templates. Together, these results demonstrate
the importance of accounting for age-specific features of brain functional organization when applying
functional alignment methods.

Methods

fMRI dataset

The Cambridge Centre for Ageing and Neuroscience (Cam-CAN) dataset comprises fMRI data of over
600 people from a cross-sectional adult lifespan (18 to 87 years old) population-based sample, with
approximately 25 minutes of fMRI data per individual (Taylor et al., 2017). All MRI datasets were collected
at MRC-CBSU using a 3T Siemens TIM Trio Scanner with a 32-channel head coil, $3.0 \times 3.0 \times 4.44$ mm^3
voxels and 20% gap. Each individual's fMRI data were collected during three different tasks:
1. 8 minutes 40 seconds of resting state with eyes closed ('rest');
2. 8 minutes of movie-watching of the film "Bang! You're dead" ('bang');
3. 8 minutes 40 seconds of a sensorimotor task ('smt') during which participants were asked to press
a button upon the presentation of a visual and/or auditory stimulus.
Both resting state and the sensorimotor task used single echo sequences with TR = 1970 ms, TE = 30
ms, flip angle = 78°, and the movie-watching task used multi-echo sequences with TR = 2470 ms, TEs =
9.4, 21.2, 33, 45, 57 ms, flip angle = 78°. 646 participants have the full records of all three functional
scans (age distribution shown in Table 1).

We classified the participants into three different age groups—young, mid, and old—with each group consisting of approximately the same number of individuals. Our analyses focus on the young and old groups.

Table 1. Age group division and corresponding training/test set sizes

Age Group	Age Range	Number of Participants	Training Group	Test Group
Young	18–45	215	144	71
Old	65–90	216	144	72

Preprocessing

We preprocessed all MRI data using fMRIPrep (Esteban et al., 2019), with version 20.2.7. For each participant, the cortical surface was reconstructed using the high-resolution structural scans. The functional data were corrected for head motion, projected onto the cortical surface model, and resampled to the onavg-ico32 cortical surface template, which uniformly samples different parts of the cortex (Feilong et al., 2024). After that, we used linear regression to partial out nuisance regressors from our data. The list of nuisance regressors includes 6 head motion parameters and their derivatives, framewise displacement, global signal, 6 aCompCor components from cerebrospinal fluid and white matter, and polynomial trends up to the 2nd order. After the regression, we normalized the time series of each cortical vertex to zero mean and unit variance.

Individual connectome calculation

We computed two kinds of connectomes based on different functional scans:

1. using both resting state and sensorimotor task data,
2. using movie-watching data,

This division allows us to examine template performance using both functional connectivity and response time series to the movie. To calculate functional connectivity, we downsampled the data matrices for each individual and each task from 'onavg-ico32' space (19341 vertices) to 'onavg-ico8' space (1210 vertices) and used the time-series for downsampled data as connectivity targets. Correlations between connectivity target time-series and vertex time-series are indices of functional connectivity. Each vertex's connectivity profile is a vector of 1210 elements, where each element is the correlation between the time series of the vertex and the time series of a connectivity target. We z-scored the connectivity profile for each of the 19341 vertices, and these connectivity profiles collectively form the connectome matrix of the individual and task.

Hyperalignment template creation

For each age group (young and old), we built the templates using approximately two thirds of the participants and withheld the remaining one third for testing. Given there are multiple ways to choose the participants, we repeated the procedure 10 times, each time randomly choosing two thirds of the participants without replacement. The participants used for evaluation were always independent from the participants used for training.

We combined fMRI data of different tasks to maximize the amount of data we use to compute the connectomes, given that differences in connectomes based on different tasks are much smaller in scale compared to individual differences (Gratton et al., 2018). Each whole brain template was created using a searchlight-based algorithm (Feilong et al., 2023, section 4.2) with a 20 mm searchlight radius, based on the training group participants' connectome data calculated from the resting state data and sensorimotor task data. There are 19341 overlapping searchlights, each containing an average of approximately 121 vertices (range: 44 to 187). For each searchlight, we created a local template so that its representational geometry and topographies are representative of the training participants. We first concatenated the vertices of all participants and performed a PCA on the concatenated data, to derive a PC template that reflects the representational geometry of the searchlight, where $M_{(PC)}$ is the PC template, $B_{(p)}$ is the local data matrix of the p-th participant, and n is the number of participants.

$$M_{(PC)} = \frac{1}{\sqrt{n}}\text{PCA}(B_{(1)}, \ldots, B_{(n)})$$

We then applied a rotational matrix R to the PC template to minimize the topographic differences without changing the information content, where $\|\cdot\|_F$ is the Frobenius norm.

$$R = \arg\min_{R} \sum_{p=1}^{n} \left\| M_{(PC)}R - B_{(p)} \right\|_F^2$$

To find the solution R, we applied the orthogonal Procrustes algorithm to concatenated data matrices (see formula below).

$$R = \arg\min_{R} \left\| \begin{bmatrix} B_{(1)} \\ \vdots \\ B_{(n)} \end{bmatrix} - \begin{bmatrix} M_{(PC)} \\ \vdots \\ M_{(PC)} \end{bmatrix} R \right\|_F^2$$

132
133

The local templates $M_{(PC)}R$ searchlights were then combined to form the whole-brain template. For each participant p, we derived two transformation matrices using Procrustes algorithm: $R_{(p)}$, which projects data from the participant's native cortical space to the template space and was used in inter-subject correlation (ISC) analyses, and $R'_{(p)}$, which projects data from the template space back to the participant's native cortical space and was used in the prediction analyses (Figure 1, see also Supplementary Figure 1). Note that these matrices differ from the rotation matrix R used to derive the local template.

Given that functional connectomes may differ across tasks, for each template based on resting state and sensorimotor data, we also computed a corresponding template based on the movie-viewing data. This was used in the analysis of predicting individual connectomes, as described below.

145 Figure 1: Schematic of the procedure for building and testing hyperalignment templates. Darker arrows
146 indicate congruent templates (i.e., from the same age group), whereas light arrows indicate incongruent
147 templates.

Inter-subject correlation (ISC)

We computed the inter-subject correlation (ISC) of connectivity profiles in the common model space to
evaluate template performance, where higher ISCs indicate better performance. For each participant in
the test set, we computed the participant's hyperalignment transformation matrix $R_{(p)}$ using the
connectome based on resting state and sensorimotor task data, and applied the transformation matrix to
the original movie-watching responses to compute the hyperaligned connectome. This ensures that the
data used to compute hyperalignment transformation are independent from the data used to evaluate
performance. We computed ISC as the correlation between the participant's connectivity profile and the
average profile across other test participants in the same age group (Figure 1). Each participant has up
to 20 ISC maps (10 young templates and 10 old templates), and we averaged ISC maps of the same
kind (young or old) for each participant. We converted *r* values to *z* values (Fisher transform, arctanh(r)),
averaged the *z* values, and converted them back to *r* values. Based on the analysis, we either averaged
them across cortical vertices (Figures 2a, 2b, Supplementary 3a, 3b) or participants of the same age
group (Figures 2c, Supplementary 3c).

Predicting individual connectome

We also tested the prediction of connectomes in held-out test participants' native anatomical space
(Figure 1). We derived each participant's predicted movie-viewing connectome as the matrix
multiplication of the movie-viewing template and the individual's transformation matrix $R'_{(p)}$, derived from
resting state and sensorimotor task data. We then compared the predicted connectome with the
participant's actual movie-viewing connectome based on the correlation of the corresponding connectivity
profiles in these two connectomes.

Predicting individual responses to the movie

Similarly, we predicted individual responses to the movie using the same templates created for the
congruent and incongruent age groups. Using the Individualized Neural Tuning (INT) model (Feilong et
al., 2023), each individual's connectome was modeled as the same template connectome with an
individualized transformation, and we established correspondence between the modeled connectome
and the brain responses to the movie using the same group of training participants used to build the
template. In other words, we applied the INT model to enrich the template so that it could predict
individualized brain responses in addition to individualized connectomes based on the template. We then
evaluated the template's performance using correlation coefficients between the measured response
time series to the movie and the predicted time series.

Validation dataset

The results based on the Cam-CAN dataset demonstrate that hyperalignment templates from the same
age group work better than templates from age-incongruent templates, and this effect generalizes across
tasks (from resting state and sensorimotor to movie-watching) and scan protocols (from single-echo
sequences to multi-echo sequences). We further tested the generalizability of our results using an
independent dataset—the DLBS dataset (Park et al., 2025), which was collected with a different scanner,
a different group of participants, and different tasks (See Supplementary).

                                                              Results

We evaluated the performance of the templates using three metrics: (a) ISC of functional connectivity in
the common template space, where higher ISCs indicate better alignment of connectivity in the template
space; (b) similarity between model-predicted and measured connectomes in each participant's native
anatomical space; and (c) similarity between model-predicted and measured neural responses to the
movie, where higher similarity suggests the template contains more relevant information and better
predicts individualized connectomes and movie responses. Across all metrics, we found that congruent
age-specific templates outperformed age-incongruent templates.

Inter-subject correlation
We first evaluated the performance of templates constructed from both young and old age groups on
ISCs of connectomes in the common model template space. We computed the z-difference (difference
in Fisher z transformed correlations) between post-alignment ISC values derived from congruent and
incongruent templates (Figure 2a). Hyperalignment based on congruent age-specific templates yields
higher ISCs in both age groups, with a more pronounced effect in the young group. Breaking down the
data by participant, we found that most participants (97.6% in the young group, 74.2% in the old group)
exhibited higher ISCs when comparing the results for congruent and incongruent templates (Figure 2b).
We also evaluated the ISC performance of an intermediate middle-aged cohort using a middle-aged
template; these results are provided in Supplementary Figure 4. The topography of mean ISC differences
displayed in Figure 2c illustrate that congruent templates perform better in the frontal, temporal, and
parietal lobes. The ISC for the young group was consistently higher than that for the old group for both
congruent and incongruent templates. This reflects, at least in part, differences in data quality between
the two age groups (Supplementary Figure 2).

Figure 2: Inter-subject Correlation Results (Cam-CAN). (a) The average z (± SD) for the old group was
0.6897 ± 0.0759 for congruent templates and 0.6700 ± 0.0839 for incongruent templates. The mean ISC
difference (± SE) was 0.0197 ± 0.0017, $t(212)$ = 11.33, Cohen's d = 0.7766 and $p < 10^{-22}$. The average z
(± SD) for the young group was 0.8566 ± 0.1151 for congruent templates, and 0.8337 ± 0.1069 for
incongruent templates. The mean ISC difference (± SE) was 0.0229 ± 0.0008, $t(209)$ = 30.09, Cohen's d
= 2.0765 and $p < 10^{-77}$. (b) Scatter plot of each participant's average ISC value derived from different

congruent and incongruent templates. (c) Topographic distribution of ISC difference across different brain
regions.

Predicting connectomes
Higher ISCs can arise from both (a) better alignment across participants and (b) filtering out noise during
hyperalignment transformations. Though it is unlikely that our ISC results were driven by reduced noise,
to rule out the possibility, we assessed how well different templates predict each participant's
connectome.

For each individual, we calculated the correlation between the predicted connectome, generated using
young and old training group hyperalignment templates calculated with rest and smt fMRI data, and the
actual connectome, calculated using movie watching fMRI data. A higher correlation indicates a more
accurate prediction, which means better performance of the hyperalignment template.

We compared the performance of congruent templates (built from the same age group) and incongruent
templates (built from a different age group). For each participant in the test sets of both age groups, we
calculated the predicted connectome using 20 templates—10 from each age group. We then computed
the correlation for each participant and averaged the individual results across templates in the same age
group. Figure 3a shows the z-difference between correlations calculated using congruent and
incongruent templates for each participant in both groups. The results clearly indicate that predictions
using congruent templates are more accurate than those using incongruent templates. Examining the
participant breakdown in Figure 3b, we observed that almost all participants (98.6% in the young group
and 94.4% in the old group) have a better connectome prediction using congruent templates than using
incongruent templates from the other group. Additional results predicting the fine-grained connectome
for the middle-aged cohort using the middle-aged template are detailed in Supplementary Figure 5. We
also evaluated connectome prediction accuracies using templates constructed from 10-year age
increments. The results show a continuous gradient of age-related divergence (Supplementary Figure
6). When predicting data for the 80–90 cohort, the 20–30 template performs the worst and the
performance steadily improves as the template age gets closer to the target demographic. This
systematic gradient further supports our main finding: the penalty for using an incongruent template
increases with the discrepancy between the template age and participant age. The topographic
distribution of mean differences between the predicted connectomes using congruent and incongruent
templates are displayed in Figure 3c. Congruent templates generally perform better in the frontal and
parietal lobes—regions primarily responsible for cognitive functions—which can be significantly
influenced by age.

Figure 3: Prediction performance comparison between congruent and incongruent templates. (a) The average z (± SD) for the old group was 0.4279 ± 0.0558 for congruent templates, and 0.4126 ± 0.0597 for incongruent templates. The mean difference of predicted connectome (± SE) was 0.0154 ± 0.0007, $t(212)$ = 21.91, Cohen's d = 1.5014 and $p < 10^{-55}$. The average z (± SD) for the young group was 0.5716 ± 0.0779 for congruent templates, and 0.5568 ± 0.0743 for incongruent templates. The mean difference of predicted connectome (± SE) was 0.0147 ± 0.0004, $t(209)$ = 39.07, Cohen's d = 2.6963 and $p < 10^{-97}$. (b) Scatter plot of each participant's average correlation value derived from different congruent and incongruent templates. (c) Topographic correlation difference across different brain regions.

To evaluate the influence of age on the performance of hyperalignment template across the entire lifespan, we computed the correlation between actual connectome and predicted connectome of all participants using both young templates and old templates. As an individual's age becomes more distant from the template age group, the relative performance of the template decreases (Figure 4a, 4b).

Overall, congruent age-specific templates better predict participants' connectomes than incongruent templates. As the participant's age diverges further from the template age group, the prediction accuracy gets worse. This result indicates that age independent templates are necessary for improving the performance of hyperalignment.

Figure 4: Comparison of individual connectome prediction across all age spans. (a) Scatter plot showing
Pearson correlation between actual connectome and predicted connectome derived from young and old
templates for individuals across all age spans (b) Correlation difference among individuals between two
age group templates, ordered by age.

Predicting brain responses to the movie
Besides functional connectivity, congruent templates also performed better than incongruent templates
in predicting neural responses to the movie (Figure 5). These results indicate that the more congruent
the template age group is with a participant's age, the more accurate the prediction becomes.
276
277 We used the same 10 functional templates for each age group, based on different participants randomly
278 chosen as described earlier, to calculate individual transformation matrices and predict movie responses.
279 We then focused on differences in performance between using congruent and incongruent templates.
280
Next, we computed correlation coefficients between the measured response time series to the movie and
the predicted time series to evaluate template performance. The correlation coefficients were Fisher-
transformed to z values and aggregated either across different parts of the brain (Figures 5a, 5b) or
across participants (Figure 5c). Prediction performance for both groups was better when using congruent
templates than incongruent templates, with the young group showing a larger congruency effect than the
old group.

Figure 5: Predicting brain responses to the movie based on congruent and incongruent templates. (a)
The average z (± SD) for the old group was 0.1661 ± 0.0600 for congruent templates, and 0.1612 ±
0.0636 for incongruent templates. The mean difference (± SE) was 0.0049 ± 0.0010, $t(212) = 5.02$,
Cohen's $d = 0.3443$ and $p < 10^{-5}$. The average z (± SD) for the young group was 0.2925 ± 0.0627 for
congruent templates, and 0.2441 ± 0.0490 for incongruent templates. The mean difference (± SE) was
0.0485 ± 0.0013, $t(209) = 35.99$, Cohen's $d = 2.4833$ and $p < 10^{-90}$. (b) Scatter plot of each participant's

average predicted response values derived from different congruent and incongruent templates. (c)
Topographic distribution of predicted response difference across different brain regions.

Discussion

In this paper, we analyzed the effect of age on hyperalignment performance. Our findings demonstrate
the significant impact of age-specific hyperalignment templates on the accuracy of individualized
connectome prediction, neural response to the movie, as well as the inter-subject correlation (ISC) values
after hyperalignment.
300
The ISC results demonstrate the age effect on hyperalignment template performance. Average ISC
values in the hyperalignment common model space are higher when projecting individual connectome to
the common model space derived from congruent age group templates—those aligned with the
participant's age group—rather than incongruent age group templates. By contrast, the congruency effect
in the visual cortex is much smaller, suggesting that the aging effect on functional connectivity is smaller
in these areas.
307
Moreover, congruent hyperalignment templates consistently achieved higher correlation between
predicted individual connectomes and actual connectomes in participants' native anatomical spaces
compared to incongruent templates. When predicting an individual's connectome in different age groups
using either old group templates (> 65 years old) or young group templates (< 45 years old), as the
individual's age becomes more distant from the template age group, the prediction accuracy drops, and
the difference between congruent and incongruent template prediction increases. Movie response
prediction further indicates that the more congruent the template age group is with the participant's age,
the more accurate the prediction becomes.
316
317 We applied ISC analysis to an independent dataset, DLBS, to further validate the generalizability of our
318 findings (see Supplementary Material). The results were consistent with those observed in the Cam-CAN
319 dataset, showing that congruent templates yielded higher average ISC values than incongruent
320 templates.
321

Previous hyperalignment study shows that the more data used in building the templates for estimating
individual tuning matrices, the better the model performs (Feilong et al., 2023). We expect, therefore, that
the effect of age-congruency of templates will be greater if the templates are built with larger data sets.
Currently, the templates are built using only approximately 16 minutes of fMRI functional data from around
200 participants. We expect that better and more stable model performance could be achieved by
incorporating data from more participants and increasing the amount of data per participant, preferably
to at least an hour. Moreover, incorporating data using richer stimulus paradigms in template construction
might provide additional information that could enhance template performance. Currently our templates
are constructed using only resting state and sensorimotor task data. Naturalistic stimuli, such as movie-
viewing, more broadly sample cognitive and brain states. With increased data collection and richer,
naturalistic stimulus paradigms, we could capture a broader range of neural activities and idiosyncrasies,
potentially leading to more robust and flexible hyperalignment templates and a more precise and reliable
alignment between individual connectomes and the common model space.
335
In this work, we only focused on the impact of age on hyperalignment templates and observed a
significant improvement using congruent age templates compared to incongruent ones. Based on these
findings, it is important to consider the practical applications of this methodology in future research. When
the goal of a case-control study is to directly compare functional organization or brain responses between
distinct populations—such as clinical and non-clinical participants—it is essential that all individuals are
hyperaligned to the same common template. For these analyses, researchers should either construct a
joint template containing a balanced, representative sample from both groups, or align all participants to
a normative control template based on age-matched data. This ensures that the resulting data share a
single coordinate system, allowing for valid statistical comparisons between groups.
345
Age-specific or disease-specific templates are highly advantageous when the research objective is to
maximize decoding accuracy or predictive performance within a specific population. Just as age
introduces specific variations in neural architecture, neurological or psychiatric conditions—such as
Alzheimer's disease and Parkinson's disease—can produce alterations in brain structure and function.
In clinical or lifespan research, if the goal is to build a reliable biomarker of differences among individuals
within a group, e.g., of disease progression or disease subtypes, or to map individualized connectomes
for a specific patient cohort, researchers should use a template congruent with that specific group. By
constructing disease-specific templates, it may be possible to capture these distinctive neural patterns
with greater accuracy, leading to more precise alignment of individual connectomes. This approach could
provide insights into the pathophysiological mechanisms underlying various clinical conditions and
broaden the use of hyperalignment models in clinical neuroscience.

References

Anderson, Z., Gratton, C., & Nusslock, R. (2021). The Value of Hyperalignment to Unpack Neural
Heterogeneity in the Precision Psychiatry Movement. *Biological Psychiatry: Cognitive*
Neuroscience and Neuroimaging, *6*(9), 935–936. https://doi.org/10.1016/j.bpsc.2021.02.006
Anderson, Z., Turner, J. A., Ashar, Y. K., Calhoun, V. D., & Mittal, V. A. (2024). Application of
hyperalignment to resting state data in individuals with psychosis reveals systematic changes in
functional networks and identifies distinct clinical subgroups. *Aperture Neuro*, *4*.

https://doi.org/10.52294/001c.91992

Cox, D. D., & Savoy, R. L. (2003). Functional magnetic resonance imaging (fMRI) "brain reading": Detecting and classifying distributed patterns of fMRI activity in human visual cortex. *NeuroImage*, *19*(2 Pt 1), 261–270. https://doi.org/10.1016/s1053-8119(03)00049-1

Esteban, O., Markiewicz, C. J., Blair, R. W., Moodie, C. A., Isik, A. I., Erramuzpe, A., Kent, J. D., Goncalves, M., DuPre, E., Snyder, M., Oya, H., Ghosh, S. S., Wright, J., Durnez, J., Poldrack, R. A., & Gorgolewski, K. J. (2019). fMRIPrep: A robust preprocessing pipeline for functional MRI. *Nature Methods*, *16*(1), 111–116. https://doi.org/10.1038/s41592-018-0235-4

Feilong, M., Guntupalli, J. S., & Haxby, J. V. (2021). The neural basis of intelligence in fine-grained cortical topographies. *eLife*, *10*, e64058. https://doi.org/10.7554/eLife.64058

Feilong, M., Jiahui, G., Gobbini, M. I., & Haxby, J. V. (2024). A cortical surface template for human neuroscience. *Nature Methods*, *21*(9), 1736–1742. https://doi.org/10.1038/s41592-024-02346-y

Feilong, M., Nastase, S. A., Guntupalli, J. S., & Haxby, J. V. (2018). Reliable individual differences in fine-grained cortical functional architecture. *NeuroImage*, *183*, 375–386. https://doi.org/10.1016/j.neuroimage.2018.08.029

Feilong, M., Nastase, S. A., Jiahui, G., Halchenko, Y. O., Gobbini, M. I., & Haxby, J. V. (2023). The individualized neural tuning model: Precise and generalizable cartography of functional architecture in individual brains. *Imaging Neuroscience*, *1*, 1–34. https://doi.org/10.1162/imag_a_00032

Gratton, C., Laumann, T. O., Nielsen, A. N., Greene, D. J., Gordon, E. M., Gilmore, A. W., Nelson, S. M., Coalson, R. S., Snyder, A. Z., Schlaggar, B. L., Dosenbach, N. U. F., & Petersen, S. E. (2018). Functional Brain Networks Are Dominated by Stable Group and Individual Factors, Not Cognitive or Daily Variation. *Neuron*, *98*(2), 439-452.e5. https://doi.org/10.1016/j.neuron.2018.03.035

Guntupalli, J. S., Feilong, M., & Haxby, J. V. (2018). A computational model of shared fine-scale structure in the human connectome. *PLOS Computational Biology*, *14*(4), e1006120. https://doi.org/10.1371/journal.pcbi.1006120

Guntupalli, J. S., Hanke, M., Halchenko, Y. O., Connolly, A. C., Ramadge, P. J., & Haxby, J. V. (2016). A Model of Representational Spaces in Human Cortex. *Cerebral Cortex (New York, N.Y.: 1991)*, *26*(6), 2919–2934. https://doi.org/10.1093/cercor/bhw068

Haxby, J. V., Connolly, A. C., & Guntupalli, J. S. (2014). Decoding neural representational spaces using multivariate pattern analysis. *Annual Review of Neuroscience*, *37*, 435–456. https://doi.org/10.1146/annurev-neuro-062012-170325

Haxby, J. V., Gobbini, M. I., Furey, M. L., Ishai, A., Schouten, J. L., & Pietrini, P. (2001). Distributed and Overlapping Representations of Faces and Objects in Ventral Temporal Cortex. *Science*, *293*(5539), 2425–2430. https://doi.org/10.1126/science.1063736

Haxby, J. V., Guntupalli, J. S., Connolly, A. C., Halchenko, Y. O., Conroy, B. R., Gobbini, M. I., Hanke, M., & Ramadge, P. J. (2011). A common, high-dimensional model of the representational space in human ventral temporal cortex. *Neuron*, *72*(2), 404–416. https://doi.org/10.1016/j.neuron.2011.08.026

Haxby, J. V., Guntupalli, J. S., Nastase, S. A., & Feilong, M. (2020). Hyperalignment: Modeling shared information encoded in idiosyncratic cortical topographies. *eLife*, *9*, e56601. https://doi.org/10.7554/eLife.56601

Park, D. C., Hennessee, J. P., Smith, E. T., Chan, M. Y., Chen, X., Dakanali, M., Farrell, M. E., Liu, P.,

Lu, H., Rofsky, N., Sun, X., Tamminga, C., Moore, W., Kennedy, K. M., Rodrigue, K., & Wig, G.
S. (2025). The Dallas Lifespan Brain Study: A Comprehensive Adult Lifespan Data Set of Brain
and Cognitive Aging. *Scientific Data*, *12*(1), 846. https://doi.org/10.1038/s41597-025-04847-7
Taylor, J. R., Williams, N., Cusack, R., Auer, T., Shafto, M. A., Dixon, M., Tyler, L. K., Cam-CAN, &
Henson, R. N. (2017). The Cambridge Centre for Ageing and Neuroscience (Cam-CAN) data
repository: Structural and functional MRI, MEG, and cognitive data from a cross-sectional adult
lifespan sample. *NeuroImage*, *144*, 262–269. https://doi.org/10.1016/j.neuroimage.2015.09.018

415