MorphoNet 2.0: An innovative approach for qualitative assessment and segmentation curation of large-scale 3D time-lapse imaging datasets

Benjamin Gallean*[1,2,3], Tao Laurent*[1], Kilian Biasuz[2], Ange Clement[1], Noura Faraj[1], Patrick Lemaire[2] & Emmanuel Faure[1]

* These authors contributed equally to this work.

Affiliation:

[1] Laboratoire d'informatique, de robotique et de microélectronique de Montpellier, LIRMM, Université de Montpellier, CNRS, Montpellier, France.

[2] Centre de Recherche de Biologie cellulaire de Montpellier, CRBM, Université de Montpellier, CNRS, Montpellier, France

[3] Montpellier Ressources Imagerie, Biocampus, Université de Montpellier, CNRS, INSERM, Montpellier France

Abstract

Thanks to recent promising advances in AI, automated segmentation of imaging datasets has made significant strides. However, the evaluation and curation of 3D and 3D+t datasets remain extremely challenging and highly resource-intensive. We present MorphoNet 2.0, a major conceptual and technical evolution in order to easily perform segmentation, self-evaluation and correction of 3D. The application is accessible to non-programming biologists through user-friendly graphical interfaces and works on all major operating systems. We showcase its power in enhancing segmentation accuracy and boosting interpretability across five previously published segmented datasets. This new approach is crucial for producing ground-truth datasets of discovery-level scientific quality, critical for training and benchmarking advanced AI-driven segmentation tools, as well as for competitive challenges.

Introduction

Recent advances in optical time-lapse microscopy now enable the 3D capture of life's temporal dynamics, from molecular assemblies to entire organisms[1], in cells, embryos, and aggregates. These technologies have thus become crucial for cell and developmental biology. The automated segmentation and tracking of these complex datasets is, however, necessary for their interpretation and quantification[1].

Recent progress in the 3D segmentation of animal and plant cells[2], or organelles[3] has made this process highly efficient, despite the persistence of algorithm-dependent systematic errors[4]. The processing of time-lapse datasets, however, remains challenging. The accumulation over hundreds of time points of even few residual segmentation errors can strongly affect data interpretation and notably disrupt long-term cell tracking. Following the excitement generated by this new generation of imaging systems, which offers the ability to image living systems at unprecedented spatial and temporal scales, a glass ceiling has now been reached due to the quality of these reconstructed data, which fails to scale to real research exploitations.

Beyond the reconstruction requirements of individual research projects, proper metrics are essential for evaluating the performance of bioimage analysis algorithms[5]. However, the training and benchmarking of next-generation AI-based segmentation tools fundamentally depend on the availability of accurate ground truth data.[6]. The critical bottleneck is the lack of a massive amount of 3D high-quality reconstructed data to train these systems.

We have decided to take on this challenge and develop a tool to produce high-precision and high-quality 3D datasets for AI. Two major barriers must be overcome to reach this milestone. The first concerns the **evaluation** of dataset reconstructions: how can we measure the accuracy of segmentations obtained by automated algorithms for these complex 3D and 3D+t datasets? The second focuses on the **curation** of reconstructed data: how can we correct and significantly enhance segmentations to achieve reliable reconstructions that are essential for major scientific breakthroughs?

2D imaging has long been a cornerstone of biological research, driving significant scientific discoveries with visual validation being largely adequate, as it could be performed directly on a 2D screen. The traditional method involves visually comparing the reconstruction by overlaying it with the acquired data, as seen in classic software like ImageJ[7], Napari[8] or Ilastik[9]. When discrepancies arise, experts can perform curation and manually adjust the pixel values to align with the desired class (e.g., a cell).

In the context of 3D and 3D+t data, the technique encounters significant obstacles that
hinder reliable scientific analysis. The 3D structure of images, inherently unsuited to the
2D digital environment, demands numerous compromises that restrict their
interpretability. Projecting 3D objects onto a 2D screen causes data masking, requiring
experts to perform extensive manipulations to verify accuracy. Additionally, the high
number and density of 3D objects further complicate the process, as visual interference
from overlapping objects increases during these adjustments. As a result, voxel-level
(3D pixel) curation becomes almost unfeasible using conventional methods, compelling
experts to revert to working in 2D. This approach becomes very time-consuming and
therefore does not allow to obtain a satisfactory reconstruction quality for scientific use.
A final obstacle is caused by the much larger size of 3D datasets, which significantly
lengthens processing time for each curation action. This computational burden becomes
daunting for 3D + t time-lapse datasets, as error propagation between consecutive time
points rapidly increases the number of segmentation and object tracking errors needing
correction. Restricting the application of advanced image processing tasks to subsets of
the image may alleviate this issue.

An unsupervised objective assessment can be derived from an *a priori* knowledge of
expected spatial (e.g. smoothness of contours, shape regularity, volume…) or temporal
(e.g. stability and smooth evolution, lifetime of objects…) features of the objects[10].
Features of the object boundaries (e.g. contrast between inside and outside of an
object) can also be computed[10]. More sophisticated strategies have been proposed
when no statistically-relevant a priori knowledge can be drawn[11]. Since curation is
typically carried out by expert biologists with limited programming skills, the computation
of image features and the projection of relevant metrics onto individual segmented
objects should be accessible through user-friendly interfaces. An alternative approach
for interacting with 3D segmented images is therefore necessary.

Results

We previously developed a novel concept of morphogenetic web browser, MorphoNet[12],
to **visualize** and **interact** with 3D+t segmented datasets through their meshed
representations. This user-friendly web solution required no installation and was suited
for datasets of moderate size (up to a thousand cells over a few hundred time points).
Since its release, this platform has been used in a variety of morphological studies in
plant and animal systems[13,14] and has been instrumental to interpret the relationship
between gene expression and complex evolving cell shapes[15–17]. This web version was
restricted to visualizing and interacting with segmented datasets through their
precomputed 3D dual meshes. This approach offered significant benefits in terms of

online 3D rendering efficiency and data management but it also came with limitations.
For example meshes are simplified representations of the segmented object that may
not capture fine details of the original volumetric data and that cannot be validated
without comparison to the original raw intensity images. Meshed representations can
also make it challenging to perform the precise computations required for detailed
geometric and topological analyses[18]. Exploration of larger datasets was nonetheless
constrained by the computational resource limitations of internet browsers.

We present here MorphoNet 2.0, a major conceptual evolution of the platform, designed
to offer powerful tools for the **reconstruction**, **evaluation**, and **curation** of 3D and 3D+t
datasets. This innovative approach leverages the richness and redundancy of
information embedded within these complex datasets. It addresses the two previously
identified challenges: **evaluating** 3D segmented data without relying on manual ground
truth by fully harnessing the data's richness, and enabling semi-automated **curation** of
3D data, now achievable with just a few clicks. This enables us to achieve data quality
at a level suitable for scientific discovery. We showcase the impact of these
advancements by revisiting and enhancing five published animal and plant datasets
previously regarded as ground truth[6].

We feature a new standalone application running on all major operating systems that
exploits the resources of the user's local machine to explore, segment, assess and
manually curate very large 3D and 3D+t datasets. Like the web version, the MorphoNet
application uses the power and versatility of the Unity game engine and includes its
main features[12]. By overcoming web-based limitations, the application can handle more
complex datasets including heavier segmented voxel images and up to several tens of
thousands of objects on a research laptop (Fig. 1h, and Supp. Table 1). The
standalone application allows users to directly explore private data stored on their own
computer, without need for an upload to the MorphoNet server. Subsequent data
sharing with other researchers or a wider public in an open science process is facilitated
by the MorphoNet server upload functions of the standalone.

MorphoNet is designed with a strong emphasis on user-friendliness, making its use
highly intuitive for experimental biologists with no coding experience (See Supp.
Movies). Every feature and interface element has been crafted to ensure a smooth,
straightforward user experience, allowing both beginners and experts to utilize its
capabilities efficiently. Additionally, the solution is fully open-source allowing bio-image
analysis to develop their own features (See Supp. Table 2).

One of the key features of this new standalone application is the automatic integration
of a duality between the 3D segmented images and their corresponding meshes (Fig
2.). This feature is achieved by linking Python, dedicated to high-performance image

processing, with the Unity Game Engine, fully optimized for seamless interaction with the dual meshes. This integration enables access to state-of-the-art reconstruction[2,19] tools, including those leveraging AI libraries, while also addressing the challenges of interacting with 3D images by harnessing the powerful interactive capabilities of game engines.

To ensure users can consistently assess segmentation quality, raw intensity images are also available by superimposition. This provides access to the entire workflow, from raw image acquisition to meshed segmentation, allowing simultaneous exploration and visualization of both meshed and voxel images (Fig. 1a-f).

We also leveraged Unity's scene management tools to implement simultaneous visualization of multiple scenes. This feature enables the display of interactive cell lineages in a dedicated, fully connected window, offering essential insights into cellular trajectories within 3D+t datasets.

Figure 1: Illustration of the visualization of datasets of various complexity and nature in the MorphoNet standalone application

a-f. Visualization of a 64-cell stage Phallusia mammillata embryo with labeled cell nuclei and cell membranes. a-c intensity images showing the nuclei (a), the membranes (b) or both (c). d . same as c. with additional nuclei segmentation obtained with the Binarize plugin (see Supp. Mat. for the full description of curation plugins). e. same as b. With additional membrane segmentation obtained with the Cellpose 3D plugin. f. same as c. with a combination of several rendering possibilities of cell and nuclei segmentations.

g. Multi-colored shaders allow the simultaneous visualization of the expression patterns of multiple genes extracted from the ANISEED[17] database and of tissue fate information. Ascidian embryo[16] at stage 15 (mid neurula); cells with a single color are coloured with larval tissue fate; multi-coloured cells are coloured with both larval tissue fate and the expression of selected genes.

h. Visualization of a 6 days post-fertilization Platynereis dumerilii embryo[20] imaged by whole-body serial block face scanning electron microscopy followed by the automated whole-cell segmentation of 16000 cells.

i-k. Visualization of a cell cycle 14 Drosophila melanogaster embryo imaged with SiMView microscopy and segmented with RACE[21]. i. Projection on each segmented cell of the mean image intensity . j. Projection on each segmented cell of the ratio between the length of the major and the minor axes of the ellipse that has the same normalized second central moments as the segmented cell. k. projection of the cell volume.

Automatic error detection

Efficient dataset curation requires the rapid identification of segmentation errors in large 3D or time-lapse datasets containing thousands of segmented objects. MorphoNet 2.0 tackles this critical challenge by introducing unsupervised metrics for objective, automated assessment, eliminating the subjectivity, inefficiency, and inconsistency inherent in manual visual inspections. These metrics leverage prior knowledge of generic data properties - such as shape regularity, contour smoothness, and temporal stability of shapes and volumes - to deliver scalable and consistent analysis. Beyond improving curation efficiency, these metrics offer quantitative scores that enable systematic comparisons across datasets, experiments, and tools. Integrated into MorphoNet, they support benchmarking, algorithm refinement, and reproducibility. Using the scikit-image library[22], we automatically compute object properties from both segmented and intensity images.   These properties quickly help identify outliers, which often correspond to segmentation errors. While the traditional approach uses some metrics to evaluate global distributions, it is crucial for curation purposes to apply these properties at the level of each individual segmented object. Thus, these properties, including shape metrics like volume, convexity, and elongation, and intensity metrics such as mean voxel intensity within or around segmented objects, can be easily projected onto meshed objects for visualization (Fig. 1i-k).

Segmentation quality assessment is further enhanced by calculating three categories of properties for each dataset: 1) Morphological features – including volume, convexity, roughness, and elongation, 2) Intensity-based measurements – within and around each

object in the original acquisition images, such as mean intensity, homogeneity, or
deviation at segmentation borders; 3) Temporal features – such as object lifetime or cell
lineage distances[16].

By projecting these values onto segmented object meshes, outliers are readily identified
as prime candidates for curation. These values can also be exported and plotted to
reveal distributions, providing an unsupervised assessment of overall segmentation
quality. This process is exemplified in various use cases described below.

Biocuration

The execution time of algorithms in 3D image processing limits the optimization of their
parameters. Additionally, the inherent heterogeneity within 3D images frequently
prevents achieving consistently high-quality results across the entire dataset. To tackle
these challenges, we defined in Morphonet the notion of multi-type representation
layers, able to combine and interoperate 3D image intensity layers with mesh-based
layers. This dual representation enables seamless interaction with meshes, facilitating
the rapid identification and precise selection of objects requiring curation. By focusing
processing efforts on these selected regions rather than the entire image, MorphoNet
significantly reduces the time and effort required, streamlining the curation workflow for
complex 3D+t datasets.

The meshed versions of the segmentations are used for 3D rendering, for the
identification and selection of objects needing curation, and to launch the needed
curation algorithms, which are performed on the segmented images (Fig. 2). A
significant acceleration of operations on 3D images is achieved by targeting the
processing activities on a subpart of the image, for instance on the bounding box of an
object or of a set of objects. This approach enables results to be generated in just
seconds for most tasks, even with highly complex 3D data. Given the heterogeneity
within 3D images, it is challenging to find a single set of parameters that works
effectively across the entire image. This approach makes it easy to run image
processing algorithms with different parameters in different subregions of the image.

Editions of objects necessitating curation can then proceed using dedicated plugins.
The curation module of MorphoNet has an expandable open-source Python plugin
architecture and provides user-friendly graphical interfaces accessible to experimental
biologists with limited programming skills. To support advanced image processing
techniques powered by deep learning, which have an increasing impact on image
analysis, the default installation package includes training libraries like Scikit-learn,
PyTorch, and TensorFlow. Plugins can take the raw intensity image into account to

perform 3D image processing tasks as exemplified by the integration of popular
segmentation tools, such as Stardist[19] and Cellpose[2]. The full list of plugins can be
found in the Supp. Mat.. Users and developers can expand the current plugin list by
creating their own through an easy-to-use python template (See Supp. Table 2).

To help the user identify suitable plug-ins, we grouped them into seven categories. The
first five are used to create or edit segmentations of 3D datasets, the last two are
dedicated to the temporal propagation of corrections in 3D+t datasets. All categories will
be exemplified in the five use cases below. Supp. Fig. 1. illustrates how the majority of
segmentation and tracking errors can be corrected using plugins, single handedly or in
combination. For example, an under-segmentation can be corrected by running locally
the *Cellpose* plugin as in use case 2 or the Temporal Propagation plugin (*Prope*) as in
use case 5.

1- *De novo Segmentation* plugins : these plugins create a *de novo* segmentation from
the original intensity images (or from a specified region of interest of the intensity
images). This category includes segmentation tools such as Cellpose 3D or Stardist as
well as simpler intensity thresholding. As described below, MorphoNet plugins allow to
specifically target the application of these tools to error-rich regions.

2- *De novo Seed* plugins : these plugins automatically create seeds (i.e. 3D points in
the 3D images), which can then be used to initiate segmentation tasks. Additionally,
seeds can also be added manually using the interface.

3- *Segmentation from Seeds* plugins : these plugins are used to perform local
segmentation using predefined seeds, for example by using a watershed algorithm.

4- Segmentation correction plugins *:* these plugins are used to correct the main classes
of segmentation errors on selected segmented objects. This includes the fusion of over-
segmented cells, the resolution of small artifactual cells or the splitting of under-
segmented cells.

5- *Shape transform* plugins : these plugins are used to edit the shape of selected
segmented objects. This includes classical morphological operators (such as dilate,
erode, etc.) or the manual deformation of a cell's shape.

6- *Propagate Segmentation* plugins *:* these plugins are used to propagate an accurate
segmentation at a specific time point to erroneous segmentations at later or earlier time
points. Examples: Propagate eroded cell masks to correct under segmentation errors.

7- Edit Temporal Links plugins *:* these plugins are used to curate cell lineage trees by
creating or editing temporal information. Examples: Create temporal links using the
spatial overlap between homologous objects at successive time points.

Figure 2: MorphoNet Standalone Schema: *From the local data (loaded from the green box), the MorphoNet Standalone application computes first the dual meshes for each of the segmented objects (in the module python in the yellow box). Then, using the 3D viewer (in the blue box), users identify detection, segmentation or tracking issues using, if necessary, the cell lineage information, the raw images and/or properties computed on the segmented objects . Errors are then corrected by choosing and executing the appropriate image processing plugin from the curation menu. Finally, new meshes are computed from the result of the plugin execution to update the visualization.*

Use cases

To highlight the efficiency of MorphoNet plugins in detecting and correcting the main types of errors across a broad range of organisms, we present five examples from previously published fluorescent live imaging datasets, representing various levels of quality and complexity. These examples collectively showcase MorphoNet's powerful segmentation quality assessment and error detection capabilities in different contexts, ranging from low-quality nuclear segmentations to high-quality whole-cell segmentations. While these examples frequently involve the use of Cellpose, the current state-of-the-art tool for 3D dataset segmentation, the focus is not on emphasizing the tool's power but on demonstrating how advanced tools can be enhanced through integration into MorphoNet's sophisticated graphical plugin interfaces.

The first use-case introduces two unsupervised metrics for assessing dataset quality in the absence of ground truth on a time-lapse light-sheet microscopy movie of a developing *Tribolium castaneum* embryo. Using these metrics, we demonstrate the power of an iterative segmentation and training strategy. By applying a Cellpose model, trained on a curated subpopulation, to the entire dataset, we improve segmentation quality.

The second use-case presents unsupervised whole-cell morphological metrics to assess the quality of several independent segmentations of a time-lapse confocal movie of a developing starfish embryo, up to the 512-cell stage, with fluorescently labeled cell plasma membranes. Originally, a bio-image analyst segmented the movie using a complex workflow. We demonstrate that running an imported, custom-trained Cellpose 3D model through MorphoNet's graphical interfaces greatly increases the number of cells that can be successfully segmented.

The third use-case focuses on detecting and resolving regions of under-segmented cells in a confocal 3D dataset of *Arabidopsis thaliana* plant apical shoot meristem, with fluorescent plasma membrane and whole-cell segmentation of 1800 cells. It demonstrates the identification of a large region with heavily under-segmented cells, which is successfully addressed by targeting Cellpose to the specific region of interest.

The fourth use-case addresses the correction of low-quality automated cell nuclei segmentation in a time-lapse confocal *Caenorhabditis elegans* embryo with poor-quality nuclei labeling up to the 350-cell stage, despite accurate manual tracking. It demonstrates how object edition plugins can be used to correct individual nuclei segmentations and propagate these corrections over time.

The final use-case illustrates the efficient detection and correction in the cell lineage of rare residual errors that escaped previous scrutiny in a published time-lapse multiview light-sheet imaging dataset of a developing *Phallusia mammillata* embryo. The dataset features labeled cell membranes and high-quality whole-cell segmentation and tracking. This polishing work is crucial for generating ground truths for studies of natural variation.

All the evaluation and curation steps for the use cases are detailed in the Supp. Mat.

Use-case 1: Assessing and improving segmentation quality of *Tribolium castaneum* Embryo using unsupervised nuclei intensity metrics and iterative training on partial annotation.

This use-case introduces two unsupervised metrics for assessing dataset quality
without ground truth, demonstrating their application in evaluating segmentation
performance. It also highlights the effectiveness of an iterative segmentation and
training approach, where applying a Cellpose model trained on a curated subset
significantly improves overall segmentation quality.

<u>Dataset description:</u> This dataset features a 59-time-step light-sheet microscopy
acquisition of labeled cell nuclei from a developing *Tribolium castaneum* embryo,
containing over 7000 cells per time step. It includes two types of ground truth: a *gold*
truth (GT), which is expert manual tracking of 181 nuclei over all time steps, and a *silver*
truth (ST), generated through a complex pipeline combining the outputs of up to 16 top-
performing algorithms selected from 39 submissions. The ST provides automated
segmentation masks using a modified label fusion approach for improved accuracy in
dense datasets. The GT and ST are independent and do not share common elements.

<u>Type of errors</u>: This dataset serves as a benchmark in the fifth Cell Tracking Challenge[6]
to evaluate and compare AI-based image segmentation methods and is therefore
regarded as a reliable ground truth. The manual tracking GT is of high quality (expert
annotation), but the automated ST is of lesser quality. To evaluate the segmentation
quality of the dataset at first time point, the intensity image and the two ground truths
(ST and GT) were simultaneously displayed in separate MorphoNet channels (Fig. 3a).
Systematic visual inspection identified 12/181 GT points without corresponding nucleus
in the ST data; 8 misplaced segmentation where the GT point is not inside the
segmentation; 56 over segmentations and many suspicious nuclear shapes.

<u>Error identification</u>:   Using the *Match* plugin, each GT position was automatically
associated with a corresponding nucleus in the ST, leaving 11 out of 181 positions
unassigned (Fig. 3a), indicating approximately 6% of missed nuclei in the ST. To
identify inaccurately shaped segmentations, we used two signal intensity-based
MorphoNet metrics. The first metric measures the distance between the geometric
center of a segmented object and the center of mass of the signal intensity (Supp. Fig. 2
et Supp. Mat. for the full properties description), with 32 of the 56 over-segmented
nuclei falling into the upper quartile of this metric's distribution (Fig 3c-d and Supp. Fig.
3). The second metric evaluates deviations in the signal intensity along the
segmentation boundary, with 29 out of 56 over-segmented nuclei identified in the upper
quartile (Fig. 3e-f and Supp. Fig. 2). These errors were visualized in 3D by projecting
both metrics onto each nucleus, enabling spatial identification of potential segmentation
issues (Supp. Fig. 3).

<u>Error correction </u>: Due to the high number of errors in the published ST, a de novo
nucleus segmentation pipeline was created in MorphoNet with minimal manual
intervention. The five-step process included initial segmentation using the standard

Cellpose nuclei model, manual curation of 181 GT nuclei, iterative training of a custom Cellpose model, and refinement of segmentation using geometric properties. Key steps involved correcting segmentation errors with various plugins, extending the Cellpose nuclei model using curated data, and refining non-convex shapes. The pipeline significantly improved segmentation quality compared to the published ST and standard Cellpose model (Fig. 3i). Analysis of the curated nuclei revealed a more heterogeneous volume distribution, fewer over-segmentations, and better alignment of intensity-based metrics (Fig. 3g-h), showing substantial improvement over the original segmentation pipeline.

Figure 3: Unsupervised quality assessment and curation of the *Tribolium castaneum* embryo

a. The 5 steps of the curation pipeline.
b. View of the original intensity images (in green) of the first time step of the published data[6]. Both Ground Truth channel (GT, red point) and Silver Truth (ST, white nucleus segmentation) are shown at the top. Blue segmentation corresponds to the match between ST and GT. Bottom, zoom at the GT region (ROI) without the intensity images.
c. Projection for the ST of the distance between the gravity center of the intensity inside the segmentation and the centroid of the segmentation. Color bar at the bottom of d.
d. Same as c. for the curated pipeline.

e. Projection for the ST of the deviation of the intensity at the border of the
segmentation. Color bar at the bottom of f.
f. Same as e. for the curated pipeline.
g. Comparative histogram of the *intensity_offset* property distribution between the
ST, the Step 1 and the Step 5 for the 181 curated nuclei (left) and the whole
image (right).
h. Same as g for the distribution of the *intensity_border_variation* property.
i. Sams as g. For the distribution of the *nuclei volume* property.

Use case 2 : Evaluating membrane segmentation quality using *smoothness*
metrics and simplifying a segmentation workflow for *Patiria miniata* starfish
embryo.

This use case thus introduces new unsupervised morphological metrics (the
smoothness property) to assess segmentation quality and demonstrates that using a
custom-trained 3D Cellpose model via graphical interfaces allows extending
segmentation to areas of the dataset with lower intensity/noise ratio. Visualization of
metrics such as smoothness and cell volumes simplifies the identification of cells that
need further manual curation.

Dataset description: This dataset comprises 300 3D stacks from time-lapse, two-
channel confocal imaging of 12 *Patiria miniata* wild-type and compressed embryos,
captured between the 128- and 512-cell stages[23]. Fluorescent labeling highlights cell
membranes and nuclei, though imaging was limited to about half of each embryo due to
poor penetration and the use of low magnification air objectives. The published whole-
cell segmentation relied on a complex, multi step workflow adapted from the CartoCel[24]
requiring advanced bioanalysis expertise. For this use case, a particularly challenging
dataset - a compressed wild-type embryo at the 512-cell stage - was selected for
evaluation and curation.

MorphoNet segmentation with the advanced Cellpose plugin:
431
We explored Cellpose's potential to improve segmentation quality in challenging regions
of a 3D dataset. Initial segmentation using the Cyto2 model identified 1187 cells, with a
bimodal size distribution and 939 cells smaller than 1000 voxels (Fig. 4i). Using the Deli
plugin (Fig. 4j) reduced the count to 211 cells; however, analysis with the *smoothness*
property (Fig. 4g) revealed rough cell surfaces. To address this, we further extend the
training of the *Cyto2* model on the published 3D database[23] (see Supp. Mat. Training
Protocol). The retrained model produced 284 cells with again a bimodal size distribution
(Fig. 4i) which was corrected with the *Deli* plugin. This much simpler procedure than the

original segmentation pipeline, produced smooth cells (Fig. 4h), with a similar size distribution as the published ground truth. While 11 cells were missing or under-segmented compared to the published data (Fig. 4f), this new approach recovered 48 additional cells (Fig. 4e). while simplifying the segmentation process compared to the original pipeline.

Figure 4: Starfish whole-cell segmentation using Cellpose

a. *Animal and Lateral view of the maximum intensity projection from the published dataset[23].*
b. *Segmented ground truth image.*

c. Result of the segmentation using Cellpose Cyto2 model followed by the removal
of small cells (<1000 voxels) with the Deli plugin
d. Result of a Cellpose segmentation with a model trained on P. miniata dataset
followed by the Deli plugin.
e. New cells created (different between b and d)
f. Under segmentation and missing cells generated by d. compared to b.
g. Vegetal view of c with smoothness representation.
h. opposite view of d with smoothness representation.
i. Cell size distribution in the published segmentation (b), Cellpose cyto2 model
(c) and Cellpose with P. miniata model (d).
j. Identical as i after application of the Deli plugin.

Colors in b-f, represent cell volume in µm^3.

Colors in g,h represent Smoothness.

Use case 3: Interactive targeted segmentation using CellPose for resolving
under-segmentation in *Arabidopsis thaliana* shoot apical meristem whole-cell
segmentation

This use case demonstrates the power of interactive selection with targeted
segmentation methods that can resolve under-segmentation issues in complex
datasets.

<u>Dataset description:</u> This dataset[25] consists of a 19-time steps time-lapse confocal
acquisition of a live *Arabidopsis thaliana* shoot apical meristem with fluorescently-
labeled cell membranes. Cell numbers ranged from 600 cells at the first time point to
around 1800 cells at the last (Fig. 5a). We use the last time step (19) with the higher
number of cells to illustrate the curation procedure.

<u>Error detection:</u> The analysis of the published segmentation uncovered multiple under-
and over-segmentation errors in the deep cell layers, caused by poor image quality in
the inner regions of the meristem (Fig. 5b). These errors hindered accurate cell tracking
over time. Observing the size homogeneity of shoot apical meristem cells (Fig. 5d), we
hypothesized that larger-than-expected cells might indicate under-segmentation errors,
while smaller cells could result from over-segmentation. By projecting the automatically
computed cell volumes as a color map onto the segmentations, we identified a large
under-segmented region containing 20 cells in the deep meristem layer (highlighted in
red in Fig. 5c), along with a few small over-segmented cells (Fig. 5i).

<u>Error correction</u>: The large number of fused cells in the under-segmented region
prompted us to test whether our interactive Cellpose plugin could outperform the
original MARS/ALT software[26]. The standard pretrained *cyto2* model of Cellpose[2]
produced numerous very small over-segmented cells (Fig. 5d and Supp. Fig. 5),
suggesting it was not well-suited for this dataset[27]. To improve performance, we used
the high-quality MARS/ALT segmentations from the first ten time points and employed
our Cellpose train plugin to extend the *cyto2* model training. We tested two training
modalities: "2D" training, using only the XY planes, and "3D" training, incorporating XY,
XZ, and YZ planes. The segmentations after additional 2D training still contained many
over-segmented cells (Fig. 5f), a problem that was significantly reduced with 3D training
(Fig. 5g). Despite this, the heterogeneity of signal intensities still caused over-
segmentation in more superficial regions of the meristem.   We thus targeted the
Cellpose plugin only to the large under-segmented region (Fig. 5h). and removed small
over-segmented cells using the *Deli* segmentation correction plugin (Fig. 5i).   This
targeted approach was fast and accurate (Fig. 5d) and allowed us to preserve the
accurate segmentations from the original published data while curating the identified
errors. With this approach, we successfully curated 20 under-segmented regions and
generated 98 new cells.

Figure 5: Curation of a segmented shoot apical meristem of *Arabidopsis thaliana*.

Visualization of the time step n°19 for several types of curation using MorphoNet.

a. *3D view of an Arabidopsis thaliana shoot apical meristem[25].*
b. *Published 3D intensity images.*
c. *Published 3D segmentation of an Arabidopsis thaliana shoot apical meristem[25] obtained using MARS-ALT[26].*
d. *Comparative histogram based on the cell volume between the published segmentation (c) , the result of the cyto2 prediction (e) and the final curated version (i) + Deli plugin for cells <1000 voxels. X and Y axes are in log scale.*
e. *Result of the Cellpose[28] 3D MorphoNet plugin using the pretrained cyto2 model.*
f. *Result using the Cellpose 3D MorphoNet plugin using the model trained over the 10 first time steps with the Cellpose training plugin with the XY planes.*
g. *Result of the Cellpose 3D MorphoNet plugin using the model trained over the 10 first time steps with the Cellpose training plugin with each plane of the 3D images.*

524 *h. Manually selected masks using morphonet on published data (c).*
525 *i. Result of the Cellpose 3D MorphoNet on the selected masks (h) using the model*
526   *trained over the 10 first time steps with the Cellpose training plugin with each*
527   *plane of the 3D images.*

529 Use-case 4: Improving segmentation quality using object editing plugins for
530 *Caenorhabditis elegans* cell lineage

This use case illustrates how object editing plugins can be employed to improve
segmentation quality in challenging datasets despite poor-quality nuclei labeling.

<u>Dataset description:</u> This dataset[29] consists of a live 3D time lapse confocal acquisition
of a developing *Caenorhabditis elegans* embryo with fluorescently-labeled cell nuclei
(Fig. 6a), over 195 time steps between the 4- and 362-cell stages. This dataset was
included in the Cell Tracking Challenge[6].

<u>Error detection:</u>   Although the manually curated published cell lineage appeared
accurate (Fig. 6a), some touching nuclei were elongated with flat vertical contact
interfaces, likely due to poor imaging quality. To identify these segmentation artifacts
systematically, we calculated the axis ratio for each segmented object and projected the
values onto the meshed dual of the object (Fig. 6b). The distribution revealed two
peaks: a sharp one around 2, containing most nuclei, and a broader one above 3.
Nuclei with an axis ratio greater than 2.9 were flagged for potential correction.

<u>Error correction</u>: We curated these errors for a specific time point by first applying a
fusion correction plugin (Fig. 6f and g) to all selected nuclei pairs with an axis ratio
greater than 2.9 (Fig. 6e). This was followed by a separation plugin (Fig. 6h) that divides
fused objects into distinct nuclei using a Gaussian mixture applied to intensity values.
We initially addressed the more complex cases manually, which included two groups of
four 4 nuclei and one group of 3 fused nuclei. Next, we automatically curated the
remaining 8 simpler cases of 2 fused nuclei by selecting nuclei with a volume greater
than 80 µm³. As anticipated, the axis ratio property of the curated set showed a
unimodal distribution, centered around 2 (Fig. 6b). The entire time step at t=150 was
fully curated with just 20 plugin actions (Fig. 6h).

Figure 6: Curation of a *Caenorhabditis elegans* embryo dataset

    a. *Cell lineage viewer of all time steps colored by clonal cells of the published segmented dataset[29].*

    b. *Comparative histogram based on the axis ratio between the published data and the curation.*

    c. *3D View of the intensity images at t=150.*

    d. *3D View of the published segmented dataset at t=150. Colors represent the ratio of the longest axis on the shortest axis of the shape.*

    e. *Automatic selection (in gray) of the nuclei with an axis ratio>2.9.*

    f. *Result of the Fusoc plugin applied on all selected nuclei. Colors represent the nuclei volume in µm^3.*

    g. *Same as f. But only previously selected nuclei are shown.*

    h. *Result of the Gaumi plugin applied independently on regions fused with 4,3 or 2 nuclei. Colors represent the axis ratio as in d.*

Use-case 5: Enhancing cell lineage accuracy by detecting segmentation errors in *Phallusia mammillata* embryos.

This use case showcases how MorphoNet can efficiently detect and correct segmentation errors in complex 3D+t datasets of developing ascidian embryos, enhancing the accuracy of cell lineage reconstructions and analysis of cell division timing variations.

Dataset description: This dataset[16] comprises 64 time steps of multi-view light-sheet microscopy of developing ascidian embryos (64–298-cell stages), segmented using the ASTEC algorithm[16]. Despite the high-quality segmentation and tracking, residual errors such as multi-component cells, over- and under-segmentations, delayed or missed divisions, and shape inaccuracies remained, with no tools available at the time of the publication to systematically validate or correct the 10,000 cell snapshots.

Error detection: MorphoNet was used to polish the cell lineage to a sufficient level to study natural variation in cell division timing. The main challenge was identifying rare errors within a cell lineage that appeared accurate by visual inspection. To address common lineage residual errors such as missing or delayed divisions and broken lineage links, we developed a set of segmentation error identification metrics. These metrics were visualized by projecting their results onto the lineage using an interactive viewer linked to the 3D dataset (Fig. 7a and b). All identified errors stemmed from segmentation issues rather than tracking, and their correction was streamlined by the bidirectional connection between the lineage and embryo representation windows, allowing direct navigation between the two.
State-of-the-art segmentation methods often produce systematic errors, such as very small segmented objects, which we identified using geometric properties like cell volume (e.g., cell a7.1, Fig. 7a). Property projection, combined with scatter visualization, facilitates the identification of cells even in dense, interior regions (Fig. 7b), while the highlight mode enhances this process by isolating the cell of interest (Fig. 7c). Occasional missing or false divisions disrupt accurate cell histories. During early ascidian embryogenesis, stable cell volumes allowed volume projections onto the lineage to identify rapid variations, revealing missed divisions (Fig. 7d).
Ascidian embryos exhibit bilateral symmetry, with homologous cells dividing almost synchronously. A l*ineage distance* property[16] revealed missed divisions (e.g., b7.11* in Fig. 7e). To distinguish segmentation errors from natural variability, a *compactness* property was used to detect inaccuracies in division timing by tracking cell rounding during mitosis (e.g., Fig. 7f).
Using MorphoNet, an expert identified approximately 20 isolated cell lineage errors in a dataset of 185 cell snapshots in just 2 hours.

<u>Error correction</u>: The 41 multi-component labels were separated using the *Disco* plugin, identifying 7 potential cells via the *volume* property analysis (Fig. 7b). The others, considered as small artifacts, were merged with neighboring cells sharing the largest surface area using the *Deli* plugin. Division timing issues often stem from over-segmentation, under-segmentation, or missing cells. Over-segmentations were resolved with the *Fuse* plugin (Fig. 7g), while under-segmentations were corrected using *Propagate segmentation* plugins by tracing back from the first accurate segmentation of sister cells to their mother's division point (Fig. 7h). For missing cells, seeds were added with seed generator plugins and segmented using local seeded watershed algorithms (Fig. 7i). If imaging quality was too poor, the bilaterally symmetrical cell served as a mirror-image proxy, using the Copy-Paste plugin to replicate, rotate, and scale the cell to the missing position (Fig. 7j).

Using a combination of using 264 MorphoNet plugin actions, 185 errors were corrected in 8 hours actions, leading to a better estimation of the natural variability in cell division timing (Fig.7k)

Figure 7: Curation of a *Phallusia mammillata* ascidian embryo *named Astec-Pm9 in the publication*[16].

a. Cell lineage of the cell b7.1 after the execution of the Disco and Deli plugins on
the published data. Projection of the volume property, the *colormap between b*
and c represents the cell volume in µm³.

b. *Scatter view of the corresponding segmented embryo described in a. at t=28*
colored by cell volume. Colormap identical as a.

c. *Same view as c. with the activation of the "highlight" mode which focuses on the*
selected cell and shows other cells in transparents colors.

d. *Several snapshots of the cell b8.21 at different time points with its associated cell*
lineage. Colormap represents the cell volume in µm³ which points to a missing
division.

e. *Cell lineage of the bilateral cells b7.11 and b7.11*. Colorbar shows the lineage*
distance between the bilateral symmetrical cells. Black region represents
snapshots with no matches between bilateral symmetrical cells.

f. *Cell lineage of the bilateral cells a7.5 and b8.6. Colorbar shows the compactness*
property. The property highlight that the delay of division between A7.5* and A7.5
is due a under-segmented error of A7.5*. B8.6 and B8.6* have expected
behavior.

g. *Result of the Fuse plugin applied on an over-segmented cell.*

h. *Top line: Several snapshots of B7.7* cell under-segmented (between time point*
31 and 33) from the original segmented embryo. Bottom: result of the Propi
plugin applied backward from time t=34 where both cells are well separated.

i. *Example of the result of the Wata plugin from a manual added seed (red dot) in*
the empty space.

j. *Result of the Copy-Paste plugin from the selected cell (in gray) on the left side of*
the embryo to the right side (the new cell appears with a mesh shader in blue).
Colormap represents cell volume in µm³.

k. *Comparison of the lifetime of bilateral symmetrical cells. The X axis shows the*
number of in time points separating the division of bilateral cell pairs. The Y axis
corresponds to the number of cell (in log)

Discussion

Recent advancements in optical time-lapse microscopy allow for the 3D capture of dynamic biological processes but face challenges in automating the segmentation and tracking of large, complex datasets. Residual segmentation errors in time-lapse datasets disrupt data interpretation and hinder long-term cell tracking. Moreover, accurate, high-quality 3D data is critical for training next-generation AI-based segmentation tools, yet the availability of such datasets remains limited.

To address these challenges, **MorphoNet 2.0** was developed as a standalone application for reconstructing, evaluating, and curating 3D and 3D+t datasets. Building on its previous web-based version, MorphoNet 2.0 integrates voxel images with meshed representations, leveraging both Unity Game Engine and Python for enhanced interactivity and processing power. Key features include tools for assessing segmentation quality through unsupervised metrics (e.g., volume, smoothness, and temporal stability), automated error detection, and visualization of segmented objects alongside raw intensity images.

Conventional image curation tools struggle with the complexities of interacting with 3D voxel images. In contrast, MorphoNet 2.0 introduces a novel approach using dual representation layers, enabling efficient biocuration by isolating problem areas and significantly accelerating dataset refinement. MorphoNet 2.0 is user-friendly, open-source, and supports both scientific discovery and AI training by producing high-precision 3D datasets and enabling reproducible, scalable data analysis.

By showcasing 5 use-cases of fluorescence datasets in which cell membranes or nuclei were labeled, we demonstrated that the tool's high versatility and user-friendliness enables biologists without programming skills to efficiently and intuitively detect and handle a broad range of errors (under-segmentation, over-segmentation, missing objects, lineage errors).

MorphoNet has a high potential to adapt to evolving datasets and segmentation challenges. First, its open-source Python plugin architecture fosters community-driven improvements. These could target cellular datasets as exemplified by the 5 use-cases presented. They could also open MorphoNet to other imaging modalities, including multi-modal datasets combining for instance fluorescence and electron microscopy. Additional plugins could accommodate new AI tools or automate the training of

segmentation models, through data augmentation, feature selection, or hyperparameter
optimization. Plugins for widely used platforms such as Napari or Fiji will also broaden
the user-base and interoperability of the tool, as would also the development of flexible
export options to integrate MorphoNet outputs with other analytical pipelines or
visualization software. The MorphoNet eco-system could be further enlarged by the
creation of a centralised repository for community-developed plugins, by the
organisation of MorphoNet-based bio-image analysis challenges to stimulate community
engagement and by the provision of curated datasets to use as benchmarks for testing
and validating new segmentation algorithms.

Curation could also be improved by the introduction of cloud-based, multi-user
capabilities to enable experts to work on the same dataset simultaneously. For now,
web browsers impose constraints on the use of computing resources, which could be
lifted in the near future, for example through the development of WebGPU.

Curation capabilities will likely also be enhanced by the implementation of adaptive
machine learning models that integrate past user corrections to suggest or automate
future edits. In the context of 3D segmentation tasks, manual expertise and curation for
voxel-wise segmentation is labor-intensive and expensive. Full annotation of large
datasets may thus not be feasible. Partial annotations allow datasets to be created with
less time and resources while still providing valuable information. Including algorithms
such as Sketchpose[30] could leverage weakly-supervised learning to generalize from the
partially annotated data and infer segmentation patterns in the unlabeled portions of the
dataset, a strategy we initiated with the Tribolium dataset. This will make it possible to
train models on diverse datasets without the burden of full annotations.

By addressing major challenges in 3D and 3D+t dataset assessment and curation,
MorphoNet 2.0 provides a versatile platform for improving segmentation quality and
generating reliable ground truths. Its user-friendliness, adaptability and extensibility
position it as a valuable tool for advancing quantitative bio-image analysis, with
significant potential for enhancement and broader application in the future.

Acknowledgements: This work was supported by grants of the Occitanie Region (ESR-
PREMAT-213) and of the French National Infrastructure France BioImaging (ANR-10-INBS-04)
to EF, and by the Cell-Whisper (ANR-19-CE13-0020) and scEmbryo-Mech (ANR-21-CE13-
0046) ANR projects coordinated by PL. EF and PL were CNRS staff scientists. NF was an
assistant professor at UM. KB was a UM Phd Student supported by the EpiGenMed Labex
(ProjetIA-10-LABX-0012) and a post-doc funded by the scEmbryo-Mech project. BG,TL were
contract CNRS engineers. AC was a UM Master student. We thank Christophe Godin, Vanessa
Barone and Volker Baecker for their valuable feedback and advice.

Author Contributions: B.G. contributed to the development of the website, the 3D viewer and
the python API. TL contributed to the development of the 3D viewer and the python API. KB
contributed to its featuring and to the help pages. AC and NF contributed to the *Deform* plugin.
P.L. contributed to the development of features and to writing the manuscript. E.F. conceived
the concept of MorphoNet, developed the code, contributed to its featuring and wrote the
manuscript. All authors contributed to discussions on the structure of the manuscript.

Competing Interests: The authors declare no competing interests.

References

1. McDole, K. *et al.* In Toto Imaging and Reconstruction of Post-Implantation Mouse

Development at the Single-Cell Level. *Cell* **175**, 859-876.e33 (2018).

2. Pachitariu, M. & Stringer, C. Cellpose 2.0: how to train your own model. *Nat. Methods* **19**,

1634–1641 (2022).

3. Cutler, K. J. *et al.* Omnipose: a high-precision morphology-independent solution for bacterial

cell segmentation. *Nat. Methods* **19**, 1438–1448 (2022).

4. Liu, Y., Jin, Y., Azizi, E. & Blumberg, A. J. Cellstitch: 3D cellular anisotropic image

segmentation via optimal transport. *BMC Bioinformatics* **24**, (2023).

5. Where imaging and metrics meet. *Nat. Methods* **21**, 151–151 (2024).

6. Maška, M. *et al.* The Cell Tracking Challenge: 10 years of objective benchmarking. *Nat.*

Methods **20**, 1010–1020 (2023).

7. Schneider, C. A., Rasband, W. S. & Eliceiri, K. W. NIH Image to ImageJ: 25 years of image

analysis. *Nat. Methods* **9**, 671–675 (2012).

8. Sofroniew, N. *et al.* napari: a multi-dimensional image viewer for Python. Zenodo

https://doi.org/10.5281/zenodo.7276432 (2022).

9. Berg, S. *et al.* ilastik: interactive machine learning for (bio)image analysis. *Nat. Methods* **16**,

1226–1232 (2019).

10. Correia, P. L. & Pereira, F. Stand-Alone Objective Segmentation Quality Evaluation.

EURASIP J. Adv. Signal Process. **2002**, 1–12 (2002).

11. Valindria, V. V. *et al.* Reverse Classification Accuracy: Predicting Segmentation

Performance in the Absence of Ground Truth. *IEEE Trans. Med. Imaging* **36**, 1597–1606

(2017).

12. Leggio, B. *et al.* MorphoNet: an interactive online morphological browser to explore complex

multi-scale data. *Nat. Commun.* **10**, 2812 (2019).

13. Manni, L. *et al.* Morphological Study and 3D Reconstruction of the Larva of the Ascidian

Halocynthia roretzi. *J. Mar. Sci. Eng.* **10**, 11 (2022).

14. Chung, J. *et al.* A single oscillating proto-hypothalamic neuron gates taxis behavior in the

primitive chordate Ciona. *Curr. Biol.* **33**, 3360-3370.e4 (2023).

15. Refahi, Y. *et al.* A multiscale analysis of early flower development in Arabidopsis provides

an integrated view of molecular regulation and growth control. *Dev. Cell* **56**, 540-556.e8

(2021).

16. Guignard, L. *et al.* Contact area–dependent cell communication and the morphological

invariance of ascidian embryogenesis. *Science* **369**, eaar5663 (2020).

17. Dardaillon, J. *et al.* ANISEED 2019: 4D exploration of genetic data for an extended range of

tunicates. *Nucleic Acids Res.* **48**, D668–D675 (2020).

18. CellMet: Extracting 3D shape metrics from cells and tissues | bioRxiv.

https://www.biorxiv.org/content/10.1101/2024.10.11.617843v1.

19. Weigert, M., Schmidt, U., Haase, R., Sugawara, K. & Myers, G. Star-convex Polyhedra for

3D Object Detection and Segmentation in Microscopy. in *2020 IEEE Winter Conference on*

Applications of Computer Vision (WACV) 3655–3662 (IEEE, Snowmass Village, CO, USA,

2020). doi:10.1109/WACV45572.2020.9093435.

20. Vergara, H. M. *et al.* Whole-body integration of gene expression and single-cell morphology.

Cell **184**, 4819-4837.e22 (2021).

21. Stegmaier, J. *et al.* Real-Time Three-Dimensional Cell Segmentation in Large-Scale

Microscopy Data of Developing Embryos. *Dev. Cell* **36**, 225–240 (2016).

22. Walt, S. van der *et al.* scikit-image: image processing in Python. *PeerJ* **2**, e453 (2014).

23. Barone, V. *et al.* Local and global changes in cell density induce reorganisation of 3D

packing in a proliferating epithelium. *Development* **151**, dev202362 (2024).

24. Andrés-San Román, J. A. *et al.* CartoCell, a high-content pipeline for 3D image analysis,

unveils cell morphology patterns in epithelia. *Cell Rep. Methods* **3**, 100597 (2023).

25. Willis, L. *et al.* Cell size and growth regulation in the Arabidopsis thaliana apical stem cell

niche. *Proc. Natl. Acad. Sci. U. S. A.* **113**, E8238–E8246 (2016).

26. Fernandez, R. *et al.* Imaging plant growth in 4D: robust tissue reconstruction and lineaging

at cell resolution. *Nat Meth* **7**, 547–553 (2010).

27. Kar, A. *et al.* Benchmarking of deep learning algorithms for 3D instance segmentation of

confocal image datasets. *PLOS Comput. Biol.* **18**, e1009879 (2022).

28. Stringer, C., Wang, T., Michaelos, M. & Pachitariu, M. Cellpose: a generalist algorithm for

cellular segmentation. *Nat. Methods* **18**, 100–106 (2021).

29. Murray, J. I. *et al.* Automated analysis of embryonic gene expression with cellular resolution

in C. elegans. *Nat. Methods* **5**, 703–709 (2008).

30. Cazorla, C., Munier, N., Morin, R. & Weiss, P. Sketchpose: Learning to Segment Cells with

Partial Annotations.

Figure 1: Illustration of the visualization of datasets of various complexity and nature in the MorphoNet standalone application

Figure 2: MorphoNet Standalone Schema

Figure 3: Unsupervised quality assessment and curation of the Tribolium castaneum embryo

Figure 4: Starfish whole-cell segmentation using Cellpose

Figure 5: Curation of a segmented shoot apical meristem of Arabidopsis thaliana.

Figure 6: Curation of a Caenorhabditis elegans embryo dataset

Figure 7: Curation of a Phallusia mammillata ascidian embryo