# A population code for semantics in human hippocampus

Melissa Franch[1], Elizabeth A. Mickiewicz[1], James L. Belanger[1,3], Brad Joiner[1,3], Kalman A. Katlowitz[1], Hanlin Zhu[1], Ana G. Chavez[1], Assia Chericoni[1], Danika Paulo[1], Eleonora Bartoli[1], Suzanne Kemmer[3], Steven T. Piantadosi[4], Nicole R. Provenza[1], Jay A. Hennig[2], Benjamin Y. Hayden[1,3]*, and Sameer A. Sheth[1]*

1. Department of Neurosurgery, Baylor College of Medicine, Houston, Texas, United States of America
2. Department of Neuroscience, Baylor College of Medicine, Houston, Texas, United States of America
3. Department of Linguistics, Rice University
4. Department of Psychology, University of California Berkeley

* Correspondence: melissa.franch@bcm.edu

**Funding statement**
This research was supported by the McNair Foundation and by NIH R01 MH129439.

**Competing interests**
The authors have no competing interests to declare.

**Acknowledgements**
We thank Jeff Johnston, Joshua Adkinson, Justin Fine, Olga Buhlak, Victoria Gates, Raissa Mathura, and George Kokalas for invaluable assistance.

**Data availability**
The data that support the findings of this study are available from the corresponding authors upon reasonable request.

## ABSTRACT

As we listen to speech, our brains track the meanings of the words we hear. Recent successes of large language models suggest that distributed population geometry can capture rich semantic relationships between words. Motivated by this idea, we hypothesized that semantic information in the brain may likewise be expressed in distributed patterns of activity across neurons, rather than in the activity of neurons narrowly tuned to a specific word. We recorded responses of hundreds of neurons in the human hippocampus while participants listened to narrative speech. We find encoding of contextual word meaning in the simultaneous activity of neurons whose individual selectivities span multiple unrelated semantic categories. Decoding and population geometry analyses revealed distinct neural coding principles for low- versus high-frequency words, likely reflecting the greater polysemy of common words. Similar to embedding vectors in semantic language models, distance between neural population responses correlates with semantic distance; however, this effect was only observed in contextual embedding models (GPT-2 and BERT), suggesting that the semantic distance effect depends critically on contextualization. Consistent with this, we find that neural population activity supports a multidimensional semantic subspace that aligns most closely with the contextual structure captured by GPT-2. Moreover, for semantically similar words, even contextual embedders showed an inverse correlation between semantic and neural distances; we attribute this pattern to the noise-mitigating benefits of contrastive coding. Ultimately, these results provide a neurocomputational account for understanding how neural populations track word meaning.

## INTRODUCTION

The principles by which neurons encode meaning remain poorly understood. One hypothesis is that the brain uses a population code, so that word meanings are represented in patterns of activation across a large number of units (Frisby et al., 2023; Goldstein et al., 2022, 2024; Landauer & Dumais, 1997; Mitchell & Lapata, 2008; Piantadosi et al., 2024; Pulvermüller, 1999; Rogers & Mcclelland, 2004). Interest in population coding has grown in recent years because it overlaps with how meaning is represented in large language models (LLMs, Devlin et al., 2018; Joulin et al., 2016; Mikolov, Chen, et al., 2013; Mikolov et al., 2013; Pennington et al., 2014; Radford et al., 2019; Vaswani et al., 2017). Population coding facilitates solutions to several important problems including similarity judgments, analogies, generalization, hierarchical reasoning, pattern completion, and efficient learning (Chen et al., 2017; Kommers et al., 2015; Mejri et al., 2024; Tversky, 1977; Piantadosi et al., 2024). For example, if population codes are structured so that words with more similar meanings evoke more similar neural responses, then judging similarity can be as simple as calculating the distance between two words' response vectors (Devlin et al., 2018; Erk, 2012; Grand et al., 2022; Joulin et al., 2016; Pennington et al., 2014; Radford et al., 2019; Tversky, 1977; Vaswani et al., 2017).

Population coding has attracted growing interest from scholars in recent years (Ebitz and Hayden 2021; Saxena and Cunningham 2019; Rigotti et al., 2013; Fusi et al., 2016; Tye et al., 2024). Here, we hypothesized specifically that (1) neural responses collectively instantiate a representation of word meaning that is reliable across repeated contexts, but (2) varies as the context of the word changes its specific meaning. Moreover, we hypothesized that (3) a large number (i.e., more than 1%) of neurons are involved in encoding any given concept, and (4) the same population of neurons is involved in a range of distinct concepts.

One difficulty in assessing the population coding hypothesis with linguistic stimuli is that language encoding is highly contextual (Devlin et al., 2018; Peters et al., 2018; Radford et al., 2019; Vaswani et al., 2017) and neuroscience research has only recently begun relating neural and contextual word embeddings (Chang et al., 2008; Deniz et al., 2023,Goldstein et al., 2022, 2023, 2024; Hong et al., 2024; Hosseini et al., 2024; Kumar et al., 2024; LeBel et al., 2021; Tang et al., 2023; Tuckute et al., 2024; Zada et al., 2024). Moreover, only one existing study has examined contextual embeddings at the single neuron level (Katlowitz et al., 2025). Indeed, word meanings in normal language are highly contextually dependent. For example, the word "sharp" may mean something entirely different in the phrases "sharp knife" and "sharp mind". Contextual semantic embedders capture these nuances of language (Linzen & Baroni, 2025; Manning et al., 2020; Pavlick, 2025; Vaswani et al., 2017; Radford et al., 2019). We hypothesized that incorporating context would improve fit quality to neural representations of semantics.

We were especially interested in the hippocampus because of its well-established
role in semantic and conceptual coding in humans (Duff and Brown-Schmidt 2012, Piai
et al., 2016, Blank et al., 2016; Davachi, 2006; Dijksterhuis et al., 2024; Fletcher et al.,
1997; Quian Quiroga et al., 2005 and 2009; Rey et al., 2025; Squire & Zola-Morgan,
1991; Tulving, 2002; Gelbard-Sagiv et al., 2008; Kolibius et al., 2023; Rutishauser et al.,
2021; Courellis et al., 2024; Cohn-Sheehy et al., 2021; Binder et al., 2009; Suthana et al.,
2015; Karkowski et al., 2025; Baldassano et al., 2017). Classic neuropsychological
studies demonstrated that hippocampal integrity is essential for forming and retrieving
semantic knowledge and relational memory (Squire & Zola-Morgan, 1991; Tulving,
2002; Davachi, 2006; Fletcher et al., 1997), and early lesion and imaging work showed
its involvement in constructing relational and conceptual meaning from experience
(Fletcher et al., 1997; Duff and Brown-Schmidt, 2012). Neuroimaging studies find
language specific responses in the hippocampus (Blank et al., 2016), and implicate the
broader medial temporal lobe in abstract semantic processing (Binder et al., 2009).
Additionally, intracranial recordings show that hippocampal activity tracks conceptual
relationships during speech and language comprehension (Piai et al., 2016).
Electrophysiological recordings from single hippocampal neurons reveal they encode
abstract, semantic-level information: they respond selectively to concepts rather than
sensory details and generalize across exemplars (Quian Quiroga et al., 2005; 2009;
Karkowski et al., 2025; Rutishauser 2021; Gelbard-Sagiv et al., 2008; Courellis et al.,
2024; Dijksterhuis et al., 2024; Rey et al., 2025). This form of conceptual coding may
support the retrieval of semantic associations and facilitate content-guided recall, as
demonstrated across several studies (Dijksterhuis et al., 2024; Kolibius et al.,, 2023;
Rutishauser 2021; Gelbard-Sagiv et al., 2008; Suthana et al., 2015). Building on this,
recent work has shown that hippocampal populations also track higher-order narrative
structure and evolving semantic content during naturalistic experiences (Cohn-Sheehy et
al., 2021; Baldassano et al., 2017). Together, these findings converge to establish the
hippocampus as a central node for representing semantic content, relational structure, and
conceptual knowledge in service of language and memory.
We recorded responses of neurons in the hippocampus of epilepsy patients
undergoing intracranial monitoring for seizure activity while those patients listened to
continuous, narrative speech. We found that individual neurons have complex, multi-
word tunings, and that lexical concepts are encoded by large and heteromorphic
populations of hippocampal neurons. Moreover, we find that semantic embedding
distance correlates with neural embedding distance, but only for language models that
involve a high degree of contextual embedding (i.e, GPT-2 and BERT). These contextual
language models predict word level neural population activity patterns better than static
word embedding models. Indeed, neural embedding variance correlates with polysemy,
changing activity with different instances of the same word. These contextually driven
neural representations may contribute to the separation of high- and low-frequency words

observed in population geometry and decoding models. Finally, we find evidence for a
strong contrastive code for highly similar words. Together, these results endorse the
hypothesis that the hippocampus employs population coding principles for semantics
during natural language comprehension. In this code, semantic relationships are reflected
in the geometry of neural population activity: words with similar meanings evoke more
similar patterns of activity across neurons, whereas semantically distinct words evoke
more divergent patterns. Importantly, these relationships align most strongly with
contextual language embeddings, indicating that the hippocampal population code
reflects context-dependent meanings rather than fixed lexical categories. Thus,
contextualized semantic structure is recapitulated in distributed neural responses in the
hippocampus.

**RESULTS**

**Neural encoding of meaning**

Ten native English-speaking patients (six males and four females) undergoing

neural monitoring for epilepsy listened to 47 minutes of English speech (six monologues

taken from the Moth podcast, **Methods, Fig. 1a and b**). This stimulus set consisted of

7,346 words, of which 1,351 were unique. We collected responses of isolated single

neurons in hippocampus (HPC, n=356 neurons, **Extended Data Fig. 1**) from 10 patients.

Overall, neurons showed a clear response to the onset of individual words with a

characteristic ramping to a peak, followed by a gradual decline in firing, although there

was a great deal of diversity across neurons (**Fig. 1c-e and Extended Data Fig. 2**).

Across words of different durations (short ~100 ms, middle ~200 ms, long ~500 ms),

neurons show a similar rise in firing rate shortly after word onset, but responses attenuate

quickly for short words and remain sustained for longer words (**Extended Data Fig. 3**).

Therefore, we computed firing rate during an epoch starting 80 ms after the onset of each

word (to account for the approximate response latency) and lasting the duration of the

word (see **Methods**). Rates were normalized by word duration. All analyses were

repeated with a variety of response epochs which yielded similar results (data not shown).

A subset of patients (n=4) also listened to monologues containing nonsense words

(Keuleers & Brysbaert, 2010, *jabberwocky stimuli*, 1,890 words, see **Methods**) following

the podcast episodes. The nonsense narratives included words modified from real ones to

create meaningless, novel terms, such as "toom" or "skook." These nonword stimuli

preserved syntactic structure by retaining function words and morphemes but lacked

coherent semantics. We found that 57% of neurons (75/125) exhibited a significant

change in firing rate to non-word stimuli, with most cells showing markedly reduced

activity for nonwords relative to words (**Fig. 1d and Extended Data Fig. 2b**).

Additionally, hippocampal neural population activity strongly distinguishes words from

nonwords, achieving an average decoding accuracy of 75% (chance is 50%; **Extended**

**Data Fig. 2c;** see **Methods**). Note that these Jabberwocky stimuli do not fully control for

language because listeners could have stopped paying attention to them once they

realized the stimuli did not carry meaning.

Next, we sought to better understand the relationship between neural activity and

semantics, particularly how language unfolds over time as words are heard in sequence.

To do this, we predicted each neuron's spike count for a given word from its

dimensionality-reduced Word2Vec embeddings (Mikolov, et al., 2013), word duration,

and their interactions (**Fig. 1f**). Word2Vec represents each word as a fixed (i.e., non-

contextual) 300-dimensional vector, meaning, for example, the embedding for "camp"

remains the same whether it is used as a noun or a verb. The Poisson linear model (cross-

validated, ridge regression; mixed effects models are not used since we fit a model to

each neuron from each patient separately) fit the responses of 62% (n=222/356) of

neurons, showing a significant and positive log-likelihood difference between actual and

shuffled models and positive adjusted R-squared values (**Fig. 1f-g; Extended Data Fig.**
**4c** see **Methods**). Semantic encoding models explained a median 26% of the neural
variance (**Extended Data Fig. 4c**). Adding semantic predictors to a duration-only model
significantly improved fit, raising adjusted $R^2$ by a median of 0.01 (Wilcoxon z = 11.35, p
$< 10^{-9}$) and improving model performance by an average of 23% across neurons
(**Extended Data Fig. 4d**). Likewise, semantic information significantly increased the
Pearson correlation between actual and predicted spiking activity by 0.02 (semantic
model median r = 0.68; Wilcoxon signed-rank z = 5.99, $p < 10^{-9}$). Together, these effects
indicate that semantics captures variance in neural responses that cannot be explained by
word duration alone. We found comparable results with contextual embeddings (e.g.,
BERT embeddings fit 62% of neurons and GPT-2 layer 37 fit 54% of neurons; Devlin et
al., 2018; Note that we extract BERT embeddings in a left-to-right, unidirectional manner
for all analyses in this study, as seen in Lyu et al., 2023, Madureira et al., 2024 and
Kahardipraja et al., 2021.). Across patients, the model fit an average of 60% of recorded
neurons, with all patients contributing fitted neurons (mean = 10% recorded neurons per
patient). Among neurons successfully fit by the model, significant predictors included
word duration, embedding dimensions, and their interactions. Notably, the first eight
embedding dimensions were commonly selected across neurons, with the number of
significant predictors gradually decreasing across higher dimensions (see **Extended Data**
**Fig. 4a-b and Methods**). Removing function words and pronouns produced a modest but
significant drop in model fit (**Extended Data Fig. 5a–b**), yet their exclusion did not alter
any main findings (neither here nor throughout other analyses in the paper; we therefore
retain them).
To investigate whether neurons encoded the semantics or phonetics of a word, we
also fit neural tuning models with the phonemes of each word as predictors instead of
their embedding values (see **Methods**). Phonetic models fit fewer neurons than semantic,
fitting 42% (n=150/356) of neurons. Additionally, for neurons fit by both models (40%, n
= 142/356), the semantic model had significantly higher performance than the phonetic
model (median phonetic – semantic ΔAIC = 136, p < 0.001 and **Extended Data Fig. 4e-**
**f**). We find that, across neurons, adding semantic predictors significantly improved model
fit relative to a phonetic-only model (median $\Delta R^2$ = 0.003, sign-rank z = 12.4, p < 0.001).
In contrast, adding phonetic predictors to a semantic model did not improve performance
and slightly but significantly reduced explained variance (median $\Delta R^2$ = –0.001, z = –2.7,
p = 0.006; **Extended Data Fig. 4f**). Together, these results indicate that neural responses
are better explained by semantic than phonetic features, suggesting that single-neuron
activity reflects the meaning rather than the sound structure of words.
To understand the relationship between hippocampal activity and semantic,
phonetic, and syntactic features, we applied the same ridge regression encoding models
with a total of 61 linguistic features. Specifically, models included (1) full phonetic
embeddings (43 IPA phones; count coded, cf. Khanna et al., 2024), (2) 10 PCs of

semantic embeddings (Word2Vec, BERT, or GPT-2), (3) word order in sentence, (4) word order in clause, (5) opening node number, (6) closing node number, (7) word frequency (SUBTLEX-US), (8) pitch, (9) a scalar representing degree of polysemy (Cruse et al., 1986; Landauer, 2001; Ethayarajh, 2019), and (10) word duration (Manning et al., 2014). We found that one or more semantic embeddings were significant predictors for a mean 64% of the neurons fit by the model, followed by phonetic embeddings as the next most common significant predictor across neurons, fitting 41% of neurons on average (**Extended Data Fig. 4g**). Semantic embeddings also had the highest weights, followed by phonetic embeddings and opening and closing nodes (**Extended Data Fig. 4h**). Linguistic features like pitch, word position in clause, and word frequency were significant predictors for only 18% of neurons on average and had lower weights than semantic and phonetic predictors. Moreover, after regressing out variance explained by non-semantic linguistic features and modeling the residual neural activity, semantic embeddings continued to significantly predict firing (92/356 neurons; adjusted $R^2$ = 0.08; r = 0.35). In summary, even with a variety of linguistic features accounted for in the model, semantic predictors have the strongest and most widespread influence on neuronal activity, indicating that meaning remains the dominant driver of neural responses in the hippocampus.

Next, we used the same linear modeling to predict neural activity from up to five words in the past and future. We found that neural responses to the current word could be predicted from word embeddings up to one word in the past and up to two words in the future (LLH differences were always significantly greater than 0, see **Methods**). However, prediction accuracy showed a characteristic decay in decodability as a function of distance forwards and backwards in time (**Fig. 1g, right**). Thus, it appears that hippocampal neurons keep track of recently heard words and also show some evidence of encoding upcoming words, just as other brain regions have been shown to do (Goldstein et al., 2024; Goldstein et al., 2022; Goldstein, Wang, et al., 2023; Jamali et al., 2024; Tang et al., 2023; Zada et al., 2024). These findings suggest that hippocampal neuron responses integrate information across multiple words and could contribute to representing contextual semantics during natural speech. Note that these effects could also arise from overlapping neural responses across adjacent words or from correlations between nearby words in natural speech. Additionally, whether this future word encoding represents a true prediction is a debated issue; our results do not resolve that debate (Schönmann et al., 2025).

We next identified the broad semantic categories that exist in our dataset. Word2Vec embedding distances recapitulate semantic distance, such that the embedding vectors for synonyms like 'dad' and 'father' have a smaller semantic distance (cosine distance) than unrelated words like 'dad' and 'emergency' (Joulin et al., 2016; Mikolov, Chen, et al., 2013; Mikolov, Sutskever, et al., 2013). We leveraged this fact to build semantic categories (**Fig. 1h**; Huth et al., 2016; Jamali et al., 2024). Silhouette criterion

analysis (**Fig. 1i**; Rousseeuw, 1987) and k-means clustering of the word embeddings (see
**Methods**) revealed 11 putative semantic categories in the story data, listed in increasing
word frequency, with examples in brackets: (1) body parts [hand, lungs, scar], (2) places-
[hospital, office, cabin], (3) emotional  [cheer, disgust, feelings], (4) mental- [know,
answer, imagine], (5) social  [friends, queen, dad] (6) objects [book, flowers, pigeon], (7)
visual  [beautiful, green, sizzling], (8) numerical [another, eleven, moment], (9) actions
[shimmied, writing, elected], (10) identity [she, y'all, their], and (11) function words [the,
about, onto] (**Fig. 1j**). Note that the categorization here is based on a static Word2Vec
embedding rather than a contextual embedding, such as that provided by BERT or GPT-
2. In this case, clustering of single words based on contextual embeddings wouldn't
produce meaningful categories, because word meanings are determined by their local
contexts. We show these categories in Extended Data Fig. 6a-b. We will cover contextual
embeddings below (**Figs. 3-4**).

**Fig. 1 | Hippocampal neurons track spoken words during language comprehension.**
**a,** Electrode recording location of hippocampal neurons from ten patients. **b,** Continuous spiking activity from five example hippocampal neurons from patient 6 during words heard during the experiment, as shown in the spectrogram. **c**, Peri-stimulus time histograms and raster plots demonstrating responses to word onsets from four distinct hippocampal neurons in patient 6 (bottom row) and 7 (top row). Dashed lines represent word onset. Plots display mean firing rate ±SEM shaded. **d,** Left - Peri-stimulus time histogram during words and jabberwocky (nonsense) non-words. Right - 71/125 neurons

from four patients that exhibit significantly different firing rates between real and non-
words. P = 5.6x10$^{-5}$, Wilcoxon signed-rank test. Red line represents the mean firing rate
from words and non-words (14.78 and 13.98). **e**, The firing rate of one neuron occurring
across the duration of all words from the six stories during language comprehension. **f**,
Regression equation used to fit an individual neuron's spike count from word
embeddings, word duration, and their pairwise interactions. Dim reflects the number of
predictors including the first 100 principal components of the word embeddings and word
duration. *SC* is a neuron's spike count for each word. **g**, Left – histogram of log-likelihood
improvements (LLH diff; actual – shuffled models) for fitted neurons (n = 222) from Poisson
ridge regression predicting neuronal spike counts using the equation in **f** for the current
word. Right – Log-likelihood improvement of all neurons from the current word duration
and embeddings (index 0) and embeddings of past and future words. Boxes reflect the
interquartile range with median; navy curve is fit to the median of each box; circles are
outliers. The y-axis is truncated for visual clarity. **h**, Similarity matrix of median pairwise
cosine distances between word embeddings within and between semantic categories
that arise from all words. **i**, Silhouette score used to determine the number of semantic
categories for K-means clustering of words. **j,** All words plotted in their dimensionality
reduced embedding space and colored according to their semantic category.
304
**A distributed coding of semantics**
One possible way to represent meaning in the brain is through neurons that
selectively respond to single words, or to single categories of semantically related words,
such as those associated with family, sports, or nature (Jamali et al., 2024). However, this
categorical coding regime could be biologically inefficient, as it would require many
neurons - enough needed for all the concepts learned across one's life. We hypothesized
instead that word coding would be highly distributed, with neurons exhibiting mixed
selectivity- meaning one word should be encoded by many different neurons and a single
neuron should encode many, semantically unrelated words (Rigotti et al., 2013; Fusi et
al., 2016; Johnston et al., 2020 and 2024).
To quantify individual neuron encoding of words, we performed a Receiver
Operating Characteristic (ROC) analysis (**Fig. 2a-b**), a standard approach that has
previously been used to characterize neural responses during behavior (Britten et al.,
1992; Li et al., 2017). For statistical reasons (**Methods**), we used only words that
occurred at least four times in the data (n = 283 words), and compared firing rates evoked
by each word to all others (see **Methods**). Every single one of these 283 words was
encoded by at least 3 neurons (**Fig. 2c-e**). The words with the least encoding (i.e., most
sparsely coded) were 'was' and 'and', encoded by exactly 3 neurons; the most dense
word, 'hit", was encoded by 67 neurons (0.8 and 18.8% of our sample, respectively, **Fig.**
**2d-e**). On average, a single word is encoded by 37 neurons (10.4%, **Fig. 2d**), suggesting a
distributed code for semantics. Likewise, most neurons encoded many words. Only 6 out

of 356 neurons did not encode any words, and the median number of words encoded by a

neuron was 6 words (**Fig. 2f**).

Are the words a neuron encodes semantically similar or different? Surprisingly,

the same neuron does not reliably encode semantically similar words. For example,

within the social category (category 5), we examined encoding of words related to the

concept of family (mom, dad, father, brother, and son), and found minimal overlap

between neurons that encode each family-related word (**Fig. 2g**). Indeed, of the 28

neurons encoding "father" and 19 encoding "dad," only 7 encode both words (**Fig. 2g**).

This low overlap reflects the contextual nature of hippocampal semantic coding during

natural language comprehension - neurons encode the meaning of a word as it is used in a

specific narrative context, rather than responding to membership in a broad semantic

category**.** Notably, the distinct words that a cell encoded spanned semantic categories and

phonology. For example, neuron 167 encodes the words: 'lot', 'remember', 'even',

'they', 'those, and 'make'; neuron 252 encodes the words: 'she', 'last', 'out', 'school',

and 'team'.  Each of those neurons encode words that span 5 unique semantic categories.

Overall, a given neuron's response field spanned 4 of our 11 semantic categories (**Fig.**

**2i**). (And, recall that these proportions refer to all sampled neurons, not just a preselected

subset of selective neurons).

Finally, for each neuron (limited to neurons that significantly encoded at least two

words, n = 334), we quantified its ***semantic range*** by computing the cosine distance

between embeddings of all pairs of words it encoded. We compared this distribution to a

null one that represents the full semantic space of the word data (**see Methods).** On

average across embedding models, 56% of neurons (186/334) encoded words that

spanned the full semantic range of the data, as determined by both bootstrap-based

significance ($\geq$ 95% support) and 95% confidence-interval coverage criteria (see

**Methods**). 91% of total neurons (304/334) encoded words that span at least 70% of the

full semantic range. Together, these results demonstrate that hippocampal neurons exhibit

broad, mixed semantic tuning.

We also wondered whether more specific concepts, like proper nouns, were

encoded in this distributed manner. Only three proper nouns appeared frequently enough

in our data to perform statistics: 'Mark,' 'God,' and 'Michelle'. These three are also

encoded across neurons in the population, with 'God' showing the highest density at 60

neurons (**Fig. 2h**). 89 neurons (25%) encoded these 3 proper nouns, with minimal

neuronal overlap between them (14 neurons encoded all 3 names). Across semantic

categories, fewer neurons encoded identity (pronouns) and function words, while more

critical and less frequent categories, such as body parts and emotion words, were

distributed - encoded by many neurons (**Fig. 2j**). We found that such densely coded

words had significantly higher classification performance (area under the curve)

compared to sparsely coded words, suggesting neurons exhibit more distinct firing rates

patterns for these less frequent words that are critical for understanding (**Fig. 2K**).

**Fig. 2 | Hippocampal neurons represent words with a distributed code. a**, Example firing rates from one neuron during all occurrences of the word, "go" and a random subset of other words. **b**, Receiver operator characteristic curve for the same neuronal activity and words in **a**. **c**, For each word (line), the standardized area under the curve (AUC) from each neuron that significantly classified that word from all others (see Methods). For each word, neurons encoding that word are sorted on the x-axis from greatest to lowest encoding performance. **d**, Histogram of the number of neurons encoding each word. Every word was encoded by at least 3 neurons. **e**, The same as in **d** but all 283 word text plotted based on the number of neurons that encode them, with added jitter for readability. **f,** Histogram of the number of words encoded by each neuron. **g,** Assessment of overlap between neurons encoding words related to the concept, family. Numbers in

the matrix and circles represent the number of coding neurons. **h,** Left - Number of
neurons encoding proper nouns from ROC analysis. Right - AUC values for proper noun
encoding. **i,** Number of semantic categories from the words that each neuron encodes.
Dashed line represents the median. **j,** Average number of neurons encoding words from
each semantic category. **k,** Probability density plots of AUC values from sparse words (
n = 1,517 AUC values from words with < 28 cells encoding them) and dense words (n =
1,632 AUC values from words with more than 55 cells encoding them). P = $1.643 \times 10^{-9}$,
Wilcoxon rank-sum test.
386
387    **Hippocampal population activity reflects semantic relationships**
388            In semantic embedders like Word2Vec, words are represented as points in a high
dimensional space, and distance in this space corresponds to semantic distance (**Fig. 3a**).
Thus, synonyms like "mom" and "mother" are located close to each other in embedding
space, while unrelated terms like "mom" and "tarmac" are located far apart. Here, we
follow the standard approach of using angular (cosine) distance between embedding
vectors to quantify vectorial distance (Mikolov et al., 2013; Pennington et al., 2014;
Radford et al., 2019). We performed an analogous analysis on the responses of a
population of neurons to ask whether *neural embedding distances* are correlated with
semantic embedding distances (**Fig. 3b**). Overall, we find that contextual embedding
distance between randomly selected word pairs is correlated with their neural embedding
distances (**Fig. 3c-e**). Consider, for example, the contextual embedder BERT (using
unidirectional embeddings; Lyu et al., 2023; Madureira et al., 2024;  Kahardipraja et al.,
2021; Devlin et al., 2018; Pearson r = 0.0650, p<0.0001, **Fig. 3d;** Note that each data
point represents the cosine distance (on the y-axis) of neural responses between two
single words, with no averaging across repetitions.). Using GPT-2, we also found a
significant positive correlation between neural distance and semantic distance (r =
0.0921, p<0.0001, **Extended Data Fig. 7a and Fig. 3j**).
405            Note that while the size of this correlation is low, this is inevitable given the
extremely high variance of single neuron firing rates and the fact that each datapoint
reflects a single occurrence of a given word pair. Indeed, we quantified the maximum
correlation achievable between the actual semantic embeddings and their altered version
that mirrors neural data (see **Methods**), and found that it was 0.122 and 0.119 for BERT
and GPT-2 respectively. Therefore, the neural-BERT correlation of 0.06 captures 54% of
the noise-limited ceiling, showing that over half of the model's representational structure
is recoverable despite the high variability shown by single neurons for single repeats of a
word (**Extended Data Fig. 7d**). The neural-GPT-2 correlation of 0.09 is, relatively, even
stronger, reaching 76% of the ceiling (**Extended Data Fig. 7b-d**). Moreover, neural-
semantic correlations exceed the entire shuffle-based null distribution where neural
responses were shuffled across words, indicating that the effect reflects true neural-
semantic structure rather than an artifact of having many data points (gray histograms,
**Extended Data Fig. 7d**).

This problem of high noise in neuron's firing rates could cause confusion for
words with the most similar embeddings. Such word pairs include "but and so", "we and
we're", and "he and him" (although the embeddings also include local context not given
here, **Fig. 3f**). While the brain needs to recognize their similarity, it also needs to
maintain their semantic separation as well. Thus, we hypothesized that, at the finest scale,
neuronal embeddings would have an additional feature of contrastive coding (sometimes
called repulsive coding; Bromley et al., 1994; Chanales et al., 2017; Prince et al., 2025;
Radford et al., 2021; Tian et al., 2020), which would allow for separation between
similar, but still distinct, words. We find precisely this: pairs of closely related words
(regardless of semantic category) tend to show a *negative* correlation between semantic
and neural distance (**Fig. 3f-g**). In other words, the relation between semantic and neural
embedding is scale-dependent: negative for the finest scale and positive for all others
(**Fig. 3g**). Specifically, the negative pattern is observed when considering the word pairs
whose semantic distances span the range of $r = 0.15$ to $r = 0.35$ (these comprise 2.16% of
the words in our sample, **Fig. 3f-g**). (Note that words with a range of $r < 0.15$ comprise
less than one tenth of one percent of pairs, and data in this range are too noisy to
meaningfully interpret). These highly similar pairs include many pairs of identical words;
however, this negative correlation in semantically close pairs is driven entirely by word
pairs consisting of different words (near-synonyms like "sort/kind" and "are/were"),
rather than identical word pairs (such as "and/and" or "the/the"). Specifically, in the
range of 0.15-0.35, we found $r = -0.151$ ($p < 0.0001$) for different word pairs (**Fig. 3f**)
and $r = +0.032$ ($p = 0.45$) for identical pairs (**Fig. 3h**).
Notably, this coding regime was not unique to BERT embeddings. The same
contrastive coding for semantically similar word pairs and pattern separation for
semantically different words is also observed in GPT-2 layer 37 embeddings (notice the
similarity between **Fig. 3g and 3i** and **Extended Data Fig. 7a-d**; Radford et al., 2019).
Interestingly, we found a negative correlation between semantic and neural distance for
early GPT-2 layers (1-13) and for Word2Vec embeddings (**Figure 3j-k**). We think this is
due to the early layers of GPT-2 being less contextual than the late layers, and thus more
similar to static, non-contextual embeddings from models like Word2Vec. Therefore, the
neural coding of semantics is both vectorial and highly contextual. Note that all results in
Figure 3 were replicated when performed with populations of neurons from each patient
individually (**Extended Data Fig. 7e-g**). Additionally, removing function words and
pronouns slightly increased neural–semantic distance correlations, suggesting that these
words add context-driven variability while content words yield more consistent semantic
responses (**Extended Data Fig. 5c**). Because this does not change our results
qualitatively, we retain them in the analysis.
Interestingly, the distance between neural embeddings of words within a semantic
category is a function of increasing word frequency (**Fig. 3l, blue**; this is the case for
inter-category distances as well). Meaning, low-frequency body part words like "hand"

and "finger" are closer in both neural space and the semantic space of contextual
embeddings, while high-frequency identity words like "everyone" and "they" show
greater distance, as seen in **Fig. 3l** (red, pink, and blue). In other words, frequent words
are more centrally positioned in the high-dimensional embedding space, a pattern that is
replicated in the hippocampal coding. Indeed, applying context to semantic embeddings
causes a reduction in semantic distance for low-frequency words and increases it for
high-frequency words, compared to static embeddings like Word2Vec (**Fig. 3l, gray**).
This shift, influenced by context, aligns with the pattern of category and frequency-
dependent neural distance, perhaps explaining why Word2Vec embedding distances are
negatively correlated with neural data, whereas contextual models show a positive
correlation, more accurately reflecting the vectorial and contextual encoding of semantics
in the hippocampus.

**Fig. 3 | Neural distance recapitulates semantic distance. a,** We define semantic
distance as the angular distance in a high dimensional space between two semantic
vectors (embedding values for each word). **b,** We define neural distance in the analogous
manner, where each word's neural embedding is the vector of firing rates from all neurons
for that word. **c,** Semantic BERT embedding and neural embedding distance correlations
among all word-pairs within each of the eleven semantic categories. While most are
positive, some categories have negative correlations, likely due to contrastive coding. **d,**
Scatter plot illustrating the correlation between neural and semantic embedding
distances between all 26,978,185 word pairs. Pink line: regression line. Each dot
represents one randomly selected word pair; magenta text indicates example pairs. **e,**
Histogram of neural embedding distances; this plot is the marginal of **d** across the x-axis.
**f,** Expanded view of the data from **d** in the neural range of 0.15-0.25; this range represents
2.16% of the data. In this range, the correlation between neural and semantic distances
is negative. **g,** Histogram of BERT semantic embedding distances; this plot is the
marginal of **d** across the y-axis. Below it is shown the semantic-neural correlation
coefficient for the sub-range of BERT values centered on the x-axis point. While this line
is generally positive in value, at especially short distances (low x-values), it turns negative.
That negative correlation may reflect contrastive coding. **h,** Same data as in **g**, but limited
to pairs in which the same word is compared in two locations. Because BERT is a
contextual embedder, these will not have precisely the same value. **i,** Same data as in **g**,
but using GPT-2 layer 37 rather than BERT. Same effects are observed, indicating that
effects are not due to BERT. **j,** Correlation between semantic and neural distance across
all layers of GPT-2. Early layers that are non-contextual embeddings have negative
correlations with neural data, while higher, contextual layers are positive. Red indicates
a layer with nonsignificant correlation. **k**, The same as in **d** but with Word2Vec semantic
embeddings. These embeddings are static and non-contextual (similar to early layers in
GPT-2), and negatively correlate with neural distance. **l,** Within-category neural distance
and semantic distances from different language models. The arrow reflects how context
changes semantic embeddings, improving their association to neural patterns of
semantic coding. Word2vec r = -0.22, BERT r =  0.62\*, GPT-2 r = 0.72\*, Neural r = 0.83\*;
Pearson correlation coefficient, \*P < 0.05, regression lines plotted.
503
**Semantic coding is contextual**
The meaningful correspondence observed between neural and semantic distances
led us to test a central prediction: that a word's semantic representation should be
decodable from its neural population activity. We applied cross-validated reduced-rank
regression to assess how well neural population activity predicted 30-dimensional
semantic embeddings from Word2Vec, BERT, and GPT-2 (Izenman 1975; Semedo et al.,
2019; Wu and Pillow, 2025). Model performance was quantified as the cross-validated
variance explained (1 – NSE) across predictive subspace dimensionalities (ranks = 0 -
15). All models showed near-zero performance at rank 0 (predicting the mean),
confirming an unbiased baseline. Across ranks, predictive performance increased

monotonically before reaching a plateau. GPT-2 achieved the highest accuracy (patient-
averaged 1–NSE = 0.06), followed by BERT (0.01) and Word2Vec (0.003), with a
significant effect of model type **(Fig. 4a**; $F(2, N) = 82.3$, $p = 9.3 \times 10^{-16}$). Additionally,
performance plateaued at different subspace dimensionalities for each language model:
median rank of 12 for GPT-2, 9 for BERT, and 3 for Word2Vec (dashed lines, **Fig. 4a**).
These optimal ranks reflect the dimensionality of the predictive neural subspace required
to account for semantic structure in each embedding space. The higher optimal rank and
superior performance for the contextual models (GPT-2 > BERT > Word2Vec) indicate
that neural population activity shares a richer, more multi-dimensional linear structure
with GPT-2 embeddings than with Word2Vec. This pattern implies that semantic
information is distributed across multiple neural dimensions rather than confined to a
single feature axis, consistent with a population-level, vector-like code. In contrast, the
lower optimal rank for Word2Vec indicates that non-contextual embeddings capture a
narrower, lower-dimensional component of the neural representation. The fact that GPT-
2 and BERT outperform Word2Vec even at rank 1 suggests that the primary neural
dimension is contextual, not categorical - if it reflected a single feature like 'people vs.
places,' all models should perform similarly at rank 1 (or Word2Vec would have the
highest performance) because the decoder is limited to expressing only that one contrast.
Together, these results demonstrate that contextual language models provide a
substantially better and higher-dimensional description of the semantic information
expressed in single-neuron population activity. Findings were consistent across patients
(**Fig. 4b-c**).
Given this evidence for a high-dimensional neural-semantic space, we next
examined how semantic categories are arranged within this population geometry. For
each patient separately, we performed Principal Component Analysis (PCA) of neurons'
firing rates for every word (7,346 words by patient's neurons), reducing the
dimensionality of their neurons' responses to 2 components. To visualize neural
organization of semantics across patients, we first projected each patient's neural data
into the first two principal components. These two components explained 44% of the
total neural variance, on average. Next, we computed the centroids of each semantic
category in PCs 1 and 2, and then aligned this data across patients into a common
reference frame, yielding a shared low-dimensional subspace (see **Methods**). Within
individual patient subspaces and within this shared one, we noticed the first axis (PC1)
separated social, objects, and places, from identity, mental, and action words. Notably,
there appeared to be an organization based on word frequency, where high-frequency
words clustered near the center and low-frequency words were more spread out (**Fig. 4d**).
Indeed, when we computed, for each patient, their semantic category centroid to subspace
center distance, we found a significant decrease in distance with increasing word
frequency ($r = -0.78$, $p = 0.004$; **Fig. 4e**), meaning high-frequency words were more
overlapping and central in the subspace.

Notably, this representational geometry aligned with decoding performance,
meaning semantic categories that were further from the center in the subspace were more
easily decodable compared to geometrically clustered categories (r = +0.37, p = 0.0001,
Pearson correlation). Each semantic category can be decoded from the others using
population activity (see **Methods**), but high frequency words like numbers, actions, and
function words had reduced decoding performance compared to low frequency words
(**Fig. 4f**). Together, these findings suggest, as do others above, that neural coding
principles differ markedly for high frequency and low frequency words.

Indeed, we also observe a trend in word frequency for neural distance. For word
pairs within each semantic category, neural distance increases with word frequency (**Fig.
3l**, blue and **Fig. 4g,** diagonal), meaning neural firing rate population patterns between
two common words are more distinct than patterns between two low frequency words. In
fact, high-frequency words exhibited the greatest neural separation both among
themselves and relative to words from other semantic categories (**Fig. 4g**). Although PCA
projects high-frequency words close to the center (because their distinctions lie in low-
variance axes not captured by PCs1-2, **Fig. 4d**), vectorial distance shows that they are
broadly separated across the full high-dimensional neural space.

Why do common words cluster in neural state space, have reduced decoding, and
increased vectorial neural distance (within-category separability) compared to other, less
spoken words? We think this is due, in large part, to the fact that common words are
more polysemous (**Fig. 4h, top;** Zipf, 1945), meaning the same word can have different
meanings depending on the context in which it is spoken. To explore this idea further, we
computed polysemy for each word by taking the cosine distance between BERT
embedding vectors of repeated occurrences of the same word (n = 594 distinct and
repeated words, see **Methods;** Cruse et al., 1986; Landauer, 2001; Ethayarajh, 2019). We
then computed "neural polysemy", or the neural distance between all occurrences of the
same word, and for each word, took the Pearson correlation between its median neural
distance and polysemy value. We find a strong significant correlation between neural
polysemy and word polysemy (r = 0.54, **Fig. 4i**). This positive correlation remains even
when function words and pronouns are removed (r = 0.49, **Extended Data Fig. 5d**).

We also computed polysemy for each word as the total number of synsets (i.e.,
distinct senses) associated with each word in WordNet (Fellbaum, 1998) and these
polysemy values yielded the same results shown in Fig. 4h-i (Pearson r = 0.514, p <
0.001). Polysemy is likely driving the larger neural distance between words occurring
*within* high-frequency categories compared to low-frequency ones (**Fig. 4g and 3l**). The
words within these categories have more nuanced and flexible meanings, resulting in
greater semantic (in contextual models) and neural distance within categories (**Fig. 4g
and 3l**).

Polysemy also explains why high frequency categories are harder to decode from
all others - because these common words activate broad, overlapping neural patterns

rather than category-specific ones. For example, 'the' may produce similar neural
patterns to the noun that it modifies, such as 'the school', making 'the' and 'school'
harder to neurally distinguish, despite being members of two different semantic
categories (function words and places, respectively). Indeed, when words are clustered
using neural embeddings rather than semantic embeddings, the resulting groups do not
align with clear semantic categories, consistent with the idea that word meaning in the
brain is highly context-dependent (**Extended Data Fig. 8**). Given that neural distance
positively correlates with semantic distance in contextual models (**Fig. 3**), it follows that
neural activity patterns also strongly correlate with polysemy (**Fig. 4h, bottom and 4i**).
In other words, the meaning of a given high-polysemy word is more contextually driven
than the meaning of a low-polysemy word, and hippocampal encoding tracks with that
contextually driven meaning.
Because multiple linguistic features covaried with neural distance and polysemy,
we next asked which of them primarily drove the observed changes in neural activity
patterns. For each word pair, we used semantic distance, differences in duration,
frequency, and polysemy, and a binary indicator of whether the words belonged to the
same semantic category (0 = same, 1 = different) as predictors in a cross-validated ridge
regression model to predict neural distance (see **Methods**). We found that all predictors
were statistically significant, but semantic distance (from contextual models such as
BERT or GPT-2, see **Extended Data Fig. 9**) was the only one with a positive coefficient,
meaning that greater semantic dissimilarity was associated with greater neural separation
(**Fig. 4j;** semantic distance results were reversed in Word2Vec, see **Extended Data Fig.
9**). Limiting the model to the contrastive-coding range (semantic distance 0.14 - 0.4)
produced a sign reversal for semantic distance, whereas all other predictors remained
negative (**Fig. 4k**). This behavior identifies semantic distance as the sole predictor whose
relationship to neural geometry systematically tracks the emergence of contrastive
coding. Additionally, we used the same model architecture to predict neural polysemy
from word polysemy, word frequency, word duration, and semantic category. We found
that only word polysemy and duration were significant predictors of neural polysemy,
with polysemy associated with greater context-driven neural variability and longer
duration associated with more stable neural responses (**Fig. 4l**). Repeating the polysemy
and related analyses using only neurons that remained semantically selective after
controlling for other linguistic features produced similar results, consistent with a
distributed population code for semantics, where semantic relationships are carried by
patterns of activity across many neurons rather than by a small group of highly selective
units (**Extended Data Fig. 10**).

**Fig. 4 | Population coding of words across frequency and context. a,** Model performance across 15 latent dimensions (ranks) from reduced rank regression (RRR) analysis predicting semantic embeddings from neural firing rate responses to words.

Models were fit separately for each patient, then averaged across. Lines represent mean
performance ±SEM. Model performance was significantly different between models with
Word2Vec, Bert, and GPT-2 embeddings.  Asterisks in **a-c** represent P-values from a
one-way ANOVA comparing metrics from GPT-2, BERT, and Word2Vec models. **b,** The
optimal latent dimension for each patient and model. **c,** Model performance at the optimal
rank for each patient and model. **d,** Centroids of words within semantic categories from
each patient plotted in a 2D shared semantic subspace. **e,** Mahalanobis distance of each
semantic category centroid to the origin (0,0), computed separately for each patient (gray
lines); crosses represent median distance.  Distance significantly decreases across
semantic categories; r = -0.78, P = 0.004.  **f**, For each patient, decoding accuracy for
each semantic category and all other categories from neural population activity, for
models using actual (blue) and shuffled (gray) labeled data. Chance is 50% (dashed line).
Crosses represent patient averaged decoding accuracy. Plots display mean prediction
accuracy on test observations (±SEM). P < 0.0001 for each category, Wilcoxon signed-
rank test comparing actual and shuffled accuracy. Decoding accuracy significantly
decreases across semantic categories; r = -0.54, P = 0.02. **g,** Similarity matrix of vectorial
neural distance between all word pairs within and across each semantic category. The
diagonal of this matrix is plotted in **Fig. 3l**. **h**, Top - polysemy values for each unique and
repeated word within each semantic category. Bottom - neural distance between
different occurrences of the same word, within each semantic category. P and r-values
are from Pearson correlation. **i**, Each word is plotted according to its polysemy value and
neural distance (median distance between all occurrences of that word). Words are
colored based on their semantic category. P and r-values are from Pearson correlation.
**j,** Weights from a ridge regression model that predicted neural distance between all word
pairs from the difference in polysemy, word frequency, word duration, and semantic
category for each word pair, and the BERT semantic distance between them. Asterisks
represent significant predictors. **k,** The same as in **j** but restricted to word pairs with
semantic distances within the contrastive coding range, 0.14 - 0.4. **l,** Weights from a ridge
regression model that predicted, for every word, the median neural distance between all
occurrences of that word from that word's polysemy (computed with BERT embeddings),
frequency, duration, and semantic category. Asterisks represent significant predictors.
Lines in e, f, h, and i are regression lines.
666
667

**DISCUSSION**

668
Here, we show that the hippocampus exhibits a distributed and contextual coding
scheme for semantics. That is, individual words are encoded in the simultaneous activity
of multiple neurons whose selectivities span multiple unrelated semantic categories (**Fig.**
**2**). While a single neuron can distinguish individual words, the semantic *relationship*
between words (even multiple occurrences of the same word) is reflected in  neural
population activity (**Figs. 3-4**). This pattern is reflected in the association between neural
activity and embeddings derived from high layers of contextual embedders (BERT and
GPT-2), which incorporate meaning from adjacent words and sentences. These results,
then, support the idea that neuronal coding of word meanings is similar to that observed
in word models and LLMs, in which single vector entries do not correspond to specific
concepts, and may not, on their own, have natural interpretations. Instead, meaning
emerges from the collective pattern of activity across the population.
In many prior studies, semantics has been operationalized in terms of discrete
lexical categories (e.g., actions, animals, or people; Jamali et al, 2024; Huth and Gallant,
2016). However, our results suggest that hippocampal neurons encode aspects of
contextual semantics - how a word's meaning is modulated by its linguistic context -
rather than fixed lexical semantic categories during natural language comprehension.
Notably, the distributed semantic coding and mixed selectivity in single hippocampal
neurons we observed appears to contrast the semantic coding regime in the left posterior
middle frontal gyrus (pmFG), where neurons respond selectively to specific semantic
domains (Jamali et al., 2024). Most pmFG neurons (30%) were selective for words
related to actions, and most neurons that exhibited such semantic selectivity (84%) were
selective for one semantic domain and no others (Jamali et al., 2024). Both that study and
ours examined semantic coding as participants listened to natural sentences. Why would
single neurons in two different brain regions, the pmFG and the hippocampus, encode
semantics so differently? We theorize pmFG favors selective coding of literal word
meanings because of its proximity and anatomical connectivity to speech production
regions, whereas the hippocampus exhibits a flexible encoding of relational and context-
dependent semantics, given its role in memory. Extending single-neuron studies to other
brain areas will reveal how broadly - and in what form - semantics is encoded across the
human brain.
Surprisingly, at short semantic distances (~0.14-0.4), we find a less expected
effect, in the form of an anti-correlation between neural responses and linguistic
embeddings for the most similar 2-4% of words. We propose that this reversal reflects a
contrastive code that allows the brain to distinguish semantically very similar words (**Fig.**
**3f and Extended Data Fig. 7e,g**). That is, for similar words (like "*house*" and "*home*"),
the coding is more different than would be expected given the pattern observed with
randomly sampled words. Contrastive coding  appears to be driven by the semantic
embedding distance between two words and not differences in their other linguistic

features like changes in word duration, word frequency, and word polysemy, or whether
the two words belong in the same semantic category (**Fig. 4j-k**). Contrastive coding is
observed in all of our patients individually (**Extended Data Fig. 7e,g**), and is highly
statistically significant. This is not a pattern that is observed in word model or large
language model embeddings, so it may reflect constraints imposed by the brain. One such
constraint is neural noise - highly similar embeddings may be more likely to be confused
with each other in the brain than *in silico*. Yet, highly similar embeddings may be crucial
to distinguish. For example, "*brother*" and "*sister*" have very similar embeddings, as do
"*hamburger*" and "*veggieburger*" and "*eighteen*" and "*nineteen*". However, these words
do not have precisely the same meaning, and there are occasions when it is important to
make the kinds of fine distinctions that they require (e.g., when buying birthday gifts,
when feeding a vegetarian friend, and when paying for a parking spot). Likewise, a
contrastive code may help with fine distinctions in context; for example, a word like
"*generous*" or "*fun*" may have both sincere and ironic meanings, or even intermediate
(shaded) meanings. Notably, confusing these word meanings may not be a problem in
word models (like word2vec and LLMs) which may have very different noise properties
than the human brain. Thus, the brain may use a distance-based approach at most scales,
but would add additional contrastive elements to the most confusable words, and rely on
a complementary approach for assessing similarity, at the finest scales. Such a
complementary approach may include a combination of high shattering dimensionality
and high generalization, which allows simultaneous separation and combination
(Bernardi et al., 2020). That contrastive code would appear in our data as the pattern we
observe; however, follow-up studies, likely with more carefully controlled datasets, will
be needed to fully test this speculative hypothesis.
Another striking result is that, even in our models incorporating many linguistic features,
semantic predictors exert the strongest and most pervasive influence on neuronal activity - even
though the variance explained by semantic embeddings, or their predictability in decoding
analyses, is modest in absolute terms (26% variance explained in encoding models, 1-6%
variance explained in population decoding models). A key consideration for interpretation is that
our naturalistic design fundamentally differs from paradigms that rely on repeated presentations
of discrete stimuli, as commonly used in most experimental paradigms that study language
processing in single neurons (Dijksterhuis et al., 2024; Xu et al., 2025; Jamali et al., 2024;
Khanna et al., 2024). Indeed, our stimuli are not presented many times in an identical form, but
instead are embedded in continuous, context-rich narrative speech and occur only once. In
natural language, the meaning of a word is strongly context-dependent, and averaging over
repetitions would inappropriately collapse distinct contextual states. Consequently, modest
explained variance is expected. Our study adds to a small but growing literature using semantic
embeddings and encoding models to investigate the neural representation of semantics. Prior
work relating semantic representations to neural activity during naturalistic language has
reported similarly modest effect sizes across different neural signals, including BOLD responses

(Huth & Gallant 2016) and intracranial field potentials (Goldstein et al. 2024; Zada et al., 2024;
Goldstein et al. 2022). Related work using human single hippocampal neurons responding to
visually presented stimuli has also reported comparable relationships between neural activity and
semantic similarity, although the specific metrics and experimental paradigms differ from those
used here (Karkowski et al. 2025). Importantly, when accounting for the intrinsic sparsity and
Poisson-like variability of single-unit activity, our results (**Fig. 3**) represent a substantial fraction
of the noise-limited ceiling for semantic relationships between words: for example, the neural-
semantic distance correlation of 0.06 for BERT reaches 54% of its estimated ceiling, and GPT-2
reaches 76%. These findings demonstrate that, even under the demanding constraints of single-
presentation naturalistic stimuli, neural population activity captures a surprisingly large
proportion of the recoverable semantic structure, supporting the view that modest absolute
variance can still reflect robust, theoretically meaningful relationships.
Why are semantic embedding distances anti-correlated with neural embedding
distances for Word2Vec? Our data do not provide a clear answer to this question, but, in
aggregate, they suggest the outlines of an answer. Overall, we find that contextual
embedding distances and neural embeddings both align with word frequency and
polysemy levels (which themselves are highly correlated, **Fig. 3l**). Thus, the meaning of a
high-polysemy word is more influenced by context than that of a low-polysemy word -
this makes sense because high polysemy words, almost by definition, have meanings that
are highly influenced by context. We suspect that it is this context that is the primary
driver of the correlation between neural and semantic embeddings. The non-contextual
(static) embedders lack all of this context and give words a single context-free
embedding. Absent the context, the underlying overall negative correlation is uncovered.
This underlying negative correlation does not have a ready explanation, but may reflect a
special property of the hippocampus, which is associated with contrastive coding
(Bromley et al., 1994; Chanales et al., 2017; Prince et al., 2025; Radford et al., 2021;
Tian et al., 2020). Note that, contrary to our findings, another study shows a positive
correlation between single neuron and semantic non-contextual embeddings in pmFG,
highlighting the distinct coding repertoire used by the hippocampus (Jamali et al., 2024).
If hippocampal semantic coding is distributed, then it shares key representational
features with semantics in LLMs. This does not imply that the brain functions like an
LLM, and our data highlight clear differences between the two systems - for example,
anticorrelations between neural and embedding distances for non-contextual embeddings
and for very close words. Rather, the parallel lies in their use of high-dimensional,
distributed population structure: individual units (neurons or embedding dimensions) are
not interpretable on their own, yet distances in the population space reliably reflect
semantic relationships. This shared geometry does not suggest a shared algorithm; it
indicates that both biological and artificial systems can converge on similar
representational organization. LLMs therefore provide a useful comparative framework
for interpreting neural population structure, not because they mirror the brain's

mechanisms, but because they offer a high-dimensional representational model against
which neural data can be contextualized.
790
791

| 792 | | **METHODS** |

**METHODS**

***Human intracranial neurophysiology***

All experiments were performed in the Epilepsy Monitoring Unit (EMU) at Baylor St. Luke's Hospital using standardized approaches (Xiao et al., 2024A and B).

Experimental data were recorded from 10 adult patients (6 males and 4 females) undergoing intracranial monitoring for epilepsy. The hippocampus was not a seizure focus area of any patients included in the study. Single neuron data were recorded from stereotactic (sEEG) probes, specifically AdTech Medical probes in a Behnke-Fried configuration. Each patient had an average of 3 probes terminating in the left and right hippocampus. Electrode locations are verified by co-registered pre-operative MRI and post-operative CT scans. Each probe includes 8 microwires, each with 8 contacts, specifically designed for recording single-neuron activity. Single neuron data were recorded using a 512-channel *Blackrock Microsystems Neuroport* system sampled at 30 kHz. To identify single neuron action potentials, the raw traces were spike sorted using the *Wave_clus* sorting algorithm (Chaure et al., 2018)and then manually evaluated. Noise was removed and each signal was classified as multi or single unit using several criteria: consistent spike waveforms, waveform shape (slope, amplitude, trough-to-peak), and exponentially decaying ISI histogram with no ISI shorter than the refractory period (1 ms). The analyses here used all single and multiunit activity (see **Extended Data Fig. 1**).

***Electrode visualization***

Electrodes were localized using the software pipeline intracranial Electrode Visualization (iELVis; Groppe et al., 2017) and plotted across patients on an average brain using Reproducible Analysis & Visualization of iEEG (RAVE; Magnotti et al., 2020). For each patient, DICOM images of the preoperative T1 anatomical MRI and the postoperative Stealth CT scans were acquired and converted to NIfTI format (Li et al., 2016). The CT was aligned to MRI space using FSL (Jenkinson et al., 2002; Jenkinson & Smith, 2001). The resulting coregistered CT was loaded into BioImage Suite (version 3.5β1; Joshi et al., 2011) and the electrode contacts were manually localized. Electrodes coordinates were converted to patient native space using iELVis MATLAB functions (Yang et al., 2012) and plotted on the Freesurfer (version 7.4.1) reconstructed brain surface (Dale et al., 1999). Microelectrode coordinates are taken from the first (deepest) macro contact on the Ad-Tech Behnke Fried depth electrodes. RAVE (Magnotti et al., 2020) was used to transform each patient's brain and electrode coordinates into MNI152 average space. The average coordinates were plotted together on a glass brain with the hippocampus segmentation and colored by patient.

***Natural language stimuli***

Patients with epilepsy and healthy language function listened to six episodes (5- to 13-minutes in duration) taken from *The Moth Radio Hour,* and totaling 47:25 minutes of listening time (7,346 words). The six stories were, "Life Flight", "The Tiniest Bouquet", "The One Club", "Wild Women and Dancing Queens", "My Father's Hands" and "Juggling and Jesus". In each story, a single speaker tells an autobiographical narrative in front of a live audience. The six selected stories were chosen to be both interesting and linguistically rich. Stories were played continuously through the built-in audio speakers of the patient's hospital television. The audio signal was synchronized to the neural recording system via analog input going directly from the computer playing the audio into the Neural Signal Processor at 30 kHz.

838 *Jabberwocky stimuli*

839    After story listening, a subset of four patients listened to 17 minutes of
Jabberwocky stories (1,890 words) to assess neural specificity for semantics (**Fig. 1d and**
**Extended Data Fig. 2b-c**). Jabberwocky stimuli are words that are altered from the real
words in the stories used in the experiment to become words that have no meaning, for
example, "toom" or "skook". An example sentence of jabberwocky stimuli is: Before I
smow it, the foodbace toom is at my frose woor, and a coakle of them have bapes of bour
under their alk. We used the software, *Wuggy*, to transform story transcripts into
jabberwocky (Keuleers & Brysbaert, 2010). This program matched the subsyllabic
segment length of each word and replaced words with letters that match phonetic
probabilities of orthographic English. Jabberwocky preserves syntactic structure by
retaining function words and morphemes, even though it lacks coherent semantics.
850

851 *Audio Transcription*

852    After experiments, the audio .wav file was automatically transcribed using Python and
Assembly AI, a state-of-the-art AI model to transcribe and understand speech. The transcribed
words and corresponding timestamp output from Assembly AI was converted to a TextGrid and
then loaded into Praat, a software for speech analysis. The original .wav file was also loaded into
Praat and we manually checked the spectrograms and timestamps, correcting each word to
ensure the word onset and offset times are accurate. The TextGrid output of corrected words and
timestamps from Praat was converted to a .xls and loaded into Matlab and Python for further
analysis.
860

861 *Semantic embedding extraction from language models*

862    *1) Word2Vec.* We used the pre-trained *fastText Word2Vec* model in MATLAB to extract
863 word embeddings for all words in our dataset (Joulin et al., 2016; Mikolov et al., 2013). This pre-
864 trained model provides 300-dimensional word embedding vectors, trained on millions of words
865 text, to capture semantic relationships between words. Any surname words, such as "Harwood" or
866 proper nouns like "Applebee's" that did not have word embeddings were discarded from the
867 analysis (these were rare in our sample).
868    *2) GPT-2 Large*. In an excel file of our transcribed words, each row corresponded to an
individual token, including punctuation and sentence terminators such as ".", "?", and "!". We
reconstructed sentences by iterating through the file and appending words until encountering a
recognized sentence delimiter. This process yielded multi-word segments that more accurately
captured natural linguistic boundaries. Any remaining words following the last delimiter were
grouped into a final sentence. Notably, punctuation tokens were preserved to maintain contextual
fidelity but were tracked carefully to avoid introducing sub-word alignment errors during
tokenization.
876    To extract GPT-2 embeddings, we employed the "gpt2-large" model (Radford et al.,
2019) from the Hugging Face Transformers library (Wolf et al., 2020). This version of GPT-2
features a total of 37 layers (1 initial embedding layer plus 36 transformer layers), each
producing 1280-dimensional hidden states, with a maximum context length of 1024 tokens.
Although GPT-2 supports a 1024-token context window, all embeddings used in this study were
computed within individual sentences only - that is, the model's context was reset whenever a
sentence-ending delimiter (e.g., ".", "!", "?") was encountered. We extracted hidden states from
all 37 layers using a progressive context approach designed to incorporate GPT-2's

autoregressive nature. Specifically, for each sentence, we began with an empty context and
added words sequentially. After adding each new word, we tokenized the updated text string via
GPT-2's Byte Pair Encoding (BPE) tokenizer, ran the token sequence through the model in no-
grad (inference-only) mode, and retrieved the hidden states. We then identified the newly
appended word's sub-word tokens and averaged their corresponding vectors to obtain a single
word-level embedding. Because GPT-2 often splits words into multiple sub-word fragments
(otherwise known as "tokens," e.g., "computa" + "tion"), averaging those fragments preserves
consistency with the transcript's original word boundaries. The GPT-2 outputs resulted in 1280-
dimensional embeddings for each layer, as seen in **Fig. 3j**. All analyses with GPT-2 used word
embeddings from the last layer 37, unless otherwise specified, as in **Fig. 3j**.
894            ***3) BERT.*** We conducted a parallel extraction procedure with the "bert-base-cased" model
(Devlin et al., 2018), also accessed via the Hugging Face Transformers library (Wolf et al.,
2020). In contrast to GPT-2, whose progressive context reflects its decoder-only design, BERT
uses a masked-language-modeling objective and an encoder-only architecture that processes all
input tokens in parallel, granting access to both past and future context. To align BERT's outputs
more closely with the unidirectional processing of GPT-2, we applied an expanding-context
procedure: beginning with an empty string, we appended one new word at a time, concatenated
the running text (preserving punctuation for contextual fidelity), and re-tokenized the updated
segment with BERT's tokenizer. This process continued until a sentence-ending delimiter (e.g.,
".", "!", or "?") was encountered, at which point the context was reset, ensuring that embeddings
were computed strictly within sentence boundaries. Although BERT inherently considers
bidirectional information, we extracted only the hidden states corresponding to the just-added
word, thereby restricting interpretation to left-contextual information only. Sub-word vectors
belonging to that word were averaged to yield one word-level embedding per layer. Hidden
states from all 13 layers (768 dimensions each) were retained, and analyses reported in this paper
used the final hidden layer 13. All code was implemented in Python using PyTorch (Paszke et
al., 2019) as the underlying deep-learning framework, and the resulting embeddings were saved
to Excel spreadsheets for subsequent analyses.
912
913     ***Clustering of semantic embeddings***
914            To identify the natural semantic categories present in our word data (**Fig. 1h-j**), all
unique words were clustered into groups based on related meanings using a word embedding
approach (Joulin et al., 2016; Mikolov, et al., 2013). For each word, we used its 300-dimensional
Word2Vec embedding. To compute and visualize semantic clusters, we used a t-distributed
Stochastic Neighbor Embedding (t-SNE) algorithm on word embedding values to reduce the
dimensionality of each unique word based on their cosine distance to all other words, thus
reflecting their semantic similarity. Words with similar meanings now have similar 2D
coordinates. We then applied the K-means clustering algorithm to these 2D word representations
and visualized clustered words on a 2D word map (k = 11 clusters, determined from the
silhouette score; Rousseeuw, 1987). We then manually inspected and assigned a distinct
semantic label to each cluster and adjusted categories for accuracy. For example, words
bordering the edges of categories might get mis-grouped and were manually corrected. This
method is comparable to those used in other studies of semantics (Huth et al., 2016; Jamali et al.,
2024). We repeated this same method to create semantic clusters from neural data (**Extended
Data Fig. 8**) and contextual embeddings (**Extended Data Fig. 6**).
929

*Firing rate responses to words*

We computed the duration for each word in the story and for each non-word in Jabberwocky stimuli. The firing rate of a neuron for each word was the number of spikes occurring during the word with an 80 ms delay after word onset to account for the approximate delay of information to hippocampus. This value was divided by word duration and then multiplied by 1000 to compute spikes per second.

*Regressing spike counts on word embeddings, phonemes, and linguistic features*

Word embeddings, such as those derived from Word2Vec or similar models, are typically high-dimensional and can exhibit substantial collinearity among dimensions - that is, many of the embedding features are correlated with one another. We first used Principal Component Analysis (`pca`, Matlab 2023b) on the full word embeddings to obtain uncorrelated features that still capture the dominant structure in the embedding space with reduced dimensionality. For each word, we used the first 100 principal components (PC) from Word2Vec or BERT embeddings because they explained at least 60% of the variance of the original embedding vectors.

We modeled the spike count responses of individual neurons using a Poisson Generalized Linear Model (GLM) with a log-link function and ridge (L2) regularization (we confirmed that spike counts for each word follow a Poisson distribution; **Fig. 1f-g**). The model aimed to predict the number of spikes a neuron fired in response to each word (summed spikes across word duration), using the top 100 principal components (PCs) of the word embedding vector, the duration of the word, and the interaction between each PC and the word's duration as predictors (z-scored prior to model fitting). This resulted in a 201-dimensional feature vector for each word: 100 PC values, 1 duration value, and 100 PC×duration interaction terms.

The Poisson GLM assumes that the spike count $y_i$ for word $i$ is drawn from a Poisson distribution with mean $\lambda_i$ where:

$$y_i \sim \text{Poisson}(\lambda_i)$$
$$\log(\lambda_i) = \beta_0 + x_i^T \beta$$

Where $\lambda_{i,n}$, the expected spike count for word ($i$) and neuron n ($n$), is modeled by the linear regression coefficients ($\beta$), one for each of the 201 predictors ($x_i^T$), plus the y-intercept ($\beta_0$). For each neuron, we used a 5-iteration nested training loop, where in each iteration, the data was split into training and held-out test sets (80/20 split). Within the training set, 5-fold cross-validation was used to select the optimal regularization strength (alpha) from a log-spaced range based on optimizing the cross-validated log-likelihood. The selected model was then evaluated on the held-out test set using several performance metrics, including log-likelihood, and adjusted $R^2$. To assess statistical significance relative to a null, we generated 100 shuffled predictor matrices per dataset, in which embeddings were shuffled while keeping word duration preserved. Each shuffle circularly shifted the embedding matrix along the observation axis by a randomly selected offset of at least ±100 samples (to avoid short-range autocorrelation artifacts). To determine if the actual model showed significant improvement from the shuffled, we performed a permutation test comparing the actual model LLH to the shuffled model LLH distribution. We then took the difference between the actual and shuffled model (mean) LLH (LLH diff; ΔLLH). A neuron was fit by the model if its ΔLLH was both positive and significant and if McFadden's pseudo $R^2$ value was positive ($P < 0.05$, permutation test, **Fig. 1g, left**). Shuffled model $R^2$ values were significantly less than those from actual models ($p < 0.05$, Wilcoxon signed-rank test; **Extended Data Fig. 4c**).

Predictor significance was assessed using p-values from a Poisson generalized linear
model fit to the same predictors, while coefficient magnitudes were taken from the L2-
regularized Poisson regression model used for prediction. As expected, word duration was
always a significant predictor, followed by the first eight embedding dimensions and their
interactions with duration, with the number of significant predictors gradually decreasing across
higher dimensions (**Extended Data Fig. 4a-b, g-h**).

We used the same Poisson linear ridge regression model to predict neural activity from
past and future word embeddings (**Fig. 1g, right**). Here, a separate model was fit for each word
index, by which we shifted the words relative to the spike counts, such that the spike count of a
neuron for word X corresponded to an embedding of a different word and word duration that was
in the future or past, based on the index. To determine whether neural activity was predicted by
each word index, the distribution of actual model performance ($\Delta$LLH) from every neuron was
compared to that of a null model (chance distribution, described above). For each word index,
these distributions were compared using the one-sided Wilcoxon signed-rank test ($p < 0.05$).
Model performance was significantly greater than chance for up to seven words in the past and
three words in the future.

**Phonetic regression.** We built a fixed-length feature space over the 43 IPA phonemes
observed in our corpus. Here, IPA refers to the International Phonetic Alphabet, a standardized
set of symbols that denote speech sounds independent of spelling. The podcast transcript was
processed word by word: tokens were lower-cased and converted from graphemes to phonemes
using the Python phonemizer package (version 3.0.1) with the eSpeak backend as the grapheme-
to-phoneme (G2P) model (https://pypi.org/project/phonemizer/3.0.1/). For each word, we took
the canonical IPA transcription returned by phonemizer. Phonemes were then manually
inspected and corrected by linguists (JB and BJ) in Praat.

Each word was then represented as a 43-dimensional count vector whose entries reflect
the number of occurrences of each IPA phoneme in that word (unigram counts; no duration or
stress information). This approach is similar to Khanna et al., in that words are represented by
the presence of their constituent phonemes; however, we did not group phonemes into broader
classes, in order to preserve the full identity of the 43 phones observed in our data and maintain
the embedding's informational richness and dimensionality (Khanna et al., 2024). To better
differentiate words that contain the same phoneme set but in different orders (e.g., dog vs god),
we double-counted the first phoneme in every word while counting all subsequent phonemes
once. The resulting word-by-phoneme matrix (N words × 43 features) was used in subsequent
analyses relating phonetic composition to neural responses. We used this word-by-phoneme
matrix, word duration, and their interactions in the same Poisson regression described above for
predicting spike counts of the current word. The data folds used for training and testing were
preserved across semantic and phonetic models and both models had the same number of words.
The results in **Extended Data Fig. 4e-f** were replicated even when using the same number of
predictors (the first 43 principal components of semantic embeddings compared to 43
phonemes).

We used the same Poisson ridge regression model to predict an individual neuron's spike
count for each word from 61 linguistic features: (1) full phonetic embeddings (43 IPA phones;
count coded, cf. Khanna et al., 2024), (2) 10 PCs of semantic embeddings, (3) word order in
sentence, (4) word order in clause (Stanford CoreNLP; Manning et al., 2014), (5) opening node
number (Stanford CoreNLP; Manning et al., 2014), (6) closing node number (Stanford
CoreNLP; Manning et al., 2014), (7) word frequency (SUBTLEX-US), (8) pitch, (9) a scalar

1021 representing degree of polysemy (Cruse et al., 1986; Landauer, 2001; Ethayarajh, 2019)  and
1022 (10) word duration (**Extended Data Fig. 4g-h**).
1023

1024 ***Single neuron encoding of words***
1025  Semantic encoding of each neuron was quantified using a ROC (receiver operating
1026 characteristic) analysis, a standard approach that has previously been used to characterize neural
1027 responses during behavior (Britten et al., 1992; Li et al., 2017). Here, the firing rate of each
1028 neuron is the classifier that is evaluated on its ability to distinguish instances of a word from all
1029 other words. For statistical reasons, since we need to compare two distributions, we performed
1030 the analysis on every neuron for every word that occurred at least 4 times (283 words, on average
1031 each word occurred 20 times, the most was 407).
1032  Upon application of a binary threshold to firing rates and comparison with a binary event
1033 vector denoting word label (1 for the current word, 0 for other words), word detection based on
1034 neural activity can be measured using the true positive rate (TPR) and the false positive rate
1035 (FPR). Plotting the TPR against the FPR over a range of binary thresholds, spanning the
1036 minimum and maximum values of the neural signal, yields an ROC curve that describes how
1037 well the neural signal detects that word at each threshold. With the `perfcurve` function in
1038 Matlab 2023b, we used the area under the ROC curve (AUC) as a metric for how strongly
1039 neurons are modulated by each word (**Fig. 2a-c**).  The number of word occurrences in the
1040 'Current word' class were balanced with the number of words in "Other" class by subsampling
1041 words from the "Other" class over 100 iterations of the analysis. For each neuron, AUC was
1042 computed, then averaged and compared to a null distribution across iterations. For each neuron,
1043 the observed AUC was compared to a null distribution of 1,000 AUC values generated from
1044 constructing ROC curves over randomly permuted neural signals (that is, firing rate permuted
1045 across words, thus destroying the relationship between neural responses and word labels). The p-
1046 value is calculated as the proportion of permuted AUC values that are greater than or equal to the
1047 observed AUC and a neuron was considered significantly responsive if $P < 0.05$. To better
1048 visualize encoding magnitude, we standardized each AUC value by subtracting chance (0.5)
1049 from every value, and took the absolute value of that difference. This results in values between 0
1050 and 0.5 (**Fig. 2c**).
1051

1052 ***Semantic range***
1053  Each neuron encodes a given set of words determined from ROC analysis (see *Single*
1054 *neuron encoding of words*). For each neuron that encoded at least two words, we defined its
1055 semantic range as the distribution of cosine distances between all pairs of words it encoded. We
1056 then compared this empirical range to that neuron's null semantic range. For the null distribution,
1057 we randomly sampled the same number of encoded words from the full set of words used in ROC
1058 analysis from the dataset (n = 283 words), computed all pairwise cosine distances, and repeated
1059 this 1,000 times for that neuron. Thus, each neuron's null distributions matched their empirical
1060 distribution count, representing samples from the full (testable) semantic space of the data. We
1061 also repeated this analysis using words and their embeddings from the full dataset (n= 7,346 words)
1062 and found comparable results.
1063  We quantified the extent to which each neuron's empirical semantic range encompassed
1064 the null range. Using nonparametric bootstrap resampling (n = 1,000), we generated distributions
1065 of the minimum and maximum for both the empirical and null ranges, and computed 95%
1066 confidence intervals (CI) from the bootstrap samples. A neuron's semantic range was considered

to cover the null range if the lower CI bound of its minimum was less than or equal to the upper
CI bound of the null's minimum, and the upper CI bound of its maximum was greater than or equal
to the lower CI bound of the null's maximum. Bootstrap support for coverage was defined as the
proportion of bootstrap iterations meeting this criterion. Coverage was deemed significant if
support was $\geq 1 - \alpha$ ($\alpha = 0.05$). A neuron was classified as spanning the full semantic range if it
met both the CI-based coverage criterion and the bootstrap-significant coverage criterion. CI-based
coverage identifies neurons whose observed range is statistically compatible with fully spanning
the null range at the 95% confidence level, whereas bootstrap-significant coverage identifies
neurons whose range covered the null range in $\geq$ 95% of bootstrap resamples. This analysis was
performed separately using Word2Vec, GPT-2 (layers 36 and 25), and BERT (last layer) semantic
embeddings.
1078
***Embedding distance***
The semantic embedding vector for each word was its full vector of embedding values
extracted from either Word2Vec (300 in length), BERT (768 in length), or GPT-2 (1280 in
length) language models. For each word, it's neural embedding vector was every neuron's firing
rate response for that word (356 in length). Neurons were combined across all 10 patients,
making a pseudo population totaling 356 neurons. We used the function `pdist`, Matlab 2023b,
to compute cosine distance between semantic embedding vectors of all 26,978,185 word pairs,
known as semantic distance. We repeated the procedure, computing cosine distance between
neural embedding vectors for all word pairs, termed neural cosine distance.  "All word pairs"
included pairs of the same word except in Word2Vec analysis, since cosine distance between
two instances of the same word will always be 0 (since embedding values are the same). This
procedure was followed for word pairs within and between each semantic category to create the
semantic distance similarity matrix in **Figure 1h**, for the neural and semantic distances within
each category in **Figure 3l**, and for the neural distance similarity matrix in **Figure 4g**. For
**Figure 3c**, we computed the semantic distance from BERT embeddings for all word pairs within
each semantic category, then computed neural distance for all word pairs within each semantic
category and correlated (Pearson) these two distance vectors to compute the values shown on the
y-axis. Similarly, we correlated semantic distance and neural distance from all word pairs (unless
otherwise specified in the caption) to compute the correlation coefficients in **Figure 3g-j**. In
**Figure 4h-i**, neural cosine distance was always computed between word pairs of multiple
instances (minimum 2) of the same word. We took the median of these distances to extract one
distance value per word.
1101

$$\text{Cosine distance } (w_1, w_2) = 1 - \frac{W1 * W2}{||W1|| \; ||W2||}$$

1102
1103
1104 Cosine distance between neural or semantic embeddings of word 1 and word 2 is the 1 minus the
1105 dot product of embedding vectors for each word, divided by the magnitudes (norms) of each word
1106 vector.
1107
***Estimating a neural noise ceiling for semantic embeddings***
To estimate a noise ceiling constrained by the variability observed in the neural data, we
generated noisy versions of the GPT-2 (or BERT or Word2Vec) embedding space by injecting
Gaussian noise whose magnitude was scaled according to the firing-rate statistics of the recorded

neurons. Let $G \in R^{W \times D}$ denote the clean GPT/linguistic embedding matrix (rows = words,
columns = embedding dimensions), and $R \in R^{W \times N}$ the neural firing-rate matrix (rows = words,
columns = neurons).
Because we empirically confirmed that hippocampal firing rates across words follow
Poisson-like statistics, with each neuron's variance closely matching its mean, we used a Poisson
noise model in which the variance-to-mean ratio was fixed at $\phi = 1$ for all neurons. This
provides a conservative, interpretable baseline for quantifying how neural-level variability would
distort the representational geometry of the language-model embeddings. Then, we injected
additive Gaussian noise into the embedding space using a subset of embedding dimensions equal
in number to the recorded neurons (D = 356).
For each word $w$ and embedding dimension $d$:

1123
$$\tilde{G}_{w,d} = G_{w,d} + \varepsilon_{w,d}, \qquad \varepsilon_{w,d} \sim N(0, \phi\, \mu_{w,n}),$$

where $\mu_{w,n}$ is the mean firing rate of neuron $n$ (taken from $R$) corresponding to embedding
dimension $d$, and $\phi = 1$. Thus, the additive noise variance scaled linearly with the neurons'
mean firing rates, emulating Poisson variability across words. This model assumes that noise
enters independently of the embedding magnitude, perturbing all points in embedding space by a
constant variance level proportional to the corresponding neuron's mean firing rate.
For each noise model, pairwise cosine-distance matrices were computed (using the
function, `pdist`, in Matlab 2023b) for the noisy language embeddings ($D_{noisyGPT}$), the original
language embeddings ($D_{GPT}$), and the neural data ($D_{neural}$). The noise-limited ceiling was
defined as the Pearson correlation between $D_{noisyGPT}$ and $D_{GPT}$:

1133
$$r_{ceiling} = corr(D_{noisyGPT}, D_{GPT}).$$

1134  The observed brain–model correspondence was computed as:

1135
$$r_{real} = corr(D_{GPT}, D_{neural}).$$

1136  The ratio $r_{real}/r_{ceiling}$ quantifies how much of the model's representational structure is
1137  recoverable in the neural data, relative to the theoretical maximum allowed by intrinsic neural
1138  variability.
1139
***Reduced Rank Regression***
To quantify how hippocampal population activity predicts high-dimensional semantic
embeddings of heard words, we applied Reduced Rank Regression (RRR) using the Matlab code
and following the framework of Semedo et al. 2019 (see also Wu and Pillow, 2025). For each
patient, neurons served as predictors and individual words as observations (**Fig. 4a-c**).
Neural data preprocessing: For each patient, we computed per word firing rates
normalized by word duration (see *Firing rate responses to words)*. The resulting matrix
contained one observation per word and one column per neuron (X). Word-level confounding
variables - the log of word frequency and position - were regressed out of the neural activity
matrix, and the residuals were used in analysis.
The first 30 Principal Components of semantic embeddings from Word2Vec, BERT layer
13, or GPT-2 layer 37 were used in the regression, forming a word by semantic embedding
matrix (Y). RRR estimates a mapping from neural activity X to semantic embeddings Y that is

constrained to lie in a low-dimensional shared subspace. We used the Semedo et al., 2019,
`ReducedRankRegress` function, which implements the closed-form solution for:

1155

1156 $$Y = XB + \epsilon \qquad B = B_{OLS}V_rV_r^\mathsf{T}$$

1157

where $V_r$ are the top $r$ eigenvectors of $Y^\mathsf{T}XX^\mathsf{T}Y$. For each patient, we computed:
$B$ : the ranked predictive components
$V$: the eigenvectors describing predictive dimensions
These define the semantic subspace captured by the neural population. To determine the number
of predictive dimensions, we evaluated models with 0–15 RRR dimensions using 10-fold cross-
validation, following Semedo et al. Model performance (averages across folds) was quantified as
the cross-validated variance explained (1 – NSE) across predictive subspace dimensionalities
(ranks = 0 - 15). The optimal dimensionality (rank) can be defined as the number of dimensions
needed for the prediction accuracy to plateau, selected using the Semedo et al., 2019 function,
`ModelSelect`. These RRR results quantify how many dimensions of semantic variation can be
linearly predicted from hippocampal population activity, as well as the geometry of the neural to
semantic mapping.

1170

***Principal Component Analysis***
We computed components (scores) from `pca`, MATLAB 2023b, on the word by neuron
firing rates matrix for each patient (neuron count ranges from 11-54 per patient). To visualize
and compare semantic representations across patients, we first constructed a common two-
dimensional subspace (**Fig. 4d**). For each patient, word-by-neuron firing rate matrices were
reduced with PCA and the first two principal components (PC1–2) were retained. Because the
scale and covariance structure of these axes can vary across patients, we whitened each patient's
PC1–2 scores using their within-patient covariance matrix. This whitening procedure ensures
that Euclidean distances in the transformed space are equivalent to Mahalanobis distances in the
original coordinates.
Semantic category centroids were then computed as the mean of the whitened word
representations belonging to each category. To align patients into a common reference frame, we
applied an orthogonal Procrustes analysis to the configuration of category centroids, restricting
the transformation to a pure rotation (no reflection, scaling, or translation). This yielded a shared
coordinate system in which all patients' category centroids could be visualized and compared.
Within this common space, we quantified the distance of each category centroid to the
origin (0,0). Because whitening centers each patient's space at their mean response, the origin
corresponds to the population-average baseline. Distances were computed as the Euclidean norm
of the whitened coordinates, which is equivalent to the Mahalanobis distance to the patient's
mean response in the original PC1–2 space. These values provide a standardized measure of how
strongly each semantic category deviates from the center of the shared semantic subspace.
Results in Figure 4d-e were replicated using Euclidean distance between centroid and center
(0,0) within each patient's individual 2D subspace.

1194

***Support Vector Machine Decoder***
We used a SVM decoder (Bishop, 2006) with a nonlinear radial-based function kernel to
determine whether firing rates during words carry information about semantics by distinguishing
each category from all others (**Fig. 4f**). We also repeated this analysis with a linear kernel, and

we found equivalent results to Figure 4f except performance was much lower, only 2-5% above
chance level (results not shown). For each patient, each semantic category, we used the firing
rate responses from every neuron (n = 11-54 across patients) for each word in the category (class
1) and all rates for all other words (class 2) to predict the class for each word from these neural
data. The number of words in each class were always balanced – across comparisons and across
semantic categories through random subsampling of words from the larger class. Random
selections of class observations were repeated for 100 iterations, giving us the average
classification accuracy over 1,000 test splits of the data for each session. To train and test the
model, we used a tenfold cross-validation. In brief, the data were split into ten subsets, and in
each iteration the training consisted of a different 90% subset of the data; the testing was done
with the remaining 10% of the data. We used the default hyperparameters as defined in
`fitcsvm`, MATLAB 2023b, with hyperparameter $C = 1.3$ and z-scored normalization of firing
rates. Decoder performance was calculated as the percentage of correctly classified test trials.
We compared model performance for predicting train and test data to check for overfitting. In
each iteration, we trained a separate decoder with randomly shuffled class labels. The
performance of the shuffled decoder was used as a null hypothesis for the statistical test of
decoder performance.
*Decoding jabberwocky stimuli.* We used the same methods described above on a linear
SVM model (default hyperparameters) to decode whether a word was a real word from podcast
stories or a non-word from the jabberwocky stimuli from neural population activity (**Extended**
**Data Fig. 2c**). We excluded the function words from jabberwocky stimuli in this analysis since
those words are real words but used in a nonsensical context.
1221
**Polysemy**
To compute polysemy for each word, we computed cosine distance between each BERT
embedding vector of all occurrences of a given word (at least 2 occurrences, 594 words total).
We took the median of this distribution to obtain one polysemy value per word (**Fig. 4h-i**). The
distribution of polysemy values for all words in each semantic category is plotted in Figure 4h –
top. We repeated the polysemy analysis using neural embeddings instead of BERT embeddings
to compute the neural cosine distance values in Figure 4h – bottom and Figure 4i.  We also
computed polysemy for each word as the total number of synsets (i.e., distinct senses) associated
with each word in WordNet (Fellbaum, 1998). These polysemy values yielded the same results
shown in **Figure 4h-i**.
1232
**Modeling neural distance and polysemy from linguistic features**
We used the same cross validated, linear Ridge Regression architecture described in
*Regressing spike counts on word embeddings, phonemes, and linguistic features* to predict neural
distance or neural polysemy from different linguistic features. Models fit in **Figure 4j-k** used
word-pairs as observations and semantic distance, differences in duration, frequency, and
polysemy, and a binary indicator of whether the words belonged to the same semantic category
(0 = same, 1 = different) as predictors in a cross-validated ridge regression model to predict
neural distance. In **Figure 4l**, the model used each word that was repeated at least twice as
observations, and the word's polysemy, frequency, duration, and semantic category (as defined
by Word2Vec: categories ranged 1-11; treated as a categorical), were predictors for neural
polysemy of that word. Ridge regularized coefficients/weights from these models are plotted in
**Figure 4j-l.**

**REFERENCES**

Baldassano, C., Chen, J., Zadbood, A., Pillow, J. W., Hasson, U., & Norman, K. A. (2017). Discovering event structure in continuous narrative perception and memory. *Neuron*, *95*(3), 709-721.

Bausch, M., Niediek, J., Reber, T. P., Mackay, S., Boström, J., Elger, C. E., & Mormann, F. (2021). Concept neurons in the human medial temporal lobe flexibly represent abstract relations between concepts. *Nature Communications*, *12*(1), 6164. https://doi.org/10.1038/s41467-021-26327-3

Bernardi, S., Benna, M. K., Rigotti, M., Munuera, J., Fusi, S., & Salzman, C. D. (2020). The geometry of abstraction in the hippocampus and prefrontal cortex. *Cell*, *183*(4), 954-967.

Bishop, C. M. (2006). *Pattern recognition and machine learning*. New York : Springer

Blanchard, T. C., Piantadosi, S. T., & Hayden, B. Y. (2018). Robust mixture modeling reveals category-free selectivity in reward region neuronal ensembles. *Journal of Neurophysiology*, *119*(4), 1305–1318. https://doi.org/10.1152/jn.00808.2017

Blank, I. A., Duff, M. C., Brown-Schmidt, S., & Fedorenko, E. (2016). Expanding the language network: Domain-specific hippocampal recruitment during high-level linguistic processing. *BioRxiv*, 091900. https://doi.org/10.1101/091900

Britten, K. H., Shadlen, M. N., Newsome, W. T., & Movshon, J. A. (1992). The analysis of visual motion: a comparison of neuronal and psychophysical performance. *The Journal of Neuroscience*, *12*(12), 4745. https://doi.org/10.1523/JNEUROSCI.12-12-04745.1992

Bromley, J., Guyon, I., Lecun, Y., Sickinger, E., Shah, R., Bell, A., & Holmdel, L. (1994). *Signature Verification using a "Siamese" Time Delay Neural Network*.

Cervera, R. L., Wang, M. Z., & Hayden, B. Y. (2020). Systems neuroscience of curiosity. *Current Opinion in Behavioral Sciences*, *35*, 48-55.

Chanales, A. J. H., Oza, A., Favila, S. E., & Kuhl, B. A. (2017). Overlap among Spatial Memories Triggers Repulsion of Hippocampal Representations. *Current Biology*, *27*(15), 2307-2317.e5. https://doi.org/https://doi.org/10.1016/j.cub.2017.06.057

Chang, K. M. K., Cherkassky, V. L., Mitchell, T., & Just, M. A. (2009, August). Quantitative modeling of the neural representation of adjective-noun phrases to account for fMRI activation. In *Proceedings of the Joint Conference of the 47th Annual Meeting of the ACL and the 4th International Joint Conference on Natural Language Processing of the AFNLP* (pp. 638-646).

Chaure, F. J., Rey, H. G., & Quian Quiroga, R. (2018). A novel and fully automatic spike-sorting implementation with variable number of features. *Journal of Neurophysiology*, *120*(4), 1859–1871. https://doi.org/10.1152/jn.00339.2018

Chavez, A. G., Franch, M., Mickiewicz, E. A., Baltazar, W., Belanger, J. L., Devara, D., ... & Hayden, B. Y. (2025). Mirror manifolds: partially overlapping neural subspaces for speaking and listening. bioRxiv, 2025-09.

Chen, D., Peterson, J. C., & Griffiths, T. L. (2017). *Evaluating vector-space models of analogy*. http://arxiv.org/abs/1705.04416

Cohn-Sheehy, B. I., Delarazan, A. I., Reagh, Z. M., Crivelli-Decker, J. E., Kim, K., Barnett, A. J., ... & Ranganath, C. (2021). The hippocampus constructs narrative memories across distant events. *Current Biology*, *31*(22), 4935-4945.

Courellis, H. S., Minxha, J., Cardenas, A. R., Kimmel, D. L., Reed, C. M., Valiante, T. A., ... & Rutishauser, U. (2024). Abstract representations emerge in human hippocampal neurons during inference. *Nature*, *632*(8026), 841-849.

Cruse, D. A. (1986). Lexical semantics. Cambridge: Cambridge University Press.

Dale, A. M., Fischl, B., & Sereno, M. I. (1999). Cortical Surface-Based Analysis: I. Segmentation and Surface Reconstruction. *NeuroImage*, *9*(2), 179–194. https://doi.org/https://doi.org/10.1006/nimg.1998.0395

Davachi, L. (2006). Item, context and relational episodic encoding in humans. *Current Opinion in Neurobiology*, *16*(6), 693–700. https://doi.org/https://doi.org/10.1016/j.conb.2006.10.012

Deniz, F., Tseng, C., Wehbe, L., Dupré la Tour, T., & Gallant, J. L. (2023). Semantic Representations during Language Comprehension Are Affected by Context. *The Journal of Neuroscience*, *43*(17), 3144. https://doi.org/10.1523/JNEUROSCI.2459-21.2023

Devlin, J., Chang, M.-W., Lee, K., Google, K. T., & Language, A. I. (2018). *BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding*. https://github.com/tensorflow/tensor2tensor

Dijksterhuis, D. E., Self, M. W., Possel, J. K., Peters, J. C., van Straaten, E. C. W., Idema, S., Baaijen, J. C., van der Salm, S. M. A., Aarnoutse, E. J., van Klink, N. C. E., van Eijsden, P., Hanslmayr, S., Chelvarajah, R., Roux, F., Kolibius, L. D., Sawlani, V., Rollings, D. T., Dehaene, S., & Roelfsema, P. R. (2024). Pronouns reactivate conceptual representations in human hippocampal neurons. *Science*, *385*(6716), 1478–1484. https://doi.org/10.1126/science.adr2813

Duff, M. C., & Brown-Schmidt, S. (2012). The hippocampus and the flexible use and processing of language. *Frontiers in human neuroscience*, *6*, 69.

Ebitz, R. B., Sleezer, B. J., Jedema, H. P., Bradberry, C. W., & Hayden, B. Y. (2019). Tonic exploration governs both flexibility and lapses. *PLoS computational biology*, *15*(11), e1007475.

Eisenreich, B. R., Hayden, B. Y., & Zimmermann, J. (2019). Macaques are risk-averse in a freely moving foraging task. *Scientific reports*, *9*(1), 15091.

Erk, K. (2012). Vector Space Models of Word Meaning and Phrase Meaning: A Survey. *Language and Linguistics Compass*, *6*(10), 635–653. https://doi.org/https://doi.org/10.1002/lnco.362

Ethayarajh, K. (2019). How contextual are contextualized word representations? Comparing the geometry of BERT, ELMo, and GPT-2 embeddings. *arXiv preprint arXiv:1909.00512*.

Fellbaum, C. (1998). *WordNet: An Electronic Lexical Database*. The MIT Press; Bradford Books.

Fletcher, P. C., Frith, C. D., & Rugg, M. D. (1997). The functional neuroanatomy of episodic memory. *Trends in Neurosciences*, *20*(5), 213–218. https://doi.org/https://doi.org/10.1016/S0166-2236(96)01013-2

Frisby, S. L., Halai, A. D., Cox, C. R., Lambon Ralph, M. A., & Rogers, T. T. (2023). Decoding semantic representations in mind and brain. *Trends in Cognitive Sciences*, *27*(3), 258–281. https://doi.org/10.1016/j.tics.2022.12.006

Fusi, S., Miller, E. K., & Rigotti, M. (2016). Why neurons mix: high dimensionality for higher cognition. *Current Opinion in Neurobiology*, *37*, 66–74. https://doi.org/10.1016/j.conb.2016.01.010

Gelbard-Sagiv, H., Mukamel, R., Harel, M., Malach, R., & Fried, I. (2008). Internally generated reactivation of single neurons in human hippocampus during free recall. *Science*, *322*(5898), 96-101.

Goldstein, A., Grinstein-Dabush, A., Schain, M., Wang, H., Hong, Z., Aubrey, B., Nastase, S. A., Zada, Z., Ham, E., Feder, A., Gazula, H., Buchnik, E., Doyle, W., Devore, S., Dugan, P., Reichart, R., Friedman, D., Brenner, M., Hassidim, A., … Hasson, U. (2024). Alignment of brain embeddings and artificial contextual embeddings in natural language points to common geometric patterns. *Nature Communications*, *15*(1), 2768. https://doi.org/10.1038/s41467-024-46631-y

Goldstein, A., Ham, E., Schain, M., Nastase, S., Zada, Z., Dabush, A., Aubrey, B., Gazula, H., Feder, A., Doyle, W. K., Devore, S., Dugan, P., Friedman, D., Reichart, R., Brenner, M., Hassidim, A., Devinsky, O., Flinker, A., Levy, O., & Hasson, U. (2023). *The Temporal Structure of Language Processing in the Human Brain Corresponds to The Layered Hierarchy of Deep Language Models*. https://doi.org/10.1101/2022.07.11.499562

Goldstein, A., Wang, H., Niekerken, L., Zada, Z., Aubrey, B., Sheffer, T., Nastase, S. A., Gazula, H., Schain, M., Singh, A., Rao, A., Choe, G., Kim, C., Doyle, W., Friedman, D., Devore, S., Dugan, P., Hassidim, A., Brenner, M., … Hasson, U. (2023). *Deep speech-to-text models capture the neural basis of spontaneous speech in everyday conversations*. https://doi.org/10.1101/2023.06.26.546557

Goldstein, A., Zada, Z., Buchnik, E., Schain, M., Price, A., Aubrey, B., Nastase, S. A., Feder, A., Emanuel, D., Cohen, A., Jansen, A., Gazula, H., Choe, G., Rao, A., Kim, C., Casto, C., Fanda, L., Doyle, W., Friedman, D., … Hasson, U. (2022). Shared computational principles for language processing in humans and deep language models. *Nature Neuroscience*, *25*(3), 369–380. https://doi.org/10.1038/s41593-022-01026-4

Grand, G., Blank, I. A., Pereira, F., & Fedorenko, E. (2022). Semantic projection recovers rich human knowledge of multiple object features from word embeddings. *Nature Human Behaviour*, *6*(7), 975–987. https://doi.org/10.1038/s41562-022-01316-8

Groppe, D. M., Bickel, S., Dykstra, A. R., Wang, X., Mégevand, P., Mercier, M. R., Lado, F. A., Mehta, A. D., & Honey, C. J. (2017). iELVis: An open source MATLAB toolbox for localizing and visualizing human intracranial electrode data. *Journal of Neuroscience Methods*, *281*, 40–48. https://doi.org/https://doi.org/10.1016/j.jneumeth.2017.01.022

Hartmann, R. R. K., & James, G. (1998). *Dictionary of Lexicography*. Psychology Press.

Hayden, B. Y. (2019). Why has evolution not selected for perfect self-control?. *Philosophical Transactions of the Royal Society B*, *374*(1766), 20180139.

Hayden, B. Y., Heilbronner, S. R., & Yoo, S. B. M. (2025). Rethinking the centrality of brain areas in understanding functional organization. Nature Neuroscience, 1-12.

Hong, Z., Wang, H., Zada, Z., Gazula, H., Turner, D., Aubrey, B., Niekerken, L., Doyle, W., Devore, S., Dugan, P., Friedman, D., Devinsky, O., Flinker, A., Hasson, U., Nastase, S. A., & Goldstein, A. (2024). Scale matters: Large language models with billions (rather than millions) of parameters better match neural representations of natural language. *BioRxiv*, 2024.06.12.598513. https://doi.org/10.1101/2024.06.12.598513

Hosseini, E. A., Schrimpf, M., Zhang, Y., Bowman, S., Zaslavsky, N., & Fedorenko, E. (2024). Artificial neural network language models predict human brain responses to language even after a developmentally realistic amount of training. Neurobiology of Language, 5(1), 43-63.

Huth, A. G., de Heer, W. A., Griffiths, T. L., Theunissen, F. E., & Gallant, J. L. (2016). Natural speech reveals the semantic maps that tile human cerebral cortex. *Nature*, *532*(7600), 453–458. https://doi.org/10.1038/nature17637

Izenman, A. J. (1975). Reduced-rank regression for the multivariate linear model. *Journal of multivariate analysis*, *5*(2), 248-264.

Jamali, M., Grannan, B., Cai, J., Khanna, A. R., Muñoz, W., Caprara, I., Paulk, A. C., Cash, S. S., Fedorenko, E., & Williams, Z. M. (2024). Semantic encoding during language comprehension at single-cell resolution. *Nature*, *631*(8021), 610–616. https://doi.org/10.1038/s41586-024-07643-2

Jenkinson, M., Bannister, P., Brady, M., & Smith, S. (2002). Improved Optimization for the Robust and Accurate Linear Registration and Motion Correction of Brain Images. *NeuroImage*, *17*(2), 825–841. https://doi.org/https://doi.org/10.1006/nimg.2002.1132

Jenkinson, M., & Smith, S. (2001). A global optimisation method for robust affine registration of brain images. *Medical Image Analysis*, *5*(2), 143–156. https://doi.org/https://doi.org/10.1016/S1361-8415(01)00036-6

Johnston, W. J., Fine, J. M., Yoo, S. B. M., Ebitz, R. B., & Hayden, B. Y. (2024). Semi-orthogonal subspaces for value mediate a binding and generalization trade-off. *Nature Neuroscience*, *27*(11), 2218–2230. https://doi.org/10.1038/s41593-024-01758-5

Johnston, W. J., Palmer, S. E., & Freedman, D. J. (2020). Nonlinear mixed selectivity supports reliable neural computation. *PLOS Computational Biology*, *16*(2), e1007544-. https://doi.org/10.1371/journal.pcbi.1007544

Joshi, A., Scheinost, D., Okuda, H., Belhachemi, D., Murphy, I., Staib, L. H., & Papademetris, X. (2011). Unified Framework for Development, Deployment and Robust Testing of Neuroimaging Algorithms. *Neuroinformatics*, *9*(1), 69–84. https://doi.org/10.1007/s12021-010-9092-8

Joulin, A., Grave, E., Bojanowski, P., & Mikolov, T. (2016). Bag of Tricks for Efficient Text Classification. *ArXiv*, *abs/1607.01759*. https://api.semanticscholar.org/CorpusID:1210515

Kahardipraja, P., Madureira, B., & Schlangen, D. (2021). Towards incremental transformers: An empirical analysis of transformer models for incremental NLU. *arXiv preprint arXiv:2109.07364*.

Karkowski, K., Kehl, M. S., Qin, Y., Darcher, A., Karkowski, P., Borger, V., ... & Mormann, F. (2025). Semantic Tuning of Single Neurons in the Human Medial Temporal Lobe. *bioRxiv*, 2025-10.

Katlowitz, K. A., Cole, E. R., Mickiewicz, E. A., Shah, S., Franch, M. C., Adkinson, J., ... & Sheth, S. A. (2025). Plasticity and Language in the Anesthetized Human Hippocampus. Biorxiv, 2025-04.

Katlowitz, K. A., Belanger, J. L., Ismail, T., Chavez, A. G., Chericoni, A., Franch, M., ... & Hayden, B. Y. (2025). Attention is all you need (in the brain): semantic contextualization in human hippocampus. bioRxiv, 2025-06.

Keuleers, E., & Brysbaert, M. (2010). Wuggy: A multilingual pseudoword generator. *Behavior Research Methods*, *42*(3), 627–633. https://doi.org/10.3758/BRM.42.3.627

Khanna, A. R., Muñoz, W., Kim, Y. J., Kfir, Y., Paulk, A. C., Jamali, M., ... & Williams, Z. M. (2024). Single-neuronal elements of speech production in humans. *Nature*, *626*(7999), 603-610.

Kolibius, L. D., Roux, F., Parish, G., Ter Wal, M., Van Der Plas, M., Chelvarajah, R., Sawlani, V., Rollings, D. T., Lang, J. D., Gollwitzer, S., Walther, K., Hopfengärtner, R., Kreiselmeyer, G., Hamer, H., Staresina, B. P., Wimber, M., Bowman, H., & Hanslmayr, S. (2023). Hippocampal neurons code individual episodic memories in humans. *Nature Human Behaviour*, *7*(11), 1968–1979. https://doi.org/10.1038/s41562-023-01706-6

Kommers, C., Ustun, V., Demski, A., & Rosenbloom, P. (2015). *Hierarchical Reasoning with Distributed Vector Representations*. http://cs.fit.edu/mmahoney/compression/textdata.html.

Kumar, S., Sumers, T. R., Yamakoshi, T., Goldstein, A., Hasson, U., Norman, K. A., Griffiths, T. L., Hawkins, R. D., & Nastase, S. A. (2024). *Shared functional specialization in transformer-based language models and the human brain*.

Landauer, T. K., & Dumais, S. T. (1997). A solution to Plato's problem: The latent semantic analysis theory of acquisition, induction, and representation of knowledge. *Psychological Review*, *104*(2), 211–240. https://doi.org/10.1037/0033-295X.104.2.211

Landauer, T. K. (2001). Single representations of multiple meanings in latent semantic analysis. In D. S. Gorfein (Ed.), On the consequences of meaning selection: Perspectives on resolving lexical ambiguity (pp. 217-232). Washington, D. C.: APA Press.

LeBel, A., Jain, S., & Huth, A. G. (2021). Voxelwise Encoding Models Show That Cerebellar Language Representations Are Highly Conceptual. *Journal of Neuroscience*, *41*(50), 10341–10355. https://doi.org/10.1523/JNEUROSCI.0118-21.2021

Lerner, Y., Honey, C. J., Silbert, L. J., & Hasson, U. (2011). Topographic mapping of a hierarchy of temporal receptive windows using a narrated story. Journal of neuroscience, 31(8), 2906-2915.

Li, X., Morgan, P. S., Ashburner, J., Smith, J., & Rorden, C. (2016). The first step for neuroimaging data analysis: DICOM to NIfTI conversion. *Journal of Neuroscience Methods*, *264*, 47–56. https://doi.org/https://doi.org/10.1016/j.jneumeth.2016.03.001

Li, Y., Mathis, A., Grewe, B. F., Osterhout, J. A., Ahanonu, B., Schnitzer, M. J., Murthy, V. N., & Dulac, C. (2017). Neuronal Representation of Social Information in the Medial Amygdala of Awake Behaving Mice. *Cell*, *171*(5), 1176-1190.e17. https://doi.org/https://doi.org/10.1016/j.cell.2017.10.015

Linzen, T., & Baroni, M. (2025). *Syntactic Structure from Deep Learning*. *21*, 43. https://doi.org/10.1146/annurev-linguistics-032020

Lyu, B., Marslen-Wilson, W. D., Fang, Y., & Tyler, L. K. (2024). Finding structure during incremental speech comprehension. *ELife*, *12*, RP89311.

Madureira, B., Kahardipraja, P., & Schlangen, D. (2024). When only time will tell: Interpreting how transformers process local ambiguities through the lens of restart-incrementality. *arXiv preprint arXiv:2402.13113*.

Magnotti, J. F., Wang, Z., & Beauchamp, M. S. (2020). RAVE: Comprehensive open-source software for reproducible analysis and visualization of intracranial EEG data. *NeuroImage*, *223*, 117341. https://doi.org/https://doi.org/10.1016/j.neuroimage.2020.117341

Manning, C. D., Surdeanu, M., Bauer, J., Finkel, J. R., Bethard, S., & McClosky, D. (2014, June). The Stanford CoreNLP natural language processing toolkit. In *Proceedings of 52nd annual meeting of the association for computational linguistics: system demonstrations* (pp. 55-60).

Manning, C. D., Clark, K., Hewitt, J., Khandelwal, U., & Levy, O. (2020). Emergent linguistic structure in artificial neural networks trained by self-supervision. *Proceedings of the National Academy of Sciences*, *117*(48), 30046–30054. https://doi.org/10.1073/pnas.1907367117

McClelland, J. L., & Rogers, T. T. (2003). The parallel distributed processing approach to semantic cognition. *Nature Reviews Neuroscience*, *4*(4), 310–322. https://doi.org/10.1038/nrn1076

Mejri, M., Amarnath, C., & Chatterjee, A. (2024). *LARS-VSA: A Vector Symbolic Architecture For Learning with Abstract Rules*. http://arxiv.org/abs/2405.14436

Mikolov, T., Chen, K., Corrado, G. S., & Dean, J. (2013). Efficient Estimation of Word Representations in Vector Space. *International Conference on Learning Representations*. https://api.semanticscholar.org/CorpusID:5959482

Mikolov, T., Sutskever, I., Chen, K., Corrado, G., & Dean, J. (2013). *Distributed Representations of Words and Phrases and their Compositionality*. http://arxiv.org/abs/1310.4546

Mitchell, J., & Lapata, M. (2008, June). Vector-based models of semantic composition. In *proceedings of ACL-08: HLT* (pp. 236-244).

O'Keefe, J., & Dostrovsky, J. (1971). The hippocampus as a spatial map. Preliminary evidence from unit activity in the freely-moving rat. *Brain Research*, *34*(1), 171–175. https://doi.org/https://doi.org/10.1016/0006-8993(71)90358-1

Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L., Desmaison, A., Köpf, A., Yang, E., DeVito, Z., Raison, M., Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., … Chintala, S. (2019). *PyTorch: An Imperative Style, High-Performance Deep Learning Library*. http://arxiv.org/abs/1912.01703

Pavlick, E. (2025). *Semantic Structure in Deep Learning Keywords*. https://doi.org/10.1146/annurev-linguistics-031120

Pennington, J., Socher, R., & Manning, C. D. (2014). *GloVe: Global Vectors for Word Representation*. http://nlp.

Peters, M. E., Neumann, M., Gardner, M., Clark, C., Lee, K., & Zettlemoyer, L. (2018). *Deep contextualized word representations*. http://allennlp.org/elmo

Piai, V., Anderson, K. L., Lin, J. J., Dewar, C., Parvizi, J., Dronkers, N. F., & Knight, R. T. (2016). Direct brain recordings reveal hippocampal rhythm underpinnings of language processing. *Proceedings of the National Academy of Sciences*, *113*(40), 11366-11371.

Piantadosi, S. T., Muller, D. C. Y., Rule, J. S., Kaushik, K., Gorenstein, M., Leib, E. R., & Sanford, E. (2024). Why concepts are (probably) vectors. In *Trends in Cognitive Sciences* (Vol. 28, Issue 9, pp. 844–856). Elsevier Ltd. https://doi.org/10.1016/j.tics.2024.06.011

Poli, D., Thiagarajan, S., Demarse, T. B., Wheeler, B. C., & Brewer, G. J. (2017). Sparse and specific coding during information transmission between co-cultured dentate gyrus and CA3 hippocampal networks. *Frontiers in Neural Circuits*, *11*. https://doi.org/10.3389/fncir.2017.00013

Prince, J. S., Alvarez, G. A., & Konkle, T. (2025). Contrastive learning explains the emergence and function of visual category-selective regions. *Science Advances*, *10*(39), eadl1776. https://doi.org/10.1126/sciadv.adl1776

Provenza, N. R., Reddy, S., Allam, A. K., Rajesh, S. V., Diab, N., Reyes, G., ... & Sheth, S. A. (2024). Disruption of neural periodicity predicts clinical response after deep brain stimulation for obsessive-compulsive disorder. Nature Medicine, 30(10), 3004-3014.

Pulvermüller, F. (1999a). *Words in the brain: Where? Why? How?* http://nbn-resolving.de/urn:nbn:de:bsz:352-opus-63798

Pulvermüller, F. (1999b). Words in the brain's language. *Behavioral and Brain Sciences*, *22*(2), 253–279. https://doi.org/DOI: 10.1017/S0140525X9900182X

Quian Quiroga, R. (2023). An integrative view of human hippocampal function: Differences with other species and capacity considerations. *Hippocampus*, *33*(5), 616–634. https://doi.org/https://doi.org/10.1002/hipo.23527

Quian Quiroga, R., Kraskov, A., Koch, C., & Fried, I. (2009). Explicit Encoding of Multimodal Percepts by Single Neurons in the Human Brain. *Current Biology*, *19*(15), 1308–1313. https://doi.org/10.1016/j.cub.2009.06.060

Quiroga, R. Q., Reddy, L., Kreiman, G., Koch, C., & Fried, I. (2005). Invariant visual representation by single neurons in the human brain. *Nature*, *435*(7045), 1102–1107. https://doi.org/10.1038/nature03687

Radford, A., Kim, J. W., Hallacy, C., Ramesh, A., Goh, G., Agarwal, S., Sastry, G., Askell, A., Mishkin, P., Clark, J., Krueger, G., & Sutskever, I. (2021). Learning Transferable Visual Models From Natural Language Supervision. *CoRR*, *abs/2103.0*. https://arxiv.org/abs/2103.00020

Radford, A., Wu, J., Child, R., Luan, D., Amodei, D., & Sutskever, I. (2019). *Language Models are Unsupervised Multitask Learners*. https://github.com/codelucas/newspaper

Rey, H. G., Panagiotaropoulos, T. I., Gutierrez, L., Chaure, F. J., Nasimbera, A., Cordisco, S., Nishida, F., Valentin, A., Alarcon, G., Richardson, M. P., Kochen, S., & Quian Quiroga, R. (2025). Lack of context modulation in human single neuron responses in the medial temporal lobe. *Cell Reports*, *44*(1). https://doi.org/10.1016/j.celrep.2024.115218

Rigotti, M., Barak, O., Warden, M. R., Wang, X. J., Daw, N. D., Miller, E. K., & Fusi, S. (2013). The importance of mixed selectivity in complex cognitive tasks. *Nature*, *497*(7451), 585-590.

Rogers, T. T., & Mcclelland, J. L. (2004). *Semantic Cognition: A Parallel Distributed Processing Approach*.

Rolls, E. T., & Tovee, M. J. (1995). Sparseness of the neuronal representation of stimuli in the primate temporal visual cortex. *Journal of Neurophysiology*, *73*(2), 713–726. https://doi.org/10.1152/jn.1995.73.2.713

Rousseeuw, P. J. (1987). Silhouettes: A graphical aid to the interpretation and validation of cluster analysis. *Journal of Computational and Applied Mathematics*, *20*, 53–65. https://doi.org/https://doi.org/10.1016/0377-0427(87)90125-7

Rutishauser, U., Reddy, L., Mormann, F., & Sarnthein, J. (2021). The architecture of human memory: insights from human single-neuron recordings. *Journal of Neuroscience*, *41*(5), 883-890.

Saxena, S., & Cunningham, J. P. (2019). Towards the neural population doctrine. *Current opinion in neurobiology*, *55*, 103-111.

Schönmann, I., Szewczyk, J., de Lange, F. P., & Heilbron, M. (2025). Stimulus dependencies—rather than next-word prediction—can explain pre-onset brain encoding during natural listening. bioRxiv, 2025-03.

Semedo, J. D., Zandvakili, A., Machens, C. K., Yu, B. M., & Kohn, A. (2019). Cortical areas interact through a communication subspace. *Neuron*, *102*(1), 249-259.

Senel, L. K., Utlu, I., Yucesoy, V., Koc, A., & Cukur, T. (2017). *Semantic Structure and Interpretability of Word Embeddings*. https://doi.org/10.1109/TASLP.2018.2837384

Squire, L. R., & Zola-Morgan, S. (1991). The Medial Temporal Lobe Memory System. *Science*, *253*(5026), 1380–1386. https://doi.org/10.1126/science.1896849

Suthana, N. A., Parikshak, N. N., Ekstrom, A. D., Ison, M. J., Knowlton, B. J., Bookheimer, S. Y., & Fried, I. (2015). Specific responses of human hippocampal neurons are associated with better memory. *Proceedings of the National Academy of Sciences*, *112*(33), 10503-10508.

Tang, J., LeBel, A., Jain, S., & Huth, A. G. (2023). Semantic reconstruction of continuous language from non-invasive brain recordings. *Nature Neuroscience*, *26*(5), 858–866. https://doi.org/10.1038/s41593-023-01304-9

Tian, Y., Krishnan, D., & Isola, P. (2020). Contrastive Multiview Coding. In A. Vedaldi, H. Bischof, T. Brox, & J.-M. Frahm (Eds.), *Computer Vision – ECCV 2020* (pp. 776–794). Springer International Publishing.

Tuckute, G., Sathe, A., Srikant, S., Taliaferro, M., Wang, M., Schrimpf, M., ... & Fedorenko, E. (2024). Driving and suppressing the human language network using large language models. Nature Human Behaviour, 8(3), 544-561.

Tulving, E. (2002). Episodic Memory: From Mind to Brain. *Annual Review of Psychology*, *53*(Volume 53, 2002), 1–25. https://doi.org/https://doi.org/10.1146/annurev.psych.53.100901.135114

Tversky, A. (1977). Features of similarity. *Psychological Review*, *84*(4), 327–352. https://doi.org/10.1037/0033-295X.84.4.327

Tye, K. M., Miller, E. K., Taschbach, F. H., Benna, M. K., Rigotti, M., & Fusi, S. (2024). Mixed selectivity: Cellular computations for complexity. *Neuron*, *112*(14), 2289-2303.

Vaswani, A., Brain, G., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., & Polosukhin, I. (2017). *Attention Is All You Need*.

Vinje, W. E., & Gallant, J. L. (2000). Sparse coding and decorrelation in primary visual cortex during natural vision. *Science (New York, N.Y.)*, *287*(5456), 1273–1276. https://doi.org/10.1126/science.287.5456.1273

Wang, M. Z., & Hayden, B. Y. (2021). Latent learning, cognitive maps, and curiosity. *Current Opinion in Behavioral Sciences*, *38*, 1-7.

Wolf, T., Debut, L., Sanh, V., Chaumond, J., Delangue, C., Moi, A., Cistac, P., Rault, T., Louf, R., Funtowicz, M., Davison, J., Shleifer, S., Von Platen, P., Ma, C., Jernite, Y., Plu, J., Xu, C., Le Scao, T., Gugger, S., … Rush, A. M. (2020). *Transformers: State-of-the-Art Natural Language Processing*. https://github.com/huggingface/

Wu, B., & Pillow, J. (2025). Reduced rank regression for neural communication: a tutorial for neuroscientists.

Xiao, J., Adkinson, J. A., Allawala, A. B., Banks, G., Bartoli, E., Fan, X., Mocchi, M., Pascuzzi, B., Pulapaka, S., Franch, M. C., Mathew, S. J., Mathura, R. K., Myers, J., Pirtle, V., Provenza, N. R., Shofty, B., Watrous, A. J., Pitkow, X., Goodman, W. K., … Hayden, B. Y. (2024). *Insula uses overlapping codes for emotion in self and others*. https://doi.org/10.1101/2024.06.04.596966

Xiao, J., Adkinson, J. A., Myers, J., Allawala, A. B., Mathura, R. K., Pirtle, V., Najera, R., Provenza, N. R., Bartoli, E., Watrous, A. J., Oswalt, D., Gadot, R., Anand, A., Shofty, B.,

Mathew, S. J., Goodman, W. K., Pouratian, N., Pitkow, X., Bijanki, K. R., … Sheth, S. A. (2024). Beta activity in human anterior cingulate cortex mediates reward biases. *Nature Communications*, *15*(1), 5528. https://doi.org/10.1038/s41467-024-49600-7

Xu, D., Chung, J. E., Silva, A. B., Metzger, S. L., Greicius, Q. R., Zhang, Y., ... & Chang, E. F. (2024). Human precentral gyrus neurons link speech sequences from listening to speaking. *bioRxiv*, 2024-12.

Yacoub, E., Grier, M. D., Auerbach, E. J., Lagore, R. L., Harel, N., Adriany, G., ... & Zimmermann, J. (2020). Ultra-high field (10.5 T) resting state fMRI in the macaque. *Neuroimage*, *223*, 117349.

Yan, X., Krishna, A., Arsdel, K. V., Gautam, I., Kim, B., Shrivastava, A., ... & Sheth, S. A. (2025). Shared neural geometries for bilingual semantic representations. bioRxiv, 2025-11.

Yang, A. I., Wang, X., Doyle, W. K., Halgren, E., Carlson, C., Belcher, T. L., Cash, S. S., Devinsky, O., & Thesen, T. (2012). Localization of dense intracranial electrode arrays using magnetic resonance imaging. *NeuroImage*, *63*(1), 157–165. https://doi.org/https://doi.org/10.1016/j.neuroimage.2012.06.039

Zada, Z., Goldstein, A., Michelmann, S., Simony, E., Price, A., Hasenfratz, L., Barham, E., Zadbood, A., Doyle, W., Friedman, D., Dugan, P., Melloni, L., Devore, S., Flinker, A., Devinsky, O., Nastase, S. A., & Hasson, U. (2024). A shared model-based linguistic space for transmitting our thoughts from brain to brain in natural conversations. *Neuron*, *112*(18), 3211-3222.e5. https://doi.org/10.1016/j.neuron.2024.06.025

Zeng, T., Li, X., & Si, B. (2019). *Learning Sparse Spatial Codes for Cognitive Mapping Inspired by Entorhinal-Hippocampal Neurocircuit*. http://arxiv.org/abs/1910.04590

Zhu, H., Franch, M., Mickiewicz, E., Belanger, J., Cowan, R. L., Katlowitz, K., ... & Hayden, B. Y. (2026). Semantic axes in the brain support analogical representations. bioRxiv, 2026-01.

Zipf, G. K. (1945). The Meaning-Frequency Relationship of Words. *The Journal of General Psychology*, *33*(2), 251–256.

1650 **Extended Data Figures**

1651

**Extended Data Fig. 1 | Single and multi-unit detection and isolation. A,** A random sample
of 5,000 individual waveforms from a single hippocampal neuron (blue) and multi unit cluster
(red) from patient 8 recorded on one electrode channel. Bolded lines represent average
waveforms. Noisy signals were already removed using *Wave_clus* sorting algorithms and
manual inspection. **B,** All waveforms from each cluster in **A** are well isolated in Principal
Component space. **C,** Interspike interval (ISI) histograms from the neurons in **A**. Single and
multi-unit clusters always have refractory period violations below 5% (as shown in figure
titles). **D,** Example hippocampal single (yellow and blue) and multiunit (red) waveforms on
individual electrode channels from four patients that were identified and sorted following the
criteria in **B-C** using *Wave_clus* software and manual inspection.

1662
**Extended Data Fig. 2 | Hippocampal neuron responses to words and non-words. A,** Peri-
stimulus time histograms of firing rate responses to words from example hippocampal neurons
in seven different patients during language comprehension. **B**, Peri-stimulus time histograms of
firing rate responses of neurons exhibiting significant changes in firing rate to words and non-
words (Wilcoxon rank-sum test, P < 0.05). Example hippocampal neurons are shown from 3
different patients. **C,** Linear decoding accuracy for words and nonwords (jabberwocky stimuli)
from neural population activity comprised of all neurons across four patients, for models using
real and shuffled data.

1671
**Extended Data Fig. 3 | Single neuron responses to words of different spoken durations.**
**A,** Histograms of the word durations for short (1,852 words), middle length (1,852 words
randomly sampled to match other groups), and long words (1,842 words). Dashed lines
represent the median word duration for each group. **B,** Peri-stimulus time histograms of firing
rate responses to words of different durations from example hippocampal neurons in seven
different patients during language comprehension. Dashed lines represent word onset.

**Extended Data Fig. 4 | Semantic, phonetic, and combined linguistic feature regression models. A,** Semantic model (Word2Vec) coefficients of significant predictors of neurons fit by the model. Word duration and embeddings 1-8 had the largest absolute valued weights. **B,**

The number of neurons for which each predictor (as seen in **A**) was significant. PC embeddings 1-8, word duration, and their interactions were significant predictors in most neurons fit by the semantic model. **C,** Left - McFadden's pseudo R-squared for neurons fit by the actual and embedding shuffled (X-shuffled) semantic model. Values from the real semantic model are significantly higher than shuffled; Wilcoxon signed-rank test, $P < 0.001$. Right- The difference in neurons' Pseudo R-squared values between the semantic and X-shuffled model distributions (left). **D,** For each neuron, the relative increase in pseudo-$R^2$ when semantic embeddings are added to a word duration-only model. Specifically, it is $R^2$ of the combined full model minus $R^2$ of the duration model, divided by $R^2$ of the duration model and multiplied by 100. **E,** Log likelihood difference between real and shuffled models for the same neurons fit by the phonetic and semantic embedding models (see Methods); Wilcoxon signed-rank test, $P < 0.001$. **F,** For each neuron, the difference in pseudo R-squared from a combined model with phonetic and semantic embeddings, and a separate model with either phonetic (green) or semantic (blue) embeddings. Semantic embeddings explain significantly more variance than phonetic embeddings. Wilcoxon signed-rank test, $P < 0.001$. **G,** The number of neurons for which each predictor was significant in the model is plotted on the y-axis, and the total number of neurons is also displayed on top of the bar plot. This model used semantic embeddings from Word2Vec, and models using BERT or GPT-2 embeddings had comparable results. **H,** The absolute value of the coefficient, or weight, of each predictor in the model is shown on the y-axis. Bars reflect the median predictor weight taken across neurons fit by the model. Predictors are sorted by decreasing weights. Poly = polysemy; Wps = word position in sentence; wpc = word position in clause; freq = word frequency; open and close represent opening and closing nodes; sem1-10 are semantic embeddings from Word2Vec.

**Extended Data Fig. 5 | Effects of function words and pronouns on semantic coding. A,**
The change in log-likelihood between the null and actual model for models fit with all words
(blue) compared to the same measure in models fit without function words or pronouns (gray,
FWE model). Delta LLH values were normalized by dividing each neuron's delta LLH value by
the number of words used in the model. P< 0.05, Wilcoxon signed-rank test. **B,** The Pseudo
R-squared values for the same neurons shown in A from models using all words or function
words and pronouns removed. P< 0.001, Wilcoxon signed-rank test. **C,** The Pearson
correlation coefficient between neural and semantic distance for either all word pairs (blue) or
word pairs excluding function words and pronouns (gray). All correlations are significant, P <
0.001. **D,** Each word is plotted according to its polysemy value and neural distance (median
distance between all occurrences of that word). Words are colored based on their semantic
category. P and r-values are from Pearson correlation.

1718
**Extended Data Fig. 6 | Semantic categories from contextual embeddings. A,** words plotted
in their dimensionality reduced BERT embedding space and colored according to their
semantic category defined in Word2Vec. Words are grouped in 30 distinct categories defined
from silhouette score and k-means clustering of BERT embeddings. Black dashed lines outline
the identified categories. **B,** The same as in A but with GPT-2 layer 37 embeddings. 23
categories are identified. 1,808 words out of 7,346 are plotted here for visualization.
1725
1726
1727
1728

1729

1730

**Extended Data Fig. 7 | The relationship between neural and semantic distance across language models, noise models, and individual patients. A,** Scatter plot illustrating the correlation between neural and GPT-2 layer 37 semantic embedding distances between all 26,978,185 word pairs. Pink line: regression line. Each dot represents one randomly selected word pair; magenta text indicates example pairs. **B,** Scatter plot illustrating the correlation between GPT-2 layer 37 semantic embedding distances and GPT-2 embedding distances that were transformed with neural noise. **C,** the same as in B, but with BERT embeddings from layer 13. **D,** Plots for each language model show the distribution of correlations between neural and semantic distances obtained from shuffled neural activity (gray), the correlation from the real neural and semantic data (red), and the neural noise ceiling (blue dashed line), computed as the correlation between the semantic embeddings and their noise-injected versions. For BERT and GPT-2, the real neural correlation is well above chance and falls below - but close to - the noise ceiling, indicating that the models capture more than half of the explainable neural-semantic structure. In contrast, Word2Vec shows a negative correlation and a modest noise ceiling, consistent with its poor alignment with neural structure. **E,** For each patient (colored line), the semantic-neural correlation coefficient computed at increasing BERT semantic

1748    distances (binwidth 0.2, step size 0.01). While this line is generally positive in value, at
1749    especially short semantic distances (low x-values), it turns negative, reflecting contrastive
1750    coding in each patient. **F,** For each language model, histograms show the neural and semantic
1751    distance correlation using neural embeddings from each patient separately. **G,** Contrastive
1752    coding for each patient, as computed in panel E but using GPT-2 embeddings.

**A**

HPC

1763

1764  **Extended Data Fig. 8 | Semantic categories from neural embeddings. A,** Words plotted in
1765  their dimensionality reduced neural embedding space and colored according to their semantic
1766  category defined in Word2Vec. Words are grouped in 3 distinct categories defined from
1767  silhouette score and k-means clustering of neural embeddings. Black dashed lines outline the
1768  identified categories. 1,808 words out of 7,346 are plotted here for visualization.

1769

1770
1771  **Extended Data Fig. 9 | The relationship between linguistic features and neural**
1772  **distance. A,** Weights from a ridge regression model that predicted neural distance
1773  between all word pairs from the difference in polysemy, word frequency, word duration,
1774  and semantic category for each word pair, and the GPT-2 layer 37 (left) or Word2Vec
1775  (right) semantic distance between them. Asterisks represent significant predictors. **B,** The

same as in A-left but restricted to word pairs with semantic distances within the contrastive coding range, 0.14 - 0.4. **C**, Weights from a ridge regression model that predicted, for every word, the median neural distance between all occurrences of that word from that word's polysemy (computed with GPT-2 layer 37 embeddings), frequency, duration, and semantic category. Asterisks represent significant predictors.

**Extended Data Fig. 10 | Comparison between semantic coding using the full population and a semantically selective subset of neurons**. **A,** For semantic embeddings from Word2Vec, BERT layer 13, and GPT-2 layer 37, the Pearson correlation between neural and semantic distance using the the full population of neurons (n = 356) or a subset of neurons whose residual activity was significantly predicted by semantic embeddings (n = 92). All r-values are significant, P < 0.001. **B,** The Pearson correlation between word and neural polysemy, where neural polysemy was computed using a subset of semantically selective neurons or the full population. All r-values are significant, P < 0.001. **C,** Reduced rank regression performance for predicting different language model embeddings from neural population activity using data from each patient individually (n ~ 30 neurons per patient), the subset of semantically selective neurons (n = 92) or the full population (n = 356). All regression models show the same trends in performance and optimal rank across the three language models.