A vectorial code for semantics in human hippocampus

Melissa Franch[1], Elizabeth A. Mickiewicz[1], James L. Belanger[1,2], Assia Chericoni[1], Ana G. Chavez[1], Kalman A. Katlowitz[1], Raissa Mathura[1], Eleonora Bartoli[1], Suzanne Kemmer[2], Steven T. Piantadosi[3], Nicole R. Provenza[1], Andrew J. Watrous[1], Sameer A. Sheth[1], and Benjamin Y. Hayden[1,2]*

1. Department of Neurosurgery, Baylor College of Medicine, Houston, Texas, United States of America
2. Department of Linguistics, Rice University
3. Department of Psychology, University of California Berkeley

* Correspondence: Benjamin.Hayden@bcm.edu

Funding statement
This research was supported by the McNair Foundation and by NIH R01 MH129439.

Competing interests
The authors have no competing interests to declare.

Acknowledgements
        We thank Jeff Johnston, Joshua Adkinson, and Victoria Pirtle for invaluable assistance.

24   **ABSTRACT**
25
As we listen to speech, our brains actively compute the meaning of individual
words. Inspired by the success of large language models (LLMs), we hypothesized that
the brain employs vectorial coding principles, such that meaning is reflected in
distributed activity of single neurons. We recorded responses of hundreds of neurons in
the human hippocampus, which has a well-established role in semantic coding, while
participants listened to narrative speech. We find encoding of contextual word meaning
in the simultaneous activity of neurons whose individual selectivities span multiple
unrelated semantic categories. Like embedding vectors in semantic models, distance
between neural population responses correlates with semantic distance; however, this
effect was only observed in contextual embedding models (like BERT) and was reversed
in non-contextual embedding models (like Word2Vec), suggesting that the semantic
distance effect depends critically on contextualization. Moreover, for the subset of highly
semantically similar words, even contextual embedders showed an inverse correlation
between semantic and neural distances; we attribute this pattern to the noise-mitigating
benefits of contrastive coding. Finally, in further support for the critical role of context,
we find that range of neural responses covaries with lexical polysemy. Ultimately, these
results support the hypothesis that semantic coding in the hippocampus follows vectorial
principles.

INTRODUCTION

As we listen to speech, we typically identify the meanings (semantics) of the words we hear. The principles by which neurons encode meaning remain poorly understood. One hypothesis is that semantic coding is fundamentally vectorial, so that word meanings are encoded in patterns of activation across a large number of distinct units (Frisby et al., 2023; Goldstein et al., 2022, 2024; Landauer & Dumais, 1997; Mitchell & Lapata, 2008; Piantadosi et al., 2024; Pulvermüller, 1999; Rogers & Mcclelland, 2004). Interest in vectorial encoding has grown in recent years because it is a core element of large language models (LLMs), which have shown great promise in a variety of applications (Devlin et al., 2018; Joulin et al., 2016; Mikolov, Chen, et al., 2013; Mikolov et al., 2013; Pennington et al., 2014; Radford et al., 2019; Vaswani et al., 2017). Inspired by the observation that such models can adroitly manipulate semantic information, we hypothesized that semantics in the human brain is also vectorial (Linzen & Baroni, 2025; Manning et al., 2020; Pavlick, 2025).

Typically, word vectors are composed of embedding values as units, but these units could be firing rates from neurons in the brain (Jamali et al., 2024). In a standard vectorial code, units do not have an identifiable semantic meaning; instead, they tend to have broad and complex response fields that encompass many apparently unrelated concepts (Frisby et al., 2023; Landauer & Dumais, 1997; McClelland & Rogers, 2003; Mitchell & Lapata, 2008; Pulvermüller, 1999b, 1999a; Rogers & McClelland, 2004). Likewise, a given word's meaning reflects the concurrent activation of a variety of units that are also selective for other words. In contrast, a good deal of evidence from the hippocampus supports the hypothesis that neurons are selective to single discrete concepts (Quian Quiroga, 2023; Quian Quiroga et al., 2005 and 2009; Rey et al., 2025), consistent with ideas that hippocampus has highly sparse codes and narrow selectivities (Kolibius et al., 2023; O'Keefe & Dostrovsky, 1971; Poli et al., 2017; Zeng et al., 2019). In a similar vein, a recent study examining neuronal activity in posterior middle frontal gyrus found, likewise, that neurons there are selective for a single semantic category, such as words relating to actions (Jamali et al., 2024).

Nonetheless, we were interested in exploring the vectorial hypothesis because it can provide ready solutions to many important problems in cognitive science, such as similarity judgments, analogies, generalization, hierarchical reasoning, pattern completion, and efficient learning (Chen et al., 2017; Kommers et al., 2015; Mejri et al., 2024; Tversky, 1977; Piantadosi et al., 2024). For example, if embeddings recapitulate semantics, then similarity judgments can be as simple as calculating the neural embedding distance between two words (Devlin et al., 2018; Erk, 2012; Grand et al., 2022; Joulin et al., 2016; Pennington et al., 2014; Radford et al., 2019; Tversky, 1977; Vaswani et al., 2017). Indeed, it is the close association between embedding and semantic distance that endows vectorial codes with many of their most useful properties (Frisby et al., 2023; Mitchell & Lapata, 2008; Rogers & Mcclelland, 2004; Senel et al., 2017). One

difficulty in assessing the vectorial hypothesis is that contextual embedding models are
relatively new (since 2017, Devlin et al., 2018; Peters et al., 2018; Radford et al., 2019;
Vaswani et al., 2017) and neuroscience research has only recently begun relating neural
and contextual word embeddings, albeit not at the single unit level (Goldstein et al., 2022,
2023, 2024; Hong et al., 2024; Hosseini et al., 2024; Kumar et al., 2024; LeBel et al.,
2021; Tang et al., 2023; Tuckute et al., 2024; Zada et al., 2024). Indeed, word meanings
in normal language are highly contextually dependent. For example, the word "sharp"
may mean something entirely different in the phrases "sharp knife" and "sharp mind".
Contextual semantic embedders capture these nuances of language.
We were especially interested in the hippocampus because of its well-established
role in semantic and conceptual coding (Blank et al., 2016; Davachi, 2006; Dijksterhuis
et al., 2024; Fletcher et al., 1997; Quian Quiroga et al., 2005 and 2009; Rey et al., 2025;
Squire & Zola-Morgan, 1991; Tulving, 2002). We recorded responses of neurons in the
hippocampus of epilepsy patients undergoing intracranial monitoring for seizure activity
while patients listened to continuous, narrative speech. We compared linguistic
embeddings from both contextual and non-contextual embedding models to neural
embedding vectors and neural responses to words and polysemy (Hartmann & James,
1998). We found that individual neurons have complex, multi-word tunings, and that
lexical concepts are encoded by large and heteromorphic populations of hippocampal
neurons. Moreover, we find that semantic embedding distance correlates with neural
embedding distance, but only for models that involve a high degree of contextual
embedding. Indeed, neural embedding variance correlated with polysemy, changing
activity with different instances of the same word. Finally, we find evidence for a strong
contrastive code for highly similar words. Together, these results endorse the hypothesis
that semantic encoding in human hippocampus is fundamentally vectorial.

	RESULTS
109	

Neural encoding of meaning

Ten native English-speaking patients undergoing neural monitoring for epilepsy
listened to 47 minutes of English speech (six monologues taken from the Moth podcast,
Methods, Figure 1A and B). This stimulus set consisted of 7,346 words, of which 1,351
were unique. We collected responses of isolated single neurons in hippocampus (HPC,
n=356 neurons) from 10 patients. Overall, neurons showed a clear response to the onset
of individual words with a characteristic ramping to a peak, followed by a gradual decline
in firing, although there was a great deal of diversity across neurons (**Figure 1C, D, and
E**). We computed firing rate during an epoch starting 80 ms after the onset of each word
(to account for the approximate response latency) and lasting the duration of the word
(see **Methods**). Rates were normalized by word duration. All analyses were repeated with
a variety of response epochs which yielded similar results (data not shown).

A subset of patients (n=4) also listened to monologues containing nonsense words
(Keuleers & Brysbaert, 2010) (*jabberwocky stimuli*, 1,890 words, see **Methods**)
following the podcast episodes. The nonsense narratives included words modified from
real ones to create meaningless, novel terms, such as "toom" or "skook." These nonword
stimuli preserved syntactic structure by retaining function words and morphemes but
lacked coherent semantics. We found that 57% of neurons (75/125) exhibited a
significant change in firing rate to non-word stimuli, with most cells showing markedly
reduced activity for nonwords relative to words (**Figure 1D**). Additionally, hippocampal
neural population activity strongly distinguishes words from nonwords, achieving an
average decoding accuracy of 75% (chance is 50%; see **Methods**).

Next, we sought to better understand the relationship between neural activity and
semantics, particularly how language unfolds over time as words are heard in sequence.
To do this, we predicted each neuron's firing rate for a given word using its
dimensionality-reduced Word2Vec embedding (Mikolov, et al., 2013, **Figure 1F**).
Word2Vec represents each word as a fixed (i.e., non-contextual) 300-dimensional vector,
meaning, for example, the embedding for "camp" remains the same whether it is used as
a noun or a verb. The linear model fit the responses of 70 neurons, showing a significant
correlation between actual and predicted firing rates (**20%, Figure 1F**). We found
comparable results with contextual embeddings (e.g., BERT embeddings fit 72 neurons,
not shown; Devlin et al., 2018).

Next, we used the same linear model to predict neural activity from up to five
words in the past and future. We found that for each word in time, model performance
was always significantly better than chance (shuffled activity model; performance
declined after five words). However, prediction accuracy showed a characteristic decay
in decodability as a function of distance forwards and backwards in time (**Figure 1G**).
Thus, it appears that hippocampal neurons keep track of recently heard words and also
show some evidence of predicting upcoming words, just as other brain regions have been

shown to do (Goldstein et al., 2024; Goldstein, Wang, et al., 2023; Jamali et al., 2024;
Tang et al., 2023; Zada et al., 2023).
We next identified the broad semantic categories that exist in our dataset.
Word2Vec embedding distances recapitulates semantic distance, such that the embedding
vectors for synonyms like 'dad' and 'father' have a smaller semantic distance (cosine
distance) than unrelated words like 'dad' and 'emergency' (Joulin et al., 2016; Mikolov,
Chen, et al., 2013; Mikolov, Sutskever, et al., 2013). We leveraged this fact to build
semantic categories (**Figure 1H**; Huth et al., 2016; Jamali et al., 2024). Silhouette
criterion analysis (**Figure1I**; Rousseeuw, 1987) and k-means clustering of the word
embeddings (see **Methods**) revealed 11 putative semantic categories in the story data,
listed in increasing word frequency, with examples in brackets: (1) body parts [hand,
lungs, scar], (2) places- [hospital, office, cabin], (3) emotional [cheer, disgust, feelings],
(4) mental- [know, answer, imagine], (5) social [friends, queen, dad] (6) objects [book,
flowers, pigeon], (7) visual [beautiful, green, sizzling], (8) numerical [another, eleven,
moment], (9) actions [shimmied, writing, elected], (10) identity [she, y'all, their], and
(11) function words [the, about, onto] (**Figure 1J**).

Figure 1. Hippocampal neurons track spoken words during language comprehension. | A, Electrode recording location of hippocampal neurons from ten patients. **B,** Continuous spiking activity from five example hippocampal neurons from patient 6 during words heard during the experiment, as shown in the spectrogram. **C,** Peri-stimulus time histograms and raster plots demonstrating responses to word onsets from four distinct hippocampal neurons in patient 6 (bottom row) and 7 (top row). Dashed lines represent word onset. Plots display mean firing rate ±SEM shaded. **D,** Left - Peri-stimulus time histogram during words and jabberwocky (nonsense) non-words. Right - 71/125

neurons from four patients that exhibit significantly different firing rates between real and
non-words. P = 5.6x10^{-5}, Wilcocxon signed-rank test. Red line represents the mean firing
rate from words and non-words (14.78 and 13.98). **E**, The firing rate of one neuron
occurring across the duration of all words from the six stories during language
comprehension. **F**, Left - regression equation used to fit an individual neuron's firing rate
from word embeddings (word2vec). PC stands for principal components of the
embeddings and *f* is a neuron's firing rate for each word. Right - Correlation coefficients
between the actual and model-predicted firing rates for significant neurons that were fitted
by the model; P < 0.05, Spearman correlation. **G**, Left - boxplot of Spearman correlation
coefficients between actual and model-predicted firing rates from the current word
embeddings and those of past and future words. Boxes reflect the interquartile range with
median; red line is the neuron averaged coefficients from shuffled models; blue curve is
gaussian density fit. Actual model coefficients for each word index are significant from
shuffled, Wilcoxon rank sum test, all P < 0.01. Right - correlation coefficients as shown on
the left across all neurons and word indexes (time). **H**, Similarity matrix of median pairwise
cosine distances between word embeddings within and between semantic categories that
arise from all words. **I**, Silhouette score used to determine the number of semantic
categories for K-means clustering of words. **J,** All words plotted in their dimensionality
reduced embedding space and colored according to their semantic category.
193
A dense and distributed coding of semantics
One possible way to represent meaning in the brain is through neurons that
selectively respond to single words, or to single categories of semantically related words,
such as those associated with family, sports, or nature. However, this regime could be
biologically inefficient, as it would require many neurons - enough needed for all the
concepts learned across one's life. Alternatively, the same neuron could encode different
concepts not simultaneously but at different moments based on context or cognitive
demands. Recently, many studies have demonstrated a clear and robust evidence for
mixed selectivity coding principles in a range of contexts (Blanchard et al., 2018; Fusi et
al., 2016; Johnston et al., 2020, 2024). Therefore, we hypothesized that word coding
would be distributed and dense - meaning a single neuron should encode many,
semantically unrelated words and one word should be encoded by many different
neurons.
To quantify individual neuron encoding of words, we performed a Receiver
Operating Characteristic (ROC) analysis (**Figure 2A-B**), a standard approach that has
previously been used to characterize neural responses during behavior (Britten et al.,
1992; Y. Li et al., 2017). For statistical reasons (**Methods**), we used only words that
occurred at least four times in the data (n = 283 words), and compared firing rates evoked
by each word to all others (see **Methods**). Every single one of these 283 words was
encoded by at least 3 neurons (**Figure 2C-E**). The words with the least encoding (i.e.,
most sparsely coded) were 'was' and 'and', encoded by exactly 3 neurons; the most

dense word, 'hit", was encoded by 67 neurons (0.8 and 18.8% of our sample,
respectively, **Figure 2D-E**). On average, a single word is encoded by 37 neurons (10.4%,
Figure 2D). Likewise, most neurons encoded many words. Only 6 out of 356 neurons did
not encode any words, and the median number of words encoded by a neuron was 6
words (**Figure 2F**).

Are the words a neuron encodes semantically similar or different? Surprisingly,
the same neuron does not reliably encode semantically similar words. For example,
within the social category (category 5), we examined encoding of words related to the
concept of family (mom, dad, father, brother, and son), and found minimal overlap
between neurons that encode each family-related word (**Figure 2G**). Indeed, of the 28
neurons encoding "father" and 19 encoding "dad," only 7 encode both words (**Figure
2G**). Notably, the distinct words that a cell encoded spanned semantic categories and
phonology. For example, neuron 167 encodes the words: 'lot', 'remember', 'even',
'they', 'those, and 'make'; neuron 252 encodes the words: 'she', 'last', 'out', 'school',
and 'team'. Each of those neurons encode words that span 5 unique semantic categories.
Overall, a given neuron's response field spanned 4 of our 11 semantic categories (**Figure
2I**). (And, recall that these proportions refer to all sampled neurons, not just a preselected
subset of selective neurons).

We also wondered whether more specific concepts, like proper nouns, were
encoded in this dense and distributed manner. Only three proper nouns appeared
frequently enough in our data to perform statistics: 'Mark,' 'God,' and 'Michelle'. These
three are also densely encoded in the population, with 'God' showing the highest density
at 60 neurons (**Figure 2H**). 89 neurons (25%) encoded these 3 proper nouns, with
minimal neuronal overlap between them (14 neurons encoded all 3 names). Across
semantic categories, fewer neurons encoded identity (pronouns) and function words,
while more critical and less frequent categories, such as body parts and emotion words,
were more densely encoded (**Figure 2J**). We found that such densely coded words had
significantly higher classification performance (area under the curve) compared to
sparsely coded words, suggesting neurons exhibit more distinct firing rates patterns for
these less frequent words that are critical for understanding (**Figure 2K**).

245
Figure 2. Hippocampal neurons represent words with a dense and distributed code.
l A, Example firing rates from one neuron during all occurrences of the word, "go" and a
random subset of other words. **B**, Receiver operator characteristic curve for the same
neuronal activity and words in a. **C**, For each word (line), the standardized area under the
curve (AUC) from each neuron that significantly classified that word from all others (see
Methods). **D**, Histogram of the number of neurons encoding each word. Every word was
encoded by at least 3 neurons. **E**, The same as in d but all 283 word text plotted based on
the number of neurons that encode them, with added jitter for readability. **F,** Histogram of
the number of words encoded by each neuron. **G,** Assessment of overlap between
neurons encoding words related to the concept, family. Numbers in the matrix and circles
represent the number of coding neurons. **H,** Left - Number of neurons encoding proper
nouns from ROC analysis. Right - AUC values for proper noun encoding. **I,** Number of
semantic categories from the words that each neuron encodes. Dashed line represents
the median. **J,** Average number of neurons encoding words from each semantic category.

K, Probability density plots of AUC values from sparse words (n = 1,517 AUC values from
words with < 28 cells encoding them) and dense words (n = 1,632 AUC values from words
with more than 55 cells encoding them). P = 1.643×10^{-9}, Wilcoxon rank sum test.
263
264

Hippocampal semantic coding is vectorial
One convenient feature of semantic embeddings derived from large language
models is that embedding distances correlate with semantic distances (Devlin et al., 2018;
Mikolov, et al., 2013; Pennington et al., 2014; Radford et al., 2019; Vaswani et al., 2017)
(**Figure 3A**). Thus, synonymous terms like "mom" and "mother" will be located close to
each other in embedding space, while unrelated terms like "mom" and "tarmac" will be
located far apart. Here, we will follow the standard convention of using angular (cosine)
distance between embedding vectors (Mikolov et al., 2013; Pennington et al., 2014;
Radford et al., 2019). We performed an analogous analysis on the responses of a
population of neurons to ask whether *neural embedding distances* are correlated with
semantic embedding distances (**Figure 3B**). Overall, we find that contextual embedding
distance between randomly selected word pairs is correlated with their neural embedding
distances (**Figure 3C-E**). Consider, for example, the contextual embedder BERT (Devlin
et al., 2018)(r = 0.0650, p<0.0001, **Figure 3D**). Note that while the size of this
correlation is low, this is expected given the extremely high variance of single neuron
firing rates and the fact that each datapoint reflects a single occurrence of a given word.
Indeed, this problem of high noise could cause confusion for words with the most
similar embeddings. Such word pairs include "but and so", "we and we're", and "he and
him" (although the embeddings also include local context not given here, **Figure 3F**).
While the brain needs to recognize their similarity, it also needs to maintain their
semantic separation as well. For example, we would not want to mix up holiday gifts for
our two parents because their semantic embeddings are nearly identical. Thus, we
hypothesized that, at the finest scale, neuronal embeddings would have an additional
feature of contrastive coding (sometimes called repulsive coding; Bromley et al., 1994;
Chanales et al., 2017; Prince et al., 2025; Radford et al., 2021; Tian et al., 2020), which
would allow for separation between similar, but still distinct, words. We find precisely
this: pairs of closely related words (regardless of semantic category) tend to show a
negative correlation between semantic and neural distance (**Figure 3F-G**). In other
words, the relation between semantic and neural embedding is scale-dependent: negative
for the finest scale and positive for all others (**Figure 3G**). Specifically, the negative
pattern is observed when considering the word pairs whose semantic distances span the
range of r = 0.15 to r = 0.35 (these comprise 2.16% of the words in our sample, **Figure**
3F-G). (Note that words with a range of r < 0.15 comprise less than one tenth of one
percent of pairs, and data in this range are too noisy to meaningfully interpret). These
highly similar pairs include many pairs of identical words; however, this negative
correlation in semantically close pairs is driven entirely by word pairs consisting of

different words (near-synonyms like "sort/kind" and "are/were"), rather than identical
word pairs (such as "and/and" or "the/the"). Specifically, in the range of 0.15-0.35, we
found $r = -0.151$ ($p < 0.0001$) for different word pairs (**Figure 3F**) and $r = +0.032$ ($p =$
0.45) for identical pairs (**Figure 3H**).
Notably, this coding regime was not unique to BERT embeddings. The same
contrastive coding for semantically similar word pairs and pattern separation for
semantically different words is also observed in GPT-2 layer 36 embeddings (notice the
similarity between **Figure 3G and 3I**; Radford et al., 2019). Interestingly, we found a
negative correlation between semantic and neural distance for early GPT-2 layers (1-13)
and for Word2Vec embeddings (**Figure 3J-K**). We think this is due to the early layers of
GPT-2 being less contextual than the late layers, and thus more similar to static, non-
contextual embeddings from models like Word2Vec. Therefore, the neural coding of
semantics is both vectorial and highly contextual.
Additionally, the distance between neural embeddings of words within a semantic
category is a function of increasing word frequency (**Figure 3L, blue**; this is the case for
inter-category distances as well). Meaning, low-frequency body part words like "hand"
and "finger" are closer in both neural space and the semantic space of contextual
embeddings, while high-frequency identity words like "everyone" and "they" show
greater distance, as seen in **Figure 3L** (red, pink, and blue). In other words, like the
cluster of stars near the center of the Milky Way, frequent words are more centrally
positioned in the high-dimensional embedding space, a pattern that is replicated in the
hippocampal coding. Indeed, applying context to semantic embeddings causes a
reduction in semantic distance for low-frequency words and increases it for high-
frequency words, compared to static embeddings like Word2Vec (**Figure 3L, gray**). This
shift, influenced by context, aligns with the pattern of category and frequency-dependent
neural distance, explaining why Word2Vec embedding distances are negatively
correlated with neural data, whereas contextual models show a positive correlation, more
accurately reflecting the vectorial and contextual encoding of semantics in the
hippocampus.

Figure 3. Neural distance recapitulates semantic distance. | A, We define semantic
distance as the angular distance in a high dimensional space between two semantic
vectors (embedding values for each word). **B,** We define neural distance in the analogous
manner, where each word's neural embedding is the vector of firing rates from all neurons
for that word. **C,** Semantic BERT embedding and neural embedding distance correlations
among all word-pairs within each of the eleven semantic categories. While most are
positive, some categories have negative correlations, likely due to contrastive coding. **D,**
Scatter plot illustrating the correlation between neural and semantic embedding distances
between all 26,978,185 word pairs. Pink line: regression line. Each dot represents one
randomly selected word pair; magenta text indicates example pairs. **E,** Histogram of neural
embedding distances; this plot is the marginal of D across the x-axis. **F,** Expanded view
of the data from D in the neural range of 0.15-0.25; this range represents 2.16% of the
data. In this range, the correlation between neural and semantic distances is negative. **G,**
Histogram of BERT semantic embedding distances; this plot is the marginal of D across
the y-axis. Below it is shown the semantic/neural correlation coefficient for the sub-range
of BERT values centered on the x-axis point. While this line is generally positive in value,
at especially short distances (low x-values), it turns negative. That negative correlation
may reflect contrastive coding. **H,** Same data as in G, but limited to pairs in which the
same word is compared in two locations. Because BERT is a contextual embedder, these
will not have precisely the same value. **I.** Same data as in G, but using GPT-2 layer 36
rather than BERT. Same effects are observed, indicating that effects are not due to BERT.
J, Correlation between semantic and neural distance across all layers of GPT-2. Early
layers that are non-contextual embeddings have negative correlations with neural data,
while higher, contextual layers are positive. Red indicates a layer with nonsignificant
correlation. **K**, The same as in D but with Word2Vec semantic embeddings. These
embeddings are static and non-contextual (similar to early layers in GPT-2), and
negatively correlate with neural distance. **L,** Within-category neural distance and semantic
distances from different language models. The arrow reflects how context changes
semantic embeddings, improving their association to neural patterns of semantic coding.
Word2vec r = -0.22, BERT r =   0.62*, GPT-2 r = 0.72*, Neural r = 0.83*; Pearson
correlation coefficient, *P < 0.05, regression lines plotted.
362

Semantic coding is high dimensional and contextual
Next, we examined neural population coding and dimensionality of semantics.
Using Principal Component Analysis (PCA) of each neuron's firing rate for every word
(7,346 words x 356 neurons), we reduced the dimensionality of our neurons' responses to
components. Only 35% of variance is explained in the first 10 components, telling us that
this code is relatively high dimensional (95% of variance explained in first 190
components, **Figure 4A**; Jazayeri & Ostojic, 2021; Manley et al., 2024**).** The fact that
many dimensions are needed to explain most of the variance is consistent with the
hypothesis that meaning is distributed across many neurons. Neural interactions
underlying meaning may be nonlinear and cannot be fully captured by a low-dimensional

projection. Indeed, each semantic category can be decoded nonlinearly from the others
using population activity, but high frequency words like numbers, actions, and function
words had reduced decoding performance compared to low frequency words (**Figure
4B**). This finding suggests, as do others above, that neural coding principles differ
markedly for high frequency and low frequency words.
Indeed, for each neuron, lifetime sparseness increased as a function of word
frequency across semantic categories, meaning that neurons respond to fewer common
words than they do rare ones (**Figure 4C, left**). Likewise, population sparseness
increased with word frequency, meaning a rare word activates more neurons than a
common word does. This is consistent with, among other explanations, an energy
efficient coding scheme, wherein words that are heard more often elicit less neural
activity (**Figure 4C, right**).
Why do common words have reduced decoding and more sparseness compared to
other, less spoken words? We think this is due, in large part, to the fact that common
words are more polysemous (**Figure 4E, top;** Zipf, 1945), meaning the same word can
have different meanings depending on the context in which it is spoken. To explore this
idea further, we computed polysemy for each word by taking the cosine distance between
BERT embedding vectors of repeated occurrences of the same word (n = 594 distinct and
repeated words, see **Methods**). Polysemy is likely driving the larger neural distance
between words occurring *within* high-frequency categories compared to low-frequency
ones (**Figure 4D and 3L**). The words within these categories have more nuanced and
flexible meanings, resulting in greater semantic (in contextual models) and neural
distance within categories (**Figure 4D and 3L**).
Polysemy also explains why high frequency categories are harder to decode from
all others - because these common words activate broad, overlapping neural patterns
rather than category-specific ones. For example, 'the' may produce similar neural
patterns to the noun that it modifies, such as 'the school', making 'the' and 'school'
harder to neurally distinguish, despite being members of two different semantic
categories (function words and places, respectively). Likewise, if a neuron is selective for
a particular meaning of a highly polysemous word, it will only fire in contexts where that
meaning is relevant, leading to a sparser response across all instances of the word. Since
polysemy increases with word frequency, this can explain the similar trend we found
across semantic categories in sparseness (**Figure 4C**). Given that neural distance
positively correlates with semantic distance in contextual models (**Figure 3**), it follows
that neural activity patterns also strongly correlate with polysemy (**Figure 4E bottom
and 4F**). In other words, the meaning of a given high-polysemy word is more
contextually driven than the meaning of a low-polysemy word, and hippocampal
encoding tracks with that contextually driven meaning.

Figure 4. Population coding of words across frequency and context. | A, The amount of variance explained for each component from PCA of neural firing rates across all words. 35% of variance is explained in the first 10 components. **B**, Decoding accuracy for each semantic category and all other categories from neural population activity, for models using actual (blue) and shuffled (gray) labeled data. Chance is 50% (dashed line). Plots display mean prediction accuracy on test observations (±SEM). P < 0.0001 for each category, Wilcoxon signed rank test comparing actual and shuffled accuracy. **C**, Left - lifetime and population sparseness measures across semantic categories, sorted by increasing word frequency. Right - schematic showing population sparseness coding regime of words based on frequency. P and r-values are from Pearson correlation. **D**, Similarity matrix of neural distance between all word pairs within and across each semantic category. Diagonal of this matrix is plotted in Figure 3L. **E**, Top - polysemy values for each unique and repeated word within each semantic category. Bottom - neural distance between different occurrences of the same word, within each semantic category. P and r-values are from Pearson correlation. **F**, Each word is plotted according to its polysemy value and neural distance (median distance between all occurrences of that word). Words are colored based on their semantic category. P and r-values are from Pearson correlation. Lines in c, e, and f are regression lines.

DISCUSSION

Here, we show that the hippocampus exhibits a dense, vectorial, and contextual
coding scheme for semantics. That is, individual words are encoded in the simultaneous
activity of multiple neurons whose selectivities span multiple unrelated semantic
categories (**Figure 2**). While a single neuron can distinguish individual words, the
semantic *relationship* between words (even multiple occurrences of the same word) is
reflected in vectors of the neural population activity (**Figure 3-4**). We find that *neural*
embedding vectors, derived from the collective responses of neural populations, closely
track word meanings as they shift across different contexts. This pattern is reflected in the
association between neural activity and embeddings derived from high layers of
contextual embedders (BERT and GPT-2), which incorporate meaning from adjacent
words and sentences. Moreover, regardless of the embedder, at short semantic distances,
this pattern is reversed. We propose that this reversal reflects a contrastive code that
allows the brain to distinguish semantically very similar words (**Figure 3**).

Our finding of dense and vectorial encoding of meaning contrasts with the idea
that there is a one-to-one correspondence between neurons and concepts (Dijksterhuis et
al., 2024; Quian Quiroga et al., 2005 and 2009; Rey et al., 2025). Of course, words are
not exactly the same as concepts; our results, therefore, raise the possibility that word
coding in the hippocampus may be dense while concept coding is sparse. Our attempt to
isolate the most canonically concept-like words speech resulted in three cases where the
single concept was repeated enough times for statistical analysis ('God', 'Mark', and
'Michelle'); in these cases, we still find that those identities are encoded by many
neurons (**Figure 2H**). These results, if found to be generally true, would suggest that
concept-related words are densely coded when situated in the context of natural speech.
That situation may imbue words with meanings of adjacent ones (Vaswani et al., 2017)
(on the other hand, see Rey et al., 2025). Nonetheless, a direct comparison of results is
difficult because of the many differences between our methods and these earlier ones.

Why are semantic embedding distances anti-correlated with neural embedding
distances for word2Vec? Our data do not provide a clear answer to this question, but, in
aggregate, they suggest the outlines of an answer. Overall, we find that contextual
embedding distances and neural embeddings both align with word frequency and
polysemy levels (which themselves are highly correlated, **Figure 3L**). Thus, the meaning
of a high-polysemy word is more influenced by context than that of a low-polysemy word
- this makes sense because high polysemy words, almost by definition, have meanings
that are highly influenced by context. We suspect that it is this context that is the primary
driver of the correlation between neural and semantic embeddings. The non-contextual
embedders lack all of this context and give words a single context-free embedding.
Absent the context, the underlying overall negative correlation is uncovered. This
underlying negative correlation does not have a ready explanation, but may reflect a
special property of the hippocampus, which is associated with contrastive coding

(Bromley et al., 1994; Chanales et al., 2017; Prince et al., 2025; Radford et al., 2021;
Tian et al., 2020). One study shows a positive correlation between single neuron and
semantic embeddings in a region outside of the hippocampus (Jamali et al., 2024).
If hippocampal semantic coding is vectorial, then it shares important features with
semantics in large language models (LLMs). This does not mean, however, that the brain
is simply a LLM itself - indeed, we find clear differences between hippocampus and
LLMs (for example, anti-correlations between neural and semantic embedding for non-
contextual embeddings and for very close words). However, if the brain is not just one
big LLM, LLMs more generally do offer a good comparison for thinking about neural
data, and as a source of interpretational guidance for human neuroscientific data. In other
words, LLMs may be more akin to a distant neuroscience model organism, like a fruit fly,
that may share some key principles in common with human brains.

METHODS

Human intracranial neurophysiology

All experiments were performed in the Epilepsy Monitoring Unit (EMU) at Baylor St. Luke's Hospital using standardized approaches (Xiao et al., 2024A and B).

Experimental data were recorded from 10 adult patients (6 males and 4 females) undergoing intracranial monitoring for epilepsy. The hippocampus was not a seizure focus area of any patients included in the study. Single neuron data were recorded from stereotactic (sEEG) probes, specifically AdTech Medical probes in a Behnke-Fried configuration. Each patient had an average of 3 probes terminating in the left and right hippocampus. Electrode locations are verified by co-registered pre-operative MRI and post-operative CT scans. Each probe includes 8 microwires, each with 8 contacts, specifically designed for recording single-neuron activity. Single neuron data were recorded using a 512-channel *Blackrock Microsystems Neuroport* system sampled at 30 kHz. To identify single neuron action potentials, the raw traces were spike sorted using the *WaveClus* sorting algorithm (Chaure et al., 2018)and then manually evaluated. Noise was removed and each signal was classified as multi or single unit using several criteria: consistent spike waveforms, waveform shape (slope, amplitude, trough-to-peak), and exponentially decaying ISI histogram with no ISI shorter than the refractory period (1 ms). The analyses here used all single and multiunit activity.

Electrode visualization

Electrodes were localized using the software pipeline intracranial Electrode Visualization (iELVis; Groppe et al., 2017) and plotted across patients on an average brain using Reproducible Analysis & Visualization of iEEG (RAVE; Magnotti et al., 2020). For each patient, DICOM images of the preoperative T1 anatomical MRI and the postoperative Stealth CT scans were acquired and converted to NIfTI format (Li et al., 2016). The CT was aligned to MRI space using FSL (Jenkinson et al., 2002; Jenkinson & Smith, 2001). The resulting coregistered CT was loaded into BioImage Suite (version 3.5β1; Joshi et al., 2011) and the electrode contacts were manually localized. Electrodes coordinates were converted to patient native space using iELVis MATLAB functions (Yang et al., 2012) and plotted on the Freesurfer (version 7.4.1) reconstructed brain surface (Dale et al., 1999). Microelectrode coordinates are taken from the first (deepest) macro contact on the Ad-Tech Behnke Fried depth electrodes. RAVE (Magnotti et al., 2020) was used to transform each patient's brain and electrode coordinates into MNI152 average space. The average coordinates were plotted together on a glass brain with the hippocampus segmentation and colored by patient.

Natural language stimuli

Patients with epilepsy and healthy language function listened to six episodes (5- to 13-minutes in duration) taken from *The Moth Radio Hour,* and totaling 47:25 minutes of listening time (7,346 words). The six stories were, "Life Flight", "The Tiniest Bouquet", "The One Club", "Wild Women and Dancing Queens", "My Father's Hands" and "Juggling and Jesus". In each story, a single speaker tells an autobiographical narrative in front of a live audience. The six selected stories were chosen to be both interesting and linguistically rich. Stories were played continuously through the built-in audio speakers of the patient's hospital television. The audio signal was synchronized to the neural recording system via analog input going directly from the computer playing the audio into the Neural Signal Processor at 30 kHz.

Jabberwocky stimuli
After story listening, a subset of four patients listened to 17 minutes of
Jabberwocky stories (1,890 words) to assess neural specificity for semantics (**Figure 1D**).
Jabberwocky stimuli are words that are altered from the real words in the stories used in
the experiment to become words that have no meaning, for example, "toom" or "skook".
An example sentence of jabberwocky stimuli is: Before I smow it, the foodbace toom is
at my frose woor, and a coakle of them have bapes of bour under their alk. We used the
software, *Wuggy*, to transform story transcripts into jabberwocky (Keuleers & Brysbaert,
2010). This program matched the subsyllabic segment length of each word and replaced
words with letters that match phonetic probabilities of orthographic English.
Jabberwocky preserves syntactic structure by retaining function words and morphemes,
even though it lacks coherent semantics.
541
Audio Transcription
After experiments, the audio .wav file was automatically transcribed using Python and
Assembly AI, a state-of-the-art AI model to transcribe and understand speech. The transcribed
words and corresponding timestamp output from Assembly AI was converted to a TextGrid and
then loaded into Praat, a software for speech analysis. The original .wav file was also loaded into
Praat and we manually checked the spectrograms and timestamps, correcting each word to
ensure the word onset and offset times are accurate. The TextGrid output of corrected words and
timestamps from Praat was converted to a .xls and loaded into Matlab and Python for further
analysis.
551
Clustering of semantic vectors
To identify the natural semantic categories present in our word data (**Figure 1H-J**), all
unique words were clustered into groups based on related meanings using a word embedding
approach (Joulin et al., 2016; Mikolov, et al., 2013). We used the pre-trained *fastText Word2Vec*
model in MATLAB to extract word embeddings for all words in our dataset (Joulin et al., 2016;
Mikolov et al., 2013). This pre-trained model provides 300-dimensional word embedding
vectors, trained on millions of words text, to capture semantic relationships between words. Any
surname words, such as "Harwood" or proper nouns like "Applebee's" that did not have word
embeddings was discarded from the analysis. To compute and visualize semantic clusters, we
used a t-distributed Stochastic Neighbor Embedding (t-SNE) algorithm on word embedding
values to reduce the dimensionality of each unique word based on their cosine distance to all
other words, thus reflecting their semantic similarity. Words with similar meanings now have
similar 2D coordinates. We then applied the K-means clustering algorithm to these 2D word
representations and visualized clustered words on a 2D word map (k = 11 clusters, determined
from the silhouette score; Rousseeuw, 1987). We then manually inspected and assigned a distinct
semantic label to each cluster and adjusted categories for accuracy. For example, words
bordering the edges of categories might get mis-grouped and were manually corrected. This
method is comparable to those used in other studies of semantics (Huth et al., 2016; Jamali et al.,
2024).
571
Firing rate responses to words
We computed the duration for each word in the story and for each non-word in
Jabberwocky stimuli. The firing rate of a neuron for each word was the number of spikes

occurring during the word, beginning with an 80 ms delay (and adding a further 80 ms delay
afterwards) to account for the approximate delay of information to hippocampus. This value was
divided by word duration and then multiplied by 1000 to compute spikes per second.
578

Regressing firing rates on word embeddings
We regressed the activity of each neuron onto five principal components from Word2Vec
or BERT semantic embedding vectors (**Figure 1F-G**). We first used Principal Component
Analysis (pca, Matlab 2023b) to reduce word embedding to five values per word (the first 5
principal components). Each of these embedding values was a predictor in the regression
(fitlm, Matlab 2023b):

600 $$Firing\ rate\ (words, n) = \beta_0 + \beta_1 V_{w1} + \beta_1 V_{w1} + \beta_1 V_{w1} + \beta_1 V_{w1} + \beta_1 V_{w1} + \epsilon_n$$
Such that the firing rate of the n^{th} neuron for each word (w) is modeled by the linear regression
coefficients (β), one for each of the five components of that word (V_w), plus the y-intercept
(β_0) and the residuals (ϵ_n). We used 10-fold cross validation to train and test the model on held-
out data, over 200 iterations. Model performance was evaluated by the root mean squared error
values relative to firing rates. A neuron was fit by the model if the Spearman correlation
between predicted and actual firing rates was significant ($p < 0.05$). For the linear models
predicting past and future words, a separate model was fit for each word index, by which we
shifted the words relative to the firing rates, such that the firing rate of a neuron for word X
corresponded to an embedding of a different word that was in the future or past, based on the
index. To determine whether neural activity was predicted by each word index, the distribution
of actual model performance (y-yhat spearman correlation) from every neuron was compared to
that of a shuffled model (chance distribution) - a model trained on shuffled firing rates of that
neuron. For each word index, these distributions were compared using the Wilcoxon rank sum
test ($P < 0.05$). Model performance was significantly better than chance for up to five words in
the past and future.

Single neuron encoding of words
Semantic encoding of each neuron was quantified using a ROC (receiver operating
characteristic) analysis, a standard approach that has previously been used to characterize neural
responses during behavior (Britten et al., 1992; Li et al., 2017). Here, the firing rate of each
neuron is the classifier that is evaluated on its ability to distinguish instances of a word from all
other words. For statistical reasons, since we need to compare two distributions, we performed
the analysis on every neuron for every word that occurred at least 4 times (283 words, on average
each word occurred 20 times, the most was 407).
Upon application of a binary threshold to firing rates and comparison with a binary event
vector denoting word label (1 for the current word, 0 for other words), word detection based on
neural activity can be measured using the true positive rate (TPR) and the false positive rate
(FPR). Plotting the TPR against the FPR over a range of binary thresholds, spanning the
minimum and maximum values of the neural signal, yields an ROC curve that describes how
well the neural signal detects POS at each threshold. With the perfcurve function in Matlab
2023b, we used the area under the ROC curve (AUC) as a metric for how strongly neurons are
modulated by each word (**Figure 2A-C**). The number of word occurrences in the 'Current word'
class were balanced with the number of words in "Other" class by subsampling words from the
"Other" class over 100 iterations of the analysis. For each neuron, AUC was computed, then

averaged and compared to a null distribution across iterations. For each neuron, the observed
AUC was compared to a null distribution of 1,000 AUC values generated from constructing
ROC curves over randomly permuted neural signals (that is, firing rate permuted across words,
thus destroying the relationship between neural responses and word labels). The p-value is
calculated as the proportion of permuted AUC values that are greater than or equal to the
observed AUC and a neuron was considered significantly responsive if $P < 0.05$. To better
visualize encoding magnitude, we standardized each AUC value by subtracting chance (0.5)
from every value, resulting in values between 0 and 0.5.
628

Contextual embeddings

In an excel file of our transcribed words, each row corresponded to an individual token,
including punctuation and sentence terminators such as ".", "?", and "!". We reconstructed
sentences by iterating through the file and appending words until encountering a recognized
sentence delimiter. This process yielded multi-word segments that more accurately captured
natural linguistic boundaries. Any remaining words following the last delimiter were grouped
into a final sentence. Notably, punctuation tokens were preserved to maintain contextual fidelity
but were tracked carefully to avoid introducing sub-word alignment errors during tokenization.
To extract GPT-2 embeddings, we employed the "gpt2-large" model (Radford et al.,
2019) from the Hugging Face Transformers library (Wolf et al., 2020). This version of GPT-2
features a total of 37 layers (1 initial embedding layer plus 36 transformer layers), each
producing 1280-dimensional hidden states, with a maximum context length of 1024 tokens. We
extracted hidden states from all 37 layers using a progressive context approach designed to
incorporate the autoregressive nature of GPT-2. Specifically, for each sentence, we began with
an empty context and added words sequentially. After adding each new word, we tokenized the
updated text string via GPT-2's Byte Pair Encoding (BPE) tokenizer, ran the token sequence
through the model in a no-grad (inference-only) mode, and retrieved the hidden states. We then
identified the newly appended word's sub-word tokens and averaged their corresponding vectors
to obtain a single word-level embedding. Because GPT-2 often splits words into multiple sub-
word fragments (otherwise known as "tokens", e.g., "computa" + "tion"), averaging those
fragments preserves consistency with the transcript's original word boundaries. The GPT-2
outputs resulted in 1280-dimensional embeddings for each layer.
We conducted a parallel extraction procedure with the "bert-base-cased" model (Devlin et
al., 2018), also accessed via the Hugging Face Transformers library (Wolf et al., 2020). In
contrast to GPT-2, whose progressive context reflects its decoder-only design, BERT uses a
masked language modeling objective and an encoder-only architecture. We therefore segmented
the data into complete utterances—often spanning multiple sentences—and tokenized them up to
BERT's 512-token limit. To ensure that these representations aligned with the transcript words,
we again averaged sub-word embeddings whenever a single word was split by the tokenizer.
However, in this instance, we extracted only the last layer of hidden states from BERT, yielding
one 768-dimensional vector per token, which was then aggregated to the word level. All code
was implemented in Python using PyTorch (Paszke et al., 2019) as the underlying deep learning
framework, and final embeddings were saved in Excel spreadsheets for subsequent analyses.

Embedding distance

664   The semantic embedding vector for each word was its full vector of embedding values
extracted from either Word2Vec (300 in length), BERT (768 in length), or GPT-2 (1280 in
length) language models. For each word, it's neural embedding vector was every neuron's firing
rate response for that word (356 in length). Neurons were combined across all 10 patients,
making a pseudo population totaling 356 neurons. We used the function `pdist`, Matlab 2023b,
to compute cosine distance between semantic embedding vectors of all 26,978,185 word pairs,
known as semantic distance. We repeated the procedure, computing cosine distance between
neural embedding vectors for all word pairs, termed neural cosine distance. "All word pairs"
included pairs of the same word except in Word2Vec analysis, since cosine distance between
two instances of the same word will always be 0 (since embedding values are the same). This
procedure was followed for word pairs within and between each semantic category to create the
semantic distance similarity matrix in **Figure 1H**, for the neural and semantic distances within
each category in **Figure 3L**, and for the neural distance similarity matrix in **Figure 4D**. For
Figure 3C, we computed the semantic distance from BERT embeddings for all word pairs
within each semantic category, then computed neural distance for all word pairs within each
semantic category and correlated (Pearson) these two distance vectors to compute the values
shown on the y-axis. Similarly, we correlated semantic distance and neural distance from all
word pairs (unless otherwise specified in the caption) to compute the correlation coefficients in
Figure 3G-J. In **Figure 4E-F**, neural cosine distance was always computed between word pairs
of multiple instances (minimum 2) of the same word. We took the median of these distances to
extract one distance value per word.

$$\text{Cosine distance } (w_1, w_2) = 1 - \frac{W1 * W2}{||W1|| \ ||W2||}$$

Cosine distance between neural or semantic embeddings of word 1 and word 2 is the 1 minus the
dot product of embedding vectors for each word, divided by the magnitudes (norms) of each word
vector.

Support Vector Machine Decoder

693   We used a SVM decoder (Bishop, 2006) with a nonlinear radial-based function kernel to
determine whether firing rates during words carry information about semantics by distinguishing
each category from all others (**Figure 4B**). For each semantic category, we used the firing rate
responses from every neuron (n = 356) for each word in the category (class 1) and all rates for all
other words (class 2) to predict the class for each word from these neural data. The number of
words in each class were always balanced – across comparisons and across semantic categories
through random subsampling of words from the larger class. Random selections of class
observations were repeated for 100 iterations, giving us the average classification accuracy over
1,000 test splits of the data for each session. To train and test the model, we used a tenfold cross-
validation. In brief, the data were split into ten subsets, and in each iteration the training
consisted of a different 90% subset of the data; the testing was done with the remaining 10% of
the data. We used the default hyperparameters as defined in `fitcsvm`, MATLAB 2023b, with
hyperparameter $C = 1$ and z-scored normalization of firing rates. Decoder performance was
calculated as the percentage of correctly classified test trials. We compared model performance

for predicting train and test data to check for overfitting. In each iteration, we trained a separate
decoder with randomly shuffled class labels. The performance of the shuffled decoder was used
as a null hypothesis for the statistical test of decoder performance.
710

Sparseness
The firing rate of each neuron during the word duration (see Methods, *Firing rate*
responses to words) was used to compute sparseness values. We applied the method used by
Vinje and Gallant (Vinje & Gallant, 2000) which is a slight modification of the method first
proposed by Treves and Rolls (Rolls & Tovee, 1995).
Lifetime sparseness. For a given neuron, for each semantic category, its lifetime sparseness was
computed using:

718
$$s = \frac{1 - \frac{1}{N}\frac{\left(\Sigma_i\, r_i\right)^2}{\Sigma_i\, r_i{}^2}}{1 - \frac{1}{N}} \quad ,$$

719   where N is the number of words in the semantic category and r_i is the response of the neuron to
720   the i^{th} stimulus. The sparseness value ranges from 0 (when the neuron is least sparse and
721   responds equally to all the words in the category) to 1 (when the neuron is maximally sparse and
722   responds only to 1 word). Lifetime sparseness was averaged across all neurons in each category
723   and plotted in **Figure 4C -** left.
724

725   *Population sparseness.* For a given word in each semantic category, its population sparseness
726   was computed using:

727
$$s = \frac{1 - \frac{1}{M}\frac{\left(\Sigma_j\, r_j\right)^2}{\Sigma_j\, r_j{}^2}}{1 - \frac{1}{M}} \quad ,$$

where M is the number of neurons and r_j is the response of the j^{th} neuron to the word. This
sparseness value also ranges from 0 (when the word is least sparse and elicits equal responses
from all the neurons) to 1 (when the word is maximally sparse and elicits response from only 1
neuron). For each semantic category, population sparseness was averaged across words in that
category and plotted in **Figure 4D** - right. Lifetime and population sparseness results in **Figure**
4D are consistent even when balancing the number of words across semantic categories by
subsampling the larger category (data not shown).
735

Polysemy
To compute polysemy for each word, we computed cosine distance between each BERT
embedding vector of all occurrences of a given word (at least 2 occurrences, 594 words total).
We took the median of this distribution to obtain one polysemy value per word (**Figure 4E-F**).
The distribution of polysemy values for all words in each semantic category is plotted in Figure
4E – top. We repeated the polysemy analysis using neural embeddings instead of BERT
embeddings to compute the neural cosine distance values in Figure 4E – bottom and Figure 4F.
We also computed polysemy for each word as the total number of synsets (i.e., distinct senses)
associated with each word in WordNet (Fellbaum, 1998). These polysemy values yielded the
same results shown in Figure 4E-F (results not shown).
746

REFERENCES

Bishop, C. M. (2006). *Pattern recognition and machine learning*. New York : Springer

Blanchard, T. C., Piantadosi, S. T., & Hayden, B. Y. (2018). Robust mixture modeling reveals category-free selectivity in reward region neuronal ensembles. *Journal of Neurophysiology*, *119*(4), 1305–1318. https://doi.org/10.1152/jn.00808.2017

Blank, I. A., Duff, M. C., Brown-Schmidt, S., & Fedorenko, E. (2016). Expanding the language network: Domain-specific hippocampal recruitment during high-level linguistic processing. *BioRxiv*, 091900. https://doi.org/10.1101/091900

Britten, K. H., Shadlen, M. N., Newsome, W. T., & Movshon, J. A. (1992). The analysis of visual motion: a comparison of neuronal and psychophysical performance. *The Journal of Neuroscience*, *12*(12), 4745. https://doi.org/10.1523/JNEUROSCI.12-12-04745.1992

Bromley, J., Guyon, I., Lecun, Y., Sickinger, E., Shah, R., Bell, A., & Holmdel, L. (1994). *Signature Verification using a "Siamese" Time Delay Neural Network*.

Cervera, R. L., Wang, M. Z., & Hayden, B. Y. (2020). Systems neuroscience of curiosity. Current Opinion in Behavioral Sciences, 35, 48-55.

Chanales, A. J. H., Oza, A., Favila, S. E., & Kuhl, B. A. (2017). Overlap among Spatial Memories Triggers Repulsion of Hippocampal Representations. *Current Biology*, *27*(15), 2307-2317.e5. https://doi.org/https://doi.org/10.1016/j.cub.2017.06.057

Chaure, F. J., Rey, H. G., & Quian Quiroga, R. (2018). A novel and fully automatic spike-sorting implementation with variable number of features. *Journal of Neurophysiology*, *120*(4), 1859–1871. https://doi.org/10.1152/jn.00339.2018

Chen, D., Peterson, J. C., & Griffiths, T. L. (2017). *Evaluating vector-space models of analogy*. http://arxiv.org/abs/1705.04416

Cisek, P., & Hayden, B. Y. (2022). Neuroscience needs evolution. Philosophical Transactions of the Royal Society B, 377(1844), 20200518.

Dale, A. M., Fischl, B., & Sereno, M. I. (1999). Cortical Surface-Based Analysis: I. Segmentation and Surface Reconstruction. *NeuroImage*, *9*(2), 179–194. https://doi.org/https://doi.org/10.1006/nimg.1998.0395

Davachi, L. (2006). Item, context and relational episodic encoding in humans. *Current Opinion in Neurobiology*, *16*(6), 693–700. https://doi.org/https://doi.org/10.1016/j.conb.2006.10.012

Devlin, J., Chang, M.-W., Lee, K., Google, K. T., & Language, A. I. (2018). *BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding*. https://github.com/tensorflow/tensor2tensor

Dijksterhuis, D. E., Self, M. W., Possel, J. K., Peters, J. C., van Straaten, E. C. W., Idema, S., Baaijen, J. C., van der Salm, S. M. A., Aarnoutse, E. J., van Klink, N. C. E., van Eijsden, P., Hanslmayr, S., Chelvarajah, R., Roux, F., Kolibius, L. D., Sawlani, V., Rollings, D. T., Dehaene, S., & Roelfsema, P. R. (2024). Pronouns reactivate conceptual representations in human hippocampal neurons. *Science*, *385*(6716), 1478–1484. https://doi.org/10.1126/science.adr2813

Erk, K. (2012). Vector Space Models of Word Meaning and Phrase Meaning: A Survey. *Language and Linguistics Compass*, *6*(10), 635–653. https://doi.org/https://doi.org/10.1002/lnco.362

Fellbaum, C. (1998). *WordNet: An Electronic Lexical Database*. The MIT Press; Bradford Books.

Fletcher, P. C., Frith, C. D., & Rugg, M. D. (1997). The functional neuroanatomy of episodic memory. *Trends in Neurosciences*, *20*(5), 213–218. https://doi.org/https://doi.org/10.1016/S0166-2236(96)01013-2

Frisby, S. L., Halai, A. D., Cox, C. R., Lambon Ralph, M. A., & Rogers, T. T. (2023). Decoding semantic representations in mind and brain. *Trends in Cognitive Sciences*, *27*(3), 258–281. https://doi.org/10.1016/j.tics.2022.12.006

Fusi, S., Miller, E. K., & Rigotti, M. (2016). Why neurons mix: high dimensionality for higher cognition. *Current Opinion in Neurobiology*, *37*, 66–74. https://doi.org/10.1016/j.conb.2016.01.010

Goldstein, A., Grinstein-Dabush, A., Schain, M., Wang, H., Hong, Z., Aubrey, B., Nastase, S. A., Zada, Z., Ham, E., Feder, A., Gazula, H., Buchnik, E., Doyle, W., Devore, S., Dugan, P., Reichart, R., Friedman, D., Brenner, M., Hassidim, A., … Hasson, U. (2024). Alignment of brain embeddings and artificial contextual embeddings in natural language points to common geometric patterns. *Nature Communications*, *15*(1), 2768. https://doi.org/10.1038/s41467-024-46631-y

Goldstein, A., Ham, E., Schain, M., Nastase, S., Zada, Z., Dabush, A., Aubrey, B., Gazula, H., Feder, A., Doyle, W. K., Devore, S., Dugan, P., Friedman, D., Reichart, R., Brenner, M., Hassidim, A., Devinsky, O., Flinker, A., Levy, O., & Hasson, U. (2023). *The Temporal Structure of Language Processing in the Human Brain Corresponds to The Layered Hierarchy of Deep Language Models*. https://doi.org/10.1101/2022.07.11.499562

Goldstein, A., Wang, H., Niekerken, L., Zada, Z., Aubrey, B., Sheffer, T., Nastase, S. A., Gazula, H., Schain, M., Singh, A., Rao, A., Choe, G., Kim, C., Doyle, W., Friedman, D., Devore, S., Dugan, P., Hassidim, A., Brenner, M., … Hasson, U. (2023). *Deep speech-to-text models capture the neural basis of spontaneous speech in everyday conversations*. https://doi.org/10.1101/2023.06.26.546557

Goldstein, A., Zada, Z., Buchnik, E., Schain, M., Price, A., Aubrey, B., Nastase, S. A., Feder, A., Emanuel, D., Cohen, A., Jansen, A., Gazula, H., Choe, G., Rao, A., Kim, C., Casto, C., Fanda, L., Doyle, W., Friedman, D., … Hasson, U. (2022). Shared computational principles for language processing in humans and deep language models. *Nature Neuroscience*, *25*(3), 369–380. https://doi.org/10.1038/s41593-022-01026-4

Grand, G., Blank, I. A., Pereira, F., & Fedorenko, E. (2022). Semantic projection recovers rich human knowledge of multiple object features from word embeddings. *Nature Human Behaviour*, *6*(7), 975–987. https://doi.org/10.1038/s41562-022-01316-8

Groppe, D. M., Bickel, S., Dykstra, A. R., Wang, X., Mégevand, P., Mercier, M. R., Lado, F. A., Mehta, A. D., & Honey, C. J. (2017). iELVis: An open source MATLAB toolbox for localizing and visualizing human intracranial electrode data. *Journal of Neuroscience Methods*, *281*, 40–48. https://doi.org/https://doi.org/10.1016/j.jneumeth.2017.01.022

Hartmann, R. R. K., & James, G. (1998). *Dictionary of Lexicography*. Psychology Press.

Hayden, B. Y. (2019). Why has evolution not selected for perfect self-control?. Philosophical Transactions of the Royal Society B, 374(1766), 20180139.

Hong, Z., Wang, H., Zada, Z., Gazula, H., Turner, D., Aubrey, B., Niekerken, L., Doyle, W., Devore, S., Dugan, P., Friedman, D., Devinsky, O., Flinker, A., Hasson, U., Nastase, S. A., & Goldstein, A. (2024). Scale matters: Large language models with billions (rather than millions) of parameters better match neural representations of natural language. *BioRxiv*, 2024.06.12.598513. https://doi.org/10.1101/2024.06.12.598513

Hosseini, E. A., Schrimpf, M., Zhang, Y., Bowman, S., Zaslavsky, N., & Fedorenko, E. (2024). Artificial neural network language models predict human brain responses to language even after a developmentally realistic amount of training. Neurobiology of Language, 5(1), 43–63.

Huth, A. G., de Heer, W. A., Griffiths, T. L., Theunissen, F. E., & Gallant, J. L. (2016). Natural speech reveals the semantic maps that tile human cerebral cortex. *Nature*, *532*(7600), 453–458. https://doi.org/10.1038/nature17637

Jamali, M., Grannan, B., Cai, J., Khanna, A. R., Muñoz, W., Caprara, I., Paulk, A. C., Cash, S. S., Fedorenko, E., & Williams, Z. M. (2024). Semantic encoding during language comprehension at single-cell resolution. *Nature*, *631*(8021), 610–616. https://doi.org/10.1038/s41586-024-07643-2

Jazayeri, M., & Ostojic, S. (2021). Interpreting neural computations by examining intrinsic and embedding dimensionality of neural activity. *Current Opinion in Neurobiology*, *70*, 113–120. https://doi.org/https://doi.org/10.1016/j.conb.2021.08.002

Jenkinson, M., Bannister, P., Brady, M., & Smith, S. (2002). Improved Optimization for the Robust and Accurate Linear Registration and Motion Correction of Brain Images. *NeuroImage*, *17*(2), 825–841. https://doi.org/https://doi.org/10.1006/nimg.2002.1132

Jenkinson, M., & Smith, S. (2001). A global optimisation method for robust affine registration of brain images. *Medical Image Analysis*, *5*(2), 143–156. https://doi.org/https://doi.org/10.1016/S1361-8415(01)00036-6

Johnston, W. J., Fine, J. M., Yoo, S. B. M., Ebitz, R. B., & Hayden, B. Y. (2024). Semi-orthogonal subspaces for value mediate a binding and generalization trade-off. *Nature Neuroscience*, *27*(11), 2218–2230. https://doi.org/10.1038/s41593-024-01758-5

Johnston, W. J., Palmer, S. E., & Freedman, D. J. (2020). Nonlinear mixed selectivity supports reliable neural computation. *PLOS Computational Biology*, *16*(2), e1007544-. https://doi.org/10.1371/journal.pcbi.1007544

Joshi, A., Scheinost, D., Okuda, H., Belhachemi, D., Murphy, I., Staib, L. H., & Papademetris, X. (2011). Unified Framework for Development, Deployment and Robust Testing of Neuroimaging Algorithms. *Neuroinformatics*, *9*(1), 69–84. https://doi.org/10.1007/s12021-010-9092-8

Joulin, A., Grave, E., Bojanowski, P., & Mikolov, T. (2016). Bag of Tricks for Efficient Text Classification. *ArXiv*, *abs/1607.01759*. https://api.semanticscholar.org/CorpusID:1210515

Keuleers, E., & Brysbaert, M. (2010). Wuggy: A multilingual pseudoword generator. *Behavior Research Methods*, *42*(3), 627–633. https://doi.org/10.3758/BRM.42.3.627

Kolibius, L. D., Roux, F., Parish, G., Ter Wal, M., Van Der Plas, M., Chelvarajah, R., Sawlani, V., Rollings, D. T., Lang, J. D., Gollwitzer, S., Walther, K., Hopfengärtner, R., Kreiselmeyer, G., Hamer, H., Staresina, B. P., Wimber, M., Bowman, H., & Hanslmayr, S. (2023). Hippocampal neurons code individual episodic memories in humans. *Nature Human Behaviour*, *7*(11), 1968–1979. https://doi.org/10.1038/s41562-023-01706-6

Kommers, C., Ustun, V., Demski, A., & Rosenbloom, P. (2015). *Hierarchical Reasoning with Distributed Vector Representations*. http://cs.fit.edu/mmahoney/compression/textdata.html.

Kumar, S., Sumers, T. R., Yamakoshi, T., Goldstein, A., Hasson, U., Norman, K. A., Griffiths, T. L., Hawkins, R. D., & Nastase, S. A. (2024). *Shared functional specialization in transformer-based language models and the human brain*.

Landauer, T. K., & Dumais, S. T. (1997). A solution to Plato's problem: The latent semantic
analysis theory of acquisition, induction, and representation of knowledge. *Psychological*
Review, *104*(2), 211–240. https://doi.org/10.1037/0033-295X.104.2.211
LeBel, A., Jain, S., & Huth, A. G. (2021). Voxelwise Encoding Models Show That Cerebellar
Language Representations Are Highly Conceptual. *Journal of Neuroscience*, *41*(50),
10341–10355. https://doi.org/10.1523/JNEUROSCI.0118-21.2021
Lerner, Y., Honey, C. J., Silbert, L. J., & Hasson, U. (2011). Topographic mapping of a
hierarchy of temporal receptive windows using a narrated story. Journal of neuroscience,
31(8), 2906-2915.
Li, X., Morgan, P. S., Ashburner, J., Smith, J., & Rorden, C. (2016). The first step for
neuroimaging data analysis: DICOM to NIfTI conversion. *Journal of Neuroscience*
Methods, *264*, 47–56. https://doi.org/https://doi.org/10.1016/j.jneumeth.2016.03.001
Li, Y., Mathis, A., Grewe, B. F., Osterhout, J. A., Ahanonu, B., Schnitzer, M. J., Murthy, V. N.,
& Dulac, C. (2017). Neuronal Representation of Social Information in the Medial
Amygdala of Awake Behaving Mice. *Cell*, *171*(5), 1176-1190.e17.
https://doi.org/https://doi.org/10.1016/j.cell.2017.10.015
Linzen, T., & Baroni, M. (2025). *Syntactic Structure from Deep Learning*. *21*, 43.
https://doi.org/10.1146/annurev-linguistics-032020
Magnotti, J. F., Wang, Z., & Beauchamp, M. S. (2020). RAVE: Comprehensive open-source
software for reproducible analysis and visualization of intracranial EEG data. *NeuroImage*,
223, 117341. https://doi.org/https://doi.org/10.1016/j.neuroimage.2020.117341
Manley, J., Lu, S., Barber, K., Demas, J., Kim, H., Meyer, D., Traub, F. M., & Vaziri, A. (2024).
Simultaneous, cortex-wide dynamics of up to 1 million neurons reveal unbounded scaling
of dimensionality with neuron number. *Neuron*, *112*(10), 1694-1709.e5.
https://doi.org/https://doi.org/10.1016/j.neuron.2024.02.011
Manning, C. D., Clark, K., Hewitt, J., Khandelwal, U., & Levy, O. (2020). Emergent linguistic
structure in artificial neural networks trained by self-supervision. *Proceedings of the*
National Academy of Sciences, *117*(48), 30046–30054.
https://doi.org/10.1073/pnas.1907367117
McClelland, J. L., & Rogers, T. T. (2003). The parallel distributed processing approach to
semantic cognition. *Nature Reviews Neuroscience*, *4*(4), 310–322.
https://doi.org/10.1038/nrn1076
Mejri, M., Amarnath, C., & Chatterjee, A. (2024). *LARS-VSA: A Vector Symbolic Architecture*
For Learning with Abstract Rules. http://arxiv.org/abs/2405.14436
Mikolov, T., Chen, K., Corrado, G. S., & Dean, J. (2013). Efficient Estimation of Word
Representations in Vector Space. *International Conference on Learning Representations*.
https://api.semanticscholar.org/CorpusID:5959482
Mikolov, T., Sutskever, I., Chen, K., Corrado, G., & Dean, J. (2013). *Distributed*
Representations of Words and Phrases and their Compositionality.
http://arxiv.org/abs/1310.4546
Mitchell, J., & Lapata, M. (2008). *Vector-based Models of Semantic Composition*.
O'Keefe, J., & Dostrovsky, J. (1971). The hippocampus as a spatial map. Preliminary evidence
from unit activity in the freely-moving rat. *Brain Research*, *34*(1), 171–175.
https://doi.org/https://doi.org/10.1016/0006-8993(71)90358-1
Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z.,
Gimelshein, N., Antiga, L., Desmaison, A., Köpf, A., Yang, E., DeVito, Z., Raison, M.,

Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., … Chintala, S. (2019). *PyTorch: An*
Imperative Style, High-Performance Deep Learning Library.
http://arxiv.org/abs/1912.01703
Pavlick, E. (2025). *Semantic Structure in Deep Learning Keywords*.
https://doi.org/10.1146/annurev-linguistics-031120
Pennington, J., Socher, R., & Manning, C. D. (2014). *GloVe: Global Vectors for Word*
Representation. http://nlp.
Peters, M. E., Neumann, M., Gardner, M., Clark, C., Lee, K., & Zettlemoyer, L. (2018). *Deep*
contextualized word representations. http://allennlp.org/elmo
Piantadosi, S. T., Muller, D. C. Y., Rule, J. S., Kaushik, K., Gorenstein, M., Leib, E. R., &
Sanford, E. (2024). Why concepts are (probably) vectors. In *Trends in Cognitive Sciences*
(Vol. 28, Issue 9, pp. 844–856). Elsevier Ltd. https://doi.org/10.1016/j.tics.2024.06.011
Poli, D., Thiagarajan, S., Demarse, T. B., Wheeler, B. C., & Brewer, G. J. (2017). Sparse and
specific coding during information transmission between co-cultured dentate gyrus and
CA3 hippocampal networks. *Frontiers in Neural Circuits*, *11*.
https://doi.org/10.3389/fncir.2017.00013
Prince, J. S., Alvarez, G. A., & Konkle, T. (2025). Contrastive learning explains the emergence
and function of visual category-selective regions. *Science Advances*, *10*(39), eadl1776.
https://doi.org/10.1126/sciadv.adl1776
Pulvermüller, F. (1999a). *. Words in the brain: Where? Why? How?* http://nbn-
resolving.de/urn:nbn:de:bsz:352-opus-63798
Pulvermüller, F. (1999b). Words in the brain's language. *Behavioral and Brain Sciences*, *22*(2),
253–279. https://doi.org/DOI: 10.1017/S0140525X9900182X
Quian Quiroga, R. (2023). An integrative view of human hippocampal function: Differences
with other species and capacity considerations. *Hippocampus*, *33*(5), 616–634.
https://doi.org/https://doi.org/10.1002/hipo.23527
Quian Quiroga, R., Kraskov, A., Koch, C., & Fried, I. (2009). Explicit Encoding of Multimodal
Percepts by Single Neurons in the Human Brain. *Current Biology*, *19*(15), 1308–1313.
https://doi.org/10.1016/j.cub.2009.06.060
Quiroga, R. Q., Reddy, L., Kreiman, G., Koch, C., & Fried, I. (2005). Invariant visual
representation by single neurons in the human brain. *Nature*, *435*(7045), 1102–1107.
https://doi.org/10.1038/nature03687
Radford, A., Kim, J. W., Hallacy, C., Ramesh, A., Goh, G., Agarwal, S., Sastry, G., Askell, A.,
Mishkin, P., Clark, J., Krueger, G., & Sutskever, I. (2021). Learning Transferable Visual
Models From Natural Language Supervision. *CoRR*, *abs/2103.0*.
https://arxiv.org/abs/2103.00020
Radford, A., Wu, J., Child, R., Luan, D., Amodei, D., & Sutskever, I. (2019). *Language Models*
are Unsupervised Multitask Learners. https://github.com/codelucas/newspaper
Rey, H. G., Panagiotaropoulos, T. I., Gutierrez, L., Chaure, F. J., Nasimbera, A., Cordisco, S.,
Nishida, F., Valentin, A., Alarcon, G., Richardson, M. P., Kochen, S., & Quian Quiroga, R.
(2025). Lack of context modulation in human single neuron responses in the medial
temporal lobe. *Cell Reports*, *44*(1). https://doi.org/10.1016/j.celrep.2024.115218
Rogers, T. T., & Mcclelland, J. L. (2004). *Semantic Cognition: A Parallel Distributed*
Processing Approach.

Rolls, E. T., & Tovee, M. J. (1995). Sparseness of the neuronal representation of stimuli in the primate temporal visual cortex. *Journal of Neurophysiology*, *73*(2), 713–726. https://doi.org/10.1152/jn.1995.73.2.713

Rousseeuw, P. J. (1987). Silhouettes: A graphical aid to the interpretation and validation of cluster analysis. *Journal of Computational and Applied Mathematics*, *20*, 53–65. https://doi.org/https://doi.org/10.1016/0377-0427(87)90125-7

Senel, L. K., Utlu, I., Yucesoy, V., Koc, A., & Cukur, T. (2017). *Semantic Structure and Interpretability of Word Embeddings*. https://doi.org/10.1109/TASLP.2018.2837384

Squire, L. R., & Zola-Morgan, S. (1991). The Medial Temporal Lobe Memory System. *Science*, *253*(5026), 1380–1386. https://doi.org/10.1126/science.1896849

Tang, J., LeBel, A., Jain, S., & Huth, A. G. (2023). Semantic reconstruction of continuous language from non-invasive brain recordings. *Nature Neuroscience*, *26*(5), 858–866. https://doi.org/10.1038/s41593-023-01304-9

Tian, Y., Krishnan, D., & Isola, P. (2020). Contrastive Multiview Coding. In A. Vedaldi, H. Bischof, T. Brox, & J.-M. Frahm (Eds.), *Computer Vision – ECCV 2020* (pp. 776–794). Springer International Publishing.

Tuckute, G., Sathe, A., Srikant, S., Taliaferro, M., Wang, M., Schrimpf, M., ... & Fedorenko, E. (2024). Driving and suppressing the human language network using large language models. Nature Human Behaviour, 8(3), 544-561.

Tulving, E. (2002). Episodic Memory: From Mind to Brain. *Annual Review of Psychology*, *53*(Volume 53, 2002), 1–25. https://doi.org/https://doi.org/10.1146/annurev.psych.53.100901.135114

Tversky, A. (1977). Features of similarity. *Psychological Review*, *84*(4), 327–352. https://doi.org/10.1037/0033-295X.84.4.327

Vaswani, A., Brain, G., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., & Polosukhin, I. (2017). *Attention Is All You Need*.

Vinje, W. E., & Gallant, J. L. (2000). Sparse coding and decorrelation in primary visual cortex during natural vision. *Science (New York, N.Y.)*, *287*(5456), 1273–1276. https://doi.org/10.1126/science.287.5456.1273

Wolf, T., Debut, L., Sanh, V., Chaumond, J., Delangue, C., Moi, A., Cistac, P., Rault, T., Louf, R., Funtowicz, M., Davison, J., Shleifer, S., Von Platen, P., Ma, C., Jernite, Y., Plu, J., Xu, C., Le Scao, T., Gugger, S., … Rush, A. M. (2020). *Transformers: State-of-the-Art Natural Language Processing*. https://github.com/huggingface/

Xiao, J., Adkinson, J. A., Allawala, A. B., Banks, G., Bartoli, E., Fan, X., Mocchi, M., Pascuzzi, B., Pulapaka, S., Franch, M. C., Mathew, S. J., Mathura, R. K., Myers, J., Pirtle, V., Provenza, N. R., Shofty, B., Watrous, A. J., Pitkow, X., Goodman, W. K., … Hayden, B. Y. (2024). *Insula uses overlapping codes for emotion in self and others*. https://doi.org/10.1101/2024.06.04.596966

Xiao, J., Adkinson, J. A., Myers, J., Allawala, A. B., Mathura, R. K., Pirtle, V., Najera, R., Provenza, N. R., Bartoli, E., Watrous, A. J., Oswalt, D., Gadot, R., Anand, A., Shofty, B., Mathew, S. J., Goodman, W. K., Pouratian, N., Pitkow, X., Bijanki, K. R., … Sheth, S. A. (2024). Beta activity in human anterior cingulate cortex mediates reward biases. *Nature Communications*, *15*(1), 5528. https://doi.org/10.1038/s41467-024-49600-7

Yang, A. I., Wang, X., Doyle, W. K., Halgren, E., Carlson, C., Belcher, T. L., Cash, S. S., Devinsky, O., & Thesen, T. (2012). Localization of dense intracranial electrode arrays using

magnetic resonance imaging. *NeuroImage*, *63*(1), 157–165.
https://doi.org/https://doi.org/10.1016/j.neuroimage.2012.06.039
Zada, Z., Goldstein, A., Michelmann, S., Simony, E., Price, A., Hasenfratz, L., Barham, E.,
Zadbood, A., Doyle, W., Friedman, D., Dugan, P., Melloni, L., Devore, S., Flinker, A.,
Devinsky, O., Nastase, S. A., & Hasson, U. (2023). A shared linguistic space for
transmitting our thoughts from brain to brain in natural conversations. *BioRxiv*,
2023.06.27.546708. https://doi.org/10.1101/2023.06.27.546708
Zada, Z., Goldstein, A., Michelmann, S., Simony, E., Price, A., Hasenfratz, L., Barham, E.,
Zadbood, A., Doyle, W., Friedman, D., Dugan, P., Melloni, L., Devore, S., Flinker, A.,
Devinsky, O., Nastase, S. A., & Hasson, U. (2024). A shared model-based linguistic space
for transmitting our thoughts from brain to brain in natural conversations. *Neuron*, *112*(18),
3211-3222.e5. https://doi.org/10.1016/j.neuron.2024.06.025
Zeng, T., Li, X., & Si, B. (2019). *Learning Sparse Spatial Codes for Cognitive Mapping Inspired
by Entorhinal-Hippocampal Neurocircuit*. http://arxiv.org/abs/1910.04590
Zipf, G. K. (1945). The Meaning-Frequency Relationship of Words. *The Journal of General
Psychology*, *33*(2), 251–256. https://doi.org/10.1080/00221309.1945.10544509