D-LMBmapX: Generalised Deep Learning Pipeline for 5D Whole-brain Circuitry Profiling

Zhongyu Li[1,2,3†*], Peiqi Li[3†], Hangzhen Pan[3†], Annabel M.J. Adams[1†], Zuqi Huang[3], Yaoyu Su[3], He Liu[3], Jinjiang Li[3], Baoming Zhong[3], Yuqin Su[3], Liam Bray[1], Robyn N. Sturgess[1], Chen Li[3], Jihua Zhu[3], Dingwen Zhang[4], Shaoting Zhang[2], Jing Ren[1*]

1. Neurobiology Division, MRC Laboratory of Molecular Biology, Francis Crick Avenue, Cambridge, CB2 0QH, United Kingdom
2. School of Computer Science, Shanghai Jiao Tong University, Shanghai, China
3. School of Software Engineering, Xi'an Jiaotong University, Xi'an, China
4. Hefei Comprehensive National Science Center, Hefei, China
†These authors contributed equally to this work
*Correspondence: Jing Ren (jren@mrc-lmb.cam.ac.uk), Zhongyu Li (zhongyuli@sjtu.edu.cn)

SUMMARY

Understanding whole-brain circuitry development is essential for uncovering the origins of disorders linked to abnormal neural wiring, yet progress has been limited by the lack of tools for accurate, comprehensive analysis. Brain development is highly dynamic and region-specific, with pronounced inter-individual variability during early stages, and no existing method achieves whole-brain profiling at arbitrary stages. The rapidly changing morphology of developing axons further complicates segmentation. Here, we present D-LMBmapX, a deep learning pipeline for automated whole-brain circuitry profiling across postnatal development. D-LMBmapX constructs sample-inferred atlases from flanking anchor stages, enabling accurate registration at any time point. By developing a foundation model for generalised axon and soma segmentation, it supports quantitative mesoscale developmental connectomics, demonstrated through spatial-temporal profiling of catecholaminergic projections. D-LMBmapX also enables robust cross-modality and cross-dimensional registration, including precise alignment of single 2D slices to 3D references, and offers generalizable strategies for 5D analysis of diverse biomedical spatial datasets.

INTRODUCTION

In-depth knowledge of neuronal connections is fundamental to understanding how the brain is functionally organised. In the past decades, great success has been achieved in mapping mammalian neural circuits, particularly in mesoscale connectomics[1–5] . Related resources, including high-resolution reference brain atlases, have rapidly expanded[6–10]. The integration of tissue-clearing techniques with light-sheet fluorescence microscopy (LSFM) has opened up remarkable opportunities for high-throughput, 3D mesoscale connectivity mapping of the entire brain[11–16]. As the proliferation of these large-scale datasets created a critical demand for corresponding analysis tools, we developed D-LMBmap, which employs deep-learning algorithms for whole-brain circuitry profiling, addressing automated axon segmentation, brain region segmentation and whole-brain 3D registration in a single workflow[17].

Crucially, mapping neuronal connections during development reveals how adult networks are established and provides essential anatomical context for disorders that arise from abnormal wiring[18,19]. Recent whole-brain connectomic analysis of adult and larval Drosophila brains revealed that around 0.5% of neurons have developmental wiring defects, leading to the hypothesis that such miswiring might contribute to individuality and

susceptibility to mental health disorders[20]. However, mapping connectivity in developing mammalian brains presents distinct challenges compared to adult brains. In adults, a single time point can serve as a stable reference for circuit architecture. In contrast, developmental connectomics must capture rapid and continuous changes throughout maturation, requiring spatiotemporal mapping across multiple developmental stages and resulting in a workload increase of more than an order of magnitude.

In postnatal mouse brains, structural stabilisation is far from reached before P28[21]. During this period, axonal fibres exhibit diverse and stage-specific morphologies, often differing significantly from those seen in the adult brain[22]. Brain development is highly dynamic and region-specific in the early postnatal period, with each system maturing on its own timeline. For example, the somatosensory cortex receives thalamocortical afferents around P0, and by P3–P4, the critical window for barrel plasticity is largely closed, with barrel hollows and septa clearly defined by P7. In the auditory system, cochlear and brainstem maturation enables the onset of hearing around P10–P12. In the visual system, the eyes open around P12–P14, with functional visual responses beginning immediately thereafter[23]. Other circuits, such as hypothalamic systems, also undergo rapid morphological and synaptic changes during the first two postnatal weeks[24]. To accurately capture such circuit dynamics, both whole-brain registration and axon segmentation must be performed at high temporal resolution—ideally at arbitrary developmental days.

Adding to this complexity is the pronounced inter-individual variability during development. Brain size, structural organisation, and neuronal morphology vary considerably more in developing brains than in adult brains. This variability is especially evident during early postnatal stages, when rapid growth and small differences in developmental timing can produce noticeable anatomical differences, even among littermates. Environmental factors—such as nutrition, maternal care, and minor genetic variation—further amplify these differences.

Current approaches would require repeated atlas construction, whole-brain registration, and axon segmentation on a near-daily basis, involving extensive manual input. This makes the workload impractical and may still result in reduced accuracy due to developmental variability. Moreover, although 3D whole-brain imaging is increasingly available, much circuitry profiling still relies on two-dimensional data, including serial-section methods[10,25–28], community resources such as the Allen Brain Atlas[29], and conventional histology. Unlocking the full value of these datasets requires registering 2D information into a 3D framework to enable integration and comparison across modalities.

To address these challenges, we developed D-LMBmapX, a deep learning pipeline for automated whole-brain circuitry profiling at any postnatal stage, offering accurate, efficient analysis through generalised modules adapted to individual samples. D-LMBmapX introduces dynamic 4D and 5D capabilities by incorporating developmental time and multiplexed signal integration. We validated our methods by profiling whole-brain tyrosine hydroxylase (TH)-positive projections and revealed the region-specific and dynamic pattern of TH+ innervations throughout postnatal development. We also achieved robust and automated cross-modality and cross-dimensional registration, demonstrated by aligning genetically defined neuronal populations from the Allen Institute's developmental ISH datasets[29] with our 4D TH+ soma maps, refining neuron subtype classification using multiple markers within a unified 5D anatomical-molecular framework. Beyond mouse brains, D-LMBmapX also provides a generalizable strategy for cross-age, cross-modality, and cross-dimensional multiplexed registration across diverse biomedical datasets.

RESULTS

A Comprehensive Framework for Developmental Neuronal Circuits Quantification

D-LMBmapX comprises interconnected modules and begins with data input and culminates in automated axon/soma quantification with visualisation in a 3D sample-infered atlas at any postnatal stage (5D, Figure 1). Each core component is powered by advanced deep neural networks (DNNs), and can operate as a stand-alone module or in combination to enable automated 5D whole-brain circuitry profiling, supporting reliable comparison of datasets across platforms.

Using a novel registration approach, we first constructed high-resolution average template brains at seven anchor postnatal stages (P0, P4, P7, P10, P14, P21, and P28). Hierarchical brain structures were then delineated by sequentially registering the Allen Mouse Brain Common Coordinate Framework (CCFv3)[7] to these templates. To address stages not covered by the seven anchor atlases, we developed a sample-inferred atlas construction strategy. This approach adaptively delineates brain regions by inferring an atlas from flanking anchor stages using even a single sample, enabling accurate whole-brain registration at any postnatal time point (Figure 1A). To achieve whole-brain axon and soma profiling throughout development, we developed a generalised foundation model CircuitFound for automated segmentation, capable of accurately segmenting axons and somata despite morphological differences across stages. Coupled with the whole-brain registration model, this allows D-LMBmapX to accept input from any postnatal brain and output region-specific quantification and 3D visualisation of axon and soma distributions, registered to the appropriate developmental atlas (Figure 1B). This cross-dimensional and cross-modality module supports end-to-end quantitative analysis of 2D histological sections via similarity-driven 2D-to-3D spatial alignment and registration—estimating each section's pose, refining with deformable alignment to correct tissue distortion, and mapping quantitative signals into atlas coordinates for region-wise analysis (Figure 1C).

D-LMBmapX integrates these components into a user-friendly software platform that is open-source, supports customisation through high-level application programming interfaces (APIs), and includes a graphical interface for selecting and executing pretrained deep learning models (Figure 1D).

Multi-Constraint Non-Rigid Pipeline for 4D Brain Atlas Construction

To achieve whole-brain registration across any postnatal stage, we first constructed high-resolution 3D brain atlases for seven anchor stages. We collected LSFM brain images from P0 to P28, and used at least 30 half-brains per stage to construct each average template. To minimise variability from sample preparation and imaging, we applied a series of image pre-processing strategies, including N4 bias field correction[30], rescaling intensity, and 3D adaptive histogram equalisation[31]. For each stage, we created an initial reference template by aligning all brains to a common centre and computing the voxel-wise average (Figure 2A). While we incorporated the conventional atlas-building pipeline[32,33]—which includes rigid, affine, and B-spline registration—we further refined the templates using a custom 2.5D non-rigid registration approach. It uses a U-Net-based neural network to perform 2D registrations in both coronal and horizontal planes. We then assembled the 3D registration results from each view and computed a 3D consistency loss to guide iterative refinement. This process allows each brain to update the template within a shared deformation space, resulting in a high-resolution, fine-grained reference template (Figure 2B).

With fine-grained brain templates established for each developmental stage, our next challenge was to delineate hundreds of brain regions for each one. Manual annotation at this scale is extremely labour-intensive, so we developed an automated pipeline for atlas mapping

and construction using cross-stage and cross-modality registration (Figure 2C). We began by registering the adult mouse brain atlas, Allen CCFv3, to our P28 brain template. This process combined brain style transfer, multi-constraint registration[17], and our 2.5D non-rigid registration approach. Specifically, we developed diffusion-based brain style transfer to convert the Allen CCFv3 images which are in STPT modality into the LSFM modality. We created multiple brain structure constraints by automatically annotated six major brain regions along with manual annotated eight smaller regions (Figure S1A). The multi-constraint strategy alleviated the alignment shifting and registration error accumulation problem during the propagation of brain region delineation (Figure S1B). Following cross-modality and cross-stage alignment from Allen CCFv3 to the P28 template, the pipeline automatically delineated hundreds of brain regions. We then propagated these annotations to earlier stages through sequential registration—P28 to P21, P21 to P14, and so on—ultimately constructing a complete atlas series across all seven postnatal stages (Figure 2D, Figure S2).

To evaluate the effectiveness of our 4D brain atlas construction pipeline and assess the accuracy of the resulting D-LMBmapX atlas, we conducted a series of comparative analyses against established methods and reference atlases. We first benchmarked our whole-brain registration pipeline against ANTs[34], a widely used non-rigid registration method which was also adopted in constructing the DevCCF atlas[32]. Region-wise Dice scores were computed across the entire brain following registration to evaluate anatomical alignment accuracy. For a fair comparison, we incorporated the same pre-processing into both pipelines. Our results demonstrate that D-LMBmapX consistently achieves higher Dice scores across multiple brain regions, indicating the superior performance of our 2.5D non-rigid registration approach (Figure S1C). We then assessed the accuracy of atlases constructed using D-LMBmapX by comparing them with two leading developmental brain atlases: DevCCF[32] and DeMBA[35]. Because these atlases were originally built using different registration strategies, we re-registered independent brain samples to each atlas using the same D-LMBmapX registration pipeline to ensure a fair comparison. Since DevCCF and DeMBA[35] do not cover all the postnatal stages available in D-LMBmapX, we restricted the evaluation to the stages present in all three atlases. For DeMBA[35], only the authentic (real-sample) atlases were included in the analysis, excluding their interpolated (synthetic) ones. Region-wise Dice scores were then used to assess anatomical alignment, with D-LMBmapX showing consistently higher anatomical correspondence (Figure 2E, Figure S3).

Together, these results validate the effectiveness of our multi-constraint non-rigid pipeline for whole-brain registration and demonstrate that D-LMBmapX produces a high-accuracy 4D brain atlas capable of capturing developmental dynamics with improved anatomical precision over existing resources.

Next, we characterised developmental volume changes at the whole-brain and regional levels across seven postnatal stages (Figure 2F and G, Table S6). At the whole-brain level, total volume increased steadily, with the fastest growth between P0 and P7 (Figure 2G). At the regional level, 276 regions grouped into 13 major brain areas showed distinct and dynamic developmental trajectories (Figure 2F). The cortical and hippocampal areas, striatum, and cerebellum broadly exhibited monotonic increases, although cortical subregions varied: the agranular insular area (AI) plateaued at P7, the primary motor cortex (MOp) at P14, and the orbital area (ORB) at P21 (Figure 2G). By contrast, thalamic regions peaked around P14, while other major brain groups displayed more heterogeneous, stage-specific patterns of change (Figure 2F).

These findings underscore that brain maturation is both nonlinear and regionally asynchronous, with different brain areas undergoing distinct developmental trajectories and

reaching critical milestones at varying postnatal timepoints—some of which may fall outside
the seven anchor stages profiled here. This biological complexity necessitates whole-brain
registration at arbitrary postnatal days to ensure anatomical accuracy. However, the
interpolation-based strategy used in DeMBA[35], which generates intermediate-stage atlases
by assuming smooth and uniform brain development between flanking timepoints, does not
account for these region-specific dynamics. As a result, such interpolated atlases may
introduce anatomical inaccuracies, particularly during periods of rapid or heterogeneous
development.

Sample-inferred Whole-brain Registration at Any Time Point

To enable accurate whole-brain registration at any postnatal stage, we developed a
pipeline that constructs a sample-inferred atlas by integrating the brain sample under study
with atlases from its adjacent developmental stages (Figure 3A). To demonstrate the pipeline,
we use a P10 brain as an example, constructing a sample-inferred P10 atlas from its flanking
stages (P7 and P14). First, the P7 and P14 atlases were registered to the P10 brain image,
generating two deformed atlases in a P10-like space while preserving their original
anatomical labels. These P10-like atlases were then voxel-wise averaged to form an initial
reference template that integrates anatomical features from both flanking stages. Following
the atlas construction pipeline illustrated in Figure 2A, the two P10-like atlases were iteratively
registered to the initial average template, producing a refined sample-inferred P10 atlas with
improved anatomical consistency (Figure S4A). Next, to delineate the brain sample, the
original P10 brain was registered to this sample-inferred atlas, and all anatomical labels were
transferred. To further enhance registration reliability and general applicability, we designed
a mutual learning–based registration framework that automatically identified reliable
anatomical constraints. Specifically, brain regions showing strong spatial correspondence
between the two sources (P10-like P7 and P10-like P14 atlases) were automatically selected
and used as constraints to guide registration from the original P10 brain to the sample-
inferred atlas. Here, two 2.5D registration models were mutually trained based on constraints
from the intersection and union of selected brain regions, respectively (Figure S4B).

This strategy leveraged reliably aligned brain regions as spatial constraints to boost
registration performance across the whole brain (Figure S4C). Importantly, all brain-region
constraints—including both major and small regions—were obtained automatically, without
any manual annotation. To assess similarity between the sample-inferred and authentic P10
atlases (Figure 3B), P10 brain samples were registered to each, as well as to the flanking-
stage atlases (P7 and P14). Dice score analysis revealed no significant differences in
registration accuracy between the sample-inferred and authentic P10 atlases for either major
or small brain regions, whereas registration to P7 or P14 yielded substantially lower accuracy
(Figure 3C). Comparable results were obtained when P7 was used as the inferred stage
(Figure S5A & B). Next, we compared the registration performance of a P10 brain sample
aligned to the interpolated P10 atlas from DeMBA versus our sample-inferred P10 atlas. Dice
score analysis showed that registration to our atlas yielded superior accuracy both globally
and across individual brain regions (Figure 3D & E).

Collectively, these results demonstrate that our sample-inferred whole-brain registration
pipeline enables accurate registration at any postnatal day. The resulting sample-inferred
atlases achieve registration accuracy comparable to authentic atlases and substantially
exceed that of interpolated alternatives.

Generalised Pipeline for Sample-Inferred 4D Atlas Generation and Registration

Our sample-inferred registration pipeline generalises beyond the developing mouse brain and

supports 4D analysis of human fetal and infant datasets. For both a 29-week fetal brain and
a 7-month infant brain, we generated a sample-inferred atlas by integrating the sample itself
with its flanking-stage atlases (e.g., 23- and 35-week, or 4- and 10-month). Each brain was
then registered to its own sample-inferred atlas, the corresponding authentic atlas, and the
flanking-stage atlases. Dice score analysis showed that registration to the sample-inferred
atlas achieved accuracy comparable to the authentic atlas and significantly exceeded that of
flanking-stage registration (Figure 3F & Figure S6).

5D Whole-brain Circuitry Profiling by a Generalised Foundation Model

Whole-brain circuitry profiling requires effective segmentation of neuronal structures (e.g.,
axon and soma) by deep learning models trained on abundant, well-annotated samples. To
eliminate the labour-intensive manual annotation of axons, previously we developed
automated annotation and data augmentation strategies[17]. However, neuronal structures,
especially axonal projections, undergo significant morphological changes throughout
development. This morphological diversity poses a major challenge for robust circuitry
profiling across stages. Segmentation modules trained on a single stage often fail to
generalise, and training new models for every stage is too costly in time and resources. To
address this challenge, we developed CircuitFound, a generalised foundation model
integrated into D-LMBmapX for axon and soma segmentation that adapts effectively to
diverse neuronal morphologies and brain images (Figure 4).

The construction of CircuitFound contained three steps: self-supervised pre-training,
automated sample annotation, and fine-tuning. More than 100,000 3D cubes randomly
cropped from anti-TH stained LSFM brain samples across seven postnatal stages are used
for self-supervised pre-training by a 3D masked autoencoder (MAE). A Vision Transformer
(ViT)[36] encoder embeds the unmasked patches, and unlike conventional MAEs that rely
solely on pixel-level reconstruction[37], we introduced a second decoder branch to reconstruct
3D Histograms of Oriented Gradients (HOG)[38] (Figure 4A). This dual-decoder design enables
the model to capture both general image features and gradient-based structural cues,
allowing it to better represent the long-range, tree-like morphology of axons critical for
accurate segmentation. Ablation study results support the effectiveness of our strategies in
pre-training (Figure S7A).

Many neural systems, such as the dopaminergic system, have somata distributed across
multiple brain regions rather than confined to a single nucleus. To accurately reconstruct
circuitry, segmentation must therefore distinguish somatic signals from axonal projections, as
conflating the two can lead to misinterpretation of connectivity. Thus, CircuitFound is
designed to characterise both axons and somata, and after pre-training, both are annotated
automatically. We used the previously reported method in D-LMBmap for axon annotation,
and developed a new pipeline for 3D soma annotation based on the segment anything model
(SAM)[39]. In this pipeline, the only manual input is a point prompt for each soma in a few 2D
slices; SAM then automatically segments the somata from these prompts. To further separate
adhered somata, we incorporated a watershed algorithm based on distance maps (Figure
4B). This lightweight strategy enables efficient and extensible annotation for diverse axon
and soma segmentation tasks. Lastly, we fine-tuned the pre-trained foundation model with
annotated cubes. While directly fine-tuning the ViT encoder is inefficient and data-hungry due
to its large number of parameters, we addressed this by introducing a parallel convolutional
neural network (CNN). At each level, the ViT encoder output is fused with the corresponding
CNN output, enabling faster convergence and improved accuracy (Figure 4C). By paralleling
ViT and CNN, our framework achieves robust whole-brain prediction of axons and somata
with only a small number of annotated samples.

Equipped with the CircuitFound module, D-LMBmapX delivers robust performance in generalisation for axon and soma segmentation. To demonstrate its effectiveness in whole-brain circuitry profiling across brain regions and developmental stages, we applied it to characterise catecholaminergic circuits over seven postnatal stages. Brains from P0, P4, P7, P10, P14, P21, and P28 mice were processed with whole-mount immunohistochemistry, iDISCO tissue clearing, and LSFM imaging. We used tyrosine hydroxylase (TH) immunostaining to label dopaminergic and noradrenergic neurons and their axonal projections. D-LMBmapX successfully segmented these labelled structures, registered each brain to its corresponding developmental stage atlas, and computed the density map of TH+ axons and somata for each stage (Figure 4D, Figure S8, Video S1-3). In comparison with traditional deep models such as TrailMap[12], D-LMBmap[40] and ACE[41], D-LMBmapX doesn't have to do sample training for the individual stage. Moreover, D-LMBmapX achieves superior performance, especially when using a smaller number of annotated samples (Figure S7B). For axon segmentation, D-LMBmapX consistently outperformed TrailMap in ClDice, ClPrecision, ClRecall and Dice scores across different brain regions and whole brain on average at any developmental stages (Figure 4E and Figure S7C). For soma segmentation, D-LMBmapX significantly outperformed ACE, which is the most advanced pipeline for mapping neuronal cell bodies, in Dice and Precision scores (Figure 4F).

Using D-LMBmapX, we quantified TH$^+$ axon densities across more than 260 brain regions spanning 13 major brain areas and generated a 4D atlas of postnatal axonal innervation (Figure 4G, Table S6, Video S2&3). This analysis revealed highly heterogeneous, region-specific patterns of TH$^+$ innervation. In the isocortex and olfactory areas, axonal density broadly increased over time, whereas other regions displayed pronounced spatiotemporal dynamics (Figure 4G–H). These included sharp increases at specific developmental stages (e.g., NTS), transient peaks (e.g., PVH and BST), stable levels from birth, or even a progressive decline (Figure 4H, Figure S9). To our knowledge, this is the first 4D whole-brain map of TH$^+$ axonal innervation. Notably, decreases in axonal density could not be fully explained by regional volume changes, suggesting a contribution from axonal pruning (Figure S9).

Generalized Cross-dimensional and Cross-modality Registration

Although 3D whole-brain imaging is increasingly adopted, much of the available circuitry profiling data remains two-dimensional. This includes advanced imaging techniques that acquire data in serial sections, major community resources such as the Allen Brain Atlas, and the widespread use of 2D histology in many neuroscience laboratories. To ensure the broader neuroscience community can fully benefit from diverse connectivity mapping resources and enable cross-platform data comparison, we developed cross-dimensional and cross-modality registration within D-LMBmapX.

The cross-dimensional and cross-modality registration pipeline includes slice pre-processing, cross-modality style transfer, spatial alignment to identify the best-matching section in a 3D reference atlas, and final 2D-to-3D registration (Figure 5A). Previously, we developed the first brain-specific style transfer method based on CycleGAN, which learns an unsupervised mapping between imaging modalities[17]. However, this approach requires retraining the model from scratch whenever a new modality is introduced. To have more generalized and consistent cross-modality style transfer, we developed a new solution based on the diffusion model, which can transfer source brain image modality to any given target style (Figure S10A). During training, only target brain images are used. Each image is gradually degraded by adding noise until it becomes indistinguishable from random noise. The model then learns to reconstruct the original target image through a denoising process.

To improve stability and accuracy, we incorporated two modules: (i) brain edge constraints,
which ensure structural boundaries in the reconstructed image remain consistent with the
input, and (ii) a denoising U-Net, which segments major brain regions (BS, CB, CTX, HPF,
CP, OLF) to preserve regional boundaries. In the prediction step, source brains from other
modalities are transformed into the target style using the trained model, with structural edges
from the source guiding reconstruction to maintain anatomical detail. This diffusion-based
approach offers two major advantages: it preserves edges and fine details across modalities,
and it requires training only once for a given target modality, independent of source
modalities. Benchmark comparisons show that D-LMBmapX achieves superior performance
in brain style transfer, including transformations from LSFM to STPT (Allen CCFv3) and from
Allen histological 2D slices to our developmental LSFM brain atlas (Figure S10B & C).

After preprocessing and style transfer to match the target 3D brain modality, each 2D
slice was automatically localised and registered within the 3D atlas using our newly
developed modules (Figure 5B). Landmarks from both the 2D slice and each orthogonal
section of the 3D atlas (e.g., sagittal view) were automatically detected using the Harris corner
detector[42] and described with Scale-Invariant Feature Transform (SIFT)[43] features. The top-
K most similar orthogonal sections were identified based on the number of matched
landmarks, and the Random Sample Consensus (RANSAC) algorithm[44] was applied to
estimate the optimal initial rotation aligning the 2D slice to these candidate sections. To refine
alignment, D-LMBmapX further performed fine-grained searches around the estimated
orientation by varying yaw and roll angles, selecting the best-matched section according to
mutual information similarity. To assess localisation accuracy, we randomly perturbed 2D
slices with controlled rotations and translations and then aligned them to the 3D atlas using
D-LMBmapX. The resulting low errors across yaw, roll, and translation confirmed the
robustness and precision of our pipeline for reliable 2D-to-3D registration (Figure 5C).

To demonstrate that D-LMBmapX enables accurate 2D-to-3D whole-brain registration for
systematic circuitry profiling, we characterised and registered marker gene expression
related to catecholaminergic systems. We first compared Th^+ soma density between Allen
2D ISH slices and anti-TH–stained 3D LSFM brains at P4, P14, and P28 (Figure 5D, Figure
S11). Across 16 brain regions containing dopaminergic or noradrenergic neurons, normalised
region-wise TH^+ soma densities were well aligned between the two datasets (Figure 5E).
Next, to further refine cell-type characterisation by integrating 2D molecular signatures with
3D anatomical organisation, we profiled and registered individual Allen 2D ISH slices
encompassing both the ventral tegmental area (VTA) and locus coeruleus (LC) for three gene
markers—*Th*, *Slc6a2*, and *Slc6a3*—at P4, P14, and P28. Heatmaps of soma density
generated by D-LMBmapX accurately localised dopaminergic neurons in the VTA (Th^+,
$Slc6a2^-$, $Slc6a3^+$) and noradrenergic neurons in the LC (Th^+, $Slc6a2^+$, $Slc6a3^-$)[45] (Figure 5F,
Figure S12). Together, these results show that D-LMBmapX can accurately place single 2D
histological sections within a 3D atlas, robustly matching them despite differences in imaging
position, rotation, or deformation, and even without continuous serial sections. To our
knowledge, this represents the first workflow to achieve automated cross-dimensional and
cross-modality whole-brain registration, providing a generalised framework for integrating
diverse spatial biomedical images.

DISCUSSION

The rapid rise of mesoscale connectomics, coupled with advances in machine learning, has
accelerated the shift toward registering circuitry and multi-omic data to standardised brain
atlases. However, compared to the growing wealth of tools and resources available for the
adult brain[46–51], equivalent resources for developing brains remain scarce. Here, we present

D-LMBmapX, an end-to-end deep-learning system for 5D mapping of mouse brain circuitry across postnatal development. D-LMBmapX includes automated tools for whole-brain registration and soma/axon segmentation across all postnatal stages, enabling efficient and robust quantitative analysis of developmental connectomics. It further offers generalised strategies for segmentation and registration across temporal, spatial, and modality domains, supporting scalable and versatile applications to a wide range of biomedical datasets.

We developed a custom 2.5D non-rigid registration strategy that enables accurate whole-brain registration between individual samples and 3D references, thereby facilitating efficient construction of anchor-stage atlases. Unlike typical 3D deep learning–based approaches, our 2.5D registration approach achieves accurate, high-resolution 3D registration without incurring heavy computational costs. This strategy is readily scalable to higher-resolution images, enabling broader applicability across diverse datasets. With it embedded in D-LMBmapX, we constructed seven anchor-stage atlases and quantified volumetric changes in 267 brain regions across postnatal development. This revealed highly diverse and dynamic growth patterns among regions (Fig. 2), underscoring the need for a method that can robustly register developing brains at any time point to support a wide range of neurodevelopmental studies.

However, achieving whole-brain registration at every developmental stage requires repeated atlas construction, involving extensive sample collection and meticulous segmentation. Beyond the heavy workload, early postnatal stages introduce substantial variability—even among samples of the same age—making accurate registration especially challenging and prone to error. As a workaround, existing strategies[35] often rely on interpolated atlases to fill unrepresented time points, but the underlying assumption of smooth, linear brain maturation introduces significant limitations and undermines the original goal. Brain development is inherently nonlinear and region-specific, with distinct circuits maturing on different timelines and undergoing rapid morphological changes during critical periods. Linearly transforming and averaging adjacent age templates—without accounting for these biological dynamics—risks producing anatomically inaccurate interpolated atlases, particularly in regions undergoing abrupt structural or positional shifts. Moreover, uniform transformations across the entire brain fail to capture the asynchronous development of different regions, potentially distorting key neuroanatomical features. These limitations underscore the need for data-driven atlas construction based on real samples, particularly during early postnatal stages when developmental trajectories are most divergent.

D-LMBmapX addresses this challenge by enabling automated construction of an inferred atlas for any given postnatal day from a single sample and the flanking anchor atlases, empowering the developmental neuroscience community with a foundational tool to study brain regions of interest on their own critical timelines rather than being constrained by atlas availability.

For mesoscale circuitry profiling, whole-brain axon and soma segmentation is typically the most time-consuming step. Although we previously developed D-LMBmap[17], an automated pipeline for whole-brain circuitry profiling that substantially reduced the need for labor-intensive manual annotations, it was designed only for the adult stage. Directly extending D-LMBmap[17] to 5D developmental analyses poses substantial challenges, as it would require extensive annotated datasets and retraining at each postnatal stage due to the marked variability in axonal and somatic morphologies throughout development. To overcome this, D-LMBmapX integrates CircuitFound, a powerful foundation model that enables large-scale self-supervised pretraining on massive brain image datasets. With only minimal sample-specific fine-tuning, this framework achieves robust and accurate axon and

soma segmentation across developmental stages, offering a generalized solution for comprehensive brain mapping.

The rapid advancement of mesoscale connectomics has been driven by both large-scale 3D imaging technologies, such as LSFM, and a variety of high-resolution 2D methods[25–28]. Concurrently, there is a growing demand to integrate multi-modality, high-throughput spatial datasets that capture complementary aspects of brain organization. These include spatial transcriptomics, cross-synaptic tracing, activity-dependent labelling, and functional imaging, among others. However, due to the complexity of these procedures, such datasets are often limited to a small number of processed 2D brain slices. Existing 2D-to-3D registration methods typically require multiple consecutive sections and are constrained by limited resolution[52,53]. In this context, D-LMBmapX represents a significant advance—its ability to perform cross-modality and cross-dimensional registration allows even a single 2D section to be accurately aligned within a common 3D reference framework. This integrative capability not only enhances the scalability of mesoscale circuitry profiling but also lays the groundwork for a unified mesoscale connectomics ecosystem that incorporate anatomical, molecular, physiological, and functional data.

Forebrain TH[+] circuits are primarily dopaminergic and noradrenergic, two critical neuromodulatory systems involved in a wide range of functions, including reward, motivation, attention, and mood regulation. Developmental deficits in these systems have long been implicated in the vulnerability to various mental disorders[54,55]. By using D-LMBmapX, we generated the first 5D whole-brain atlas of TH[+] axonal innervation, spanning over 260 brain regions across postnatal development. While the striatum receives extremely dense innervation from P0 and cannot be segmented at the axonal level with current imaging resolution, its regional densities were quantified by intensity to ensure comprehensive coverage. In cortical areas, TH[+] axonal density increased steadily over time, consistent with reports of prolonged growth and pathfinding of prefrontal cortex–projecting dopaminergic axons during adolescence[56]. In contrast, other regions exhibited diverse spatiotemporal dynamics, including sharp developmental surges, transient peaks (e.g., PVH and BST), or progressive declines not attributable to brain volume changes—patterns that align with evidence for system-level refinement of dopamine innervation[57]. Our atlas provides a brain-wide developmental reference for these systems and a foundation to explore how region-specific innervation trajectories relate to windows of vulnerability in neurodevelopmental and mental health conditions. The successful whole-brain profiling of TH[+] axons highlights D-LMBmapX as an effective end-to-end workflow for mesoscale circuitry analysis, enabling precise anatomical mapping, developmental trajectory tracking, and cross-study comparisons.

D-LMBmapX marks a shift from static mapping to dynamic, integrative brain profiling, enabling automated, precise analysis of the developmental assembly of diverse neural circuits and neurodevelopmental disorders. Beyond the developing mouse brain, it offers a powerful and generalizable 5D strategy for studying growth, ageing, and disease through integrated spatial, temporal, and multi-omic analysis.

ACKNOWLEDGEMENTS

We thank Drew Friedmann for advice on anti-TH whole brain staining. We thank the MRC Laboratory of Molecular Biology (LMB) Biological Service Group and the Ares staff for their support with animal husbandry. This work was supported by the Medical Research Council, as part of United Kingdom Research and Innovation (also known as UK Research and Innovation) [MC_UP_1201/22]. For the purpose of open access, the MRC Laboratory of Molecular Biology has applied a CC BY public copyright licence to any Author Accepted

Manuscript version arising. A.M.A was supported by the MRC LMB PhD program with an MRC studentship.

AUTHOR CONTRIBUTIONS

J.R. conceptualised the project. J.R. and Z.L. supervised the project. Z.L. led the development of D-LMBmapX. J.R. and Z.L. designed all the experiments. A.MJ.A. performed brain sample collections, tissue-clearing, immunostaining and light-sheet imaging. Z.L., P. L., Z.H., and S.Z. designed and implemented the neuron foundation model. Z. L., H.P. and J. L. designed and constructed the developmental brain atlas. Z. L., B.Z., C.L., and J.Z. designed and implemented the 2.5D registration methods. Z.L., H.P., and Y.S. designed the sample-inferred 4D atlas generation and registration pipeline. Z.L., H.P., H. L., P.L. and D.Z. designed and implemented the brain style transfer and the 2D to 3D localisation pipeline. Z.L., Y.S., and P.L. developed the D-LMBmapX software. Z.L., P.L., H.P., H.L., Z.H., Y.S., A.MJ.A, and J.R. co-annotated and checked the testing data. L.B. performed brain sample collections. R.N.S. assisted with the tissue-clearing. Z.L. and J.R. wrote the manuscript with input from all co-authors.

DATA AND CODE AVAILABILITY

The source code of all D-LMBmapX modules, including developmental atlas construction, 2.5D registration, sample-inferred 4D atlas generation, CircuitFound, diffusion-based brain style transfer, cross-dimensional and cross-modality brain profiling, along with the executable files of D-LMBmapX software and sample data can be found at D-LMBmapX's Github page (https://github.com/jtneuron/D-LMBmapX). Further information and requests for resources and reagents should be directed to and will be fulfilled by the lead contact, Jing Ren (jren@mrc-lmb.cam.ac.uk).

COMPETING INTERESTS

The authors declare that they intend to file a patent application related to the methods and applications described in this study.

REFERENCES

1. Xu, F., Shen, Y., Ding, L., Yang, C.-Y., Tan, H., Wang, H., Zhu, Q., Xu, R., Wu, F., Xiao, Y., et al. (2021). High-throughput mapping of a whole rhesus monkey brain at micrometer resolution. Nat. Biotechnol. *39*, 1521–1528. https://doi.org/10.1038/s41587-021-00986-5.

2. Ngai, J. (2024). BRAIN @ 10: A decade of innovation. Neuron *112*, 3003–3006. https://doi.org/10.1016/j.neuron.2024.09.007.

3. Hintiryan, H., Zhu, M., Zhao, P., Zhang, M., Barry, J., Nanda, S., Rudd, M., Wong, A., Miller, S., Gou, L., et al. (2025). Neural networks of the mouse visceromotor cortex. Nature. https://doi.org/10.1038/s41586-025-09360-w.

4. Xiong, F., Liu, L., and Peng, H. (2025). Reconstruction of a connectome of single neurons in mouse brains by cross-validating multi-scale multi-modality data. Nat. Methods. https://doi.org/10.1038/s41592-025-02784-2.

5. Oh, S.W., Harris, J.A., Ng, L., Winslow, B., Cain, N., Mihalas, S., Wang, Q., Lau, C., Kuan, L.,

Henry, A.M., et al. (2014). A mesoscale connectome of the mouse brain. Nature *508*, 207–214.
https://doi.org/10.1038/nature13186.

6. Mansour, H., Azrak, R., Cook, J.J., Hornburg, K.J., Qi, Y., Tian, Y., Williams, R.W., Yeh, F.-C.,
White, L.E., and Johnson, G.A. (2025). The Duke Mouse Brain Atlas: MRI and light sheet
microscopy stereotaxic atlas of the mouse brain. Sci. Adv. *11*, eadq8089.
https://doi.org/10.1126/sciadv.adq8089.

7. Wang, Q., Ding, S.-L., Li, Y., Royall, J., Feng, D., Lesnar, P., Graddis, N., Naeemi, M., Facer, B.,
Ho, A., et al. (2020). The Allen Mouse Brain Common Coordinate Framework: A 3D Reference
Atlas. Cell *181*, 936-953.e20. https://doi.org/10.1016/j.cell.2020.04.007.

8. Feng, Z., Li, X., Luo, Y., Liu, X., Long, B., Jiang, T., Jia, X., Chen, X., Luo, J., Chai, X., et al.
(2025). A mouse brain stereotaxic topographic atlas with isotropic 1-μm resolution. Nature *645*,
448–456. https://doi.org/10.1038/s41586-025-09211-8.

9. Sunkin, S.M., Ng, L., Lau, C., Dolbeare, T., Gilbert, T.L., Thompson, C.L., Hawrylycz, M., and
Dang, C. (2012). Allen Brain Atlas: an integrated spatio-temporal portal for exploring the central
nervous system. Nucleic Acids Res. *41*, D996–D1008.

10. Li, A., Gong, H., Zhang, B., Wang, Q., Yan, C., Wu, J., Liu, Q., Zeng, S., and Luo, Q. (2010).
Micro-optical sectioning tomography to obtain a high-resolution atlas of the mouse brain.
Science *330*, 1404–1408. https://doi.org/10.1126/science.1191776.

11. Dodt, H.U., Leischner, U., Schierloh, A., Jährling, N., Mauch, C.P., Deininger, K., Deussing, J.M.,
Eder, M., Zieglgänsberger, W., and Becker, K. (2007). Ultramicroscopy: Three-dimensional
visualization of neuronal networks in the whole mouse brain. Nat. Methods *4*.
https://doi.org/10.1038/nmeth1036.

12. Friedmann, D., Pun, A., Adams, E.L., Lui, J.H., Kebschull, J.M., Grutzner, S.M., Castagnola, C.,
Tessier-Lavigne, M., and Luo, L. (2020). Mapping mesoscale axonal projections in the mouse
brain using a 3D convolutional network. Proc. Natl. Acad. Sci. *117*, 11068–11075.
https://doi.org/10.1073/pnas.1918465117.

13. Hobson, C.M., Guo, M., Vishwasrao, H.D., Wu, Y., Shroff, H., and Chew, T.-L. (2022). Practical
considerations for quantitative light sheet fluorescence microscopy. Nat. Methods *19*, 1538–
1549. https://doi.org/10.1038/s41592-022-01632-x.

14. Ueda, H.R., Dodt, H.-U., Osten, P., Economo, M.N., Chandrashekar, J., and Keller, P.J. (2020).
Whole-Brain Profiling of Cells and Circuits in Mammals by Tissue Clearing and Light-Sheet
Microscopy. Neuron *106*, 369–387. https://doi.org/10.1016/j.neuron.2020.03.004.

15. Gao, R., Asano, S.M., Upadhyayula, S., Pisarev, I., Milkie, D.E., Liu, T.-L., Singh, V., Graves, A.,
Huynh, G.H., Zhao, Y., et al. (2019). Cortical column and whole-brain imaging with molecular
contrast and nanoscale resolution. Science *363*, eaau8302.
https://doi.org/10.1126/science.aau8302.

16. Zhong, S., Zhang, X., Gao, X., Li, Z., Huang, L., Guo, Q., Gong, R., Ren, J., Luo, M., and Lin, R. (2025). Ultrabright chemical labeling enables rapid neural connectivity profiling in large tissue samples. Neuron, S0896-6273(25)00657-9. https://doi.org/10.1016/j.neuron.2025.08.022.

17. Li, Z., Shang, Z., Liu, J., Zhen, H., Zhu, E., Zhong, S., Sturgess, R.N., Zhou, Y., Hu, X., Zhao, X., et al. (2023). D-LMBmap: a fully automated deep-learning pipeline for whole-brain profiling of neural circuitry. Nat. Methods *20*, 1593–1604. https://doi.org/10.1038/s41592-023-01998-6.

18. Sur, M., and Rubenstein, J.L.R. (2005). Patterning and Plasticity of the Cerebral Cortex. Science *310*, 805–810. https://doi.org/10.1126/science.1112070.

19. Marín, O. (2016). Developmental timing and critical windows for the treatment of psychiatric disorders. Nat. Med. *22*, 1229–1238. https://doi.org/10.1038/nm.4225.

20. Winding, M., Pedigo, B.D., Barnes, C.L., Patsolic, H.G., Park, Y., Kazimiers, T., Fushiki, A., Andrade, I.V., Khandelwal, A., Valdes-Aleman, J., et al. (2023). The connectome of an insect brain. Science *379*, eadd9330. https://doi.org/10.1126/science.add9330.

21. Qiu, L.R., Fernandes, D.J., Szulc-Lerch, K.U., Dazai, J., Nieman, B.J., Turnbull, D.H., Foster, J.A., Palmert, M.R., and Lerch, J.P. (2018). Mouse MRI shows brain areas relatively larger in males emerge before those larger in females. Nat. Commun. *9*, 2615. https://doi.org/10.1038/s41467-018-04921-2.

22. Katz, L.C., and Shatz, C.J. (1996). Synaptic activity and the construction of cortical circuits. Science *274*, 1133–1138. https://doi.org/10.1126/science.274.5290.1133.

23. Kirkby, L.A., Sack, G.S., Firl, A., and Feller, M.B. (2013). A Role for Correlated Spontaneous Activity in the Assembly of Neural Circuits. Neuron *80*, 1129–1144. https://doi.org/10.1016/j.neuron.2013.10.030.

24. Ralevski, A., and Horvath, T.L. (2015). Developmental programming of hypothalamic neuroendocrine systems. Front. Neuroendocrinol. *39*, 52–58. https://doi.org/10.1016/j.yfrne.2015.09.002.

25. Harris, J.A., Mihalas, S., Hirokawa, K.E., Whitesell, J.D., Choi, H., Bernard, A., Bohn, P., Caldejon, S., Casal, L., Cho, A., et al. (2019). Hierarchical organization of cortical and thalamic connectivity. Nature *575*, 195–202. https://doi.org/10.1038/s41586-019-1716-z.

26. Zheng, T., Yang, Z., Li, A., Lv, X., Zhou, Z., Wang, X., Qi, X., Li, S., Luo, Q., Gong, H., et al. (2013). Visualization of brain circuits using two-photon fluorescence micro-optical sectioning tomography. Opt. Express *21*, 9839–9850. https://doi.org/10.1364/OE.21.009839.

27. Gong, H., Xu, D., Yuan, J., Li, X., Guo, C., Peng, J., Li, Y., Schwarz, L.A., Li, A., Hu, B., et al. (2016). High-throughput dual-colour precision imaging for brain-wide connectome with cytoarchitectonic landmarks at the cellular level. Nat. Commun. *7*. https://doi.org/10.1038/ncomms12142.

28. Ragan, T., Kadiri, L.R., Venkataraju, K.U., Bahlmann, K., Sutin, J., Taranda, J., Arganda-Carreras, I., Kim, Y., Seung, H.S., and Osten, P. (2012). Serial two-photon tomography for automated ex vivo mouse brain imaging. Nat. Methods *9*, 255–258. https://doi.org/10.1038/nmeth.1854.

29. Thompson, C.L., Ng, L., Menon, V., Martinez, S., Lee, C.-K., Glattfelder, K., Sunkin, S.M., Henry, A., Lau, C., Dang, C., et al. (2014). A high-resolution spatiotemporal atlas of gene expression of the developing mouse brain. Neuron *83*, 309–323. https://doi.org/10.1016/j.neuron.2014.05.033.

30. Tustison, N.J., Avants, B.B., Cook, P.A., Yuanjie Zheng, Egan, A., Yushkevich, P.A., and Gee, J.C. (2010). N4ITK: Improved N3 Bias Correction. IEEE Trans. Med. Imaging *29*, 1310–1320. https://doi.org/10.1109/TMI.2010.2046908.

31. Amorim, P., Moraes, T., Silva, J., and Pedrini, H. (2018). 3D Adaptive Histogram Equalization Method for Medical Volumes. VISIGRAPP.

32. Kronman, F.N., Liwang, J.K., Betty, R., Vanselow, D.J., and Wu, Y.-T. (2024). Developmental mouse brain common coordinate framework. Nat. Commun. *15*, 1–17.

33. Wang, Q., Ding, S.-L., Li, Y., Royall, J., Feng, D., Lesnar, P., Graddis, N., Naeemi, M., Facer, B., Ho, A., et al. (2020). The Allen Mouse Brain Common Coordinate Framework: A 3D Reference Atlas. Cell *181*, 936-953.e20. https://doi.org/10.1016/j.cell.2020.04.007.

34. Tustison, N.J., Chen, M., Kronman, F.N., Duda, J.T., Gamlin, C., Tustison, M.G., Kunst, M., Dalley, R., Sorensen, S.A., Wang, Q., et al. (2024). The ANTsX Ecosystem for Mapping the Mouse Brain. Preprint at Neuroscience, https://doi.org/10.1101/2024.05.01.592056 https://doi.org/10.1101/2024.05.01.592056.

35. Carey, H., Kleven, H., Øvsthus, M., Yates, S.C., Csucs, G., Puchades, M.A., McMullan, S., Bjaalie, J.G., Leergaard, T.B., and Bjerke, I.E. (2025). DeMBA: a developmental atlas for navigating the mouse brain in space and time. Nat. Commun. *16*, 8108. https://doi.org/10.1038/s41467-025-63177-9.

36. Han, K., Wang, Y., Chen, H., Chen, X., Guo, J., Liu, Z., Tang, Y., Xiao, A., Xu, C., Xu, Y., et al. (2023). A Survey on Vision Transformer. IEEE Trans. Pattern Anal. Mach. Intell. *45*, 87–110. https://doi.org/10.1109/TPAMI.2022.3152247.

37. He, K., Chen, X., Xie, S., Li, Y., Dollar, P., and Girshick, R. (2022). Masked Autoencoders Are Scalable Vision Learners. Proc. IEEECVF Conf. Comput. Vis. Pattern Recognit.

38. Dalal, N., and Triggs, B. (2005). Histograms of Oriented Gradients for Human Detection. In 2005 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'05) (IEEE), pp. 886–893. https://doi.org/10.1109/CVPR.2005.177.

39. Kirillov, A., Mintun, E., Ravi, N., Mao, H., Rolland, C., Gustafson, L., Xiao, T., Whitehead, S., Berg, A.C., Lo, W.-Y., et al. (2023). Segment Anything. Proc. IEEECVF Int. Conf. Comput. Vis.

40. Li, Z., Shang, Z., Liu, J., Zhen, H., Zhu, E., Zhong, S., Sturgess, R.N., and Zhou, Y. (2023). D-LMBmap: a fully automated deep-learning pipeline for whole-brain profiling of neural circuitry. Nat. Methods *20*, 1593–1604.

41. Attarpour, A., Osmann, J., Rinaldi, A., Qi, T., Lal, N., Patel, S., Rozak, M., Yu, F., Cho, N., Squair, J., et al. (2025). A deep learning pipeline for three-dimensional brain-wide mapping of local neuronal ensembles in teravoxel light-sheet microscopy. Nat. Methods *22*, 600–611. https://doi.org/10.1038/s41592-024-02583-1.

42. Harris, C., and Stephens, M. (1988). A Combined Corner and Edge Detector. In Procedings of the Alvey Vision Conference 1988 (Alvey Vision Club), p. 23.1-23.6. https://doi.org/10.5244/C.2.23.

43. Lowe, D.G. (2004). Distinctive Image Features from Scale-Invariant Keypoints. Int. J. Comput. Vis. *60*, 91–110. https://doi.org/10.1023/B:VISI.0000029664.99615.94.

44. Fischler, M.A., and Bolles, R.C. Random sample consensus. *24*.

45. Lorang, D., Amara, S.G., and Simerly, R.B. (1994). Cell-type-specific expression of catecholamine transporters in the rat brain. J. Neurosci. Off. J. Soc. Neurosci. *14*, 4903–4914. https://doi.org/10.1523/JNEUROSCI.14-08-04903.1994.

46. Feng, Z., Li, X., Luo, Y., Liu, X., Long, B., Jiang, T., Jia, X., Chen, X., Luo, J., Chai, X., et al. (2025). A mouse brain stereotaxic topographic atlas with isotropic 1-μm resolution. Nature *645*, 448–456. https://doi.org/10.1038/s41586-025-09211-8.

47. Wang, Q., Ding, S.-L., Li, Y., Royall, J., Feng, D., Lesnar, P., Graddis, N., Naeemi, M., Facer, B., Ho, A., et al. (2020). The Allen Mouse Brain Common Coordinate Framework: A 3D Reference Atlas. Cell *181*, 936-953.e20. https://doi.org/10.1016/j.cell.2020.04.007.

48. Jiang, S., Wang, L., Yun, Z., Chen, H., Liu, L., Yao, J., and Peng, H. (2025). NeuroXiv: AI-powered open databasing and dynamic mining of brain-wide neuron morphometry. Nat. Methods *22*, 1195–1198. https://doi.org/10.1038/s41592-025-02687-2.

49. Claudi, F., Petrucco, L., Tyson, A., Branco, T., Margrie, T., and Portugues, R. (2020). BrainGlobe Atlas API: a common interface for neuroanatomical atlases. J. Open Source Softw. *5*, 2668. https://doi.org/10.21105/joss.02668.

50. Claudi, F., Tyson, A.L., Petrucco, L., Margrie, T.W., Portugues, R., and Branco, T. (2021). Visualizing anatomically registered data with brainrender. eLife *10*, e65751. https://doi.org/10.7554/eLife.65751.

51. Tyson, A.L., Vélez-Fort, M., Rousseau, C.V., Cossell, L., Tsitoura, C., Lenzi, S.C., Obenhaus, H.A., Claudi, F., Branco, T., and Margrie, T.W. (2022). Accurate determination of marker location within whole-brain microscopy images. Sci. Rep. *12*, 867. https://doi.org/10.1038/s41598-021-04676-9.

52. Xiong, J., Ren, J., Luo, L., and Horowitz, M. (2018). Mapping Histological Slice Sequences to
the Allen Mouse Brain Atlas Without 3D Reconstruction. Front. Neuroinformatics *12*, 93.
https://doi.org/10.3389/fninf.2018.00093.

53. Puchades, M.A., Csucs, G., Ledergerber, D., Leergaard, T.B., and Bjaalie, J.G. (2019). Spatial
registration of serial microscopic brain images to three-dimensional reference atlases with the
QuickNII tool. PloS One *14*, e0216796. https://doi.org/10.1371/journal.pone.0216796.

54. Grace, A.A. (2016). Dysregulation of the dopamine system in the pathophysiology of
schizophrenia and depression. Nat. Rev. Neurosci. *17*, 524–532.
https://doi.org/10.1038/nrn.2016.57.

55. Poe, G.R., Foote, S., Eschenko, O., Johansen, J.P., Bouret, S., Aston-Jones, G., Harley, C.W.,
Manahan-Vaughan, D., Weinshenker, D., Valentino, R., et al. (2020). Locus coeruleus: a new
look at the blue spot. Nat. Rev. Neurosci. *21*, 644–659. https://doi.org/10.1038/s41583-020-
0360-9.

56. Avramescu, R.G., Capolicchio, T., and Flores, C. (2024). Dynamic Insights into Dopamine Axon
Growth in Adolescence and its Implications for Psychiatric Risk. Curr. Opin. Behav. Sci. *59*,
101435. https://doi.org/10.1016/j.cobeha.2024.101435.

57. Hoops, D., and Flores, C. (2017). Making Dopamine Connections in Adolescence. Trends
Neurosci. *40*, 709–719. https://doi.org/10.1016/j.tins.2017.09.004.

FIGURE LEGENDS

Figure 1. Overview of D-LMBmapX.

A. The pipeline for 3D registration of any postnatal day using cross-stage registration. 3D brain atlases were constructed based on LSFM brain samples at postnatal stages P0, P4, P7, P10, P14, P21, and P28. Given an intermediate stage (between Pi and Pj), brain structures can be adaptively quantified through sample-inferred atlas generation and registration with its two flanking atlases.

B. The pipeline for quantitative analysis of axons and somata across any developmental stages. Following the extraction of extensive 3D image cubes from whole-brain data, a neuron foundation model is designed to segment axons and somata.

C. The pipeline for cross-modality and cross-dimension whole-brain profiling. An example 2D histological slice from the Allen Brain Atlas is used to illustrate the pipeline. The slice undergoes style transfer to match the LSFM modality, followed by automatic localisation and registration of the corresponding section from a digitally sliced 3D atlas. Soma segmentation is then performed to enable region-wise quantification of soma density.

D. The software interface of the D-LMBmapX for neural circuitry profiling and atlas visualisation of developing mouse brains.

Figure 2. Construction of 3D mouse brain atlas across seven postnatal stages.

A. The pipeline for the construction of 3D averaged brain in each developmental stage. Original brain samples from each stage are first pre-processed and voxel-wise averaged. The individual brain was registered to the voxel-wise averaged brain with rigid, affine, and deformable transformations to generate the initial reference template. Finally, a fine-grained average template was generated through iterative registration of pre-processed brains to the initial reference template using the developed 2.5D registration method.

B. Multiview 2.5D registration framework. The coronal and horizontal views of the input 3D brain sample are first registered to the corresponding 2D image slices of the reference brain. Deformation field obtained from two views are used for registration. 3D Registered results from either views are used for the computation of the 3D consistency loss.

C. The pipeline of brain atlas construction based on fine-grained average templates. The P28 atlas was delineated from Allen CCFv3, and subsequent stages (P21–P0) were sequentially derived, with each delineation performed using 2.5D registration with multiple brain region constraints.

D. Visualisation of the 3D developmental brain atlases across seven postnatal stages in horizontal view. For each atlas, the left side is shown with the average brain template and the right half with anatomical delineations.

E. Evaluation and comparison of three developmental mouse brain atlases, DevCCF, DeMBA and D-LMBmapX. Performance was assessed by calculating region-wise Dice scores for major brain areas (BS, CB, CP, CTX, HPF) after registering LSFM sample brains to each atlas at P14 (n=7), P7 (n=5), and P4 (n=8). Box plot: centre line, median; box limits, upper and lower quartiles; whiskers, 1.5× interquartile range.

F. Radial plot illustrating the temporal progression in anatomical volume changes of 276 profiled brain regions across seven postnatal stages. Individual brain regions are grouped according to their boarder anatomical categories (Table. S5). Colour code indicates scaled

volume changes across developmental stages for each brain region.

G. Volume changes of the whole brain and selected brain regions across postnatal
development. Top left, whole brain; top right, selected brain regions from cortical and thalamic
areas; bottom left, selected brain regions containing dopaminergic neurons; bottom right,
selected brain regions from the hypothalamus (n=8 brains in each stage; solid lines and
shadows represent mean ± SEM).

Figure 3. Generalised Sample-Inferred Pipeline for 4D Atlas Generation and
Registration at Arbitrary Developmental Stages.

A. Pipeline for constructing a sample-inferred 3D brain atlas at any developmental stage
using flanking atlases — illustrated with a P10 mouse brain as an example. When a P10 brain
sample needs to be registered but only P7 and P14 atlases are available, D-LMBmapX
constructs a sample-inferred P10 atlas. The P7 and P14 atlases are non-linearly registered
to the P10 brain, averaged, and iteratively refined into a consistent inferred template. The
P10 brain is then registered to this atlas, enabling full-brain anatomical delineation through
label transfer.

B. Representative horizontal view of the sample-inferred P10 atlas and the authentic P10
atlas constructed by D-LMBmapX. The sample-inferred P10 atlas was constructed using a
single P10 brain and two flanking atlases (P7 and P14), following the pipeline described
above. The authentic P10 atlas was constructed from 30 P10 brain samples following the
standard template construction pipeline shown in Figure 2.

C. Quantitative comparison of P10 registration to sample-inferred, authentic, and flanking-
stage atlases. Left, region-wise Dice score for major brain regions (BS, CB, CP, CTX, HPF)
and small brain regions (LGvc, lgd, RN, Hb, ac). Right, average median Dice score after
registering the sample brain to each atlas (calculated by ordinary one-way ANOVA with
Dunnett's multiple comparison, n=3 brains. ns indicates non-significant, ***$P<0.001$,
***$P<0.0001$). Measure of centre, mean; error bars, mean±SEM.

D. Representative horizontal view of a P10 sample brain registered to the DeMBA
interpolated P10 atlas and the D-LMBmapX sample-inferred P10, respectively, with orange
lines marking anatomical region boundaries in each atlas.

E. Quantitative comparison of P10 sample brains registration to the DeMBA interpolated P10
atlas and the D-LMBmapX sample-inferred P10. Left, region-wise Dice score for major brain
regions (BS, CB, CP, CTX, HPF) and small brain regions (LGvc, lgd, RN, Hb, ac). Right,
average median Dice score after registering sample brains to each atlas (calculated by Two-
tailed paired t-test, n=3 brains. **$P<0.01$). Measure of centre, mean; error bars, mean±SEM.

F. Whole-brain registration of a 29-week human fetal brain to the sample-inferred atlas and
authentic atlas. Construction of the 29-week human fetal brain sample-inferred atlas was
based on the authentic flanking atlases at 23-week and 35-week.

G. Quantitative comparison of a 29-week human fetal brain registration to the sample-inferred
29-week atlas, authentic 29-week atlas, and two flanking 23-week and 35-week atlases.
Average median Dice score after registering sample brains to each atlas (calculated by one-
way ANOVA with Dunnett's multiple comparisons, n=9 brains, *ns* indicates non-significant,
*$P<0.05$ ****$P<0.0001$). Measure of centre, mean; error bars, mean±SEM.

Figure 4. CircuitFound, a generalised foundation model for 4D whole-brain circuitry

profiling.

A. The self-supervised pre-training framework designed in CircuitFound. Over 100,000 3D cubes were randomly cropped from LSFM brain samples. A customised dual-decoder 3D masked autoencoder (MAE) was trained from scratch in a self-supervised manner. In addition to reconstructing voxel-level cubes, the network also reconstructed cubes after computing histograms of oriented gradients (HOG), enabling improved capture of long-range, tree-like axon morphologies.

B. Automated and semi-automated annotation of axon and soma in selected sample cubes. Axon annotation was performed using the binarisation and skeletonisation pipeline embedded in D-LMBmap. Soma annotation was carried out with a newly developed pipeline combining manual 2D point prompting, prediction with the Segment Anything Model (SAM), and post-processing.

C. Task-specific fine-tuning network in CircuitFound. With a small number of task-specific cubes containing automated annotations (axons or somata), features were extracted using the ViT encoder from the pre-trained CircuitFound model. A multi-level cascading CNN module was then introduced in parallel with the ViT encoder, enabling faster convergence and robust performance with only a few fine-tuning samples.

D. Whole-brain axon segmentation and projection mapping of anti-TH stained brains in postnatal stages from P0 to P28. Top row, representative LSFM brains across seven stages in the anti-TH stained channel. Middle row, representative results of whole-brain segmentation of TH+ axon across seven stages, where axons located in different major brain regions are visualised in distinct colours. (white: CTX and OLF, blue: CP, ACB, and OT, green: BS, yellow: CB, pink: HPF). Bottom row, heatmaps of averaged TH+ axon distribution in horizontal view from P0 to P28 (n=3 for each stage).

E. Quantitative comparison of axon segmentation effectiveness between TrailMap and D-LMBmapX by the ClDice metric. A total of 46 annotated cubes (150 × 150 × 150) were used for training both models. For evaluation, 84 cubes were sampled from four major brain regions (BS, CB, HPF, and CTX) across 21 anti-TH–stained brains, with three brains assessed at each developmental stage (P0, P4, P7, P10, P14, P21, P28). Two-tailed paired *t*-test. Error bars represent mean ± SEM.

F. Quantitative comparison of soma segmentation effectiveness between ACE and D-LMBmapX under the evaluation metric of Dice and Precision. A total of 36 annotated cubes (150 × 150 × 150) were used for training both models. For evaluation, 44 cubes were sampled from 21 anti-TH–stained brains across seven developmental stages. Two-tailed paired t-test. Error bars represent mean ± SEM.

G. Radial plot illustrating the temporal progression in TH+ axon density during postnatal development across 276 profiled brain regions. Individual brain regions are grouped according to their boarder anatomical categories (Table. S6). Colour code indicates scaled axonal density across developmental stages for each brain region.

H. Waterfall plot showing the TH+ axon density changes during postnatal development for selected brain regions. Top, selected brain regions where TH+ axon density is significantly increased in the other six postnatal stages compared to P0. Bottom, selected brain regions where TH+ axon density is increased in other six postnatal stages compared to P7 (One-way ANOVA followed by Bonferroni correction. P value in Table S8), n=3 brains for each stage. Error bars, mean±SEM.

Figure 5. Cross-modality and cross-dimensional profiling at any postanal stages.

A. Automated pipeline for comprehensive 2D-to-3D brain mapping and region-wise quantification. It includes slice pre-processing, cross-modality style transfer, and spatial alignment to identify the best-matching sections in a 3D reference atlas. This is followed by 2D-to-3D registration, automated soma/axon segmentation, and region-wise quantitative analysis.

B. Design of the automated 2D-to-3D spatial alignment module. Corner-based landmarks are extracted from style-transferred 2D histological slices and from all orthogonal sections (e.g., sagittal) of the 3D reference atlas. Top-K candidate sections are selected based on matched landmarks (K=40 in our experiment). Initial orientation is estimated using RANSAC to align 2D slice landmarks with those from top-K sections. D-LMBmapX then refines localisation by applying small yaw and roll adjustments, selecting the best-matching section using a Mutual Information (MI) metric.

C. Evaluation of 2D-to-3D spatial localization accuracy. The Allen 3D CCFv3 atlas (STPT modality) was first registered to the D-LMBmapX P28 3D atlas (LSFM modality) to establish ground truth alignment. A total of 169 2D slices were randomly selected from the Allen CCFv3 STPT atlas and subjected to arbitrary yaw (rotation in Z-axis), roll (rotation in Y-axis), and translation (linear shifts along x, y, or z). Each slice was then spatially aligned to the 3D LSFM atlas using the D-LMBmapX pipeline. Localisation accuracy was assessed by comparing yaw, roll, and translation errors against the ground truth.

D. Comparison of TH$^+$ somata density in corresponding sagittal panels from two sources: P28 Allen 2D ISH slices (top) and matched sections extracted from a P28 3D anti-TH–stained LSFM brain (bottom) profiled by D-LMBmapX. The 3D whole-brains stained with TH$^+$ somata were registered to the P28 LSFM atlas to profile the somata density in 3D. The P28 Allen 2D TH$^+$ slices were localised to the 3D P28 atlas in matching similar sections, combining with somata segmentation to achieve the TH$^+$ somata profiling in 2D slices.

E. Evaluation of consistency in normalised region-wise TH$^+$ soma density between Allen 2D ISH slices and 3D LSFM whole-brain data profiled with D-LMBmapX at P28.

F. Examples of registering a single 2D slice into 3D brain atlas. Selected P28 Allen 2D ISH slices for three gene markers (*Th*, *Slc6a2*, and *Slc6a3*), each containing the ventral tegmental area (VTA) and locus coeruleus (LC), are profiled. Left: original Allen ISH slices for *Th*, *Slc6a2*, and *Slc6a3*. Middle: corresponding sections localised, registered, and mapped within the P28 LSFM 3D atlas. Right: heatmaps of region-wise soma density for *Th*, *Slc6a2*, and *Slc6a3*. Soma segmentation, 2D-to-3D registration, and region-wise density profiling were performed using D-LMBmapX. Heatmap colours indicate normalized somata density per sample, with colour scales shown in the corresponding bars for each gene.

SUPPLEMENTARY FIGURE LEGENDS

Figure S1. Quantitative evaluation of the 2.5D registration framework with multiple constraints.

A. Horizontal view (left) and 3D visualisation (right) showing the brain regions used as constraints for the 2.5D registration, including 5 major brain regions (CTX, CP, HPF, BS, CB) and 8 small brain regions, i.e., ac (aco, act), Hb (MH, LH), LGd, fr, LGvc, RN.

B. Confusion matrices showing the effect of individual brain region constraints on P7 brains (n=3, left) and P14 brains (n=3, right). The X-axis denotes the applied region constraint, and

the Y-axis shows the change in Dice score for each brain region after adding that constraint.

C. Comparison of whole-brain registration results from ANTs and D-LMBmapX across seven
postnatal stages. Region-wise median Dice scores were computed for five major regions (BS,
CB, CP, CTX, HPF) and five smaller regions (LGvc, LGd, Hb, ac, RN) (n=3 brains per stage).
Error bars represent mean ± SEM.

Figure S2. Multi-view representation of the constructed 3D brain atlas across seven
developmental stages.

From left to right, the 3D average brain template, the 3D anatomical brain region delineation,
the anatomical delineation in coronal view, and the anatomical delineation in sagittal view.

Figure S3. Visualisation of 2.5D registration in developmental stages from P0 to P28.

Representative results of D-LMBmapX 2.5D registration, the newly developed module used
for both atlas construction and whole-brain sample registration. Shown are detailed
delineation results after registration, with orange lines marking anatomical region boundaries
in each developmental atlas. Boundaries are illustrated in selected horizontal and coronal
views for developmental stages from P0 to P28.

Figure S4. Mutual learning–guided whole-brain registration using automatic flanking-
atlas constraints.

A. Pipeline for automated acquisition of multiple brain region constraints from two flanking
atlases. Illustrated with a P10 mouse brain as an example, the flanking P7 and P14 atlases
were first registered and overlaid onto the P10 brain sample. The Dice score of each brain
region was then computed and ranked between the P10-like P7 atlas and the P10-like P14
atlas. The pipeline automatically selected the highly overlapping regions as constraints for
mutual learning–guided registration.

B. Pipeline for mutual learning–guided whole-brain registration. Illustrated with the
registration of a P10 brain sample to the inferred P10 atlas as an example. Each brain region
selected in the previous step was first computed for intersection and union between two
sources (i.e., the P10-like P7 atlas and the P10-like P14 atlas). The intersection and union
constraints were then applied for iterative P10 brain registration to the sample-inferred P10
atlas using the 2.5D registration framework shown in Figure 2A. The intersection-based and
union-based models were mutually trained for every 10 epochs, with the parameters of the
other model fixed during each iteration. Dice loss, similarity loss, regularisation loss, spatial
consistency loss and deformation-based mutual learning loss were used during training.

C. Evaluation of the effectiveness of the mutual learning–guided registration pipeline for
delineating P10 and P7 brain samples. Left, region-wise Dice scores for major brain regions
(BS, CB, CP, CTX, HPF) and smaller brain regions (LGvc, LGd, RN, Hb, ac) at P10 stage.
Right, region-wise Dice scores for major brain regions (BS, CB, CP, CTX, HPF) and smaller
brain regions (LGvc, LGd, RN, Hb, ac) at P7 stage. Measure of centre, mean; error bars,
mean ± SEM.

Figure S5. Evaluation of the sample-inferred atlas at P7 in mouse brains.

A. Representative horizontal view of the sample-inferred P7 atlas and the authentic P7 atlas
constructed by D-LMBmapX. The P7 sample-inferred atlas was constructed using a single

P7 brain and two flanking atlases (P4 and P10), following the pipeline described in Figure 3A. The authentic P7 atlas was constructed from 30 P7 brain samples following the standard template construction pipeline shown in Figure 2.

B. Quantitative comparison of P7 sample brains registration to sample-inferred P7 atlas, authentic P7 atlas, and two flanking authentic P4 and P10 atlases. Left, region-wise Dice score for major brain regions (BS, CB, CP, CTX, HPF) and small brain regions (LGvc, lgd, RN, Hb, ac). Right, average median Dice score after registering sample brains to each atlas (calculated by ordinary one-way ANOVA with Dunnett's multiple comparison, n=3 brains. ns indicates non-significant, *P<0.05, **P<0.01). Measure of centre, mean; error bars, mean±SEM.

Figure S6. Evaluation of the sample-inferred atlas construction pipeline at selected developmental stages in human fetal and infant brains.

A. Quantitative comparison of 29-week human fetal sample brains registration to the sample-inferred 29-week atlas, authentic 29-week atlas, and two flanking 23-week and 25-week atlases. Region-wise Dice score for 6 brain structures, i.e., Extra-axial cerebrospinal fluid (CSF), Grey Matter and developing cortical plate (GM), White matter and subplate (WM), Lateral ventricles (LV), Cerebellum (CBM), Thalamus and putamen (SGM), Brain stem (BS). Measure of centre, mean; error bars, mean±SEM.

B. Representative horizontal view of the sample-inferred 7-month human infant brain atlas and the authentic 7-month human infant brain atlas. The construction of the human infant brain 7-month sample-inferred atlas is based on the 4-month and 10-month authentic atlases.

C. Quantitative comparison of a 7-month human infant sample brain registration to the sample-inferred 7-month atlas, authentic 7-month atlas, and two flanking 4-month and 10-month atlases. Left, Region-wise Dice score for grey matter and white matter. Right, average median Dice score after registering sample brains to each atlas (calculated by ordinary one-way ANOVA with Dunnett's multiple comparison, n=5 brains. *P<0.05, **P<0.01). Measure of centre, mean; error bars, mean±SEM.

Figure S7. Effectiveness validation of CircuitFound.

A. Ablation study of strategies applied in CircuitFound. Left and right panels: ClDice scores for axon segmentation at P28 (n = 12) and soma segmentation (n = 44), respectively, comparing D-LMBmapX without pre-training, without HOG, and with full implementation. Box plots: centre line, median; box limits, upper and lower quartiles; whiskers, 1.5× interquartile range; points, individual data values.

B. Quantitative evaluation of CircuitFound with varying numbers of training samples. Left and middle panels: average ClDice scores for axon segmentation at P28 and P7 using D-LMBmap and D-LMBmapX trained with 46, 115, and 228 cubes. Right panel: average Dice scores for soma segmentation using ACE and D-LMBmapX trained with 36, 142, 353, and 705 cubes.

C. Quantitative evaluation of axon segmentation methods used in TrailMap and D-LMBmapX across seven developmental stages. For each stage, segmentation performance was assessed using ClDice, ClPrecision, ClRecall, and Dice score, with 46 annotated cubes used for training. For evaluation, 12 image cubes (150 × 150 × 150) were sampled per stage from four major brain regions (BS, CB, HPF, and CTX), with three anti-TH–stained brains analyzed

962 at each stage.

Figure S8. Whole-brain segmentation and registration of TH⁺ somata from P0 to P28.
Top row: representative LSFM brains across seven developmental stages in the anti-TH channel. Middle row: representative results of whole-brain segmentation of TH⁺ somata across the seven stages, with somata in major brain regions shown in distinct colors (white: CTX and OLF; blue: CP, ACB, and OT; green: BS; yellow: CB; pink: HPF). Bottom row: heatmaps of averaged TH⁺ soma distributions in horizontal view from P0 to P28 (n = 3 brains per stage).

Figure S9. Region-wise TH+ axon density changes across postnatal development.

TH+ axon density (blue) and corresponding brain region volume (red) across 40 selected brain regions from P0 to P28. N=3 brains for each stage. Error bars, mean±SEM.

Figure S10. Brain image style transfer based on diffusion model with brain region and edge constraints.
A. Pipeline of the newly designed brain image style transfer method, including both training and prediction phases, illustrated with LSFM as the reference modality. During training, original LSFM 2D sections were diffused into random noise over steps from x_0 to x_t. Unlike general stable diffusion pipelines, two additional constraints were introduced to improve consistency between the diffused sections (x_t) and the original sections (x_0): (1) brain region edges automatically extracted using the Sobel operator, and (2) a denoising U-Net that automatically segmented major brain regions. During prediction, 2D ISH slices and other modalities were diffused and denoised using the trained stable diffusion model.
B. Quantitative validation of brain image style transfer methods (CycleGAN, DDPM, and D-LMBmapX), evaluated by SSIM, PSNR, and FID metrics.
C. Visual evaluation of brain image style transfer and 2D-to-3D localisation. From left to right: original Allen 2D ISH slices, images after preprocessing, edge extraction, style-transferred outputs generated by D-LMBmapX, and the most similar localised sections in the 3D atlas.

Figure S11. Comparison of TH⁺ somata density between Allen 2D ISH slices and corresponding digital sections from 3D anti-TH–stained LSFM brains.

A. Comparison of TH⁺ somata density in corresponding sagittal panels from two sources: P14 Allen 2D ISH slices (top) and matched sections extracted from a P14 3D anti-TH–stained LSFM brain (bottom) profiled by D-LMBmapX.

B. Comparison of TH⁺ somata density in corresponding sagittal panels from two sources: P4 Allen 2D ISH slices (top) and matched sections extracted from a P4 3D anti-TH–stained LSFM brain (bottom) profiled by D-LMBmapX.

1000

Figure S12. Postnatal monoaminergic gene marker profiling in Allen 2D ISH slices with D-LMBmapX.

A. Selected examples of P14 Allen 2D ISH slices for three gene markers (*Th*, *Slc6a2*, and *Slc6a3*), each containing the ventral tegmental area (VTA) and locus coeruleus (LC). Left: original Allen ISH slices for *Th*, *Slc6a2*, and *Slc6a3*. Middle: corresponding sections localised,

registered, and mapped within the P14 LSFM 3D atlas. Right: heatmaps of region-wise soma density for *Th*, *Slc6a2*, and *Slc6a3*.

B. Selected examples of P4 Allen 2D ISH slices for three gene markers (*Th*, *Slc6a2*, and *Slc6a3*), each containing the ventral tegmental area (VTA) and locus coeruleus (LC). Left: original Allen ISH slices for *Th*, *Slc6a2*, and *Slc6a3*. Middle: corresponding sections localised, registered, and mapped within the P4 LSFM 3D atlas. Right: heatmaps of region-wise soma density for *Th*, *Slc6a2*, and *Slc6a3*. Soma segmentation, 2D-to-3D registration, and region-wise density profiling were performed using D-LMBmapX. Heatmap colours indicate normalized somata density per sample, with colour scales shown in the corresponding bars for each gene.

Figure 1. Overview of D-LMBmapX.

Figure 2. Construction of 3D mouse brain atlas across seven postnatal stages.

Figure 3. Generalised Sample-Inferred Pipeline for 4D Atlas Generation and Registration at Arbitrary Developmental Stages.

Figure 4. CircuitFound, a generalised foundation model for 4D whole-brain circuitry profiling.

Figure 5. Cross-modality and cross-dimensional profiling at any postanal stages.