WaveSeekerNet: Accurate Prediction of Influenza A Virus Subtypes and Host Source

Using Attention-Based Deep Learning

Hoang-Hai Nguyen[1,2#], Josip Rudar[1,4#], Nathaniel Lesperance[4], Oksana Vernygora[1], Graham W.

Taylor[5,6], Chad Laing[1], David Lapen[7], Carson K. Leung[2], Oliver Lung[1,3]

[1] National Centre for Foreign Animal Disease, Canadian Food Inspection Agency, Winnipeg,

Manitoba, Canada

[2] Department of Computer Science, University of Manitoba, Winnipeg, Manitoba, Canada

[3] Department of Biological Sciences, University of Manitoba, Winnipeg, Manitoba, Canada

[4] Department of Integrative Biology & Centre for Biodiversity Genomics, University of Guelph,

Guelph, Ontario, Canada

[5] School of Engineering, University of Guelph, Guelph, Ontario, Canada

[6] Vector Institute, Toronto, Ontario, Canada

[7] Agriculture and Agri-Food Canada, Ottawa, Canada

#Address correspondence to Hoang-Hai Nguyen (nguyen92@myumanitoba.ca) and Josip Rudar

(joe.rudar@inspection.gc.ca)

Abstract

Background

Influenza A virus (IAV) poses a significant threat to animal health globally, with its ability to overcome species barriers and cause pandemics. Rapid and accurate IAV subtype and host source prediction are crucial for effective surveillance and pandemic preparedness. Deep learning has emerged as a powerful tool for analyzing viral genomic sequences, offering new ways to uncover hidden patterns associated with viral characteristics and host adaptation.

Findings

We introduce WaveSeekerNet, a novel deep learning model for accurate and rapid prediction of IAV subtypes and host source. The model leverages attention-based mechanisms and efficient token mixing schemes, including the Fourier Transform and the Wavelet Transform, to capture intricate patterns within viral RNA and protein sequences. Extensive experiments on diverse datasets demonstrate WaveSeekerNet's superior performance to existing models that use the traditional self-attention mechanism. Notably, WaveSeekerNet rivals VADR (Viral Annotation DefineR) in subtype prediction using the high-quality RNA sequences, achieving the maximum score of 1.0 on metrics including the Balanced Accuracy, F1-score (Macro Average), and Matthews Correlation Coefficient (MCC). Our approach to subtype and host source prediction also exceeds the pre-trained ESM-2 (Evolutionary Scale Modeling) models with respect to generalization performance and computational cost. Furthermore, WaveSeekerNet exhibits remarkable accuracy in distinguishing between human, avian, and other mammalian hosts. The ability of WaveSeekerNet to flag potential cross-species transmission

42 events underscores its significant value for real-time surveillance and proactive pandemic

43 preparedness efforts.

Conclusions

WaveSeekerNet's superior performance, efficiency, and ability to flag potential cross-

species transmission events highlight its potential for real-time surveillance and pandemic

preparedness. This model represents a significant advancement in applying deep learning for

IAV classification and holds promise for future epidemiological, veterinary studies, and public

health interventions.

Keywords: deep learning, alternate attention mechanisms, Fourier Transform, Wavelet

Transform, chaos game representation, influenza A virus, antigenic types, viral host source, viral

genomics.

1   Introduction

Influenza viruses are a constant threat to public and animal health and a leading cause of

acute respiratory diseases worldwide. Avian influenza is a contagious disease caused by

infection with influenza A virus (IAV), which naturally resides and circulates in waterfowl [1].

Host barriers prevent IAV from freely infecting new non-avian hosts; however, cross-species

transmission can occur when viruses evolve to overcome these barriers [2]. One crucial

determinant of IAV infection is hemagglutinin (HA) receptor binding specificity. Human

influenza virus strains prefer to bind to α2,6-sialic acid linkages, whereas avian virus strains

preferentially bind receptors of α2,3-sialic acid linkages [3]. IAV has a complex genome

structure with eight negative-sense, single-stranded RNA gene segments: PB2, PB1, PA, HA,

NP, NA, M, and NS [4]. The hemagglutinin (HA) and neuraminidase (NA) gene segments are

two major determinants of IAV antigenicity and virulence. IAV is classified into subtypes based

on the HA and NA segments. There are 18 different HA subtypes (H1 through H18), 11 different

NA subtypes (N1 through N11), and a possibility for new subtypes to be discovered, such as

putative H19 [5], creating many possible combinations, such as H5N1, H3N2, and H7N9. Since

1918, there have been four major influenza epidemics and pandemics caused by IAV: the

Spanish flu 1918 (H1N1), the Asian flu 1957 (H2N2), the Hong Kong flu 1968 (H3N2), and the

2009 swine flu pandemic (H1N1) [6,7]. Between 2003 and 2005, H5N1 IAV emerged in China

and spread to other countries, causing widespread poultry outbreaks across Asia, Africa, the

Middle East, and Europe [8,9]. In November 2021, a highly pathogenic avian influenza (HPAI)

variant of H5N1 IAV emerged in domestic birds at a farm in Newfoundland, Canada, likely

caused by transatlantic spread from Europe by wild birds [10]. Since its emergence, H5N1 IAV

has circulated throughout North America. As of May 2025, this outbreak has affected more than

14.5 million birds in Canada [11] and more than 169 million birds in the United States [12]. This

has significantly impacted poultry production, leading to rising egg prices and food inflation in

the United States [13]. The virus has also spread to mammals such as skunks, foxes, raccoons,

dogs, and dairy cows, including humans [14,15]. Because of this widespread impact and

potential for further spread, understanding and predicting the host source of IAV is crucial for

active surveillance and our preparedness for future pandemics. There is also a considerable need

to accurately and rapidly identify different circulating IAV subtypes. Such identification is

essential for effectively treating new and existing infections, as well as for planning and

executing robust strategies for viral surveillance and outbreak prevention [16].

Although progress has been made in understanding IAV transmission, significant

knowledge gaps remain [17,18]. Recently, machine learning (ML) and artificial intelligence (AI)

have been used to analyze large-scale viral genomic sequences to facilitate a deeper

understanding of the evolution and biology of pathogens. For example, machine learning

algorithms like Random Forest and Support Vector Machine (SVM) have been used to identify

genomic patterns associated with expanded host-range in severe acute respiratory syndrome

coronavirus 2 (SARS-CoV-2) [19] and IAV [20–23]. However, increasing focus is being

directed towards deep learning methods due to their robust applicability and ability to uncover

complex relationships by weighing and transforming information contained within multiple

genomic regions within a single model [24,25].

Ensemble learning has been successfully applied to supervised classification tasks in

diverse fields [26,27]. Breiman (2001) demonstrated that this procedure is successful since

decorrelation between ensemble members enables diverse learners to compensate for the errors

of other ensemble members [28]. This observation was further developed in methods such as

stacked generalization and voting classifiers, which exploit differences in the inductive biases of

different machine learning algorithms to improve classification performance [29]. Deep learning

has also leveraged the advantages of ensembles. For example, deep ensembles, which borrow

from the work of Breiman (2001), have been used as an alternative to Bayesian Neural Networks

to estimate prediction uncertainties [30,31]. Other innovations, such as dropout [32], act like

ensembling by activating a different set of neurons with each training iteration. Finally,

approaches such as multi-head attention [33] and Mixture-of-Experts [34] also contribute to good

generalization.

This study presents a new deep learning model, WaveSeekerNet, based on an ensemble

of different efficient attention-like and feed-forward network (FFN) mechanisms.

WaveSeekerNet first splits image representations of RNA and protein sequences into different

'word' patches known as tokens. Our ensemble attention-like mechanism, the WaveSeeker

block, then aggregates information from each token, forming a kind of genomic signature

allowing the modelling of underlying biological patterns and functional relationships tied to

important outcomes such as the host source. WaveSeekerNet precisely classifies subtypes and

predicts the host source of IAV by using the RNA and protein sequences of the HA and NA gene

segments. Tests on held-out data reveal that WaveSeekerNet achieved state-of-the-art

performance. Furthermore, WaveSeekerNet successfully identified zoonosis, reverse zoonosis,

and enzootic strains.

2   Material and Methods

2.1   Influenza A virus dataset and general workflow

The RNA and protein sequences of the HA and NA segments were downloaded from

EpiFlu GISAID in January and June 2024 [35] along with subtype, host, and other available

metadata. The EpiFlu GISAID database contains numerous identical sequences (Figure 1a). For

example, the HA segment of the avian H5N1 strain *A/goose/Zhejiang/727098/2014* (EPI681274)

is identical to that of the swine H5N1 strain *A/swine/Zhejiang/SW57/2015* (EPI1600724).

Effective deduplication, particularly across different hosts, presents challenges. In this work, we

kept the earliest collected sequence and its associated metadata, based on the inference that this

sequence originated from the initially identified host. Any identical sequences that were

collected at a later time were removed from the analysis. After this step, an additional length and

ambiguity filtering was performed (Figure 1a). The lengths of the HA and NA segments from the

reference strain *A/New York/392/2004* (H3N2 - HA segment: EPI79008, NA segment:

EPI79013) were used as the baselines for identifying sequences that are either too short or too

long. HA or NA sequences with a length at least 80% and at most 120% of the reference and

with a maximum of 10 ambiguous sequence characters were included in the set of high-quality

sequences. Sequences that did not meet either of these criteria were placed into a low-quality

dataset, and if they had an extended minimum length of 1000nt or 350aa (for HA) and 850nt or

250aa (for NA). Otherwise, they were excluded from the analysis (Figure 1a). We screened RNA

sequences in the collected datasets using the VADR (Viral Annotation DefineR) tool [36] and

reverse-complemented any sequences not in the 5' to 3' direction.

To predict future viral characteristics, we temporally split the high-quality and low-

quality sequences. High-quality sequences collected before January 1, 2020, were reserved for

training, while those collected since 2020 were used for evaluating generalization performance

(Figure 1a). This strategy ensured that highly similar strains were not found in training and test

sets. Due to the over-representation of some HA and NA subtypes and the under-representation

of others, we down-sampled over-represented subtypes (defined as having more than 6,000

sequences) to 6,000 sequences per subtype. Examples of over-represented subtypes include H1

(56,593 RNA sequences), H3 (59,661 RNA sequences), N1 (47,592 RNA sequences), and N2

(58,750 RNA sequences). Rare subtypes, defined as having fewer than 600 sequences, were up-

sampled to 600 sequences per subtype. Notably, subtypes H17 (2 sequences), H18 (1 sequence),

N10 (2 sequences), and N11 (1 sequence) are extremely rare and were only included in the

training data (Supplementary Tables S1, S3). Maintaining sequence diversity during training is

crucial to prevent model bias, particularly towards rare subtypes. While the approximately 6,000-

sequence provides sufficient diversity for prevalent subtypes [37], the 600-sequence for rare

subtypes requires up-sampling to mitigate this risk. We performed down-sampling and up-

sampling (copying the original multiple times) using the 'resample' function from scikit-learn

(v.1.5.1). This resulted in a final training set consisting of 18 HA and 11 NA subtypes (classes)

(Figure 1b).

Sequences were also labeled for the host source prediction datasets, according to the

source from which they were isolated. In this work, we grouped sequences into three major host

groups: Humans, Avian (e.g., falcon, turkey, goose), and Non-human Mammals (e.g., swine,

horses, dogs) (Figure 1b). Since the human and avian hosts accounted for the majority of

sequences, these groups were down-sampled to 16,000 sequences per group, while all Non-

human mammal sequences were used. We used the high-quality and low-quality sequences

collected after December 31, 2019, to evaluate the performance of models. We also identified the

subset of strains where both an HA and NA sequence were present and used these sequences

together for host source prediction (Figure 2a and Supplementary Table S5). The data

distribution used in this study is shown in Supplementary Tables S1-5, and Figure 1 illustrates

the major steps in this study.

Figure 1: The general workflow consists of several steps. (a) The IAV sequences used in this study were retrieved
from EpiFlu GISAID. The subtype information of each sequence and the host source information from which each
sequence was obtained were also downloaded. If two or more sequences were identical, only one sequence with the
earliest collection date and associated metadata was retained. Next, the sequences underwent quality control and
binning into training and test sets. (b) The quality-controlled sequences were encoded into the form of images (2D
matrix) using one-hot encoding and Frequency Chaos Game Representation (FCGR). Repeated stratified 10-fold
cross-validation was used to train each model. Two training data resampling strategies were deployed to evaluate the
models: (Strategy A) resampling the pre-2020 training data within each cross-validation fold versus (Strategy B)
resampling the entire pre-2020 training data before cross-validation. High-quality and low-quality independent test
sets were used to assess the overall quality of the trained models. This figure was created with BioRender.

2.2   Transforming sequences into feature vectors

To enable the neural network models to learn and recognize patterns of RNA and protein

sequences, we employed two methods to encode sequences into the form of images: Frequency

Chaos Game Representation (FCGR) and one-hot encoding. The information content within

nucleic acid and protein sequences can be viewed as a signal that can be transformed into an

image and used as input for machine learning algorithms [38–40]. Numerous examples in the

literature have taken the Chaos Game Representation (CGR) approach. In the early 1990s, for

example, the CGR of nucleic acids was used to visualize the structure of DNA sequences [41].

The CGR maps a DNA/RNA sequence   onto the unit square using an algorithm illustrated in

Supplementary Algorithm S1.

An extension of CGR, the FCGR [41–43], subdivides the CGR into a   grid of

sub-squares. Each sub-square corresponds uniquely to a particular k-mer and represents its

number of occurrences (i.e., its frequency) within the original sequence S. Due to variations in

sequence length within the collected data, k-mer frequencies within the FCGRs require

standardization for comparison. To address this, we applied the standardization method proposed

by Wang et al. [44] (Equation 1) to create the standardized FCGR, $\bar{A}$, which was used for our

analysis of IAV RNA sequences. FCGRs were created using the 'complexcgr' package version

0.8.0 (https://github.com/AlgoLab/complexCGR) in a Python 3.12 environment.

197
$$\bar{A} = \frac{4^k}{\sum_{i=1}^{2^k} \sum_{j=1}^{2^k} a_{i,j}} A \qquad (1)$$

where A is the kth-order FCGR of the sequence S, and $a_{i,j}$ denotes the elements of A.

We used one-hot encoding for protein sequences to transform sequences into

representations suitable for machine learning applications. This method has been used

successfully to study influenza viruses, rotavirus A, and rabies lyssavirus and to predict host-

range, antigenic types, and pathogenicity [25,45]. Each character in the protein sequence is

encoded as a 21-dimensional vector via one-hot encoding. The aggregation of these vectors

forms a 2D matrix encoding an amino-acid sequence. For example, A (Alanine) can be encoded

as (1, 0, 0, …, 0, 0, 0), C (Cysteine) as (0, 1, 0, …, 0, 0, 0), D (Aspartate) as (0, 0, 1, …, 0, 0, 0),

and X as (0, 0, 0, …, 0, 0, 1). We zero-padded the C-terminal end of each HA and NA

polypeptide sequence to ensure that the inputs to each deep learning model have the same length.

3   Model Architecture

209 We propose a deep learning network called WaveSeekerNet, as illustrated in Figure 2,

210 which is based on the attention-like architecture [33] and Vision Transformer [46]. Figure 2a

211 presents the overall structure of WaveSeekerNet. The first step of our approach is to split the

212 FCGRs and one-hot encodings of input sequences into 'word' patches (tokens). These 'word'

patches are then flattened and linearly projected using noisy factorized linear layers to create an embedding of each patch [47]. A learnable sinusoidal positional encoding, based on positional encoding in the Transformer model, is then added to according to Equation 2 to create the final embedding [48], where b, n, and d are the batch, token, and hidden (embedding) size, respectively. For multiple channels, WaveSeekerNet concatenates the embeddings along the token dimension. The final embedding is fed to the transformer-like WaveSeeker block (Figure 2b). After passing through the WaveSeeker block, the transformed embeddings are pooled using Global Expectation Pooling [49] and sent to the classification head. Finally, the traditional feed-forward network or the Kolmogorov-Arnold Network (KAN) [50] will perform the classification.

$$ \tag{2} $$

Figure 2: (a) The overall structure of WaveSeekerNet. (b) The WaveSeeker block contains token mixing schemes based on (c) the Fourier Transform, (d) the Wavelet Transform, and (e) gMLP. A modified StarNet (f) that uses an MLP-Mixer layer and noisy factorized linear layers is employed following token mixing. This is followed by an MH-SMoE layer, which processes tokens along the hidden dimension. This figure was created with BioRender.

3.1 WaveSeeker block

The key component of WaveSeekerNet is the WaveSeeker block (Figure 2b). We incorporate significant changes in this block to utilize lessons learned from ensemble approaches. In this study, the attention mechanism [33] is replaced by three token mixing approaches: the Fourier Transform (Figure 2c), the Wavelet Transform (Figure 2d), and the gating Multilayer Perceptron (gMLP) architecture (Figure 2e) [51]. The outputs of these token mixing blocks are concatenated along the hidden dimension and then merged using a modified version of the recently released StarNet [52]. In the StarNet block (Figure 2f), we replace depthwise convolution with an MLP-Mixer layer [53] and apply noisy factorized linear layers [47] before the star operation (element-wise multiplication). To improve the network capacity, the traditional feed-forward layer of Vision Transformer [46] is replaced by a Sparsely Gated Multi-Head Mixture-of-Experts layer (MH-SMoE) [34,54,55].

3.1.1 Fourier Transform block

A significant amount of effort has been directed towards developing alternatives to the self-attention mechanism due to its high computational and memory cost [53,56,57]. Research conducted thus far strongly suggests that algorithms that efficiently share information between tokens are required to develop an efficient alternative to the transformer; one of the first works to identify this approach is the FNET [56]. At the heart of this alternative to the transformer is the Fourier Transform. FNET applies a 2D discrete Fourier Transform (DFT) to the input embeddings. This transform block mixes information from each of the tokens, and during training, the model learns the weights associated with the best combination of tokens that minimizes the loss function. In image processing, the Fast Fourier Transform (FFT) is commonly used to compute the DFT, transforming an image into its frequency domain. Low frequencies

253 represent global patterns, while high frequencies correspond to abrupt changes, such as edges,

254 providing more image details. The 2D DFT and inverse DFT (iDFT) of an image array can be

255 calculated using Equations 3 and 4:

256
$$F(x, y) = \sum_{m=0}^{M-1} \sum_{n=0}^{N-1} f(m, n) e^{-j2\pi(\frac{x}{M}m + \frac{y}{N}n)} \qquad (3)$$

257
$$f(m, n) = \frac{1}{MN} \sum_{x=0}^{M-1} \sum_{y=0}^{N-1} F(x, y) e^{j2\pi(\frac{x}{M}m + \frac{y}{N}n)} \qquad (4)$$

where $F(x, y)$ is the function representing the image in the frequency domain, $f(m, n)$ is a pixel

at position (m, n) in the spatial domain, and $M \times N$ represents the image's dimensions.

In this study, we modified the original FNET architecture [56] to design an additional

token mixing scheme as illustrated in Figure 2c. Tokens are first mixed by applying the 2D DFT

to transform the sequence embedding $E_{fft\_in} \in \mathbb{R}^{b \times n \times d}$ into frequency coefficients. Like

FNET, we only keep the real part of the transform result. Since the FFT of a real signal is

Hermitian-symmetric, we omit the negative frequencies, producing $X_{fft} \in \mathbb{R}^{b \times n \times (d/2+1)}$.

Subsequently, X_{fft} is projected back to the embedding dimension d and reshaped to create

multi-head $X_{MHA} \in \mathbb{R}^{(b*h) \times n \times 32}$, where the number of heads $h = d/32$. We then employ an

efficient attention with linear complexities [57] on X_{MHA} to capture intricate interactions within

the frequency space. The output of this efficient attention mechanism is then enhanced with

dropout, RMS normalization [58], and skip connections, yielding $X_{MHA}^{out} \in \mathbb{R}^{b \times n \times d}$. Next, we

merge heads of X_{MHA}^{out} into $X_{merge} \in \mathbb{R}^{b \times n \times (d/2+1)}$. This merging prepares the representation

for subsequent processing and transformation back into the spatial domain.

Likely, the information needed to reconstruct each embedding from X_{merge} using the

iDFT will be concentrated within the low-frequency components, presenting an opportunity to

promote sparsity and regularize this block of the network. This can be accomplished by applying

a soft-thresholding operation on X_{merge} (Equations 4-6) [59]. Finally, tokens are demixed by

inverse FFT (iFFT), which transforms the thresholded X_{thresh} (Equation 6) back into the spatial

domain $X_{ifft} \in \mathbb{R}^{b \times n \times d}$. X_{ifft} is then scaled so that each element is between +5 and -5, which

is then passed through the feed-forward network, followed by dropout along the token

dimension. Supplementary Algorithm S2 presents the pseudo-code of the Fourier Transform

block.

281
$$X_{shrunk} = X_{merge} - \arctan\left(X_{merge}\right) \qquad (4)$$

282
$$X_{gate} = \{1 \; if \; |X_{shrunk}| - \lambda > 0 \; else \; 0\} \qquad (5)$$

283
$$X_{thresh} = X_{shrunk} * X_{gate} \qquad (6)$$

3.1.2   Wavelet Transform block

While the Fourier Transform captures global frequency information, it does not localize

the frequency within a sequence. The Wavelet Transform can address this shortcoming since this

transformation can identify where frequency components occur within a signal. This capacity is

particularly useful in sequence analysis since biological signals found in nucleic acid and protein

sequences change over time [60]; thus, the Wavelet Transform can be applied to locate relevant

frequency components in local regions of the sequence. In image processing, the discrete

Wavelet Transform (DWT) is used to divide spatial information present in the image into low-

frequency and high-frequency components corresponding to approximation and detail

coefficients, respectively. In the Wavelet Transform, a signal is convolved with bandpass filters

or mother wavelets $\psi_{a,b}(t)$ (Equation 7), where a and b determine the scale and location of the

wavelet, respectively [61,62]. The wavelet will be compressed when the scaling value a

decreases, capturing high-frequency components. In contrast, increasing the scaling value a will

stretch the wavelet and capture low-frequency components. The translational value b shifts the

wavelet in time (or space), allowing us to localize where specific frequency components occur in

the signal.

300
$$\psi_{a,b}(t) = \frac{1}{\sqrt{a}}\psi\left(\frac{t-b}{a}\right) \quad a > 0, \; a \in \mathbb{R}^+, b \in \mathbb{R} \qquad (7)$$

Formally, let $E_{dwt\_in} \in \mathbb{R}^{b \times n \times d}$ be the sequence embedding, we perform initial

projection on E_{dwt_in} and then split the embedding dimension into h heads, where $h = d/32$,

creating initial input $X_{init} \in \mathbb{R}^{b \times h \times n \times 32}$ for the Wavelet Transform. Next, we apply 2D DWT

using the Pytorch Wavelets package version 1.3.0 [63] to transform the input space X_{init} into the

Wavelet coefficients. Concretely, the Wavelet Transform applies low-pass and high-pass filters

to transform X_{init} into Y_L and Y_H subbands. Y_L refers to the approximation coefficients that reflect

the overall structure of the input space at a coarse-grained level. Y_H represents detail coefficients

at a fine-grained level, which is a single stacked tensor of Y_{LH} (horizontal detail), Y_{HL} (vertical

detail), and Y_{HH} (diagonal detail). Rather than employing an efficient attention layer (which was

utilized in the Fourier Transform block), the Wavelet coefficients Y_L and Y_H are processed by

StarNet layers. Like the Fourier Transform block, we apply the skip-connections and RMS

normalization in the Wavelet coefficient space and shrink high-frequency components in the Y_H

subbands using Equations 4-6. The processed Y_L and Y_H are then used to transform feature maps

back into the spatial domain using inverse DWT (iDWT), which is then passed through a feed-

forward network, followed by dropout along the token dimension. Supplementary Algorithm S3

presents the pseudo-code of the Wavelet Transform block.

4 Implementation and evaluation methods

4.1 Model selection, training, and testing

In this study, we compared the prediction performance of WaveSeekerNet with that of established Transformer-only models using the traditional self-attention mechanism. Xu et al. previously employed the Transformer-only models to predict IAV host source and antigenic types [24,64]. These models were among the most effective applications of machine learning algorithms for predicting IAV host source and subtypes. As part of our comparative analysis, we explored the integration of the FNET architecture [56] into the Transformer-only models, replacing the conventional multi-head self-attention mechanism. We also evaluated the performance of the pre-trained ESM-2 models with transfer learning for protein sequences [65]. Table 1 presents the hyperparameter settings used to train deep learning models. We also introduce a new activation function, ErMish (Equation 8), which allows for a greater range of negative activations. This activation function uses a learnable parameter, α, to adjust how positive and negative input values influence the magnitude and sign of the function's output:

$$ErMish(x) = \frac{3x}{2}erf\left(\alpha + \frac{\tanh\left(\ln\left(1 + e^x\right)\right)}{\sqrt{2}}\right) \qquad (8)$$

We trained WaveSeekerNet using a composite loss function (Equation 9). The first part of the composite loss function is the cross-entropy loss function. This function is typically used to measure how much the prediction from the model, $\hat{y}$, deviates from the expected classification outcome, y. The second part of the loss function, the router z-loss, penalizes large logits during routing into the MoE network to force the model to balance the number of tokens routed to each expert. The last part of the loss function encourages the selection of specific activation functions within each of the KAN networks used in the classification head by reducing the impact of

unnecessary activation functions on the final output of the KAN layer [50]. See Supplementary

Algorithms S4 and S5 for details.

$$Loss(y, \hat{y}, x, w) = CE\ Loss(y, \hat{y}) + Z\ Loss(x) + KAN\ Loss(w) \qquad (9)$$

We observed that the Transformer-only models required more converging time than our

model. Therefore, the Transformer-only models were trained with 150 epochs, while

WaveSeekerNet and the pre-trained ESM-2 models were trained with only 35 epochs. We used

repeated stratified 10-fold cross-validation to assess the generalization performance of models

(Figure 1b). The test set within each cross-validation fold was used to check and ensure the

training   process   functioned   properly.   The   early-stopping-pytorch   package

(https://github.com/Bjarten/early-stopping-pytorch), with a patience value set to 7 and a delta of

0.001, was used to determine when the pre-trained ESM-2 models converged and training could

cease. All models were trained on an NVIDIA GPU A100. For model evaluation, the weights of

the last epoch (except for the pre-trained ESM-2 models that use the early stopping strategy)

were used, and the reported scores represent the mean across the 10 folds. Finally, a negative

control is needed for a proper assessment of learning. The dummy classifier from scikit-learn

(v.1.5.1) using a stratified selection strategy was used for this purpose.

We conducted ablation studies to evaluate the impact of different hyperparameters (Table

1) on WaveSeekerNet's performance. We used the baycomp package version 1.0.3

(https://github.com/janezd/baycomp) [66] to compare the generalization performance of

WaveSeekerNet with various hyperparameters. In this work, we performed up-sampling for the

minority classes and down-sampling for the majority classes in the pre-2020 training data during

cross-validation (Strategy A). In this resampling approach, we performed up-sampling for the

sporadic subtypes, which have fewer than 10 sequences, such as H15 (5 protein sequences), H17

(2 sequences), H18 (1 sequence), N10 (2 sequences), and N11 (1 sequence) before cross-

validation. This procedure is necessary to maintain the diversity and the same number of classes

for training data in each cross-validation fold; otherwise, the sporadic subtypes would only be

seen in a single or several folds. We also tested the second scenario of resampling, in which up-

sampling and down-sampling were performed on the entire pre-2020 dataset before cross-

validation (Strategy B). This was done to evaluate how up-sampling and down-sampling impact

bias in predicting host source and subtypes. The 'two_on_single' function in the baycomp

package was used to determine the probability of one scenario being better. To do this, we chose

a region of practical equivalence (ROPE) to be 0.025. This region quantifies the probability that

the overall generalization performance of models of each resampling approach differs by less

than 0.025.

Table 1: The hyperparameter settings used by the WaveSeekerNet, Transformer-only, and pre-trained ESM-2
models during cross-validation.

Model	Hyperparameter Settings	Explanation of Parameters
WaveSeekerNet	Default Settings (Baseline Model): ● *use_fft* = True ● *use_wavelets* = True ● *used_gmlp* = True ● *wavelet_names* = "sym4" ● *emb_dim* = 64 ● *final_hidden_size* = 24 ● *use_kan* = True ● *use_smoe* = True ● *use_gc* = True ● *use_lookahead* = True ● *activation* = ErMish Common Settings: ● *batch size* = 256 ● *epochs* = 35 Settings for FCGR representation of RNA sequences (apply for all hyperparameters, models): ● *k*-mer = 6 (FCGR array size of 64 × 64) ● *patch size* = (4, 4)	● *use_fft* – Specify whether the Fourier Transform block is used in the WaveSeeker block. ● *use_wavelets* – Specify whether the Wavelet Transform block is used in the WaveSeeker block. ● *use_gmlp* – Specify whether the gMLP block is used in the WaveSeeker block. ● *wavelet_names* – Specify the wavelet family for the Wavelet Transform. It will be used when *use_wavelets* = True. ● *emb_dim* – The embedding dimension of the model. ● *final_hidden_size* – The size of the penultimate layer in the classification head. ● *use_kan* – Specify whether the KAN network is used as the classification head. ● *use_smoe* – Specify whether the MH-SMoE network is used in the FFN layer of the WaveSeeker block.

	Settings for one-hot encoding data of protein sequences (apply for all hyperparameters, models): • *patch size* = (3, 21)	• *use_gc* – Specify whether the Gradient Centralization is used in the optimizer [67]. • *use_lookahead* – Specify whether lookahead is used in the optimizer [68]. • *activation* – Specify activation for model (ErMish, Mish [69], GELU [70], ReLU [71]). • *k*-mer – the *k*th-order of FCGR. • *patch size* – size of 'word' patches.
Pre-trained ESM-2 (esm2_t6_8M_UR50D or we called ESM-2_t6 for short)	• *n_layers* = 6 • *emd_dim* = 320 • *batch size* = 64	• *n_layers* – the number of the Transformer encoder layers • *emb_dim* – The embedding dimension of the model.
Pre-trained ESM-2 (esm2_t12_35M_UR50D or we called ESM-2_t12 for short)	• *n_layers* = 12 • *emd_dim* = 480 • *batch size* = 32	• *n_layers* – the number of the Transformer encoder layers • *emb_dim* – The embedding dimension of the model.
Transformer-only using FNET	• *emb_dim* = 64, 128 • *activation* = ReLU • *epochs* = 150 • *batch size* = 256	• *emb_dim* – The embedding dimension of the model.
Transformer-only using conventional multi-head attention (MHA)	• *emb_dim* = 64, 128 • *nhead* = 4 • *activation* = ReLU • *epochs* = 150 • *batch size* = 256	• *emb_dim* – The embedding dimension of the model. • *nhead* – The number of heads in the multi-head attention

4.2   Sequence similarity search methods

We evaluated the performance of deep learning models against BLAST, a widely used sequence similarity search method in computational biology and bioinformatics. Comparisons to the BLAST search served as a sanity check to ensure that our model and other deep learning

methods did not suffer from systemic failures and worked as expected. BLASTp (v2.16.0) [72]

with options '-num_alignments 100 -evalue 1e-5' was used for protein sequence-based subtype

prediction. The BLASTp database was built using the same training splits of the pre-2020 high-

quality dataset used for model training. This was done to ensure that results using sequence

similarity search methods would be comparable. The query is the sequences in the post-2020

high-quality and low-quality test data. The top hit was determined to be the hit with the highest

bit score after filtering for hits with at least 85% identity and an alignment length of at least 50.

We assigned an arbitrary subtype (1-18 for HA subtype, 1-11 for NA subtype) as the prediction

to query sequences without hits.

We used VADR [36], a viral sequence classification and annotation tool for subtype

prediction using RNA sequences. VADR uses a model library from a subset of references to

classify and annotate virus sequences. We used the *v-annotate.pl* VADR script (v1.6.4) with

influenza models (v1.6.3-2) [73] for subtype classification.

4.3   Analysis of the ongoing H5Nx avian influenza outbreak in North America

To investigate WaveSeekerNet's ability to identify the most probable source of a

transmission event, we used data from the ongoing H5Nx avian influenza outbreak in North

America as a test case. We identified a subset of our data consisting of 1,659 unique HA RNA

sequences from various H5Nx strains circulating in North America in 2023 and 2024. These

strains represent a recent snapshot of the ongoing H5Nx avian influenza outbreak. To support the

predictions made by WaveSeekerNet, we performed a phylogenetic analysis of the H5Nx virus

dataset. Sequences were aligned with MAFFT version v7.520 [74,75]. Time-calibrated

phylogenetic analysis was performed in BEAST v1.10.4 [76] using a coalescent Bayesian

skyline model [77,78] and a general time-reversible substitution model with the across-site rate

heterogeneity sampled from a gamma distribution with four discrete categories and an

uncorrelated relaxed log-normal molecular clock [79]. Two independent runs were performed

with a chain length of 50 million generations each, and parameter values were sampled every

1,000 generations. Stationarity and convergence of independent runs were assessed in Tracer

v1.7 [80]. The LogCombiner module in the BEAST software was used to remove the burn-in

fraction and combine the log and tree files. The maximum clade credibility tree with median

node heights was produced using TreeAnnotator [76]. Phylogenetic trees were visualized using

FigTree v.1.4.3 (https://github.com/rambaut/figtree) and Inkscape (https://inkscape.org/).

4.4   Evaluation Metrics

Evaluation metrics used in this study include F1-score (Macro Average), Balanced

Accuracy, and Matthews Correlation Coefficient (MCC). Since the dataset is imbalanced and we

treat all classes equally regardless of their support values, we used the F1-score (Macro Average)

to compare the performance between methods. This metric is computed by taking the arithmetic

mean of the F1-score (Equation 10) of all classes. This measurement approach is appropriate

since we are interested in assessing the performance across the diverse range of IAV subtypes

and host categories in our data.

The equations of F1-score for each class, Balanced Accuracy, and MCC are defined as

follows:

$$F1 - score = \frac{2*TP}{2*TP+FP+FN} \qquad (10)$$

$$Balanced\ Accuracy = \frac{1}{2}\left(\frac{TP}{TP+FN} + \frac{TN}{TN+FP}\right) \qquad (11)$$

$$MCC = \frac{TP*TN-FP*FN}{\sqrt{(TP+FP)(TP+FN)(TN+FP)(TN+FN)}} \qquad (12)$$

where *TP*, *FP*, *TN*, and *FN* stand for True Positive, False Positive, True Negative and False

Negative, respectively.

5   Results

5.1   WaveSeekerNet is robust to changes in hyperparameter settings

We conducted initial ablation studies to evaluate the impact of various hyperparameters,

as illustrated in Table 1, on WaveSeekerNet's performance. For example, we disabled one or two

token mixing schemes and used various activation functions. The experimental results of host

source prediction, presented in Supplementary Tables S6, S7 and Supplementary Figures S1, S2,

S3, demonstrate WaveSeekerNet's robustness to changes in hyperparameter settings under this

testing regime. While some hyperparameter choices did influence performance, the baseline

WaveSeekerNet model consistently demonstrated strong performance. This model of choice,

using all three token mixing schemes (Fourier Transform, Wavelet Transform and gMLP

blocks), ranked at or near the top across various data representations and datasets. When the

baseline model did rank lower, the generalization performance of the alternative models was

often similar to that of the baseline. Our results also show that disabling any of the three token

mixing schemes decreased generalization performance in most RNA sequence tests, while

yielding mixed results in protein sequence tests. Generally, empirical evidence from these tests

indicated that the probability of modifications to the baseline settings is unlikely to improve

classification performance (Supplementary Tables S6, S7).

WaveSeekerNet's performance with the Wavelet Transform block was particularly

impactful when trained on FCGR representation of RNA sequences (Supplementary Table S6

and Supplementary Figures S1a, S1b, S2a, S2b, S3a, S3b). The Wavelet Transform block

improved the WaveSeekerNet's performance significantly. For example, when tested with HA

RNA sequences, using gMLP-only, FFT and gMLP, and FFT-only token mixing schemes,

WaveSeekerNet achieved F1-scores (Macro Average) of 0.737±0.07, 0.824±0.084, and

0.781±0.121, respectively (Supplementary Table S6). While the baseline model (using all three

token mixing schemes), Wavelet Transform-only, Wavelet Transform and gMLP, and FFT and

Wavelet Transform achieved F1-scores (Macro Average) of 0.965±0.015, 0.962±0.033,

0.964±0.014, and 0.969±0.007, respectively.

The Lookahead optimizer was another hyperparameter that influenced generalization

performance. Disabling this optimizer consistently degraded WaveSeekerNet's performance

across various data representations and datasets (Supplementary Tables S6, S7 and

Supplementary Figures S1, S2, S3). For instance, when assessing the host source prediction

using the FCGRs of the HA segment (Supplementary Table S6), the F1-scores (Macro Average)

were 0.867±0.266 and 0.701±0.23 for high-quality and low-quality datasets, respectively, when

the Lookahead optimizer was disabled. In the baseline model, where the Lookahead optimizer is

enabled, the F1-scores (Macro Average) in these tests were 0.965±0.015 and 0.713±0.074,

respectively. Gradient centralization was also important, but primarily impacted results in tests

using FCGRs. Disabling gradient centralization resulted in up to an 11% decrease in F1-score

(Macro Average) (Supplementary Table S6 and Supplementary Figure S1a). Our use of the

ErMish activation positively impacted WaveSeekerNet's performance (Supplementary Tables

S6, S7). Alternative activations, such as Mish, GELU, and ReLU, often had a probability of less

than 0.5 of outperforming the baseline model. Finally, we observed that alternative

configurations, such as disabling KAN and MH-SMoE, negatively impacted generalization

performance. This observation was evident in both RNA and protein sequence datasets, where

the baseline model without KAN or MH-SMoE generally underperformed the baseline model

(Supplementary Tables S6, S7).

5.2   WaveSeekerNet achieves excellent subtype and host source classification using a

parameter-efficient design

WaveSeekerNet also demonstrated a favorable balance between predictive performance

and computational resource requirements. Due to the very high GPU memory requirements of

the pre-trained ESM-2 model, we were restricted to a training batch size of 64 (for the ESM-2_t6

model) or 32 (for the ESM-2_t12 model). Furthermore, this approach demanded significantly

more training time and parameters than WaveSeekerNet and Transformer-only, yet it only

resulted in comparable generalization performance to WaveSeekerNet when tested on the high-

quality protein sequences (Table 2 and Supplementary Table S8). When tested on the low-quality

protein sequences, the performance of the pre-trained ESM-2 models was better than that of the

Transformer-only models. However, the F1-score (Macro Average) of the pre-trained ESM-2

models was up to 46 percentage points lower than WaveSeekerNet's score in these tests. For

example, with HA subtype prediction using the low-quality protein sequences, the ESM-2_t12

model achieved an F1-score (Macro Average) of 0.473, while WaveSeekerNet with FFT-based

head achieved an F1-score (Macro Average) of 0.932 (Table 2). Similarly, WaveSeekerNet with

FFT-based and the ESM-2_t6 model achieved F1-scores (Macro Average) of 0.823 and 0.684,

respectively, for host source prediction using the low-quality protein sequences of the HA

segment (Supplementary Table S8). The FNET and MHA approaches took the least training time

per epoch, but neither method could extract enough information to match the generalization

performance of WaveSeekerNet. Finally, depending on the selected hyperparameters,

WaveSeekerNet's parameter count, and by proxy memory efficiency, can be on the same order

of magnitude as the MHA-based transformer. For example, by only using the FFT-based head or

disabling the KAN network in the classification head, total parameters are reduced by nearly

29% and 50%, respectively (Table 2). Notably, such changes do not meaningfully change the

classification performance on the high-quality protein sequences.

Table 2: Comparison of computational costs and efficiency for the WaveSeekerNet, Transformer-only, and pre-
trained ESM-2 models when trained to predict HA and NA subtypes using protein sequences. For the
WaveSeekerNet models, we show the baseline model with complete options and the modified baseline models using
the fewest parameters.

Segment	Model	Number of Parameters	Training Time/Epoch (s)	F1-score (Macro Average)	
				High-quality	Low-quality
HA	WaveSeekerNet (Baseline)	1,210,264	18.2	0.984±0.009	0.903±0.09
	WaveSeekerNet (FFT-only)	859,837	11.3	0.985±0.011	0.932±0.099
	WaveSeekerNet (No KAN)	606,832	17.5	0.97±0.015	0.846±0.128
	Transformer-FNET-64	19,506	1.0	0.792±0.079	0.207±0.05
	Transformer-FNET-128	52,658	1.16	0.859±0.075	0.27±0.087
	Transformer-MHA-64	292,082	1.51	0.929±0.039	0.379±0.084
	Transformer-MHA-128	612,146	1.67	0.93±0.04	0.38±0.107
	ESM-2_t6	7,542,132	170.1	0.987±0.021	0.451±0.091
	ESM-2_t12	33,563,302	375	0.976±0.025	0.473±0.055
NA	WaveSeekerNet (Baseline)	1,144,454	10	0.999±0.0	0.98±0.035
	WaveSeekerNet (FFT-only)	837,827	7	0.999±0.0	0.968±0.056
	WaveSeekerNet (No KAN)	541,022	9.5	0.999±0.0	0.887±0.161

Transformer-FNET-64	19,275	0.56	0.97±0.021	0.249±0.045
Transformer-FNET-128	52,427	0.63	0.975±0.019	0.236±0.064
Transformer-MHA-64	291,851	0.82	0.965±0.018	0.345±0.138
Transformer-MHA-128	611,915	0.9	0.988±0.011	0.392±0.154
ESM-2_t6	7,541,845	82.3	0.997±0.007	0.674±0.131
ESM-2_t12	33,563,085	175	0.977±0.044	0.622±0.113

5.3 WaveSeekerNet is robust to different up-sampling and down-sampling strategies

Our results showed that the choice of resampling approach has little impact on WaveSeekerNet's ability to generalize in both the subtype and host source prediction tasks. Supplementary Tables S9-12 provide performance and statistical comparison of WaveSeekerNet with various hyperparameters, contrasting two training data resampling strategies. When predicting subtypes and host source using the high-quality independent datasets, the probability that the same type of model will have a mean F1-score (Macro Average) falling within the ROPE is often greater than 90% in the subtype prediction task (Supplementary Tables S9, S10) and usually over 50% in the host prediction task (Supplementary Tables S11, S12). For example, when predicting host source using the high-quality RNA sequences of the HA segment, the baseline model achieved an F1-score (Macro Average) of 0.969±0.008 if up-sampling and down-sampling were performed before cross-validation, versus 0.965±0.015 if they were only performed on each training split (Supplementary Table S11). These two scenarios had a 100% probability of being within the ROPE, indicating that the difference between the two resampling methods is negligible. Similarly, when tested on the high-quality RNA sequences, the baseline

model achieved an F1-score (Macro Average) of 1.0±0.0 for both HA and NA subtype prediction

in both resampling approaches (Supplementary Table S9).

However, generalization performance appeared more likely to differ when the low-

quality independent datasets were used. In these tests, the probability of a difference between the

up-sampling and down-sampling scenarios tends to be higher (over 50%). To assess for a

directionality to this difference (e.g., if resampling is preferred before cross-validation), we

conducted the trinomial test using the mean difference in the F1-score (Macro Average) of each

scenario for each experiment conducted (e.g., HA subtype prediction using the RNA or protein

sequences) [81,82]. After correcting for multiple comparisons using the Benjamini-Hochberg

correction, the test indicated no significant preference in where resampling was applied (p-value

$\geq$ 0.05, Supplementary Table S13). Finally, we analyzed the F1-scores for specific hosts and

subtypes to assess for differences between strategies. Once again, the trinomial test indicated no

significant preference (p-value $\geq$ 0.05, Supplementary Table S14), whether using a ROPE of

0.025 or the stricter ROPE of 0.01.

5.4   WaveSeekerNet can predict Influenza HA and NA subtypes with high accuracy

We compared WaveSeekerNet's performance in predicting HA subtypes with the

Transformer-only models, the pre-trained ESM-2 models, VADR, and BLASTp (Supplementary

Figure S4 and Figure 3). When tested on the high-quality datasets of RNA and protein

sequences, WaveSeekerNet achieved a minimum score of 0.97 across all evaluation metrics and

hyperparameters (Supplementary Figures S4a, S4c), except when the Lookahead hyperparameter

was not used. Disabling the Lookahead optimizer, the WaveSeekerNet only achieved an F1-

score (Macro Average) of 0.872 on the high-quality dataset of RNA sequences. Notably, when

WaveSeekerNet was trained using FCGR representation of RNA sequences (Figures 3a, 3b), it

obtained F1-scores (Macro Average) of 1.0 and 0.998 for high-quality and low-quality datasets,

respectively. In contrast, the Transformer-only models achieved maximum F1-scores (Macro

Average) of 0.849 and 0.404 for high-quality and low-quality datasets of RNA sequences,

respectively. Supplementary Table S15 reports the F1-scores for the specific HA subtypes,

demonstrating WaveSeekerNet's superiority in correctly identifying common and rare HA

subtypes. For example, the H1 ($n_{train} = 56,593$, $n_{test} = 19,599$) and H8 ($n_{train} = 189$,

$n_{test} = 12$) subtypes each achieved an F1-score of 1.0, contributing to WaveSeekerNet's

overall F1-score (Macro Average) of 1.0. When compared with sequence similarity search

methods, WaveSeekerNet's performance was comparable to VADR (Figures 3a, 3b) and

BLASTp (Figures 3c, 3d). Notably, when tested on both high-quality and low-quality datasets of

RNA sequences, VADR produced an F1-score (Macro Average) of 1.0. It is also notable that

although the pre-trained ESM-2 models achieved high performance on the high-quality protein

sequences (Figure 3c), WaveSeekeNet still significantly outperformed them when tested on the

low-quality protein sequences (Figure 3d).

Figure 3: Performance comparison of HA subtype prediction when the best-performing WaveSeekerNet, pre-
trained ESM-2, and Transformer-only models are tested. The performance of the baseline WaveSeekerNet is also
shown as a point of reference. The bar plots of Balanced Accuracy, F1-score (Macro Average), and MCC are
reported for the high-quality (a) and low-quality (b) FCGR representations of RNA sequences. The bar plots of
scores for tests on the datasets constructed from high-quality and low-quality one-hot encoded protein sequences are
reported in panels (c) and (d), respectively. Horizontal dashed lines present the F1-scores (Macro Average) for
VADR and BLASTp. The WaveSeekerNet, pre-trained ESM-2, and Transformer-only models are labeled in Black,
Orange, and Blue, respectively.

When classifying NA subtypes (Supplementary Figures S5, S6), the results mirrored the

strong performance observed in HA subtype prediction. WaveSeekerNet achieved a minimum

score of 0.995 across all evaluation metrics and hyperparameters on the high-quality datasets of

RNA and protein sequences (Supplementary Figures S5a, S5c), except when the Lookahead

hyperparameter was not used. Disabling the Lookahead optimizer, WaveSeekerNet only

achieved an F1-score (Macro Average) of 0.818 on the high-quality dataset of RNA sequences

(Supplementary Figure S5a). WaveSeekerNet also obtained an F1-score (Macro Average) of 1.0

on the high-quality dataset of RNA sequences, while the Transformer-only models achieved a

maximum F1-score (Macro Average) of 0.966 (Supplementary Figure S6a). Supplementary

Table S16 reports the F1-scores for the specific NA subtypes. Similarly to the HA subtype

classification, both prevalent and rarer subtypes were accurately identified by WaveSeekerNet.

For example, the F1-score for N2 ($n_{train} = 58{,}750$, $n_{test} = 23{,}671$) and N4 ($n_{train} = 347$,

$n_{test} = 41$) was 1.0, contributing to WaveSeekerNet's overall F1-score (Macro Average) of 1.0.

When tested on the low-quality datasets of RNA and protein sequences, the Transformer-only

models still performed the worst, with maximum F1-scores (Macro Average) of 0.728 and 0.392,

respectively (Supplementary Figures S6b, S6d). In contrast, WaveSeekerNet maintained an F1-

score (Macro Average) of 0.939, underperforming VADR, and a score of 0.998, outperforming

BLASTp, when tested on the low-quality datasets of RNA and protein sequences, respectively.

As expected, the performance of the dummy classifier was essentially random in each subtype

prediction task. For example, using the high-quality RNA sequences, the dummy classifier

achieved an F1-score (Macro Average) of 0.066 with NA subtype prediction.

5.5   WaveSeekerNet accurately identifies the host source using influenza A virus

consensus sequences

Figures 4 and 5 show the comparisons between the best-performing WaveSeekerNet, pre-

trained ESM-2, and Transformer-only models in predicting host source when tested on the HA

segment and the combined HA and NA segments. We also evaluated the performance of the pre-

trained ESM-2 model for host source prediction, using the protein sequences of the combined

HA and NA segments (Figures 5c, 5d). Owing to the substantial GPU memory demands of the

pre-trained ESM-2, particularly with this 2-channel configuration, the test was restricted to the

ESM-2_t6 model, employing a training batch size of 32. When tested on the high-quality

datasets of the HA segment, the best-performing WaveSeekerNet models achieved F1-scores

(Macro Average) of 0.969 and 0.962 for RNA and protein sequences, respectively (Figures 4a,

4c). In contrast, the Transformer-only models achieved maximum F1-scores (Macro Average) of

0.917 and 0.916 for RNA and protein sequences, respectively. However, when evaluated on the

high-quality datasets of the combined HA and NA segments (Figures 5a, 5c) and the NA

segment (Supplementary Figures S7a, S7c), the best-performing Transformer-only models were

comparable to WaveSeekerNet. The pre-trained ESM-2 models also achieved the same

performance level as WaveSeekerNet for host source prediction using the high-quality protein

sequences (Figures 4c, 5c, and Supplementary Figure S7c). The performance of the dummy

classifier was essentially random, achieving an F1-score (Macro Average) of 0.267 when tested

with the RNA sequences of the HA segment.

A substantial difference in performance was observed when evaluating the low-quality

datasets derived from protein sequences. WaveSeekerNet significantly surpassed the

performance of the Transformer-only models by up to 44% in terms of F1-score (Macro

Average) and by up to 67% in terms of MCC on the combined HA and NA segments (Figure 5d)

and the HA segment (Figure 4d). The pre-trained ESM-2 models were significantly better than

the Transformer-only models, but still lagged behind WaveSeekerNet (Figures 4d, 5d).

Figure 4: Performance comparison of host source prediction using the HA segment when the best-performing
WaveSeekerNet, pre-trained ESM-2, and Transformer-only models are tested. The performance of the baseline
WaveSeekerNet is also shown as a point of reference. The bar plots of Balanced Accuracy, F1-score (Macro
Average), and MCC are reported for the high-quality (a) and low-quality (b) FCGR representations of RNA
sequences. The bar plots of scores for tests on the datasets constructed from high-quality and low-quality one-hot
encoded protein sequences are reported in panels (c) and (d), respectively. The WaveSeekerNet, pre-trained ESM-2,
and Transformer-only models are labeled in Black, Orange, and Blue, respectively.

Figure 5: Performance comparison of host source prediction using the combined HA and NA segments (2 channels) when the best-performing WaveSeekerNet, pre-trained ESM-2, and Transformer-only models are tested. The performance of the baseline WaveSeekerNet is also shown as a point of reference. The bar plots of Balanced Accuracy, F1-score (Macro Average), and MCC are reported for the high-quality (a) and low-quality (b) FCGR representations of RNA sequences. The bar plots of scores for tests on the datasets constructed from high-quality and low-quality one-hot encoded protein sequences are reported in panels (c) and (d), respectively. The WaveSeekerNet, pre-trained ESM-2, and Transformer-only models are labeled in Black, Orange, and Blue, respectively.

5.6   Host prediction discrepancies can carry important information about recent transmission events.

In the previous sections, we demonstrated that WaveSeekerNet can accurately predict

subtypes and host sources. Prediction discrepancies were noted and likely carry important

information concerning recent transmission events since they imply that the extracted consensus

sequence signature more closely resembles the signature from a different host. WaveSeekerNet

produced multiple lines of evidence to support this hypothesis. For example, two H5N1 IAVs,

A/CastillaLaMancha/3739/2022   (EPI_ISL_15542438)   and   *A/CastillaLaMancha/3869/2022*

(EPI_ISL_16813290), were isolated in humans but were classified as having an avian origin by

WaveSeekerNet. Upon further investigation, we found that the Spanish Influenza National

Reference Laboratory (NRL) linked these samples to an outbreak from a poultry farm where

workers were likely infected by hens [83]. In another case, our approach identified the HA and NA genes from a sample *A/China/ZMD-22-2/2022* (EPI_ISL_15613648) as having an avian origin. This was the case since this strain is nested within clades of H3 and N8 genes isolated from ducks and other waterfowl [84]. In another instance, a sample isolated in March 2024, *A/Vietnam/KhanhhoaRV1-005/2024* (EPI_ISL_19031556), was correctly identified by WaveSeekerNet as having an avian origin. Contact tracing and viral characterization revealed that the 21-year-old man from Khanh Hoa Province, Vietnam, was exposed to wild birds and subsequently infected with an H5N1 avian influenza virus [85,86].

In addition, our results suggest that discrepancies can identify reverse zoonotic transmission events. For example, our model classified *A/swine/North Carolina/A02751330/2022* (EPI_ISL_16891306), *A/swine/Ohio/A02751292/2022* (EPI_ISL_16891307), *A/swine/Cambodia/PFC37/2021* (EPI_ISL_17885993), and *A/swine/Cambodia/PFC33/2020* (EPI_ISL_17886005) as human sequences. These discrepancies could be interpreted as these strains containing a genomic signature resembling other human sequences. Subsequent phylogenetic analyses and molecular characterization demonstrated that these sequences are closely related to those circulating in nearby human populations, suggesting a human-to-swine transmission event [87,88]. Supplementary Tables S17-19 provide additional details of discrepancies identified by our model.

5.7 WaveSeekerNet flags spillover events from the ongoing H5Nx avian influenza outbreak in North America

WaveSeekerNet successfully identified the most probable animal source of transmission in 1,659 sequences collected from the ongoing H5Nx avian influenza outbreak in North America. The model predicted that 100% of the sequences were of avian origin. For example,

infections of mammals with the HPAI clade 2.3.4.4b H5N1, H5N5 viruses were recently

detected [14,15,89]. These include H5N5 cases collected in Canada (e.g., *A/Raccoon/PEI/FAV-*

0199-1/2023 and *A/Striped_Skunk/PEI/FAV-0210-1/2023)*, H5N1 cases in dairy cows in the

United States (e.g., *A/dairy_cow/Colorado/24_018028-008/2024* and

A/dairy_cow/Colorado/24_018028-013/2024). Furthermore, a phylogenetic analysis supported

the predictions for other H5N1 cases (e.g., humans, cats, dairy cows, goats, and swine). This

analysis revealed that these samples are nested within avian sub-clades (Figure 6). Additionally,

the collection sites of these samples are within the same geographical areas, providing additional

evidence for a relationship between the avian strains and closely related strains isolated from

non-avian hosts. Details of the sequences and predictions made by WaveSeekerNet are available

in Supplementary Table S20.

Figure 6: Pruned time-calibrated phylogeny of 1,659 HA RNA sequences collected from the ongoing H5Nx
outbreak in North America. Different spillover events into mammalian hosts are highlighted in blue, orange, and
green. WaveSeekerNet identified these strains as having an avian origin, a discrepancy supported by the
phylogenetic analysis. Bars at the nodes indicate the 95% highest posterior density of the estimated node dates.

676
677

6   Discussion

This work presents a transformer-like architecture, WaveSeekerNet, inspired by ensemble learning, which can sufficiently capture and generalize information found in relatively simple sequence transformations and encodings, into a coherent internal representation of human, avian or non-human mammal-adapted IAV irrespective of subtype. The exceptional accuracy of WaveSeekerNet in predicting IAV subtypes and host source in both high-quality and low-quality test data underscores the role modern deep learning can play in rapid and effective influenza surveillance and characterization: especially with human activities such as hunting, agriculture, movement, and urbanization dramatically increasing interactions between humans and animal populations, subsequently increasing the risk of zoonotic transmission [90,91]. This increase in transmission risk is best exemplified by the emergence of the 2009 H1N1 IAV pandemic, which was a triple reassortant virus between human, avian, and swine strains [92], and the recent emergence of SARS-CoV-2 virus, which was associated with wildlife sold at the Huanan seafood market in Wuhan, China [93].

The approach presented here is advantageous since WaveSeekerNet was trained using simple sequence transformations and encodings. Simple transformations are effective since they are well studied and their applicability to problems such as these is known [25,38,39,45]. By utilizing these transformation methods, we can have greater confidence that any observed improvements can be attributed to our architectural choices rather than a lightly investigated and poorly understood choice of transformation. For example, the frequency of specific k-mers and codon pairs was found to be important for classifying potential hosts of H3Nx viruses [23]. Depending on the depth of the FCGR, these frequencies and features are natural features of the representation. Furthermore, by using the FCGR, we can also capture the unique fractal

properties within the genome [43,94,95]. Together, this allows the model to learn from an

information-dense set of features, which we demonstrate with our exceptional performance in

subtype and host source prediction. Finally, since these transformations can be created by

applying existing tools and do not require specialized knowledge, the workflow needed to run an

analysis is greatly simplified. This is a critical requirement in diagnostic settings where the

generation of accurate and reproducible reports for a timely and effective response to a disease

outbreak is needed.

To test the efficacy of the different models, we used time-based data partitioning. This is

a departure from the more traditional approach of random data partitioning that allows us to

estimate the performance of a model better, since new viral strains are constantly emerging over

time. Time-based data partitioning, therefore, can potentially minimize the likelihood of

generating overly optimistic predictions since there is more novelty in the validation data due to

the combined effect of antigenic drifts and shifts, exemplified by the emergence of novel

reassortants with increased fitness in the H5Nx avian influenza outbreak in North America

[14,96]. Generalizing when trained on imbalanced data is also important because recognizing

rarer, emerging variants is essential for successful viral surveillance and characterization, which

in turn informs public health responses. Often, this information is discarded, or analyses do not

fully consider information from rarer variants and noisy data. This can potentially result in an

overestimation of generalization performance. For example, Xu et al. considered rare subtypes

(e.g., H15, H17, H18, N10, and N11) together as a single group when testing their Transformer-

only models and used a weighted one-vs-all strategy to produce F1-scores [24,64]. However, this

strategy is biased towards good performance in the majority classes and, as we show, can result

in overly optimistic performance scores (Supplementary Tables S15, S16). Alternatively, up-

sampling and down-sampling of under-represented and over-represented classes can be used to

work with highly imbalanced data. Different biases can be introduced depending on where up-

sampling and down-sampling occur, and the results can be overly optimistic towards minority

classes [97]. In our experiments, WaveSeekerNet appears robust to different up-sampling and

down-sampling strategies since the choice in strategy is unlikely to result in large differences in

generalization performance. The ability to generalize patterns found in noisy, imbalanced data

that evolves through time is vital in real-world scenarios since information is often missing.

Approaches, such as those adopted in WaveSeekerNet, which are better at extracting key

information from this type of data, can enhance the ability of public health authorities to detect

and properly respond to outbreaks caused by emerging or rare strains.

WaveSeekerNet is an alternative to traditional tools used in bioinformatics, such as

VADR. While robust, VADR's performance is tied to the quality of underlying reference models

and databases. Adapting VADR for novel subtypes typically requires highly trained experts since

their input is necessary to update the reference models, databases, and underlying processes.

WaveSeekerNet, on the other hand, learns to extract and use relevant features from the training

data without expert guidance. The resulting model can then be used as part of an end-to-end

process starting with consensus sequences and ending with viral subtypes and host source

prediction. This is particularly advantageous when data is diverse and/or noisy. For example, our

tests using low-quality datasets have demonstrated that it is possible to use deep learning to

accurately predict viral subtypes and host source in diverse and noisy real-world datasets. This

can save time and resources in analyzing degraded samples, which can be reallocated towards

annotating and investigating truly interesting or problematic cases. While WaveSeekerNet

requires retraining with new data so that novel subtypes are accounted for, it may be possible to

streamline this process using recent advances in transfer learning and model fine-tuning

[65,98,99].

WaveSeekerNet presents a compelling alternative to models that use the traditional self-

attention mechanism. This advantage stems directly from WaveSeekerNet's balancing of

computational costs and excellent predictive performance. Depending on the choice of

hyperparameters, WaveSeekerNet's parameter count can be even less than that of the more

commonly used multi-head self-attention-based model. This highlights another key advantage of

WaveSeekerNet: it can be a scalable and flexible alternative for viral classification and host

source prediction. Specifically, WaveSeekerNet can be trained using off-the-shelf consumer

parts within a reasonable amount of time, meaning it can be used widely and, depending on the

hyperparameter choices, without a high-performance cluster. More importantly, we show that a

relatively simple approach, when compared to large pre-trained models such as ESM-2, can be

efficiently used to develop classification models for medically relevant pathogens.

WaveSeekerNet's ability to accurately classify host source, even when trained on diverse

subtypes, suggests that the model is learning underlying genomic signatures linked to host

adaptation and subtype. This is best exemplified by our model's ability to accurately identify the

correct subtype and host source in temporally separated data. Furthermore, we provide evidence

that discrepancies between prediction and known host source likely indicate higher similarity

with genome signatures from another host. This could mean that viruses have had limited time to

evolve within and adapt to a new host. For example, our phylogenetic analysis of IAVs

associated with the ongoing H5Nx outbreak in North America reveals that the genomic signature

found in sequences in non-human mammals is very similar to that of circulating avian strains,

suggesting a recent introduction into the non-human mammal group. This observation is likely

influenced by the fact that influenza viruses tend to accumulate mutations over time that

optimize their fitness within a particular host species, leading to distinct genomic signatures

associated with different hosts (e.g., avian, swine, humans) [100–102]. Therefore, if a virus

jumps to a new host and retains a signature similar to its previous host, it suggests the jump was

recent and there has not been sufficient time for the virus to undergo the extensive mutations

needed to adapt fully to the new host environment.

WaveSeekerNet's design is based on an ensemble attention-like mechanism that

involves splitting viral sequences into 'word' patches and mixing them. This process allows the

model to develop an internal representation of each class and leverages this representation to

make predictions. Further work is needed to identify 'word' patches strongly impacting

predictions, which can reveal important sequence properties underpinning viral adaptation and

transmission in new hosts. This could be achieved by using Explainable AI (XAI) techniques,

like SHAP (SHapley Additive exPlanations) [103], which measure how impactful a feature is on

the output of a trained model. In this work, 'word' patches with high SHAP values can be

interpreted as specific genetic determinants of host adaptation. Previously, SHAP values were

used to find specific mutations in the genome of SARS-CoV-2 potentially associated with

adaptation in deer and mink hosts [19]. While a similar approach can be taken here, additional

care must be taken to understand how much each feature's SHAP value changes with different

initial parameterizations of WaveSeekerNet. Therefore, an optimal strategy that identifies

maximally relevant features inextricably involves minimizing the impact of noise arising from

differences in the initial state of WaveSeekerNet. Once found, the insights revealed using these

tools could deepen our understanding of viral evolution and biology in novel hosts and provide a

secondary, independent source of evidence to support and complement traditional phylogenetic

analyses and experimentation using animal models.

To enhance the robustness and capacity of our model, we incorporated some new ideas

that yielded promising results. For example, replacing the traditional feed-forward network

within the WaveSeeker block with the MH-SMoE network led to a demonstrable improvement

in the performance of WaveSeekerNet. This work also demonstrated the potential of the KAN

network, a recently developed alternative to traditional feed-forward networks, in improving the

identification of biological sequences in most tests. The applicability of KAN and MH-SMoE

networks extends beyond the identification and characterization of IAV, and we believe that

these approaches can be effectively applied to broader taxonomic identification problems such as

assigning taxonomic labels (e.g., species, genus, family) to DNA and RNA sequences generated

by high-throughput sequencing technologies. While the baseline WaveSeekerNet model has

exhibited strong performance, the impact of specific hyperparameters, such as the Wavelet

Transform block, KAN, MH-SMoE, optimizer, and the choice of activation functions, highlights

the importance of careful model design and hyperparameter tuning. Future work should focus on

refining these hyperparameters and further exploring additional architectural enhancements to

improve WaveSeekerNet's accuracy and generalizability. Moreover, incorporating XAI

techniques is essential to better understand the model's decision-making processes, ultimately

facilitating more effective model refinement and optimization.

WaveSeekerNet represents an advancement in applying deep learning for influenza virus

classification and host source prediction. Its accuracy, efficiency, and potential for revealing

novel biological insights position it as a valuable tool for future influenza surveillance and

pandemic preparedness. We will integrate WaveSeekerNet into CFIA-NCFAD/nf-flu

(https://github.com/CFIA-NCFAD/nf-flu) [104], an existing IAV analysis workflow at the

Canadian Food Inspection Agency (CFIA) - National Centre for Foreign Animal Disease

(NCFAD), which houses the World Organization for Animal Health reference laboratory for

avian influenza. This integration will enable a more comprehensive analysis of IAV, ultimately

contributing to enhanced Canadian and global IAV surveillance and pandemic preparedness.

Furthermore, our work highlights the crucial role of deep learning in analyzing medically

important data, such as genomic sequences and clinical records, derived from a wide spectrum of

viral pathogens. This includes not only influenza virus, with its seasonal and pandemic potential,

but also other viruses posing significant public health threats like rotavirus and SARS-CoV-2.

The power of deep learning in this context stems from its ability to discover subtle, long-range

patterns within complex and diverse datasets, leading to demonstrably improved prognostic

accuracy in predicting disease severity, treatment response, or outbreak trajectories [105,106].

Given these capabilities, we foresee the broad application of WaveSeekerNet to other high-

consequence viruses such as rotavirus and SARS-CoV-2, potentially aiding in rapid surveillance

and outbreak prevention.

7   Limitations and Future Work

While this study presents a significant advancement in IAV prediction, there are

limitations to address in future research:

• *Explainable AI*: Using explainable AI approaches would enhance the

interpretability of WaveSeekerNet's predictions, providing insights into the

specific sequence features driving its classifications. This would also provide

mutations associated with host prediction that could be verified experimentally.

• *Complex Transformations*: Exploring more complex input transformations,

incorporating amino-acid properties, could further improve the model's ability to

capture subtle differences between strains and hosts.

• *Species-Level Breakdown*: Expanding host source prediction to a species-level

breakdown within avian and non-human mammals would offer more granular

insights for targeted surveillance and control measures.

By addressing these limitations, future iterations of WaveSeekerNet can provide even

more powerful tools for understanding and combating IAV.

Figure Legends

Figure 1: The general workflow consists of several steps. (a) The IAV sequences used in this study were retrieved
from EpiFlu GISAID. The subtype information of each sequence and the host source information from which each
sequence was obtained were also downloaded. If two or more sequences were identical, only one sequence with the
earliest collection date and associated metadata was retained. Next, the sequences underwent quality control and
binning into training and test sets. (b) The quality-controlled sequences were encoded into the form of images (2D
matrix) using one-hot encoding and Frequency Chaos Game Representation (FCGR). Repeated stratified 10-fold
cross-validation was used to train each model. Two training data resampling strategies were deployed to evaluate the
models: (Strategy A) resampling the pre-2020 training data within each cross-validation fold versus (Strategy B)
resampling the entire pre-2020 training data before cross-validation. High-quality and low-quality independent test
sets were used to assess the overall quality of the trained models. This figure was created with BioRender.

Figure 2: (a) The overall structure of WaveSeekerNet. (b) The WaveSeeker block contains token mixing schemes
based on (c) the Fourier Transform, (d) the Wavelet Transform, and (e) gMLP. A modified StarNet (f) that uses an
MLP-Mixer layer and noisy factorized linear layers is employed following token mixing. This is followed by an
MH-SMoE layer, which processes tokens along the hidden dimension. This figure was created with BioRender.

Figure 3: Performance comparison of HA subtype prediction when the best-performing WaveSeekerNet, pre-
trained ESM-2, and Transformer-only models are tested. The performance of the baseline WaveSeekerNet is also
shown as a point of reference. The bar plots of Balanced Accuracy, F1-score (Macro Average), and MCC are
reported for the high-quality (a) and low-quality (b) FCGR representations of RNA sequences. The bar plots of
scores for tests on the datasets constructed from high-quality and low-quality one-hot encoded protein sequences are
reported in panels (c) and (d), respectively. Horizontal dashed lines present the F1-scores (Macro Average) for
VADR and BLASTp. The WaveSeekerNet, pre-trained ESM-2, and Transformer-only models are labeled in Black,
Orange, and Blue, respectively.

Figure 4: Performance comparison of host source prediction using the HA segment when the best-performing
WaveSeekerNet, pre-trained ESM-2, and Transformer-only models are tested. The performance of the baseline
WaveSeekerNet is also shown as a point of reference. The bar plots of Balanced Accuracy, F1-score (Macro
Average), and MCC are reported for the high-quality (a) and low-quality (b) FCGR representations of RNA
sequences. The bar plots of scores for tests on the datasets constructed from high-quality and low-quality one-hot
encoded protein sequences are reported in panels (c) and (d), respectively. The WaveSeekerNet, pre-trained ESM-2,
and Transformer-only models are labeled in Black, Orange, and Blue, respectively.

Figure 5: Performance comparison of host source prediction using the combined HA and NA segments (2 channels) when the best-performing WaveSeekerNet, pre-trained ESM-2, and Transformer-only models are tested. The performance of the baseline WaveSeekerNet is also shown as a point of reference. The bar plots of Balanced Accuracy, F1-score (Macro Average), and MCC are reported for the high-quality (a) and low-quality (b) FCGR representations of RNA sequences. The bar plots of scores for tests on the datasets constructed from high-quality and low-quality one-hot encoded protein sequences are reported in panels (c) and (d), respectively. The WaveSeekerNet, pre-trained ESM-2, and Transformer-only models are labeled in Black, Orange, and Blue, respectively.

Figure 6: Pruned time-calibrated phylogeny of 1,659 HA RNA sequences collected from the ongoing H5Nx outbreak in North America. Different spillover events into mammalian hosts are highlighted in blue, orange, and green. WaveSeekerNet identified these strains as having an avian origin, a discrepancy supported by the phylogenetic analysis. Bars at the nodes indicate the 95% highest posterior density of the estimated node dates.

Additional Files

Figure S1: The generalization performance of WaveSeekerNet for host source prediction was evaluated on the HA segment using various hyperparameter settings. The Balanced Accuracy, F1-score (Macro Average), and MCC are reported for high-quality (a) and low-quality (b) FCGR representations of RNA sequences. Scores for tests on the datasets constructed from high-quality and low-quality one-hot encoded protein sequences are reported in panels (c) and (d), respectively.

Figure S2: The generalization performance of WaveSeekerNet for host source prediction was evaluated on the NA segment using various hyperparameter settings. The Balanced Accuracy, F1-score (Macro Average), and MCC are reported for high-quality (a) and low-quality (b) FCGR representations of RNA sequences. Scores for tests on the datasets constructed from high-quality and low-quality one-hot encoded protein sequences are reported in panels (c) and (d), respectively.

Figure S3: The generalization performance of WaveSeekerNet for host source prediction was evaluated on the combined HA and NA segments (2 channels) using various hyperparameter settings. The Balanced Accuracy, F1-score (Macro Average), and MCC are reported for high-quality (a) and low-quality (b) FCGR representations of RNA sequences. Scores for tests on the datasets constructed from high-quality and low-quality one-hot encoded protein sequences are reported in panels (c) and (d), respectively.

Figure S4: The generalization performance of WaveSeekerNet and Transformer-only for HA subtype prediction using various hyperparameter settings. The Balanced Accuracy, F1-score (Macro Average), and MCC are reported for high-quality (a) and low-quality (b) FCGR representations of RNA sequences. Panels (c) and (d) show scores for high-quality and low-quality one-hot encoded protein sequences, respectively. The WaveSeekerNet and Transformer-only models using various hyperparameter settings are labeled in Black and Blue, respectively. The F1-scores (Macro Average) for VADR and BLASTp are shown as red horizontal dashed lines.

Figure S5: The generalization performance of WaveSeekerNet and Transformer-only for NA subtype prediction using various hyperparameter settings. The Balanced Accuracy, F1-score (Macro Average), and MCC are reported for high-quality (a) and low-quality (b) FCGR representations of RNA sequences. Panels (c) and (d) show scores for high-quality and low-quality one-hot encoded protein sequences, respectively. The WaveSeekerNet and Transformer-only models using various hyperparameter settings are labeled in Black and Blue, respectively. The F1-scores (Macro Average) for VADR and BLASTp are shown as red horizontal dashed lines.

Figure S6: Performance comparison of NA subtype prediction when the best-performing WaveSeekerNet, pre-trained ESM-2, and Transformer-only models are tested. The performance of the baseline WaveSeekerNet is also shown as a point of reference. The bar plots of Balanced Accuracy, F1-score (Macro Average), and MCC are reported for the high-quality (a) and low-quality (b) FCGR representations of RNA sequences. The bar plots of scores for tests on the datasets constructed from high-quality and low-quality one-hot encoded protein sequences are reported in panels (c) and (d), respectively. Horizontal dashed lines present the F1-scores (Macro Average) for VADR and BLASTp. The WaveSeekerNet, pre-trained ESM-2, and Transformer-only models are labeled in Black, Orange, and Blue, respectively.

Figure S7: Performance comparison of host source prediction using the NA segment when the best-performing WaveSeekerNet, pre-trained ESM-2, and Transformer-only models are tested. The performance of the baseline WaveSeekerNet is also shown as a point of reference. The bar plots of Balanced Accuracy, F1-score (Macro Average), and MCC are reported for the high-quality (a) and low-quality (b) FCGR representations of RNA sequences. The bar plots of scores for tests on the datasets constructed from high-quality and low-quality one-hot encoded protein sequences are reported in panels (c) and (d), respectively. The WaveSeekerNet, pre-trained ESM-2, and Transformer-only models are labeled in Black, Orange, and Blue, respectively.

Table S1: The data distribution of HA subtypes.

Table S2: The data distribution of HA sequences used for host source prediction.

Table S3: The data distribution of NA subtypes.

Table S4: The data distribution of NA sequences used for host source prediction.

Table S5: The data distribution of the combined HA and NA sequences used for host source prediction.

Table S6: The experimental results of host source prediction when testing the trained WaveSeekerNet using FCGR representation of RNA sequences.

Table S7: The experimental results of host source prediction when testing the trained WaveSeekerNet using one-hot encoding representation of protein sequences.

Table S8: Comparison of computational costs and efficiency for the WaveSeekerNet, Transformer-only, and pre-trained ESM-2 models when they were trained to predict host source using protein sequences of the HA and NA segments. For the WaveSeekerNet models, we show the baseline model with complete options and the modified baseline models using the fewest parameters.

Table S9: Performance and statistical comparison of WaveSeekerNet with various hyperparameters, contrasting two training data resampling strategies: (A) resampling training data within each cross-validation fold, (B) resampling the entire training data before cross-validation. The table provides F1-scores (Macro Average) for subtype prediction when testing the trained model using the high-quality and low-quality independent RNA sequences. The probabilities were computed using the Bayesian correlated t-test. A region of practical equivalence (ROPE) of 0.025 was used to quantify the probability that the overall generalization performance of models of each resampling approach differs by less than 0.025.

Table S10: Performance and statistical comparison of WaveSeekerNet with various hyperparameters, contrasting two training data resampling strategies: (A) resampling training data within each cross-validation fold, (B) resampling the entire training data before cross-validation. The table provides F1-scores (Macro Average) for subtype prediction when testing the trained model using the high-quality and low-quality independent protein sequences. The probabilities were computed using the Bayesian correlated t-test. A region of practical equivalence (ROPE) of 0.025 was used to quantify the probability that the overall generalization performance of models of each resampling approach differs by less than 0.025.

Table S11: Performance and statistical comparison of WaveSeekerNet with various hyperparameters, contrasting two training data resampling strategies: (A) resampling training data within each cross-validation fold, (B) resampling the entire training data before cross-validation. The table provides F1-scores (Macro Average) for host source prediction when testing the trained model using the high-quality and low-quality independent RNA sequences. The probabilities were computed using the Bayesian correlated t-test. A region of practical equivalence (ROPE) of 0.025 was used to quantify the probability that the overall generalization performance of models of each resampling approach differs by less than 0.025.

Table S12: Performance and statistical comparison of WaveSeekerNet with various hyperparameters, contrasting two training data resampling strategies: (A) resampling training data within each cross-validation fold, (B) resampling the entire training data before cross-validation. The table provides F1-scores (Macro Average) for host source prediction when testing the trained model using the high-quality and low-quality independent protein sequences. The probabilities were computed using the Bayesian correlated t-test. A region of practical equivalence (ROPE) of 0.025 was used to quantify the probability that the overall generalization performance of models of each resampling approach differs by less than 0.025.

Table S13: The two-tailed trinomial test results for each classification task using the high-quality and low-quality datasets. After applying the Benjamini-Hochberg correction for multiple comparisons, the tests indicated no significant preference regarding where resampling was applied.

Table S14: The two-tailed trinomial test results for each classification task for specific subtypes and hosts using the high-quality and low-quality datasets. Asterisks (*) indicate the absence of data for specific subtypes and hosts in the test sets. After applying the Benjamini-Hochberg correction for multiple comparisons, the tests indicated no significant preference regarding where resampling was applied.

Table S15: The report of HA subtype-specific performance when testing models using FCGR representation of RNA sequences. The F1-scores were obtained using the best-performing WaveSeekerNet and Transformer-only models. Models were trained to recognize the 18 HA subtypes (18 classes in the training data). Asterisks (*) indicate the absence of data for specific subtypes in the testing datasets. For these subtypes, we report an F1-score of N/A. F1-scores were calculated after 10 cross-validation folds and are presented for both high-quality and low-quality datasets.

Table S16: The report of NA subtype-specific performance when testing models using FCGR representation of RNA sequences. The F1-scores were obtained using the best-performing WaveSeekerNet and Transformer-only models. Models were trained to recognize the 11 NA subtypes (11 classes in the training data). Asterisks (*) indicate the absence of data for specific subtypes in the testing datasets. For these subtypes, we report an F1-score of N/A. F1-scores were calculated after 10 cross-validation folds and are presented for both high-quality and low-quality datasets.

Table S17: The report of host discrepancies identified by WaveSeekerNet when testing on the HA segment.

Table S18: The report of host discrepancies identified by WaveSeekerNet when testing on the NA segment.

Table S19: The report of host discrepancies identified by WaveSeekerNet when testing on the combined HA and NA segments.

Table S20: The report of host source identified by WaveSeekerNet when testing on 1,659 HA RNA sequences from the ongoing H5Nx outbreak in North America.

Algorithm S1: An algorithm to transform a DNA/RNA sequence into a chaos game representation.

Algorithm S2: Pseudo-code for the Fourier Transform block.

Algorithm S3: Pseudo-code for the Wavelet Transform block.

Algorithm S4: Calculation of the Router Z-loss.

Algorithm S5: Calculation of the KAN Regularization Loss.

Disclosure of use of AI-assisted tools

In the revision phases, the authors used Google Gemini 2.5 Pro (preview) and Grammarly to improve the readability and check for misspellings and grammar mistakes. Prompts such as "check grammar" and "check grammar with academic writing" were used with Google Gemini 2.5 Pro (preview). The authors reviewed and edited the suggestions generated by tools and took full responsibility for the content of the publication.

Data Availability

The metadata is available at the project home page (https://github.com/nhhaidee/WaveSeekerNet), and the RNA and protein sequences of the HA and NA segments of IAV can be downloaded from EpiFlu GISAID (https://gisaid.org/) after creating an account and accepting the terms of use.

Availability of Source Code and Requirements

- Project Name: WaveSeekerNet: Accurate Prediction of Influenza A Virus Subtypes and Host Source Using Attention-Based Deep Learning
- Project home page: https://github.com/nhhaidee/WaveSeekerNet
- RRID:SCR_026942
- biotools:waveseekernet
- Operating System(s): e.g, Platform independent
- Programming Language: Python 3.12.5
- Other requirements: Python 3.12+, pytorch 2.4.1, pytorch-optimizer 3.1.1, pytorch-wavelets 1.3.0, scikit-learn 1.5.1, seaborn 0.13.2, pyfastx 2.1.0, pandas 2.2.2, numpy 1.26.4, TriominalTest 1.0.4
- License: MIT license

Funding

H-H.N., J.R., C.L., O.V., and O.L. are supported by the Canadian Safety and Security Program (CSSP) grant CSSP-2022-CP-2538 (Artificial Intelligence for Front-Line Laboratories: Preparing for High-Consequence Pathogens to Reduce Their Risk). J.R., D.L., C.L., and O.L. are supported by the CSSP grant CSSP-2023-CP-2620 (Pilot Pan-Canadian Surveillance for

Mammalian Viral Pathogens Using Hematophagic Organisms and Environmental Samples). H-

H.N. and C.K.L. are partially supported by the Natural Sciences and Engineering Research

Council of Canada (NSERC) and the University of Manitoba. G.W.T. and N.L. are supported by

the INSPIRE (Integrated Network for the Surveillance of Pathogens: Increasing REsilience and

capacity in Canada's pandemic response) project funded through the Canada Biomedical

Research Fund (grant CBRF2-2023-00008), the Biomedical Research Infrastructure Fund, and

the Ontario Research Fund. This research was supported, in part, by the Province of Ontario and

the Government of Canada through the Canadian Institute for Advanced Research (CIFAR), and

companies sponsoring the Vector Institute (https://vectorinstitute.ai/partnerships/current-

partners/).

Author's Contributions

H-H.N. designed the models, wrote the code/manuscript, prepared data, trained models,

performed experiments and completed the data analysis. J.R. designed models, wrote the code,

reviewed/edited the manuscript, mentored and provided critical feedback. O.V. performed

phylogenetic analysis and reviewed/edited the manuscript. N.L. demonstrated the viability of the

FCGR. O.L., C.K.L., and G.W.T. supervised the study and reviewed/edited the manuscript. D.L.

and C.L. reviewed/edited the manuscript. All authors contributed to finalizing the manuscript.

Acknowledgements

1048 We thank Peter Kruczkiewicz, Cass Erdelyan, Dr. Anthony Signore, and Dr. Yohannes Berhane

1049 at the Canadian Food Inspection Agency (CFIA) - National Centre for Foreign Animal Disease

1050 (NCFAD) and reviewers for their valuable comments and feedback.

Competing Interests

1052 The authors have declared that no competing interests exist.

1053

References

[1]   Webster RG, Bean WJ, Gorman OT, Chambers TM, Kawaoka Y. Evolution and ecology of influenza A viruses. Microbiol Rev 1992;56:152–79. https://doi.org/10.1128/mr.56.1.152-179.1992.

[2]   Kuiken T, Holmes EC, McCauley J, Rimmelzwaan GF, Williams CS, Grenfell BT. Host Species Barriers to Influenza Virus Infections. Science 2006;312:394–7. https://doi.org/10.1126/science.1122818.

[3]   Imai M, Kawaoka Y. The role of receptor binding specificity in interspecies transmission of influenza viruses. Curr Opin Virol 2012;2:160–7. https://doi.org/10.1016/j.coviro.2012.03.003.

[4]   Bouvier NM, Palese P. The biology of influenza viruses. Vaccine 2008;26:D49–53. https://doi.org/10.1016/j.vaccine.2008.07.039.

[5]   Fereidouni S, Starick E, Karamendin K, Di Genova C, Scott SD, Khan Y, et al. Genetic characterization of a new candidate hemagglutinin subtype of influenza A viruses. Emerg Microbes Infect 2023;12:2225645. https://doi.org/10.1080/22221751.2023.2225645.

[6]   Kilbourne ED. Influenza Pandemics of the 20th Century. Emerg Infect Dis 2006;12:9–14. https://doi.org/10.3201/eid1201.051254.

[7]   Al Hajjar S, McIntosh K. The first influenza pandemic of the 21st century. Ann Saudi Med 2010;30:1–10. https://doi.org/10.4103/0256-4947.59365.

[8]   Smith GJD, Fan XH, Wang J, Li KS, Qin K, Zhang JX, et al. Emergence and predominance of an H5N1 influenza variant in China. Proc Natl Acad Sci 2006;103:16936–41. https://doi.org/10.1073/pnas.0608157103.

[9]   Emergence and Evolution of H5N1 Bird Flu | Avian Influenza (Flu) 2024. https://archive.cdc.gov/www_cdc_gov/flu/avianflu/communication-resources/bird-flu-origin-infographic.html (accessed November 4, 2024).

[10] Caliendo V, Lewis NS, Pohlmann A, Baillie SR, Banyard AC, Beer M, et al. Transatlantic spread of highly pathogenic avian influenza H5N1 by wild birds from Europe to North America in 2021. Sci Rep 2022;12:11729. https://doi.org/10.1038/s41598-022-13447-z.

[11] Agency CFI. Status of ongoing avian influenza response by province 2023. http://inspection.canada.ca/en/animal-health/terrestrial-animals/diseases/reportable/avian-influenza/latest-bird-flu-situation/status-ongoing-response (accessed May 17, 2025).

[12] CDC. USDA Reported H5N1 Bird Flu Detections in Poultry. Avian Influenza Bird Flu 2025. https://www.cdc.gov/bird-flu/situation-summary/data-map-commercial.html (accessed May 17, 2025).

[13] Bohannon M. Egg Shortage: As Prices Climb 15%, Stores Nationwide Begin To Ration Egg Purchases. Forbes n.d. https://www.forbes.com/sites/mollybohannon/2025/02/14/egg-shortage-as-prices-climb-15-stores-nationwide-begin-to-ration-egg-purchases/ (accessed February 19, 2025).

[14] Erdelyan CNG, Kandeil A, Signore AV, Jones MEB, Vogel P, Andreev K, et al. Multiple transatlantic incursions of highly pathogenic avian influenza clade 2.3.4.4b A(H5N5) virus into North America and spillover to mammals. Cell Rep 2024;43:114479. https://doi.org/10.1016/j.celrep.2024.114479.

[15] Caserta LC, Frye EA, Butt SL, Laverack M, Nooruzzaman M, Covaleda LM, et al.
Spillover of highly pathogenic avian influenza H5N1 virus to dairy cattle. Nature
2024;634:669–76. https://doi.org/10.1038/s41586-024-07849-4.
[16] Vinikoor M, Stevens J, Nawrocki J, Singh K. Influenza A Virus Subtyping: Paradigm Shift
in Influenza Diagnosis. J Clin Microbiol 2009;47:3055–6.
https://doi.org/10.1128/JCM.01388-09.
[17] Sempere Borau M, Stertz S. Entry of influenza A virus into host cells — recent progress
and remaining challenges. Curr Opin Virol 2021;48:23–9.
https://doi.org/10.1016/j.coviro.2021.03.001.
[18] Aiello AE, Coulborn RM, Aragon TJ, Baker MG, Burrus BB, Cowling BJ, et al. Research
findings from nonpharmaceutical intervention studies for pandemic influenza and current
gaps in the research. Am J Infect Control 2010;38:251–8.
https://doi.org/10.1016/j.ajic.2009.12.007.
[19] Rudar J, Kruczkiewicz P, Vernygora O, Golding GB, Hajibabaei M, Lung O. Sequence
signatures within the genome of SARS-CoV-2 can be used to predict host source. Microbiol
Spectr 2024;12:e03584-23. https://doi.org/10.1128/spectrum.03584-23.
[20] Eng CL, Tong JC, Tan TW. Predicting host tropism of influenza A virus proteins using
random forest. BMC Med Genomics 2014;7:S1. https://doi.org/10.1186/1755-8794-7-S3-
S1.
[21] Eng CLP, Tong JC, Tan TW. Predicting Zoonotic Risk of Influenza A Viruses from Host
Tropism Protein Signature Using Random Forest. Int J Mol Sci 2017;18:1135.
https://doi.org/10.3390/ijms18061135.
[22] Yin R, Zhou X, Rashid S, Kwoh CK. HopPER: an adaptive model for probability
estimation of influenza reassortment through host prediction. BMC Med Genomics
2020;13:9. https://doi.org/10.1186/s12920-019-0656-7.
[23] Alberts F, Berke O, Maboni G, Petukhova T, Poljak Z. Utilizing machine learning and
hemagglutinin sequences to identify likely hosts of influenza H3Nx viruses. Prev Vet Med
2024;233:106351. https://doi.org/10.1016/j.prevetmed.2024.106351.
[24] Xu Y, Wojtczak D. MC-NN: An End-to-End Multi-Channel Neural Network Approach for
Predicting Influenza A Virus Hosts and Antigenic Types. SN COMPUT SCI 2023;4.
https://doi.org/doi.org/10.1007/s42979-023-01839-5.
[25] Mock F, Viehweger A, Barth E, Marz M. VIDHOP, viral host prediction with deep
learning. Bioinformatics 2021;37:318–25. https://doi.org/10.1093/bioinformatics/btaa705.
[26] Sarmah U, Borah P, Bhattacharyya DK. Ensemble Learning Methods: An Empirical Study.
SN Comput Sci 2024;5:924. https://doi.org/10.1007/s42979-024-03252-y.
[27] Rudar J, Porter TM, Wright M, Golding GB, Hajibabaei M. LANDMark: an ensemble
approach to the supervised selection of biomarkers in high-throughput sequencing data.
BMC Bioinformatics 2022;23:110. https://doi.org/10.1186/s12859-022-04631-z.
[28] Breiman L. Random Forests. Mach Learn 2001;45:5–32.
https://doi.org/10.1023/A:1010933404324.
[29] Wolpert DH. Stacked generalization. Neural Netw 1992;5:241–59.
https://doi.org/10.1016/S0893-6080(05)80023-1.
[30] Lakshminarayanan B, Pritzel A, Blundell C. Simple and scalable predictive uncertainty
estimation using deep ensembles. Proc. 31st Int. Conf. Neural Inf. Process. Syst., Red
Hook, NY, USA: Curran Associates Inc.; 2017, p. 6405–16.
[31] Abe T, Buchanan EK, Pleiss G, Zemel R, Cunningham JP. Deep ensembles work, but are

they necessary? Proc. 36th Int. Conf. Neural Inf. Process. Syst., Red Hook, NY, USA: Curran Associates Inc.; 2022, p. 33646–60.

[32] Srivastava N, Hinton G, Krizhevsky A, Sutskever I, Salakhutdinov R. Dropout: A Simple Way to Prevent Neural Networks from Overfitting. J Mach Learn Res 2014;15:1929–58.

[33] Vaswani A, Shazeer N, Parmar N, Uszkoreit J, Jones L, Gomez AN, et al. Attention is all you need. Proc. 31st Int. Conf. Neural Inf. Process. Syst., Red Hook, NY, USA: Curran Associates Inc.; 2017, p. 6000–10.

[34] Shazeer N, Mirhoseini A, Maziarz K, Davis A, Le QV, Hinton GE, et al. Outrageously Large Neural Networks: The Sparsely-Gated Mixture-of-Experts Layer. CoRR 2017;abs/1701.06538.

[35] Shu Y, McCauley J. GISAID: Global initiative on sharing all influenza data – from vision to reality. Eurosurveillance 2017;22. https://doi.org/10.2807/1560-7917.ES.2017.22.13.30494.

[36] Schäffer AA, Hatcher EL, Yankie L, Shonkwiler L, Brister JR, Karsch-Mizrachi I, et al. VADR: validation and annotation of virus sequence submissions to GenBank. BMC Bioinformatics 2020;21:211. https://doi.org/10.1186/s12859-020-3537-3.

[37] Wang Y, Bao J, Du J, Li Y. Rapid Detection and Prediction of Influenza A Subtype using Deep Convolutional Neural Network based Ensemble Learning. Proc. 2020 10th Int. Conf. Biosci. Biochem. Bioinforma., New York, NY, USA: Association for Computing Machinery; 2020, p. 47–51. https://doi.org/10.1145/3386052.3386053.

[38] Avila Cartes J, Anand S, Ciccolella S, Bonizzoni P, Della Vedova G. Accurate and fast clade assignment via deep learning and frequency chaos game representation. GigaScience 2023;12:giac119. https://doi.org/10.1093/gigascience/giac119.

[39] Löchel HF, Eger D, Sperlea T, Heider D. Deep learning on chaos game representation for proteins. Bioinformatics 2020;36:272–9. https://doi.org/10.1093/bioinformatics/btz493.

[40] Chen D, Jacob L, Mairal J. Biological sequence modeling with convolutional kernel networks. Bioinformatics 2019;35:3294–302. https://doi.org/10.1093/bioinformatics/btz094.

[41] Jeffrey HJ. Chaos game representation of gene structure. Nucleic Acids Res 1990;18:2163. https://doi.org/10.1093/nar/18.8.2163.

[42] Almeida JS, Carriço JA, Maretzek A, Noble PA, Fletcher M. Analysis of genomic sequences by Chaos Game Representation. Bioinformatics 2001;17:429–37. https://doi.org/10.1093/bioinformatics/17.5.429.

[43] Deschavanne PJ, Giron A, Vilain J, Fagot G, Fertil B. Genomic signature: characterization and classification of species assessed by chaos game representation of sequences. Mol Biol Evol 1999;16:1391–9. https://doi.org/10.1093/oxfordjournals.molbev.a026048.

[44] Wang Y, Hill K, Singh S, Kari L. The spectrum of genomic signatures: from dinucleotides to chaos game representation. Gene 2005;346:173–85. https://doi.org/10.1016/j.gene.2004.10.021.

[45] Luo N, Wang X, Wang B, Meng R, Zhao Y, Chai Z, et al. Flu-CNN: predicting host tropism of influenza A viruses via character-level convolutional networks 2023:2023.08.28.23294703. https://doi.org/10.1101/2023.08.28.23294703.

[46] Dosovitskiy A, Beyer L, Kolesnikov A, Weissenborn D, Zhai X, Unterthiner T, et al. An Image is Worth 16x16 Words: Transformers for Image Recognition at Scale 2021. https://doi.org/10.48550/arXiv.2010.11929.

[47] Fortunato M, Azar MG, Piot B, Menick J, Osband I, Graves A, et al. Noisy Networks for

Exploration 2019. https://doi.org/10.48550/arXiv.1706.10295.

[48] Wang G, Lu Y, Cui L, Lv T, Florencio D, Zhang C. A Simple yet Effective Learnable
Positional Encoding Method for Improving Document Transformer Model. In: He Y, Ji H,
Li S, Liu Y, Chang C-H, editors. Find. Assoc. Comput. Linguist. AACL-IJCNLP 2022,
Online Only: Association for Computational Linguistics; 2022, p. 453–63.
https://doi.org/10.18653/v1/2022.findings-aacl.42.

[49] Luo X, Tu X, Ding Y, Gao G, Deng M. Expectation pooling: an effective and interpretable
pooling method for predicting DNA–protein binding. Bioinformatics 2020;36:1405–12.
https://doi.org/10.1093/bioinformatics/btz768.

[50] Liu Z, Wang Y, Vaidya S, Ruehle F, Halverson J, Soljačić M, et al. KAN: Kolmogorov-
Arnold Networks 2024. https://doi.org/10.48550/arXiv.2404.19756.

[51] Liu H, Dai Z, So D, Le QV. Pay Attention to MLPs. Adv. Neural Inf. Process. Syst., vol.
34, Curran Associates, Inc.; 2021, p. 9204–15.

[52] Ma X, Dai X, Bai Y, Wang Y, Fu Y. Rewrite the Stars 2024.
https://doi.org/10.48550/arXiv.2403.19967.

[53] Tolstikhin I, Houlsby N, Kolesnikov A, Beyer L, Zhai X, Unterthiner T, et al. MLP-mixer:
an all-MLP architecture for vision. Proc. 35th Int. Conf. Neural Inf. Process. Syst., Red
Hook, NY, USA: Curran Associates Inc.; 2024, p. 24261–72.

[54] Wu X, Huang S, Wang W, Wei F. Multi-Head Mixture-of-Experts 2024.
https://doi.org/10.48550/arXiv.2404.15045.

[55] Zoph B, Bello I, Kumar S, Du N, Huang Y, Dean J, et al. ST-MoE: Designing Stable and
Transferable Sparse Expert Models 2022. https://doi.org/10.48550/arXiv.2202.08906.

[56] Lee-Thorp J, Ainslie J, Eckstein I, Ontañón S. FNet: Mixing Tokens with Fourier
Transforms. CoRR 2021;abs/2105.03824.

[57] Shen Z, Zhang M, Zhao H, Yi S, Li H. Efficient Attention: Attention with Linear
Complexities 2024. https://doi.org/10.48550/arXiv.1812.01243.

[58] Zhang B, Sennrich R. Root mean square layer normalization. Proc. 33rd Int. Conf. Neural
Inf. Process. Syst., Red Hook, NY, USA: Curran Associates Inc.; 2019, p. 12381–92.

[59] Guibas J, Mardani M, Li Z, Tao A, Anandkumar A, Catanzaro B. Adaptive Fourier Neural
Operators: Efficient Token Mixers for Transformers 2022.
https://doi.org/10.48550/arXiv.2111.13587.

[60] Graur D, Li W-HL. Fundamentals of Molecular Evolution. Second Edition. Oxford, New
York: Oxford University Press; 2000.

[61] Chen Y. An Introduction to Wavelet Analysis with Applications to Image and JPEG 2000.
2022 4th Int. Conf. Intell. Med. Image Process., New York, NY, USA: Association for
Computing Machinery; 2022, p. 49–57. https://doi.org/10.1145/3524086.3524094.

[62] Soman KP, Ramachandran KI. Insight Into Wavelets From Theory To Practice 2Nd Ed.
Prentice-Hall Of India Pvt. Limited; 2005.

[63] Cotter F. Uses of Complex Wavelets in Deep Convolutional Neural Networks 2020.
https://doi.org/10.17863/CAM.53748.

[64] Xu Y, Wojtczak D. Dive into machine learning algorithms for influenza virus host
prediction with hemagglutinin sequences. Biosystems 2022;220.
https://doi.org/10.1016/j.biosystems.2022.104740.

[65] Rives A, Meier J, Sercu T, Goyal S, Lin Z, Liu J, et al. Biological structure and function
emerge from scaling unsupervised learning to 250 million protein sequences. Proc Natl
Acad Sci 2021;118:e2016239118. https://doi.org/10.1073/pnas.2016239118.

[66] Benavoli A, Corani G, Demšar J, Zaffalon M. Time for a Change: a Tutorial for Comparing
Multiple Classifiers Through Bayesian Analysis. J Mach Learn Res 2017;18:1–36.
[67] Yong H, Huang J, Hua X, Zhang L. Gradient Centralization: A New Optimization
Technique for Deep Neural Networks. Comput. Vis. – ECCV 2020 16th Eur. Conf. Glasg.
UK August 23–28 2020 Proc. Part I, Berlin, Heidelberg: Springer-Verlag; 2020, p. 635–52.
https://doi.org/10.1007/978-3-030-58452-8_37.
[68] Zhang MR, Lucas J, Hinton G, Ba J. Lookahead optimizer: k steps forward, 1 step back.
Proc. 33rd Int. Conf. Neural Inf. Process. Syst., Red Hook, NY, USA: Curran Associates
Inc.; 2019, p. 9597–608.
[69] Misra D. Mish: A Self Regularized Non-Monotonic Activation Function 2020.
https://doi.org/10.48550/arXiv.1908.08681.
[70] Hendrycks D, Gimpel K. Gaussian Error Linear Units (GELUs) 2023.
https://doi.org/10.48550/arXiv.1606.08415.
[71] Agarap AF. Deep Learning using Rectified Linear Units (ReLU) 2019.
https://doi.org/10.48550/arXiv.1803.08375.
[72] Camacho C, Coulouris G, Avagyan V, Ma N, Papadopoulos J, Bealer K, et al. BLAST+:
architecture and applications. BMC Bioinformatics 2009;10:421.
https://doi.org/10.1186/1471-2105-10-421.
[73] Calhoun VC, Hatcher EL, Yankie L, Nawrocki EP. Influenza sequence validation and
annotation using VADR. Database 2024;2024:baae091.
https://doi.org/10.1093/database/baae091.
[74] Katoh K, Misawa K, Kuma K, Miyata T. MAFFT: a novel method for rapid multiple
sequence alignment based on fast Fourier transform. Nucleic Acids Res 2002;30:3059–66.
https://doi.org/10.1093/nar/gkf436.
[75] Katoh K, Standley DM. MAFFT Multiple Sequence Alignment Software Version 7:
Improvements in Performance and Usability. Mol Biol Evol 2013;30:772–80.
https://doi.org/10.1093/molbev/mst010.
[76] Suchard MA, Lemey P, Baele G, Ayres DL, Drummond AJ, Rambaut A. Bayesian
phylogenetic and phylodynamic data integration using BEAST 1.10. Virus Evol
2018;4:vey016. https://doi.org/10.1093/ve/vey016.
[77] Drummond AJ, Rambaut A, Shapiro B, Pybus OG. Bayesian Coalescent Inference of Past
Population Dynamics from Molecular Sequences. Mol Biol Evol 2005;22:1185–92.
https://doi.org/10.1093/molbev/msi103.
[78] Drummond AJ, Nicholls GK, Rodrigo AG, Solomon W. Estimating Mutation Parameters,
Population History and Genealogy Simultaneously From Temporally Spaced Sequence
Data. Genetics 2002;161:1307–20. https://doi.org/10.1093/genetics/161.3.1307.
[79] Drummond AJ, Ho SYW, Phillips MJ, Rambaut A. Relaxed Phylogenetics and Dating with
Confidence. PLOS Biol 2006;4:e88. https://doi.org/10.1371/journal.pbio.0040088.
[80] Rambaut A, Drummond AJ, Xie D, Baele G, Suchard MA. Posterior Summarization in
Bayesian Phylogenetics Using Tracer 1.7. Syst Biol 2018;67:901–4.
https://doi.org/10.1093/sysbio/syy032.
[81] Rudar J, Lung O. TrinomialTest 2025. https://doi.org/10.5281/zenodo.15353378.
[82] Bian G, McAleer M, Wong W-K. A trinomial test for paired data when there are many ties.
Math Comput Simul 2011;81:1153–60. https://doi.org/10.1016/j.matcom.2010.11.002.
[83] Aznar E, Casas I, Praetorius AG, Ramos MJR, Pozo F, Moros MJS, et al. Influenza
A(H5N1) detection in two asymptomatic poultry farm workers in Spain, September to

October 2022: suspected environmental contamination. Eurosurveillance 2023;28:2300107. https://doi.org/10.2807/1560-7917.ES.2023.28.8.2300107.

[84] Bao P, Liu Y, Zhang X, Fan H, Zhao J, Mu M, et al. Human infection with a reassortment avian influenza A H3N8 virus: an epidemiological investigation study. Nat Commun 2022;13:6817. https://doi.org/10.1038/s41467-022-34601-1.

[85] Avian Influenza A(H5N1) – Viet Nam n.d. https://www.who.int/emergencies/disease-outbreak-news/item/2024-DON511 (accessed December 3, 2024).

[86] Authority EFS, European Centre for Disease Prevention and Control, Influenza EURL for A, Alexakis L, Fusaro A, Kuiken T, et al. Avian influenza overview March–June 2024. EFSA J 2024;22:e8930. https://doi.org/10.2903/j.efsa.2024.8930.

[87] Zeller MA, Carnevale de Almeida Moraes D, Ciacci Zanella G, Souza CK, Anderson TK, Baker AL, et al. Reverse zoonosis of the 2022–2023 human seasonal H3N2 detected in swine. Npj Viruses 2024;2:1–12. https://doi.org/10.1038/s44298-024-00042-4.

[88] Zeller MA, Ma J, Wong FY, Tum S, Hidano A, Holt H, et al. The genomic landscape of swine influenza A viruses in Southeast Asia. Proc Natl Acad Sci U S A 2023;120:e2301926120. https://doi.org/10.1073/pnas.2301926120.

[89] Baker AL, Arruda B, Palmer MV, Boggiatto P, Sarlo Davila K, Buckley A, et al. Dairy cows inoculated with highly pathogenic avian influenza virus H5N1. Nature 2024:1–8. https://doi.org/10.1038/s41586-024-08166-6.

[90] Soulsbury CD, White PCL. Human–wildlife interactions in urban areas: a review of conflicts, benefits and opportunities. Wildl Res 2015;42:541–53. https://doi.org/10.1071/WR14229.

[91] Richardson S, Mill AC, Davis D, Jam D, Ward AI. A systematic review of adaptive wildlife management for the control of invasive, non-native mammals, and other human–wildlife conflicts. Mammal Rev 2020;50:147–56. https://doi.org/10.1111/mam.12182.

[92] Garten RJ, Davis CT, Russell CA, Shu B, Lindstrom S, Balish A, et al. Antigenic and Genetic Characteristics of Swine-Origin 2009 A(H1N1) Influenza Viruses Circulating in Humans. Science 2009;325:197–201. https://doi.org/10.1126/science.1176225.

[93] Lu R, Zhao X, Li J, Niu P, Yang B, Wu H, et al. Genomic characterisation and epidemiology of 2019 novel coronavirus: implications for virus origins and receptor binding. The Lancet 2020;395:565–74. https://doi.org/10.1016/S0140-6736(20)30251-8.

[94] Anitas EM. Fractal Analysis of DNA Sequences Using Frequency Chaos Game Representation and Small-Angle Scattering. Int J Mol Sci 2022;23:1847. https://doi.org/10.3390/ijms23031847.

[95] Correia JP, Silva R, Anselmo DH a. L, Vasconcelos MS, da Silva LR. Multifractal Properties of Human Chromosome Sequences. Fractal Fract 2024;8:312. https://doi.org/10.3390/fractalfract8060312.

[96] Kandeil A, Patton C, Jones JC, Jeevan T, Harrington WN, Trifkovic S, et al. Rapid evolution of A(H5N1) influenza viruses after intercontinental spread to North America. Nat Commun 2023;14:3082. https://doi.org/10.1038/s41467-023-38415-7.

[97] Demircioğlu A. Applying oversampling before cross-validation will lead to high bias in radiomics. Sci Rep 2024;14:11563. https://doi.org/10.1038/s41598-024-62585-z.

[98] Devlin J, Chang M-W, Lee K, Toutanova K. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In: Burstein J, Doran C, Solorio T, editors. Proc. 2019 Conf. North Am. Chapter Assoc. Comput. Linguist. Hum. Lang. Technol. Vol. 1 Long Short Pap., Minneapolis, Minnesota: Association for Computational Linguistics;

2019, p. 4171–86. https://doi.org/10.18653/v1/N19-1423.

[99] Ji Y, Zhou Z, Liu H, Davuluri RV. DNABERT: pre-trained Bidirectional Encoder
Representations from Transformers model for DNA-language in genome. Bioinformatics
2021;37:2112–20. https://doi.org/10.1093/bioinformatics/btab083.

[100] Sanjuán R, Nebot MR, Chirico N, Mansky LM, Belshaw R. Viral Mutation Rates. J Virol
2010;84:9733–48. https://doi.org/10.1128/jvi.00694-10.

[101] Elderfield RA, Watson SJ, Godlee A, Adamson WE, Thompson CI, Dunning J, et al.
Accumulation of Human-Adapting Mutations during Circulation of A(H1N1)pdm09
Influenza Virus in Humans in the United Kingdom. J Virol 2014;88:13269–83.
https://doi.org/10.1128/jvi.01636-14.

[102] Taubenberger JK, Kash JC. Influenza Virus Evolution, Host Adaptation, and Pandemic
Formation. Cell Host Microbe 2010;7:440–51. https://doi.org/10.1016/j.chom.2010.05.009.

[103] Lundberg SM, Lee S-I. A unified approach to interpreting model predictions. Proc. 31st
Int. Conf. Neural Inf. Process. Syst., Red Hook, NY, USA: Curran Associates Inc.; 2017, p.
4768–77.

[104] Kruczkiewicz P, Nguyen HH, Meknas A, Erdelyan C, Lung O. CFIA-NCFAD/nf-flu:
3.7.0 2025. https://doi.org/10.5281/zenodo.14728750.

[105] Zhu W, Xie L, Han J, Guo X. The Application of Deep Learning in Cancer Prognosis
Prediction. Cancers 2020;12:603. https://doi.org/10.3390/cancers12030603.

[106] Wekesa JS, Kimwele M. A review of multi-omics data integration through deep learning
approaches for disease diagnosis, prognosis, and treatment. Front Genet 2023;14.
https://doi.org/10.3389/fgene.2023.1199087.