Contrastive Learning Enables Epitope Overlap Predictions for Targeted Antibody Discovery

Clinton M. Holt [1,2,3], Alexis K. Janke [1,4], Parastoo Amlashi [1,4], Parker J. Jamieson [1,4], Toma M. Marinov [1,3,4], Ivelin S. Georgiev [1,2,3,4,5,6,7,8,9,10]

Affiliations

[1] Vanderbilt Center for Antibody Therapeutics, Vanderbilt University Medical Center, Nashville, TN 37232, USA

[2] Program in Chemical and Physical Biology, Vanderbilt University Medical Center, Nashville, TN 37232, USA

[3] Center for Computational Microbiology and Immunology, Vanderbilt University Medical Center, Nashville, TN 37232, USA

[4] Department of Pathology, Microbiology, and Immunology, Vanderbilt University Medical Center, Nashville, TN 37232, USA

[5] Department of Computer Science, Vanderbilt University, Nashville, TN 37232, USA

[6] Department of Biomedical Informatics, Vanderbilt University, Nashville, TN 37232, USA

[7] Department of Chemical and Biomolecular Engineering, Vanderbilt University, Nashville, TN 37232, USA

[8] Department of Biochemistry, Vanderbilt University, Nashville, TN 37232, USA

[9] Vanderbilt Institute for Infection, Immunology, and Inflammation, Vanderbilt University Medical Center, Nashville, TN 37232, USA

[10] Center for Structural Biology, Vanderbilt University, Nashville, TN 37232, USA

Summary

Computational epitope prediction remains an unmet need for therapeutic antibody development. We present three complementary approaches for predicting epitope relationships from antibody amino acid sequences. First, we analyze ~18 million antibody pairs targeting ~250 protein families and establish that a threshold of >70% CDRH3 sequence identity among antibodies sharing both heavy and light chain V-genes reliably predicts overlapping-epitope antibody pairs. Next, we develop a supervised contrastive fine-tuning framework for antibody large language models which results in embeddings that better correlate with epitope information than those from pre-trained models. Applying this contrastive learning approach to SARS-CoV-2 receptor binding domain antibodies, we achieve 82.7% balanced accuracy in distinguishing same-epitope versus different-epitope antibody pairs and demonstrate the ability to predict relative levels of structural overlap from learning on functional epitope bins (Spearman ρ = 0.25). Finally, we create AbLang-PDB, a generalized model for predicting overlapping-epitope antibodies for a broad range of protein families. AbLang-PDB achieves five-fold improvement in average precision for predicting overlapping-epitope antibody pairs compared to sequence-based methods, and effectively predicts the amount of epitope overlap among overlapping-epitope pairs (ρ = 0.81). In an antibody discovery campaign searching for overlapping-epitope antibodies to the HIV-1 broadly neutralizing antibody 8ANC195, 70% of computationally selected candidates demonstrated HIV-1 specificity, with 50% showing competitive binding with 8ANC195. Together, the computational models presented here provide powerful tools for epitope-targeted antibody discovery, while demonstrating the efficacy of contrastive learning for improving epitope-representation.

Introduction

Monoclonal antibody therapeutics have revolutionized modern medicine since their first FDA approval in 1986, with blockbuster treatments for cancers, autoimmune diseases, and infectious diseases generating billions in annual revenue[1]. Beyond therapeutics, antibodies serve as fundamental research tools and provide crucial insights into immune responses to vaccines and pathogens. Despite their clinical success, developing therapeutic antibodies remains resource-intensive, with epitope characterization—identifying the specific region on an antigen where an antibody binds—posing a significant bottleneck[2]. For example, in the development of broadly neutralizing antibodies against HIV-1, epitope mapping is critical to ensuring efficacy across diverse viral strains[3].

Epitope characterization typically proceeds through three complementary approaches:
(1) structural mapping to define physical contact points between antibody and antigen,
(2) functional mapping to identify binding-critical residues through mutation, and (3)
competition binding experiments to group antibodies that interfere with each other's
binding. Each approach helps guide therapeutic development, whether identifying sites
of vulnerability on pathogens or developing complementary antibody combinations [4–6].

Understanding the similarities and differences (or the level of overlap) between the
epitopes of different antibody candidates provides critical information that can be utilized
when developing antibody therapeutics. For example, in pandemic response efforts
against a newly emerging virus, the selection of two or more non-competing antibodies
which synergize to form a more effective drug than either individual antibody can be
critical for counteracting potential virus escape. In other cases, identifying multiple
antibodies against the same functionally important epitope can provide a larger set of
candidates for further evaluation, down-selection, and development.

While experimental approaches for antibody epitope characterization are undoubtedly
effective, computational approaches can present an efficient and cost-effective
alternative. Generally, computational approaches can interrogate the relationship
between antibody sequence features and epitope similarity, in order to predict the level
of epitope overlap between antibody candidates (Fig. 1). These approaches range from
direct comparisons of the full amino acid sequence or just the complementarity
determining region 3 (CDR3) amino acid sequence within gene groups, to comparing
predicted structures or predicted antigen-binding residues[5,7–16]. While the direct
sequence-based methods have shown success in clustering functionally-related
antibodies, the antibody sequence similarity thresholds utilized by these approaches
have been rigorously validated for only a few antigens and epitopes [5,8–10,17]. The indirect
approaches allow for searching a broader antibody sequence-space, but accuracies are
low and are unable to detect overlapping epitope antibodies using distinct structural
mechanisms, such as targeting the same site from different angles—an aspect that can
significantly influence Fc effector functions and binding breadth [16,18–20]. This limitation is
particularly problematic when searching for therapeutic candidates, where expanding
the candidate pool beyond highly similar structures could be necessary to overcome
challenges like low yields or suboptimal binding properties [21].

The emergence of antibody-specific language models, particularly AbLang, has opened
new possibilities for computational antibody analysis [22]. AbLang was trained on millions
of naturally occurring antibodies through masked language modeling, where it learned
to predict hidden amino acids based on surrounding sequence context [23]. This training
approach enabled the model to capture both evolutionary relationships and structural
constraints within antibody sequences. However, like other current antibody language
models, AbLang faces a critical limitation: its embeddings naturally cluster by sequence

identity and germline gene usage, making it more adept at finding similar sequences
than functionally similar antibodies with divergent sequences [24,25].

Recent advances in machine learning, particularly contrastive learning approaches,
offer promising solutions to these limitations. Contrastive learning provides a framework
for teaching models to recognize when two examples should be considered similar or
different, even when observers see no clear patterns in their features. A useful analogy
is image classification of flowers: while images of flowers from the same species may
display distinct color, shape, and size differences, contrastive learning enables a model
to recognize their fundamental similarities and distinguish them from similar species. By
applying this approach to antibody analysis, we can explicitly train models to recognize
structural or functional epitope similarity even when sequence similarity is low. Using
carefully curated training data from structural databases and high-throughput epitope
mapping experiments, we demonstrate how this approach can enrich antibody language
model embeddings with epitope-specificity information while maintaining their broad
understanding of antibody sequence space.

In this work, we address three key challenges in antibody epitope prediction. First, we
establish reliable sequence-based thresholds for identifying overlapping-epitope
antibodies, providing a simple yet powerful tool for repertoire analysis. Second, we
develop and validate a model using the well-characterized SARS-CoV-2 receptor
binding domain (RBD), where extensive epitope mapping data enables us to
demonstrate how targeted training can overcome the germline bias of current language
models. Finally, we present a generalized model capable of predicting epitope
relationships across diverse protein families, which we validate through the successful
identification of antibodies targeting overlapping epitopes with the HIV-1 broadly
neutralizing antibody 8ANC195, a therapeutic candidate that targets a unique epitope
on the HIV-1 envelope protein. These advances provide a comprehensive framework for
computational epitope analysis, offering new possibilities for therapeutic antibody
discovery and optimization.

Results

Sequence determinants for overlapping-epitope antibodies

To identify sequence features that reliably predict when antibodies target overlapping
epitopes, we initially interrogated antibody sequence identity as a potential determinant.
To that end, we focused on two key features of antibody recognition: variable (V) gene
usage and CDR3 sequence similarity. We analyzed 1,909 non-redundant human
antibodies from the Structural Antibody Database (SAbDab), generating approximately

1.8 million pairwise comparisons [26,27]. These pairs were categorized based on both their
V-gene sharing patterns and binding properties, specifically examining: (1) pairs binding
overlapping epitopes, (2) pairs binding non-overlapping epitopes within the same
protein family (Pfam), and (3) pairs binding different protein families (Fig. 2, S1A-B) [28].

Our analysis revealed a hierarchical relationship between sequence features and
epitope overlap. For antibody pairs sharing both heavy and light chain V-genes, we
identified a heavy chain CDR3 (CDRH3) amino acid identity threshold of 70% that
serves as a virtually perfect predictor - all pairs exceeding this threshold invariably
bound overlapping epitopes within the same protein family (Fig. 2, top row). This
predictive power persisted when antibodies shared only one V-gene, though with an
important caveat (Fig. 2, rows 2 and 3): while pairs exceeding the CDRH3 threshold and
targeting the same protein family consistently bound overlapping epitopes, 17 of 190
antibody pairs that exceeded this threshold bound antigens from entirely different
protein families. This distinction suggests that when both the heavy and light chain
germline V genes are shared, this provides additional constraints on antigen specificity
beyond epitope recognition patterns.

While these sequence-based rules provide a clear framework for predicting epitope
overlap, they also have two major limitations. First, the most predictive rule applies only
to the small subset of antibody pairs sharing both V-genes. Second, even within this
subset, the threshold fails to identify 82% of antibody pairs that do bind overlapping
epitopes, resulting in a high false-negative rate. These limitations suggest that while
sequence identity can provide absolute confidence in some cases, more sophisticated
computational approaches may be needed for broader applicability in therapeutic
antibody discovery.

To address these limitations, we next explored the ability of antibody large language
models to learn the rules of epitope specificity. We focused on two domains: learning
discrete epitope bins within one antigen and learning continuous epitope information
across diverse protein families. These approaches, detailed in the following sections,
demonstrate how modern computational methods can overcome the constraints of
simple sequence-based rules [34].

Contrastive Learning Enables Epitope-Specific Encoding of SARS-CoV-2 RBD
Antibodies

While sequence-based thresholds provide reliable predictions in specific cases, their
limited applicability motivated us to develop more sophisticated approaches for
predicting epitope relationships. We leveraged the extensive epitope mapping data
available for SARS-CoV-2 receptor binding domain (RBD) antibodies to develop and

validate a contrastive learning framework that could encode epitope-specificity
information directly into antibody sequence embeddings (Fig. 3) [29–31].

Our model, AbLang-RBD, builds upon the established AbLang heavy and light chain
language models through targeted fine-tuning using a supervised contrastive learning
framework [22,32,33]. The architecture processes paired antibody sequences through a
dual-stream transformer network - 12 separate transformer blocks per chain - followed
by a six-layer multi-layer perceptron that generates unified sequence embeddings. We
optimized these embeddings using a modified normalized temperature-scaled cross-
entropy (NT-Xent) loss that simultaneously processes multiple positive examples,
allowing the model to learn from groups of antibodies targeting the same epitope rather
than individual pairs (Fig. 3). This approach differs from standard contrastive learning by
concurrently attracting all antibodies sharing an epitope within a training batch while
repelling those binding distinct epitopes, creating a more nuanced embedding space
that captures epitope relationships [33–35]. Critically, by training on same-epitope
antibodies that fall outside our previously established V-gene and CDRH3 identity
thresholds, the model learns new antibody sequence patterns indicative of shared
epitope binding that are missed by our outlined V gene and CDRH3 thresholds.

We trained the model using a previously characterized set of 3,041 SARS-CoV-2 RBD
antibodies binned into 12 epitopes based on deep mutational scanning results [30,31].
Notably, no antibody pairs in the training and test sets shared a heavy V gene and
CDRH3 identity above 65%. Despite this, visualizing the cosine similarity distributions
reveals that our contrastive learning approach effectively distinguishes epitope-bin
information (Fig. 4A). The pretrained AbLang model showed poor separation between
same-epitope and different-epitope pairs (56.0% balanced accuracy), whereas AbLang-
RBD improved this distinction, achieving 74.4% balanced accuracy on test set
comparisons and 82.7% when comparing test antibodies to the training set.

The effectiveness of our epitope-specific encoding is further demonstrated through
dimensionality reduction analysis. T-distributed stochastic neighbor embedding (t-SNE)
visualization reveals that while the pretrained model's embeddings show minimal
epitope-based clustering (31.2% k-means accuracy), AbLang-RBD achieves near-
perfect clustering of training data (99.6%) and substantially improved clustering of test
data (54.6%) (Fig. 4B) [36,37]. Notably, when test antibodies were misclassified, 43% of
errors still placed them within the correct RBD epitope class (out of 4 generally
accepted classes), suggesting the model captures meaningful spatial relationships
between epitopes despite this information not being provided in training [38].

To validate that our model learned genuine epitope-specificity information rather than
arbitrary clustering, we evaluated its performance against two continuous data sources.
First, we examined correlation with the underlying deep mutational scanning data by

mapping escape scores onto the RBD structure to generate weighted average
coordinates for each epitope (Fig. 4C, S1C). AbLang-RBD improved correlation with
these spatial coordinates (Spearman's ρ = -0.39, p < 5e-300) compared to the
pretrained model (ρ = -0.08, p < 5e-300) for the training set as well as for the test set
antibodies (ρ = -0.21, p = 5.2e-149). Second, we assessed performance on an
independent set of 237 RBD-specific antibodies with structural epitope information from
the PDB (Fig. 4D, S1A). AbLang-RBD demonstrated superior correlation with buried
surface area overlap (ρ = 0.25, p < 5e-300) compared to both CDRH3 sequence identity
(ρ = 0.09, p = 2e-47) and the pretrained model (ρ = 0.1, p = 8e-65).

These results demonstrate that supervised contrastive learning can effectively encode
epitope-specificity information into antibody embeddings, establishing a powerful new
framework for computational antibody analysis. While the model shows some limitation
in distinguishing relative distances between non-overlapping epitopes, as evidenced by
the presence of discrete bands in cosine similarity distributions rather than a continuous
gradient (Fig. 4C), its ability to accurately identify antibodies targeting shared epitopes
represents a significant advance over existing sequence-based methods. This
capability, validated against both deep mutational scanning and structural data, provides
a valuable new tool for therapeutic antibody discovery, particularly in cases where
traditional sequence similarity metrics fail to identify functionally related antibodies. Most
importantly, this framework establishes a foundation for developing even more
sophisticated models that can capture the continuous nature of epitope relationships
across diverse antigen families.

Developing a Generalized Model for Continuous Epitope Overlap Prediction

To extend beyond predictions for a single antigen, we developed AbLang-PDB, a model
capable of predicting the degree of epitope overlap for antibodies targeting antigens
from diverse protein families represented in the Protein Data Bank (PDB) [39–41]. Unlike
AbLang-RBD's discrete epitope binning approach, AbLang-PDB employs a regression
framework to predict relative degrees of epitope overlap. We maintained the same dual-
stream transformer architecture but modified the training objective to a mean squared
error loss function to optimize for accurate comparisons between unseen antibodies and
those in our curated training set.

The training data encompassed approximately 2,000 antibodies spanning 250 protein
families, with relationships between antibody pairs encoded on a continuous scale.
Antibodies targeting different protein families received a label of -1, while those binding
non-overlapping epitopes within the same protein family were assigned 0.2. For
antibodies exhibiting epitope overlap, we assigned continuous labels from 0.5 to 1.0
based on their relative degree of structural overlap (Fig S1A-B). This nuanced labeling

strategy enabled the model to learn the spectrum of possible epitope relationships
rather than enforcing binary classifications.

The impact of this training approach is evident in the distribution of cosine similarities
across different antibody pair categories (Fig. 5A). While the pretrained AbLang model
showed minimal separation between the three categories (39.1% balanced accuracy),
AbLang-PDB achieved clear differentiation (62.5% balanced accuracy), with
overlapping-epitope pairs predominantly exhibiting cosine similarities above 0.75. More
importantly, the model demonstrated strong correlation with ground truth labels (ρ =
0.304 out of a possible 0.525 due to ties) across all comparisons, suggesting it learned
meaningful relationships between sequence features and epitope overlap (Fig. 5B).

Notably, the model performs exceptionally well on high-confidence predictions among
overlapping-epitope pairs. When considering only these pairs with model-predicted
cosine similarities above 0.5, the correlation with actual epitope overlap increases
dramatically to ρ = 0.811 (p < 5e-300) (Fig. 5C). This indicates that while the model may
not perfectly separate all antibody pairs, it can be used within this application for highly
reliable predictions on the extent of epitope overlap.

Comprehensive evaluation through receiver operating characteristic and precision-recall
analyses revealed substantial improvements over existing methods (Fig. 5D-F). For
overlapping-epitope classification, AbLang-PDB achieved an ROC-AUC of 0.809, an
average precision of 0.542 and an F1-score of 0.52, significantly outperforming both the
pretrained model (0.632, 0.077, 0.124) and sequence-identity-based predictions (0.610,
0.094, and 0.087). Similar improvements were observed for Pfam prediction, with 1.32x,
3.36x, and 2.14x enhancements over the best alternative classifier in the respective
categories (Fig. 5D-F).

These results demonstrate that our continuous learning approach successfully captures
epitope relationships across diverse protein families while maintaining high precision for
overlapping-epitope predictions. The model's ability to provide reliable confidence
scores through cosine similarities makes it particularly valuable for therapeutic antibody
discovery, where false positives can be costly. In the following section, we validate this
capability through the successful identification of novel antibodies targeting a
therapeutically relevant HIV-1 epitope.

Experimental validation of AbLang-PDB through epitope-targeted HIV-1 antibody
discovery

297 To validate AbLang-PDB's practical utility, we applied it to identify antibodies sharing
298 epitope overlap with the HIV-1 broadly neutralizing antibody 8ANC195 [42–44]. This
299 antibody represents an ideal test case due to its unique binding site at the gp120-gp41

interface and its therapeutic potential, despite having somewhat limited neutralization breadth compared to other broadly neutralizing antibodies [45]. We analyzed a dataset of 7,056 class-switched antibodies from persons living with HIV-1, computing cosine similarities between each antibody and 8ANC195's embedding (Fig. 6A-B) [46,47]. These antibodies were identified through LIBRA-seq (linking B cell receptor to antigen specificity through sequencing), a high-throughput technology that enables simultaneous identification of antigen specificity and BCR sequences at single-cell resolution. In this approach, B cells are exposed to oligonucleotide-barcoded antigens, allowing quantitative assessment of antigen binding through unique molecular identifiers during subsequent single-cell sequencing. The dataset comprised 21 LIBRA-seq experiments where antigen-specific B cells were isolated from peripheral blood mononuclear cells (PBMCs) using fluorescence-activated cell sorting (FACS). To ensure specificity, each B cell's antigen-binding profile was determined using both target antigens and control antigens (both positive and negative) conjugated to the same fluorophore. While this experimental design enriched for HIV-1 specific antibodies in the dataset, the majority of sequences are not expected to be HIV-1 specific. From this analysis, we identified 20 candidates with the highest cosine similarities (range: 0.567-0.655). After eliminating eight antibodies with high sequence identity to other selected candidates and two showing potential reactivity to respiratory syncytial virus or hepatitis C virus in their LIBRA-seq profiles, we prioritized 10 antibodies for experimental characterization. Notably, the intermediate cosine similarity scores suggested partial rather than complete epitope overlap, consistent with 8ANC195's unique epitope characteristics (Fig. 6A).

We first assessed HIV-1 specificity through ELISA against three diverse HIV-1 envelope SOSIP.664 constructs: BG505 (Clade A), CZA97 (Clade C), and ZM106.9 (Clade C), using human parainfluenza virus 3 fusion (HPIV3 F) protein as a negative control (Fig. 6C, S2A-B [46]). Seven of the ten selected antibodies (70%) demonstrated HIV-1 envelope specificity, with six (60%) showing cross-clade binding. Out of our unbiased selection, two had previously been characterized—2723-3055 and 3602-870—both of which had been shown to potently neutralize a broad panel of tier 2 HIV-1 viruses (12/12 and 11/14 viruses tested) [46].

To assess epitope overlap, we performed competition ELISAs against BG505 SOSIP.664 using a panel of well-characterized HIV-1 antibodies targeting distinct epitopes: 8ANC195 (gp120-gp41 interface), VRC01 (CD4 binding site), and PG9 (V1-V2 region) (Fig. 6D-F, S2C) [48,49]. Five antibodies (50%) showed competition with 8ANC195, defined as >30% reduction in binding, with four of those displaying strong competition (>70% reduction). These same antibodies also competed with VRC01 at a slightly weaker level but not with PG9, consistent with the structural overlap between the 8ANC195 and VRC01 epitopes.

The success rate of our computational predictions - 50% for identifying 8ANC195-
competing antibodies and 70% for HIV-1 Env specificity - highlights AbLang-PDB's
potential to streamline therapeutic antibody discovery by accurately identifying
functionally relevant candidates that conventional sequence similarity metrics can miss.
This is particularly noteworthy given that the model identified two previously validated
broadly neutralizing antibodies without any prior knowledge of their functional
properties. These results support AbLang-PDB's utility for therapeutic antibody
discovery, especially in cases where conventional sequence similarity metrics would fail
to identify functionally related candidates.

Discussion

The identification of antibodies targeting overlapping epitopes remains a critical
challenge in therapeutic antibody development. Current approaches typically rely on
experimental screening or database searches for sequence-similar antibodies, both of
which have significant limitations [7,50]. Our work establishes three complementary
computational strategies that address this challenge at different levels of complexity and
applicability.

First, we provide rigorously validated sequence identity-based thresholds for predicting
epitope overlap. When antibody pairs share both heavy and light chain V-genes and
have CDRH3 amino acid identity exceeding 70%, they not only consistently bind
overlapping epitopes but are also guaranteed to target the same protein family. This
constraint relaxes slightly when only one V-gene is shared - while the 70% CDRH3
identity threshold still perfectly predicts overlapping epitopes when antibodies target the
same protein family, some pairs meeting this criterion may bind antigens from different
protein families altogether. While these findings appear straightforward, they represent
the first systematic validation of such thresholds across more than 200 antigen
specificities. These simple yet powerful criteria provide immunologists with reliable tools
for initial repertoire analysis, particularly valuable when analyzing vaccine responses or
comparing antibody lineages across individuals.

Second, through AbLang-RBD, we demonstrate how supervised contrastive learning
can enhance language model embeddings with epitope-specificity information. Using
the well-characterized SARS-CoV-2 RBD as a model antigen, we showed that this
approach achieved 74.4% accuracy in predicting epitope relationships between
previously unseen antibodies. The model's ability to generalize beyond its training data
is evidenced by its improved correlation with both deep mutational scanning data and
structural epitope measurements compared to sequence-based metrics or the

pretrained model. This indicates that our contrastive learning framework indeed
captures genuine epitope-specificity information rather than merely clustering similar
sequences.

Third, we developed AbLang-PDB, which extends epitope prediction capabilities across
diverse protein families while capturing continuous relationships between epitopes. This
model demonstrates substantial improvements over existing methods, achieving a five-
fold increase in average precision for overlapping-epitope prediction while
simultaneously improving antigen protein family average precision 3.4-fold. Particularly
noteworthy is AbLang-PDB's ability to provide reliable confidence scores through cosine
similarities for overlapping epitope antibodies, with high-confidence predictions (cosine
similarity > 0.5) showing strong correlation ($\rho = 0.811$) with actual epitope overlap.

The practical utility of these approaches is demonstrated by our successful identification
of HIV-specific antibodies sharing epitope overlap with 8ANC195. Among our
computationally selected candidates, 70% showed HIV specificity and 50% competed
with 8ANC195 for binding. Additionally, despite this dataset containing only two
previously characterized broadly neutralizing antibodies, both antibodies were among
the model's top 10 cosine similarity scores validating the model's ability to mine
datasets for therapeutically relevant antibodies without requiring the complex
experimental screening methods typically needed for identifying such candidates.

We also note, however, that our approaches have important limitations. The sequence
identity-based thresholds, while providing perfect precision for predicting overlapping
epitopes, exhibit low recall - failing to identify 82% of antibody pairs that do share
epitope overlap. AbLang-RBD demonstrates high performance on SARS-CoV-2 index
strain RBD epitope prediction but faces two key constraints: it is not clear that it will
generalize to RBD-specific antibodies incapable of binding the index strain, and its
training approach using deep mutational scanning data has not been validated for the
more commonly available antibody-antibody competition binding data. AbLang-PDB's
training paradigm is optimized for comparing novel antibodies against those in its
training set rather than directly comparing two previously unseen antibodies, making it
more suitable for analyses that leverage known reference antibodies to assess similarity
and epitope overlap. While we validated the model using HIV-1 envelope as a test case,
this antigen is well-represented in our training data, though notably, our validation
epitope (8ANC195's epitope) had minimal representation.

Despite these limitations, our work provides a comprehensive framework for
computational epitope analysis that will be of significance for the field of therapeutic
antibody discovery. The combination of simple sequence rules and sophisticated
machine learning models offers researchers a tiered approach to identifying
overlapping-epitope antibodies, from rapid initial screening to detailed prediction of

epitope relationships. Looking forward, these methods can be further enhanced through
integration with emerging structural prediction tools and expanded training datasets,
potentially enabling even more accurate prediction of antibody-antigen interactions.

Figure Captions

Figure 1: Motivating Question for this Work. Can antibody sequence features predict
epitope overlap? If possible, then two antibodies (blue and gray) which have sequence
feature similarities above a given similarity threshold are always known to target
overlapping epitopes (top right). If their feature similarities are below this threshold they
would be known to always target non-overlapping epitopes (bottom right). This study
interrogates whether simple sequence features or more complicated features extracted
from antibody amino acid sequences via machine learning are able to reliably
distinguish overlapping epitope and non-overlapping epitope antibody pairs.

Figure 2. V-gene Usage and CDRH3 Sequence Identity Define Reliable Thresholds
for Predicting Overlapping Epitopes. A comprehensive analysis of antibody
sequence features predictive of epitope overlap within the Structural Antibody Database
(SAbDab). Scatter plots show complementarity determining region 3 (CDR3) sequence
identity relationships between antibody pairs (n = 1,909 antibodies, ~1.8 million pairs)
categorized by epitope relationship (columns) and V-gene sharing status (rows). The
columns represent: overlapping epitopes (left), non-overlapping epitopes on the same
protein family (middle), and different protein families (right). Rows indicate V-gene
sharing patterns: both heavy and light V-genes shared (top), only heavy V-gene shared
(second), only light V-gene shared (third), or neither V-gene shared (bottom). X-axis
shows CDRH3 amino acid sequence identity; Y-axis shows CDRL3 amino acid
sequence identity. Data density is represented by hexagonal binning with color scaling
from minimum (dark red) through yellow to maximum density (dark blue). Dashed
vertical lines indicate the 70% CDRH3 identity threshold. Numbers in bottom corners
indicate pair counts within the half desigated by the line. When antibodies share at least
one V-gene and target the same protein family, pairs exceeding 70% CDRH3 identity
consistently bind overlapping epitopes (0 pairs in central columns). This relationship
breaks down when no V-genes are shared (29 pairs in central column).

Figure 3. Contrastive Learning Framework for Encoding Epitope-Specificity
Information in Antibody Sequence Embeddings. Schematic representation of the
contrastive learning approach for training antibody language models to predict epitope
overlap. Monoclonal antibody (mAb) amino acid sequences are processed through a
large language model (LLM) encoder to generate sequence embeddings. During

training, embeddings of antibodies binding overlapping epitopes (two blue antibodies)
are pulled together (green arrows, "Attract"), while embeddings of antibodies binding
non-overlapping epitopes (pink compared to blue) are pushed apart (red arrows,
"Repel"). This framework enables the model to learn sequence features predictive of
epitope overlap beyond simple sequence similarity metrics.

Figure 4. AbLang-RBD Learns to Predict Epitope Relationships from Binned Deep
Mutational Scanning Data Fine-tuning performance of AbLang-RBD on SARS-
CoV-2 RBD antibody epitope prediction. (A) Distribution of cosine similarities
between antibody pairs binding same (blue) or different (red) epitopes. Left: Pretrained
AbLang model shows poor separation (56.0% balanced accuracy). Middle: AbLang-
RBD comparing training to test antibodies achieves 82.7% balanced accuracy. Right:
AbLang-RBD comparing test antibodies achieves 74.4% balanced accuracy. Optimal
decision thresholds (dashed lines) were determined using validation data. (B) t-SNE
visualization of antibody embeddings colored by epitope class. Pretrained AbLang
shows poor epitope clustering (31.2% k-means accuracy, left), while AbLang-RBD
achieves near-perfect clustering on training data (99.6%, middle) and improved
clustering on test data (54.6%, right). (C) Model performance assessed against deep
mutational scanning (DMS) data. Scatter plots show relationship between antibody pair
cosine similarities (y-axis) and weighted average spatial coordinates derived from DMS
escape maps (x-axis). Hexagonal bins colored by pair density from minimum (dark red)
to maximum (dark blue). Spearman's (ρ) and Pearson's (r) correlation coefficients
shown. (D) Validation using structural data from PDB. Scatter plots compare CDRH3
sequence identity (left), pretrained AbLang (middle), and AbLang-RBD (right) against
buried surface area (BSA) overlap between antibody pairs. AbLang-RBD shows
improved correlation with structural epitope overlap (ρ = 0.25, p < 5e-300) compared to
CDRH3 identity (ρ = 0.09, p = 2e-47) or pretrained AbLang (ρ = 0.1, p = 8e-65).

Figure 5. AbLang-PDB Enables Accurate Prediction of Epitope Relationships
Across Diverse Protein Families. Evaluation of AbLang-PDB's performance on the
Structural Antibody Database (SAbDab). (A) Distribution of cosine similarities between
antibody pairs categorized as overlapping epitopes (blue), non-overlapping epitopes on
the same protein family (yellow), or different protein families (red). Left: Pretrained
AbLang shows poor separation (balanced accuracy 39.1%, total accuracy 58.4%).
Right: AbLang-PDB achieves improved separation (balanced accuracy 62.5%, total
accuracy 82.3%). Optimal classification thresholds for balanced accuracy on the
validation set shown as dashed lines. (B) Relationship between model-predicted cosine
similarities and ground truth labels. Hexagonal bins colored by pair density (white to
dark blue). Black bars indicate mean ± 95% confidence intervals. Spearman
correlations (ρ) and maximum possible correlations (ρ_{max}) shown. (C) Detailed view of
high-confidence predictions (cosine similarity and label ≥ 0.5) showing strong correlation

for overlapping-epitope pairs (ρ = 0.811, p < 5e-300). (D) Receiver operating
characteristic curves comparing classification performance of AbLang-PDB (blue)
against pretrained AbLang (orange), full-sequence identity (green), CDRH3 identity
(red), and random prediction (gray) for overlapping epitopes (left) and shared protein
family (right). (E) Corresponding precision-recall curves demonstrating AbLang-PDB's
several fold improvement relative to other prediction methods. (F) Summary metrics
including area under ROC curve (ROC AUC), average precision (Avg Prec), and F1
scores for epitope and protein family predictions across methods.

Figure 6. AbLang-PDB Successfully Identifies HIV Antibodies which compete for
binding with 8ANC195. Experimental validation of AbLang-PDB predictions using HIV
broadly neutralizing antibody 8ANC195. (A) Sequence characteristics of top candidate
antibodies selected by cosine similarity to 8ANC195. Table shows model predictions,
sequence identity metrics, gene usage, and CDR information for each antibody.
Reference antibodies 8ANC195 and VRC01 included for comparison. (B) Distribution of
cosine similarities across the complete LIBRA-seq dataset (n = 7,056 antibodies), with
dashed line indicating recommended threshold (0.5) for mining overlapping-epitope
candidates. (C) ELISA binding profiles against HIV-1 envelope SOSIP.664 constructs
(BG505, CZA97, ZM106.9) and HPIV3 F control protein. Binding strength indicated by
area under the curve (white to blue). 3X1 antibody included as HPIV3-specific control.
(D) Structural representation of HIV-1 BG505 envelope showing competitor antibody
epitopes: 8ANC195 (green, gp120-gp41 interface), VRC01 (pink, CD4-binding site), and
PG9 (tan, V1-V2 region) from PDB IDs 5VJ6 and 8VGW. Envelope surface shown with
gp120 (light gray) and gp41 (black). (E) Competition ELISA curves showing percent
reduction in binding of biotinylated 8ANC195 (10 µg/mL) to BG505 SOSIP.664 in
presence of increasing concentrations of blocking antibodies. Filled symbols indicate
mAbs displaying competition with 8ANC195. (F) Competition matrix showing percent
reduction in binding at fixed concentrations (blocking: 100 µg/mL; detection: 8ANC195
10 µg/mL, VRC01 and PG9 1 µg/mL). Values range from no competition (white) to
complete competition (black).

Supplemental Figure Captions

Figure S1. Quantitative Framework for Defining Epitope Relationships and
Dataset Characteristics. (A) Systematic approach for determining epitope overlap and
machine learning labels for antibody pairs targeting antigens within the same Pfam
family. Two complementary metrics are employed: (1) SASA-based residue-level
epitope overlap, calculated as the overlapping solvent-accessible surface area buried
by the antibodies (threshold >20 Å²), and (2) distance-based atom-level epitope overlap,
defined by antigen atoms within 4.5 Å of each antibody (threshold >5 Å²). Pairs

exceeding both thresholds receive a machine learning label of MAX(1, 0.5 +
Average(RELATIVE_BSA_OVERLAP, RELATIVE_ATOM_OVERLAP)$^{0.75}$) otherwise,
they are assigned a non-overlapping label of 0.2. (B) Relationship between machine
learning labels and buried surface area (BSA) overlap visualized through hexagonal
binning density plot (r = 0.89, Y_{Fit} = 4.07e-4*x + 0.584 for pairs with labels ≥ 0.5). Color
intensity indicates pair density from minimum (red) to maximum (blue). (C) Three-
dimensional visualization of deep mutational scanning (DMS) weighted average
coordinates, with points colored by epitope classification. Coordinate calculation
methodology detailed in Methods. Data demonstrates points maintain clear spatial
segregation of epitope classes.

Figure S2: ELISA data for 8ANC195-targeted antibody discovery campaign. (A-B)
ELISA curves pertaining to Figure 6C AUC values. Binding to trimeric HIV-1
envelope (BG505, CZA97, ZM106.9) or to a negative control antigen, human
parainfluenza virus 3 fusion protein. (B) ELISA curves for antibody 3602-870,
reproduced from data collected from 3602-870's initial publication. Antigens listed
without underscores refer to the use of 3602-870 as the primary antibody whereas
antibodies after underscores are positive controls for that antigen. H1 NC99 stands for
the Influenza A hemagglutinin from the strain A/New Caledonia/20/99 (H1). (C)
Competition ELISA curves showing detection of biotinylated antibody binding to BG505
SOSIP.664 with the biotinylated antibody as the title (8ANC195, VRC01, or PG9).
Absorbance at 450 nm shown in presence of increasing concentrations of competitor
antibodies. Filled symbols indicate mAbs displaying competition with 8ANC195.

Resource availability

Lead Contact

Further information and requests for resources and reagents should be directed to and
will be fulfilled by the lead contact, Ivelin S. Georgiev (ivelin.georgiev@vanderbilt.edu).

Materials availability

Materials will be made available upon request under a completed material transfer
agreement (MTA).

Data and code availability

Sequences for antibodies identified and characterized in this study will be deposited to
GenBank following journal acceptance and prior to publication.

Associated code for AbLang-RBD and AbLang-PDB will be made available at
https://github.com/IGlab-VUMC/AbLangRBD1 and https://github.com/IGlab-
VUMC/AbLangPDB1 and the links for downloading model weights will also be made
available there prior to peer-reviewed publication.

Any additional data or code reported in this paper will be shared by the lead contact
upon request.

Acknowledgements:

We thank Perry Wasdin for his help in curating antigen-specific training sets which
helped interrogate the efficacy of different models and loss functions, and Alexandra
Abu-Shmais for her insights on drawing conclusions from pairwise antibody
comparisons. We additionally thank Andrea Shiakolas, Ian Setliff, Kelsey Pilewski, and
Lauren Walker for LIBRA-seq data. This work was supported by NIH R01AI175245 and
G. Harold and Leila Y. Mathers Charitable Foundation (MF-2107-01851). The funders
had no role in the conceptualization or execution of any studies or drafting of the
manuscript.

Methods

Data curation.

We curated a comprehensive dataset from the Structural Antibody Database (SAbDab,
February 19, 2024 cutoff date) for training and validating the AbLang-PDB model [26,27].
Starting with 16,105 antibody-antigen complexes, we applied the following filtering
criteria: resolution ≤ 4.5 Å, human antibodies with both chains present, and ≥5 amino
acid differences between antibodies. This yielded 1,909 non-redundant complexes, of
which 184 had no same-Pfam pairs and 485 had no overlapping-epitope pairs.

Antigen classification utilized pfam_scan software to group antigens by domain
architecture using hidden Markov models [28,51]. Multiple Pfam assignments were
consolidated such that any shared Pfam between antigens classified their respective
antibodies as targeting the "same Pfam" and thus a machine learning label of 0.2. When
no overlap was present these pairs were assigned a machine learning label of -1. For
quantifying epitope overlap, we employed two complementary approaches. First, we
calculated buried surface area (BSA) per residue using DSSP by comparing the amount
of surface area at each residue for the antigen either in complex with the antibody or
without the antibody [52]. We did this after aligning antigen sequences using the
BLOSUM62 matrix and Needleman-Wunsch algorithm [53,54]. Per-residue BSA overlap
was calculated as $MIN(BSA_{res1, complex1}, BSA_{res1, complex2})$. Antibody pairs with total BSA

overlap summed over all residues ≤ 20 Å² were labeled as non-overlapping (Fig S1A,
label = 0.2). Second, we defined epitopes as antigen heavy atoms within 4.5 Å of
antibody atoms and calculated overlap volume using PyMOL's overlap function, with
pairs showing overlap ≤ 5 Å³ labeled as non-overlapping (label = 0.2) [55].

For overlapping epitopes, final labels were assigned on a continuous scale from 0.5 to
1.0 using the formula: Label = max(1, 0.5 + (rBSA_OVERLAP +
rATOM_OVERLAP)×0.75), where rBSA_OVERLAP and rATOM_OVERLAP represent
overlap relative to the smaller of the two self-overlap values seen for each epitope pair.
For partitioning antibodies between datasets, antibodies sharing both heavy and light V-
genes and CDRH3 amino acid identity >65% were assigned to the same clone group.
These groups were then distributed across training (80%), validation (10%), and test
(10%) sets, ensuring no clone group appeared split between multiple sets. Additionally,
pairs with >92.5% sequence identity in either chain were excluded to maintain diversity.

For AbLang-RBD, we utilized published deep mutational scanning data comprising
3,195 antibodies from 2 papers, of which only the 3,093 which demonstrated binding to
SARS-CoV-2 index strain were kept [30,31]. These antibodies were clustered based on
heavy chain V-gene usage and CDRH3 amino acid identity >70%, with clusters
distributed across training (80%), validation (10%), and test (10%) sets such that no
antibodies in the same cluster existed in the training and test sets. A separate test set
was curated from the PDB by selecting RBD-specific antibodies from CoV-AbDab that
demonstrated index strain binding, and were unique from those in the deep mutational
scanning dataset [29]. This left 237 antibodies and 27,345.

Model Architecture.

Our approach built upon the pretrained AbLang framework, which comprises separate
heavy and light chain transformer models for antibody sequence analysis. We utilized
the published AbLang model weights from Huggingface (qilowoq/AbLang_heavy and
qilowoq/AbLang_light) accessed through the transformers library (AutoModel,
AutoTokenizer) [22,56]. The base architecture follows RoBERTa with modifications for
antibody sequence processing: each chain is processed through 12 transformer blocks
containing 12 attention heads, with hidden dimension 768 and intermediate dimension
3072. A learned positional embedding layer handles sequences up to length 160 [57].

For sequence processing, antibody amino acid sequences were first tokenized using
the transformers module. Heavy and light chain sequences were processed
independently through their respective models to generate chain-specific embeddings.
For each chain, the final hidden layer outputs (768-dimensional vectors) from all non-
masked positions were mean-pooled. While for the pretrained AbLang model we simply
concatenated these chain embeddings, the architecture for AbLang-RBD and AbLang-
PDB introduces additional processing layers to enable cross-chain information flow.

Specifically, the concatenated 1536-dimensional vector (768 dimensions per chain) is
processed through a 6-layer multi-layer perceptron with ReLU activation between
layers, except for the final layer. The normalized output of this network serves as the
unified antibody embedding.

To enable efficient fine-tuning while preserving pretrained weights, we employed
QLORA (Quantized Low-Rank Adaptation) with rank R=16, alpha=32, and dropout=0.3
[32]. This dual-stream architecture - with 12 transformer blocks per chain followed by the
cross-chain mixing network - allows the model to capture both chain-specific features
and relationships between heavy and light chain sequences.

AbLang-RBD training.

The AbLang-RBD model was trained using a supervised contrastive learning approach
with a modified NT-Xent (InfoNCE) loss function [33,35]. During training, we froze all
pretrained weights except for the QLORA adaptation parameters and the six "mixing"
layers that enable cross-talk between heavy and light chain embeddings. Optimization
was performed using the AdamW optimizer with a learning rate of 1e-5 and batch size
of 256.

Specifically, the loss function is a multi-positive variant of the NT-Xent (InfoNCE) loss,
where each sample $z_{i,}$ may have multiple positive samples $\{z_j\}$ sharing the same label
and sim stands for cosine similarity [33,58,59] . For each positive pair, we take

655
$$-log(\frac{\exp{(\frac{sim(\exp{(sim(z_i,z_j)})}{\tau})}}{\sum_{k \neq i} \exp{(sim(z_{i,}z_k)/\tau}})$$

and then average the resulting losses over all positive pairs in the batch using a
temperature $\tau = 0.5$ and a batch size of 256.

Training proceeded for 400 epochs on a single NVIDIA A6000 GPU, requiring
approximately 5 hours including inter-epoch evaluations. Model selection was based on
ROC-AUC performance on the validation set (weighted by epitope class size), with the
epoch 280 checkpoint achieving optimal performance.

Histogram generation and pairwise accuracy or F1 calculation

Distributions of antibody pair relationships were visualized and analyzed using
histograms implemented in Python 3.8.18 with seaborn 0.13.1. All histograms were
generated using probability density normalization with 30 uniform-width bins.
Classification thresholds were determined differently for AbLang-RBD and AbLang-PDB
versus the pretrained model. For AbLang-RBD and AbLang-PDB, thresholds were
optimized to maximize balanced accuracy on the validation dataset. The pretrained
model threshold in Figure 5A was similarly optimized using train versus validation

parameterization, while in Figure 4A it was optimized for maximal balanced accuracy
across the complete dataset (note: this approach overestimates model performance).

For three-category classification, optimal decision boundaries were determined via grid
search across 90,000 threshold combinations (300 x 300 cosine similarity values). The
threshold pair yielding maximum balanced accuracy across all three categories
(overlapping epitopes, non-overlapping epitopes within the same Pfam, and different
Pfams) was selected. Balanced accuracy was calculated as the mean of individual
category accuracies, in contrast to total accuracy which can be biased by class
imbalance.

Calculation of a representative deep mutational scanning coordinate

Deep mutational scanning (DMS) escape data were obtained for 1,375 SARS-CoV-2
RBD antibodies from the publicly available Bloom laboratory database [30,31,60,61]. For
each antibody, a representative three-dimensional coordinate was calculated using
position-specific escape scores as weights. Specifically, escape scores were first
aggregated by residue position, with the weighted average coordinate ($\bar{x}$) calculated as:

$$\bar{x} = \frac{\sum_i w_i x_i}{\sum_i w_i}$$

where w_i is the sum of the escape scores for all mutations at residue i, and x_i is the 3D
coordinates of the alpha carbon for residue i coming from the SARS-CoV-2 RBD
structure (PDB ID 8SGU)[62]. Pairwise distances between antibody coordinates were
calculated using Euclidean distance metrics. To validate this coordinate representation
scheme, we visualized the three-dimensional distribution of antibody positions colored
by epitope class, confirming minimal distortion of known epitope relationships (Fig.
S1C).

Regression analysis

Statistical analyses were performed using SciPy (version 1.10.1) for correlation
calculations and significance testing [63]. Spearman's rank correlation (spearmanr) and
Pearson correlation (pearsonr) coefficients were calculated for various pairwise
comparisons. In Figure S1B, the relationship between buried surface area (BSA) and
training labels was fit using linear regression (scipy.stats.linregress), excluding pairs
with labels below 0.5. For correlation analyses in Figures 4D and 5B-C, Spearman
correlations were calculated with associated p-values; p-values below the numerical
precision limit of 64-bit floating point numbers are reported as p < 5e-300.

For Figure 5B, we calculated the maximum achievable Spearman correlation (ρmax) by
considering the optimal ranking scenario where: (1) all antibody pairs with label -1 rank
below those with label 0.2, (2) all pairs with label 0.2 rank below those with labels ≥ 0.5,
and (3) pairs with labels between 0.5 and 1.0 are perfectly rank-ordered. Mean values

with 95% confidence intervals were calculated for discrete label categories (-1 and 0.2)
and for the continuous range of labels ≥ 0.5 (plotted at x = 0.75). For Figure 5C,
analysis was restricted to pairs with both predicted cosine similarities and ground truth
labels between 0.5 and 1.0 to assess performance on high-confidence predictions.

T-SNE analysis and K-means accuracy calculation

Dimensionality reduction and clustering analyses were performed using scikit-learn
(version 1.3.2). For t-SNE visualization, 1536-dimensional antibody embeddings were
reduced to two dimensions using the following parameters: PCA initialization, automatic
learning rate determination, perplexity of 30, and maximum 1000 iterations with a
learning rate of 1000. For AbLang analysis, the complete dataset was visualized in
aggregate. For AbLang-RBD, while dimensionality reduction was performed on the
complete dataset, training and test sets were subsequently visualized separately to
assess generalization performance.

Clustering analysis was performed using k-means with cosine similarity as the distance
metric. The algorithm was initialized with 12 clusters using the k-means++ strategy for
greedy centroid initialization and allowed to run for a maximum of 300 iterations.
Clustering accuracy was assessed by assigning the most highly represented epitope
class within each cluster as the cluster's representative epitope. Antibodies within each
cluster were considered accurately clustered if they matched this epitope and incorrectly
clustered otherwise. This approach, while disadvantaging underrepresented epitopes
due to class imbalance, provides a conservative estimate of clustering performance.

For visualization clarity, we cycled through three marker shapes (circles, squares, and
triangles) as well as ten distinct colors.

AbLang-PDB training.

The AbLang-PDB model was trained using the architecture described in the Model
Architecture section, utilizing the curated structural antibody dataset. During training, we
maintained the pretrained weights of the base model, modifying only the QLORA
adaptation parameters and the six "mixing" layers responsible for cross-chain
information integration. Training employed the AdamW optimizer with a learning rate of
1e-5 and mean squared error loss function, using a batch size of 16.

To address class imbalance in the training data, we implemented a balanced sampling
strategy where each epoch processed 15,270 antibody pairs, evenly distributed across
three categories: overlapping epitopes, non-overlapping epitopes within the same
protein family, and pairs targeting different protein families. While this approach ensured
equal representation of each category during training, it resulted in more unique pairs
from the non-overlapping epitope classes being trained on.

Training proceeded for 500 epochs on an NVIDIA A6000 GPU, requiring approximately
36 hours including inter-epoch evaluations. Model selection was based on ROC-AUC
performance comparing training and test sets, with the epoch 240 checkpoint achieving
optimal performance.

Receiver Operating Characteristic, Precision-Recall, and F1 Score calculation

Model performance was evaluated using multiple complementary metrics implemented
through scikit-learn. For receiver operating characteristic (ROC) analysis, we calculated
true positive and false positive rates across 2,001 equally spaced thresholds spanning
the range of possible prediction values (cosine similarity from -1 to 1 for model
predictions; 0 to 1 for sequence identity comparisons). The area under the ROC curve
was computed using scikit-learn's trapezoidal rule implementation. For AbLang-RBD,
ROC-AUC values were calculated separately for each of the 12 epitope classes and
combined using a weighted average based on class size. For AbLang-PDB, the
calculation used a binary classification scheme where overlapping epitope pairs
constituted the positive class and non-overlapping pairs the negative class.

Precision-recall characteristics were assessed using scikit-learn's
precision_recall_curve and average_precision_score functions. For F1-score
calculations, we utilized the previously determined optimal threshold that maximized
balanced accuracy. In the case of Pfam classification, F1-scores were calculated
considering all antibody pairs targeting the same protein family as positives, regardless
of their specific epitope overlap status.

LIBRA-seq dataset curation

LIBRA-seq dataset curation was performed on 7,056 class-switched antibody
sequences compiled from previous LIBRA-seq experiments using PBMCs from persons
living with HIV-1. Analysis included only functional, single-cell records from 10X
Genomics VDJ sequencing where cells had undergone fluorescence-activated cell
sorting using PE-labeled antigens, including at least one HIV envelope protein and one
unrelated control antigen. Each antibody was assigned a unique identifier containing a
4-digit sequencing run prefix, with most run prefixes corresponding to unique donors
except for runs 2723 and 3514, which both originated from Donor 45 (source of VRC01)
[46,64]. Nucleotide sequences were processed through IMGT HighV-Quest to determine
amino acid sequences, germline gene assignments, CDR3 sequences, and percent
identity to germline [65–68]. The resulting amino acid sequences were embedded using the
AbLang-PDB model, and cosine similarities were calculated between each antibody and
8ANC195. Selection of the top 20 candidates was performed blind to all functional
annotations and specificity data, including suspected antigen-specificity towards positive
control and negative control antigens, enabling unbiased identification of antibodies with

potential epitope overlap based solely on sequence features learned by the AbLang-
PDB model.

Antibody production.

Antibody heavy and light chains were synthesized as cDNA by Twist Bioscience or
Genscript. Variable genes were inserted into either bicistronic plasmids encoding the
constant regions of the H chain and either the kappa or lambda light chain or into
separate heavy and light chain plasmids. mAbs made in house were transiently
expressed using the Expifectamine transfection reagent (Thermo Fischer Scientific) in
Expi293F cells in FreeStyle F17 media supplemented with 0.1% Poloxamer 188 and
20% 4mM L-glutamine (Thermo Fisher). Transfected cultures were incubated shaking
for 5 days at 37°C with 8% CO2 saturation. After five days, cultures were harvested and
centrifuged at a minimum of 4000 rpm for 20 minutes. Supernatant was then filtered
with Nalgene Rapid Flow Disposable Filter Units with PES membrane (0.45 or 0.22 µm).
Filtrate was run over PBS equilibrated columns containing protein A resin. Columns
were then washed with PBS, and purified antibodies were eluted using 10mls of 100mM
glycine HCL at pH 2.7 into 1 mL of 1M Tris-HCl, pH 8. These were then buffer
exchanged into PBS. Remaining mAbs were synthesized by Genscript in their 10mL
TurboCHO High Throughput Antibody Expression system.

Antigen production.

HPIV3 prefusion stabilized F ectodomain (Protein Data Bank [PDB] accession no.
6MJZ) was expressed in Expi293F cells through transient transfection using
Expifectamine transfection reagents (Thermo Fisher Scientific) in Freestyle F17
expression media (Thermo Fisher) with the addition of 0.1% pluronic acid F-68 and 20%
4 mM l-glutamine [69].

Upon transfection, cultures were grown at 37 °C and 8% CO_2 saturation levels. Six days
after transfection, cultures were centrifuged at 4000 xg for 20 minutes and filtered with
Nalgene Rapid-Flow Disposable Filter Units with PES membrane (0.45 or 0.22 µM).
Protein was purified through nickel affinity chromatography using an equilibrated, 1mL,
prepacked HisTrap HP Column (GE Healthcare, Chicago, IL). The column was
equilibriated with 15mL binding buffer (20mM sodium phosphate, 0.5M NaCl, 0.3 M
imidazole, pH 7.4). Purified protein was eluted from the column with 15mL binding buffer
supplemented with 0.5 M imidazole. Concentrated protein was buffer exchanged into
PBS. The HisTrap purified protein was further purified by size exclusion on Superose 6
Increase 10/300 GL on the AKTA fast protein liquid chromatography (FPLC) system.
Fractions containing pure trimeric HPIV3 were identified through SDS-PAGE and the
molecular mass. Antigenicity was confirmed with binding to 3X1. Protein concentration
was quantified using UV/visible spectroscopy and frozen at -80°C until use.
817

HIV-1 envelope proteins (BG505, CZA97, and ZM106.9) were designed using the
SOSIP platform to yield soluble Env proteins stabilized in the pre-fusion conformation.
These SOSIP constructs incorporated several stabilizing mutations: an intermolecular
disulfide bond between gp120 and gp41 (A501C and T605C), a trimer-stabilizing
mutation (I559P), a truncated gp41 transmembrane region at position 664, and an
I201C/A433C mutation to inhibit CD4-induced movement of Env. Additionally, a flexible
serine-glycine linker was inserted between gp120 and gp41 (positions 507 and 512) to
create single-chain constructs [70].

HIV-1 envelope proteins were expressed in a highly similar fashion but with the
following caveats. Post-culture and centrifugation, the filtered supernatant was applied
to an affinity column of agarose-bound Galanthus nivalis lectin (Vector Laboratories) at
4°C. After washing with PBS, proteins were eluted with 30 mL of 1 M methyl-α-D-
mannopyranoside. The eluate was buffer-exchanged three times into PBS and
concentrated using either 30 kDa or 100 kDa Amicon Ultra centrifugal filter units.

Final purification was achieved by size-exclusion chromatography using either a
Superose 6 Increase 10/300 GL or Superdex 200 Increase 10/300 GL column on an
AKTA FPLC system. Fractions corresponding to correctly folded trimeric Env proteins
were collected and validated by SDS-PAGE for molecular weight determination and by
ELISA for antigenicity using Env-specific monoclonal antibodies.

Indirect ELISA.

In a 96-well plate, 100 µL of antigen was coated at 2 ug/mL overnight at 4°C. The plates
were then washed three times with PBS supplemented with 0.05% Tween20 (PBS-T)
and blocked using 5% bovine serum albumin in PBS. Plates were incubated for one
hour at room temperature and then washed three times using PBS-T. Primary
antibodies were diluted in 1% BSA in PBS-T starting at 10 µg/mL with a 1:5 dilution.
After incubating at room temperature for one hour and washing with PBS-T, 100 µL of
goat anti-human IgG conjugated to peroxidase was added at a 1:10,000 dilution in 1%
BSA in PBS-T. These were incubated for one hour at room temperature, washed three
times with PBS-T, then developed using TMB substrate. Plates developed for ten
minutes at room temperature and were then stopped using 1 N sulfuric acid. Then,
absorbance was then measured at 450 nm.

Competition ELISA.

Wells of a 96-well plate were coated with 100 µL of 2 µg/mL purified BG505 N332T
SOSIP and were left at 4 °C overnight. Plates were then washed three times using
PBS-T and each well was blocked using 100ul of 5% BSA in PBS for 1 hour. After
washing three times using PBS-T, primary antibodies were diluted 10-fold starting at
100 µg/mL using 1% BSA in PBS-T and 75 µL was added each well. After incubating for
one hour at room temperature, without washing, 25 µL of biotinylated antibody was

added to each well to the final concentrations of 1 µg/mL and 0.1 µg/mL. This was
incubated at room temperature for one hour and was washed three times using PBS-T.
Then, 100 µL of streptavidin-HRP at a dilution of 1:10,000 in 1% BSA in PBST was
added to each well and was incubated for one hour at room temperature. These plates
were then washed three times and bound antibodies were detected using TMB
substrate and sulfuric acid. Competition ELISAs were repeated at least 2 times. Data is
displayed as the percentage change in binding relative to the binding of an antibody
when no competitor is present.

Structural representation of HIV reference antibodies G

A composite image of VRC01, 8ANC195, and PG9 binding BG505 Envelope was
generated by first loading PDB ID 5VJ6 into open-source PyMOL™ © Schrodinger, LLC
Version 2.4.0 [49,55]. The antibody-antigen complex was represented as a surface, and
PG9 was colored wheat, 8ANC195 in light green, gp120 in light gray, and gp41 in dark
gray. PDB ID 8VGW was then loaded into PyMOL and the gp120 structures from one
protomer were aligned to that of one gp120 protomer in 5VJ6. VRC01 was then colored
pink and shown as a surface without visualization of the Envelope protein present in its
native complex. Finally, ray tracing was performed with default parameters.

Conflicts of Interest

I.S.G. is listed as an inventor on patents filed describing antibodies characterized here.
I.S.G. is listed as an inventor on the patent applications for the LIBRA-seq technology.
I.S.G. is a co-founder of AbSeek Bio. I.S.G. has served as a consultant for Sanofi. The
Georgiev laboratory at VUMC has received unrelated funding from Merck and Takeda
Pharmaceuticals.

Bibliography

1. Lu, R.-M., Hwang, Y.-C., Liu, I.-J., Lee, C.-C., Tsai, H.-Z., Li, H.-J., and Wu, H.-C. (2020).
Development of therapeutic antibodies for the treatment of diseases. Journal of
Biomedical Science *27*, 1. https://doi.org/10.1186/s12929-019-0592-z.

2. Chames, P., Van Regenmortel, M., Weiss, E., and Baty, D. (2009). Therapeutic
antibodies: successes, limitations and hopes for the future. Br J Pharmacol *157*, 220–
233. https://doi.org/10.1111/j.1476-5381.2009.00190.x.

3. Mahomed, S. (2024). Broadly neutralizing antibodies for HIV prevention: a
comprehensive review and future perspectives. Clinical Microbiology Reviews *37*,
e00152-22. https://doi.org/10.1128/cmr.00152-22.

4.   Labrijn, A.F., Janmaat, M.L., Reichert, J.M., and Parren, P.W.H.I. (2019). Bispecific
antibodies: a mechanistic review of the pipeline. Nat Rev Drug Discov *18*, 585–608.
https://doi.org/10.1038/s41573-019-0028-1.

5.   Saphire, E.O., Schendel, S.L., Fusco, M.L., Gangavarapu, K., Gunn, B.M., Wec, A.Z.,
Halfmann, P.J., Brannan, J.M., Herbert, A.S., Qiu, X., et al. (2018). Systematic analysis of
monoclonal antibodies against Ebola virus GP defines features that contribute to
protection. Cell *174*, 938-952.e13. https://doi.org/10.1016/j.cell.2018.07.033.

6.   Zost, S.J., Gilchuk, P., Case, J.B., Binshtein, E., Chen, R.E., Nkolola, J.P., Schäfer, A.,
Reidy, J.X., Trivette, A., Nargi, R.S., et al. (2020). Potently neutralizing and protective
human antibodies against SARS-CoV-2. Nature *584*, 443–449.
https://doi.org/10.1038/s41586-020-2548-6.

7.   Olsen, T.H., Abanades, B., Moal, I.H., and Deane, C.M. (2023). KA-Search, a method for
rapid and exhaustive sequence identity search of known antibodies. Sci Rep *13*, 11612.
https://doi.org/10.1038/s41598-023-38108-7.

8.   Chen, E.C., Gilchuk, P., Zost, S.J., Suryadevara, N., Winkler, E.S., Cabel, C.R., Binshtein,
E., Chen, R.E., Sutton, R.E., Rodriguez, J., et al. (2021). Convergent antibody responses
to the SARS-CoV-2 spike protein in convalescent and vaccinated individuals. Cell
Reports *36*, 109604. https://doi.org/10.1016/j.celrep.2021.109604.

9.   Chen, E.C., Gilchuk, P., Zost, S.J., Ilinykh, P.A., Binshtein, E., Huang, K., Myers, L.,
Bonissone, S., Day, S., Kona, C.R., et al. (2023). Systematic analysis of human antibody
response to ebolavirus glycoprotein shows high prevalence of neutralizing public
clonotypes. Cell Rep *42*, 112370. https://doi.org/10.1016/j.celrep.2023.112370.

10. Abu-Shmais, A.A., Vukovich, M.J., Wasdin, P.T., Suresh, Y.P., Marinov, T.M., Rush, S.A.,
Gillespie, R.A., Sankhala, R.S., Choe, M., Joyce, M.G., et al. (2024). Antibody sequence
determinants of viral antigen specificity. mBio *15*, e01560-24.
https://doi.org/10.1128/mbio.01560-24.

11. Chinery, L., Wahome, N., Moal, I., and Deane, C.M. (2023). Paragraph—antibody
paratope prediction using graph neural networks with minimal feature vectors.
Bioinformatics *39*, btac732. https://doi.org/10.1093/bioinformatics/btac732.

12. Olsen, T.H., Boyles, F., and Deane, C.M. (2022). Observed Antibody Space: A diverse
database of cleaned, annotated, and translated unpaired and paired antibody
sequences. Protein Sci *31*, 141–146. https://doi.org/10.1002/pro.4205.

13. Richardson, E., Galson, J.D., Kellam, P., Kelly, D.F., Smith, S.E., Palser, A., Watson, S.,
and Deane, C.M. (2021). A computational method for immune repertoire mining that
identifies novel binders from different clonotypes, demonstrated by identifying anti-

pertussis toxoid antibodies. mAbs *13*, 1869406.
https://doi.org/10.1080/19420862.2020.1869406.

14. Wong, W.K., Robinson, S.A., Bujotzek, A., Georges, G., Lewis, A.P., Shi, J., Snowden, J.,
Taddese, B., and Deane, C.M. (2021). Ab-Ligity: identifying sequence-dissimilar
antibodies that bind to the same epitope. MAbs *13*, 1873478.
https://doi.org/10.1080/19420862.2021.1873478.

15. Robinson, S.A., Raybould, M.I.J., Schneider, C., Wong, W.K., Marks, C., and Deane, C.M.
(2021). Epitope profiling using computational structural modelling demonstrated on
coronavirus-binding antibodies. PLOS Computational Biology *17*, e1009675.
https://doi.org/10.1371/journal.pcbi.1009675.

16. Spoendlin, F.C., Abanades, B., Raybould, M.I.J., Wong, W.K., Georges, G., and Deane,
C.M. (2023). Improved computational epitope profiling using structural models
identifies a broader diversity of antibodies that bind to the same epitope. Frontiers in
Molecular Biosciences *10*.

17. Wang, Y., Yuan, M., Lv, H., Peng, J., Wilson, I.A., and Wu, N.C. (2022). A large-scale
systematic survey reveals recurring molecular features of public antibody responses to
SARS-CoV-2. Immunity *55*, 1105-1117.e4.
https://doi.org/10.1016/j.immuni.2022.03.019.

18. Strasser, J., de Jong, R.N., Beurskens, F.J., Wang, G., Heck, A.J.R., Schuurman, J.,
Parren, P.W.H.I., Hinterdorfer, P., and Preiner, J. (2019). Unraveling the Macromolecular
Pathways of IgG Oligomerization and Complement Activation on Antigenic Surfaces.
Nano Lett. *19*, 4787–4796. https://doi.org/10.1021/acs.nanolett.9b02220.

19. Goldberg, B.S., and Ackerman, M.E. (2020). Antibody-mediated complement activation
in pathology and protection. Immunol Cell Biol *98*, 305–317.
https://doi.org/10.1111/imcb.12324.

20. Huang, J., Kang, B.H., Ishida, E., Zhou, T., Griesman, T., Sheng, Z., Wu, F., Doria-Rose,
N.A., Zhang, B., McKee, K., et al. (2016). Identification of a CD4-Binding-Site Antibody
to HIV that Evolved Near-Pan Neutralization Breadth. Immunity *45*, 1108–1121.
https://doi.org/10.1016/j.immuni.2016.10.027.

21. Makowski, E.K., Wu, L., Gupta, P., and Tessier, P.M. Discovery-stage identification of
drug-like antibodies using emerging experimental and computational methods. MAbs
13, 1895540. https://doi.org/10.1080/19420862.2021.1895540.

22. Olsen, T.H., Moal, I.H., and Deane, C.M. (2022). AbLang: an antibody language model
for completing antibody sequences. Bioinformatics Advances *2*, vbac046.
https://doi.org/10.1093/bioadv/vbac046.

23. Bepler, T., and Berger, B. (2021). Learning the Protein Language: Evolution, Structure
and Function. Cell Syst *12*, 654-669.e3. https://doi.org/10.1016/j.cels.2021.05.017.

24. Olsen, T.H., Moal, I.H., and Deane, C.M. (2024). Addressing the antibody germline bias
and its effect on language models for improved antibody design. Preprint at bioRxiv,
https://doi.org/10.1101/2024.02.02.578678
https://doi.org/10.1101/2024.02.02.578678.

25. Burbach, S.M., and Briney, B. Improving antibody language models with native pairing.

26. Dunbar, J., Krawczyk, K., Leem, J., Baker, T., Fuchs, A., Georges, G., Shi, J., and Deane,
C.M. (2014). SAbDab: the structural antibody database. Nucleic Acids Research *42*,
D1140–D1146. https://doi.org/10.1093/nar/gkt1043.

27. Schneider, C., Raybould, M.I.J., and Deane, C.M. (2022). SAbDab in the age of
biotherapeutics: updates including SAbDab-nano, the nanobody structure tracker.
Nucleic Acids Research *50*, D1368–D1372. https://doi.org/10.1093/nar/gkab1050.

28. Punta, M., Coggill, P.C., Eberhardt, R.Y., Mistry, J., Tate, J., Boursnell, C., Pang, N.,
Forslund, K., Ceric, G., Clements, J., et al. (2012). The Pfam protein families database.
Nucleic Acids Res *40*, D290-301. https://doi.org/10.1093/nar/gkr1065.

29. Raybould, M.I.J., Kovaltsuk, A., Marks, C., and Deane, C.M. (2020). CoV-AbDab: the
Coronavirus Antibody Database. Bioinformatics, btaa739.
https://doi.org/10.1093/bioinformatics/btaa739.

30. Cao, Y., Jian, F., Wang, J., Yu, Y., Song, W., Yisimayi, A., Wang, J., An, R., Chen, X., Zhang,
N., et al. (2023). Imprinted SARS-CoV-2 humoral immunity induces convergent
Omicron RBD evolution. Nature *614*, 521–529. https://doi.org/10.1038/s41586-022-
05644-7.

31. Cao, Y., Yisimayi, A., Jian, F., Song, W., Xiao, T., Wang, L., Du, S., Wang, J., Li, Q., Chen,
X., et al. (2022). BA.2.12.1, BA.4 and BA.5 escape antibodies elicited by Omicron
infection. Nature *608*, 593–602. https://doi.org/10.1038/s41586-022-04980-y.

32. Hu, E.J., Shen, Y., Wallis, P., Allen-Zhu, Z., Li, Y., Wang, S., Wang, L., and Chen, W.
(2021). LoRA: Low-Rank Adaptation of Large Language Models. arXiv.org.
https://arxiv.org/abs/2106.09685v2.

33. Oord, A. van den, Li, Y., and Vinyals, O. (2018). Representation Learning with
Contrastive Predictive Coding. arXiv.org. https://arxiv.org/abs/1807.03748v2.

34. Chen, T., Kornblith, S., Norouzi, M., and Hinton, G. (2020). A Simple Framework for
Contrastive Learning of Visual Representations. arXiv.org.
https://arxiv.org/abs/2002.05709v3.

35. Khosla, P., Teterwak, P., Wang, C., Sarna, A., Tian, Y., Isola, P., Maschinot, A., Liu, C.,
and Krishnan, D. (2020). Supervised Contrastive Learning. arXiv.org.
https://arxiv.org/abs/2004.11362v5.

36. Maaten, L. van der, and Hinton, G. (2008). Visualizing Data using t-SNE. Journal of
Machine Learning Research 9, 2579–2605.

37. Lloyd, S.P. (1957). Lloyd, S.P. (1957) Least Square Quantization in PCM. , 28, 129-137.
https://doi.org/10.1109/TIT.1982.1056489. IEEE Transactions on Information Theory.

38. Deshpande, A., Harris, B.D., Martinez-Sobrido, L., Kobie, J.J., and Walter, M.R. (2021).
Epitope Classification and RBD Binding Properties of Neutralizing Antibodies Against
SARS-CoV-2 Variants of Concern. Front Immunol 12, 691715.
https://doi.org/10.3389/fimmu.2021.691715.

39. Berman, H., Henrick, K., and Nakamura, H. (2003). Announcing the worldwide Protein
Data Bank. Nat Struct Mol Biol 10, 980–980. https://doi.org/10.1038/nsb1203-980.

40. Berman, H., Henrick, K., Nakamura, H., and Markley, J.L. (2007). The worldwide Protein
Data Bank (wwPDB): ensuring a single, uniform archive of PDB data. Nucleic Acids Res
35, D301–D303. https://doi.org/10.1093/nar/gkl971.

41. Protein Data Bank: the single global archive for 3D macromolecular structure data -
PMC https://pmc-ncbi-nlm-nih-gov.proxy.library.vanderbilt.edu/articles/PMC6324056/.

42. Scheid, J.F., Mouquet, H., Ueberheide, B., Diskin, R., Klein, F., Oliveira, T.Y.K., Pietzsch,
J., Fenyo, D., Abadir, A., Velinzon, K., et al. (2011). Sequence and Structural
Convergence of Broad and Potent HIV Antibodies That Mimic CD4 Binding. Science
333, 1633–1637. https://doi.org/10.1126/science.1207227.

43. Scharf, L., Scheid, J.F., Lee, J.H., West, A.P., Chen, C., Gao, H., Gnanapragasam, P.N.P.,
Mares, R., Seaman, M.S., Ward, A.B., et al. (2014). Antibody 8ANC195 Reveals a Site of
Broad Vulnerability on the HIV-1 Envelope Spike. Cell Reports 7, 785–795.
https://doi.org/10.1016/j.celrep.2014.04.001.

44. Scharf, L., Wang, H., Gao, H., Chen, S., McDowall, A.W., and Bjorkman, P.J. (2015).
Broadly Neutralizing Antibody 8ANC195 Recognizes Closed and Open States of HIV-1
Env. Cell 162, 1379–1390. https://doi.org/10.1016/j.cell.2015.08.035.

45. Griffith, S.A., and McCoy, L.E. (2021). To bnAb or Not to bnAb: Defining Broadly
Neutralising Antibodies Against HIV-1. Front. Immunol. 12.
https://doi.org/10.3389/fimmu.2021.708227.

46. Setliff, I., Shiakolas, A.R., Pilewski, K.A., Murji, A.A., Mapengo, R.E., Janowska, K.,
Richardson, S., Oosthuysen, C., Raju, N., Ronsard, L., et al. (2019). High-Throughput

Mapping of B Cell Receptor Sequences to Antigen Specificity. Cell *179*, 1636-1646.e15.
https://doi.org/10.1016/j.cell.2019.11.003.

47. Walker, L.M., Shiakolas, A.R., Venkat, R., Liu, Z.A., Wall, S., Raju, N., Pilewski, K.A.,
Setliff, I., Murji, A.A., Gillespie, R., et al. (2022). High-Throughput B Cell Epitope
Determination by Next-Generation Sequencing. Frontiers in Immunology *13*.
https://doi.org/10.3389/fimmu.2022.855772.

48. Henderson, R., Anasti, K., Manne, K., Stalls, V., Saunders, C., Bililign, Y., Williams, A.,
Bubphamala, P., Montani, M., Kachhap, S., et al. (2024). Engineering immunogens that
select for specific mutations in HIV broadly neutralizing antibodies. Nat Commun *15*,
9503. https://doi.org/10.1038/s41467-024-53120-9.

49. Wang, H., Gristick, H.B., Scharf, L., West, A.P., Jr, Galimidi, R.P., Seaman, M.S., Freund,
N.T., Nussenzweig, M.C., and Bjorkman, P.J. (2017). Asymmetric recognition of HIV-1
Envelope trimer by V1V2 loop-targeting antibodies. eLife *6*, e27389.
https://doi.org/10.7554/eLife.27389.

50. Jespers, L.S., Roberts, A., Mahler, S.M., Winter, G., and Hoogenboom, H.R. (1994).
Guiding the selection of human antibodies from phage display repertoires to a single
epitope of an antigen. Biotechnology (N Y) *12*, 899–903.
https://doi.org/10.1038/nbt0994-899.

51. Zielezinski, A. (2025). aziele/pfam_scan.

52. Kabsch, W., and Sander, C. (1983). Dictionary of protein secondary structure: Pattern
recognition of hydrogen-bonded and geometrical features. Biopolymers *22*, 2577–2637.
https://doi.org/10.1002/bip.360221211.

53. Henikoff, S., and Henikoff, J.G. (1992). Amino acid substitution matrices from protein
blocks. Proc Natl Acad Sci U S A *89*, 10915–10919.

54. Needleman, S.B., and Wunsch, C.D. (1970). A general method applicable to the search
for similarities in the amino acid sequence of two proteins. Journal of Molecular Biology
48, 443–453. https://doi.org/10.1016/0022-2836(70)90057-4.

55. The PyMOL Molecular Graphics System (2010). Version 2.4.0 (Schrodinger, LLC).

56. Wolf, T., Debut, L., Sanh, V., Chaumond, J., Delangue, C., Moi, A., Cistac, P., Rault, T.,
Louf, R., Funtowicz, M., et al. (2019). HuggingFace's Transformers: State-of-the-art
Natural Language Processing. arXiv.org. https://arxiv.org/abs/1910.03771v5.

57. Liu, Y., Ott, M., Goyal, N., Du, J., Joshi, M., Chen, D., Levy, O., Lewis, M., Zettlemoyer, L.,
and Stoyanov, V. (2019). RoBERTa: A Robustly Optimized BERT Pretraining Approach.
arXiv.org. https://arxiv.org/abs/1907.11692v1.

58. Chen, T., Kornblith, S., Swersky, K., Norouzi, M., and Hinton, G. (2020). Big Self-
Supervised Models are Strong Semi-Supervised Learners. arXiv.org.
https://arxiv.org/abs/2006.10029v2.

59. [2004.11362] Supervised Contrastive Learning https://arxiv-
org.proxy.library.vanderbilt.edu/abs/2004.11362.

60. Xie, X. jbloomlab SARS2_RBD_Ab_escape_data Xie_XS.
https://media.githubusercontent.com/media/jbloomlab/SARS2_RBD_Ab_escape_map
s/refs/heads/main/processed_data/escape_data.csv
https://media.githubusercontent.com/media/jbloomlab/SARS2_RBD_Ab_escape_map
s/refs/heads/main/processed_data/escape_data.csv.

61. Greaney, A.J., Starr, T.N., and Bloom, J.D. (2022). An antibody-escape estimator for
mutations to the SARS-CoV-2 receptor-binding domain. Virus Evolution *8*, veac021.
https://doi.org/10.1093/ve/veac021.

62. Sankhala, R.S., Dussupt, V., Chen, W.-H., Bai, H., Martinez, E.J., Jensen, J.L., Rees, P.A.,
Hajduczki, A., Chang, W.C., Choe, M., et al. (2024). Antibody targeting of conserved
sites of vulnerability on the SARS-CoV-2 spike receptor-binding domain. Structure *32*,
131-147.e7. https://doi.org/10.1016/j.str.2023.11.015.

63. Virtanen, P., Gommers, R., Oliphant, T.E., Haberland, M., Reddy, T., Cournapeau, D.,
Burovski, E., Peterson, P., Weckesser, W., Bright, J., et al. (2020). SciPy 1.0: fundamental
algorithms for scientific computing in Python. Nat Methods *17*, 261–272.
https://doi.org/10.1038/s41592-019-0686-2.

64. Wu, X., Yang, Z.-Y., Li, Y., Hogerkorp, C.-M., Schief, W.R., Seaman, M.S., Zhou, T.,
Schmidt, S.D., Wu, L., Xu, L., et al. (2010). Rational Design of Envelope Identifies
Broadly Neutralizing Human Monoclonal Antibodies to HIV-1. Science *329*, 856–861.
https://doi.org/10.1126/science.1187659.

65. Alamyar, E., Duroux, P., Lefranc, M.-P., and Giudicelli, V. (2012). IMGT(®) tools for the
nucleotide analysis of immunoglobulin (IG) and T cell receptor (TR) V-(D)-J repertoires,
polymorphisms, and IG mutations: IMGT/V-QUEST and IMGT/HighV-QUEST for NGS.
Methods Mol Biol *882*, 569–604. https://doi.org/10.1007/978-1-61779-842-9_32.

66. IMGT/HIGHV-QUEST: THE IMGT® WEB PORTAL FOR IMMUNOGLOBULIN (IG) OR
ANTIBODY AND T CELL RECEPTOR (TR) ANALYSIS FROM NGS HIGH THROUGHPUT
AND DEEP SEQUENCING (2012). Immunome Res *08*. https://doi.org/10.4172/1745-
7580.1000056.

67. Li, S., Lefranc, M.-P., Miles, J.J., Alamyar, E., Giudicelli, V., Duroux, P., Freeman, J.D.,
Corbin, V.D.A., Scheerlinck, J.-P., Frohman, M.A., et al. (2013). IMGT/HighV QUEST

paradigm for T cell receptor IMGT clonotype diversity and next generation repertoire
immunoprofiling. Nat Commun *4*, 2333. https://doi.org/10.1038/ncomms3333.

68. V, G. (2015). From IMGT-ONTOLOGY to IMGT/HighVQUEST for NGS Immunoglobulin (IG)
and T cell Receptor (TR) Repertoires in Autoimmune and Infectious Diseases.
Autoimmun Infec Dis *1*. https://doi.org/10.16966/2470-1025.103.

69. Stewart-Jones, G.B.E., Chuang, G.-Y., Xu, K., Zhou, T., Acharya, P., Tsybovsky, Y., Ou, L.,
Zhang, B., Fernandez-Rodriguez, B., Gilardi, V., et al. (2018). Structure-based design of
a quadrivalent fusion glycoprotein vaccine for human parainfluenza virus types 1–4.
Proceedings of the National Academy of Sciences *115*, 12265–12270.
https://doi.org/10.1073/pnas.1811980115.

70. Georgiev, I.S., Joyce, M.G., Yang, Y., Sastry, M., Zhang, B., Baxa, U., Chen, R.E., Druz, A.,
Lees, C.R., Narpala, S., et al. (2015). Single-Chain Soluble BG505.SOSIP gp140 Trimers
as Structural and Antigenic Mimics of Mature Closed HIV-1 Env. J Virol *89*, 5318–5329.
https://doi.org/10.1128/JVI.03451-14.

1113

Motivating Question:

Can antibody sequence features predict epitope overlap?

Figure 1

Figure 2

Figure 3

Figure 4

Figure 5

A

Name	8ANC195 Cosine Similarity	8ANC195 % Identity		Gene Usage				Germline % Identity		CDR Information			
		Heavy Chain	Light Chain	VH	JH	VK/L	JK/L	VH	VL	CDRH3	CDRL3	CDRH Lengths	CDRL Lengths
2723-3055 (1-0)	0.655	37	48	IGHV1-2	IGHJ4	IGKV3-20	IGKJ2	70	72	VRGRSCCDGRRYCNGADCFNWDFEH	QCF......EG	8.8.25	7.3.5
2723-6245 (1-1)	0.653	35	46	IGHV1-2	IGHJ4	IGKV3-20	IGKJ2	72	76	VRGSSCCGGRRHCNGADCFNWDFQY	QCL......EA	8.8.25	7.3.5
3602-2 (1-2)	0.650	38	51	IGHV1-46	IGHJ4	IGKV3-20	IGKJ3	73	86	AKDAGEPGWTAY..RRGYPIFFFDT	QQYVR..TPLT	8.8.23	7.3.9
5157-3 (1-3)	0.621	45	39	IGHV1-8	IGHJ3	IGLV2-14	IGLJ3	74	81	AVATI...............SAFDI	SSYIHTGPPWL	8.8.10	9.3.11
3514-4 (1-4)	0.619	38	39	IGHV1-2	IGHJ5	IGLV3-10	IGLJ2	77	85	YIFIHWA...........NGYMKDH	YSTHS.SLYSA	8.8.14	6.3.10
3602-870 (1-5)	0.610	37	55	IGHV1-46	IGHJ4	IGKV3-20	IGKJ3	72	83	ARDAGERGLR......GYSVGFFDS	HQYG..TTPYT	8.8.19	7.3.9
2723-6 (1-6)	0.603	37	45	IGHV1-2	IGHJ1	IGKV3-20	IGKJ2	68	77	ARGKSCCEGRRFCSPNDCYNWDFEH	QFH......EA	8.8.25	7.3.5
2723-4886 (1-7)	0.602	33	50	IGHV1-2	IGHJ1	IGKV3-20	IGKJ2	66	75	AMRDYCRDD.......NCNIWDLRH	QHR......ET	8.8.18	6.3.5
4513-8 (1-8)	0.582	45	53	IGHV1-69	IGHJ4	IGKV3D-20	IGKJ4	78	86	ARGGFSN............NWLGAY	HQYGF..APLT	8.8.13	7.3.9
6420-9 (1-9)	0.567	49	40	IGHV1-69	IGHJ4	IGLV7-46	IGLJ2	85	94	ARETLGYSG........SYGPAFDF	LLSHS..GVPV	8.8.17	9.3.9
8ANC195 (+)	1.000	100	100	IGHV1-69	IGHJ4	IGKV1-5	IGKJ1	53	86	TTTSTYDKWSG...LHHDGVMAFSS	QQYDT..YPGT	9.7.25	7.3.9
VRC01	0.534	39	58	IGHV1-2	IGHJ2	IGKV3-20	IGKJ2	69	64	TRGKNCD..........YNWDFEH	QQY......EF	8.8.14	6.3.5

B

LIBRA-seq Dataset Similarities

C

ELISA Binding

D

E

Reduction in 8ANC195 Binding

F

BG505 SOSIP.664 Competition ELISA

Figure 6