# Predictive Coding Explains Asymmetric Connectivity in the Brain: A Neural Network Study

**Romesa Khan[1], Hongsheng Zhong[2], Shuvam Das[2], Jack Cai[3], Matthias Niemeier[1,4,5,*]**

[1] Department of Psychology, University of Toronto Scarborough, Toronto, ON, Canada, M1C1A4

[2] Department of Computer Science, University of Toronto, Toronto, ON, Canada, M5S1A1

[3] Department of Electrical and Computer Engineering, University of Toronto, Toronto, ON, Canada, M5S1A1

[4] Centre for Vision Research, York University, Toronto, ON, Canada, M4N3M6

[5] Vision: Science to Applications, York University, Toronto, ON, Canada, M4N3M6

[*] Correspondence concerning this article should be addressed to Matthias Niemeier at m.niemeier@utoronto.ca

**Conflict of interest statement**: The authors declare no competing financial interests.

**Acknowledgement:** This research was supported in part by a grant from the Natural Sciences and Engineering Research Council of Canada (NSERC).

**Abstract**

Seminal frameworks of predictive coding propose a hierarchy of generative modules, each attempting to infer the neural representation of the module one level below; the predictions are carried by top-down feedback projections, while the predictive error is propagated by reciprocal forward pathways. Such symmetric feedback connections support visual processing of noisy stimuli in computational models. However, neurophysiological studies have yielded evidence of asymmetric cortical feedback connections. We investigated the contribution of neural feedback during sensorimotor processes, in particular visual processing during grasp planning, by utilizing convolutional neural network models that had been augmented with predictive feedback and were trained to compute grasp positions for real-world objects. After establishing an ameliorative effect of symmetric feedback on grasp detection performance when evaluated on noisy stimuli, we characterized the performance effects of asymmetric feedback, similar to that observed in the cortex. Specifically, we tested model variants extended with *short*-, *medium*- and *long*-range feedback connections (i) originating at the same source layer or (ii) terminating at the same target layer. We found that the performance-enhancing effect of predictive coding under adverse conditions was optimal for *medium*-range asymmetric feedback. Moreover, this effect was most prominent when *medium*-range feedback originated at a level of representational abstraction that was proximal to the input layer, in contrast to more distal layers. To conclude, our simulations show that introducing biologically realistic asymmetric predictive feedback improves model robustness to noisy visual stimuli in a neural network model optimized for grasp detection.

40                                    **Significance statement**

It is commonly held that the brain predicts the causes of its sensorium via top-down neural

pathways. While canonical models of predictive coding assume reciprocal feedforward and

feedback connections, functional evidence highlights the importance of non-reciprocal

'asymmetric' feedback, whose role remains poorly understood, particularly in sensorimotor

functions. Using neural network models of grasp planning, we characterized optimal pathlengths

and source regions for asymmetric feedback facilitating visuomotor processing of noisy sensory

inputs. Our findings show that *medium*-range feedback from early layers marks a sweet spot,

incorporating optimal distance between the neural representations of source/target layers and

representational abstraction of the feedback source. This intimates an uncharted role of

intermediate brain areas along the visuomotor stream as a source of predictive signals.

**Introduction**

Descending neural pathways transmit neural signals from higher cortical areas back to

earlier processing stages, enabling top-down modulation of lower-level neural circuits. Such

feedback has been recognized as central for perceptual and cognitive processes, enabling the

brain to implement learning mechanisms (Roelfsema & Holtmaat, 2018), attentional modulation

(Baluch & Itti, 2011; Desimone & Duncan, 1995) and refinement of sensory representations

based on context, expectations, and prior experience (Gilbert & Li, 2013; Kok, Jehee, et al.,

2012; Mumford, 1992). Crucially, feedback is believed to be instrumental for conveying

predictions.

That is, the brain has been widely conceptualized as a "prediction machine" that relies on

internal generative models to actively construct explanations for the causes of noisy sensory

inputs (Friston, 2005). Specifically, it is held that predictive feedback signals are conveyed via

cortico-cortical top-down projections that are then compared to bottom-up signals such that the

deviations from these signals, in the form of predictions errors, are carried forward. An

influential framework of such predictive coding proposes a hierarchy of generative modules,

each attempting to infer the neural representation of the module below, with topographically

reciprocal feedforward connections (Lee & Mumford, 2003; Pennartz et al., 2019; Rao &

Ballard, 1999a; Shipp, 2016).  This idea maps well on previous anatomical data: Felleman and

Van Essen (1991) proposed a hierarchical model of the visual cortex where adjacent areas often

maintain both feedforward and feedback pathways, implying a measure of reciprocity in the

network (Markov et al., 2011; Rockland & Pandya, 1979). Indeed, tracing studies in macaques

reveal that reciprocal links between closely related visual areas significantly account for

interareal communication (Markov et al., 2011). Such symmetric feedback connections are

particularly important for object recognition under noisy or ambiguous viewing conditions. Hupé

et al. (1998) have shown that area V2 modulates V1 responses, enhancing the detection of

figures embedded in cluttered or noisy images. Furthermore, recurrent interactions between V1

and higher visual areas, including V2, are crucial for figure–ground segregation (Lamme &

Roelfsema, 2000). Similarly, in computer simulations, symmetric feedback connections support

object discrimination (Wen et al., 2018), particularly when processing noisy stimuli (Choksi et

al., 2021; Huang et al., 2020).

However, there is growing evidence of asymmetric, non-reciprocated cortical feedback

connections from quantitative mapping studies (Markov et al., 2014; Salin & Bullier, 1995).

Long-range descending pathways cascade over multiple cortical areas (Kravitz et al., 2013;

Rockland & Van Hoesen, 1994), and an advantage of long-latency over short-latency visuomotor

feedback has been observed during cortical reward processing (Codol et al., 2023). Furthermore,

experiments studying visuospatial attention in primates indicate a functional role of medium-

range predictive feedback, extending from area V4 to area V1, in encoding accuracy of input

stimuli (Debes & Dragoi, 2023), suggesting a potential benefit of *medium*-range feedback in

signal processing under noise. This is similar to the previously suggested role of *medium*-range

feedback in disambiguating signal from noise during global contour integration (Chen et al.,

2014).

To investigate the contribution of asymmetrical neural feedback, here we simulated

sensorimotor functions utilizing convolutional neural networks (CNNs) as a modelling

framework. Hierarchical CNN architectures have been commonly used for object recognition

tasks (Girshick et al., 2014) and are posited as suitable models of vision in the primate brain

(Guclu & van Gerven, 2015; Yamins et al., 2014). Crucially, rather than solely relying on the

feedforward flow of information in the canonical architecture of CNNs, we augmented them with

symmetric, or asymmetric generative feedback loops that carried advanced representations to

earlier layers of the networks, mimicking various aspects of feedback in the biological brain. The

aim of the study was to understand (a) if an ameliorative effect of feedback can be isolated

during action-guided visual tasks when the incoming signal is corrupted, and (b) to explore the

layer-dependence of such predictive feedback in our model, thus shedding light on the relative

functional contribution of cortico-cortical connectivity of asymmetric feedback originating at

varying levels of representational abstraction.

105                                             **Methods**

106     **Neural network architecture**

107             We first trained two versions of a feedforward model, a short and a long backbone, on the

108     task of grasp point generation. As a second step we then augmented the networks with feedback

109     connections (feedback model) that conveyed predictive signals.

110             **Short feedforward model.** In detail, for step 1 we obtained the architecture of the short

backbone model by modifying a custom convolutional neural network (CNN) architecture (see

Figure 1(a)) into which we inputted photographic images with 4 channels (aside from red, green,

and blue there was a depth channel, RGB-D, as an approximation of stereovision, that is known

to be relevant for grasp performance (Watt & Bradshaw, 2000b)). The RGB-D images were

passed into an input layer with two arms, specialized for receiving RGB and depth channels,

respectively. The backbone contained a 'feature compression' module consisting of 4

convolution blocks that were connected through maximum pooling (MaxPool) layers to attain

dimensionality reduction and invariant feature extraction (Simonyan & Zisserman, 2014). That

is, each convolution block consisted of two or three convolution (Conv) layers, each of which

was sandwiched together with a batch normalization (BN) and a rectified linear unit (ReLU)

activation layer. Next, we added a 'feature expansion' module, composed of Conv and

ConvTranspose2d layers (Paszke et al., 2019) that upscaled the feature maps back to the same

spatial dimensions as the input (i.e., the entire network had an autoencoder style architecture).

The output layer was a regression head that generated a 6-channel array of pixel-wise maps, each

corresponding to one of six grasp parameters required for grasping (grasp centre coordinates (x,

y); orientation; grasp opening; gripper size; grasp quality score), similar to (Kumra et al., 2022).

The sole purpose of the feature expansion module together with its map-style output was not to

attain biological realism but to facilitate interpolation of the infinite number of correct grasp

solutions from the finite set of ground truth labels thereby facilitating training of the feedforward

network (e.g., (Kumra et al., 2022)). The network architecture of the short backbone is detailed

in Table 1.

132            **Long feedforward model.** The long backbone once again had a compression module

followed by an expansion module similar to the short backbone, except, here the compression

module comprised of a VGG16 model (Simonyan & Zisserman, 2014) with 5 convolution blocks

where each convolution block contained two or three Conv layers with ReLU activation layers,

followed by a MaxPool layer, and BN layers interspersed between each Conv and ReLU layer.

Just like before the model architecture was modified with a two-arm input layer to receive 4-

channel RGB-D input images. Also, the classification head of the canonical VGG16 architecture

was replaced with the same regression head as the short backbone model to return the required

parametric map output (see Table 1 for details).

**Predictive coding dynamics for feedback models**

143            After training the feedforward backbone models, we augmented them with generative

feedback connections adapting the PyTorch *Predify* library (Choksi et al., 2021) with some

modifications that we made to the original code to introduce custom feedback connectivity. The

library is designed to add predictive coding dynamics to existing deep neural networks. The

predictive coding framework posits that the brain maintains an internal model of the world to

actively predict sensory inputs (Rao & Ballard, 1999b). In this hierarchical model, higher areas

generate predictions for lower areas, and discrepancies between predicted and actual inputs

(prediction errors) are used to update and refine the higher-layer representations. This iterative

process allows the network to minimize prediction errors and enhance perception of sensory

information. For example, CNNs have been recently combined with feedback mechanisms for

robust object perception (Choksi et al., 2021; Huang et al., 2020).

In the present study, we selected $N$ encoding modules, $e_n$ ($n \in \{1, 2, \ldots, N\}$ with $N \in \mathbb{Z}^+$) from

the network backbone of the feedforward model and added $N$ corresponding decoding modules,

$d_n$. An encoding module, $e_n$, and the corresponding decoding module, $d_n$, collectively

constituted a *PCoder*. Each $e_n$ (except for e$_I$) consisted of the MaxPool layer of a given

convolution block and the two or three Conv/BN/ReLU layers of the subsequent convolution

block. The output of $e_n$ was then passed through a feedback layer (deconvolution layer) $d_n$ that

predicted the output of the last Conv/BN/ReLU layer of the previous convolution block (target).

To this end, each $d_n$ consisted of a ConvTranspose2d layer that upscaled the input feature map to

match the spatial dimensions of the target with feedback weights connecting module $n + 1$ to

module $n$ being denoted by $W^b_{n+1,n}$. This way, when an input image initially activated all

encoding modules through a feedforward pass, over subsequent successive recurrent iterations

(timesteps $t$), both the decoding and encoding module representations were updated using the

following equations:

$$d_n(t) = W^b_{n+1,n} e_{n+1}(t) \tag{1}$$

$$e_n(t + 1) = e_n(\beta_n e_{n-1}(t + 1) + \lambda_n d_{n-1}(t) + \gamma_n e_n(t) - \alpha_n \nabla \epsilon_{n-1}(t) \tag{2}$$

Here, $\beta_n, \lambda_n, \gamma_n$ (with $\beta_n + \lambda_n + \gamma_n = 1$) and $\alpha_n$ served as balancing coefficients for the

feedforward, feedback, recurrence and error-correction terms, respectively. The recurrence term,

$\gamma_n$, functioned as a memory buffer for retaining the encoding representation at the current

timestep. The reconstruction error at module $n - 1$, denoted $\epsilon_{n-1}(t)$, was defined as the mean

squared error (MSE) between the feedforward representation $e_{n-1}(t)$ and the predicted

reconstruction $d_{n-1}(t)$ at that timestep. The feedforward and feedback weights remained frozen

across iterations.

**Feedback models.** Modifications were made to the original code from (Choksi et al.,

2021) to introduce custom feedback connectivity to the forward models.

***Experiment 1.*** To test whether predictive coding aids not only object classification

(Choksi et al., 2021; Huang et al., 2020) but also visuomotor processes, the network backbone of

the short backbone model was augmented with 4 consecutive PCoders, similar to the feedback

connectivity pattern attempted in (Choksi et al., 2021). The feedback connectivity for

Experiment 1 is shown in Figure 1(a).

***Experiment 2.*** In order to identify the most effective source of feedback, feedback

connections were implemented with a consistent feedback target layer and varying feedback

source layers across model variants. Specifically, for each feedback type, 2 PCoders were

designed. For Experiment 2, $e_1$ was kept fixed as the first convolution block, across all feedback

model variants. Notably, the feedback target layer for $e_1$ was the input layer of the network; the

input representations were configured to be static and were not updated by iterative recurrent

mechanisms. The associated feedback loop was merely an appendage, which had no functional

effect but was required in the model architecture for technical reasons. Additionally, the feedback

source layer of $e_2$ did not receive any recurrent feedback. Therefore, all model variants of

feedback connectivity effectively contained a single functional loop of feedback, shown as solid

red lines in Figure 2, for controlled comparisons between different feedback types.

*Short backbone.* Three variants of feedback connectivity were compared: *short*-range,

*medium*-range and *long*-range feedback, as shown in Figure 2(a). $e_1$ comprised of the

Conv/BN/ReLU layers of convolution block 1 for all model variants. $e_2$ comprised of the

following: the MaxPool layer of block 1 and the Conv/BN/ReLU layers of block 2 (*short*-range);

the MaxPool layers of blocks 1 and 2, and the Conv/BN/ReLU layers of blocks 2 and 3 (*medium-*

range); the MaxPool layers of blocks 1, 2 and 3, and the Conv/BN/ReLU layers of blocks 2,3 and

4 (*long*-range).

*Long backbone.* Four variants of feedback connectivity were compared: *short*-range,

*medium*-range, *long*-range and *longer*-range feedback, illustrated in Figure 2(a). Similar to the

short backbone, $e_1$ comprised of the Conv/BN/ReLU layers of convolution block 1 for all model

variants. $e_2$ comprised of the following: the MaxPool layer of block 1 and the Conv/BN/ReLU

layers of block 2 (*short*-range); the MaxPool layers of blocks 1 and 2, and the Conv/BN/ReLU

layers of block 2 and 3 (*medium*-range); the MaxPool layers of blocks 1 ,2 and 3, and the

Conv/BN/ReLU layers of block 2, 3 and 4 (*long*-range); the MaxPool layers of blocks 1, 2, 3 and

4, and the Conv/BN/ReLU layers of block 2, 3, 4 and 5 (*longer*-range).

**Experiment 3.** To further isolate any effects of the feedback target layer, the feedback

source layer was kept constant, while varying feedback target layers across model variants.

Again, 2 PCoders were introduced into the feedforward network. Crucially, the feedback

connection emanating from $e_2$ was the only functional feedback loop. For all model variants, $e_1$

spanned a single Conv layer that immediately precedes $e_2$.

*Short backbone.* Three variants of feedback connectivity were compared: *short*-range,

*medium*-range and *long*-range feedback. The feedback source layer of $e_2$ was kept fixed as the

final ReLU layer of convolution block 4 for all feedback variants.  $e_2$ comprised of the

following: the MaxPool layer of block 3 and the Conv/BN/ReLU layers of block 4 (*short*-range);

the MaxPool layers of blocks 2 and 3, and the Conv/BN/ReLU layers of blocks 3 and 4 (*medium-*

range); the MaxPool layers of blocks 1,2 and 3, and the Conv/BN/ReLU layers of blocks 2, 3 and

4 (*long*-range). These model variants of feedback connectivity are shown in Figure 3(a).

*Long backbone.* Four variants of feedback connectivity were compared: *short*-range,

*medium*-range, *long*-range and *longer*-range feedback. The feedback source layer of $e_2$ was

maintained as the final ReLU layer of convolution block 5 for all feedback variants. $e_2$

comprised of the following: the MaxPool layer of block 4 and the Conv/BN/ReLU layers of

block 5 (*short*-range); the MaxPool layers of blocks 3 and 4, and the Conv/BN/ReLU layers of

blocks 4 and 5 (*medium*-range); the MaxPool layers of blocks 2, 3 and 4, and the

Conv/BN/ReLU layers of blocks 3, 4 and 5 (*long*-range); the MaxPool layers of blocks 1, 2, 3

and 4, and the Conv/BN/ReLU layers of blocks 2, 3, 4 and 5 (*longer*-range). Model variants of

feedback connectivity are shown in Figure 3(a).

***Experiment 4.*** The effect the abstraction level of the feedback source on model

performance was also investigated. *Medium*-range feedback (i.e., the most effective feedback

distance in Experiments 2 and 3) was implemented at three different levels of abstraction along

the long backbone: *proximal*, *intermediate* and *distal* feedback loops. The naming convention is

in relation to the distance from the input layer of the network. For each level of source

abstraction, 2 PCoders were integrated into the network backbone. Like Experiment 2, feedback

emerging from $e_2$ was the only operant feedback connection, whereas the feedback loop across

$e_1$ traversed a single layer and had no predictive function.

For the three model variants, $e_2$ comprised of the MaxPool layers of blocks 1 and 2, and

the Conv/BN/ReLU layers of blocks 2 and 3 (*proximal*); the MaxPool layers of blocks 2 and 3,

and the Conv/BN/ReLU layers of blocks 3 and 4 (only the first two Conv/BN/ReLU layers of

block 4 were included in order to implement *medium*-range feedback distance) (*intermediate*);

the MaxPool layers of blocks 3 and 4, and the Conv/BN/ReLU layers of blocks 4 and 5 (only the

first two Conv/BN/ReLU layers of block 5 were included in order to maintain *medium*-range

feedback distance) (*distal*). The model variants of medium-range feedback that were

implemented are detailed in Figure 4(a).

**Model training and hyperparameters**

Both, short and long backbone models were initialized with random weights (Xavier

initialization) and trained on the task of grasp parameter estimation. Training involved error

back-propagation and gradient descent to minimize the mean squared error (MSE) loss for the

pixelwise regression output.

After hyperparameter optimization using a grid search strategy, both, the short and long

forward models were trained using a Ranger optimizer, with a learning rate of 0.01, weight decay

of 0, and a batch size of 75. The short and long backbone models were trained for 17 and 9

epochs, respectively.

The feedback models were created by adding recurrent feedback to the already trained

backbone models. The activations of all encoding modules, $e_n$ were initiated with a feedforward

pass. Then the forward weights were frozen, and the weights of the feedback deconvolution

layers, $d_n$, were trained using an unsupervised reconstruction objective. This seeks to minimize

the reconstruction loss (prediction error), modelled as MSE between the outputs of $e_{n-1}$ and $d_n$.

Hyperparameters for predictive coding dynamics, including layer-dependent balancing

coefficients for the feedforward ($\beta_n$), feedback ($\lambda_n$), recurrence ($\gamma_n$) and error-correction ($\alpha_n$)

terms, were optimized using a grid search strategy. The respective hyperparameters were

conserved across all model variants within each experiment and are presented in Table 2.

Model training was performed on the NVIDIA T4 and the NVIDIA QUADRO RTX 8000

GPUs.

**Dataset**

Both, the backbone and feedback models, were trained on the grasp detection task using

the large-scale Jacquard dataset for robotic grasp detection (Depierre et al., 2018). The Jacquard

dataset is composed of 11,619 distinct objects with a total of ~5,000,000 possible grasp

annotations. The grasp annotations corresponding to each image constituted a list of grasp

candidate labels. Each grasp candidate was described by parameters including center pixel

coordinates (x, y), orientation (theta), and dimensions (pixel width, pixel height) of the grasp.

For each object instance (a distinct camera viewpoint of an object), a rendered RGB image, a

segmentation mask, two depth images and the grasps annotations are available. The dataset was

split into three parts: 66% for model training, 17% for model validation, and 17% for model

testing.

*Preprocessing*. The data preprocessing pipeline transformed lists of grasp candidates into

pixel-wise grasp maps. A grasp map array, of spatial dimensions corresponding to the image size,

was initialized with six channels to represent the five grasp parameters and a count of

overlapping grasp bounding boxes for each pixel.  The preprocessing operation converted grasp

annotations to bounding boxes, identified the bounding box boundaries, and iterated over each

pixel within these boundaries to determine the grasp candidate closest to the pixel based on

Euclidean distance. Each pixel was then labeled with the attributes of the nearest grasp and the

count of valid bounding boxes covering it. The final channel, representing the count of bounding

boxes per pixel, was normalized by dividing by the maximum count across all pixels. This

preprocessed data format was used for training the backbone and feedback neural network

models on the task of predicting grasp locations in an input image.

Feature normalization was applied to all images (RGB and depth) and grasp labels, to

promote training stability and model convergence. Image pixel intensities and label values were

normalized to a range between 0 and 1.

*Additive noise*. During model inference, all test images were injected with varying levels

of additive Gaussian noise of standard deviation, $\sigma \in \{0, \; 0.25, 0.5, 0.75, 1\}$.

**Statistics**

A repeated measures analysis of variance (ANOVA) (Girden, 1992) was conducted to assess the

effects of feedback type and noise level on the grasp detection accuracy of the model, using the

Jamovi statistical software (The jamovi project, 2024). This analysis accounted for within-object

effects and included tests for sphericity. Mauchly's test of sphericity (Mauchly, 1940) was

performed to check the assumption of sphericity for feedback type, noise level, and their

interaction. Where the assumption was violated, Greenhouse-Geisser corrections (Greenhouse &

Geisser, 1959) were applied to adjust the degrees of freedom. Post hoc comparisons were

conducted using Tukey's HSD test (Tukey, 1949) to evaluate pairwise differences between the

levels of feedback type.

A One-Way ANOVA (David C. Howell, 2002) was conducted to compare the difference

in model performance between the first and final timestep during the test, across noise different

noise levels (The jamovi project, 2024).

**Code Availability**

All code used for this study is available at https://github.com/khanrom/Feedback_Grasping.

312                                    **Results**

We investigated the contribution of feedback to vision for action, such as grasp planning,

using a neural network model that was optimized to detect grasp points on objects.

**Feedback improves robustness of sensorimotor control to noise**

We evaluated the effect of predictive feedback on the performance of the trained model,

when presented with adversarial images that were injected with varying levels of Gaussian noise

$(\sigma = \{0, 0.25, 0.5, 0.75, 1.0\})$ (Experiment 1 in Methods). In effect, the performance of a

feedback model at the first timestep $(t = 1)$ of the iterative predictive coding dynamics is

identical to the performance of the corresponding feedforward backbone. This backbone

performance was compared to the performance of the feedback model after several recurrent

timesteps $(t = 15)$ after which performance no longer changed. We observed an improvement in

the grasp detection accuracy of the model after predictive coding iterations, across all levels of

Gaussian noise (Figure 1B; n.b., there was a small decline in performance for zero noise). The

average difference in model performance between the first $(t = 0)$ and the final $(t = 15)$

timestep was significant across noise levels, $F(4, 22267) = 220036.00, p < .001$ (Figure 1C).

Figure 1E depicts progressive noise removal in the model output (represented by the grasp

quality score map) across successive predictive coding timesteps, for a sample object from the

test dataset (Figure 1D).

**Performance-related effects of feedback are layer-dependent**

Next, we tested whether the performance-enhancing effects of feedback were contingent

on layer-specific feedback connectivity. To probe this question, we contrasted different patterns

of feedback connectivity.

**Constant feedback target.** First, we set up model variants augmented with a constant

feedback target (final ReLU layer of convolution block 1) that received *short-*, *medium-*, or *long-*

range feedback, for the short backbone and an additional *longer*-range feedback variant for the

long backbone, as detailed in the Methods (see Experiment 2). The average difference in model

performance between the first (t=0) and the final (t=15) for all feedback model variants was

compared.

For the short backbone, *medium*-range feedback confers the largest advantage on model

performance on average under Gaussian noise ($\sigma = \{0, 0.25, 0.5, 0.75\}$), as seen in Figure 2(b,c).

A repeated measures ANOVA after Greenhouse-Geisser correction yielded a significant main

effect of noise-dependent benefit of feedback on model performance (see Table 3) reflecting that

performance declined with increasing noise, as expected. More importantly, there was a

significant main effect of feedback distance (see Table 4). Post hoc comparisons using Tukey's

HSD test revealed significant differences in model performance between all pairs of feedback

types with medium-range feedback being the most effective on average (see Table 6).

Additionally, there was a significant interaction between feedback distance and noise level (see

Table 5), indicating that most effective feedback distance depended on the noise-dependent

benefit (*medium*-range feedback for intermediate levels of noise, *short*-range for zero noise,

*long*-range for high levels of noise).

Similarly, in the case of the long backbone, *medium*-range feedback showed on average the

greatest robustness to noise ($\sigma = \{0.5, 0.75, 1.0\}$), as shown in Figure 2(b,c). A Greenhouse-

Geisser corrected repeated measures ANOVA showed significant main effects of noise level (see

Table 3), and feedback distance (see Table 4), where Tukey's HSD test confirmed that *medium-*

range feedback was most effective establishing significant differences between various pairs of

feedback types (see Table 6). Once again, the interaction between feedback distance and noise-

dependent feedback benefit was also significant (see Table 3), indicating that *medium*-range

feedback was most effective for intermediate and high levels of noise whereas *short*-range

feedback was more effective for zero and low levels of noise.

**Constant feedback source.** Secondly, we compared model performance under

adversarial noise, when the feedback connections originated from the same source layer across

all model variants (for details of the model architecture, see Experiment 3 in Methods). Model

variants were evaluated after timestep $t = 15$. Once again for the short backbone we found

*medium*-range feedback was most ameliorative, when presented with stimuli injected especially

with intermediate levels of Gaussian noise ($\sigma = \{0.25, 0.5, 0.75\}$), as shown in Figure 3(b,c). A

repeated measures ANOVA with Greenhouse-Geisser correction demonstrated a significant main

effect of noise-dependent benefit of feedback (see Table 3). More importantly, we observed a

significant main effect of feedback distance on model performance (see Table 4), with *medium-*

range feedback yielding the greatest benefit on average. In detail, Tukey's HSD test revealed

significant differences between various pairs of feedback types (see Table 6). Finally, there was a

significant interaction between feedback distance and noise-dependent benefit (see Table 5), *,*

indicating that *medium*-range feedback was optimal for intermediate levels of noise whereas

*long*-range feedback was more ameliorative for high and zero levels of noise.

Similar effects of feedback connectivity on model performance were observed in the case

of the long backbone, Figure 3(b,c). The network augmented with *medium*-range feedback was

most resilient to all levels of additive noise tested, except for zero noise ($\sigma =$

$\{0.25, 0.5, 0.75, 1.0\}$). A repeated measures ANOVA with Greenhouse-Geisser correction showed

significant main effects of noise-dependent feedback benefit (see Table 3), and feedback distance

(see Table 4). Post hoc comparisons using Tukey's HSD test revealed significant differences

between the various pairs of feedback types (see Table 6). These results are consistent with

*medium*-range feedback being most beneficial across noise levels on average. Furthermore, a

significant interaction between feedback distance and noise-dependent benefit of feedback (see

Table 6) reflected that *medium*-range feedback was optimal for most noise levels except zero

noise.

**Proximal neural feedback loops improve robustness to noise**

390            Having established the precedence of medium-range neural feedback loops in two

distinct neural network architectures, we investigated if the performance-enhancing effects of

such feedback were sensitive to the level of abstraction of the feedback source, i.e., feedback

originating from early vs. late areas in the dorsal visual stream. Using the long backbone

architecture, we set up three different model variants, augmented with *medium*-range feedback

connections, originating at *proximal*, *intermediate* or *distal* layers relative to the input (see

Experiment 4 in Methods), which were then presented with input images corrupted with

Gaussian noise. Feedback most *proximal* to the input layer, had the greatest performance-

enhancing effect, as seen in Figure 4(b). A repeated measures ANOVA with Greenhouse-Geisser

correction examined the effects of feedback source abstraction level, as well as noise level on the

change in performance of the model between timestep $t = 0$ and timestep $t = 15$. The analysis

identified significant main effects of noise-dependent benefit of feedback (see Table 3), as well

as feedback abstraction level (Table 4). The latter effect reflected proximal feedback to be

optimal as shown with post hoc comparisons using Tukey's HSD test indicating significant

differences between various pairs of feedback abstraction levels (see Table 6). Moreover, the

interaction between abstraction and noise level was significant (see Table 5) due to the influence

of abstraction level being less prominent for zero noise than for other noise levels.

**Discussion**

In the present study, we investigated the contribution of neural feedback to sensorimotor

functions, in particular visual processing during grasp planning, by utilizing convolutional neural

network models that had been augmented with predictive feedback and that were trained to

compute grasp positions for real-world objects. After establishing an ameliorative effect of

symmetric feedback on grasp detection from noisy images, we characterized the performance

effects of asymmetric feedback, similar to that observed in the cortex. We found that the

performance-enhancing effect of predictive coding under adverse conditions was optimal, across

a range of noise levels, for *medium*-range asymmetric feedback. Moreover, this effect was most

prominent when *medium*-range feedback originated at a level of representational abstraction that

was proximal to the input layer, in contrast to more distal layers.

Prior computational work has demonstrated that symmetric feedback, originating from

the immediate next higher area in the cortical hierarchy, helps suppress irrelevant noise to

enhance performance in an object classification task (Choksi et al., 2021; Huang et al., 2020).

Importantly, our work extends the role of predictive feedback in noise-cleanup to the more

general function of sensorimotor processing. This involves progressively denoising the feature

representations during the test phase, essentially by projecting the representations onto the

learned manifolds in the representational space of the trained model. Consistent with this idea,

iterative predictive coding dynamics worsen the model's performance when presented with clean

images, possibly because the model, after finding a suitable solution with the first forward pass,

converged onto a less optimal average solution within the latent representational space.

However, accumulating neurophysiological evidence has suggested that cortical feedback

pathways are not strictly reciprocal (Salin & Bullier, 1995) and may traverse multiple areas at

different latencies (Bullier, 2001; Markov et al., 2014). By systematically comparing different

feedback path lengths and levels of representational abstraction, we illustrated that too short a

feedback loop may lack the broader contextual information needed to mitigate noise effectively,

while longer loops may carry overly abstract predictions. We propose that *medium*-range

feedback marks a unique sweet spot, putatively incorporating an optimal neural transmission

delay and an informative level of abstraction of the feedback source. Moreover, our results

suggest that *medium*-range feedback benefits noise clean-up the most when it originates from

layers that are proximal to the input, suggesting that relatively early representations are most

effective in removing noise.

Of note is the observed U-shaped effect of noise-dependent performance benefit of

predictive feedback for the short backbone experiments (Fig 2C, left; Fig3C, left) vs. a linear

decrease observed for the long backbone models (Fig 2C, right; Fig3C, right; Fig 4B, left),

across the five discrete levels of additive Gaussian noise $\sigma = \{0, 0.25, 0.5, 0.75, 1.0\}$ that were

tested. We speculate that the linear trend seen for the long backbone is the arm of a shifted, wider

U-shape reflecting robustness to noise perturbation and recovery for the higher-dimensional (in

terms of parametric space) long backbone models. The hypothesized U-shaped may emerge if

the long backbone model variants are evaluated on higher levels of additive Gaussian noise e.g.

$\sigma = \{1.25, 1.5, 1.75, ...\}$.

Together our findings suggest a previously uncharted role of intermediate cortical areas

along the dorsal stream, e.g., roughly similar to area V6A in the primate brain, as a source of

predictive feedback. V6A is primarily involved in encoding action-guided vision during grasping

behaviors (Galletti & Fattori, 2018). It plays a key role in guiding prehension movements

(Galletti et al., 2003). Importantly, V6A integrates both visual inputs and somatosensory

feedback from the upper limbs (Gamberini et al., 2011). Our results indicate that V6a might be at

a strategically optimal position to exert dynamic top-down influence onto early visual areas

during visuomotor processing, this way constituting an important hypothesis for future research.

although the extent to which the present neural networks exhibit V6a-like properties requires

further investigation.

458             Also intriguing is the observation that feedback arising from proximal layers of the

network is more beneficial than feedback coming from distal layers. Interestingly, the opposite

pattern of effectiveness was reported for simulated feedback emulating attentional effects in a

VGG16 network (Lindsay & Miller, 2018). Lindsay and Miller (2018) found that attentional

effects were most noticeable when injected into more distal layers. This difference in proximal

vs. distal efficacy of feedback is not explained by structural differences in the feedforward

networks given that the current study used the same long backbone employed previously

(Lindsay & Miller, 2018). The difference in efficacy could be due to task differences. However,

Lindsay and Miller (2018) observed the same distal benefits a range of tasks. Instead, the

proximal vs. distal differences might, and probably do, come from the disparity in feedback.

Whereas in the present study we implemented predictive feedback signals, Lindsay and Miller

(2018) simulated attentional feedback according to the feature similarity gain model (Martinez-

Trujillo & Treue, 2004; Treue & Trujillo, 1999) where neuronal activity changes as a function of

similarity of a neuron's tuning to an attended feature. Whether this particular kind of attentional

modulation or more generally the function of attention as a form of task-relevant resource

allocation in contrast to task-independent predictive coding (Kok, Rahnev, et al., 2012) can

explain the differences between proximal vs. distal effectiveness should be explored in the

future.

In conclusion, our simulations show that introducing biologically realistic asymmetric

predictive feedback improves model robustness to noisy visual stimuli in a neural network model

optimized for sensorimotor transformations. Our findings highlight the possible functional

significance of mid-tier dorsal stream areas (e.g., V6A) that lie between low-level (V1) and high-

level (parietal) representations, suggesting these areas might serve as ideal "predictors" for early

visuomotor processing.

**References**

Baluch, F., & Itti, L. (2011). Mechanisms of top-down attention. *Trends in Neurosciences*, *34*(4),

210–224. https://doi.org/10.1016/j.tins.2011.02.003

Bullier, J. (2001). Integrated model of visual processing. *Brain Research Reviews*, *36*(2–3), 96–

107. https://doi.org/10.1016/S0165-0173(01)00085-6

Chen, M., Yan, Y., Gong, X., Gilbert, C. D., Liang, H., & Li, W. (2014). Incremental Integration

of Global Contours through Interplay between Visual Cortical Areas. *Neuron*, *82*(3), 682–

694. https://doi.org/10.1016/j.neuron.2014.03.023

Choksi, B., Mozafari, M., Biggs O'May, C., Ador, B., Alamia, A., & VanRullen, R. (2021).

Predify: Augmenting deep neural networks with brain-inspired predictive coding dynamics.

*NeurIPS*.

Codol, O., Kashefi, M., Forgaard, C. J., Galea, J. M., Pruszynski, J. A., & Gribble, P. L. (2023).

Sensorimotor feedback loops are selectively sensitive to reward. *ELife*, *12*.

https://doi.org/10.7554/eLife.81325

David C. Howell. (2002). *Statistical Methods for Psychology* (5th ed.). Duxbury Press.

Debes, S. R., & Dragoi, V. (2023). Suppressing feedback signals to visual cortex abolishes

attentional modulation. *Science*, *379*(6631), 468–473.

https://doi.org/10.1126/science.ade1855

Depierre, A., Dellandréa, E., & Chen, L. (2018). Jacquard: A Large Scale Dataset for Robotic

Grasp Detection. *2018 IEEE/RSJ International Conference on Intelligent Robots and*

*Systems (IROS)*, 3511–3516. https://api.semanticscholar.org/CorpusID:215827111

Desimone, R., & Duncan, J. (1995). Neural Mechanisms of Selective Visual Attention. *Annual*

*Review of Neuroscience*, *18*(1), 193–222.

https://doi.org/10.1146/annurev.ne.18.030195.001205

Felleman, D. J., & Van Essen, D. C. (1991). Distributed Hierarchical Processing in the Primate

Cerebral Cortex. *Cerebral Cortex*, *1*(1), 1–47.

Friston, K. (2005). A theory of cortical responses. *Philosophical Transactions of the Royal*

*Society B: Biological Sciences*, *360*(1456), 815–836. https://doi.org/10.1098/rstb.2005.1622

Galletti, C., & Fattori, P. (2018). The dorsal visual stream revisited: Stable circuits or dynamic

pathways? *Cortex*, *98*, 203–217. https://doi.org/10.1016/j.cortex.2017.01.009

Gamberini, M., Galletti, C., Bosco, A., Breveglieri, R., & Fattori, P. (2011). Is the Medial

Posterior Parietal Area V6A a Single Functional Area? *The Journal of Neuroscience*, *31*(13),

5145–5157. https://doi.org/10.1523/JNEUROSCI.5489-10.2011

Gilbert, C. D., & Li, W. (2013). Top-down influences on visual processing. *Nature Reviews*

*Neuroscience*, *14*(5), 350–363. https://doi.org/10.1038/nrn3476

Girden, E. R. (1992). ANOVA:  Repeated measures. In *ANOVA:  Repeated measures.* Sage

Publications, Inc.

Girshick, R., Donahue, J., Darrell, T., & Malik, J. (2014). Rich Feature Hierarchies for Accurate

Object Detection and Semantic Segmentation. *2014 IEEE Conference on Computer Vision*

*and Pattern Recognition*, 580–587. https://doi.org/10.1109/CVPR.2014.81

Greenhouse, S. W., & Geisser, S. (1959). On methods in the analysis of profile data.

*Psychometrika*, *24*(2), 95–112. https://doi.org/10.1007/BF02289823

Guclu, U., & van Gerven, M. A. J. (2015). Deep Neural Networks Reveal a Gradient in the

Complexity of Neural Representations across the Ventral Stream. *Journal of Neuroscience*,

*35*(27), 10005–10014. https://doi.org/10.1523/JNEUROSCI.5023-14.2015

Huang, Y., Gornet, J., Dai, S., Yu, Z., Nguyen, T., Tsao, D. Y., & Anandkumar, A. (2020). Neural

Networks with Recurrent Generative Feedback. *NeurIPS*.

Hubel, D. H., & Wiesel, T. N. (1962). Receptive fields, binocular interaction and functional

architecture in the cat's visual cortex. *The Journal of Physiology*, *160*(1), 106–154.

https://doi.org/10.1113/jphysiol.1962.sp006837

Hupé, J. M., James, A. C., Payne, B. R., Lomber, S. G., Girard, P., & Bullier, J. (1998). Cortical

feedback improves discrimination between figure and background by V1, V2 and V3

neurons. *Nature*, *394*(6695), 784–787. https://doi.org/10.1038/29537

Kok, P., Jehee, J. F. M., & de Lange, F. P. (2012). Less Is More: Expectation Sharpens

Representations in the Primary Visual Cortex. *Neuron*, *75*(2), 265–270.

https://doi.org/10.1016/j.neuron.2012.04.034

Kok, P., Rahnev, D., Jehee, J. F. M., Lau, H. C., & de Lange, F. P. (2012). Attention Reverses the

Effect of Prediction in Silencing Sensory Signals. *Cerebral Cortex*, *22*(9), 2197–2206.

https://doi.org/10.1093/cercor/bhr310

Kravitz, D. J., Saleem, K. S., Baker, C. I., Ungerleider, L. G., & Mishkin, M. (2013). The ventral

visual pathway: an expanded neural framework for the processing of object quality. *Trends*

*in Cognitive Sciences*, *17*(1), 26–49. https://doi.org/10.1016/j.tics.2012.10.011

Kumra, S., Joshi, S., & Sahin, F. (2022a). GR-ConvNet v2: A Real-Time Multi-Grasp Detection

Network for Robotic Grasping. *Sensors*, *22*(16), 6208. https://doi.org/10.3390/s22166208

Kumra, S., Joshi, S., & Sahin, F. (2022b). GR-ConvNet v2: A Real-Time Multi-Grasp Detection

Network for Robotic Grasping. *Sensors*, *22*(16), 6208. https://doi.org/10.3390/s22166208

Lamme, V. A. F., & Roelfsema, P. R. (2000). The distinct modes of vision offered by feedforward

and recurrent processing. *Trends in Neurosciences*, *23*(11), 571–579.

https://doi.org/10.1016/S0166-2236(00)01657-X

Lee, T. S., & Mumford, D. (2003). Hierarchical Bayesian inference in the visual cortex. *Journal

of the Optical Society of America A*, *20*(7), 1434. https://doi.org/10.1364/JOSAA.20.001434

Lindsay, G. W., & Miller, K. D. (2018). How biological attention mechanisms improve task

performance in a large-scale visual system model. *ELife*, *7*.

https://doi.org/10.7554/eLife.38105

Markov, N. T., Ercsey-Ravasz, M. M., Ribeiro Gomes, A. R., Lamy, C., Magrou, L., Vezoli, J.,

Misery, P., Falchier, A., Quilodran, R., Gariel, M. A., Sallet, J., Gamanut, R., Huissoud, C.,

Clavagnier, S., Giroud, P., Sappey-Marinier, D., Barone, P., Dehay, C., Toroczkai, Z., …

Kennedy, H. (2014). A Weighted and Directed Interareal Connectivity Matrix for Macaque

Cerebral Cortex. *Cerebral Cortex*, *24*(1), 17–36. https://doi.org/10.1093/cercor/bhs270

Markov, N. T., Misery, P., Falchier, A., Lamy, C., Vezoli, J., Quilodran, R., Gariel, M. A., Giroud,

P., Ercsey-Ravasz, M., Pilaz, L. J., Huissoud, C., Barone, P., Dehay, C., Toroczkai, Z., Van

Essen, D. C., Kennedy, H., & Knoblauch, K. (2011). Weight Consistency Specifies

Regularities of Macaque Cortical Networks. *Cerebral Cortex*, *21*(6), 1254–1272.

https://doi.org/10.1093/cercor/bhq201

Martinez-Trujillo, J. C., & Treue, S. (2004). Feature-Based Attention Increases the Selectivity of

Population Responses in Primate Visual Cortex. *Current Biology*, *14*(9), 744–751.

https://doi.org/10.1016/j.cub.2004.04.028

Mauchly, J. W. (1940). Significance Test for Sphericity of a Normal $n$-Variate Distribution.

*The Annals of Mathematical Statistics*, *11*(2), 204–209.

https://doi.org/10.1214/aoms/1177731915

Mumford, D. (1992). On the computational architecture of the neocortex. *Biological*

*Cybernetics*, *66*(3), 241–251. https://doi.org/10.1007/BF00198477

Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z.,

Gimelshein, N., Antiga, L., Desmaison, A., Kopf, A., Yang, E., DeVito, Z., Raison, M.,

Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., … Chintala, S. (2019). PyTorch: An

Imperative Style, High-Performance Deep Learning Library. In H. Wallach, H. Larochelle,

A. Beygelzimer, F. d Alché-Buc, E. Fox, & R. Garnett (Eds.), *Advances in Neural*

*Information Processing Systems* (Vol. 32). Curran Associates, Inc.

https://proceedings.neurips.cc/paper_files/paper/2019/file/bdbca288fee7f92f2bfa9f7012727

740-Paper.pdf

Pennartz, C. M. A., Dora, S., Muckli, L., & Lorteije, J. A. M. (2019). Towards a Unified View on

Pathways and Functions of Neural Recurrent Processing. *Trends in Neurosciences*, *42*(9),

589–603. https://doi.org/10.1016/j.tins.2019.07.005

Rao, R. P. N., & Ballard, D. H. (1999a). Predictive coding in the visual cortex: a functional

interpretation of some extra-classical receptive-field effects. *Nature Neuroscience*, *2*(1), 79–

87. https://doi.org/10.1038/4580

Rao, R. P. N., & Ballard, D. H. (1999b). Predictive coding in the visual cortex: a functional

interpretation of some extra-classical receptive-field effects. *Nature Neuroscience*, *2*(1), 79–

87. https://doi.org/10.1038/4580

Rockland, K. S., & Pandya, D. N. (1979). Laminar origins and terminations of cortical

connections of the occipital lobe in the rhesus monkey. *Brain Research*, *179*(1), 3–20.

https://doi.org/10.1016/0006-8993(79)90485-2

Rockland, K. S., & Van Hoesen, G. W. (1994). Direct Temporal-Occipital Feedback Connections

to Striate Cortex (V1) in the Macaque Monkey. *Cerebral Cortex*, *4*(3), 300–313.

https://doi.org/10.1093/cercor/4.3.300

Salin, P. A., & Bullier, J. (1995). Corticocortical connections in the visual system: structure and

function. *Physiological Reviews*, *75*(1), 107–154.

https://doi.org/10.1152/physrev.1995.75.1.107

Shipp, S. (2016). Neural Elements for Predictive Coding. *Frontiers in Psychology*, *7*.

https://doi.org/10.3389/fpsyg.2016.01792

Simonyan, K., & Zisserman, A. (2014). Very Deep Convolutional Networks for Large-Scale

Image Recognition. *CoRR*, *abs/1409.1556*.

https://api.semanticscholar.org/CorpusID:14124313

The jamovi project. (2024). *jamovi* (2.5). Retrieved from https://www.jamovi.org.

Treue, S., & Trujillo, J. C. M. (1999). Feature-based attention influences motion processing gain

in macaque visual cortex. *Nature*, *399*(6736), 575–579. https://doi.org/10.1038/21176

Tukey, J. W. (1949). Comparing Individual Means in the Analysis of Variance. *Biometrics*, *5*(2),

99. https://doi.org/10.2307/3001913

Watt, S. J., & Bradshaw, M. F. (2000a). Binocular cues are important in controlling the grasp but

not the reach in natural prehension movements. *Neuropsychologia*, *38*(11), 1473–1481.

https://doi.org/10.1016/S0028-3932(00)00065-8

Watt, S. J., & Bradshaw, M. F. (2000b). Binocular cues are important in controlling the grasp but

not the reach in natural prehension movements. *Neuropsychologia*, *38*(11), 1473–1481.

https://doi.org/10.1016/S0028-3932(00)00065-8

Wen, H., Han, K., Shi, J., Zhang, Y., Culurciello, E., & Liu, Z. (2018). *Deep Predictive Coding*

*Network for Object Recognition*.

Yamins, D. L. K., Hong, H., Cadieu, C. F., Solomon, E. A., Seibert, D., & DiCarlo, J. J. (2014).

Performance-optimized hierarchical models predict neural responses in higher visual cortex.

*Proceedings of the National Academy of Sciences*, *111*(23), 8619–8624.

https://doi.org/10.1073/pnas.1403112111

**Table 1. Neural network architecture of the short and long feedforward models.** Layer-wise

architecture of the feedforward models is described. All layers were implemented in PyTorch.

The Conv2d (output channels, kernel size, stride) and ConvTranspose2d (output channels, kernel

size, stride) refer to convolutional and deconvolutional layers, respectively. The MaxPool (kernel

size, stride) layer implements feature pooling. BatchNorm2d: batch normalization; ReLU:

rectifying linear unit; Tanh: hyperbolic tangent; Sigmoid: sigmoid function.

| Module | | Layers | Short | Long |
|---|---|---|---|---|
| **Input** | RGB | Conv2d (64, 3, 1) | ● | ● |
| | Depth | Conv2d (64, 3, 1) | ● | ● |
| **Feature compression** | | BatchNorm2d \| ReLU | ● | ● |
| | Conv block 1 | Conv2d (64, 3, 1) \| BatchNorm2d \| ReLU | ● | ● |
| | | MaxPool (2, 2) | ● | ● |
| | Conv block 2 | Conv2d (128, 3, 1) \| BatchNorm2d \| ReLU | ● | ● |
| | | Conv2d (128, 3, 1) \| BatchNorm2d \| ReLU | ● | ● |
| | | MaxPool (2, 2) | ● | ● |
| | Conv block 3 | Conv2d (256, 3, 1) \| BatchNorm2d \| ReLU | ● | ● |
| | | Conv2d (256, 3, 1) \| BatchNorm2d \| ReLU | ● | ● |
| | | Conv2d (256, 3, 1) \| BatchNorm2d \| ReLU | ● | ● |
| | | MaxPool (2, 2) | ● | ● |
| | Conv block 4 | Conv2d (256, 3, 1) \| BatchNorm2d \| ReLU | ● | |
| | | Conv2d (256, 3, 1) \| BatchNorm2d \| ReLU | ● | |
| | | Conv2d (512, 3, 1) \| BatchNorm2d \| ReLU | | ● |
| | | Conv2d (512, 3, 1) \| BatchNorm2d \| ReLU | | ● |
| | | Conv2d (512, 3, 1) \| BatchNorm2d \| ReLU | | ● |
| | | MaxPool (2, 2) | | ● |
| | Conv block 5 | Conv2d (512, 3, 1) \| BatchNorm2d \| ReLU | | ● |
| | | Conv2d (512, 3, 1) \| BatchNorm2d \| ReLU | | ● |
| | | Conv2d (512, 3, 1) \| BatchNorm2d \| ReLU | | ● |
| **Feature expansion** | | ConvTranspose2d (256, 3, 2) \| ReLU | | ● |
| | | Conv2d (256, 5, 1) \| ReLU | | ● |
| | | ConvTranspose2d (128, 3, 2) \| ReLU | ● | ● |
| | | Conv2d (128, 5, 1) \| ReLU | ● | ● |
| | | ConvTranspose2d (64, 3, 2) \| ReLU | ● | ● |
| | | Conv2d (128, 5, 1) \| ReLU | ● | ● |
| | | ConvTranspose2d (64, 3, 2) \| ReLU | ● | ● |
| **Output** | Grasp | ConvTranspose2d (5, 3, 1) \| Tanh | ● | ● |
| | Confidence | ConvTranspose2d (1, 3, 1) \| Sigmoid | ● | ● |

633    **Table 2. Predictive coding hyperparameters.** The balancing coefficients for the feedforward

634    ($\beta_n$), feedback ($\lambda_n$), recurrence ($\gamma_n$) and error-correction ($\alpha_n$) terms that were selected after

635    hyperparameter optimization, are stated for the short and/or long feedforward model(s), for all

636    experiments.

| PCoder | Feedback hyperparameters | Experiments | | | | | |
|---|---|---|---|---|---|---|---|
| | | 1 | 2 | | 3 | | 4 |
| | | Short | Short | Long | Short | Long | Long |
| 1 | $\beta_n$ | 0.2 | 0.3 | 0.35 | 0.35 | 0.2 | 0.35 |
| | $\lambda_n$ | 0.05 | 0.3 | 0.25 | 0.25 | 0.4 | 0.25 |
| | $\gamma_n$ | 0.75 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 |
| | $\alpha_n$ | 0.01 | 0.01 | 0.01 | 0.01 | 0.01 | 0.01 |
| 2 | $\beta_n$ | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 |
| | $\lambda_n$ | 0.1 | 0 | 0 | 0 | 0 | 0 |
| | $\gamma_n$ | 0.5 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 |
| | $\alpha_n$ | 0.01 | 0.1 | 0.1 | 0.1 | 0.01 | 0.1 |
| 3 | $\beta_n$ | 0.4 | - | - | - | - | - |
| | $\lambda_n$ | 0.1 | - | - | - | - | - |
| | $\gamma_n$ | 0.5 | - | - | - | - | - |
| | $\alpha_n$ | 0.01 | - | - | - | - | - |
| 4 | $\beta_n$ | 0.4 | - | - | - | - | - |
| | $\lambda_n$ | 0 | - | - | - | - | - |
| | $\gamma_n$ | 0.6 | - | - | - | - | - |
| | $\alpha_n$ | 0.01 | - | - | - | - | - |

638 **Table 3. Within Subjects Effects - Noise-dependent benefit**

| | Experiment | | df | F | p | $\eta^2$ |
|---|---|---|---|---|---|---|
| 2 | Short backbone | Noise-dependent benefit | 1.68 | 109649 | < .001 | 0.454 |
| | | Residual | 15772.36 | | | |
| | Long backbone | Noise-dependent benefit | 1.64 | 43410 | < .001 | 0.426 |
| | | Residual | 15398.52 | | | |
| 3 | Short backbone | Noise-dependent benefit | 1.56 | | | |
| | | Residual | 14671.10 | 59300 | < .001 | 0.652 |
| | Long backbone | Noise-dependent benefit | 2.71 | 24519 | < .001 | 0.376 |
| | | Residual | 25388.71 | | | |
| 4 | Long backbone | Noise-dependent benefit | 2.13 | 48395 | < .001 | 0.520 |
| | | Residual | 19937.27 | | | |

640 **Table 4. Within Subjects Effects - Feedback distance (abstraction level)**

| | Experiment | | df | F | p | $\eta^2$ |
|---|---|---|---|---|---|---|
| **2** | Short backbone | Feedback distance | 1.18 | 87764 | < .001 | 0.194 |
| | | Residual | 11072.25 | | | |
| | Long backbone | Feedback distance | 1.64 | 10542 | < .001 | 0.080 |
| | | Residual | 15429.00 | | | |
| **3** | Short backbone | Feedback distance | 1.10 | 5365 | < .001 | 0.010 |
| | | Residual | 10297.82 | | | |
| | Long backbone | Feedback distance | 2.61 | 2908 | < .001 | 0.004 |
| | | Residual | 24479.40 | | | |
| **4** | Long backbone | Feedback abstraction level | 1.35 | 13523 | < .001 | 0.039 |
| | | Residual | 12629.91 | | | |

642 **Table 5. Within Subjects Effects - Feedback distance (abstraction level) x Noise-dependent benefit.**

| | Experiment | | df | F | p | $\eta^2$ |
|---|---|---|---|---|---|---|
| 2 | Short backbone | Feedback distance x Noise-dependent benefit | 2.79 | 60426 | < .001 | 0.176 |
| | | Residual | 26216.36 | | | |
| | Long backbone | Feedback distance x Noise-dependent benefit | 4.94 | 5272 | < .001 | 0.057 |
| | | Residual | 46387.80 | | | |
| 3 | Short backbone | Feedback distance x Noise-dependent benefit | 1.94 | 13862 | < .001 | 0.030 |
| | | Residual | 18161.08 | | | |
| | Long backbone | Feedback distance x Noise-dependent benefit | 7.35 | 1884 | < .001 | 0.009 |
| | | Residual | 68946.23 | | | |
| 4 | Long backbone | Feedback abstraction level x Noise-dependent benefit | 5.61 | 1290 | < .001 | 0.008 |
| | | Residual | 52603.38 | | | |

644     **Table 6. Post Hoc Comparisons - Feedback distance (abstraction level)**

| Experiment | | Comparison | | Mean Difference | SE | df | t | $p_{tukey}$ |
|---|---|---|---|---|---|---|---|---|
| | | Feedback distance (Exp 2-3); Feedback source abstraction (Exp 4) | Feedback distance (Exp 2-3); Feedback source abstraction (Exp 4) | | | | | |
| **2** | Short backbone | 1 | 2 | 0.01316 | 4.05e-5 | 9381 | 324.5 | < .001 |
| | | | 3 | 0.01195 | 4.21e-5 | 9381 | 284.1 | < .001 |
| | | 2 | 3 | -0.00121 | 1.43e-5 | 9381 | -85.0 | < .001 |
| | Long backbone | 1 | 2 | 0.00274 | 1.97e-5 | 9381 | 138.88 | < .001 |
| | | | 3 | 8.92e-5 | 2.56e-5 | 9381 | 3.48 | 0.003 |
| | | | 4 | -1.42e−4 | 2.42e-5 | 9381 | -5.87 | < .001 |
| | | 2 | 3 | -0.00265 | 1.57e-5 | 9381 | -168.80 | < .001 |
| | | | 4 | -0.00288 | 1.56e-5 | 9381 | -185.02 | < .001 |
| | | 3 | 4 | -2.31e−4 | 7.16e-6 | 9381 | -32.33 | < .001 |
| **3** | Short backbone | 1 | 2 | 9.75e-4 | 1.77e-5 | 9381 | 55.3 | < .001 |
| | | | 3 | -0.00200 | 2.55e-5 | 9381 | -78.4 | < .001 |
| | | 2 | 3 | -0.00297 | 4.01e-5 | 9381 | -74.1 | < .001 |
| | Long backbone | 1 | 2 | 2.80e-4 | 1.29e-5 | 9381 | 21.81 | < .001 |
| | | | 3 | 2.91e-4 | 1.38e-5 | 9381 | 21.03 | < .001 |
| | | | 4 | -7.83e−4 | 1.62e-5 | 9381 | -48.41 | < .001 |
| | | 2 | 3 | 1.06e-5 | 1.06e-5 | 9381 | 1.01 | 0.745 |
| | | | 4 | -0.00106 | 1.32e-5 | 9381 | -80.30 | < .001 |
| | | 3 | 4 | -0.00107 | 1.21e-5 | 9381 | -88.67 | < .001 |
| **4** | Long backbone | 1 | 2 | -0.00157 | 1.54e-5 | 9381 | -101.8 | < .001 |
| | | | 3 | -0.00223 | 1.68e-5 | 9381 | -132.5 | < .001 |
| | | 2 | 3 | -6.59e−4 | 7.83e-6 | 9381 | -84.2 | < .001 |

**Figure 1. Predictive coding dynamics improve model performance for noisy stimuli. (a)**

Architecture of the grasping neural network, derived from the *short* feedforward backbone. Red

arrows denote top-down feedback connections. Black arrows represent the error-correction

process, whereby the predictive error ($\varepsilon$) drives the higher layer (feedback source) representation

to better match the early layer representation (feedback target). Green arrows denote recurrent

memory processes, for conserving the layer representation over consecutive predictive cycles.

Conv: convolutional layer; BatchNorm: batch normalization layer; ReLU: rectifying linear unit;

MaxPool: pooling layer; ConvTranspose: deconvolutional layer. The network received a 3-

channel RGB image and a 1-channel depth image of the input object. The network output

consisted of a 6-channel array, each channel representing a pixelwise map with the same

dimensions as the input images and corresponding to one of the 6 grasp parameters: grasp centre

coordinates (x, y); orientation ($\theta$); grasp opening (h); gripper size (w); grasp quality (confidence)

score. **(b)** Model performance during the inference phase, across 15 predictive coding timesteps,

measured as the average mean squared error at each timestep, when presented with the test

dataset that had been injected with varying levels of additive Gaussian noise. The right panel

shows a representative sample object, corrupted with the different noise levels. **(c)** The average

difference in test performance of the model between the initial (t=1) and final (t=15) timestep,

for each noise level. Black bars denote standard errors of mean. **(d)** Left panel: an RGB image of

a sample object from the test dataset. Right panel: the RGB image with Gaussian noise ($\sigma =$

0.25). **(e)** The grasp quality score maps of the sample object, at even timesteps.

**Figure 2. Layer-dependent effects of feedback with a uniform target. (a)** Left panel: short

feedforward model, augmented with *short*-range (first row; solid red arrow), *medium*-range

(second row; dashed red arrow) and *long*-range (third row; dotted red arrow) feedback. Right

panel: long feedforward model, augmented with *short*-range (first row; solid red arrow),

*medium*-range (second row; dashed red arrow), *long*-range (third row; dash-dotted red arrow)

and *longer*-range (fourth row; dotted red arrow) feedback. All effective feedback connections,

pertaining to the second PCoder in each model variant, terminate at the same target layer: the

final ReLU layer of convolution block 1. The first PCoder (translucent) does not represent a

functional feedback connection. **(b)** Performance of feedback model variants across 15 predictive

coding timesteps, on test dataset injected with varying levels of Gaussian noise (standard

deviation, $\sigma = \{0, 0.25, 0.5, 0.75, 1.0\}$). Left panel: short feedforward backbone. Right panel:

long feedforward backbone. **(c)** The average difference in test performance of the feedback

model variants, between the initial (t=1) and final (t=15) timestep, for each noise level. Black

bars denote standard errors of mean.

**Figure 3. Layer-dependent effects of feedback with a uniform source. (a)** Left panel: short

feedforward model, augmented with *short*-range (first row; solid red arrow), *medium*-range

(second row; dashed red arrow) and *long*-range (third row; dotted red arrow) feedback. Right

panel: long feedforward model, augmented with *short*-range (first row; solid red arrow),

*medium*-range (second row; dashed red arrow), *long*-range (third row; dash-dotted red arrow)

and *longer*-range (fourth row; dotted red arrow) feedback. All effective feedback connections,

pertaining to the second PCoder in each model variant, originate at the same source layer; short

feedforward backbone: final ReLU layer of convolution block 4; long feedforward backbone:

final ReLU layer of convolution block 5. The first PCoder (translucent) does not represent a

functional feedback connection. **(b)** Performance of feedback model variants across 15 predictive

coding timesteps, on test dataset injected with varying levels of Gaussian noise (standard

deviation, $\sigma = \{0, 0.25, 0.5, 0.75, 1.0\}$). Left panel: short feedforward backbone. Right panel:

long feedforward backbone. **(c)** The average difference in test performance of the feedback

model variants, between the initial (t=1) and final (t=15) timestep, for each noise level. Black

bars denote standard errors of mean.

**Figure 4. Effect of feedback source abstraction level. (a)** Long feedforward model, augmented

with *medium*-range feedback connections (pertaining to the second PCoder in each model

variant), originating at layers *proximal* (first row; solid red arrow), *intermediate* (second row;

dashed red arrow), or *distal* (third row; dash-dotted red arrow) to the input layer. The first

PCoder (translucent) does not represent a functional feedback connection. **(b)** Left panel:

performance of feedback model variants across 15 predictive coding timesteps, on test dataset

injected with varying levels of Gaussian noise (standard deviation, $\sigma = \{0, 0.25, 0.5, 0.75, 1.0\}$).

Right panel: the average difference in test performance of the feedback model variants, between

the initial (t=1) and final (t=15) timestep, for each noise level. Black bars denote standard errors

of mean.