Revealing the mechanisms underlying latent learning with successor representations

Matheus Menezes[1,2], Xiangshuai Zeng[2], Sen Cheng[2*]

[1] Doctoral Program in Computer Science, Federal University of Maranhão, São Luís, Brazil
[2] Institute for Neural Computation, Faculty of Computer Science, Bochum, North Rhine-Westphalia, Germany

* sen.cheng@rub.de

Abstract

Latent learning experiments were critical in shaping Tolman's cognitive map theory. In a spatial navigation task, latent learning means that animals acquire knowledge of their environment through exploration, without explicit reinforcements. Animals pre-exposed in this way perform better on a subsequent learning task than those that were not. This learning enhancement is dependent on the specific design of the pre-exposure phase. Here, we investigate latent learning and its modulation using computational modeling based on the deep successor representation (DSR), a recent model for cognitive map formation. Our results confirm experimental observations in that exploration aligned with the future reward location significantly improves reward learning compared to random or no exploration. This effect generalizes across different action selection strategies. We show that these performance differences follow from the spatial information encoded in the structure of the DSR acquired in the pre-exposure phase. In summary, this study sheds light on the mechanisms underlying latent learning and how such learning shapes cognitive maps, impacting their effectiveness in goal-directed spatial tasks.

Author summary

Latent learning enables animals to construct cognitive maps of their environment without direct reinforcement. This process facilitates efficient navigation when rewards are introduced later, that is, animals familiar with a maze through prior exposure learn rewarded tasks faster than those without pre-exposure. Evidence suggests that the design of the pre-exposure phase significantly impacts the effectiveness of latent learning. Targeted pre-exposure focused on future reward locations enhances learning more than generic pre-exposure. However, the underlying mechanisms driving these differences remain understudied. This study investigates how pre-exposure methods influence subsequent navigation task performance using an artificial agent based on deep successor representations – a model for learning cognitive maps – within a reinforcement learning framework. Our findings reveal that before reward learning, agents receiving targeted pre-exposure develop spatial features more closely aligned with those of agents learning from rewards, compared to agents experiencing generic pre-exposure. This alignment enables the targeted pre-exposure agent to take more effective goal-oriented actions, resulting in accelerated initial learning. The persistence

of this advantage, even when modifying the agent's exploration policy, indicates a robust cognitive map within the successor representation.

Introduction

Latent learning demonstrates that animals can learn information about the spatial layout of their environment without forming specific associations between spatial locations and rewards and that this spatial information speeds up learning when rewards are introduced later [1,2]. These types of experiments have played a crucial role in shaping Tolman's theory of cognitive map [3]. Notably, environmental constraints do not prevent latent learning from occurring. For example, Tolman incorporated doors into his latent learning experiments [3] and Daub tested their effect — the inability of animals to retrace their steps and only move forward — on the maze's learning criteria [4]. Latent learning was observed no matter the structure of the environment.

Nevertheless, the design of the pre-exposure has a significant impact on reward learning of rats in the Dashiell maze [5]. Karn and Munn compared the learning performance of five groups of animals. The first group received no pre-exposure and behavior was reinforced immediately when animals were introduced to the maze (direct learning). In their study, the second and fifth groups' pre-exposures focused on habituation to the confinement without explicit maze exploration. The third group explored the maze for five consecutive days, with trials ending when the animal reached the empty place where the reward would be provided later in the following experimental phase (targeted pre-exposure). The animals in the fourth group also explored once a day for a duration matched to that of the third group and were removed from any location in the maze (continuous pre-exposure). It was found that targeted pre-exposure facilitated learning and improved animals' performance significantly more than continuous pre-exposure did. The continuous pre-exposure group in turn learned more effectively than the direct learning and the groups without explicit exploration.

Consistent with the observations by Karn and Munn, a study by Sutherland and Linggard found a similar pattern in rats that were trained to swim to an invisible platform in the Morris water maze [6]. The animals were divided into three groups: one was repeatedly exposed to the correct platform location (targeted pre-exposure), another to an incorrect location (analogous to continuous pre-exposure), and the third to an unrelated water basin in a different room (naive group, direct learning). Before being exposed to the platforms, the targeted and continuous pre-exposure groups had a 30-second window for swimming around the water maze, while the naive group was allowed to swim around the unrelated water basin. During the (rewarded) learning phase, animals were placed on an arbitrary starting platform, followed by 90 seconds to complete the task. The targeted pre-exposure group rapidly acquired the spatial location of the escape platform, easily surpassing the performance of the other two groups. Intriguingly, even though the continuous pre-exposure group took longer to locate the platform than the naive group initially, they quickly outperformed the naive animals after learning the correct location.

To account for the above experiments, it has been hypothesized that animals built a cognitive map during the exploration in the pre-exposure phase. The cognitive map is thought to encode spatial relationships within the environment [3,7,8], which enhances learning to navigate to the reward location. Guo and colleagues have suggested that the effectiveness of the encoding occurs after repeated exposures to the environment and sleep in-between [9]. They found that hippocampal cells in mice did not quickly develop into strongly spatially tuned place cells, but remained weakly tuned to space and gradually developed correlated activity with the other neurons. They propose that weakly spatially tuned cells build connections that link discrete place fields to a map. In

another recent study, Scleidorovich and colleagues proposed a computational framework for latent learning based on hippocampal replay [10]. They showed that targeted pre-exposure improves the agent's learning phase when updating a state-action path matrix such that it reinforces the connectivity toward the goal location. However, this agent failed to show latent learning during continuous pre-exposure. In summary, the influence of diverse experimental designs on the outcomes of latent learning and the development of the cognitive map remain poorly understood.

Here, we use computational modelling to test the cognitive map explanation for latent learning. In particular, we wondered whether and how the cognitive map hypothesis could account for the different effectiveness of the various designs of the pre-exposure phase. To this end, we modelled latent learning experiments using reinforcement learning (RL), specifically a version of the successor representation (SR) algorithm [11] supported by deep neural network and memory replay. The SR learns a spatial relationship between states in an environment independent of a reward function, allowing learning in an environment when no rewards are provided. The SR has consistently supported behavioral and neural findings [12–14] and outperformed other RL algorithms, such as model-free and model-based methods [11, 14, 15]. We study the behavior and learned spatial representations during and after targeted and continuous pre-exposure (as well as direct learning) and find that the SR accounts for the differences between different pre-exposure designs. Importantly, we find that the behavioral effects are mediated by the differences in what spatial representations are learned, contributing to a deeper understanding of how animals learn to efficiently navigate space.

Materials and methods

The successor representation in reinforcement learning

We study latent learning in the framework of RL where an agent interacts with an environment by taking an action a to transition from state s of the environment to another state s' with the probability $p(s'|s,a)$. The agent chooses actions according to a policy $\pi(a|s)$ and receives an instant reward in each state $R(s)$. The goal of the agent is to maximize the total amount of rewards. One way to achieve this is based on the state-action value function, also called the Q function, which is formally defined as the expected cumulative discounted reward under the policy π:

$$Q(s,a) = \mathbb{E}_\pi \left(\sum_{t=0}^{\infty} \gamma^t R(s_t) | s_0 = s, a_0 = a \right), \tag{1}$$

where γ is the discount factor. During decision-making, the action with the highest Q value will be selected with the highest probability. To maximize the total reward, the agent has to find the optimal function Q^*, which has to satisfy the Bellman equation ([16]):

$$Q^*(s_t, a_t) = R(s_t) + \gamma \max_{a'} \mathbb{E}\left[Q^*(s_{t+1}, a')\right] \tag{2}$$

There are two major classes of RL algorithms for solving this problem: model-free and model-based. Model-free approaches directly learn an action policy on the data collected from the interactions with the environment. They usually leads to a good policy, but are data-hungry and require many interactions with the environment. They also struggle to generalize to new tasks and need to relearn the policy when the environment dynamics change. By contrast, model-based approaches learn a model of the dynamics of the environment and leverage the model to optimize the policy. This makes them more data-efficient, but increases the complexity of the computation and is

prone to accumulate errors due to inaccuracy of the model, particularly with large state spaces. A third approach that lies on a middle ground between data-efficiency and model complexity is the successor representation (SR) [11].

The SR algorithm estimates the expected frequency of transiting from a certain state to successor states [13]. Specifically, one row of the transition matrix M represents the expected visitation frequencies from the current state to all states. M can be expanded by one extra dimension to incorporate actions, such that given a state s, an action a, and future state s', M is defined as:

$$M(s, s', a) = \mathbb{E}\left[\sum_{t=0}^{\infty} \gamma^t \mathbf{I}[\ s_{t+1} = s']\ |s_0 = s, a_0 = a\right], \tag{3}$$

where $\mathbf{I}[.] = 1$ when its argument is true and 0 otherwise. Note, M is independent of any reward function, enabling rapid adaptation to changes in the environment's reward structure. In this sense, SR agents are more robust to changes than model-free methods, as the agent only needs to relearn the new reward function $R(s)$ while maintaining the existing transition model M, resulting in fast integration of changing reward functions in dynamic environments.

The transition matrix has to satisfy a Bellmann equation:

$$M(s_t, s', a_t) = \mathbf{I}[\ s_t = s'] + \gamma \mathbb{E}(M(s_{t+1}, s', a_{t+1})) \tag{4}$$

where a_{t+1} is selected based on the running policy. As the agent acquires new experiences over steps, $M(s, s', a)$ is updated with a temporal-difference learning rule [16]. Assuming the agent goes from $s_t \to s_{t+1}$ by taking action a_t, then the agent can implement the learning rules:

$$M(s_t, s', a_t) \leftarrow M(s_t, s', a_t) + \alpha \left[\mathbf{I}[s_t = s'] + \gamma M(s_{t+1}, s', a') - M(s_t, s', a_t)\right] \tag{5}$$

$$\tag{6}$$

Given the SR, the Q value function of selecting action a at state s can be computed by summing the product of $M(s, s', a)$ and the immediate reward for each corresponding successor state [11]. This process captures the anticipated long-term value of the state-action pair based on SR's predictions about future interactions [12]:

$$Q(s, a) = \sum_{s'} M(s, s', a) R(s'), \tag{7}$$

Decision-making with deep successor representation

In complex environments, e.g., with high-dimensional states and continuous actions, tabular methods become infeasible and deep neural networks are used to approximate value functions [17]. Kulkarni and colleagues [18] combined deep learning with SR algorithm by learning the spatial and temporal relationship between states with deep neural networks, and representing the reward function as a trainable weight vector. We refer to this agent as the deep successor representation (DSR) in the rest of this paper.

The key concept in DSR is the successor feature (SF), denoted as $m_\Phi(s, a)$ where Φ refers to the parameters of the neural network, which represents the expected future occupancy of the state features, starting from the state-action pair (s, a):

$$m_\Phi(s, a) = \mathbb{E}_\pi\left(\sum_{t=0}^{\infty} \gamma^t \phi(s_t)|s_0 = s, a_0 = a\right), \tag{8}$$

where ϕ is a feature extraction function. When the reward function is a linear function of the state feature: $R(s) \approx \phi(s) \cdot \mathbf{w}$, the Q function can be decomposed as follows:

$$Q^\pi \approx m_\Phi(s, a) \cdot \mathbf{w} \tag{9}$$

with $\mathbf{w}$ being a weight vector.

Throughout our simulations, we implement a version of DSR as the running algorithm to model the effects of latent learning [19, 20]. We employed a simple replay mechanism where all visited (state, action, next state, reward) tuples are equally sampled from the memory buffer and replayed to update the neural networks. The agent learns a separate successor feature network for each action. The SF vector of a particular state encodes an expected summation of the future state vectors, which in our case are one-hot encoded. Therefore, entry i in the SF vector represents exactly the expected future occupancy of state i from the current state. This also means that a SF vector in our simulation can be directly mapped onto the environment's topology.

Latent learning simulation setup

In T-maze experiments by Blodgett and Tolman [1–3], rats exposed to the maze without explicit reinforcement, such as food, initially exhibited no apparent decrease in error (entering dead alleys) and improvement in performance in reaching the goal box. However, when food was introduced at the goal location from 3 to 11 days later, they displayed a significant advantage over those who had not explored the maze and had received food at the goal from the beginning of the experiment.

All simulations were conducted in virtual environments designed in the CoBeL-RL (Closed-loop Simulator of Complex Behavior and Learning based on Reinforcement Learning and deep neural networks) framework [20]. CoBeL-RL allows the creation of a VR environment for trial-based experimental designs, where each trial consists of agent-environment interactions referred to as steps. Each step in CoBeL-RL corresponds to an experience tuple (s, a, r, s'), which the agent can either use for online learning or store in a memory structure for later replay.

We built two grid-world environments with one-hot encoded states to simulate latent learning: a 10x10 open grid-world (Fig. 1a) and a 14-unit T-maze (Fig. 1b) similar to those used by Tolman. Each environment had a fixed goal ($\mathbf{g}$, green color) and starting ($\mathbf{s}$, red color) state. To navigate, the agent selected one of four actions (up, right, down, or left). We adopted an action mask that disallowed the section of actions that would violate the geometric constraints of the environment. This prevented the agent from getting stuck in the same state, thus leading to a more dynamic exploration. Furthermore, we incorporated virtual doors (dotted lines) in the Tolman maze that, when enabled, constrained the agent's movement in one direction (along the arrow).

We tested our DSR agents in learning tasks with or without pre-exposure. In direct learning, just as in the rewarded control group in Tolman's experiment, the agent receives rewards from the first trial, if it reaches the goal location. Each following trial begins at the start location. By contrast, in the two latent learning conditions, the agent goes through a pre-exposure phase for 50 trials that are not rewarded. This was followed by 50 trials, in which the agent received a reward at the goal location. Additionally, there is a maximum of 300 and 1500 time steps per trial in the open gridworld and Tolman maze, respectively.

Task designs

We set up two experimental designs for latent learning simulations. During targeted pre-exposure trials terminated when the agent reached the unrewarded goal state. This

is similar to the experiments coined as Blodgett type [7], and conducted by Tolman and other researchers [2,3]. During continuous pre-exposure, the agent explored the empty maze for the maximum pre-defined time steps [5,7], whether or not it reached the goal state. Moreover, the agent initiated a trial from multiple locations, including the goal state (Fig. 1, starting states are $\mathbf{i} + \mathbf{s} + \mathbf{g}$ states). The learning phase was identical for the latent and direct learning groups: the agent started at the $\mathbf{s}$ state, and a trial ended upon reaching either the goal $\mathbf{g}$ or the maximum number of steps.

To assess how direct and latent learning designs influence the agent, we monitor its variables using CoBeL-RL embed tools [20]. These include analyzing behavioral variables, such as escape latency and success rate, alongside the learned successor feature (SF) vectors and Q values. For the latter, we recorded the learned SF and Q values estimated by the agent's network at different phases of training.

Results

Learning the spatial connectivity during exploration drives latent learning

We first compared targeted pre-exposure with direct learning. The agent selects actions based on an ε-greedy policy, with $\varepsilon = 0.3$. By the end of learning phase, both agents mastered the spatial task in both environments, shown by the error reduction, with the latent learning agent outperforming the direct learning counterpart (Fig. 1b, c, averaged over 30 simulations). These results qualitatively match the behavior of animals [3,7] and previous computational simulations [10,15], in which trajectory errors dropped as latent learning animals encountered rewards. Similarly, the escape latency of our latent learning agent notably decreased by the moment they experienced rewards (trial 0, blue curves, Fig. 1b). During pre-exposure (-50 to -1 trials), this agent gradually progressed towards the goal, with notable variation across simulations (shaded area, escape latency s.d). A similar trend is observed when measuring the agent's success rate in reaching the goal state (Fig. 1c). The variability of performance during the pre-exposure is higher than during learning, indicating no discernible progress on the task during the pre-exposure phase. Nevertheless, once the reward was introduced, the success rate of the pre-exposed agent increased considerably faster than that of the direct learning agent, an indication of latent learning.

The gradual drop in error rates in the pre-exposure phase might be due to the targeted pre-exposure design. Although receiving no rewards, the agent still slightly increased its expectation of the future occupancy of the goal location because the pre-exposure phase was terminated at the (future) goal state. With the learned reward function being near-zero for all states, but not exactly zero due to the nature of the minimization procedure, the tendency for the agent to go to the goal state was increased.

The successor features (SF) generated by the neural networks reveal the spatial structure learned by the agents (Fig. 2). For the direct learning agent, the SFs at trial 0 reflect the random initialization of the network (Glorot uniform algorithm [21]). In contrast, for the latent learning agent the SFs at trial 0 show a pattern that captures the local connectivity of states with no directional bias. This was the result of a random exploration strategy during the pre-exposure phase. By the end of learning phase, both agents have developed a similar SF structure that reflects a movement from the start to the goal location. This progression is further evident for the SF of individual states, where activity is inhibited to dead-end or backward states. (Fig. 3, observed states are marked with orange crosses).

Additionally, we examine the Q-values resulting from multiplying the deep SR with the reward weight vector (Eq. 7). The Q-values are initially stochastic for the direct

Fig 1. Simulation environments and learning curves demonstrating latent learning. a) Spatial setup of the environments. The gridworld is a 10×10 arena. Tolman maze is a 72-state environment [3]. Virtual doors (dotted lines) can restrict the agent's movement to only one direction (along arrow) when activated. The starting and goal states are indicated by **s** and **g**, respectively. The states marked with **i** serve as additional starting locations during latent learning. **b**) Latent learning agents (blue curve) with prior exposure to the environment (trials -50 to -1, targeted pre-exposure) consistently reach the goal faster than direct learning agents (orange dashed curve), after a reward is introduced from trial 0 on. Curves represent averages over 30 simulations and the shaded area the s.d. The reward is $r = 5$. Left: gridworld. Right: Tolman maze. **c**) Latent learning agents are unsuccessful on the spatial task during the pre-exposure phase, but after the introduction of rewards they reach the goal state more consistently than the direct learning agents do. Left: gridworld. Right: Tolman maze.

Fig 2. Successor features (SF) reveal the effect of latent learning. SF for all states are shown for the **a**) gridworld for the right action and **b**) Tolman maze for the up action, averaged over 30 simulations. Each row of panels corresponds to the successor transitions of a particular state to every state in the environment. Trials 0 and 50 correspond to before and after the learning phase, respectively. The SF shows that in both mazes the latent learning agent has learned the local connectivity of the maze during the pre-exposure phase before the learning phase commences. At the end of the learning phase, both agents exhibit similar transition patterns that reflect a movement from the start to the goal location in both mazes.

Fig 3. SF mapped onto the spatial structure of the environment for latent learning agents. Shown are visualizations of the SF, mapped onto the environment structure, for the state indicated by the orange cross in the **a**) gridworld and **b**) Tolman maze. Trial −50 corresponds to the randomly initialized SF. After the pre-exposure to the environment (trial 0), the future states which are expected to be visited by the agent are mostly near the current state, whereas by the end of learning (trial 50), the future occupancy of states has evolved into a path leading to the goal.

learning agent due to its randomly initialized successor features and the reward weight (Fig 4, trial 0). This contrasts with the latent learning agent, which has acquired both the SR local connectivity and an approximate reward function ($R(s) \approx 0$, for all s) after exploring the environment devoid of reward (trial 0 of latent learning). This leads to a more uniform distribution of Q-values across various regions of the environment. The color intensity of each arrow in the graph represents the normalized values $(0 - 1)$ associated with each state-action pair. At the end of the learning trials (trial 50), the Q-values for both agents show prioritized actions that lead to the goal.

Impact of differences in task design on latent learning

Next, we investigated a different latent learning experimental design: continuous pre-exposure. This agent also exhibited latent learning, consistently outperforming the direct learning agent in escape latency (Fig. 5). However, it initially required more trials to learn the task than the agent receiving targeted pre-exposure. This subtle difference in performance aligns with findings from the literature [5,6], indicating that targeted pre-exposure may confer an advantage in terms of learning speed of latent learning.

To examine the cause of the difference between the two different pre-exposure paradigms, we compared the resulting SFs at the end of the exploration. Targeted pre-exposure led the agent to develop a spatial structure with higher similarity to the SF of the direct learning agent by the end of the rewarded learning than continuous pre-exposure did (Fig. 6). This higher similarity for the targeted pre-exposure agent was particularly pronounced for states closer to the goal, as estimated by the cosine similarity between the outputs of the SF network at each state for the direct learning agent and the latent learning agents (Fig. 6c,d). These findings indicate that even without rewards, the targeted pre-exposure helps the agent build spatial knowledge of the environment that favors movement towards the goal location, which potentially explains the observed faster learning compared to the continuous pre-exposure agent.

To confirm this explanation, we further studied the RL policy that emerges from the SF just after the pre-exposure phase. To this end, we computed the Q values (Fig. 7a,b) by combining the agents' SF and an approximate ground truth reward function $R(\mathbf{g}) \approx 1$, where $\mathbf{g}$ represents the goal state, and $R(\mathbf{s}) = 0$ for all other states. In contrast to continuous pre-exposure, these values are higher for the targeted pre-exposure agent in states further from the goal — which facilitates the agent selecting the correct action when the learning phase begins. Furthermore, we compared the optimal actions for the task in the Tolman maze with the actions selected by the latent learning policies in the last trial before introducing the reward (Fig. 7c, trial 0). The learned policy selects the actions that lead to the goal state more frequently in most states for the targeted pre-exposure agent (30 simulations, dead-end states are omitted because they have only one viable action, and the action mask matches the optimal action with probability 1, see Methods). Our results suggest a pre-existing bias that carries over to the learning phase.

Effect of exploration strategies on latent learning

To investigate how robust the subtle learning speed differences are that emerge from different latent learning designs, we studied different RL exploration strategies (Fig. 8). The targeted pre-exposure agent learned the task faster when using the *softmax* policy (similar to results with ε-greedy policy) using inverse-temperature $\beta = 1$, followed by continuous pre-exposure and direct learning agents. Nonetheless, the latter two also significantly progressed in the learning phase, narrowing the performance gap observed under the ε-greedy (Fig. 6a,b).

Fig 4. Learned state-action values. For the **a**) gridworld environment and **b**) Tolman maze, the color of each arrow represents the Q value (indicated by color) of the corresponding action in that state. For direct learning agents, both the SF network and the reward weight vector are randomly initialized, resulting in a stochastic distribution of Q-values at trial 0. Latent learning agents have encoded the transition structure between neighboring states and a proper reward function ($R(s) \approx 0$, for all s) by the end of the pre-exposure phase. This leads to a more uniform distribution of Q values. Following learning with reward, both agents converge towards similar Q values, with higher values for actions leading toward the goal.

Fig 5. Experimental task design subtly influences latent learning. Comparison of two experimental designs for the pre-exposure phase to direct learning for the **a**) Tolman maze and **b**) gridworld. Continuous pre-exposure clearly leads to latent learning, i.e., faster task improvements than direct learning. However, the performance after continuous pre-exposure is inferior to targeted pre-exposure.

We account for this performance gain under the softmax policy, as compared to ε-greedy policy, as follows. After exploration, Q values tend to become more uniformly distributed (see Fig. 7). If Q values of different actions in the same state are similar, the softmax policy chooses stochastically between these actions with almost equal probability, depending on the inverse temperature β. This leads the softmax policy to prioritize exploration in the initial states, potentially guiding the agent to the goal state faster during early learning. In contrast, the ε-greedy policy selects actions with the highest Q value with $(1 - \varepsilon)$ probability, even if the differences in Q values are small. This reduces exploration and might cause the policy to select the same action repeatedly during its greedy steps. This is especially detrimental if Q values for non-optimal actions leading to dead-ends are initially highest.

Next, we examined the impact of using doors on latent learning. The doors were set up in Blodgett's and Tolman's experiments [1,3] to speed up learning by preventing the animals from revisiting mapped locations. Daub further studied the effects of doors by comparing latent learning in environments with and without doors [4] using four groups of animals in a 2×2 design. The groups were either pre-exposed to the environment without doors or not pre-exposed. In the learning phase, the door were either engaged or kept open. If no doors were used, animals that received pre-exposure performed better than animals without pre-exposure, demonstrating the usual latent learning effect. Interestingly, when doors were activated, animals without pre-exposure performed virtually identically those with pre-exposure.

In our simulations we considered the four cases studied by Daub, plus one more case that he did not study, where doors were present both during the pre-exposure and the learning phase. Analogous to time limits in the experimental study, we imposed a stricter time limit of 500 step. Our simulations reveal interesting features (Fig. 9). First, direct and latent learning agents both failed to master the task if no doors were used (Fig. 9, blue and orange curves), emphasizing the difficulty of the task under the stricter step limit. Nevertheless, the latent learning agent outperformed the direct agent during the learning phase despite reaching the goal during the pre-exposure phase only in a few trials. Second, activating doors in the learning phase vastly improved the performance of both the latent and direct learning agents (Fig. 9, green and red curves) and the learning speeds were comparable, as they were in Daub's experiment. Third, activating

Fig 6. The structure of successor features (SF) accounts for performance difference in the two different pre-exposure paradigms. a) Left: Well-learned SF for the direct learning agent in the gridworld. Center: After targeted pre-exposure, the SF structure is similar to what the direct learning agent learns from rewards, particularly in states near the goal (shown in inset). Right: After continuous pre-exposure, the structure is more dissimilar to that of the direct learning agent. **b**). Same as in a) for the Tolman maze. **c**) For the gridworld. The cosine similarity between the SF vector from the latent learning agents at the end of the pre-exposure phase and that from the direct learning agent at the task's conclusion. Targeted pre-exposure results in superior scores in states close to the goal (last state). **d**) Same as in c) for the Tolman maze.

Fig 7. Evaluation of the policies learned during the pre-exposure phase. Q values for targeted and continuous pre-exposure in the **a**) gridworld environment, and **b**) Tolman maze, computed from the learned SF multiplied with the ground-truth reward function. Targeted pre-exposure drives elevated values for states that are more distant from the goal, compared to continuous pre-exposure. The green edges show the action with the highest Q-value in that state. **c**) The probability of selecting the optimal action at the conclusion of the pre-exposure phase in the Tolman maze, averaged over 30 simulations. Targeted pre-exposure tends to lead to the optimal actions more frequently than continuous pre-exposure. Dead-end states, where only one action is viable, exhibit an action selection probability of 1 and are omitted here for clarity.

Fig 8. Latent learning observed with different RL exploration strategies.
Evaluation of the softmax policy for exploration in the **a**) gridworld and **b**) Tolman
maze. Latent learning agents consistently exhibit faster learning during the learning
phase, compared to direct learning agents. The subtle performance differences between
targeted and continuous pre-exposures persist even as the exploration policy changes.

Fig 9. The impact of doors on latent learning. Activating doors that prevent
returns to previous locations in the Tolman maze during pre-exposure and learning
phases significantly influences the performance of the agent (average over 30
simulations, with a maximum of 500 steps per trial). Performance is improved when
doors are active. Labels for agents with pre-exposure indicate the door conditions
during both pre-exposure and learning phases, e.g. No doors/Doors correspond to no
doors during pre-exposure and having doors during learning.

doors during both pre-exposure and learning phase simulations led to the best performance (Fig. 9, purple curves).

Our simulation results suggest that the activation of the doors helped the agent explore the environment more efficiently and, thus, find the goal location within the short time limit in the initial learning trials. This, in turn, helped the agents learn faster trial-by-trial than in the simulations without doors. This learning aid diminished the advantage of pre-exposure (second observation). Nevertheless, even in this setup there is room for latent learning as evident in the third observation.

Discussion

The reinforcement learning (RL) agent based on deep successor representation (DSR) successfully exhibited latent learning by learning the spatial layout during pre-exposure phases. The agent encoded spatial information in two ways: a transition model representing connections between neighboring states and a forward state transition model connecting the current state directly to the goal state. The latent learning effect is modulated by the task design in the pre-exposure phase and mediated via the SR learning during pre-exposure. Targeted pre-exposure improves performance more on subsequent learning tasks compared to continuous pre-exposure, because it learns a policy during pre-exposure that guides the agent toward the goal more efficiently when the reward is introduced. These results are qualitatively consistent with experimental results [5, 6].

Our modeling results point to a key role of the exploration strategy, for which we have only very simplistic mechanisms in our model, i.e., ε-greedy and softmax. On the one hand, the exploration strategy helps the agent search the environment more efficiently and find the goal more quickly. On the other hand, the exploration strategy also helps build a more useful cognitive map, because the SR depends on the policy. Exploration has traditionally been considered a simple behavior compared to other spatial navigation behaviors and strategies, but more recently we have suggested that the reverse might be true and exploration might be the most complex navigation process of all [8, 22].

Our results also emphasize the role of doors that limit exploration to moving forward in improving exploration and task performance in a spatial learning task. In these cases, doors primarily accelerate the goal finding in the early trials of the learning phase, narrowing the effect of latent learning. Our findings are consistent with Daub's behavioral study [4], particularly the similar time scores observed between direct and latent learning animals that learned the task with doors.

Ideally, a cognitive map for an environment should encode spatial information as richly as possible, including route connections, locations of landmarks, distance and direction relations, etc. Even non-spatial attributes such as emotional associations can be stored as well [23]. However, given the limited computational resources in the brain, a cognitive map should balance its usefulness and encoding/decoding efficiency. The successor representation (SR) algorithm offers a trade-off between the two by encoding the temporal and spatial distance between each pair of states in the environment. It enables the animal to quickly generate a route to a given goal location when a reward is delivered.

The cognitive map has been suggested to reside in the hippocampus almost since the discovery of place cells in the hippocampus [24]. Recently, the SR has been suggested as an alternative view to place cell coding in the hippocampus [12]. Using the SR as a cognitive map, hence closes the loop involving hippocampus, place cells, SR, and the cognitive map. However, the spatial information in SR is represented rather implicitly in such a way that the transition dynamics of the external world are not captured, i.e.

the next state from a state-action pair is not stored, unlike a graph representation. Therefore, flexible planning such as generating and comparing multiple routes are not straightforward to implement by using SR. For instance, it is hard to explain the replay of sequences of place cells [25, 26], if states in SR are not explicitly connected. Nevertheless, SR offers a useful and efficient representation of the external environment, and its biological basis needs further investigation.

Our modeling study makes multiple predictions for the neural mechanisms underlying latent learning. First, neural representations of space are learned in the absence of a navigation task. Surprisingly, there is little experimental evidence on this because in traditional place cell recording studies animals are rewarded for running back and forth on a linear track or chase food pallets in an open arena. Second, the nature of the spatial representation depends on the task-design of the pre-exposure phase. Third, the spatial representation of the environment at the end of pre-exposure correlates with the degree of latent learning later on. This correlation is independent of the exploration strategy.

In summary, this work contributes to a deeper understanding of the mechanisms of latent learning and its underlying neural mechanisms. It potentially explains how such learning shapes cognitive maps and influences their efficacy in spatial tasks.

Acknowledgements

We thank Dr. Nicolas Diekmann for his valuable contributions to the CoBeL-RL framework implemented in this work.

References

1. Blodgett HC. The effect of the introduction of reward upon the maze performance of rats. University of California Publications in Psychology. 1929;4:113–134.

2. Tolman EC, Honzik CH. Introduction and removal of reward, and maze performance in rats. University of California Publications in Psychology. 1930;4:257–275.

3. Tolman EC. Cognitive maps in rats and men. Psychological Review. 1948;55:189–208. doi:10.1037/h0061626.

4. Daub CT. The effect of doors on latent learning. Journal of Comparative Psychology. 1933;15:49–58. doi:10.1037/h0070697.

5. Karn HW, Porter Jr JM. The effects of certain pre-training procedures upon maze performance and their significance for the concept of latent learning. Journal of Experimental Psychology. 1946;36:461–469. doi:10.1037/h0061422.

6. Sutherland RJ, Linggard R. Being there: a novel demonstration of latent spatial learning in the rat. Behavioral and Neural Biology. 1982;36(2):103–107. doi:https://doi.org/10.1016/S0163-1047(82)90101-7.

7. Thistlethwaite D. A critical review of latent learning and related experiments. Psychological Bulletin. 1951;48:97–129. doi:10.1037/h0055171.

8. Wang MZ, Hayden BY. Latent learning, cognitive maps, and curiosity. Current Opinion in Behavioral Sciences. 2021;38:1–7. doi:https://doi.org/10.1016/j.cobeha.2020.06.003.

9. Guo W, Zhang JJ, Newman JP, Wilson MA. Latent learning drives sleep-dependent plasticity in distinct CA1 subpopulations. bioRxiv. 2020;doi:10.1101/2020.02.27.967794.

10. Scleidorovich P, Llofriu M, Fellous JM, Weitzenfeld A. A Computational Model for Latent Learning based on Hippocampal Replay. In: 2020 International Joint Conference on Neural Networks (IJCNN); 2020. p. 1–8.

11. Dayan P. Improving Generalization for Temporal Difference Learning: The Successor Representation. Neural Computation. 1993;5(4):613–624. doi:10.1162/neco.1993.5.4.613.

12. Stachenfeld KL, Botvinick MM, Gershman SJ. The hippocampus as a predictive map. Nature Neuroscience. 2017;20(11):1643–1653. doi:10.1038/nn.4650.

13. Momennejad I, Russek EM, Cheong JH, Botvinick MM, Daw ND, Gershman SJ. The successor representation in human reinforcement learning. Nature Human Behaviour. 2017;1(9):680–692. doi:10.1038/s41562-017-0180-8.

14. Russek EM, Momennejad I, Botvinick MM, Gershman SJ, Daw ND. Predictive representations can link model-based reinforcement learning to model-free mechanisms. PLOS Computational Biology. 2017;13(9):1–35. doi:10.1371/journal.pcbi.1005768.

15. Ducarouge A, Sigaud O. The Successor Representation as a model of behavioural flexibility. In: Journées Francophones sur la Planification, la Décision et l'Apprentissage pour la conduite de systèmes (JFPDA 2017). Actes des Journées Francophones sur la Planification, la Décision et l'Apprentissage pour la conduite de systèmes (JFPDA 2017). Caen, France; 2017.Available from: https://hal.science/hal-01576352.

16. Sutton RS, Barto AG. Reinforcement Learning: An Introduction. Cambridge, MA, USA: A Bradford Book; 2018.

17. Mnih V, Kavukcuoglu K, Silver D, Rusu AA, Veness J, Bellemare MG, et al. Human-level control through deep reinforcement learning. Nature. 2015;518(7540):529–533. doi:10.1038/nature14236.

18. Kulkarni TD, Saeedi A, Gautam S, Gershman SJ. Deep Successor Reinforcement Learning; 2016.

19. Stoewer P, Schlieker C, Schilling A, Metzner C, Maier A, Krauss P. Neural Network Based Successor Representations to Form Cognitive Maps of Space and Language. Scientific Reports. 2022;12(1):11233. doi:10.1038/s41598-022-14916-1.

20. Diekmann N, Vijayabaskaran S, Zeng X, Kappel D, Menezes MC, Cheng S. Cobel-RL: A neuroscience-oriented simulation framework for complex behavior and learning. Frontiers in Neuroinformatics. 2023;17. doi:10.3389/fninf.2023.1134405.

21. Glorot X, Bengio Y. Understanding the difficulty of training deep feedforward neural networks. In: Teh YW, Titterington M, editors. Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics. vol. 9 of Proceedings of Machine Learning Research. Chia Laguna Resort, Sardinia, Italy: PMLR; 2010. p. 249–256. Available from: https://proceedings.mlr.press/v9/glorot10a.html.

22. Parra-Barrero E, Vijayabaskaran S, Seabrook E, Wiskott L, Cheng S. A map of spatial navigation for neuroscience. Neuroscience & Biobehavioral Reviews. 2023;152:105200. doi:https://doi.org/10.1016/j.neubiorev.2023.105200.

23. Downs RM, Stea D. Cognitive maps and spatial behaviour: Process and products. In: The map reader: Theories of mapping practice and cartographic representation. Chichester, UK: John Wiley & Sons, Ltd; 2011. p. 312–317.

24. O'Keefe J, Nadel L. The hippocampus as a cognitive map. Oxford, United Kingdom: Clarendon Press; 1978.

25. Diekmann N, Cheng S. A model of hippocampal replay driven by experience and environmental structure facilitates spatial learning. eLife. 2023;12:e82301. doi:10.7554/eLife.82301.

26. Buhry L, Azizi AH, Cheng S. Reactivation, replay, and preplay: how it might all fit together. Neural Plast. 2011;2011:203462.