Accumulation of virtual tokens towards a jackpot reward enhances performance and value encoding in dorsal anterior cingulate cortex

Demetrio Ferro[1,2,3], Habiba Azab[4], Benjamin Hayden[4] and Rubén Moreno-Bote[1,2,5]

[1] Center for Brain and Cognition, Universitat Pompeu Fabra, 08002, Barcelona, Spain;

[2] Department of Information and Communications Technologies, Universitat Pompeu Fabra, 08002, Barcelona, Spain;

[3] Centre de Recerca Matemàtica, Edifici C, Campus Bellaterra, 080193, Bellaterra (Barcelona), Spain;

[4] Department of Neurosurgery, Baylor College of Medicine, Houston, TX, 77030;

[5] Serra Húnter Fellow Programme, Universitat Pompeu Fabra, Barcelona, 08002, Spain.

*Corresponding author: ferrodemetrio@gmail.com

Abstract

Normatively, our decisions ought to be made relative to our total wealth, but in practice, we make our decisions relative to variable, decision-time-specific set points. This predilection introduces a major behavior bias that is known as reference-point dependence in Prospect Theory, and that has close links to mental accounting. Here we examined neural activity in the dorsal anterior cingulate cortex (dACC) of macaques performing a token-based risky choice task, in which the acquisition of six tokens (accumulated over several trials) resulted in a jackpot reward. We find that subjects make faster and more accurate choices, and that they are less prone to risk-taking as offer contingencies are easier and the jackpot reward becomes more likely to be achieved. By comparing alternative models that accounted for progressive token accumulation, we found that subjective evaluations are best explained by a reference-dependent value 'RDV' model where offer values are considered as potential gains or losses with respect to a token-dependent reference. The reference-dependent model allows to implement a dynamical comparison of the two offered values to each other and to the number of missing tokens to reach the six tokens threshold as jackpot approached. In dACC, we find that gains in subjective values entail higher fractions of encoding cells than losses, and that the encoding tuning of expected utility variables is best aligned to choices in gains than in losses. These results suggest a neural basis of reference dependence biases in shaping decision-making behavior and highlight the critical role of value representations in dACC in driving evaluations.

Introduction

In their seminal work, Kahneman and Tversky[1] fundamentally reshaped our understanding of decision-making under risk. While utility and probability distortion components of Prospect Theory are important, the assessment of context-dependent references used in value-based decisions is equally critical. Yet, whereas the neural basis of risk and probability distortion is well understood, the neural processes underlying reference dependence remain less clearly delineated. In animal studies, reference dependence can be difficult to study on single trials, but it becomes tractable when considering behavioral variability across decision trials. Previous studies have examined the influence of behavioral history on decision-making[2–5], typically using paradigms in which subjects choose between probabilistic options with immediate reward delivery. However, adopting token-based economic tasks allows to investigate the progressive effects of delayed rewards on choice and its neural representations.

Token-based decision-making tasks provide a powerful framework for studying the progressive effects of delayed rewards on subjective value (SV), influencing risk preferences and decision strategies[15]. In these paradigms, choices deliver virtual tokens rather than immediate rewards, contributing to a large jackpot reward once a predetermined token count is reached. Token accumulation naturally introduces shifting internal evaluation of reference-dependent gains or losses inspired by Prospect Theory.

Advances in the field of neurophysiology have substantially contributed to our understanding of neural mechanisms functionally involved in decision-making, which include brain regions associated with reward processing such as the orbitofrontal cortex (OFC), the ventromedial prefrontal cortex (vmPFC), the anterior cingulate cortex (ACC), and the ventral striatum[6–14]. The vmPFC and OFC are predominantly associated with the computation of relative offer value[15–21] and have been functionally linked to cumulative reward signals in token-based tasks[22], whereas the ACC plays a role in evaluating potential outcomes, monitoring action costs, and tracking motivational signals[23–33]. Importantly, the dorsal ACC (dACC) has been implicated in reward anticipation[34,35], cognitive effort computation[36,37], and in the integration of delayed or cumulative rewards across various decision-making contexts[29,38–42]. Neural signals in ACC have been previously associated with multi-trial[43], post-decisional variables[42,44] and virtual reward expectation[45], suggesting that this region could support reference-dependent value encoding and behavioral adjustments[46,47].

In this work we analyzed behavioral and neural data from two macaques performing a token-
based decision-making task (Fig. 1A)[21,38–41]. On each trial, subjects chose between two
probabilistic offers associated with token gains or losses (ranging from -2 to +3 tokens). Tokens
accumulated across trials, and upon reaching a total of six, a large jackpot reward was delivered.
We tested whether decision-making strategies and neural encoding in dACC reflected value-based
signals alone or if they were shaped by a reference-dependent utility defined by token
accumulation.

At the behavioral level, we found that choices were strongly influenced by the expected
value (EV) and risk (R) of the two offers, but also by jackpots on previous trials (JPT), and by
accumulated tokens count (ATC), which modulated accuracy, reaction time, and risk propensity
(Figures 2-4). As subjects approached the jackpot threshold, choices became more accurate and
faster, and risk-seeking declined. To formalize these effects, we compared three models of
subjective value (SV): two logistic models that related EV and R (with or without ATC
interactions) to choice, and a reference-dependent value (RDV) model that treated ATC as a
dynamic reference point separating gains and losses in a logistic model of SV and the choice. The
RDV model followed the intuition that subjects dynamically switched the way the evaluated
offered values as potential gains or losses relative to the number of missing tokens to jackpot ($6 -$
ATC) whenever jackpot was achievable in current trial, or relative to zero whenever jackpot was
not achievable. Comparing the three models, we found converging evidence that the RDV model
provides the best fit across all behavioral metrics, supporting the hypothesis that token
accumulation induces reference-dependent valuation.

Finally, we examined neural correlates of these computations in dACC by regressing the
spike rate of each recorded cell to SV defined according in the three behavioral models tested.
Across models, substantial fractions of neurons encoded the two SVs, peaking during offer
presentation epochs. Critically, the RDV model revealed a gain-dominant recruitment of cells in
the encoding pattern: gains were represented by significantly larger fractions of cells than losses,
and the neural tuning of gain-related EV encoding predicted choice behavior more accurately than
loss-related EV, or R variables in either gains or losses. These findings indicate that dACC
dynamically integrates expected value with ATC-dependent reference signals to guide goal-
directed behavior.

Results

The two subjects performed correct choices, i.e., choices that maximized outcomes, as measured by the offer expected value (EV), in most trials (subject 1: $79.78 \pm 0.19\%$ mean $\pm$ s.e.m., subject 2: $74.19 \pm 0.18\%$). By using a generalized model of the choice (Methods 2.1), we found that correct choices, i.e., choices for the offer with best EV, were predominantly influenced by the difference in expected values ($\Delta_{EV} = |EV_1 - EV_2|$), the average magnitude of the two EVs ($M_{EV} = EV_1/2 + EV_2/2$), the difference in risk between the offer with the best EV and the offer with worst EV (the offers risk level, ORL), the tokens collected in task trials previous to current trial (accumulated tokens count, ATC), and the achievement of a jackpot on previous trial (JPT) (Fig. 2A, Supp. Table ST3). These factors had a strong and statistically significant impact on the decisions made by the two subjects, suggesting that both relied on these variables to form heuristics and choose offers with the best EV. Here, the influence of ATC is particularly critical, as it not only reflects the motivational drive toward jackpot but also provides a progressive context for value computations. The tokens count shifts the decision frame from evaluating offer values relative to each other when jackpot is out of reach to comparing offer values to jackpot threshold when nearing jackpot, a reference-dependent evaluation paradigm that is central to our investigations. Additionally, we find that subject 2 tended to make fewer choices for the offer with the best EV for better outcomes on previous trial (OPT), and both subjects made fewer best EV choices as the number of trials since the last jackpot reward ($TSLR$) increased.

The role of accumulated tokens in choice performance

We found that the accumulated tokens count (ATC) has an important impact on the subject's choices. When considering choices for the offer with the best offer EV (Methods 2.2), we found that subjects were more accurate (Fig. 2B) and faster (Fig. 2C) when they had collected more tokens, i.e. when they got closer to the possibility of achieving a jackpot reward (Supp. Table ST4). Conversely, the subjects took longer to perform the task and were less accurate when the accumulated tokens count was lower. To investigate this aspect further, we modeled the probability of choosing one of the two offers in relation to the difference in expected value of the two offers, by using a logistic model $\mathrm{logit}(ch_1) = \beta_0 + \beta_1(EV_1 - EV_2)$, and fit the model separately in trials with 'Low' ($ATC = 0 - 1$) or 'High' ($ATC = 4 - 5$) accumulated tokens count

(Fig. 2D). We found a significant increase in the slope of the logistic relationship ($\beta_{1,High}$ −

$\beta_{1,Low}$, p= $1.77 \cdot 10^{-4}$ in subject 1, p= $1.34 \cdot 10^{-19}$ in subject 2, two-tailed Wilcoxon signed rank

test for zero median), corroborating previous insights about higher task engagement for higher

accumulated tokens count (Fig. 2E).

Jackpot, accumulated tokens count, and best offer discriminability improve choice

performances

We computed the fraction of errors in choosing the offer with the best EV based on whether the

current trial was preceded or not by a jackpot reward, for different ranges of accumulated tokens

count, and for different levels of difficulty in discriminating between the best and the worst offer.

For accumulated tokens count, we used the ranges 'Low' ($ATC = [0,1]$), 'Medium' ($ATC =$

$[2,3]$) and 'High' ($ATC = [4,5]$) (Supp. Table ST1). For the difficulty, we used Δ_{EV} and the

respective median(Δ_{EV}) = 1 as difficulty discriminant, leading to split data in 'Hard' and 'Easy'

trials, respectively based on whether $\Delta_{EV} < 1$ or $\Delta_{EV} \geq 1$ (Supp. Table ST2). Combining the

jackpot conditions, accumulated tokens count, and difficulty, we find that the fraction of errors in

choosing the offer with best EV most differentiate based on the trial difficulty (Fig. 3, Supp. Table

ST5). The presence of jackpot before the current trial did not have a significant impact on the

fraction of errors of subject 1 (Easy trials: No Jackpot versus Jackpot, p= 0.067, two-tailed

Wilcoxon signed-rank test; Hard trials: p= 0.24), while in subject 2 the fraction of errors

significantly increased after jackpot only in easy trials (Easy trials:, p= $1.21 \cdot 10^{-10}$; Hard trials:

p= 0.31, Fig. 3A, Supp. Table ST5).

The accumulated tokens count had a significant impact on the fraction of errors of both subjects,

showing a decreasing trend in the fraction of errors in choosing the offer with the best EV as the

ATC increased (Fig. 3A, Supp. Table ST5). Note that the task trial occurrences become fewer and

fewer as ATC values grow from Low to High, regardless of the task difficulty (Supp. Table ST1).

Since the most prominent difference in fractions of errors was based on task difficulty, we also

investigated fractions of errors for binned values of Δ_{EV}, which we used as an inverse metric of

difficulty. As expected, the fraction of errors decreased with Δ_{EV}, as larger Δ_{EV} indicates easier

detection of the best offer. By comparing the fractions of errors in High and Low accumulated

tokens counts, we found a lower fraction of errors in High accumulated tokens, indicating that

accumulating a larger number of tokens boosts the best EV discrimination, most prominent and

significant in both subjects for intermediate difficulty (Δ_{EV}=[1, 3] subject 1, significant for all Δ_{EV}

in subject 2, Fig. 3B). In similar way as for ATC, we find fewer trial occurrences when considering

larger Δ_{EV} bins, coinciding with easier trials (Supp. Table ST2). These results align with the

observation that subjects tend to be more accurate and faster whenever they accumulate more

tokens before the current trial, adding a further level of stratification in considering the difficulty,

that has a prominent role in committing best offer contingency detection errors.

Jackpot, accumulated tokens count, and difficulty in best offer discriminability impact

risk-taking propension

We asked whether previous results suggesting improvement in choice speed and accuracy with

ATC could relate to a higher propensity for risky options whenever subjects felt that achieving a

jackpot reward was less likely and far apart, requiring further accumulation of tokens. By

comparing the fraction of trials where subjects chose the offer with the highest risk, we observed

that the presence of a jackpot on the previous trial decreased the fraction of choices for the riskiest

option, significant for subject 1 (subject 1: p$= 1.04 \cdot 10^{-3}$, two-tailed Wilcoxon signed-rank test,

subject 2: p$= 0.37$, Supp. Table ST6). We found that both subjects significantly made more risky

choices when choosing the offer with best EV was hard ($\Delta_{EV} < 1$) as opposed to easy ($\Delta_{EV} \geq 1$)

trials (subject 1: p$= 1.47 \cdot 10^{-19}$, two-tailed Wilcoxon signed-rank test, subject 2: p$= 4.21 \cdot$

10^{-21}, Supp. Table ST6).

By combining difficulty and jackpot conditions, we found that subjects consistently chose risky

offers less frequently after a jackpot reward in Hard trials (Fig.4A, Supp. Table ST6), while in

Easy trials risky choices after jackpot were less frequent in subject 1 (Fig. 4A, Supp. Table ST6),

and more frequent in subject 2 (Fig. 4A, Supp. Table ST6). We reported a remarked difference in

the fraction of choices for the riskiest option between Easy and Hard trials, with Hard trials

involving higher fractions of choices for the riskiest option across ATC conditions (Fig. 4A, Supp.

Table ST6). We found a consistent inverted U-shape relationship between the fraction of risky

choices and ATC ranges in Hard trials in both subjects, showing increasing trend for $ATC = [0, 2]$,

and decreasing trend for $ATC = [3, 5]$ (Fig. 4A; Supp. Table ST6). To further investigate the effect

of risk on the decisions of the two subjects, we quantified the risk attitude of subjects by using a

Markowitz model, i.e., computing the ratio between the weight of the risk (β_2) and EV (β_1)

differences between the two offers in a logistic model of the choice including these two variables

as choice predictors (Methods 2.4). The model parameter $\theta = -\beta_2/\beta_1$ describes the subjective

behavioral attitude as risk aversion ($\theta > 0$) or risk-seeking ($\theta < 0$). We report a risk-seeking

attitude in both subjects, with higher risk aversion (reduced magnitude of θ) as the number of

accumulated tokens increases, and in Easy trials (Fig. 4B, Supp. Table ST6). Comparing jackpot

conditions, we find that θ has smaller, negative magnitude for Hard trials following a jackpot

reward, consistent in the two subjects (Fig. 4B; Supp. Table ST6), in line with lower risky choice

fractions results (Fig. 4A, Supp. Table ST6).

We found that the EV difference has an increasing impact (β_1) on choices for the riskiest option,

consistent in the two subjects for Hard trials (Fig. 4C, Supp. Table ST6) than in Easy trials (Fig.

4C, Supp. Table ST6). The risk difference weight (β_2) shows an inversed U-shape, most prominent

and consistent in the two subjects for Hard trials (Fig. 4D, Supp. Table ST6), larger than for Easy

trials (Fig. 4D, Supp. Table ST6), both results are in line with the fraction of risky choices (Fig.

4A, Supp. Table ST6). The Markowitz variable $\theta = -\beta_2/\beta_1$, shows decreased magnitude as the

accumulated token counts increases for 'High' ATC ranges, in both Hard (Fig. 4D, Supp. Table

ST6), suggesting that when the jackpot reward becomes more likely in tokens count, the subjects

are more averse to risk. All the above results found for Low, Medium, High ATC ranges are also

found for discrete values of ATC (Supp. Fig. S1).

Models of choice: Subjective Values and reference-dependent evaluation in token-based
decision-making

To further investigate how subjects integrate behavioral variables and contextual information into their decision, we formalized choice behavior using predictive models of Subjective Value (SV). Given the observed effects of EV, R, and ATC on behavior, we compared three alternative models that differed in how these factors were combined. The first model, a 'linear model of choice without ATC interaction' defined SV as a linear combination of EV, R and ATC, without interaction terms (Methods 2.4.1). This was extended to a second 'linear model of choice with ATC interaction' in which ATC modulated the influence of EV and R through interaction terms to capture how the influence of EV and R varied with ATC (Methods 2.4.2). We then introduced a reference-dependent value 'RDV' model that incorporates the key idea that token accumulation dynamically defines a reference point for evaluating gains and losses (Methods 2.4.3). In this model, the perceived value of each offer is computed relative to a shifting internal reference $r(ATC)$, which approaches zero when ATC is low and jackpot is out of reach, and transitions to the number of tokens required to reach the jackpot $(6 - ATC)$ as jackpot achievement becomes closer. The offer values, instructed by cue colors (v, ranging -2 to $+3$ tokens) was shaped by a token-dependent utility function $u(v, ATC)$ adapted from Prospect Theory. The curvature of this function depend on ATC in two ways: the value sensitivity parameter $\gamma(ATC)$ increases linearly with ATC, reflecting stronger weighting of EV with token accumulation (Fig. 4C, Supp. Fig S1C); the loss-aversion parameter $\lambda(ATC)$ varies quadratically with ATC, consistent with the inverted U-shaped relationship observed between risk taking and ATC (Fig. 4D, Supp. Fig. S1D). This formulation captures how motivational proximity to the jackpot reshapes value computation and risk sensitivity, enabling a smooth reference-dependent transition.

We trained each model using choice, EV, R and ATC features to estimate regression weights via maximum likelihood and assessed performance using cross-validated test data ($k = 4$ folds). Across all models, EV difference emerged as the strongest predictor of choice (Supp. Fig. S2, Supp. Table ST7). In the first model, risk was the second-largest positive weight, followed by a negative constant term and the ATC regressor weight, showing relatively low magnitude, statistically significant in subject 1 and in data pooled for the two subjects (Supp. Fig. S2, Supp. Table ST7). In the second model, the EV and ATC interaction term had second-largest positive weight, followed in magnitude by R, a negative constant term, the linear and quadratic interactions

between R and ATC (Supp. Fig. S2, Supp. Table ST7). In the RDV model, we also found meaningful parameter estimates, consistent between subjects. The reference $r(ATC)$ was defined by two parameters: a threshold κ_1, determining the ATC value above which jackpot achievement became behaviorally relevant (subject 1: 3.28±0.05 mean ± s.e.m across sessions, subject 2: 3.09±0.06), and a steepness parameter κ_0 controlling the sharpness of the transition (subject 1: 2.61±0.25, subject 2: 0.97±0.12). The value sensitivity function increased linearly with ATC ($\gamma(ATC) \approx 0.79 + 0.02ATC$ in subject 1, $0.66 + 0.03ATC$ in subject 2). Since the parameters $\gamma(ATC)$ is used as exponent of reference-dependent values, it makes value utility tend to linearity as subjects approach jackpot. The loss-aversion parameter followed an inverted-U profile ($\lambda(ATC) \approx 0.49 + 0.18ATC - 0.02ATC^2$ in subject 1, and $\approx 0.27 + 0.16ATC - 0.01ATC^2$ in subject 2), aligning with observed shifts in risk preference (Fig. 4D, Supp. Fig. S1D). The RDV model shows strongest regression weight for reference-dependent EV terms, followed in magnitude by reference-dependent R terms, and by a negative constant term.

Model comparison showed that RDV consistently outperformed the two first models across all metrics, including cross-validated choice prediction accuracy, adjusted coefficient of determination, negative log likelihood, Akaike Information Criteria (AIC), and Bayesian Information Criteria (BIC) (Supp. Fig. S3, Supp. Table S8), providing strong evidence that a reference-dependent, token-based SV framework best explains choice behavior in this task. We also assessed that RDV consistently outperformed concurrently adopted models implementing normative temporal discount of delayed reward values[48] and adaptive biases based on cumulative reward history[22].

Neural encoding of Subjective Value: the role of token accumulation and value tuning in behavioral choice readout

We tracked the neural encoding of task-related variables by designing time-resolved spike-rate analyses to detect the fractions of cells ($n = 129$, $n = 55$ in subject 1, $n = 74$ in subject 2) significantly encoding relevant task variables during execution time (Methods 3.1). We designed linear spike-rate models using the same SV definitions introduced for the three choice models assessed. In addition, we tested the possibility to predict behavioral choices based on neural encoding weights by designing Receiver Operating Characteristics (ROC) analyses using regressed spike rate model weights multiplied by test variable data. Lastly, we correlated the Area

Under the Curve of ROC analyses to time-averaged spike-rate model weights, investigating how

neural tuning properties to task variables also aligned with choice prediction.

The first spike-rate model, which excluded ATC interactions, revealed significant fractions of

cells significantly encoding the two SVs defined as in the 'linear choice model without ATC

interactions' (Methods 2.4.1, 3.1.1). The fractions of significantly encoding cells peaked around

the respective offer presentation epochs (Figure 5A-B, Supp. Fig S4). This model also included a

regressor for ATC, which was associated with notably higher fractions of significantly encoding

cells during late task execution epochs, posterior to offer presentation epochs (Figure 5A-B, Supp.

Fig S4). We quantified the fraction of cells exclusively or synergistically encoding task variables

in task epochs, considering the exclusive encoding of SV_1, SV_2, ATC, and their combinations

(SV_1&SV_2; SV_1&ATC; SV_2&ATC; SV_1&SV_2&ATC). The significance of fractions of cells were

assessed by comparison to the 95th percentile of equivalent fractions from trial-order shuffled data.

Since pre-offer 1 and throughout task epochs, cells exclusively encoding ATC represented the

largest and significant fraction, in line with the task design by which current trial ATC is cumulated

at the end of previous trial. The fraction of cells encoding ATC tended to lower during offer 1 and

offer 2 epochs, when SV encoding peaked. Following offer 1 onset, a significant proportion of

cells encoded SV_1, either exclusively or in combination with ATC, while the proportion of cells

encoding SV_2, either exclusive or simultaneous to SV_1 and/or ATC, was significant after offer 2

onset. Following delay 2, the fractions of cells exclusively encoding the two SVs gradually

lowered, and ATC emerged as the most encoded variable across cells, with minor, though

significant fractions of cells showing joint encoding of the two SVs and/or ATC (Fig. 5C, Supp.

Fig. S5).

To examine the relationship between neural tuning and behavioral choice, we performed a

Receiver Operating Characteristics (ROC) analysis, quantifying the predictive strength of spike-

rate regression weights with respect to key decision variables: the EV difference between the two

offers, the risk difference, and ATC (Methods 3.2.1). Predictive performance was assessed using

the Area Under the ROC Curve (AUC). Among regressors, the EV difference exhibited the

strongest choice (median AUC for positive regression weights $\beta_1' > 0$: 0.84, median AUC for

negative weights $\beta_1' < 0$: 0.17, data pooled across the two subjects, Fig. 5D). The risk difference

regressor followed (median AUC for $\beta_2' > 0$: 0.68, $\beta_2' < 0$: 0.31, Fig. 5D). As we expected, the

ATC variable itself did not show meaningful choice predictability (median AUC for $\beta_3' > 0$: 0.49,

$\beta_3' < 0$: 0.51, Fig. 5D).

Furthermore, spike-rate regression weights for both EV and R difference showed strong

correlations with the respective AUC values ($\rho = 0.84$ for EV difference, p<0.001, $\rho = 0.82$ for

R difference, p<0.001; significance assessed via two-tailed t-tests, Fig. 5D). In line with ROC

results, the ATC regressor showed modest correlation ($\rho = 0.05$, n.s., Fig. 5D). Importantly, all

AUC-related findings and regression weight correlations were consistent and statistically

significant across both individual subjects (Supp. Fig. S6).

The second spike-rate model combined value-based variables with accumulated tokens by

considering interactions between EV, R and ATC as in the 'linear model of choice with ATC

interactions' (Methods 2.4.2, 3.1.2). Regressors in this model comprised the main effect EV

difference between the two offers, the interaction of EV difference with ATC, the risk R difference,

a linear interaction term between R difference and ATC, and a quadratic interaction term between

R and ATC. This approach was motivated by prior observations indicating that the influence of

EV difference on choice increases with ATC (Fig. 4C, Supp. Fig. S1C), and that the relationship

between risk-seeking behavior and ATC follows an inverted-U profile (Fig. 4D, Supp. Fig. S1D).

The introduction of interaction terms did not fundamentally alter the overall SV encoding profiles:

the largest fractions of cells encoding SVs remained concentrated around offer presentation epochs

(Fig. 6A-B). However, the inclusion of these interaction terms did lead to a modest increase in the

fractions of cells encoding SVs during later task epochs in subject 2 (Supp. Fig. S7).

A more detailed analysis of SV encoding revealed that significant fraction of cells encoding

the two offers either exclusively (SV_1 or SV_2) or synergistically (SV_1 and SV_2) during task epochs

following the respective offer presentation, with only exception for the exclusive encoding of SV_1,

that was not significant in the choice-go epoch time (Fig. 6C). This pattern was prominent in cells

recorded in subject 2 (n=74), and in data combined across the two subjects (n=129). In contrast,

cells recorded in subject 1 (n=55) primarily showed significant encoding around offer presentation

epochs (Supp. Fig. S8).

In the spike-rate model with ATC interactions, we assessed choice predictability using ROC

analysis (Methods 3.2.2). Specifically, we assessed the AUC scores for the following regressors:

EV difference, EV difference and ATC interaction, R difference, R difference and ATC interaction,

R difference and ATC^2 interaction (Methods 3.2.1). Consistent with findings from the model

without ATC interactions, the EV difference regressor shows the strongest choice predictability

(median AUC for $\beta_1' > 0$: 0.84, $\beta_1' < 0$: 0.17, data combined for the two subjects, Fig. 5D). This

was followed by the EV difference and ATC interaction (median AUC for $\beta_2' > 0$: 0.77, $\beta_2' <$

0: 0.23, Fig. 5D), with gradually declining predictability for the Risk difference regressors

(median AUC for $\beta_3' > 0$: 0.69, $\beta_3' < 0$: 0.31, Fig. 5D), R difference and ATC (median AUC for

$\beta_4' > 0$: 0.64, $\beta_4' < 0$: 0.36, Fig. 5D), R difference and ATC^2 (median AUC for $\beta_5' >$

0: 0.63, $\beta_5' < 0$: 0.37, Fig. 5D).

All spike-rate regression weights showed strong and significant correlations with their

respective AUC values, with similar Pearson correlation coefficients across regressors ($\rho = 0.83$

for EV difference, p<0.001; $\rho = 0.81$ for EV difference and ATC interaction, p<0.001; $\rho = 0.79$

for R difference, p<0.001; $\rho = 0.79$ for R difference and ATC, p<0.001; $\rho = 0.79$ for R difference

and ATC^2; significance assessed via two-tailed t-test). All results from these AUC analyses were

significant and consistent in the two subjects (Supp. Fig. S9).

The RDV spike-rate model enabled the classification of offer value variables in gains and losses

based on their relationship between a token-dependent reference value, $r(ATC)$. This reference

shifted dynamically: it was set to 0 when jackpot was not achievable and changed to the number

of tokens missing to reach the jackpot ($6 - ATC$) once reaching the jackpot was possible. The

fraction of values resulting in gains ($\approx 43\%$, Supp. Table ST12) tended to be lower than the

number of values resulting in losses ($\approx 57\%$, Supp. Table ST12) as defined by the RDV utility

function (Methods 2.4.3). Within each offer, when the value cued by the top portion of offers

resulted in a gain, the value of the bottom portion tended to result in a loss. However, there was

very little interdependence between the two offers, as confirmed by gains/losses correlations

(Supp. Table ST13).

The RDV spike-rate analysis showed that a substantial fraction of dACC cells significantly

encoded SVs derived from the reference-dependent utility function (Methods 2.4.3, 3.1.3). Like in

the other models that we tested, the highest fraction of SV-encoding cells was observed around

offer presentation epochs (Fig. 7A-B). Significant SV encoding tended to persist in later task

epochs for both gains and losses (Fig. 7A-B, mainly in subject 2 cells Supp. Fig. S10). For SV_1

gains, the fractions of significantly encoding cells were significantly higher than for SV_1 losses in

almost all task epochs following offer 1 presentation, with exception of the delay 2 epoch (Fig.

7B). For SV_2 gains, the fractions of significantly encoding cells were significantly higher than for

SV_2 losses at offer 2, delay 2 and feedback (Fig. 7B).

We further analyzed encoding patterns by testing whether cells exclusively or synergistically

encoded gains and/or losses for the two SVs. Significance was determined by comparing empirical

fractions to the 95$^{\text{th}}$ percentile of equivalent fractions from trial-order shuffles. We found that as

soon as offers were presented, the respective SVs were significantly encoded exclusively for gains,

or in synergy for gains and losses, but not significantly for losses exclusively (Fig. 7C). During

offer 2, we found a modest, though significant fraction of cells encoding all SVs, including SV_1

and SV_2, in both gains and losses (Fig. 7C). Consistent with previous analyses, we found that the

fractions of significant cells gradually decayed after offer presentation epochs (Fig. 7C).

Finally, we assess how the neural tuning to SV in gains and losses related to the behavioral choice,

evaluating choice predictability using ROC analysis (Methods 3.2.3). We used as regressors the

EV and R variables defined over reference-dependent values (Methods 2.4.3), by keeping gains

and losses in separate regressors. We found that reference-dependent EV difference in gains is

remarkably more accurate in choice prediction (median AUC for $\beta_1' > 0: 0.85, \beta_1' < 0: 0.15$, Fig.

7D) than EV difference in losses (median AUC for $\beta_2' > 0: 0.65, \beta_2' < 0: 0.36$, Fig. 7D) or

reference-dependent Risk difference in gains (median AUC for $\beta_3' > 0: 0.62, \beta_3' < 0: 0.38$, Fig.

7D) or losses (median AUC for $\beta_4' > 0.64, \beta_4' < 0: 0.37$, Fig. 7D).

The spike-regression weights had strong and statistically significant correlations with their

respective AUC values, with EV difference regressors showing higher Pearson correlation

coefficients across regressors ($\rho = 0.73$ for EV difference in gains, $p < 0.001$; $\rho = 0.72$ for EV

difference in losses, $p < 0.001$; $\rho = 0.58$ for R difference in gains, $p < 0.001$; $\rho = 0.68$ for R

difference in losses, p<0.001; significance assessed via two-tailed t-tests). Importantly, these

AUC-based results were consistent in the two subjects (Supplementary Figure S12).

The RDV model results refine previous spike-rate model designs by allowing us to categorize

value-based regressors as gains or losses and extract the fraction of cells recruited for value

encoding in the two cases. This specific aspect is central to our investigations, as assessing a

reference-based method for neural encoding detection can be impacted by data size, in a way that

low trial availability can lead to miss the detection of significant encoding, yet lower trial

availability does not increase the false alarm rate. As control analysis, we have repeated results in

the 'linear model without ATC interactions' and the 'linear model with ATC interactions' by

considering value respectively as in Methods 3.1.1 or Methods 3.1.2 but by splitting value

variables labelled as gains or losses by the RDV utility function defined in Methods 2.4.3. This

showed two main results: reducing trial counts by splitting value variables into gains and losses

reduced the encoding detection power of spike-rate models (Supplementary Figures S13 and S15);

regression weights became correlated or anti-correlated with AUCs depending on whether gain or

loss trials were analyzed (Supplementary Figures S14 and S16). Lastly, to rule out the possibility

that our findings were artifacts of uneven trial availability in gain versus loss trials, we performed

a trial-matching control. We randomly sub-sampled trials (regardless of gain/loss classification)

to match the number of gain and loss trials used in the split analyses for both the 'linear spike-rate

model without ATC interaction' (Supp. Fig. S17) and the 'linear spike-rate model with ATC

interactions' (Supp. Fig. S18). This approach yielded similar reductions in encoding detection,

confirming that data size alone impacts sensitivity. Importantly, however, in control analyses

(Supp. Fig. S17-S18) loss trials consistently showed a higher fraction of significantly encoding

cells, consistent with their greater prevalence (≈57% of trials vs. ≈43% gains, Supp. Table ST12).

This control supports the robustness of our main finding that gains are encoded by a higher fraction

of neurons, despite being less frequent; if the observed effects were driven by trial count, we would

expect the opposite predominance pattern seeing losses encoded by higher fractions of cells than

gains. Lastly, we also observed that SV^+ always assume positive value since both EU^+ and VU^+

terms are positive, but that SV^- could be either positive or negative, since EU^- is negative but

VU^- is positive. This asymmetry fairly follows the RDV utility definition, and is also present in

the RDV choice model, which best explains behavioral data. We have checked that our main

results suggesting that SV encoding in gains entails larger fractions of cells than in losses also

holds by flipping the sign of the expected utility EU in losses, thus making SV_1^-, SV_2^- positive

$SV_1^- = -\hat{\beta}_2 EU_1^- + \hat{\beta}_6 VU_1^-$, $SV_2^- = -\hat{\beta}_4 EU_2^- + \hat{\beta}_8 VU_2^-$ (Methods 3.1.3, Supp. Fig. S19) and by

applying neural spike-rate analyses on z-scored $SV_1^+, SV_2^+, SV_1^-, SV_2^-$ (Supp. Fig. S20).

Discussion

This study shows that the accumulation of multi-trial tokens toward a final jackpot significantly

shapes trial-based decision-making, both behaviorally and at the neural level. The accumulation

of virtual tokens strongly influenced the accuracy and speed of subjects solving the task: choices

were faster and more accurate for higher ATC, particularly when jackpot achievement was more

likely. Logistic modeling confirmed a significant increase in the slope of the choice accuracy for

high ATC conditions, corroborating the idea of stronger engagement when jackpot proximity

increased. These effects coincided with a negative trend in errors when more tokens were

accumulated, and with a lower propensity for risk-taking whenever the cumulative jackpot

approached. Importantly, these results were also modulated by task difficulty, with easier trials

showing substantially fewer errors and risky choices.

To capture the mechanisms underlying these behavioral adjustments, we introduced three

alternative definitions of SV, combining trial-specific, value-based offer attributes EV and R and

ATC. We formalized the assessment of our findings by testing three alternative logistic choice

models for ATC integration and showed that offer evaluation is best modelled by a dynamically

adapted reference-dependent value 'RDV' that follows cumulative token accumulation. The RDV

model allows the decision contingencies to adapt from the comparison of offer values when it is

not possible to achieve jackpot, to the comparison of offer value to the jackpot threshold when

jackpot is can be achieved, i.e., to dynamically switch from value-based to goal-oriented task

solving strategies. Model comparisons revealed that RDV best explains behavior, suggesting that

decisions are best modelled as dynamic, reference-dependent processes tied to cumulative token

progress rather than trial-specific value differences alone, even when including relevant interaction

terms between offer values and ATC.

In addition to token-dependent behavioral effects, we also included model comparisons for temporal discounting models (Supp. Materials, Supp. Tables ST14-ST15, Supp. Figure S21). In temporal discounting, the SVs scale with time delay D to reward achievement, following an exponential factor e^{-kD}. In our formulation, we propose that temporal discounting relates to token accumulation through the exponent $kD \approx (6 - ATC)/\tau$ (Supp. Materials), with $\tau \approx 3.4$ (Supp. Table ST12), fit via maximum likelihood estimation. Inverting the above equation, we estimate effective time-discount rates of $k \approx 0.88$ Hz for $ATC = 0$, and ≈ 0.15 Hz for $ATC = 5$, comparable to reports from previous studies[49,50]. However, in line with works showing that conventional intertemporal choice tasks often overestimate discounting and may capture heuristic, reward-rate maximizing strategies rather than genuine devaluation of delayed outcomes[51,52], adding time-discounting terms to our models did not improve predictive performance beyond RDV. Crucially, the regression weight magnitudes for RDV coefficients remained stable across combined variants (Supp. Table ST12), indicating that RDV captures the substantial and behaviorally meaningful component of subjective decisions based on expected outcomes (gains/losses) observed across token accumulation (Supplementary Methods, Supp. Tables ST14-ST15, Supp. Fig. S21).

Overall, these findings extend previous work on token-based paradigms, where progressive, multi-trial reference effects did not previously emerge[43,45]. While our results align with previous behavioral theories for subjective preferences[1,53,54], our data demonstrate that reference-dependent dynamics strongly influence accuracy and response time at cumulative stages before jackpot attainment, with measurable effects on best choice discrimination accuracy and risk-taking attitude. The integration of positive or negative tokens as reinforcers refines the understanding of how virtual rewards and punishments modulate risk-taking and learning, aspects of investigation typically only studied at a coarser level[55,56].

At the neural level, we tracked the encoding of SVs defined by the three models that were used for behavioral choice assessment. Across all models, we found that the encoding of offer SV involved the most prominent portion of dACC cells during the respective offer presentation and gradually faded across subsequent task epochs. The first neural encoding model that we considered did not include ATC in the SV definition but included it as independent regressor. This showed that ATC is encoded by large fractions of cells in dACC, often beyond the extent of SV encoding fractions, especially outside offer presentation epochs. By correlating the neural encoding weights

for the EV and R differences and the AUC computed via ROC analyses for choice prediction, we

found that EV difference weights were most aligned in tuning with choices than other variables

considered. Crucially, this also revealed that, as expected, the encoding tuning of EV and R

differences variables is aligned to choices, whereas the encoding tuning of ATC is not aligned to

choices. The second neural encoding model that we considered included ATC interaction terms in

the definition of SVs. Comparing results to first model, we observed that including ATC in SVs

led to higher fractions of cells significantly encoding SVs at later task times, and that correlating

the encoding weights of EV and R differences to the AUC of choice predictions results in lower

alignment in encoding tuning when EV and R difference terms interact with ATC. This latter result

indicates that ATC interaction with EV and R does not provide choice-related tuning adjustment

at the neural level. By using a token-dependent reference, we introduced a third neural encoding

model that followed the 'RDV' choice model best explaining behavioral data that allowed us to

consider value-based variables as gains or losses based on their relationship with an ATC-

dependent reference. Notably, this revealed that significantly larger fractions of dACC cells

encode SVs resulting from gains. By analyzing the fractions of cells exclusively or synergistically

encoding gains- and/or losses-related variables, we found that that differently from gains, the

losses-related variables were not exclusively encoded by significant fractions of cells, but that they

were always encoded in synergy with gain-related variables. In addition, we found that the neural

encoding of EV in gains was robustly aligned to choices, whereas this was not the case in losses.

In contrast to behavioral insights suggesting that 'losses hurt more than gains', neural analyses

result indicate that dACC possibly follows a reference-dependent neural tuning that aligns value

encoding weights to choice mainly for gains, and less for losses. We further verified that adopting

a model combining reference-dependency with time-discounting yields a qualitative match to the

neural results (Supp. Fig. S22), supporting the evidence that reference-dependent valuation

provides an explanatory framework for both behavioral adjustments and dACC encoding in our

task.

Converging evidence suggests that expected rewards are updated by experience and estimated

in the frontal cortex and basal ganglia[57]. Our evidence that dACC encoding follows reference-

dependent principles aligns with previous theories by which dACC supports the selection and

maintenance of context-specific sequences of behavior directed toward delayed goals[58]. [5110] Our

results extend previous findings relating ACC signals to post-decisional variables related to gains

or losses [42,55,59], as well as to context-dependent attentional drive[60,61], elaborating on previous

interpretations about dACC not being directly involved in ongoing decisions but in outcome

evaluations[44]. Remarkably, we find that dACC recruits larger fractions of cells for RDV gains than

for losses, and that their encoding tuning aligns with upcoming choices, linking gains to reward

anticipation [16], and connecting to theories for distinct specialized circuitry for reward anticipation

and punishment across brain structures[62,63]. This may have notable implications, linking the

observed reduction in risk-taking and faster responses near jackpot completion to motivational

shifts possibly mediated by dopaminergic modulation[64]. This reinforcement learning perspective

suggests prioritization of rewards maximization[65–68], by enhancing of neural encoding for positive

expected outcomes.

Furthermore, the involvement of the dACC in token accumulation reinforcement is particularly

noteworthy. Previous research has implicated the dACC in cognitive control[7,69], conflict

monitoring[23–25], and value-based decision-making[12,14,26,29]. Our findings further support its role in

encoding the subjective value of outcomes in a dynamic, multi-trial context, adjusting its

representation as the likelihood of jackpot attainment increases. This suggests that dACC supports

ongoing monitoring of a probabilistic, history-dependent reference frame, an often overlooked

dimension of the putative functional role of value encoding in dACC. The dynamic influence of

tokens accumulation towards a jackpot reward provides a critical advancement for realistic

decision-making models that incorporate history-dependent value signals and reinforcement-

driven, reference-dependent shaping in reward probability[2–5,70,71].

In conclusion, this study underscores the importance of considering accumulated rewards in

decision-making frameworks. By showing how both behavior and dACC encoding adapt to

reference-dependent, multi-trial dynamics, we extend current understanding of the neural

computations supporting value-based and goal-directed behavior in environments where reward

attainability context unfolds over time.

Methods

1. Experimental settings and reproducibility

The data includes n = 227 behavioral sessions from two subjects (109 sessions, 433.28 ± 8.70 mean ± s.e.m. trials per session for subject 1, 118 sessions, 500.68 ± 10.97 trials for subject 2), of which n = 108 sessions (65 sessions, 479.16 ± 14.57 mean ± s.e.m. trials per session for subject 1, 43 sessions, 519.35 ± 14.62 trials for subject 2) include extracellular activity of dACC (Area 24) recorded using single electrodes (Frederick Haer & Co., impedance range 0.8 ± 4 MΩ), while monkeys performed the task. The electrode probes were lowered using a microdrive (NAN Instruments) until well-isolated activity was encountered. Data covered 1-3 simultaneous single neurons, Plexon system (Plexon, Inc.) was used to isolate the action potential waveforms. Cells are included based on quality of isolation but not on task–related response properties. Here we present neuronal data consisting of $n = 129$ single units (55 for subject 1 and 74 for subject 2). These data were published in the context of different research questions[39,40].

1.1 Experimental Procedures and Neural Recordings

All procedures were approved by the University Committee on Animal Resources at the University of Rochester and were designed and conducted in compliance with the Guide for the Care and Use of Animals of the Public Health Service's Guide for the Care and Use of Animals (protocol UCAR-2010-169). Two male macaques (*Macaca mulatta*; subject 1: age, 8 years, 11 months; subject 2: age, 10 years, 9 months) served as subjects. Recorded brain regions covered dACC, using single-contact probes. Data include 47228 behavioral trials (433.28 ± 8.70, mean ± sem across sessions) from subject 1 and 59080 (500.68 ± 10.97) from subject 2. Of these, 20604 (479.16 ± 14.57) from subject 1, and 33758 (519.35 ± 14.62) from subject 2 were simultaneous to dACC data recordings.

1.2 Behavioral Task

The token-based reward gambling task consists of the sequential presentation of two visual stimuli at the opposite sides of the screen, providing reward offers to be subsequently chosen by performing saccade to either target location (Fig. 1A)[21,38–40]. The task starts with a first offer presentation (*offer 1*, 600 ms), followed by a first delay time (*delay 1*, 150 ms), a second offer presentation (*offer 2*, 600 ms), respectively followed by a second delay time (*delay 2*, 150 ms). After fixating a central cross (*re-fixate*), for at least 100 ms, the choice can be reported upon *choice-go* cue onset, consisting of the simultaneous presentation of both offer stimuli previously presented. Choice is reported by fixation on target offer cue for at least 200 ms (*choice*). A successful choice selection fixation was followed by 750 ms delay period after which the gamble was resolved. Regardless of the outcome, within the next 300 ms a small juice reward (100 μL) was delivered to keep subjects engaged in the task. If, after the outcome resolution less than six tokens are collected, the trial ends. If six or more tokens are collected, after a 500 ms delay period a "jackpot" large liquid reward (300 μL) is delivered, the token count is reset, and the trial ends. Trials were separated by a random inter–trial interval ranging between 0.5 and 1.5 s. Circular indicators at the bottom of the screen report the token count through task time as empty circles, filled according to token count. The visual offer stimuli are split horizontally into top and bottom parts of different colors, with associated reward magnitude and probability. The height of the top/bottom part is informative of the associated reward probability, while the color is informative of the magnitude. Thanks to the split, the probability of the outcomes color-cued by the top and bottom parts of the stimuli is always complementary. The probabilities are discretized as

592   10%, 30%, 50%, 70% and 90%, the magnitudes consist of reward counts
593   ($-2, -1, 0, +1, +2, +3$ tokens) including negative values. In addition, offers include safe options
594   where 0 (red) or 1 (blue) token are achieved with 100% probability. Each gamble includes at least
595   one positive or zero outcome. This allows a less trivial level of choice computation and keeps the
596   subjects motivated throughout behavioral execution.
597
2. Behavioral Data Analyses
We analyzed behavioral data at multiple levels. First, we assessed the factors that influenced the
subjects' choices. The visual offers cued at magnitude v and probability p of the top (t) and bottom
(b) parts of the offers, e.g., in Fig. 1A we show a sample configuration where the left offer is of
$v^t = +3$ tokens, and $v^b = -2$ tokens, while the right offer has $v^t = +1$ tokens, $v^b = -1$ tokens.
We defined the expected value as: $EV = p^t v^t + p^b v^b$, where p^t and $p^b = 1 - p^t$ are indicated
by the height fraction of the top or bottom offer segments respectively. Similarly, we defined the
risk associated with the offers as: $R = p^t(v^t - EV)^2 + (1 - p^t)(v^b - EV)^2$. In behavioral data
analyses, we stratified the analyses in ranges of accumulated tokens: 'Low', 'Medium', 'High, and
in levels of difficulty in detecting the offer with best EV: 'Easy' and 'Hard'. As accumulated tokens
count ranges, we use 'Low' $ATC = [0, 1]$, 'Medium' $ATC = [2, 3]$, and 'High' $ATC = [4, 5]$
(Supp. Table ST1).We defined difficulty as inversely related to the absolute EV difference $\Delta_{EV} =$
$|EV_1 - EV_2|$, i.e., larger Δ_{EV} indicate lower difficulty. We used the median value of Δ_{EV},
$median(\Delta_{EV}) = 1$ as discriminant for 'Easy' ($\Delta_{EV} \geq 1$) and 'Hard' ($\Delta_{EV} < 1$) trials (Supp. Table
ST2).
613
2.1 Generalized linear model of choice
To assess the choice performance, in Fig. 2A we used a logistic model for the 'correct choice' CC,
defined as choice for the offer with best EV. In symbols, $CC = 1$ if choice is for offer 1 when
$EV_1 > EV_2$, and for offer 2 when $EV_2 > EV_1$; $CC = 0$ in all other cases. The logistic model
assumes a logistic relationship between the correct choice CC and the above variables: $\text{logit}(CC) =$
$\beta_0 + \beta_1 \Delta_{EV} + \beta_2 M_{EV} + \beta_3 ORL + \beta_4 ATC + \beta_5 TSLR + \beta_6 OPT + \beta_7 JPT$. We considered as
regressors: the absolute EV difference between the two offers (Δ_{EV}); the 'Mean expected value'
as the average EV in each trial: $M_{EV} = (EV_1 + EV_2)/2$; the 'Offer Risk Level' $ORL = R_{Best} -$
R_{Worst} where R_{Best} or R_{Worst} indicates the risk associated to the offer with best or worst EV,
respectively; the 'Accumulated Tokens Count' ATC, i.e., the token count at the start of the trial;
the 'Trials Since Last Reward' $TSLR$ that is, the count, in number of trials, since last jackpot
reward; the 'Outcome of Previous Trial' OPT, that is the number of tokens achieved in previous
trial; and the 'Jackpot on Previous Trial' JPT, a binary variable $= 1$ if previous trial ended with
jackpot, $= 0$ otherwise. Due to using previous trial variables, the first trial in each session was
removed in this analysis ($n = 47030$ total trials in subject 1, $n = 58911$ total trials in subject 2).
Prior to least squares estimation of the weights $\beta_{i=[0,7]}$, the regressed variables are normalized to
their absolute maximum value so that ($\Delta_{EV}, ATC, TSLR, JPT$) are in the range [0, 1], and
(M_{EV}, ORL, OPT) are in the rage [-1, 1], and assessed for significance via two-tailed F-Statistics
tests.

2.2 Behavioral choice accuracy and execution time

In Fig. 2B we compute the fraction of trials with correct choice (i.e., choice for the offer with best EV) for '*No Jackpot*' (JPT $= 0$) or '*Jackpot*' (JPT $= 1$) on previous trial, for 'Low' $ATC = [0, 1]$, 'Medium' $ATC = [2, 3]$, and 'High' $ATC = [4, 5]$ accumulated tokens count (Supp. Table ST1). The same conditions are used in Fig. 2C to analyze the fraction of errors (i.e., trials where the subjects did not choose the offer with best EV), as well as for binned levels of Δ_{EV}, inversely related to the difficulty in detecting the best offer (Supp. Table ST2). Finally, in Fig. 2D we show the logistic relationship between expected value difference $EV_1 - EV_2$ and the choice $\text{logit}(p(ch = 1)) = \beta_0 + beta_1(EV_1 - EV_2)$ for 'Low' and 'High' accumulated tokens count ($ATC = [0,1]$ or $ATC = [4,5]$ respectively). We assess the difference in β_0, β_1 for low and high ATC in Fig. 2E.

2.3 Risk propension

The Markowitz risk return model is defined via the weights of the logistic regression of offer choice ($ch1 = 1$ for first offer choice, 0 otherwise) as $\text{logit}(ch1) = \beta_0 + \beta_1(EV_1 - EV_2) + \beta_2(R_1 - R_2)$. The subject's utility for the i^{th} offer is modelled as a trade-off between EV and risk, defined as $U_i = EV_i - \theta R_i$. The model parameter $\theta = -\beta_2/\beta_1$, describes the behavioral attitude as risk aversion ($\theta > 0$) or risk seeking ($\theta < 0$).

2.4 Choice models and Subjective Values

The definition of Subjective Value (SV) followed the assessment of alternative models of choice prediction, including task variables such as value of the top and bottom part of the offers (v^t, v^b), expected values (EV_1, EV_2), risks (R_1, R_2) and ATC. We considered three alternatives:'linear model of choice without ATC interaction', 'linear model of choice with ATC interaction', and a 'reference-dependent model of choice'.

2.4.1 Linear model of choice without ATC interaction

We define a linear model the choice as:

$$\text{logit}(p(ch1)) = \beta_0 + \beta_1(EV_1 - EV_2) + \beta_2(R_1 - R_2) + \beta_3 ATC, \tag{1}$$

with $ch1 = 1$ indicating choice for the first offer, $ch1 = 0$ for the second offer. The model includes separate terms for EV, R, and ATC. The model weights $\widehat{\Theta} = [\hat{\beta}_0, \hat{\beta}_1, \hat{\beta}_2, \hat{\beta}_3]$ are estimated via ordinary least squares regression, i.e., by minimizing the negative log-likelihood of the predicted variable

$$\hat{p}_i = 1/(1 + \exp(\hat{\beta}_0 + \hat{\beta}_1(EV_{1,i} - EV_{2,i}) + \hat{\beta}_2(R_{1,i} - R_{2,i}) + \hat{\beta}_3 ATC_i), \tag{2}$$

for test data $y_i = 1$ if first option is chosen, 0 otherwise. We use $k = 4$ fold cross-validation to estimate parameters over train subsets and test predictions using estimated parameters over test subsets. We apply a Ridge penalty to the negative log-likelihood, i.e., we minimize

$$-\log L(\widehat{\Theta}|y_i) = -\Sigma_i[y_i \log \hat{p}_i + (1 - y_i)\log(1 - \hat{p}_i)] + \lambda_{ridge}|\widehat{\Theta}_{ridge}|^2 \tag{3}$$

with $\lambda_{ridge} = 0.1$ and $\widehat{\Theta}_{ridge} = [\hat{\beta}_1, \hat{\beta}_2, \hat{\beta}_3]$.

677 Following this model of choice, we define subjective values as:

$$SV_{1,i} = \hat{\beta}_1 EV_{1,i} + \hat{\beta}_2 R_{1,i},$$
$$SV_{2,i} = \hat{\beta}_1 EV_{2,i} + \hat{\beta}_2 R_{1,i}.$$

$$(4)$$

We include an ATC term in this logistic model for two main reasons. First, it allows us to explicitly
isolate the contribution of ATC without conflating its effect with offer EV and R. Second, it
controls for potential ATC-related variability that could otherwise bias the estimation of β_1 and β_2
, ensuring that EV and R related weights remain interpretable. While this model does not include
interaction terms between ATC and the other predictors, the estimated effect of ATC was very
weak ($\hat{\beta}_3$ subject 1: 0.03 ± 0.01; subject 2: 0.01 ± 0.01, Supp. Fig S2, Supp. Table ST7).
685

686 **2.4.2 Linear model of choice with ATC interaction**
687 We extend the linear model of the choice to include ATC interaction terms:

$$\text{logit}(p(ch1)) = \beta_0 + \beta_1(EV_1 - EV_2) + \beta_2(EV_1 - EV_2)ATC + \beta_3(R_1 - R_2)$$
$$+ \beta_4(R_1 - R_2)ATC + \beta_5(R_1 - R_2)ATC^2,$$

$$(5)$$

688 combining a linear interaction for EV with linear and quadratic interaction terms for R. This design
689 was inspired by results in Fig. 4 and Supp. Fig. S1, showing linear increase in EV with ATC, and
690 inverted-u relation between R and ATC.

691 Also in this case, we estimate the model weights $\hat{\Theta} = [\hat{\beta}_0, \hat{\beta}_1, \hat{\beta}_2, \hat{\beta}_3, \hat{\beta}_4, \hat{\beta}_5]$ via ordinary least
692 squares regression, i.e., by minimizing the negative log-likelihood of the predicted variable

$$\hat{p}_i = 1/(1 + \exp(\hat{\beta}_0 + \hat{\beta}_1(EV_{1,i} - EV_{2,i}) + \hat{\beta}_2(EV_{1,i} - EV_{2,i})ATC_i + \hat{\beta}_3(R_{1,i} - R_{2,i})$$
$$+ \hat{\beta}_4(R_{1,i} - R_{2,i})ATC_i + \hat{\beta}_5(R_{1,i} - R_{2,i})ATC_i^2)).$$

$$(6)$$

693 We use $k = 4$ fold cross-validation and Ridge penalty with $\lambda_{ridge} = 0.1$ and $\hat{\Theta}_{ridge} =$
694 $[\hat{\beta}_1, \hat{\beta}_2, \hat{\beta}_3, \hat{\beta}_4, \hat{\beta}_5]$. Following this model of choice, we define subjective values as:

$$SV_{1,i} = \hat{\beta}_1 EV_{1,i} + \hat{\beta}_2 EV_{1,i} \cdot ATC_i + \hat{\beta}_3 R_{1,i} + \hat{\beta}_4 R_{1,i} \cdot ATC_i + \hat{\beta}_5 R_{1,i} \cdot ATC_i^2,$$
$$SV_{2,i} = \hat{\beta}_1 EV_{2,i} + \hat{\beta}_2 EV_{2,i} \cdot ATC_i + \hat{\beta}_3 R_{1,i} + \hat{\beta}_4 R_{2,i} \cdot ATC_i + \hat{\beta}_5 R_{2,i} \cdot ATC_i^2.$$

$$(7)$$

696 **2.4.3 Reference-dependent value (RDV) model of choice**
697 We define a reference-dependent value 'RDV' model based on Prospect Theory principles. This
698 model design relies on a token-based reference-dependent utility function for offer values
699 v_1^t, v_1^b, v_2^t, and $v_2^b \in [-2, +3]$:

$$u(v, ATC) = \begin{cases} (v - r(ATC))^{\gamma(ATC)} & \text{if } v \geq r(ATC) \text{ (gains)} \\ -\lambda(ATC)(r(ATC) - v)^{\gamma(ATC)} & \text{if } v < r(ATC) \text{ (losses)} \end{cases}.$$

$$(8)$$

702   Here, the reference point $r(ATC)$ is token-dependent and defined as:

$$r(ATC) = \frac{6 - ATC}{1 + e^{-\kappa_0(ATC - \kappa_1)}}. \tag{9}$$

The $r(ATC)$ function tends toward $6 - ATC$ when $ATC \geq \kappa_1$, and toward 0 for $ATC < \kappa_1$. The
formulation is grounded in the intuition that subjects consider offered values as potential "gains"
or "losses" relative to a "missing tokens to jackpot" threshold $(6 - ATC)$ when jackpot is
achievable, or they consider offer values relative to zero when jackpot is not achievable. In our
data, κ_1 is numerically fit to data in each subject: 3.29±0.05 in subject 1, 3.08±0.06 in subject 2
(mean ± s.e.m). These values are consistent with using $6 - ATC$ as reference when jackpot is
reachable (i.e., $ATC \geq 3$, for $v \in [-2, +3]$ allows $ATC + v \geq 6$), and 0 when ATC jackpot is not
reachable $(ATC < 3)$.

The utility function $u(v, ATC)$ transforms the reference-dependent value $|v - r(ATC)|$ via a gain-
sensitive parameter $\gamma(ATC) = \gamma_0 + \gamma_1 ATC$, increasing the steepness of the value-to-choice
mapping in the gain domain. Losses are penalized by scaling factor $\lambda(ATC) = \lambda_0 + \lambda_1 ATC +$
$\lambda_2 ATC^2$, with $\lambda_0, \lambda_1, \lambda_2$ reflecting the Prospect Theory asymmetry principle by which "losses hurt
more than gains". The quadratic penalty also captures the inverted-U pattern in risk-taking (Fig. 4
and Supp. Fig. S1), as losses correspond with riskiest choices in our task.
718
719   Finally, the reference-dependent utilities are used in a logistic regression predicting choice:

$$\begin{aligned}\text{logit}(p(ch1)) = \beta_0 &+ \beta_1\big(\mathbb{E}[u(v_{1,}, ATC)] - \mathbb{E}[u(v_{2,}, ATC)]\big) \\ &+ \beta_2\big(VAR[u(v_{1,}, ATC)] - VAR[u(v_{2,}, ATC)]\big).\end{aligned} \tag{10}$$

721   Regression was performed via ordinary least squares, using

$$\begin{aligned}\mathbb{E}[u(v_i, ATC)] &= u(v_i^t, ATC)p_i^t + u(v_i^b, ATC)(1 - p_i^t), \\ VAR[u(v_i, ATC) &= (u(v_i^t, ATC) - \mathbb{E}[u(v_i, ATC)])^2 p_i^t \\ &\quad + (u(v_i^b, ATC) - \mathbb{E}[u(v_i, ATC)])^2(1 - p_i^t).\end{aligned} \tag{11}$$

723   We use $k = 4$ cross-validation folds, and apply Ridge penalty to the negative log likelihood
724    $L(\widehat{\Theta}|y_i)$ as in the linear model, estimate $\widehat{\Theta} = [\hat{\kappa}_0, \hat{\kappa}_1, \hat{\gamma}_0, \hat{\gamma}_1, \hat{\lambda}_0, \hat{\lambda}_1, \hat{\lambda}_2, \hat{\beta}_0, \hat{\beta}_1, \hat{\beta}_2]$, with $\lambda_{ridge} =$
725   0.1, $\widehat{\Theta}_{ridge} = [\hat{\beta}_1, \hat{\beta}_2]$, and

$$\begin{aligned}\hat{p}_i = 1 / \Big(1 + \exp\Big(&-\big(\hat{\beta}_0 + \hat{\beta}_1\big(\mathbb{E}[\hat{u}(v_{1,i}, ATC_i)] - \mathbb{E}[\hat{u}(v_{2,i}, ATC_i)]\big) \\ &+ \hat{\beta}_2\big(VAR[\hat{u}(v_{1,i}, ATC_i)] - VAR[\hat{u}(v_{2,i}, ATC_i)]\big)\big)\Big)\Big),\end{aligned} \tag{12}$$

727   where $\hat{u}(v, ATC) = (v - \hat{r}(ATC))^{\hat{\gamma}_0 + \hat{\gamma}_1 ATC}$ if $v \geq \hat{r}(ATC)$ and $\hat{u}(v, ATC) = -(\hat{\lambda}_0 + \hat{\lambda}_1 ATC +$
728    $\hat{\lambda}_2 ATC^2)(\hat{r}(ATC) - v)^{\hat{\gamma}_0 + \hat{\gamma}_1 ATC}$ if $v < \hat{r}(ATC)$, with $\hat{r}(ATC) = (6 - ATC)/(1 +$
729    $e^{-\hat{\kappa}_0(ATC - \hat{\kappa}_1)})$.

731 In the RDV model, we define Subjective Values (SV) as:

$$SV_{1,i} = \hat{\beta}_1 \mathbb{E}\big[\hat{u}\big(v_{1,i}, ATC_i\big)\big] + \hat{\beta}_2 VAR\big[\hat{u}\big(v_{1,i}, ATC_i\big)\big],$$
$$SV_{2,i} = \hat{\beta}_1 \mathbb{E}\big[\hat{u}\big(v_{2,i}, ATC_i\big)\big] + \hat{\beta}_2 VAR\big[\hat{u}\big(v_{2,i}, ATC_i\big)\big].$$

(13)

732 The SVs are computed estimating $\widehat{\Theta} = [\hat{\kappa}_0, \hat{\kappa}_1, \hat{\gamma}_0, \hat{\gamma}_1, \hat{\lambda}_0, \hat{\lambda}_1, \hat{\lambda}_2, \hat{\beta}_0, \hat{\beta}_1, \hat{\beta}_2]$ on train data and
733 $[v_{1,i}^t, v_{1,i}^b, p_{1,i}^t, v_{2,i}^t, v_{2,i}^b, p_{2,i}^t, ATC_i]$ from the i^{th} test trial, using $k = 4$ cross-validation folds.

735 3. Neural data analyses

We analyzed the spiking activity of neurons in dACC to compute the fraction of cells that show
significant encoding of the SV. Following the SV computation (Methods 2.4), we run a time-
resolved analysis of the spike rate $\eta_i(t)$ of i^{th} trial at time t in 200 ms boxcar time windows,
sliding at 10 ms offset bins during task time. We used a linear model of the spike rate, and tracked
the fraction of cells showing significant encoding of the two SVs. The significance of SV
interaction slope is assessed to be different from zero via two-tailed F-statistics tests on the sum
of squared errors (SSE) of the full model $SSE^F = \sum_{i=1}^n |\eta_i - (\beta_0 + \hat{\beta}_1 SV_{1,i} + \{...\})|^2$, and of the
reduced model $SSE_{j=1,2}^R = \sum_{i=1}^n |\eta_i - (\beta_0 + \{...\})|^2$, including only $\hat{\beta}_2$ and other eventual
regressors (indicated here with $\{...\}$) for the assessment of $\hat{\beta}_1$, and, respectively, only $\hat{\beta}_1$ and other
eventual regressors for the assessment of $\hat{\beta}_2$. The F-value for $\beta_{j=1,2}(t)$ is defined as $F_{j=1,2}^* = $
$\big((SSE_j^R - SSE^F)/1\big)/\big(SSE^F/(n-2)\big)$, with n being the number of trials observations. The p-
values are computed by comparing empirical F-values with the F-distribution. The significance
of the fractions of cells showing significant encoding is further assessed via the comparison of the
significant fractions of cells with surrogate results run over $n = 1000$ trial order randomizations,
independently generated across variables. Lastly, consecutive runs of significant bins are assessed
in length via run-length, cluster-based significance tests[20].

754 3.1. Spike-rate models for the encoding of value in the dACC

We investigated three models of the spike-rate derived from choice prediction frameworks outlined in
Methods 2.4. The first model consisted of a linear combination of EV and risk variables alongside ATC,
which we include to assess the neural encoding of such variable independently of its interactions with value-
based parameters, as by the 'choice model without ATC interactions' introduced in Methods 2.4.1. The
second model extended the linear approach by introducing interaction terms between ATC and value
variables as by the 'choice prediction model with ATC interactions' detailed in Methods 2.4.2. The third
model adopted a reference-dependent definition of value-based parameters, consistent with the 'RDV
model of the choice' described in Methods 2.4.3.

764 3.1.1 Linear spike-rate model without ATC interactions

To dissect the respective contribution of EV, R, and ATC, we defined a model of subjective value starting
with a simplified linear model of choice, considering SV as a weighted sum of EV and R, and regressing
the two SVs in a spike model with SV_1, SV_2 and ATC as in the 'linear model of the choice without ATC
interactions' (Methods 2.4.1). To ensure independence between the estimation of SV value rates and the

neural rate regression, trials were split into two disjoint subsets S1 and S2. First, we used S1 trials to

compute SV weights via a logistic fit of the choice $\mathrm{logit}(ch^{(S1)} = 1) = \beta_0 + \beta_1 EV_1^{(S1)} + \beta_2 EV_2^{(S1)} +$

$\beta_3 R_1^{(S1)} + \beta_4 R_2^{(S1)} + \beta_5 ATC^{(S1)}$. Then, weights $\beta_{i=0,\ldots,5}^{(S1)}$, are combined with S2 data to define $SV_1^{(S2)} =$

$\hat{\beta}_1^{(S1)} EV_1^{(S2)} + \hat{\beta}_3^{(S1)} R_1^{(S2)}$, and $SV_2^{(S2)} = \hat{\beta}_2^{(S1)} EV_2^{(S2)} + \hat{\beta}_4^{(S1)} R_2^{(S2)}$. Following SV computation on S2 trial

data, the subsets S1 and S2 are swapped, to compute SVs on S1, $SV_1^{(S1)}, SV_2^{(S1)}$. This procedure allows

cross-validation by which choice-relevant SV weights are computed on a first subset, then combined with

independent EV, R and ATC from a second, disjoint subset. Finally, SVs from the two disjoint subsets are

pooled together in the set S and regressed against spiking data. The $SV_1^{(S)}, SV_2^{(S)}$ are regressed with rate

model $\eta_i^{(S)}(t) = \beta_0'(t) + \beta_1'(t) SV_1^{(S)} + \beta_2'(t) SV_2^{(S)} + \beta_3'(t) ATC^{(S)}$, for the i^{th} cell, and time bin t.

3.1.2 Linear spike-rate model with ATC interactions

We consider a spike-rate model where EV and R interact with the variable ATC as in the 'linear model of

the choice with ATC interactions' (Methods 2.4.2). We split trials into two disjoint subsets S1 and S2 as in

the 'linear spike-rate model without ATC interactions' (Methods 3.1.1). In this case the SV weights are

computed via logistic fit of the choice model $\mathrm{logit}(ch^{(S1)} = 1) = \beta_0 + \beta_1 EV_1^{(S1)} + \beta_2 EV_2^{(S1)} +$

$\beta_3 EV_1^{(S1)} ATC^{(S1)} + \beta_4 EV_2^{(S1)} + \beta_5 R_1^{(S1)} + \beta_6 R_2^{(S1)} + \beta_7 R_1^{(S1)} ATC^{(S1)} + \beta_8 R_2^{(S1)} ATC^{(S1)} +$

$\beta_9 R_1^{(S1)} (ATC^{(S1)})^2 + \beta_{10} R_2^{(S1)} (ATC^{(S1)})^2$. We estimate the parameters $\beta_{i=0,\ldots,10}^{(S1)}$, and define $SV_1^{(S2)} =$

$\hat{\beta}_1^{(S1)} EV_1^{(S2)} + \hat{\beta}_3^{(S1)} EV_1^{(S2)} ATC^{(S2)} + \hat{\beta}_5^{(S1)} R_1^{(S2)} + \hat{\beta}_7^{(S1)} R_1^{(S2)} ATC^{(S2)} + \hat{\beta}_9^{(S1)} R_1^{(S2)} (ATC^{(S2)})^2$,

$SV_2^{(S2)} = \hat{\beta}_2^{(S1)} EV_2^{(S2)} + \hat{\beta}_4^{(S1)} EV_2^{(S2)} ATC^{(S2)} + \hat{\beta}_6^{(S1)} R_2^{(S2)} + \hat{\beta}_8^{(S1)} R_2^{(S2)} ATC^{(S2)} +$

$\hat{\beta}_{10}^{(S1)} R_2^{(S2)} (ATC^{(S2)})^2$. The subsets S1 and S2 are swapped to compute $SV_1^{(S1)}, SV_2^{(S1)}$. The SVs are then

pooled in the set S as $SV_1^{(S)}, SV_2^{(S)}$ and regressed using the rate model $\eta_i^{(S)}(t) = \beta_0'(t) + \beta_1'(t) SV_1^{(S)} +$

$\beta_2'(t) SV_2^{(S)}$, for the i^{th} cell, and time bin t.

3.1.3 RDV spike-rate model

We use reference-dependent SVs to define RDV spike-rates models following methods in 'Reference-

dependent model of the choice' (Methods 2.4.3). Prior to computing the SV weights, we compute the

factors $\hat{u}(v_i^t, ATC)^+, \hat{u}(v_i^t, ATC)^-, \hat{u}(v_i^b, ATC)^+, \hat{u}(v_i^b, ATC)^-$, for both first and second offer $i = 1,2$,

separating gains (+) from losses (-). Although offer values v_i^t, v_i^b are anti-correlated by task design ($\rho =$

$-0.74, p < 0.001$ for both first and second offer), gains and losses could vary in top/bottom parts (t, b) of

the offers. We define the gains Expected Utility

$$EU_i^+ = \begin{cases} \mathbb{E}[\hat{u}(v_i^t, ATC)] & \text{if } t \text{ is gain} \\ \mathbb{E}[\hat{u}(v_i^b, ATC)] & \text{if } b \text{ is gain} \\ \mathbb{E}[\hat{u}(v_i^t, ATC)] + \mathbb{E}[\hat{u}(v_i^b, ATC)], & \text{if both are gains} \\ 0, & \text{if none is gain} \end{cases}, i = 1,2. \qquad (14)$$

799 The same definition applies to losses Expected Utility $EU_i^-, i = 1,2$, and to the respective VAR utility

800 $VU_i^+, VU_i^-, i = 1,2$. The SV weights are computed via logistic fit of the choice model $\mathrm{logit}(ch^{(S1)} = 1) =$

801     $\beta_0 + \beta_1 EU_1^+ + \beta_2 EU_1^- + \beta_3 EU_2^+ + \beta_4 EU_2^- + \beta_5 VU_1^+ + \beta_6 VU_1^- + \beta_7 VU_2^+ + \beta_8 VU_2^-$, by estimating the

802     $\widehat{\Theta} = \left[\hat{\kappa}_0, \hat{\kappa}_1, \hat{\gamma}_0, \hat{\gamma}_1, \hat{\lambda}_0, \hat{\lambda}_1, \hat{\lambda}_2, \widehat{\beta}_{0,\dots,8}\right]^{(S1)}$ (Methods 2.4.3), and defining:

$$
\begin{aligned}
SV_1^{+\,(S2)} &= \hat{\beta}_1^{(S1)} EU_1^{+\,(S2)} + \hat{\beta}_5^{(S1)} VU_1^{+\,(S2)}, \\
SV_1^{-\,(S2)} &= \hat{\beta}_2^{(S1)} EU_1^{-\,(S2)} + \hat{\beta}_6^{(S1)} VU_1^{-\,(S2)}, \\
SV_2^{+\,(S2)} &= \hat{\beta}_3^{(S1)} EU_2^{+\,(S2)} + \hat{\beta}_7^{(S1)} VU_2^{+\,(S2)}, \\
SV_2^{-\,(S2)} &= \hat{\beta}_4^{(S1)} EU_2^{-\,(S2)} + \hat{\beta}_8^{(S1)} VU_2^{-\,(S2)}.
\end{aligned}
\tag{15}
$$

803   Following SV computation on S2, we swap S1 and S2 to compute $SV_1^{+\,(S1)}$, $SV_1^{-\,(S1)}$, $SV_2^{+\,(S1)}$, $SV_2^{-\,(S1)}$.

804   The SVs from the two subsets are pooled in the set S and regressed separately for gains and losses as

805     $\eta_i^{(S)}(t) = \beta_0'(t) + \beta_1'(t)SV_1^{+\,(S)} + \beta_3'(t)SV_2^{+\,(S)}$ for   gains,   and $\eta_i^{(S)}(t) = \beta_0'(t) + \beta_2'(t)SV_1^{-\,(S)} +$

806     $\beta_4'(t)SV_2^{-\,(S)}$ for losses, for the i^{th} cell, and time bin t.

3.2 Receiver Operating Characteristics analysis on spike-rate models choice predictions

809   We refined the study of spike-rate models to study their relationship with the choice, correlating choice

810   predicted using the spike-rate weights (β' in the respective models) in a Receiver Operating Characteristics

811   (ROC) analysis, estimating the Area Under the Curve (AUC) Importantly, this analysis allowed to detect

812   behavioral readout[72] from neural signals.

3.2.1 ROC analysis in the linear spike-rate model without ATC interaction

814   First, we compute the weights $\hat{\beta}'_{i=0,\dots,3}$ using trials in the subset S1 (Methods 3.1.1) in the model $\eta_i^{(S1)}(t) =$

815     $\beta_0'(t) + \beta_1'^{(S1)}(t)(EV_1^{(S1)} - EV_2^{(S1)}) + \beta_2'^{(S1)}(t)(R_1^{(S1)} - R_2^{(S1)}) + \beta_3'^{(S1)}(t)ATC^{(S)}$.   We   compute

816   predictive variables

$$
\begin{aligned}
p_1^{(S2)}(t) &= \beta_1'^{\,(S1)}(t)(EV_1^{(S2)} - EV_2^{(S2)}), \\
p_2^{(S2)}(t) &= \beta_2'^{\,(S1)}(t)(R_1^{(S2)} - R_2^{(S2)}), \\
p_3^{(S2)}(t) &= \beta_3'^{\,(S1)}(t)ATC^{(S2)},
\end{aligned}
\tag{16}
$$

We predict the choice by sorting the variable $p_{i=1,2,3}^{(S2)}(t)$, and sweeping a threshold assuming all possible

values of $p_{i=1,2,3}^{(S2)}(t)$. At each threshold value, we compute the true positive rate (TPR) and false positive

rate (FPR) comparing the prediction variable the choice variable $ch^{(S2)}$, and constructing the ROC curve

by tracing FPR versus TPR. The $AUC_{i=1,2,3}^{(S2)}(t)$ for the respective $p_{i=1,2,3}^{(S2)}(t)$ is computed as the discrete

integral of the ROC curve. Lastly, we correlate the $\langle AUC_{i=1,2,3}^{(S2)}(t)\rangle$ and $\langle \beta_{i=1,2,3}'^{\,(S1)}(t)\rangle$ using Pearson's

correlation, $\langle \cdot \rangle$ is the time- average across time bins posterior to offer 2 presentation and up to the end of

the trial. We only used time-averages posterior to offer 2 onset time to consider time bins where subjects

had access to second offer information, thus EV and R difference could be possibly encoded at the neural

level.

3.2.2 ROC analysis in the linear spike-rate model with ATC interaction

In this case we compute predictive variables based on the ATC interaction model (Methods 3.1.2)

$$
\begin{aligned}
p_1^{(S2)}(t) &= \beta_1'^{(S1)}(t)(EV_1^{(S2)} - EV_2^{(S2)}), \\
p_2^{(S2)}(t) &= \beta_2'^{(S1)}(t)(EV_1^{(S2)} - EV_2^{(S2)})ATC^{(S2)}, \\
p_3^{(S2)}(t) &= \beta_3'^{(S1)}(t)(R_1^{(S2)} - R_2^{(S2)}), \\
p_4^{(S2)}(t) &= \beta_4'^{(S1)}(t)(R_1^{(S2)} - R_2^{(S2)})ATC^{(S2)}, \\
p_5^{(S2)}(t) &= \beta_5'^{(S1)}(t)(R_1^{(S2)} - R_2^{(S2)})(ATC^{(S2)})^2.
\end{aligned}
\tag{17}
$$

829 As in 3.2.1, $p_{i=1,\dots,5}^{(S2)}(t)$ is a predictor of choice $ch^{(S2)}$ used to compute $\langle AUC_{i=1,\dots,5}^{(S2)}(t)\rangle$ and we correlate it
830 to $\langle \beta_{i=1,\dots,5}'^{(S1)}(t)\rangle$.

831 **3.2.3 ROC analysis in the RDV spike-rate model**
832
833 In this case, since the model needs to compute parameter estimates $\widehat{\Theta}$ (Methods 3.1.3), we split the trials
834 into three separate subsets. We estimate parameters $\widehat{\Theta}$ on a first subset S1, and use them to define
835 $EU_1^{+\,(S2)}, EU_1^{-\,(S2)}, EU_2^{+\,(S2)}, EU_2^{-\,(S2)}, VU_1^{+\,(S2)}, VU_1^{-\,(S2)}, VU_2^{+\,(S2)}, VU_2^{-\,(S2)}$ on a second subset S2. We
836 fit the spike-rate

$$
\begin{aligned}
\eta_i^{(S2)}(t) &= \beta_0'^{(S1)}(t) + \beta_1'^{(S1)}(t)(EV_1^{+\,(S2)} - EV_2^{+\,(S2)}) + \beta_2'^{(S1)}(t)(EV_1^{-\,(S2)} - EV_2^{-\,(S2)}) \\
&\quad + \beta_3'^{(S1)}(t)(VU_1^{+\,(S2)} - VU_2^{+\,(S2)}) + \beta_4'^{(S1)}(t)(VU_1^{-\,(S2)} - VU_2^{-(S2)})
\end{aligned}
\tag{18}
$$

837 and compute:

$$
\begin{aligned}
p_1^{(S3)}(t) &= \beta_1'^{(S2)}(t)(EU_1^{+\,(S3)} - EU_2^{+\,(S3)}), \\
p_2^{(S3)}(t) &= \beta_2'^{(S2)}(t)(EU_1^{-\,(S3)} - EU_2^{-\,(S3)}), \\
p_3^{(S3)}(t) &= \beta_3'^{(S2)}(t)(VU_1^{+\,(S3)} - VU_2^{+\,(S3)}), \\
p_4^{(S3)}(t) &= \beta_4'^{(S2)}(t)(VU_1^{-\,(S3)} - VU_2^{-\,(S3)}),
\end{aligned}
\tag{19}
$$

838 to predict the choice variable $ch^{(S3)}$. Based on choice predictions $p_{i=1,\dots,4}^{(S3)}(t)$, we compute the
839 $\langle AUC_{i=1,\dots,4}^{(S3)}(t)\rangle$ as in 3.2.1 and correlate it to $\langle \beta_{i=1,\dots,4}'^{(S2)}(t)\rangle$.

Data availability

Data used in this study is available at the DOI: <u>10.12751/g-node.1kkrw6</u>.

Code availability

Code developed for the presented analyses is available at the DOI: <u>10.12751/g-node.1kkrw6</u>.

References

1. Kahneman, D. & Tversky, A. *Prospect Theory: An Analysis of Decision under Risk*. vol. 47 https://about.jstor.org/terms (1979).

859
860

2. Anke Braun, X., Urai, A. E., Tobias, X. & Donner, H. Adaptive History Biases Result from Confidence-Weighted Accumulation of past Choices. *Journal of Neuroscience* **38**, (2018).

861
862
863

3. Nogueira, R. *et al.* Lateral orbitofrontal cortex anticipates choices and integrates prior with current information. *Nat Commun* **8**, (2017).

864
865

4. Mochol, G., Kiani, R. & Moreno-Bote, R. Prefrontal cortex represents heuristics that shape choice bias and its integration into future behavior. *Current Biology* **31**, 1234-1244.e6 (2021).

866
867
868

5. Hermoso-Mendizabal, A. *et al.* Response outcomes gate the impact of expectations on perceptual decisions. *Nat Commun* **11**, (2020).

869
870

6. Bartra, O., McGuire, J. T. & Kable, J. W. The valuation system: A coordinate-based meta-analysis of BOLD fMRI experiments examining neural correlates of subjective value. *Neuroimage* **76**, 412–427 (2013).

871
872
873

7. Ebitz, R. B. & Hayden, B. Y. Dorsal anterior cingulate: A Rorschach test for cognitive neuroscience. *Nature Neuroscience* vol. 19 1278–1279 Preprint at https://doi.org/10.1038/nn.4387 (2016).

874
875
876

8. Haber, S. N. & Behrens, T. E. J. The Neural Network Underlying Incentive-Based Learning: Implications for Interpreting Circuit Disruptions in Psychiatric Disorders. *Neuron* vol. 83 1019–1039 Preprint at https://doi.org/10.1016/j.neuron.2014.08.031 (2014).

877
878
879
880

9. Heilbronner, S. R. & Hayden, B. Y. Dorsal Anterior Cingulate Cortex: A Bottom-Up View. *Annu Rev Neurosci* **39**, 149–170 (2016).

881
882

10. Kable, J. W. & Glimcher, P. W. The neural correlates of subjective value during intertemporal choice. *Nat Neurosci* **10**, 1625–1633 (2007).

883
884

11. Camille, N., Griffiths, C. A., Vo, K., Fellows, L. K. & Kable, J. W. Ventromedial frontal lobe damage disrupts value maximization in humans. *Journal of Neuroscience* **31**, 7527–7532 (2011).

885
886
887

12. Rushworth, M. F. S. & Behrens, T. E. J. Choice, uncertainty and value in prefrontal and cingulate cortex. *Nat Neurosci* **11**, 389–397 (2008).

888
889

13. Rushworth, M. F. S., Noonan, M. A. P., Boorman, E. D., Walton, M. E. & Behrens, T. E. Frontal Cortex and Reward-Guided Learning and Decision-Making. *Neuron* vol. 70 1054–1069 Preprint at https://doi.org/10.1016/j.neuron.2011.05.014 (2011).

890
891
892

14.   Kennerley, S. W., Behrens, T. E. J. & Wallis, J. D. Double dissociation of value
computations in orbitofrontal and anterior cingulate neurons. *Nat Neurosci* **14**, 1581–1589
(2011).
15.   Padoa-Schioppa, C. & Assad, J. A. Neurons in the orbitofrontal cortex encode economic
value. *Nature* **441**, 223–226 (2006).
16.   Wallis, J. D. Orbitofrontal cortex and its contribution to decision-making. *Annu Rev*
Neurosci **30**, 31–56 (2007).
17.   Rich, E. L. & Wallis, J. D. Decoding subjective decisions from orbitofrontal cortex. *Nat*
Neurosci **19**, 973–980 (2016).
18.   Padoa-Schioppa, C. Neuronal origins of choice variability in economic decisions. *Neuron*
80, 1322–1336 (2013).
19.   Strait, C. E., Blanchard, T. C. & Hayden, B. Y. Reward value comparison via mutual
inhibition in ventromedial prefrontal cortex. *Neuron* **82**, 1357–1366 (2014).
20.   Ferro, D., Cash-Padgett, T., Wang, M. Z., Hayden, B. Y. & Moreno-Bote, R. Gaze-
centered gating, reactivation, and reevaluation of economic value in orbitofrontal cortex.
Nat Commun **15**, (2024).
21.   Maisson, D. J. N. *et al.* Choice-relevant information transformation along a ventrodorsal
axis in the medial prefrontal cortex. *Nat Commun* **12**, (2021).
22.   Juechems, K., Balaguer, J., Ruz, M. & Summerfield, C. Ventromedial Prefrontal Cortex
Encodes a Latent Estimate of Cumulative Reward. *Neuron* **93**, 705-714.e4 (2017).
23.   Botvinick, M., Nystrom, L. E., Fissell, K., Carter, C. S. & Cohen, J. D. Conflict
monitoring versus selection-for-action in anterior cingulate cortex. *Nature 1999 402:6758*
402, 179–181 (1999).
24.   Van Veen, V., Cohen, J. D., Botvinick, M. M., Stenger, V. A. & Carter, C. S. Anterior
cingulate cortex, conflict monitoring, and levels of processing. *Neuroimage* **14**, 1302–
1308 (2001).
25.   Botvinick, M. M., Cohen, J. D. & Carter, C. S. Conflict monitoring and anterior cingulate
cortex: An update. *Trends Cogn Sci* **8**, 539–546 (2004).
26.   Shenhav, A., Botvinick, M. M. & Cohen, J. D. The expected value of control: An
integrative theory of anterior cingulate cortex function. *Neuron* **79**, 217–240 (2013).
27.   Hadland, K. A., Rushworth, M. F. S., Gaffan, D. & Passingham, R. E. The anterior
cingulate and reward-guided selection of actions. *J Neurophysiol* **89**, 1161–1164 (2003).
28.   Vassena, E., Holroyd, C. B. & Alexander, W. H. Computational models of anterior
cingulate cortex: At the crossroads between prediction and effort. *Front Neurosci* **11**,
(2017).
29.   Vassena, E., Deraeve, J. & Alexander, W. H. Surprise, value and control in anterior
cingulate cortex during speeded decision-making. *Nat Hum Behav* **4**, 412–422 (2020).
30.   Vassena, E. *et al.* Overlapping neural systems represent cognitive effort and reward
anticipation. *PLoS One* **9**, (2014).
31.   Kurniawan, I. T., Guitart-Masip, M., Dayan, P. & Dolan, R. J. Effort and valuation in the
brain: The effects of anticipation and execution. *Journal of Neuroscience* **33**, 6160–6169
(2013).
32.   Goh, A. X. A., Bennett, D., Bode, S. & Chong, T. T. J. Neurocomputational mechanisms
underlying the subjective value of information. *Commun Biol* **4**, (2021).
33.   Amiez, C., Joseph, J. P. & Procyk, E. Anterior cingulate error-related activity is
modulated by predicted reward. *European Journal of Neuroscience* **21**, 3447–3452
(2005).

34.   Blanchard, T. C., Strait, C. E. & Hayden, B. Y. Ramping ensemble activity in dorsal
941   anterior cingulate neurons during persistent commitment to a decision. *J Neurophysiol*
942   **114**, 2439–2449 (2015).
943   35.   Bush, G. *et al. Dorsal Anterior Cingulate Cortex: A Role in Reward-Based Decision
944   Making*. vol. 99 www.pnas.orgcgidoi10.1073pnas.012470999 (2002).
945   36.   Vassena, E., Holroyd, C. B. & Alexander, W. H. Computational models of anterior
946   cingulate cortex: At the crossroads between prediction and effort. *Front Neurosci* **11**,
947   (2017).
948   37.   Aarts, E. & Roelofs, A. *Attentional Control in Anterior Cingulate Cortex Based on
949   Probabilistic Cueing*. http://mitprc.silverchair.com/jocn/article-
950   pdf/23/3/716/1774802/jocn.2010.21435.pdf (2010).
951   38.   Strait, C. E. *et al.* Neuronal selectivity for spatial positions of offers and choices in five
952   reward regions. *J Neurophysiol* **115**, 1098–1111 (2016).
953   39.   Azab, H. & Hayden, B. Y. Correlates of decisional dynamics in the dorsal anterior
954   cingulate cortex. *PLoS Biol* **15**, (2017).
955   40.   Azab, H. & Hayden, B. Y. Correlates of economic decisions in the dorsal and subgenual
956   anterior cingulate cortices. *European Journal of Neuroscience* **47**, 979–993 (2018).
957   41.   Farashahi, S., Azab, H., Hayden, B. & Soltani, A. On the flexibility of basic risk attitudes
958   in monkeys. *Journal of Neuroscience* **38**, 4383–4398 (2018).
959   42.   Blanchard, T. C. & Hayden, B. Y. Neurons in dorsal anterior cingulate cortex signal
960   postdecisional variables in a foraging task. *Journal of Neuroscience* **34**, 646–655 (2014).
961   43.   Shidara, M. & Richmond, B. J. Anterior Cingulate: Single Neuronal Signals Related to
962   Degree of Reward Expectancy. *Science (1979)* **296**, 1709–1711 (2002).
963   44.   Cai, X. & Padoa-Schioppa, C. Neuronal activity in dorsal anterior cingulate cortex during
964   economic choices under variable action costs. *Elife* **10**, (2021).
965   45.   Hayden, B. Y., Pearson, J. M. & Platt, M. L. Fictive reward signals in the anterior
966   cingulate cortex. *Science (1979)* **324**, 948–950 (2009).
967   46.   Kerns, J. G. *et al.* Anterior Cingulate Conflict Monitoring and Adjustments in Control.
968   *Science (1979)* **303**, 1023–1026 (2004).
969   47.   Hayden, B. Y., Heilbronner, S. R., Pearson, J. M. & Platt, M. L. Surprise signals in
970   anterior cingulate cortex: Neuronal encoding of unsigned reward prediction errors driving
971   adjustment in behavior. *Journal of Neuroscience* **31**, 4178–4187 (2011).
972   48.   Bos, W. Van Den & McClure, S. M. Towards a general model of temporal discounting. *J
973   Exp Anal Behav* **99**, 58–73 (2013).
974   49.   Kim, S., Hwang, J. & Lee, D. Prefrontal Coding of Temporally Discounted Values during
975   Intertemporal Choice. *Neuron* **59**, 161–172 (2008).
976   50.   Louie, K. & Glimcher, P. W. Separating value from choice: Delay discounting activity in
977   the lateral intraparietal area. *Journal of Neuroscience* **30**, 5498–5507 (2010).
978   51.   Blanchard, T. C., Pearson, J. M. & Hayden, B. Y. Postreward delays and systematic biases
979   in measures of animal temporal discounting. *Proc Natl Acad Sci U S A* **110**, 15491–15496
980   (2013).
981   52.   Hayden, B. Y. Time discounting and time preference in animals: A critical review.
982   *Psychon Bull Rev* **23**, 39–53 (2016).
983   53.   Tversky, A. & Kahneman, D. Judgment under Uncertainty: Heuristics and Biases Biases
984   in judgments reveal some heuristics of thinking under uncertainty. *Science (1979)* **185**,
985   1124–1131 (1974).

54.   Tversky, A. & Kahneman, D. Advances in Prospect Theory: Cumulative Representation
of Uncertainty. *J Risk Uncertain* **5**, 297–323 (1992).
55.   O'Doherty, J., Kringelbach, M. L., Rolls, E. T., Hornak, J. & Andrews, C. Abstract
reward and punishment representations in the human orbitofrontal cortex. *Nat Neurosci* **4**,
95–102 (2001).
56.   Tobler, P. N., O'Doherty, J. P., Dolan, R. J. & Schultz, W. Reward value coding distinct
from risk attitude-related uncertainty coding in human reward systems. *J Neurophysiol* **97**,
1621–1632 (2007).
57.   Lee, D., Seo, H. & Jung, M. W. Neural basis of reinforcement learning and decision
making. *Annual Review of Neuroscience* vol. 35 287–308 Preprint at
https://doi.org/10.1146/annurev-neuro-062111-150512 (2012).
58.   Holroyd, C. B. & Yeung, N. Motivation of extended behaviors by anterior cingulate
cortex. *Trends in Cognitive Sciences* vol. 16 122–128 Preprint at
https://doi.org/10.1016/j.tics.2011.12.008 (2012).
59.   Sallet J. *et al.* Expectations, gains, and losses in the anterior cingulate cortex. *Cogn Affect*
Behav Neurosci **7**, 327–336 (2007).
60.   Hajnal, M. A. *et al.* Shifts in attention drive context-dependent subspace encoding in
anterior cingulate cortex in mice during decision making. *Nat Commun* **15**, (2024).
61.   Weissman, D. H., Gopalakrishnan, A., Hazlett, C. J. & Woldorff, M. G. Dorsal anterior
cingulate cortex resolves conflict from distracting stimuli by boosting attention toward
relevant events. *Cerebral Cortex* **15**, 229–237 (2005).
62.   Lake, J. I. *et al.* Reward anticipation and punishment anticipation are instantiated in the
brain via opponent mechanisms. *Psychophysiology* **56**, (2019).
63.   Aarts, E., Roelofs, A. & Van Turennout, M. Anticipatory activity in anterior cingulate
cortex can be independent of conflict and error likelihood. *Journal of Neuroscience* **28**,
4671–4678 (2008).
64.   Meder, D., Herz, D. M., Rowe, J. B., Lehéricy, S. & Siebner, H. R. The role of dopamine
in the brain - lessons learned from Parkinson's disease. *NeuroImage* vol. 190 79–93
Preprint at https://doi.org/10.1016/j.neuroimage.2018.11.021 (2019).
65.   Berridge, K. C. & Robinson, T. E. Parsing reward. *Trends Neurosci* **26**, 507–513 (2003).
66.   Glimcher, P. W. Understanding dopamine and reinforcement learning: The dopamine
reward prediction error hypothesis. *Proc Natl Acad Sci U S A* **108**, 15647–15654 (2011).
67.   Westbrook, A. *et al.* Dopamine promotes cognitive effort by biasing the benefits versus
costs of cognitive work. *Science (1979)* https://www.science.org (2020).
68.   Chakroun, K. *et al.* Dopamine regulates decision thresholds in human reinforcement
learning in males. *Nat Commun* **14**, (2023).
69.   Kennerley, S. W., Walton, M. E., Behrens, T. E. J., Buckley, M. J. & Rushworth, M. F. S.
Optimal decision making and the anterior cingulate cortex. *Nat Neurosci* **9**, 940–947
(2006).
70.   Morcos, A. S. & Harvey, C. D. History-dependent variability in population dynamics
during evidence accumulation in cortex. *Nat Neurosci* **19**, 1672–1681 (2016).
71.   Abrahamyan, A., Silva, L. L., Dakin, S. C., Carandini, M. & Gardner, J. L. Adaptable
history biases in human perceptual decisions. *Proc Natl Acad Sci U S A* **113**, E3548–
E3557 (2016).
72.   McGinty, V. B. & Lupkin, S. M. Behavioral read-out from population value signals in
primate orbitofrontal cortex. *Nat Neurosci* **26**, 2203–2212 (2023).
1032

1033

1034

Acknowledgements

This project was supported by grants funded by the Spanish Ministry of Science, Innovation and Universities (MICIU/AEI/10.13039/501100011033) and by "FEDER A way of making Europe" (ref: PID2023-146524NB), and by ICREA ACADÈMIA (2022) funded by the Catalan Institution for Research and Advanced Studies to R.M.B.

Author contributions

D.F., R.M.B. conceptualized and designed the analyses. B.H. ideated the task. D.F. analyzed the data. B.H., H.A. collected the data. D.F., B.H., R.M.B. wrote the manuscript.

Declaration of interests

The authors declare no competing interests.

1045

1046
1047
1048

Figure 1. Behavioral task and recording sites. A. Two offers are sequentially presented (*offer 1-2*, 600 ms), interleaved by blank screen delays (*delay 1-2*, 150 ms). After the offers presentation, subjects are instructed to re-acquire fixation to a central cross (*re-fixate*) for at least 100 ms and report their choice after a *choice-go* cue, consisting of the presentation of both previous offer stimuli. Choice is reported via target fixation for at least 200 ms (*choice*). The outcome of the chosen probabilistic offer is drawn from uniform distributions, providing (positive or negative) virtual tokens upon risky choice resolution. A small fluid reward (100 µL) is provided in all trials. The token count is visible through execution time as initially unfilled circles at the bottom of the screen, filled by tokens as they are collected. At 6 tokens count, subjects receive a "jackpot", large reward (300 µL), and the count is reset. The height of the bar stimuli is informative of the associated reward probability, while the color is informative of the magnitude. The probability of the outcomes color-cued by the top and bottom parts of the stimuli are complementary. The probabilities are discretized as 10%, 30%, 50%, 70% and 90%, the magnitudes consist of reward counts (-2, -1, 0, +1, +2, +3) and could include negative values. Offers could also include safe options where 0 (red) or 1 (blue) token are achieved with 100% probability. **B.** Illustration of dACC, brain area targeted for neural data recordings.

Figure 2. Value-based behavioral variables and accumulated tokens count influence decision-making performances. A. Logistic model of the correct choice (Methods 2.1), i.e., choice for the offer with the best expected value (EV). We use $\Delta_{EV} = |EV_1 - EV_2|$ to define the discriminability of best EV, inversely related to task difficulty; $M_{EV} = (EV_1 + EV_2)/2$ the mean offer EV; the offer risk level (ORL) the difference between the risk of the offer with highest EV and the risk of the offer with lowest EV; the accumulated tokens count (ATC) as of the the start of current trial; the presence of a jackpot on previous

trial ($JPT = 1$ jackpot, $JPT = 0$ no jackpot); the number of trials since last jackpot reward ($TSLR$); and
the outcome of previous trial (OPT), i.e. the number of tokens resulting from the risky choice made on
previous trial. The analysis is applied separately for the two subjects (red, subject 1, $n = 47030$ trials;
blue, subject 2, $n = 58911$, Supp. Table ST1). The intercept term $\beta_0 = -0.18 \pm 0.04$ in subject 1, and
-0.46 ± 0.04 in subject 2, $p < 0.001$ in both subjects. Inserts on the top right of the panel show zoomed
results for the logistic weights of OPT and TSLR. Numerical model weight estimates ± SE and numerical
p-values are reported in Supp. Table ST3. Model coefficients were estimated using maximum likelihood,
and significance was assessed via two-sided Wald tests based on the standard errors of the estimated
coefficients. **B.** Probability of correct choice (± s.e.m.) vs accumulated reward at the start of each trial (Low:
$ATC = [0,1]$; Medium: $ATC = [2,3]$; High: $ATC = [4,5]$). Sample size for each condition (number of
trials pooled across sessions) is detailed in Supp. Table ST1. Numeric means ± s.e.m. are reported in Supp.
Table ST4. **C)** Same as B but showing the task execution time. Numeric means ± s.e.m. are reported in
Supp. Table ST4. **D)** Logistic regression of first offer choice (ch1), designed as $\text{logit}(ch1) = \beta_0 +$
$\beta_1(EV_1 - EV_2)$ for Low ($ATC = [0,1]$) and High ($ATC = [4,5]$) accumulated tokens count (data
combined for the two subjects, High: $\beta_0 = -0.2, p = 3.6 \cdot 10^{-31}, \beta_1 = 1.52, p < 10^{-308}, n = 24099$,
Low: $\beta_0 = -0.21, p = 5.6 \cdot 10^{-82}, \beta_1 = 1.09, p < 10^{-308}, n = 47563$; Methods 2.2; Supp. Table ST1).
Model coefficients were estimated using maximum likelihood, and significance was assessed via two-sided
Wald tests based on the standard errors of the estimated coefficients. **E)** Difference in (β_0, β_1) weights in
D for High minus Low accumulated tokens count. Dots are weights differences in each session ($n = 109$
sessions, red for subject 1, $n = 118$, blue for subject 2). Bars show mean ± s.e.m. across sessions,
significance is assessed via two-tailed Wilcoxon signed-rank tests, $p = 1.77 \cdot 10^{-3}$ for β_1 in subject 1, $p =$
$1.34 \cdot 10^{-19}$ in subject 2.

Figure 3. Fraction of errors in reporting correct choice decreases with accumulated tokens count and
task difficulty. A) Average fraction of errors (subject 1, n=109 sessions; subject 2, n=118) for cases of no
jackpot ($JPT = 0$) or jackpot ($JPT = 1$) on previous trial and for different ranges of accumulated tokens
count as of the start of current trial (Low: $ATC = [0,1]$; Medium: $ATC = [2,3]$; High: $ATC = [4,5]$).
Sample size for each condition (number of trials pooled across sessions) is detailed in Supp. Table ST1.
Data are split based on difficulty as 'Hard' (filled markers, $\Delta_{EV} < \text{median}(\Delta_{EV})$) and 'Easy' (empty
markers, $\Delta_{EV} \geq \text{median}(\Delta_{EV})$). Sample size for each condition is detailed in Supp. Table ST2. Left: subject
1, right: subject 2. Differences in ATC ranges are tested via two-sided Wilcoxon signed-rank tests, FDR
corrected via Benjamini-Hochberg procedure (*p< 0.05, **p< 0.01, ***p< 0.001). **B)** Average fraction
of errors ± s.e.m. (subject 1, n=109 sessions; subject 2, n=118) for binned values of difficulty, inversely
related to $\Delta_{EV} = |EV_1 - EV_2|$. Sample size for each condition is detailed in Supp. Table ST2. Data are split
in 'Low' (solid, $ATC = [0,1]$) and 'High' (dotted, $ATC = [4,5]$) accumulated tokens count. Left: subject
1, right: subject 2. Differences in bins are assessed via two-tailed Wilcoxon rank sum (*p< 0.05, **p<
0.01, ***p< 0.001). Numeric means ± s.e.m. and p-values for all comparisons are reported in Supp. Table
ST5.

Figure 4. Risk seeking attitude increases with accumulated tokens count and easier best offer
discriminability. A. Fraction of trials (mean ± s.e.m.) with choice for the offer with higher risk. The data
are split in 'No Jackpot' ($JPT = 0$), 'Jackpot' ($JPT = 1$), and for accumulated tokens count ('Low' $ATC =$
$[0,1]$, 'Medium' $ATC = [2,3]$, 'High' $ATC = [4,5]$). Data are split for subject 1 (red) and subject 2 (blue),
and for Easy ($\Delta_{EV} \geq 1$, empty markers) and Hard ($\Delta_{EV} < 1$, filled markers). **B.** Markowitz risk return
model for the offer utility based on the mean value (EV) and risk (R) of the offers. The model parameter
(θ) describes risk attitude ($\theta < 0$ risk seeking, $\theta > 0$ risk avoiding) for jackpot cases and for values of
accumulated token counts. Data is split in difficulty and across subjects as in A. **C.** Markowitz risk return
model, parameter β_1 relative to EV weights for jackpot cases and for values of accumulated token counts.
Data is split as in A. **D.** Markowitz risk return model, parameter β_2 relative to risk R weights for jackpot
cases and for values of accumulated token counts. Data is split as in A. **A-D)** Sample size for each condition

is detailed in Supp. Table ST1. Numeric values for mean ± s.e.m. or mean ± CI across sessions are reported
in Supp. Table ST6.

Figure 5. Neural encoding of SVs and ATC in a spike-rate model without ATC interactions and their
link to choice prediction. A. Solid lines show the fraction of cells significantly encoding SV_1, SV_2 and
ATC in the 'linear model without ATC interaction' (Methods 3.1.1). The dotted line represents the 95th
percentile threshold from trial-order shuffled data. The percentiles are computed independently and
coincide across regressors, reflecting chance level of significance expected under null interaction. Bottom
lines indicate time bins where significant fractions exceed the percentile threshold, further assessed in
length by cluster-based run length analysis, considering runs whose length is significantly longer than the
95th percentile of equivalent lengths computed within shuffled data. Results are shown for the two subjects
separately in Supp. Fig. S4. **B.** Fractions of significant cells for SV_1 (top), SV_2 (middle) and ATC (bottom)
in task epochs (mean ± s.e.m. across time bins, $n = 129$ total cells). Dotted lines represent the 95th
percentile of fractions of significant cells run over trial-order shuffled data, computed separately for each
regressor. Significance is assessed via one-tailed signed rank, FDR corrected via Benjamini-Hochberg
procedure, testing that empirical data exceed 95th percentile thresholds (*$p < 0.05$, **$p < 0.01$, ***$p < $
0.001, Supp. Table ST9). **C.** Time-averaged fractions of $n = 129$ total cells that exclusively encode SV_1,
SV_2, ATC, or jointly encode (SV_1 and ATC), (SV_2 and ATC), (SV_1, SV_2 and ATC), or are non-significant
(n.s.). Results in B represent aggregate categories from C. For example, the fraction of cells encoding SV_1
includes cells exclusively encoding SV_1 as well as cells encoding SV_1 jointly with SV_2 and/or ATC. Fractions
in bold exceed the 95th percentile of equivalent fractions from trial-order shuffles. Subject-specific results,
percentiles and significance are in Supp. Fig. S5. **D.** Correlations between Area Under the Curve (AUC)
from ROC analyses of choice and model weights $\beta_1' = \langle \beta_1'(t) \rangle$ (left), $\beta_2' = \langle \beta_2'(t) \rangle$ (middle), $\beta_3' = \langle \beta_3'(t) \rangle$
(right) time-averaged at times posterior to the offer 2 onset, for the linear spike-rate model without
interactions (Methods 3.2.1). Each dot represents a cell ($n = 129$, subjects combined), with AUC and
model weights averaged in time bins posterior to offer 2 onset and cross-validation folds. Pearson's
coefficients ρ are assessed in significance via two-tailed t-tests (***$p < 0.001$, $p = 5.4 \cdot 10^{-36}$ for β_1', $p = $
$3.6 \cdot 10^{-32}$ for β_2', $p = 0.57$ for β_3'). Solid lines show linear regression lines, shaded areas indicate ±CI
computed using the standard error of the regression coefficients. The values at the bottom-right of each
panel report the median AUC across time bins posterior to offer 2 onset, cells, cross-validation folds for
positive (top) and negative (bottom) weights. Results are shown separately for the two subjects in Supp.
Fig. S6.

Figure 6. Encoding of SVs during task execution in the spike-rate model with ATC interactions and
neural tuning of EV and R differences and ATC interactions encoding weights to choice prediction
accuracy. A. Solid lines show the fractions of cells significantly encoding SV_1 and SV_2 in the 'linear model
with ATC interaction' (Methods 3.1.2). The dotted lines indicate trial-order shuffles percentiles and bottom
lines show significant time bins as in Fig. 5A. Results are shown for the two subjects separately in Supp.
Fig. S7. **B.** Fractions of significant cells for SV_1 (top) and SV_2 (bottom) in task epochs (mean ± s.e.m. across
time bins, $n = 129$ total cells). Dotted lines show trial-order shuffles percentiles as in Fig. 5B. Significance
is assessed via one-tailed signed rank, FDR corrected via Benjamini-Hochberg procedure, testing that
empirical data exceed 95th percentile thresholds (*$p < 0.05$, **$p < 0.01$, ***$p < 0.001$, Supp. Table
ST10). **C.** Time-averaged fractions of $n = 129$ total cells that exclusively encode SV_1 or SV_2, or jointly
SV_1 and SV_2, or are non-significant (n.s.). Results in B represent aggregate categories from C. The fraction
of cells encoding SV_1 includes cells exclusively encoding SV_1 as well as cells encoding SV_1 jointly with
SV_2, and similarly for SV_2. Fractions in bold exceed the 95th percentile of equivalent fractions from trial-
order shuffles. Subject-specific results, percentiles and significance are in Supp. Fig. S8. **D.** Correlations
between Area Under the Curve (AUC) from ROC analyses of choice and model weights $\beta_i' = \langle \beta_i'(t) \rangle$ ($i = $
$1, \ldots 5$, from left to right) time-averaged at times posterior to the offer 2 onset, for the linear model with
ATC interactions (Methods 3.2.2). Each dot represents a cell ($n = 129$, subjects combined), with AUC and
model weights averaged in time bins posterior to offer 2 onset and cross-validation folds. Pearson's

coefficients ρ are assessed in significance using two-tailed t-tests (***$p < 0.001$, $p = 1.04 \cdot 10^{-33}$ for β_1',
$p = 1.76 \cdot 10^{-31}$ for β_2', $p = 2.09 \cdot 10^{-28}$ for β_3', $p = 3.51 \cdot 10^{-28}$ for β_4', $p = 2.25 \cdot 10^{-28}$ for β_5'). Solid
lines show linear regression lines, shaded areas indicate $\pm$CI computed using the standard error of the
regression coefficients. The values at the bottom-right of each panel report the median AUC across time
bins posterior to offer 2 onset, cells, cross-validation folds for positive (top) and negative (bottom) weights.
Results are shown separately for the two subjects in Supp. Fig. S9.

Figure 7. Encoding of SVs for relative gains and losses during task execution in the spike-rate RDV
model and neural tuning of EV and R differences encoding weights in gains and losses to choice
prediction accuracy. A. Solid lines show fractions of cells significantly encoding SV_1 gains, SV_1 losses,
SV_2 gains and SV_2 losses in the 'RDV spike-rate model' (Methods 3.1.3). The dotted lines indicate trial-
order shuffles percentiles and bottom lines indicate significant time bins as in Fig. 5A. Results are shown
for the two subjects separately in Supp. Fig. S10. **B.** Fractions of significant cells for SV_1 (top) gains (dark)
and losses (light), and for SV_2 (bottom) gains (dark) and losses (light) in task epochs (mean $\pm$ s.e.m. across
time bins, $n = 129$ total cells). Dotted lines indicate trial-order shuffles percentiles as in Fig. 5B.
Significance is assessed via one-tailed signed rank, FDR corrected via Benjamini-Hochberg procedure,
testing that empirical data exceed the 95[th] percentile thresholds (*$p < 0.05$, **$p < 0.01$, ***$p < 0.001$,
Supp. Table ST11). **C.** Time-averaged fractions of $n = 129$ total cells that encode SV_1 gains (SV_1^+), SV_1
losses (SV_1^-), SV_2 gains (SV_2^+), SV_2 losses (SV_2^-) exclusively, jointly encode SVs (e.g., SV_1^+ and SV_1^-), or
are non-significant (n.s.). We group joint cases that show significant in minor quantity ($< 1\%$ of total cells).
Results in B represent aggregate categories from C. For example, the fraction of cells encoding SV_1^+
includes cells exclusively encoding SV_1^+ as well as cells encoding it jointly to SV_1^- and/or SV_2^+, SV_2^-.
Fractions in bold exceed the 95[th] percentile of equivalent fractions from trial-order shuffles. Subject-specific
results, percentiles and significance are in Supp. Fig. S11. **D.** Correlations between Area Under the Curve
(AUC) from ROC analyses of choice and model weights $\beta_i' = \langle \beta_i'(t) \rangle$ ($i = 1, ... 4$, from left to right) time-
averaged at time posterior to the offer 2 onset, for the RDV model (Methods 3.2.3). Each dot represents a
cell ($n = 129$, subjects combined), with AUC and model weights averaged in time bins posterior to offer
2 onset and cross-validation folds. Pearson's correlation coefficients ρ are assessed in significance via two-
tailed t-tests (***$p < 0.001$, $p = 1.21 \cdot 10^{-22}$ for β_1', $p = 1.62 \cdot 10^{-21}$ for β_2', $p = 7.84 \cdot 10^{-13}$ for β_3', $p =$
$7.46 \cdot 10^{-15}$ for β_4'). Solid lines show linear regression lines, shaded areas indicate $\pm$CI computed using the
standard error of the regression coefficients. The values at the bottom-right of each panel report the median
AUC across time bins posterior to offer 2 onset, cells, cross-validation folds for positive (top) and negative
(bottom) weights. Results are shown separately for the two subjects in Supp. Fig. S12.

1201

Figure 1

A

offer1	delay1	offer2	delay2	re-fixate	choice-go	choice	delay	feedback	delay3	jackpot
600 ms	150 ms	600 ms	150 ms	≥100 ms	variable time	≥200 ms	750 ms	300 ms	500 ms	300 ms

when tokens ≥6

small reward

large reward

reward magnitude/probability cues

- ■ chance of -2 tokens
- ■ chance of -1 token
- ■ chance of no token change
- ■ chance of +1 token
- ■ chance of +2 tokens
- ■ chance of +3 tokens

B

● dACC

Figure 2

Figure 3

Figure 4

Figure 5

Figure 6

Figure 7