Zero-shot segmentation using embeddings from a protein language model identifies functional regions in the human proteome

Ami G. Sangster[1], Cameron Dufault[2], Haoning Qu.[1], Denise Le.[1], Julie D. Forman-Kay[3,4], Alan M. Moses[1,2*]

1. Cell & Systems Biology, University of Toronto, Toronto, Ontario, Canada

2. Department of Computer Science, University of Toronto, Toronto, Ontario, Canada

3. Molecular Medicine Program, Hospital for Sick Children, Toronto, Ontario, Canada

4. Department of Biochemistry, University of Toronto, Toronto, Ontario, Canada

* Corresponding author

E-mail: alan.moses@utoronto.ca (AMM)

Abstract

The biological function of a protein is often determined by its distinct functional units, such as folded domains and intrinsically disordered regions. Identifying and categorizing these protein segments from sequence has been a major focus in computational biology which has enabled the automatic annotation of folded protein domains. Here we show that embeddings from the unsupervised protein language model ProtT5 can be used to identify and categorize protein segments without relying on conserved patterns in primary amino acid sequence. We present Zero-shot Protein Segmentation (ZPS), where we use embeddings from ProtT5 to predict the boundaries of protein segments without training or fine-tuning any parameters. We find that ZPS boundary predictions for the human proteome are more consistent with reviewed annotations from UniProt than established bioinformatics tools and ProtT5 embeddings of ZPS segments can categorize folded domains, sub-domains, and intrinsically disordered regions. To explore ZPS predictions, we introduce a new way to visualize protein embeddings that closely resembles diagrams of distinct functional units in protein biology. Since ZPS and segment embeddings can be used without training or fine-tuning, the approach is not biased towards known annotations and can used to identify and categorize unannotated protein segments. We used the segment embeddings to identify unannotated mitochondrion targeting signals and SYGQ-rich prion-like domains, which are functional regions within intrinsically disordered regions. We expect the protein segment organization revealed here to lead to valuable information about protein function,

including about intrinsically disordered regions and other less understood protein

regions.

Introduction

Proteins can contain a variety of distinct functional units including independently folding

regions, known as folded domains, and regions lacking stable structure, such as

intrinsically disordered regions (IDRs). Together, these distinct functional units

determine the overall function of the protein. Powerful bioinformatics tools, such as

Pfam [1] and Prosite [2], are widely used to identify and categorize folded domains from

amino acid sequences alone. Other approaches are applied to protein structures to

identify folded domains within proteins, referred to as protein segmentation [3,4]. In

addition to folded domains, IDRs are present in over 60% of human proteins [5],

perform important functions [6], and can be identified directly from amino acid

sequences with high accuracy [7]. Unlike folded domains, functional categorization of

IDR types remains challenging, though recent works have shown some success using

conserved sequence properties [8,9] and supervised deep learning [10,11].

Unsupervised bioinformatics approaches, such as fLPS2 [12] and a Chi-Score Analysis

[13], can segment proteins more generally based on statistical properties of amino acid

sequences. These approaches can distinguish IDRs from domains and have revealed a

non-random modular architecture within IDRs [13].

Here we explore the use of Protein Language Models (pLMs) to identify and categorize

folded domains and IDRs from the human proteome. We use the pLM ProtT5 [14] to

encode protein sequences into high-dimensional vectors known as embeddings. ProtT5

was pre-trained through unsupervised learning, a process where the model predicts

masked (or hidden) amino acids in protein sequences and therefore does not require

labelled data. Performing this task requires ProtT5 to develop contextualized

embeddings of each amino acid based on the surrounding protein sequence, which are

then used to predict the masked amino acids. After pre-training, visualizations of

dimensionally reduced embeddings can reveal associations with amino acid properties,

structure, and evolutionary relationships [14–16]. Additionally, pLMs can be used as a

starting point for further training, known as fine-tuning, or the embeddings from a pre-

trained model can be used as input to train another model. Both options have been

applied to a variety of protein related tasks [15–20], including amino acid level domain

annotation [21].

Embeddings or pLMs can also be used to make predictions on a new task, different

from the pre-training task, without training or fine-tuning on the new task. This is

referred to as "zero-shot" prediction. Protein embeddings have been used for zero-shot

prediction of variant effects [22,23] and drug-target binding [24]. Zero-shot applications

offer the potential for biological discovery without being tied to the original training task

or being biased by the content and availability of training data. Recent work in image

analysis has demonstrated that an unsupervised vision transformer can identify the

boundaries of objects in images without human labelled examples; this is referred to as

zero-shot image segmentation [25,26]. Inspired by this work, we sought to test whether

a transformer-based pLM, ProtT5 [14], can perform zero-shot protein segmentation.

Here, we demonstrate that a change point analysis applied to ProtT5 embeddings can identify the boundaries of biologically meaningful protein segments. We achieved this without training or fine-tuning any parameters, so we refer to this as Zero-shot Protein Segmentation (ZPS). We compare ZPS boundary predictions to annotations from UniProt [27], a protein annotation database which curates annotations from the literature and combines annotations from other databases and bioinformatics tools such as MobiDB [28] and ProRule [2]. We show that for the human proteome, the segments defined by ZPS match the boundaries of annotations from MobiDB for disorder and compositional biases more closely than other unsupervised methods designed specifically for these types of protein sequences [12,13]. Furthermore, we find that the ProtT5 embeddings of protein segments defined by ZPS can be used to categorize domains, sub-domains, and types of IDRs. Finally, as a specific application of these approaches, we identify unannotated mitochondrion targeting signals and SYGQ-rich prion-like domains in the human proteome.

Results

Known domains, IDRs, and motifs are found within ProtT5 embedding of FUS

To investigate whether ProtT5 embeddings can be used to identify the boundaries of biologically meaningful protein segments, we first visualized the ProtT5 embedding of human RNA-binding protein FUS [14] as a heatmap (Fig 1A). We selected FUS

because it is a well-studied protein with a combination of annotated folded domains and

IDRs. In the heatmap, we observed distinct segments in the embedding along the

protein's amino acid sequence. We identified boundaries of these segments using a

change point analysis, which we refer to as Zero-shot Protein Segmentation (ZPS) (see

Methods) and then visualized them (Fig 1B). The segments defined by ZPS closely

matched with annotations from UniProt and the literature [29,30] (Fig 1C).

We noted that in addition to known boundaries, the embedding also appears to contain

higher resolution information than its annotations (Fig 1). For example, the RNA

Recognition Motif (RRM) domain (folded) is broken into two segments by ZPS.

Generally, RRM domains have the structure $\beta_1\alpha_1\beta_2\beta_3\alpha_2\beta_4$ with an RNP2 motif in β_1 and

an RNP1 motif in β_3 [31] which align with the 2 faint vertical bands within the embedding

of the RRM domain (amino acids 287-293 and 333-341, Fig 1A). Each of the two ZPS

segments within the RRM domain begins with one of these motifs, suggesting that the

pLM is distinguishing a real functional or structural boundary within the RRM domain.

Similarly, within the IDRs, arginine-glycine-glycine (RGG) regions are defined by

multiple short repeating motifs of arginine and glycine and are associated with specific

biological functions [32]. In the RGG regions of the FUS embedding, the bold vertical

lines are the arginines and the thicker vertical bands are the glycines, which clearly

distinguishes these segments (amino acids 161-279, 376-419, 453-509, Fig 1A) from

other IDRs. The increased magnitude in the embedding for these specific residues in

the RGG regions suggests the pLM recognizes their significance in these regions of the

protein. These results are consistent with previous observations that pLMs learn key

functional residues and regions within proteins [15,22,33] and indicates that this

observation applies to both folded domains and IDRs.

For a more compact and interpretable visualization of the high-dimensional segment

embeddings, we display each segment as a block of colour along the linear protein

sequence (Fig 1B), as commonly seen in the molecular biology literature [29,30,32,34].

We achieve this by averaging the per-residue embeddings over the sequence length of

a ZPS protein segment to obtain a "segment embedding" (see Methods). Then the

segment embedding is reduced from a 1024-dimensional space to a 3-dimensional

RGB colour space to obtain a specific colour for that segment (see Methods). Just as

distinct clusters in a 2-dimensional visualization of protein embeddings can be

associated with biologically meaningful annotations (such as domains, evolutionary

relationships, and folded structures) [15,16,19,35], distinct colours in the 3-dimensional

RGB space can be associated with biologically meaningful annotations from the

literature (Fig 1). For example, there are SYGQ-rich and RGG regions within the N-

terminal IDR of FUS that are easily distinguishable by their segment colour and well-

defined in the literature, but these are not well-characterized in UniProt (Fig 1). Despite

over-segmentation relative to annotations from UniProt and the literature, segments with

the same colour fall under the same annotation, suggesting that segment embeddings

in the high-dimensional space can be associated with annotations (explored further in

later sections).

Fig 1. Zero-Shot Protein Segmentation Summary and Comparison to the

Literature. (A) A per-residue protein embedding from ProtT5 for human protein FUS

(UniProt ID: P35637). The embedding is visualized as a heatmap where the x-axis

represents each amino acid along the proteins sequence (which is maintained across

the panels in this Figure) and the y-axis is the ProtT5 embedding space. The

embedding space is ordered by hierarchical agglomerate clustering to make patterns in

the embedding space more visible. (B) Segments of FUS found using Zero-shot Protein

Segmentation (ZPS). The colour of each protein segment was obtained by reducing 1024-dimensional segment embeddings to 3-dimensions, which were scaled to RGB colours (see Methods). (C) FUS annotations from the literature (see Methods) and UniProt. MobiDB and ProRule annotations were retrieved from UniProt.

Segment embeddings can be used to categorize annotated regions of RNA binding proteins

To assess whether segment embeddings can be used to categorize segments across multiple proteins, we segmented well-characterized RNA binding proteins using ZPS, then compared their segments to annotations from the literature and AlphaFoldDB structures [36]. We selected the FET family (FUS, EWSR1, and TAF15), TDP-43, and HnRNPA1 which have a variety of annotated folded domains, IDRs, and regions within IDRs. The ZPS boundaries and segment embedding colours of these proteins are consistent with their folded domain and IDR sub-region annotations from the literature [29,30] (Fig 2A). Further, clustering the high-dimensional segment embeddings of these proteins separates the visually similar nuclear localization signals from RGGs (Fig 2B), consistent with the different annotations of these regions. Interestingly, the two N-terminal TDP-43 segments (Fig 2, purple) that comprise the N-terminal domain [34] cluster more closely with disordered SYGQ-rich regions than folded domains, despite AlphaFoldDB displaying a confident structure (pLDDT>90) (Fig 2C, purple). Surprisingly, this is consistent with the literature since the stability of this structure is debated [37,38]. Taken together these results suggest that the similarity of segment embeddings can be used to categorize different folded domains and different IDR sub-

2 method can simultaneously categorize both folded domains and IDRs. Additionally, the

3 above analysis demonstrates that visualizing protein embeddings as segments in the 3-

4 dimensional colour space offers a simple strategy for insight into unsupervised pLM

5 embeddings.

Fig 2. Segment Embeddings and Segment Colours of RNA-Binding Proteins. (A)

Segment embedding boundaries and colours compared to annotations from the

literature (see Methods) for the FET family (FUS, EWSR1 (UniProt ID: Q01844), and

TAF-15 (UniProt ID: Q92804)), HnRNPA1 (UniProt ID: P09651), and TDP-43 (UniProt

ID: Q13148). (B) Segment embeddings shown in panel A were ordered by hierarchical

agglomerate clustering and visualized as a heatmap. Corresponding colours of the

segment embeddings are shown to the right of the heatmap and labelled with

annotations from the literature. (C) AlphaFoldDB structure of TDP-43 (ID: Q13148)

showing segment colours. Abbreviations for folded domains labelled here include RNA

Recognition Motifs (RRM), N-terminal domain (NTD), and Zinc Fingers (ZF).

Abbreviations for IDR sub-regions labelled here include canonical Nuclear Localization

Signal (cNLS), Low Complexity (LC) regions, PY-motif Nuclear Localization Signals

(PY-NLS), and RGG (arginine-glycine-glycine motif) regions. G-rich and SYGQ-rich

regions describe compositional biases that define sub-regions of IDRs.

Zero-shot protein segmentation can reproduce the boundaries of UniProt annotations from the human proteome

To quantitatively assess the boundaries predicted by ZPS, we systematically compared

segment boundaries to annotated segments in the human proteome from UniProt. We

compare ZPS to Pfam [1] and PrositeScan [2], which are supervised bioinformatics

tools that primarily identify folded domains in proteins. We also compare ZPS to fLPS2

[12] and Chi-Score Analysis [13], which are unsupervised bioinformatics tools that

segment proteins. Additionally, we distinguish between UniProt, MobiDB, and ProRule,

where MobiDB and ProRule are separate databases that are included in UniProt.

MobiDB contains IDR and compositional biases annotations while ProRule contains

domain annotations.

First, we evaluated this approach as a segmentation problem using Intersection over

Union (IoU), a widely used measure of segmentation agreement from image analysis

[25,39]. A measure similar to IoU was previously proposed for assessing protein

secondary structure prediction of proteins [40]. We find that when evaluated on all

human proteome annotations in UniProt (including both MobiDB and ProRule), ZPS

outperforms both the supervised and unsupervised bioinformatics approaches on

average IoU and recall (Table 1). This is consistent with our results for FUS and other

proteins (Figs 1 and 2), where ZPS can identify the boundaries of both folded domains

and IDRs. Since we have previously observed over-segmentation relative to

annotations from UniProt and the literature (Figs 1 and 2), we also report metrics for

over-segmentation corrected ZPS (see Methods), which improves precision and

reduces recall (Table 1). We find that ZPS outperforms both supervised and

unsupervised bioinformatics approaches on average IoU and recall for annotations from

MobiDB (Table 1). Finally, for ProRule annotations we find that ZPS performance falls

between supervised and unsupervised bioinformatics approaches, where as expected,

supervised bioinformatics approaches trained on domains have the best performance

(Table 1).

	All UniProt (N=91k)				MobiDB (N=23k)				ProRule (N=22k)			
	Predicted Segments	Average IoU	Precision	Recall	Predicted Segments	Average IoU	Precision	Recall	Predicted Segments	Average IoU	Precision	Recall
Supervised												
Pfam	152k	0.436	0.264	0.456	74k	0.103	0.025	0.080	97k	0.765	0.195	0.872
Prosite Scan	32k	0.357	**0.830**	0.347	18k	0.128	0.132	0.108	26k	**0.877**	**0.725**	**0.897**
Unsupervised												
fLPS2	151k	0.367	0.177	0.303	95k	0.409	0.088	0.362	84k	0.316	0.058	0.223
fLPS2 (low complexity)	57k	0.155	0.199	0.128	45k	0.344	**0.165**	0.327	33k	0.080	0.038	0.057
Chi-Score Analysis	554k	0.345	0.039	0.240	316k	0.434	0.029	0.393	310k	0.282	0.009	0.126
Chi-Score (filtered)	81k	0.380	0.346	0.333	51k	0.396	0.160	0.357	43k	0.337	0.133	0.265
Our Method												
ZPS	253k	**0.532**	0.189	**0.538**	152k	**0.587**	0.096	**0.635**	144k	0.541	0.080	0.530
ZPS (corrected)	164k	0.516	0.257	0.482	98k	0.534	0.121	0.519	93k	0.549	0.125	0.533

15 **Table 1. Segmentation Evaluation for Human Proteome Segment Annotations**

16 **from UniProt.**

We report the number of predicted segments and Intersection over Union (IoU) metrics

for established bioinformatics tools and ZPS. ZPS (corrected) uses a simple correction

for over-segmentation (see Methods). The best performance for each measure is shown

in **bold.** N shows the number of annotated segments in the dataset. We use an IoU

threshold of 0.5 to define precision and recall.

In addition to IoU, we assessed the accuracy of boundaries by calculating the distance

in amino acids between the boundaries of annotated segment and predicted segment

pairs (see Methods). Overall, we found that ~40-50% of ZPS boundaries are less than

10 amino acids from a known boundary (Table 2). This demonstrates that on average,

ZPS can accurately predict about half the boundaries of known segment annotations.

Furthermore, ZPS outperforms supervised and unsupervised bioinformatics tools by

about 10-30% when we consider all human proteome annotations in UniProt or only this

subset from MobiDB. As expected, Prosite Scan and Pfam perform best on the ProRule

annotations from UniProt. Nevertheless, a change point analysis on ProtT5 embeddings

can consistently outperform unsupervised bioinformatics tools developed with specific

biological knowledge for IDRs and compositional biases. Furthermore, unlike other

methods, our approach shows reasonable performance on both folded domains and

IDRs in the human proteome.

	All UniProt (N=91k)			MobiDB (N=23k)			ProRule (N=22k)		
	Predicted Segments	Unpaired UniProt Segments	<10 amino acids	Predicted Segments	Unpaired MobiDB Segments	<10 amino acids	Predicted Segments	Unpaired ProRule Segments	<10 amino acids
Supervised									
Pfam	152k	24k	33.40%	74k	16k	6.01%	97k	0.8k	65.72%
Prosite Scan	32k	40k	30.54%	18k	15k	8.38%	26k	0.7k	**82.70%**
Unsupervised									
fLPS2	151k	5k	22.14%	95k	0.4k	31.80%	84k	1k	15.73%
fLPS2 (low complexity)	57k	50k	13.22%	45k	7k	30.35%	33k	15k	6.89%
Chi-Score Analysis	554k	10k	28.44%	316k	3k	37.59%	310k	3k	20.24%
Chi-Score (filtered)	81k	10k	23.73%	51k	3k	30.44%	43k	3k	16.05%
Our Method									
ZPS	253k	0	**41.95%**	152k	0	**49.10%**	144k	0	39.15%
ZPS (corrected)	164k	0	37.58%	98k	0	41.82%	93k	0	36.09%

Table 2. Boundary Evaluation for Human Proteome Segment Annotations from UniProt.

We report the number of predicted segments, the number of annotated segments without an overlapping predicted segment (Unpaired Segments), and the percentage of annotated boundaries with a predicted boundary less than 10 amino acids away. ZPS (corrected) uses a simple correction for over-segmentation (see Methods). The best performance for each measure is shown in **bold.** N shows the number of annotated segments in the dataset.

Segment embeddings can distinguish folded domains from intrinsically disordered regions and 5 different compositional biases

Our results for well-characterized RNA binding proteins (Fig 2) suggested that segment embeddings can distinguish different types of regions within proteins. So, we tested

whether segment embeddings can be used to distinguish protein segments with

different biological properties associated with function, such as compositional biases

and whether the protein segment can fold independently. Protein segments defined by

ZPS were labelled by transferring annotations from UniProt with the highest IoU (see

Methods) and then compared to their 1-nearest neighbour (1-nn) in the high

dimensional segment embedding space. Here, we find that MobiDB IDRs and ProRule

domains are clearly separated in the segment embedding space. The 1-nn accuracy

(see Methods) for ProRule domains and MobiDB IDRs are 0.985 +/-0.002 and 0.979 +/-

0.002, respectively (Fig 3A). This is as expected since IDRs and domains can be

distinguished based on amino acid composition, which we confirmed using one hot

encoding embeddings of these segments (0.895 +/-0.004 and 0.904 +/-0.004 for

ProRule domains and MobiDB IDRs, respectively). Similarly, segment embeddings can

distinguish the 5 different types of compositional bias annotations, where the 1-nn

accuracies range from 0.687 to 0.820 with confidence intervals ranging from +/-0.012 to

+/-0.059 (Fig 3B). By reducing the dimensionality of the segment embeddings using a

UMAP, we can visualize segment embeddings in a scatter plot. This shows that folded

domains and IDRs are clearly separable (Fig 3C). The compositional biases

visualization shows more overlap between protein segments with different

compositional biases, but still reveals patterns associated with their compositional bias

(Fig 3D). This demonstrates that segment embeddings contain sufficient information to

categorize structural state and compositional biases.

Fig 3. Segment Embedding Evaluation and Visualization of IDRs, Domains, and

Compositional Biases. (A, B) Normalized confusion matrices for 1-nn assessment for

(A) ProRule Domain compared to MobiDB Disorder Consensus and (B) MobiDB

compositional biases. In the confusion matrix, we report 1-nn accuracy with the binomial

proportion confidence interval shown below in brackets for true positive predictions (n is

the number of ZPS segments). (C, D) Shows 2-dimensional UMAPs of segment

embeddings labelled with (C) ProRule domains compared to MobiDB disorder

consensus and (D) MobiDB compositional biases. Each point in the UMAP is a protein

segment, and each segment shown in the UMAP was used in the respective 1-nn

assessment.

Segment embeddings can distinguish different types of

protein domains and sub-domains

We next tested whether segment embeddings can distinguish different types of protein

domains. Here, we transfer ProRule annotations from UniProt to segment embeddings

and analyze the top 20 most common domain annotations amongst the segment

embeddings using 1-nn. We find different types of domains are easily distinguishable

and have 1-nn accuracies that range from 0.935 to 0.997 with a confidence interval

ranging from +/-0.001 to +/-0.036 (Fig 4A). To confirm that segment embeddings from

the T5 model are more informative than embeddings of simple amino acid sequences,

we compare our results to 3-mer embeddings (see Methods) of the same protein

segments. Segment embeddings show an average of 0.241 increase compared to 3-

mer embeddings, where their 1-nn accuracies range from 0.435 to 0.992 (+/-0.009 to +/-

0.078) (S1 Table).

Fig 4. Segment Embedding Evaluation and Visualization Domain Types and Sub-Domains. (A, B) Normalized confusion matrices for 1-nn assessment (n is the number of ZPS segments). (A) Top 20 most commonly occurring ProRule domains in the ZPS segments and (B) shows clusters a, b, c, and d of the protein kinase domain (as labelled in panel C). In (B) we report 1-nn accuracy with the binomial proportion confidence interval shown below in brackets along the diagonal (S1 Table). (C) A 2-

dimensional UMAP of segment embeddings coloured by the type of domain the

segment overlaps with. This shows clusters a, b, c, and d of the protein kinase domain

segments. Each of the protein segments shown here were used in the 1-nn

assessment. (D) The AlphaFoldDB structure of KAPCA (UniProt ID: P17612) with the

protein kinase domain shown in colour, with sub-domains 1-5 (red), 5-7 (blue), 8-9

(orange), and 10-11(green). Sub-domains 1-5 are the small lobe and 5-11 are the large

lobe, as defined in [41]. (E) AlphaFoldDB structures of KAPCA, CDK2 (UniProt ID:

P24941), and PLK1 (UniProt ID: P53350), where colours are defined by clusters of

protein kinase segments, including cluster c (red), cluster d (blue), cluster b (orange),

and cluster a (green).

We visualized segment embeddings with different domain annotations using UMAP,

where we noted some domains organized into multiple clusters, such as the protein

kinase domain (Fig 4C and S2 Table). First, we established that these clusters exist in

the high dimensional space by performing the same 1-nn analysis and found the 1-nn

accuracies range from 0.989 to 1 (Fig 4B). Once again, the T5 segment embeddings

are more informative than 3-mer embeddings with 1-nn accuracies ranging from 0.849

to 0.948 (+/-0.027 to +/-0.037). We then found the segments in these clusters can be

ordered linearly within the protein kinase domain amino acid sequence, starting from the

N-term with cluster c, then d, then b, and cluster a, for 425/481 (88%) protein kinase

domains in the human proteome. From this, we determined that segments in clusters a,

b, c, and d are associated with sub-domains of the protein kinase domain. The protein

kinase domain is comprised of 12 sub-domains which can be grouped into 2 lobes, a

small lobe containing sub-domains 1-5 (Fig 4D, red) and a large lobe containing

domains 5-11 (Fig 4D, blue, orange and green), where sub-domain 5 spans both lobes

[41]. We found that the small lobe (Fig 4D, red) corresponds to segments from cluster c

(Fig 4E, red). In the large lobe, sub-domains 5, 6A, 6B, and 7, (Fig 4D, blue) identified

by their structural components (a-helix D, a-helix E, and B-strands 6-9 [41]), correspond

to cluster d (Fig 4E, blue). We observe slight variations with the sub-domains included

in clusters a and b, most notably whether cluster a includes a few extra alpha helices

(Fig 4E, CDK2) or is missing a few alpha helices (Fig 4E, PLK1). Despite these small

variations in how a few short alpha helices are distributed between clusters a and b, our

approach can zero-shot segment protein domains and sub-domains and distinguish

them more effectively than 3-mer embeddings.

Segment embeddings can distinguish intrinsically

disordered regions

We next assessed whether segment embeddings can be used to distinguish different

IDRs. This is a difficult problem for which few supervised approaches have been

developed [7,11]. We selected segments that overlap with IDR annotations from

MobiDB then transferred additional overlapping annotations, such as compositional

biases, to define different IDRs, and then selected the top 20 most common IDR

annotations (see Methods). We use this set of IDR annotations because there is a lack

of consensus on IDR types and identifying a broad range of meaningful large-scale

annotations remains challenging. Then we calculated the 1-nn accuracy and visualized

the segment embeddings of the IDRs using UMAP (Fig 5). We observe a wide range of

1-nn accuracies with an average of 0.650 (S1 Table), which we believe is due, at least

in part, to the broader definition of IDR annotations compared to folded domain

annotations. For example, we have labels with non-exclusive meanings such as

Collagen-Related and Triple Helical Region as well as COILED and HELIX [42,43].

Nevertheless, we see a clear improvement over random (average improvement of

0.561) and 3-mer embeddings of the same segments (average improvement 0.339) (S1

Table). This demonstrates that segment embeddings can be used to distinguish

different IDRs.

Fig 5. Segment Embedding Evaluation and Visualization of IDRs. (A) The

normalized confusion matrix for 1-nn assessment of the top 20 most common

annotations that overlap with IDRs defined by MobiDB. n is the number of ZPS

segments with each annotation. (B) UMAP of the segments used in the 1-nn

assessment labelled with the IDR types.

Discovery of unannotated mitochondrial targeting signals in the human proteome

To investigate whether the segment embeddings can be used to make predictions

about unannotated protein segments, we used Leiden clustering [44,45] to identify

clusters of unannotated segments in the human proteome (see Methods). We then

projected all human protein segment embeddings to a 2-dimensions space using UMAP

to visualize clusters of unannotated segments in the context of the whole human

proteome. After correction for over-segmentation (See Methods) we find 51

unannotated segments that are separate from the majority of the human proteome (Fig

6A, S3 Table). We found that there are 609 annotated segments that appear near this

cluster on the UMAP (S3 Table), which overlap with 435/495 (87.8%) of the annotated

mitochondrion targeting signals in the human proteome from UniProt. Consistent with

this, since typical mitochondrial targeting signals are located at the N-terminus of the

protein sequence [46], 644/660 (97.6%) of these segments (annotated and

unannotated) begin at the N-terminus of the protein. Further, 625/648 (96.5%, 7

unmapped proteins) of the proteins containing these segments localize to the

mitochondria (p=0), including 44/48 (91.7%, 3 unmapped proteins) proteins with

unannotated segments (p=8.98E-39). Interestingly, UniProt includes 58 mitochondrion

targeting signals of unknown length in the human proteome that begin at the N-terminus

of the protein, of which 39 (76.5%) are found in this cluster of 51 unannotated

segments. This evidence strongly suggests that the remaining 12 unannotated

segments in this cluster (Fig 6A, cyan) are undiscovered mitochondrion targeting

signals, and we can use this information to determine the size of the 39 mitochondrion

targeting signals of unknown length.

Fig 6. Identification of Mitochondrion-Related Cluster and SYQG-Rich Prion-Like

Domains Similar to FUS. (A) UMAP of segment embeddings of the entire human

proteome. Disordered segments (defined by MobiDB) are shown in a warmer shade of

grey to give context to the UMAP. Mitochondria Related cluster (cyan) was defined by

Leiden clustering of unannotated protein segments (see Methods). Segment

embeddings of FUS are shown along with the top 10 nearest-neighbours to the

segment embeddings of FUS's SYGQ-rich regions. (B) AlphaFoldDB structures of

COX18 (UniProt ID: Q8N8Q8), ADCK2 (UniProt ID: Q7Z695), CA5A (UniProt ID:

P35218), and HTRA2 (UniProt ID: O43464) colored by pLDDT confidence score (very

low in orange, low in yellow, high in cyan, and very high in blue), showing UniProt

mitochondrion targeting signal annotations (red) and ZPS segments (green). COX18

has a UniProt mitochondrion targeting signal annotation of unknown length starting at

the N-terminus and ADCK2 has no UniProt mitochondrion targeting signal annotation

but is known to localize to the mitochondrion [47].

To test whether segment embeddings associated with this unannotated segment cluster

(Fig 6A, cyan) are simply the N-terminal IDRs of mitochondrial proteins instead of actual

mitochondrion targeting signals, we compared examples of these segments to predicted

structures from AlphaFoldDB and annoated mitochondrial targeting signals from

UniProt. In some cases, such as CA5A, the boundaries of UniProt annotations of

mitochondrial targeting signals (Fig 6B, red) align closely with ZPS boundaries (Fig 6B

green) and a region having AlphaFold pLDDT confidence scores <50 ("very low", highly

correlated with structural disorder, Fig 6B, orange). However, in other cases such as

HTRA2, the UniProt mitochondrion targeting signal occupies only the first 30 residues

(Fig 6B, red) with the ZPS boundaries matching the UniProt annotation (Fig 6B, green),

while the very low confidence region spans the first 131 residues (Fig 6B, orange). This

use of ZPS and segment embeddings to annotate mitochondrion localization signals

provides evidence that pLM embeddings can provide valuable insight without training or fine-tuning.

Identifying similar IDRs to FUS's SYGQ-rich region using the k-nearest neighbours of segment embeddings

We chose to investigate the 4 SYGQ-rich segments in FUS because these segments represent "prion-like domain" elements of IDRs with well-studied role in forming condensates, such as in response DNA damage stress, or in forming aggregates, such as in amyotrophic lateral sclerosis and frontotemporal dementia [48–50]. In general, prion-like domains have a strong compositional bias and can be identified from amino acid sequences using Prion-Like Amino Acid Composition (PLAAC) scores [51].

We identified the 10 nearest-neighbours for each of the 4 segments of FUS's SYGQ-rich prion-like domain in the human proteome. After removing duplicates and joining adjacent segments (see Methods), we have 14 segments from 11 proteins (S4 Table). On average the amino acid content of these segments is 56% SYGQ, and 771/943 (81.8%) amino acids are predicted to be in a prion-like domain by PLAAC (Fig 7 shows 4 examples). Encouragingly, the SYGQ-rich regions of all 3 FET proteins (FUS, EWSR1, and TAF-15) were included in these segments, given the known conservation of these prion-like domains across the FET family [30,52,53]. Despite visually similar sequence composition in these amino acid sequences (Fig 7), performing a default protein BLAST [54] in the human proteome using FUS's SYGQ-rich prion-like domain

only retrieves anomalous fusion proteins and isoforms of FUS and EWSR1 – the search

does not identify any other proteins.

Fig 7. Zero-Shot Protein Segmentation of Proteins with Similar Segments to

FUS's SYGQ-Rich Region and PLAAC scores. Prion-Like Amino Acid Content

(PLAAC) scores adapted from the web tool described in [51], segment embedding

visualization (ZPS) as shown in Fig 1 and Fig 2, and the amino acid sequence of the

query segments from FUS and query result segments (S, Y, G, and Q shown in red).

Interestingly, in addition to the FET family, we identified 8 other proteins with similar

segment embeddings to FUS's SYGQ-rich regions. Encouragingly, the segments in 3 of

the 8 proteins, YTHD1, YTHD3, and AKAP8, have been reported to form condensates

and bind RNA, just as the FET family's SYGQ-rich regions can. Similar to FUS, the N-

terminal IDR in YTHD1 and YTHD3 is required to form condensates with RNA in the

cytosol in response to stress [55,56]. Also, similar to FUS, AKAP8 forms condensates in

the nucleus and binds RNA to regulate splicing, and condensate formation is required

for RNA regulation [57]. While other elements of AKAP8 have been identified to be

required for condensation [57], we predict that the prion-like domain segment (Fig 7)

makes a significant contribution to condensation. We observed other prion-like domains

predicted by PLAAC that are not nearest-neighbours of FUS (Fig 7). However, in FUS

these segments have a different compositional bias, G-rich or RGG (which also has

high G content), that is also known to be enriched in prion-like domains [51]. This

suggests we can distinguish prion-like domains by their compositional biases, beyond

the binary classification provided by PLAAC. Taken together, our analysis suggests that

the most similar segment embeddings to those of FUS's SYGQ-rich prion-like domain

are other prion-like domains with similar compositional biases that cannot be found

using BLAST, or uniquely identified by PLAAC.

Discussion

Here we show that embeddings from ProtT5 can be used to predict the boundaries of

protein regions and categorize protein segments without training or fine-tuning any

parameters. We predicted the boundaries of annotations from UniProt more effectively

than established bioinformatics tools and demonstrated that segment embeddings are

more informative than k-mer embeddings of the same sub-sequences at categorizing

protein domains, sub-domains, and types of IDRs. We then used these approaches to

identify unannotated mitochondria localization signals and SYGQ-rich prion-like

domains in the human proteome. Additionally, we present a novel approach for

visualizing pLM embeddings using protein segments and colours.

The boundaries defined by ZPS over-segment proteins relative to annotations on

UniProt and the literature (Fig 1, 2, 4). While this leads to poorer performance when

benchmarking against annotations from UniProt, when we investigated well-annotated

proteins, we found that the over-segmentation captured meaningful biology such as

motifs in structured domains and IDRs (Fig 1, RRM and RGG) as well as sub-domains

(Fig 4). We also observe over-segmentation relative to IDR annotations where some

segments align with different annotations (Fig 1, C-term RGG and PY-NLS), while other

instances of over-segmentation (Fig 1, N-term multiple SYGQ-rich segments) remain

unexplained. Given the motifs and sub-domains identified by the increased

segmentation relative to UniProt and some literature annotations, it's likely that this

"over-segmentation" also represents a more detailed and informative annotation.

To visualize the high-dimensional segment embeddings, we represented the segments

as colours along the protein sequence length. Colouring proteins by distinct annotations

is widely done in the molecular biology literature to help understand complex proteins

[29,30,32,34]. We found that for well-characterized RNA-binding proteins, we could

reproduce these diagrams using boundaries defined by ZPS and colours resulting from

a dimensionality reduction on segment embeddings. We believe that these

visualizations will be a useful tool for biologists to visualize and compare the functional

organization of proteins that they study. Further, we believe that converting embeddings

from unsupervised language models to RGB-colour space represents a new way to

visualize the information learned during pre-training that can be applied to any language

model (A. G. Sangster, Micaela Consens, A. M. Moses, in preparation).

Our approach demonstrates an advantage over classical bioinformatics approaches

based on sequence similarity, such as HMMs and alignments [2,54,58], because it does

not rely on positional evolutionary conservation of primary amino acid sequence.

Consistent with this, ZPS can identify the boundaries of IDRs and regions with

compositional biases (Table 1 and 2), which have poor positional conservation at the

primary amino acid level but have meaningful conservation of amino acid properties

distributed across their sequence [8,9]. Furthermore, these types of protein segments

can be categorized using segment embeddings (Fig 2, 3, 5). Additionally, we can use

segment embeddings to identify IDR protein segments that are believed to have similar

functions, such as mitochondrial targeting signals and SYGQ-rich prion-like domains

that drive condensation.

Finally, unlike other deep learning methods that use supervised learning, fine-tuning, or

transfer learning, our approach is zero-shot. Generalizability is therefore less impacted

by the content or availability of training data. This enables us to identify protein regions

for which there are too few known examples to train a supervised model, such as

SYGQ-rich prion-like domains. In principle, this means we can discover novel

categorizations of protein regions that do not have any current characterized examples.

However, task-specific fine-tuning on per-residue embeddings would likely lead to

improved performance for identifying boundaries and categorizations of known regions

for which there is sufficient training data. This has been demonstrated recently for

genome language models that were fine-tuned for genome segmentation [59].

Looking forward, we anticipate that the continuing developments in image segmentation

and deep learning can be applied to make further advancements in protein annotation

and genomics. For example, leveraging the drop loss function presented in zero-shot

image segmentation [25], which allows for novel object discovery, can enable pLMs to

discover overlapping, novel, and biologically meaningful regions in proteins. Our work is

a first step towards integrating the advancements of zero-shot image segmentation and

protein language models for understanding functional organization within proteins.

Methods

RNA-binding protein annotations from the literature

14   Annotations from the literature are shown in Figs 1 and 2 for RNA binding proteins,

15   including FUS (UniProt ID: P35637), EWSR1 (UniProt ID: Q01844), TAF-15 (UniProt ID:

16   Q92804), hnRNPA1 (UniProt ID: P09651), and TDP-43 (UniProt ID: Q13148). We show

17   annotations along the protein's sequence as described in the literature [29,30,34].

UniProt protein sequences and annotation data

These experiments use protein sequences and annotations for the human proteome

from UniProtKB/Swiss-Prot (UniProt) [27] (available on Zenodo). The sequences on

UniProt have reviewed annotations from a variety of sources including bioinformatics

tools, academic literature, and other databases. Here "annotations" only refer to

annotations that are associated with specific amino acids in the protein (available on

Zenodo). We removed annotations that include non-numeric characters in their

sequence positions, such as "1-?", "100-?150" and "<1-100", as it indicated uncertainty

in the position or length of the sequence in the annotation. For evaluating protein

segmentation, we use annotations from UniProt with any evidence level, including those

from sequence analysis, prediction, curation, citation, MobiDB [28], and ProRule, a

database provided by Prosite [2]. To assess performance on specific types of protein

segments, we include a partition of UniProt that only includes IDR consensus

predictions and compositional bias annotations from MobiDB. Additionally, we use a

partition of UniProt that only includes domains annotated by ProRule.

13 Zero-shot protein segmentation (ZPS)

We use the ProtT5 [14] encoder to generate protein embeddings for the whole human

proteome for sequences less than 8k amino acids in length. Here we use "embedding"

to refer to the output of the ProtT5 encoder. The ProtT5 embedding is a 2-dimensional

matrix where one dimension is the length of the protein and the other is the embedding

space of length 1024 (Lx1024). Next, a change point analysis is performed on each

ProtT5 embedding (see below for Change Point Analysis). This defines the boundaries

between protein segments. For example, if the boundaries are a, b, and c in a protein of

length 100, the segments are (0, a), (a, b), (b, c), and (c, 100). These ranges include the

first position and go up to but not including the second, as conventionally seen in zero-

based indexing. These segments are defined without fine-tuning or training any

parameters.

Change point analysis

A change point analysis is commonly used to detect changes in a signal or time series

[60]. We selected this method to perform zero-shot protein segmentation because it

does not require training parameters. We use a sliding window with a window size of 30

for our search algorithm and RBF kernel as our cost function. We chose a sliding

window algorithm because this has previously been used in protein biology to identify

modular organization within proteins [13]. This compares a segment of 15 amino acids

to the next 15 amino acids for all amino acids in the protein. If there is a significant

change between the first 15 amino acids and the next 15 amino acids, the space

between them becomes a boundary that defines protein segments. See [60] for sliding

window algorithm and RBF kernel function definition.

The number of boundaries predicted by the change point analysis is determined by one

of two pre-selected hyperparameters: either set a threshold on the cost function that

acts across the whole dataset or set a threshold on the number of boundaries for each

protein. Interestingly, we found a way to avoid doing either, making our approach free

from hyper-parameter selection in addition to not training or fine-tuning any parameters.

Initially we set a threshold on the number of boundaries per protein based on the

protein's length, but we found that allowing more than 3 boundaries per 100 amino

acids did not increase the total number of predicted boundaries. Therefore allowing 3 or

more boundaries per 100 amino acids allows the change point analysis to predict the

maximum number of boundaries it can find. To allow the method to function without

restraint, we gave the threshold of 3 boundaries per 100 amino acids, which yields

approximately 253k segments. Compared to methods we benchmark against, such as

Pfam (152k segments), fLPS2 (151k segments), and Chi-Score Analysis (554k

segments), 253k segments is reasonable considering Pfam and fLPS2 are tailored

towards a single type of protein segment whereas we are attempting to predict any type

of protein segment, so we moved forward with this set of predictions.

Segment embeddings

We define segment embeddings by cutting the ProtT5 embedding at the boundaries

defined by the change point analysis and then average pooling the segmented

embedding to 1x1024. For example, if a segment spans amino acids (100, 125) the

ProtT5 protein embedding would be cut at position 100 and 125 producing an

embedding of size 25x1024 which would be average pooled down to 1x1024. Segment

embeddings were generated without training or fine-tuning any parameters.

K-mer embeddings

We use k-mer embeddings as a baseline comparison for the content of the segment

embeddings. K-mer embeddings are defined using the same protein segments as

segment embeddings. 1-mer embeddings are equivalent to one hot encoding where

each dimension in the embedding represents the number of occurrences of each amino

acid. 3-mer embeddings contain the number of occurrences of each permutation of 3

amino acids (AAA, AAC, AAD, …). We use overlapping k-mers and normalize k-mer

embeddings before evaluations.

Correcting for over-segmentation

After analyzing FUS and other RNA-binding proteins, it was apparent that ZPS over-

segments relative to annotations on UniProt despite the meaningful biology, such as

motifs, that is captured by this over-segmentation (Fig 1 and 2). We attempt to correct

for over-segmentation by merging adjacent segments if they have similar segment

embeddings. We measure the cosine similarity between all segments in a protein; if the

segments with the highest cosine similarity are adjacent to each other in the protein

sequence, then they are merged. We only correct for over-segmentation if there are 6 or

more segments in a protein since this algorithm leads to poor results for proteins with a

small number of segments. For example, if there are only 3 segments in the protein,

then the middle segment will always get merged since it is adjacent to all the other

segments of the protein, regardless of their similarity. Increasing the number of

segments to 6 reduces the chance of "accidental" merging while still reducing the total

number of segments by ~100k (40%).

We also correct for over-segmentation when analyzing clusters (Fig 4 and 6). Here, we

simply join adjacent protein segments that are in the same cluster.

UMAPs

We used Uniform Manifold Approximation and Projection (UMAP) [61] to reduce the dimensionality of segment embeddings in two different instances. One is to visualize segment embeddings in a 2-dimensional scatter plot and the other is to visualize segment embeddings as 3-dimensional colours (see next section).

Segment embeddings to RGB colours

For our visualization approach, we reduced the segment embeddings (1x1024) of the whole human proteome to 3 dimensions (1x3) using a UMAP [61]. Each of the 3 dimensions is mean-centered across the whole proteome. Then we apply a sigmoid function to each of the RGB values for all segments and multiply by 255. We do this to scale the values and change their distribution from an approximately normal distribution to a more uniform distribution. This shifts the colours from mid-tone greys to increase their vibrancy and make the colours more distinct from each other. After this step, each segment has 3 values ranging from 0-225, one for red, green, and blue, which can be directly converted to a specific RGB colour.

$$X = [X_1, X_2, X_3] = \text{UMAP}(\text{human proteome segment embeddings})$$

$$[R, G, B] = \frac{255}{1 + e^{-(X - mean(X))}}$$

This function is applied element-wise, where X_1 maps to R, X_2 maps to G, and where X_3 maps to B.

Supervised bioinformatics approaches for protein segmentation

To our knowledge, there are not any supervised bioinformatics approaches designed for segmenting proteins that do not focus only on a specific type of protein region, such as domains. So, we use two supervised bioinformatics approaches that are designed to identify and categorize protein domains, Pfam and Prosite. We use HMMER 3.1b2 [58] to identify protein domains defined by Pfam (Pfam-A.hmm) [1] with default parameters. Additionally, we define another set of domains with Prosite Scan from ps_scan_linux_x86_elf.tar.gz (updated 2018) also using default parameters [2]. Prosite Scan is not to be confused with ProRule. While both are provided by PROSITE, Prosite Scan is an automatic domain annotation tool and ProRule is more of a "master set" of domain annotations including domains defined by manual curation. ProRule is included in UniProt.

Unsupervised bioinformatics approaches for protein segmentation

We use unsupervised bioinformatics approaches designed to segment proteins according to changes in amino acid compositional biases as a contrast to domain annotation tools. We ran fLPS2 [12] on the whole human proteome with default parameters and parameters specifically for short low complexity compositional biases (./fLPS2 -t1e-5 -m5 -M25, see fLPS2 README for further details). fLPS2 predicts protein segments with compositional biases and can make multiple overlapping

predictions; we included overlapping predictions in the evaluation. We also ran a Chi-Score Analysis [13], which predicts boundaries where there are significant changes in amino acid composition and has a built-in boundary filtering approach. We evaluated this approach with and without filtering boundaries. For Chi-Score Analysis we only included sequences less than 2k in length due to time complexity issues.

Intersection Over Union (IoU)

The Intersection over Union (IoU) is the number of amino acids in the intersection of a pair of predicted and annotated segments divided by the number of amino acids in the union of those two segments. This produces a measurement that is relative to the size of both segments. Predicted segments include those defined by ZPS, Pfam, Prosite Scan, fLPS2, and the Chi-Score Analysis. Annotated segments include human protein annotations from UniProt that are at least 30 amino acids in length and do not span the entire length of the protein from proteins that are at least 60 amino acids in length.

$$\text{IoU} = \frac{Predicted \ \cap Annotated}{Prediced \ \cup Annotated}$$

$$\text{IoU} = \frac{\max\left[\min(Pedicted_{end}, Annotated_{end}) - \max(Pedicted_{start}, Annotated_{start}), 0\right]}{\max(Pedicted_{end}, Annotated_{end}) - \min(Pedicted_{start}, Annotated_{start})}$$

Next, we measure the average IoU. For each annotated segment we select the predicted segment with the largest IoU value as its pair, then average over all annotations. We use a threshold of 0.5 on IoU to define precision and recall. If a pair of

segments has an IoU above the threshold, it is a true positive. If a predicted segment

does not have a pair above the threshold, it is a false positive. If an annotated segment

does not have a pair above the threshold, it is a false negative. Precision measures the

proportion of predicted segments that have a paired segment above the threshold and

recall measures the proportion of annotated segments that have a paired segment

above the threshold.

8
$$Recall = \frac{True\ Positives}{True\ Positives + False\ Negatives}$$

10
$$Precision = \frac{True\ Positives}{True\ Positives + False\ Positives}$$

Boundary evaluation

To evaluate the accuracy of the predicted boundaries, we select predicted and

annotated segment pairs by those with the highest IoU (as described above). Then we

measure the difference in amino acids at the beginning and end of the segments for

each segment pair. If no predicted segment overlaps with the annotated segment, we

count it as an "unpaired segment". The percent of boundaries within 10 amino acids of

the annotated segments is relative to the total number of annotations, even if the

annotated segment does not have an overlapping predicted segment (unpaired

segments are counted towards the total percentage).

Transferring UniProt annotations to label segment embeddings

We transfer annotations from UniProt to segments defined by ZPS based on how much the segment overlaps with a UniProt annotation. When labeling segments, we allow UniProt annotations of any size, as opposed to evaluating segmentation/boundary prediction only allow annotations that are 30 amino acids or larger. We handle the many overlapping annotations that can be found on UniProt by selecting the annotation that has the highest IoU with the ZPS protein segment. An annotation is only considered to be transferred if the intersection between the UniProt annotation and the ZPS protein segment is at least 30% of the ZPS protein segment.

When we consider annotations that are overlapping IDRs to assess segment embeddings of IDRs, we first define ZPS segments as IDRs if at least 30% of their amino acids overlap with a disordered annotation from MobiDB, then we perform the annotation transfer described above only for ZPS segments that are at least partially IDRs.

Nearest neighbours

Here we use nearest neighbour to identify similar segment embeddings using cosine distance. We use this to predict the annotations of segment embeddings by finding the label of their 1-nearest neighbour (1-nn) and evaluate with a normalized confusion

matrix (see below). We also use nearest neighbours to find protein segments that are

similar to the SYGQ-rich prion-like domain in FUS (Fig 7).

Normalized Confusion Matrix

We use cosine similarity to identify the 1-nn of protein segment embeddings and use

annotation of the 1-nn as the predicted label. We do not allow a segment to have the

predicted label from another segment from the same protein; we simply choose the next

nearest neighbour that is not from the same protein. We use this to define a confusion

matrix which is normalized by the number of segments with that label. We also report a

binomial proportion confidence interval for values along the diagonal. When we perform

1-nn to evaluate on a specific set of labels, such as the top 20 ProRule domain

annotations, only segments with those annotations are included in the evaluation.

PyMOL

We use open-source Pymol available on github. We used their interactive interface to

colour protein structures by protein segments defined by ZPS (Figs 2C, 4D, 4E).

The PyMOL Molecular Graphics System, Version 2.5.0 Schrödinger, LLC.

https://github.com/schrodinger/pymol-open-source

Clustergrams with Plotly

We use clustergrams available through Plotly DashBio application to generate

heatmaps of ProtT5 embeddings (Fig 1A) and perform clustering (Fig 1A, 2B). We

cluster using hierarchical agglomerative clustering with average linkage and cosine

distance; we also use optimal leaf ordering.

Clustering unannotated segments with Leiden

We use ScanPy [44] to perform Leiden clustering [45] of unannotated ZPS segments

from the human proteome. We do not reduce the dimensionality of the segment

embeddings before clustering, and we allow for the model to find the optimal clusters;

we do not limit the number of iterations it runs and chose a cluster resolution of 2.

GO enrichment (PANTHER)

To determine which proteins localized to the mitochondria, we performed a GO

Enrichment using PantherDB [62] (Version 19.0, released 2024-06-20). We report FDR

corrected p-values.

Acknowledgements

We would like to acknowledge Alex Lu, Mica Consens, Alex Huang, and Andrew

Duncan for their valuable feedback on the manuscript.

Data and Code Availability

The following data used for this analysis is available on Zenodo.

https://zenodo.org/records/14962518

1. Human protein sequences that were used to generate per-residue ProtT5

embeddings and segment embeddings.

2. UniProt annotations that were used to evaluate ZPS and label segment embeddings.

3. A list of segment boundaries for the human proteome defined by ZPS.

4. Segment embeddings for the human proteome.

Code to generate per-residue ProtT5 embeddings, define the boundaries of protein

segments using change point analysis, and generate segment embeddings is available

on GitHub and can be run on colab.

https://github.com/moses-lab/zero-shot-protein-segmentation

Code to visualize protein segment embeddings from the human proteome as colours

along the protein's sequence is available on GitHub and can be run on colab.

https://github.com/moses-lab/pLM-Visualization

References

1. Mistry J, Chuguransky S, Williams L, Qureshi M, Salazar GA, Sonnhammer ELL, et al. Pfam: The protein families database in 2021. Nucleic Acids Res. 2021 Jan 8;49(D1):D412–9.

2. Sigrist CJA, de Castro E, Cerutti L, Cuche BA, Hulo N, Bridge A, et al. New and continuing developments at PROSITE. Nucleic Acids Res. 2013 Jan 1;41(D1):D344–7.

3. Lau AM, Kandathil SM, Jones DT. Merizo: a rapid and accurate protein domain segmentation method using invariant point attention. Nat Commun. 2023 Dec 19;14(1):8445.

4. Wells J, Hawkins-Hooker A, Bordin N, Sillitoe I, Paige B, Orengo C. Chainsaw: protein domain segmentation with fully convolutional neural networks. Bioinformatics. 2024 May 1;40(5):btae296.

5. Tsang B, Pritišanac I, Scherer SW, Moses AM, Forman-Kay JD. Phase Separation as a Missing Mechanism for Interpretation of Disease Mutations. Cell. 2020 Dec 23;183(7):1742–56.

6. Holehouse AS, Kragelund BB. The molecular basis for cellular function of intrinsically disordered protein regions. Nat Rev Mol Cell Biol. 2023 Nov 13;

7. Conte AD, Mehdiabadi M, Bouhraoua A, Miguel Monzon A, Tosatto SCE, Piovesan D. Critical assessment of protein intrinsic disorder prediction (CAID) - Results of round 2. Proteins Struct Funct Bioinforma. 2023;91(12):1925–34.

8. Zarin T, Strome B, Nguyen Ba AN, Alberti S, Forman-Kay JD, Moses AM. Proteome-wide signatures of function in highly diverged intrinsically disordered regions. eLife. 2019;8:e46883.

9. Zarin T, Strome B, Peng G, Pritišanac I, Forman-Kay JD, Moses AM. Identifying molecular features that are associated with biological function of intrinsically disordered protein regions. Eisen MB, editor. eLife. 2021 Feb 22;10:e60220.

10. Hu G, Katuwawala A, Wang K, Wu Z, Ghadermarzi S, Gao J, et al. flDPnn: Accurate intrinsic disorder prediction with putative propensities of disorder functions. Nat Commun. 2021 Jul 21;12(1):4438.

11. Pang Y, Liu B. DMFpred: Predicting protein disorder molecular functions based on protein cubic language model. PLOS Comput Biol. 2022 Oct 31;18(10):e1010668.

12. Harrison PM. fLPS 2.0: rapid annotation of compositionally-biased regions in biological sequences. PeerJ. 2021;9:e12363.

13. McConnell BS, Parker MW. Protein intrinsically disordered regions have a non-random, modular architecture. Bioinforma Oxf Engl. 2023 Dec 1;btad732.

14. Elnaggar A, Heinzinger M, Dallago C, Rehawi G, Wang Y, Jones L, et al. ProtTrans: Toward Understanding the Language of Life Through Self-Supervised Learning. IEEE Trans Pattern Anal Mach Intell. 2022 Oct;44(10):7112–27.

15. Rives A, Meier J, Sercu T, Goyal S, Lin Z, Liu J, et al. Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. Proc Natl Acad Sci. 2021 Apr 13;118(15).

16. Nallapareddy V, Bordin N, Sillitoe I, Heinzinger M, Littmann M, Waman VP, et al. CATHe: detection of remote homologues for CATH superfamilies using embeddings from protein language models. Bioinforma Oxf Engl. 2023 Jan 1;39(1):btad029.

17. Brandes N, Ofer D, Peleg Y, Rappoport N, Linial M. ProteinBERT: a universal deep-learning model of protein sequence and function. Bioinformatics. 2022 Apr 12;38(8):2102–10.

18. Kaminski K, Ludwiczak J, Pawlicki K, Alva V, Dunin-Horkawicz S. pLM-BLAST: distant homology detection based on direct comparison of sequence representations from protein language models. Bioinformatics. 2023 Oct 1;39(10):btad579.

19. Heinzinger M, Littmann M, Sillitoe I, Bordin N, Orengo C, Rost B. Contrastive learning on protein embeddings enlightens midnight zone. NAR Genomics Bioinforma. 2022 Jun;4(2):lqac043.

20. Hamamsy T, Morton JT, Blackwell R, Berenberg D, Carriero N, Gligorijevic V, et al. Protein remote homology detection and structural alignment using deep learning. Nat Biotechnol. 2024 Jun;42(6):975–85.

21. Sarkar A, Krishnan K, Eddy SR. Protein Sequence Domain Annotation using Language Models. bioRxiv; 2024. p. 2024.06.04.596712. Available from: https://www.biorxiv.org/content/10.1101/2024.06.04.596712v2

22. Meier J, Rao R, Verkuil R, Liu J, Sercu T, Rives A. Language models enable zero-shot prediction of the effects of mutations on protein function. In: Advances in Neural Information Processing Systems. Curran Associates, Inc.; 202. p. 29287–303.

23. Mansoor S, Baek M, Juergens D, Watson JL, Baker D. Zero-shot mutation effect prediction on protein stability and function using RoseTTAFold. Protein Sci Publ Protein Soc. 2023 Nov;32(11):e4780.

24. Wang Y, Xia Y, Yan J, Yuan Y, Shen HB, Pan X. ZeroBind: a protein-specific zero-shot predictor with subgraph matching for drug-target interactions. Nat Commun. 2023 Nov 29;14(1):7861.

25. Wang X, Girdhar R, Yu SX, Misra I. Cut and Learn for Unsupervised Object Detection and Instance Segmentation. arXiv; 2023. Available from: http://arxiv.org/abs/2301.11320

26. Caron M, Touvron H, Misra I, Jégou H, Mairal J, Bojanowski P, et al. Emerging Properties in Self-Supervised Vision Transformers. arXiv; 2021. Available from: http://arxiv.org/abs/2104.14294

27. UniProt Consortium. UniProt: the Universal Protein Knowledgebase in 2023. Nucleic Acids Res. 2023 Jan 6;51(D1):D523–31.

28. Piovesan D, Necci M, Escobedo N, Monzon AM, Hatos A, Mičetić I, et al. MobiDB: intrinsically disordered proteins in 2021. Nucleic Acids Res. 2021 Jan 8;49(D1):D361–7.

29. Yoshizawa T, Nozawa RS, Jia TZ, Saio T, Mori E. Biological phase separation: cell biology meets biophysics. Biophys Rev. 2020 Mar 18;12(2):519.

30. Couthouis J, Hart MP, Erion R, King OD, Diaz Z, Nakaya T, et al. Evaluating the role of the FUS/TLS-related gene EWSR1 in amyotrophic lateral sclerosis. Hum Mol Genet. 2012 Jul 1;21(13):2899–911.

31. Maris C, Dominguez C, Allain FHT. The RNA recognition motif, a plastic RNA-binding platform to regulate post-transcriptional gene expression. FEBS J. 2005;272(9):2118–31.

32. Thandapani P, O'Connor TR, Bailey TL, Richard S. Defining the RGG/RG motif. Mol Cell. 2013 Jun 6;50(5):613–23.

33. Brandes N, Goldman G, Wang CH, Ye CJ, Ntranos V. Genome-wide prediction of disease variant effects with a deep protein language model. Nat Genet. 2023 Sep;55(9):1512–22.

34. Jiang LL, Xue W, Hong JY, Zhang JT, Li MJ, Yu SN, et al. The N-terminal dimerization is required for TDP-43 splicing activity. Sci Rep. 2017 Jul 21;7(1):6196.

35. Odrzywolek K, Karwowska Z, Majta J, Byrski A, Milanowska-Zabel K, Kosciolek T. Deep embeddings to comprehend and visualize microbiome protein space. Sci Rep. 2022 Jun 20;12(1):10332.

36. Varadi M, Anyango S, Deshpande M, Nair S, Natassia C, Yordanova G, et al. AlphaFold Protein Structure Database: massively expanding the structural coverage of protein-sequence space with high-accuracy models. Nucleic Acids Res. 2022 Jan 7;50(D1):D439–44.

37. Mompeán M, Romano V, Pantoja-Uceda D, Stuani C, Baralle FE, Buratti E, et al. Point mutations in the N-terminal domain of transactive response DNA-binding protein 43 kDa (TDP-43) compromise its stability, dimerization, and functions. J Biol Chem. 2017 Jul 14;292(28):11992–2006.

38. Li R, Singh R, Kashav T, Yang C, Sharma RD, Lynn AM, et al. Computational Insights of Unfolding of N-Terminal Domain of TDP-43 Reveal the Conformational Heterogeneity in the Unfolding Pathway. Front Mol Neurosci. 2022 Apr 25;15:822863.

39. Rezatofighi H, Tsoi N, Gwak J, Sadeghian A, Reid I, Savarese S. Generalized Intersection over Union: A Metric and A Loss for Bounding Box Regression. arXiv; 2019. Available from: http://arxiv.org/abs/1902.09630

40. Rost B, Sander C, Schneider R. Redefining the goals of protein secondary structure prediction. J Mol Biol. 1994 Jan 7;235(1):13–26.

41. Hanks SK, Hunter T. Protein kinases 6. The eukaryotic protein kinase superfamily: kinase (catalytic) domain structure and classification. FASEB J Off Publ Fed Am Soc Exp Biol. 1995 May;9(8):576–96.

42. Shoulders MD, Raines RT. COLLAGEN STRUCTURE AND STABILITY. Annu Rev Biochem. 2009;78:929–58.

43. Lupas AN, Bassler J, Dunin-Horkawicz S. The Structure and Topology of α-Helical Coiled Coils. Fibrous Proteins Struct Mech. 2017 Jan 19;82:95–129.

44. Wolf FA, Angerer P, Theis FJ. SCANPY: large-scale single-cell gene expression data analysis. Genome Biol. 2018 Feb 6;19(1):15.

45. Traag VA, Waltman L, van Eck NJ. From Louvain to Leiden: guaranteeing well-connected communities. Sci Rep. 2019 Mar 26;9(1):5233.

46. Bolender N, Sickmann A, Wagner R, Meisinger C, Pfanner N. Multiple pathways for sorting mitochondrial precursor proteins. EMBO Rep. 2008 Jan;9(1):42–9.

47. Vázquez-Fonseca L, Schäefer J, Navas-Enamorado I, Santos-Ocaña C, Hernández-Camacho JD, Guerra I, et al. ADCK2 Haploinsufficiency Reduces Mitochondrial Lipid Oxidation and Causes Myopathy Associated with CoQ Deficiency. J Clin Med. 2019 Sep 2;8(9):1374.

48. Franzmann TM, Alberti S. Prion-like low-complexity sequences: Key regulators of protein solubility and phase behavior. J Biol Chem. 2019 May 3;294(18):7128–36.

49. Gitler AD, Shorter J. RNA-binding proteins with prion-like domains in ALS and FTLD-U. Prion. 2011;5(3):179–87.

50. Franzmann TM, Jahnel M, Pozniakovsky A, Mahamid J, Holehouse AS, Nüske E, et al. Phase separation of a yeast prion protein promotes cellular fitness. Science. 2018 Jan 5;359(6371):eaao5654.

51. Lancaster AK, Nutter-Upham A, Lindquist S, King OD. PLAAC: a web and command-line application to identify proteins with prion-like amino acid composition. Bioinforma Oxf Engl. 2014 Sep 1;30(17):2501–2.

52. Johnson CN, Sojitra KA, Sohn EJ, Moreno-Romero AK, Baudin A, Xu X, et al. Insights into Molecular Diversity within the FUS/EWS/TAF15 Protein Family: Unraveling Phase Separation of the N-Terminal Low-Complexity Domain from RNA-Binding Protein EWS. J Am Chem Soc. 2024 Mar 27;146(12):8071–85.

53. Tan AY, Manley JL. The TET family of proteins: functions and roles in disease. J Mol Cell Biol. 2009 Dec;1(2):82–92.

54. Altschul SF, Gish W, Miller W, Myers EW, Lipman DJ. Basic local alignment search tool. J Mol Biol. 1990 Oct 5;215(3):403–10.

55. Fu Y, Zhuang X. m6A-binding YTHDF proteins promote stress granule formation. Nat Chem Biol. 2020 Sep;16(9):955–63.

56. Ries RJ, Zaccara S, Klein P, Olarerin-George A, Namkoong S, Pickering BF, et al. m6A enhances the phase separation potential of mRNA. Nature. 2019 Jul;571(7765):424–8.

57. Li W, Hu J, Shi B, Palomba F, Digman MA, Gratton E, et al. Biophysical properties of AKAP95 protein condensates regulate splicing and tumorigenesis. Nat Cell Biol. 2020 Aug;22(8):960–72.

58. Eddy SR. Accelerated Profile HMM Searches. PLOS Comput Biol. 2011 Oct 20;7(10):e1002195.

59. Bernardo P. de Almeida, Hugo Dalla-Torre, Guillaume Richard, Christopher Blum, Lorenz Hexemer, Maxence Gélard, et al. SegmentNT: annotating the genome at single-nucleotide resolution with DNA foundation models. bioRxiv. Available from: https://www.biorxiv.org/content/10.1101/2024.03.14.584712v1

60. Truong C, Oudre L, Vayatis N. Selective review of offline change point detection methods. Signal Process. 2020 Feb;167:107299.

61. McInnes L, Healy J, Saul N, Großberger L. UMAP: Uniform Manifold Approximation and Projection. J Open Source Softw. 2018 Sep 2;3(29):861.

62. Thomas PD, Ebert D, Muruganujan A, Mushayahama T, Albou LP, Mi H. PANTHER: Making genome-scale phylogenetics accessible to all. Protein Sci. 2022;31(1):8–22.

Supporting Information

S1 Table. 1-Nearest Neighbour Normalized Confusion Matrix Accuracy and Binomial Proportion Confidence Intervals. See separate tables within the excel file for the different 1-nn confusion matrices. This includes tables for IDR vs domain, 5 compositional biases, protein domains, protein sub-domains, and IDRs as well as the corresponding 1-mer (one hot encoding) or 3-mer tables, for instances when they are compared to these in the main text.

S2 Table. Protein Identifiers and Segment Boundaries of Protein Kinase Domain Segment Clusters. Identifiers are UniProt IDs, boundaries use zero-based indexing and labels include a, b, c, and d as shown in Fig 4. These segments have not been corrected for over-segmentation, meaning there can be multiple segments from the same proteins (UniProt IDs are non-unique).

S3 Table. Protein Identifiers and Segment Boundaries of Protein Segments in the

Mitochondrion Analysis. Identifiers are UniProt IDs, boundaries use zero-based

indexing and labels include "Annotated" (only includes protein segments that overlap

with Mitochondrion Related cluster in the UMAP, Fig 6A) and "10" (corresponding to

Leiden cluster number 10, labelled as "Mitochondrion Related" in cyan in Fig 6). These

segments have not been corrected for over-segmentation, meaning there can be

multiple segments from the same proteins (UniProt IDs are non-unique).

S4 Table. Protein Identifiers and Segment Boundaries of Protein Segments

Similar to FUS's SYGQ-rich Prion-Like Domain. Identifiers are UniProt IDs and

boundaries use zero-based indexing. These segments have been corrected for over-

segmentation, meaning "POS" contains a list of start and stop boundaries of each

segment for each protein.