Predictions from Deep Learning Propose Substantial Protein-Carbohydrate Interplay

Samuel W. Canner[1], Ronald L. Schnaar[2,3], Jeffrey J. Gray[1,4]*

[1]Program in Molecular Biophysics, Johns Hopkins University, Baltimore, MD, United States

[2]Department of Pharmacology and Molecular Sciences, Johns Hopkins University School of Medicine, Baltimore, Maryland, United States

[3]Department of Neuroscience, Johns Hopkins University School of Medicine, Baltimore, Maryland, United States

[4]Department of Chemical and Biomolecular Engineering, Johns Hopkins University, Baltimore, MD, United States

* Correspondence: Jeffrey J. Gray, jgray@jhu.edu

Abstract

It is a grand challenge to identify all the protein – carbohydrate interactions in an organism. Direct experiments would require extensive libraries of glycans to definitively distinguish binding from non-binding proteins. Computational screening of proteins for carbohydrate-binding provides an attractive and ultimately testable alternative. Recent computational techniques have focused primarily on which protein residues interact with carbohydrates or which carbohydrate species a protein binds to. Current estimates label 1.5 to 5% of proteins as carbohydrate-binding proteins; however, 50-70% of proteins are known to be glycosylated, suggesting a potential wealth of proteins that bind to carbohydrates. We therefore developed a novel dataset and neural network architecture, named **P**rotein **i**nteraction of **Ca**rbohydrates **P**redictor (PiCAP), to predict whether a protein non-covalently binds to a carbohydrate. We trained PiCAP on a dataset of known carbohydrate binders, and we selected proteins that we identified as likely *not* to bind carbohydrates, including DNA-binding transcription factors, cytoskeletal components, selected antibodies, and selected small-molecule-binding proteins. PiCAP achieves a 90% balanced accuracy on protein-level predictions of carbohydrate binding/non-binding. Using the same dataset, we developed a model named **Ca**rbohydrate **P**rotein **S**ite **I**denti**f**ier 2 (CAPSIF2) to predict protein residues that interact non-covalently with carbohydrates. CAPSIF2 achieves a Dice coefficient of 0.57 on residue-level predictions on our independent test dataset, outcompeting all previous models for this task. To demonstrate the biological applicability of PiCAP and CAPSIF2, we investigated cell surface proteins of human neural cells and further predicted the likelihood of three proteomes, notably *E. coli, M. musculus,* and *H. sapiens*, to bind to carbohydrates. PiCAP predicts that approximately 35-40% of proteins in these proteomes bind carbohydrates, indicating a substantial interplay of protein-carbohydrate interactions for cellular functionality.

Keywords

Glycan, carbohydrate, lectome, interactome, glycome, proteome

Significance Statement

The totality of carbohydrate-protein interactions remains elusive, in part due to the inability to test proteomes versus glycomes in a high throughput manner. Here we show the first high-throughput methodology to predict protein-carbohydrate interactions at proteomic scales by using structural and sequence information. This information will allow scientists to target predicted protein-carbohydrate interactions to better determine how the elusive carbohydrate biomolecules play roles in all cellular functions.

Introduction

In mammalian biology, carbohydrates are studied as two distinct families of molecules that are the focus of two disciplines. As metabolic precursors, from food or stored reserves, polysaccharides and monosaccharides (primarily glucose) are transported into and stored in the cytoplasm where they are subject to catabolic transformations to produce energy.[1] In contrast, distinct covalent groupings of varied monosaccharide building blocks covalently bound to proteins (glycoproteins and proteoglycans) and lipids (glycolipids) are relatively stable and are abundant at the cell surface and in the extracellular milieu.[2] A notable exception is O-GlcNAcylation, the reversible covalent attachment of the single sugar N-acetylglucosamine (GlcNAc) to serines and threonines of many cytoplasmic and nuclear proteins.[3]

Like their structures, the functions of carbohydrates are diverse. Among other functions they play essential roles in metabolism, they contribute to protein, cell and tissue structures, and they engage in molecular recognition upstream of cell-cell adhesion and cell regulation.[2] Most of these functions involve engagement of glycans by proteins.[4] These protein-carbohydrate interactions have predominantly been studied using chemical and biochemical methods, despite recent advances in the computational field.[5–7]

With the advent of the third generation of machine learning and large datasets, many novel algorithms have been created to better understand biophysical phenomena.[8,9] Deep learning methods have recently overtaken most traditional algorithms for all biomolecular methods on all biopolymers, including prediction of protein structure, protein-small molecule interactions, and *de novo* protein design.[10–14] Two of the largest computational steps in biophysics made recently are the releases of AlphaFold 2 (AF2)[10] and ESM[15]. AF2 revolutionized the protein structure landscape by creating a public, easily accessible, and accurate method for protein structure prediction. AF2 additionally predicted the protein structures of 48 organisms that are publicly accessible.[12] ESM (named for evolutionary scale modeling) revolutionized protein sequence representations through its transformer architecture, with ability to richly encode the language of protein sequences.[15]

Leveraging recent computational advances, scientists are beginning to explore the breadth of protein-carbohydrate interactions. We expect some of these protein-carbohydrate interactions to be involved in carbohydrate metabolism, some in intermolecular recognition and regulation of protein functions (e.g. O-GlcNAc), and others in cell adhesion and cell regulation. The goal of this work is to use computational advances to predict proteins amenable to carbohydrate binding, in its broadest interpretation. We use the term "lectome" to designate these proteins as a group, although here we identify proteins well beyond the original use of the term "lectin" on which it is based. The term lectin designates carbohydrate-binding proteins (other than antibodies), but excludes enzymes, carriers, or native sugar sensors. Here we computationally explore carbohydrate-binding

proteins without excluding them based on function; we expect to capture proteins across metabolic,
structural and molecular recognition functions. As discovery progresses, further sub-
characterization may be of value.
Recently we developed a dataset and two models, named CArbohydrate Protein Site
IdentiFier (CAPSIF):Graph and CAPSIF:Voxel, to predict the protein residues involved in
noncovalent carbohydrate-protein interactions.[16] CAPSIF:V and CAPSIF:G are trained and tested
on the same datset and use the same residue level encodings, but CAPSIF:V encodes proteins onto
a 3D voxelized grid with a UNet architecture whereas CAPSIF:G uses an equivariant graph neural
network (EGNN) message passing framework; CAPSIF:V slightly outperformed CAPSIF:G by
all measured metrics.
Since both CAPSIF models were released, two similar models have been created. Bibekar
et al. released Protein Structure Transformer (PeSTo)-Carbs, which uses a geometric transformer
architecture to predict residues involved in protein-carbohydrate interactions.[17,18] PeSTo-Carbs
employs a query-key-value attention mechanism with message passing across atoms that are then
pooled for residue-wise predictions.[17] He et al. released DeepGlycanSite, which leverages a
geometric message-passing architecture to predict a glycan binding site in both the case of a known
ligand and an unknown ligand.[18] PeSTo-Carbs modestly outperforms both CAPSIF models on all
reported metrics, whereas DeepGlycanSite focuses on binding to nucleotide structures as
compared to carbohydrate-only polymers.
Most carbohydrate-protein interaction algorithms rely on multiple datasets to extract
experimental coordinates for prediction.[16,17] Currently the standard protein-carbohydrate dataset is
UniLectin; however, UniLectin focuses only on proteins in the lectin family and thereby does not
include other carbohydrate binding proteins.[19] Recently, DIONYSUS was released detailing an
immense set of experimental carbohydrate binding proteins with non-covalently bound
carbohydrate as well as glycosylated proteins.[20]
Since experimentally solved structures can be difficult to obtain, especially in the presence
of a carbohydrate ligand, some datasets of sequences exist that identify carbohydrate binding
proteins. The Carbohydrate Active enZymes (CAZy) dataset identifies sequences of catalytically
active proteins that act on glycosidic bonds.[21] LectomeXplore is a dataset that identifies known
lectins, their associated structures (if known) and potential lectins as identified by sequence
similarity via a hidden Markov model (HMM).[22] Rather than limiting their work to known lectins,
Zhang et al. developed high throughput experiments with a ganglioside probe that identified 873
putative human proteins that likely interact with gangliosides.[23] These works are limited by their
scope, requiring either specific protein families or specific carbohydrate species to interact.
Here, we present novel frameworks to both predict whether a protein can bind to
carbohydrates and where on that protein the carbohydrate binds, entitled **P**rotein **i**nteraction of
CArbohydrate **P**redictor (PiCAP) and **CA**rbohydrate **P**rotein **S**ite **I**denti**F**ier **2** (CAPSIF2). Both
models leverage a large dataset with two training stages, first using all small molecule binding
interfaces and then fine tuning with carbohydrate-specific data. We assess the ability of these
models in their tasks. We then validate PiCAP against the work of Zhang et al.[23] and identify
potential outliers in their dataset. Finally, we use these models to make the first prediction of
carbohydrate binding proteins, and residues of these proteins, of three proteomes. While these first
proteome-wide predictions are likely noisy, they define the broad scope of the problem and invite
refinement by future experimental and computational methods.
124

Results

NoCAP: a novel non-binder dataset

Many datasets exist for protein-carbohydrate interactions, with the most notable being DIONYSUS (Table 1). However, there is no dataset of proteins that do *not* bind to carbohydrates; therefore, we developed a novel dataset consisting of proteins known to bind carbohydrates and proteins that likely do not bind carbohydrates based on biophysical intuition. Although the non-binder dataset is likely mildly contaminated with some currently unknown carbohydrate binding proteins, we believe this dataset to be generally representative of proteins that do not bind carbohydrates. We denote this novel combined dataset as Nonbinder and binder of CArbohydrate Protein interactions (NoCAP) (Table 1). In addition, we created a subset of NoCAP, named DIONYSUS-Residue (DR) as all binding proteins in NoCAP with a bound ligand, retaining the DIONYSUS name as most protein structures were retrieved from the DIONYSUS dataset (Table 1).

Table 1: Experimental structural datasets. Columns 2 and 3 indicate dataset inclusion in our NoCAP or DR datasets.

Dataset	NoCAP	DR	Description	n proteins
CAPSIF[16]	✓	✓	Bound protein-glycan complexes	802
TS 90	✓	✓	Test set for Pesto-Carbs; a subset of the CAPSIF test set	90
DIONYSUS[20]	✓	✓	Bound protein-glycan complexes	5,461
UniLectin[19]	✓		Lectin structures and sequences	2,881
ProGen[24]	✓		*De novo* designed lysozymes	69
Designed-NB[25]	✓	✓	List of crystal and complementary designed non-binders	2,800
SAbDab[26]	✓	✓	Crystalized antibodies to their antigen (filtered)	2,925
PDB-Bind[27]	✓	✓	Small molecule binders (filtered to remove carbs)	17,191
PDIDB[28]	✓		DNA-binding proteins (putative non-carb binders)	922
Manual selection	✓		Biophysically putative non-binding proteins (fatty acyl synthases, cytoskeletal components, flippases, ion transporters, ribosomal proteins)	606

CAPSIF2 outcompetes all previous models identifying carbohydrate-binding residues

We constructed an equivariant graph neural network (EGNN) named Carbohydrate Protein Site IdentiFier 2 (CAPSIF2) leveraging the same general architecture of our previous work CAPSIF:Graph (CAPSIF:G). Although CAPSIF:G underperformed CAPSIF:V, we chose the EGNN architecture because it is scalable to proteins of any size, while CAPSIF:V is limited by

149 the size of the underlying convolutional voxels. Although the dataset of this work (6,724 protein
150 structures) is substantially larger than our previous work (~800 protein structures), there is still an
151 intrinsic data imbalance in that most protein residues (~95%) do not bind carbohydrates. To
152 address this, we once again leveraged the Dice loss (Table 2) to emphasize the residues that bind
153 carbohydrates (see methods).
154
155 **Table 2**: **Average metrics for each deep learning architecture on test sets.** Dice coefficient is
156 described as 2TP / (2TP + FP + FN), where TP, FP, and FN are the counts of the true positives,
157 false positives, and false negatives, respectively. MCC is the Matthews correlation coefficient.
158 Boldface indicates the best performance for each metric.

Model	DR Dice	DR MCC	TS 90 Dice	TS 90 MCC
CAPSIF2	**0.573**	**0.574**	0.616	0.607
Pesto-Carbs	0.493	0.492	**0.638**	**0.624**
CAPSIF:V	0.226	0.202	0.608	0.622

Figure 1: Comparison of CAPSIF2 and PeSTo-Carbs on residue-wise prediction tasks. (A) Distribution of Dice coefficient across prediction targets (proteins) for CAPSIF2 (blue), PeSTo-Carbs (red), and CAPSIF:V (black) on the DR test set. Densities smoothed with a Gaussian kernel density estimate (KDE, bandwidth $h = 0.04$) . (B) Per-target comparison of CAPSIF2 to PeSTo-Carbs. (C) Side-by-side comparison of carbohydrate (yellow) bound proteins (gray) predictions by CAPSIF2 (blue, left) and PeSTo-Carbs (orange, right) on α-amylase (1BAG), SALT protein (5GVY), polyglucosamine subunit B (4P7R), and galactose binding lectin (5XFD). Per-target Dice coefficients shown below.

In Figure 1 and Table 2, we compare our results to PesTo-Carbs[17] and our previous model CAPSIF:V[16]. On the TS-90 test set, CAPSIF2 achieves 0.616 Dice and 0.607 MCC metrics and PesTo-Carbs outcompetes our model on this test set with a 0.638 Dice coefficient and 0.624 MCC (Table 2). Contrarily on the DR test set, CAPSIF2 achieves 0.573 Dice coefficient and 0.574 MCC, while PesTo-Carbs only achieves 0.493 Dice and 0.492 MCC metrics. On a per target basis,

CAPSIF2 performs greater than 0.15 Dice better than PesTo-Carbs on 40% of targets and PesTo-
Carbs performs greater than 0.15 Dice than CAPSIF2 on 15% of targets (Figure 1B).
We further show the results of specific targets in Figure 1C. In most of these cases, PesTo-
Carbs and CAPSIF2 can successfully find the binding region, with varying accuracy; however,
they both appear to fail on some targets, such as polyglucosamine B. This target notably has an
observable pocket in the center of the structure, which CAPSIF2 and PesTo-Carbs incorrectly
identifies as the binding region, wherein the experimentally solved oligosaccharide is proximal to
the pocket.

184 PiCAP accurately predicts carbohydrate binding and non-binding on
185 experimental structures

Leveraging the same foundational network structure as CAPSIF2, we constructed the
equivariant graph neural network (EGNN) named Protein interaction of Carbohydrate Predictor
(PiCAP) with five additional layers to yield a single value prediction of whether a protein does or
does not bind a carbohydrate. PiCAP assesses the spatial relationship of residues over an increasing
context window, pooling the sequence into a fixed size 2D image, and providing a singular
classification prediction based on that 2D representation. To our knowledge, PiCAP is the first DL
model to assess protein-noncovalent binding of carbohydrates at a protein level.
193

Table 3: Metrics for PiCAP on the NoCAP test set and associated subsets with the number of proteins in parentheses. BACC is balanced accuracy. TPR is True Positive Rate TPR = TP / (TP + FP). TNR is True Negative Rate TNR = TN / (TN + FN).

Test Set	Accuracy
NoCAP BACC (4,411)	0.896
NoCAP TPR (2,374)	0.963
NoCAP TNR (2,037)	0.828
TNR Ribosome (7)	1.0
TNR Holdout (92)	0.902
TPR ProGen Lysozymes (69)	0.841
TNR Designed Nonbinders (186)	0.608
Antibody BACC (50)	0.562

Figure 2: **T-distributed stochastic neighbor embedding (T-SNE) diagrams of the PiCAP final layer embeddings of the NoCAP test set**. (A) The randomly initialized model's final layer output. (B) The final trained model's final layer output.

We tested PiCAP on a holdout set based on sequence similarity, finding that PiCAP achieves an 89.6% balanced accuracy (BACC), with a 96.3% true positive rate (TPR) and 82.8% true negative rate (TNR) (Table 3). The ability to separate out carbohydrate binding (blue) and non-binding (red) proteins is further demonstrated in 2D t-distributed stochastic neighbor embedding (T-SNE) plots (Figure 2)[29]. Despite our best efforts, we do expect that the nonbinder dataset is likely contaminated with some carbohydrate binding proteins, therefore we must further discriminate PiCAP's ability to predict on specific test set subsets.

When inspecting subsets of NoCAP (Table 3), we find PiCAP correctly predicts all the protein chains of the ribosome assembly as non-binders. We further have a holdout set of multiple proteins from various protein families, consisting of fatty acyl synthases, actin, myosin, and flippases, where PiCAP achieves an encouraging 90.2% accuracy on this negative subset. We observed that PiCAP performed well on designed lysozymes from the ProGen language model[24] with an 84.1% accuracy. Contrarily, PiCAP achieves poor accuracy on computationally designed non-binder proteins, these being poor designs regarded as non-binding to the carbohydrate on the designed pocket, with an accuracy of only 60.8%. As a final test, we asked how our model performed on antibodies – specifically to identify antibodies that bind proteins or the glycans of

220   glycoproteins. Of the 50 tested antibody structures, PiCAP achieved a 79% TNR and 33% TPR
221   for a BACC of 56%. The antibodies and designed nonbinders are proteins hypervariably mutated
222   at the binding site for specificity, which has the poorest performance of PiCAP, whereas PiCAP
223   performs encouragingly on more evolutionarily and biologically defined proteins.
224

PiCAP agrees with LectomeXplore and experimental evidence

Our NoCAP dataset for training and testing PiCAP comprises *experimentally* solved
structures; therefore, we decided to investigate how our model performs on two datasets of
computationally predicted structures. The first dataset is LectomeXplore published by Bonnardel
et al., which identifies likely lectins across 37,794 organisms using a hidden Markov model
(HMM) based on sequence and structural similarity.[22] We also investigated the ganglioside
interactome as published by Zhang et al., where they developed a high throughput assay to identify
putative human proteins that interact with gangliosides.[23] Both of these datasets have only
sequence/UniProt gene IDs, therefore, for input into our algorithm, we used the predicted
structures of the AF2 model proteomes[12], only retaining confident segments of the structure
(pLDDT larger than 70).
236
237

238
Figure 3: PiCAP validation against computational datasets. (A) Plot of Zhang et al. identified
proteins across nine experiments alongside the fraction of proteins in each bin predicted as a
carbohydrate binder by PiCAP. (B) PiCAP and CAPSIF2 predictions of selected ganglioside
interactome proteins. The top row (blue) indicates proteins predicted as carbohydrate binders by
PiCAP and bottom row (red) as proteins predicted as non-binders by PiCAP with the number of
experiments the protein was identified by in parentheses. Highlighted residues in cyan (top
column) and red (bottom column) are the predicted binding regions by CAPSIF2.

LectomeXplore

The most closely related work to PiCAP is LectomeXplore, which identified putative
lectins through sequence and structure homology. Unlike LectomeXplore, PiCAP does not limit
proteins to be only of the lectin superfamily. We compared the likelihood of all predicted

LectomeXplore lectins (greater than 0.25 confidence) present in the AF2 reference proteomes of
two model species, *M. Musculus* and *H. Sapiens*, finding the agreement between the available AF2
structures of LectomeXplore and PiCAP to be 100% (225 of 225) for *M. Musculus* and 99.6% (229
of 230) for *H. Sapiens*. These results suggest a strong true positive rate (TPR) of PiCAP on the
simplest class of sugar binding proteins.

Ganglioside Interactome

Zhang et al. developed a high throughput method to identify proteins that interact with
gangliosides. They created ganglioside probes with photoaffinity tags that covalently linked the
probe to nearby proteins, and then they used mass spectroscopy and statistical methods to identify
those proteins. They used six different probes in two different cell lines (A431 and SH-SY5Y),
and for a total of nine experiments; we filtered the putative proteins by experiment. We selected
the top 250 proteins above background from each experiment and removed CRAPome proteins.[30]
This identified 873 unique proteins across all nine experiments.[23]. As a high throughput method,
and the first and largest of its kind, the error rates of their method have yet to be explored and
cross-validated across other experimental methods. We therefore will use PiCAP to investigate the
putative proteins of the ganglioside interactome work.
Of the 873 identified candidate ganglioside binding proteins, we were able to identify 848
proteins in the AF2 reference human proteome. PiCAP predicts 506 (60%) of these proteins as
carbohydrate binders. Further, PiCAP also predicts that 988 of 3,500 putative non-ganglioside
binding proteins (28%) as likely carbohydrate binders. Although these numbers at first suggest a
substantial disagreement between our works, we see a strong positive increase in the fraction of
proteins predicted as carbohydrate binders compared to the number of experiments that identified
a binding protein (Figure 3A).
To explore the agreement and disagreement between our experiments, we selected four
representative proteins: Frizzled-1 (FZD1), ATPase sarcoplasmic/endoplasmic reticulum Ca2+
transporting 2 (ATP2A2), transmembrane protein 164 (TMEM164), and mothers against
decapentaplegic homolog 4 (SMAD4). FZD1 is involved in the Wnt signalling pathway and was
identified by four of Zhang et al.'s experiments; PiCAP predicts FZD1 as a carbohydrate binder,
and FZD1 was a subject of close scrutiny in the ganglioside interactome work[23]. ATP2A2 is an
intracellular calcium/ATP pump and was identified by three experiments, and predicted as a
carbohydrate binding protein by PiCAP. ATP2A2 has a specific role in ATP-mediated transport
of calcium ions and likely little specific affinity for carbohydrates, let alone gangliosides[31].
TMEM164 is a regulator of ferropoptosis (iron mediated cell death) by an enzyme reaction with
polyunsaturated fatty acids (PUFA) and was identified by three experiments[32]. PiCAP disagrees
with the experimental results and predicts TMEM164 as a non-binder, which could indicate a
potential error in the experimental evidence. Finally, SMAD4 is a transcription factor[33], which was
identified to not interact with gangliosides in all experiments, where PiCAP agrees and predicts
the protein as a carbohydrate non-binder.
288

PiCAP and CAPSIF2 can predict putative proteome scale interactomes

290   With PiCAP validated to an acceptable level, we sought to understand the protein-
291   carbohydrate interactome with greater breadth than studied before. We chose three model
292   organisms from the AF2 proteome datasets[12], *E. coli*, *M. musculus,* and *H. sapiens*. Of the 4,363
293   proteins in the AF2 *E.coli* proteome, PiCAP yielded predictions on 4,339 accessible proteins and

predicted 1,677 (39%) proteins as carbohydrate binders. Of the 21,615 proteins in the AF2 *M. musculus* proteome, PiCAP yielded predictions on 21,304 proteins and predicts 8,177 (38%) proteins as carbohydrate binders. Of the 20,650 proteins in the AF2 *H. sapiens* proteome, PiCAP yielded predictions on 20,067 proteins and predicts 7,029 (35%) proteins as carbohydrate binders (Figure 4A). We further provide the results of three additional model species: *Drosophila*, *C. elegans*, and *S. cerevisiae* in the supplemental information, without detailed analysis. We further analyze proteins of unknown function from *E. Coli* in Figure S1.

Figure 4: PiCAP predictions of proteomes. (Top) comparison of the fraction of proteins predicted as carbohydrate binders by PiCAP across three proteomes. (Bottom) PiCAP and CAPSIF2 predictions of four selected human proteins.

Human Proteome

The primary proteome we analyzed was the AF2 human proteome (UP000005640), which contains 20,650 unique proteins with substantial resolution. PiCAP predicted 7,029, or 34%, of proteins to bind to carbohydrates. For comparison, the total number of lectins identified by LectomeXplore is 230, or 1.1% of the UniProt reference proteome[22], and the number known by CaZy is 349, or 1.7%[21]. In contrast, the number of proteins experimentally identified as likely to bind gangliosides, a unique glycan family, is 873, or 4.2%[23]. To reconcile the differences between our work and the work of many others, we spot checked PiCAP's predictions with several randomly selected proteins. We selected four proteins that appear representative of the distribution (Fig 4B).

PiCAP predicts sonic hedgehog (SHH), a protein implicated in cellular differentiation that can exist in the extracellular space to mediate the anterior-posterior axis, as a carbohydrate binding protein[34]. PiCAP additionally predicts pro-glucagon (GLUC) as a carbohydrate binding protein.

GLUC is a protein that becomes proteolyzed into constituent peptides, such as glucagon-like
peptide 1 (GLP-1), which stimulate glucose-dependent insulin release, which can be mimicked by
GLP-1 agonist pharmaceuticals such as dulaglutide (Trulicity) and semaglutide (Ozempic)[35].
PiCAP predicts E1 regulatory subunit 1 (ULA1), a protein that binds β-amyloid precursor protein,
as a non-binder[36]. PiCAP additionally predicts dynein axonemal protein (DYH6), a protein
implicated in microtubule-associated motor proteins, as a carbohydrate non-binder[37].

Discussion

We have demonstrated (1) an updated protein carbohydrate site identifier CAPSIF2 that
outcompetes all current models on a generalized dataset and (2) a novel model named PiCAP that
predicts *whether* a protein binds to carbohydrates or not. We validate our models against other
models and datasets and applied to proteome scale analysis to garner more information about the
protein-carbohydrate interactome.
CAPSIF2 boasts modest improvements in prediction accuracy on the original
CAPSIF/TS90 dataset compared to CAPSIF:G and CAPSIF:V, but it underperforms PesTo-Carbs.
CAPSIF2 however excels the most at a larger dataset containing ~1k structures with substantially
larger sequence variability, outcompeting all tested models. CAPSIF2 leverages a graph neural
network operating on residues, using the same foundational approach as CAPSIF:G, while
CAPSIF:V used a 3D voxelized CNN approach. PesTo-Carbs also leverages a graph neural
network approach; however, it operates at an atom-wise level and only pools to the residue level
late in the architecture. These graph architectures however have a similar level of parameters,
where CAPSIF:G has 236K parameters, CAPSIF2 has 1.6M parameters, and PesTo-Carbs has
1.1M parameters; while CAPSIF:V has substantially more with 102M parameters.
We believe that the differences in performance are primarily not attributable to the
architectures themselves, but rather the datasets. All models perform in a Matthews correlation
coefficient (MCC) range from 0.55 to 0.63; thus, we attribute the largest differences to the
stochastic training of these models and the slight variations in architectures. Structural protein-
carbohydrate datasets are limited currently by the size of the PDB, as these interactions must be
strong and stable to observe with experimental methods, where in physiology these interactions
are often guided by avidity over affinity and/or enzymatic activity on the carbohydrates
themselves. We believe larger datasets is only one part to improving these models, but improving
the datasets with manual interrogation of all structures and with the identification of continuous
biophysical pockets is necessary to improve the models' performance.
To improve carbohydrate-protein structural datasets and improve our general biological
understanding of the carbohydrate-protein interactome, we created PiCAP. PiCAP is the first
model of its kind as it predicts carbohydrate binding of proteins independent of family/function –
whether it be a cell surface protein for adhesion and communication or for metabolic enzymatics.
The dataset we used to train PiCAP primarily separates known carbohydrate binders and proteins
that are unlikely to bind to carbohydrates physiologically inside the cell – ranging from small
molecule binders to cytoskeletal components. Although this approach is imperfect, it is the first
attempt of this kind and leverages biophysical intuition of the cellular systems. Ultimately PiCAP
achieves 89.6% accuracy on the experimental dataset with 1.8M parameters. PiCAP predicts most
subsets of the test set with equivalent accuracy (designed lysozymes, cytoskeletal proteins,
flippases, and fatty acyl binding proteins); however, it proves notably worse on designed-non
binders and antibodies. The designed non-binders were created using Rosetta, where the binding

pocket itself was designed but the remainder of the protein remained untouched[25]. These designs
were labeled as non-binders by positive Rosetta binding energy scores – and never experimentally
expressed nor tested. In a similar vein, to bind carbohydrates, antibodies use their hypervariable
regions which are local regions that undergo somatic hypermutation. Our input to the protein is
ESM2 embeddings, which uses full sequence context to extract a large 1280-dimensional
embedding of each residue. As the ESM2 model is only trained and tested on biological proteins,
the signal specificity of the binding pocket sequence of the designed non-binders may be masked
by its more evolutionarily conserved residue, leading PiCAP to predict these non-biological
proteins as carbohydrate binders. PiCAP studies protein sequence and structural information
together, indicating PiCAP as a strong candidate for proteome wide studies of protein-
carbohydrate interactions.
Since PiCAP performed well on NoCAP data, we sought to validate the model against
other methods that predicted carbohydrate binders: the ganglioside interactome and
LectomeXplore. While we saw only 60% of proteins in the ganglioside interactome as positive,
after closely evaluating a subset of the data, we reconciled the difference with the error of the high
throughput experimental method. Although PiCAP appears to disagree with a good fraction of the
ganglioside dataset, it has a strong linear relationship with the high throughput experiments. The
more experiments that identified a protein, the higher likelihood that PiCAP predicted the protein
as a carbohydrate binder. We further observe strong agreement between LectomeXplore and
PiCAP, with an average of 95% agreement across three model species.
With experimental and computational validation, we then leveraged PiCAP against the
AF2 proteome datasets. PiCAP predicts 35~40% of all proteins in three biological model species
to be carbohydrate binding proteins – the highest prediction to date. As carbohydrates are
ubiquitous across all species and are the foundational building block of energy storage and integral
to most all extracellular communication, it is unsurprising for such a high fraction of proteins bind
to carbohydrates. PiCAP results can be further validated by proteomic evaluation by experiments
such as the pull-downs from Zhang et al.[23] or liquid glycan arrays[38,39]. The computational
predictions can help elucidate more functionality of proteins and provide a larger context to their
roles inside the cell and the suggestion of more protein moonlighting than previously understood.
Despite their biophysical importance in most all cellular functions, carbohydrates remain
elusive with few studies determining the exact extent of protein-carbohydrate interactions. Our
work expands to all proteins/carbohydrates in an agnostic manner that abstains from any limits on
protein family or carbohydrate species. We released the results of CAPSIF2 and PiCAP of six
model system proteomes for all proteins for open-source scientific use. Additional steps can now
be taken for the ultimate goals to design proteins to carbohydrate and glycoprotein targets for
therapeutic purposes. Firstly, we encourage the expansion of this work or LectinOracle[40] or
GlyNet[41] to predict carbohydrate species to all carbohydrate binding proteins. One simple step
would be to predict whether proteins bind to just a specific species of carbohydrate – such as
chitins or sialic acids. Another step would a high throughput computational docking of those
carbohydrate species to the identified proteins, using CAPSIF2 or PesTo-Carbs[17] or
DeepGlycanSite[18] to identify an initial hypothesis to feed GlycanDock[42], or directly *de novo* with
programs like DiffDock[13], RosettaFold-All Atom (RF-AA)[43], AlphaFold3[11], or Boltz-1[44]
(although there are currently no validation studies testing whether these methods provide high
accuracy on carbohydrate-specific docking).
In addition, all these methods leverage deep learning techniques. Deep learning methods
require multitudes of data, and although we were able to demonstrate impressive results on low

accuracy/messy data, we believe a clean dataset is integral and necessary for the future of this
field. A better annotated set of proteins that do not bind carbohydrates would be helpful, as well
as all structural proteins to have all ligands together, where currently there is a high redundancy in
protein structures with slightly different ligands or crystallization techniques, which reduce the
accuracy of the test metrics in comparing CAPSIF2 and PesTo-Carbs. We also believe tandem
experiments, such as those done by Zhang et al.[23] or selective exo-enzymatic labeling (SEEL)
glyco-engineering high throughput methods[45] to validate these models could further demonstrate
a larger wealth of carbohydrate binding proteins, alongside their specificity, allowing for further
annotation of the genome on a large scale.
419

Methods

Dataset

Carbohydrate-binding proteins were selected by combining multiple datasets. We selected
carbohydrate binding antibodies from SAbDab,[26] all experimentally solved proteins from
UniLectin[19] (with and without bound carbohydrates), the CAPSIF dataset,[16] and most notably, the
DIONYSUS dataset.[20] Further, we included the computationally designed and experimentally
viable lysozymes from ProGen,[24] with structures predicted by the Colab distribution of
AlphaFold2.[46]
There are several datasets of protein-carbohydrate interactions; however, there is no dataset
of proteins that do not bind to carbohydrates, so we constructed one (Table 1). In the creation of
such dataset, an intrinsic difficulty is that it is not possible to prove that a protein does not bind to
a carbohydrate of any kind; therefore, we selected proteins that biophysically have low likelihood
to bind to carbohydrates due to their function or location inside the cell. The experimentally solved
proteins selected were primarily chosen as small molecule binding proteins, DNA binding
proteins, nuclear pore complex proteins, serine proteases, cytoskeletal proteins, aminotransferases,
flippases, fatty acid binding proteins, selected antibodies (antibodies), and ribosomal proteins. In
addition to these proteins, Luo et al. computationally constructed a dataset of carbohydrate non-
binder proteins with the Rosetta software[25].
Small molecule data constitutes the largest portion of the non-binders (~18k pdbs), as we
used the PDB-Bind 2020 dataset.[27] Some proteins in the PDB-Bind dataset contain carbohydrates
as the ligand, in which case we identified those ligands using PyRosetta[47] and removed them from
the non-binder dataset and added them to the binder dataset. Antibodies were selected using the
SAbDab dataset by finding all proteins that were bound to proteins or nucleic acids and further
filtering to structures not containing any carbohydrates in the structure nor an NX(S/T) motif in
the antigen.[26] Ribosomal proteins were selected from the bacterial ribosome structure.[48] The
remainder of protein structures were selected by inspection from the RCSB PDB.[49]
After combining the datasets and adjusting for duplicate PDBs across different datasets,
the final NoCAP dataset contains 30,849 total unique protein structures. Of these structures, 9,608
bind to carbohydrates, with 6,724 having an experimentally bound carbohydrate. Of the 21,412
non carbohydrate binders, 17,191 have an experimentally resolved small molecule bound to it,
leaving 4,221 as nonbinders. To encourage generalizability to minor errors in structure predictions,
we also reconstructed the 12,021 shortest sequence proteins of the 30,849 with the Colab

implementation of AlphaFold 2[46], where we only kept the 11,042 of predicted structures with a
pLDDT greater than 80.
454

Preprocessing

With our dataset, we desired to leverage both sequence and structural information to predict
carbohydrate-binding capabilities of proteins. Family information of sequence similarity can
strongly indicate carbohydrate binding capabilities, while structural motifs can be present across
protein families for carbohydrate binding, and we desire our method to identify both. We extracted
the sequence and the Cβ positions of all protein residues (Cα for glycine) using PyRosetta.[47] Next,
we used ESM2[15] to provide a high-dimensional sequence embedding for each protein residue of
each protein chain. We labeled protein residues that were within 4.2 Å of a non-covalently bound
carbohydrate (or small molecule) as a binding residue.
Most previous work has used single protein chains for protein-carbohydrate
predictions[16,17]; however, many proteins only exist in the context of multiple chains. For this
reason, we preprocessed all protein structures with all chains in the PDB file, except the initial
CAPSIF dataset and antibodies. To limit the redundancy of the training set, we used MMseqs to
cluster protein sequences by 60% sequence identity into distinct clusters for training/testing.[50] We
then split the clusters into an 80/5/15 train/validation/test, maintaining the same proteins from
CAPSIF remain in the same dataset distribution. This left 24,957 structures in training, 1,479
structures for validation, and 4,413 structures for testing.

Secondary validation set

We have a primary dataset of carbohydrate-protein binding; however, we need to
demonstrate the ability of PiCAP to predict outside of the crystally solved structures. To do this,
we gathered all UniProt[51] accession codes from Zhang et al.[23] and LectomeXplore[22] and matched
them to the AF2 publicly accessible organism proteomes. This captured 848 of 878 (97%) of
putative ganglioside binding proteins and 3,400 of 4,335 (78%) of non-ganglioside binding
proteins. LectomeXplore uses sequence and structural protein information, alongside infectious
pathogens that affect these species, and lists all reference sequences and structures (UniProt,
ensembl, NCBI, RCSB, etc.) with severe redundancy. Therefore, for a direct quantitative
comparison, we therefore used only those that existed singly as UniProt values inside the reference
proteomes of AF2. We used the confidence metric of 0.25 for identification of lectins, which
yielded 230 human proteins and 225 mouse proteins.
For our proteome analysis, we used the AF2 publicly accessible organism proteomes.[12]
AF2 generates structures with an internal confidence metric called pLDDT, where low confidence
regions will have pLDDTs under 70. We therefore performed analysis and studies on AF2 protein
regions with high confidence, or residues with greater than 70 pLDDT, independent of structural
continuity. We applied the analysis to the following model organisms: *E. Coli, M. Musculus,* and
H. Sapiens. We further provide the results of the full-length sequence, independent of pLDDT in
Supplemental information alongside the results of three other model organisms: *C. elegans, D.*
melanogaster, and *S. cerevesia*.

Architectures

We fed the residue coordinates and sequence embeddings into the CAPSIF2 and PiCAP
architectures (Figure 1A) into the main model block, which uses a message passing equivariant

graph neural network (EGNN) of equivariant graph convolutional layers (EGCL).[52] Each layer
sums the outputs of a multilayer perceptron (MLP) that inputs the features of the central node and
the features of all of its neighboring nodes and the edge attributes of the neighbors. Following
Ingraham et al.[53], the edge attributes are a radial basis function (RBF) of the distance, the
orientation, and direction of the neighboring residues.

CAPSIF2, a carbohydrate binding residue predictor, has 12 residual ECGLs with an
embedding dimension of 128 (Figure 5). The neighborhood context window is fixed at the 16
nearest neighbors. After the graph convolutions, each residue is passed to a two-layer dense
decoder, finally outputting the carbohydrate-binding likelihood of each residue. CAPSIF2 contains
1,600,387 parameters.

PiCAP, a predictor of whether a protein binds to carbohydrates, has 12 total residual
EGCLs with an embedding dimension of 128 and leverages an increasing neighborhood context
window for information propagation, as inspired by PeSTo[54] and PeSTo-Carbs[17]. The first three
layers use the 10 nearest neighbors, layers 4 to 6 use the 20 nearest neighbors, layers 7 to 9 use 40
neighbors, and layers 10 to 12 use 60 neighbors. (Figure 5). The model specific block is a pooling
block that uses an adaptive pool to truncate or slightly expand the size of the protein to a fixed
length (150), where the model then uses two convolutional layers and three dense layers to predict
the likelihood of a protein to bind to carbohydrates. PiCAP contains 1,798,895 parameters.

514
515 **Figure 5: Architectures of CArbohydrate Protein Site IdentiFier 2 (CAPSIF2) and Protein**
516 **interaction of CArbohydrate Predictor (PiCAP).**

Training

We trained both models using two cycles: small molecule binding residue prediction and
the model specific task (protein or residue level predictions). The first training cycle used the
CAPSIF2 base architecture with randomized initial weights $\sim N(0,0.02)$ for the residue level
prediction. The model was trained for a maximum of 1,000 epochs, with training prematurely
stopped once the validation loss did not decrease after 35 epochs. This training cycle had a learning
rate of 2 x 10^{-6} and a weight decay of 10^{-7} with the Adam optimizer with the loss function $L =$
$1 - d$, where d is the Dice-Sorenson coefficient (also known as the F1 score) and a batch size of

1. To improve model generalization, each epoch sampled a single protein from every training cluster available from the small molecule dataset. The smallest 12,000 protein sequences were modeled structurally with the colab distribution of AF2,[10,46] and if the selected protein was available via AF2, we selected the crystal structure 40% of the time and the AF2 structure 60% of the time.

For the second training cycle, CAPSIF2 used the same architecture as the first training cycle and required no randomization. CAPSIF2 was trained only on proteins with experimentally determined carbohydrate binding sites with learning rate of 2×10^{-5} and weight decay of 10^{-6} with the Adam optimizer and the same loss function of $L = 1 - d$. Similar to the first training cycle, we randomly selected an available AF2 structure 60% of the time.

For the second training cycle, PiCAP used the weights where available from the first training iteration of CAPSIF2 and randomized weights for the model specific block $\sim N(0,0.02)$. PiCAP was trained on the entire training set for binary classification with a learning rate of 2×10^{-5} and weight decay of 10^{-6} with the Adam optimizer and binary cross entropy (BCE) loss function. Similar to the first training cycle, we randomly used an available AF2 structure 60% of the time.

Data Availability

Data, code, and datasets are available at Github, where CAPSIF2 and PiCAP can be run at: https://github.com/Graylab/picap. We further provide a webserver on ROSIE where CAPSIF2 and PiCAP can additionally be run: https://r2.graylab.jhu.edu/apps/index .

Author Contributions

S.W.C. conceived the project, performed the research, analyzed data, wrote the manuscript, and created all figures. R.L.S. supervised the project, analyzed data, and wrote the text. J.J.G. conceptualized and supervised the project, analyzed data, and wrote the text.

Funding

This work was supported by NIH R35-GM141881 (JJG and SWC), and NIH R01-AI162381 (JJG and SWC).

Acknowledgements

We thank Yijie Luo and Fabio Parmeggiani (Univeristy of Bristol) for the non-binder dataset. All model training and testing was performed on Johns Hopkins Advanced Research Computing at Hopkins (ARCH). We thank Sergey Lyskov for assisting in the implementation of the CAPSIF2 and PiCAP web server on ROSIE.

References

1. Chandel, N. S. Carbohydrate Metabolism. *Cold Spring Harb Perspect Biol* **13**, a040568 (2021).

2. Varki, A. *et al. Essentials of Glycobiology*. (Cold Spring Harbor Laboratory Press, Cold Spring Harbor, 2022).

3. Lazarus, M. B., Nam, Y., Jiang, J., Sliz, P. & Walker, S. Structure of human O-GlcNAc transferase and its complex with a peptide substrate. *Nature* **469**, 564–567 (2011).

4. Zhang, S., Chen, K. Y. & Zou, X. Carbohydrate-protein interactions: advances and challenges. *Commun Inf Syst* **21**, 147–163 (2021).

5. Kellman, B. P. *et al.* Decoding glycosylation potential from protein structure across human glycoproteins with a multi-view recurrent neural network. *bioRxiv* (2024) doi:10.1101/2024.05.15.594334.

6. Walklett, A. J. *et al.* The Retaining Pse5Ac7Ac Pseudaminyltransferase KpsS1 Defines a Previously Unreported glycosyltransferase family (GT118). *Angewandte Chemie International Edition* **63**, (2024).

7. Abdallah, A., Gillon, E., Rannou, P., Imberty, A. & Halila, S. Microwave-Assisted Synthesis of β- *N* -Aryl Glycoamphiphiles with Diverse Supramolecular Assemblies and Lectin Accessibility. *Bioconjug Chem* **35**, 1200–1206 (2024).

8. Canner, S. W., Feller, S. E. & Wassall, S. R. Molecular Organization of a Raft-like Domain in a Polyunsaturated Phospholipid Bilayer: A Supervised Machine Learning Analysis of Molecular Dynamics Simulations. *J Phys Chem B* **125**, 13158–13167 (2021).

9. Jänes, J. & Beltrao, P. Deep learning for protein structure prediction and design—progress and applications. *Mol Syst Biol* **20**, 162–169 (2024).

10. Jumper, J. *et al.* Highly accurate protein structure prediction with AlphaFold. *Nature* **596**, 583–589 (2021).

11. Abramson, J. *et al.* Accurate structure prediction of biomolecular interactions with AlphaFold 3. *Nature* **630**, 493–500 (2024).

12. Varadi, M. *et al.* AlphaFold Protein Structure Database in 2024: providing structure coverage for over 214 million protein sequences. *Nucleic Acids Res* **52**, D368–D375 (2024).

13. Corso, G., Stärk, H., Jing, B., Barzilay, R. & Jaakkola, T. DiffDock: Diffusion Steps, Twists, and Turns for Molecular Docking. *ICLR* (2023).

14. Zhang, F. *et al.* MetalNet2: an enhanced server for predicting metal-binding sites in proteomes. *Natl Sci Rev* **11**, (2024).

15. Lin, Z. *et al.* Evolutionary-scale prediction of atomic-level protein structure with a language model. *Science (1979)* **379**, 1123–1130 (2023).

16. Canner, S. W., Shanker, S. & Gray, J. J. Structure-based neural network protein–carbohydrate interaction predictions at the residue level. *Frontiers in Bioinformatics* **3**, (2023).

17. Bibekar, P., Krapp, L. & Peraro, M. D. PeSTo-Carbs: Geometric Deep Learning for Prediction of Protein–Carbohydrate Binding Interfaces. *J Chem Theory Comput* **20**, 2985–2991 (2024).

18. He, X. *et al.* Highly accurate carbohydrate-binding site prediction with DeepGlycanSite. *Nat Commun* **15**, 5163 (2024).

19.   Imberty, A., Bonnardel, F. & Lisacek, F. UniLectin, A One-Stop-Shop to Explore
and Study Carbohydrate-Binding Proteins. *Curr Protoc* **1**, (2021).

20.   Gheeraert, A. *et al.* DIONYSUS: a database of protein–carbohydrate interfaces. *Nucleic*
Acids Res (2024) doi:10.1093/nar/gkae890.

21.   Henrissat, B. A classification of glycosyl hydrolases based on amino acid sequence
similarities. *Biochem J* **280 (Pt 2)**, 309–16 (1991).

22.   Bonnardel, F., Mariethoz, J., Pérez, S., Imberty, A. & Lisacek, F. LectomeXplore, an
update of UniLectin for the discovery of carbohydrate-binding proteins based on a new
lectin classification. *Nucleic Acids Res* **49**, D1548–D1554 (2021).

23.   Zhang, G.-L. *et al.* The Human Ganglioside Interactome in Live Cells Revealed Using
Clickable Photoaffinity Ganglioside Probes. *J Am Chem Soc* **146**, 17801–17816 (2024).

24.   Madani, A. *et al.* Large language models generate functional protein sequences across
diverse families. *Nat Biotechnol* **41**, 1099–1106 (2023).

25.   Luo, Y. & Parmeggiani, F. CLIMBS: assessing Carbohydrate-Protein interactions through
a graph neural network classifier using synthetic negative data. Preprint at
https://doi.org/10.1101/2025.02.27.640667 (2025).

26.   Dunbar, J. *et al.* SAbDab: the structural antibody database. *Nucleic Acids Res* **42**, D1140–
D1146 (2014).

27.   Liu, Z. *et al.* Forging the Basis for Developing Protein–Ligand Interaction Scoring
Functions. *Acc Chem Res* **50**, 302–309 (2017).

28.   Norambuena, T. & Melo, F. The Protein-DNA Interface database. *BMC Bioinformatics*
11, 262 (2010).

29.   van der Maaten, L. & Hinton, G. Visualizing Data using t-SNE. *Journal of Machine*
Learning Research **9**, 2579–2605 (2008).

30.   Mellacheruvu, D. *et al.* The CRAPome: a contaminant repository for affinity purification–
mass spectrometry data. *Nat Methods* **10**, 730–736 (2013).

31.   Mikkelsen, S. A., Vangheluwe, P. & Andersen, J. P. A Darier disease mutation relieves
kinetic constraints imposed by the tail of sarco(endo)plasmic reticulum Ca2+-ATPase 2b.
Journal of Biological Chemistry **293**, 3880–3889 (2018).

32.   Reed, A., Ware, T., Li, H., Fernando Bazan, J. & Cravatt, B. F. TMEM164 is an
acyltransferase that forms ferroptotic C20:4 ether phospholipids. *Nat Chem Biol* **19**, 378–
388 (2023).

33.   Tan, X. *et al.* Loss of Smad4 promotes aggressive lung cancer metastasis by de-repression
of PAK3 via miRNA regulation. *Nat Commun* **12**, 4853 (2021).

34.   Carballo, G. B., Honorato, J. R., de Lopes, G. P. F. & Spohr, T. C. L. de S. e. A highlight
on Sonic hedgehog pathway. *Cell Communication and Signaling* **16**, 11 (2018).

35.   Alfaris, N. *et al.* GLP-1 single, dual, and triple receptor agonists for treating type 2
diabetes and obesity: a narrative review. *EClinicalMedicine* **75**, 102782 (2024).

36.   Muffels, I. J. J. *et al.* Bi-allelic variants in NAE1 cause intellectual disability, ischiopubic
hypoplasia, stress-mediated lymphopenia and neurodegeneration. *The American Journal*
of Human Genetics **110**, 146–160 (2023).

37.   Li, Y. *et al.* DNAH6 and Its Interactions with PCD Genes in Heterotaxy and Primary
Ciliary Dyskinesia. *PLoS Genet* **12**, e1005821 (2016).

38.   Lin, C.-L., Carpenter, E. J., Li, T., Ahmed, T. & Derda, R. Liquid Glycan Array. in 143–
159 (2024). doi:10.1007/978-1-0716-3798-2_10.

39. Lima, G. M. *et al.* The liquid lectin array detects compositional glycocalyx differences
using multivalent DNA-encoded lectins on phage. *Cell Chem Biol* (2024)
doi:10.1016/j.chembiol.2024.09.010.
40. Lundstrøm, J., Korhonen, E., Lisacek, F. & Bojar, D. LectinOracle: A Generalizable Deep
Learning Model for Lectin–Glycan Binding Prediction. *Advanced Science* **9**, (2022).
41. Carpenter, E. J., Seth, S., Yue, N., Greiner, R. & Derda, R. GlyNet: a multi-task neural
network for predicting protein–glycan interactions. *Chem Sci* **13**, 6669–6686 (2022).
42. Nance, M. L., Labonte, J. W., Adolf-Bryfogle, J. & Gray, J. J. Development and
Evaluation of GlycanDock: A Protein–Glycoligand Docking Refinement Algorithm in
Rosetta. *J Phys Chem B* **125**, 6807–6820 (2021).
43. Krishna, R. *et al.* Generalized biomolecular modeling and design with RoseTTAFold All-
Atom. *Science (1979)* **384**, (2024).
44. Wohlwend, J. *et al.* Boltz-1 Democratizing Biomolecular Interaction Modeling. Preprint at
https://doi.org/10.1101/2024.11.19.624167 (2024).
45. Babulic, J. L., De León González, F. V. & Capicciotti, C. J. Recent advances in
photoaffinity labeling strategies to capture Glycan–Protein interactions. *Curr Opin Chem*
Biol **80**, 102456 (2024).
46. Mirdita, M. *et al.* ColabFold: making protein folding accessible to all. *Nat Methods* **19**,
679–682 (2022).
47. Chaudhury, S., Lyskov, S. & Gray, J. J. PyRosetta: a script-based interface for
implementing molecular modeling algorithms using Rosetta. *Bioinformatics* **26**, 689–91
(2010).
48. Watson, Z. L. *et al.* Structure of the bacterial ribosome at 2 Å resolution. *Elife* **9**, (2020).
49. Berman, H. M. The Protein Data Bank. *Nucleic Acids Res* **28**, 235–242 (2000).
50. Hauser, M., Steinegger, M. & Söding, J. MMseqs software suite for fast and deep
clustering and searching of large protein sequence sets. *Bioinformatics* **32**, 1323–1330
(2016).
51. Bateman, A. *et al.* UniProt: the Universal Protein Knowledgebase in 2023. *Nucleic Acids*
Res **51**, D523–D531 (2023).
52. Satorras, V. G., Hoogeboom, E. & Welling, M. E(n) Equivariant Graph Neural Networks.
Proceedings of the 38 th International Conference on Machine Learning **139**, (2021).
53. Ingraham, J., Garg, V. K., Barzilay, R. & Jaakkola, T. Generative Models for Graph-
Based Protein Design. *Adv Neural Inf Process Syst* (2019).
54. Krapp, L. F., Abriata, L. A., Cortés Rodriguez, F. & Dal Peraro, M. PeSTo: parameter-
free geometric deep learning for accurate prediction of protein binding interfaces. *Nat*
Commun **14**, 2175 (2023).
685