Expectation management in humans and LLMs

Benjamin Menashe[1]*, Austin Drake[1], Michal Ben-Shachar[1]

[1]The Gonda Multidisciplinary Brain Research Center, Bar-Ilan University, Ramat-Gan, Israel
*Corresponding author. Contact: menashb@biu.ac.il
Additional contact: michalb@mail.biu.ac.il

Abstract

Mirative markers, such as "surprisingly", explicitly encode a violation of expectations. Such markers are used for expectation management during communication. Sensitivity to mirative markers relies on two abilities: i) updating expectations upon recognizing a mirative marker, and ii) identifying expectation violations warranting the use of a mirative marker. In this study, we compared sensitivity to mirative markers in humans and large language models (LLMs). In part 1, we used a sentence-completion task, where humans and LLMs were presented with sentence fragments and asked to continue them. Results show that for both humans and LLMs, the presence of a mirative marker significantly increased response entropy and decreased top-response probability, in line with theoretical accounts of mirative processing. In part 2, we created a novel task, mirative polarity selection, where humans and LLMs are presented with a sentence pair and asked to select whether it was connected by a mirative marker ("surprisingly") or an anti-mirative marker ("unsurprisingly"). Results show that LLMs perform at an impressive human-equivalent level. We conclude that both humans and LLMs use mirative markers as cues for calibrating their subsequent expectations during sentence processing.

Introduction

Humans constantly form expectations about upcoming stimuli[1,2]. Linguistic stimuli are no exception: it is well-demonstrated that humans use context and prior knowledge to form expectations and predictions about upcoming linguistic information, and then test those predictions against the actual upcoming input[3–5]. Encountering a violation of semantic expectations is associated with longer processing time[6–10], an elevated amplitude of the N400 event-related potential (ERP) component[11–14], and neural activation across many brain regions throughout the language network[15–19]. These results are in line with "predictive processing" theories of the brain, whereby such violations of expectations are regarded as prediction errors which the system attempts to minimize by calibrating expectations[20–23].

In natural discourse, speakers often attempt to manage their interlocutors' expectations explicitly, using *mirative markers*. Mirative markers are linguistic elements that encode violation of expectations[24–26], including words such as "surprisingly" and "remarkably". Mirative markers are widely used to inform about an upcoming unexpected message. In theory, such expectation management may help interlocutors avoid (or reduce) prediction errors and the associated increase in processing time and difficulty incurred by such errors.

In recent years, large language models (LLMs) have revolutionized the field of natural language processing. LLMs provide a probability estimate, for each token in their vocabulary, reflecting that likelihood that this token would follow a given sequence of text. Such predictions are based on exposure to enormous corpora of language, during training[39–42]. This process has been compared to forming expectations in humans, in what has been called a "shared computational principle of language comprehension"[43]. LLMs have been previously used to gain insight into human behavior[44,45] and neural activity[46–48].

This study investigates expectation management in humans and LLMs, by quantifying and comparing their sensitivity to mirative markers. Sensitivity to mirative markers relies on two abilities: i) updating expectations upon recognizing a mirative marker, and ii) identifying expectation violations warranting the use of a mirative marker. Comparing humans and LLMs serves two purposes: first, if LLMs demonstrate a similar sensitivity to mirative markers as humans, LLMs could serve as efficient "test subjects" for future explorations of expectation management. Second, expectation management is theorized to be a byproduct of predictive processing, as it is hypothesized to reduce prediction error. Since humans and LLMs both form predictions during discourse (while being otherwise radically

different), observing emergent expectation management in LLMs would provide evidence that it is a

byproduct of predictive communication systems.

Mirativity is considered to be a language-universal category[24]. It can be marked using words (e.g.,

"surprisingly"), exclamatory particles or intonation (e.g., "Wow!"), or, in some languages, by specialized

morphological affixes[27]. Conversely, a confirmation of expectations can also be marked using words such

as "unsurprisingly" and "expectedly", which we refer to as *anti-mirative markers*. According to linguistic

theory, mirative markers are licensed only when there exists a more expected proposition that is false[28].

This implies that mirative markers modify expectations by decreasing the probability of the most-

expected upcoming stimuli and increasing the probability of lesser-expected upcoming stimuli. Such a

process is referred to as *domain widening*, whereby the domain of plausible upcoming stimuli is

expanded to include lesser-expected stimuli[29,30]. We propose that this is effectively equivalent to an

increase in the entropy of the distribution of expectations (a quantitative measure of uncertainty[31]). The

effects of increased entropy on human behavior and neural activity have been studied extensively[32–36].

Two previous studies that addressed the neural effects of expectation-disconfirming markers, both using

ERPs, report conflicting results. In the first study[37], participants read scenarios containing unexpected

target words, which were preceded by the discourse marker "even so" on half the trials. Results showed

that the presence of "even-so" attenuated the amplitude of the N400 component for otherwise

unexpected target words. In a later study[38], participants read dialogues in Dutch with unexpected

endings, which were preceded by the discourse marker "eigenlijk" ("actually") on half the trials. Results

showed no evidence for a main effect of discourse marker on the N400 amplitude, nor an interaction

effect of the discourse marker and predictability on the N400 amplitude. As such, there is currently only

limited and conflicting empirical evidence on processing mirative markers and subsequent expectation

modification.

In part 1 of this paper, we studied how mirative markers modify expectations. We used a sentence-

completion task, where human participants and LLMs were presented with sentence fragments and

asked to continue them. We manipulated the sentences to begin either with a mirative marker or a

neutral marker, and compared the respective responses. Since a mirative marker indicates an upcoming

violation of expectations, we predicted that it would lead to a decrease in the probability of the most-

expected response and to a general increase in the probability of lesser-expected responses, leading to

an overall increase in the entropy of responses, for both humans and LLMs. In part 2, we studied

whether LLMs identify violations of expectations to the same level as human participants do. We

created a novel task, *mirative polarity selection*, where human participants and LLMs are presented with

a sentence pair and asked to select whether it was connected by a mirative marker or by an anti-

mirative marker. We predicted humans would perform well on the task, and that LLMs would perform

near or at a human-equivalent level, in line with the performance of LLMs on theory-of-mind tasks[51].

Altogether, the two tasks allowed us to examine the core conditions required for successful expectation

management using mirative markers: their ability to modify subsequent expectations appropriately and

the capacity to deploy them in appropriate contexts.

Results

Part 1: Increased entropy in response to mirative markers

Using a sentence-completion task, we tested how the presence of a mirative marker ("surprisingly") at

the beginning of a sentence fragment, compared to a neutral marker ("yesterday"), affects expectations

for upcoming words. We tested human participants using an online questionnaire that contained thirty

novel sentence fragments. We then tested the Meta-Llama-3/3.1/3.2 series of LLMs on the same

sentence fragments.

In human participants, we found that the inclusion of a mirative marker in the beginning of a sentence

fragment resulted in a significant *decrease* in the probability of the most common response to the

neutral marker (t_{28} = −6.85, p<.001, Fig. 1A), and a significant *increase* in the entropy of the response

distributions (t_{28} = 5.58, p<.001, Fig. 1B. See also Fig. 1C for an example of response distributions). In

LLMs, similarly to human participants, mirative markers evoked a significant decrease in probability of

the top response (see Fig. 1D for an example LLM and Supplementary Table S1 for the full statistics of all

LLMs tested). Moreover, the entropy of the response distribution following a mirative marker increased

for all LLMs, although this increase was significant in only three of the six LLMs tested (Llama-3-8B,

Llama-3.1-8B, Llama-3.2-3B; See Fig. 1E for an example LLM). A visual inspection of the top 10K tokens

suggested that mirative markers decreased the probability of the top 10-20 tokens and increased the

probability of the rest of the tokens (Fig. 1F). Taken together, this provides evidence that humans and

LLMs process the mirative marker as an indicator for an upcoming violation of expectation, and both

humans and LLMs modify their expectations accordingly.

In a follow-up analysis, we generated 1,365 text fragments of varying lengths taken from the Provo

corpus[49]. We defined a "window of altered expectations" as the location and range of the increased

entropy due to the presence of a mirative marker. The distance from the mirative marker was measured

by number of sentences using a linear mixed-effects regression, and separately by number of words

using a spline regression. Results from both methods converge to show that the window of altered

expectations extends up to 2 sentences ahead (Fig. 2A) and approximately 5-40 words ahead (Fig. 2B,

see also Supplementary Table S2 for the full statistics). This suggests that mirative markers have a

limited window in which the violation of expectations is anticipated to occur.

In a linear mixed-effects model predicting the increased entropy by the POS of the most-expected word,

all POS showed a significant increase in entropy and no significant difference was found between

content words and function words (t_{830} = 0.38, p=.705, Fig. 2C). Additionally, we wanted to check if

mirative markers modify expectations differently for different levels of contextual constraint, measured

by the entropy in the neutral condition. No correlation was found between the level of contextual

constraint and the increase in entropy in the mirative condition (standardized correlation coefficient =

−0.010, p=.774, Fig. 2D). This suggests that the addition of a mirative marker generally results in an

increase in entropy, regardless of the level of contextual constraint. Importantly, this also shows that the

increase in entropy is not due to regression to the mean.

134
Figure 2. Mirative markers increase entropy. We used an LLM (Meta-Llama-3.1-8B) to quantify the entropy following each
word in 1,365 text fragments taken from the Provo corpus (Luke & Christianson, 2018). Texts began either neutrally, i.e., as
they were in the corpus, or with a mirative marker ("surprisingly"). All plots show the difference in entropy between the
mirative and the neutral condition, per word. **A)** Entropy difference per sentence number. Black dots show the estimated
means from a linear mixed-effects model. Error bars show the 95% confidence interval (CI). Outliers above (n=51) and below
(n=38) the y-axis range are not shown but were included in the model. **B)** Entropy difference by the word's distance from the
mirative marker. Black line shows the locally estimated scatterplot smoothing (LOESS) with span=20 over the entropy difference
of all words. The gray surface around the black line shows the 95% CI. Outliers above (n=51) and below (n=38) the y-axis range
are not shown but were included in the locally estimated scatterplot smoothing model. **C)** Entropy difference for each predicted
token, categorized by part-of-speech. Black icons show the estimated means from a linear mixed-effects model fit separately
for each part-of-speech, with squares for content words and diamonds for function words. Error bars show the 95% CI. Outliers
above (n=26) and below (n=17) the y-axis range are not shown but were included in the model. **D)** Entropy difference by the
entropy in the neutral condition. Black line shows the estimated trendline from a linear mixed-effects model. The gray surface
around the black line shows the 95% CI. Outliers above (n=26) and below (n=17) the y-axis range are not shown but were
included in the model. *** p<.001, n.s. not significant.

Part 2: Identifying expectation violations

We tested human and LLM performance in identifying violations of expectation. For that, we devised a novel "mirative polarity selection" task. Participants and LLMs were presented with a sentence pair and asked to select whether it was connected with a mirative marker ("surprisingly") or an anti-mirative marker ("unsurprisingly"). Sentence pairs were sampled from the Discovery dataset[50], and were originally connected by one of the markers in the corpus (this constitutes the correct response). We tested human participants using an online questionnaire, and we used the Meta-Llama-3/3.1/3.2-instruct series and the chatGPT-3.5/4/4o series of LLMs.

Human mean accuracy on the mirative polarity selection task was 75.5% ± 1%. Participant performance varied widely (Fig. 3B), ranging between 46.7% to 90%. This suggests high variability in the participants' ability to identify violations of expectations. Participant agreement on the responses was fair (percent agreement: 68.2%, Gwet's AC1: 0.376, significantly better than chance agreement, p<.001). The relatively low level of mean accuracy and agreement may reflect the natural stimuli we used, as the sentence pairs may not have contained sufficient information for selecting the correct marker (see Supplementary Table S5 for examples with low human accuracy). Thus, we take the mean human accuracy and the top human accuracy as tentative benchmarks for this task.

LLM task performance varied, with some models approaching and some exceeding mean human performance (see Supplementary Table S3 for the full statistics, and Fig. 3C for a comparison between human performance and selected LLMs). Within the Meta-Llama series, Llama-3-8B-Instruct and Llama-3.1-8B-Instruct performed well above chance but still below human level. The newer Llama-3.2 models both performed at a chance level. This result may be due to their smaller number of parameters. Within the chatGPT series, GPT-3.5 performed above chance level but below human level, GPT-4 performed at human level, and GPT-4o performed above the mean human level and near the top human level. GPT-4o-mini saw a drop in performance, which may also be due to its smaller number of parameters (see Table S3). A stricter measure of accuracy is the joint order accuracy, where LLM responses were considered correct only if they selected the correct label twice for a given sentence pair (once for each choice order presented). LLM performance as measured by joint order accuracy was lower than model accuracy for all models, although many models still performed above chance level and GPT-4o still performed at an impressive mean human level (see Supplementary Table S3 for the full statistics).

To examine whether the high accuracy of LLMs reflects their ability to identify expectation violations or

some other variable, we measured the discriminability of the sentence pairs using several simple

variables. Discriminability, measured using area under the curve (AUC), was very poor for most of the

variables checked (second sentence length: 0.462, perplexity: 0.492, max surprisal: 0.546, similarity:

0.495, question: 0.508, negativity: 0.558). One exception was the length of the first sentence: anti-

mirative markers tended to be preceded by longer sentences as compared to mirative markers (AUC =

0.647, see Fig. 3D for the ROC of the various criteria). However, discriminability based on the length of

the first sentence is still not sufficient to explain the performance of the better performing LLMs, as the

classification accuracy at the optimal threshold was only 61.4%. Moreover, the length of the first

sentence was not a significant predictor of the LLM response for the errors the LLMs made (using a

logistic regression with a covariate for stimulus label, $p > .42$ for all LLMs). This supports the claim that

LLMs succeed in mirative polarity selection due to some form of sensitivity to mirativity.

To further assess this claim, we tested LLM performance on manipulated versions of the stimuli,

presenting just the first or just the second sentence of the pair. LLM performance decreased

substantially in both conditions (Fig. 3E, see Supplementary Table S4 for the full statistics). This also

suggests that LLM performance is not due to data contamination (where the model was trained on the

stimuli and thus was "supervised" for the correct label), as even one sentence is unique enough to allow

retrieval of the appropriate connector if the testing data was memorized. Next, we presented LLMs with

sentence pairs where the first and second sentence were randomly shuffled between pairs within the

same label (mirative or anti-mirative). The goal of this condition was to eliminate the semantic relation

between sentences within each pair, while preserving other global properties (e.g., possible syntactic

structure, common function words, register, sentiment…) which might differ between labels. LLM

performance decreased substantially on this condition as well (Fig. 3E, see Supplementary Table S4 for

the full statistics). This shows that LLM performance is tied to the semantic information in the sentence

pair, most likely the occurrence of an expectation violation (or confirmation). Altogether, results from

the manipulated stimulus conditions support the view that LLMs succeed in the original task due to

some form of sensitivity to mirativity, not due to data contamination or sensitivity to other properties of

the stimuli.

Mirative bias: Participants tended to select the mirative marker slightly more than the anti-mirative

marker, although this difference was not significant ($p = .055$). Importantly, the mirative marker

"surprisingly" is an order of magnitude more frequent than the anti-mirative marker "unsurprisingly" in

natural corpora (the Zipf frequency of "surprisingly" is 4.09, compared to 3.01 for "unsurprisingly",

resulting in a frequency ratio of 12.02 to one; these estimates were retrieved using the *wordfreq* python

library[52]). This suggests that some mirative bias may be expected if the base frequency of the markers is

taken into account when selecting the markers. Of the LLMs which performed above chance level,

different tendencies were observed: Llama-3-8B-Instruct and Llama-3.1-8B-Instruct displayed a

significant bias towards selecting the mirative marker (p<.001), GPT-4o was not significantly biased

towards any label (p=.378), and GPT-4 was significantly biased to select the anti-mirative marker

(p<.001, Fig. 3F, see Supplementary Table S3 for the coefficient values). Overall, the different bias

tendencies suggest that while some LLMs perform at or above human level, they likely do so through

different processes than humans (and of other LLMs).

Order bias: LLMs also differed from human participants in their sensitivity to the order of the choices

presented (Fig. 3G, see Supplementary Table S3 for the coefficient values). In humans, no significant

effect of order was found when estimating using all human participants (N=63; coefficient = -0.02 ± 0.1,

p=.880) or when only using the subset of participants (N=22) who were presented with both orders

(coefficient = 0.10 ± 0.2, p=.513). In contrast, all LLMs displayed a significant order bias: Llama-3-8B-

Instruct and Llama-3.1-8B-Instruct were more likely to select the first choice presented (p<.001), GPT-4o

was also more likely to select the first choice presented albeit to a lesser degree (p=.004), and GPT-4

was more likely to select the last choice presented (p<.001). This is consistent with previous reports of

order biases in LLMs[53,54]. The fact that LLMs, but not humans, display an order bias in this task further

supports the idea that LLMs do not attain their high accuracy in a similar way to humans.

Figure 3. LLMs achieve near human performance on mirative-polarity selection. Mirative-polarity selection is a novel task where participants and LLMs are presented with a sentence pair and asked to select whether it was connected with a mirative marker ("surprisingly") or an anti-mirative marker ("unsurprisingly"). We used 1000 sentence pairs (500 per marker) from the Discovery dataset (Sileo et al., 2019). Human participants were presented with 60 randomly selected stimuli (30 per marker). **A)** Example stimulus, presented in a mirative-first order. The correct choice is the mirative marker ("surprisingly, they have menus in English"). **B)** Distribution of human accuracy levels in the mirative-polarity selection task. **C)** Accuracy levels achieved by human participants and several LLMs. Choice order with the mirative marker presented first is shown in light blue, and the reverse choice order, with the anti-mirative marker presented first, is shown in dark blue. Error bars indicate a 95% CI for human performance levels. **D)** Area under the curve (AUC) for several discrimination criteria are all close to chance level. Criteria include: length of first or second sentence in tokens, the perplexity and the max surprisal of the second sentence, the cosine similarity between the sentences, whether the first sentence is a question, and the presence of negation in any of the sentences. **E)** LLM mean performance on several conditions of manipulated stimuli. Sentence 1: LLMs were presented with the first sentence only and asked to select which marker, mirative or anti-mirative, is most likely to follow it. Sentence 2: similar manipulation, presenting only the second sentence and asking which marker is likely to precede it. Shuffled: LLMs were presented with random combinations of first and second sentences of different pairs. **F-G)** Mirative bias and choice-order bias estimates, per model, obtained using logistic mixed-effects models. **F)** Mirative bias: positive values suggest a higher probability of selecting the mirative marker over the anti-mirative marker, and negative values vice versa. **G)** Order bias: positive values suggest a higher probability of selecting the second choice presented over the first, and negative values vice versa. Error bars show the 95% CI. [n.s.] not significant. ** p<0.01. *** p<.001.

General discussion

In this study, we assessed sensitivity to mirativity in both human participants and LLMs. We measured how the presence of a mirative marker ("surprisingly") affects subsequent expectations, and whether humans and LLMs are able to detect expectation violations warranting the use of a mirative marker.

Results from a sentence-completion task show that both humans and LLMs use mirative markers as an

indication of an upcoming expectation violation. Results from the mirative-polarity selection task show

that both humans and the best-performing LLMs display a similar level of sensitivity to mirativity.

Within "predictive processing" theories[20,22], there is a clear advantage for giving a warning signal prior to

an expectation violation, which allows a preemptive modification of expectations, thus reducing the

would-be prediction error. Within linguistic pragmatic theory, Grice's cooperative principle of

communication asserts that speakers aim to help their interlocutors process the conveyed message[55].

Along these lines, a speaker may use a mirative marker as part of the cooperative principle to help their

interlocutor reduce their prediction error for an upcoming unexpected message. Thus, sensitivity to

mirativity can provide an advantage for more efficient processing of information. Further studies can

directly test this claim by measuring the effect of mirative markers on behavioral and neural correlates

of prediction error.

As shown in part 1, human participants modified expectations upon encountering a mirative marker, as

did LLMs. The expectation modification involved a reduction (but not an elimination) in the probability

of the most-expected response, and an increase in entropy. The reduction in probability of the most-

expected response is easily explained, as the literal meaning of mirative markers such as "surprisingly" is

that the current message is not the most-expected one[30,28]. The increase in entropy can be interpreted

as a general increase in the uncertainty as to the identity of the next upcoming word. This is because,

while mirative markers signal an upcoming expectation violation, they do not specify the content of the

violation, leading the interlocutor to increase their expectations for many different upcoming words, all

of which violate expectations. Additionally, mirative markers do not specify the exact location of the

upcoming expectation violation (only that it will appear soon). During word-by-word prediction, this

prevents the interlocutor from discounting highly expected words, since the violation could appear later

on. Instead, it leads to *domain widening*, where the set of plausible next words expands while

preserving the most-expected words[29,30]. Domain widening is congruent with the increase in entropy

observed. Moreover, when comparing the top tokens of the LLM responses, overall token rankings

remained stable but the probability decreased for the top 10-20 tokens and increased for the rest of the

tokens. This supports the notion that uncertainty about the location and identity of the expectation

violation leads to expanded expectations when predicting the next word.

In a follow-up analysis, we investigated factors that influence the change in expectations following a

mirative marker using a large number of sentence fragments, in LLMs only. Using language models for

measuring predictability and entropy of expectations is a standard method that can produce hypotheses

regarding the human performance[56,45,43]. Results show a "window of altered expectations" (where

mirative markers led to increased entropy in next word predictions) extending approximately two

sentences or 5-40 words ahead. Notably, the stimuli were not designed to contain expectation

violations, as the Provo corpus passages were taken from a variety of sources (e.g., news articles,

popular science magazines) designed for naturalistic reading[49], to which we added, artificially, a

preceding mirative marker. We theorize that, in natural settings, mirative markers may alter

expectations until encountering a violation, which is likely to occur within two sentences. The entropy

increase was of similar magnitude for expected content words and function words. For example, for the

sentence fragment "All that the brain has to work with are ___", the most-expected token was "the",

which is a function word (a determiner). When preceded by the mirative marker "surprisingly", entropy

nonetheless increased, although the word "the" is not related to the semantic content of the message.

This result may be because less-expected content words remain possible in such positions (for example,

"neurons"), or because mirative markers create a general uncertainty in expectations. Since our human

experiments were designed to elicit nouns, we are not able to assess conclusively the effect of word

type (content or function word) and POS in human participants. Furthermore, entropy increase was

independent of the availability of semantically constraining context. The fact that even lower-

constraining sentence fragments produced an increase in entropy when preceded by a mirative marker

suggests that mirative markers alter expectations at all levels, even weakly held ones. Additionally, this

affirms that the increase in entropy is not due to regression to the mean (where extreme values of

entropy would have become more moderate).

As shown in part 2, LLMs reached human performance level in selecting the mirative marker as the

appropriate connector between a pair of sentences. Identifying if a sentence pair contains a violation of

expectations is complex and requires several cognitive abilities: reading comprehension, detecting

(often implicit) expectations by applying world knowledge and theory-of-mind in context, and

recognizing mismatches between the expectations and the actual message. Thus, success on the task is

far from trivial. Human performance varied considerably, ranging from chance level to 90% accuracy.

This could reflect individual differences in the ability to detect expectation violations. It could also reflect

differences in the specific expectations people form due to different life experiences, which would lead

some to judge that a certain message contains a violation of expectations while others would disagree

(but notice that the inter-subject agreement was around 68%, significantly above chance). It could also

reflect the possibility that human participants differed in the level of attention and task engagement.

LLMs performed impressively, reaching and exceeding average human level (although still below top

human performers). A possible concern is that the stimuli used, taken from the internet, could have

been in the training data for the LLMs we tested ("data contamination"). This is unlikely for several

reasons: (a) LLM performance is at human-average rather than at ceiling level, (b) LLM's accuracy

dropped when tested on the first or second sentence only (which are sufficient by their own for

retrieving a memorized sequence), and (c) the order of the options influenced LLM selection

systematically, which is unexpected if the LLM is operating based on memorized examples. An AUC

analysis did not reveal any superficial variable that could be used to perform the task (e.g., sentence

length, see Fig. 3D). Moreover, performance dropped when sentence pairs were shuffled, ruling out

some non-semantic property of the stimuli that the LLMs could have used to classify them. Additionally,

a supplementary analysis revealed that the presence of a mirative marker affected LLMs' responses in a

common-sense reasoning task where detecting expectation violations is involved, but not in a

vocabulary task where detecting expectation violations is irrelevant for task performance (see

Supplementary Fig. S1 in Supplementary Materials). Taken together, this evidence suggests that the

success of LLMs in performing the mirative polarity selection task is likely due to their ability to identify

expectation violations, which is a core part of sensitivity to mirativity.

The astounding breakthrough success of LLMs in recent years has raised questions about their ability to

construct a world model[57,58] and a theory-of-mind[59,51,60]. A world model can be defined as an internal

representation of the properties and causal dynamics of the physical world. Theory-of-mind can be

defined as a model of the mental states of another agent, including their beliefs and expectations.

Success in the mirative polarity selection task requires a basic level of both a world model and a theory-

of-mind, because, in order to identify what would constitute an expectation violation, one must first

have a good approximation of the expectation formed by their interlocutor. There is ample evidence

showing that humans possess an understanding of "folk physics", even at a young age[61–63]. Thus, a world

model is helpful in informing the speaker about what their interlocutor expects to happen, under

normal circumstances. In an example stimulus, such as: "I saw the issue. Surprisingly/Unsurprisingly, it

was easy to fix", to correctly select the mirative marker ("surprisingly"), one must first have a world

model wherein issues are usually difficult to fix, and second, use their theory-of-mind to understand that

their interlocutor would also expect the issue to be difficult to fix. The success of LLMs on the task

suggests that LLMs may have some sort of a functioning theory-of-mind and informative world model

(albeit not necessarily similar in representation to humans), or at least that they display behaviors which

would make it appear as though they have them. While this study did not aim to assess the extent,

robustness, and human-likeness of the theory-of-mind and world models that LLMs may or may not

possess, the performance of LLMs in this study provides some initial evidence for such capabilities,

which future studies can assess and quantify.

As noted previously, LLMs displayed different biases than humans in the mirative polarity selection task.

Humans showed a small but non-significant preference towards selecting mirative markers (over anti-

mirative markers). On the other hand, Meta-Llama models showed a significant mirative preference,

GPT-4 showed a significant anti-mirative preference, and GPT-4o showed no preference. Bayesian

inference can explain the mirative bias (in humans and Meta-Llama models): when the stimulus lacks

sufficient information to determine its label, prior knowledge must be used instead, and the base

frequency of "surprisingly" is substantially higher than "unsurprisingly" in natural language. Another

source of bias observed in LLMs (but not in humans) was the presentation order of choices, in line with

previous research[53,54]. Whether considering all participants or only the subset of participants who

completed the task under both choice orders (within-subject analysis), no significant order bias was

found in humans. In contrast, the Meta-Llama models and GPT-4o displayed a significant preference

towards the first choice presented, and GPT-4 displayed a significant preference towards the last choice

presented. The combination of a last-choice bias and an anti-mirative bias renders GPT-4 as particularly

un-human-like in this task. The biases exhibited by LLMs suggest that although LLMs achieve comparable

accuracy to humans, they arrive at their response through a different underlying process.

Limitations

This study has several limitations. First, there are several known drawbacks of using online

questionnaires administered through the internet. Although participants were instructed to dedicate 20

minutes of their time and complete the tasks in an environment free from distractions, there is no way

to verify that this occurred. Nonetheless, participants' responses in the sentence-completion task

showed no indication of randomly typing words or misreading the sentence fragments, and participants'

performance on the mirative-polarity selection task was high. This suggests that, overall, participants

were engaged with the tasks.

Another limitation is that, in the mirative-polarity selection task, we assumed that each stimulus

contains an expectation violation (or confirmation, for the anti-mirative label). This assumption is

somewhat justified since the stimuli were naturally produced, but there is no way to independently

verify this. Moreover, since the stimuli were sampled from the internet, the identity of their authors

(and relevant information such as whether they are fluent English speakers) is unknown, although we

did select stimuli that appeared well-formed and contained no clear misspellings. We take top human

performance (90% accuracy) as a tentative approximation that 90% of the stimuli were discernible in

nature and thus contained an expectation violation or confirmation.

Finally, in this study, we treated the presence of a mirative marker as a sincere indicator of a violation of

expectations. However, in natural text, sarcasm allows speakers to use markers to convey their opposite

meaning[64]. While we believe this usage is rare, we cannot discount the possibility of human participants

or LLMs treating the mirative marker (or the anti-mirative marker) as sarcastic, which may add noise to

our measurements.

Conclusions

This study researched the sensitivity of humans and LLMs to mirativity, the explicit marking of

expectation violations. The two parts of this study can be viewed as investigating the two sides of

discourse: the receiver of a textual message and the transmitter of the message. In Part 1, we examined

expectation modification after a mirative marker is encountered, which is analogous to the receiving

end of discourse. In Part 2, we examined the selection between mirative and anti-mirative connectors

for a given sentence pair, which is analogous to producing and transmitting a message, and signaling the

level of unexpectedness of a message (in context) to the receiver. We found that both humans and LLMs

use mirative markers as cues for calibrating their subsequent expectations during sentence processing,

and both humans and LLMs accurately identify when mirative markers are appropriate, albeit with

different biases. Together, these findings highlight the active role of expectation management processes

during sentence comprehension, and demonstrate how mirative markers modulate the process of

communicating unexpected information.

Methods

Part 1: Completing sentence fragments with mirative markers

Participants

A total of 40 native English speakers with no diagnosed dyslexia or learning disabilities participated in this part of the study by completing an online questionnaire. Participants were recruited through Facebook posts and word of mouth. All participants completed high-school in an English-speaking country. All participants electronically signed an informed consent form and were compensated for their participation.

Stimuli

For our main analysis we created 30 novel sentence fragments. The sentence fragments were 4-10 words long, all contained a subject and a verb, and all terminated just before the object appears. The sentence fragments were constructed such that there was at least one appropriate object that could plausibly continue the sentence, although in many cases there was more than one plausible continuation. Each sentence fragment appeared in two conditions: the *neutral* condition where the sentence fragment was preceded by a neutral marker ("yesterday"), and the *mirative* condition where the sentence fragment was preceded by a mirative marker ("surprisingly").

Procedure

Human: Participants performed an online sentence-completion (cloze) task. They were instructed to type a plausible word that would continue each sentence fragment. Participants were presented with each sentence fragment once: 15 sentences in the neutral condition and 15 in the mirative condition, presented in a pseudo-random order (no more than 3 consecutive trials of the same condition). The assignment of sentence fragments to conditions was counterbalanced between participants. Due to an unfortunate set-up error, one sentence fragment was presented in the mirative condition only, and was excluded from analyses. Responses were recorded while correcting for any typos (e.g., shampane was replaced with the correct spelling, champagne).

LLM: The following LLMs were included: Llama-3-8B/70B, Llama-3.1-8B/70B, and Llama-3.2-1B/3B (base versions)[65]. These LLMs were chosen because they are open source, allowing us to calculate the probability of the top token and the overall entropy. The LLMs were accessed with permission through

the *Hugging Face transformers* library[66]. LLMs were presented with each sentence fragment twice, once

per condition. For each sentence fragment, the full next token probability distribution was recorded.

The LLM was re-initialized between trials to ensure that no conversational history or prior context

influenced the responses.

Analysis

Human data: We identified the most popular response under the neutral condition ('top response'),

then calculated its response probability under the neutral condition and the mirative condition. We also

calculated the entropy of the response distribution per sentence fragment, per condition. We then

tested if the inclusion of a mirative marker modifies the probability of the 'top response' and the next

word entropy using two-tailed paired t-tests. Probabilities were logit-transformed prior to statistical

testing[67].

LLM data: For each sentence fragment, we calculated the next token entropy (calculated over the

entire vocabulary) for the neutral and mirative conditions. We also recorded the top 10K tokens under

the neutral condition and their probability in the neutral condition and the mirative condition. Similarly

to the human case, we then tested if the inclusion of a mirative marker modifies the probability of the

'top response' and the next token entropy, using two-tailed paired t-tests. Probabilities were logit-

transformed[67]. We also inspected the mean next token probability per marker, calculated across all

sentence fragments, for each of the top 10K tokens produced in the neutral condition. Data points were

smoothed using locally estimated scatterplot smoothing (LOESS) with span=10.

Follow-up testing and analyses (LLM only): We conducted a follow-up analysis to investigate the scope

of the expectation-modification effect of mirative markers and the factors that modulate it. To this end,

we used Llama-3.1-8B, the largest open-source LLM we tested, which has shown a significant increase in

entropy comparable to human participants. **Stimuli:** We selected 30 passages from the Provo corpus[49].

We selected passages that contained a minimal number of punctuation marks and non-English

characters, and no connectors (such as "however", "for example") or other markers as the first word of

the passage (which would have prevented us from adding a mirative marker in that position). We also

made sure that the passage was not explicitly about expectations or surprises. Passages were 2-3

sentences long (39-62 words, mean sentence length 21.35 words). Passages were then converted into

all possible sentence fragments, 3 words and longer, starting at the beginning of the passage (e.g., "All

that the", "All that the brain", "All that the brain has", "All that the brain has to", and so on…). Overall,

1,365 sentence fragments were generated from the original 30 passages. Each sentence fragment

appeared in two conditions: the neutral condition, where sentence fragments began as they were found

in the corpus, or the mirative condition, where sentence fragments began with a mirative marker

("surprisingly") that was added to the passage. **Procedure:** The procedure was identical to the main

analysis. The LLM was presented with each sentence fragment twice, once per condition. The LLM was

re-initialized between trials to ensure that no conversational history or prior context influenced the

responses. **Analyses:** For each sentence fragment, we calculated the difference in the next token

entropy between the mirative and neutral conditions (positive values indicate higher entropy in the

mirative condition). To assess the scope of the mirative marker's effect on expectations, we used two

separate methods. First, we fit a linear mixed-effects model to the differences in entropy, with a fixed

effect of sentence number within the passage and random intercepts per passage. Second, we fit a

LOESS regression (with span=20), predicting the difference in entropy based on the distance (number of

words) from the beginning of the passage. These methods allowed us to locate a "window of altered

expectations", defined as the location and range of the increased entropy following a mirative marker.

The size of the window could be measured in number of sentences or in number of words. Finally, we

further assessed two additional factors which may influence the entropy: the POS of the 'top response'

(and whether it is a content or a function word), and the level of contextual constraint per sentence

fragment (i.e., to what extent does the sentence fragment limits the upcoming tokens). Taking only the

data within the "window of altered expectations", we then fit a linear mixed-effect model to the

differences in entropy and tested for the significance of the fixed effects. The model included the

predicted token's syntactic POS (obtained using an automatic POS tagger[68]), the entropy in the neutral

condition (which is taken as a measure for the level of contextual constraint), a control variable of a

cubic B-spline for the word number within the passage, and random intercepts per passage. A post-hoc

test was performed, using estimated marginal means, to compare content vs. function words. All

regressions were conducted using the *lme4* package[69] in R[70].

Part 2: Identifying expectation violations

Participants

A total of 63 native English speakers with no diagnosed dyslexia or learning disability participated in this

part of the study by responding to an online questionnaire. Participants were recruited through

Facebook posts and word of mouth. All participants completed high-school in an English-speaking

country. Two different versions of the online questionnaire were presented, with a different order of

the two presented choices. A subset of 22 participants completed both versions of the questionnaire.

One participant was excluded from this study due to not completing the questionnaire. All participants

electronically signed an informed consent form and were compensated for their participation.

Stimuli

For our main analysis, we selected 1000 sentence pairs from the Discovery discourse marker dataset[50],

500 per label: for the *mirative* label, sentence pairs were connected with a mirative marker

("surprisingly"), while for the *anti-mirative* label, sentence pairs were connected with an anti-mirative

marker ("unsurprisingly"). The sentences were originally taken from a corpus of natural text, and the

mirative or anti-mirative connector was embedded between the sentences in the original text. Thus, the

connector that actually appeared in the original text constituted the correct label for that pair. A reason

for using sentence pairs as the stimuli in this task is that pair structure lends itself to setting up an

expectation in the first sentence, indicating a violation of that expectation with a mirative marker

connector, and conveying the violation in the second sentence. Sentence pairs were selected such that

they contained minimal punctuation marks or non-English characters, the sentences were well-formed,

there were no clear misspellings, and there were no sentences that clearly came from "non-

communicative" texts such as movie scripts or website menus. Stimulus selection was performed

blindly, without knowing the correct label (mirative or anti-mirative), in order to avoid any potential

bias.

Procedure

Human: To estimate human level performance on this task, two lists of 30 randomly sampled sentence

pairs (15 per label in each list) were presented to human participants through an online questionnaire.

Sentence pairs were presented in a 2-alternative forced choice paradigm as follows: the first sentence in

the pair was presented, and underneath it appeared two possible continuations: the second sentence in

the pair preceded by a mirative marker or by an anti-mirative marker (e.g., "You will only see locals at

this restaurant. A) Surprisingly, they have menus in English. B) Unsurprisingly, they have menus in

English.") Participants were instructed to select the most natural continuation out of the two choices (A

or B). There were two possible versions of the questionnaire, one where the choice order presented was

mirative marker first, and another where the choice order presented was anti-mirative marker first. A

subset of participants responded to both questionnaire versions, presented with different sentence

pairs in each session, with a break of at least a week between sessions.

LLM: The following LLMs were included: Llama-3-8B-Instruct, Llama-3.1-8B-Instruct, Llama-3.2-1B/3B-

Instruct[65], GPT-3.5, GPT-4/4-0613[71], and GPT-4o/4o-mini[72] ("chat" versions). The Meta-Llama series of

LLMs was accessed with permission through the *Hugging Face transformers* library[66]. The chatGPT series

of LLMs was accessed using the OpenAI API. LLMs were presented with each stimulus as a prompt and

their text response was recorded. Each prompt began with the instructions: "Please select the most

natural continuation of the text from the multiple-choice list. Respond with your choice only." The

instructions were followed by the first sentence and two possible choices, which were the second

sentence of the pair either connected with a mirative or anti-mirative marker, exactly like the

presentation for the human participants. We looked for LLMs' responses to contain the second sentence

with their chosen connector. Responses were set to be deterministic and we always considered the top

token returned as the LLM's response. For the chatGPT series of LLMs, which are closed-source and

cannot be made to respond deterministically, the text response did not always match the top token

which was provided separately in the output. In those cases, we coded the LLM response as the top

token provided, such that if it was the beginning of the mirative marker (*Sur/sur/ Sur/ sur*) the response

was coded as mirative and if it was the beginning of the anti-mirative marker (*Un/un/ Un/ un*) the

response was coded as anti-mirative, taking into account different capitalizations and possible inclusions

of preceding spaces. If the response returned by the LLM did not begin with any of the markers, it was

coded as an invalid response and excluded from later accuracy calculations. Each LLM was presented

with all the sentence pairs twice, once where the choice order presented was mirative marker first, and

another where the choice order presented was anti-mirative marker first.

Analysis

Human data: Using the participants' responses, we calculated the accuracy and the response rate per

label for each participant, and from that we calculated the mean and standard error (SE) across all

participants. We also looked at the accuracy of the top performing participants as an additional

benchmark to compare LLM performance against. Agreement between participants was calculated using

Gwet's AC1 metric[73].

LLM data: Accuracy and response rate per label were calculated. An additional stricter measure of

accuracy, which we called j*oint order accuracy*, was calculated by considering the LLM response as

correct only if it selected the correct label for a given sentence pair under both presentations with

different order of choices. We then compared LLM performance with the mean human performance

and the top human performance.

Follow up testing and analyses (LLM only):

Data discriminability: To ensure that the high performance of the LLMs was derived from some ability to identify expectation violations and not by relying on other heuristics, we measured the discriminability of the data using several simple variables: the length of the first sentence or the second sentence (measured in tokens using the Llama-3 tokenizer), the perplexity and the maximum-surprisal (max-surprisal) of the second sentence given the first sentence without any connector (measured using Llama-3-8B base version), the cosine similarity between the first and second sentence (measured using OpenAI's embeddings model text-embedding-3-small), whether the first sentence was a question or not, and whether the first or second sentence contained any negativity markings (i.e., whether the sentence pair includes any of the following words: *no/not/_n't/none/nothing/never/neither/cannot).* Discriminability was measured using the receiver operating characteristic (ROC) and the area under the curve (AUC) was calculated for each variable.

Manipulated stimuli: An additional test, using manipulated stimuli, was conducted on the best performing LLMs (Llama-3-8B-Instruct, Llama-3.1-8B-Instruct, chatGPT-4, chatGPT-4o). The manipulated stimuli included: (a) only the first sentence of each pair, (b) only the second sentence of each pair, and (c) sentence pairs generated by shuffling randomly the first and second sentences within a given label. Once again, each LLM was presented with all the sentence pairs twice: once with the choice of a mirative marker presented first, and another with the choice of an anti-mirative marker presented first.

Biases: Beyond comparing human and LLM task performance, we also compared their respective biases in task performance. Two sources of bias were considered: the 'mirative bias', the propensity to select a mirative marker over the alternative, and the 'order bias', the propensity to select the last choice presented. We estimated the biases using a logistic mixed-effects regression, using the mirative response rate as the dependent variable, an intercept and choice order as the independent variables, and another random intercept per stimulus. For human participants, we also included a random intercept per participant. The intercept and order coefficients extracted from the regression model were interpreted as the log odds-ratio to select the mirative marker over the anti-mirative marker and the log odds-ratio to select the second choice presented over the first choice presented, respectively. A more conservative estimate for the human bias was calculated in the same manner but using only the 22 participants who completed both versions of the questionnaire. All regressions were conducted using the *lme4* package[69] in R[70].

References

1. Summerfield, C. & Egner, T. Expectation (and attention) in visual cognition. *Trends in Cognitive*
Sciences **13**, 403–409 (2009).
2. *Predictions in the Brain: Using Our Past to Generate a Future*. xiv, 383 (Oxford University Press, New
York, NY, US, 2011).
3. Federmeier, K. D. Thinking ahead: The role and roots of prediction in language comprehension.
Psychophysiology **44**, 491–505 (2007).
4. Kuperberg, G. R. & Jaeger, T. F. What do we mean by prediction in language comprehension?
Language, Cognition and Neuroscience **31**, 32–59 (2016).
5. Pickering, M. J. & Gambi, C. Predicting while comprehending language: A theory and review.
Psychological Bulletin **144**, 1002–1044 (2018).
6. Ehrlich, S. F. & Rayner, K. Contextual effects on word perception and eye movements during
reading. *Journal of Verbal Learning and Verbal Behavior* **20**, 641–655 (1981).
7. Arnon, I. & Snider, N. More than words: Frequency effects for multi-word phrases. *Journal of*
Memory and Language **62**, 67–82 (2010).
8. Smith, N. J. & Levy, R. The effect of word predictability on reading time is logarithmic. *Cognition* **128**,
302–319 (2013).
9. Staub, A. The Effect of Lexical Predictability on Eye Movements in Reading: Critical Review and
Theoretical Interpretation. *Language and Linguistics Compass* **9**, 311–327 (2015).
10. Frisson, S., Harvey, D. R. & Staub, A. No prediction error cost in reading: Evidence from eye
movements. *Journal of Memory and Language* **95**, 200–214 (2017).
11. Kutas, M. & Hillyard, S. A. Reading Senseless Sentences: Brain Potentials Reflect Semantic
Incongruity. *Science* **207**, 203–205 (1980).
12. Kutas, M. & Hillyard, S. A. Brain potentials during reading reflect word expectancy and semantic
association. *Nature* **307**, 161–163 (1984).
13. Kutas, M. & Federmeier, K. D. Thirty Years and Counting: Finding Meaning in the N400 Component
of the Event-Related Brain Potential (ERP). *Annual Review of Psychology* **62**, 621–647 (2011).
14. Frank, S. L., Otten, L. J., Galli, G. & Vigliocco, G. The ERP response to the amount of information
conveyed by words in sentences. *Brain and Language* **140**, 1–11 (2015).
15. Brennan, J. R., Stabler, E. P., Van Wagenen, S. E., Luh, W.-M. & Hale, J. T. Abstract linguistic structure
correlates with temporal activity during naturalistic comprehension. *Brain and Language* **157–158**,
81–94 (2016).
16. Willems, R. M., Frank, S. L., Nijhof, A. D., Hagoort, P. & van den Bosch, A. Prediction During Natural
Language Comprehension. *Cerebral Cortex* **26**, 2506–2516 (2016).
17. Lopopolo, A., Frank, S. L., Bosch, A. van den & Willems, R. M. Using stochastic language models
(SLM) to map lexical, syntactic, and phonological information processing in the brain. *PLOS ONE* **12**,
e0177794 (2017).
18. Shain, C., Blank, I. A., van Schijndel, M., Schuler, W. & Fedorenko, E. fMRI reveals language-specific
predictive coding during naturalistic sentence comprehension. *Neuropsychologia* **138**, 107307
(2020).
19. Heilbron, M., Armeni, K., Schoffelen, J.-M., Hagoort, P. & de Lange, F. P. A hierarchy of linguistic
predictions during natural language comprehension. *Proceedings of the National Academy of*
Sciences **119**, e2201968119 (2022).
20. Friston, K. & Kiebel, S. Predictive coding under the free-energy principle. *Philosophical Transactions*
of the Royal Society B: Biological Sciences **364**, 1211–1221 (2009).
21. Friston, K. Prediction, perception and agency. *International Journal of Psychophysiology* **83**, 248–252
(2012).

22. Clark, A. Whatever next? Predictive brains, situated agents, and the future of cognitive science.
Behavioral and Brain Sciences **36**, 181–204 (2013).
23. D'Astolfo, L. & Rief, W. Learning about Expectation Violation from Prediction Error Paradigms - A
Meta-Analysis on Brain Processes Following a Prediction Error. *Front Psychol* **8**, 1253 (2017).
24. Delancey, S. Mirativity: The grammatical marking of unexpected information. **1**, 33–52 (1997).
25. Delancey, S. Still mirative after all these years. *Linguistic Typology* **16**, 529–564 (2012).
26. Aikhenvald, A. Y. The essence of mirativity. *Linguistic Typology* **16**, 435–485 (2012).
27. Dickinson, C. Mirativity in tsafiki. *Studies in Language. International Journal sponsored by the*
Foundation "Foundations of Language" **24**, 379–422 (2000).
28. Simeonova, V. On the semantics of mirativity. in *Proceedings of the 2015 annual conference of the*
Canadian Linguistic Association 1–15 (Linguistic Society of America Washington, DC, 2015).
29. Kadmon, N. & Landman, F. Any. *Linguistics and Philosophy* **16**, 353–422 (1993).
30. Zanuttini, R. & Portner, P. Exclamative Clauses: At the Syntax-Semantics Interface. *Language* **79**, 39–
81 (2003).
31. Shannon, C. E. A mathematical theory of communication. *The Bell System Technical Journal* **27**, 379–
423 (1948).
32. Roark, B., Bachrach, A., Cardenas, C. & Pallier, C. Deriving lexical and syntactic expectation-based
measures for psycholinguistic modeling via incremental top-down parsing. in *Proceedings of the*
2009 Conference on Empirical Methods in Natural Language Processing: Volume 1 - Volume 1 324–
333 (Association for Computational Linguistics, USA, 2009).
33. Staub, A., Grant, M., Astheimer, L. & Cohen, A. The influence of cloze probability and item constraint
on cloze task response time. *Journal of Memory and Language* **82**, 1–17 (2015).
34. Willems, R. M., Frank, S. L., Nijhof, A. D., Hagoort, P. & van den Bosch, A. Prediction During Natural
Language Comprehension. *Cerebral Cortex* **26**, 2506–2516 (2016).
35. Aurnhammer, C. & Frank, S. L. Evaluating information-theoretic measures of word prediction in
naturalistic sentence reading. *Neuropsychologia* **134**, 107198 (2019).
36. Grisoni, L., Tomasello, R. & Pulvermüller, F. Correlated Brain Indexes of Semantic Prediction and
Prediction Error: Brain Localization and Category Specificity. *Cereb Cortex* **31**, 1553–1568 (2020).
37. Xiang, M. & Kuperberg, G. Reversing expectations during discourse comprehension. *Language,*
Cognition and Neuroscience **30**, 648–672 (2015).
38. Rasenberg, M., Rommers, J. & van Bergen, G. Anticipating predictability: an ERP investigation of
expectation-managing discourse markers in dialogue comprehension. *Language, Cognition and*
Neuroscience **35**, 1–16 (2020).
39. Vaswani, A. Attention is all you need. *Advances in Neural Information Processing Systems* (2017).
40. Radford, A. *et al.* Language models are unsupervised multitask learners. *OpenAI blog* **1**, 9 (2019).
41. Brown, T. *et al.* Language Models are Few-Shot Learners. in *Advances in Neural Information*
Processing Systems vol. 33 1877–1901 (Curran Associates, Inc., 2020).
42. Zhao, W. X. *et al.* A Survey of Large Language Models. Preprint at
https://doi.org/10.48550/arXiv.2303.18223 (2024).
43. Goldstein, A. *et al.* Shared computational principles for language processing in humans and deep
language models. *Nat Neurosci* **25**, 369–380 (2022).
44. Wilcox, E. G., Gauthier, J., Hu, J., Qian, P. & Levy, R. P. On the Predictive Power of Neural Language
Models for Human Real-TimeComprehension Behavior. *Proceedings of the Annual Meeting of the*
Cognitive Science Society **42**, (2020).
45. Cevoli, B., Watkins, C. & Rastle, K. Prediction as a basis for skilled reading: insights from modern
language models. *Royal Society Open Science* **9**, 211837 (2022).
46. Schrimpf, M. *et al.* The neural architecture of language: Integrative modeling converges on
predictive processing. *Proceedings of the National Academy of Sciences* **118**, e2105646118 (2021).

47. Heilbron, M., Armeni, K., Schoffelen, J.-M., Hagoort, P. & de Lange, F. P. A hierarchy of linguistic
predictions during natural language comprehension. *Proceedings of the National Academy of*
Sciences **119**, e2201968119 (2022).
48. Caucheteux, C., Gramfort, A. & King, J.-R. Evidence of a predictive coding hierarchy in the human
brain listening to speech. *Nat Hum Behav* **7**, 430–441 (2023).
49. Luke, S. G. & Christianson, K. The Provo Corpus: A large eye-tracking corpus with predictability
norms. *Behavior Research Methods* **50**, 826–833 (2018).
50. Sileo, D., Van De Cruys, T., Pradel, C. & Muller, P. Mining Discourse Markers for Unsupervised
Sentence Representation Learning. in *Proceedings of the 2019 Conference of the North American*
Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1
(Long and Short Papers) (eds. Burstein, J., Doran, C. & Solorio, T.) 3477–3486 (Association for
Computational Linguistics, Minneapolis, Minnesota, 2019).
51. Strachan, J. W. A. *et al.* Testing theory of mind in large language models and humans. *Nat Hum*
Behav **8**, 1285–1295 (2024).
52. Speer, R. rspeer/wordfreq: v3.0. Zenodo https://doi.org/10.5281/zenodo.7199437 (2022).
53. Pezeshkpour, P. & Hruschka, E. Large Language Models Sensitivity to The Order of Options in
Multiple-Choice Questions. Preprint at https://doi.org/10.48550/arXiv.2308.11483 (2023).
54. Wei, S.-L., Wu, C.-K., Huang, H.-H. & Chen, H.-H. Unveiling Selection Biases: Exploring Order and
Token Sensitivity in Large Language Models. Preprint at https://doi.org/10.48550/arXiv.2406.03009
(2024).
55. Grice, H. P. Logic and conversation. *Syntax and semantics* **3**, (1975).
56. Smith, N. & Levy, R. Cloze but no cigar: The complex relationship between cloze, corpus, and
subjective probabilities in language processing. *Proceedings of the Annual Meeting of the Cognitive*
Science Society **33**, (2011).
57. Hao, S. *et al.* Reasoning with Language Model is Planning with World Model. in *Proceedings of the*
2023 Conference on Empirical Methods in Natural Language Processing (eds. Bouamor, H., Pino, J. &
Bali, K.) 8154–8173 (Association for Computational Linguistics, Singapore, 2023).
58. Haijima, W., Nakakubo, K., Suzuki, M. & Matsuo, Y. The Embodied World Model Based on LLM with
Visual Information and Prediction-Oriented Prompts. Preprint at
https://doi.org/10.48550/arXiv.2406.00765 (2024).
59. Srivastava, A. *et al.* Beyond the Imitation Game: Quantifying and extrapolating the capabilities of
language models. Preprint at https://doi.org/10.48550/arXiv.2206.04615 (2023).
60. Kosinski, M. Evaluating Large Language Models in Theory of Mind Tasks. *Proc. Natl. Acad. Sci. U.S.A.*
121, e2405460121 (2024).
61. Spelke, E. S. & Kinzler, K. D. Core knowledge. *Developmental Science* **10**, 89–96 (2007).
62. Piaget, J. *The Construction of Reality in the Child*. (Routledge, 2013).
63. Kubricht, J. R., Holyoak, K. J. & Lu, H. Intuitive Physics: Current Research and Controversies. *Trends*
in Cognitive Sciences **21**, 749–759 (2017).
64. Gibbs, R. W. On the psycholinguistics of sarcasm. *Journal of Experimental Psychology: General* **115**,
3–15 (1986).
65. Grattafiori, A. *et al.* The Llama 3 Herd of Models. Preprint at
https://doi.org/10.48550/arXiv.2407.21783 (2024).
66. Wolf, T. *et al.* HuggingFace's Transformers: State-of-the-art Natural Language Processing. Preprint at
https://doi.org/10.48550/arXiv.1910.03771 (2020).
67. Jaeger, T. F. Categorical Data Analysis: Away from ANOVAs (transformation or not) and towards
Logit Mixed Models. *J Mem Lang* **59**, 434–446 (2008).
68. Bird, S., Klein, E. & Loper, E. Natural Language Processing with Python. (2009).

69. Bates, D., Mächler, M., Bolker, B. & Walker, S. Fitting Linear Mixed-Effects Models Using lme4.
Journal of Statistical Software **67**, 1–48 (2015).
70. R Core Team. R: A Language and Environment for Statistical Computing. R Foundation for Statistical
Computing (2024).
71. OpenAI *et al.* GPT-4 Technical Report. Preprint at https://doi.org/10.48550/arXiv.2303.08774
(2024).
72. OpenAI *et al.* GPT-4o System Card. Preprint at https://doi.org/10.48550/arXiv.2410.21276 (2024).
73. Gwet, K. Handbook of inter-rater reliability: How to estimate the level of agreement between two or
multiple raters. *Gaithersburg, MD: STATAXIS Publishing Company* (2001).

Acknowledgements

This study was conducted as part of Benjamin Menashe's doctoral dissertation, under the supervision of Prof. Michal Ben-Shachar at the Gonda Multidisciplinary Brain Research Center, Bar-Ilan University. This project was supported by the Data Science Institute at Bar-Ilan University. B.M. is supported in part by the President's scholarship of BIU. We thank Prof. Yael Greenberg and Prof. Yoav Goldberg for many thoughtful discussions.

Author contributions

Benjamin Menashe ran the experiments, analyzed the data, and wrote the manuscript. Austin Drake developed stimuli and helped review the manuscript. Michal Ben-Shachar supervised this study.

Competing interests

The authors declare no competing interests.

Data availability statement (mandatory)

The datasets generated and analyzed during the current study will be made available in an open-source public repository [LINK].