Expectation management in humans and LLMs

Benjamin Menashe[1]*, Austin Drake[2], Michal Ben-Shachar[1]

[1]The Gonda Multidisciplinary Brain Research Center, Bar-Ilan University, Ramat-Gan, Israel
[2]Department of Psychology, University of Jyväskylä, Jyväskylä, Finland

*Corresponding author: menashb@biu.ac.il

Abstract

Mirative markers, such as "surprisingly", explicitly encode a violation of expectations. Such markers are used for expectation management during communication. Sensitivity to mirative markers relies on two abilities: i) updating expectations upon recognizing a mirative marker, and ii) identifying expectation violations warranting the use of a mirative marker. In this study we compared sensitivity to mirative markers in humans and large language models (LLMs). In part 1, we used a sentence-completion task, where humans and LLMs were presented with sentence fragments and asked to continue them. Results show that for both humans and LLMs, the presence of a mirative marker significantly increased response entropy and decreased top response probability, in line with theoretical proposals for mirative markers. In part 2, we created a novel task of mirative polarity selection where humans and LLMs are presented with a sentence pair and asked to select whether it was connected by a mirative marker ("surprisingly") or an anti-mirative marker ("unsurprisingly"). Results show that LLMs perform at an impressive human level. We conclude that both humans and LLMs use mirative markers as cues for calibrating their subsequent expectations during sentence processing.

Intro

Humans constantly form expectations about upcoming stimuli[1,2]. Linguistic stimuli are of no exception: it is well-demonstrated that humans use context and prior knowledge to form expectations and predictions about upcoming linguistic information, and then test those predictions against the actual incoming input[3–5]. Encountering a semantic violation of expectations is associated with longer processing time[6–10], an elevated amplitude of the N400 ERP component[11–14], and neural activation across many brain regions[15–19]. These results are in line with "predictive processing" theories of the brain, whereby such violations of expectations are regarded as "prediction errors" which the brain aims to minimize[20–23].

In natural discourse, speakers often attempt to explicitly manage their interlocutors' expectations by using mirative markers. *Mirative markers* are linguistic elements that encode violation of expectations[24–26], including words such as "surprisingly" and "remarkably". Mirative markers are widely used by speakers to inform their interlocutors about an upcoming unexpected message. In theory, such expectation management helps interlocutors avoid "prediction errors" and the associated increase in processing time and difficulty incurred by such errors. In this paper, we aim to study expectation management using mirative markers, in humans and in large language models (LLMs). The aim of this

study is to quantify and compare sensitivity to mirative markers, which relies on two abilities: i) updating

expectations upon recognizing a mirative marker, and ii) identifying expectation violations warranting

the use of a mirative marker. The extent to which expectation management is successful depends on the

sensitivity to mirativity of both the speaker and interlocutor.

Mirativity is considered to be a language-universal category[24]. Mirativity can be marked using words

(e.g., "surprisingly"), exclamatory particles or intonation (e.g., "Wow!"), and even morphological affixes

in certain languages[27]. Conversely, a confirmation of expectations can also be marked using words such

as "unsurprisingly" and "expectedly", which we refer to as *anti-mirative markers*. According to linguistic

theory, mirative markers are appropriate only there exists a more expected proposition that is false[28].

This implies that mirative markers should modify expectations in the following way: decrease the

probability for the most-expected upcoming stimuli, and increase it for lesser-expected upcoming

stimuli. Such a process is referred to as *domain widening*, whereby the domain of plausible upcoming

stimuli is expanded to include lesser-expected stimuli[29,30]. This is effectively equivalent to an increase in

the entropy of the expectation distribution. Entropy is a quantitative measure of uncertainty taken

directly from information theory[31], and its effects on human behavior and neural activity have been

extensively researched[32–36].

Two previous studies which addressed the neural effects of expectation-disconfirming markers, both

using ERPs, have presented conflicting results. In the first study[37], participants read scenarios containing

unexpected target words. On half the trials, the target word was preceded by the discourse marker

"even so", which is assumed to reverse readers' expectations. Results showed that the presence of

"even-so" attenuated the amplitude of the N400 component for the otherwise unexpected target

words. In a later study[38], participants read dialogues in Dutch with unexpected endings. On half the trials

the ending was preceded by discourse marker "eigenlijk" ("actually"), which signals expectation-

disconfirmation. Results showed no evidence for a main effect of discourse marker or interaction of

discourse marker and predictability on the N400 amplitude. As such, there is currently only limited and

conflicting empirical evidence on processing mirative markers and subsequent expectation modification.

In recent years, LLMs have revolutionized the field of natural language processing. In essence, LLMs are

trained to predict the next token given a sequence of text, based on exposure to enormous corpora of

language[39–42]. Post training, an LLM takes a sequence of text as input and provides a probability estimate

for each token (in its vocabulary) to be the next token in the sequence. This has been compared to

forming expectations in humans, in what has been called a "shared computational principle of language

comprehension"[43]. LLMs have been used to gain insight into human behavior[44,45], and neural activity[46–]

[48]. While state-of-the-art LLMs have shown impressive performance on various tasks and benchmarks, it

is yet unclear how LLMs explicitly manage expectations or respond to expectation management

markers, if at all.

In this study, we measured human participants and LLMs on their sensitivity to mirativity. In part 1, we

studied how mirative markers modify expectations. We used a sentence-completion task, where human

participants and LLMs were presented with sentence fragments and asked to continue them. We

manipulated the sentences to begin either with a mirative marker or a neutral marker, and compared

the respective responses. In part 2, we studied if LLMs identify violations of expectations to the same

level as human participants do. We created a novel task called *mirative polarity selection* where human

participants and LLMs are presented with a sentence pair and asked to select whether it was connected

by a mirative marker or by an anti-mirative marker.

Results

Part 1: Increased entropy in response to mirative markers

Using a sentence-completion task, we tested how the presence of a mirative marker ("surprisingly") in

the beginning of a sentence fragment affects expectations about upcoming words as compared to a

neutral marker ("yesterday"). We tested human participants using an online questionnaire containing

thirty novel sentence fragments were presented. We then tested the meta-llama-3/3.1/3.2 series of

LLMs on the same sentence fragments. Since a mirative marker indicates an upcoming violation of

expectations, we predicted that it will lead to a decrease in the probability of the most-expected

response and to a general increase in the probability of lesser-expected responses, leading to an overall

increase in the entropy of expected responses.

We found that, in human participants, the inclusion of a mirative marker in the beginning of a sentence

fragment resulted in a significant decrease in the probability of the most common response to the

neutral marker (t_{28} = −6.85, p<.001, Fig. 1A), and a significant increase in the entropy of the response

distributions (t_{28} = 5.58, p<.001, Fig. 1B). Similar to human participants, a significant decrease in

probability for the top response to the neutral marker was found for all LLMs (see Supplementary Table

1 for the full statistics. See Fig. 1D for an example LLM). Moreover, the entropy of the response

distribution increased for all LLMs, although this increase was significant in only three of the six LLMs

tested (Llama-3-8B, Llama-3.1-8B, Llama-3.2-3B. See Fig. 1E for an example LLM). A visual inspection of

the top 10K tokens suggested that mirative markers decrease the probability of the top 10-20 tokens

and increase the probability of the rest of the tokens (Fig. 1F). Taken together, this provides evidence

that humans and LLMs process the mirative marker as an indicator for an upcoming violation of

expectation, and both humans and LLMs modify their expectations accordingly.

96
*Figure 1. Mirative markers modify expectations. **Top:** Human participants were presented with 30 sentence fragments and*
asked to continue them with the next word. Stimuli began either with a neutral marker ("yesterday") or a mirative marker
*("surprisingly"). **A)** Probability of the most common response in the neutral condition, and of the same response in the mirative*
*condition. *** p<.001. **B)** Entropy over the response distribution, per condition. *** p<.001. **C)** Example of response distributions*
for the same sentence fragment ("the birthday girl celebrated with a bottle of ___") in the neutral condition in grey and in the
*mirative condition in red. **Bottom:** we used an LLM (meta-llama-3.1-8b) to generate next token predictions for the same 30*
*sentence fragments presented to human participants. **D)** Probability of the top token in the neutral condition, and of the same*
*token in the mirative condition. The difference is significant even when removing the top outlier point. *** p<.001. **E)** Entropy*
*over the next token distribution, per condition. ** p= .002. **F)** Mean probability by marker, calculated across all stimuli, for each*
of the top 10K tokens in the neutral condition. X-axis represents token rank, determined by descending probability in the neutral
condition. Y-axis is in log-scale. Data points were smoothed using locally estimated scatterplot smoothing (LOESS) with span=10.
The upper panel is a magnified view of the top 30 ranks.

In a follow-up analysis, we generated 1,365 text fragments of varying lengths taken from the Provo

corpus[49]. We defined a "window of altered expectations" as the location and range of the increased

entropy due to the presence of a mirative marker. The window was found to extend up to 2 sentences

ahead (Fig. 2A) and approximately 5-40 words ahead (Fig. 2B, see also Supplementary Table 2 for the full

statistics). This suggests that mirative markers have a limited window in which the violation of

expectations is anticipated to occur.

In a linear mixed-effects model predicting the increased entropy by the POS of the most-expected word,

all POS showed a significant increase in entropy and no significant difference was found between

content words and function words (t_{830} = 0.38, p=.705, Fig. 2C). Additionally, we wanted to check if

mirative markers modify expectations differently for different levels of contextual constraint, measured

by the entropy in the neutral condition. No correlation was found between the level of contextual

constraint and the increase in entropy in the mirative condition (standardized correlation coefficient =

−0.010, p=.774, Fig. 2D). This suggests that the addition of a mirative marker generally results in an

increase of entropy, regardless of the level of contextual constraint. Importantly, this also shows that

the increase in entropy is not due to regression to the mean.

124
Figure 2. Mirative markers increase entropy. *We used an LLM (meta-llama-3.1-8B) to quantify the entropy following each word*
in 30 texts taken from the Provo corpus (Luke & Christianson, 2018). Texts began either neutrally, i.e., as they were in the
corpus, or with a mirative marker ("surprisingly"). All plots show the difference in entropy between the mirative and the neutral
condition, per word. ***A)*** *Entropy difference per sentence number. Black points show the estimated means from a linear mixed-*
effects model per sentence number in the text. Errors bars show the 95% CI. Outliers above (n=51) and below (n=38) the y-axis
limits are not shown but were included in the model. *** p<.001. n.s. not significant. ***B)*** *Entropy difference per the word's*
distance from the mirative marker. Black line shows the locally estimated scatterplot smoothing (LOESS) with span=20 over the
entropy difference of all words. Error regions show the 95% CI. Outliers above (n=51) and below (n=38) the y-axis limits are not
shown but were included in the locally estimated scatterplot smoothing model. ***C)*** *Entropy difference per the predicted token's*
part-of-speech. Only words which were in the first 2 sentences and within the mirative window (5 to 40 words) were used. Black
points show the estimated means from a linear mixed-effects model per part-of-speech, with squares for content words and
diamonds for function words. Errors bars show the 95% CI. Outliers above (n=26) and below (n=17) the y-axis limits are not

Part 2: Identifying expectation violations

We tested human and LLM performance in identifying violations of expectation. For that, we devised a

novel task called mirative polarity selection. Participants and LLMs were presented with a sentence pair

and asked to select whether it was connected with a mirative marker ("surprisingly") or an anti-mirative

marker ("unsurprisingly"). Sentence pairs were sampled from the Discovery dataset[50], and were

originally connected by one of the markers in the corpus (this constitutes the correct response). We

tested human participants using an online questionnaire, and we used the meta-llama-3/3.1/3.2-instruct

series and the chatGPT-3.5/4/4o series of LLMs. We predicted that LLMs will perform near or at a

human level, in line with their performance on theory-of-mind tasks[51].

Human mean accuracy on the mirative polarity selection task was 75.5% ± 1%. Participant performance

varied widely (Fig. 3B), ranging between 46.7% (N=2) and 90% (N=3). This suggests high variability in the

participants' ability to identify violations of expectations. Participant agreement on the responses was

fair (percent agreement: 68.2%, Gwet's AC1: 0.376, p<.001). The relatively low level of mean accuracy

and agreement may reflect the natural stimuli we used, as the sentence pairs may not have contained

sufficient information for selecting the correct marker (see Supplementary Table 4 for examples with

low human accuracy). Thus, we take the mean human accuracy and the top human accuracy as tentative

benchmarks for estimated mean and top performance on this task.

LLM task performance varied, with some models approaching and some exceeding mean human

performance (see Table 1 for the full statistics, and Fig. 3C for a comparison between human

performance and selected LLMs). Within the meta-llama series, Llama-3-8B-Instruct and Llama-3.1-8B-

Instruct performed well above chance but still below human level. The newer Llama-3.2 models both

performed at chance level. This result may be due to their smaller number of parameters. Within the

chatGPT series, GPT-3.5 performed above chance level but below human level, GPT-4 performed at

human level, and GPT-4o performed above mean human level and near the top human level. GPT-4o-

mini saw a drop in performance, which also may be due to its smaller number of parameters (see Table

1). A stricter measure of accuracy is the joint order accuracy, where LLM responses were considered

correct only if they selected the correct label twice for a given sentence pair: once per each choice order

presented. LLM performance as measured by joint order accuracy was lower than model accuracy for all

Table 2. Mirative polarity selection – summary of responses

model	mean accuracy	joint order accuracy	invalid responses	first choice presented	accuracy	mirative accuracy	anti-mirative accuracy	mirative response rate	anti-mirative response rate	mirative bias	order bias
Human	75.5% ± 1%			mirative	74.9% ± 2%	83.5% ± 2%	66.3% ± 4%	58.6% ± 2%	41.4% ± 2%	0.51 ± 0.3	−0.02 ± 0.1
				anti-mirative	76.1% ± 2%	81.6% ± 2%	70.5% ± 3%	55.6% ± 2%	44.4% ± 2%		
Llama-3-8B-Instruct	65.2%	40.4%	0.7%	mirative	63.9%	87.7%	40.2%	73.7%	26.3%	0.60 ± 0.1	−0.87 ± 0.1
				anti-mirative	66.4%	70.4%	62.4%	54.0%	46.0%		
Llama-3.1-8B-Instruct	67.9%	41.5%	1.8%	mirative	65.7%	88.0%	43.5%	72.3%	27.7%	0.31 ± 0.1	−1.43 ± 0.1
				anti-mirative	70.0%	60.8%	79.3%	40.9%	59.1%		
Llama-3.2-1B-Instruct	47.4%	24.6%	35.1%	mirative	48.2%	0.5%	99.7%	0.4%	99.6%	−14.4 ± 1.6	6.04 ± 1.6
				anti-mirative	46.4%	1.6%	97.8%	1.8%	98.2%		
Llama-3.2-3B-Instruct	52.1%	6.3%	0.5%	mirative	54.3%	12.6%	96.0%	8.3%	91.7%	1.56 ± 0.3	7.92 ± 0.5
				anti-mirative	49.9%	99.6%	0.4%	99.6%	0.4%		
GPT-3.5-turbo-0125	61.3%	26.4%	0.5%	mirative	55.7%	96.4%	14.6%	90.9%	9.1%	0.64 ± 0.1	−3.44 ± 0.2
				anti-mirative	66.8%	42.8%	91.0%	26.0%	74.0%		
GPT-4-0613	76.9%	62.8%	0.2%	mirative	72.4%	49.3%	95.4%	26.9%	73.1%	−1.06 ± 0.1	1.62 ± 0.2
				anti-mirative	81.3%	78.6%	84.0%	47.2%	52.8%		
GPT-4-turbo-2024-04-09	78.5%	61.7%	0.0%	mirative	72.2%	46.8%	97.6%	24.6%	75.4%	−0.88 ± 0.1	2.59 ± 0.2
				anti-mirative	84.7%	90.2%	79.2%	55.5%	44.5%		
GPT-4o-mini-2024-07-18	68.7%	48.3%	0.3%	mirative	61.6%	97.4%	25.7%	85.9%	14.1%	1.20 ± 0.1	−2.23 ± 0.2
				anti-mirative	75.9%	77.5%	74.3%	51.6%	48.4%		
GPT-4o-2024-08-06	84.8%	77.1%	0.0%	mirative	84.3%	87.0%	81.6%	52.7%	47.3%	0.12 ± 0.1	−0.32 ± 0.1
				anti-mirative	85.2%	84.6%	85.8%	49.4%	50.6%		

Mean ± SE where applicable.

Table 1. Mirative polarity selection – summary of responses. Mirative polarity selection is a novel task where participants and
LLMs are presented with a sentence pair and asked to select whether it was connected with a mirative marker ("surprisingly") or
an anti-mirative marker ("unsurprisingly"). We used 1000 sentence pairs (500 per marker) from the Discovery dataset (Sileo et
al., 2019). Human participants were presented with 60 randomly selected stimuli (30 per marker). Human participants and
models were presented with stimuli where the choices were presented either mirative marker first or anti-mirative marker first.
Mean accuracy is the mean accuracy over both choice orders. Joint order accuracy is the accuracy only if the model responded
correctly for both choice orders. Invalid responses are the percent of response where the model did not respond with selecting a
mirative or an anti-mirative marker. For every choice order, for human participants and for each model, we also report the
accuracy, accuracy per correct marker (corresponding to true positive rate and false positive rate), and response rate per marker
(corresponding to predicted positive rate and predicted negative rate). We then fit a logistic mixed-effects regression per model
using the mirative response rate as the dependent variable, an intercept and choice order as the independent variables, and a
random intercept per stimulus, in order to estimate the mirative marker bias and the order bias, respectively. Similarly, for the
human participants we fit a logistic mixed effects regression with the same specification but with the addition of random
intercepts per participant.

To ensure that the high accuracy of the LLMs was derived from some ability to identify expectation

violations and not due to some other variable, we measured the discriminability of the sentence pairs

using several simple variables. Discriminability, measured using AUC, was very poor for most of the

variables checked (second sentence length: 0.462, perplexity: 0.492, max surprisal: 0.546, similarity:

0.495, question: 0.508, negativity: 0.558), with the exception of the length of the first sentence where

anti-mirative markers tended to be preceded by longer sentences as compared to mirative markers

(AUC = 0.647, see Fig. 3D for the ROC of the various criteria). However, discriminability based on the

length of the first sentence is still not sufficient to explain the performance of the better performing

LLMs. Moreover, it was not a significant predictor of the LLM response beyond the stimulus label (using

a logistic regression with a covariate for stimulus label, p>.42 for all LLMs). This supports the claim that

LLMs succeed in mirative polarity selection due to some form of sensitivity to mirativity.

To further assess this claim, we tested LLM performance on manipulated versions of the stimuli:

presenting just the first or just the second sentence of the pair. LLM performance decreased

substantially in both conditions (Fig. 3E, see Supplementary Table 3 for the full statistics). This also

suggests that LLM performance is not due to data contamination (where the model was trained on the

stimuli and thus was "supervised" for the correct label). Following that, we presented LLMs with

sentence pairs where the first and second sentence were randomly shuffled between pairs within the

same label. The goal of this condition was to eliminate the semantic information between each pair of

sentences, while preserving other global properties which might differ between labels. LLM

performance decreased substantially on this condition as well (Fig. 3E, see Supplementary Table 3 for

the full statistics). This shows that LLM performance is tied to the semantic information in the sentence

pair, most likely the occurrence of an expectation violation (or confirmation). Thus, altogether, results

from the manipulated stimuli conditions support the claim that LLMs succeed in the original task due to

some form of sensitivity to mirativity and not due to data contamination or sensitivity to other

properties of the stimuli.

Participants tended to select the mirative marker slightly more than the anti-mirative marker, although

this difference was not significant (p=.055). Of the LLMs which performed above chance level, different

tendencies were observed: Llama-3-8B-Instruct and Llama-3.1-8B-Instruct displayed a significant bias to

select the mirative marker (p<.001, but it was of a similar magnitude to humans), GPT-4o was not

significantly biased towards any label (p=.378), and GPT-4 had a significant bias to select the anti-

mirative marker (p<.001, Fig. 4F, see Table 1 for the coefficient values). This suggests that while LLM

performance can reach or exceed human level, it does not necessarily do so in a similar way to humans.

Importantly, the mirative marker "surprisingly" is an order of magnitude more frequent than the anti-

mirative marker "unsurprisingly" in natural corpora (using the *wordfreq* python library[52]: "surprisingly"

Zipf frequency = 4.09, "unsurprisingly" Zipf frequency = 3.01, frequency ratio = 12.02), which means that

some mirative bias may be expected if the base frequency of the markers is taken into account when

selecting the markers.

Finally, LLMs also differed from human participants by their sensitivity to the order of the choices

presented (Fig. 4G, see Table 1 for the coefficient values). In humans, no significant effect of order was

found when estimating using all human participants (p=.880) or when only using the subset of

participants who responded to both orders (coefficient = 0.10 ± 0.2, p=.513). However, all LLMs

displayed a significant order bias, such that Llama-3-8B-Instruct and Llama-3.1-8B-Instruct were more

likely to select the first choice presented (p<.001), GPT-4o was also more likely to select the first choice

presented albeit to a lesser degree (p=.004), and GPT-4 was actually more likely to select the last choice

presented (p<.001). This is consistent with previous findings of order bias in LLMs[53,54]. The fact that

LLMs, but not humans, display an order bias in this task raises the possibility that LLMs do not

necessarily attain their high accuracy in a similar way to humans.

232
Figure 3. LLMS achieve near human performance on mirative polarity selection. *Miratve polarity selection is a novel task*
where participants and LLMs are presented with a sentence pair and asked to select whether it was connected with a mirative
marker ("surprisingly") or an anti-mirative marker ("unsurprisingly"). We used 1000 sentence pairs (500 per marker) from the
Discovery dataset (Sileo et al., 2019). Human participants were presented with 60 randomly selected stimuli (30 per marker). ***A)***
Example stimulus, presented in mirative first order. The correct choice is the mirative marker ("surprisingly, they have menus in
English"). ***B)*** *Human accuracy distribution in the task.* ***C)*** *Accuracy on the task for human participants and several LLMs. Choice*
order with the mirative marker presented first is shown in light blue, and the reverse choice order with the anti-mirative marker
presented first is shown in dark blue. Error bars show the 95% CI. ***D)*** *AUC for several discrimination criteria are all close to*
chance level. Criteria include: length of first or second sentence in tokens, the perplexity and the max surprisal of the second
sentence, the cosine similarity between the sentences, whether the first sentence is a question, and the presence of a negative
marker in any of the sentences. ***E)*** *LLM mean performance on several conditions of manipulated stimuli. Sentence 1: presented*
with the first sentence only. Sentence 2: presented with the second sentence only. Shuffled: the first and second sentences of
different pairs were randomly shuffled within the same marker. ***F-G)*** *Estimates for a mirative bias and a choice order bias, per*
model, obtained using logistic mixed-effects models. ***F)*** *Mirative bias: positive values suggest higher probability of selecting the*
*mirative marker over the anti-mirative marker, and negative values vice-versa. [n.s.] not significant. *** p<.001.* ***G)*** *Order bias:*
positive values suggest higher probability of selecting the second choice presented over the first, and negative values vice-versa.
*Error bars show the 95% CI. [n.s.] not significant. ** p<0.01. *** p<.001.*

General discussion

In this study, we assessed sensitivity to mirativity in both human participants and LLMs. We measured how the presence of a mirative marker ("surprisingly") affects subsequent expectations using a sentence-completion task, and whether humans and LLMs are able to detect expectation violations warranting the use of a mirative marker. Results show that both humans and LLMs use mirative markers as an indication for an upcoming expectation violation, and that both humans and LLMs display a similar level of sensitivity to mirativity, as measured by our tasks.

Within "predictive processing" theories[20,22], there is a clear advantage for giving a warning signal prior to an expectation violation, which allows a preemptive modification of expectations, thus reducing the would-be prediction error. Grice's cooperative principle of communication asserts that speakers aim to help their interlocutors process the conveyed message[55]. Along these lines, a speaker may use a mirative marker as part of the cooperative principle to help their interlocutor reduce their prediction error for an upcoming unexpected message. Thus, sensitivity to mirativity can provide an advantage for more efficient processing of information. Further studies can directly test this claim by measuring the effect of mirative markers on behavioral and neural correlates of prediction error.

As shown in part 1, human participants modified expectations upon encountering a mirative marker, as did LLMs. The expectation modification involved a reduction (but not an elimination) in the probability of the most-expected response, and an increase in entropy. The reduction in probability of the most-expected response may be considered a trivial result, as the literal meaning of mirative markers such as "surprisingly" is that the current message is not the most-expected one[30,28]. The increase in entropy can be interpreted as a general increase in the uncertainty as to the identity of the next upcoming word. This is because while mirative markers signal an upcoming expectation violation, they do not specify the content of the violation, leading the interlocutor to increase their expectations for many different upcoming words, all of which violate expectations. Additionally, mirative markers do not specify the exact location of the upcoming expectation violation (only that it will appear soon). During word-by-word prediction, this prevents the interlocutor from discounting the highly expected words, since the violation could appear later on. Instead, it leads to domain widening, where the set of plausible next words expands while preserving the most-expected words. Domain widening is congruent with the increase in entropy observed. Moreover, when comparing the top tokens of the LLM responses, overall token rankings remained stable but the probability decreased for the top 10-20 tokens and increased for

the rest of the tokens. This supports the notion that uncertainty about the location and identity of the

expectation violation leads to expanded expectations when predicting the next word.

In a follow-up analysis, we used a large number of sentence fragments to investigate factors which

influence the change in expectations in an LLM following a mirative marker. Using language models for

measuring predictability and entropy of expectations is a standard method[56,45,43] and can be suggestive

of the effects in human participants even without testing humans directly. Results show a "window of

altered expectations" (in which mirative markers led to increased) to be approximately two sentences

long or 5-40 words ahead. Notably, the stimuli used was not designed to contain expectation violation,

and we theorize that in natural settings mirative markers alter expectation until encountering a

violation, which likely will occur within two sentences. Entropy increase was consistent for expected

content words and function words. For an illustrating example, for the sentence fragment "All that the

brain has to work with are ___", the most-expected token was "the", which is a function word (a

determiner). When preceded by the mirative marker "surprisingly", entropy nonetheless increased,

although the word "the" is not related to the semantic content of the message. This result may be

because less-expected content words remain possible in such positions (for example, "neurons"), or

because mirative markers create a general uncertainty in expectations. Since our human experiments

were designed to elicit nouns, we are not able to conclusively assess difference by word type and POS in

human participants in this study. Furthermore, entropy increase was independent of the contextual

constraint of the sentence fragments. The fact that even lower-constraining sentence fragments

(wherein there isn't one clear expectation for the upcoming word) nonetheless see an increase in

entropy suggests that mirative markers alter expectations at all levels, even weakly held ones.

Additionally, this affirms that the increase in entropy is not due to regression to the mean (where

extreme values of entropy would have become more moderate).

As shown in part 2, LLMs reached human performance level in selecting the mirative marker as the

appropriate connector between a pair of sentences. Identifying if a sentence pair contains a violation of

expectations is complex and requires several cognitive abilities: reading comprehension, detecting

(often implicit) expectations by applying world knowledge and theory-of-mind in context, and

recognizing mismatches between the expectations and the actual message. Thus, success on the task is

far from trivial. Human performance varied considerably, ranging between chance level to 90%

accuracy. This could possibly reflect individual differences in the ability to detect expectation violations.

It could also reflect differences in the specific expectations people form due to different life experiences,

which would lead some to judge that a certain message contains a violation of expectations while others

would disagree (but notice that the inter-subject percent agreement was around 68%, significantly

above chance). It could also reflect the possibility that human participants differed on the level of

attention and engagement with the task.

LLMs performed impressively at the task, reaching and exceeding average human level (although still

below top human performers). A possible concern is that the stimuli used, taken from the internet,

could have been in the training data for the LLMs we tested ("data contamination"), although we argue

otherwise for several reasons: LLM performance is at human-average rather than ceiling level, accuracy

dropped when tested on the first or second sentence only (which are sufficient by their own for

retrieving a memorized sequence), and the order of the options presented systematically influenced

LLM selection. An AUC analysis did not reveal any variable (e.g., sentence length) which could be used to

discriminate the stimuli (see Fig. 3D), and performance dropped when sentence pairs were shuffled,

ruling out some non-semantic property of the stimuli that the LLMs could have used to classify it.

Additionally, a supplementary analysis revealed that the presence of a mirative marker affected LLMs'

common-sense reasoning but not vocabulary testing (see Supplementary Materials). Taken together,

this evidence suggests that LLMs' success on the task is likely due to an ability to identify expectation

violations, which is a core part of their general sensitivity to mirativity.

The astounding breakthrough success of LLMs in recent years has raised questions about their ability to

construct a world model[57,58] and a theory-of-mind[59,51,60]. A world model can be defined as an internal

representation of the properties and causal dynamics of the physical world. Theory-of-mind can be

defined as a model of the mental states of another agent, including their beliefs and expectations.

Success in the mirative polarity selection task requires a basic level of both a world model and a theory-

of-mind, because in order to identify what would constitute an expectation violation one must first have

a good approximation of the expectation their interlocutor would form. There is ample evidence

showing that humans possess an understanding of "folk physics", even at a young age[61–63]. Thus, a world

model is helpful in informing about what their interlocutor would expect to happen, under normal

circumstances. To take an example stimulus: "I saw the issue. Surprisingly/Unsurprisingly, it was easy to

fix". To correctly select the mirative marker ("surprisingly"), one must i) have a world model wherein

issues are usually difficult to fix, and ii) use their theory-of-mind to understand that their interlocutor

would also expect the issue to be difficult to fix. The success of LLMs on the task suggests that LLMs may

have some sort of a functioning theory-of-mind and informative world model (albeit not necessarily

similar in representation to humans), or at least that they display behaviors which would make it appear

as though they have them. While this study did not aim to assess the extent, robustness, and human-

likeness of the theory-of-mind and world models that LLMs may or may not possess, their performance

in this study may provide some initial evidence for such capabilities, upon which future studies can be

conducted.

As noted previously, LLMs displayed different biases than humans in the mirative polarity selection task.

In terms of the tendency to select each marker, humans showed a non-significant mirative preference,

meta-llama models showed a significant mirative preference, GPT-4 showed a significant anti-mirative

preference, and GPT-4o showed no preference. Bayesian inference can explain the mirative bias: when

the stimulus lacks sufficient information to determine its label, prior knowledge must be used instead,

and the base frequency of "surprisingly" is substantially higher than "unsurprisingly" in natural language.

LLMs were also influenced by the presentation order of choices, in line with previous research[53,54], while

humans were not. Whether considering all participants or only the subset of participants who

completed the task under both choice orders, no significant order bias was found. In contrast, the meta-

llama models and GPT-4o displayed a significant preference towards the first choice presented, and

GPT-4 displayed a significant preference towards the last choice presented. The combination of a last-

choice bias and an anti-mirative bias renders GPT-4 as particularly un-human-like in this task.

Limitations

This study has several limitations. First, there are several known drawbacks of using online

questionnaires administrated through the internet. Although participants were instructed to dedicate 20

minutes of their time and complete the tasks in an environment free from distractions, there is no way

to verify this actually occurred. Nonetheless, participants' responses in the sentence-completions

showed no indication of randomly typing words or misreading the sentence fragments, and participants'

performance on the mirative polarity selection task was high. This suggest that, overall, participants

were engaged with the tasks.

Another limitation is that, in the mirative polarity selection task, we assumed that each stimulus actually

contains an expectation violation (or confirmation, for the anti-mirative label). This assumption is

somewhat justified since the stimuli were naturally produced, but there is no way to independently

verify this. Moreover, since the stimuli were taken from the internet, the identity of their authors (and

relevant information such as whether they are fluent English speakers) is unknown, although we did

select stimuli which appeared well-formed and contained no clear misspellings. We take top human

performance, at 90% accuracy, as a tentative approximation that 90% of the stimuli were discernable in

nature and thus contained an expectation violation or confirmation.

Finally, in this study we treated the presence of a mirative marker as a sincere indicator of a violation of

expectations. However, in natural conversation, sarcasm allows speakers to use markers for their

opposite meaning[64]. While we believe this usage is rare, we cannot discount the possibility of human

participants or LLMs treating the mirative marker (or the anti-mirative marker) as sarcastic, with the

intention to indicate an opposite meaning.

Conclusions

In conclusion, this study researched the sensitivity of humans and LLMs to mirativity, the explicit

marking of expectation violations. The two parts of this study can be viewed as investigating the two

roles in discourse: the listener/reader who receives a message, and the speaker/writer who transmits it.

Part 1, where we examined expectations following sentence fragments, is analogous to receiving and a

message, since the listener/reader does not know what the upcoming words will be and generates

expectations for them. Upon encountering a mirative marker, expectations are modified accordingly.

Part 2, where we examined selecting the mirative or anti-mirative connector for sentence pairs, is

analogous to producing and transmitting a message, since the speaker/writer knows the content of the

message they would like to convey. If they recognize the message contains an expectation violation,

they can use a mirative marker to indicate so. We conclude that both humans and LLMs use mirative

markers as cues for calibrating their subsequent expectations during sentence processing, and both

humans and LLMs accurately identify when mirative markers are appropriate, albeit with different

biases. Together, this study highlights the effects of expectation management, and demonstrates how

mirative markers serve as indicators when communicating and processing unexpected information.

Methods

Part 1: Completing sentence fragments with mirative markers

Participants

A total of 40 native English speakers with no diagnosed dyslexia or learning disabilities participated in this part of the study by completing an online questionnaire. Participants were recruited through Facebook posts and word of mouth. All participants completed high-school in an English-speaking country. All participants electronically signed an informed consent form and were compensated for their participation.

Stimuli

For our main analysis we created 30 novel sentence fragments. The sentence fragments were 4-10 words long, all contained a subject and verb, and all terminated where the object is expected to appear. The sentence fragments were constructed such that there was at least one appropriate object that can plausibly continue the sentence, although in many cases there was more than one plausible continuation. Each sentence fragment appeared in two conditions: the *neutral* condition where the sentence fragment began with a neutral marker ("yesterday"), and the *mirative* condition where the sentence fragment began with a mirative marker ("surprisingly").

Procedure

Human: Participants performed an online sentence-completion (cloze) task. They were instructed to type a plausible word that will continue each sentence fragment. Participants were presented with each sentence fragment once: 15 sentences in the neutral condition and 15 in the mirative condition, presented in a pseudo-random order (no more than 3 consecutive trials of the same condition). The assignment of sentence fragments to conditions was counterbalanced between participants. Due to an unfortunate set-up error, one sentence fragment was presented in the mirative condition only, and was excluded from analyses. Responses were recorded while correcting for any typos (any misspelling of, e.g., champagne: champane, shampane etc. was replaced with the correct spelling).

LLM: The following LLMs were included: Llama-3-8B/70B, Llama-3.1-8B/70B, and Llama-3.2-1B/3B (base versions)[65]. These LLMs were chosen because they are open source, allowing to calculate the probability of the top token and the overall entropy. The LLMs were accessed with permission through the *Hugging*

Face transformers library[66]. LLMs were presented with each sentence fragment twice, once per

condition. For each sentence fragment, the full next token probability distribution was recorded.

Analysis

Human data: We calculated the most popular response under the neutral condition and its response

probability under both conditions. We also calculated the entropy of the response distribution per

sentence fragment, per condition. We then tested if the inclusion of a mirative marker modifies the

probability of the top neutral response and the next word entropy using two-tailed paired t-tests.

Probabilities were logit-transformed prior to testing[67].

LLM data: For each sentence fragment we calculated the next token entropy (calculated over the entire

vocabulary) for the neutral and mirative conditions. We also recorded the top 10K tokens under the

neutral condition and their probability in both the neutral and the mirative conditions. Similarly to

humans, we then tested if the inclusion of a mirative marker modifies the probability of the top neutral

response and the next token entropy using two-tailed paired t-tests. Probabilities were logit-

transformed[67]. We also inspected the mean next token probability per marker, calculated across all

sentence fragments, for each of the top 10K tokens in the neutral condition. Data points were smoothed

using locally estimated scatterplot smoothing (LOESS) with span=10.

Follow up testing and analyses (LLM only):

We conducted a follow-up analysis to investigate the scope of the expectation-modification effect of

mirative markers and the factors that modulate it. To this end, we used Llama-3.1-8B, the largest open

source LLM we tested which has shown a significant increase in entropy comparable to human

participants.

Stimuli: We selected 30 passages from the Provo corpus[49]. Passages were selected such that they

contained a minimal number of punctuation marks and non-English characters, no connectors (such as

"however", "for example") or other markers as the first word of the passage (which would have

prevented us from adding a mirative marker in that position). We also made sure that the passage was

not explicitly about expectations or surprises. Passages were 2-3 sentences long (39-62 words, mean

sentence length 21.35 words). Passages were then converted into all possible sentence fragments by

taking every subset of the passage from the third word onwards (e.g., "All that the", "All that the brain",

"All that the brain has", "All that the brain has to", and so on…). Overall, there were 1,365 sentence

fragments. Each sentence fragment appeared in two conditions: the neutral condition, where sentence

fragments began as they were found in the corpus, or the mirative condition, where sentence fragments

began with a mirative marker ("surprisingly") that was added to the passage.

Procedure: procedure was identical to the main analysis. The LLM was presented with each sentence

fragment twice, once per condition.

Analyses: As a dependent variable, we calculated for each sentence fragment the difference in the next

token entropy between the mirative and neutral conditions (positive values indicate higher entropy in

the mirative condition). To assess the scope of the mirative marker's effect on expectations, we used

two separate methods. First, we fit a linear mixed-effects model to the differences in entropy, with a

fixed effect of sentence number within the passage and random intercepts per passage. Second, we fit a

LOESS regression to the difference in entropy with span=20 using the word number in passage. These

methods allowed us to locate a "window of altered expectations", defined as the location and range of

the increased entropy following a mirative marker. The size of the window could be measured in

number of sentences or in number of words. The "window of altered expectations" was found to extend

up to 2 sentences, ranging between 5 to 40 words from the mirative marker.

Following that, we further assessed two additional factors which may influence the increased entropy:

the POS of the top predicted response (and whether it is a content or function word), and the level of

contextual constraint per sentence fragment (i.e., to what extent does the sentence fragment limits the

upcoming probable next tokens). Taking only the data within the "window of altered expectations", we

then fit a linear mixed-effect model to the differences in entropy and tested for the significance of the

fixed effects. The model included the predicted token's syntactic POS (obtained using an automatic POS

tagger[68]), the entropy in the neutral condition (which is taken as a measure for the level of contextual

constraint), a control variable of a cubic B-spline for the word number within the passage, and random

intercepts per passage. For the effects of POS, a post-hoc test was performed, using estimated marginal

means, to compare the content and function POS. All regressions were conducted using *lme4* package[69]

in R[70].

Part 2: Identifying expectation violations

Participants

A total of 63 native English speakers with no diagnosed dyslexia or learning disability participated in this

part of the study by responding to an online questionnaire. Participants were recruited through

Facebook posts and word of mouth. All participants completed high-school in an English-speaking

country. Two different versions of the online questionnaire were presented, with a different order of

the two presented choices. A subset of 22 participants completed both versions of the questionnaire.

One participant was excluded from this study due to not completing the questionnaire. All participants

electronically signed an informed consent form and were compensated for their participation.

Stimuli

For our main analysis we selected 1000 sentence pairs from the Discovery discourse marker dataset[50],

500 per label: for the *mirative* label, sentence pairs were connected with a mirative marker

("surprisingly"), while for the *anti-mirative* label, sentence pairs were connected with an anti-mirative

marker ("unsurprisingly"). The sentences were originally taken from a corpus of natural text, and the

mirative or anti-mirative connector was a part of the sentence pair in the original text. Thus, the

connector which actually appeared in the original text constituted the correct label for that pair. A

reason for using sentence pairs as the stimuli in this task is that pair structure lends itself to setting up

an expectation in the first sentence, indicating a violation of that expectation with a mirative marker

connector, and conveying the violation in the second sentence. Sentence pairs were selected such that

they contained minimal punctuation marks or non-English characters, sentences appeared well-formed,

there were no clear misspellings, and there were no sentences which clearly came from "non-

communicative" texts such as movie scripts or website menus. When we selected the sentence pairs to

be used as stimuli, the correct label (mirative or anti-mirative) was not known, in order to avoid a

possible bias.

Procedure

Human: To estimate human level performance on this task, two lists of 30 randomly sampled sentence

pairs (15 per label in each list) were used presented to human participants through an online

questionnaire. Sentence pairs were presented in a 2-atlernative forced choice paradigm as follows: the

first sentence in the pair was presented, and underneath it a choice was given between two possible

choices, which were the second sentence in the pair either connected with a mirative or an anti-mirative

marker (e.g., "You will only see locals at this restaurant. A) Surprisingly, they have menus in English. B)

Unsurprisingly, the have menus in English.") Participants were instructed to select the most natural

continuation of the first sentence out of the two choices. There were two possible versions of the

questionnaire, one where the choice order presented was mirative marker first and another where the

choice order presented was anti-mirative marker first, for all stimuli in that version. The subset of

participants who responded to both questionnaire versions were presented with different sentence

pairs in each one, and did so with a break of at least a week between them.

LLM: The following LLMs were included: Llama-3-8B-Instruct, Llama-3.1-8B-Instruct, Llama-3.2-1B/3B-

Instruct[65], GPT-3.5, GPT-4/4-0613[71], and GPT-4o/4o-mini[72] ("chat" versions). The meta-Llama series of

LLMs were accessed with permission through the *Hugging Face transformers* library[66]. The chatGPT

series of LLMs were accessed using the OpenAI API. LLMs were presented with the stimuli in a prompt

and their text response was recorded. Each prompt began with the instructions: "Please select the most

natural continuation of the text from the multiple-choice list. Respond with your choice only." Followed

by the first sentence and two possible choices, which were the second sentence of the pair either

connected with a mirative or anti-mirative marker, exactly like the presentation for the human

participants. Responses were set to be deterministic and we considered the top token returned as the

LLM's response. For the chatGPT series of LLMs, which are closed-source and cannot be made to

respond deterministically, the text response did not always match the top token which was provided

separately in the output. In those cases, we coded the LLM response as the top token provided, such

that if it was the beginning of the mirative marker (*Sur/sur/ Sur/ sur*) the response was coded as mirative

and if it was the beginning of the anti-mirative marker (*Un/un/ Un/ un*) the response was coded as anti-

mirative, taking into account different capitalizations and possible inclusions of preceding spaces. If the

response returned by the LLM did not begin with any of the markers, it was coded as an invalid response

and excluded from later accuracy calculations. Each LLM was presented with all the sentence pairs

twice, once where the choice order presented was mirative marker first and another where the choice

order presented was anti-mirative marker first.

Analysis

Human data: Using the participants' responses, we calculated the accuracy and the response rate per

label for each participant, and from that we calculated the mean ± SE of all participants. We also looked

at the accuracy of the top performing participants as an additional benchmark to compare LLM

performance against. Agreement between participants was calculated using Gwet's AC1 metric[73].

LLM data: Accuracy and response rate per label were calculated. An additional stricter measure of

accuracy, which we called j*oint order accuracy*, was calculated by considering the LLM response as

correct only if they selected the correct label for given sentence pair under both presentations with

different order of choices. We then compared LLM performance with the mean human performance

and the top human performance.

Follow up testing and analyses (LLM only):

Data discriminability: To ensure that the high performance of the LLMs was derived from some ability

to identify expectation violations and not by relying on other heuristics, we measured the

discriminability of the data using several simple variables: the length of the first sentence or the second

sentence (measured in tokens using the Llama-3 tokenizer), the perplexity and the max surprisal of the

second sentence given the first sentence without any connecter (measured using Llama-3-8B base

version), the cosine similarity between the first and second sentence (measured using OpenAI's

embeddings model text-embedding-3-small), whether the first sentence was a question or not, and

whether the first or second sentence contained any negativity markings (where the sentence pair

includes any of the following words: *no/not/_n't/none/nothing/never/neither/cannot).* Discriminability

was measured using the ROC and the Area Under the Curve (AUC) was calculated for each variable.

Manipulated stimuli: An additional test, using manipulated stimuli, was conducted on the best

performing LLMs (Llama-3-8B-Instruct, Llama-3.1-8B-Instruct, chatGPT-4, chatGPT-4o). The manipulated

stimuli included using only the first sentence of each pair, using only the second sentence of each pair,

and using sentence pairs wherein the first and second sentences were shuffled randomly within the

same label. Once again, each LLM was presented with all the sentence pairs twice, once where the

choice order presented was mirative marker first and another where the choice order presented was

anti-mirative marker first.

Biases: Beyond comparing human and LLM performance, we also compared their respective biases in

the responses on the task: the mirative bias, which is the propensity to select the mirative marker, and

the order bias, which is the propensity to select the first choice presented. We estimated the biases

using a logistic mixed-effects regression using the mirative response rate as the dependent variable, an

intercept and choice order as the independent variables, and a random intercept per stimulus. For

human participants, we also included a random intercept per participant. The intercept and order

coefficients extracted from the regression model were interpreted as the log odds-ratio to select the

mirative marker over the anti-mirative marker and the log odds-ratio to select the second choice

presented over the first choice presented, respectively. A more conservative estimate for the human

bias was calculated in the same manner but using only the 22 participants who completed both versions

of the questionnaire. All regressions were conducted using *lme4* package[69] in R[70].

References

1. Summerfield, C. & Egner, T. Expectation (and attention) in visual cognition. *Trends in Cognitive Sciences* **13**, 403–409 (2009).

2. *Predictions in the Brain: Using Our Past to Generate a Future*. xiv, 383 (Oxford University Press, New York, NY, US, 2011).

3. Federmeier, K. D. Thinking ahead: The role and roots of prediction in language comprehension. *Psychophysiology* **44**, 491–505 (2007).

4. Kuperberg, G. R. & Jaeger, T. F. What do we mean by prediction in language comprehension? *Language, Cognition and Neuroscience* **31**, 32–59 (2016).

5. Pickering, M. J. & Gambi, C. Predicting while comprehending language: A theory and review. *Psychological Bulletin* **144**, 1002–1044 (2018).

6. Ehrlich, S. F. & Rayner, K. Contextual effects on word perception and eye movements during reading. *Journal of Verbal Learning and Verbal Behavior* **20**, 641–655 (1981).

7. Arnon, I. & Snider, N. More than words: Frequency effects for multi-word phrases. *Journal of Memory and Language* **62**, 67–82 (2010).

8. Smith, N. J. & Levy, R. The effect of word predictability on reading time is logarithmic. *Cognition* **128**, 302–319 (2013).

9. Staub, A. The Effect of Lexical Predictability on Eye Movements in Reading: Critical Review and Theoretical Interpretation. *Language and Linguistics Compass* **9**, 311–327 (2015).

10. Frisson, S., Harvey, D. R. & Staub, A. No prediction error cost in reading: Evidence from eye movements. *Journal of Memory and Language* **95**, 200–214 (2017).

11. Kutas, M. & Hillyard, S. A. Reading Senseless Sentences: Brain Potentials Reflect Semantic Incongruity. *Science* **207**, 203–205 (1980).

12. Kutas, M. & Hillyard, S. A. Brain potentials during reading reflect word expectancy and semantic association. *Nature* **307**, 161–163 (1984).

13. Kutas, M. & Federmeier, K. D. Thirty Years and Counting: Finding Meaning in the N400 Component of the Event-Related Brain Potential (ERP). *Annual Review of Psychology* **62**, 621–647 (2011).

14. Frank, S. L., Otten, L. J., Galli, G. & Vigliocco, G. The ERP response to the amount of information conveyed by words in sentences. *Brain and Language* **140**, 1–11 (2015).

15. Brennan, J. R., Stabler, E. P., Van Wagenen, S. E., Luh, W.-M. & Hale, J. T. Abstract linguistic structure correlates with temporal activity during naturalistic comprehension. *Brain and Language* **157–158**, 81–94 (2016).

16. Willems, R. M., Frank, S. L., Nijhof, A. D., Hagoort, P. & van den Bosch, A. Prediction During Natural Language Comprehension. *Cerebral Cortex* **26**, 2506–2516 (2016).

17. Lopopolo, A., Frank, S. L., Bosch, A. van den & Willems, R. M. Using stochastic language models (SLM) to map lexical, syntactic, and phonological information processing in the brain. *PLOS ONE* **12**, e0177794 (2017).

18. Shain, C., Blank, I. A., van Schijndel, M., Schuler, W. & Fedorenko, E. fMRI reveals language-specific predictive coding during naturalistic sentence comprehension. *Neuropsychologia* **138**, 107307 (2020).

19. Heilbron, M., Armeni, K., Schoffelen, J.-M., Hagoort, P. & de Lange, F. P. A hierarchy of linguistic predictions during natural language comprehension. *Proceedings of the National Academy of Sciences* **119**, e2201968119 (2022).

20. Friston, K. & Kiebel, S. Predictive coding under the free-energy principle. *Philosophical Transactions of the Royal Society B: Biological Sciences* **364**, 1211–1221 (2009).

21. Friston, K. Prediction, perception and agency. *International Journal of Psychophysiology* **83**, 248–252 (2012).

22. Clark, A. Whatever next? Predictive brains, situated agents, and the future of cognitive science. *Behavioral and Brain Sciences* **36**, 181–204 (2013).

23. D'Astolfo, L. & Rief, W. Learning about Expectation Violation from Prediction Error Paradigms - A Meta-Analysis on Brain Processes Following a Prediction Error. *Front Psychol* **8**, 1253 (2017).

24. Delancey, S. Mirativity: The grammatical marking of unexpected information. **1**, 33–52 (1997).

25. Delancey, S. Still mirative after all these years. *Linguistic Typology* **16**, 529–564 (2012).

26. Aikhenvald, A. Y. The essence of mirativity. *Linguistic Typology* **16**, 435–485 (2012).

27. Dickinson, C. Mirativity in tsafiki. *Studies in Language. International Journal sponsored by the Foundation "Foundations of Language"* **24**, 379–422 (2000).

28. Simeonova, V. On the semantics of mirativity. in *Proceedings of the 2015 annual conference of the Canadian Linguistic Association* 1–15 (Linguistic Society of America Washington, DC, 2015).

29. Kadmon, N. & Landman, F. Any. *Linguistics and Philosophy* **16**, 353–422 (1993).

30. Zanuttini, R. & Portner, P. Exclamative Clauses: At the Syntax-Semantics Interface. *Language* **79**, 39–81 (2003).

31. Shannon, C. E. A mathematical theory of communication. *The Bell System Technical Journal* **27**, 379–423 (1948).

32. Roark, B., Bachrach, A., Cardenas, C. & Pallier, C. Deriving lexical and syntactic expectation-based measures for psycholinguistic modeling via incremental top-down parsing. in *Proceedings of the*

2009 Conference on Empirical Methods in Natural Language Processing: Volume 1 - Volume 1 324–333 (Association for Computational Linguistics, USA, 2009).

33. Staub, A., Grant, M., Astheimer, L. & Cohen, A. The influence of cloze probability and item constraint on cloze task response time. *Journal of Memory and Language* **82**, 1–17 (2015).

34. Willems, R. M., Frank, S. L., Nijhof, A. D., Hagoort, P. & van den Bosch, A. Prediction During Natural Language Comprehension. *Cerebral Cortex* **26**, 2506–2516 (2016).

35. Aurnhammer, C. & Frank, S. L. Evaluating information-theoretic measures of word prediction in naturalistic sentence reading. *Neuropsychologia* **134**, 107198 (2019).

36. Grisoni, L., Tomasello, R. & Pulvermüller, F. Correlated Brain Indexes of Semantic Prediction and Prediction Error: Brain Localization and Category Specificity. *Cereb Cortex* **31**, 1553–1568 (2020).

37. Xiang, M. & Kuperberg, G. Reversing expectations during discourse comprehension. *Language, Cognition and Neuroscience* **30**, 648–672 (2015).

38. Rasenberg, M., Rommers, J. & van Bergen, G. Anticipating predictability: an ERP investigation of expectation-managing discourse markers in dialogue comprehension. *Language, Cognition and Neuroscience* **35**, 1–16 (2020).

39. Vaswani, A. Attention is all you need. *Advances in Neural Information Processing Systems* (2017).

40. Radford, A. *et al.* Language models are unsupervised multitask learners. *OpenAI blog* **1**, 9 (2019).

41. Brown, T. *et al.* Language Models are Few-Shot Learners. in *Advances in Neural Information Processing Systems* vol. 33 1877–1901 (Curran Associates, Inc., 2020).

42. Zhao, W. X. *et al.* A Survey of Large Language Models. Preprint at https://doi.org/10.48550/arXiv.2303.18223 (2024).

43. Goldstein, A. *et al.* Shared computational principles for language processing in humans and deep language models. *Nat Neurosci* **25**, 369–380 (2022).

44. Wilcox, E. G., Gauthier, J., Hu, J., Qian, P. & Levy, R. P. On the Predictive Power of Neural Language Models for Human Real-TimeComprehension Behavior. *Proceedings of the Annual Meeting of the Cognitive Science Society* **42**, (2020).

45. Cevoli, B., Watkins, C. & Rastle, K. Prediction as a basis for skilled reading: insights from modern language models. *Royal Society Open Science* **9**, 211837 (2022).

46. Schrimpf, M. *et al.* The neural architecture of language: Integrative modeling converges on predictive processing. *Proceedings of the National Academy of Sciences* **118**, e2105646118 (2021).

47. Heilbron, M., Armeni, K., Schoffelen, J.-M., Hagoort, P. & de Lange, F. P. A hierarchy of linguistic predictions during natural language comprehension. *Proceedings of the National Academy of Sciences* **119**, e2201968119 (2022).

48. Caucheteux, C., Gramfort, A. & King, J.-R. Evidence of a predictive coding hierarchy in the human brain listening to speech. *Nat Hum Behav* **7**, 430–441 (2023).

49. Luke, S. G. & Christianson, K. The Provo Corpus: A large eye-tracking corpus with predictability norms. *Behavior Research Methods* **50**, 826–833 (2018).

50. Sileo, D., Van De Cruys, T., Pradel, C. & Muller, P. Mining Discourse Markers for Unsupervised Sentence Representation Learning. in *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)* (eds. Burstein, J., Doran, C. & Solorio, T.) 3477–3486 (Association for Computational Linguistics, Minneapolis, Minnesota, 2019).

51. Strachan, J. W. A. *et al.* Testing theory of mind in large language models and humans. *Nat Hum Behav* **8**, 1285–1295 (2024).

52. Speer, R. rspeer/wordfreq: v3.0. Zenodo https://doi.org/10.5281/zenodo.7199437 (2022).

53. Pezeshkpour, P. & Hruschka, E. Large Language Models Sensitivity to The Order of Options in Multiple-Choice Questions. Preprint at https://doi.org/10.48550/arXiv.2308.11483 (2023).

54. Wei, S.-L., Wu, C.-K., Huang, H.-H. & Chen, H.-H. Unveiling Selection Biases: Exploring Order and Token Sensitivity in Large Language Models. Preprint at https://doi.org/10.48550/arXiv.2406.03009 (2024).

55. Grice, H. P. Logic and conversation. *Syntax and semantics* **3**, (1975).

56. Smith, N. & Levy, R. Cloze but no cigar: The complex relationship between cloze, corpus, and subjective probabilities in language processing. *Proceedings of the Annual Meeting of the Cognitive Science Society* **33**, (2011).

57. Hao, S. *et al.* Reasoning with Language Model is Planning with World Model. in *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing* (eds. Bouamor, H., Pino, J. & Bali, K.) 8154–8173 (Association for Computational Linguistics, Singapore, 2023).

58. Haijima, W., Nakakubo, K., Suzuki, M. & Matsuo, Y. The Embodied World Model Based on LLM with Visual Information and Prediction-Oriented Prompts. Preprint at https://doi.org/10.48550/arXiv.2406.00765 (2024).

59. Srivastava, A. *et al.* Beyond the Imitation Game: Quantifying and extrapolating the capabilities of language models. Preprint at https://doi.org/10.48550/arXiv.2206.04615 (2023).

60. Kosinski, M. Evaluating Large Language Models in Theory of Mind Tasks. *Proc. Natl. Acad. Sci. U.S.A.* **121**, e2405460121 (2024).

61. Spelke, E. S. & Kinzler, K. D. Core knowledge. *Developmental Science* **10**, 89–96 (2007).

62. Piaget, J. *The Construction of Reality in the Child*. (Routledge, 2013).

63. Kubricht, J. R., Holyoak, K. J. & Lu, H. Intuitive Physics: Current Research and Controversies. *Trends in Cognitive Sciences* **21**, 749–759 (2017).

64. Gibbs, R. W. On the psycholinguistics of sarcasm. *Journal of Experimental Psychology: General* **115**, 3–15 (1986).

65. Grattafiori, A. *et al.* The Llama 3 Herd of Models. Preprint at https://doi.org/10.48550/arXiv.2407.21783 (2024).

66. Wolf, T. *et al.* HuggingFace's Transformers: State-of-the-art Natural Language Processing. Preprint at https://doi.org/10.48550/arXiv.1910.03771 (2020).

67. Jaeger, T. F. Categorical Data Analysis: Away from ANOVAs (transformation or not) and towards Logit Mixed Models. *J Mem Lang* **59**, 434–446 (2008).

68. Bird, S., Klein, E. & Loper, E. Natural Language Processing with Python. (2009).

69. Bates, D., Mächler, M., Bolker, B. & Walker, S. Fitting Linear Mixed-Effects Models Using lme4. *Journal of Statistical Software* **67**, 1–48 (2015).

70. R Core Team. R: A Language and Environment for Statistical Computing. R Foundation for Statistical Computing (2024).

71. OpenAI *et al.* GPT-4 Technical Report. Preprint at https://doi.org/10.48550/arXiv.2303.08774 (2024).

72. OpenAI *et al.* GPT-4o System Card. Preprint at https://doi.org/10.48550/arXiv.2410.21276 (2024).

73. Gwet, K. Handbook of inter-rater reliability: How to estimate the level of agreement between two or multiple raters. *Gaithersburg, MD: STATAXIS Publishing Company* (2001).

Acknowledgements

This study was conducted as part of Benjamin Menashe's doctoral dissertation, under the supervision of Prof. Michal Ben-Shachar at the Gonda Multidisciplinary Brain Research Center, Bar-Ilan University. This project was supported by the Data Science Institute at Bar-Ilan University. B.M. is supported in part by the President's scholarship of BIU.

Competing interests

The authors declare no competing interests.

Data availability statement (mandatory)

The datasets generated and analyzed during the current study will be made available in an open-source public repository [LINK].