A neural circuit framework for economic choice: from building blocks of valuation to compositionality in multitasking

Aldo Battista[1,], Camillo Padoa-Schioppa[2,3,4,5,], and Xiao-Jing Wang[1,5,6,*,]

[1]Center for Neural Science, New York University, New York, NY 10003, USA
[2]Department of Neuroscience, Washington University in St. Louis, St. Louis, MO 63110, USA
[3]Department of Economics, Washington University in St. Louis, St. Louis, MO 63105, USA
[4]Department of Biomedical Engineering, Washington University in St. Louis, St. Louis, MO 63105, USA
[5]Senior author
[6]Lead contact
[*]Correspondence: xjwang@nyu.edu

HIGHLIGHTS

- A biologically plausible recurrent neural network reveals a two-stage framework for economic choice

- Offer value is computed upstream by input weights that store preferences and multiply features

- Competitive recurrent inhibition provides a mechanism for winner-take-all comparison

- A single network learns to multitask via a compositional code of shared and specialized modules

IN BRIEF

Battista et al. develop a biologically plausible recurrent neural network (RNN) that performs diverse economic choice tasks. They reveal a two-stage framework where offer value is computed in a feedforward pathway whose synaptic weights store learned preferences and approximate the multiplication of offer features like quantity and probability, while value comparison, a winner-take-all (WTA) process, is implemented by a competitive recurrent inhibition (CRI) motif. A single network develops a compositional code, combining a shared computational core with specialized modules to achieve multitasking.

SUMMARY

Value-guided decisions are a cornerstone of cognition, yet the underlying circuit-level mechanisms remain elusive. How does the brain compute subjective value by integrating multiple features, such as quantity and probability? Where are learned preferences physically stored? And how do these computations generalize to novel situations? We address these questions by developing a biologically plausible, excitatory-inhibitory recurrent neural network trained on a diverse battery of economic choice tasks. Our analyses reveal a two-stage computational framework. First, value computation occurs upstream of the recurrent circuit, where learned input weights both encode the relative value between goods and approximate the non-linear multiplication of offer features. This feedforward valuation mechanism directly enables the network to generalize to unseen choice options. Second, value comparison is implemented within

the recurrent circuit via a Competitive Recurrent Inhibition (CRI) mechanism, in which specific connectivity motifs between excitatory and inhibitory neurons mediate a robust winner-take-all decision. By training a single network on multiple tasks, we show the emergence of compositional representations that combine a shared computational schema with specialized neural modules. Our model reproduces key neurophysiological findings from the primate orbitofrontal cortex, unifying value computation, comparison, and generalization into a coherent framework with testable predictions for the neural basis of economic choice.

KEYWORDS

Economic Choice/Decision Making, Orbitofrontal Cortex (OFC), Neural Circuit Model, Reinforcement Learning, Value Computation-Comparison, Multiplicative Integration, Competitive Recurrent Inhibition (CRI), Compositionality, Generalization, NeuroAI

INTRODUCTION

Economic choice—the process by which individuals make decisions based on subjective preferences—is fundamental to both human and animal behavior[1,2]. Neuro-scientific studies of economic choice at the single-cell level took off around the turn of this century[3–6]. Understanding economic decisions relies on the concept of *subjective value*, a measure that facilitates the comparison of different choices[6]. By assigning values to available options and making choices based on these values, the brain reduces complex, multidimensional decisions to a single dimension, facilitating efficient decision making[7].

The *orbitofrontal cortex* (OFC) has been identified as a key region supporting good-based decisions. Studies in non-human primates have revealed three groups of neurons in OFC essential for economic choice: *offer value neurons*, encoding the value of individual options; *chosen value neurons*, representing the value of the selected option; and *chosen good neurons*, indicating the identity of the chosen good[6]. As our model operates in the good space and does not simulate spatial contingencies, we will hereafter refer to this latter category as choice neurons for simplicity. These neurons exhibit *menu invariance*, maintaining consistent encoding regardless of alternative options—a property supporting choice transitivity[8]. Electrical stimulation studies have established a causal link between OFC neuronal activity and choice behavior in support of OFC's integral role in the decision circuit[9,10], though the precise division of labor between the OFC and adjacent prefrontal areas in representing different value components remains an active area of investigation[11].

However, the *circuit mechanisms* underlying *value computation* and *value comparison* remain largely unknown[10,12]. Specifically, key open questions remain: How does a neural circuit, using additive synaptic inputs, implement the fundamentally multiplicative computation needed to calculate an expected value from probability and quantity? Where in the circuit are the learned relative values that define economic indifference points physically stored? And how are these value representations composed to allow a single circuit to flexibly perform multiple, diverse tasks? Moreover, existing studies often focus on single-neuron analyses and binary choice tasks, which do not fully capture neural population dynamics as well as the complexity of real-world decisions involving multiple options and attributes[7].

To gain mechanistic insights, computational modeling is essential[13–15]. However, previous models have been limited by being either overly constrained, assuming a strict segregation of neuronal roles and tuning properties not observed experimentally[16], or too abstract, employing architectures like Gated Recurrent Units (GRUs) that lack clear biological counterparts[17].

To bridge these gaps and provide concrete, testable hypotheses for these open questions, we developed a biologically plausible computational model. Our model consists of a continuous-time recurrent neural network of the vanilla type (with no GRUs) that adheres to *Dale's law* with 80% excitatory (E) and 20% inhibitory (I) neurons and long-range excitatory projections[18,19]. Neurons have biologically realistic single-unit time constants. We trained the network using the *Proximal Policy Optimization (PPO)* reinforcement learning algorithm[20,21]. This approach is more biologically plausible than supervised learning, as it mirrors how animals are trained via reward feedback[21]. Furthermore, PPO's training stability enabled us to use a simple vanilla RNN, avoiding less biologically plausible gated architectures.

Here, we show that networks trained on a diverse battery of economic choice tasks discover a two-stage computational framework. First, value computation occurs in a feedforward manner, where learned input weights physically store subjective preferences and approximate the non-linear multiplication of offer features. This mechanism directly enables generalization to novel offers[22]. Second, value comparison is implemented within the recurrent circuit via a Competitive Recurrent Inhibition (CRI) motif that mediates a robust winner-take-all decision[23,24]. Finally, we demonstrate that this architecture supports multitasking through the emergence of a compositional code that combines a shared computational core with specialized neural modules[25,26]. Our model reproduces key neurophysiological findings from the primate OFC[6] and provides a coherent, mechanistically grounded framework for the neural basis of economic choice.

RESULTS

Training neural networks for multiple economic choice tasks

To investigate the neural mechanisms underlying economic decisions, we developed biologically plausible excitatory-inhibitory recurrent neural networks (RNNs) capable of performing a range of complex economic choice tasks (Figure 1A). These tasks were designed to capture key aspects of decision making, requiring the networks to compute and compare values in diverse contexts involving different goods, quantities, probabilities, and temporal structures.

Each task began with a fixation period, followed by a rule cue indicating the current task, the presentation of offers, and finally, a response phase. Choice tasks included the *standard task*, where two goods were offered in varying quantities; the *risky task*, similar to the standard task but with probabilistic outcomes; the *bundles task*, where offers consisted of bundles of two goods; the *ternary task*, involving choices among three goods; and the *sequential task*, where two goods were presented sequentially in random order, and choices relied on the network's working memory[7].

The networks were designed to be biologically plausible, consisting of continuous-time vanilla RNNs with excitatory and inhibitory neurons that obeyed Dale's law (Figure 1B)[18,19,27]. Inputs included fixation signals, quantities, and probabilities of the offered goods, as well as task-specific rule cues. The network produced two distinct outputs: a policy for action selection (the "actor") and a value function that predicted the expected discounted future reward (the "critic"). The policy output represented the probabilities over available actions at each time step, while the value function provided an ongoing estimate of the expected return. This dual-readout architecture guided action selection and enabled the network to compute and evaluate the value of the presented options.

We trained the networks using Proximal Policy Optimization (PPO)[20], a reinforcement learning algorithm suitable for optimizing performance in complex tasks, which simultaneously optimizes both action selection and value estimation. This approach mirrors how animals are typically trained in laboratory tasks (e.g., through trials and errors, with reward feedback[21]) and

is thus more biologically plausible than supervised learning. The training involved an agent-environment interaction loop, where the network received inputs and selected actions leading to new stimuli and action outcomes.

The networks achieved high performance across all tasks, satisfying two performance criteria: on a held-out test set of $25,000$ trials, they achieved at least 99% of trials completed without fixation breaks and selected the offer with the highest value in at least 90% of those trials (Figure S1).

To illustrate the network's behavior, we present sample trials for each choice task from a network trained simultaneously on all tasks (Figure S2). In each trial, the network selects the highest-value offer among those presented. The value function output predicts the expected return shortly after the offers are presented, demonstrating the network's ability to compute the options' value. The policy outputs show the correct action selection during the response phase and indicate that the network maintains fixation during the required periods. Notably, the network's forthcoming choice can often be inferred from the policy outputs during the offer presentation phase, well before the response period begins. This observation suggests that the network separates the economic decision (what to choose) from the motor command (when to respond).

In the sequential task, we analyzed the example trial shown in Figure S2E. In this trial, the network received the first offer and maintained this information in memory during the subsequent delay period. Upon presentation of the second offer, the network compared it with the first offer. During the response phase, the network selected the higher-value offer, indicating effective integration of sequential information. This performance suggests that the network developed working memory capabilities, as it must retain information about the first offer over the delay period to make the correct choice in the sequential task. Without such working memory processes, the network would have been unable to compare the offers and select the higher value.

These results demonstrate that our RNNs could effectively perform multiple and complex choice tasks. Indeed, the networks achieved high accuracy across all tasks and were able to process different types of information, such as quantities, probabilities, and temporal sequences, required for these tasks. Thus, the networks developed the necessary computational mechanisms to perform value-based decisions in diverse contexts.

Networks learn a robust, value-based behavioral strategy

Choice data were analyzed using logistic regression[7]. For example, in the risky task, each trial involved choices between goods C and E, each varying in quantity and probability. Initially, plotting the networks' choices in the space of quantities and probabilities revealed no clear decision boundary (Figure 2A, left and center panels). However, when we fitted a logistic regression model to the choice data, a linear separation emerged in the resulting *offer value space* (Figure 2A, right panel and B). This space was constructed by calculating offer values as the product of quantity (q_X), probability (p_X) raised to a power ($\hat{\gamma}$), and an intrinsic value ($\hat{\rho}_X$). In this model, $\hat{\gamma}$ and $\hat{\rho}_X$ were key behavioral parameters estimated by the regression: $\hat{\gamma}$ quantified the network's risk attitude, and $\hat{\rho}_X$ represented the inferred relative value between goods (see STAR Methods).

Extending this analysis to the other tasks revealed a consistent strategy across the networks. Indeed, in the standard task, networks compared the computed values of two goods based on their quantities and intrinsic values, reliably selecting the good with the higher value. Similarly, in the bundles task, networks computed the total value of each bundle by summing the values of individual goods and chose the bundle with the higher total value. In the ternary task, despite the increased complexity of comparing three options, networks reliably selected the good with the highest computed value. In the sequential task, networks effectively maintained the value of the first offer in working memory and compared it with the second offer to make the optimal

choice (Figure S3). ₁₇₆

Logistic analysis allowed us to assess whether the network had truly learned the relative values of the different goods from reward feedback alone. To address this critical question, we treated the relative values as free parameters in the model ($\hat{\rho}_X$) and estimated them directly from the network's choice behavior. This analysis revealed a striking correspondence: the *inferred relative values* ($\hat{\rho}_X$) closely matched the *ground-truth intrinsic values* (ρ_X) used to generate rewards during training across all tasks (Figure 2C). This one-to-one mapping confirms that the networks successfully learned the hidden value structure of the environment and used this internal knowledge to guide their decisions.

We also examined *behavioral biases* such as risk attitude and order bias. For tasks involving probabilistic outcomes, such as the risky, bundles, ternary, and sequential tasks, we estimated the risk attitude parameter ($\hat{\gamma}$) for each network (Figure 2D). A $\hat{\gamma} > 1$ indicated risk aversion, while $\hat{\gamma} < 1$ signified risk-seeking behavior. As illustrated in Figure 2D, while the networks were risk-neutral on average ($\hat{\gamma} \approx 1$), individual networks exhibited a range of mild risk preferences, with $\hat{\gamma}$ values typically falling between 0.8 and 1.2. This variability was not systematically imposed but likely arose from stochastic factors in the training process, such as random weight initializations and the order of trials encountered during learning, as the networks were trained to performance criteria without being overtrained. Notably, the risk attitude of a given network was largely consistent across all tasks involving probability, providing behavioral evidence for a shared computational mechanism for processing risk—a key principle of compositionality that we revisit later. In the sequential task, we assessed the estimated order bias ($\hat{\epsilon}'$), which quantified a preference for either the first or second offer regardless of their values. Again, while the average order bias across networks was negligible, individual networks exhibited slight preferences, reflecting stochastic fluctuations during learning.

Finally, we assessed the relationship between *task complexity and choice accuracy*. The logistic regression provided a measure of choice consistency ($\hat{\eta}$) proportional to the slope of the psychometric function. We found that network performance scaled with task complexity: networks achieved higher choice consistency ($\hat{\eta}$) and accuracy on simpler tasks, such as the standard task, and lower performance on more complex ones, such as the sequential task (Figure 2E). This pattern aligns with empirical observations in non-human primates, suggesting that task difficulty impacts decision performance[7].

To ensure our findings were not the result of a single idiosyncratic solution, we trained and analyzed 20 independent networks on the full set of tasks. A critical question was whether these networks, each starting with different random initializations, would converge on a similar behavioral strategy. Our analysis revealed a remarkable degree of consistency. While minor quantitative differences existed between networks, logistic regression showed that all 20 networks robustly converged on the same fundamental value-based strategy: they successfully learned the intrinsic relative values of the goods, exhibited comparable choice consistency, and developed modest idiosyncratic biases in risk attitude and choice order (Figures 2C-E). This behavioral convergence suggests that the underlying computational mechanisms found by the learning algorithm represent a robust solution to the tasks. Whether different networks also converged on similar internal connectivity and dynamics is a central question addressed in the following sections.

Single-neuron signatures of value computation and comparison

To investigate the neural code for economic choice, we first examined the activity of individual neurons. These single-neuron properties were not an idiosyncrasy of one particular network. Across the 20 independently trained networks, we consistently observed the emergence of the

same key functional cell types—offer value, chosen value, and choice neurons—indicating that these neural representations were a convergent solution for solving the tasks. The following analyses are therefore representative of a general coding strategy found across all networks. We assessed whether individual neurons represented decision variables similar to those observed in the orbitofrontal cortex (OFC) of non-human primates[6,28]. First, we focused on tasks involving binary choices between goods C and E (standard, risky, and sequential tasks). As in neurophysiology studies, we defined a series of candidate variables that could potentially explain the activity of individual cells, including individual offer values (OVC, OVE), the chosen value (CV), the choice (CH), the value sum (OVC + OVE), and the value difference (OVC - OVE). We also defined two good-specific chosen values (CVC, CVE), which represented the value of a good (C or E) when that good was chosen and zero otherwise.

The correlation matrix shown in Figure 3A revealed significant patterns due to the task design. In particular, the chosen value correlated positively with the maximum of the offer values and with the value sum, as it represented the higher of the two offer values. Similarly, the choice was strongly correlated with the value difference between the offers since larger differences made the choice more deterministic. The conjunctive variables CVC and CVE were also correlated with their respective offer values and choices, reflecting their composite nature.

Analyzing the tuning properties of individual neurons, we found that many neurons displayed significant linear relationships with specific decision variables. Figure 3B illustrated examples of neurons tuned to different variables in binary choice tasks. One neuron showed activity that increased linearly with the offer value of good E, another neuron's firing rate correlated with the chosen value, and a third neuron was selective for the binary choice of good E. These neurons exhibited significant coefficients of determination ($R^2 > 0.9$, $p < 0.05$), indicating robust tuning (see STAR Methods).

To investigate the dynamics of neuronal selectivity, we calculated the fraction of neurons tuned to each decision variable at each time point (Figure 3C). Using a standard statistical criterion for selectivity (see STAR Methods), we found that a substantial fraction of neurons—peaking around 40–50% for key variables—were significantly tuned. This proportion was consistent with experimental observations in primate OFC[6]. The temporal evolution of this selectivity revealed a clear sequence that mirrored the decision process: during the offer presentation phase, the fraction of neurons encoding offer value peaked first, followed by a rise in the proportion of neurons encoding the chosen value, and finally the choice.

For the sequential task, by stimulus onset, we indicated the onset of the *second* stimulus. At this point, the network held information about the first stimulus in working memory and processed the second stimulus, enabling it to compare both offers to make a decision (see STAR Methods). This approach ensured that our analysis captured the period when the network had access to all relevant information for the decision.

Interestingly, both excitatory and inhibitory neurons showed robust, dynamic selectivity. While the proportion of selective inhibitory neurons was higher than that of excitatory neurons (Figure 3C), it was crucial to consider the absolute numbers. Given the network's $80/20$ E/I ratio, the total number of selective excitatory neurons was substantially larger, forming the primary substrate for encoding. The high fraction of selective inhibitory cells was consistent with their critical role in shaping circuit dynamics and actively participating in encoding decision variables[29].

To assess the temporal stability of the neuronal tuning, we computed a Temporal Stability Index (TSI) for each neuron (Figure 3D; see STAR Methods). The majority of neurons showed high TSI values, indicating consistent encoding of a single decision variable throughout the trial. However, some neurons displayed lower TSI scores, suggesting dynamic coding where neurons might switch from encoding offer value to encoding choice as the decision process unfolded. This dynamic tuning aligned with observations in OFC, where neurons can change their selectivity over the course of a decision[28].

We next investigated whether neurons encoded decision variables categorically or conjunctively. To directly parallel analyses from primate electrophysiology[28], we analyzed the distribution of R^2 differences ($\triangle R^2$) between pairs of variables (Figure 3E; see STAR Methods). This analysis revealed a dual coding scheme depending on neuronal specialization. While the general population of task-modulated neurons exhibited widespread mixed selectivity (see Supplementary Figure S4), a distinct subpopulation of highly specialized neurons developed categorical representations. When we isolated these strongly selective neurons by applying a stringent inclusion criterion ($R^2 \geq 0.5$ for at least one variable), the resulting $\triangle R^2$ distributions became clearly bimodal (Figure 3E). This indicated that these "expert" neurons tended to encode one variable exclusively over another, allowing for an unambiguous representation of key decision variables to emerge from the network.

Examining the sign of encoding, we found that both excitatory and inhibitory neurons displayed a mix of positive and negative correlations with their respective decision variables (Figure 3F). While a bias towards positive encoding was apparent, the emergence of a population of negatively tuned neurons was a critical feature. This positive bias was not related to the valence of outcomes, as synaptic signs were fixed by Dale's Law. Instead, it likely reflected the network's architecture: with all external inputs being excitatory, the circuit had a predominantly excitatory drive that may have favored positive tuning slopes. In contrast, the negative tuning was a non-trivial emergent property of the learned recurrent circuitry. As shown later, this heterogeneity—especially the negative encoding generated by targeted inhibition—was crucial for enhancing the contrast between competing options during value comparison. This overall diversity in tuning, including the bias towards positive slopes, was consistent with empirical findings in primate OFC[6,28,30,31].

In conclusion, our single-neuron analyses reproduced key features of neuronal encoding observed in OFC of non-human primates during economic choice tasks[6]. The sequential activation of neurons encoding offer value, chosen value, and choice reflected the computational stages of decision making. The active participation of inhibitory neurons and the presence of both positive and negative tuning expanded our understanding of the neural mechanisms underlying value computation and comparison. These findings supported the notion that economic decisions emerged from distributed computations within recurrent neural circuits, with neurons dynamically encoding relevant variables to guide behavior.

Population-level signatures of value computation and comparison

To understand how neural populations collectively implemented economic choice, we analyzed their dynamics in the state space. While single-neuron analyses revealed the building blocks of the neural code, population-level analyses uncovered the geometric principles of the computation.

We first quantified the complexity of the neural representations across all tasks by measuring the embedding dimensionality of the population activity using the participation ratio (PR). The PR provided an intuitive, continuous estimate of the number of dimensions a neural population used to represent information (see STAR Methods for formal definition). The analysis revealed that for all binary choice tasks, the neural activity was highly constrained to a low-dimensional manifold (PR ≈ 2), increasing to PR ≈ 3 only for the three-choice ternary task (Figure 4A). This low-dimensional structure suggested that the network efficiently organized its activity around the few variables essential for the decision, a pattern that held for both excitatory and inhibitory populations.

At the level of the population, the decision manifested as a geometric separation of neural states. Focusing on the risky task as a representative example, at the end of the offer period,

the collective state of the network for each trial—projected onto the first two principal components—occupied a position in a highly structured cloud (Figure 4B). This cloud was organized by key decision variables: the states were separated into distinct clusters based on the network's final choice, while the position within each cluster was graded by the chosen value. The full dynamic process leading to this state, where the population evolved from a common starting point and separated over time as the decision formed, is shown in Supplementary Video S1. To systematically quantify this encoding across the entire population, we regressed the principal component projections against all task variables (Figure 4C). The results revealed a remarkably consistent coding scheme across all tasks for the first two components: PC1 consistently and strongly encoded the chosen value, while PC2 robustly encoded the choice itself. The role of the third principal component (PC3), however, was highly task-dependent. While PC3 was largely un-encoded in the simpler binary tasks, the regression analysis confirmed that it became critical for representing the third option in the ternary task (Fig. 4C, third column). This demonstrated a highly efficient coding strategy: a core, two-dimensional geometric solution for value and choice was conserved across all contexts, and the network flexibly recruited additional dimensions only as required by the specific demands of more complex tasks.

This emergent geometric solution was not an idiosyncratic feature of a single network. We found that this same separation of population states into choice-specific clusters, organized by chosen value, was a convergent strategy discovered by all 20 independently trained networks, demonstrating the robustness of this computational solution (see Supplementary Figure S5 for examples from two other networks).

Dissecting the circuit mechanisms of value computation

A targeted lesion analysis, in which we removed all recurrent connections ($W^{\text{rec}} = 0$), revealed a stark functional dissociation between feedforward and recurrent processing. While the lesioned networks were unable to make choices, their feedforward architecture could still represent value-related information (Supplementary Fig. S6, S7). This causal analysis established that value computation is largely a feedforward process, while value comparison is a distinct, competitive process that is fundamentally reliant on the recurrent circuit. Having isolated the role of the feedforward pathway, we next sought to dissect the specific circuit mechanisms it employed to solve two fundamental computational problems: how to integrate multiple offer features into a single value, and where to store the learned subjective preferences that define those values.

First, logistic analyses described above indicated that our networks chose by computing the expected values of individual options (Fig. 2). This observation raised a computational question: How did a circuit endowed only with additive synapses approximate the non-linear *multiplication* of quantity and probability required to solve the task? To shed light on this issue, we performed a computational dissection. The results of our analyses were unequivocal: activity in the isolated feedforward pathway was far better explained by the multiplicative product of quantity and probability than by their additive sum (Fig. 5B). This finding provided strong mechanistic evidence that the network's feedforward architecture was specifically configured to approximate a non-linear, multiplicative-like computation. The network achieved this by developing a powerful function approximation over the domain of its experience, a hallmark of neural networks equipped with non-linear activation functions, rather than by learning an abstract, symbolic rule. Importantly, while this dissection analysis provided strong evidence for the mechanism's *capability*, a stronger test for a learned computational principle required demonstrating its use by the intact network to solve novel challenges. We returned to this issue in a later section (see 'Multiplicative value computation enables generalization to novel offers').

Second, where are the learned subjective *relative values* (ρ_X) physically stored? To move be-

yond correlation and propose a specific, falsifiable hypothesis, we posited that these preferences are encoded in the synaptic strengths of the input projections. Placing this learned parameter upstream is computationally efficient, as it allows the network to generalize to choices between novel goods without needing to retrain the more complex recurrent decision circuitry. To test this hypothesis, we performed a dedicated set of simulations, training 50 independent networks on the risky task while systematically varying the intrinsic value of one good across networks. A strong, significant linear correlation emerged between the behaviorally inferred relative values and the average learned input weights for that good's quantity (Fig. 5E; $R^2 = 0.84$). This result provided robust evidence for our hypothesis: learned economic preferences are physically embedded in the synaptic efficacies of long-range inputs.

Finally, why did the population geometry in the feedforward pathway rotate to represent the *sum and difference* of offer values, rather than the individual offer values themselves (Supplementary Fig. S7B)? We hypothesized that this geometry was not arbitrary but was specifically optimized for the downstream decision process. A representation based on the sum and difference of values is computationally advantageous for a downstream readout, as the chosen value (the primary variable for the critic and actor) is highly correlated with the value sum under the uniform sampling distribution for the offers used during training. To identify the structural basis for this organization, we first examined the correlation structure of the input weights, which revealed a mix of specialized and integrated pathways for the different offer features (Fig. 5A). To directly quantify this wiring scheme, we performed a Selectivity Index (SI) analysis on the input weights. This revealed a sophisticated dual architecture (Supplementary Fig. S9): in addition to two populations of highly specialized neurons that exclusively processed a single offer's value (corresponding to the sharp peaks at SI $= -1$ and $+1$), we found a large, unimodal population of mixed-selective neurons that received balanced inputs from both offers (the broad distribution centered at SI $= 0$). To causally verify that this mixed-selective wiring was sufficient to produce the geometric rotation, we constructed a simplified feedforward "toy model" designed to replicate the computation in the isolated feedforward pathway. A model with only segregated input populations failed to reproduce the rotated geometry, instead representing the two offer values on orthogonal axes (Fig. 5C). However, after incorporating a population of mixed-selective neurons, the model successfully replicated the value sum/difference representation observed in the lesioned networks (Fig. 5D). This dissection demonstrated how the network learned a specific, non-trivial input wiring scheme that is explicitly structured to facilitate the downstream decision.

Taken together, these analyses revealed that the feedforward pathway to the decision circuit performed sophisticated value computation, integrating external features with internal, learned preferences via a specific, learned connectivity structure that was optimized for the downstream decision.

Dissecting the circuit mechanisms of value comparison

Having established that value was computed in an upstream, feedforward stage, we next investigated how the recurrent circuit *compares* these values to generate a decision. To distinguish between the computational outcome—a winner-take-all (WTA) competition—and the circuit mechanism that implemented it, we analyzed the network's learned connectivity and dynamics. Our analyses revealed that the WTA outcome was implemented by a specific E/I motif we termed Competitive Recurrent Inhibition (CRI). We then causally validated the necessity of this motif with a series of specific lesion analyses that went beyond predictable manipulations and tested the roles of its key constituent parts.

We first analyzed the activity of the network's policy output units during the risky task (Fig. 6A). These units represented the actions available to the agent and were distinct from the activity of

the recurrent neurons themselves. Their dynamics revealed a competition that unfolded well before the go cue. During stimulus presentation, the "Fixation" output was dominant and gated the motor response (Fig. 6A, first panel). Meanwhile, a subtle but decisive competition emerged between the outputs associated with the choice options. When good C was the forthcoming choice (red traces), its corresponding output showed a higher activity that progressively diverged from the output for good E (Fig. 6A, third vs. fourth panels), and vice versa when good E was chosen (blue traces). This demonstrated that the network internally committed to a choice long before the response was executed. This early commitment was further corroborated by our finding that reaction times (RTs) were not significantly influenced by the decision difficulty (Supplementary Fig. S10A). In contrast, the critic's "Expected Return" output robustly encoded the chosen value, independent of the choice identity (Fig. 6A, fifth panel). This WTA dynamic at the output level was further confirmed by regression analysis, which showed that a choice output's activity was predictive of the corresponding offer's value only on trials where it was chosen (Fig. 6B).

To identify the specific circuit motif responsible for this WTA competition, we moved from the full 256×256 recurrent weight matrix (Supplementary Fig. S10B, left), whose low-rank structure (Supplementary Fig. S10B, right) suggested that the network's dynamics were governed by a few powerful connectivity motifs[32], to an interpretable circuit diagram. We developed a *many-to-one functional abstraction* pipeline, shown for a single network in Supplementary Figure S11. This process involved classifying each neuron by cell type (E/I) and functional selectivity, grouping them into functional pools, and averaging their connection strengths. The result of this process, when averaged across all 20 networks, revealed the Competitive Recurrent Inhibition (CRI) motif (Fig. 6C). In this circuit, visualized in Figure 6D, choice-selective excitatory neurons drove same-choice inhibitory neurons, which in turn preferentially suppressed the excitatory neurons selective for the competing choice. For instance, 'Choice C' excitatory neurons strongly recruited inhibitory neurons that then powerfully suppressed 'Choice E' excitatory neurons, implementing the WTA dynamic.

This targeted, cross-choice inhibition provided a mechanistic explanation for two key findings. First, it directly implemented the WTA competition. Second, it explained the emergence of heterogeneous tuning. While feedforward inputs were excitatory, the targeted recurrent inhibition from the CRI motif could powerfully subtract from a neuron's input drive, effectively inverting the response profiles of some neurons to create negatively encoding cells that sharpened the contrast between choice representations. We hypothesized that these negatively tuned neurons were computationally critical. To test this, we performed a targeted lesion analysis, silencing all neurons with significant negative encoding of offer value and chosen value. This manipulation substantially impaired decision-making across all tasks, significantly reducing choice accuracy (Supplementary Fig. S12). This result provided causal evidence that negatively tuned neurons, a direct consequence of the CRI architecture, were essential for robust value comparison.

Finally, to causally validate that the CRI motif itself was the necessary mechanism for value comparison, we performed a highly specific "functional ablation" analysis. This non-trivial manipulation went beyond simply removing recurrence and instead tested the specific hypothesis about which functional cell groups mattered most. We computationally silenced entire functional pools of neurons and evaluated the impact on performance in the risky task. As shown in Supplementary Figure S13, the results revealed a distributed and critical role for the choice-selective populations. While silencing the choice-selective inhibitory population 'CHE_I' had the largest impact on trial completion, ensuring choice accuracy relied on a broader set of neurons. Critically, silencing choice-selective inhibitory populations ('CHC_I', 'CHE_I') and the chosen-value excitatory population ('CV_E') had effects on accuracy that were as large, or even larger, than silencing their excitatory choice counterparts. This confirmed that both the excitatory and inhibitory components of the choice-selective populations formed the functional backbone of the

decision circuit. ⁠464

This same core CRI motif was found across all choice tasks (Supplementary Fig. S10C), ⁠465 suggesting it was a general and robust strategy for implementing competitive selection in neural ⁠466 circuits. In summary, our findings demonstrated that the recurrent network performed value ⁠467 comparison through the CRI mechanism—structured recurrent connectivity that implemented ⁠468 winner-take-all dynamics and generated heterogeneous neuronal tuning to maximize contrast ⁠469 between competing offers. ⁠470

Compositionality in economic decisions ⁠471

A key feature of intelligent behavior is the ability to flexibly solve multiple tasks by composing a ⁠472 repertoire of learned skills. To investigate if a single neural circuit could develop such compo- ⁠473 sitional representations for economic choice, we analyzed a group of 20 networks trained on all ⁠474 five tasks simultaneously. We sought to understand how the network balanced the use of shared ⁠475 neural resources against the need for task-specific computations. ⁠476

First, we examined the neural subspaces activated during the rule cue period. We found ⁠477 that low-dimensional subspaces for the standard, risky, bundles, and ternary choice tasks were ⁠478 largely overlapping, as indicated by the small principal angles between them (Fig. 7AB). This ⁠479 shared geometry, which was consistent with the highly correlated rule input weights for these ⁠480 tasks (Fig. 7A), meant that a dimensionality-reduction basis found for one task would general- ⁠481 ize well to the others. This finding also clarified the role of the explicit task cue: for these four ⁠482 tasks, the cue became largely redundant after training because the network had developed a ⁠483 shared internal context. However, for the sequential task, the cue remained critical to signal ⁠484 its unique temporal structure and engage the necessary working memory circuits. The analy- ⁠485 sis revealed two key specializations: the sequential task occupied a distinct, nearly orthogonal ⁠486 subspace, reflecting its unique working memory demands, while the ternary task, though over- ⁠487 lapping, required an additional dimension to represent the third choice option (Fig. 4A). Together, ⁠488 these results showed that the network developed a core set of shared dimensions for common ⁠489 computations while flexibly allocating specialized subspaces for unique task demands. ⁠490

While these tasks shared a common economic choice structure, they were specifically de- ⁠491 signed to impose unique computational demands that test for true compositionality. For ex- ⁠492 ample, the *ternary task* demanded that the winner-take-all competition be scaled from two to ⁠493 three options, while the *sequential task* introduced the distinct requirement of working mem- ⁠494 ory to hold a value over time. To test if the network developed distinct modules to meet these ⁠495 specific demands, we clustered neurons based on their firing rate variance across tasks, ana- ⁠496 lyzing excitatory and inhibitory populations separately (Fig. 7C). This analysis revealed a similar ⁠497 functional organization in both cell populations, identifying principal clusters: a population of neu- ⁠498 rons shared across all tasks, a cluster specialized for the ternary task, and a cluster exclusively ⁠499 dedicated to the sequential task. To causally test the function of these identified modules, we ⁠500 performed a series of targeted lesion analyses. We computationally silenced all neurons belong- ⁠501 ing to each of the clusters individually and re-evaluated performance across all tasks. The results ⁠502 revealed a clear functional dissociation (Fig. S14). Lesioning the sequential-task cluster induced ⁠503 a performance drop specifically in the sequential task while leaving performance on other tasks ⁠504 largely intact. Similarly, lesioning the ternary-task cluster selectively impaired performance on ⁠505 the ternary task. Conversely, lesioning the shared cluster resulted in a profound deficit across ⁠506 all five tasks. This provided direct causal evidence that the network developed a compositional ⁠507 architecture of both shared and functionally specialized modules to meet unique task demands. ⁠508

We further quantified the relationships between tasks by examining the distributions of task ⁠509 variance differences for each neuron across task pairs (Fig. 7D; see STAR Methods). Following ⁠510

established methods[25], we classified the shape of these distributions to characterize the organizational relationship between the neural populations recruited for different tasks. The analysis revealed a spectrum of relationships, including patterns that resembled archetypal *inclusive* relationships (where one task's neural representation is a subset of another's, characterized by a large peak at zero and a smaller peak at ± 1) and *disjoint* relationships (where tasks recruit largely separate sets of neurons, identified by bimodal distributions with peaks at ± 1). This supported a flexible network architecture that balanced common processing with task-specific adaptations.

To visualize whether all 20 networks converged on a similar compositional architecture, we needed to compare their population-level representations. However, a direct comparison of principal components is not meaningful, as each independently trained network develops its own arbitrary set of principal component axes—akin to each network learning its own private coordinate system. To overcome this, we used a rotational alignment procedure (Procrustes analysis; see STAR Methods) to map each network's state space onto a common reference frame, effectively translating all the private coordinate systems into a single, shared language. Projecting the mean population activity for each task into this aligned space (Fig. 7E) revealed a robust, convergent solution: across all networks, the representations for the four simultaneous-offer tasks consistently clustered together, while the sequential task formed a separate, distinct cluster, graphically underscoring the unique neural dynamics required for working memory.

A critical question was whether this compositional architecture was a unique product of the multitasking paradigm, or if single-task training would suffice. To address this, we performed a systematic "zero-shot" generalization analysis. We trained five separate groups of networks (10 per group) on each of the five tasks individually and then tested their performance on all other tasks without any further training (Fig. S15). The results revealed a pattern of strongly asymmetric generalization that causally demonstrated the compositional nature of the learned skills. For example, networks trained on the complex ternary task could immediately perform the simpler standard and risky tasks with high accuracy. Conversely, networks trained only on the standard task failed catastrophically on the sequential task, as they had not learned a working memory component. This analysis confirmed that while multitasking is not required to solve any single task, it is a training condition that enables a single circuit to develop a flexible repertoire of reusable computational modules.

Finally, we tested whether the network could leverage prior experience to accelerate the acquisition of more complex skills. We designed a series of curriculum learning protocols for three complex target tasks: Ternary, Bundles, and Sequential (Fig. 7F). For each target, we compared the learning speed under three conditions, using 10 independent networks for each condition: (1) training from a random initialization (Rand), (2) pre-training on the simpler Standard task before learning the target, and (3) pre-training on the Standard and then the Risky task before learning the target. This design allowed us to isolate how learning foundational components (e.g., temporal structure from the Standard task, then probabilistic integration from the Risky task) facilitated the acquisition of a final, more complex skill. The additional experience from pre-training was not a confound but rather the experimental variable of interest, as it was the proposed mechanism for schema formation. The critical question was whether this prior experience provided a useful computational scaffold that sped up future learning. The results showed a clear affirmative (Fig. 7F); for each target task, there was a graded and significant acceleration in learning, with the number of trials required to learn the *final* task in the curriculum decreasing at each stage of pre-training. This demonstrated the formation of a cognitive "schema"—a reusable set of computational components that was transferred to the new context and accelerated subsequent learning.

In summary, our analyses demonstrated that networks trained to be multitask-proficient developed a compositional architecture that combined a shared circuit core with functionally spe-

cialized, task-specific modules. The formation of these reusable schemas supported efficient learning and flexible decision making across diverse contexts.

Multiplicative value computation enables generalization to novel offers

A hallmark of intelligent behavior is the ability to generalize learned knowledge to new situations. We previously hypothesized that our networks solved economic choice tasks by learning a functional approximation of multiplication in their feedforward pathways. Here, we provided the definitive behavioral validation for this claim in the intact network. We challenged networks trained on a limited subset of experiences to infer the general valuation rule and apply it to entirely novel offers[22].

We trained 10 networks exclusively on the risky task using a constrained, orthogonal set of offers. In this regime, the network never saw quantity and probability vary simultaneously, forcing it to learn their contributions independently (Fig. 8A; see STAR Methods). After training, networks performed with high accuracy on this familiar, constrained set. We then assessed generalization by testing the networks on a full, unconstrained set of offers, which included countless novel combinations of quantity and probability that the networks had never seen before (Fig. 8B).

The networks demonstrated robust generalization. Behaviorally, they accurately selected the higher-valued offer despite the novelty of the stimuli. Logistic regression analysis confirmed that the core valuation strategy was preserved: key behavioral parameters, including inferred relative value and risk attitude, remained remarkably stable between the constrained training and the unconstrained test sets (Fig. 8C). While choice consistency and accuracy showed a slight, expected decrease on the more challenging novel set, overall performance remained high, confirming robust generalization at the behavioral level.

This powerful generalization was a direct consequence of the network having learned the underlying mathematical structure of the task, and it provided the conclusive evidence for a multiplicative strategy that was sought in the previous section. The network's success demonstrated that it learned a computation functionally equivalent to multiplication, as a simpler, non-multiplicative strategy, such as one based on an additive heuristic, would have lacked a principle for evaluating these novel quantity-probability conjunctions and would have failed this test.

Crucially, this behavioral generalization was supported by a consistent neural implementation. We performed principal component analysis on the population activity of the networks as they processed novel offers. The analysis revealed that the underlying low-dimensional geometry of the decision remained unchanged. Population activity again separated into distinct, choice-specific clusters, with activity within each cluster graded by the chosen value, mirroring the structure observed in standard-trained networks (Fig. 4B and Supplementary Fig. S16). This showed that the network applied the exact same low-dimensional computational strategy to both familiar and novel situations, providing a robust neural basis for its generalizable behavior.

Our findings thus align with and provide a mechanistic explanation for observations in non-human primates, where subjects also generalize valuation processes to novel stimuli[22]. The model shows how neural circuits can leverage the learning of fundamental computational principles, such as approximate multiplication, to achieve flexible, adaptive behavior that extends far beyond their direct experience.

DISCUSSION

In this work, we developed a biologically plausible E/I recurrent neural network to advance and test specific hypotheses about the circuit basis of economic choice. Our primary contributions

lie not in replicating known neural patterns, but in proposing concrete circuit mechanisms for fundamental, yet poorly understood, computations. We show how: (1) a neural circuit with additive synapses can approximate the non-linear multiplication of reward features, a mechanism that provides a novel explanation for the ability to generalize learned values to unseen offers; (2) subjective economic preferences are physically stored in the synaptic weights of long-range inputs to the decision circuit; (3) value comparison is implemented by a specific Competitive Recurrent Inhibition (CRI) motif, a detailed E/I connectivity pattern that underlies winner-take-all (WTA) dynamics; and (4) a single circuit can achieve multitasking through compositional representations that flexibly allocate shared and specialized neural resources. Together, these findings constitute a coherent, mechanistically grounded framework for value-based decision making.

Notably, the networks were not explicitly trained to adopt any particular risk preference, yet they developed idiosyncratic risk attitudes, with some becoming mildly risk-averse and others risk-seeking (Figure 2D). This emergent variability, likely arising from stochastic factors in the training process such as weight initialization and trial history, mirrors the individual differences observed in biological agents and suggests that such biases can arise naturally from reinforcement learning principles without a specialized objective. This provides a powerful computational platform for testing hypotheses about the circuit origins of choice biases[33], including those observed in neuropsychiatric disorders characterized by impaired decision-making. For example, one could manipulate circuit properties hypothesized to be altered in a given condition (e.g., E/I balance) and examine the specific consequences for risk preference and choice consistency. Furthermore, this framework generates new, testable predictions. For instance, to induce risk aversion, one could train networks on skewed reward distributions. Based on our model's architecture, we predict that a learned risk-averse policy would be implemented upstream of the decision circuit, through systematic changes in the input weights that distort the representation of probability, a mechanism consistent with neurophysiological findings in OFC[7,34].

A central finding is that a model constrained by core biological principles reproduces a wide range of neurophysiological phenomena observed in the primate OFC. Neurons in the model exhibit tuning for key variables like offer value, chosen value, and choice[1,6], with both excitatory and inhibitory cells displaying heterogeneous—positive and negative—tuning profiles. This heterogeneity, particularly the emergence of negatively tuned neurons, is a non-trivial property of the learned recurrent circuitry. We propose that these neurons are not epiphenomenal but are computationally critical for robust decisions by enhancing the contrast between competing options. A targeted lesion analysis confirmed that silencing negatively tuned neurons impaired choice accuracy. This result provides a strong, causal demonstration of their functional importance and offers a testable prediction for future optogenetic studies.

That both excitatory and inhibitory cells were found to be deeply involved in encoding decision variables highlights a broader conceptual point about circuit computation. Modern experimental tools allow targeting specific cell types, which can encourage hypotheses of the form "cell type A performs the function X". However, our work underscores the principle that neural function is an emergent property of network interactions, not an isolated property of a cell class. For example, inhibitory neurons in our model are not simply 'choice neurons' or 'offer value neurons'; rather, their structured connectivity within the recurrent E/I circuit is what *enables* the network to perform value comparison and generates the diversity of tuning required for robust computation. This network-centric perspective aligns with a long-standing tradition in computational neuroscience[23] and provides a theoretical lens for interpreting cell-type-specific data in the context of distributed network computations.

At the population level, our results demonstrate that these computations are organized within low-dimensional dynamics where specific neural activity patterns correspond to decision variables[32], with chosen values potentially encoded as line attractors[35]. Our study provides testable hypotheses about the implementation of these computations. We propose that the non-linear

multiplication of reward features occurs upstream of the recurrent circuit and that the learned relative values that define economic indifference points are physically stored in the synaptic efficacy of these input projections. This architecture not only provides a mechanism for generalization to novel offers[22], but also explains how value comparison can be implemented by a more general-purpose competitive dynamic within the recurrent circuit itself[23,24,29].

With respect to compositionality, our networks developed both shared and specialized representations to solve five distinct economic choice tasks. While four of the tasks elicited highly overlapping neural activity patterns, the sequential task required a specialized neural subspace, likely to support its unique working memory demands. In other words, our networks reused a core set of computational components for common operations (e.g., value integration and comparison) while flexibly engaging specialized modules when faced with novel computational demands[25,26]. This flexible allocation of resources, which facilitated accelerated learning via curriculum protocols[36,37], suggests a general principle for how the brain balances task-specific adaptation with the efficiency of a shared architecture[38,39].

Although this study was motivated by neurophysiology findings from OFC, we intend our model to serve as a general framework for how a biologically plausible circuit can implement core computations for economic choice. This naturally leads to considering how this framework fits within a multi-regional architecture and engages with key debates in the field. An important example is the "Rudebeck/Murray challenge", which posits a functional double dissociation between OFC and ventrolateral prefrontal cortex (VLPFC) based on lesion studies[11]. While a large body of neurophysiological work provides detailed evidence that OFC neurons robustly encode economic variables including risk and probability[40–43], our model does not presuppose that OFC is the sole locus of computation. As technical advances enable simultaneous recording from multiple brain regions, it is increasingly recognized that neural coding of information is distributed; value computation is no exception and likely involves several cortical and subcortical brain regions. A major question for the field is how to understand the functional specialization of brain regions like OFC in a manner that is compatible with distributed neural representations[44]. In fact, our framework is readily extendable to test distributed architectures. For instance, the abstract 'probability' input to our network could be modeled as an output from a VLPFC-like area, and their interaction could be studied. Future multi-regional models that can reconcile findings from both lesion and neurophysiology studies are a crucial next step for the field, and our work provides a robust single-module component for such larger-scale theories.

It is also important to clarify the simplifying assumptions of our model. The use of an explicit task cue aligns with experimental paradigms where rules are cued[34], but our analysis reveals this cue becomes largely redundant for four of the five tasks as a shared internal context is formed (Figure 7A). Similarly, modeling a fixation-maintenance signal at the same output level as good-based choices is a deliberate simplification. We acknowledge that our model is a framework for economic choice computation, not strictly a model of OFC anatomy. Indeed, as with virtually all trained RNNs to date, our model is limited to a single neural population, whereas the brain is a multi-regional system. In the brain, action selection and fixation control are likely managed by a broader network, including fixation-related neurons in the frontal eye fields (FEF) and superior colliculus (SC)[45] and downstream areas like the lateral prefrontal cortex (LPFC), which must integrate value signals from OFC-like areas to guide behavior[46,47]. Investigating these multi-regional interactions, as well as uncued task switching[27], represents a critical direction for future work.

In conclusion, our work establishes a robust computational framework for exploring the neural circuits underlying economic decisions. By providing a mechanistically-grounded and biologically-constrained model, we bridge single-neuron observations with population-level dynamics and offer a new suite of testable hypotheses to guide future empirical research into the neural basis of decision-making.

RESOURCE AVAILABILITY

Lead contact

Requests for further information and resources should be directed to and will be fulfilled by the lead contact, Xiao-Jing Wang (xjwang@nyu.edu).

Materials availability

This study did not generate new unique reagents or biological materials.

Data and code availability

All original code to train network models and generate data for this study have been deposited on GitHub at `https://github.com/aldobattista/neural-circuit-economic-choice` and are publicly available as of the date of publication. Any additional information is available from the lead contact upon reasonable request.

ACKNOWLEDGMENTS

We thank G. Tavoni, C. Constantinople, E. Rich, and V. Fascianelli for their critical comments on the manuscript, as well as current and former members of the Wang lab, especially W. Soo, G. Benigno, Maryada, Y. Liu, V. Goudar, and A. Fanthomme, for fruitful discussions. This work was supported by the Swartz Foundation (A.B.); ONR grant N00014-23-1-2040 (X.-J.W.); NIH grants R01MH104494 (X.-J.W.), R01DA032758 (X.-J.W.), the National Institute of Neurological Disorders and Stroke (NINDS) and National Institute on Drug Abuse (NIDA) of the National Institutes of Health grant number U19NS123714 (X.-J.W.), and R01DA055709 (C.P.-S.); and the NYU IT High Performance Computing resources, services, and staff expertise.

AUTHOR CONTRIBUTIONS

A.B., C.P.-S., and X.-J.W. conceptualized the study. A.B. developed the software, trained the networks, performed the data analysis, and visualized the results under the supervision of X.-J.W. C.P.-S. provided critical intellectual input throughout the project. A.B. wrote the initial draft of the manuscript. All authors contributed to manuscript revision and approved the final version.

DECLARATION OF INTERESTS

The authors declare no competing interests.

DECLARATION OF GENERATIVE AI AND AI-ASSISTED TECH-NOLOGIES

During the preparation of this work, the author(s) used Gemini 2.5 Pro (Google) to assist in improving the clarity and prose of the manuscript. After using this tool, the author(s) reviewed

and edited the content as needed and take full responsibility for the content of the publication. ₇₃₆

SUPPLEMENTAL INFORMATION INDEX ₇₃₇

Supplemental Information includes 16 figures and 2 videos and can be found with this article ₇₃₈ online. ₇₃₉

Figures S1–S16. A single PDF document containing all supplementary figures, their legends, ₇₄₀ and descriptions for Supplementary Videos S1 and S2. ₇₄₁

Video S1. Dynamic visualization of decision formation in an intact trained network, related to ₇₄₂ Figure 4. (MP4) ₇₄₃

Video S2. Dynamic visualization of failed decision formation in a lesioned network, related to ₇₄₄ Figure S7. (MP4) ₇₄₅

Figure 1. Task structures and network architecture. 748

(A) Schematic representation of economic choice tasks. Each trial begins with a fixation period, 749
followed by a rule cue indicating the current task. Offers are then presented, followed by a 750
response phase. Tasks include the standard, risky, bundles, ternary, and sequential tasks. For 751
each offer, the circle's radius indicates quantity, the filled area indicates probability, and the color 752
corresponds to the intrinsic value of the good (A–E). 753

(B) Architecture of the biologically plausible recurrent neural network. The network consists of 754
excitatory (E) and inhibitory (I) neurons adhering to Dale's law. Inputs include fixation signals, 755
offer quantities, offer probabilities, and task-specific rule cues. The network has two readouts: 756

a policy output for action selection (the "actor") and a value function output that predicts the expected return (the "critic"). The network is trained using Proximal Policy Optimization in an agent-environment interaction loop.

Figure 2. Logistic behavioral analysis of networks trained on all choice tasks.

(A) Choice patterns in the *risky task* from a representative network. Left and center panels: In the space of raw offer features (quantity and probability), the network's choices (red for C, blue for E) are not linearly separable. Right panel: When plotted in the computed *offer value space* ($OV_X = \hat{\rho}_X \times q_X \times p_X^{\hat{\gamma}}$), where parameters are fit to behavior, the same choices become clearly separable by the identity line, demonstrating a value-based strategy.

(B) Psychometric function for the risky task, visualized as a 3D surface plot. The surface shows the percentage of choices for good E as a function of the log-ratio of quantities ($\log(q_E/q_C)$) and the log-ratio of probabilities ($\log(p_E/p_C)$). The steep sigmoidal shape of the surface demonstrates highly consistent, value-driven choices.

(C) Inferred relative values ($\hat{\rho}_X$) across all 20 networks (each point is one network) closely match the ground-truth intrinsic values used in training (ρ_X, dashed lines). The learned value ranking ($\hat{\rho}_A > \hat{\rho}_B > \hat{\rho}_C > \hat{\rho}_D > \hat{\rho}_E$) is robustly preserved.

(D) Estimated behavioral biases are minimal on average. Left: The risk attitude parameter ($\hat{\gamma}$)

clusters around 1.0 (risk-neutrality), with minor variability across networks. Right: The order bias ($\hat{\epsilon}'$) in the sequential task is centered at zero (no bias).

(E) Estimated choice consistency ($\hat{\eta}$) and choice accuracy vary systematically with task complexity. Performance is highest for the simple standard task and lowest for the more cognitively demanding sequential task, mirroring empirical findings.

Figure 3. Single-neuron analysis in networks trained on all economic choice tasks.

(A) Correlation matrix of behavioral variables for binary choice tasks. The matrix reveals intrinsic correlations in the task structure, such as the positive correlation between chosen value (CV) and the sum of offer values.

(B) Example tuning curves from individual neurons in binary choice tasks. The activity of different neurons is strongly predictive of the offer value of good E (OVE), the chosen value (CV), and the choice (CH). The high coefficients of determination ($R^2 > 0.9$) for these examples illustrate the existence of highly specialized neurons within the network.

(C) Fraction of neurons selective for each decision variable over time. Using a standard statistical criterion ($p < 0.05$ and $R^2 \geq 0.005$), the analysis reveals a substantial fraction of selective neurons in both the excitatory (left) and inhibitory (right) populations. Note that while the fraction of selective inhibitory neurons is high, the absolute number of selective excitatory neurons is larger due to the $80/20$ E/I ratio in the network.

(D) Distributions of the Temporal Stability Index (TSI). Most neurons show high TSI values, indicating stable encoding of a single decision variable throughout the trial.

(E) Categorical encoding in a subpopulation of highly specialized neurons. Histograms show the difference in R^2 values between pairs of decision variables. The analysis includes only neuron-time points where at least one of the variables was explained with high efficacy ($R^2 \geq 0.5$). The resulting bimodal distributions suggest that these highly specialized neurons encode variables categorically.

(F) Distribution of regression slopes for selective neurons. Both excitatory and inhibitory populations contain a mix of positively and negatively tuned cells for each key decision variable.

Figure 4. Low-dimensional population dynamics reveal a robust geometric solution for decision-making.

(A) Neural dimensionality across tasks, measured by the participation ratio (PR). For both excitatory (blue) and inhibitory (orange) populations, neural activity was low-dimensional (PR ≈ 2), increasing to PR ≈ 3 only for the three-choice ternary task.

(B) In the risky task, at the end of the offer period, population states were geometrically organized by the key decision variables. Each point represents the population state for a single trial projected onto the first two principal components (PC1, PC2). The states were separated into distinct clusters based on choice (red vs. blue), and the position within each cluster was graded by the chosen value.

(C) Summary of population-level encoding across all tasks, quantified by the coefficient of deter-

mination (R^2) from regressing PC projections against key behavioral variables. The x-axis labels represent: offer values for specific tasks (*OVA*: Offer Value of good A; *OVBC*: Offer Value of Bundle B+C; *OVDE*: Offer Value of Bundle D+E), a general value metric (*Val Sum*: the sum of all presented offer values), and post-decision variables (*CV*: Chosen Value; *CHA*, *CHBC*, *CHDE*: categorical variables for the Choice of good A, bundle B+C, or bundle D+E, respectively). The heatmaps revealed a consistent coding scheme: PC1 robustly encoded the Chosen Value (CV), PC2 encoded the Choice, and PC3 was selectively recruited for the ternary task.

Figure 5. Dissecting the circuit mechanisms of value computation.

(A) Correlation matrix of input weight vectors for offer features. Strong positive correlations (bright colors) were observed between the weights for features of the same offer (e.g., quantity C, q_C, and probability C, p_C), with weaker correlations across offers.

(B) Evidence for multiplicative computation in the isolated feedforward pathway. In networks where recurrent connections had been lesioned, the first two principal components (PCs) of population activity were far better explained by the multiplicative product of quantity and probability (OVC, OVE) than by their additive sum (OVCs, OVEs). Bars show the mean coefficient of

determination (R^2) across 20 networks; error bars denote SEM.

(C) A simplified feedforward toy model with segregated input populations failed to reproduce the geometric rotation observed in the trained lesioned networks (Supplementary Fig. S7B). PCA of the hidden units' activity revealed principal axes corresponding to the individual offer values (Offer Value C on PC1, Offer Value E on PC2).

(D) Extending the toy model with a population of mixed-selective neurons causally reproduced the rotation of the principal component axes to align with value sum and difference. This validated the hypothesis that mixed-selective wiring (Supplementary Fig. S9) explains this key geometric feature.

(E) Learned relative values are physically encoded in input weights. We trained 50 independent networks while systematically varying the ground-truth intrinsic value of good C (ρ_C) across five groups (from 1 to 5). The plot reveals a strong, significant linear correlation ($R^2 = 0.84$) between the average learned input weight for that good's quantity (y-axis) and the behaviorally inferred relative value ($\hat{\rho}_C$), estimated from each network's choices (x-axis). The color of each point indicates the ground-truth intrinsic value (ρ_C) used to train that network. Thus, networks trained with a higher intrinsic value (brighter magenta points) not only developed stronger corresponding input weights but also learned to choose in a way that accurately reflected this value, as the inferred behavioral values ($\hat{\rho}_C$) clustered correctly around their ground-truth counterparts.

Figure 6. Dissecting the neural circuit mechanisms of value comparison.

(A) Average activity of the policy (actor) and value (critic) output nodes during the risky task, separated by the network's final choice (red for chosen C, blue for chosen E). From left to right: fixation output, an irrelevant choice output, choice C output, choice E output, and the critic's expected return output. The divergence between red and blue traces for the choice outputs indicated an early commitment.

(B) Heatmap of regression R^2 values, confirming the WTA dynamic. Each panel corresponds to a different task. Within each heatmap, a row represents one of the network's output nodes (e.g., 'BC Ch' is the policy output for choosing good C or B+C). The columns represent key decision variables, including general variables like Chosen Value ('CV') and conjunctive, choice-specific variables like 'CVBC' (the value of good C or B+C on trials where C or B+C was chosen, and zero otherwise). Each cell shows the R^2 from a simple linear regression of a single output node's activity against a single variable across all trials. The analysis revealed a clear WTA pattern: the activity of a choice-specific output node was strongly predicted by its corresponding conjunctive value variable, but not by the variable for the competing choice. For instance, in the 'Risky' task, the 'BC Ch' output was well-predicted by 'CVBC' (bright square), but poorly predicted by 'CVDE' (dark square). This demonstrated selective encoding of the chosen option's value at the level of the actor.

(C) Reduced connectivity matrix, averaged across 20 networks. This was derived by averaging synaptic weights between functionally defined neural pools (see Supp. Fig. S11). The matrix revealed the Competitive Recurrent Inhibition (CRI) motif, highlighted by the strong inhibitory connections (dark blue squares, outlined in green) from choice-selective inhibitory neurons to competing choice-selective excitatory neurons.

(D) A simplified circuit diagram visualizing the CRI motif. Choice-selective excitatory neurons (e.g., CHE_E) drove same-choice inhibitory neurons (e.g., CHE_I), which in turn suppressed the excitatory neurons corresponding to the competing choice (e.g., CHC_E), implementing the WTA competition. Acronyms: OVC/E (Offer Value C/E), CV (Chosen Value), CHC/E (Choice C/E). Subscripts $_E$ and $_I$ denote excitatory and inhibitory populations, respectively.

Figure 7. Compositionality and curriculum learning in networks trained on all tasks.

(A) Correlation matrix of rule cue input weights. High correlation (light colors) among the standard, risky, bundles, and ternary tasks indicated a shared input structure, distinct from the sequential task.

(B) Subspace analysis of population activity during the rule cue period. The heatmap shows the principal angles between the low-dimensional subspaces for each pair of tasks. Small angles (dark colors) between the subspaces for standard, risky, bundles, and ternary tasks indicated they shared a common representational geometry. The sequential task occupied a distinct, nearly orthogonal subspace (bright colors).

(C) Clustering of neurons by task variance revealed shared and specialized modules. Neurons (columns), separated by excitatory and inhibitory populations, were grouped based on their normalized activity variance across tasks (rows). The analysis identified distinct clusters, including a shared module of neurons active across all tasks, a specialized module of neurons with high variance primarily in the ternary task, and another specialized module almost exclusively dedi-

cated to the sequential task.

(D) Histograms of fractional task variance differences between task pairs, calculated as $(TV_1 - TV_2)/(TV_1 + TV_2)$ for each neuron. The shapes of these distributions revealed the organizational relationship between the neural populations recruited for different tasks. Following Yang et al.[25], we characterized these shapes, which revealed patterns resembling archetypal *inclusive* relationships (e.g., Standard-Bundles) and *disjoint* relationships (e.g., Ternary-Sequential).

(E) Visualization of task representations in a common, rotationally-aligned PCA space that aggregates data from all 20 networks. Each point represents the mean population activity for one task in one network. The four simultaneous-offer tasks (Standard, Risky, Ternary, Bundles) formed a tight cluster, while the Sequential task formed a separate cluster, highlighting its distinct neural dynamics.

(F) Curriculum learning accelerated skill acquisition. Box plots show the normalized number of training trials required to learn only the *final* complex target task (Ternary, Bundles, or Sequential) in each curriculum. For each target, learning speed was compared across three conditions (10 networks per condition): from random initialization (Rand), after pre-training on the Standard task (Rand→Stand), or after pre-training on Standard and then Risky tasks (Rand→Stand→Risky). Pre-training provided a significant, graded acceleration in learning the final task, demonstrating schema reuse.

Figure 8. Multiplicative value computation enables robust generalization to novel offers in networks trained on a constrained risky task.

(A) Training was conducted on a constrained set of offers where quantity and probability were not varied simultaneously, forcing the network to learn their contributions independently. Left and Center: The offer space for goods C and E during training forms a cross-like structure. Each point is a trial, colored by the network's choice (red for C, blue for E). This visualization shows that the network was never exposed to trials where both quantity and probability varied from their central values. Right: Despite the constrained inputs, choices plotted in the computed offer value space are correctly and linearly separated by the identity line (dashed green), indicating successful learning on the training set.

(B) Generalization was tested on a full, unconstrained set of offers containing novel combinations of quantity and probability. Left and Center: The test offer space covers the full range of quantity-probability combinations, most of which were never seen during training. Right: The network correctly evaluates these novel offers, as its choices remain well-separated by the identity line. This demonstrates successful generalization of the learned value function to unseen regions of the offer space.

(C) Key behavioral parameters are stable between training and testing, confirming that the network applies the same valuation strategy to novel stimuli. Each colored dot represents one of ten trained networks. Box plots show the median and interquartile range. *Inferred Relative Value C* and *Risk Attitude* remain unchanged between the training set (Train) and the novel test set (Test). *Choice Consistency* and *Choice Accuracy* show a slight, expected decrease on the more challenging novel test set but remain high, confirming robust and effective generalization.

References

1. Padoa-Schioppa, C. (2011). Neurobiology of economic choice: a good-based model. Annual review of neuroscience *34*, 333–359.

2. Padoa-Schioppa, C., and Conen, K.E. (2017). Orbitofrontal cortex: a neural circuit for economic decisions. Neuron *96*, 736–754.

3. Platt, M.L., and Glimcher, P.W. (1999). Neural correlates of decision variables in parietal cortex. Nature. *400*, 233–238.

4. Sugrue, L.P., Corrado, G.C., and Newsome, W.T. (2004). Matching behavior and representation of value in parietal cortex. Science *304*, 1782–1787.

5. Barraclough, D.J., Conroy, M.L., and Lee, D. (2004). Prefrontal cortex and decision making in a mixed-strategy game. Nat. Neuroscience *7*, 404–410.

6. Padoa-Schioppa, C., and Assad, J.A. (2006). Neurons in the orbitofrontal cortex encode economic value. Nature *441*, 223–226.

7. Padoa-Schioppa, C. (2022). Logistic analysis of choice data: A primer. Neuron *110*, 1615–1630.

8. Padoa-Schioppa, C., and Assad, J.A. (2008). The representation of economic value in the orbitofrontal cortex is invariant for changes of menu. Nature neuroscience *11*, 95–102.

9. Ballesta, S., Shi, W., Conen, K.E., and Padoa-Schioppa, C. (2020). Values encoded in orbitofrontal cortex are causally related to economic choices. Nature *588*, 450–453.

10. Ballesta, S., Shi, W., and Padoa-Schioppa, C. (2022). Orbitofrontal cortex contributes to the comparison of values underlying economic choices. Nature communications *13*, 4405.

11. Rudebeck, P.H., Saunders, R.C., Lundgren, D.A., and Murray, E.A. (2017). Specialized representations of value in the orbital and ventrolateral prefrontal cortex: desirability versus availability of outcomes. Neuron *95*, 1208–1220.

12. Raghuraman, A.P., and Padoa-Schioppa, C. (2014). Integration of multiple determinants in the neuronal computation of economic values. Journal of Neuroscience *34*, 11583–11603.

13. Solway, A., and Botvinick, M.M. (2012). Goal-directed decision making as probabilistic inference: a computational framework and potential neural correlates. Psychological review *119*, 120.

14. Friedrich, J., and Lengyel, M. (2016). Goal-directed decision making with spiking neurons. Journal of Neuroscience *36*, 1529–1546.

15. Zhang, Z., Cheng, Z., Lin, Z., Nie, C., and Yang, T. (2018). A neural network model for the orbitofrontal cortex and task space acquisition during reinforcement learning. PLOS Computational Biology *14*, e1005925.

16. Rustichini, A., and Padoa-Schioppa, C. (2015). A neuro-computational model of economic decisions. Journal of neurophysiology *114*, 1382–1398.

17. Song, H.F., Yang, G.R., and Wang, X. (2017). Reward-based training of recurrent neural networks for cognitive and value-based tasks. Elife *6*, e21492.

18. Song, H.F., Yang, G.R., and Wang, X. (2016). Training excitatory-inhibitory recurrent neural networks for cognitive tasks: a simple and flexible framework. PLoS computational biology *12*, e1004792.

19. Yang, G.R., and Wang, X. (2020). Artificial neural networks for neuroscientists: a primer. Neuron *107*, 1048–1070.

20. Schulman, J., Wolski, F., Dhariwal, P., Radford, A., and Klimov, O. (2017). Proximal policy optimization algorithms. arXiv preprint arXiv:1707.06347.

21. Sutton, R., and Barto, A. (2018). Reinforcement learning: An introduction. MIT press.

22. Bongioanni, A., Folloni, D., Verhagen, L., Sallet, J., Klein-Flügge, M.C., and Rushworth, M.F. (2021). Activation and disruption of a neural mechanism for novel choice in monkeys. Nature *591*, 270–274.

23. Wang, X.J. (2002). Probabilistic decision making by slow reverberation in cortical circuits. Neuron *36*, 955–968.

24. Wong, K.F., and Wang, X.J. (2006). A recurrent network mechanism of time integration in perceptual decisions. Journal of Neuroscience *26*, 1314–1328.

25. Yang, G.R., Joglekar, M.R., Song, H., Newsome, W.T., and Wang, X. (2019). Task representations in neural networks trained to perform many cognitive tasks. Nature neuroscience *22*, 297–306.

26. Driscoll, L.N., Shenoy, K., and Sussillo, D. (2024). Flexible multitask computation in recurrent networks utilizes shared dynamical motifs. Nature Neuroscience pp. 1–15.

27. Liu, Y., and Wang, X.J. (2024). Flexible gating between subspaces in a neural network model of internally guided task switching. Nature Communications *15*, 6497.

28. Padoa-Schioppa, C. (2013). Neuronal origins of choice variability in economic decisions. Neuron *80*, 1322–1336.

29. Roach, J.P., Churchland, A.K., and Engel, T.A. (2023). Choice selective inhibition drives stability and competition in decision circuits. Nature communications *14*, 147.

30. Padoa-Schioppa, C. (2009). Range-adapting representation of economic value in the orbitofrontal cortex. Journal of Neuroscience *29*, 14004–14014.

31. Kennerley, S.W., Behrens, T.E., and Wallis, J.D. (2011). Double dissociation of value computations in orbitofrontal and anterior cingulate neurons. Nature neuroscience *14*, 1581–1589.

32. Dubreuil, A., Valente, A., Beiran, M., Mastrogiuseppe, F., and Ostojic, S. (2022). The role of population structure in computations through neural dynamics. Nature neuroscience *25*, 783–794.

33. Fascianelli, V., Battista, A., Stefanini, F., Tsujimoto, S., Genovesio, A., and Fusi, S. (2024). Neural representational geometries reflect behavioral differences in monkeys and recurrent neural networks. Nature Communications *15*, 6479.

34. Shi, W., Ballesta, S., and Padoa-Schioppa, C. (2022). Economic choices under simultaneous or sequential offers rely on the same neural circuit. Journal of Neuroscience *42*, 33–43.

35. Pereira-Obilinovic, U., Hou, H., Svoboda, K., and Wang, X.J. (2024). Brain mechanism of foraging: Reward-dependent synaptic plasticity versus neural integration of values. Proceedings of the National Academy of Sciences *121*, e2318521121.

36. Bengio, Y., Louradour, J., Collobert, R., and Weston, J. (2009). Curriculum learning. In Proceedings of the 26th annual international conference on machine learning. pp. 41–48.

37. Goudar, V., Peysakhovich, B., Freedman, D.J., Buffalo, E.A., and Wang, X.J. (2023). Schema formation in a neural population subspace underlies learning-to-learn in flexible sensorimotor problem-solving. Nature Neuroscience *26*, 879–890.

38. Johnston, W.J., and Fusi, S. (2023). Abstract representations emerge naturally in neural networks trained to perform multiple tasks. Nature Communications *14*, 1040.

39. Johnston, W.J., Fine, J.M., Yoo, S.B.M., Ebitz, R.B., and Hayden, B.Y. (2024). Semi-orthogonal subspaces for value mediate a binding and generalization trade-off. Nature Neuroscience pp. 1–13.

40. O'Neill, M., and Schultz, W. (2010). Coding of reward risk by orbitofrontal neurons is mostly distinct from coding of reward value. Neuron *68*, 789–800.

41. O'Neill, M., and Schultz, W. (2013). Risk prediction error coding in orbitofrontal neurons. Journal of Neuroscience *33*, 15810–15814.

42. O'Neill, M., and Schultz, W. (2015). Economic risk coding by single neurons in the orbitofrontal cortex. Journal of Physiology-Paris *109*, 70–77.

43. Ferrari-Toniolo, S., and Schultz, W. (2023). Reliable population code for subjective economic value from heterogeneous neuronal signals in primate orbitofrontal cortex. Neuron *111*, 3683–3696.

44. Wang, X.J. (2022). Theory of the multiregional neocortex: large-scale neural dynamics and distributed cognition. Ann. Rev. Neurosci. *45*, 533–560.

45. Schall, J.D., and Thompson, K.G. (1999). Neural selection and control of visually guided eye movements. Annual review of neuroscience *22*, 241–259.

46. Cai, X., and Padoa-Schioppa, C. (2014). Contributions of orbitofrontal and lateral prefrontal cortices to economic choice and the good-to-action transformation. Neuron *81*, 1140–1151.

47. Yim, M.Y., Cai, X., and Wang, X.J. (2019). Transforming the choice outcome to an action plan in monkey lateral prefrontal cortex: A neural circuit model. Neuron *103*, 520–532.

48. Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L. et al. (2019). Pytorch: An imperative style, high-performance deep learning library. Advances in neural information processing systems *32*.

49. Huang, S., Dossa, R.F.J., Ye, C., Braga, J., Chakraborty, D., Mehta, K., and Araújo, J.G. (2022). Cleanrl: High-quality single-file implementations of deep reinforcement learning algorithms. Journal of Machine Learning Research *23*, 1–18. URL: `http://jmlr.org/papers/v23/21-1342.html`.

50. Brockman, G., Cheung, V., Pettersson, L., Schneider, J., Schulman, J., Tang, J., and Zaremba, W. (2016). Openai gym. . `arXiv:arXiv:1606.01540`.

51. Harris, C.R., Millman, K.J., van der Walt, S.J., Gommers, R., Virtanen, P., Cournapeau, D., Wieser, E., Taylor, J., Berg, S., Smith, N.J., Kern, R., Picus, M., Hoyer, S., van Kerkwijk, M.H., Brett, M., Haldane, A., del Río, J.F., Wiebe, M., Peterson, P., Gérard-Marchant, P., Sheppard, K., Reddy, T., Weckesser, W., Abbasi, H., Gohlke, C., and Oliphant, T.E. (2020). Array programming with NumPy. Nature *585*, 357–362. URL: `https://doi.org/10.1038/s41586-020-2649-2`. doi: `10.1038/s41586-020-2649-2`.

52. Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., and Duchesnay, E. (2011). Scikit-learn: Machine learning in Python. Journal of Machine Learning Research *12*, 2825–2830.

53. Markram, H., Toledo-Rodriguez, M., Wang, Y., Gupta, A., Silberberg, G., and Wu, C. (2004). Interneurons of the neocortical inhibitory system. Nature reviews neuroscience *5*, 793–807.

54. Douglas, R.J., and Martin, K.A. (2007). Recurrent neuronal circuits in the neocortex. Current biology *17*, R496–R500.

55. Schultz, W., Dayan, P., and Montague, P.R. (1997). A neural substrate of prediction and reward. Science *275*, 1593–1599.

56. Glimcher, P.W. (2011). Understanding dopamine and reinforcement learning: the dopamine reward prediction error hypothesis. Proceedings of the National Academy of Sciences *108*, 15647–15654.

57. Kingma, D., and Ba, J. (2014). Adam: A method for stochastic optimization. arXiv preprint arXiv:1412.6980.

STAR Methods

Key resources table

REAGENT or RESOURCE	SOURCE	IDENTIFIER
Software and Algorithms		
Custom code for network training and data generation	This paper	https://github.com/aldobattista/neural-c
PyTorch	Paszke et al.[48]	https://pytorch.org/
CleanRL	Huang et al.[49]	https://github.com/vwxyzjn/cleanrl
OpenAI Gym	Brockman et al.[50]	https://gymnasium.farama.org/
Python	Python Software Foundation	https://www.python.org/
NumPy	Harris et al.[51]	https://numpy.org/
Scikit-learn	Pedregosa et al.[52]	https://scikit-learn.org/

Method details

Network Model

Architecture and Dynamics. The model was an excitatory-inhibitory (E/I) continuous-time vanilla recurrent neural network (RNN)[18,25], adhering to key biological constraints (Figure 1B). For the main multitasking analysis, we trained 20 independent networks. The networks consisted of $N = 256$ neurons, with an 80% excitatory and 20% inhibitory neuron ratio, reflecting cortical distributions[53]. Neurons had a single-unit time constant $\tau = 100$ ms, consistent with NMDA receptor-mediated synaptic dynamics[23]. The dynamics of the network's firing rate vector, $\mathbf{r}(t)$, were governed by:

$$\tau \frac{d\mathbf{r}(t)}{dt} = -\mathbf{r}(t) + \left[W^{\mathsf{rec}}\,\mathbf{r}(t) + W^{\mathsf{in}}\,\mathbf{u}(t) + \mathbf{b} + \sqrt{2\tau}\,\sigma_{\mathsf{rec}}\,\boldsymbol{\xi}_{\mathsf{rec}}(t) \right]_+ . \tag{1}$$

In this equation, W^{rec} is the recurrent weight matrix, W^{in} is the input weight matrix, $\mathbf{u}(t)$ is the input vector, and $\mathbf{b}$ is a bias term. The term $\boldsymbol{\xi}_{\mathsf{rec}}(t)$ represents Gaussian white noise with a standard deviation of $\sigma_{\mathsf{rec}} = 0.15$. The network's dynamics were integrated using the Euler method with a temporal discretization of $\delta t = 20$ ms. The rectified linear unit (ReLU) activation function, $[\cdot]_+$, ensured non-negative firing rates.

The input vector $\mathbf{u}(t)$ included scalar representations of a fixation signal, the quantities and probabilities of offered goods, and task-specific rule cues. All scalar inputs were normalized between 0 and 1 and included a baseline of $u_0 = 0.2$ and additive input noise:

$$\mathbf{u}(t) = \mathbf{u}_{\mathsf{signal}}(t) + u_0 + \sqrt{2\tau}\,\sigma_{\mathsf{in}}\,\boldsymbol{\xi}_{\mathsf{in}}(t), \tag{2}$$

where $\mathbf{u}_{\mathsf{signal}}(t)$ represents the normalized input signals and $\boldsymbol{\xi}_{\mathsf{in}}(t)$ is Gaussian white noise with a standard deviation of $\sigma_{\mathsf{in}} = 0.01$.

Biological Constraints and Readouts. The network architecture strictly adhered to Dale's Law: outgoing weights from excitatory neurons were constrained to be non-negative, and those from inhibitory neurons were non-positive. These constraints were enforced by applying fixed masks to the weight matrix during training[18]. Similarly, all long-range projections (input and output weights) were constrained to be excitatory[54].

The network produced two distinct outputs from separate linear readouts: a policy for action selection (the "actor") and a value function predicting the expected future reward (the "critic"). Crucially, both readouts originated from the same recurrent network, a design choice that aligns with experimental evidence that value-related areas are causally involved in choice[9] and avoids the biological implausibility of entirely separate actor-critic modules[17]. The action space available to the actor included selecting one of the available offers or maintaining fixation, treating fixation as a distinct "hold" or "no-go" action. This integrated action space allows the network to learn not only what to choose but also when to execute the choice.

Initialization of Parameters. All weight matrices and biases were initialized as follows:

- **Recurrent weights** (W^{rec}) were sampled from a Gamma distribution (shape and scale parameters of 4) and then rescaled so the spectral radius of the matrix was 1.5. The Dale's Law mask was then applied.

- **Input weights** (W^{in}) were sampled from a uniform distribution over $[0, 1/\sqrt{N_{in}}]$, where $N_{in} = 16$ is the number of inputs.

- **Output weights** ($W^{\text{out}}_{\text{actor}}$, $W^{\text{out}}_{\text{critic}}$) were sampled from a uniform distribution over $[0, 0.4/\sqrt{N}]$.

- **All biases** (b, b_{actor}, b_{critic}) were initialized to zero.

Task Design and Training Paradigms

Networks were trained on a diverse set of five economic choice tasks designed to simulate aspects of primate decision-making experiments[7]. Each task required the network to evaluate and compare offers by integrating information about different goods, quantities, probabilities, and temporal structures. To investigate different aspects of learning and representation, networks were trained in three distinct paradigms: (1) *multitasking*, where a single network was trained concurrently on all five tasks; (2) *single-task training*, where a separate network was trained for each individual task; and (3) *curriculum learning*, where a single network was trained sequentially on tasks of increasing complexity.

Common Task Structure and Stimuli. Each trial began with a fixation period of variable duration drawn from a uniform distribution between 500 and 1500 ms, followed by a rule cue (uniformly distributed, $500 - 1500$ ms) indicating the current task. After offer presentation, a response period of up to 1000 ms was provided for the network to make a choice. The variable epoch durations prevent the network from relying on temporal cues and encourage it to learn stable, state-dependent computational policies (e.g., attractor states) (Figure 1A).

Network Inputs and Rewards. While tasks were visualized with colored circles (Figure 1A), the network itself received scalar inputs. Dedicated input channels encoded the quantity and probability for each offered good. The intrinsic values of the goods (e.g., $\rho_A = 3, \rho_E = 1$) were not provided as inputs but were learned by the network from reward feedback based on choice outcomes. The fixation and task rule cues were also provided as distinct scalar inputs, representing abstract contextual and task-set information. Prematurely breaking fixation resulted in

trial abortion and a negative reward of -1. Choosing an offer yielded a terminal reward. For deterministic offers, the reward was equal to the offer's value ($\rho_X \times$ Quantity$_X$, for good X). For probabilistic offers, a reward of ($\rho_X \times$ Quantity$_X$) was delivered with probability p_X, and a reward of 0 was delivered with probability $(1 - p_X)$.

Offer Value Calculation. The value of each offer was calculated as:

$$\text{Offer Value}_X = \rho_X \times \text{Quantity}_X \times \text{Probability}_X, \tag{3}$$

where ρ_X is the intrinsic value of the good X, Quantity$_X$ was sampled uniformly from a range of 0 to $10/\rho_X$ (to ensure comparable value ranges across goods), and Probability$_X$ was sampled uniformly from 0 to 1. In deterministic tasks, probability was set to 1. Finally, to ensure all choices presented to the network were non-trivial, a threshold was applied: if the computed Offer Value for a given offer was less than 1, its quantity and probability parameters were re-sampled until the criterion was met.

Task Details. The five tasks were designed to impose distinct computational demands:

- **Standard Task:** Choice between two goods (C vs. E) varying only in quantity. Demands basic value comparison.

- **Risky Task:** Choice between two goods (C vs. E) varying in both quantity and probability. Requires multiplicative integration of features.

- **Bundles Task:** Choice between two bundles of goods (e.g., B+C vs. D+E). The total value of each bundle was the sum of its components' expected values. Requires summation of values within an offer.

- **Ternary Task:** Three-way choice between goods A, C, and E. Increases the dimensionality of the choice space.

- **Sequential Task:** Choice between two goods (C vs. E) presented sequentially with an intervening delay. Requires working memory to hold the value of the first offer for comparison.

Reinforcement Learning Procedure

Algorithm and Loss Function. We trained the networks using Proximal Policy Optimization (PPO)[20,49], a state-of-the-art policy gradient algorithm that optimizes the policy directly to maximize the expected cumulative reward. The total loss function $\mathcal{L}(\theta)$ to be maximized is a weighted sum of a policy loss, a value function loss, and an entropy bonus to encourage exploration:

$$\mathcal{L}(\theta) = \mathbb{E}\left[\mathcal{L}_t^{\text{PPO}}(\theta) - c_1 \mathcal{L}_t^{\text{VF}}(\theta) + c_2 S[\pi_\theta](s_t)\right]. \tag{4}$$

The coefficients $c_1 = 0.5$ and $c_2 = 0.01$ are hyperparameters. The expectation $\mathbb{E}$ is taken over batches of experience collected by running 20 parallel environments for $T = 128$ steps, where each step corresponds to one simulation time step of $\delta t = 20$ ms.

The PPO policy loss uses a clipped objective function to ensure stable policy updates:

$$\mathcal{L}_t^{\text{PPO}}(\theta) = -\min\left(\rho_t(\theta)A_t, \text{clip}\left(\rho_t(\theta), 1 - \epsilon, 1 + \epsilon\right)A_t\right), \tag{5}$$

where $\rho_t(\theta) = \frac{\pi_\theta(a_t|s_t)}{\pi_\theta^{\mathsf{old}}(a_t|s_t)}$ is the probability ratio between the current and old policies, and $\epsilon = 0.1$ is the clipping parameter.

The policy update is guided by the advantage function A_t, which is analogous to the reward prediction error (RPE) in neuroscience[55,56]. It is calculated as the difference between the empirical return and the value function's prediction:

$$A_t = -V_\theta(s_t) + R_t, \tag{6}$$

where $V_\theta(s_t)$ is the value function's estimate for state s_t, and R_t is the bootstrapped return, computed as:

$$R_t = \sum_{k=0}^{T-t-1} \gamma^k r_{t+k} + \gamma^{T-t} V_\theta(s_T). \tag{7}$$

Here, r_t is the reward at time step t, and $\gamma = 0.99$ is the discount factor.

The value function loss trains the critic to accurately predict the bootstrapped return:

$$\mathcal{L}_t^{\mathsf{VF}}(\theta) = \frac{1}{2}\left(V_\theta(s_t) - R_t\right)^2. \tag{8}$$

The entropy bonus encourages exploration:

$$S[\pi_\theta](s_t) = -\sum_a \pi_\theta(a|s_t) \log \pi_\theta(a|s_t). \tag{9}$$

Optimization and Performance Criteria. All trainable parameters (θ) were updated via gradient ascent and backpropagation through time using the Adam optimizer with a learning rate of 2.5×10^{-4}[57]. The gradient norm was clipped at 1.0 to prevent exploding gradients. For curriculum learning protocols, networks were trained on simpler tasks before progressing to more complex ones. For example, a network might first be trained on the standard task with two deterministic options, then introduced to probabilistic outcomes in the risky task, and finally trained on the ternary task involving a third choice option.

Training continued until the network met two stringent performance criteria on a held-out test set of $25,000$ trials ($\sim 5,000$ per task): (1) completing at least 99% of trials without breaking fixation, and (2) achieving at least 90% accuracy on correctly completed trials (Figure S1). The learning curves show that networks typically progressed through three distinct phases: first, learning to maintain fixation throughout the trial without making a choice; second, learning to select an action randomly during the response period; and finally, learning the value-based policy of selecting the highest-value offer (Figure S1C). All code was implemented in PyTorch[48], Gym[50], NumPy[51], and Scikit-learn[52].

Quantification and statistical analysis

Behavioral Analysis via Logistic Regression

To quantitatively characterize network decision-making and extract behavioral parameters, we performed logistic regression analyses on the choice data from each task, following methodologies applied in primate studies[7].

Data Collection. For each network, we collected $25,000$ trials (about $5,000$ trials per task) where the network made choices among different offers. Each offer was defined by its quantity (q_X), probability (p_X) when applicable, and ground-truth intrinsic value (ρ_X). The intrinsic values were set during training, with $\rho_A > \rho_B > \rho_C > \rho_D > \rho_E$.

Models for Binary Choices. In tasks involving choices between two options—the *standard*, *risky*, *bundles*, and *sequential* tasks—we modeled the probability of choosing one option over another using logistic regression. The models estimate a set of free parameters $(\hat{\rho}_X, \hat{\gamma}, \hat{\eta}, \hat{\epsilon}')$ that best explain the network's choice behavior. The estimated relative value, $\hat{\rho}_X$, is defined relative to a reference good (good E), for which we set $\hat{\rho}_E = 1$.

Standard Task. In the *standard task*, the probability of choosing good C over good E is modeled as:

$$P_{\text{choose C}} = \frac{1}{1 + \exp\left(-\hat{\eta}\left(\ln\left(\frac{\hat{\rho}_C q_C}{q_E}\right)\right)\right)}, \tag{10}$$

where $\hat{\rho}_C$ and $\hat{\eta}$ are the estimated relative value and choice consistency parameters, respectively.

Risky Task. In the *risky task*, we also estimate the risk attitude parameter, $\hat{\gamma}$:

$$P_{\text{choose C}} = \frac{1}{1 + \exp\left(-\hat{\eta}\left(\ln\left(\frac{\hat{\rho}_C q_C p_C^{\hat{\gamma}}}{q_E p_E^{\hat{\gamma}}}\right)\right)\right)}. \tag{11}$$

Bundles Task. In the *bundles task*, the probability of choosing Bundle 1 (B+C) over Bundle 2 (D+E) is modeled as:

$$P_{\text{choose Bundle 1}} = \frac{1}{1 + \exp\left(-\hat{\eta}\left(\ln\left(\frac{V_1}{V_2}\right)\right)\right)}, \tag{12}$$

where $V_1 = \hat{\rho}_B q_B p_B^{\hat{\gamma}} + \hat{\rho}_C q_C p_C^{\hat{\gamma}}$ and $V_2 = \hat{\rho}_D q_D p_D^{\hat{\gamma}} + \hat{\rho}_E q_E p_E^{\hat{\gamma}}$ (with $\hat{\rho}_E = 1$).

Sequential Task. In the *sequential task*, we additionally estimate the order bias parameter, $\hat{\epsilon}'$:

$$P_{\text{choose C}} = \frac{1}{1 + \exp\left(-\hat{\eta}\left(\ln\left(\frac{\hat{\rho}_C q_C p_C^{\hat{\gamma}}}{q_E p_E^{\hat{\gamma}}}\right) + \hat{\epsilon}' \cdot \text{Order}\right)\right)}, \tag{13}$$

where Order $= +1$ if good C was presented second, and -1 if it was presented first.

Model for Multinomial Choices. In the *ternary task* (choices among A, C, E), we used multinomial logistic regression:

$$P_{\text{choose X}} = \frac{\left(\hat{\rho}_X q_X p_X^{\hat{\gamma}}\right)^{\hat{\eta}}}{\sum_{Y \in \{A,C,E\}} \left(\hat{\rho}_Y q_Y p_Y^{\hat{\gamma}}\right)^{\hat{\eta}}}. \tag{14}$$

Parameter Estimation. We estimated all behavioral parameters $(\hat{\rho}_X, \hat{\gamma}, \hat{\eta}, \hat{\epsilon}')$ using maximum likelihood estimation for each task and network individually. The estimated relative values, denoted by $\hat{\rho}_X$ to distinguish them from the ground-truth values ρ_X used in training, are relative measures, with $\hat{\rho}_E = 1$ serving as the reference point, allowing for comparison across tasks and networks. The choice consistency parameter ($\hat{\eta}$) indicates the steepness of the psychometric function; higher values correspond to more consistent choices based on offer value differences.

Single-Neuron Analyses

Data Collection and Trial Structure. For neural analyses, we collected test trials ($25,000$ per network) with fixed epoch durations to facilitate temporal alignment of activity across trials. In the sequential task, neural activity was aligned to the onset of the *second* stimulus, as this is the point where all information required for the decision becomes available to the network.

Single-Neuron Selectivity Analysis. To analyze neuronal selectivity for decision variables, we performed linear regression of each neuron's firing rate ($r(t)$) against each candidate behavioral variable (X) independently at each time point: $r(t) = \beta_0 + \beta X + \epsilon$. The variables considered included offer values (OVC, OVE), chosen value (CV) and choice (CH). These analyses were performed on a set of approximately 5,000 test trials per task for each of the 20 networks.

To determine whether a neuron was selective for a given variable at a specific time point, we applied a standard two-step statistical criterion. First, the linear regression had to be statistically significant ($p < 0.05$). Second, to ensure a minimum effect size, the regression had to explain a baseline amount of variance ($R^2 \geq 0.005$). For analyses where a neuron was assigned to a single best-fit variable category (e.g., for the fraction of selective neurons plot in Figure 3C), we chose the variable that yielded the maximum R^2 among all variables that satisfied both criteria. If no variable met these criteria, the neuron was considered non-selective at that time point.

Temporal Stability Index (TSI). For each neuron deemed selective at any point during the trial, its "primary variable" was identified as the one it encoded for the majority of time steps. The TSI was then calculated as:

$$\text{TSI} = \frac{\text{Number of times the neuron encodes its primary variable}}{\text{Total number of times the neuron is selective}}. \tag{15}$$

A TSI of 1 indicates that the neuron consistently encodes the same variable whenever it is selective, while lower values suggest dynamic selectivity, where a neuron's tuning changes over time.

Analysis of Categorical and Mixed Selectivity. To investigate the nature of neural encoding, we analyzed the distribution of differences in the coefficient of determination ($\Delta R^2 = R^2_{\text{Var1}} - R^2_{\text{Var2}}$) for pairs of decision variables. This approach was chosen to directly parallel analyses in primate neurophysiology[28]. We performed this analysis using two different criteria for neuronal inclusion to distinguish between the coding schemes of specialized versus general neuronal populations. **Categorical encoding in highly selective neurons (Main Text, Figure 3E):** To test for categorical encoding within the most specialized neurons, we applied a stringent inclusion threshold. For each pair of variables, we included a neuron-time point in the analysis only if it was very strongly modulated by at least one of the two variables ($R^2 \geq 0.5$). The resulting ΔR^2 distributions for this subpopulation were plotted to assess their modality. **Mixed selectivity in the general population (Supplementary Figure S4):** To characterize the coding scheme of the broader population of task-related neurons, we used a more lenient inclusion criterion. Here, a neuron-time point was included if it was significantly modulated by at least one of the variables ($p < 0.05$ and $R^2 \geq 0.005$). The ΔR^2 distributions for this general population were then analyzed. Together, these two analyses provide a comprehensive view of the network's dual coding strategy.

Neural Population Analyses

Population State-Space Analysis and Dimensionality. To investigate population-level encoding, we performed principal component analysis (PCA) on the activity of the $N = 256$ recurrent neurons. For each task, the data matrix for PCA was constructed from the neural activity during the last 200 ms of the stimulus presentation phase, concatenated across all available test trials (approx. $5,000$ per task). This resulted in a matrix of size $N \times (\text{num\_trials} \times \text{num\_time\_steps})$. We analyzed the full population as well as the excitatory and inhibitory populations separately.

We estimated the effective dimensionality of the neural activity using the participation ratio (PR). The PR is a standardized, continuous measure of dimensionality derived from the eigenvalues (λ_i) of the activity's covariance matrix, which avoids the need for an arbitrary variance threshold. Intuitively, it quantifies how broadly the variance of population activity is distributed across principal components. If all variance is concentrated in a single dimension, the PR is 1; if variance is spread evenly across M dimensions, the PR is M. It is formally defined as:

$$D_{\mathsf{PR}} = \left(\sum_i \lambda_i \right)^2 \bigg/ \sum_i \lambda_i^2. \tag{16}$$

Principal Component Regression.   To interpret the dimensions of population activity, we projected the single-trial neural activity onto the first three principal components. We then performed a multiple linear regression where the dependent variables were the projections onto each PC, and the independent variables were the key decision variables for that trial (e.g., offer values, chosen value, choice). The coefficient of determination (R^2) from these regressions quantifies the proportion of variance in each principal component that is explained by each decision variable.

Computational Lesion Analyses.   To causally dissect the contributions of different circuit elements, we performed computational lesion experiments after network training was complete. The primary lesion reported here involved removing all recurrent connections by setting the recurrent weight matrix to zero ($W^{\mathsf{rec}} = 0$), thereby isolating the feedforward processing pathway. After this lesion, we re-evaluated the network on a full set of test trials and analyzed two key outcomes: (1) Behavioral Performance, by quantifying the performance drop in trial completion rate (Figure S6B), and (2) Neural Activity, by re-calculating firing rate distributions and repeating the full PCA and dimensionality analyses on the lesioned network activity (Supplementary Figures S6A and S7). This allowed for a direct comparison of the population geometry and behavioral capacity between the intact and lesioned circuits.

Visualization of Population Dynamics.   To visualize the evolution of the population state, we created both static plots and dynamic videos. For static plots like Figure 4B, we show the state of all trials projected onto the first two PCs at a single, representative time point (the end of the offer period). For dynamic visualizations (Supplementary Videos S1 and S2), we created an animation by plotting this full cloud of trial-points at each successive 20 ms time step over the course of the entire trial. This method allows visualization of how the entire distribution of population states evolves during decision formation.

Analyses of Input Weights and Upstream Computation

Analysis of Input Weight Structure and Mixed Selectivity   To directly test for the existence of mixed-selective neurons hypothesized to cause the geometric rotation of the value representation, we analyzed the input weight matrices (W^{in}) of trained networks. We first visualized the overall structure by computing the Pearson correlation coefficients between the input weight vectors for all offer features (Fig. 5A). To provide a quantitative and direct measure of input integration, we calculated a Selectivity Index (SI) for each recurrent neuron. This analysis was performed on the 50 networks trained exclusively on the risky task (the same cohort used for the analysis in Fig. 5E). For each recurrent neuron i in each network, the SI was calculated based

on its synaptic input weights from the quantity of good C (w_{qC}) and good E (w_{qE}) as follows:

$$SI_i = \frac{w_{i,qC} - w_{i,qE}}{w_{i,qC} + w_{i,qE}} \tag{17}$$

The SI was defined using only quantity weights because the input weights for the quantity and probability of any given offer were found to be highly correlated (Fig. 5A), making the quantity-based index a robust measure of a neuron's overall offer preference. An SI value of $+1$ or -1 indicates a neuron is exclusively driven by input from good C or good E, respectively, while an SI of 0 indicates perfectly balanced inputs from both. For each of the 50 networks, we computed the probability density function of the SI values across its recurrent population. These 50 distributions were then averaged to produce the final histogram shown in Supplementary Figure S9, which visualizes the converged wiring strategy found by the learning algorithm.

Testing for Multiplicative Computation in the Feedforward Pathway   To investigate the circuit mechanism responsible for the emergent multiplicative-like computation, we performed a computational dissection to isolate the feedforward pathway from the recurrent circuitry. After training was complete, we analyzed networks with their recurrent connections computationally lesioned (e.g., setting the recurrent weight matrix $W^{\text{rec}} = 0$). We collected neural activity from the last 200 ms of the stimulus presentation phase across approximately $5{,}000$ trials of the risky task. We then performed Principal Component Analysis (PCA) on the resulting feedforward population activity. To determine if this isolated pathway supported a multiplicative or additive integration scheme, we used linear regression to compare how well two different models could explain the variance in the top two principal components (PCs). The first model used the multiplicative product of quantity and probability for each offer (OVC and OVE) as predictors. The second model used their additive sum (OVCs and OVEs). Higher coefficients of determination (R^2) for the product-based model were taken as strong evidence that the feedforward architecture had learned to perform a non-linear, multiplicative computation (Fig. 5B).

Toy Feedforward Network Model for Multiplication and Mixed Selectivity   To provide a proof-of-principle for how a neural circuit can both approximate multiplication and generate a rotated value representation, we constructed a simplified feedforward network. The demonstration is two-fold: first, we provide a constructive proof that the architecture can approximate a multiplicative function, and second, we use this capability to test the mechanistic origin of the geometric rotation observed in the full network.

Constructive Proof of Multiplicative Approximation: Our proof rests on the principle of function approximation with basis functions. The goal is to approximate the non-linear value surface $V(q,p) = q \cdot p$ by forming a linear combination of simpler, non-linear basis functions provided by a population of neurons. The activity r_i of a single neuron i with a ReLU activation provides a simple, ramp-like basis function:

$$r_i(q,p) = [w_{iq}q + w_{ip}p + b_i]_+ \tag{18}$$

where q and p are inputs, w_{iq} and w_{ip} are weights, and b_i is a bias. A single such neuron is insufficient. However, a population of N neurons, each with different weights and biases, can generate a diverse set of these basis functions that tile the input space. A downstream linear readout can then learn to weight the contribution of each neuron to reconstruct the target multiplicative surface. We provide a constructive proof of this by engineering the weights and biases to achieve this tiling systematically. For the i-th neuron in a population of size N, we set the parameters as:

$$w_{iq} = w_{ip} = \alpha_i \tag{19}$$

$$b_i = -\beta_i \cdot E[q \cdot p] \tag{20}$$

where $E[q \cdot p]$ is the mean value of the product over the task's offer distribution. By making α_i and β_i vary across the population (e.g., linearly with neuron index i), we ensure that different neurons become active at different locations and with different sensitivities across the quantity-probability space. This architecture is thus mathematically capable of approximating multiplication. We provide empirical validation for this constructive proof with a parameter search (Supplementary Fig. S8). In this search, where for simplicity all neurons shared the same α and β, we demonstrated that there exists an optimal parameter regime where the population activity is overwhelmingly better explained by a multiplicative ($q \cdot p$) than an additive ($q + p$) model. This confirms that the architecture is not only capable but also predisposed to learn a multiplicative integration rule.

Modeling Mixed Selectivity to Explain Geometric Rotation: Having established the network's ability to compute value, we applied this module to test the origin of the value sum/difference representation.

1. *Segregated Model* (Fig. 5C): We used two independent populations, each approximating the value of one offer, to show this wiring is insufficient to produce the observed rotation.

2. *Mixed-Selectivity Model* (Fig. 5D): We added a third population receiving summed inputs from both offers. This structure, mimicking our analysis of the full network's weights (Supplementary Fig. S9), successfully reproduced the geometric rotation, thereby providing a causal, mechanistic explanation for this emergent geometric feature.

Correlation of Relative Values and Input Weights   To test the hypothesis that learned subjective values are physically encoded in the synaptic strengths of input projections, we performed a dedicated experiment designed to establish a causal link between a manipulated training parameter, the resulting circuit structure, and the emergent behavioral preference. We trained a total of 50 independent networks exclusively on the risky task, organized into five groups of ten. For each group, the intrinsic value of the reference good E was held constant ($\rho_E = 1$), while the intrinsic value of the target good C was systematically set to a different ground-truth value: $\rho_C \in \{1, 2, 3, 4, 5\}$. After each of the 50 networks was trained to the standard performance criteria, we extracted two key quantities. First, to capture the network's learned preference, we inferred its behavioral relative value, $\hat{\rho}_C$, by fitting the logistic regression model for the risky task to $5,000$ of its choice trials. Second, to quantify the underlying circuit parameter, we calculated the average input synaptic strength by taking the mean of all non-zero excitatory weights connecting the input for the quantity of good C (q_C) to the recurrent population. Finally, we performed a linear regression across the 50 resulting pairs of values (inferred behavioral value vs. average input weight) to quantify the relationship between the network's learned behavior and its input circuit structure, as shown in Figure 5E.

Analyses of Recurrent Circuitry and Value Comparison

Analysis of Output Dynamics   To characterize the dynamics of the decision process at the action-selection level, we analyzed the activity of the network's output units during the risky task. These units include the policy outputs (the "actor") corresponding to available actions (e.g., 'Choose C') and the value function output (the "critic"). For Figure 6A, we averaged the output activity across all trials, separating trials based on the network's final choice. For Figure 6B, we constructed a heatmap summarizing a series of linear regressions. Each row of the heatmap corresponds to an output node, and each column to a decision variable. The R^2 value in each cell represents the coefficient of determination from a simple linear regression of a single output

node's activity against a single decision variable, performed across all trials for a given task. To reveal choice-specific encoding, the set of regressors included conjunctive variables. For instance, the variable 'CVBC' ('Chosen Value BC') was defined as the value of good C or B+C on trials where C or B+C was chosen, and was set to zero on all other trials. The winner-take-all (WTA) dynamic is demonstrated by a choice-specific output (e.g., 'BC Ch') being strongly predicted by its corresponding conjunctive variable (e.g., 'CVBC') but not by the variable for the competing choice (e.g., 'CVDE').

Reaction Time Analysis   Reaction times (RTs) were measured from the onset of the response phase (when the fixation signal turned off) to the time step at which the network executed a choice action. We collected RTs across all correctly completed trials for all tasks. We plotted the probability density of these RTs and, to assess the relationship between decision difficulty and response latency, performed a linear regression between RTs and the absolute value difference of the two offers on a trial-by-trial basis (Supplementary Fig. S10A).

Recurrent Connectivity Analysis   To identify learned connectivity patterns, we examined the recurrent weight matrices (W^{rec}) of the trained networks (Supplementary Fig. S10B, left). To assess the effective dimensionality of this connectivity, we performed a Singular Value Decomposition (SVD) on the full 256×256 weight matrix for each network. A low-rank matrix, indicated by a spectrum of singular values that decays rapidly, implies that the network's dynamics are governed by a few dominant connectivity motifs (Supplementary Fig. S10B, right).

Reduced Connectivity Matrix and Circuit Diagram   To abstract the core functional architecture from the full connectivity matrix and make it interpretable, we performed a many-to-one functional abstraction, visualized for a single network in Supplementary Fig. S11. This procedure consists of three steps. First, for a given task (with the risky task used for the main analysis in Figure 6), we performed a regression analysis to classify each of the 256 individual neurons into a functional pool based on its cell type (excitatory or inhibitory) and its primary selectivity (e.g., 'Choice C'). Second, all neurons with the same classification were grouped into a single functional pool. Third, we constructed a reduced connectivity matrix by computing the mean synaptic weight of all connections between each pair of neuron pools. The final matrix shown in Figure 6C represents the average of these reduced matrices across all 20 networks. This matrix highlights the dominant connectivity motifs, from which we created the simplified circuit diagram in Figure 6D. To test the generality of this finding, this entire procedure was repeated for the standard, bundles, ternary, and sequential tasks, revealing that the same core Competitive Recurrent Inhibition (CRI) motif emerged in all choice contexts (Supplementary Fig. S10C).

Lesion Experiments for Causal Validation   To causally test the functional roles of specific circuit elements, we performed two targeted computational lesion experiments on the fully trained networks.

1. Lesion of Negatively Tuned Neurons: To test the hypothesis that negatively tuned neurons are computationally critical, we first identified all neurons in each of the 20 multitask networks that had a statistically significant negative regression slope ($p < 0.05$) for either 'Offer Value' or 'Chosen Value' variables during the offer period. During subsequent test simulations across all five tasks, the activity of these specific neurons was clamped to zero. We then measured the percentage change in performance (both trial completion and choice accuracy) relative to the intact network (Supplementary Fig. S12).

2. Functional Ablation of Neuronal Pools: To identify the most critical functional populations, we performed a systematic ablation study on the 20 multitask networks, tested on the risky task. We first classified all neurons into functional pools as described above. We then, in separate experiments, silenced each functional pool by clamping the activity of all its member neurons to zero throughout the trial. We measured the percentage change in trial completion and choice accuracy for each ablation experiment to determine the causal importance of each cell group (Supplementary Fig. S13).

Analyses of Compositionality and Learning

Analysis of Rule Cue and Neural Subspaces. To investigate how networks represent different tasks, we analyzed both the input weights and the resulting population activity of the 20 multitasking networks. First, we extracted the input weight vectors (W^{in}) connecting each of the five rule cue inputs to the recurrent neurons. We then computed the pairwise Pearson correlation between these vectors for each network and averaged the resulting correlation matrices across all 20 networks to produce the matrix shown in Fig. 7A. Second, for the subspace analysis (Fig. 7B), we performed principal component analysis (PCA) on the population activity during the last 200 ms of the rule cue period for each task, using data concatenated across all 20 networks. To determine the intrinsic dimensionality of each task's representation, we first calculated the Participation Ratio (PR) for each task's activity. The number of principal components (n_{PC}) used to define the subspace for each task was then set to the closest integer to its calculated PR value. Finally, we computed the principal angle between the subspaces spanned by the top n_{PC} principal components for each pair of tasks. A smaller angle indicates more overlapping, or shared, neural representations.

Task Variance and Neuronal Clustering. To identify shared and specialized neural populations in multitasking networks, we calculated the variance of each neuron's firing rate during the stimulus presentation phase across all trials for each task. This variance was then normalized for each neuron by its maximum variance across all five tasks, creating a 5-dimensional task-variance profile for each neuron. For each network, we then used the k-means clustering algorithm (from scikit-learn[52]) on these profiles to group neurons based on their functional contribution to different tasks. The analysis was performed independently on the excitatory and inhibitory populations. For each population in each network, the optimal number of clusters (k) was determined by maximizing the silhouette score across a range of possible k values (from 2 to 20). While the precise optimal number of clusters could vary slightly between networks, the qualitative functional organization was highly consistent. The heatmaps in Figure 7C show the results from a representative network, for which the optimal number of clusters was found to be $k = 3$ for the excitatory population and $k = 2$ for the inhibitory population. Critically, across all networks, this procedure consistently identified a 'shared' cluster (neurons active in all tasks) and 'specialized' clusters (neurons with high variance in only one or two tasks, such as the ternary and sequential tasks).

Lesion Analysis of Neuronal Clusters. To causally assess the functional importance of the identified neuronal clusters, we performed a series of targeted lesion analyses on the representative multitasking network shown in Figure 7C. For each of the excitatory and inhibitory clusters identified in this network (Shared, Ternary-specialized, and Sequential-specialized), we performed a separate lesion experiment. During test trials across all five tasks, we computationally silenced all neurons belonging to the targeted cluster by clamping their firing rates to zero

throughout the entire trial. We then evaluated the network's performance by measuring two metrics: (1) the Trial Completion Rate and (2) the Accuracy on successfully completed trials. The results, shown in Fig. S14, are presented as the percentage drop in performance for the lesioned network compared to its intact (unlesioned) control performance.

Fractional Task Variance Analysis. For each pair of tasks in the 20 multitasking networks, we computed the fractional variance difference for each neuron, defined as $(TV_1 - TV_2)/(TV_1 + TV_2)$, where TV_1 and TV_2 are the normalized firing rate variances for the two tasks. We then plotted histograms of these values across the entire neural population (Fig. 7D) to visualize the organizational relationship between the neural resources recruited for different tasks.

Visualization of Task Representations in a Common PCA Space. To visualize the compositional structure across all 20 independently trained multitasking networks, it was necessary to align their individual state spaces. Because PCA yields a basis set whose component signs and order are arbitrary, the principal components are not directly comparable across networks. We therefore implemented a rotational alignment procedure using a Procrustes analysis. First, we designated one network as the reference. Then, for each of the other 19 networks, we found the optimal orthogonal rotation matrix that minimized the sum of squared distances between its mean task representations and those of the reference network. After applying this rotation to align each network's state space to the common reference, we projected the mean population activity for each of the five tasks from all 20 networks into this single, aligned space to create the visualization in Fig. 7E.

Zero-Shot Transfer Learning Analysis. To directly test whether multitasking is necessary for developing a flexible, multi-skilled circuit, we performed a zero-shot transfer learning analysis (Fig. S15). We trained five separate groups of networks (10 networks per group), with each group trained exclusively on one of the five tasks until the standard performance criteria were met. After training on its single source task, each network was evaluated on a held-out test set of $5,000$ trials from all five tasks without any further weight updates. We calculated and plotted two performance metrics for this cross-task evaluation: the Trial Completion Rate and the Accuracy on successfully completed trials.

Curriculum Learning Protocols. To assess whether prior experience accelerates the acquisition of new skills, we implemented curriculum learning protocols (Fig. 7F). We focused on three complex target tasks: Ternary, Bundles, and Sequential. For each target task, we compared the number of training trials required to reach the performance criterion under three distinct training curricula. A separate group of 10 independent networks was trained for each condition, for a total of 90 networks in this analysis (3 target tasks $\times$ 3 curricula $\times$ 10 networks). The three curricula were:

1. *From Scratch* (Rand): Networks were trained on the target task directly from a random weight initialization.

2. *Single Pre-training* (Rand→Stand): Networks were first trained to criterion on the Standard task, and then training continued on the target task.

3. *Double Pre-training* (Rand→Stand→Risky): Networks were first trained to criterion on the Standard task, then to criterion on the Risky task, and finally trained on the target task.

The box plots in Fig. 7F show the number of training trials required to learn only the *final* target task in each curriculum. To facilitate direct comparison on a common scale, for each target task (e.g., Ternary), the trial counts for all three curriculum conditions were normalized by the maximum number of trials required by any single network across all conditions for that specific task. This ensures that the y-axis in each panel ranges from 0 to 1, representing the fraction of the maximum observed learning time.

Analyses of Generalization to Novel Offers

Generalization Test Design   To test if the network could generalize a learned valuation rule to novel stimuli, we trained ten networks exclusively on the risky task using a constrained, orthogonal set of offers. During this *training phase*, for each trial, offers for goods C and E were generated under one of two conditions, chosen randomly with 50% probability: (1) probabilities for both goods were fixed at 0.5 while quantities varied across their full range, or (2) quantities were fixed at half their maximum value (e.g., $q_C = 2.5, q_E = 5$) while probabilities varied across their full range (0 to 1). This orthogonal design (visualized in Fig. 8A) ensured that the network never encountered offers where both quantity and probability varied simultaneously from their central values, forcing it to learn their contributions to value independently. Training continued until networks achieved high performance ($\geq 90\%$ accuracy) on this constrained set. During the subsequent *testing phase*, we assessed generalization by evaluating the fully trained networks on a new, unconstrained set of $5,000$ offers where both quantity and probability for both goods varied independently and simultaneously across their full ranges. This test set was therefore composed almost entirely of novel quantity-probability combinations that the networks had not encountered during training.

Behavioral Analysis   We performed logistic regression analysis on the choice data from both the constrained training set and the unconstrained test set for each of the ten networks. We used the same logistic model defined for the risky task in the "Behavioral Analysis via Logistic Regression" section. By fitting this model separately to the training and test data, we extracted and compared the key behavioral parameters (inferred relative value $\hat{\rho}_C$, risk attitude $\hat{\gamma}$, choice consistency $\hat{\eta}$, and choice accuracy) to assess the consistency of the network's learned valuation strategy when faced with novel offer combinations (Fig. 8C).

Analysis of Neural Dynamics during Generalization   To determine if the neural implementation of the decision generalized along with the behavior, we analyzed the population activity of the ten constrained-trained networks during the test phase with novel, unconstrained offers. We collected neural activity from the last 200 ms of the stimulus presentation phase across all test trials ($5,000$ trials per network). We then performed principal component analysis (PCA) on the population activity to visualize the structure of the neural state space, as shown for a representative network in Supplementary Fig. S16. The consistency of the PCA geometry (Supplementary Fig. S16) with that of the standard multitasking networks (Fig. 4B) demonstrates that the same low-dimensional computational solution was employed for both familiar and novel stimuli.