Revealing a coherent cell state landscape across single cell datasets with CONCORD

Qin Zhu[1*], Zuzhi Jiang[2], Matt Thomson[3], Zev Gartner[1,4,5*]

[1] Department of Pharmaceutical Chemistry, University of California San Francisco; San Francisco, CA 94158, USA

[2] Tetrad Graduate Program, University of California San Francisco; San Francisco, CA 94158, USA.

[3] Division of Biology and Biological Engineering, California Institute of Technology; Pasadena, CA 91125, USA

[4] Chan Zuckerberg Biohub; San Francisco, CA 94158, USA

[5] Center for Cellular Construction, University of California San Francisco; San Francisco, CA 94158, USA

*Correspondence to Q. Zhu at qin.zhu@ucsf.edu and Z. J. Gartner at zev.gartner@ucsf.edu

Author information

Qin Zhu, qin.zhu@ucsf.edu

Zuzhi Jiang, zuzhi.Jiang@ucsf.edu

Matt Thomson, mthomson@caltech.edu

Zev J. Gartner, zev.gartner@ucsf.edu

Abstract

Batch integration, denoising, and dimensionality reduction remain fundamental challenges in single-cell data analysis. While many machine learning tools aim to overcome these challenges by engineering model architectures, we use a different strategy, building on the insight that optimized mini-batch sampling during training can profoundly influence learning outcomes. We present CONCORD, a self-supervised learning approach that implements a unified, probabilistic data sampling scheme combining neighborhood-aware and dataset-aware sampling: the former enhancing resolution while the latter removing batch effects. Using only a minimalist one-hidden-layer neural network and contrastive learning, CONCORD achieves state-of-the-art performance without relying on deep architectures, auxiliary losses, or supervision. It generates high-resolution cell atlases that seamlessly integrate data across batches, technologies, and species, without relying on prior assumptions about data structure. The resulting latent representations are denoised, interpretable, and biologically meaningful—capturing gene co-expression programs, resolving subtle cellular states, and preserving both local geometric relationships and global topological organization. We demonstrate CONCORD's broad applicability across diverse datasets, establishing it as a general-purpose framework for learning unified, high-fidelity representations of cellular identity and dynamics.

Introduction

Cells express thousands of genes to perform specialized functions and maintain homeostasis. Gene expression is highly correlated, orchestrated by intricate gene regulatory networks and cell-cell interactions that constrain cells to a structured, low-dimensional "state landscape" within the high-dimensional gene expression space[1,2]. Advances in single-cell technologies, particularly single-cell RNA sequencing (scRNA-seq), enable empirical mapping of this landscape. Emerging evidence suggests that such landscapes may contain diverse features—including discrete clusters, continuous trajectories, branching trees, and cyclic transitions—reflecting the underlying organization of cellular states[3,4]. However, the presence and arrangement of these features are typically unknown a priori, underscoring the need for computational methods that can robustly and accurately capture their topology and geometry to illuminate the principles of development, homeostasis, and disease progression.

Dimensionality reduction, a form of representation learning, is commonly employed to uncover the structure of the cell state landscape. By projecting high-dimensional data into a lower-dimensional space, key structural patterns become more tractable to visualize and analyze. However, conventional methods—such as principal component analysis (PCA), non-negative matrix factorization (NMF)[5], and factor analysis[6]—often overemphasize broad cell type distinctions, overlook subtle states, and can confound processes like differentiation with cell cycle progression. These challenges are exacerbated by batch effects, poorly understood sources of technical variation that obscure or skew genuine biological signals. Although an array of batch-correction tools—such as Harmony[7], Scanorama[8], Seurat[9], scVI[10], LIGER[11] and MNN[12] —have been developed, they frequently assume an underlying structure to technical variation and therefore can distort features by over- or under-correcting batch effects[13], and many face scalability issues when applied to massive atlas-level datasets.

Among the growing number of representation learning approaches useful in single cell analysis, contrastive learning has recently shown promise[14-20]. Initially developed for domains such as image and natural language processing[21-23], these methods learn informative cell representations by comparing similar ("positive") cells against dissimilar ("negative") ones within mini-batches - small subsets of cells iteratively sampled during training. However, current contrastive methods face fundamental limitations: supervised approaches require extensive manual annotation and struggle to generalize to novel states or continuous trajectories[19,20], whereas unsupervised methods form mini-batches through uniform sampling, emphasizing coarse cell-type differences while overlooking subtle biological variation[14-17]. When applied across datasets, contrasting cells randomly sampled from different datasets can amplify dataset-specific artifacts rather than isolating true biological signals. While strategies involving generative adversarial networks (GANs)[17,24,25], unsupervised domain adaptation via backpropagation[26], and conditional variational autoencoders (CVAEs)[27] attempt to mitigate batch effects, their objective of minimizing dataset-specific differences inherently conflicts with contrastive learning's goal of maximizing differences between dissimilar cells, frequently leading to incomplete batch-effect correction and potentially introducing distortions to the latent space. This dilemma raises a critical question: can contrastive learning fully capture cellular diversity while minimizing batch effects?

Here, we address this open question by transforming a core limitation of contrastive learning—its sensitivity to mini-batch composition—into a strength. The central insight is that mini-batch composition fundamentally determines the outcome of contrastive learning. We introduce CONCORD (COntrastive learNing for Cross-dOmain Reconciliation and Discovery), a framework that redefines the contrastive learning process through a probabilistic, neighborhood- and dataset-aware mini-batch sampling strategy. By enriching each mini-batch with biologically informative contrasts drawn from within datasets, CONCORD simultaneously enhances embedding resolution and mitigates batch-specific

artifacts. In contrast to prior methods that rely on complex architectures or

auxiliary losses for batch correction, CONCORD achieves dimensionality

reduction, denoising, and data integration solely through principled sampling. We

demonstrate its effectiveness using a minimalist, single-hidden-layer neural

network across simulated and real datasets spanning a range of biological and

technical complexity. CONCORD consistently outperforms state-of-the-art

methods, producing high-resolution, denoised encodings that robustly capture

diverse structures—including loops, trajectories, trees, and specialized cell

states—reflecting bona fide biological processes even when the data originate

from multiple technologies, time points, or species. This minimalistic, highly

extensible framework scales from small to large datasets, generalizes to

modalities beyond scRNA-seq, and establishes a rigorous foundation for next-

generation single-cell machine learning models to power diverse downstream

biological discoveries.

Results

The CONCORD framework

Analysis of single-cell sequencing data suggest that gene expression is not

randomly sampled; rather, the mechanism of gene regulation imposes strong

constraints, producing dynamically changing gene co-expression patterns

reflected as intricate structures in the low dimensional embedding of cells[1-3,28].

For example, at homeostasis, cells typically form discrete clusters corresponding

to stable types or states, with adjacent clusters representing closely related

states (Figure 1A, left). In developmental or pathological contexts—such as early

embryogenesis, tissue repair, or tumorigenesis— cells often follow branching

trajectories from progenitors to terminal fates, with semi-stable intermediate

states forming denser clusters (Figure 1A, middle). Cyclic gene expression

programs, such as those regulating the cell cycle, give rise to loop-like

structures[3,4] (Figure 1A, right). Despite these rich patterns, conventional

dimensionality reduction methods like PCA or NMF capture only partial

representations of the cell state landscape, either oversimplifying complex

structures or disproportionately emphasizing certain features while obscuring

others.

We hypothesized that a representation learning approach capable of encoding

cells based on gene co-expression programs would provide a more

comprehensive view of the cell state landscape. Recent evidence suggests that

self-supervised contrastive learning significantly improves clustering and cell-type

classification performance[15-17], likely due to its ability to recover sparse,

structured gene co-expression signals from high-dimensional data[29] (see

Methods). Like many modern machine learning methods, contrastive learning

relies on mini-batches— small subsets of data sampled iteratively during

stochastic gradient descent—as the basic unit of training. However, contrastive

learning is uniquely sensitive to how mini-batches are composed: each cell is

contrasted against every other cell within the same mini-batch, making the mini-

batch itself the universe over which learning is defined. By differentiating each

cell from others in the mini-batch, the model learns features that distinguish

distinct cellular states. Simultaneously, aligning augmented versions of the same

cell (typically generated through random masking) encourages the model to

capture robust gene co-expression patterns, rather than relying on the

expression of individual genes[29]. As a result, the learned representations are

inherently more robust to technical noise and dropout—pervasive artifacts in

single-cell RNA-seq[30].

This reliance on within–mini-batch comparisons makes the sampling strategy—

which dictates mini-batch composition—a critical determinant of the learned

representation[31]. Existing methods adopt uniform sampling across the entire

single cell datasets, leading to two key limitations. First, uniform sampling

emphasizes broad differences, such as major cell types, while underrepresenting

rare subpopulations or subtle distinctions, leading to poor resolution of fine-scale

cellular states (Figure 1B). Second, mixing cells from different datasets within the

same mini-batch can amplify dataset-specific differences, inadvertently encoding

batch effects rather than isolating biologically meaningful variation.

To address the first issue, we developed a neighborhood-aware sampler, inspired

by k-nearest-neighbor (kNN) based sampling[31]. In this approach, cells are

sampled probabilistically from both the global distribution and local

neighborhoods (Figure 1B). Local sampling, guided by a coarse graph

approximation of the cellular state landscape, compels the model to contrast cells

against their neighbors, allowing it to capture subtle differences between closely

related states. Meanwhile, global sampling preserves a broad perspective of

major cell types, ensuring the model robustly encodes large-scale distinctions. By

iteratively presenting the model with local neighborhoods (e.g., T cells in one

mini-batch, epithelial cells in another) alongside the global distribution, the model

allocates capacity to represent both large-scale distinctions and nuanced local

details, leading to improved resolution in the learned latent space (Figure 1B).

When applied to a single dataset, contrastive learning effectively captures

biological variation in the latent space (Figure 1C). However, with uniform

sampling across multiple datasets, both biological and dataset-specific variations

are encoded, leading to latent spaces that separate by dataset as well as cell

type (Figure 1D). To address this, we also introduce a dataset-aware sampler

that restricts mini-batches to a single dataset, ensuring contrasts reflect only

biological differences, as in the single-dataset setting (Figure 1E). Dataset-

specific biases are further diminished through random mini-batch shuffling: if

such signals are encoded in one batch, they are disrupted and overwritten by

subsequent mini-batches from other datasets. Consequently, only biologically

meaningful signals, such as gene co-expression patterns, persist throughout

training, resulting in a latent space that reflects biological variation with minimal

batch effects (Figure 1E). Importantly, this strategy of removing batch effect

imposes no assumptions on the structure of the data beyond the existence of

shared biological programs across datasets. In cases where datasets have

minimal or no overlap, a "leaky" dataset-aware sampler enables soft alignment

without imposing artificial harmonization, supporting flexible integration across

both fully and partially overlapping datasets (Figure 1F). Unlike prior batch-

correction strategies that struggle in contrastive learning due to competing

objectives, CONCORD integrates batch correction directly into the contrastive

learning process via its sampling design, resulting in latent representations

inherently robust to batch effects.

Both the neighborhood-aware and dataset-aware samplers follow a unified

principle: probabilistically structuring mini-batches to balance global biological

diversity with local and dataset-specific variation. We integrate both samplers into

a joint sampling framework, where the likelihood of selecting a cell satisfies both

sampling schemes (Figure 1F). This generalized sampling scheme fundamentally

reconfigures contrastive learning, enabling both high-resolution representation

learning and robust dataset integration within a single contrastive objective, and

forms the core of the CONCORD framework (Supplemental Figure 1). With this

simple innovation to contrastive learning, CONCORD achieves state-of-the-art

performance using only a minimalist encoder with a single hidden layer,

demonstrating that the sampling framework alone can transform contrastive

learning performance—even without deep or complex architectures. This

simplicity reduces training data requirements, enhances robustness, and

increases interpretability by efficiently compressing heterogeneous cell states

into a compact latent space.

CONCORD learns denoised latent representations that preserve underlying

structures

Recovering biologically meaningful insights from single-cell data requires

preserving both the geometric organization and topological structure of the gene

expression space. To evaluate whether CONCORD meets this criterion, we

benchmarked its performance on both simulated and real-world datasets.

Existing simulators (e.g., splatter[32]) produce discrete clusters but fail to capture

complex biological structures such as branching, loops, and multi-scale

hierarchies. We therefore developed a custom simulation workflow that

generates a wide range of realistic structures with flexible control over noise and

batch effects (Figure 2A).

To assess the quality of learned representations, we implemented an evaluation

pipeline combining geometric and topological metrics (Figure 2B.). Traditional

benchmarking pipelines like scIB[33] focus on label preservation and batch

correction but overlook structural fidelity. We addressed this by incorporating

geometric metrics such as trustworthiness and distance correlation, along with

topological data analysis (TDA) based on persistent homology and Betti numbers

(Figure 2B). Trustworthiness quantifies local neighborhood preservation, while

persistent homology captures global topological features—like clusters (Betti-0),

loops (Betti-1), and voids (Betti-2)—across scales. These features are visualized

in persistence diagrams and Betti curves, where stable structures appear as

long-lived features in the persistence diagram and extended plateaus in the Betti

curve, whereas transient, noise-induced features vanish quickly.

We first evaluated CONCORD on a simple simulation of three well-separated

clusters corrupted by cluster-specific Gaussian noise (Figure 2C, Supplemental

Figure 2A). Compared to a broad set of dimensionality reduction methods—

including diffusion map, NMF, Factor Analysis, FastICA, Latent Dirichlet

Allocation (LDA), ZIFA, scVI, and PHATE —CONCORD cleanly separated

clusters and closely matched the ground truth in both the latent space and

pairwise distance matrix. In contrast, many methods failed to fully resolve the

clusters or introduced spurious structures, such as trajectory-like artifacts (Figure

2C). Persistent homology confirmed these observations: CONCORD's Betti-0

plateau accurately reflected the expected three-cluster topology and closely

matched the noise-free reference, highlighting its combined strength in denoising

and structure preservation.

For more complex structures, such as a self-connecting trajectory with three

loops and multiple branching points (Figure 2D, Supplemental Fig. 2B),

CONCORD was the only method that accurately recovered the full topology.

Other methods either collapsed the structure into discrete clusters or failed to

detect multiple loops in Betti analysis, likely due to excessive noise retention.

Although PHATE produced a visually smooth embedding, its Betti curve revealed

only a single persistent loop, missing key topological features of the underlying

structure.

We evaluated performance across simulated structures using geometric and

topological metrics, finding that CONCORD consistently outperformed alternative

methods (Figure 2E, 2F). Notably, despite its denoising capabilities, CONCORD

preserved relative noise levels in the latent space, evidenced by the strong

correlation between input and latent variance—critical for retaining biologically

meaningful variability such as transcriptional noise. It also maintained high

trustworthiness across a wide range of neighborhood sizes, underscoring its

ability to preserve local geometry at multiple scales (Supplemental Figure 2C,

2D). In contrast, other methods exhibit sharp declines in trustworthiness,

indicating a loss of fine-scale geometric relationships in the latent space.

To assess the impact of neighborhood-aware sampling, we simulated a

hierarchical branching tree mimicking a hypothetical differentiation trajectory

(Figure 2G, Supplemental Figure 2E). Without local sampling, sub-branches

were unresolved. Moderate enrichment improved resolution, while excessive

local focus (>0.6 intra-kNN probability) suppressed global distinctions

(Supplemental Figure 2E-F). These results support using intra-kNN sampling

probabilities below 0.5 to balance fine-grained resolution with global structure

preservation.

CONCORD learns a coherent, batch-effect-mitigated latent representation

Batch effects often appear as dataset-specific global signals that can obscure

biological variation. In CONCORD, these signals rapidly diminish during training

when mini-batches are restricted to single datasets (Figure 1E, Figure 3A).

Unlike conventional batch-correction methods that rely on explicit alignment

models, CONCORD makes minimal assumptions about the source or form of

batch effects and instead prioritizes learning coherent, biologically meaningful

gene covariation patterns. This leads to more accurate preservation of biological

structure while mitigating technical artifacts.

We tested CONCORD on a simulated dataset with five clusters corrupted by

batch effects and noise. CONCORD was the only method to accurately recover

all clusters; others either failed to resolve closely related states or introduced

artifacts - such as the ring-like structure produced by Scanorama[8]. Notably, using

a conventional uniform sampler without dataset-aware sampling resulted in

pronounced batch effects (Figure 3A). While effectively denoising, CONCORD

preserved cluster-specific variance rather than over-smoothing (Supplemental

Figure 3A), and its performance was consistent across various noise models

(e.g. Gaussian, Poisson) and batch-effect types, underscoring its flexibility and

generalizability (see Methods; data not shown).

Beyond clustering, a key challenge in integration is aligning datasets

representing related but distinct conditions - such as developmental stages,

perturbations, or species - with partial or no overlap in cell states. Methods

relying on matched clusters or mutual nearest neighbors often fail under such

conditions, producing distorted or fragmented embeddings, especially when the number of datasets increases. To systematically assess this, we simulated batch effects across clusters, trajectories, loops, and trees (Figure 3B–D, Supplemental Figure 3B–E). On a trajectory simulation where batches were fully overlapping, most methods achieved some degree of alignment, though several exhibited suboptimal corrections (e.g., scVI, LIGER) (Figure 3B). As overlap decreased, performance deteriorated: some methods failed to align batches (e.g., LIGER, Harmony), while others introduced artifacts, such as artificial loops (Scanorama) or merged clusters (scVI). In contrast, CONCORD consistently recovered the correct structure with reduced noise, even when shared cell states were sparse or absent (Figure 3A–D, Supplemental Figure 3B–E, Supplemental Table 1).

CONCORD's robustness arises from its focus on learning gene co-expression programs (see Methods, Figure 1B, Supplemental Figure 2A, 2B, 2E), which naturally group transcriptomically similar cells without requiring explicit reference anchors - a key distinction from many batch-correction approaches. As a result, CONCORD achieves high biological label conservation in scIB benchmarks (Figure 3E, 3F), though its batch-correction score is slightly lower because it does not explicitly merge batches. It also excels at preserving local geometry, as indicated by high trustworthiness scores, but shows lower global distance correlation - a common trade-off in manifold learning[34,35] (Figure 3F, Supplemental Table 1). Nonetheless, CONCORD consistently ranks among the top methods for topological preservation, label conservation, and overall performance (Figure 3F). These results demonstrate that CONCORD provides a reliable and generalizable framework for dimensionality reduction and batch correction, even in scenarios with unknown structure or limited batch overlap.

CONCORD aligns whole-organism developmental atlases and resolves high-resolution lineage trajectories

To assess whether CONCORD captures biologically meaningful structures

across technologies, we first benchmarked it against popular integration methods

on lung and pancreas atlases[33] (Supplemental Figure 4A, B). While CONCORD

effectively identified discrete cell types, these datasets lack continuous or

hierarchical structure, limiting their utility for evaluating performance in common

yet complex scenarios such as development and disease progression. To

address this, we turned to C. elegans embryogenesis—a well-characterized

system with a nearly invariant lineage tree[36], conserved in the related species *C.*

briggsae[37]. Packer et al. initially generated a lineage-resolved atlas of *C.*

elegans[38], which was recently expanded by Large et al. to include over 200,000

C. elegans cells and 190,000 *C. briggsae* cells[37]. With expert-curated

annotations generated through iterative, labor-intensive zoom-in analyses and

validated by fluorescent imaging, these datasets provide an ideal benchmark for

evaluating whether integration methods can accurately reconstruct and align

developmental trajectories across species.

Running CONCORD on the C. elegans dataset[38] produced UMAP embeddings

that recapitulated known developmental trajectories (Supplemental Figure 5A).

The effect of neighborhood-aware sampling mirrored trends observed in

simulations: moderate local enrichment improved resolution of subtle differences

among neurons, while excessive local sampling disrupted the global structure

(Supplemental Fig. 5A-C).

Applied to the larger, cross-species dataset, CONCORD generated a unified

developmental atlas closely aligned with original cell-type and lineage

annotations (Figure 4A), clearly separating broad cell classes (Supplemental

Figure 6A) and capturing smooth developmental transitions (Figure 4B). The

complexity of the learned structure exceeded the capacity of 2D UMAP,

necessitating 3D visualization to resolve trajectory crossovers (Figure 4A).

Running CONCORD with or without a decoder yielded similar UMAP

embeddings (Figure 4B), and we present the with-decoder version due to slightly

less entangled trajectories. To fully explore the intricate structures captured by

CONCORD, we highly encourage readers to view the interactive 3D

visualizations

(https://qinzhu.github.io/Concord_documentation/galleries/cbce_show/#__tabbed

_1_1).

To quantitatively evaluate integration, we analyzed each method's latent space.

As standard benchmarking tools (e.g., scIB[33]) could not scale to this dataset, we

adapted a neighborhood-based species mixing analysis - similar to kBET[39] -

stratified by developmental time (Figure 4C). CONCORD maintained expected

species fractions within local neighborhoods, while methods such as Scanorama,

scVI, and LIGER showed poor mixing or high variability. Harmony and scVI

achieved species alignment but at the cost of resolution, obscuring subtypes and

trajectories (Figure 4B-C). Seurat and CONCORD recovered divergent terminal

fates, but only CONCORD preserved continuous, fine-grained trajectories from

progenitors to terminal cell types.

Projecting the lineage tree onto CONCORD's embedding revealed strong

concordance with known lineage and fate relationships (Supplemental Figure 6B,

C). For example, the ASE, ASJ, and AUA neurons—derived from AB

progenitors—formed branching trajectories that mirrored their true lineage

structure (Figure 4D). In contrast, scVI and Seurat introduced large

discontinuities between parent and daughter lineages, failed to resolve key

bifurcation points, and generated artificial trajectory distortions. CONCORD's

latent space also distinguished functional subtypes, such as ASE-left (ASEL) and

ASE-right (ASER) neurons, characterized by differential expression of GCY

receptors (Figure 4E). Although morphologically symmetric, these neurons

exhibit functional asymmetry in salt-sensing responses[40,41].

To systematically assess the preservation of lineage structure, we replicated the

analysis from Packer et al.[38] by correlating latent distances with lineage

distances for AB-derived cells, which produce ~70% of terminal embryonic cells

(Figure 4F). Consistent with the original study - where transcriptome distances

correlated with lineage distances - CONCORD's latent distances showed strong

correlation with lineage distances, even in early generations where transcriptomic

differences were minimal. This highlights CONCORD's ability to capture subtle,

progressive molecular changes. Notably, it outperformed all other methods in

overall correlation (Figure 4G), underscoring its potential for trajectory inference

in developmental studies[42,43].

The advantage of CONCORD in resolving fine-scale structure became even

more evident when zooming into specific cell subsets. In early embryonic cells,

Scanorama, Harmony, and scVI failed to fully align species or lost resolution,

whereas CONCORD revealed extensive lineage bifurcations (Supplemental

Figure 6D). On muscle formation, CONCORD showed the MS, C, and D lineages

converge into sub-branches of body wall muscle, positioned from the head

(anterior) to the tail (posterior) in an orientation reflecting genuine spatial gene

expression gradients (Figure 4H, Supplemental Figure 6E). CONCORD also

resolved rare lineage convergence events, such as the integration of

ABplp/ABprp- and MS-derived cells into intestinal muscle (mu_int). Pharyngeal

development, involving complex branching and convergence of AB- and MS-

derived cells, was likewise resolved by CONCORD (e.g., pm3–5 deriving from

both AB and MS lineages, and pm1–2, 6–8 specific to AB/MS lineage), whereas

scVI and Seurat recovered fewer fine-grained details (Figure 4I, Supplemental

Figure 6F). Crucially, all analyses were performed directly on CONCORD's global

latent space, without the need for subset-specific variable gene selection or re-

alignment – steps that are often recommended for other methods.

Finally, CONCORD showed superior scalability, integrating the 400,000-cell, 20-batch dataset in ~30 minutes on an NVIDIA A100 GPU - significantly faster and more memory-efficient than LIGER, Seurat, and scVI (Figure 4J). These results establish CONCORD as a powerful and scalable tool for aligning and reconstructing complex developmental trajectories.

CONCORD captures cell cycle and differentiation trajectories in mammalian intestinal development

Unlike C. elegans, where early divisions are largely driven by maternal transcripts[44], mammalian development involves extensive proliferation coupled with ongoing differentiation. To assess whether CONCORD can resolve these intertwined processes, we applied it to a single-cell atlas of embryonic mouse intestinal development[45], which spans multiple developmental stages, batches, spatial segments, and enriched cell populations—posing a challenging integration task due to incomplete batch coverage (Figure 5A).

CONCORD efficiently integrated the data and resolved fine-grained substructures across diverse cell types (Figure 5A, Supplemental Fig. 7A, 8). It uniquely revealed loop-like patterns within many cell types—often missed by other methods—corresponding to cell cycle progression. Erythrocytes, which lack proliferative capacity, appropriately showed no such loop (Supplemental Figure 8). Given the complexity of these structures, 3D UMAP visualizations better preserved trajectory continuity than 2D projections (Supplemental Figure 7B), and we strongly encourage readers to explore the interactive embedding: (https://qinzhu.github.io/Concord_documentation/galleries/huycke_show/).

In intestinal epithelial cells, CONCORD not only resolved rare subtypes such as enteroendocrine cells (EECs), but also revealed two parallel differentiation trajectories, each forming its own cell cycle loop corresponding to spatially

distinct regions (Figure 5B). These structures were not captured by other

methods and were supported by adult zonation markers such as *Bex4* and

Onecut2[46], suggesting that CONCORD can detect epithelial zonation as early as

embryonic day 13.5.

In the enteric nervous system (ENS), CONCORD captured cell cycle of *Sox10*[+]

progenitor cells and identified a *Cck*[+] neuroblast population as the branch point

leading to two purported differentiation trajectories marked by *Etv1* and *Bnc2*[47]

(Figure 5C). These trajectories appear to converge through shared expression of

neuronal maturation genes broadly active at late stage of both branches

(Supplemental Figure 7C). Notably, CONCORD was the only method that

preserved both the cell cycle loop and the bifurcation, whereas other methods

introduced discontinuities or misplaced the branching point (Supplemental Figure

8).

For mesenchymal cells, which comprise a major fraction of this dataset,

CONCORD recovered the previously studied *Pdgfra*[+] trajectory involved in villus

formation[45] (Supplemental Figure 8) and uncovered extensive heterogeneity

within the *Pdgfra*[−] and smooth muscle populations (Figure 5D). These included

four consecutive cell cycle loops marked by expression of *Ebf1*, *Slit2*, *Kit*, and

Acta2, with gradual transitions between the loops (Figure 5D). Interestingly, *Ebf1*

and *Slit2* have been linked to mesenchymal multipotency[48,49], while *Kit* marks

interstitial cells of Cajal (ICC) and their progenitors[50,51]. Unlike traditional

approaches where cell cycle often confounds cell type annotation, CONCORD

preserves both proliferation and differentiation structures, enabling the

identification of previously uncharacterized subpopulations.

Unlike Seurat and scVI, which left many latent dimensions underutilized,

CONCORD produced a dense and interpretable latent space that reflects rich

biological structure and makes full use of its representational capacity (Figure

5E). As such, Each latent dimension in CONCORD typically encapsulates

multiple gene co-expression programs and can be interpreted at single-cell or

cell-state resolution using gradient-based attribution methods[52] in a context-

dependent manner (Figure 5F). For instance, latent neuron 46 (N46) was

activated in both epithelial cells and the ENS cells but driven by two distinct sets

of highly co-expressed genes in each context (Figure 5F, Supplemental Figure

7C). In epithelial cells, N46 activation was linked to goblet cell–specific genes

enriched in glycosylation pathways, while in ENS cells, it reflected neuronal

maturation genes expressed in late-stage neurons. Neither gene set shows

strong expression outside its respective context, indicating that CONCORD latent

captures biologically meaningful, context-specific gene co-expression programs.

Discussion

Mini-batch gradient descent underpins modern machine learning—including large

language models, foundation models, and diffusion models. Growing evidence

suggests that the composition of these mini-batches can influence model

performance[31,53]. In contrastive learning, where each sample is contrasted

against others within a mini-batch, this influence is amplified—especially in

biological datasets spanning multiple batches, where naive sampling can

exacerbate batch effects and distort learned representations. Yet in contrastive

learning for single cell data, uniform random sampling remains the norm, limiting

the method's ability to capture biological meaningful structure.

Our central insight is that, in contrastive learning, mini-batch composition not only

influences, but fundamentally shapes the outcome. By rethinking how mini-

batches are assembled, we turn contrastive learning's sensitivity to mini-batch

composition into a strength - transforming a conventional self-supervised

framework into a powerful, generalizable approach for denoising, dimensionality

reduction, and batch integration.

At the core of CONCORD is a unified, probabilistic sampler that integrates

neighborhood-aware and dataset-aware strategies. The neighborhood-aware

sampler balances global diversity with local variation, enabling the model to

resolve both broad and fine-grained biological structures—as validated by

geometric and topological benchmarks. The dataset-aware sampler ensures that

each mini-batch is enriched with cells from a single dataset, allowing the model

to learn biological variation without entangling batch effects. Unlike traditional

methods that rely on overlapping states or explicit batch-distortion models,

CONCORD mitigates batch effects solely through principled sampling and

training. As a result, it implicitly aligns cells based on shared gene co-expression

programs—a hallmark of transcriptomic data[6,54,55]—making it especially robust

when datasets have minimal or no overlap.

Importantly, CONCORD achieves state-of-the-art performance using a

minimalistic architecture—just a single hidden layer—demonstrating that

substantial gains can be achieved through rational sampling and training alone,

without relying on deep architectures, complex objectives, or supervision. Across

both simulated and real datasets, CONCORD consistently learns latent spaces

that are denoised, interpretable, and topologically faithful. In whole-organism

embryogenesis atlases, it accurately reconstructs fate bifurcations and lineage

convergences, enabling detailed tracing from progenitor cells to terminal states.

In contrast, existing methods often misalign these datasets, lose resolution, or

fragment continuous trajectories. In mammalian intestinal development,

CONCORD captures complex hierarchies, spatial zonation, and cell cycle

loops—all within a single integrated analysis. Unlike traditional workflows that

regress out cell cycle effects, CONCORD preserves and resolves both

proliferative and differentiation programs, facilitating investigations into their

interplay. Its interpretable latent space further enables gradient-based attribution

analyses, allowing gene-level mechanistic insights at single-cell or cell-type

resolution.

The current implementation of CONCORD emphasizes simplicity to enhance

robustness and scalability, but the framework is fully extensible to more complex

architectures—such as transformers[56]—to support more intricate data modalities

or biological contexts. This minimalist design reduces the number of tunable

parameters, though several hyperparameters remain critical for optimal

performance, including neighborhood size, enrichment probability, masking

fraction, and contrastive temperature. To support users, we provide a set of

default parameters validated across diverse datasets, along with detailed

tutorials and insights from prior studies[57] to guide effective parameter

optimization. Future improvements may include adaptive neighborhood sampling

that scales with distance or density, removing the need for manually defined radii

and enrichment probabilities.

In addition to the core contrastive encoder, CONCORD supports an optional

decoder and classifier modules for gene-level batch correction, label transfer,

and annotation-guided learning. Preliminary results suggest these tasks benefit

from the model's robust latent space, though further validation is ongoing. While

the current benchmarks focused on single-cell RNA-seq, we have observed

promising outcomes across other modalities, including spatial transcriptomics

and scATAC-seq. Owing to its domain-agnostic design and generalized sampling

framework, CONCORD holds potential beyond single-cell biology, offering a

flexible and powerful approach for representation learning across a wide range of

domains.

Methods

Self-supervised contrastive learning and sparse coding

We implemented CONCORD in PyTorch, building on a self-supervised contrastive learning approach inspired by SimCLR[21] and SimCSE[22], but with a unique dataset- and neighborhood-aware sampler design. The core loss function is the Normalized Temperature-scaled Cross Entropy Loss (NT-Xent loss)[21,22,58] applied to cell representations generated via random masking - following the design principles of unsupervised SimCSE[22].

Theoretically, it has been shown[29] that if input data x can be approximated as:

$$x = Mz + \varepsilon$$

where Mz represents the sparse signal with $\|z\|_0 = \tilde{O}(1)$, and ε denotes noise, contrastive learning can provably recover the underlying sparse features when trained with ReLU networks and random masking augmentation. CONCORD adopts similar conditions: we apply LeakyReLU activations and independent random masking to each augmented view, which enhances the model's ability to capture correlated gene co-expression patterns while suppressing spurious noise.

This sparse coding formulation provides a generalizable framework for modeling gene expression, extending beyond traditional methods such as non-negative matrix factorization (NMF), principal component analysis (PCA), factor analysis, and variational autoencoders (VAEs). Unlike these methods, sparse coding:

- Does not enforce orthogonality on M (as in PCA),
- Does not require non-negativity constraints (as in NMF),
- Does not assume a probabilistic generative model (as in factor analysis and VAEs),
- Does not enforce Gaussian priors on the latent space (as in VAEs).

Instead, it assumes an intrinsic low-rank structure shaped by gene co-expression programs—an assumption widely supported by single-cell transcriptomic studies[6,54,55]. By relaxing constraints on orthogonality, non-negativity, and

Gaussian priors, the contrastive learning framework is better positioned to

capture diverse gene regulatory programs that deviate from conventional

assumptions. Finally, the use of random masking improves robustness to

dropout—a pervasive artifact in scRNA-seq—and enhances biological

interpretability, enabling the latent space to more faithfully represent gene

programs underlying both discrete cell types and continuous trajectories.

Dataset and neighborhood-aware probabilistic sampler

At the heart of CONCORD is a probabilistic mini-batch sampler that determines

how cells are grouped and contrasted during training. Unlike conventional

contrastive learning frameworks that rely on uniform random sampling,

CONCORD introduces a unified, generalizable sampling strategy that

simultaneously (i) enriches for local neighborhoods and (ii) restricts each mini-

batch primarily to a single dataset. This principled design reshapes the outcome

of contrastive learning, enabling the model to produce a coherent, high-

resolution, and batch-effect-mitigated representation of the cell state landscape.

We begin by coarsely approximating the global data manifold using a k-nearest

neighbors (kNN) graph, where k is a user-defined parameter (typically

moderately large). The graph can be constructed from normalized gene

expression values, PCA projections, or a preliminary CONCORD batch-corrected

embedding generated with the dataset-aware sampler. For scalability, we

leverage the Faiss library[59] for efficient neighbor retrieval in large datasets. This

kNN graph then guides neighborhood-aware sampling, modulated by a user-

defined neighborhood enrichment probability, p_{kNN}.

To construct mini-batches that are both dataset- and neighborhood-enriched, we

partition each mini-batch into four subsets—in-dataset neighbors, in-dataset

global samples, out-of-dataset neighbors, and out-of-dataset global samples

(Figure 1F). A "core sample" is randomly selected from one dataset to anchor

both neighborhood and dataset-aware sampling. The four subsets are then

sampled based on P_d (the probability of sampling from the same dataset, default

0.95) and P_{kNN} (the probability of sampling from the local kNN neighborhood,

default 0.3) as follows:

• In-dataset neighbors: $P_d \times P_{kNN}$

Cells from the same dataset and within the core cell's kNN neighborhood.

• In-dataset global samples: $P_d \times (1 - P_{kNN})$

Uniformly sampled cells from the same dataset, outside the neighborhood.

• Out-of-dataset neighbors: $(1 - P_d) \times P_{kNN}$

Cells from other datasets that fall within the core cell's kNN neighborhood.

• Out-of-dataset global samples: $(1 - P_d) \times (1 - P_{kNN})$

Uniformly sampled cells from all other datasets.

The sampler is implemented using vectorized operations in PyTorch and NumPy

to optimize memory efficiency and minimize computational overhead, ensuring

scalability across large datasets and enabling rapid training.

Model architecture

A key advantage of CONCORD lies in its architectural flexibility. In this study, we

implement a minimalist encoder with a single hidden layer, demonstrating that

significant performance gains can be achieved through principled sampling and

training alone, without the need for deep or complex neural networks. However,

the architecture is fully extensible: users may substitute the encoder with more

advanced models - such as transformers - to accommodate different data

modalities or capture higher-order biological structures.

1. Encoder:

The encoder receives randomly masked gene expression vectors and

produces low-dimensional latent representations. By default, it consists of

a fully connected network with a single hidden layer, although users can

modify the number of layers and neurons as needed. An optional

learnable feature masking module can be added before the encoder to

differentially weight input genes, encouraging sparse and interpretable

feature usage.

Input gene-expression values are typically normalized by total count and

log-transformed, though CONCORD remains robust to various

normalization schemes provided they are applied consistently and avoid

introducing negative or zero values. During training, each cell is

augmented by randomly masking a subset of genes (recommended

dropout probability: 0.3–0.6), and two independently masked versions are

encoded to generate embeddings used in contrastive learning.

2. Layer normalization and activation:

Each linear layer is followed by layer normalization and a user-

configurable activation function (default: Leaky ReLU). Layer

normalization operates across features within each sample, offering

robustness to batch-specific variation—making it preferable to batch

normalization[60], though the latter is also supported.

3. Contrastive objective:

CONCORD employs the NT-Xent loss[21,22,58] operating on mini-batches of

N cells. Each cell is randomly masked and encoded twice, yielding two

different latent representations: z_i and z_j, then the contrastive loss is:

$$l_{i,j} = -\log\left(\frac{\exp\left(sim(z_i, z_i')/\tau\right)}{\sum_{k=1}^{2N} 1_{[k \neq i]}\exp\left(sim(z_i, z_k)/\tau\right)}\right)$$

where $sim(z_i, z_i') = \frac{z_i^T z_j}{\|z_i\|\|z_j\|}$ is the cosine similarity, and τ (default 0.5) is a

customizable temperature hyperparameter that controls the extent of local

separation and global uniformity of the embeddings[57].

4. Optional decoder and classifier:

For applications requiring reconstruction of gene expression profiles, a

decoder can be attached to the latent embeddings. To prevent the

decoder from reintroducing batch-specific variation, a separate, learnable

dataset embedding is appended only at decoding time—keeping the core

latent space batch-effect-free.

A classification head (i.e., a multi-layer perceptron trained with cross-

entropy loss) can be appended to the encoder for downstream tasks such

as cell-type annotation or doublet detection. The classifier can be trained

on top of a pre-trained encoder or jointly with the encoder to actively guide

cell-type separation in the latent space. While joint training can enhance

class distinction, it may also impose a strong prior on the latent structure,

potentially disrupting the continuity of trajectories. To mitigate overfitting,

we recommend a train–validation split with early stopping during classifier

training.

Model training

During each training epoch, CONCORD constructs mini-batches using its

dataset- and neighborhood-aware sampler, followed by random mini-batch

shuffling. The core contrastive objective—NT-Xent loss—is optimized using the

Adam optimizer[61]. Optional loss terms, including mean squared error (MSE) for

the decoder, cross-entropy loss for classification, and L1/L2 regularization for

feature-masking modules, can be incorporated as needed. By default, all loss

components are weighted equally, but users may adjust these weights to suit

specific tasks. A learning rate scheduler is employed to gradually reduce the

learning rate over time, promoting stable convergence.

Simulation pipeline

We developed a versatile simulation pipeline to generate synthetic single-cell

gene expression data with diverse underlying structures. Unlike conventional

simulators that predominantly produce discrete clusters, our pipeline

accommodates a broad range of topologies, including linear trajectories,

branching trees, loops, and intersecting paths frequently observed in real single-

cell datasets.

In the first stage the state simulator constructs data according to a user-defined

structure:

•   Clusters: Cells form discrete groups characterized by unique gene

programs, optionally including shared or ubiquitously expressed genes.

•   Trajectories: Cells exhibit gradual shifts in gene expression, emulating cell

differentiation processes.

•   Loops and intersecting paths: Continuous trajectories that close into loops

or intersect, representing cyclic biological processes.

•   Trees: Hierarchical, branching lineages representing progenitor-to-terminal

fate differentiation, configurable by branching factor and tree depth.

With the chosen structure, the pipeline first generates a *noise-free* data matrix

with customizable cell and gene numbers. Expression values are then sampled

from selected distributions (e.g., Normal, Poisson, Negative Binomial),

introducing realistic variability and dropout patterns. Users can precisely control

parameters including mean baseline expression, dispersion (noise level), dropout

probability, and can enforce non-negativity or integer rounding of the generated

values.

In the second step, an optional batch simulator introduces dataset-specific

technical variability. This stage enables simulation of batch effects through

scaling factors, differential sampling rates, batch-specific gene subsets, and

expression-dependent dropout mechanisms. Multiple simulated batches are then

concatenated into a single dataset, with customizable proportions and varying

degrees of batch overlap to mimic real-world sampling scenarios.

By combining diverse gene expression structures with realistic noise models and

customizable batch effects, this simulation pipeline can approximate a broad

spectrum of biological and technical scenarios. As such, it provides a powerful

testbed for benchmarking data-integration techniques, trajectory-inference

algorithms, and manifold-learning methods under controlled yet biologically

realistic conditions.

Benchmarking pipeline

To comprehensively evaluate the performance of CONCORD and other

dimensionality reduction or data integration methods, we designed a robust

benchmarking pipeline that integrates geometric, topological, biological, and

batch-mixing metrics. This multifaceted assessment framework consists of the

following components:

1. Topological assessments:

To quantify the preservation of intrinsic topological features, we employed

persistent homology analysis implemented via Giotto-TDA[62]. Persistent

homology captures structural properties of the data across multiple scales,

using Vietoris-Rips complexes constructed over increasing radii to

generate persistence diagrams and Betti curves. Persistence diagrams

reveal the lifespan of topological features such as connected components

(Betti-0), loops (Betti-1), and voids (Betti-2). We summarized these

diagrams through Betti curves and compared their mode—representing

the most persistent Betti number across all scales—to the known

topological ground truths. Additionally, we computed the entropy of Betti

curves to quantify the stability and complexity of the inferred topology, with

lower entropy reflecting stable and distinct structures, and higher entropy

indicating noisy or unstable topologies. These metrics were scaled

between 0 and 1 using min-max normalization to facilitate comparisons

among methods.

2. Geometric assessments:

We evaluated the preservation of geometric relationships by calculating

distance correlations between embeddings and the corresponding noise-

free reference data, averaging Pearson, Spearman, and Kendall's tau

correlations to robustly quantify global geometric similarity. For local

neighborhood preservation, we employed trustworthiness[63], a metric

assessing how faithfully high-dimensional neighborhood structures are

maintained in lower-dimensional embeddings. Trustworthiness scores

range from 0 (poor preservation) to 1 (perfect preservation), and we

computed average trustworthiness scores across neighborhood sizes (k-

values) from 10 to 100 in increments of 10. Additionally, we visualized

trustworthiness as a function of k to reveal how each method performs at

different local scales. In cluster simulations with cluster-specific noise, we

further assessed the correlation of variance between the latent embedding

and the noisy input data, quantifying how accurately each method

preserves relative noise levels.

3. Batch mixing and biological label conservation:

We adopt established metrics from the scIB-metrics package[33] to

systematically evaluate biological label conservation and batch mixing.

Biological label conservation was quantified using metrics such as

Normalized Mutual Information (NMI) and Adjusted Rand Index (ARI),

which measure the correspondence between known biological labels and

inferred clusters. Batch mixing quality was assessed using silhouette

scores and graph metrics to determine how effectively embeddings

integrate cells from different batches or datasets.

A key limitation of the scIB pipeline is that the pipeline does not fully

accommodate the hierarchical and continuous nature of many biological

systems. Consequently, for simulations with continuous trajectories or

loops, we first apply Leiden clustering to noise-free data to define

"clusters" as ground truth, or use "branch" labels as a proxy for cell states

in tree simulations. Under these conditions, the scIB metrics are applied in

a more coarse-grained manner, offering an approximate assessment in

these more complex scenarios.

Data Availability

The human lung and pancreas datasets were compiled by Luecken et al.[33], and

obtained from the scIB-metrics website (https://scib-

metrics.readthedocs.io/en/stable/notebooks/lung_example.html) and the Open

Problems in Single-Cell Analysis website

(https://openproblems.bio/datasets/openproblems_v1/pancreas), respectively.

The *C. elegans* embryogenesis atlas was downloaded from the Gene Expression

Omnibus (GEO) (www.ncbi.nlm.nih.gov/geo) under accession code GSE126954.

The joint *C. elegans* and *C. briggsae* dataset was obtained via email request

from the authors of Large et al[37]. The mouse intestinal developmental atlas was

acquired from GEO under accession code GSE233407.

Code Availability

832 Concord is available at https://github.com/Gartner-Lab/Concord under the MIT

833 License. All benchmarking codes to generate results in this manuscript are

834 deposited to https://github.com/Gartner-Lab/Concord_benchmark. Full

835 documentation of Concord can be found at:

836 https://qinzhu.github.io/Concord_documentation/.

References

1   Wagner, D. E. & Klein, A. M. Lineage tracing meets single-cell omics:
opportunities and challenges. *Nature Reviews Genetics* **21**, 410-427
(2020).
2   Tanay, A. & Regev, A. Scaling single-cell genomics from phenomenology
to mechanism. *Nature* **541**, 331-338 (2017).
3   Flores-Bautista, E. & Thomson, M. Unraveling cell differentiation
mechanisms through topological exploration of single-cell developmental
trajectories. *bioRxiv*, 2023.2007. 2028.551057 (2023).
4   Riba, A. *et al.* Cell cycle gene regulation dynamics revealed by RNA
velocity and deep-learning. *Nature communications* **13**, 2865 (2022).
5   Johnson, J. A. *et al.* Inferring cellular and molecular processes in single-
cell data with non-negative matrix factorization using Python, R and
GenePattern Notebook implementations of CoGAPS. *Nature protocols* **18**,
3690-3731 (2023).
6   Kunes, R. Z., Walle, T., Land, M., Nawy, T. & Pe'er, D. Supervised
discovery of interpretable gene programs from single-cell data. *Nature
Biotechnology* **42**, 1084-1095 (2024).
7   Korsunsky, I. *et al.* Fast, sensitive and accurate integration of single-cell
data with Harmony. *Nature methods* **16**, 1289-1296 (2019).
8   Hie, B., Bryson, B. & Berger, B. Efficient integration of heterogeneous
single-cell transcriptomes using Scanorama. *Nature biotechnology* **37**,
685-691 (2019).
9   Stuart, T. *et al.* Comprehensive integration of single-cell data. *cell* **177**,
1888-1902. e1821 (2019).
10   Lopez, R., Regier, J., Cole, M. B., Jordan, M. I. & Yosef, N. Deep
generative modeling for single-cell transcriptomics. *Nature methods* **15**,
1053-1058 (2018).
11   Welch, J. D. *et al.* Single-cell multi-omic integration compares and
contrasts features of brain cell identity. *Cell* **177**, 1873-1887. e1817
(2019).
12   Haghverdi, L., Lun, A. T., Morgan, M. D. & Marioni, J. C. Batch effects in
single-cell RNA-sequencing data are corrected by matching mutual
nearest neighbors. *Nature biotechnology* **36**, 421-427 (2018).
13   Zhang, Z. *et al.* Recovery of biological signals lost in single-cell batch
integration with CellANOVA. *Nature Biotechnology*, 1-17 (2024).
14   Richter, T., Bahrami, M., Xia, Y., Fischer, D. S. & Theis, F. J. Delineating
the effective use of self-supervised learning in single-cell genomics.
Nature Machine Intelligence, 1-11 (2024).
15   Ciortan, M. & Defrance, M. Contrastive self-supervised clustering of
scRNA-seq data. *BMC bioinformatics* **22**, 280 (2021).
16   Wang, J., Xia, J., Wang, H., Su, Y. & Zheng, C.-H. scDCCA: deep
contrastive clustering for single-cell RNA-seq data based on auto-encoder
network. *Briefings in Bioinformatics* **24**, bbac625 (2023).
17   Zhao, B., Song, K., Wei, D.-Q., Xiong, Y. & Ding, J. scCobra allows
contrastive cell embedding learning with domain adaptation for single cell

data integration and harmonization. *Communications Biology* **8**, 233
(2025).
18 Yang, M. *et al.* Contrastive learning enables rapid mapping to multimodal
single-cell atlas of multimillion scale. *Nature Machine Intelligence* **4**, 696-
709 (2022).
19 Heimberg, G. *et al.* A cell atlas foundation model for scalable search of
similar human cells. *Nature*, 1-3 (2024).
20 Heryanto, Y. D., Zhang, Y.-z. & Imoto, S. Predicting cell types with
supervised contrastive learning on cells and their types. *Scientific Reports*
14, 430 (2024).
21 Chen, T., Kornblith, S., Norouzi, M. & Hinton, G. in *International
conference on machine learning.* 1597-1607 (PMLR).
22 Gao, T., Yao, X. & Chen, D. Simcse: Simple contrastive learning of
sentence embeddings. *arXiv preprint arXiv:2104.08821* (2021).
23 He, K., Fan, H., Wu, Y., Xie, S. & Girshick, R. in *Proceedings of the
IEEE/CVF conference on computer vision and pattern recognition.* 9729-
9738.
24 Goodfellow, I. *et al.* Generative adversarial networks. *Communications of
the ACM* **63**, 139-144 (2020).
25 Lotfollahi, M., Wolf, F. A. & Theis, F. J. scGen predicts single-cell
perturbation responses. *Nature methods* **16**, 715-721 (2019).
26 Ganin, Y. & Lempitsky, V. in *International conference on machine learning.*
1180-1189 (PMLR).
27 Sohn, K., Lee, H. & Yan, X. Learning structured output representation
using deep conditional generative models. *Advances in neural information
processing systems* **28** (2015).
28 Heimberg, G., Bhatnagar, R., El-Samad, H. & Thomson, M. Low
dimensionality in gene expression data enables the accurate extraction of
transcriptional programs from shallow sequencing. *Cell systems* **2**, 239-
250 (2016).
29 Wen, Z. & Li, Y. Toward understanding the feature learning process of self-
supervised contrastive learning. *International Conference on Machine
Learning*, 11112-11122 (2021).
30 Alaqeeli, O. A comparison of dropout rate of three commonly used single
cell RNA-sequencing protocols. *Biotechnology & Biotechnological
Equipment* **38**, 2379837 (2024).
31 Yang, Z. *et al.* Batchsampler: Sampling mini-batches for contrastive
learning in vision, language, and graphs. *Proceedings of the 29th ACM
SIGKDD Conference on Knowledge Discovery and Data Mining*, 3057-
3069 (2023).
32 Zappia, L., Phipson, B. & Oshlack, A. Splatter: simulation of single-cell
RNA sequencing data. *Genome biology* **18**, 174 (2017).
33 Luecken, M. D. *et al.* Benchmarking atlas-level data integration in single-
cell genomics. *Nature methods* **19**, 41-50 (2022).
34 Van der Maaten, L. & Hinton, G. Visualizing data using t-SNE. *Journal of
machine learning research* **9** (2008).

35 Tenenbaum, J. B., Silva, V. d. & Langford, J. C. A global geometric
framework for nonlinear dimensionality reduction. *science* **290**, 2319-2323
(2000).
36 Sulston, J. E., Schierenberg, E., White, J. G. & Thomson, J. N. The
embryonic cell lineage of the nematode Caenorhabditis elegans.
Developmental biology **100**, 64-119 (1983).
37 Large, C. R. *et al.* Lineage-resolved analysis of embryonic gene
expression evolution in C. elegans and C. briggsae. *bioRxiv*, 2024.2002.
2003.578695 (2024).
38 Packer, J. S. *et al.* A lineage-resolved molecular atlas of C. elegans
embryogenesis at single-cell resolution. *Science* **365**, eaax1971 (2019).
39 Büttner, M., Miao, Z., Wolf, F. A., Teichmann, S. A. & Theis, F. J. A test
metric for assessing single-cell RNA-seq batch correction. *Nature*
methods **16**, 43-49 (2019).
40 Ortiz, C. O. *et al.* Searching for neuronal left/right asymmetry:
genomewide analysis of nematode receptor-type guanylyl cyclases.
Genetics **173**, 131-149 (2006).
41 Yu, S., Avery, L., Baude, E. & Garbers, D. L. Guanylyl cyclase expression
in specific sensory neurons: a new family of chemosensory receptors.
Proceedings of the National Academy of Sciences **94**, 3384-3387 (1997).
42 Saelens, W., Cannoodt, R., Todorov, H. & Saeys, Y. A comparison of
single-cell trajectory inference methods. *Nature biotechnology* **37**, 547-554
(2019).
43 Kuang, D., Qiu, G. & Kim, J. Reconstructing Cell Lineage Trees from
Phenotypic Features with Metric Learning. *arXiv* **2503.13925** (2025).
44 Koreth, J. & van den Heuvel, S. Cell-cycle control in Caenorhabditis
elegans: how the worm moves from G1 to S. *Oncogene* **24**, 2756-2764
(2005).
45 Huycke, T. R. *et al.* Patterning and folding of intestinal villi by active
mesenchymal dewetting. *Cell* **187**, 3072-3089. e3020 (2024).
46 Zwick, R. K. *et al.* Epithelial zonation along the mouse and human small
intestine defines five discrete metabolic domains. *Nature Cell Biology* **26**,
250-262 (2024).
47 Morarach, K. *et al.* Diversification of molecularly defined myenteric neuron
classes revealed by single-cell RNA sequencing. *Nature neuroscience* **24**,
34-46 (2021).
48 Derecka, M. *et al.*   (American Society of Hematology Washington, DC,
2017).
49 Chen, C.-P., Wang, L.-K., Chen, C.-Y., Chen, C.-Y. & Wu, Y.-H. Placental
multipotent mesenchymal stromal cell-derived Slit2 may regulate
macrophage motility during placental infection. *Molecular Human*
Reproduction **27**, gaaa076 (2021).
50 Al-Shboul, O. A. The importance of interstitial cells of cajal in the
gastrointestinal tract. *Saudi Journal of Gastroenterology* **19**, 3-15 (2013).

51 Torihashi, S. *et al.* Blockade of kit signaling induces transdifferentiation of interstitial cells of cajal to a smooth muscle phenotype. *Gastroenterology* **117**, 140-148 (1999).

52 Ancona, M., Ceolini, E., Öztireli, C. & Gross, M. Gradient-based attribution methods. *Explainable AI: Interpreting, explaining and visualizing deep learning*, 169-191 (2019).

53 Smirnov, E. *et al.* in *Proceedings of the IEEE/CVF International Conference on Computer Vision Workshops.* 0-0.

54 Jiang, J. *et al.* D-SPIN constructs gene regulatory network models from multiplexed scRNA-seq data revealing organizing principles of cellular perturbation response. *BioRxiv*, 2023.2004. 2019.537364 (2024).

55 Kotliar, D. *et al.* Identifying gene expression programs of cell-type identity and cellular activity with single-cell RNA-Seq. *Elife* **8**, e43803 (2019).

56 Vaswani, A. *et al.* Attention is all you need. *Advances in neural information processing systems* **30** (2017).

57 Wang, F. & Liu, H. in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition.* 2495-2504.

58 Sohn, K. Improved deep metric learning with multi-class n-pair loss objective. *Advances in neural information processing systems* **29** (2016).

59 Douze, M. *et al.* The faiss library. *arXiv preprint arXiv:2401.08281* (2024).

60 Lei Ba, J., Kiros, J. R. & Hinton, G. E. Layer normalization. *ArXiv e-prints*, arXiv: 1607.06450 (2016).

61 Kingma, D. P. & Ba, J. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980* (2014).

62 Tauzin, G. *et al.* giotto-tda:: A topological data analysis toolkit for machine learning and data exploration. *Journal of Machine Learning Research* **22**, 1-6 (2021).

63 Venna, J. & Kaski, S. in *International conference on artificial neural networks.* 485-491 (Springer).

1004

Acknowledgement

We thank Dr. Junhyong Kim, Dr. John Murray, and Dr. Honesty Kim for providing valuable feedback on the manuscript. We also thank the authors of Large et al.[37] for sharing the *C. elegans* and *C. briggsae* dataset, with special acknowledgement to Dr. Christopher R. L. Large for facilitating data access. Additionally, we thank members of the Gartner Lab for providing critical discussions and support and help with testing early versions of CONCORD. We thank ChatGPT for assistance with code refinement and annotation. This research was supported by grants from the NIH (U01CA199315, R01GM135462, R01DK126376, U01DK103147, and R33CA247744), the Chan Zuckerberg Initiative (CZI 2023-332284), and the UCSF Center for Cellular Construction (DBI-1548297), an NSF Science and Technology Center. Q.Z. is supported by a Cancer Research Institute Immuno-Informatics Postdoctoral Fellowship (CRI5054). Z.J.G. is a Chan Zuckerberg BioHub San Francisco Investigator.

Author Contributions

Q.Z. and Z.J.G. conceived the project. Q.Z. designed and implemented the method. Q.Z. conducted benchmarking analyses with assistance from Z.J. M.T. provided critical feedback and methods for topological data analysis. Z.J.G. supervised the project. Q.Z. and Z.J.G. wrote the manuscript. All authors reviewed and edited the manuscript.

Competing Interests

ZJG is an author on patents associated with sample multiplexing and ZJG is an equity holder and advisor to Provenance Bio.

Materials & Correspondence

1032   Correspondence to Q. Zhu (qin.zhu@ucsf.edu) and Z. J. Gartner

1033   (zev.gartner@ucsf.edu).

1034

 Figures

Figure 1. The CONCORD sampler enables high-resolution, batch-effect-mitigated latent representation of scRNA-seq data generated by contrastive learning.

(A) Illustration of hypothetical cell state landscapes and corresponding dimensionality-reduced representations that capture key structural features of the landscape. (**B**) Comparison of neighborhood-aware and uniform sampling and their impact on contrastive learning in a simulated four-cell-state dataset. The heatmap shows the actual simulated expression. For each sampling scheme, PCA plots are color-coded by cell state, with black points indicating cells selected in a representative mini-batch, accompanied by density curves illustrating their distribution. Latent heatmaps display the representations learned using uniform and neighborhood-aware sampling, with black lines marking cells included in the selected mini-batch and density plots depicting their distribution. The resulting UMAP embeddings computed from the latent representations for each sampling method are also shown. (**C**) Contrastive learning performed in a single batch with the conventional sampler, which draws cells uniformly from the entire dataset to form mini-batches. (**D**) When applying standard contrastive learning to multiple datasets (represented by the blue or pink background), contrasting cells from different datasets within the same mini-batch amplifies dataset-specific biases, which is manifested in the latent embeddings. (**E**) CONCORD mitigates these dataset-specific artifacts by predominantly contrasting cells within each dataset and randomly shuffling mini-batches for each training epoch. (**F**) The CONCORD sampling framework. A "leaky" dataset-aware sampler addresses minimal or absent overlap between datasets and can be combined with the neighborhood-aware sampler to support both data integration and enhanced resolution. This is achieved by a joint probabilistic sampling framework, where the likelihood of selecting a given cell reflects the combined probabilities of dataset-aware (P_d) and neighborhood-aware sampling (P_{kNN}).

1036

1037

Figure 2. Benchmarking CONCORD and other dimensionality reduction methods across diverse structures.

(A) Simulation pipeline for generating data structures. The pipeline first produces a noise-free gene expression matrix based on a user-defined structure, then introduces noise following a specified noise model, and finally

applies batch effects in various forms. (**B**) Evaluation pipeline. Using the simulated datasets, the latent representations produced by each method was compared with the noise-free ground truth to assess how well topological and geometric features are preserved. For cluster simulations, we further evaluate the correlation of cluster-specific variances in the noisy data versus the latent space. Metrics from the scIB[33] package were incorporated for evaluating conservation of biological labels and harmonization of batch effects. (**C**) Performance on simulated clusters, highlighting the resulting UMAP visualization, cosine distance matrices, persistence diagrams, and Betti curves for CONCORD and other methods. In the persistent homology analysis, the H_0 point representing infinity was excluded from the persistence diagram and curve. (**D**) Performance on a complex trajectory with 3 loops, highlighting the same diagnostic plots as C. (**E**) Summary table for the three-cluster simulation, listing key topological and geometric evaluation metrics. (**F**) Table summarizing the methods' performance on the complex trajectory-loop simulation. (**G**) KNN graph visualization of latent embeddings from each method on a complex tree simulation, with zoomed-in views of the darkened region highlighting detail on one of the branches.

1038

1039

Figure 3. Benchmarking CONCORD and other data integration methods across diverse structures.

(**A**) Two-batch, five-cluster simulation. For ground truth, we show kNN graphs (k=15 by default, with edges omitted) of both the noise-free and noise-added data (no batch effect). Latent spaces from each integration method are

visualized by kNN graphs, colored by batch (top) and cluster (bottom). (**B**) Trajectory simulation with varying batch overlap. The ground truth is shown with PCA and a kNN graph. For each method, the resulting latent space is depicted with a kNN graph (k = 15) to assess how well cells are integrated across batches along the trajectory. In the gap simulation, an additional kNN graph (k = 30), colored by simulated time, demonstrates that CONCORD accurately captures the correct orientation of the trajectories along time despite the gap. (**C**) Loop simulation with varying batch overlap. Shown here are kNN graphs of the ground truth (with edges omitted) and the CONCORD latent space. Full results for other methods are provided in Supplementary Figure 3D. (**D**) Tree simulation with varying batch overlap. kNN graphs for the ground truth and the CONCORD latent space are shown. Full results for other methods are provided in Supplementary Figure 3E. (**E**) scIB benchmarking on the two-batch, five-cluster simulation. Integration performance was evaluated using metrics from the scIB-metrics package[33]. (**F**) Ranking of integration methods. Each method's performance is scored across topological, geometric, and scIB metrics. The overall rank is based on the average ranking across all metrics.

1040

1041

Figure 4. Benchmarking CONCORD on *C. elegans/C.briggsae* embryogenesis atlas.

(A) Global 2D and 3D UMAPs of CONCORD (with decoder) colored by cell type and estimated embryo time. (**B**) UMAP of CONCORD and other integration methods colored by estimated embryo time and species. (**C**) Boxplots show the fraction of *C. elegans* cells within randomly sampled 100-

nearest-neighbor (100-NN) neighborhoods, stratified by embryo time bins. The red horizontal line represents the expected species fraction based on the global composition of each time bin. Well-integrated datasets should show species fractions closely matching this expected value with minimal variation. (**D**) Global 3D UMAPs of CONCORD (with decoder), Seurat and scVI, highlighting cells mapped to the lineage sub-tree that give rise to ASE, ASJ and AUA neurons. For each method, the most representative view was selected. (**E**) Heatmap showing the top 50 most variable latent dimensions in the ASE, ASJ, and AUA neuron subset for scVI, Seurat, and CONCORD (with decoder). Expression of gcy-5 and gcy-14 were plotted on the CONCORD (with decoder) UMAP. (**F**) Latent space distance between medoids of ectodermal cells (AB lineage), stratified by cell generation and lineage relationship. AB5 refers to cells derived after five successive divisions of the AB founder cell, with AB6 to AB9 representing progressively later generations. (**G**) Spearman correlation between lineage distance and latent space distance across integration methods for AB lineages from generations 5 to 9. Statistical significance of differences in correlations was assessed using a two-sided Mann-Whitney U test, with asterisks indicating significance levels (**p < 0.01, ***p < 0.001, ****p < 0.0001). (**H**) Zoom-in UMAPs for mesoderm cells excluding pharynx. Major input lineages and cell types were highlighted. Each lineage was represented by its cluster medoid on the UMAP, and lines connect each parental lineage to its daughter lineages following the lineage tree. (**I**) Zoom-in UMAPs for pharynx, annotated with cell types and broad input lineages. Selected lineage paths that give rise to pm1/2, pm3-5, and pm6 are highlighted. (**J**) Run time comparison of different integration methods. *Harmony was run using a 300-dimensional PCA input, whereas all other methods were applied to the gene expression matrix containing 10,000 variably expressed genes.

1042

1043

Figure 5. Benchmarking CONCORD on mammalian intestine development.

(**A**) 2D and 3D UMAP visualizations of CONCORD latent space, colored by cell type and cell cycle phase, with cell-type-colored UMAPs from scVI and Seurat shown for comparison. (**B**) Zoom-in views of epithelial cells in the 3D global

UMAP, colored by cell subtype, zonation, and expression of zonation-specific markers (*Bex4*, *Onecut2*). A red marker and arrow indicate the viewing angle within the 3D global UMAP. (**C**) Zoom-in view of enteric nervous system (ENS) cells, colored by cell cycle phase and cell state/branch annotations, based on Morarach et al[47], along with state-specific gene expression. A red marker and arrow indicate the viewing angle. (**D**) Zoom-in view of Pdgfra- mesenchymal cells and smooth muscle cells, colored by cell cycle phase, subtype annotation, and selected subtype-specific markers. A red marker and arrow indicate the viewing angle. (**E**) Heatmap of all latent encodings generated by CONCORD, Seurat, and scVI. (**F**) Interpretation of CONCORD latent space using gradient-based attribution techniques. Activation of Neuron 46 (Z46) in epithelial and ENS cells is attributed to the co-expression of epithelial- and neuron-specific gene sets in their respective contexts. GO enrichment analysis of these gene sets is shown.

1044

Supplementary Information

Supplementary Figures

Supplemental Figure 1. The CONCORD framework.

Each cell undergoes random masking twice, and contrastive loss is computed on the latent encodings of mini-batches sampled using the dataset- and neighborhood-aware sampler. The model architecture used in this work is a minimalistic neural network with a single hidden layer, though the framework supports reconfiguration with more complex designs. An optional decoder, incorporating a learnable dataset covariate, enables batch-free gene expression inference, while an optional classifier can be included for cell type classification or annotation-guided learning.

1048

Supplemental Figure 2. Benchmarking CONCORD and other dimensionality reduction methods across diverse structures.

(A) Heatmaps of the simulated expression for the 3-cluster structure and the corresponding CONCORD latent encoding. (**B**) Heatmaps of the simulated expression for the trajectory-loop structure and the corresponding CONCORD latent encoding. (**C**) Trustworthiness measured across varying neighborhood sizes in the 3-cluster simulation. Note that in the noise-free setting, within-cluster neighbors are assigned randomly, so trustworthiness does not equal 1 for the no-noise data. (**D**) Trustworthiness measured across varying neighborhood sizes in the complex trajectory-loop simulation. (**E**) Heatmaps of the simulated expression for the complex tree structure shown in Figure 2G and the CONCORD latent encoding with different intra-kNN enrichments. (**F**)

Trustworthiness measured across varying neighborhood sizes in the complex tree simulation, evaluated under different intra-kNN enrichment conditions. A zoomed-in view of the region where k < 20 and trustworthiness > 0.96 highlights improvements in capturing local neighborhood relationships with moderate intra-kNN enrichments.

1049

1050

Supplemental Figure 3. Benchmarking CONCORD and other data integration methods across diverse structures. (**A**) Correlation of cluster-specific variances between noise-added ground truth and latent from each integration methods. (**B**) Two-batch, five-cluster simulation with minimal overlap. The two batches share only one cluster. kNN graphs (edges omitted) from each integration method are shown. (**C**) Trajectory simulation with full and

partial overlap. kNN graphs (edges omitted) of the ground truth and CONCORD latent with varying intra-dataset enrichment (P_d) are shown, colored by batch (top) and time (bottom). (**D**) Loop simulation with varying batch overlap. kNN graphs (edges omitted) of the ground truth and each integration method are shown. (**E**) Tree simulation with varying batch overlap. kNN graphs (edges omitted) of the ground truth and each integration method are shown.

1051

1052

1053

Supplemental Figure 4. Performance of CONCORD on lung and pancreas datasets. (**A**) UMAPs were generated for both unintegrated lung data[33] and the latent space from each integration method, colored by technology and cell type. Benchmarking statistics from the scIB-metrics package[33] were shown. (**B**) Benchmarking of CONCORD on the integration of pancreas dataset[33]. UMAPs were generated for both unintegrated data and the latent space from each

integration method, colored by technology and cell type. Benchmarking statistics from the scIB-metrics package[33] were shown.

1054

Supplemental Figure 5. Effect of neighborhood-aware sampling on *C. elegans* embryogenesis atlas. (**A**) Global UMAP of CONCORD latent space with varying levels of intra-kNN enrichment, colored by embryonic time. (**B**) Global and zoomed-in UMAPs highlighting ciliated neurons, colored by embryonic time, generated from CONCORD latent representations across different levels of intra-kNN enrichment. (**C**) Visualization of cells sampled within a single mini-batch using an intra-kNN probability of 0.5. These cells are highlighted in the global UMAPs of CONCORD without neighborhood enrichment and with 0.5 neighborhood enrichment, demonstrating the effect of local sampling on structural resolution.

1055

Supplemental Figure 6. Cell lineage tree and zoom-in analysis of C.
elegans/C.briggsae embryogenesis atlas. (**A**) Global UMAP of CONCORD
(with decoder) colored by broad cell class. (**B**) The lineage annotations by
Large et al. were mapped to the *C. elegans* lineage tree, with some ambiguous
mappings due to symmetry. Each lineage was represented by its cluster
medoid on the UMAP, and lines connect each parental lineage to its daughter
lineages following the lineage tree. (**C**) For CONCORD (with decoder), lineage

sub-trees of major lineage groups were separately highlighted. (**D**) UMAPs of early embryo cells with embryo time before or equal to 200 minutes, colored by lineage and species. (**E**) Zoom-in UMAPs for mesoderm cells excluding pharynx. Each input lineage was represented by its cluster medoid on the UMAP, and lines connect each parental lineage to its daughter lineages following the lineage tree. Estimated embryo time was also plotted on the UMAP generated with CONCORD (with decoder) latent. (**F**) Zoom-in UMAPs for pharynx, colored by cell types and input lineages. Lineage paths were plotted following the lineage tree. Estimated embryo time was also plotted on the UMAP generated with CONCORD (with decoder) latent.

1056

Supplemental Figure 7. Benchmarking CONCORD on mammalian intestine development. (**A**) UMAPs of the mouse intestinal developmental atlas[45] generated from CONCORD latent space, other integration methods, and unintegrated data, colored by broad cell type, batch, cell cycle phase, developmental stage, and zonation. (**B**) 3D UMAPs of CONCORD with and without the decoder, colored by cell type and cell cycle phase. (**C**) Expression patterns of the top genes contributing to Neuron 46 activation in the epithelial context (top) and ENS context (bottom).

1057

Supplemental Figure 8. Zoom-in UMAPs of major cell types in the mammalian intestinal developmental atlas. Zoom-in UMAPs for each major cell type computed from CONCORD latent space, other integration methods, and unintegrated data, colored by batch (top) and cell cycle phase (bottom).

Supplementary Tables

Supplemental Table 1. Benchmarking data integration methods across
diverse structures with varying degrees of overlap. For each structure type
(cluster, trajectory, loop, and tree), we simulated varying degrees of overlap (full
overlap, partial overlap, connected without overlap, and gap between batches).
The table displays the score of each method using topological, geometric, and
scIB metrics