Revealing a coherent cell state landscape across single cell datasets with CONCORD

Qin Zhu[1*], Zuzhi Jiang[1,2], Binyamin Zuckerman[3], Leor Weinberger[3], Matt Thomson[4], Zev Gartner[1,5,6*]

[1] Department of Pharmaceutical Chemistry, University of California San Francisco; San Francisco, CA 94158, USA

[2] Tetrad Graduate Program, University of California San Francisco; San Francisco, CA 94158, USA.

[3] Department of Cell Biology, University of Miami; Miami, FL, 33136, USA.

[4] Division of Biology and Biological Engineering, California Institute of Technology; Pasadena, CA 91125, USA

[5] Chan Zuckerberg Biohub; San Francisco, CA 94158, USA

[6] Center for Cellular Construction, University of California San Francisco; San Francisco, CA 94158, USA

*Correspondence to Q. Zhu at qin.zhu@ucsf.edu and Z. J. Gartner at zev.gartner@ucsf.edu

Author information

Qin Zhu, qin.zhu@ucsf.edu

Zuzhi Jiang, zuzhi.Jiang@ucsf.edu

Binyamin Zuckerman, bzuckerman@med.miami.edu

Leor Weinberger, leor.weinberger@miami.edu

Matt Thomson, mthomson@caltech.edu

Zev J. Gartner, zev.gartner@ucsf.edu

Abstract

Revealing the underlying cell-state landscape from single-cell data requires overcoming the critical obstacles of batch integration, denoising, and dimensionality reduction. Here, we present CONCORD, a unified framework that simultaneously addresses these challenges within a single self-supervised model. At its core, CONCORD implements a unified probabilistic sampling strategy that corrects batch effects via dataset-aware sampling and enhances biological resolution through hard-negative sampling. Remarkably, using only a minimalist neural network with a single hidden layer and contrastive learning, CONCORD surpasses state-of-the-art performance without relying on deep architectures, auxiliary losses, or external supervision. It seamlessly integrates data across batches, technologies, and even species to generate high-resolution cell atlases. The resulting latent representations are denoised and biologically meaningful—capturing gene co-expression programs, revealing detailed lineage trajectories, and preserving both local geometric relationships and global topological structures. We demonstrate CONCORD's broad applicability across diverse datasets, establishing it as a general-purpose framework for learning unified, high-fidelity representations of cellular identity and dynamics.

Introduction

Cells express thousands of genes to perform specialized functions and maintain homeostasis. Gene expression is highly correlated, orchestrated by intricate gene regulatory networks and cell-cell interactions that constrain cells to a structured, low-dimensional "state landscape" within the high-dimensional gene expression space[1,2]. Advances in single-cell technologies, particularly single-cell RNA sequencing (scRNA-seq), enable empirical mapping of this landscape. Emerging evidence suggests that such landscapes may contain diverse features—including discrete clusters, continuous trajectories, branching trees, and cyclic transitions—reflecting the underlying organization of cellular states[3,4]. However, the presence and arrangement of these features are typically unknown a priori, underscoring the need for computational methods that can robustly capture their topology and geometry to illuminate the principles of development, homeostasis, and disease progression.

Dimensionality reduction, a form of representation learning, is commonly employed to uncover the structure of the cell state landscape. By projecting high-dimensional data into a lower-dimensional space, key structural patterns become more tractable to visualize and analyze. However, conventional methods—such as principal component analysis (PCA), non-negative matrix factorization (NMF)[5], and factor analysis[6]—often overemphasize broad cell type distinctions at the expense of subtle states, and can confound processes like differentiation with cell cycle progression. These challenges are exacerbated by batch effects— poorly understood sources of technical variation that obscure or skew genuine biological signals. Although an array of batch-correction tools—such as Harmony[7], Scanorama[8], Seurat[9], scVI[10], LIGER[11] and MNN[12] —have been developed, they frequently make strong assumptions about the structure of technical variation, leading to distortions from over- or under-correcting batch effects[13]. Furthermore, many face scalability issues when applied to massive atlas-level datasets.

Among emerging representation learning approaches, contrastive learning has
recently shown promise for single-cell analysis[14-20]. Initially developed for
domains such as image and natural language processing[21-23], these methods
learn informative cell representations by comparing similar ("positive") cells
against dissimilar ("negative") ones within mini-batches—small subsets of cells
iteratively sampled during training. However, current contrastive methods face
fundamental limitations: supervised approaches require extensive manual
annotation and struggle to generalize to novel states or continuous
trajectories[19,20], whereas unsupervised methods form mini-batches through
uniform sampling, emphasizing coarse cell-type differences while overlooking
subtle biological variation[14-17]. When applied across datasets, contrasting cells
randomly sampled from different datasets can amplify dataset-specific artifacts
rather than isolating true biological signals. While strategies involving generative
adversarial networks (GANs)[17,24,25], unsupervised domain adaptation via
backpropagation[26], and conditional variational autoencoders (CVAEs)[27] attempt
to mitigate batch effects, their objective of minimizing dataset-specific differences
inherently conflicts with contrastive learning's goal of maximizing differences
between dissimilar cells, frequently leading to incomplete batch-effect correction
and potentially introducing distortions to the latent space. This dilemma raises a
critical question: can contrastive learning fully capture cellular diversity while
minimizing batch effects?

Here, we address this open question by transforming a core limitation of
contrastive learning—its sensitivity to mini-batch composition—into a strength.
Our central insight is that mini-batch composition fundamentally determines the
outcome of contrastive learning. We introduce CONCORD (COntrastive learNing
for Cross-dOmain Reconciliation and Discovery), a framework that redefines the
contrastive learning process through a probabilistic mini-batch sampling strategy
combining dataset-aware sampling and hard-negative sampling. By strategically

composing each mini-batch primarily with cells from the same dataset—thereby preventing the model from learning technical differences among batches while focusing on biological differences among cells—CONCORD simultaneously enhances embedding resolution and mitigates batch-specific artifacts. In contrast to prior methods that rely on complex architectures or auxiliary losses for batch correction, CONCORD achieves dimensionality reduction, denoising, and data integration solely through principled sampling. We demonstrate its effectiveness using a minimalist, single-hidden-layer neural network across simulated and real datasets spanning a range of biological and technical complexity. CONCORD consistently outperforms state-of-the-art methods, producing high-resolution, denoised encodings that robustly capture diverse structures—including clusters, loops, trajectories and trees—reflecting bona fide biological processes even when the data originate from multiple technologies, time points, or species. This versatile framework scales from small to large datasets, generalizes to modalities beyond scRNA-seq, and establishes a rigorous foundation for next-generation single-cell machine learning models to drive diverse downstream biological discoveries.

Results

The CONCORD framework

Analyses of single-cell sequencing data suggest that gene expression is not randomly sampled; rather, the mechanism of gene regulation imposes strong constraints, producing dynamically changing gene co-expression patterns reflected as intricate structures in the low dimensional embedding of cells[1-3,28]. For example, at homeostasis, cells typically form discrete clusters corresponding to stable types or states, with adjacent clusters representing closely related states (Figure 1A, left). In developmental or pathological contexts—such as early embryogenesis, tissue repair, or tumorigenesis—cells often follow branching trajectories from progenitors to terminal fates, with semi-stable intermediate states forming denser clusters (Figure 1A, middle). Cyclic gene expression

programs, such as those regulating the cell cycle, give rise to loop-like

structures[3,4] (Figure 1A, right). Despite these rich patterns, conventional

dimensionality reduction methods like PCA or NMF capture only partial

representations of the cell state landscape, either oversimplifying complex

structures or disproportionately emphasizing certain features while obscuring

others.

We hypothesized that a representation-learning approach capable of encoding

cells based on gene co-expression programs would provide a more

comprehensive view of the cell state landscape. Recent evidence suggests that

self-supervised contrastive learning recovers sparse, structured gene co-

expression signals from high-dimensional data[29], significantly improving

clustering and cell-type classification performance[15-17] (see Methods). Like many

modern machine learning methods, contrastive learning relies on mini-batches—

small subsets of data sampled iteratively during stochastic gradient descent—as

the basic unit of training. However, contrastive learning is uniquely sensitive to

mini-batch composition: each cell is contrasted against every other cell within the

same mini-batch, making the mini-batch the universe over which learning is

defined. By differentiating each cell from others in the mini-batch, the model

learns features that distinguish distinct cellular states. Simultaneously, aligning

augmented versions of the same cell (typically generated through random

masking) encourages the model to capture robust gene co-expression patterns,

rather than relying on the expression of individual genes[29]. As a result, the

learned representations are intrinsically more robust to technical noise and

dropout—pervasive artifacts in single-cell datasets[30].

This reliance on within-mini-batch comparisons makes the sampling strategy—

which dictates mini-batch composition—a critical determinant of the learned

representation[31]. Existing methods typically adopt uniform sampling across

single-cell datasets (Fig. 1B), leading to two key limitations. First, uniform

sampling emphasizes broad differences (e.g., major cell types) while

underrepresenting rare subpopulations or subtle distinctions, resulting in poor

resolution of fine-scale cellular states (Figure 1C). Second, mixing cells from

different datasets within the same mini-batch can amplify technical dataset-

specific differences, also known as "batch effects," inadvertently encoding these

batch effects rather than isolating biologically meaningful variation.

To address the first issue, we adopt hard-negative sampling[32], in which each

mini-batch is enriched with closely related cells (Fig. 1C), encouraging the model

to extract features that distinguish these "hard negatives". We implemented two

variants. First, inspired by previous work[31], we developed a k-nearest neighbor

(kNN)-based sampler that probabilistically draws cells from both their local

neighborhoods and the global distribution. Local sampling—guided by a coarse

graph approximation of the cellular state landscape—compels the model to

contrast each cell with its neighbors, enabling detection of subtle differences

between closely related states. Simultaneously, global sampling preserves a

broad perspective of major cell types, ensuring robust encoding of large-scale

distinctions. By iteratively presenting the model with local neighborhoods (e.g., T

cells in one mini-batch, epithelial cells in another) alongside the global

distribution, the model allocates capacity to represent both large-scale

distinctions and nuanced local details, leading to improved resolution in the

learned latent space (Figure 1C). As a second variant (referred to as *hcl* mode,

following the original authors), we implement the approach by Robinson et al.[32],

which uses Monte-Carlo importance sampling to approximate the expected loss

of hard-negative sampling without explicit neighborhood-based sampling (see

Methods).

When applied to a single dataset, contrastive learning effectively captures

biological variation in the latent space (Figure 1D). However, with uniform

sampling across multiple datasets, both biological and dataset-specific variations

are encoded, yielding latent spaces that separate by dataset as well as cell type

(Figure 1E). To address this, we introduce a dataset-aware sampler that restricts

mini-batches to a single dataset, ensuring contrasts reflect only biological

differences—as in the single-dataset setting (Figure 1F). Dataset-specific biases

are further diminished through random mini-batch shuffling: if such signals are

encoded in one batch, they are disrupted and overwritten by subsequent mini-

batches from other datasets. Consequently, only biologically meaningful signals,

such as gene co-expression patterns, persist throughout training, producing

latent spaces that reflect biological variation with minimal batch effects (Figure

1F). In cases where datasets have minimal or no overlap, a leaky dataset-aware

sampler enables soft alignment without imposing artificial harmonization,

supporting flexible integration that respects dataset-specific signals

(Supplemental Figure 1A). Notably, this approach does not perform any explicit

modeling of batch effects; instead, it selectively captures and encodes biological

programs shared across datasets. Unlike prior batch-correction strategies that

struggle in contrastive settings due to competing objectives, CONCORD

integrates batch correction directly into the contrastive learning process via its

sampling design, producing latent representations inherently robust to batch

effects.

Both the hard-negative and dataset-aware samplers follow a unified principle:

probabilistically structuring mini-batches to balance global biological diversity with

local and dataset-specific variation. We integrate both samplers into a joint

sampling framework, where the likelihood of selecting a cell satisfies both

sampling schemes (Supplemental Figure 1A, B, also see Methods). This

generalized sampling strategy fundamentally reconfigures contrastive learning,

enabling high-resolution representation learning and robust dataset integration

within a single contrastive objective, and forms the core of the CONCORD

framework (Supplemental Figure 1C). With this simple innovation, CONCORD

outperforms state-of-the-art methods using only a minimalist encoder with a

single hidden layer, demonstrating that sampling design alone can transform

contrastive learning performance on single cell data—even without deep or

complex architectures. This simplicity reduces training data requirements,

enhances robustness, and increases interpretability of the learned latent space.

CONCORD learns denoised latent representations that preserve underlying

structures

Recovering biologically meaningful insights from single-cell data requires

preserving the underlying geometric and topological structure of the gene

expression space. To evaluate whether CONCORD meets this criterion, we

benchmarked its performance on a suite of simulated datasets. As existing

simulators often fail to generate complex biological structures like branching or

loops, we developed a custom workflow to create realistic structures with flexible

control over noise and batch effects (Figure 2A).

To assess the quality of learned representations, we established a

comprehensive evaluation pipeline. While standard benchmarks like the scIB

framework[33] effectively measure label preservation and batch mixing, they are

often insufficient for evaluating the preservation of complex biological

structures[34,35]. We therefore supplemented them with probing classifiers[36,37]—a

standard approach for evaluating representation learning—to assess the

conservation of biological labels in the latent space. Additionally, to quantify

structure fidelity, we incorporated geometric metrics like trustworthiness and

global distance correlation, as well as topological data analysis (TDA) based on

persistent homology and Betti numbers (Figure 2B). These metrics evaluate

embedding at complementary scales: trustworthiness quantifies local

neighborhood preservation, while persistent homology captures global

topological features—such as clusters (Betti-0), loops (Betti-1), and voids (Betti-

2). These features are visualized in persistence diagrams and Betti curves,

where stable structures appear as long-lived features in the persistence diagram

and extended plateaus in the Betti curve, whereas transient, noise-induced

features vanish quickly.

We evaluated both CONCORD variants on a simple, single-batch simulation

consisting of three well-separated clusters corrupted by cluster-specific Gaussian

noise (Figure 2C, Supplemental Figure 2A). Compared to a broad set of

dimensionality reduction methods—including diffusion map[38], NMF[39], Factor

Analysis[40], FastICA[41], Latent Dirichlet Allocation (LDA)[42], ZIFA[43], scVI[10], and

PHATE[44]—CONCORD cleanly separated clusters, as reflected in both the latent

space and pairwise distance matrices. In contrast, many methods failed to fully

resolve the clusters or introduced spurious structures, such as trajectory-like

artifacts (Figure 2C). Persistent homology confirmed these observations:

CONCORD's Betti-0 plateau accurately reflected the expected three-cluster

topology and closely matched the noise-free reference, highlighting its strength in

both denoising and structure preservation.

On a more complex simulation with three loops and multiple branching points

(Figure 2D, Supplemental Fig. 2B), CONCORD was the only method that

accurately recovered the full topology. Other methods either distorted the

structure or failed to detect the correct number of loops in Betti analysis, likely

due to excessive noise retention. Although PHATE produced a visually similar

embedding, its Betti curve identified only a single persistent loop, indicating that

critical topological features were obscured in its latent space.

Quantitative evaluation of geometric and topological metrics confirmed that

CONCORD consistently outperformed competing methods (Figure 2E, 2F).

Notably, CONCORD maintained high trustworthiness across a wide range of

neighborhood sizes, underscoring its ability to preserve local geometry at

multiple scales (Supplemental Figure 2C, 2D). In contrast, other methods exhibit

considerable declines in trustworthiness, indicating a loss of fine-scale geometric

relationships.

To assess the impact of hard-negative sampling, we simulated a hierarchical

branching tree (Figure 2G, Supplemental Figure 2E-G). Without hard negative

sampling, sub-branches were unresolved. Moderate enrichment of hard

negatives substantially improved resolution for both CONCORD variants, with the

kNN mode being more susceptible to excessive local focus, which obscured

global distinctions (Supplemental Figure 2F, G).

CONCORD learns a coherent, batch-effect-mitigated latent representation

Batch effects often appear as dataset-specific global signals that can obscure

biological variation. In CONCORD, these signals rapidly diminish during training

when mini-batches are restricted to single datasets (Figure 1E, Figure 3A).

Unlike conventional batch-correction methods that rely on explicit alignment

models, CONCORD makes minimal assumptions about the source or form of

batch effects and instead prioritizes learning coherent, biologically meaningful

gene covariation patterns. This leads to more accurate preservation of biological

structure while mitigating technical artifacts.

We first evaluated CONCORD on a simulated five-cluster dataset with varying

noise, batch effects, and batch size imbalance (Figure 3A, Supplemental Figure

3A). Across these conditions, CONCORD was the only method to robustly

recover all five clusters. This success is attributable to its dataset-aware sampler,

as using a conventional uniform sampler (i.e., the naïve contrastive approach)

resulted in pronounced batch effects. In more challenging scenarios with more

batches and greater imbalance, CONCORD and Harmony were the only

methods that consistently separated the underlying clusters (Supplemental Fig.

3B).

Single-cell studies often involve continuous state transitions sampled across

different conditions, where cell states may only partially overlap. Methods that

make explicit assumptions about the data structure—such as requiring matched

clusters—often fail in these scenarios and produce distorted embeddings. We

systematically tested this by simulating batch effects on trajectories, loops, and

trees with varying degrees of state overlap (Figure 3B-D, Supplemental Figure

3B-D). Many competing methods exhibited poor alignment and introduced

artificial structures. In contrast, both CONCORD variants consistently recovered

the correct topology with reduced noise, even when the overlap between batches

was minimal.

We further tested performance on a trajectory with 16 distinct batch effects

(Figure 3E). While scVI and CONCORD both aligned the batches, scVI showed

incomplete alignment at fine resolution. In contrast, CONCORD—particularly the

kNN variant—achieved superior alignment and noise reduction. Quantitative

metrics confirmed these observations: CONCORD preserved local geometry,

evidenced by high trustworthiness (Figure 3E,F), while exhibiting lower global

distance correlation—a common trade-off in manifold learning[45,46]. Robustness

was further demonstrated in a stress test where models were trained on a few

randomly selected batches and used to predict the remaining ones (Figure 3G).

CONCORD maintained strong alignment, whereas scVI's performance degraded

markedly as the number of training batches decreased. This suggests

CONCORD's robustness stems from learning gene co-expression programs

rather than explicitly modeling and correcting batch effects.

Across all simulations, CONCORD achieved high biological label conservation

(Figure 3G, Supplemental Table 1), with slightly lower batch-correction scores

because it does not explicitly merge batches. By contrast, although scVI

achieved high batch-mixing scores, it often produced over-mixed embeddings

that obscured underlying structure (Supplemental Figure 3). The aggregate

geometric score for CONCORD was reduced by its lower global distance

correlation despite consistently strong trustworthiness; however, for data with

manifold structures—such as single cell data—global distances are often not

reflective of true distance relationships between cell states. Therefore, preserving

local neighborhood fidelity is typically prioritized in single cell analysis[47].

Nevertheless, CONCORD consistently ranks among the top methods for

topological preservation, biological label conservation, and overall performance.

These results demonstrate that CONCORD provides a reliable and generalizable

framework for dimensionality reduction and batch correction, even when the data

structure is unknown or batch overlap is limited.

CONCORD aligns whole-organism developmental atlases and resolves

high-resolution lineage trajectories

To assess whether CONCORD captures biologically meaningful structures, we

benchmarked it against popular integration methods on *C. elegans*

embryogenesis[48]—a well-characterized system with a nearly invariant lineage

tree[49] that is also conserved in the related species *C. briggsae*[50]. Packer et al.

initially generated a lineage-resolved atlas of *C. elegans*[48], which was recently

expanded by Large et al. to include over 200,000 *C. elegans* cells and 190,000

C. briggsae cells[50]. With expert-curated annotations generated through iterative,

labor-intensive zoom-in analyses and validated by fluorescent imaging, these

datasets provide an ideal benchmark for evaluating whether integration methods

can accurately reconstruct and align developmental trajectories across species.

We first tested CONCORD on the original *C. elegans* atlas (>90,000 cells). The

resulting embedding revealed disconnected trajectories among early-stage cells,

which we hypothesized reflected missing states. These gaps persisted even after

including *C. elegans* cells from the expanded Large et al. dataset. We therefore

collected a new *C. elegans* dataset enriched for early embryos; adding this

dataset resolved the gaps and yielded a continuous trajectory from zygote to

terminal fates (Supplemental Fig. 4A). Using the extensive cell-type and lineage

annotations, we benchmarked CONCORD against other methods for batch

correction and label conservation, and assessed its sensitivity to key

hyperparameters (Supplemental Figure 4B-E). CONCORD significantly

outperformed existing methods, with stable performance across the

recommended hyperparameter range. Notably, the effect of hard-negative

sampling mirrored trends observed in simulations: moderate local enrichment

improved resolution, whereas excessive local sampling disrupted global structure

(Supplemental Figure 4F).

When applied to over 410,000 cells from the combined cross-species dataset

and our new early-embryo collection, CONCORD generated a unified

developmental atlas that closely matched the expert annotations, achieving

cross-species alignment and resolving lineages at ultra-high resolution (Figure

4A,B). Both the *hcl* and *kNN* modes yielded similar, high-quality embeddings

(Figure 4A, Supplemental Figure 5A). Because scIB[33] could not scale to this

dataset, we quantified integration performance using probing classifiers to

assess batch mixing, cell type, and lineage label preservation (Figure 4C).

CONCORD excelled on these metrics, whereas other methods either failed to

fully align the species or lost resolution, consistent with visual inspection of the

UMAP embeddings. As the complexity of the learned structure exceeded the

capacity of 2D UMAP, we encourage readers to explore the interactive 3D

visualizations

(https://qinzhu.github.io/Concord_documentation/galleries/cbce_show/#__tabbed

_1_1).

Projecting the lineage tree onto CONCORD's embedding revealed strong

concordance with established lineage and fate relationships (Supplemental

Figure 5B). For example, the ASE, ASJ, and AUA neurons—derived from AB

progenitors—formed branching trajectories that mirrored their true lineage
structure (Figure 4D). In contrast, other methods introduced discontinuities, failed
to resolve key bifurcations, or generated artificial structures. Strikingly,
CONCORD's latent space resolved ASE-left (ASEL) and ASE-right (ASER)
neurons, characterized by differential expression of GCY receptors (Figure 4E).
Although morphologically symmetric, these neurons exhibit functional asymmetry
in salt-sensing responses[51,52].

To systematically assess preservation of lineage structure in the latent space, we
evaluated lineage purity and average lineage distance within randomly selected
kNN neighborhoods, with k ranging from 30 to 300 (Figure 4F). We reasoned that
if a latent representation reflects lineage structure, each cell's neighbors should
belong predominantly to the same lineage or an immediate relative—captured by
high purity and low average lineage distance. CONCORD maintained high
lineage purity even at large values of k. Furthermore, neighboring cells from
different lineages were often close relatives, as reflected by a low average
lineage distance. In contrast, other methods produced embeddings with
significantly more mixed-lineage neighborhoods. Collectively, these findings
indicate that the CONCORD latent space preserves genuine lineage structures,
enabling refinement of existing annotations (Supplemental Figure 5C) and
highlighting its broader utility for inferring bona fide differentiation trajectories in
developmental studies[53,54].

In addition to fate bifurcation in neuronal development, fate convergence from
different lineages is a common pattern in *C. elegans* organogenesis. In the
context of muscle formation, CONCORD accurately resolved how the MS, C, and
D lineages converge into well-resolved sub-branches of body wall muscle, as
well as rare convergence events such as the integration of ABplp/ABprp- and
MS-derived cells into intestinal muscle (mu_int) (Figure 4G). Pharyngeal
development—featuring complex branching and convergence of AB- and MS-

derived cells—was likewise resolved in detail by CONCORD (e.g., pm3–5

deriving from both AB and MS lineages, and pm1–2, 6–8 specific to AB/MS

lineages), whereas other methods recovered fewer fine-grained details (Figure

4H). Crucially, all analyses were performed directly in CONCORD's global latent

space, without subset-specific variable gene selection or re-alignment—steps

that are often necessary for other methods.

Finally, to test model generalizability, we trained CONCORD and scVI on a

subset of *C. elegans* batches and projected them onto unseen *C. elegans* and all

C. briggsae data (Figure 4I). CONCORD successfully integrated the held-out

batches, aligned the two species, and resolved the majority of cell types. In

contrast, scVI produced a markedly lower-quality projection, with poor cross-

species alignment and diminished cell type resolution.

CONCORD captures cell cycle and differentiation trajectories in mammalian

intestinal development

Unlike *C. elegans*, where early divisions are largely driven by maternal

transcripts[55], mammalian development involves extensive proliferation coupled

with ongoing differentiation. To assess whether CONCORD can resolve these

intertwined processes, we applied it to a single-cell atlas of embryonic mouse

intestinal development[56], which spans multiple developmental stages, batches,

spatial segments, and enriched cell populations—posing a challenging

integration task due to incomplete batch coverage.

CONCORD effectively integrated the data and resolved fine-grained

substructures across diverse cell types (Figure 5A, Supplemental Figure 6A).

Both *hcl* and *kNN* modes revealed loop-like patterns within many cell types—as

evidenced by persistent homology—and often missed by other methods (Figure

5B-D, Supplemental Figure 6B). The majority of these loops correspond to cell

cycle progression, supported by progressive expression of cell-cycle gene

programs along the loops (Supplemental Figure 6B). For example, in intestinal

epithelial cells, CONCORD not only resolved rare subtypes such as

enteroendocrine cells (EECs), but also revealed two parallel trajectories—each

encompassing both a cell-cycle loop and a differentiation path—corresponding to

stem cell proliferation and differentiation in spatially distinct regions (Figure 5B).

These structures were not captured by other methods and were supported by

adult zonation markers such as *Bex4* and *Onecut2*[57], suggesting that CONCORD

can detect epithelial zonation as early as embryonic day 13.5.

In the enteric nervous system (ENS), CONCORD captured the cell cycle of

Sox10[+] progenitor cells and identified two distinct branches of neuronal

development marked by *Etv1* and *Bnc2*, matching previous observations[58]

(Figure 5C). These branches appear to converge through shared expression of

neuronal maturation genes broadly active at late stages of both branches

(Supplemental Figure 6C).

In mesenchymal cells—which comprise a major fraction of this dataset—

CONCORD uncovered extensive heterogeneity within the *Pdgfra*[−] and smooth

muscle populations (Figure 5D). These included four consecutive cell-cycle loops

marked by expression of *Ebf1*, *Slit2*, *Kit*, and *Acta2*, with gradual transitions

between the loops. Notably, *Ebf1* and *Slit2* have been linked to mesenchymal

multipotency[59,60], while *Kit* marks interstitial cells of Cajal (ICC) and their

progenitors[61,62]. Unlike traditional approaches where cell cycle often confounds

cell type annotation, CONCORD preserves both proliferation and differentiation

structure, enabling the identification of previously uncharacterized

subpopulations. The complexity of these structures necessitates 3D visualization,

and we encourage readers to explore the interactive embeddings:

(https://qinzhu.github.io/Concord_documentation/galleries/huycke_show/).

Unlike Seurat and scVI, which left many latent dimensions underutilized,

CONCORD produced a dense and interpretable latent space that reflects rich

biological structure and makes full use of its representational capacity (Figure

5E). Each latent dimension typically encapsulates multiple gene co-expression

programs, which can be interpreted at either single-cell or cell-state resolution

using gradient-based attribution methods[63] in a context-dependent manner

(Figure 5F). For instance, latent neuron 46 (Z_{46}) is activated in both epithelial

cells and the ENS cells, but attribution analysis reveals it is driven by two distinct

sets of highly co-expressed genes depending on the cellular context (Figure 5F,

Supplemental Figure 6C). In epithelial cells, Z_{46} activation is linked to goblet cell–

specific genes enriched in glycosylation pathways, whereas in ENS cells, it

reflects neuronal maturation genes expressed in late-stage neurons. Notably,

neither gene set shows strong expression outside its respective context,

demonstrating that the CONCORD latent space captures biologically meaningful,

context-specific gene co-expression programs.

CONCORD generalizes across modalities and scales

CONCORD's domain-agnostic design allows it to be applied to diverse data

modalities beyond scRNA-seq. We tested this on a challenging single-cell ATAC-

seq benchmark dataset comprising PBMCs from two donors profiled across eight

different technologies[64](Figure 6A). On both quantitative metrics and visual

inspection of the embeddings, CONCORD yielded significantly better batch

correction and biological label conservation than other methods, including the

original study's Harmony-based analysis (Figure 6B,C, Supplemental Figure

7A,B).

The CONCORD embedding revealed fine-grained immune subtypes not present

in the original annotations. To validate these, we refined the cell type labels using

paired scRNA-seq and scMultiome data and projected them back onto the

scATAC-seq embedding via shared scMultiome cells. Strikingly, refined clusters

in scRNA-seq (e.g., naïve and memory B cells) corresponded precisely to

clusters uncovered by CONCORD in scATAC-seq. This validation also uncovered

a mis-annotation in the original study, where CD8$^+$ naïve T cells were incorrectly

labeled as CD4$^+$ T cells. Therefore, CONCORD significantly improved analysis

on existing scATAC datasets. Notably, CONCORD achieved this high-resolution

result using only simple log-normalization, forgoing the complex, modality-

specific data transformations often required for scATAC-seq analysis.

When applied to a breast cancer tumor–microenvironment sample profiled with

Xenium, 3′ and 5′ scRNA-seq, and Fixed RNA Profiling (FLEX) technologies[65]—

sharing only 307 genes—CONCORD in *hcl* mode achieved markedly better

integration and cell-type resolution than other approaches (Figure 6D,

Supplemental Figure 7C). A key finding of the original study was that two DCIS

(ductal carcinoma in situ) subtypes exhibit distinct adjacent microenvironments:

DCIS-1 is bordered by both KRT15$^+$ and ACTA2$^+$ myoepithelial cells, whereas

DCIS-2 is encircled exclusively by ACTA2$^+$ myoepithelial cells (Figure 6E).

Notably, without access to spatial coordinates, CONCORD recapitulated these

adjacency patterns by revealing differential connectivity between DCIS and

myoepithelial clusters—consistent with signal bleed or segmentation-related

transcript carryover commonly observed in spatial single-cell assays[66].

Finally, we benchmarked CONCORD on six additional scRNA-seq datasets

curated by the Open Problems in single cell analysis initiative[67], including Tabula

Sapiens (>1 million cells)[68]. CONCORD consistently achieved top performance

across these datasets (Figure 6F, Supplemental Table 2) while running

substantially faster and with modest RAM/VRAM requirements (Figure 6G,

Supplemental Figure 7D). By contrast, several methods—including LIGER,

Scanorama, and Seurat—failed to run at atlas scale owing to heavy resource

demands or violations of method assumptions. CONCORD-derived 2D UMAP

embeddings for these datasets are provided in Supplemental Figure 8, and

additional examples, tutorials, and resources are available on the CONCORD

project website (https://qinzhu.github.io/Concord_documentation/).

Discussion

Mini-batch gradient descent underpins modern machine learning—including large

language models, foundation models, and diffusion models. Growing evidence

suggests that the composition of these mini-batches can influence model

performance[31,69]. In contrastive learning, where each sample is contrasted

against others within a mini-batch, this effect is amplified—especially in biological

datasets spanning multiple batches, where naive sampling can exacerbate batch

effects and distort learned representations. Yet in contrastive learning for single

cell data, uniform random sampling remains the norm, limiting the method's

ability to capture biologically meaningful structure.

Our central insight is that, in contrastive learning, mini-batch composition not only

influences, but fundamentally shapes the outcome. By rethinking how mini-

batches are assembled, we turn contrastive learning's sensitivity to mini-batch

composition into a strength—transforming a conventional self-supervised

framework into a powerful, generalizable approach for denoising, dimensionality

reduction, and batch integration.

At the core of CONCORD is a unified probabilistic sampler that integrates hard-

negative sampling with dataset-aware sampling. Hard-negative sampling

markedly enhances the representational power of the contrastive model,

enabling it to capture intricate gene co-expression programs that separate

closely related cell states. The dataset-aware sampler enriches each mini-batch

with cells from a single dataset, allowing the model to learn biological variation

without entangling batch effects. Unlike traditional methods that rely on

overlapping states or explicit batch-distortion models, CONCORD mitigates batch

effects solely through principled sampling and training. As a result, it aligns cells

based on shared co-varying features—a hallmark of single cell data[6,70,71]—

making it especially robust when datasets have minimal overlap or unusual

geometric and topological structures. The dataset-aware strategy integrates

seamlessly with either the *hcl* or *kNN* hard-negative sampling variants, with both

configurations yielding robust batch correction and faithful structure preservation

across diverse benchmarks.

Importantly, CONCORD achieves state-of-the-art performance using a

minimalistic encoder architecture—just a single hidden layer—demonstrating that

substantial gains can be achieved through rational sampling and training alone,

without relying on deep architectures, complex objectives, or supervision. Across

both simulated and real datasets with different scale and modalities, CONCORD

consistently learns latent spaces that are denoised, interpretable, and

topologically faithful. In whole-organism embryogenesis atlases, it accurately

reconstructs fate bifurcations and lineage convergences, enabling detailed

tracing from progenitor cells to terminal states. In contrast, existing methods

often misalign these datasets, lose resolution, or fragment continuous

trajectories. In mammalian intestinal development, CONCORD captures complex

hierarchies, spatial zonation, and cell cycle loops—all within a single integrated

analysis. Unlike traditional workflows that regress out cell cycle effects,

CONCORD preserves and resolves both proliferative and differentiation

programs, facilitating investigations into their interplay. Its interpretable latent

space further enables gradient-based attribution analyses, allowing gene-level

mechanistic insights at single-cell or cell-type resolution.

CONCORD features a speed-optimized, memory-efficient design. Key

components—including a vectorized sampling algorithm, native sparse matrix

support, and out-of-core data loading—enable it to readily analyze million-cell

atlases that may exceed available system memory. While the current

implementation emphasizes simplicity, the framework is also fully extensible to

more complex architectures—such as deeper neural networks or

transformers[72]—to support more intricate data modalities or biological contexts.

This minimalist design reduces the number of tunable parameters, though

several hyperparameters remain critical for optimal performance. Although we

provide default parameter settings and recommended parameter ranges based

on extensive benchmarking, users may need to tune key parameters for optimal

performance for untested scenarios and modalities.

Beyond the core contrastive encoder, CONCORD supports optional decoder and

classifier modules for gene-level batch correction, label transfer, and annotation-

guided learning. Preliminary results suggest these tasks benefit from the model's

robust latent space, though further validation is ongoing. Owing to its domain-

agnostic design and generalized sampling framework, CONCORD holds

potential beyond single-cell biology, offering a flexible and powerful approach for

representation learning across a wide range of domains.

Methods

Self-supervised contrastive learning and sparse coding

We implemented CONCORD in PyTorch, building on a self-supervised contrastive learning approach inspired by SimCLR[21] and SimCSE[22], but with a unique dataset- and neighborhood-aware sampler design. The core objective is the normalized temperature-scaled cross entropy (NT-Xent)[21,22,73], applied to cell representations generated via random masking, following unsupervised SimCSE[22].

Theoretically, contrastive learning with ReLU networks and random masking augmentation can provably recover underlying sparse features from data approximated as:

$$x = Mz + \varepsilon$$

where Mz represents the sparse signal with $\|z\|_0 = \tilde{O}(1)$, and ε denotes noise[29]. CONCORD adopts similar conditions: we use LeakyReLU activations and independent random masking augmentations to capture correlated gene co-expression patterns while suppressing noise.

This sparse coding approach generalizes beyond traditional methods like non-negative matrix factorization (NMF), principal component analysis (PCA), factor analysis, and variational autoencoders (VAEs). Unlike these:

- It does not enforce orthogonality on M (as in PCA),
- It does not require non-negativity constraints (as in NMF),
- It does not assume a probabilistic generative model (as in factor analysis and VAEs),
- It does not enforce Gaussian priors on the latent space (as in standard VAEs).

Instead, it assumes an intrinsic low-rank structure shaped by gene co-expression programs, supported by single-cell studies[6,70,71]. By relaxing constraints on orthogonality, non-negativity, and Gaussian priors, the contrastive learning framework is better positioned to capture diverse gene regulatory programs that

deviate from conventional assumptions. Furthermore, random masking enhances

robustness to scRNA-seq dropout and improves biological interpretability,

allowing the latent space to represent gene programs faithfully.

Model architecture

CONCORD emphasizes architectural flexibility and minimalism, using a single-

hidden-layer encoder for all presented benchmarking analyses to show gains

from sampling and training alone. However, the architecture is fully extensible:

users may substitute the encoder with more advanced models—such as deeper

neural networks or transformers—to accommodate different data modalities or

capture higher-order biological structures.

1. Data augmentation:

Input gene-expression values are normalized by total count and log-

transformed to ensure consistency. We apply two complementary

augmentation strategies within each mini-batch to enhance robustness

and encourage reliance on redundant gene programs:

• Feature-wise masking: Randomly sets the expression of a specific

675   gene to 0 across all cells in the mini-batch, simulating gene

676   dropout.

677   • Element-wise masking: Randomly sets the expression of a specific

678   gene to 0 for individual cells, mimicking localized noise or missing

679   data.

Both techniques compel the encoder to leverage correlated gene co-

expression patterns rather than depending on individual genes, improving

generalization and noise resilience.

2. Encoder:

The encoder maps masked gene expression vectors to low-dimensional

embeddings. By default, it is a fully connected network with one hidden

layer, though the number of layers or neurons can be customized. An

optional learnable feature-weighting module can precede it to weight

genes sparsely and interpretably.

3. Layer normalization and activation:

Each linear layer is followed by layer normalization and a user-

configurable activation function (default: Leaky ReLU). Layer

normalization operates across features within each sample, offering

robustness to batch-specific variation—making it preferable to batch

normalization[74], though the latter is also supported.

4. Optional decoder and classifier:

A decoder can be appended to the latent embeddings to reconstruct

batch-corrected gene expression profiles. It supports joint training with the

encoder or training with a frozen or partially frozen encoder. To prevent

reintroduction of batch-specific variation, a distinct, learnable dataset

embedding is appended during decoding, preserving the batch-effect-free

nature of the core latent space.

A classification head, implemented as a multi-layer perceptron with cross-

entropy loss, can be added to the encoder for tasks like cell-type

annotation or doublet detection. The classifier can be trained on a pre-

trained encoder or jointly with the encoder to enhance cell-type separation

in the latent space. While joint training boosts class discrimination, it may

impose a strong prior that disrupts trajectory continuity. To address

overfitting, we recommend using a train-validation split with early stopping

during classifier training.

Contrastive objective

We adopt the noise-contrastive estimation (NCE) framework with the normalized

temperature-scaled cross entropy (NT-Xent) loss[21,22,73]. Given a mini-batch of B

cells, we generate two augmented views per sample, yielding embeddings z_k

and z_{k^+} from the encoder. The standard NT-Xent loss encourages the model to

pull positive pairs (different views of the same sample) closer while pushing

negative pairs (views from different samples) apart. For a concatenated batch of

$2B$ embeddings $z = [z_k; z_{k^+}]$, the loss is computed as:

723
$$\mathcal{L} = \frac{1}{2B} \sum_{k=1}^{2B} - \log\left(\frac{\exp(s(z_k, z_{k^+})/T)}{\sum_{m=1, m \neq k}^{2B} \exp(s(z_k, z_m)/T)}\right),$$

where $s(z_k, z_{k^+}) = \frac{z_k^T z_{k^+}}{\|z_k\|\|z_{k^+}\|}$ is the cosine similarity, and T is a customizable

temperature hyperparameter that controls the trade-off between local separation

and global uniformity of the embeddings[75]. The denominator sums over all other

embeddings in the batch, approximating negatives sampled from the data

distribution P. The loss is efficiently implemented using matrix operations: the

logit matrix $L = zz^T/T$ is computed, diagonal entries are set to $-\infty$ to exclude

self-similarities, and cross-entropy is applied with positive indices corresponding

to z_{k^+} for each z_k.

Dataset and neighborhood-aware probabilistic sampler

At the heart of CONCORD is a probabilistic mini-batch sampler that determines

how cells are grouped and contrasted during training. Unlike conventional

contrastive learning frameworks that rely on uniform random sampling,

CONCORD introduces a unified, generalizable sampling strategy that

simultaneously (i) performs hard negative sampling in either *kNN* or *hcl* mode

and (ii) restricts each mini-batch primarily to a single dataset. This principled

design reshapes the outcome of contrastive learning, enabling the model to

produce a coherent, high-resolution, and batch-effect-mitigated representation of

the cell state landscape.

1. *kNN* mode

We begin by coarsely approximating the global data manifold using a k-

nearest neighbors (kNN) graph, where k is a user-defined parameter

746	(typically moderately large). The graph can be initialized from normalized
747	gene expression values, a PCA projection, or a CONCORD batch-
748	corrected embedding generated with the dataset-aware sampler. By
749	default, we run CONCORD with the dataset-aware sampler for 2 epochs,
750	followed by the remaining epochs with joint sampling. For scalability, we
751	leverage the *Faiss* library[76] for efficient neighbor retrieval in large datasets.
752	This kNN graph then guides neighborhood-aware sampling, modulated by
753	a user-defined neighborhood enrichment probability P_{kNN}. To construct
754	mini-batches that are both dataset- and neighborhood-enriched, we
755	partition each mini-batch into four subsets—in-dataset neighbors, in-
756	dataset global samples, out-of-dataset neighbors, and out-of-dataset
757	global samples (Figure 1F). A "core sample" is randomly selected from
758	one dataset to anchor both neighborhood and dataset-aware sampling.
759	The four subsets are then sampled based on P_d (the probability of
760	sampling from the same dataset) and P_{kNN} as follows:

- 761 In-dataset neighbors: $P_d \cdot P_{kNN} \cdot B$ cells from the same dataset and
- 762 within the core cell's kNN neighborhood.
- 763 In-dataset global samples: $P_d \cdot (1 - P_{kNN}) \cdot B$ uniformly sampled cells
- 764 from the same dataset, outside the neighborhood.
- 765 Out-of-dataset neighbors: $(1 - P_d) \cdot P_{kNN} \cdot B$ cells from other datasets
- 766 that fall within the core cell's kNN neighborhood.
- 767 Out-of-dataset global samples: $(1 - P_d) \cdot (1 - P_{kNN}) \cdot B$ uniformly
- 768 sampled cells from all other datasets.

2. *hcl* mode

771	Unlike *kNN* mode, which explicitly samples cells from within the kNN
772	neighborhood, *hcl* mode implements the hard negative sampling algorithm
773	from Robinson et al.[32], utilizing importance sampling to compute the
774	expected hard-negative loss directly within the contrastive objective
775	without altering the mini-batch sampling procedure. We briefly explain the
776	method here and refer readers to the original publication for details.

Given an anchor embedding z_k, to enrich negative samples z_m, we

propose sampling from the mixed hard negative distribution $q_\beta(z_m) \propto$

$\exp(\beta s(z_k, z_m)/T) \cdot P(z_m)$, where the similarity $s(z_k, z_m) = z_k^T z_m$ (with

embeddings ℓ_2-normalized), and $\beta > 0$ is a "concentration parameter".

The exponential term acts as a von Mises–Fisher kernel: larger β

concentrates mass on points whose embeddings already lie close to the

anchor (harder negatives), while $\beta = 0$ recovers the uniform sampler over

the data distribution P.

Since sampling directly from q_β is computationally inefficient, we apply

importance weights in the contrastive loss to approximate the expected

contribution under q_β. Specifically, the contrastive loss under *hcl* mode is:

788
$$\mathcal{L}_{hcl} = \frac{1}{2B} \sum_{k=1}^{2B} - \log \left(\frac{\exp(s(z_k, z_{k+})/T)}{\exp(s(z_k, z_{k+})/T) + (2B-2)\mathbb{E}_{z_m \sim q_\beta}[\exp(s(z_k, z_m)/T)]} \right).$$

Note that this omits an optional debiasing term (from Equation 4 in

Robinson et al.[32]), which subtracts potential contamination from false

positives (same-class negatives) using the class prior τ_+. We set $\tau_+ = 0$,

as single-cell data are highly heterogeneous, making it unlikely to sample

cells with identical molecular states within a mini-batch.

The expectation is computed using Monte-Carlo importance sampling:

795
$$\mathbb{E}_{z_m \sim q_\beta}[\exp(s(z_k, z_m)/T)] = \mathbb{E}_{z_m \sim P}[\exp((1+\beta)s(z_k, z_m)/T)/Z_\beta],$$

796　　　　where $Z_\beta = \mathbb{E}_{z_m \sim P}[\exp(\beta s(z_k, z_m)/T)$ is the partition function, empirically

797　　　　estimated as:

798
$$\hat{Z}_\beta = \frac{1}{2B-2} \sum_{m=1}^{2B-2} \exp(\beta s(z_k, z_m)/T),$$

799　　　　Thus,

800
$$\log(\hat{Z}_\beta) = \log \sum_{m=1}^{2B-2} \exp(\beta l_m) - \log(2B-2),$$

with $l_m = s(z_k, z_m)/T$ as the original negative logits. This leads to

reweighted negative logits $l'_m = (1+\beta)l_m - \log(\hat{Z}_\beta)$, which replace the

originals in the NT-Xent denominator.

To integrate the *hcl* hard-negative sampler with the dataset-aware

sampler, apply the *hcl* contrastive loss to mini-batches constructed under

the dataset-aware probability distribution (determined by P_d) instead of the

uniform data distribution P, enabling simultaneous batch correction by

focusing contrasts primarily within datasets. In practice, we find that the

hcl mode is more sensitive to the dataset-aware sampling probability (P_d),

performing optimally with strict intra-dataset sampling (P_d = 1.0). We

hypothesize this is due to *hcl*'s strong emphasis on close neighbors: when

such neighbors are drawn across batches, they may represent the same

biological state, leading the model to inadvertently penalize correct

alignments.

Both variants of CONCORD samplers are implemented using vectorized

operations in PyTorch and NumPy to optimize memory efficiency and minimize

computational overhead, ensuring scalability across large datasets and enabling

rapid training.

Model training

Mini-batches are constructed via the sampler, shuffled, and optimized with NT-

Xent using the Adam optimizer[77]. Interestingly, and in contrast to trends often

seen in computer vision, we found that CONCORD's performance did not

improve with very large batch sizes (relative to the total number of cells). Instead,

for the *C.elegans* dataset (>90,000 cells), performance peaked at moderate sizes

(e.g., 256-512) and then began to decline as the batch size exceeded 1,000

(Supplemental Fig. 4E). We hypothesize that this is because the benefit of hard-

negative sampling strategy is diluted in very large batches. For resolving the fine-

grained distinctions common in biological data, the model requires an enrichment

of "hard negative" contrasts. As batch size increases, the mini-batch distribution

approaches the global data distribution, reducing the effectiveness of this

targeted sampling. Therefore, for all benchmarking analyses, we adopted a

moderate default batch size of 256, which not only achieves optimal performance

across our diverse benchmarks but also makes CONCORD highly accessible.

This choice ensures that VRAM requirements are minimal (Supplemental Fig.

7D), allowing the method to be run efficiently on widely available, cost-effective

GPUs.

Besides the core contrastive objective, optional loss terms, including mean

squared error (MSE) for the decoder, cross-entropy loss for classification, and

L1/L2 regularization for feature-weighting modules, can be incorporated with

adjustable weights. A learning rate scheduler is employed to gradually reduce the

learning rate over time, promoting stable convergence.

Simulation pipeline

We developed a versatile simulation pipeline to generate synthetic single-cell

gene expression data with diverse underlying structures. Unlike conventional

simulators that predominantly produce discrete clusters, our pipeline

accommodates a broad range of topologies, including linear trajectories,

branching trees, loops, and intersecting paths frequently observed in real single-

cell datasets.

The pipeline proceeds in three sequential stages, as illustrated in Figure 2A.

1. Groundtruth data model:

In the first stage, the state simulator constructs a noise-free data matrix

$[N \times D]$ (where N is the number of cells and D is the number of genes)

according to a user-defined structure:

• Clusters: Cells form discrete groups characterized by unique gene

programs, optionally including shared or ubiquitously expressed genes.

• Trajectories: Cells exhibit gradual shifts in gene expression, emulating

cell differentiation processes.

• Loops and intersecting paths: Continuous trajectories that close into

loops or intersect, representing cyclic biological processes.

- 863   • Trees: Hierarchical, branching lineages representing progenitor-to-
- 864   terminal fate differentiation, configurable by branching factor and tree
- 865   depth.

2. Noise model:

Expression values are then sampled from selected distributions (e.g.,

Gaussian, Poisson, Log-normal, Negative Binomial), introducing realistic

variability and dropout patterns. Users can precisely control parameters

including mean baseline expression, dispersion (noise level), dropout

probability, and can enforce non-negativity or integer rounding of the

generated values, yielding a noisy data matrix $[\mathrm{N} \times \mathrm{D}]$.

3. Batch model:

In the final stage, an optional batch simulator introduces dataset-specific

technical variability to mimic batch effects. For each batch, a user-

specified effect type is applied to a subset of cells (determined by

customizable proportions), enabling simulation of various technical

artifacts. Supported effect types include:

• Variance inflation: Multiplies each entry by $1 + N(0, \sigma^2)$, where σ is the

dispersion parameter.

• Batch-specific distribution: Adds noise sampled from a specified

distribution (e.g., Normal, Poisson, Negative Binomial, Log-normal)

with configurable mean and dispersion.

• Uniform dropout: Randomly sets a fixed fraction of values to zero.

• Value-dependent dropout: Drops values with probability $1 -$

$\exp(-\lambda \cdot x^2)$, where λ is the level parameter and x is the expression

value.

• Down-sampling: Subsamples UMI counts to a specified ratio,

simulating reduced sequencing depth.

• Scaling factor: Multiplies the entire matrix by a scalar to shift overall

expression levels.

• Batch-specific expression: Adds distribution-based noise to a random

subset of genes.

•   Batch-specific features: Appends new genes unique to the batch, with

895   expression sampled from a specified distribution.

Multiple simulated batches are then concatenated into a single dataset,

with varying degrees of batch overlap to mimic real-world sampling

scenarios, producing the final input data matrix $[N \times D]$ with noise and

batch effects.

By combining diverse gene expression structures with realistic noise models and

customizable batch effects, this simulation pipeline can approximate a broad

spectrum of biological and technical scenarios. As such, it provides a powerful

testbed for benchmarking data-integration techniques, trajectory-inference

algorithms, and manifold-learning methods under controlled yet biologically

realistic conditions.

Benchmarking pipeline

To comprehensively evaluate the performance of CONCORD and other

dimensionality-reduction or data-integration methods, we designed a robust

benchmarking pipeline that integrates geometric, topological, biological label

conservation, and batch-correction metrics. This multifaceted assessment

framework consists of the following components:

1. Topological assessments:

To quantify the preservation of intrinsic topological features, we employed

persistent homology analysis implemented via Giotto-TDA[78]. Persistent

homology captures structural properties of the data across multiple scales,

using Vietoris-Rips complexes constructed over increasing radii to

generate persistence diagrams and Betti curves. Persistence diagrams

reveal the lifespan of topological features such as connected components

(Betti-0), loops (Betti-1), and voids (Betti-2). We derived Betti curves from

these diagrams, interpolating them onto a common filtration grid (number

of bins = 100) for consistency. For each homology dimension, we

computed the mode of the Betti curve (representing the most persistent

Betti number across scales) and compared it to known topological ground

truths using L1 distance across dimensions, yielding a Betti number

accuracy score of $1/(1 + \mathrm{L1})$. Additionally, we computed the stability of

Betti curves as $1/(1 + \mathrm{variance})$, where variance is the variance of the

Betti values across the filtration grid. The Betti curve stability score is

averaged across dimensions to quantify topological robustness (scores

range from 0 for highly variable curves to 1 for perfectly stable ones). The

final topology score is a weighted average: 0.8 × Betti number accuracy +

0.2 × Betti curve stability.

2. Geometric assessments:

We evaluated the preservation of geometric relationships by calculating

Pearson correlations between pairwise distances in the embeddings and

those in the corresponding noise-free reference data, providing a measure

of global geometric fidelity. For local neighborhood preservation, we

employed trustworthiness[79], a metric that assesses how faithfully high-

dimensional neighborhood structures are maintained in lower-dimensional

embeddings. Trustworthiness scores range from 0 (poor preservation) to 1

(perfect preservation), and we computed average trustworthiness scores

across neighborhood sizes (k-values) from 10 to 100 in increments of 10.

Additionally, we visualized trustworthiness as a function of k to reveal how

each method performs at different local scales.

3. Batch correction metrics

We adopt established metrics from the scIB-metrics package[33] to

systematically evaluate batch correction, including:

- Graph connectivity: Assesses whether cells of the same biological label form a connected component in the integrated k-nearest neighbor (kNN) graph, with scores ranging from 0 to 1 (1 indicating full connectivity).
- iLISI (integration Local Inverse Simpson's Index): Measures batch mixing by estimating the effective number of batches in local neighborhoods, rescaled to 0–1 (higher scores indicate better integration).
- KBET (k-nearest neighbor Batch Effect Test): Determines whether the batch label composition in a cell's k-nearest neighborhood is similar to the expected global composition, computing a rejection rate (higher rejection indicates poorer mixing); the rate is averaged across labels and subtracted from 1 to rescale to 0–1, with higher scores denoting better batch removal.
- PCR comparison (Principal Component Regression): Quantifies the variance contribution of batch effects via regression on principal components, comparing pre- and post-integration, rescaled to 0–1.
- Silhouette batch (Batch ASW): Computes the average silhouette width (ASW) using the absolute silhouette width on batch labels per cell, subtracted from 1 (so 1 indicates perfect mixing), averaged within each cell type and then across types; ranging from 0 (strong separation) to 1 (ideal integration).

4. Biological label conservation:
These metrics, also from scIB-metrics[33], evaluate the preservation of biological variance and cell-type separation:

- Isolated labels: Assesses handling of rare or batch-specific labels using F1 score and ASW, scaled to 0-1 (higher scores indicate better separation of isolated labels).

- Leiden ARI (Adjusted Rand Index): Measures overlap between true biological labels and clusters obtained via Leiden clustering on the integrated data, with scores from 0 (random) to 1 (perfect match).
- Leiden NMI (Normalized Mutual Information): Quantifies information shared between true labels and Leiden clusters, ranging from 0 (no overlap) to 1 (perfect correspondence).
- Silhouette label (Cell Type ASW): Evaluates cell-type separation using average silhouette width on labels, scaled to 0-1 (1 indicating dense, well-separated clusters).
- cLISI (cell-type Local Inverse Simpson's Index): Estimates cell-type purity in local neighborhoods, rescaled to 0-1 (higher scores indicate better separation).

A key limitation of the scIB pipeline is that the pipeline does not fully accommodate the hierarchical and continuous nature of many biological systems. Consequently, for simulations with continuous trajectories or loops, we first apply Leiden clustering to noise-free data to define "clusters" as ground truth, or use "branch" labels as a proxy for cell states in tree simulations. Under these conditions, the scIB metrics are applied in a more coarse-grained manner, offering an approximate assessment in these more complex scenarios.

5. Probing classifiers:
   To further assess embedding quality, we implemented probing classifiers—often used in evaluating representation learning methods. Two types of probing classifiers are implemented: a k-nearest neighbors (KNN) probe and a linear probe. The KNN probe fits a k-nearest neighbors classifier on 80% of the data and evaluates on the held-out 20%. The linear probe fits a single fully connected layer to the fixed embeddings using AdamW optimization, with cross-entropy loss for classification or MSE for regression. It uses a train-validation split (80/20) and performs

1010   early stopping based on validation loss (default patience 5 epochs) to

1011   prevent overfitting.

1012

We use these probes for evaluating biological label conservation or batch

mixing via classification. For the former task, the classification accuracy is

used, while for the latter we use the classification error to evaluate the

degree of batch mixing. Note that on datasets with imbalanced batch

composition and coverage, high classification error could sometimes

indicate over-correction. We therefore only use batch classification error to

quantify batch mixing when scIB metrics failed to run (e.g., *C. elegans*/*C.*

briggsae atlas), and include label classification accuracy under the

biological label conservation metrics for all evaluations.

1022

For all benchmarking analyses, we applied standard total count normalization

and log transformation to the datasets, followed by selection of highly variable

features (5,000 for all Open Problems datasets and 10,000 for the *C. elegans*/*C.*

briggsae datasets, intestine atlas, and PBMC scATAC-seq data). The resulting

normalized matrices served as input for all integration algorithms except

Harmony, which requires PCA-projected coordinates. All methods were

benchmarked in latent spaces of identical dimensionality: 30 dimensions for

simulated datasets, 50 dimensions for most real-world datasets, and 300

dimensions for complex datasets—such as the *C. elegans*/*C. briggsae* and

Tabula Sapiens atlases—to adequately capture the extensive diversity of cell

states. All methods were executed on an Amazon EC2 environment equipped

with an NVIDIA Tesla T4 GPU.

1035

Transcriptomic profiling of early *C. elegans* embryos by scRNA-seq

Wildtype N2 worms were grown on NGM plates and synchronized by bleaching.

Eggs hatched on 10-cm plates and were grown until L3/L4 stage. To enrich for

early embryos, plates were transferred to a 12ºC and incubated for 48 h. Adult

worms were lysed by bleaching, and embryos were dissociated into single cells

as previously described[80]. Cells were loaded onto a Chromium GEM-X Single

Cell 3' Chip Kit v4 with GEM-X Universal 3' Gene Expression v4 reagents (10x

Genomics, 1000686). Libraries were prepared following the 10x Genomics

protocol, sequenced on NovaSeq X, and processed with CellRanger (9.0.1)

utilizing the WBcel235 transcriptome. A total of 12,899 cells were recovered, with

median of approximately 69,000 reads per cell.

1047

Data Availability

Single-cell RNA-seq data of *C. elegans* early embryos have been deposited in

the Gene Expression Omnibus (GEO) under accession number GSE305031.

Public datasets analyzed in this study include: the human lung atlas, compiled by

Luecken et al.[33] and obtained from the scIB-metrics website (https://scib-

metrics.readthedocs.io/en/stable/notebooks/lung_example.html); GTEX v9,

HypoMap, immune cell atlas, mouse pancreatic islet, Tabula Sapiens datasets,

sourced from the Open Problems in Single-Cell Analysis website

(https://openproblems.bio/benchmarks/batch_integration?version=v2.0.0); the *C.*

elegans embryogenesis atlas, downloaded from GEO under accession

GSE126954; the joint *C. elegans* and *C. briggsae* dataset, available under GEO

accession GSE292756; and the mouse intestinal developmental atlas, acquired

from GEO under accession GSE233407.

1061

Code Availability

Concord is available at https://github.com/Gartner-Lab/Concord under the MIT

License. All benchmarking codes to generate results in this manuscript are

deposited to https://github.com/Gartner-Lab/Concord_benchmark. Full

documentation of Concord can be found at:

https://qinzhu.github.io/Concord_documentation/.

1068

References

1   Wagner, D. E. & Klein, A. M. Lineage tracing meets single-cell omics:
opportunities and challenges. *Nature Reviews Genetics* **21**, 410-427 (2020).
2   Tanay, A. & Regev, A. Scaling single-cell genomics from phenomenology to
mechanism. *Nature* **541**, 331-338 (2017).
3   Flores-Bautista, E. & Thomson, M. Unraveling cell differentiation
mechanisms through topological exploration of single-cell developmental
trajectories. *bioRxiv*, 2023.2007. 2028.551057 (2023).
4   Riba, A. *et al.* Cell cycle gene regulation dynamics revealed by RNA velocity
and deep-learning. *Nature communications* **13**, 2865 (2022).
5   Johnson, J. A. *et al.* Inferring cellular and molecular processes in single-cell
data with non-negative matrix factorization using Python, R and GenePattern
Notebook implementations of CoGAPS. *Nature protocols* **18**, 3690-3731
(2023).
6   Kunes, R. Z., Walle, T., Land, M., Nawy, T. & Pe'er, D. Supervised discovery of
interpretable gene programs from single-cell data. *Nature Biotechnology* **42**,
1084-1095 (2024).
7   Korsunsky, I. *et al.* Fast, sensitive and accurate integration of single-cell data
with Harmony. *Nature methods* **16**, 1289-1296 (2019).
8   Hie, B., Bryson, B. & Berger, B. Efficient integration of heterogeneous single-
cell transcriptomes using Scanorama. *Nature biotechnology* **37**, 685-691
(2019).
9   Stuart, T. *et al.* Comprehensive integration of single-cell data. *cell* **177**, 1888-
1902. e1821 (2019).
10 Lopez, R., Regier, J., Cole, M. B., Jordan, M. I. & Yosef, N. Deep generative
modeling for single-cell transcriptomics. *Nature methods* **15**, 1053-1058
(2018).
11 Welch, J. D. *et al.* Single-cell multi-omic integration compares and contrasts
features of brain cell identity. *Cell* **177**, 1873-1887. e1817 (2019).
12 Haghverdi, L., Lun, A. T., Morgan, M. D. & Marioni, J. C. Batch effects in single-
cell RNA-sequencing data are corrected by matching mutual nearest
neighbors. *Nature biotechnology* **36**, 421-427 (2018).
13 Zhang, Z. *et al.* Recovery of biological signals lost in single-cell batch
integration with CellANOVA. *Nature Biotechnology*, 1-17 (2024).
14 Richter, T., Bahrami, M., Xia, Y., Fischer, D. S. & Theis, F. J. Delineating the
effective use of self-supervised learning in single-cell genomics. *Nature
Machine Intelligence*, 1-11 (2024).
15 Ciortan, M. & Defrance, M. Contrastive self-supervised clustering of scRNA-
seq data. *BMC bioinformatics* **22**, 280 (2021).
16 Wang, J., Xia, J., Wang, H., Su, Y. & Zheng, C.-H. scDCCA: deep contrastive
clustering for single-cell RNA-seq data based on auto-encoder network.
Briefings in Bioinformatics **24**, bbac625 (2023).

17 Zhao, B., Song, K., Wei, D.-Q., Xiong, Y. & Ding, J. scCobra allows contrastive
cell embedding learning with domain adaptation for single cell data
integration and harmonization. *Communications Biology* **8**, 233 (2025).
18 Yang, M. *et al*. Contrastive learning enables rapid mapping to multimodal
single-cell atlas of multimillion scale. *Nature Machine Intelligence* **4**, 696-
709 (2022).
19 Heimberg, G. *et al*. A cell atlas foundation model for scalable search of
similar human cells. *Nature*, 1-3 (2024).
20 Heryanto, Y. D., Zhang, Y.-z. & Imoto, S. Predicting cell types with supervised
contrastive learning on cells and their types. *Scientific Reports* **14**, 430
(2024).
21 Chen, T., Kornblith, S., Norouzi, M. & Hinton, G. in *International conference*
on machine learning. 1597-1607 (PMLR).
22 Gao, T., Yao, X. & Chen, D. Simcse: Simple contrastive learning of sentence
embeddings. *arXiv preprint arXiv:2104.08821* (2021).
23 He, K., Fan, H., Wu, Y., Xie, S. & Girshick, R. in *Proceedings of the IEEE/CVF*
conference on computer vision and pattern recognition. 9729-9738.
24 Goodfellow, I. *et al*. Generative adversarial networks. *Communications of the*
ACM **63**, 139-144 (2020).
25 Lotfollahi, M., Wolf, F. A. & Theis, F. J. scGen predicts single-cell perturbation
responses. *Nature methods* **16**, 715-721 (2019).
26 Ganin, Y. & Lempitsky, V. in *International conference on machine learning*.
1180-1189 (PMLR).
27 Sohn, K., Lee, H. & Yan, X. Learning structured output representation using
deep conditional generative models. *Advances in neural information*
processing systems **28** (2015).
28 Heimberg, G., Bhatnagar, R., El-Samad, H. & Thomson, M. Low
dimensionality in gene expression data enables the accurate extraction of
transcriptional programs from shallow sequencing. *Cell systems* **2**, 239-250
(2016).
29 Wen, Z. & Li, Y. Toward understanding the feature learning process of self-
supervised contrastive learning. *International Conference on Machine*
Learning, 11112-11122 (2021).
30 Alaqeeli, O. A comparison of dropout rate of three commonly used single cell
RNA-sequencing protocols. *Biotechnology & Biotechnological Equipment* **38**,
2379837 (2024).
31 Yang, Z. *et al*. Batchsampler: Sampling mini-batches for contrastive learning
in vision, language, and graphs. *Proceedings of the 29th ACM SIGKDD*
Conference on Knowledge Discovery and Data Mining, 3057-3069 (2023).
32 Robinson, J., Chuang, C.-Y., Sra, S. & Jegelka, S. Contrastive learning with
hard negative samples. *arXiv preprint arXiv:2010.04592* (2020).
33 Luecken, M. D. *et al*. Benchmarking atlas-level data integration in single-cell
genomics. *Nature methods* **19**, 41-50 (2022).

34 Wang, H., Leskovec, J. & Regev, A. Limitations of cell embedding metrics
assessed using drifting islands. *Nature Biotechnology*, 1-4 (2025).
35 Rautenstrauch, P. & Ohler, U. Shortcomings of silhouette in single-cell
integration benchmarking. *Nature Biotechnology*, 1-5 (2025).
36 Belinkov, Y. Probing classifiers: Promises, shortcomings, and advances.
Computational Linguistics **48**, 207-219 (2022).
37 Marks, M. *et al.* A closer look at benchmarking self-supervised pre-training
with image classification. *International Journal of Computer Vision*, 1-13
(2025).
38 Coifman, R. R. & Lafon, S. Diffusion maps. *Applied and computational
harmonic analysis* **21**, 5-30 (2006).
39 Lee, D. D. & Seung, H. S. Learning the parts of objects by non-negative matrix
factorization. *nature* **401**, 788-791 (1999).
40 Bartholomew, D. J., Knott, M. & Moustaki, I. *Latent variable models and factor
analysis: A unified approach*. (John Wiley & Sons, 2011).
41 Hyvarinen, A. Fast and robust fixed-point algorithms for independent
component analysis. *IEEE transactions on Neural Networks* **10**, 626-634
(1999).
42 Blei, D. M., Ng, A. Y. & Jordan, M. I. Latent dirichlet allocation. *Journal of
machine Learning research* **3**, 993-1022 (2003).
43 Pierson, E. & Yau, C. ZIFA: Dimensionality reduction for zero-inflated single-
cell gene expression analysis. *Genome biology* **16**, 241 (2015).
44 Moon, K. R. *et al.* Visualizing structure and transitions in high-dimensional
biological data. *Nature biotechnology* **37**, 1482-1492 (2019).
45 Van der Maaten, L. & Hinton, G. Visualizing data using t-SNE. *Journal of
machine learning research* **9** (2008).
46 Tenenbaum, J. B., Silva, V. d. & Langford, J. C. A global geometric framework
for nonlinear dimensionality reduction. *science* **290**, 2319-2323 (2000).
47 Becht, E. *et al.* Dimensionality reduction for visualizing single-cell data using
UMAP. *Nature biotechnology* **37**, 38-44 (2019).
48 Packer, J. S. *et al.* A lineage-resolved molecular atlas of C. elegans
embryogenesis at single-cell resolution. *Science* **365**, eaax1971 (2019).
49 Sulston, J. E., Schierenberg, E., White, J. G. & Thomson, J. N. The embryonic
cell lineage of the nematode Caenorhabditis elegans. *Developmental biology*
100, 64-119 (1983).
50 Large, C. R. *et al.* Lineage-resolved analysis of embryonic gene expression
evolution in C. elegans and C. briggsae. *Science* **388**, eadu8249 (2025).
51 Ortiz, C. O. *et al.* Searching for neuronal left/right asymmetry: genomewide
analysis of nematode receptor-type guanylyl cyclases. *Genetics* **173**, 131-
149 (2006).
52 Yu, S., Avery, L., Baude, E. & Garbers, D. L. Guanylyl cyclase expression in
specific sensory neurons: a new family of chemosensory receptors.
Proceedings of the National Academy of Sciences **94**, 3384-3387 (1997).

53 Saelens, W., Cannoodt, R., Todorov, H. & Saeys, Y. A comparison of single-
cell trajectory inference methods. *Nature biotechnology* **37**, 547-554 (2019).
54 Kuang, D., Qiu, G. & Kim, J. Reconstructing Cell Lineage Trees from
Phenotypic Features with Metric Learning. *arXiv* **2503.13925** (2025).
55 Koreth, J. & van den Heuvel, S. Cell-cycle control in Caenorhabditis elegans:
how the worm moves from G1 to S. *Oncogene* **24**, 2756-2764 (2005).
56 Huycke, T. R. *et al.* Patterning and folding of intestinal villi by active
mesenchymal dewetting. *Cell* **187**, 3072-3089. e3020 (2024).
57 Zwick, R. K. *et al.* Epithelial zonation along the mouse and human small
intestine defines five discrete metabolic domains. *Nature Cell Biology* **26**,
250-262 (2024).
58 Morarach, K. *et al.* Diversification of molecularly defined myenteric neuron
classes revealed by single-cell RNA sequencing. *Nature neuroscience* **24**,
34-46 (2021).
59 Derecka, M. *et al.*   (American Society of Hematology Washington, DC,
2017).
60 Chen, C.-P., Wang, L.-K., Chen, C.-Y., Chen, C.-Y. & Wu, Y.-H. Placental
multipotent mesenchymal stromal cell-derived Slit2 may regulate
macrophage motility during placental infection. *Molecular Human*
Reproduction **27**, gaaa076 (2021).
61 Al-Shboul, O. A. The importance of interstitial cells of cajal in the
gastrointestinal tract. *Saudi Journal of Gastroenterology* **19**, 3-15 (2013).
62 Torihashi, S. *et al.* Blockade of kit signaling induces transdifferentiation of
interstitial cells of cajal to a smooth muscle phenotype. *Gastroenterology*
117, 140-148 (1999).
63 Ancona, M., Ceolini, E., Öztireli, C. & Gross, M. Gradient-based attribution
methods. *Explainable AI: Interpreting, explaining and visualizing deep*
learning, 169-191 (2019).
64 De Rop, F. V. *et al.* Systematic benchmarking of single-cell ATAC-sequencing
protocols. *Nature biotechnology* **42**, 916-926 (2024).
65 Janesick, A. *et al.* High resolution mapping of the tumor microenvironment
using integrated single-cell, spatial and in situ analysis. *Nature*
communications **14**, 8353 (2023).
66 Petukhov, V. *et al.* Cell segmentation in imaging-based spatial
transcriptomics. *Nature biotechnology* **40**, 345-354 (2022).
67 Luecken, M. D. *et al.* Defining and benchmarking open problems in single-
cell analysis. *Nature Biotechnology*, 1-6 (2025).
68 Consortium*, T. T. S. *et al.* The Tabula Sapiens: A multiple-organ, single-cell
transcriptomic atlas of humans. *Science* **376**, eabl4896 (2022).
69 Smirnov, E. *et al.* Face representation learning using composite mini-
batches. *Proceedings of the IEEE/CVF International Conference on*
Computer Vision Workshops, 0-0 (2019).

70   Jiang, J. *et al.* D-SPIN constructs gene regulatory network models from
multiplexed scRNA-seq data revealing organizing principles of cellular
perturbation response. *BioRxiv*, 2023.2004. 2019.537364 (2024).
71   Kotliar, D. *et al.* Identifying gene expression programs of cell-type identity and
cellular activity with single-cell RNA-Seq. *Elife* **8**, e43803 (2019).
72   Vaswani, A. *et al.* Attention is all you need. *Advances in neural information
processing systems* **30** (2017).
73   Sohn, K. Improved deep metric learning with multi-class n-pair loss
objective. *Advances in neural information processing systems* **29** (2016).
74   Lei Ba, J., Kiros, J. R. & Hinton, G. E. Layer normalization. *ArXiv e-prints*, arXiv:
1607.06450 (2016).
75   Wang, F. & Liu, H. in *Proceedings of the IEEE/CVF conference on computer
vision and pattern recognition.* 2495-2504.
76   Douze, M. *et al.* The faiss library. *arXiv preprint arXiv:2401.08281* (2024).
77   Kingma, D. P. & Ba, J. Adam: A method for stochastic optimization. *arXiv
preprint arXiv:1412.6980* (2014).
78   Tauzin, G. *et al.* giotto-tda:: A topological data analysis toolkit for machine
learning and data exploration. *Journal of Machine Learning Research* **22**, 1-6
(2021).
79   Venna, J. & Kaski, S. in *International conference on artificial neural networks.*
485-491 (Springer).
80   Williams, R. T., Nishimura, E. O., Zuckerman, B. & Weinberger, L. S. Embryo
stage C. elegans dissociation for FACS isolation and RNA-seq analysis.
(2025).
81   Eraslan, G. *et al.* Single-nucleus cross-tissue molecular reference maps
toward understanding disease gene function. *Science* **376**, eabl4290 (2022).
82   Steuernagel, L. *et al.* HypoMap—a unified single-cell gene expression atlas of
the murine hypothalamus. *Nature metabolism* **4**, 1402-1419 (2022).
83   Domínguez Conde, C. *et al.* Cross-tissue immune cell analysis reveals
tissue-specific features in humans. *Science* **376**, eabl5197 (2022).
84   Hrovatin, K. *et al.* Delineating mouse β-cell identity during lifetime and in
diabetes with a single cell atlas. *Nature metabolism* **5**, 1615-1637 (2023).

1271

Acknowledgement

We thank the reviewers for their constructive feedback, which was instrumental in driving major enhancements to CONCORD and strengthening the manuscript. We thank Junhyong Kim, John Murray, and Honesty Kim for valuable feedback on the manuscript. We also thank the authors of Large et al.[50] for sharing the *C. elegans* and *C. briggsae* dataset, with special acknowledgement to Christopher R. L. Large for facilitating data access. We are grateful to authors of De Rop et al.[64] for providing key metadata for the benchmarking analysis. Additionally, we thank members of the Gartner Lab for critical discussions, support and assistance in testing early versions of CONCORD. We acknowledge the use of ChatGPT and Gemini for assistance with code refinement and annotation.

This work was supported by grants from the NIH (U01CA199315, R01GM135462, R01DK126376, U01DK103147, and R33CA247744), the Chan Zuckerberg Initiative (CZI 2023-332284), and the UCSF Center for Cellular Construction (DBI-1548297), an NSF Science and Technology Center. Q.Z. is supported by a Cancer Research Institute Immuno-Informatics Postdoctoral Fellowship (CRI5054). Z.J.G. is a Chan Zuckerberg BioHub San Francisco Investigator. Sequencing was performed at the UCSF Center for Advanced Technology (CAT), supported by UCSF PBBR, RRP IMIA, and NIH 1S10OD028511-01 grants.

Author Contributions

Q.Z. and Z.J.G. conceived the project. Q.Z. designed and implemented the method. Q.Z. and Z.J conducted benchmarking analyses. B.Z. collected the new *C. elegans* dataset under the supervision of L.W and Z.J.G. M.T. provided critical feedback and methods for topological data analysis. Z.J.G. supervised the project. Q.Z. and Z.J.G. wrote the manuscript. All authors reviewed and edited the manuscript.

Competing Interests

ZJG is an author on patents associated with sample multiplexing and ZJG is an equity holder and advisor to Provenance Bio.

Materials & Correspondence

Correspondence to Q. Zhu (qin.zhu@ucsf.edu) and Z. J. Gartner (zev.gartner@ucsf.edu).

Figure 1. CONCORD mini-batch sampling enables high-resolution, batch-effect-mitigated representation learning of single cell data.

(**A**) Schematic of hypothetical cell-state landscapes and corresponding low-dimensional representations that capture key structural features. (**B**) Overview of the CONCORD framework, which replaces the conventional mini-batch sampler with a joint hard-negative and dataset-aware sampling scheme, enabling integrated, high-resolution representation learning with a minimalist contrastive model. (**C**) Uniform versus hard-negative sampling in a simulated four-state dataset. Heatmaps show simulated expression and latent space, accompanied by density curves with black lines indicating the distribution of cells in an example mini-batch under each scheme. Resulting UMAP embeddings are shown. (**D**) Contrastive learning on a single dataset using the conventional uniform sampler, which draws cells uniformly from the entire dataset to form mini-batches. (**E**) Applying standard contrastive learning across multiple datasets mixes datasets within mini-batches and amplifies batch effects, as reflected in the latent embeddings. (**F**) CONCORD mitigates batch effects by predominantly contrasting cells within each dataset and randomly shuffling mini-batches across epochs.

1310

1311

Figure 2. Benchmarking CONCORD and other dimensionality-reduction methods across diverse structures.

(A) Schematic of the simulation pipeline, which first produces a noise-free gene expression matrix based on a user-defined data structure, then introduces noise following a specified noise model, and finally applies batch effects. **(B)**

Schematic of the benchmarking pipeline. Latent representations from each method are compared with the noise-free ground truth to assess preservation of topological and geometric features. The scIB[33] package and probing classifiers are used to evaluate biological label conservation and batch harmonization. (**C**) Performance of CONCORD and competing methods on a three-cluster simulation with dimensions listed. UMAP embeddings, cosine-distance matrices and persistent-homology analysis (persistence diagram and Betti curves) are shown for each method. The H_0 point at infinity was excluded from the persistence diagram and curve. (**D**) Performance on a complex trajectory with three loops, highlighting the same diagnostic plots as in (C). (**E, F**) Summary of key geometric and topological performance metrics for the cluster simulation (**E**) and the complex trajectory simulation (**F**). (**G**) KNN-graph visualization of the latent spaces from a complex-tree simulation, with zoomed-in views of the highlighted branch.

1312

1313

Figure 3. Benchmarking CONCORD and other data-integration methods across diverse structures.

(**A**) Two-batch, five-cluster simulation with imbalanced batch sizes. Heatmaps show the noise-free ground truth and the input data with noise and batch effects. Latent spaces from each method are visualized by UMAPs, colored by batch. Full cluster-simulation results are in Supplemental Figure 3A-B.

"Contrastive" refers to naïve contrastive learning that uses the same encoder architecture and objective as CONCORD, but with uniform sampling. (**B**) Trajectory simulation with varying batch overlap. The input structure is shown by a heatmap and PCA. For each method, the latent space is visualized by a kNN graph (k = 15) colored by simulated time to assess cross-batch integration along the trajectory. (**C**) Loop simulation with varying batch overlap. kNN graphs are shown for the ground truth (edges omitted) and for CONCORD and selected methods. Full results are in Supplemental Figure 3C. (**D**) Tree simulation with varying batch overlap. kNN graphs are shown for the ground truth, CONCORD, and selected methods. Full results are in Supplemental Figure 3D. (**E**) Trajectory simulation with 16 batches, each with a different batch effect (heatmap). kNN graphs (k = 15) colored by batch are shown for each method's latent embeddings; for scVI and both CONCORD modes (*hcl* and *kNN*), kNN graphs colored by simulated time are also shown. A table displaying detailed benchmarking metrics is provided; see Methods for details on metric definitions. (**F**) Trustworthiness across neighborhood sizes for the multi-batch simulation in (E). (**G**) Prediction with limited training data for scVI and CONCORD. A specified number of batches were held out during training; we ran five replicates with random batch withholding and quantified batch mixing via kNN-based batch classification error (k = 30). Means and 95% confidence intervals are plotted. (**H**) Ranking of integration methods across simulated data, showing ranks for batch correction, biological-label conservation, topological and geometric metrics, and overall score. For cluster simulations, Betti curves become noisy when the number of clusters exceeds three, and we did not find a robust way to infer Betti numbers; therefore, topology scores were excluded for these datasets.

1314

1315

Figure 4. Benchmarking CONCORD on *C. elegans/C.briggsae* embryogenesis atlas.

(A) UMAPs from CONCORD and other integration methods, colored by inferred embryo time and species. Zoomed-in UMAPs for scVI and CONCORD (*hcl*) show approximately matched regions, colored by lineage and species. **(B)**

Global 2D and 3D CONCORD (*hcl*) embeddings colored by cell type and inferred embryo time. (**C**) Overlap between expert-curated cell-type and lineage annotations. A histogram shows lineage annotations concentrated in early-stage cells and cell-type annotations predominantly in late-stage cells. Integration performance was evaluated separately for early-stage cells (lineage labels) and late-stage cells (cell-type labels) using probing classifiers. (**D**) Global 3D UMAPs of CONCORD, scVI and Harmony, highlighting cells mapped to the lineage sub-tree that give rise to ASE, ASJ and AUA neurons. For each method, the most representative view was selected. (**E**) Heatmap showing the top 50 most variable latent dimensions in the ASE, ASJ, and AUA neuron subset for scVI, Harmony, and CONCORD (*hcl*). Expression of *gcy-5* and *gcy-14* is overlaid on a zoomed UMAP recomputed from the CONCORD latent space. (**F**) Lineage purity and average lineage distance computed across 2,000 randomly selected kNN neighborhoods for each method. For each randomly sampled anchor cell, we retrieve its k nearest neighbors in the embedding and compare their lineage relationships to the lineage graph. Purity is the fraction of neighbors assigned to the same lineage as the anchor; average lineage distance is the mean hop distance on the lineage tree from the anchor to its neighbors. Box plots show: median (center line), quartiles (box limits), 1.5× IQR (whiskers), and outliers (points). (**G**) Zoomed-in UMAPs for mesoderm (excluding pharynx), highlighting major input lineages and cell types. Each lineage is represented by its cluster medoid; edges connect parental lineages to daughters following the lineage tree. (**H**) Zoomed-in UMAPs for pharynx, annotated by cell type and broad input lineages. Selected lineage paths yielding pm1/2, pm3–5, and pm7 are highlighted. (**I**) scVI and CONCORD were trained on the combined *C. elegans* data from Packer et al.[48] and our newly-collected batch, then used to project the full atlas including *C. elegans* and *C. briggsae* data from Large et al[50]. Resulting UMAPs are colored by species, and integration performance was evaluated with probing classifiers.

1316

1317

Figure 5. Benchmarking CONCORD on mammalian intestine development.

(**A**) 2D and 3D UMAP visualizations of CONCORD (*kNN* mode) latent space, colored by cell type and cell-cycle phase, with UMAPs from scVI and Seurat (colored by cell type) for comparison. (**B**) Zoomed-in views of epithelial cells in the 3D global UMAP, colored by cell subtype, zonation, and expression of zonation-specific markers (*Bex4*, *Onecut2*). A red marker and arrow indicate

the viewing angle within the 3D global UMAP. Persistence diagrams are shown for scVI and CONCORD. (**C**) Zoomed-in view of enteric nervous system (ENS) cells, colored by cell-cycle phase and cell state/branch annotations, based on Morarach et al[58], along with state-specific marker expression. A red marker and arrow indicate the viewing angle. Persistence diagrams are shown for CONCORD and scVI. (**D**) Zoomed-in view of Pdgfra$^-$ mesenchymal cells and smooth muscle cells, colored by cell-cycle phase, subtype annotation, and selected subtype-specific markers. A red marker and arrow indicate the viewing angle. (**E**) Heatmap of latent representations generated by CONCORD (*kNN*), Seurat, and scVI. (**F**) Interpretation of the CONCORD latent space using gradient-based attribution techniques. Activation of Neuron 46 (Z46) in epithelial and ENS cells is attributed to the co-expression of epithelial- and neuron-specific gene sets in their respective contexts. Gene ontology (GO) enrichment analysis of these gene sets is shown.

1318

1319

Figure 6. Performance of CONCORD across modalities and scales.

(**A**) Schematic of the PBMC scATAC-seq benchmarking experiment spanning multiple technologies and experimental batches[64]. (**B**) Summary scores for all integration methods on the PBMC scATAC-seq data; detailed metric values are provided in Supplemental Figure 7B. (**C**) t-SNE embeddings from the original publication (Harmony integration) and embeddings produced by scVI and CONCORD, colored by batch and original cell-type annotations. To refine annotations, we analyzed paired scRNA-seq datasets with CONCORD and

projected the refined labels onto the scATAC-seq embedding via shared scMultiome cells. (**D**) Schematic of the experimental design for the breast cancer tumor microenvironment sample, where a single FFPE tissue block was analyzed with multiple technologies[65]. UMAP embeddings derived from the CONCORD and scVI latent spaces are colored by batch and original cell-type annotations. Full results for all integration methods are shown in Supplemental Figure 7C. (**E**) H&E image and overlay of cell-type annotations based on Xenium data, reproduced under the Creative Commons Attribution 4.0 International License from the original publication[65] without modification. Scale bar = 0.2 mm. (**F**) Ranking of integration method performance across all real-world benchmarking datasets, excluding datasets where scIB metrics could not be robustly computed. Each method was scored on both batch-correction and biological label conservation metrics, and the overall rank was computed based on the average score. Missing values indicate the method failed to run due to excessive resource requirements or violated assumptions. (**G**) Runtime of integration methods across all real-world benchmarking datasets. *Harmony was run using a reduced-dimensional PCA projection, whereas all other methods were applied to gene-expression matrices with 5,000–10,000 variable features.

1320

Supplemental Figure 1. The CONCORD framework.

(A) The CONCORD mini-batch sampling framework. A dataset-aware sampler that enriches each mini-batch with within-dataset cells is combined with a hard-negative sampler to support both data integration and enhanced resolution. Two hard-negative variants can be used with the dataset-aware sampler: the *kNN* sampler performs explicit local and global sampling via a kNN graph of cells; the *hcl* mode computes the expected hard-negative loss directly within the contrastive objective (see Methods). (B) Joint probabilistic sampler (kNN mode). We construct a probabilistic mini-batch sampler in which the likelihood of selecting a cell reflects the combined probabilities of dataset-aware (P_d) and neighborhood-aware sampling (P_{kNN}). (C) During training, each cell is

augmented twice via random feature-wise and element-wise masking, and the contrastive loss is computed on latent encodings of mini-batches drawn by the joint sampler. The model architecture used here is a minimalist neural network with a single hidden layer, though the framework supports more complex designs. Optional modules include a decoder with a learnable dataset/batch covariate for batch-free gene-expression inference and a classifier for cell-type classification or annotation-guided learning.

1323

1324

Supplemental Figure 2. Benchmarking CONCORD and other dimensionality reduction methods across diverse structures.

(A) Heatmaps of simulated expression for the three-cluster structure and the corresponding CONCORD latent encoding in *hcl* or *kNN* modes. **(B)** Heatmaps of simulated expression for the trajectory-loop structure and the corresponding CONCORD latent encoding in *hcl* or *kNN* modes. **(C)** Trustworthiness

measured across neighborhood sizes (k) in the three-cluster simulation. In the noise-free reference, within-cluster neighbors are assigned at random, so trustworthiness is < 1. CONCORD (h, k) denotes the *hcl* and *kNN* modes, respectively. (**D**) Trustworthiness measured across neighborhood sizes in the complex trajectory-loop simulation. (**E**) Heatmaps of simulated expression for the complex-tree structure shown in Figure 2G and the CONCORD latent encoding under medium hard-negative enrichment in *hcl* and *kNN* modes. (**F**) Trustworthiness across neighborhood sizes for *hcl* and *kNN* modes in the complex-tree simulation, evaluated under varying degrees of hard-negative sampling. An inset for k < 20 highlights improved local neighborhood preservation with hard-negative sampling.

1325

1326

Supplemental Figure 3. Benchmarking CONCORD and other data-integration methods across diverse structures. (**A**) Two-batch, five-cluster simulations with increasing batch-size imbalance and full state overlap. Heatmaps of the input data (dimensions indicated) and UMAPs of the ground truth and each method's latent space, colored by batch, are shown. (**B**) Cluster simulations with increased batch number and imbalance, with partial overlap of

cell states across batches. Heatmaps of inputs and UMAPs of the ground truth and each method's latent space, colored by batch, are shown. (**D**) Loop simulations with varying batch overlap. kNN graphs (k = 15; edges omitted) colored by batch are shown for the ground truth and each method. (**E**) Tree simulations with varying batch overlap. kNN graphs (k = 30; edges omitted) colored by batch are shown for the ground truth and each method.

1327

1328

1329

Supplemental Figure 4. Performance of CONCORD on *C. elegans* atlas.
(**A**) UMAPs of the *C. elegans* atlas from Packer et al. generated from the
CONCORD latent space. Gaps among early-stage cells are apparent; adding
our newly collected *C. elegans* dataset enriched for early embryos fills these
gaps, yielding continuous trajectories. The combined UMAP is colored by

inferred embryo time and batch. (**B**) Overlap between expert-curated cell-type and lineage annotations. A histogram shows that lineage annotations are concentrated in early-stage cells, whereas cell-type annotations are predominantly in late-stage cells. (**C**) Integration performance of CONCORD and other methods, evaluated separately for early-stage cells with lineage annotations and late-stage cells with cell-type annotations. See Methods for details on metric definitions. (**D**) Performance of the two CONCORD modes (*hcl* and *kNN*) across combinations of element- and feature-masking ratios, assessed by average classification accuracy using linear and kNN probes. (**E**) Performance of both modes across key hyperparameters, quantified by the average of label-classification accuracy and batch-classification error. Each run varies one hyperparameter while fixing the rest (default value indicated on plot). Scores from other methods are included for comparison. (**F**) UMAPs illustrating results with the dataset-aware sampler alone (no hard negatives) and with moderate versus excessive hard-negative sampling for *hcl* and *kNN* modes. Moderate local sampling improves cell-type and lineage resolution, whereas excessive local sampling without balanced global sampling disrupts global structure.

1330

Supplemental Figure 5. CONCORD analysis of *C. elegans/C.briggsae* embryogenesis atlas. (**A**) 2D and 3D UMAPs of the CONCORD latent space (kNN mode), colored by cell type and inferred embryo time. (**B**) *C. elegans* lineage tree and its projection onto the CONCORD (hcl) embedding. Lineage annotations from Large et al. were mapped to the *C. elegans* lineage tree (with some ambiguous mappings due to symmetry). Each lineage is represented by its cluster medoid on the UMAP; lines connect each parent lineage to its daughters following the lineage tree. Subtrees for major lineage groups are shown separately. (**C**) Label refinement in the CONCORD latent space via kNN majority vote. For each cell, we examine its k = 30 nearest neighbors; if ≥50% of neighbors carry expert-curated lineage/cell-type labels, we assign the neighborhood's majority label to unlabeled cells (and relabel when the majority disagrees). We iterate this procedure twice so newly assigned labels can vote. This recovers labels for many unlabeled cells and flags likely mis-annotations.

1331

Supplemental Figure 6. Benchmarking CONCORD on mammalian intestine development. (**A**) UMAP embeddings derived from the latent spaces of CONCORD and other integration methods for the mouse intestinal developmental atlas[56], colored by broad cell type, batch, cell-cycle phase, developmental stage, and zonation. (**B**) For epithelial and smooth-muscle cells, loop-like trajectories were identified and pseudotime was assigned along each circular path. Heatmaps show top differentially expressed genes (DEGs) along

each loop, as well as DEGs distinguishing the two epithelial loops. Persistence diagrams computed from each method's latent representations are shown for both cell types. (**C**) Expression patterns of the top-ranked genes contributing to Neuron 46 activation in the ENS context (top) and epithelial context (bottom), as determined by gradient-based attribution.

1332

Supplemental Figure 7. Performance of CONCORD across modalities and scales. (**A**) UMAPs of PBMC scATAC-seq data from unintegrated inputs and from CONCORD and other integration methods, colored by original cell-type annotations and batch. (**B**) Full benchmarking statistics for the PBMC scATAC-seq dataset. (**C**) UMAPs of breast cancer tumor microenvironment data generated by CONCORD and other integration methods, colored by cell type and technology/batch. (**D**) RAM and VRAM usage of different integration

methods. For all methods except Seurat, we report ΔRAM (end–start RSS) because Python does not support resetting peak RSS mid-process; for Seurat, we report peak RAM using the *peakRAM* R package. VRAM usage is shown only for GPU-enabled methods. Missing values indicate the method failed to run due to excessive resource requirements or violated assumptions.

1333

1334

Supplemental Figure 8. Performance of CONCORD on public human and mouse scRNA-seq datasets. UMAP embeddings derived from each method's latent space are shown for all datasets and colored by batch and cell type. (A) Lung atlas spanning multiple spatial regions, donors, and two scRNA-seq protocols[33]. (B) GTEX v9: human single-nucleus RNA-seq data from eight

tissue types across 16 individuals[81]. (C) HypoMap: single-cell atlas of the murine hypothalamus (~380k cells) across four assays[82]. (D) Immune cell atlas: human immune cells from 16 tissues and 12 donors[83]. (E) Mouse pancreatic islet: scRNA-seq atlas comprising 56 samples across sex, age, and diabetes models[84]. (F) Tabula Sapiens: human cell atlas of over 1.1M cells from 28 organs of 24 normal human donors[68].

1335

Supplementary Tables

Supplemental Table 1. Benchmarking data-integration methods across

diverse simulated structures. For each structure type (clusters, trajectories,

loops, and trees), we simulated varying degrees of batch overlap (full, partial and

connected). For the cluster setting, we additionally varied the number of batches

and their imbalance. The table reports, for each method and each simulation,

scores for topological and geometric preservation, batch correction, and

biological-label conservation.

1344

1345 **Supplemental Table 2. Benchmarking data-integration methods across real-**

1346 **world datasets.** For each dataset, we computed batch-correction and biological-

1347 label conservation metrics using the scIB[33] package and probing classifiers. The

1348 table reports per-method metric values and summary scores.

1349