1

Main Manuscript for

Neural and computational evidence for a predictive learning account of the testing effect

Haopeng Chen[1], Pieter Verbeke[2], Stefania Mattioni[1], Cristian Buc Calderon[3], Tom Verguts[1]

[1]Department of Experimental Psychology, Faculty of Psychology and Educational Sciences,
Ghent University, Ghent, 9000, Belgium

[2]AI Lab, Howest University of Applied Sciences, Kortrijk, 8500, Belgium.

[3]Centro Nacional de Inteligencia Artificial (CENIA), Santiago, 8320000, Chile

*Haopeng Chen.

Email: haopeng.chen@ugent.be

Author Contributions: H.C. designed the research, collected the data, performed data analysis,
and wrote the manuscript. P.V. designed the research, collected the data, and performed data
analysis. S.M. designed the research. C.B.C. designed the research and wrote the manuscript.
T.V. designed the research and wrote the manuscript. All authors discussed the results and
commented on the manuscript.

Competing Interest Statement: There is no competing interest.

Classification: Biological Sciences: Psychological and Cognitive Sciences.

Keywords: Testing effect; Predictive learning; fMRI; Ventral Striatum, Insula**.**

Abstract

Testing enhances memory more than studying. Although numerous studies have demonstrated the robustness of this classic effect, its neural and computational origin remains debated. Predictive learning is a potential mechanism behind this phenomenon: Because predictions and prediction errors (mismatch between predictions and feedback) are more likely to be generated in testing (relative to in studying), testing can benefit more from predictive learning. We shed light on the testing effect from a multi-level analysis perspective via a combination of cognitive neuroscience experiments (fMRI) and computational modeling. Behaviorally and computationally, only a model incorporating predictive learning can account for the full breadth of behavioral patterns and the robust testing effect. At the neural level, testing and prediction error both activate the canonical reward-related brain areas in the ventral striatum, insula, and midbrain. Crucially, back sorting analysis revealed that activation in the ventral striatum, insula, and midbrain can enhance declarative memory. These results provide strong and converging evidence for a predictive learning account of the testing effect.

Significance Statement

An exam is not a neutral measurement of memory. The *testing effect* entails that a test (e.g., an exam), is more effective than study for learning and memory. The same effect can be harnessed also before events of significance take place, rendering it an important aspect of an active learning strategy. Nevertheless, its origin remains unknown. We propose a novel predictive learning account, which posits that testing (vs studying) facilitates predictions about study material and promotes learning from prediction errors. Computationally, the testing effect was explained through a predictive-learning-based neural network. Neurally, testing and prediction error activate common neural areas, which in turn enhance declarative memory. This account may extend beyond testing to support active learning.

Main Text

Introduction

A remarkable finding is the testing effect, the robust phenomenon that testing enhances declarative memory retention more effectively than studying (1, 2). For instance, after an initial study session, taking tests instead of engaging in repeated study helps one to retain knowledge (3-5). Accordingly, learning apps such as Duolingo are increasingly advocating users to have tests and retrieval, rather than restudy. Previous work has attributed the testing effect to myriad factors, such as retrieval effort (6, 7) and elaborative semantic organization during testing (8, 9), which are absent during studying. Nevertheless, its underlying mechanisms remain a topic of debate. Here, we report and test an emergent predictive learning account as its cognitive and neural origin (10-12).

Predictive learning implies that minimizing prediction errors is a key objective for learning (13). This is a foundational principle in computational approaches to learning (including in Artificial Intelligence) and has more recently found its way into human declarative memory as well. Indeed, several studies have demonstrated that prediction errors can significantly promote declarative memory (14-16). For example, a student might initially predict that a dolphin is a type of fish, but is then corrected that it is, in fact, a mammal. Here, prediction errors can restructure and cement the student's information (neural representations) in memory.

Of importance for the present purpose, prediction error is more likely to appear in testing, relative to studying (10). Indeed, testing provides more opportunities to predict possible answers, relative to studying. For example, students have no opportunity to guess (predict) which city is the capital of Australia when the teacher provides the answer directly. The mismatch between predictions

and subsequent, external or internal, feedback generates prediction errors driving learning in a testing context (10, 12). External feedback comes from the environment, while internal feedback can manifest as internal (confidence) feelings about whether a prediction is correct (17, 18). Indeed, the neural signature of external feedback can also be active when people have an internal feeling of being correct or incorrect (18-20). Importantly, both external and internal prediction errors are consistently localized in the midbrain across animal species including rodents (21), macaques (22, 23), and humans (17, 24), where they are encoded by dopaminergic bursts. Recent studies suggest that the effect of prediction error on declarative memory can be fully mediated by the neural activation in the ventral striatum (25), a key target for dopamine release. Based on these results, we propose a dopaminergic neural basis (ventral striatum) for the testing effect and suggest that this neural basis can be explained from a predictive learning perspective. To substantiate this account, we employed a combination of cognitive neuroscience (fMRI) experiments and computational modeling techniques to investigate whether both testing and prediction errors elicit ventral striatum activation, and whether such activation enhance declarative memory.

Results

Experimental design.

Our declarative memory task consisted of four phases designed to help participants learn 90
Dutch-Swahili word pairs (Figure 1A) (10). In Phase 1, participants underwent initial learning,
during which each word pair was displayed on the screen for 3 seconds. This phase ensured that
participants acquired initial knowledge for the subsequent tests. Phase 2 involved a no-feedback
assessment to control participants' initial learning performance. During this phase, participants
selected the correct Swahili translation for a given Dutch word from four options and rated their
confidence in their choice. A previous study used strategies such as excluding correct or high-
confidence items from Phase 2 to filter out extreme initial learning (10). However, here and in
previous study (10), the behavioral patterns remain unchanged with or without applying these
filters (See Supplementary Figure S1). For this reason, and to maintain strong statistical power in
our fMRI analyses, we chose not to filter. The primary variable, Test vs. Study, was manipulated
in Phase 3. Participants selected the correct Swahili translation of a Dutch word, either from four
boxed options (test trials) or from a single boxed option containing the correct answer (study
trials). After making their selections, participants rated their confidence and received (informative
but non-monetary) feedback with the correct answer. Importantly, participants were informed in
advance that the solely boxed option in each study trial was always correct, and they were only
allowed to select this correct option. Therefore, they were always confident in their choices and
experienced no (or the smallest possible) prediction errors in the studying condition. Phase 4
consisted of two final assessments without feedback. A word pair was considered fully learned
only if it was correctly identified in both final assessments[*]. Only Phase 3 was conducted in the
fMRI scanner.

Robust testing effect in behavioral data.

111 As shown in Figure 1B, the final assessment accuracy (Phase 4) after test is better than that after
112 study, which replicates the robust testing effect (χ^2(1, N = 48) = 6.382, p = .012, $\beta \pm 95\%\ CI$ =
113 .036 ± .029, R^2 = .001). The testing effect became more robust (χ^2(1, N = 48) = 81.702, p < .001,
114 $\beta \pm 95\%\ CI$ = .225 ± .050, R^2 = .078) after controlling for feedback valence and confidence ratings
115 from Phase 3 (Figure 1C).

Predictive learning model accounts for the behavioral data.

We next turned to computational modeling and constructed an associative memory neural
network model (Figure 2A; see Methods) where Dutch and Swahili words were presented as
input and output, respectively (10). Initial connections between Dutch and Swahili units were
based on participants' confidence ratings from Phases 2 and 3. The model then underwent
testing and studying trials based on predictive learning, Hebbian learning, or a combination of
both. Hebbian learning learns from feedback. We included Hebbian learning as a baseline model
to evaluate empirical fit of a model that does not learn from prediction error. Finally, the model
completed a simulated final assessment to evaluate its performance. Based on different
combinations of learning components (initial learning, predictive learning, and Hebbian learning),
a total of seven models were constructed (Table 1).

Model comparison with wAIC (higher means better) suggested that the model with both initial
learning and predictive learning (Model 5) fit the human data best (Figure 2B). Replicating

---

[*] Final assessment accuracy was coded as 1 for correct responses in both final assessments, 0.5
for one correct response, and 0 for no correct response.

previous research (10), model simulations showed that only the models incorporating predictive
learning (Models 3, 5, 6, 7; Figure 2B) could replicate the testing effect in human data.

Additionally, we developed an enhanced Hebbian learning model that incorporates an
implementation of the retrieval effort hypothesis (6, 7). That is, greater learning occurs following
difficult but successful tests, compared to easier successful tests or study. In our experiment,
confidence ratings serve as a proxy for difficulty. Accordingly, we specified a minimal baseline
learning rate applied across all trials, with the learning rate in each trial inversely modulated by
correct confidence ratings (i.e., higher learning rates for low-confidence correct trials; see
Methods). Under this scheme, both incorrect testing trials (with wrong confidence ratings) and
studying trials (with maximum confidence ratings) were assigned only the minimal learning rate.
However, model comparisons still favor a model that combines initial learning and predictive
learning (Model 5; Supplementary Figure S2, Panel A). Moreover, the model combining initial
learning and retrieval effort (Hebbian) learning did not show a clear distinction between testing
and studying conditions (Model 8; Supplementary Figure S2, Panel B).

Finally, we estimated trial-level prediction errors for each participant from the best-fitting model
(Model 5) and examined their relationship with final assessment accuracy (bottom right panel in
Figure 2B). For clarity in visualization, prediction error values were rounded to one decimal place.
The influence of prediction errors on final assessment accuracy followed a W-shaped pattern,
highlighting three key peaks. The first peak occurred at extremely negative prediction errors
(around -1), and the second at extremely positive prediction errors (around 1), consistent with a
critical role of (unsigned) prediction errors in memory consolidation (15, 26, 27). The third peak, at
small positive prediction errors (around 0), was driven by initial learning rather than prediction
errors. Specifically, strong initial learning enabled participants (and the model) to consistently
provide correct answers in both Phase 3 and Phase 4, resulting in small prediction errors in
Phase 3 but high final assessment accuracy in Phase 4. Indeed, the initial learning effect is
obvious in the human behavioral pattern, in which participants' final assessment accuracy
increases with correct confidence ratings in Phase 3 (Figure 1C). Importantly, this W-shaped
relationship was consistent across all relevant datasets, including the behavioral data from the
current fMRI study and two behavioral datasets with the same experimental design from a
previous study (10) that we re-analyzed (see Supplementary Figure S2, Panels C-D).

Testing triggers neural activation in the ventral striatum, insula, and midbrain.

The fMRI analysis first examined neural activation associated with testing (relative to studying)
during the feedback onsets of Phase 3. In the Test-GLM1 (see Methods), we included three main
regressors (correct test, incorrect test, and study) separately for the feedback onsets and choice
onsets (a total of 6 main regressors). Consistent with our assumption, testing elicited stronger
activation than studying in the ventral striatum (VS; Figure 3A). Additionally, the insula, midbrain,
superior and middle frontal gyrus (SFG and MFG) also showed greater activation during feedback
onsets following test, compared to study (Figure 3A). Notably, both correct (Figure 3B) and
incorrect (Figure 3C) test trials showed greater activation in the VS, insula, and midbrain
compared to study trials, indicating that these brain responses are not merely driven by positive
feedback in correct tests (or negative feedback in incorrect tests). In the following fMRI analyses,
we mainly focus on VS, insula, and midbrain, as other testing-related regions such as MFG and
SFG did not consistently emerge in both correct and incorrect tests.

As an exploratory analysis, we also examined neural activity during choice onsets, where testing
(relative to studying) elicited significant activation in the VS and visual cortex (Supplementary
Figure S3, Panel A). The visual cortex activation may reflect visual search (i.e., selecting the
correct answer among four options), while the VS activation may reflect active anticipation.
Consistently, in another Test-GLM2 (see Methods) that included trial-level confidence ratings as a
parametric modulator for the (testing) choice onset regressors, we found that confidence

positively modulated VS activation (Supplementary Figure S3, Panel B). This finding aligns with
prior evidence that dopaminergic activity increases when agents anticipate a positive outcome
(22, 23), and with a previous study showing that the VS is also active when participants feel they
have grasped the meaning of a new word (28).

To ensure that the VS activation observed during feedback onsets was not simply residual VS
activation from the preceding choice onsets, we examined the testing (vs. studying) related neural
activity during two fixation periods between choice and feedback onsets (Additional regressors in
Test-GLM1; see Methods). However, no fixation periods showed increased VS activation
following test compared to study (Supplementary Figure S3, Panels C-D).

Prediction error also triggers neural activation in the VS, insula, and midbrain.

Our theory also predicts an overlap between prediction error and testing-related signals in the VS.
Accordingly, in the PE-GLM1, trial-level prediction errors and feedback valence were jointly
included as parametric modulators of one feedback onset regressor (See Methods). Neural
activity positively modulated by prediction error (Figure 4A) was localized in the VS, insula, and
midbrain. In contrast, the feedback valence parametric modulator revealed non-overlapping
neural signatures in the anterior cingulate cortex (ACC) and posterior cingulate cortex (PCC;
Figure 4B). We conclude that the VS, insula, and midbrain are sensitive to prediction errors,
rather than to feedback valence. Importantly, the neural activation elicited by testing and
prediction error overlap in the VS, insula, and midbrain (Figure 4C).

To examine how the VS, insula, and midbrain encode prediction errors, we defined regions of
interest (ROIs) based on overlapping VS, insula, and midbrain regions between prediction error
and testing. We then constructed another PE-GLM2, in which feedback onsets associated with
different prediction errors (rounded to one decimal place for statistical robustness of the
estimates) were modeled as separate regressors (See Methods). For each participant, we
extracted the mean beta values across voxels within the VS, insula, and midbrain ROIs for each
regressor. Interestingly, VS activity seems to track signed prediction errors (Figure 4D), whereas
insula activity reflects the absolute (unsigned) magnitude of prediction errors (Figure 4E). Indeed,
when using either signed or unsigned prediction errors in separate general linear mixed models
(separate signed model and unsigned model; with the PE-GLM2 betas as dependent variables;
the feedback valence was always included as a covariate) to predict neural activity within the VS,
insula, and midbrain ROIs, we observed different patterns. VS activation was primarily predicted
by the signed prediction errors (Figure 4G; Lower BIC indicates better model fit; Signed prediction
error: $\chi^2(1, N = 48) = 10.414$, $p = .001$, $\beta \pm 95\% \; CI = .146 \pm .089$, $R^2 = .007$; Unsigned prediction
error: $\chi^2(1, N = 48) = 4.605$, $p = .032$, $\beta \pm 95\% \; CI = .060 \pm .055$, $R^2 = .003$). In contrast, insula
activation was better explained by unsigned prediction errors (Figure 4H; Signed prediction error:
$\chi^2(1, N = 48) = 31.561$, $p < .001$, $\beta \pm 95\% \; CI = .247 \pm .086$, $R^2 = .034$; Unsigned prediction error:
$\chi^2(1, N = 48) = 39.674$, $p < .001$, $\beta \pm 95\% \; CI = .171 \pm .053$, $R^2 = .039$). Additionally, midbrain
activity was slightly better predicted by signed prediction errors (Figure 4I; Signed prediction
error: $\chi^2(1, N = 48) = 8.464$, $p = .004$, $\beta \pm 95\% \; CI = .132 \pm .089$, $R^2 = .010$; Unsigned prediction
error: $\chi^2(1, N = 48) = 7.589$, $p = .006$, $\beta \pm 95\% \; CI = .078 \pm .056$, $R^2 = .009$).

Notably, neither VS nor insula encoded positive prediction errors in a strictly linear fashion. When
the prediction error was close to zero, both regions exhibited minimal activation. Both VS and
insula activations peaked around a prediction error of 0.2, possibly reflecting a state in which
participants strongly anticipated the positive outcome and received confirmatory feedback. A
second peak in VS and insula activation was observed at the large prediction error range (around
1), reflecting neural responses to highly unexpected positive feedback.

VS, insula, and midbrain influence the final assessment accuracy.

Finally, we conducted a back sorting analysis (Bsort-GLM1) by categorizing feedback onsets in
Phase 3 based on final assessment accuracy in Phase 4 (feedback onsets followed by correct vs.
incorrect Phase 4 assessments), modeling them as two main regressors in the Bsort-GLM1 (see
Methods). To minimize the confounding effects of initial learning on final assessment, we included
only incorrect trials and correct trials associated with high prediction errors (prediction error ≥ 0.7)
from Phase 3, as these trials were less likely to be influenced by the initial learning. Consistent
with our assumption, the VS (and dorsal striatum), insula, and midbrain showed increased
activation during feedback onset when the following final assessment was correct (relative to
incorrect; Figure 5A), overlapping with VS and insula regions elicited by testing and prediction
error (Figure 5B-D).

To ensure the robustness of our findings, we conducted an additional Bsort-GLM2 that included
again the incorrect trials and correct trials (with a looser threshold of prediction error ≥ 0.5) from
Phase 3. This analysis still revealed VS and insula activations that overlapped with those
associated with testing and prediction error (Supplementary Figure S3, Panels E-F). Moreover,
another exploratory Bsort-GLM3 targeted at choice onsets revealed no stronger brain activation
for correct compared to incorrect final assessment. The latter result demonstrates that the effect
observed in VS and insula is, as predicted, specific for the feedback onsets.

Discussion

This study combined behavioral, modeling, and fMRI approaches to explore predictive learning as
a potential account for the testing effect. The behavioral and modeling results reveal (unsigned)
prediction errors as a key driver of the testing effect. Further fMRI results suggest that both Test
(vs Study) and prediction error activate VS, insula, and midbrain during feedback onsets.
Importantly, the VS encoded signed prediction errors, while insula encoded unsigned prediction
errors. Furthermore, activations in the VS and insula were associated with the final assessment
accuracy.

Predictive learning as a behavioral explanation of the testing effect.

Our computational modeling results indicate that the testing effect in human data could only be
explained by an associative memory neural network model that incorporates predictive learning,
but not Hebbian learning. This aligns with the computational principle that predictive learning is
more efficient than Hebbian learning (29). Unlike Hebbian learning, predictive learning requires
active retrieval or prediction, consistent with the cognitive and educational trends that advocate
for active, prediction error-based learning (30, 31). Augmenting the Hebbian learning model with
retrieval effort modulation (6, 7) did not enhance its explanatory power beyond that of the
predictive learning model. However, it is worth noting that the retrieval effort theory (6, 7), along
with several other previous explanations (extra semantic organization or extra feedback during
test compared to study) of the testing effect (5, 8, 32), share key assumptions with our predictive
learning account, so they may eventually be integrated within a broader predictive learning
framework. First, consistent with the retrieval effort assumption, individuals may experience
strong prediction errors during tests that are difficult but ultimately successful (6, 7). Second,
predictive learning may help organize an elaborative semantic network (29, 33), a possibility that
future studies could further investigate. Finally, the exact function of feedback is to trigger
prediction errors in a testing context.

The trial-level prediction errors estimated by the optimal predictive learning model influences final
assessment accuracy in a W-shaped pattern. This pattern suggests an unsigned prediction error
effect that both extremely positive and negative prediction errors enhance declarative memory
(15, 34). Notably, extremely negative prediction errors are triggered by high-confidence errors,

which is labeled the hypercorrection effect (26, 35-37). The hypercorrection effect suggests that
high-confidence errors are more easily corrected than low-confidence errors (37). Although
several studies support the hypercorrection effect (26, 35, 36), a recent study has reported
contradictory findings, indicating that small errors are easier to correct (38). Considering our
findings, one possible explanation is that the study failing to observe the hypercorrection effect
might not elicit extremely negative prediction errors.

It is important to clarify that while prediction errors are more likely to occur in the testing condition,
they are not exclusive to testing and may also arise during study. For example, if people distrust
the provided answer or unexpectedly receive negative feedback during a studying trial, they may
also experience high prediction errors and potentially enhanced declarative memory. We did not
include such manipulations in our study to avoid blurring the distinction between testing and
studying conditions. However, we believe that predictive learning may serve as a general learning
rule across different contexts (both testing and studying), as long as active prediction is
encouraged. In other words, the most effective learning strategy may not necessarily be testing,
but rather continuously engaging in critical thinking and active prediction, even when the "correct
answer" has already been revealed.

Testing effect and prediction error effect share the same neural basis.

Our fMRI results revealed that both test and prediction errors robustly activate VS, insula, and
midbrain during feedback onsets, which reveals a shared dopaminergic basis between testing
and prediction errors. Indeed, the VS is a key target of dopaminergic transmission (39), and the
midbrain serves as a primary source of dopamine release (21, 40). Dopaminergic signals are
broadly transmitted across brain regions, including VS, hippocampus, and neocortex (39, 41),
forming a distributed learning system (25, 28). Previous studies have reported VS activation and
its functional connectivity with neocortex when participants successfully acquire the meaning of a
novel word (28). Additionally, VS-hippocampus connectivity emerges during Swahili word learning
and is modulated by reward prediction errors (25), suggesting that prediction errors play a crucial
role in activating the above complementary learning system. Future studies can explore how this
complementary dopaminergic learning system promotes testing and prediction error-based
learning.

In our original theoretical framework, we largely overlooked the important role of insula. The
insula also has intensive dopaminergic receptors (42-44). Besides, a recent study suggests that
the insula serves as a top-down modulator of the dopaminergic release in the midbrain (45).
Importantly, the insula receives not only dopaminergic afferents, but also cholinergic,
serotonergic, and noradrenergic inputs (44), suggesting a potential interplay among multiple
neuro-modulatory systems.

Consistent with previous findings, VS and insula encode prediction errors in distinct ways (25,
46). Specifically, VS activation encodes the original prediction errors as signed prediction errors
(25), while the insula encodes the absolute magnitude of the prediction errors as unsigned
prediction errors (46). Given that final assessment accuracy was influenced by unsigned
prediction errors, the insula may serve as an important neural hub in the current study.
Interestingly, both VS and insula exhibited two peak points in response to positive prediction
errors. The first peak point occurs at a low but non-zero prediction error range, aligning with a
recent finding that participants are most curious when they are close to the correct answer (47).
The second peak point emerges in the large prediction error range, likely reflecting surprise to
unexpected positive feedback. Future studies could investigate how these peak points influence
learning in different tasks, offering important insights for both cognitive research and educational
practice. Future modeling studies could explore whether incorporating complementary systems
for signed and unsigned prediction errors, along with dynamic learning rates that peak at the
above points, can enhance learning efficiency.

Our study offers a piece of puzzle into the ongoing debate over whether declarative memory is
influenced by signed versus unsigned prediction errors (48). First, our behavioral results, together
with previous studies on the hypercorrection effect (36, 37), suggest that internally generated,
extremely negative prediction errors may be critical for eliciting unsigned prediction error effects.
Indeed, prior studies demonstrating signed prediction error effects typically manipulated
prediction errors through external cues, rather than through participants' internal confidence (14,
49, 50). Second, our neural findings suggest a potential dissociation in prediction error encoding
between the VS and insula. Complementing this spatial dissociation, a previous EEG study
reported that signed and unsigned prediction errors are encoded by late and early EEG
components, respectively, during the feedback stage (51). Taken together, these findings indicate
that signed and unsigned prediction errors may coexist within spatially and temporally dissociable
neural systems.

Internal feedback as a potential explanation of the testing effect.

In our study, prediction error was elicited by external feedback. However, the testing effect can
occur in the absence of external feedback, leading to a classification of testing effects with
external feedback (52, 53) and those without (3, 7). Although the current predictive learning
framework can account for the testing effect with external feedback, it requires modifications to
explain the testing effect without external feedback. As mentioned earlier, some neural studies
have shown that internal feedback (e.g., confidence) can also elicit VS activation and modulate
learning (18, 28). Moreover, post-test confidence rating can replace reward signal to elicit VS-
encoded internal prediction errors (17). Consistent with these studies, our study also found that
confidence modulated the VS activity during testing. Therefore, predictive learning may contribute
to the testing effect by providing both internal and external feedback and prediction errors.
However, because initial learning is inherently confounded with confidence, it remains challenging
to disentangle the effect of initial learning from learning driven by internal feedback (confidence),
which may be an important topic for future research.

Summary

In summary, the current study supports the notion that the testing effect benefits from predictive
learning, as evidenced by cognitive neuroscience and modeling findings. Notably, the testing
effect represents just one instance of a broader range of active learning strategies that
emphasize active predictions (54, 55). Predictive learning may not only serve as a specific
mechanism underlying the testing effect but also offer a broader cognitive framework for general
active learning approaches, such as the generation effect (54), problem-based learning (30, 31) ,
and error-driven learning (26, 55).

Materials and Methods

Participants.

Fifty-five participants, all native Dutch speakers, with no reports of smoking, alcohol consumption,
medication use within 24 hours of scanning, or psychiatric disorders, were recruited for this study.
Each participant was compensated 35€. Data from seven participants were excluded from the
final analysis: six due to technical issues during the experiment, and one due to being left-
handed. This resulted in a final sample of 48 right-handed participants (mean age = 22.44, SD =
2.65, range = 18-29; 34 female participants, 14 male participants). The study was approved by
the local ethics committee at Ghent University Hospital, and all participants provided informed
consent.

Experimental design.

Participants were instructed to learn 90 Dutch-Swahili word pairs (Figure 1A). They underwent 4
phases: Initial learning (Phase 1), Initial assessment (Phase 2), Test vs Study (Phase 3), and
Final assessment (Phase 4). Given our primary interest in the neural mechanism underlying Test
vs Study comparison, only Phase 3 was conducted in the fMRI scanner.

Phase 1: Initial learning

Participants were required to familiarize themselves with all word pairs before proceeding to the
subsequent phases. All word pairs were randomly presented on the screen, with each pair
displayed for 3 seconds.

Phase 2: Initial assessment

Following initial learning, a test without feedback was conducted in Phase 2 to assess
participants' learning progress before the formal manipulations in Phase 3. In each trial,
participants selected the Swahili translation of a randomly presented Dutch word from four
random options by pressing "f", "v", "n", or "j" on the keyboard, followed by a 4-point confidence
rating ("very uncertain," "uncertain," "certain," or "very certain") for their choice.

Phase 3: Test vs Study

Phase 3 was the critical phase, designed to manipulate the Test vs Study conditions and induce
prediction errors. In each trial, participants were presented with a randomly selected Dutch cue
and four random Swahili options, some of which were boxed. Participants could only choose from
the boxed options, provide a confidence rating, and then receive feedback indicating whether
their choice was correct ("Correct" in green or "Wrong" in red), along with the correct answer.
Responses were made using a Cedrus Lumina LS-Pair MRI-compatible ergonomic response
pad, where participants used their left middle finger, left index finger, right index finger, and right
middle finger to select corresponding options. In testing trials, participants selected from four
boxed Swahili options, allowing them to predict the possible answer and experience the
prediction error when feedback was provided. In contrast, during studying trials, the correct
Swahili option was the only one boxed, leaving no opportunity for prediction errors as participants
could only select the correct answer. Among the 90 trials in Phase 3, 72 trials (80%) were
assigned to the testing condition, and 18 trials (20%) to the studying condition. We included more
testing trials because the testing condition involves correct and incorrect trials (and different
prediction errors), which requires enough trials for reliable analysis. The exact number of correct
and incorrect testing trials varied across participants, depending on initial learning. After data
collection, each participant, on average, had 37.75 correct (52.43%) and 34.25 incorrect testing
trials (47.57%) in Phase 3, which was nearly balanced. All word pairs were randomly assigned to
testing and studying conditions, and the trial order was randomized for each participant. After
data collection, the mean confidence rating (in Phase 2) was 0.388 in the testing condition and
0.389 in the studying condition, indicating that initial learning was well counterbalanced between
the two conditions. Additionally, three fixation intervals with optimized jittering were inserted
before the onsets of choices (Jitter 1), confidence rating (Jitter 2), and feedback (Jitter 3). Since
feedback onset was the most critical, Jitters 1 and 3 were longer than Jitter 2. Specifically, Jitters
1 and 3 were sampled from a Poisson distribution with a mean of 4.35 seconds (ranging from 3 to
8 seconds), while Jitter 2 was sampled from a shorter Poisson distribution with a mean of 2.35
seconds (ranging from 1 to 6 seconds).

Phase 4: Final assessment

Two final assessments were conducted to evaluate the learning performance, following the same
procedure as in Phase 2. Administering two assessments was diagnostic to know whether
participants selected the correct answer based on actual knowledge rather than chance.
Specifically, a Swahili answer was considered fully learned only if a participant selected this
correct answer in both assessments, which is unlikely to occur by chance on two consecutive
assessments.

Behavioral data analysis.

A Generalized Linear Mixed Model (GLMM) was employed to analyze the trial-level data. The
predictors in the model included Test vs. Study (Test = 1, Study = 0), Feedback (Positive = 1,
Negative = 0), and confidence ratings (0, 0.33, 0.67, 1). The model incorporated subject-specific
random slopes for predictors and a random intercept[†]. Final assessment accuracy was the
dependent variable, coded as 1 for correct responses in both final assessments (Phase 4 and
Phase 5), 0.5 for one correct response[‡], and 0 for no correct response[§].

Modelling analysis.

Model architecture

Several neural networks incorporating Hebbian learning and/or predictive learning were
developed to fit the behavioral data (Figure 2A). By adjusting the combination of learning
components within the model, we assessed which components were critical for replicating the
testing effect. For instance, if the testing effect could only be replicated when predictive learning
was included, it suggests that predictive learning is essential for the testing effect. Besides, if the
predictive learning model is the best-fitting model, its optimized parameters would be used to
estimate trial-level prediction errors in human data, which would then be applied in the fMRI
analysis to investigate the neural basis of prediction errors.

The model's task was to establish accurate connections between 90 Dutch input units and 360
Swahili output units. Its initial connections were aligned with participants' confidence ratings from
Phase 2 and Phase 3, simulating the initial learning from Phase 1 (10). The exact equation is
shown below:

437
$$w_{ij}^0 = \alpha \times \left(c_{ij}^2 + c_{ij}^3 \right)$$

In this equation, c_{ij}^2 and c_{ij}^3 represent the confidence ratings from Phase 2 and 3, respectively.
The relationship between confidence ratings and initial connections was scaled by parameter α.
In the study condition, participants were given the correct answer directly and could not express
their internal confidence in Phase 3, meaning we had no confidence data for those items in
Phase 3. To address this, we substituted study-trial confidence c_s with the mean confidence
rating from the testing condition:

$$c_s = \frac{\sum_i^I \sum_j^J c_{ij}^t}{N_t}$$

444 for each studied (rather than tested) word.

[†] Statistical results remained unchanged when only a random intercept was added.
[‡] A score of 0.5 means a lucky guess rather than intermediate knowledge between know and not know.
[§] Another binary strategy encoded final assessment accuracy as 1 for correct responses in both final assessments, and 0 otherwise, which led to the same statistical results.

After establishing the initial connections, the model proceeded with testing and studying trials like
Phase 3 in human task. In testing trials, the model selected the correct Swahili translation of a
Dutch word from four options, while in the studying trials, the model could only choose the correct
Swahili answer. The connections between Dutch and Swahili words were updated using Hebbian
learning or/and predictive learning. Hebbian learning strengthened the Dutch and Swahili target
connections in reward contexts (positive feedback trials), while predictive learning adjusted the
connections based on prediction errors.

Regardless of which learning component was applied, the model generated its predictions
according to the following equation:

$$\hat{y}_j = \frac{1}{1 + e^{-s(\sum_i^I w_{ij}x_i - b)}}$$

454 Thus, the activation of each element $\hat{y}_j$ in the output layer was determined by the weighted (w_{ij})
455 sum of the input values x_i, which was then passed through the sigmoid function. Non-option
456 output units always have zero activations in a trial.

457 Hebbian learning, modulated by reward, was implemented as follows:

$$\Delta w_{ij} = \beta \times x_i \times y_j \times r_j$$

458 In this equation, the model updated the weight w_{ij} only when a reward r_j was present (i.e., when
459 feedback was positive). Note that Hebbian learning not modulated by reward would promote
460 learning in testing and studying conditions equally, thus was impossible to explain the testing
461 effect.

462 Hebbian learning incorporated retrieval effort assumption (7) was implemented as follows:

$$\beta_t = \beta_0 + k \times (1 - c_t) \times r_t$$

$$\Delta w_{ij} = \beta_t \times x_i \times y_j$$

463 Here, β_0 represents the minimal learning rate applied in each trial. Building on this baseline, the
464 exact learning rates were inversely modulated by correct confidence ratings (scaled by *k*).
465 Consequently, incorrect testing trials (with wrong confidence ratings) and studying trials (with
466 maximum confidence ratings) relied solely on the minimal learning rate.

467 Predictive learning followed the standard Rescorla-Wagner learning model (56):

$$\Delta w_{ij} = \beta \times x_i \times (y_j - \hat{y}_j)$$

468 Here, the model updated the weight w_{ij} based on the error between the actual feedback y_j and
469 the model's prediction $\hat{y}_j$.

470 After the learning phase, the model completed a final assessment, replicating the procedure used
471 in Phase 4 of the human task. The activations in the output layer were normalized as follows:

$$p_j = \frac{\hat{y}_j}{\sum_n^N \hat{y}_n}$$

472 with the activation level (p_j) of the correct Swahili unit serving as an indicator of the model's
473 accuracy for each trial.

Model fitting

Since the main goal was to replicate human responses in Phase 4, the model's final assessment results were used to fit the human final assessment data, which determined the optimal model parameters. The optimization was conducted by maximizing the log-likelihood function for each participant's data. Parameters α and β were allowed to range from 0 to 1, while s and b were allowed to range from 0 to 10. Additionally, the sum of α and β was constrained to 1, ensuring the relative contribution of initial learning versus Hebbian learning (and/or predictive learning) was accounted for.

Model comparison

Importantly, we developed seven models based on all possible combinations of the three learning components mentioned earlier ($2^3 - 1 = 7$): initial, Hebbian, and predictive learning. An additional model (Model 8) incorporated initial learning and retrieval effort learning. The weighted Akaike information criterion (wAIC; higher means better) was employed to compare the model fits (57).

fMRI data acquisition.

fMRI data were collected with a 3T Prisma scanner system (Siemens), with a 64-channel head coil. A 3D high-resolution anatomic image was obtained using a T1-weighted MPRAGE sequence [flip angle (FA) = 9°; matrix size = 176 × 256 × 256; interpolated voxel size = 1.0 × 1.0 × 1.0mm]. In addition, we acquired a field map per participant, to correct for magnetic field inhomogeneities (TR= 528ms; TE = 7.38ms; FA= 60°). Whole-brain functional images were acquired using a T2p-weighted EPI sequence (TR = 1780ms; TE = 27ms; FA= 66°; matrix size = 54 × 64 × 64; voxel size = 2.5 × 2.5 × 2.5 mm).

fMRI data analysis.

Preprocessing

The fMRI data analysis was conducted using SPM 12 and MATLAB. After converting the raw DICOM data to BIDS format, the first five functional images for each participant were discarded to avoid transient spin saturation effects. The remaining functional images underwent slice timing correction, realignment, normalization, and smoothing. The structural image was co-registered with the mean realigned functional image. Event-related regressors (delta functions) were convolved with the canonical Hemodynamic Response Function (HRF) in the General Linear Model (GLM) to model the BOLD signal.

GLM for Test vs Study

In Test-GLM1, we modeled the choice onsets (correct test, incorrect test, and study) and feedback onsets (correct test, incorrect test, and study) as six main regressors. Here and in all other GLMs, fixation onsets and confidence onsets were always modeled as additional regressors. Beta maps from these regressors generate individual contrasts for group-level analysis (voxel level; False Discovery Rate, FDR corrected $p < 0.05$). First, we contrasted the beta maps of Test vs. Study (0.5 × correct test + 0.5 × incorrect test – 1 × study), Correct test vs. Study (1 × correct test – 1 × study), and Incorrect test vs. Study (1 × incorrect test – 1 × study) during feedback onsets to identify significantly stronger brain activation in test, correct test, and incorrect test conditions (compared to study). Second, the same neural contrasts were applied for choice onsets. Test-GLM2 modeled same regressors as Test-GLM1 but added trial-level confidence ratings as the parametric modulator of (testing) choice onset regressors.

GLM for prediction error

We constructed two general linear models to examine the neural correlates of prediction errors. In
the PE-GLM1, feedback onsets were modeled as a single main regressor, with trial-level (mean-
centered) prediction errors and feedback valence jointly included as parametric modulators of
feedback onsets. Individual beta maps corresponding to the prediction error modulator were
submitted to group-level analysis (voxel level; FDR corrected $p < 0.05$). Brain regions showing
positive activation in the group-level analysis were interpreted as being positively modulated by
prediction error. Neural responses associated with the feedback valence modulator were
examined using the same procedure.

The overlapping active brain regions between the testing and prediction error were defined as
ROIs for PE-GLM2. In this model, feedback onsets associated with different prediction error
levels in the testing condition and in the studying condition (only zero prediction error in this case)
were modeled as separate regressors. To avoid creating regressors for nearly every trial,
prediction errors were rounded to one decimal place. For each participant, we extracted the mean
beta values within each ROI for each prediction error regressor. The relationship between
prediction errors and mean beta values (of each ROI) across all participants was then visualized
in Figure 4.

Back sorting analysis

In the first and second back sorting GLMs (Bsort-GLM1 and Bsort-GLM2), feedback onsets
followed by correct Phase 4 assessment and those followed by incorrect Phase 4 assessment
were modeled as two main regressors. Individual contrast maps (Correct - Incorrect) were
submitted to group-level analysis (cluster level; cluster-forming threshold at $p < 0.005$; cluster-
level significance at FDR-corrected $p < 0.05$). Bsort-GLM3 was constructed in the same manner
for choice onsets.

Acknowledgments

We thank Jonas Simoens, Ruth Krebs, and Filip Van Opstal for useful discussions about the topic
of this study. H.C. received support from China Scholarship Council [CSC202206990008]. C.B.C.
discloses support for the publication of this work from Centro Nacional de Inteligencia Artificial
[FB210017]. The funders had no role in study design, data collection and analysis, decision to
publish or preparation of the manuscript.

References

1.   K. B. McDermott, Practicing Retrieval Facilitates Learning. *Annual Review of Psychology*
72, 609-633 (2021).
2.   H. L. Roediger, A. C. Butler, The critical role of retrieval practice in long-term retention.
Trends in Cognitive Sciences **15**, 20-27 (2011).
3.   H. L. Roediger, J. D. Karpicke, Test-enhanced learning: Taking memory tests improves
long-term retention. *Psychological science* **17**, 249-255 (2006).
4.   B. Jonsson, C. Wiklund-Hörnqvist, T. Stenlund, M. Andersson, L. Nyberg, A learning
method for all: The testing effect is independent of cognitive ability. *Journal of*
Educational Psychology **113**, 972-985 (2021).
5.   T. R. Jonker, H. Dimsdale-Zucker, M. Ritchey, A. Clarke, C. Ranganath, Neural
reactivation in parietal cortex enhances memory for episodically linked information.
Proceedings of the National Academy of Sciences **115**, 11084-11089 (2018).
6.   J. D. Karpicke, H. L. Roediger, Expanding retrieval practice promotes short-term
retention, but equally spaced retrieval enhances long-term retention. *Journal of*
Experimental Psychology: Learning, Memory, and Cognition **33**, 704-719 (2007).
7.   M. A. Pyc, K. A. Rawson, Testing the retrieval effort hypothesis: Does greater difficulty
correctly recalling information lead to higher levels of memory? *Journal of Memory and*
Language **60**, 437-447 (2009).
8.   S. K. Carpenter, E. L. DeLosh, Impoverished cue support enhances subsequent retention:
Support for the elaborative retrieval explanation of the testing effect. *Memory &*
cognition **34**, 268-276 (2006).
9.   S. K. Carpenter, Cue strength as a moderator of the testing effect: The benefits of
elaborative retrieval. *Journal of Experimental Psychology: Learning, Memory, and*
Cognition **35**, 1563-1569 (2009).
10.   H. Chen, C. Hauspie, K. Ergo, C. Buc Calderon, T. Verguts, Predictive learning as the basis
of the testing effect. *Communications Psychology* **3**, 18 (2025).
11.   Y. Zheng, X. L. Liu, S. Nishiyama, C. Ranganath, R. C. O'Reilly, Correcting the hebbian
mistake: Toward a fully error-driven hippocampus. *PLOS Computational Biology* **18**,
e1010589 (2022).
12.   X. L. Liu, R. C. O'Reilly, C. Ranganath, "Chapter Four - Effects of retrieval practice on
tested and untested information: Cortico-hippocampal interactions and error-driven
learning" in Psychology of Learning and Motivation, K. D. Federmeier, L. Sahakyan, Eds.
(Academic Press, 2021), vol. 75, pp. 125-155.
13.   R. Sutton, A. Barto, *Reinforcement learning: an introduction* (MIT, Cambridge, MA,
2018).
14.   E. De Loof *et al.*, Signed reward prediction errors drive declarative learning. *PLoS One*
13, e0189212 (2018).
15.   N. Rouhani, K. A. Norman, Y. Niv, Dissociable effects of surprising rewards on learning
and memory. *Journal of Experimental Psychology: Learning, Memory, and Cognition* **44**,
1430 (2018).
16.   A. Greve, E. Cooper, A. Kaula, M. C. Anderson, R. Henson, Does prediction error drive
one-shot declarative learning? *Journal of Memory and Language* **94**, 149-165 (2017).
17.   R. Daniel, S. Pollmann, Striatal activations signal prediction errors on confidence in the
absence of external feedback. *NeuroImage* **59**, 3457-3467 (2012).

18.   T. Balsdon, M. A. Pisauro, M. G. Philiastides, Distinct basal ganglia contributions to
learning from implicit and explicit value signals in perceptual decision-making. *Nature*
Communications **15**, 5317 (2024).

19.   T. D. Satterthwaite *et al.*, Being right is its own reward: Load and performance related
ventral striatum activation to correct responses during a working memory task in youth.
NeuroImage **61**, 723-729 (2012).

20.   C. B. Holroyd *et al.*, Dorsal anterior cingulate cortex shows fMRI response to internal and
external error signals. *Nature neuroscience* **7**, 497-498 (2004).

21.   N. Eshel, J. Tian, M. Bukwich, N. Uchida, Dopamine neurons share common response
function for reward prediction error. *Nature Neuroscience* **19**, 479-486 (2016).

22.   P. Montague, P. Dayan, T. Sejnowski, A framework for mesencephalic dopamine systems
based on predictive Hebbian learning. *The Journal of Neuroscience* **16**, 1936-1947
(1996).

23.   W. Schultz, P. Dayan, P. R. Montague, A Neural Substrate of Prediction and Reward.
Science **275**, 1593-1599 (1997).

24.   K. D'Ardenne, S. M. McClure, L. E. Nystrom, J. D. Cohen, BOLD Responses Reflecting
Dopaminergic Signals in the Human Ventral Tegmental Area. *Science* **319**, 1264-1267
(2008).

25.   C. B. Calderon *et al.*, Signed Reward Prediction Errors in the Ventral Striatum Drive
Episodic Memory. *J Neurosci* **41**, 1716-1726 (2021).

26.   L. K. Fazio, E. J. Marsh, Correcting false memories. *Psychological science* **21**, 801-803
(2010).

27.   J. Metcalfe, B. Finn, People's hypercorrection of high-confidence errors: Did they know it
all along? *Journal of Experimental Psychology: Learning, Memory, and Cognition* **37**, 437
(2011).

28.   P. Ripollés *et al.*, The Role of Reward in Word Learning and Its Implications for Language
Acquisition. *Current Biology* **24**, 2606-2611 (2014).

29.   T. Verguts, *Introduction to Modeling Cognitive Processes* (MIT Press, 2022).

30.   D. F. Wood, Problem based learning. *BMJ* **326**, 328-330 (2003).

31.   M. Prince, Does Active Learning Work? A Review of the Research. *Journal of Engineering*
Education **93**, 223-231 (2004).

32.   C. Yang, L. Luo, M. A. Vadillo, R. Yu, D. R. Shanks, Testing (quizzing) boosts classroom
learning: A systematic and meta-analytic review. *Psychological Bulletin* **147**, 399–435
(2021).

33.   J. L. McClelland, B. L. McNaughton, R. C. O'Reilly, Why there are complementary
learning systems in the hippocampus and neocortex: insights from the successes and
failures of connectionist models of learning and memory. *Psychol Rev* **102**, 419-457
(1995).

34.   A. Pine, N. Sadeh, A. Ben-Yakov, Y. Dudai, A. Mendelsohn, Knowledge acquisition is
governed by striatal prediction errors. *Nature communications* **9**, 1-14 (2018).

35.   B. Butterfield, J. A. Mangels, Neural correlates of error detection and correction in a
semantic retrieval task. *Cognitive Brain Research* **17**, 793-817 (2003).

36.   J. Metcalfe, B. Butterfield, C. Habeck, Y. Stern, Neural correlates of people's
hypercorrection of their false beliefs. *Journal of Cognitive Neuroscience* **24**, 1571-1583
(2012).

638	37.	B. Butterfield, J. Metcalfe, Errors committed with high confidence are hypercorrected. *Journal of Experimental Psychology: Learning, Memory, and Cognition* **27**, 1491 (2001).
640	38.	T. Seabrooke, C. J. Mitchell, A. J. Wills, A. B. Inkster, T. J. Hollins, The benefits of impossible tests: Assessing the role of error-correction in the pretesting effect. *Memory & Cognition* **50**, 296-311 (2022).
643	39.	M. Watabe-Uchida, N. Eshel, N. Uchida, Neural Circuitry of Reward Prediction Error. *Annu Rev Neurosci* **40**, 373-394 (2017).
645	40.	W. Schultz, Reward prediction error. *Current Biology* **27**, R369-R371 (2017).
646	41.	S. J. Sara, The locus coeruleus and noradrenergic modulation of cognition. *Nature Reviews Neuroscience* **10**, 211-223 (2009).
648	42.	P. T. Ohara *et al.*, Dopaminergic input to GABAergic neurons in the rostral agranular insular cortex of the rat. *Journal of Neurocytology* **32**, 131-141 (2003).
650	43.	M. G. Kutlu *et al.*, Role of insular cortex D_1 and D_2 dopamine receptors in nicotine self-administration in rats. *Behav Brain Res* **256**, 273-278 (2013).
652	44.	N. Gogolla, The insular cortex. *Current Biology* **27**, R580-R586 (2017).
653	45.	E. Hernández-Ortiz, J. Luis-Islas, F. Tecuapetla, R. Gutierrez, F. Bermúdez-Rattoni, Top-down circuitry from the anterior insular cortex to VTA dopamine neurons modulates reward-related memory. *Cell Reports* **42**, 113365 (2023).
656	46.	C. W. Hoy *et al.*, Asymmetric coding of reward prediction errors in human insula and dorsomedial prefrontal cortex. *Nature Communications* **14**, 8520 (2023).
658	47.	J. Metcalfe, M. Vuorre, E. Towner, T. S. Eich, Curiosity: The effects of feedback and confidence on the desire to know. *J Exp Psychol Gen* **152**, 464-482 (2022).
660	48.	K. Ergo, E. De Loof, T. Verguts, Reward Prediction Error and Declarative Memory. *Trends in Cognitive Sciences* **24**, 388-397 (2020).
662	49.	Juliet Y. Davidow, K. Foerde, A. Galván, D. Shohamy, An Upside to Reward Sensitivity: The Hippocampus Supports Enhanced Reinforcement Learning in Adolescence. *Neuron* **92**, 93-99 (2016).
665	50.	A. I. Jang, M. R. Nassar, D. G. Dillon, M. J. Frank, Positive reward prediction errors during decision-making strengthen memory encoding. *Nature human behaviour* **3**, 719-732 (2019).
668	51.	K. Ergo, E. De Loof, C. Janssens, T. Verguts, Oscillatory signatures of reward prediction errors in declarative learning. *Neuroimage* **186**, 137-145 (2019).
670	52.	N. Kornell, M. J. Hays, R. A. Bjork, Unsuccessful retrieval attempts enhance subsequent learning. *Journal of Experimental Psychology: Learning, Memory, and Cognition* **35**, 989-998 (2009).
673	53.	N. Kornell, P. J. Klein, K. A. Rawson, Retrieval attempts enhance learning, but retrieval success (versus failure) does not matter. *Journal of Experimental Psychology: Learning, Memory, and Cognition* **41**, 283 (2015).
676	54.	S. Bertsch, B. J. Pesta, R. Wiscott, M. A. McDaniel, The generation effect: A meta-analytic review. *Memory & Cognition* **35**, 201-210 (2007).
678	55.	S. S. H. Wong, S. W. H. Lim, The derring effect: Deliberate errors enhance learning. *Journal of Experimental Psychology: General* **151**, 25-40 (2022).
680	56.	R. A. Rescorla, A. R. Wagner, "A theory of Pavlovian conditioning: variations in the effectiveness of reinforcement and nonreinforcement" in Classical Conditioning II: Current Research and Theory, A. H. Blake, W. F. Prokasy, Eds. (Appleton-Century-Croft, 1972), pp. 64–99.

684   57.   E.-J. Wagenmakers, S. Farrell, AIC model selection using Akaike weights. *Psychonomic*
685   *bulletin & review* **11**, 192-196 (2004).

Figures and Tables

Figure 1. Experimental procedure (A) and behavioral results (B-C). A. Participants completed a four-phase task to learn 90 Dutch-Swahili word pairs. Phase 1: All word pairs were presented randomly, with each pair displayed for 3 seconds to facilitate initial learning. Phase 2: An assessment without feedback was administered to assess initial learning. In each trial, participants selected the Swahili translation of a Dutch cue from four options and rated their confidence in being correct (Confidence scale simplified for illustration purposes). Phase 3: This phase introduced the Test vs. Study manipulation and prediction errors. In testing trials, participants selected the Swahili translation from four boxed options, while in studying trials, they could only choose the boxed correct answer. After each choice, they rated their confidence and received feedback, including whether they were correct and the correct answer. Importantly, three optimized jitter intervals were inserted between the choice onsets, confidence rating, and feedback to ensure precise timing and minimize expectancy effects. Phase 4: Two final assessments, using the same procedure as Phase 2 (test without feedback), were conducted to evaluate final learning performance. **B.** Behavioral pattern in the current study replicated the robust testing effect. **C-D.** The testing effect was still robust after controlling feedback valance and confidence ratings from Phase 3. Individual data points are represented by the dots; The error bars reflect the standard errors; Confidence ratings were from Phase 3; $p < 0.05$*. N (subjects) = 48.

709
Figure 2. Model architecture (A) and modeling results (B). A. An associative memory neural
network with 90 Dutch input units and 360 Swahili output units was developed to simulate human
learning behavior. The model's initial connections were scaled according to human confidence
ratings from Phase 2 and Phase 3. After initial connections, the model went through testing and
studying trials as in Phase 3 of the human task. The model updated connections via Hebbian
learning during both studying and testing trials. Predictive learning, however, was applied
exclusively during testing trials. Final assessment was conducted as in Phase 4 of the human
task. **B.** The model comparison with wAIC (higher means better) and model simulations
suggested that the model (Model 5) with both initial learning and predictive learning was the best
model. Moreover, only models with predictive learning (Models 3, 5, 6, 7) could replicate the
testing effect. Bottom right panel: Both extremely positive (around 1) and negative prediction
errors (around -1) enhance the final assessment accuracy. The peak point around small positive
prediction errors (around 0.1) was triggered by good initial learning. Individual data points are
represented by the dots; The error bars reflect the standard errors; Confidence ratings were from
Phase 3. N (subjects) = 48.
725
726

Figure 3. Test (vs Study) related neural activations during feedback onsets. A-C: Test (vs Study; A), Correct test (vs Study; B), and Incorrect Test (vs Study; C) all revealed increased neural activation in the VS, insula, and midbrain during feedback onsets. **D**. The test-related activation in the VS, insula, and midbrain were defined as regions of interest (ROIs). The mean activations in these ROIs were high for both correct and incorrect test trials, but low for study trials. Individual data points are represented by the dots; The error bars reflect the standard errors. *N* (subjects) = 48.

Figure 4. Neural signatures of prediction errors. A: The VS, insula, and midbrain activations increase with the prediction errors during the feedback onsets. **B:** Positive feedback elicited stronger neural activations in ACC and PCC, relative to negative feedback. **C:** Testing and prediction errors elicited overlapping neural activations in the VS, insula, and midbrain. **D-F:** The relationship between prediction errors and mean neural activation (across participants) in the VS, insula, and midbrain ROIs (overlapping regions between testing and prediction errors). VS activation tracked signed prediction errors (Panel D), insula activation reflected unsigned prediction errors (Panel E), and midbrain activation showed a better fit with signed prediction errors (Panel F). The error bars reflect the standard errors. **G-I:** Signed or unsigned prediction errors were included into separate general linear mixed models to predict neural activity within the VS, insula, and midbrain regions of interest (ROIs). Signed prediction errors better predicted activation in the VS (Panel G; lower BIC means a better fit) and midbrain (Panel I), whereas unsigned prediction errors better predicted activation in the insula (Panel H). Because the BIC values are large, the y-axes in Panels G-I are truncated to improve visibility. Axis breaks (=) are used to indicate the truncation. *N* (subjects) = 48.

Figure 5: Neural signatures of final assessment accuracy during feedback onsets. A:
Activation in VS (and dorsal striatum), insula, and midbrain during feedback onsets was
associated with final assessment accuracy. **B:** Neural activation related to testing, prediction
errors, and final assessment accuracy overlapped in the VS and insula. **C-D:** The overlapping
regions in the VS and insula were defined as ROIs. Mean activation within these ROIs were
higher during feedback onsets when the subsequent final assessment was correct, compared to
when it was incorrect. Individual data points are represented by the dots; The error bars reflect
the standard errors. *N* (subjects) = 48.

763 **Table 1:** Computational models with different learning components.

Model	Learning components	Parameters	wAIC
1	Initial learning	3	0.016
2	Hebbian learning	3	0.001
3	Predictive learning	3	0.004
4	Initial + Hebbian learning	4	0.008
5	Initial + Predictive learning	4	0.515
6	Hebbian + Predictive learning	4	0.048
7	Initial + Hebbian + Predictive learning	4	0.187
8	Initial + Retrieval effort learning	5	0.221