Complementary roles for hippocampus and anterior cingulate in composing continuous choice

Justin M. Fine[1]*†, Assia Chericoni[1]*, Gabriela Delgado[2], Melissa C. Franch[1], Elizabeth A. Mickiewicz[1], Ana G. Chavez[1], Eleonora Bartoli[1], Danika Paulo[1], Nicole R. Provenza[1], Andrew Watrous[1], Seng Bum Michael Yoo[3], Sameer A. Sheth[1] and Benjamin Y. Hayden[1]

[1] Department of Neurosurgery, Baylor College of Medicine
[2] Department of Neuroscience, University of Minnesota
[3] Institute for Basic Science, Sungkyunkwan University

* Denotes equal contribution

†Corresponding author

Acknowledgements: We thank Paul Schrater, Xaq Pitkow, Jon Pearson, and Scott Linderman for invaluable discussions and insights on solving the controller problems. We thank Jeff Johnston for discussion on neural analysis. We also thank Joshua Adkinson, Raissa Mathura, and Victoria Pirtle for invaluable assistance. This project was supported by NIH grants R01 DA038615, R01 MH125377, U01 NS121472, and R01 MH129439, and by the McNair foundation.

Statement of Conflict: SAS is a consultant for Boston Scientific, Zimmer Biomet, Neuropace, Koh Young, Abbott; Co-founder, Motif Neurotech. None of the authors have any competing interests to declare.

34   **ABSTRACT**

Naturalistic, goal directed behavior often requires continuous actions directed at

dynamically changing goals. In this context, the closest analogue to choice is a strategic

reweighting of multiple goal-specific control policies in response to shifting

environmental pressures. To understand the algorithmic and neural bases of choice in

continuous contexts, we examined behavior and brain activity in humans performing a

continuous prey-pursuit task. Using a newly developed control-theoretic decomposition

of behavior, we find pursuit strategies are well described by a meta-controller dictating a

mixture of lower-level controllers, each linked to specific pursuit goals. Examining

hippocampus and anterior cingulate cortex (ACC) population dynamics during goal

switches revealed distinct roles for the two regions in parameterizing continuous

controller mixing and meta-control. Hippocampal ensemble dynamics encoded the

controller blending dynamics, suggesting it implements a mixing of goal-specific control

policies. In contrast, ACC ensemble activity exhibited value-dependent ramping activity

before goal switches, linking it to a meta-control process that accumulates evidence for

switching goals. Our results suggest that hippocampus and ACC play complementary

roles corresponding to a generalizable mixture controller and meta-controller that

dictates value dependent changes in controller mixing.

INTRODUCTION

Our understanding of how the brain implements reward-based decisions

(including foraging) is largely based on studies of discrete choices over static options.

Yet many of the decision problems organisms face in the real world are both continuous

and interactive (Gordon et al., 2021; Maseli et al., 2023; Yoo et al., 2021). Consider a

predator pursuing fleeing prey (Fabian et al., 2018; Fine et al., 2024; Yoo et al., 2020).

At each moment, the predator can choose a trajectory from a continuous set of actions;

across time, the predator must continuously adjust its actions to move closer to its goal,

integrating feedback and predictions of future states. When there are multiple prey, the

predator must also decide whether and when to adjust which goal is pursued (Cisek,

2012; Gomi and Kawato, 1993; Sridhar et al., 2021). Decision-makers may even blend

their pursued goals, allowing them to hedge against the risk of needing large course

corrections if they change their mind (Gallivan et al., 2016; Haith et al., 2015; Yang et

al., 2022).

In continuous choice with multiple goals, including prey pursuit, the value

landscape for choosing the best goal has multiple stable states because different

control actions are required for distinct goals. Therefore, choosing the best goal at any

moment requires an action controller that can solve a non-trivial and nonlinear goal

optimization problem (Bertsekas, 1996; Sutton and Barto, 1998). While such nonlinear

controllers are theoretically attainable, a new nonlinear controller would have to be

learned for each new set of goals experienced, and could not be generalized outside

the goals it was designed around (Theorodou et al, 2010). A solution to this problem is

the usage of compositional control, which builds on modern control theory, artificial

intelligence and robotics (Dvijotham and Todorov, 2012; Peng et al., 2019; Haarnoja et

al., 2024). Optimal control theory has shown that the nonlinear control needed for

solving continuous multi-goal decisions can be approximated via composition of

individual linear controllers (Dvijotham and Todorov, 2012; Gomez et al., 2014; Pan et

al., 2015; Peng et al., 2019; Wolpert and Kawato, 1998). In this framework, each

individual controller is focused on resolving the best actions for a single goal, and the

system's behavior reflects a blended weighting of multiple controllers. A key benefit of

INTRODUCTION

Our understanding of how the brain implements reward-based decisions

(including foraging) is largely based on studies of discrete choices over static options.

Yet many of the decision problems organisms face in the real world are both continuous

and interactive (Gordon et al., 2021; Maseli et al., 2023; Yoo et al., 2021). Consider a

predator pursuing fleeing prey (Fabian et al., 2018; Fine et al., 2024; Yoo et al., 2020).

At each moment, the predator can choose a trajectory from a continuous set of actions;

across time, the predator must continuously adjust its actions to move closer to its goal,

integrating feedback and predictions of future states. When there are multiple prey, the

predator must also decide whether and when to adjust which goal is pursued (Cisek,

2012; Gomi and Kawato, 1993; Sridhar et al., 2021). Decision-makers may even blend

their pursued goals, allowing them to hedge against the risk of needing large course

corrections if they change their mind (Gallivan et al., 2016; Haith et al., 2015; Yang et

al., 2022).

In continuous choice with multiple goals, including prey pursuit, the value

landscape for choosing the best goal has multiple stable states because different

control actions are required for distinct goals. Therefore, choosing the best goal at any

moment requires an action controller that can solve a non-trivial and nonlinear goal

optimization problem (Bertsekas, 1996; Sutton and Barto, 1998). While such nonlinear

controllers are theoretically attainable, a new nonlinear controller would have to be

learned for each new set of goals experienced, and could not be generalized outside

the goals it was designed around (Theorodou et al, 2010). A solution to this problem is

the usage of compositional control, which builds on modern control theory, artificial

intelligence and robotics (Dvijotham and Todorov, 2012; Peng et al., 2019; Haarnoja et

al., 2024). Optimal control theory has shown that the nonlinear control needed for

solving continuous multi-goal decisions can be approximated via composition of

individual linear controllers (Dvijotham and Todorov, 2012; Gomez et al., 2014; Pan et

al., 2015; Peng et al., 2019; Wolpert and Kawato, 1998). In this framework, each

individual controller is focused on resolving the best actions for a single goal, and the

system's behavior reflects a blended weighting of multiple controllers. A key benefit of

compositional control is that a shared weighting mechanism can be generalized across

environments with different goal-specific controllers (Gomez et al., 2014; Lake and

Baroni, 2018; Matsuo et al., 2022; Todorov, 2009). A compositional controller also

requires a separate meta-controller, which monitors both the environmental context and

internal shifts of goal priorities to determine the need for changes in the blending of

individual controllers. Understanding if and how the brain might implement a flexible,

compositional control strategy is crucial, as it can elucidate the neural mechanisms

enabling humans to arbitrate between competing goals in dynamic pursuit-like

environments.

One implication of the blending hypothesis is that the brain should compute and

explicitly represent the goal-specific policy weighting. Brain regions coding for a policy

weighting should have preferential access to information needed for creating mappings

of goals (e.g., goal distance) and goal specific control policies, and be able to compose

them together (Kurth-Nelson et al., 2023; Whittington et al., 2022). We hypothesized

this goal policy weighting would be present in the hippocampus, given its demonstrated

role in encoding goal related information in cognitive maps (Behrens et al., 2018;

Wikenheiser and Schoenenbaum, 2016). Indeed, a good deal of evidence links the

hippocampus to encoding of goal specific information (McNaughton and Bannerman,

20254; Nyberg et al., 2022; Wikenheiser and Redish, 2015), including the coding of

goal-directed actions (Zutshi et al., 2025), goal distance or goal heading (Chadwick et

al., 2015; Howard et al., 2014; Sarel et al., 2017; Ormond and O'keefe, 2022), and

place-like coding modulated by goals (Muhle-Karbe et al., 2023; Jercog et al., 2019).

The hypothesis that the hippocampus represents the composition of controllers is

further supported by previous theoretical and empirical work indicating the hippocampus

forms maps and representations of novel objects or action policies through

compositional coding (Barron et al., 2013; Bakkermans et al., 2025; Garvert et al., 2023;

Kurth-nelson et al., 2023; Schwartenbeck et al., 2023; Whittington et al., 2020). This

capacity for compositional coding and mapping of goal related information suggests that

the hippocampus is ideally positioned to combine goal specific controllers during

continuous choice.

The second implication of our hypothesis is the brain must exert meta-control
over the policy blending strategies. The meta-controller must monitor and regulate
lower-level control processes and shifts in goals by tracking changes in the task
environment (Eppinger et al., 2021; Musslick et al., 2024; Yeung and Summerfield,
2012). A wealth of evidence links the anterior cingulate cortex (ACC) to monitoring and
regulation processes across a variety of contexts (Alexander and Brown, 2011; Akam et
al., 2021; Kolling et al., 2016; Sarafyazd and Jazayeri, 2019; Shenhav et al., 2013). It is
also involved in high-level response strategy selection (Kennerley et al., 2006; Sheth et
al., 2012; Shima and Tanji, 1998). During decisions, ACC often shows a clear ramping
of activity leading up to choices and strategy switches, possibly reflecting an
accumulation of evidence for computing decisions (Balewski et al., 2023; Blanchard et
al., 2015; Hayden et al, 2011; Kane et al., 2022; Sarafyazd and Jazayeri, 2019; Voloh
et al., 2023). Building on these findings, we hypothesize that ACC operates as a meta-
controller in the context of continuous and multi-goal choice; we therefore predicted that
switches in goals should be preceded by ACC ramping signals that terminate at the time
of the switch.

To test these predictions, we examined neural activity in the human brain during
performance of a joystick-controlled interactive prey-pursuit task (**Figure 1A**). We
developed a novel mixture of controllers model that allowed us to infer subjects'
moment-to-moment blending of different prey specific controllers. Examining goal-
switching decisions, we found that hippocampus population dynamics closely mirrored
the states of the policy mixing behavioral dynamics. ACC showed ramping activity that
predicted these decisions before they occurred, with ramping dynamics that depend on
the value of switching goals. These results demonstrate that hippocampus and ACC
have complementary roles corresponding to implementation of continuous choice
strategies and meta-control, respectively.

138   **RESULTS**

Thirteen human participants performed a joystick-controlled prey-pursuit task

(**Figure 1A-D,** Chericoni et al., 2025). On each trial, the participant used a joystick to

move an avatar freely in a two-dimensional area to pursue fleeing prey

(**Supplementary Video**). On each trial, there were two prey that evaded the participant.

The prey were specified by different colors, indicating their value which changed along

the dimensions of reward and speed (**Figure 1A-B**). Participants completed trials with

three different combinations of prey value, ranging from no difference to a large

difference in value. As the difference in prey value increased, the trials also took longer

(as anticipated, because the larger value prey moved faster, increasing the difficulty,

Figure 1D). Capture rate performance was high; the mean across-participant capture

rate was 85.3% (78.4% - 92.1%; **Figure 1E**).

Inferring continuous choice strategies

In discrete decision-making tasks, assessing a participant's choice between

options is trivial. In continuous decision contexts, inferring a participant's moment-to-

moment decision strategy is quite a bit more challenging. We need to estimate how their

control signal (in this case, avatar velocity) is driven by one or more goals, in this case,

by either a single prey or mixture of prey. One difficulty with identifying these mixing

strategies is that participants may use a variety of low-level control strategies for

pursuing individual targets. For example, participants may opt to minimize positional

error, velocity error, integral of position error, estimated future position error, or any

combination of these. The control strategy is unknown to the experimenter. Therefore,

we must estimate both the participant's per-target control strategy and the mixture of

controllers.

The problems of estimating low-level controllers and target mixing are

interrelated. To identify the target mixing at every point in time, we must estimate both

the participant's target specific controller and the mixture weight that combines these

target controllers (W_t; see **Methods** eq. 2-3). For the case of two possible pursuit

targets, W_t encodes the continuum from fully pursuing one target ($W_t = 0$), to fully mixing

targets (W_t = 0.5), to fully pursuing the other target (W_t = 1). W_t determines how much

each target in our task contributes to the participant's momentary control signal. If

instead of estimating the controllers, however, we only used current position error

controllers in tandem with estimating W_t, this would provide incorrect estimates of W_t if

they are using a different control strategy (e.g., current and future position error; **Figure**

1F). To overcome this problem, we developed a model-based decomposition that

leverages optimal control and compositionality theory to estimate these controllers and

their mixtures (Todorov, 2009).

For each trial, we estimated W_t by modelling the participant's joystick control

using a second-order linear dynamic system (i.e., acceleration; see **Methods**). This

process involved optimizing separate controller gains for each target simultaneous with

optimizing W_t. We repeated this process for all types and combinations of controller

classes (see **Methods**), ranging from the usage of current position errors between

cursor and target, to integral error, or one step ahead future position error (see

Methods for a list of all classes). We used a Bayesian model averaging framework to

recover the per trial estimate of W_t. This involved weighting W_t for each controller class

combination by the posterior probability of that fit.

To test the validity of our approach, we performed model validation analysis of

ground-truth simulated W_t signals. We could recover W_t with high fidelity, and

independent of controller classes or W_t complexity, quantified by a linear regression of

the predicted and ground-truth W_t (r^2 = 0.87 ± 0.08; **Table S1**). We also found W_t is

largely unrelated to subject speed (r = 0.14 ± 0.18, p =0.38), relative distance (r = 0.11±

0.06, p=0.53) or relative speed (r = 0.09 ± 0.02, p=0.25) of the two prey across

subjects. Importantly, these results indicate the controller mixing is identifiable and is a

unique construct that is not just a reflection of a singular state variable such as relative

distance.

We compared the fit of the blended controller model to participant behavior

against two other potential strategies: (1) all-or-none target selection (i.e., winner-take-

all) or (2) a blending strategy that mixes target input (e.g., relative position to subject)

and uses a single controller. Notably, the all-or-none strategy is nested within the

blending model, but the input blending model is distinct (**Figure 1G-I**, see proof in **S2**).

Using simulations and ground-truth model recovery, we found a low confusion rate

across models (correct classification for blending: 93.2%, all-or-none: 85.8%, and input

mixing: 89.2%). We next evaluated fits of participant behavior with a Bayesian model

comparison, with per trial and per subject model fits. The model posterior probabilities

were used to adjudicate between the propensity of each strategy type. Model

comparison indicated all subject's behavior was best captured by a blended controller

strategy (84% $\pm$ 8%, posterior model probability across subject; **Figure 1I**).

We used the recovered W_t trajectories to understand participants' pursuit

behavior (example in **Figure 1K**). To visualize W_t behavior, we plot their subject

averaged distributions across different levels of reward difference between prey,

including a small and large difference (**Figure 1J**). If we define the pursuit of the more

rewarding targets as moments when $W_t > 0.85$ and pursuit of the lower reward targets as

moments when $W_t < 0.15$, we see the expected behavior. Participants spent a larger

portion of time pursuing the more rewarding target in the small (t = 16.12, $p < 0.0001$)

and large (t = 15.01, $p < 0.0001$) reward difference trials. The majority of the time

(55.4%), pursuit behavior was spent in a blended state ($0.15 < W_t < 0.85$). In summary,

participants pursued the more rewarding target more often as the reward difference

increased but generally hedged their actions between controllers, acting in accordance

with a softmax weighted decision strategy.

Multiplexed states underlie goal switching

To determine which factors drove switches between targets, we first identified

target switches (**Methods**), e.g., time series of switching from $W_t < 0.15$ to $W_t > 0.85$

(**Figure 1K**). We used a hierarchical Bayesian logistic model to determine factors that

lead to changes in propensity for target switching (% change in odds of switching;

Figure 1L). Differences in the prey value increased the likelihood of switching

dramatically (85.9%). The speed at which the switched-to target was moving away from

the participant also predicted switching (49.2%), as well as the elapsed trial length

(19.7%). Switching behavior was also driven by a complex interaction between the

distance from the abandoned target and differences in prey value (34.2%). This pattern

supports the idea that participants switched as the currently pursued prey got farther

away, particularly with larger differences in prey value (**Figure 1L**), alongside other

complex predictor interactions.

Figure 1. | **Continuous pursuit task and control choice model.** (**A**) Schematic of pursuit taks
design. Prey were displayed as colored squares that denote their reward if caught and maximum
speed. Participants' avatar was displayed as a yellow circle, with avatar velocity controlled by the
joystick position. (**B**). Each row represents a different trial type where the prey reward differed
(three in total). Participants also played trials in which prey of the same reward level were
presented across all three unique prey types. (**C**). The left and right column show example
movement traces from two different trial types performed by a participant. (**D**). Kernel
smoothing density (per participant) of the time it took to capture a prey in trials with a small prey
reward difference (left column) and large reward difference (right column). (**E**). Boxplot
showing the capture rate median was higher for small prey reward difference (difference = 2)
compared to large reward differences (difference = 4). This results from the larger difference
including faster prey. (**F**). The top and bottom cartoons are designed to illustrate how the control
blending variable W_t for a single time point is dependent on the type of low level control policies
being deployed. The Blue and green arrows show theoretical control signals for the participant
directed towards each potential prey. The top and bottom plots are examples of if the participant
only used a current position control strategy or a current and future position control strategy,
respectively. What is conveyed is that, even though both scenarios could have the same
measured control signal (red arrow), changes to the underlying policy type are interrelated to the
level of W_t, necessitating estimation of both. (**G**). Graphical model describing control blending
model. Shaded circles are latent parameters (W) or variables (u_1,u_2 = target specific controls).
Transparent circles are measured variables, including inputs (x_1,x_2) and participant control
signals ($u^\wedge$). (**H**). Graphical model describing the input blending model. (**I**). Posterior bayesian
model probability of models fit to subject data for control blending, input blending, and winner-
take all models. The control blending was a significantly better fit across participants ($p < 0.001$
denoted by *). (**J**). Kernel smoothing density showing the distribution of controller blending (W_t)
for small (bottom) and large (top) prey reward difference. The key explains that as W_t is greater
than 0.5, they are putting more controls to pursuing the larger reward target and vice versa. (**K**).
An exemplar set of time series from a single trial, showing the independence of fit W_t (top plot),
relative prey distance to participant (middle plot), and relative prey to participant speed (bottom
plot). The green arrow in the top plot of W_t shows how we found target switches as points where
W_t crossed 0.5. (**L**). Coefficients from hierarchical GLM predicting % change in odds of
switching prey (significant predictors denoted by * with posterior probability > 0.95).
265

Controller blending is differentially encoded in ACC and hippocampus neurons

To examine the neural basis of continuous choice and W_t, we recorded neurons

in the hippocampus (n=314 neurons; **Figure 2A**) and anterior cingulate cortex (ACC,

n=149 neurons; **Figure 2A**). We characterized neural tuning to W_t by fitting neuron

spikes with a Poisson generalized additive model (**Methods; Figure 2B**) that uses a

spline basis to estimate the tuning curves to W_t (**Figure 2C**), alongside auxiliary task

parameters (e.g., relative prey value, relative prey distance, relative prey speed, avatar

speed, trial time elapsed). We found neurons were tuned linearly to W_t in both

hippocampus (25.5%; **Figure 2D**) and ACC (15.8%; **Figure 2D**). We also found a

substantial portion of neurons exhibiting nonlinear mixing of W_t with relative prey value

in hippocampus (31.2%; **Figure 2D-E**) and ACC (46.1%; **Figure 2D-E**). Besides W_t, we

also found neurons tuned to all the auxiliary variables (**Figure 2D**; binomial test was $p <$

0.01 for all variables in both regions).

An important question is whether the hippocampus and ACC differ in terms of

their population tuning distribution to W_t. To compare how the hippocampus and ACC

represent W_t, we used fisher information (see **Methods**) because it quantifies how well

a neural tuning distribution can discriminate small changes in W_t. For example, if a

population is chiefly concerned with the value of a pursuit strategy, the fisher

information will be skewed toward certain W_t values (e.g., pursuing higher-value prey).

Conversely, a more similar fisher information around low and high W_t indicates a more

balanced representation of pursuing different prey. By comparing fisher information

across low and high W_t values, we can pinpoint whether each brain region's tuning to

W_t is more directed at coding for pursuit value (skewed fisher information) versus

faithfully coding for W_t (similar low and high fisher information).

We first visualized the population tuning to W_t using a non-negative matrix

factorization for dimensionality reduction (**Figure 2F**). Inspection of the hippocampus

components suggests a similar population tuning to low ($W_t < 0.15$) and high W_t ($W_t >$

0.85; **Figure 2F**), while ACC components point to a coding skewed towards high value

prey ($W_t > 0.85$; **Figure 2F**). We next quantify this by examining fisher information in

separate permutations test for each of the low and high W_t levels, and then comparing

the levels for differences and equivalences. Confirming visual intuition (**Figure 2F**),

there was significant fisher information in the hippocampus for W_t (**Figure 2E**) linked to

low (permutation test, $p < 0.005$) and high value prey (permutation test, $p < 0.005$), but

the information for these two W_t levels was similar (equivalence test, both $p < 0.05$).

Considering ACC (**Figure 2E**), we found evidence for W_t information at high prey levels

(permutation test, $W_t > 0.85$, $p < 0.001$), and significant difference between these low

and high prey reward levels (permutation test, $p < 0.005$). The hippocampal distribution

of coding W_t similarly for low and high value prey is consistent with the idea that it

implements a policy blending code. In contrast, ACC's skewed representation towards

high value prey suggests it may be involved in regulating the value of a pursuit blending

strategy.

Figure 2. | **Neurons in the hippocampus and ACC are differentially tuned to W_t.** (**A**).
Recording sites for the Hippocampus (top) and ACC (bottom) for 13 patients. (**B**). Diagram of
Poisson generalized additive model (GAM) used to model tuning curves with spline bases. (**C**).
Exemplar tuning curves to W_t for both hippocampus (left) and ACC (right). (**D**). The percent of
neurons tuned to each variable for hippocampus (left) and ACC (right), estimated with the GAM.
(**E**). Example neuron tuning curve and fit tuning from GAM (dashed line) that exhibited
nonlinear mixed selectivity between W_t and Δ reward, for both hippocampus (left) and ACC
(right). (**F**). Non-negative matrix factorization components showing low-dimensional tuning
bases to W_t for hippocampus (left) and ACC (right). The units are normalized spikes/s. (**G**).
Cross-validated Fisher information with mean (black line) and standard error (blue shading).

Permutation distribution with 95% confidence intervals are the gray shading. Significant
information is shown per bin with an asterisk.
320

Hippocampal dynamics track controller blending

If a brain region encodes the controller W_t then neural population dynamics
should exhibit a close parallel to behaviorally derived W_t dynamics (Khona and Fiete,
2022). In addition, if the neural coding of W_t is used to compose controllers, the neural
population should convey a linear readout of W_t that is at least partially independent of
different reward prey combinations. To assess whether neural dynamics encode the W_t
dynamics, we aligned neural activity to target switches because the W_t trajectory during
target switches follows a canonical sigmoidal-like pattern (**Figure 3A**). This sigmoidal W_t
provides a template to assess whether neural population dynamics track W_t. To quantify
the similarity in neural and W_t dynamics, we decomposed the neural populations aligned
to target switches using demixed principal components analysis (dPCA; Kobak et al.,
2016), and did so separately for ACC and hippocampus. The decomposition was
designed to separate dynamics from two types of switches, switches from the low to the
high-value target and vice versa (see **Methods**). We visualized the dynamics by
projecting the population activity for each area onto the top dPCA component related to
the controller W_t and projected held-out test trials on the top component to quantify
linearly decodable information about W_t (see **Methods**).

We found the hippocampus had significant linearly decodable information about
W_t (permutation test; $p < 0.01$) during the target switch. The top dPCA component for W_t
explained 16.2% of the variance of the hippocampus population activity. Visual
inspection of the hippocampal projection showed its neural dynamics closely mirrored
the sigmoidal W_t trajectory predicted by behavior (**Figure 3C**). We also found a
significant interaction of reward difference and W_t that accounted for 4.89% of
population variance (**Figure 3B**). This suggests hippocampus populations directly track
how controllers are mixed with a generalizable (linear) code.

We also found linearly decodable W_t related information in ACC during target
switches (permutation test; $p < 0.01$; **Figure 3D**). The top dPCA component for W_t
explained 10% of the variance of the ACC population activity (**Figure 3B**). Visually

examining the ACC dynamics indicates W_t information only became available 150 ms

after the switch onset, then hit a peak again close to the target switch offset (**Figure**

3D). These results are more consistent with ACC potentially driving the switch decision

itself and monitoring the decision progress, rather than directly tracking W_t. Together,

the combined hippocampus and ACC results indicate they engage in distinct processes

that relate to shifting weighting strategies and versus implementing controller weighting,

respectively.

The dPCA also indicated substantial condition-independent modes (CIM) in both

brain areas. The CIMs explained 21% and 24% (**Figure 3B**) variance of population

activity in hippocampus and ACC dynamics, respectively. Visually examining the CIMs

in both hippocampus (**Figure 3E**) and ACC (**Figure 3F**) reveal dynamics that

monotonically increase during the time-course of the target switch. While the origins of

these CIM dynamics are unclear, their profiles indicate distinct profiles for tracking the

progression of switch decisions between hippocampus and ACC.

Figure 3.| **Low-dimensional controller blending dynamics during goal switch. (A).**
Controller blending dynamics extracted during target switches (**Methods**) for a single
participant. Orange traces are switches from a high to low value prey, and green traces are
switches from low to high value prey. (**B**). dPCA percent variance of each task factor for each
area. (**C**) Hippocampus projection onto top dPCA component for blending weight factor. Gray
shaded bars mark the median timing of the onset and offset of the target switch. Black lines show
time points of significant decoding. (**D**). ACC projection onto top dPCA component for blending
weight factor. Same format as (**C**) (**E**). Hippocampus projection onto top dPCA component for
condition independent factor. (**F**). ACC projection onto top dPCA component for the condition
independent factor.

Neural ramping predicts goal switching

Previous studies examining discrete decisions indicate ACC population ramping

signals are predictive of the onset of decisions (Balewski et al., 2023; Sarafyazd and

Jazayeri, 2019). Building on these findings, we hypothesized that ACC may also play a

role in driving target switch decisions exemplified by ramping signals coinciding with the

target switch onset (**Figure 4A**), while no such ramping should appear during time

windows without switches. To compute the ramping, we adopted an approach applied

previously in perceptual decision making that uses a linear support vector machine

(SVM; Steinemann et al., 2024). We built separate SVMs for hippocampus and ACC

activity time-locked to the onset of target switch decisions. The SVMs were trained to

predict whether a target switch will happen within the next 100 ms (**Methods**), with

separate SVMs for switches going low to high value targets and vice versa.

Examining time-resolved decoding in the hippocampus indicated target switches

could be decoded in both switch directions (permutation test $p < 0.05$; **Figure 4B**).

Importantly, however, this information only became significantly decodable after the

onset of the target switch (>200 ms after switch onset; **Figure 4B**). Target switch

decoding was also significant in the ACC (permutation test $p < 0.05$; **Figure 4C**). We

found decoding accuracy in ACC starts to ramp up around 100 ms before the switch

onset and peaks around the switch onset, providing support for the hypothesis that ACC

ramping predicts target switches (**Figure 4C**). However, these target switches were only

decodable in ACC when going from a high to low value target. The differences in timing

of decoding between areas were confirmed by examining the time lag of peak decoding

between areas (**Methods**). We found they were different using a permutation test ($p <$

0.05), with ACC peak ramp decoding occurring approximately 195 ms (± 27 ms) earlier

than hippocampus.

Previous studies of the neural decision-making processes often find ramping

profiles at the single neuron level (e.g., Gold and Shadlen, 2007; Kiani et al., 2014; Luo

et al., 2024). Therefore, we asked whether the population ramping profiles we found

above were also evident in clusters of single neurons. We used a method that combines

k-means clustering with linear dynamic systems, which allows us to cluster based on

the dynamics (**Methods**). The number of clusters were optimized (silhouette score)

separately for hippocampus and ACC, and only clusters exhibiting significant selectivity

for whether a target switch occurred were retained using a permutation test.

This process yielded two clusters for the hippocampus (both permutation tests, p

< 0.01; **Figure 4D-E**). Visually examining their temporal properties, we find that cluster

one (C1) recapitulates what we found in population decoding (**Figure 4D**). Specifically,

this cluster of neurons reflects selectivity to target switches after the onset rather than

ramping up to the decision point (time = 0). Examining cluster two (C2) suggests it

closely tracked controller W_t rather than ramping, as well (**Figure 4D**). Examining ACC

clusters (all permutation tests, $p < 0.01$; **Figure 4F-G**), we found cluster one (C1)

neurons exhibit a ramp up and down time-locked with the target switch onset (**Figure**

4F). The other two clusters (C2 and C3; **Figure 4F**) exhibited selectivity to target

switches but neither exhibited the same ramping profile as cluster one. Together, these

results indicate that ACC exhibits a ramping that signals target switch decisions,

implicating it in driving decisions to change targets and reweight control policies. The

specificity of the ACC ramping to different switch conditions further indicates this

decision process is sensitive to the value of the target switch, rather than being a

generic decision signal.

Figure 4. | Ramp decoding subspaces signal changes of mind. (A). Graphical depiction of our predicted ramping dynamics expected from choice accumulation, which should preempt the choice and peak around switch onset (left), versus ramping that is postdictive and describes target switches after completion. (**B**). decoding accuracy for hippocampus time locked to switch onsets, with bars overlaid denoting significant decoding time-points ($p < 0.05$) with a permutation test (1000 permutes), and shaded error bar showing the 5th to 95th percentile of the null distribution. Different colored lines represent decoding accuracy for the different switch conditions. (**C**). decoding accuracy for Hippocampus, with the same format as (**C**). (**D**). Mean cluster sorted firing rate acquired from hippocampus time locked to switch onset. (**E**). Hippocampus z-scored cluster selectivity to target versus no-target switch trials, separated for high to low value (left column) and low to high value target switches (right column). (**F**). Mean cluster sorted firing rate acquired from ACC time locked to switch onset. (**G**). ACC z-scored cluster selectivity to target versus no-target switch trials, separated for high to low value (left column) and low to high value target switches (right column).

DISCUSSION

Decision-making in continuous contexts poses multiple interrelated control

problems (Merel et al., 2019; Yoo et al., 2021; Burge and Bonnen, 2025). We must

combine dynamic feedback and predictions of future target states to decide which goals

to pursue and how to pursue them. Here, we identified the algorithmic and neural basis

of these processes by examining human behavior in a multi-prey pursuit task. We

developed a control-theoretic model that we used to identify goal pursuit decisions that

underlie moment-to-moment actions. We find that control is parsimoniously explained

as continuously composing low-level, goal-specific control policies. A key benefit to

using compositional control is that it provides an efficient neural mechanism for

generalizing decision strategies across novel environments (Driscoll et al., 2024;

Johnston et al., 2024; Sandbrink et al, 2024); the challenging problem of learning

specific controllers for each combination of rewards thereby becomes simplified to a

compositional solution. For example, when novel combinations of familiar prey are

encountered during pursuit, there is no need to learn a new set of controllers, as

existing ones can be readily combined. More strikingly, this compositional approach

supporting pursuit parallels modern solutions for training AI agents and robots to learn

generalizable complex and skilled behavior (Haarnoja et al., 2018; Matsuo et al., 2022).

Our modeling approach opens the door to understanding a wide range of

naturalistic behaviors not well captured by standard approaches (Pearson et al., 2014;

Yoo et al., 2021) such as cooperative hunting or any situation in which continuous

behavior involves the choice between multiple, competing goals. Previous studies have

used unsupervised and clustering methods to identify behavioral motifs in naturalistic

behavior (Anderson and Perona, 2014; Calhoun et al., 2019; Voloh et al., 2023;

Weinreb et al., 2024; Wiltschko et al., 2015). While these studies have been useful for

behavioral parcellation, their focus has been on overt and discrete behavior states (e.g.,

turning). Nonetheless, these approaches remain largely agnostic to the neural

implementation of an agent's internal cognitive states, such as the hierarchical choice to

switch between states and which mixture of goals they are pursuing. While

unsupervised methods may aid in finding clusters of overt behavior, we find that

uncovering the moment-by-moment subject choice requires positing task- and theory-

driven constraints on how the subjects might solve the problem (Kwon et al., 2020).

Such a finding indicates that understanding ethological, high-dimensional behavior must

go beyond simply categorizing discrete behavioral motifs.

Using our modeling, we found neural results that align with and extend the theory

that the hippocampus implements a cognitive map (Behrens et al., 2018; O'keefe and

Nadel, 1979; Behrens). The cognitive map theory posits that the hippocampus creates

structured representations of the world and does so by composing and binding

individual basis elements (Kurth-Nelson et al., 2023; Whittington et al., 2022). Previous

studies have focused on hippocampal compositions over visual scene construction

(Schwartenbeck et al., 2023), spatial information (Hoydal et al., 2019), or novel concept

compounds (Barron et al., 2013). We extend these findings by showing the

hippocampus also encodes compositions that bind goal-specific control policies.

Specifically, we found that low-dimensional (dPCA) hippocampal dynamics follow a

general and compositional code that can be used to combine different prey-specific

controllers. Thus, these results point to a role of the hippocampus in forming both maps

of the world and goal-directed actions (Zuthsi et al., 2025).

Based on the known involvement of the ACC in cognitive flexibility and decision-

making, we reasoned here that it serves the crucial role of driving switching of goals and

policy reweighting during continuous choice. In support of this, we found ACC

population ramping activity predicted an impending target switch. This pattern aligns

with a large literature demonstrating that ACC accumulates evidence for strategic shifts

in decision-making or rule application (Hayden et al., 2011; Johnston et al., 2007;

Kennerly et al., 2006; Kolling et al., 2012; Sarafyazd and Jazayeri, 2019; Shenhav et al.,

2016). However, our results also show this ramping switch signal is dependent on the

value of switching goals, a finding in line with previous studies and theories linking ACC

to integrating cost-benefit information into decisions (Amiez et al., 2007; Friedman et al.,

2015; Shenhav et al., 2016). A possible explanation of our result is that abandoning a

high value versus low value prey represents decisions with different values and costs,

thus eliciting different ramping signals. The implication is ACC is not merely signaling

movement transitions but is integrating decision variables. This integration likely

involves weighing the cost and benefits of switching targets, aligning with foraging

models (Stephens & Krebs, 1986; Hayden et al., 2011; Kane et al., 2022). Such cost-

benefit decisions could also include computing the expected value of persistence and

control for a current goal (Blanchard et al., 2015; Kolling et al., 2012 ; Shenhav et al.,

2016). Our work extends this role of ACC as a value driven meta-controller to the realm

of continuous choice.

More broadly, our results are consistent with a network where hippocampus and

ACC play complementary roles in ethological decisions like prey pursuit and foraging.

ACC has been a key consideration in previous studies of foraging because it integrates

information from regions coding for reward and environment information and is

associated with choosing alternative options (Kolling et al., 2016; Tervo et al., 2014).

This indicates ACC is concerned with representing decision control signals that are

related to the value of choices. Consistent with this, we found ACC neural tuning to

policy blending was skewed towards high value prey. Such a higher-order control signal

is useful for driving changes in low-level control blending but may be distinct from the

source implementation of online goal blending (Fine et al., 2024). Our results point to

the hippocampus as a node responsible for directly implementing the continuous

blending. In this complementary network, ACC signals changes to controls while

hippocampus represents the control blending in an unbiased manner.

REFERENCES

Akam, T., Rodrigues-Vaz, I., Marcelo, I., Zhang, X., Pereira, M., Oliveira, R. F., Dayan, P., & Costa, R. M. (2021). The anterior cingulate cortex predicts future states to mediate model-based action selection. *Neuron, 109*(1), 149-163.e7.

Alexander, W. H., & Brown, J. W. (2011). Medial prefrontal cortex as an action-outcome predictor. *Nat. Neurosci., 14*(10), 1338–1344.

Amiez, C., Joseph, J. P., & Procyk, E. (2006). Reward encoding in the monkey anterior cingulate cortex. *Cereb. Cortex, 16*(7), 1040–1055.

Anderson, D. J., & Perona, P. (2014). Toward a science of computational ethology. *Neuron, 84*(1), 18–31.

Bakermans, J. J. W., Warren, J., Whittington, J. C. R., & Behrens, T. E. J. (2025). Constructing future behavior in the hippocampal formation through composition and replay. *Nat. Neurosci.*, 1–12.

Balewski, Z. Z., Elston, T. W., Knudsen, E. B., & Wallis, J. D. (2023). Value dynamics affect choice preparation during decision-making. *Nat. Neurosci., 26*(9), 1575–1583.

Balzani, E., Lakshminarasimhan, K. J., Angelaki, D., & Savin, C. (2020). Efficient estimation of neural tuning during naturalistic behavior. *Neural Inf Process Syst, 33*, 12604–12614.

Barron, H. C., Dolan, R. J., & Behrens, T. E. J. (2013). Online evaluation of novel choices by simultaneous representation of multiple memories. *Nat. Neurosci., 16*(10), 1492–1498.

Behrens, T. E. J., Muller, T. H., Whittington, J. C. R., Mark, S., Baram, A. B., Stachenfeld, K. L., & Kurth-Nelson, Z. (2018). What is a cognitive map? Organizing knowledge for flexible behavior. *Neuron, 100*(2), 490–509.

Bertsekas, D. P. (1996). *Neuro-Dynamic Programming*. Athena Scientific.

Blanchard, T. C., Strait, C. E., & Hayden, B. Y. (2015). Ramping ensemble activity in dorsal anterior cingulate neurons during persistent commitment to a decision. *J. Neurophysiol., 114*(4), 2439–2449.

Burge, J., & Bonnen, K. (2025). Continuous psychophysics: Past, present, future. *Trends Cogn. Sci.*

Calhoun, A. J., Pillow, J. W., & Murthy, M. (2019). Unsupervised identification of the internal states that shape natural behavior. *Nat. Neurosci., 22*(12), 2040–2049.

Cervera, R. L., Wang, M. Z., & Hayden, B. Y. (2020). Systems neuroscience of curiosity. Current Opinion in Behavioral Sciences, 35, 48-55.

Chadwick, M. J., Jolly, A. E. J., Amos, D. P., Hassabis, D., & Spiers, H. J. (2015). A goal direction signal in the human entorhinal/subicular region. *Curr. Biol., 25*(1), 87–92.

Chericoni, A., Fine, J. M., Chavez, A. G., Franch, M., Mickiewicz, E., Mathura, R., ... & Hayden, B. Y. (2025). Independent Continuous Tracking of Multiple Agents in the Human Hippocampus. bioRxiv, 2025-03.

Cisek, P. (2012). Making decisions through a distributed consensus. *Curr. Opin. Neurobiol., 22*(6), 927–936.

Driscoll, L. N., Shenoy, K., & Sussillo, D. (2024). Flexible multitask computation in recurrent networks utilizes shared dynamical motifs. *Nat. Neurosci.*, *27*(7), 1349–1363.

Driscoll, L., Shenoy, K., & Sussillo, D. (2022). Flexible multitask computation in recurrent networks utilizes shared dynamical motifs. *bioRxiv*.

Dvijotham, K., & Todorov, E. (2013). Linearly Solvable Optimal Control. In *Reinforcement Learning and Approximate Dynamic Programming for Feedback Control* (pp. 119–141). John Wiley & Sons, Inc.

Ebitz, R. B., Sleezer, B. J., Jedema, H. P., Bradberry, C. W., & Hayden, B. Y. (2019). Tonic exploration governs both flexibility and lapses. PLoS computational biology, 15(11), e1007475.

Eisenreich, B. R., Hayden, B. Y., & Zimmermann, J. (2019). Macaques are risk-averse in a freely moving foraging task. Scientific reports, 9(1), 15091.

Eppinger, B., Goschke, T., & Musslick, S. (2021). Meta-control: From psychology to computational neuroscience. *Cogn. Affect. Behav. Neurosci.*, *21*(3), 447–452.

Fabian, S. T., Sumner, M. E., Wardill, T. J., Rossoni, S., & Gonzalez-Bellido, P. T. (2018). Interception by two predatory fly species is explained by a proportional navigation feedback controller. *J. R. Soc. Interface*, *15*(147), 20180466.

Fine, J. M., Yoo, S.-B. M., & Hayden, B. Y. (2024). Control over a mixture of policies determines change of mind topology during continuous choice. *bioRxivorg*.

Friedman, A., Homma, D., Gibb, L. G., Amemori, K.-I., Rubin, S. J., Hood, A. S., Riad, M. H., & Graybiel, A. M. (2015). A corticostriatal path targeting striosomes controls decision-making under conflict. *Cell*, *161*(6), 1320–1333.

Gallivan, J. P., Logan, L., Wolpert, D. M., & Flanagan, J. R. (2016). Parallel specification of competing sensorimotor control policies for alternative action options. *Nat. Neurosci.*, *19*(2), 320–326.

Garvert, M. M., Saanum, T., Schulz, E., Schuck, N. W., & Doeller, C. F. (2023). Hippocampal spatio-predictive cognitive maps adaptively guide reward generalization. *Nat. Neurosci.*

Gold, J. I., & Shadlen, M. N. (2007). The neural basis of decision making. *Annu. Rev. Neurosci.*, *30*(1), 535–574.

Gómez, V., Kappen, H. J., Peters, J., & Neumann, G. (2014). Policy search for path integral control. In *Machine Learning and Knowledge Discovery in Databases* (pp. 482–497). Springer Berlin Heidelberg.

Gomi, H., & Kawato, M. (1993). Recognition of manipulated objects by motor learning with modular architecture networks. *Neural Netw.*, *6*(4), 485–497.

Gordon, J., Maselli, A., Lancia, G. L., Thiery, T., Cisek, P., & Pezzulo, G. (2021). The road towards understanding embodied decisions. *Neurosci. Biobehav. Rev., 131*, 722–736.

Haarnoja, T., Moran, B., Lever, G., Huang, S. H., Tirumala, D., Humplik, J., Wulfmeier, M., Tunyasuvunakool, S., Siegel, N. Y., Hafner, R., Bloesch, M., Hartikainen, K., Byravan, A., Hasenclever, L., Tassa, Y., Sadeghi, F., Batchelor, N., Casarini, F., Saliceti, S., … Heess, N. (2024). Learning agile soccer skills for a bipedal robot with deep reinforcement learning. *Sci. Robot., 9*(89), eadi8022.

Haarnoja, T., Pong, V., Zhou, A., Dalal, M., Abbeel, P., & Levine, S. (2018, May). Composable deep reinforcement learning for robotic manipulation. *2018 IEEE International Conference on Robotics and Automation (ICRA)*.

Haith, A. M., Huberdeau, D. M., & Krakauer, J. W. (2015). Hedging your bets: Intermediate movements as optimal behavior in the context of an incomplete decision. *PLoS Comput. Biol.*, *11*(3), e1004171.

Hayden, B. Y., Pearson, J. M., & Platt, M. L. (2011). Neuronal basis of sequential foraging decisions in a patchy environment. *Nat. Neurosci.*, *14*(7), 933–939.

Hayden, B. Y. (2019). Why has evolution not selected for perfect self-control?. Philosophical Transactions of the Royal Society B, 374(1766), 20180139.

Howard, L. R., Javadi, A. H., Yu, Y., Mill, R. D., Morrison, L. C., Knight, R., Loftus, M. M., Staskute, L., & Spiers, H. J. (2014). The hippocampus and entorhinal cortex encode the path and Euclidean distances to goals during navigation. *Curr. Biol.*, *24*(12), 1331–1340.

Høydal, Ø. A., Skytøen, E. R., Andersson, S. O., Moser, M.-B., & Moser, E. I. (2019). Object-vector coding in the medial entorhinal cortex. *Nature*, *568*(7752), 400–404.

Jercog, P. E., Ahmadian, Y., Woodruff, C., Deb-Sen, R., Abbott, L. F., & Kandel, E. R. (2019). Heading direction with respect to a reference point modulates place-cell activity. *Nat. Commun.*, *10*(1), 2333.

Johnston, K., Levin, H. M., Koval, M. J., & Everling, S. (2007). Top-down control-signal dynamics in anterior cingulate and prefrontal cortex neurons following task switching. *Neuron*, *53*(3), 453–462.

Johnston, W. J., Fine, J. M., Yoo, S. B. M., Ebitz, R. B., & Hayden, B. Y. (2024). Semi-orthogonal subspaces for value mediate a binding and generalization trade-off. *Nat. Neurosci.*, *27*(11), 2218–2230.

Kane, G. A., James, M. H., Shenhav, A., Daw, N. D., Cohen, J. D., & Aston-Jones, G. (2022). Rat anterior cingulate cortex continuously signals decision variables in a patch foraging task. *J. Neurosci.*, *42*(29), 5730–5744.

Kennerley, S. W., Walton, M. E., Behrens, T. E. J., Buckley, M. J., & Rushworth, M. F. S. (2006). Optimal decision making and the anterior cingulate cortex. *Nat. Neurosci.*, *9*(7), 940–947.

Khona, M., & Fiete, I. R. (2022). Attractor and integrator networks in the brain. *Nat. Rev. Neurosci.*, *23*(12), 744–766.

Kiani, R., Cueva, C. J., Reppas, J. B., & Newsome, W. T. (2014). Dynamics of neural population responses in prefrontal cortex indicate changes of mind on single trials. *Curr. Biol.*, *24*(13), 1542–1547.

Kobak, D., Brendel, W., Constantinidis, C., Feierstein, C. E., Kepecs, A., Mainen, Z. F., Qi, X.-L., Romo, R., Uchida, N., & Machens, C. K. (2016). Demixed principal component analysis of neural population data. *Elife*, *5*, e10989.

Kolling, N., Behrens, T. E. J., Mars, R. B., & Rushworth, M. F. S. (2012). Neural mechanisms of foraging. *Science*, *336*(6077), 95–98.

Kolling, N., Behrens, T., Wittmann, M. K., & Rushworth, M. (2016). Multiple signals in anterior cingulate cortex. *Curr. Opin. Neurobiol.*, *37*, 36–43.

Kriegeskorte, N., & Wei, X.-X. (2021). Neural tuning and representational geometry. *Nat. Rev. Neurosci.*, *22*(11), 703–718.

Kurth-Nelson, Z., Behrens, T., Wayne, G., Miller, K., Luettgau, L., Dolan, R., Liu, Y., & Schwartenbeck, P. (2023). Replay and compositional computation. *Neuron*, *111*(4), 454–469.

Kwon, M., Daptardar, S., Schrater, P., & Pitkow, X. (2020). Inverse Rational Control with Partially Observable Continuous Nonlinear Dynamics. *Adv. Neural Inf. Process. Syst.*, *33*, 7898–7909.

Lake, B., & Baroni, M. (2017). Generalization without systematicity: On the compositional skills of sequence-to-sequence recurrent networks. *ICML*, *80*, 2879–2888.

Luo, T. Z., Kim, T. D., Gupta, D., Bondy, A. G., Kopec, C. D., Elliot, V. A., DePasquale, B., & Brody, C. D. (2023). Transitions in dynamical regime and neural mode underlie perceptual decision-making. *bioRxivorg*.

Maselli, A., Gordon, J., Eluchans, M., Lancia, G. L., Thiery, T., Moretti, R., Cisek, P., & Pezzulo, G. (2023). Beyond simple laboratory studies: Developing sophisticated models to study rich behavior. *Phys. Life Rev.*, *46*, 220–244.

Matsuo, Y., LeCun, Y., Sahani, M., Precup, D., Silver, D., Sugiyama, M., Uchibe, E., & Morimoto, J. (2022). Deep learning, reinforcement learning, and world models. *Neural Netw.*, *152*, 267–275.

McNaughton, N., & Bannerman, D. (2024). The homogenous hippocampus: How hippocampal cells process available and potential goals. *Prog. Neurobiol.*, *240*(102653), 102653.

Merel, J., Botvinick, M., & Wayne, G. (2019). Hierarchical motor control in mammals and machines. *Nat. Commun.*, *10*(1), 5489.

Muhle-Karbe, P. S., Sheahan, H., Pezzulo, G., Spiers, H. J., Chien, S., Schuck, N. W., & Summerfield, C. (2023). Goal-seeking compresses neural codes for space in the human hippocampus and orbitofrontal cortex. *Neuron*, *111*(23), 3885-3899.e6.

Murphy, K. P. (2022). *Probabilistic machine learning: An introduction*. MIT Press.

Musslick, S., Cohen, J. D., & Goschke, T. (2024). Meta-control. In *Reference Module in Neuroscience and Biobehavioral Psychology* (pp. 1–17). Elsevier.

Nyberg, N., Duvelle, É., Barry, C., & Spiers, H. J. (2022). Spatial goal coding in the hippocampal formation. *Neuron*, *110*(3), 394–422.

Ormond, J., & O'Keefe, J. (2022). Hippocampal place cells have goal-oriented vector fields during navigation. *Nature*, *607*(7920), 741–746.

Pan, Y., Theodorou, E. A., & Kontitsis, M. (2015). Sample efficient path integral control under uncertainty. *Neural Inf Process Syst*, *abs/1509.01846*.

Passingham, R. E. (1979). *The hippocampus as a cognitive mapl J. O'Keefe & L. Nadel, Oxford University Press, Oxford (1978). 570 pp.,£ 25.00*.

Pearson, J. M., Watson, K. K., & Platt, M. L. (2014). *Decision making: The neuroethological turn*. *82*(5), 950–965.

Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., &
Duchesnay. (2011). Scikit-learn: Machine learning in Python. *The Journal of*
Machine Learning Research, 12, 2825–2830.
Peng, X. B., Chang, M., Zhang, G., Abbeel, P., & Levine, S. (2019). MCP: Learning
composable hierarchical control with multiplicative compositional policies.
Neural Inf Process Syst, abs/1905.09808.
Sandbrink, K., Bauer, J. P., Proca, A. M., Saxe, A. M., Summerfield, C., & Hummos,
A. (2024). Flexible task abstractions emerge in linear networks with fast and
bounded units. *arXiv [Cs.LG]*.
Sarafyazd, M., & Jazayeri, M. (2019). Hierarchical reasoning by neural circuits in
the frontal cortex. *Science, 364*(6441), eaav8911.
Sarel, A., Finkelstein, A., Las, L., & Ulanovsky, N. (2017). Vectorial representation
of spatial goals in the hippocampus of bats. *Science, 355*(6321), 176–180.
Schwartenbeck, P., Baram, A., Liu, Y., Mark, S., Muller, T., Dolan, R., Botvinick, M.,
Kurth-Nelson, Z., & Behrens, T. (2023). Generative replay underlies
compositional inference in the hippocampal-prefrontal circuit. *Cell, 186*(22),
4885-4897.e14.
Seabold, S., & Perktold, J. (2010). Statsmodels: Econometric and statistical
modeling with python. *SciPy, 7*(1), 92–96.
Shenhav, A., Botvinick, M. M., & Cohen, J. D. (2013). The expected value of
control: An integrative theory of anterior cingulate cortex function. *Neuron,*
79(2), 217–240.
Shenhav, A., Cohen, J. D., & Botvinick, M. M. (2016). Dorsal anterior cingulate
cortex and the value of control. *Nat. Neurosci., 19*(10), 1286–1291.
Sheth, S. A., Mian, M. K., Patel, S. R., Asaad, W. F., Williams, Z. M., Dougherty, D.
D., Bush, G., & Eskandar, E. N. (2012). Human dorsal anterior cingulate cortex
neurons mediate ongoing behavioural adaptation. *Nature, 488*(7410), 218–221.
Shima, K., & Tanji, J. (1998). Role for cingulate motor area cells in voluntary
movement selection based on reward. *Science, 282*(5392), 1335–1338.
Sridhar, V. H., Li, L., Gorbonos, D., Nagy, M., Schell, B. R., Sorochkin, T., Gov, N.
S., & Couzin, I. D. (2021). The geometry of decision-making in individuals and
collectives. *Proc. Natl. Acad. Sci. U. S. A., 118*(50).
Steinemann, N., Stine, G. M., Trautmann, E., Zylberberg, A., Wolpert, D. M., &
Shadlen, M. N. (2024). Direct observation of the neural computations
underlying a single decision. *Elife, 12*.
Sutton, R. S., & Barto, A. G. (1998). *Reinforcement learning: An introduction*.
cambridge.org.
Tervo, D. G. R., Proskurin, M., Manakov, M., Kabra, M., Vollmer, A., Branson, K., &
Karpova, A. Y. (2014). Behavioral variability through stochastic choice and its
gating by anterior cingulate cortex. *Cell, 159*(1), 21–32.
Theodorou, E., Buchli, J., & Schaal, S. (2010). A generalized path integral control
approach to reinforcement learning. *The Journal of Machine Learning*
Research, 11, 3137–3181.

Todorov, E. (2009). Compositionality of optimal control laws. *Neural Inf Process*
Syst, *22*, 1856–1864.
Voloh, B., Maisson, D. J.-N., Cervera, R. L., Conover, I., Zambre, M., Hayden, B., &
Zimmermann, J. (2023). Hierarchical action encoding in prefrontal cortex of
freely moving macaques. *Cell Rep.*, *42*(9), 113091.
Wang, M. Z., & Hayden, B. Y. (2021). Latent learning, cognitive maps, and curiosity.
Current Opinion in Behavioral Sciences, 38, 1-7.
Whittington, J. C. R., McCaffary, D., Bakermans, J. J. W., & Behrens, T. E. J.
(2022). How to build a cognitive map. *Nat. Neurosci.*, *25*(10), 1257–1272.
Whittington, J. C. R., Muller, T. H., Mark, S., Chen, G., Barry, C., Burgess, N., &
Behrens, T. E. J. (2020). The Tolman-Eichenbaum machine: Unifying space
and relational memory through generalization in the hippocampal formation.
Cell, *183*(5), 1249-1263.e23.
Wikenheiser, A. M., & Redish, A. D. (2015). Hippocampal theta sequences reflect
current goals. *Nat. Neurosci.*, *18*(2), 289–294.
Wikenheiser, A. M., & Schoenbaum, G. (2016). Over the river, through the woods:
Cognitive maps in the hippocampus and orbitofrontal cortex. *Nat. Rev.*
Neurosci., *17*(8), 513–523.
Wolpert, D. M., & Kawato, M. (1998). Multiple paired forward and inverse models for
motor control. *Neural Netw.*, *11*(7–8), 1317–1329.
Wood, S. N. (2017). *Generalized additive models: An introduction with R*. Chapman
and Hall/CRC.
Yang, Q., Lin, Z., Zhang, W., Li, J., Chen, X., Zhang, J., & Yang, T. (2022). Monkey
plays Pac-Man with compositional strategies and hierarchical decision-making.
Elife, *11*.
Yeung, N., & Summerfield, C. (2012). Metacognition in human decision-making:
Confidence and error monitoring. *Philos. Trans. R. Soc. Lond. B Biol. Sci.*,
367(1594), 1310–1321.
Yoo, S. B. M., Hayden, B. Y., & Pearson, J. M. (2021). Continuous decisions.
Philos. Trans. R. Soc. Lond. B Biol. Sci., *376*(1819), 20190664.
Yoo, S. B. M., Tu, J. C., Piantadosi, S. T., & Hayden, B. Y. (2020). The neural basis
of predictive pursuit. *Nat. Neurosci.*, *23*(2), 252–259.
Zutshi, I., Apostolelli, A., Yang, W., Zheng, Z. S., Dohi, T., Balzani, E., Williams, A.
H., Savin, C., & Buzsáki, G. (2025). Hippocampal neuronal activity is aligned
with action plans. *Nature*.
773

782
783
Data availability statement:
All data will be made available upon publication

786
787
Code availability statement:
All code will be made available at https://github.com/JustFineNeuro/PacManMain

790
791

METHODS

All procedures were approved by the Baylor College of Medicine Institutional review board.

Human intracranial neurophysiology. Experimental data were recorded from 13 adult patients (6 males and 7 females) undergoing intracranial monitoring for epilepsy. The hippocampus was not a seizure focus area of any patients included in the study. Single neuron data were recorded from stereotactic (sEEG) probes, specifically AdTech Medical probes in a Behnke-Fried configuration. Each patient had an average of 3 probes terminating in left and right hippocampus. Electrode locations are verified by co-registered pre-operative MRI and post-operative CT scans. Each probe includes 8 microwires, each with 8 contacts, specifically designed for recording single-neuron activity. Single neuron data were recorded using a 512-channel Blackrock Microsystems Neuroport system sampled at 30 kHz. To identify single neuron action potentials, the raw traces were spike-sorted using the WaveClus sorting algorithm (Chaure et al., 2018) and then manually evaluated. Noise was removed and each signal was classified as multi or single unit using several criteria: consistent spike waveforms, waveform shape (slope, amplitude, trough-to-peak), and exponentially decaying ISI histogram with no ISI shorter than the refractory period (1 ms). We only used single neuron activity for all analyses.

Experimental apparatus. To control their computer avatar, subjects used a joystick that was a modified version of a commercially available joystick with a built-in potentiometer (Logitech Extreme Pro 3D).. The joystick position was read out in the MATLAB psychophysics toolbox running on the stimulus control computer.

Task description. At trial start, two or three shapes appeared on a gray computer

monitor placed directly in front of the subject. The yellow circle (15-pixels in diameter)

was an avatar that represented the subject and began at the center of the screen.

Subject position was determined by the joystick and was limited by the screen

boundaries. A square (30 pixels in length) represented the prey(s). Prey movement

was determined by a simple algorithm (see below). Each trial ended with either the

successful capture of the prey or after 20 seconds, whichever came first. Successful

capture was defined as any spatial tangency between the avatar circle and the prey

square. Capture resulted in an immediate numeric reward.

Prey movement was generated interactively using an A-star algorithm.

Specifically, for every frame (16.67 ms), we computed the cost of 15 possible future

positions the prey could move to in the next time-step. These 15 positions were equally

spaced on the circumference of a circle centered on the current position of the prey,

with a radius equal to the maximum distance the prey could travel within one time-step.

The cost was based on two factors: the position in the field and the position of the

subject's avatar. The field that the prey moved in had a built-in bias for cost, which

made the prey more likely to move toward the center. The cost due to distance from the

avatar of the subject was transformed using a sigmoidal function: the cost became zero

beyond a certain distance so that the prey did not move, and it became greater as

distance from the avatar of the subject decreased. From these 15 positional costs, the

position with the lowest cost was selected for the next movement. If the next movement

was beyond the screen range, then the position with the next lowest cost was selected

until it was within the screen range.

The maximum subject speed was 23 pixels per frame (each frame = 16.67 ms).

The maximum and minimum speeds of the prey varied across subjects and were set by

the experimenter to obtain a large number of trials. Specifically, speeds were selected

so that subjects could capture prey on no more than 85% of trials. To ensure sufficient

time of pursuit, the minimum distance between the initial position of each subject avatar

and prey was 400 pixels.

Behavioral modeling

Overview of control choice decomposition. The problem we are studying here

is how subject's decide between how to pursue goals on a moment to moment basis.

This means we must estimate a decision variable over how targets are selected to drive

control actions. We motivate this problem by first considering the low-level, individual

goal problem.

For a given target, subject's must deploy some policy that dictates their actions

for reaching that goal, $u_k(t)$. Here, we consider the controls as the output of a linear

controller that is driven by a set of gains that dictate controls (library of controller types

considered in Table 1). For example, the simplest proportional controller with a gain (g_k)

that minimizes distance to target (e_k) for a single target k is :

857                    $$u_k(t){=}g_k\,e_k$$

When there are multiple goals, and each target has different controllers gains,

inferring a decision variable requires inferring how a weighted mixture of targets drives

subjects' control actions. To do this, we used ideas from control theory to develop a

method for decomposing the subject's instantaneous control (i.e., acceleration) into

distinct contributions from each target. This previous work has shown control in a

nonlinear cost landscape – when there are multiple targets and thus minima in the

landscape – can be approximated by a compositional mixture of linear controllers, and

the mixing weights in optimal settings are given by the relative cost/value of individual

controllers (Todorov, 2009; Dvijotham and Todorov, 2012). Next, we state the general

problem and connection to common mixture models, then our approach to estimating

this quantity from behavioral data.

At every time point, we want to decompose the subjects measured control signal

($u_{obs}(t)$ = acceleration) into the proportion of their control signal attributable to individual

prey (K) targets ($u_k(t)$).

874
$$p\big(u_{obs}(t)\big) = \sum_{i=1}^{K} p(target_k|u_{obs}(t))\, u_k(t)$$

These controls are weighted by the posterior probability of them following a target,

given their control signal. Estimation of these weights implicitly defines a multinomial

posterior probability over *K* targets given the control signal. This posterior is the same

form as the familiar gaussian mixture model (Murphy, 2022). Posterior latent target

probabilities are then computed via Bayes rule:

$$w_k(t) \propto p(target_k|u_{obs}(t)) = \frac{p(u_{obs}(t)|target_{k=1})\, p(target_{k=1})}{\sum_{k=1}^{K} p(u_{obs}(t)|target_{j=1})\, p(target_{j=1})}$$

This shows that estimating $w_k(t)$ will implicitly define the integration of an observed data

likelihood and categorical prior. Because solving for the weights is a convex

optimization problem, we will explicitly optimize (see Model parameterization) the

controller weights $w_k(t)$:

$$p\big(u_{obs}(t)\big) = \sum_{i=1}^{K} w_k(t)\, u_k(t)$$

A final note worth mention is how optimizing $w_k(t)$ (ie., target posterior) as a

mixture model mixture approach is different from hidden Markov models. Mixture

modeling applies soft-assignment or weighting and, as such, using $w_k(t)$ to explain

subject's control signal allows blending of controllers and smooth transitions between

them. Hidden Markov models use state decoding or hard-assignment, and effectively

apply an argmax[$w_k(t)$] to choose a singular controller. In the supplementary (section:

model optimization) we show with simulations using a soft-assignment picks up both

cases, where switching is either gradual or binary between targets; thus, using soft-

assigned weights will correctly detect the target pursuit and switching strategy for either

blending of controllers (soft-assignment) or discrete controller choices (hard-

assignment).

Model parameterization

To infer an estimated $w_k(t)$ time-series per trial, we estimated maximum a

posteriori parameters from behavioral data, including the parameters of w_k ($[\phi, \psi]$) and

controller gains ($g_k = \theta$). Both sets of parameters are explained below. Optimization of

these parameters proceeded by minimizing the negative log posterior:

907
$$-log\ p(u_{obs}) \propto \sum_{t=1}^{T} -log\ p\big(u_{pred,K}(t; \theta, \phi, \psi)\big) - log\ p(\theta, \phi, \psi)$$

908   The first term on the r.h.s. is the negative log likelihood (priors are second). u_{pred} is the

909   model predicted control signal that is determined by the mixture of controls across

910   targets:

912
$$u_{pred}(\theta, \phi, \psi) = w_1(t; \phi, \psi)\ u_{pred,k=1}(t; \theta) + w_2(t; \phi, \psi)\ u_{pred,k=2}(t; \theta)$$

w_k **parameterization**. Mixture weights (w_k) were parameterized by implicitly modeling

time dependent logits with (n=30) radial basis functions equally-spaced over each trial's

time. Basis parameters included weights (ϕ) and a shared width parameter (ψ). We

chose to implicitly parameterize w_k with basis functions as it allows a flexible and

smooth parametrization of transitions between target control blending. Practically, w_k

are defined though a softmax over the logits (eq. Xand X). Logits are computed by

multiplying basis functions by their optimized parameters.

922
$$w_1(t) = softmax\big(logits_1(t; \phi, \psi)\big)$$

923
$$w_2(t) = 1 - w_1(t)$$

Note, this approach is readily extended to the case of K > 2 targets by constraining one

target's logits to 1 and increasing the basis parameters to n*K-1.

$u_{pred,k}$ **parameterization**. For generating predicted controls per target, $u_{pred,k}$, we

tested different controller types and estimate their gain parameters per controller (g_k).

We model the predicted subject's states (x_{pred} ={positions, velocities}) and controls as

a linear dynamic system mapping joystick input to the cursor. Joystick position

controlled the cursor velocity, and therefore control signals from the subject (u_{obs}) are

acceleration, which are composed of the controls from distinct targets ($u_{pred,k}$). These

controls and states step the predictions forward and generate a new set of control

predictions in each optimization iteration. The linear system describing the subject's

cursor is:

$$x_{pred}(t+1) = Ax_{pred}(t) + Bu_{pred}(t)$$

Where **A** and **B** are known system parameters (Δt = sampling rate (1/60 Hz)) that

determine the mapping from joystick to subject cursor dynamics.

$A = [1\ 0\ \Delta t\ 0\ ;\ 0\ 1\ 0\ \Delta t\ ;\ 0\ 0\ 1\ 0\ ;\ 0\ 0\ 0\ 1]$, $B = [0\ 0\ \Delta t\ 0\ ;\ 0\ 0\ 0\ \Delta t]$

Because the subject's control strategy for a given target is unknown, we must also fit

the mixing weights using different combinations of controller classes that could generate

responses. We considered controllers that use different combinations of error signals to

drive target pursuit. Model classes included either proportional or integral errors, where

the error signals were of different classes described below, including feedback and

feedforward predictive controller errors. All model classes are listed in Table 1

960   Table 1

Equation	Description
$u_{pred} = g_p\, e_p$	Current position error
$u_{pred} = g_p\, e_p\ + g_v\, e_v$	Current position and velocity errors
$u_{pred} = g_p\, e_p\ + g_f\, e_f$	Current and future position errors
$u_{pred} = g_p\, e_p\ + g_i \int e_p\, e_p$	Current and integral position errors
$u_{pred} = g_p\, e_p\ + g_f\, e_f + g_i \int e_p$	Current, future, and integral position errors
$u_{pred} = g_p\, e_p\ + g_f\, e_v + g_i \int e_p$	Current, velocity, and integral position errors
$u_{pred} = g_p\, e_p\ + g_f\, e_v + g_f\, e_f$	Current, velocity, and future position errors

Error signals are denoted e with subscripts indicating type (e.g., e_p is current position

error)

e.g., $e_p = x_{position,cursor} - x_{position,target=k}$

962   Note that we also included models with future position errors. This controller

963   class allows the subject's predicted controls to be driven by feedforward signals based

964   on the target's predicted (1-step ahead) position. The error signal encodes the

965   difference between the subject's current (t) position and target's future (t+1) position.

966   Target future position was computed using the forward kinematics of the target:

967                $x_{target}(t + 1) = x_{target}(t) + \Delta t x'_{target} + \Delta t^2 x''_{target}$

969   **Model loss priors.** The parameter priors for the loss are denoted as:

971
$$p(\theta)\, p(\psi)\, p(\phi) = N\big(0, I\sigma_\theta^2\big)\, N\big(0, \sigma_\psi^2\big)\, N\big(0, (\lambda S)^{-1}\big)$$

The prior over controller gains (θ) was a zero-mean normal distribution, with

identity variance – constraining gains independently. A similar prior was used for the

basis function width (ψ). For both priors, increasing σ^2 decreases the regularization of

the prior. For basis function weights (ϕ), we wanted to penalize deviations from

smoothness. For this, we used a gaussian laplacian prior (multivariate gaussian) often

used in spline models to penalize the wiggliness of functions (Wood, 2017). This prior

uses the inverse precision matrix with a regularization coefficient $(\lambda S)^{-1}$. S is a penalty

matrix defined as the 2nd order difference between adjacent weights, penalizing the

curvature:

981
$$\Delta^2\phi = \phi_{i+1} - 2\phi_i + \phi_{i-1}$$

Model optimization. For parameter estimation, we used trust-const in scipy.optimize.

During each parameter update, the current parameter set (θ, ϕ, ψ) is used to simulate

the predicted dynamics and compute the loss. Loss Jacobians and Hessians were

computed automatically using Jax and parameters were iteratively optimized by

maximizing the negative log posterior. To ensure positively constrained controller gains

(θ) and basis width (ψ) we optimized their log, and used a softplus transform. Each trial

was optimized separately. For each optimization run, we fit a specific controller class

(same for both targets). This was repeated 4 times for each controller class, with

different parameter initializations, and the one with best loss was retained for cross

model performance comparisons (next section). This was repeated for each of the

seven model classes (Table 1).

Quantifying model performance and computing mixture. After optimizing

parameters and retaining the best fit for each model class (and each trial), we computed

the evidence lower bound (ELBO) for each model using a Laplace approximation to the

parameter posteriors (see Murphy, 2022). The ELBO provides an estimate of lower

bound on the marginal log-likelihood of each model, balancing model fit and penalizing

the number of parameters.

The next step is computing a mixing trajectory ($e.g., w_1$) for each trial that

marginalizes over each model, while accounting for each model's uncertainty in

predicted parameters. Because the model probability is quantified via the ELBO, we can

use these ELBOs to compute posterior probabilities for each model.

1004

1005
$$p(M_k \,|u_{obs}) = \frac{exp(ELBO_m)}{\sum_1^j exp(ELBO_j)}$$

1006

1007   We use these model probabilities to perform Bayesian model averaging to

1008   obtain a singular w_1 trajectory. In short, the w_1 trajectory around the MAP parameters

1009   for each model class is weighted and summed. Computing w_1 through model averaging

1010   accounts for model uncertainty by marginalizing over the generating models, and this is

1011   the target blending estimate we use for downstream analysis.

1012

1013
$$\text{BMA}(w_1) = w_{1,k}\, p(M_k \,|u_{obs})$$

1014

Comparison of different control mixing strategies

We also want to compare a smooth controller blending model to two other

possible controller selection models that could drive behavior. We can use the same

model fitting framework as above. For one comparison model, we fit a model that

assumes subject's choose a single controller at an given moment. This is equivalent to

argmax model over individual target controllers, is nested within the smooth blending

model, and is akin to how an HMM would choose the generative controller. Comparison

of this model to the smooth blending effectively tells us how much of behavior is

explainable by a continuous mixing versus discrete selection strategy. This argmax

model is formulated for the predicted control as:

1025

1026
$$u_{pred}(\theta, \phi, \psi) = argmax_{\,u_{pred,k}}\,(w_1(t; \phi, \psi), w_2(t; \phi, \psi))$$

1027

Another strategy that subjects could use is blending inputs with a single

controller. Note that this control strategy is not nested within the smooth controller

blending model, as control signals produced by multiple controllers versus one

produced by weighting multiple inputs are not related through any linear transform

(Supplementary note X). The input blending model is formulated using a single set of

controller gains rather than distinct gains per target, and weighting the inputs:

1034

1035
$$u_{obs}(t) = \theta \sum_{i=1}^{K} w_k(t) \, x_k(t)$$

1036   Both comparison models were fit using the same approach as the controller blending

1037   model. Bayesian model selection with the ELBO was used to select the best fitting

1038   model for each trial. For each subject, we computed the mean posterior probability of

1039   each model type for group level model selection.

1040

Behavioral analysis

Finding behavioral switch points. To separate instantaneous moments into pursuit

versus change-of-mind points between targets, we first searched each trial to find points

where W_t =0.5. These W_t points denote crossings between targets. We excluded any

putative switch points that occurred within 150 ms of the trial start time, under the

assumption that these likely represent a correction to an initial choice rather than true

pursuit switching or change-of-mind. Using the remaining potential switch points, we

created a window of -300 to +300 ms around these points. The switch trajectories were

then categorized as falling into one of three categories. The main category (1) was

those where a full switch was made between targets, the other two were either (2)

partial switches or (3) were unclassifiable. To achieve this classification, we used a PCA

across all switch trajectories from within a session. The 1st principal component (PC)

always captured the sigmoidal shaped full switch trajectory of interest. We computed

the cosine similarity of this 1st PC score and all switch trajectories and retained those

with a similarity of > 0.9. We ran a PCA again on this subset, with the 1st PC again

producing the canonical sigmoidal trajectory. In this case, we retained those with cosine

similarity of >0.97. This threshold proved to be conservative enough to remove all partial switches, based on visual inspection. In total, an average of 35% of W_t crossing-points were labeled as legitimate switches and forwarded for further analysis. Switch onset and offset timing were determined using a linear fitting change-point algorithm that looked for changes in mean and slope of the W_t trajectory. To find the switch start, we searched backward in time from the crossing of $W_t = 0.5$. Switch ends were found by searching forward in time.

Switch statistics. The factors underlying the propensity to make target switches were modeled using a Bayesian binomial mixed effects model implemented in statsmodels in python (Seabold and Perktold, 2010). We used this approach to allow modeling all participants together, while accounting for individual variation in predictors. Predictor significance was determined using the 95% posterior credible interval. In terms of predictors, we asked if switch probability was sensitive to the time elapsed in trial, the difference in prey reward, and several prey distance variables. Specifically, we included the mean distance to the prey being pursued and the mean distance of the prey switched to, where the mean is calculated in the 100 ms leading up to a switch. We also included a factor to determine the mean rate of change of distance (distance closure) between both preys, too. The distance closure captures whether either prey getting closer or farther away (on average) altered switch probability. Each of these variables was centered by using their median values extracted from trials in which there were no switches. This allows interpreting the coefficients in terms of changes with respect to control, no-switch trials. We used the mixed

Neural analysis

Single neuron encoding of task variables. To assess how neurons are tuned to task variables, we employed a linear-nonlinear Poisson model as a Generalized additive model (GAM; Balzani et al., 2020; Wood, 2017). Specifically, we aimed to quantify how neurons were tuned to subject speed, relative prey distance, relative prey speed, relative time in trial, prey reward difference, and the model-based blending variable

(W_t). As our main goal was estimating tuning W_t, we included all of these terms and

interactions with W_t in the model to control for any confounding.

The GAM was fit with a penalized regression smoothing spline model (Wood,

2017). Penalized smoothing spline GAMs were chosen as they have been shown to

offer good recovery of nonlinear neuron tuning, particularly in tasks where tuning is

estimated with respect to continuously changing variables (e.g., speed; Balzani et al.,

2020). Natural cubic regression splines served as a basis function. Cubic splines are

convenient as a smooth interpolant basis because their only hyperparameter is the

number of bases (J; Wood, 2017). The spike counts y_t are fit in a GAM with univariate

and interaction effects with basis functions b_{j,x_1} (basis j and variable x_1). As an

example, in a two-variable model the firing is modeled as:

1098

1099 $$log(y_t) = \sum_{j=1}^{J} b_{j,x_1}\beta_{j,x_1} + \sum_{j=1}^{J} b_{j,x_2}\beta_{j,x_2} + \sum_{j=1}^{J} (b_{j,x_1} \otimes b_{j,x_2})\beta_{j,x_{1\otimes 2}}$$

1100

The first two terms are examples of single (marginal) variable tuning effects. The latter

component encodes the interaction (nonlinear mixed selectivity) term as a tensor over

the two univariate basis functions.

The model was fit in a Bayesian framework using stochastic variational inference

in NumPyro. To estimate smooth and regularized tuning functions, we follow previous

implementations (Balzani et al., 2020; Wood, 2017) and implement two types of

regularization. Specifically, regularization was implemented through two types of priors

on model coefficients that (1) control for basis wiggliness and enforce smoothness

across basis functions, and (2) force sparse sets of bases similar to an L1

regularization. Combining these two effectively performs model selection by both

smoothing across bases (1) and (2) forcing bases that don't contribute to the model

likelihood to be zero. These priors are implemented for basis coefficients as a

multivariate normal distribution, for a given variable as:

1114

1115 $$\beta \sim MVN(0, \Sigma_\beta)$$

1116

1117
$$\Sigma_\beta = (\lambda_j S + \lambda_* S_*)$$

1118

The smoothing/regularization terms (λ) are treated as random variables in the Bayesian

approach, with Half-Cauchy priors. This allowed estimating separate smoothing terms

per univariate and tensor model term directly from the data, without cross-validation. S

encodes a 2^{nd}-order difference penalty between basis coefficients, inducing smoothing

as a Laplacian graph prior that is used to construct the coefficients prior covariance. We

point the reader to Wood (2017) for more specifics on how S and S_* are constructed.

To fit the models and approximate the posterior distribution of parameters, we

employed a variational inference approach with a Gaussian guide. Variational

parameters (mean and covariance) were optimized by minimizing the negative evidence

lower bound (ELBO). This approach balances computational efficiency with parameter

uncertainty estimation. All models were optimized using Adam (learning rate: 1e-3),

each run for 10,000 steps.

To further determine coefficient significance, 99% posterior credible intervals

were used to evaluate whether they included zero. Those variables with intervals non-

overlapping with zero were retained. To determine whether the full interaction (nonlinear

mixing with blending) model was a significantly better fit only a model with marginal

effects, or a baseline intercept-only model, we computed a z-score test using the

difference in expected log predictive density (ELPD) between each set of two models

and the standard of the difference in ELPD (Gelman, 2013). The ELPD was computed

using WAIC. Models with a z-score corresponding to $p < 0.01$ were denoted as

significant. Specifically, we first tested whether the marginal effects model only was a

better fit than the baseline. Then we used the ELPD test again to select whether the full

model with interactions was a more probable model than the marginal effects model.

The winning model was retained as the tuning coefficients for that neuron.

1143

Fisher information of W tuning. We computed a cross-validated and denoised

estimate of fisher information using neuron tuning to W_t. We computed tuning curves for

each neuron in twelve bins. We used 5-fold cross-validation when computing the tuning

curves. Tuning curves from the training set for each brain region were reduced using

principal components analysis, retaining enough dimensions to account for 90% of

variance. Fisher information was computed using PCA projections of the test set, and

taking the euclidean distance between adjacent levels of W_t of these projections

(Kriegeskorte and Wei, 2021). To test for significant information, we created a null

distribution for permutation testing by permuting W_t labels during calculation of the

tuning curves. This distribution was created by repeating this process 1000 times, and

the p-value was computed by comparing the mean actual 5-fold information to the

permutation distribution.

1156

Demixed principal components analysis. To examine the low-dimensional population

dynamics related to behavioral controller blending, we performed dimensionality

reduction on neural data using demixed principal components analysis (dPCA; Kobak et

al., 2016). Using dPCA, we can extract linear subspaces of population activity that

maximize the variance specifically related to separating levels of blending. In effect, this

approach allows us to determine whether the population has linearly decodable

representations of blending.

Because our aim was assessing whether neural population dynamics closely

tracked the behavioral blending variable, we focused on time windows in which there

was an explicitly consistent blending trajectory: change of mind between prey targets.

To decompose the neural data, we first sorted all switch points, during a trial, for a given

subject, and within a session, into those that switched from a low to high or high to low

value target. Under the assumption that blending differs in a mirrored fashion (high to

low versus low to high W_t), across time, for these switch directions, we can take the

decoding subspace as the dynamic subspace for W_t. We additionally separated the data

in low and high levels of prey reward difference.

We fit the dPCA model to firing rate tensors as pseudo-populations that included

all subjects. The model included the effects for W_t , prey reward difference, and their

interaction. Each fit was done separately for dACC (n =149) and Hippocampus (n =

314). The fitting and significance testing procedure was carried out by performing 1000

repetitions randomly sampling (stratified monte-carlo) the data, and holding-out 5% of

trials (balanced between switch directions). A dPCA model was then trained using a

fixed regularization of 1×10^{-5}. Firing rate test-sets were then projected along the top

decoder dimension for the switch direction. We took the decoded switch direction to be

the minimum distance of the projected test data to the projected training data. This

classification was computed for each of the 30 time-points in the switch window.

Second, we established significance thresholds by repeating the above procedure, but

randomly swapping trial labels to create a null accuracy distribution. We created the null

distribution by repeating the 1000 iterations 50 times. For each of the 50 sets, we

computed the null decoding accuracy. We determined that decoding was statistically

significant when the decoding accuracy was greater than the null for 100% of the 50

sets.

1189

Ramp decoding. We estimated ramping population signals used in Figure 4 by

adopting a decoding method previously used for perceptual decision making

(Steinemann et al., 2024). Ramping signals were estimated by assessing whether we

could decode if a switch decision was going to happen within 100 ms.

For pre-processing neural data, we first aligned spikes to the target switch onset.

Then we split the data into the separate switch directions. These splits were then split

into training and test folds (5 folds), retaining only neurons that had at least 25 instances

in each condition. We then sampled time-windows of firing of length equal to the switch

decision period (30 samples) that did not contain a switch. We sampled control data

equal to the length of train and test folds. Sampling of control condition spikes was

repeated for each training-test fold. These firing windows provide the comparator neural

activity for decoding.

For each fold, we z-scored and performed PCA on the concatenated control and

training data. The z-scoring and PCA transforms were then applied to the concatenated

control and test fold data. Time-based decoding was performed on 80ms windows that

were stepped by one window (16.67 ms sampling rate). We then trained and tested a

linear support vector machine on each window, and used the average performance over

folds for decoding accuracy. Decoding significance was estimated by repeating this trial

sampling procedure 1,000 times but permuting the condition labels. All decoding was

implied in scikit-learn (Pedregosa et al., 2011).

1210

Clustering ramp. We clustered firing during the target switches to assess whether

classes of single neurons also exhibit ramping behavior. To obtain a meaningful

clustering based on latent neural dynamics and potential, we first fit a linear dynamic

system to trial-averaged, gaussian smoothed (FWHM 60 ms) firing rates using the ssm

package in Python. In addition, the models were fit to both switch directions (high to low

and low to high value prey) simultaneously, giving them shared parameters but different

inputs. We used the normalized relative target distance as inputs to the model. This

approach to clustering accounts for similar latent dynamics evolving under different

inputs. The number of the latent state dynamics for each model were optimized by

computing the loss (ELBO) from a held out test in 5-fold cross-validation. This was done

separately for each brain region. We found three latent states were suitable for

describing each area.

Clustering was then performed on the firing rate embedding matrix C using K-

means. The C matrix links latent states to firing rates. The number of clusters was

optimized using the silhouette score, separate for each brain region. We chose clusters

to retain based on those that exhibited significant differences in activity between time-

locked segments with switched and control segments without. Significance was

determined by permuting (1,000 times) the mean clustered firing rate between the

actual switches and controls.

Supplementary Material

S1. Mixture of controllers model fitting accuracy and ground-truth recovery

To test the validity of our modeling approach using basis functions and controllers, we simulated ground-truth data with a known W_t that we designed. To cover the space from simple to complex W_t profiles, we considered five different types of W_t. We show examples of these five types in Table S1. To simulate data, we sampled 20 random trials across both subjects' sessions, with 5 of each having an approximate length of 0.91 sec, 1.45 sec, 2.83 sec, 4.1 sec long. In the main text, we fit across a range of number of bases and model-average. We chose a fixed number of bases in simulation to fix the complexity of the model, as increasing basis numbers will always increase fit quality.

As a first test, we compared whether different controller types (see Table 1) could be recovered as the best fitting model compared to a baseline of just a position controller (**Figure S1A**). The posterior model probabilities indicated that for all controller classes we could recover the true generative controller model on average better compared to a baseline (all probabilities > 0.5 for the generative model).

We next examined how well we could recover the generative kinematics for each controller model class. In **Figure S1B** we show the average correlation between predicted and actual positions for 20 simulated trials per controller model type. We get good recovery across all model types, with an average correlation of 0.83 across model classes.

The quality of inferring ground-truth W_t was similar to positions. The correlations between the true and predicted W_t are shown in **Figure S1C.** Across the generative models, we get an average correlation of 0.87. These correlations are averaged over different levels of W_t complexity, which was controlled using a scaling parameter for a generating gaussian process model. In Figure **S1D-I**, we show example fits of the simulated and recovered W_t for each class of generative models.

Overall, these simulations and analysis indicate that our method did a job at detecting the correct model class (**Figure S1A)**, as well as recovering the actual latent target specific controls (**Figure S1B**) and W_t (**Figure S1C**).

1266
Figure S1.| **Model recovery of Wt and controllers.** (**A**) Probability of choosing the generative
model as being better than a baseline, position only controller model. Higher values indicate
better recovery. (**B**). Correlation between true and predicted controller position time series based
on fit of generative model class. Higher correlations indicate better recovery, and each bar is the
average of 30 runs. (**C**). Correlation between true and predicted Wt time series based on fit of
generative model class. Higher correlations indicate better recovery, and each bar is the average
of 30 runs. (**D**) - (**I**) examples from simulations and fits showing the generative Wt and the
predicted model recovered Wt. Each set of plots is a different generative model. The left

columns in each (scaling = 1) are those with simple generating Wt, and the right right columns
are more complex Wt (scaling = 5). The scaling is the scale parameters used in a gaussian
process generator.
1278
1279
S2. Proof of controller model non-equivalencies
We outline a simple algebraic proof here that two of the considered model
classes – mixing of controllers versus mixing of inputs – are not related by any linear
transform, making them constitute different behavioral model classes. We formulate this
argument for a single time-point, input feature and controller dimension. An assumption
we make is that controller gains are at steady state, as formulated in an infinite horizon
or average cost scenario; ie., controller gains are not state or time-dependent. This
problem is formulated is as follows:
1288

1289
$$u_{obs:controller\ mixing} = \sum_{k=1}^{K} w_k\, u_k$$

1290
1291 Which represents the controller blending model, where control signals for two
1292 controllers are specified with gains (L_k):
1293
$$u_1 = -L_1\, x_1$$
1294
$$u_2 = -L_2\, x_2$$

1295
1296 Using this, it is convenient to rewrite this as:
1297
1298
$$u_{obs:controller\ mixing} = -w_1 L_1\, x_1 - w_2 L_2\, x_2$$

1299
1300 For comparison, we create the same setup for input mixing models:
1301

1302
$$u_{obs:input\ mixing} = -L \sum_{k=1}^{K} w_k\, x_k$$

1303 Rewriting in expanded form:
1304
1305
$$u_{obs:input\ mixing} = -L\,(w_1\, x_1 + w_2\, x_2)$$

1306
1307 Now testing for equivalence across models, we find that are only equivalent when the
1308 controller gains are identical:
1309
1310
$$u_{obs:controller\ mixing} = u_{obs:input\ mixing}$$

1311
1312
$$-w_1 L_1\, x_1 - w_2 L_2\, x_2 = -L\,(w_1\, x_1 + w_2\, x_2)\ iif\ L_1 = L_2$$
1313 Thus, the two models can only be seen as equal when the gains of both controllers are
1314 equal.