Delta Marches: Generative AI based image synthesis to decode disease-driving morphologic transformations.

Thuong Nguyen[1], Vandana Panwar[2], Vipul Jarmale[1], Averi Perny[1], Cecilia Dusek[2], Qi Cai[2], Payal Kapur[2,3,4], Gaudenz Danuser[1,5, #], Satwik Rajaram[1,2,3,#]

[1] Lyda Hill Department of Bioinformatics, University of Texas Southwestern Medical Center, Dallas, TX, USA

[2] Department of Pathology, University of Texas Southwestern Medical Center, Dallas, TX, USA

[3] Kidney Cancer Program, Simmons Comprehensive Cancer Center, University of Texas Southwestern Medical Center, Dallas, TX, USA

[4] Department of Urology, University of Texas Southwestern Medical Center at Dallas, Dallas, TX, USA

[5] Department of Cell Biology, University of Texas Southwestern Medical Center. Dallas, TX, USA

[#] Corresponding Authors: Gaudenz Danuser (Gaudenz.Danuser@UTSouthwestern.edu), Satwik Rajaram (Satwik.Rajaram@UTSouthwestern.edu)

Abstract

Deep learning has revealed that tissue morphology contains rich biological information beyond human understanding. However, approaches to convert these spatially distributed signals into precise subcellular insights informing disease mechanism are lacking. We introduce Delta-Marches, an interpretability-first approach that nominates distinguishing morphological features rather than explaining existing models' decisions. Delta-Marches leverages a generative AI framework with latent-space traversals that simulate idealized morphological changes between classes. Comparing each image to its class-shifted counterpart allows downstream feature extractors to infer aspects most affected by the shift, reducing sample-to-sample variability and yielding interpretable morphological transformations at subcellular resolution. Prototyped in renal carcinoma histopathological grading, Delta-Marches generates realistic grade transitions and pinpoints tumor-cell nuclear phenotypes as key properties of tumor grades. It also reveals reduced vasculature associated with increasing grade, a pattern reported in studies but absent from standard grading rubrics. These results indicate Delta-March's ability to parse complex image phenotypes and catalyze hypothesis generation.

INTRODUCTION

The ultimate opportunity of applying artificial intelligence (AI) to biomedicine[1,2] is to exploit subtle and complex patterns in data with a sensitivity and precision that surpass human intuition—and to transform these patterns into meaningful scientific and clinical insights. In genomics, for example, models[3-5] such as Puffin have predicted regulatory motifs and revealed syntax rules, such as the spacing and orientation of transcription factors binding sites, that govern enhancer activity, yielding insights that extend well beyond traditional motif discovery.

In contrast, tissue microscopy, while central to clinical workflows, remains underutilized for AI-driven discovery, despite widespread recognition that these images contain rich, untapped insight into disease mechanisms[6,7]. This gap is evident in tumor histopathology. Historically, the rules of tumor assessment have been developed under criteria of ensuring consistency across observers rather than capturing the full range of morphologically predictive information. Many disease-

driving features involve subtle molecular or spatial patterns that interact in complex, non-linear
ways, making them difficult to isolate by visual inspection. Classical machine learning approaches
(Fig. 1A top), which rely on manually engineered features, were initially expected to offer more
comprehensive diagnostics with a high-level of interpretability. In practice, however, even
generating relevant biological features, such as identifying cell types, can be a substantial
undertaking[8-19]. Moreover, sample-to-sample variation often masks class-defining morphological
differences, and without counterfactual examples—samples that differ only in the property of
interest—the true discriminative features remain difficult to pinpoint. Modern deep learning has
demonstrated remarkable performance across a range of pathology tasks, including achieving
expert-level performance in tumor grading and subtyping and has even surpassed human intuition,
predicting mutation status directly from morphology[20-41]. Despite this success, these models have
rarely translated predictive power into biological insight.

While there is much work in interpretable deep learning (IDL) and Explainable AI (xAI), much of
it focuses on a different target: learning how a classifier makes its decisions[42-52] rather than
revealing biological insights. As standard models are typically optimized for classification
prowess rather than post-hoc deconstruction, this creates a gap between these objectives. This
limitation is exacerbated in tissue microscopy. Unlike natural images where a class is often
localized to a single object, pathological signals are spatially scattered and intermixed (Fig. 1A
bottom). Because discriminative convolutional neural networks (CNNs) aggregate these diffuse
signals into a single class probability, methods that retroactively explain this process[42-50,53-57]
inevitably smear fine-grained details into broad, nonspecific heatmaps. This tradeoff persists with
more recent architectures such as Vision Transformers (ViTs), albeit with a distinct failure mode.
Driven by the objective of finding the most efficient path to a classification decision, ViTs often
spotlight a minimal set of highly discriminative tokens[58,59], such as a single tumor nucleus (Fig.
S1). For a human observer, this sparsity is confusing: it leaves biologically identical tumor nuclei
unhighlighted, appearing as false negatives undermining the corresponding biological hypothesis.
Thus, while traditional xAI is important to establish confidence in existing models, it remains ill-
suited for generating novel biological hypotheses in microscopy.

We previously developed a conceptually distinct IDL approach leveraging generative AI —not to
explain a DL prediction in the traditional sense, but to explore the morphological basis of an image-
based classifier of metastatic propensity of single melanoma cells in culture[60]. Specifically, we
trained a latent representation capable of generating images of cells with different levels of
metastatic spreading. By examining the warping of images as we traversed the latent space
between areas of high and low metastatic propensity, we identified extension of pseudopods as the
defining feature of high metastatic potential. Both the classifier and the IDL-predicted
morphological behavior of aggressively metastasizing melanoma cells were validated in follow-
up studies using human xenografts in mice[60,61]. Of note, it would not only be very difficult to
human-engineer a detector of pseudopodal extension in these images, but the cell-to-cell
heterogeneity completely obfuscates the differential in pseudopodia extension as a defining
characteristic of metastatic cells. Rather, this discovery was made possible by the power of
generative AI to gradually parse the complex mix of phenotypes across cells with differing
metastatic potential even beyond the range of available experimental data. While several studies[62-
64] have since applied generative AI models to histopathology for expanding datasets and
visualizing class transformations[65-73], these approaches primarily function as image synthesis tools
rather than analytical engines. By producing synthetic transformations with either coarse or

implicit characterizations, current methods effectively shift the interpretability burden back to the
human observer, who must subjectively 'spot the difference' to resolve subtle, subcellular features
amidst complex, heterogeneous tissue architectures. Consequently, the potential of generative AI
to elucidate the relationship between tissue structure and disease state has remained largely
untapped.

Here, we design a hypothesis generation framework that extends the concept of interpretability via
latent space traversal from single cells to patient tissue samples via two key innovations (Fig. 1B).
First, we adopt diffusion models (DMs)[74-79] to learn a meaningful high level semantic latent space
that is agnostic to interchangeable low level image features, which are nonetheless crucial for the
production of realistic images (Fig. 1B). Second, we introduce the concept of the *Delta-March*, a
system to analyze changes between counterfactual images, images of the same tissue that differ in
class, produced by the latent space traversal to identify the disease-associated features. By
generating estimates of counterfactual differences with sub-cellular resolution, our method enables
deep quantitative analysis of morphological transformations, robustly capturing subtle and
spatially dispersed patterns and providing subcellular-resolution interpretation even in complex
tissue architectures. As a test case, we demonstrate that the proposed model faithfully recovers the
clinically applied grading rules for clear cell renal cell carcinoma (ccRCC). Delta-Marches also
highlight an additional feature that, while accepted by pathologists as plausible, has yet to be
entered into the official grading scheme. This provides a glimpse of the potential of this AI
framework to complement existing diagnostic approaches with novel biomarkers and to assist
clinicians in the generation of hypotheses on cancer biology that has so far escaped the current
body of medical knowledge.

RESULTS

Tumor grading rules as a benchmark for hypothesis generating IDL

Pathologists classify ccRCC into four grades of tumor aggressiveness based on hematoxylin and
eosin (H&E) stained histopathology slides. The scoring systems have been updated over time but
are largely focused on nuclear size and nucleolar prominence, both of which increase with higher-
grade aggressive tumors[80-82]. Specifically, distinctions of grades 1, 2, and 3 are purely based on
these features, while grade 4 also considers non-nuclear properties of tumor cells such as
sarcomatous or rhabdoid differentiation, which are associated with poor prognosis and more
aggressive tumor behavior[80-82]. Additionally, while not part of the official grading rules, the extent
of vasculature is known to decrease with increasing grade[83-85]. We note that ccRCC tumors exhibit
a high degree of intra-tumor heterogeneity[20], and grade is traditionally assigned at a patient level
based on the highest grade area within a tumor. We employ a dataset of 1,128 whole-slide images
from about 1,120 patients (Methods), with patch level tumor grade assignments rather than
conventional patient-level grading, to test the ability of the proposed approach to autonomously
nominate discriminative morphological features recovering the same or alternative grading criteria
(Fig. 1C).

Fig. 1. Overview of the study. (A) Understanding of the association between tissue morphology and its biology has evolved through centuries of observation and empirical study. In recent years, rule-building by human inspection has been complemented by classical machine learning (ML) techniques that can analyze features across biological categories by rigorous statistics. However, tissue complexity and within- and across-tumor variability hinders the engineering and interpretation of meaningful features. Deep learning (DL) excels in the classification of disease states by tapping into complex image features that are inaccessible to humans. However, DL

models are seen as "black boxes" with limited transparency on which image information drives the classification. Efforts in developing interpretable DL (IDL) models have attempted to overcome this deficit by revealing the links between input data and predictions. However, traditional IDL methods tend to rely on saliency maps that mark classifier-informing regions in broad strokes but fail to extract from histopathological data the local and often spatially dispersed image properties that are critical for the classifier performance. **(B)** The framework proposed in this work implements an autoencoder model and latent space traversal (blue arrow) to generate synthetic images of the same tissue with different classes. These synthetic images are utilized to create a Delta-Map, which underscores significant across-class transformations and provides insights into the mechanisms driving morphological changes associated with biological progression. **(C)** Definition of goals of the present study: Evaluate the ability of the proposed model to autonomously learn clinically-established tumor grading rules and in potentially creating new rules that may inform an enhanced tumor grading procedure.

Diffusion Autoencoders provide semantically meaningful latent spaces

Following our previous successes of implementing hypothesis-generating IDL for single melanoma cell behavior based on the generative arm of an Adversarial Autoencoder (AAE) model[60] we sought to learn similar latent space representations of H&E patches. To adapt the approach to the structurally more complex tissue image patches, we increased the latent space dimension and added an adversarial arm to encourage the reconstructed images to be indistinguishable from the real ones (Fig. 2A). Although the AAE produced visually accurate reconstructions (Fig. S2A), the underlying latent space was biologically sub-optimal: image patches with highly similar latent vectors often shared a similar tissue architecture, but could exhibit highly different traits, such as originating from different slides and grades (Fig. 2B, S2B). This phenomenon was true regardless of the latent vector size we chose (Fig. S2B). We reasoned that the discordant nature of the AAE's latent space arises from the representations having to perfectly recover all aspects of the image, including many trivial aspects such as absolute positions of nuclei that are unrelated to the tumor grade.

162
Fig. 2. Unsupervised Autoencoder models for the Delta-Marches framework. (A) Structure of
Adversarial Autoencoder (AAE) model for tissue images, comprising a 1024-dimensional latent
space and a discriminator model to distinguish between original and reconstructed images, thereby
encouraging the AAE model to produce images that are indistinguishable from the originals. **(B)**
Two examples (rows) of patches and their nearest neighbors in the 1024-dimensional AAE latent

space. These patches exhibit differing morphology and tumor grades, indicating that the AAE
latent space is discontinuous in these variables. **(C)** Structure of Diffusion Autoencoder (DIFFAE)
comprising a 512-dimensional semantic encoder and a stochastic encoder. **(D)** Examples of
neighboring patches in latent space obtained by DIFFAE exhibit consistent morphological and
tumor grade characteristics, indicating the increased continuity in these variables. **(E)** Comparison
of the percentage of 10 nearest patches (N=120,000) of a patch which come from the same slides
or have the same grade based on the AAE (pink) and DIFFAE (green) latent spaces. Accuracy of
an LDA classifier   to distinguish between low and high-grade patches in the respective latent
spaces. **(F)** Comparison of images reconstructed by AAE and DIFFAE. Accuracy of image
reconstruction in AAE and DIFFAE (N=1000 patches), measured using MSE, SSIM, and FID. **(G)**
Demonstration of the interaction between semantic latent vector and noise image of the stochastic
encoder. Two tissue images (rows) were encoded into semantic vectors, combined with 10 random
noise inputs to synthesize images. Synthetic images on same row share the input tissue phenotype
and (with the exception of 1 patch) have the same grade as predicted by VGG19 tumor grade
classifier but differ in spatial structure. Images in the same column share the spatial patterns as
they are generated by the same noise inputs. **(H)** Demonstration of tumor grade transformation by
traversal of the semantic latent space while preserving spatial structure. Semantic vectors and
stochastic noise images are extracted from two grade 1 tissue image patches. The semantic vectors
were then shifted along the linear classifier axis toward grade 4 and combined with the unchanged
noise images in the DIFFAE decoder to generate a synthetic image sequence illustrating a smooth
transition of tissue characteristics across grades.
189
To overcome the need for specifying low level detail in our latent vector, we adopted diffusion
models that are widely used for generating high quality images based on broad descriptive prompts
(e.g., DALL-E[74]). Diffusion models[75,76,78,79] learn to generate the full spectrum of training images
by iteratively denoising a random signal, and the prompt vector associated with each image merely
serves as a bias directing this process. Specifically, we chose to replace the AAE with a Diffusion
Autoencoder[75] where the image representation is effectively bifurcated into two parts (Fig. 2C):
the latent vector captures the high-level, semantic image content, whereas the low level
interchangeable image aspects (such as the absolute locations of nuclei) are delegated to the
stochastic encoder. Compared to the AAE, DIFFAE i) generates a more biologically meaningful
latent space in which tissue images with similar latent vectors originate from the same slide and
grades (Fig. 2D, E); ii) provides better separability of grades based on Linear Discriminant
Analysis (LDA) in the semantic latent space (Fig. 2E); and ultimately iii) also improves the quality
of image reconstructions, as assessed by visual inspection and standard image quality metrics (Fig.
2F, S2C). Together, these advantages allow the DIFFAE to generate different tissue images
representing the same grade (Fig. 2G) and to simulate the different appearances of the same tissue
as it would progress from Grade 1 to Grade 4 (Fig. 2H). The former image series are generated by
varying the noise component for a fixed position in the semantic latent space. The latter image
series are generated by traversing the semantic latent space (Methods) from regions encapsulating
Grade 1 to regions encapsulating Grade 4, leaving the noise component fixed. The direction of
traversal in this case is defined by the vector of maximal grade separation as determined by a 4-
class linear classifier.
211
212

     Evaluation of synthetic tumor grade data by human pathologists

Fig. 3: Classification of DIFFAE-generated images by expert pathologists. Four pathologists
were tasked with determining for N=80 tissue image patches whether i) the image was real or
synthetic and ii) it displays a low grade (grades 1 or 2) or high grade (grades 3 or 4) tumor. **(A)**
Accuracy of distinguishing real from synthetic images at low (left) or high (right) grade. The
average accuracy obtained is comparable to a random chance level regardless of tumor grade. **(B)**
Tumor grading accuracy on synthetic (left) and real (right) data. Ground truth grade levels were
determined by grade classification model (see Fig. S3 for between pathologist agreement).

We sought to gauge the realism of the DIFFAE-synthesized images by engaging the inspection of
experienced pathologists who were blinded for the source 'synthetic' vs 'real' and grade of the
tumor tissue image patch. Specifically, using the DIFFAE we generated 40 synthetic images
equally split across all four grades (as determined by our grade model) and merged them with a
similarly distributed set of 40 real images. We then presented these 80 images one–by-one in
randomized order to four pathologists with experience in ccRCC pathology. They were tasked with
specifying for each patch the source (real vs synthetic) and grade (low: 1/2 or high: 3/4). The
ability to distinguish real from synthetic images was no better than random (45% vs 56%) for both
low- and high-grade images (Fig. 3A). On average pathologists achieved 92% accuracy in
identifying the grade on both real and synthetic images (Fig. 3B) with ground truth based on our
grade model and similar results using individual pathologists to assign grade (Fig S3A). Albeit not
statistically significant, lower accuracies were observed in classifying low-grade images both real
and synthetic, with about 11% being mistaken for high-grade. This possibly reflects the challenge
of grading small patches: as grade calls are based on the most aggressive cells, a small number of

cells with more aggressive appearing phenotypes could lead to a high-grade call in a low-grade
region. The tumor grading performance was comparable on real and synthetic data both in terms
of agreement with the grade model (Fig S3B, C) and among pathologists (Fig. S3A). Overall, we
conclude that the DIFFAE model generates realistic tissue images that preserve the characteristics
of assigned tumor grades.

Leveraging synthetic image series of grade transitions to nominate grade-driving image
features

Our goal for the hypothesis generating system is to autonomously identify image features that
distinguish specific sample properties of interest – here, cancer grades – and aid pathologists in
formulating hypotheses on the underlying property-driving mechanisms. To this end, we
developed an analysis referred to as *Delta-March* (Fig. 4A) that facilitates the identification of
phenotypes linked to changes in the specific sample properties. Rather than comparing different
tissue images across different grades, which vary in numerous other aspects besides the grade,
Delta-Marches reveal how a particular tissue patch changes solely because of a grade
transformation. While one could attempt to quantify these changes by subtracting raw RGB
intensities between counterfactual images, such differences primarily reflect pixel-level
fluctuations in color lacking semantic or structural context. Therefore, the resulting maps highlight
nearly all tissue regions—excluding only very dark pixels—thereby overwhelming the image with
nonspecific signals and failing to isolate meaningful morphological changes (Fig. S4, S5). In
contrast, to nominate class-defining morphological features in complex tissue images, we utilize
the encoder in the pretrained AAE to extract semantic differentials—noting that a supervised grade
encoder yields similar results (Fig. S4). We subsequently track hotspots of representation changes,
captured in a *Delta-Map*, between consecutive steps of the Delta-March.

The Delta-Maps across grade transitions demonstrate a high degree of spatial modulation with
localized attention hotspots (Fig. 4B). Qualitative comparison with standard class activation
methods suggests that this approach resolves fine-grained structures often smeared by CNN-based
heatmaps, while consistently highlighting the full distribution of altered phenotypes, avoiding the
sparse or fragmented explanations typical of ViT-based approaches (Fig. S1). Intriguingly, visual
inspection of these results highlights a focus on tumor nuclei, consistent with grading rules. The
significance of these hotspots can be appreciated in comparison to a direct jump from grade 1 to 4
(Fig. S4) and to a within-grade negative control (Fig. 4B left column), where we preserve the noisy
image (and hence the position of nuclei) of the initial patch but replace its semantic latent vector
with that of a different patch of the same grade. For a more systematic and unbiased analysis, we
cross-referenced the Delta-Maps with segmentations of tumor and other nuclei, as well as the
vascular network[85]. We then evaluated the enrichment of the Delta-Maps intensity across these
segmented areas. Specifically, we binarized the Delta-Maps into low- and high-intensity regions
and calculated the Jaccard similarity index, defined as the ratio of the intersection to the union
between the binarized Delta-Map and the segmentation mask. Additionally, we compared this
Jaccard index to a random baseline, calculated using segmentation masks from a different
randomly selected patch of the same grade. The table in Fig. 4C presents the ratio of Jaccard
indexes (actual mask to random mask). Higher ratios indicate stronger alignment of the Delta-Map
with the segmented tissue component of interest. The ratios reveal that the Delta-Map produced
by marches across grade transitions is significantly elevated at the loci of tumor nuclei, but not at

the loci of non-tumor nuclei (e.g. immune cells and other cell types) (Fig. 4C). Hence, the Delta-
March determines that cancer cell nuclei are a key indicator of grade transitions, as postulated by
today's clinically implemented grading rules[80-82]. Interestingly, the decreased focus on tumor
nuclei between grades 3 and 4 (bar plots Fig. 4C) is consistent with the inclusion of non-nuclear
tumor cell phenotypes (e.g., rhabdoid or sarcomatoid features) in calling grade 4 (as opposed to
grades 1-3 which are purely nuclear). Negative controls, based on within-grade (across-patient)
transitions, show lower and less specific ratios, further demonstrating the unique roles tumor nuclei
ought to play in across-grade transitions. Although the Jaccard indexes were relatively high in the
other regions, i.e. tissue parts not associated with cell nuclei or vasculature derived from true
masks, they were lower than those obtained from the random masks leading to ratios below 1. This
suggests that no major features exist in the tissue background that would determine the grade
transition. Finally, while the Jaccard indexes associated with vasculature segmentation across
grade transitions were lower than those for tumor nuclei, they were still higher than the indexes
from random masks, i.e. the index ratios between true to random masks are consistently above 1
for all grade transitions. This indicates that vasculature may be a secondary marker of tumor grade.
Interestingly, small-step marches captured vascular changes, whereas direct large jumps from
grade 1 to grade 4 overlooked these subtle features. This underscores the advantages of the Delta-
March, which integrates changes in tissue appearance over a continuous, controlled progression,
allowing the detection of subtle grade-related morphological shifts that may be obscured by tissue
heterogeneity and variation agnostic to the grade transition.

Fig. 4. The capacity to generate hypotheses on grade-driving mechanisms by Delta-Marches.
(A) Overview of the Delta-March framework to identify image features that vary across image classes. The proposed method relies on the detection of spatially distributed features that significantly alter during a semantic latent space traversal in the direction of grade transitions. Within class (across patient) transitions serve as the negative control. **(B)** An example of the Delta-March. Depicting the real/synthetic images from the latent space transition (top) the corresponding cell types (middle) and an overlay of the Delta-Map intensities between successive steps (bottom) during latent space transitions between indicated tumor grades. **(C)** Jaccard similarity analysis comparing Delta-Maps to tissue segmentations. For N=977 real grade 1 samples transitioning through four grades, Delta-Maps were binarized (threshold = 0.5) and evaluated, against both actual tissue segmentations and random masks, using the Jaccard index (intersection over union). The table displays the median ratio of Jaccard indexes for actual masks to random masks, revealing the prominent variation of tumor nuclei during grade transitions. Bar plots depict Jaccard indexes for indicated tissue components during grade transitions. Dash line is the average Jaccard rate across all samples and components in each transition. **(D)** Variation of tumor and non-tumor nuclear phenotypes across grades in real and synthetic data (N=500 patches per grade). Synthetic grades 1–2 patches are generated by traversing from real grade 4 images (N = 556) toward grade 1, and grades 3–4 patches from grade 1 (N = 977) toward grade 4. Nucleoli are identified as local extrema in the hematoxylin channel, considering them as "nucleoli". **(E)** Relationship between

tumor nuclear area and "nucleoli" number in real and synthetic data. Contour plot highlights the
joint distribution (N=500). Inset, correlation between nuclear size and nucleolar count (with
N=100 random samples of 100 patches per grade) in real vs synthetic data **(F)** Comparison of the
statistical power to detect increase in per-patch average tumor nuclear size with grade using
samples from real and synthetic data. In the real data, for each grade pair comparison, images
(N=100 for each grade) were randomly sampled (Real-Unpair), while in the synthetic data, images
were generated either from the same (Syn-Pair) or from independent (Syn-Unpair) latent
transitions from grade 1 to grade 4. The sign test was used to compare average nuclear size between
two groups (N = 100 patches), repeated 1,000 times and to compute the mean of log(p-value)
across repetitions. **(G)** Analysis of percentage area covered by vasculature across grade. The
coverage decreases in both real and synthetic data (N=500 patches per grade).

Next, we focused on the putative phenotypic changes in nuclei from across-grade transitions in
synthetic tissue image patches (Fig. 4D). We found that tumor cell nuclei, but not nuclei of other
cell types, increased in size with grade, highlighting the cell-type awareness of the semantic latent
space. Moreover, the count of peaks of hematoxylin intensity per nucleus, which we use as a proxy
for prominent "nucleoli" (Methods), also grew only in tumor cells (Fig. 4D). Notably, the change
in nuclear size and nucleoli between grade 3 and grade 4 was relatively less pronounced compared
to other grade transitions in both real and synthetic data, reflecting nuclear features are not the
primary distinguishing feature for grade 4 classification, consistent with the reduced Jaccard ratio
shown in Fig. 4C. This shows that the IDL system based on Delta-Marches reproduces established
grading rules directly for the data. Interestingly, the tumor grade effect on nuclei is more
pronounced in grade transitions in the semantic latent space, with significantly smaller nuclei in
synthetic low grades (1–2) and larger nuclei in synthetic high grades (3–4) compared to real data
(Fig. 4D). While the individual trends for nuclei and "nucleoli" are largely in agreement between
real and synthetic data, the correlation between these two features is stronger in the synthetic data
(Fig. 4E, S6). Thus, while real image patches display some of the expected grade related features,
these are more consistently present in synthetic data.

We sought to more formally test whether the ability of latent space traversals to solely modulate
grade increased the statistical power over traditional cross-grade comparison where other non-
grade aspects may also change. Specifically, we wondered to what extent any differences arose
from our synthetic trajectories exaggerating grade features as opposed to overcoming interpatient
heterogeneity within a grade by following the same patch across grades. To address this, we
compared the average nuclear size across tumor grades (1 to 4) using both real and synthetic data.
In the real data, images were randomly sampled from each grade group (Real-Unpair). For
synthetic data, two approaches were used for each grade-pair comparison: (1) Syn-Unpair, where
samples originated from independent latent space transitions, which would allow us to test solely
the difference between synthetic and real feature distributions; (2) Syn-Pair, where counterfactual
samples were derived from the same latent space trajectories grade 1 to grade 4, thereby potentially
overcoming interpatch variability. For each grade pair, we applied the sign test to compare the per-
patch average nuclear size between groups (N = 100 patches), repeating the analysis 1,000 times.
The modest and inconsistent p-value improvements in Syn-Unpair (Fig. 4F) suggest that feature
amplification alone has a limited impact on statistical separation. In contrast, the consistently
smaller p-values observed in the Syn-Pair data highlight the power of counterfactual analysis
enabled by Delta Marches to emphasize grade-relevant tissue features more effectively than

conventional cross-grade comparisons. Notably, the synthetic pair comparisons produced the most significant results, with p-values up to 10^{20} times smaller than those observed in real data for adjacent grade pairs (Fig. 4F), where strong correlations within a trajectory help control for heterogeneity. For more distant grades, the correlation between nuclear sizes weakens, and differences are increasingly driven by distributional shifts. While in this case, the nuclear size has a strong enough effect to be detected also in real data, this approach will allow us to pinpoint more complex traits with smaller effect sizes and in more data-limited applications. Taken together these findings highlight two key advantages of the proposed Delta-March: (1) the ability to isolate the effect of individual variables on phenotype changes using analysis of counterfactual images, and (2) the use of small, controlled transitions along a biologically meaningful latent axis to enhance statistical power and provide a more precise and interpretable means of uncovering underlying disease mechanisms.

Finally, we were curious to see whether the reduction in vasculature with grade previously conjectured by us and others[85] was also reflected in synthetic image series of latent space transitions in the direction from low to high tumor grades. We found indeed that the model recapitulated this effect to a level comparable to that in real data (Fig. 4G). We note that unlike tumor-nuclei, within grade transitions seemed to impact the vasculature pattern (Fig. 4C, 1st column), possibly because there are non-grade related aspects that also impact the specific vascular pattern observed.

DISCUSSION

There are three fundamental challenges in using real world data to identify meaningful phenotypic associations between tissue morphology and disease properties (e.g. mutation status of a single gene or tumor aggressiveness for which grade is a proxy). First, morphological traits manifest highly non-linearly as image features, and much of the variation in the image pixel space, such as absolute positions of nuclei, is irrelevant. Second, it is rare to find samples differing solely in the disease property of interest, and thus observed morphologic changes across specimens are confounded by differences in non-related properties. Third, even if we could solely change the disease property of interest, large biological changes (e.g. a jump from grade 1 to 4) will impact multifarious aspects of morphology due to the complex inter-connected networks of influence. In attempting to overcome these challenges, we take inspiration from the production of caricatures where cartoonists identify the essence of a subject they wish to highlight and then depict it with a minimal set of strokes. Translating this process into an AI system, we address these challenges by a) using a DIFFAE to produce meaningful latent representations of images consigning irrelevant parts into a noise vector, b) identifying a direction in the latent space such that changes are solely associated with the property of interest, and by c) traversing the latent space in a Delta-March along this direction to identify the most salient affected regions in the image. Thus, the presented framework serves as an AI-powered cartoonist that, when presented with representative data of both consequential and inconsequential variations, autonomously extracts the association between tissue appearance and the property of interest.

Although xAI activation maps and Delta-Marches both highlight areas of importance overlaid on images, they represent fundamentally different concepts and corresponding outputs. Delta-Maps represent generative estimates of counterfactual differences between class-shifted images, an

explicit simulation of how tissue morphology would change under an idealized shift in biological
state. As a result, Delta-Maps not only carry directionality but the area highlighted represents the
scale of the phenotypes being changed, whether sub-cellular or architectural. In contrast, xAI
activation maps measure a pre-defined classifier's local sensitivity to perturbations in the image.
As classifiers are optimized for classification accuracy, the spatial distribution of these maps,
whether focused on a single pixel or a broad range, primarily reflects the functioning of the
classifier and less so the underlying biological principles.

While the proposed strategy is agnostic to data type and biological process, we provide proof of
principle demonstration in recovering grading criteria for ccRCC pathology. Our previous
generative approach for single cell images[60] used a simpler AAE encoder and needed to exaggerate
effects beyond the naturally observed variation to highlight pseudopodal extensions as a readout
of metastatic propensity. Here in a more complex tissue setting, we used a more sophisticated
approach to remove distracting features and highlight features of interest. First, we showed that
the DIFFAE's split of the latent space into meaningful and "noise" aspects (associated e.g., with
nuclear positions) results in a more biologically meaningful representation of histopathology
images than a simple AAE[60]. Next, by moving in the direction of grade change in the latent space
we synthetically warped images to model idealized tumor grade transitions while holding other
aspects of tumor tissue variation fixed. The resulting synthetic images more consistently exhibited
changes to multiple grade-related image features (nuclear size and nucleolar count) than real
images (Fig. 4D, E) and even led to a slight increase in pathologists' classification of grades (Fig.
3B). Moreover, comparing nuclei to their synthetically grade warped versions increased statistical
power relative to real samples differing in grade (Fig. 4F), suggesting our counterfactual approach
overcomes sample to sample variation. This could enable detection of subtle effects for which
available experimental data does not provide adequate power. Finally, the Delta-March enables a
continuous, controlled modeling of the increase of grade with single-cell spatial resolution, thereby
allowing us to identify a minimal set of grade-associated changes. Specifically, our Delta-March
process highlighted the tumor nuclei as most impacted, allowing us to then recover the known
grading rule of increased nuclear size while the increase in number of local intensity maxima
within the nuclear masks mirrors the rule of increased nucleolar prominence. Interestingly, in
identifying the decrease of vasculature with grades, which we and others have noted before[83-85],
our approach goes beyond the formally identified grading rules. VHL loss, an initiating event in
ccRCC, causes increased vasculature as cells perceive themselves to be in hypoxic conditions[86],
but with increasing grade cells can survive without such vasculature, likely due to a metabolic shift
away from oxidative metabolism towards the Warburg effect[87]. Taking together these results
suggest our approach has the capacity to distill the essence of image properties associated with
tumor grade change.

Future work can build on our work in several ways. Conditional diffusion models[76,88] have shown
promise in transforming histopathologic images to reflect changes in molecular state, but the large
image changes produced in these transformations limit interpretability. Our Delta-March type
procedure instead uses smaller steps in a latent space to capture an integral of more subtle changes.
More work is needed to determine the optimal nature of this space (e.g. learnt during the diffusion
model training as done here or using pre-existing representations from foundation models[77,89-91]),
and its best traversal. If successful, such an approach has the ability to nominate novel relationships
between morphology and genetic/disease state. Cancer is an excellent application area for the

proposed Delta-March framework because of the multifactorial root causes of disease progression
and their manifestation in complex morphological signals. Other diseases with similar traits
include neurodegeneration, where different strains (protein assemblies differing in structure) have
been hypothesized to underlie complex aggregate morphologies that are the gold standard for
disease classification[92]. More broadly, image classification and generation have traditionally been
separate domains. Yet, as the adoption of machine learning algorithms in biomedical domains is
limited by their interpretability rather than their classification performance, we anticipate that the
development of representations that enable both classification and generative visualization of this
space will become important. Thus, our study paves the way for deeper investigations into disease
mechanisms, providing a tool to explore how morphological features may relate in unexpected
ways to disease progression and treatment outcomes. We anticipate that the proposed Delta-March
framework will uncover patterns in tissue samples that will inform both clinicians and life
scientists in their quests to deliver more specific and personalized treatment, and to identify the
processes that govern a particular pathophysiology.

MATERIALS AND METHODS

Data

All analyses were performed on 224x224-pixel image patches extracted at 20X magnification
(~0.5 microns per pixel) from "tumor" regions of Hematoxylin and Eosin (H&E)-stained whole
slide images (WSIs) of clear cell renal cell carcinoma (ccRCC). The image patches were drawn
from one of two cohorts:

1. Grade cohort: Comprising 128 slides with localized grade annotation. An expert
pathologist (V. Panwar) annotated specific areas within tumor regions and individually
assigned them grades (1- 4), to provide a more precise grade ground truth than the patient
level grade used in the clinic. Patches were randomly sampled from these annotations and
inherited the grade of their parent annotation.
2. Mayo Cohort: Comprising 1,000 WSIs from the Mayo Clinic repository, as previously
described[93]. Tumor regions were automatically identified using a pretrained region
classification model, and patches were randomly sampled within these regions.

Adversarial Autoencoder (AAE)

Architecture: The AAE model adopts an unsupervised framework[60], employing a convolutional
encoder-decoder architecture. The encoder compresses image through five convolutional blocks,
incrementally increasing channel sizes (256, 512, 1024, 1024, and 1024), each followed with batch
normalization and Leaky ReLU activation layers. Latent space representations are generated via a
fully connected layer. The decoder reverses this process, reconstructing the original image via
transposed convolutional layers, batch normalization, and sigmoid activations. Following the
original AAE paper[94], our model uses an adversarial component intended to make the latent
distribution indistinguishable from a normal distribution. Additionally, to enhance the
reconstruction quality of high-resolution tissue images, we added a discriminator, similar to those
used in Generative Adversarial Networks (GANs), that ensures the real and synthetic images were

indistinguishable. This discriminator has five convolutional layers with batch normalization and
Leaky ReLU activations, concluding with a fully connected layer and sigmoid output.

Training: Training was unsupervised, as is standard for autoencoders. However, to ensure that the
model sees a wide distribution of grades, for training and testing, we utilized 120,000 patches, with
30,000 patches per tumor grade derived from the Grade cohorts. Training involved minimizing a
composite loss function comprising reconstruction, adversarial, and discriminator loss terms,
balanced for optimal performance. The model was trained for 30 epochs with a fixed learning rate
$r = 10^{-4}$ for the AAE and $r = 10^{-5}$ for the discriminator, respectively.

Diffusion Autoencoder (DIFFAE)

Architecture: We adopted the DIFFAE model[75] from https://github.com/phizaz/diffae. Briefly, the
architecture of a diffusion autoencoder integrates a semantic encoder, a diffusion process, and a
decoder to create a robust generative framework. The semantic encoder compresses input data into
a latent representation, which is then progressively corrupted through a series of controlled noise-
injecting steps in the forward diffusion process. The decoder reverses these steps, refining the
latent representation to reconstruct the original input. For our experiments, we retained all default
parameter values from the original implementation, with adjustments made solely for the input
image dimensions (224x224 pixels).

Training: Two distinct training protocols were utilized. For the comparative analysis (Fig. 2)
against the AAE model, we trained the DIFFAE model on a subset of 8,000 patches subsampled
from the 120,000 patches used in AAE training, evenly distributed across tumor grades. For the
final model used in downstream analyses, we trained the unsupervised DIFFAE model on an
extended dataset of 18,000 images augmented with 10,000 unannotated tissue patches extracted
from the Mayo Cohort to capture broader tissue structural variability.

Image Grade Classification and CAM

We trained a grade classifier with a VGG19 backbone on 120,000 patches over 50 epochs with a
learning rate of 10^{-4}, achieving 92% accuracy on the training dataset. The VGG19 model was
pretrained on the ImageNet dataset and fine-tuned for four-grade classification using cross-entropy
loss.

Class activation map (CAM) is a widely used technique for generating heatmaps that visualize
important regions influencing deep learning model predictions. To validate the performance of
CAM-based approaches on detecting critical features related to tumor grade, we performed
GradCam++, FullGrad, and AblationCAM for our pretrained VGG19 grade classifier focusing on
the last convolution layer. These CAM-based models were implemented using the
pytorch_grad_cam library.

We additionally sought to test if these results extended to non-CNN architectures. To this end, we
trained a Vision Transformer (ViT), which reached slightly higher accuracy (~97%). We
visualized the model's focus using the attention rollout process[59] (Fig. S1).

DIFFAE latent space transitions

Our methodology for class transitions is based on the attribute manipulation technique from the DIFFAE framework[75]. Specifically, in addition to the unsupervised autoencoder, DIFFAE framework[75] introduces a linear classifier trained on latent vectors from the semantic encoder to identify the axes that separates classes. Attribute manipulation is then performed by traversing the semantic vector along the corresponding axis. In our work, we applied this approach to 8,000 annotated patches across four tumor grades, analyzing the projection of latent spaces onto classifier axes (Fig. S7). Based on the classifier projections, to transition towards higher grades, we adjust the latent representation linearly along the direction of the grade 4 weight vector, while to transition towards lower grades, we shift it along the grade 1 weight vector.

To simulate progression from grade 1 to higher grades, we manipulate the semantic latent vector while keeping the stochastic component fixed, as obtained from the semantic and stochastic encoders of DIFFAE. The stochastic component (noisy image) is obtained from the real grade 1 image by applying the forward diffusion process up to $T = 250$, a mid-range diffusion depth that introduces substantial Gaussian corruption in fine-scale details while retaining coarse spatial structure. By fixing this stochastic component, we ensure that the generative process is anchored to the original tissue architecture; denoising with a shifted semantic vector thus yields a "warped" version of the original image that retains spatial correspondence while exhibiting the target grade phenotype. The semantic vector is then standardized and incrementally shifted along the grade 4 weight vector in step sizes proportional to the square root of the vector's dimensionality. This step size, used in DIFFAE[75] for isotropic random walks in 512-dimensional Euclidean space, ensures smooth progression between grades while maintaining the meaningful structure of the tissue representation. The shifted vector is subsequently de-standardized and passed to the DIFFAE decoder along with the original stochastic noisy image to generate synthetic tissue images. The transition halts either when the generated image is classified as grade 4 by the pretrained VGG19 tumor-grade classifier or after a maximum of four steps. Upon determining the endpoint, 20 intermediate semantic nodes are interpolated along the transition path. These nodes, along with the original noisy image, are input to the DIFFAE decoder to generate synthetic images depicting the across-grade transition. The tumor grades of these generated images are validated using the VGG19 classifier.

Synthetic Data Sets:

Generating a synthetic image from a source of the same grade is not equivalent to generating it from a different grade, as the former constitutes simple reconstruction while the latter requires active transformation. To ensure all synthetic images were produced through the same generative process, we exclusively generated target phenotypes by traversing real samples starting from the opposite grade extreme. We generated synthetic images for two purposes:

1. Pathologist evaluation (Fig. 3): We applied this strategy to real samples from all four grades. Transitions pushed toward grade 1 and grade 4 were used to produce the requisite low and high-grade representations, respectively (Table S1).
2. Identification of grade associated features: To generate high grade samples, we traversed 5,000 real grade 1 samples, confirmed by both pathologist and model prediction, toward grade 4. Of these, 977 trajectories transitioned across all four grades (1–4) and the highest-confidence

images were selected for each grade. Conversely, for low grade samples we reversed the process by shifting 5,000 real grade 4 patches toward grade 1, yielding 556 synthetic samples spanning all grades. For within-grade transitions (across patients), we generated synthetic pairs where the stochastic encoding of a tissue sample was preserved, but its semantic vector was replaced with that of a random tissue sample of the same grade from a different patient.

Additional visualizations of latent transitions are shown in Fig. S4 and S5.

Deep Learning filter for Delta-March

To identify phenotypes linked to class changes, we developed the Delta-March analysis pipeline (Fig. 4A). This pipeline uses a CNN filter derived from the first 9 layers of our pretrained AAE. Each image pair is passed through this filter, generating 28x28 feature arrays with 1024 channels. These feature arrays are subtracted to compute Delta arrays, which are then upscaled to match the original image dimensions of 224x224. The absolute values of the resulting arrays are averaged across all 1024 channels to produce Delta maps, highlighting areas of morphological difference between the two input images. Additionally, we also evaluated the Delta-Maps derived from the first 13 layers of our pretrained VGG19-based tumor grade classifier following a similar pipeline (Fig. S4, S5, and S8). We selected this depth for Delta-March filter to capture feature maps that retain low-level structural details while beginning to incorporate high-level tumor-grade features. To demonstrate the necessity of a CNN filter for capturing morphological feature changes, we computed a naïve baseline that subtracts raw RGB pixel intensities and reports the mean absolute difference across channels (Fig. S4, S5).

Delta-March Transitions

We initially focused on the 977 across-grade transitions (described above) from grade 1 to grade 4, which pass through intermediate grades 2 and 3. To capture fine-grained morphological changes, the transitions were subdivided into sub-transitions: real grade 1 to synthetic grade 2, synthetic grade 2 to synthetic grade 3, and synthetic grade 3 to synthetic grade 4. We also extended the Delta-March analysis to across-patient transitions by swapping semantic vectors of tissue samples between different patients of the same grade, enabling a deeper understanding of tumor grading features.

Delta-March average intensity rate

To identify key tissue components influencing tumor grading we calculate the average intensity of the Delta-March across tumor nuclei, non-tumor nuclei, vasculature, and other (not nucleus or vasculature). Nuclei classification and vasculature segmentation masks for a single grade image were derived using corresponding models developed by the Rajaram lab[85]. The nuclei segmentation pipeline classifies pixels into three classes: 2 = tumor nuclei, 1 = non-tumor nuclei, and 0 = non-nuclei. The vasculature segmentation model assigns pixels as either 1 = vasculature or 0 = non-vasculature. Composite, across-grade masks were derived as follows:

1. Merging: Nuclear/Vascular masks from the initial and final tissue images were merged by assigning each pixel the maximum label present across both images.

2. Artifact Removal: We identified "ghost nuclei" (nuclei appearing in one mask but not the other,
typical of generative artifacts) and eliminated them from the combined mask to prevent
biological misinterpretation.
3. Integration: The merged nuclei and vasculature masks were integrated into a single four-class
map: 3 = tumor nuclei, 2 = non-tumor nuclei, 1 = vasculature, and 0 = background. To prevent
bias in overlapping regions, pixels classified as both vasculature and nucleus were randomly
reassigned to a single class.

To quantify the localization of morphological changes to specific cell types, we calculated the
Jaccard similarity index (intersection over union, IoU) between binarized Delta-maps and the
segmentation masks as follows. First, the Delta-map values were linearly normalized to the [0,1]
range per patch and values greater than 0.5 were set to 1 and the rest to 0. The Jaccard similarity
index for each component was computed as: $J_i = \frac{|BH \cap M_i|}{|BH \cup M_i|}$, where M_i, $i = 0,1,2,3$ represents the
binary segmentation of component i (3 = tumor nuclei, 2 = non-tumor nuclei, 1 = vasculature, 0 =
other), and BH denotes the binary Delta-Map in each sample.

To establish a baseline for comparison, we computed the Jaccard index against segmentation
masks from randomly selected patches within the same sub-transition grade. Next, we computed
ratio of true and random Jaccard indexes for each patch and reported the median value across all
patches for a grade transition (Table in Fig. 4C). Additionally, we assessed the statistical
significance of enrichment in specific cell types by comparing the Delta-map similarity against the
random baseline, using a one-sided T-test (Bar plot in Fig. 4C).

Nucleoli Detection

Since standardized nucleolus detection algorithms are unavailable, we developed a heuristic
approach that identifies "nucleoli" as intensity peaks in Hematoxylin-stained sections of H&E
images. We first convert the image to the HED color space and isolate the hematoxylin channel,
normalizing and smoothing it using a Gaussian filter with standard deviation $\delta = 1$ to enhance
nucleoli detection. We then identify nuclei on the nuclei mask, distinguishing between non-tumor
and tumor nuclei based on our pretrained nuclei segmentation. "Nucleoli" are detected as local
maxima (prominence threshold $\alpha = 0.08$) in the smoothed hematoxylin image, representing
darker, separate spots within the nuclei. However, as nuclei themselves represent local peaks in
hematoxylin intensity, this approach initially detected "nucleoli" in nearly all nuclei (Fig. S9). To
correct this, we subtract a count of one from each nucleus with detected nucleoli. Finally, we
calculate the average number of "nucleoli" per nucleus for each type, providing quantitative
nucleoli statistics.

Counterfactual analysis on real and synthetic data

To highlight Delta-March's ability to improve statistical power in detecting underlying biological
mechanisms, we performed a counterfactual analysis (Fig. 4F) examining average nuclear area
across tumor grades 1 to 4. We analyzed latent traversal from grade 1 to grade 4 with 977
corresponding patches per grade. For real data, we sampled 977 patches per grade to maintain
comparability with synthetic data. Samples for each grade-pair (N = 100 patches per group) are
obtained through three strategies: (1) Real-Unpair: Randomly sampled image patches from each

grade group using the real dataset, (2) Syn-Pair: Synthetic image patches for each grade pair derived from the same random latent trajectory, thus preserving progression continuity in the synthetic generation, (3) Syn-Unpair: Synthetic image patches from independent latent trajectories, simulating samples from unrelated transitions. To quantify differences in nuclear area, we applied the sign test to compare the per-patch average nuclear area between the two grades. The entire process was repeated 1,000 times to assess the robustness and consistency of the statistical signal, measured by the mean log-transformed P-value.

Data and Code Availability:

WSI for the Mayo cohort are available at https://doi.org/10.25452/figshare.plus.19310870. All code used in this paper, including a Jupiter notebook to generate all figures, is attached as supplementary material and will be released on the Rajaram Lab GitHub page upon acceptance.

SUPPLEMENTARY MATERIALS

Figure S1-S9, Table S1.

REFERENCES AND NOTES

Topol, E. J. High-performance medicine: the convergence of human and artificial intelligence. *Nat Med* **25**, 44–56 (2019). https://doi.org/10.1038/s41591-018-0300-7

Gu, J., Gao, C. & Wang, L. The Evolution of Artificial Intelligence in Biomedicine: Bibliometric Analysis. *JMIR AI* **2**, e45770 (2023). https://doi.org/10.2196/45770

Avsec, Z. *et al.* Effective gene expression prediction from sequence by integrating long-range interactions. *Nat Methods* **18**, 1196–1203 (2021). https://doi.org/10.1038/s41592-021-01252-x

Dudnyk, K., Cai, D., Shi, C., Xu, J. & Zhou, J. Sequence basis of transcription initiation in the human genome. *Science* **384**, eadj0116 (2024). https://doi.org/10.1126/science.adj0116

Yang, M. *et al.* Integrating convolution and self-attention improves language model of human genome for interpreting non-coding regions at base-resolution. *Nucleic Acids Res* **50**, e81 (2022). https://doi.org/10.1093/nar/gkac326

Zhang, Y. *et al.* Histopathology images-based deep learning prediction of prognosis and therapeutic response in small cell lung cancer. *NPJ Digit Med* **7**, 15 (2024). https://doi.org/10.1038/s41746-024-01003-0

Bychkov, D. *et al.* Deep learning based tissue analysis predicts outcome in colorectal cancer. *Scientific Reports* **8** (2018).

Nitti, P. *et al.* Cell-Tissue Interaction: The Biomimetic Approach to Design Tissue Engineered Biomaterials. *Bioengineering (Basel)* **10** (2023). https://doi.org/10.3390/bioengineering10101122

Bhattacharya, A. *et al.* Exploring the interaction between extracellular matrix components in a 3D organoid disease model to replicate the pathophysiology of breast cancer. *J Exp Clin Cancer Res* **42**, 343 (2023). https://doi.org/10.1186/s13046-023-02926-4

Cai, X., Wang, K. C. & Meng, Z. Mechanoregulation of YAP and TAZ in Cellular Homeostasis and Disease Progression. *Front Cell Dev Biol* **9**, 673599 (2021). https://doi.org/10.3389/fcell.2021.673599

11   Cotteret, S. & Chernoff, J. The evolutionary history of effectors downstream of Cdc42 and
Rac. *Genome Biol* **3**, REVIEWS0002 (2002). https://doi.org/10.1186/gb-2002-3-2-
reviews0002
12   Graziani, V., Rodriguez-Hernandez, I., Maiques, O. & Sanz-Moreno, V. The amoeboid
state as part of the epithelial-to-mesenchymal transition programme. *Trends Cell Biol* **32**,
228–242 (2022). https://doi.org/10.1016/j.tcb.2021.10.004
13   Park-Holohan, S. J. *et al.* Stress-dependent activation of myosin in the heart requires thin
filament activation and thick filament mechanosensing. *Proc Natl Acad Sci U S A* **118**
(2021). https://doi.org/10.1073/pnas.2023706118
14   Venturini, V. *et al.* The nucleus measures shape changes for cellular proprioception to
control dynamic cell behavior. *Science* **370** (2020).
https://doi.org/10.1126/science.aba2644
15   Weems, A. D. *et al.* Blebs promote cell survival by assembling oncogenic signalling hubs.
Nature **615**, 517–525 (2023). https://doi.org/10.1038/s41586-023-05758-6
16   Theocharis, A. D., Skandalis, S. S., Gialeli, C. & Karamanos, N. Extracellular matrix
structure. *Advanced drug delivery reviews* **97**, 4–27 (2016).
17   Zhang, Y. J. *et al.* Single-cell RNA sequencing in cancer research. *Journal of Experimental*
& Clinical Cancer Research **40** (2021). https://doi.org/ARTN 81

10.1186/s13046-021-01874-1
18   Aleskandarany, M. A. *et al.* Tumour Heterogeneity of Breast Cancer: From Morphology
to Personalised Medicine. *Pathobiology* **85**, 23–34 (2018).
https://doi.org/10.1159/000477851
19   Paritala, P. K. *et al.* Plaque Longitudinal Heterogeneity in Morphology, Property, and
Mechanobiology. *Cerebrovascular Diseases* **50**, 510–519 (2021).
https://doi.org/10.1159/000515690
20   Acosta, P. H. *et al.* Intratumoral Resolution of Driver Gene Mutation Heterogeneity in
Renal Cancer Using Deep Learning. *Cancer Research* **82**, 2792–2806 (2022).
https://doi.org/10.1158/0008-5472.Can-21-2318
21   Vega, A. R. *et al.* Deep learning reveals disease-specific signatures of white matter
pathology in tauopathies. *Acta Neuropathologica Communications* **9** (2021).
https://doi.org/ARTN 170

10.1186/s40478-021-01271-x
22   Kromp, F. *et al.* Evaluation of Deep Learning Architectures for Complex
Immunofluorescence Nuclear Image Segmentation. *Ieee Transactions on Medical Imaging*
40, 1934–1949 (2021). https://doi.org/10.1109/Tmi.2021.3069558
23   Wang, Y. X. *et al.* Predicting Molecular Phenotypes from Histopathology Images: A
Transcriptome-Wide Expression-Morphology Analysis in Breast Cancer. *Cancer Research*
81, 5115–5126 (2021). https://doi.org/10.1158/0008-5472.Can-21-0482
24   Chen, X. X. *et al.* Recent advances and clinical applications of deep learning in medical
image analysis. *Medical Image Analysis* **79** (2022). https://doi.org/ARTN 102444

10.1016/j.media.2022.102444
25   Campanella, G. *et al.* Clinical-grade computational pathology using weakly supervised
deep learning on whole slide images. *Nat Med* **25**, 1301–1309 (2019).
https://doi.org/10.1038/s41591-019-0508-1

26 Coudray, N. *et al.* Classification and mutation prediction from non-small cell lung cancer
histopathology images using deep learning. *Nat Med* **24**, 1559–1567 (2018).
https://doi.org/10.1038/s41591-018-0177-5
27 Ehteshami Bejnordi, B. *et al.* Diagnostic Assessment of Deep Learning Algorithms for
Detection of Lymph Node Metastases in Women With Breast Cancer. *JAMA* **318**, 2199–
2210 (2017). https://doi.org/10.1001/jama.2017.14585
28 Sbaraglia, M., Bellan, E. & Dei Tos, A. P. The 2020 WHO Classification of Soft Tissue
Tumours: news and perspectives. *Pathologica* **113**, 70–84 (2021).
https://doi.org/10.32074/1591-951X-213
29 Turkki, R. *et al.* Breast cancer outcome prediction with tumour tissue images and machine
learning. *Breast Cancer Res Treat* **177**, 41–52 (2019). https://doi.org/10.1007/s10549-019-
05281-1
30 Nagtegaal, I. *et al.* Morphological changes in tumour type after radiotherapy are
accompanied by changes in gene expression profile but not in clinical behaviour. *J Pathol*
204, 183–192 (2004). https://doi.org/10.1002/path.1621
31 Birch, J. M. *et al.* Relative frequency and morphology of cancers in carriers of germline
TP53 mutations. *Oncogene* **20**, 4621–4628 (2001). https://doi.org/10.1038/sj.onc.1204621
32 Ahmed, A. A. & Abedalthagafi, M. Cancer diagnostics: The journey from
histomorphology to molecular profiling. *Oncotarget* **7**, 58696–58708 (2016).
https://doi.org/10.18632/oncotarget.11061
33 Oumarou Hama, H., Aboudharam, G., Barbieri, R., Lepidi, H. & Drancourt, M.
Immunohistochemical diagnosis of human infectious diseases: a review. *Diagn Pathol* **17**,
17 (2022). https://doi.org/10.1186/s13000-022-01197-5
34 Guarner, J. & Brandt, M. E. Histopathologic diagnosis of fungal infections in the 21st
century. *Clin Microbiol Rev* **24**, 247–280 (2011). https://doi.org/10.1128/CMR.00053-10
35 Wang, W. *et al.* Glioblastoma pseudoprogression and true progression reveal spatially
variable transcriptional differences. *Acta Neuropathol Commun* **11**, 192 (2023).
https://doi.org/10.1186/s40478-023-01587-w
36 Riefolo, M., Conti, M., Longhi, S., Fabbrizio, B. & Leone, O. Amyloidosis: What does
pathology offer? The evolving field of tissue biopsy. *Frontiers in Cardiovascular Medicine*
9 (2022).
37 Nakamura, K. *et al.* Expression of Interleukin-6 and the Interleukin-6 Receptor Predicts
the Clinical Outcomes of Patients with Soft Tissue Sarcomas. *Cancers (Basel)* **12** (2020).
https://doi.org/10.3390/cancers12030585
38 Aswolinskiy, W. *et al.* PROACTING: predicting pathological complete response to
neoadjuvant chemotherapy in breast cancer from routine diagnostic histopathology
biopsies with deep learning. *Breast Cancer Res* **25**, 142 (2023).
https://doi.org/10.1186/s13058-023-01726-0
39 Zhu, W. *et al.* Development of a prognostic pyroptosis-related gene signature for head and
neck squamous cell carcinoma patient. *Cancer Cell Int* **22**, 62 (2022).
https://doi.org/10.1186/s12935-022-02476-3
40 van Leeuwen, M. M. *et al.* Clinicopathological and prognostic value of calcification
morphology descriptors in ductal carcinoma in situ of the breast: a systematic review and
meta-analysis. *Insights Imaging* **14**, 213 (2023). https://doi.org/10.1186/s13244-023-
01529-z

Chatila, W. K. *et al.* Genomic and transcriptomic determinants of response to neoadjuvant therapy in rectal cancer. *Nat Med* **28**, 1646–1655 (2022). https://doi.org/10.1038/s41591-022-01930-z

Niehues, J. M. *et al.* Generalizable biomarker prediction from cancer pathology slides with self-supervised deep learning: A retrospective multi-centric study. *Cell Rep Med* **4**, 100980 (2023). https://doi.org/10.1016/j.xcrm.2023.100980

Fong, R. C. & Vedaldi, A. Interpretable Explanations of Black Boxes by Meaningful Perturbation. *2017 Ieee International Conference on Computer Vision (Iccv)*, 3449–3457 (2017). https://doi.org/10.1109/Iccv.2017.371

Zhang, Q. S. & Zhu, S. C. Visual interpretability for deep learning: a survey. *Frontiers of Information Technology & Electronic Engineering* **19**, 27–39 (2018). https://doi.org/10.1631/Fitee.1700808

Tang, Z. *et al.* Interpretable classification of Alzheimer's disease pathologies with a convolutional neural network pipeline. *Nat Commun* **10**, 2173 (2019). https://doi.org/10.1038/s41467-019-10212-1

Li, X. H. *et al.* Interpretable deep learning: interpretation, interpretability, trustworthiness, and beyond. *Knowledge and Information Systems* **64**, 3197–3234 (2022). https://doi.org/10.1007/s10115-022-01756-8

Kang, W. J. *et al.* An Interpretable Machine Learning Model with Deep Learning-Based Imaging Biomarkers for Diagnosis of Alzheimer's Disease. *Medical Image Computing and Computer Assisted Intervention, Miccai 2023 Workshops* **14393**, 69–78 (2023). https://doi.org/10.1007/978-3-031-47401-9_7

Rezk, E., Eltorki, M. & El-Dakhakhni, W. Interpretable Skin Cancer Classification based on Incremental Domain Knowledge Learning. *J Healthc Inform Res* **7**, 59–83 (2023). https://doi.org/10.1007/s41666-023-00127-4

Arun, N. *et al.* Assessing the Trustworthiness of Saliency Maps for Localizing Abnormalities in Medical Imaging. *Radiol Artif Intell* **3**, e200267 (2021). https://doi.org/10.1148/ryai.2021200267

Cao, R. *et al.* A transferrable and interpretable multiple instance learning model for microsatellite instability prediction based on histopathology images. *bioRxiv* (2020).

Kim, C. *et al.* Transparent medical image AI via an image-text foundation model grounded in medical literature. *Nat Med* **30**, 1154–1165 (2024). https://doi.org/10.1038/s41591-024-02887-x

Kaczmarzyk, J. R., Saltz, J. H. & Koo, P. K. Explainable AI for computational pathology identifies model limitations and tissue biomarkers. *ArXiv* (2024).

Diao, J. A. *et al.* Human-interpretable image features derived from densely mapped cancer pathology slides predict diverse molecular phenotypes. *Nat Commun* **12**, 1613 (2021). https://doi.org/10.1038/s41467-021-21896-9

Wang, R., Khurram, S. A., Walsh, H., Young, L. S. & Rajpoot, N. A Novel Deep Learning Algorithm for Human Papillomavirus Infection Prediction in Head and Neck Cancers Using Routine Histology Images. *Mod Pathol* **36**, 100320 (2023). https://doi.org/10.1016/j.modpat.2023.100320

Kunes, R. Z., Walle, T., Land, M., Nawy, T. & Pe'er, D. Supervised discovery of interpretable gene programs from single-cell data. *Nat Biotechnol* (2023). https://doi.org/10.1038/s41587-023-01940-3

Azher, Z. L. *et al.* Assessment of emerging pretraining strategies in interpretable multimodal deep learning for cancer prognostication. *BioData Min* **16**, 23 (2023). https://doi.org/10.1186/s13040-023-00338-w

Wang, Z. *et al.* Surformer: An interpretable pattern-perceptive survival transformer for cancer survival prediction from histopathology whole slide images. *Comput Methods Programs Biomed* **241**, 107733 (2023). https://doi.org/10.1016/j.cmpb.2023.107733

Chefer, H., Gur, S. & Wolf, L. in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition.* 782–791.

Abnar, S. & Zuidema, W. Quantifying attention flow in transformers. *arXiv preprint arXiv:2005.00928* (2020).

Zaritsky, A. *et al.* Interpretable deep learning uncovers cellular properties in label-free live cell images that are predictive of highly metastatic melanoma. *Cell Systems* **12**, 733–+ (2021). https://doi.org/10.1016/j.cels.2021.05.003

Mohan, A. S. *et al.* Enhanced Dendritic Actin Network Formation in Extended Lamellipodia Drives Proliferation in Growth-Challenged Rac1(P29S) Melanoma Cells. *Dev Cell* **49**, 444–460 e449 (2019). https://doi.org/10.1016/j.devcel.2019.04.007

Lamiable, A. *et al.* Revealing invisible cell phenotypes with conditional generative modeling. *Nature Communications* **14** (2023). https://doi.org/ARTN 6386

10.1038/s41467-023-42124-6

Soelistyo, C. J. & Lowe, A. R. Discovering interpretable models of scientific image data with deep learning. *ArXiv* **abs/2402.03115** (2024).

Rotem, O. *et al.* Visual interpretability of image-based classification models by generative latent space disentanglement applied to in vitro fertilization. *bioRxiv* (2023).

Xue, Y. *et al.* Synthetic Augmentation and Feature-Based Filtering for Improved Cervical Histopathology Image Classification. *Medical Image Computing and Computer Assisted Intervention - Miccai 2019, Pt I* **11764**, 387–396 (2019). https://doi.org/10.1007/978-3-030-32239-7_43

Shrivastava, A. & Fletcher, P. T. NASDM: Nuclei-Aware Semantic Histopathology Image Generation Using Diffusion Models. *Medical Image Computing and Computer Assisted Intervention, Miccai 2023, Pt Vi* **14225**, 786–796 (2023). https://doi.org/10.1007/978-3-031-43987-2_76

Li, M., Li, C., Peng, C. & Lovell, B. C. Conditioned Generative Transformers for Histopathology Image Synthetic Augmentation. *ArXiv* **abs/2212.09977** (2022).

Wei, J. W. *et al.* Generative Image Translation for Data Augmentation in Colorectal Histopathology Images. *Proceedings of machine learning research* **116**, 10–24 (2019).

Schutte, K., Moindrot, O., Hérent, P., Schiratti, J.-B. & Jégou, S. Using StyleGAN for Visual Interpretability of Deep Learning Models on Medical Images. *ArXiv* **abs/2101.07563** (2021).

Xue, Y. *et al.* Selective synthetic augmentation with HistoGAN for improved histopathology image classification. *Med Image Anal* **67**, 101816 (2021). https://doi.org/10.1016/j.media.2020.101816

Ktena, I. *et al.* Generative models improve fairness of medical classifiers under distribution shifts. *Nat Med* **30**, 1166–1173 (2024). https://doi.org/10.1038/s41591-024-02838-6

Carrillo-Perez, F. *et al.* Generation of synthetic whole-slide image tiles of tumours from RNA-sequencing data via cascaded diffusion models. *Nat Biomed Eng* (2024). https://doi.org/10.1038/s41551-024-01193-8

73 Baumgartner, C. F., Koch, L. M., Tezcan, K. C., Ang, J. X. & Konukoglu, E. in *Proceedings of the IEEE conference on computer vision and pattern recognition.* 8309–8319.

74 Ramesh, A. *et al.* Zero-Shot Text-to-Image Generation. *International Conference on Machine Learning, Vol 139* **139** (2021).

75 Preechakul, K., Chatthee, N., Wizadwongsa, S. & Suwajanakorn, S. Diffusion Autoencoders: Toward a Meaningful and Decodable Representation. *2022 Ieee/Cvf Conference on Computer Vision and Pattern Recognition (Cvpr)*, 10609–10619 (2022). https://doi.org/10.1109/Cvpr52688.2022.01036

76 Li, Z. *et al.* His-MMDM: Multi-domain and Multi-omics Translation of Histopathological Images with Diffusion Models. *medRxiv*, 2024.2007. 2011.24310294 (2024).

77 Graikos, A. *et al.* in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition.* 8532–8542.

78 Harb, R., Pock, T. & Müller, H. in *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision.* 5131–5140.

79 Ho, J., Jain, A. & Abbeel, P. Denoising Diffusion Probabilistic Models. *ArXiv* **abs/2006.11239** (2020).

80 Fuhrman, S. A., Lasky, L. C. & Limas, C. Prognostic significance of morphologic parameters in renal cell carcinoma. *Am J Surg Pathol* **6**, 655–663 (1982). https://doi.org/10.1097/00000478-198210000-00007

81 Browning, L., Colling, R. & Verrill, C. WHO/ISUP grading of clear cell renal cell carcinoma and papillary renal cell carcinoma; validation of grading on the digital pathology platform and perspectives on reproducibility of grade. *Diagn Pathol* **16**, 75 (2021). https://doi.org/10.1186/s13000-021-01130-2

82 Pacheco, R. R. *et al.* Multinucleated tumor cells in clear cell renal cell carcinoma. *Am J Clin Pathol* **160**, 603–611 (2023). https://doi.org/10.1093/ajcp/aqad096

83 Lin, Q., Choyke, P. L. & Sato, N. Visualizing vasculature and its response to therapy in the tumor microenvironment. *Theranostics* **13**, 5223–5246 (2023). https://doi.org/10.7150/thno.84947

84 Hormuth, D. A., 2nd *et al.* Biologically-Based Mathematical Modeling of Tumor Vasculature and Angiogenesis via Time-Resolved Imaging Data. *Cancers (Basel)* **13** (2021). https://doi.org/10.3390/cancers13123008

85 Jasti, J. *et al.* Histopathology Based AI Model Predicts Anti-Angiogenic Therapy Response in Renal Cancer Clinical Trial. *Nature Communications* **16**, 2610 (2025).

86 Guillaume, Z. *et al.* Renal Carcinoma and Angiogenesis: Therapeutic Target and Biomarkers of Response in Current Therapies. *Cancers (Basel)* **14** (2022). https://doi.org/10.3390/cancers14246167

87 Wettersten, H. I. *et al.* Grade-Dependent Metabolic Reprogramming in Kidney Cancer Revealed by Combined Proteomics and Metabolomics Analysis. *Cancer Res* **75**, 2541–2552 (2015). https://doi.org/10.1158/0008-5472.CAN-14-1703

88 Wang, J. *et al.* Self-improving generative foundation model for synthetic medical image generation and clinical applications. *Nat Med* (2024). https://doi.org/10.1038/s41591-024-03359-y

89 Ding, T. *et al.* Multimodal Whole Slide Foundation Model for Pathology. *arXiv preprint arXiv:2411.19666* (2024).

90   Sun, Y. *et al.* in *Proceedings of the AAAI Conference on Artificial Intelligence.* 5034–5042.

91   Juyal, D. *et al.* PLUTO: Pathology-Universal Transformer. *arXiv preprint arXiv:2405.07905* (2024).

92   Sanders, D. W. *et al.* Distinct tau prion strains propagate in cells and mice and define different tauopathies. *Neuron* **82**, 1271–1288 (2014). https://doi.org/10.1016/j.neuron.2014.04.047

93   Joseph, R. W. *et al.* Clear cell renal cell carcinoma subtypes identified by BAP1 and PBRM1 expression. *The Journal of urology* **195**, 180–187 (2016).

94   Makhzani, A., Shlens, J., Jaitly, N. & Goodfellow, I. J. Adversarial Autoencoders. *ArXiv* **abs/1511.05644** (2015).

Acknowledgments:

We thank the patients who provided tissues that enabled this research project and are grateful to the Kidney Cancer Program for their support and assistance. We acknowledge BioHPC at UT Southwestern Medical Center for providing the computational infrastructure used in this work. We also acknowledge the insightful feedback and suggestions provided by the Rajaram Lab and the Danuser Lab, especially Dr. Felix Zhou for pointing out the potential usefulness of the DIFFAE model. Work in the Danuser lab has been funded by NIH R35 GM136428, in the Kapur lab by DOD (KC200285) and NIH (P50CA196516), and in the Rajaram lab by CPRIT (RP220294), DOD (KC200285) and startup funds from the Lyda Hill Department of Bioinformatics.