Differential performance of polygenic prediction across traits and populations depending on genotype discovery approach

Yi-Sian Lin[1], Taotao Tan[1,2], Ying Wang[3,4], Bogdan Pasaniuc[5], Alicia R. Martin[3,4], Elizabeth G. Atkinson[1,6*]

1. Department of Molecular and Human Genetics, Baylor College of Medicine, Houston, TX 77030, USA

2. Department of Integrative Physiology, Baylor College of Medicine, Houston, TX 77030, USA

3. Analytic and Translational Genetics Unit, Massachusetts General Hospital, Boston, MA 02114, USA

4. Stanley Center for Psychiatric Research and Program in Medical and Population Genetics, Broad Institute of MIT and Harvard, Cambridge, MA 02142, USA

5. Department of Genetics, Perelman School of Medicine, University of Pennsylvania, Philadelphia, PA 19104, USA

6. Jan and Dan Duncan Neurological Research Institute, Houston, TX 77030, USA

*Corresponding author contact information:

Baylor College of Medicine

One Baylor Plaza, Taub Research Building Room 621

Houston, TX, USA 77030

Email: elizabeth.atkinson@bcm.edu

Abstract

Polygenic scores (PGS) are widely used for estimating genetic predisposition to complex traits by aggregating the effects of common variants into a single measure. They hold promise in identifying individuals at increased risk for diseases, allowing earlier screening and interventions. Genotyping arrays, commonly used for PGS computation, are affordable and computationally efficient, while whole-genome sequencing (WGS) offers a comprehensive view of genetic variation. Using the same set of individuals, we compared PGS derived from arrays and WGS across multiple traits to evaluate differences in predictive performance, portability across populations, and computational efficiency. We computed PGS for 10 traits across the spectrum of heritability and polygenicity in the three largest genetic ancestry groups in *All of Us* (European, African American, Admixed American), trained on the multi-ancestry meta-analyses from the Pan-UK Biobank. Using the clumping and thresholding (C+T) method, we found that WGS-based PGS outperformed array-based PRS for highly polygenic traits but showed differentially reduced accuracy for sparse traits in certain populations. This may be attributable to the lower allele frequency observed in clumped variants from WGS compared to arrays. Using the LD-informed PRS-CS method, we observed overall improved prediction performance compared to C+T, with WGS outperforming arrays across most non-cancer traits. In conclusion, while PGS computed using WGS generally provide superior predictive power with PRS-CS, the advantage over arrays is context-dependent, varying by trait, population, and the PGS method. This study provides insights into the complexities and potential advantages of using different genotype discovery approach for polygenic predictions in diverse populations.

49 **Keywords**

50 polygenic score, genotyping array, whole-genome sequencing, biobanks, global data

53 **Graphical abstract**

Introduction

Polygenic scores (PGS), also known as polygenic risk scores (PRS), estimate an individual's genetic predisposition to complex traits or diseases. As an emerging tool in precision medicine, PGS holds significant potential for informing early disease detection, risk stratification, prevention, and intervention[1]. PGS is calculated by aggregating the genotypes (i.e., the dosage of minor or risk alleles) from a target cohort, weighted by their corresponding effect sizes derived from relevant genome-wide association studies (GWAS) conducted in a discovery cohort[2]. The prediction accuracy of PGS is influenced by several factors, such as the sample size of the discovery cohort and the genetic similarity between the discovery and target population[3,4]. However, with up to 90% of GWAS for complex traits conducted in populations with predominantly European ancestry[5,6], PGS estimates are often less accurate for individuals of non-European ancestries, which can contribute to health disparities across populations[7].

Genotype data from both discovery and target cohorts are typically obtained using array technologies that detect known genetic polymorphisms. Since 2005, Affymetrix has developed high-throughput microarray genotyping platforms widely used in early GWAS and PGS studies[8,9], which initially assayed between 500,000 and nearly a million SNPs[10]. More recently, Illumina's Omni series arrays expanded this coverage to detect millions of genetic markers[11]. In addition to capturing genetic variation in European populations, arrays designed for global and diverse populations, such as the Global Screening Array[12], Global Diversity Array[13,14], Asian Screening Array[15], and H3 Africa Array[16,17], became available following the completion of the 1000 Genomes Project (1kGP) Phase 3[18] and other diverse reference resources. To allow for more comprehensive genome-wide coverage, imputation is often employed to infer untyped variants, thereby enhancing the accuracy of GWAS and PGS predictions[19].

With the ongoing reduction in costs and advancements in high-throughput sequencing,

both whole exome sequencing (WES) and whole genome sequencing (WGS) have become

increasingly integrated into population-level genomic studies and clinical applications[20,21]. In

contrast to array-based genotyping, sequencing offers several distinct advantages. Unlike

genotyping arrays, which are typically designed to assay common variants and require imputation

to enhance coverage, sequencing captures all forms of genetic variants ranging from ultra-rare to

common alleles[22,23]. Additionally, imputation accuracy for genotyping arrays can impact the

predictive performance of PGS[24], particularly in non-European populations. This is due to their

inability to reliably impute variants with low frequency, and variants enriched in populations that

are not well represented in existing reference panels. WGS enables the direct assessment of low-

frequency variants and loci that are missed or poorly imputed in arrays. Therefore, these

advantages could potentially lead to more accurate and robust PGS, especially for

underrepresented populations and traits influenced by rarer variants. However, WGS remains

more expensive, and generates vast amounts of data which requires computationally intensive

processing.

Previous studies have demonstrated comparable results between low-coverage

sequencing and array-based genotyping in gene discovery[25–27] and PGS for diseases like

Parkinson's disease[28]. However, few studies have assessed the impact of different genotype

discovery technologies on PGS performance at the biobank scale or considered high-coverage

WGS versus arrays. The *All of Us* Research Program[14] (V6), with 95,562 samples with both array

and WGS data, provides a unique opportunity to evaluate the predictive accuracy across

technologies in multiple ancestral groups and numerous phenotypes. In this study, we

benchmarked the performance of PGS derived from genotyping arrays and 30x high-coverage

WGS across ten traits and three populations in *All of Us*. To evaluate differential prediction

accuracy across diverse populations, we trained 10 PGS using meta-analyzed GWAS summary

statistics from multiple ancestries in the Pan-UK Biobank (Pan-UKBB)[29] and computed PGS on

three major genetic ancestry groups in the *All of Us* cohort (**Figure 1**). Through these efforts, we

aim to assess the conditions under which WGS-based PGS outperforms array-based PGS and

identify trade-offs that may inform the choice of genomic data type for risk prediction in diverse

settings.

Figure 1: Study design. For each trait in *the All of Us* cohort, we downloaded the corresponding

summary statistics from the Pan UKBB to obtain estimated effect sizes. PGS were calculated for

each sample in *All of Us* from the EUR, AMR, or AFR populations, using genotypes derived from

either array or WGS approaches. Two PGS methods were benchmarked across the entire

pipeline: C+T and PRS-CS. The color codes used throughout the paper are as follows: [yellow]

array, [blue] WGS, [red] EUR, [orange] AMR, and [purple] AFR.

Results

Selection of traits across a range of genetic architectures

The primary goal of this study is to benchmark the predictive performance from array-based versus WGS-based genotypes. We first selected 95,562 target samples from the *All of Us* V6 dataset, each with both array and WGS genotype data. PGS are expected to exhibit higher predictive accuracy when the ancestry of the discovery and target cohorts is matched[30]. However, since this study aims to develop a generalized PGS model rather than focusing on a single ancestry, we used effect sizes derived from a multi-ancestry GWAS meta-analysis of the Pan-UKBB cohort. For the target samples in *All of Us*, we focused on European (EUR), Latino/Admixed American (AMR), and African/African American (AFR) cohorts based on predicted genetic ancestry (**Figure S1**), as these groups had sample sizes sufficiently large to support multi-trait comparative analyses.

We selected 10 complex traits with distinct genetic architectures (**Table S1**) from the Pan-UKBB and their equivalents in the *All of Us* dataset (**Table S2**): standing height (Height), diastolic blood pressure (DBP), white blood cell count (Leukocyte), red blood cell count (RBC), high-density lipoprotein cholesterol (HDL), total cholesterol (TC), asthma, breast cancer, colorectal cancer, and type 2 diabetes (T2D). Height exhibits the highest heritability among the traits, while cancers show the lowest heritability (**Figure S2**). The polygenicity of the traits was indirectly assessed by the number of GWAS hits, with height displaying thousands of significant loci, whereas binary traits, such as cancer, show only a few significant peaks (**Figure S3**).

WGS does not improve prediction accuracy over array when variants are clumped

We first assessed the PGS using the classic clumping and thresholding (C+T) method. Notably, the raw average PGS for array-based and WGS-based genotypes were highly correlated across

traits ($r > 0.9$ for all traits except for height and TC), suggesting that both platforms captured similar

genetic information, resulting in comparable polygenic predictions. This also indicates that the

genotype coverage from unimputed array data is sufficient for constructing reliable PGS

comparable to those from WGS in the *All of Us* dataset for most of the traits considered.

Furthermore, it is noteworthy that EUR populations tend to show smaller and more homogenous

raw PGS, whereas AFR populations tend to exhibit larger and more widely spread PGS,

particularly for colorectal cancer and breast cancer (**Figure S4**).

The predictive accuracy, measured by R^2 or Nagelkerke's R^2, was assessed across different

genotype discovery approaches and populations (**Figure 2**, **Table S4** and **5**). Given that EUR

individuals constitute a large proportion of both the discovery cohort (95%) and the target cohort

(52%), predictive accuracy in EUR was generally higher than in other populations, as expected,

regardless of the genotyping approach (ranging from $1.58 \times 10^{-3} \pm 1.28 \times 10^{-3}$ to $1.07 \times 10^{-1} \pm$

6.12×10^{-4}). AFR populations generally showed lower performance compared to other groups

(ranging from $7.33 \times 10^{-4} \pm 7.53 \times 10^{-4}$ to $3.37 \times 10^{-2} \pm 1.07 \times 10^{-3}$, **Table 1**). Surprisingly, PGS

performance from WGS genotypes was suboptimal relative to array genotypes for multiple traits,

and only outperformed arrays in all three populations for one trait - height. This discrepancy may

be due to height's highly polygenic nature, suggesting that the higher number of variants detected

by WGS provides more informative variants for PGS prediction than array genotypes. Additionally,

there are a few phenotypes with notable differences in R^2 across genotype discovery approaches.

In addition to height, prediction from WGS also performed better for TC, RBC, and leukocyte

count in EUR, and for leukocyte count and asthma in AFR. In contrast, we observed that PGS

derived from array genotypes performed better for several other traits, particularly HDL in AMR

(average array-based R^2=0.061; average WGS-based R^2=0.048; paired t-test $p = 3.43 \times 10^{-4}$)

and AFR populations (average array-based R^2=0.027; average WGS-based R^2=0.009; paired t-

test $p = 7.7 \times 10^{-7}$), as well as RBC in AFR, T2D in AMR, and breast cancer in EUR (**Table 1** and

 Table S6). Several findings from previous studies may provide insights for interpreting these

 observations, including aspects of population-enriched architecture, as detailed in **Table S7**.

Figure 2: Comparison of PGS performance across genotype discovery approaches using

C+T. PGS were computed for samples with array- and WGS-genotypes in *All of Us*. R² or

Nagelkerke's R² were determined by adjusting for age, sex, and the first 16 genetic PCs. Error

bars indicate 95% confidence intervals.

More variants were called from the WGS platform compared to the array (8,996,707 versus

975,876 after quality control, QC); however, a higher number of variants did not generally result

in better predictive accuracy. We next examined the relationship between the number of variants

used in PGS calculation and PGS performance. Based on the optimal *p*-value thresholds

determined through 10-fold cross-validation, the number of variants selected for PGS calculation

decreased as the thresholds became more stringent (**Figure S5**). We observed that the best PGS

performance in EUR populations tended to occur at looser thresholds for most traits, with the

number of variants selected positively correlated with improved performance. The greater number

of variants selected for PGS calculation in EUR, relative to other populations, may reflect the

higher informativity of genetic data from EUR, which is the largest cohort in the training dataset.

In contrast, for traits such as HDL, TC, RBC, and leukocyte, fewer variants selected for PGS were

associated with higher performance in the AFR and AMR populations (**Figure 3**).

Figure 3: Relationship between C+T p-value threshold and prediction accuracy. a. Scatter

plot depicting the best *p*-value thresholds and the corresponding prediction performance derived

from array variants. **b.** Scatter plot depicting the best *p*-value thresholds and the corresponding

prediction performance derived from WGS variants. Each population is represented by 10 dots,

with each dot corresponding to the best PGS from a threshold using 10-fold cross-validation.

Allele frequency is higher in array variants than in WGS variants

For common traits, variants with higher allele frequencies are more likely to explain larger portions

of genetic variation. We hypothesized that variants with higher allele frequencies contribute to

greater explanatory power for PGS because they are more frequently present in samples. To test

whether this assumption explains the lower R^2 observed with WGS-based PGS compared to

array-based PGS for traits such as HDL and others, we computed the allele frequencies of

variants from both array and WGS data, stratified by population. Using HDL as an example, we

found that the allele frequencies of 464,726 WGS SNPs were lower than those of 261,583 array

SNPs for HDL after LD clumping, regardless of population (**Figure S6a, b**). The allele frequencies

of overlapping variants from both genotyping platforms were highly correlated ($r > 0.999$),

indicating strong concordance between array and WGS variant calls (**Figure S6c**). Although the

allele frequency patterns were largely consistent across traits (**Figure S7a, b**), these findings

provide some support for a hypothesis that lower allele frequencies in WGS variants contribute to

poorer predictive accuracy compared to array variants, particularly for less polygenic traits.

Using HDL as an example, population comparisons revealed that jointly QC'd variants for all

samples in the *All of Us* dataset, after clumping, captured a higher proportion of variants with a

minor allele frequency (MAF) < 0.01 in the EUR population alone. Conversely, the allele frequency

of clumped variants in the AFR population was higher than in other populations (**Figure S6a, b**).

We considered whether further removal of relatively rare variants in AFR would improve polygenic

prediction for HDL. To test this, we performed additional population-specific QC by filtering out

WGS variants with MAF < 0.01 in AFR, beginning from variants that were already QC filtered

jointly in *All of Us*. Using C+T, this approach resulted in an increase in the mean MAF from

0.14$\pm$0.23 to 0.17$\pm$0.24 (**Figure S8a**) and a slight improvement in predictive performance (R^2

from 0.009 to 0.01) compared to the full jointly-QC'd variant set (**Figure S8b**), suggesting that the

removal of relatively rare variants in AFR modestly reduced noise in polygenic prediction. This

finding further suggests that population-specific QC is likely to result in optimal selection of

variants for PGS in populations less well represented in large datasets.

C+T retains only quasi-independent variants within each LD block after LD clumping; however,

this approach may remove informative variants important for PGS calculation. In contrast, PRS-

CS does not rely on clumping but instead continuously shrinks effect size estimates in an LD-

informed manner to retain as many informative variants as possible[31]. We benchmarked C+T and

PRS-CS to determine whether prediction accuracy would differ between the two methods across

data generation technologies. For raw PGS using PRS-CS, we again observed a high correlation

between PGS derived from array-based genotypes and WGS genotypes across traits ($r > 0.9$ for

continuous traits). The range of raw PGS was largest for height, but smaller for binary traits. All

populations covered a broad spectrum of PGS values (**Figure S9**). When comparing the

predictive accuracy of PGS generated using PRS-CS to those generated using the C+T method,

we found that PRS-CS generally outperformed C+T, with performance being approximately two

times better for most traits, except for cancers. Additionally, performance using WGS variants was

higher than that using array variants for all traits except for cancers and TC. The relative gain in

performance using WGS compared to arrays was similar across populations, but smaller in AFR

for asthma and T2D (**Figure 4**).

Figure 4: Comparison of PGS performance across genotype discovery approaches using PRS-CS. PGS were computed for samples with array- and WGS-genotypes in *All of Us*. R² or Nagelkerke's R² were determined by adjusting for age, sex, and the first 16 genetic PCs.

WGS outperforms arrays and achieves maximal accuracy with continuous effect size adjustment rather than LD clumping

Note that the variants selected for PGS computation were restricted to approximately 1.1 million HapMap3 variants, as the default LD panel used in PRS-CS was based on HapMap3 variants. This is reflective of the general implementation of the PRS-CS software. To fully assess the advantage of using WGS genotypes, however, which include around 9 million variants, we additionally computed an EUR-derived LD matrix using samples from the 1kGP and the Human Genome Diversity Project (HGDP) joint call sets, resulting in approximately 7.3 million reference variants. In the *All of Us* dataset, the intersection between the QC'd array data and the HapMap3 LD matrix was approximately 0.3 million variants (~29% of the array variants), while the intersection with the full-scale LD matrix was around 0.7 million variants (~71% of the array

variants). For the QC'd WGS data, the intersection with the HapMap3 LD matrix was

approximately 0.9 million variants (~10% of the WGS variants), while the intersection with the full-

scale LD matrix was around 5.5 million variants (~62% of the WGS variants). Switching from the

default LD panel to this new panel, we observed similar levels of predictive accuracies for traits

using array genotypes, but lower accuracy using WGS variants in AMR and AFR for multiple traits

(**Figure S10**, **Table S8** and **9**). This could be attributable to the higher number of variants in the

EUR LD panel, which does not tag well for non-EUR population. However, taken together, LD

information from HapMap3 variants is generally sufficient to perform PRS-CS and achieve optimal

performance without the computationally demanding need to construct fuller LD resources.

Trade-off between computational efficiency and prediction accuracy

In terms of computational comparisons, C+T is much faster than PRS-CS. Focusing on post-QC

computation, C+T generally took less than 20 minutes of cloud computing per trait in the *All of Us*

dataset during the processes of clumping and determining the best PGS using 10-fold cross-

validation. In contrast, inferring posterior effect sizes with PRS-CS required 9 to 20 hours using a

local server outside *All of Us*, and up to 4 weeks when using a full-sized LD matrix with WGS data

(**Table S10**). The actual PGS computation in *All of Us* following this step also took 4 to 30 minutes

per trait, depending on the data scale, using 80 to 160 compute cores. Once the panel was

created, the PGS computation time using the full-scale LD panel upstream is shorter compared

to the runtime with the default LD panel. This improvement is due to modifications made to the

PRS-CS source code to recognize hg38 variant IDs in a format optimized for Hail genomics

analysis in *All of Us*. The default PRS-CS, in contrast, only recognizes hg19 rsIDs.

In conclusion, the performance of polygenic prediction varies across genotype discovery

approaches, PGS methods, traits, and populations. WGS data, when used with LD-informed

methods like PRS-CS, generally provides higher predictive power compared to array data,

especially for traits with higher heritability. However, array-derived PGS are more cost-effective

and computationally efficient, making them a favorable option for rapid generation, particularly for

traits with sparser genetic architectures. This study provides insights for researchers in selecting

the most suitable genotype discovery approach and PGS method for prediction, considering the

specific traits and populations involved.

Table 1. Comparison of polygenic prediction across traits and genotype discovery

approaches using C+T and PRS-CS.

Phenotype	Population	R^2			
		C+T		*PRS-CS*	
		Array	**WGS**	**Array**	**WGS**
Height	EUR	9.95E-02 (4.61E-04)	1.07E-01 (6.12E-04)	1.34E-01	1.45E-01
	AMR	5.22E-02 (1.19E-03)	5.34E-02 (2.64E-03)	9.45E-02	1.04E-01
	AFR	3.14E-02 (1.75E-03)	3.37E-02 (1.07E-03)	4.82E-02	5.68E-02
DBP	EUR	1.12E-02 (1.41E-03)	1.02E-02 (1.07E-03)	2.16E-02	2.54E-02
	AMR	5.43E-03 (1.31E-03)	4.78E-03 (1.17E-03)	2.37E-02	2.68E-02
	AFR	1.36E-03 (5.50E-04)	1.37E-03 (6.89E-04)	5.53E-03	8.13E-03
HDL	EUR	5.44E-02 (1.22E-03)	5.28E-02 (2.95E-03)	9.31E-02	1.02E-01
	AMR	6.14E-02 (7.67E-03)	4.81E-02 (3.55E-03)	9.83E-02	1.02E-01
	AFR	2.73E-02 (1.80E-03)	8.86E-03 (4.44E-03)	3.27E-02	3.81E-02
TC	EUR	2.14E-02 (5.89E-04)	2.35E-02 (9.19E-04)	4.08E-02	4.27E-02
	AMR	2.02E-02 (4.24E-03)	2.09E-02 (1.49E-03)	4.46E-02	4.33E-02
	AFR	7.55E-03 (3.54E-03)	5.02E-03 (4.09E-03)	2.34E-02	2.20E-02
RBC	EUR	2.72E-02 (1.18E-03)	2.81E-02 (1.11E-03)	4.75E-02	5.20E-02
	AMR	9.24E-03 (2.68E-03)	1.10E-02 (3.13E-03)	2.11E-02	2.65E-02
	AFR	1.09E-02 (2.86E-03)	6.82E-03 (3.54E-03)	1.43E-02	1.55E-02
Leukocyte	EUR	9.83E-03 (4.16E-04)	1.06E-02 (4.17E-04)	1.55E-02	1.90E-02
	AMR	7.73E-03 (2.61E-03)	6.61E-03 (2.63E-03)	1.22E-02	1.59E-02
	AFR	8.89E-03 (1.89E-03)	1.02E-02 (2.54E-03)	1.36E-02	1.45E-02
Asthma	EUR	1.08E-02 (2.50E-03)	1.04E-02 (6.84E-04)	1.39E-02	1.77E-02
	AMR	4.71E-03 (1.41E-03)	2.55E-03 (1.59E-03)	1.15E-02	1.74E-02
	AFR	6.82E-04 (4.37E-04)	1.39E-03 (5.10E-04)	3.33E-03	3.67E-03
T2D	EUR	2.29E-02 (1.60E-03)	2.05E-02 (1.97E-03)	3.65E-02	4.41E-02
	AMR	8.50E-03 (2.04E-03)	4.88E-03 (9.23E-04)	2.21E-02	2.90E-02
	AFR	3.83E-03 (1.18E-03)	3.74E-03 (1.06E-03)	1.08E-02	1.09E-02
Colorectal Cancer	EUR	2.41E-03 (1.22E-03)	1.58E-03 (1.28E-03)	2.60E-03	1.37E-03
	AMR	1.36E-03 (2.02E-03)	3.81E-04 (3.72E-04)	3.10E-03	1.50E-03
	AFR	1.44E-03 (2.06E-03)	1.08E-03 (1.45E-03)	1.67E-04	4.80E-04
Breast Cancer	EUR	1.17E-02 (1.52E-03)	8.02E-03 (8.83E-04)	1.57E-02	1.30E-02
	AMR	2.93E-03 (1.93E-03)	2.77E-03 (2.07E-03)	1.41E-02	1.31E-02

AFR	1.07E-03 (1.03E-03)	7.33E-04 (7.53E-04)	4.11E-03	3.93E-03

288 The R² columns refer to both R² and pseudo-R². The values for C+T were averaged from 10 R²

289 values. The standard deviations are indicated in parentheses.

Discussion

In this study, we benchmarked the prediction accuracy of PGS generated from array and WGS

genotypes across a range of traits and populations. The performance was influenced by several

factors, which are discussed below.

Using the C+T method, polygenic prediction generally did not perform better with WGS variants

than with array variants, even when the array data were not imputed (**Figure 2**). This can be

explained by several factors. First, LD clumping for each trait drastically reduced the number of

WGS variants from approximately 9 million to ~467K (~95% reduction), while array variants were

clumped from ~1 million to ~262K (~73% reduction) (**Table S3**). Moreover, the overlap of SNPs

between discovery GWAS summary statistics and the target genome also restricts the variants

included in the PGS calculation. The large reduction in WGS variants may have removed

important variants for polygenic prediction, leading to comparable or even lower prediction

accuracy than PGS derived from array variants. Second, the field standard of GWAS and PGS

methods is designed to model bi-allelic SNPs, which could lead to comparable prediction using

array versus WGS. Given that sequencing can capture additional important genetic variations

such as INDELs and CNVs that arrays often cannot, incorporating more complex genetic variation

could boost PGS performance for WGS and recover some missing heritability. Third, sequencing

error rates range from 0.1% to 1% across platforms[32,33]. However, even low error rates can

introduce significant errors when large numbers of nucleotides are sequenced[34]. These errors

may contribute noise to the PGS, thereby reducing predictive accuracy. Fourth, allele frequencies

are lower in WGS-derived clumped variants than in array-derived clumped variants (**Figure S6a**,

b for HDL). This could differentially impact phenotypes. For example, prediction for HDL, which

has a sparse genetic architecture, is significantly affected by lower allele frequencies in WGS

variants, while prediction for highly polygenic height benefits from the higher number of variants

available in WGS data. Even if the array variants were imputed, however, it is unclear whether

this would improve prediction accuracy, given that WGS variants did not show significantly better

performance than non-imputed array variants for most traits.

On the other hand, WGS-based PGS generally performed better than array-based PGS when

using PRS-CS (**Figure 4**). It is possible that if array variants were imputed to the genomic

coverage equivalent to WGS, their performance might approach that of WGS-based PGS using

this method. The lack of imputation for array genotypes is one limitation of this study due to budget

considerations and limitations from leveraging the controlled cloud compute environment of the

All of Us Research Program. However, given this is the format by which the arrays are centrally

released in *All of Us*, this is an accurate capture of the general pipelines deployed in this

foundational resource. Further, expanding the variants considered by WGS by computing our own

LD matrix (rather than utilizing the provided PRS-CS LD matrix that is restricted to HapMap3

SNPs) with 6.2 M more sites did not improve WGS based results compared to the more limited

variant set (**Figure S10**). Together, these results suggest that fewer, reliably captured, more

common, and well-tagging variants appear to suffice for PGS computation for most traits,

particularly those that are less polygenic. This can be illustrated with the theoretical accuracy of

PGS, where the expected $R^2 \approx h^2/[1 + M/(h^2N)]$[35]. With the same sample size N, using WGS

over array variants might increase the heritability h^2, but it does not necessarily provide a benefit

when a very large number of variants M are involved.

As our focus was on benchmarking genotype discovery approaches, in this study we did not

investigate the impact of using reference panels with different population compositions on

polygenic prediction. It may be optimal to match the population proportions between the reference

panel and discovery GWAS[30], or to compute in-sample LD, given that LD patterns differ across

populations. Specifically, our GWAS data from Pan-UKBB consists of 95% European samples,

however, the proportion of European samples in the 1kGP reference panel used for C+T was only

about 20%[18]. It remains to be tested whether prediction accuracy could be improved by reducing

the proportion of other populations to 5%, or if maintaining a large reference panel sample size

outweighs the advantage of using a proportion-matched reference panel. This approach could

potentially provide more accurate LD estimates for our discovery GWAS samples and improve

prediction accuracy. This may also partially explain why PRS-CS performed better than C+T, as

the reference panel used for PRS-CS was the UK Biobank EUR LD panel, provided by the

developers of PRS-CS, from which a high percentage of samples overlap with those in the Pan-

UKB discovery data.

Traditional SNP arrays have predominantly been based on genomes of European ancestry due

to the higher availability of EUR samples in reference databases[36]. In contrast, sequencing does

not rely on pre-selected markers and is expected to provide greater benefits for underrepresented

groups in genomic studies. Consequently, we anticipated a greater improvement in prediction

accuracy using variants from sequencing compared to those from arrays, particularly in non-

European populations. However, this trend was not universally observed. We hypothesize that

the significantly higher allele frequencies of utilized SNPs stemming from array data as compared

to WGS data may explain this result. Additionally, the population-level allele frequencies

calculated in *All of Us* were highest in AFR (**Figure S6a**, **b**), suggesting that the Global Diversity

Array used in *All of Us* is not biased toward European populations. Ongoing efforts generating

array data for diverse populations would do well to similarly consider capturing variation

represented in the target samples.

As has been demonstrated previously[3,37,38], prediction performance was generally better in EUR

than in other populations, likely due to the overrepresentation of EUR in the discovery GWAS.

Although underrepresented in Pan-UKBB, AMR achieved similar performance to EUR for some

traits, while AFR always had low predictive power (**Figure 2** and **Figure 4**). This may be attributed

to the larger proportion of European ancestry in the genomes of AMR[39], and the scale of genetic

distances from EUR, as has been previously explored[4]. We specifically observed a four-fold

reduction in performance for T2D in AFR compared to EUR in this study (**Figure 2** and **Figure 4**),

highlighting the ongoing performance disparities of PGS for diverse populations across genotype

discovery approaches and PGS methods. Another consideration is that AMR and AFR are

admixed populations, with genomes composed of genetic segments from multiple ancestries[40].

Ancestry-informed GWAS methods tailored to admixed populations, such as *Tractor* GWAS[41],

may produce summary statistics for polygenic prediction that function better for admixed

individuals[30].

Despite the differential advantages of using WGS over arrays for better prediction with PRS-CS,

the cost of WGS and arrays remains a key factor in choosing which genotype discovery platform

to use for individual researchers and consortia generating their own data. As of 2024, the cost for

genotyping arrays ranges from $80 for a screening array to $135 for a global diversity array, while

the cost for 30X short-read WGS is about $600. However, the price of WGS has dramatically

declined since next-generation sequencing technology came into use in 2007[42]. With the rapid

advancement of sequencing technology, WGS is expected to become more affordable and

potentially replace arrays as the standard platform in large-scale genomic studies and personal

health screening. This development is anticipated to not only accelerate genomic discovery for

historically underrepresented populations but also advance PGS method development. The larger

and more representative GWAS and reference panels generated from WGS for populations with

diverse genetic architectures will enhance prediction accuracy for traits and diseases that have

lacked statistical power. This will create many opportunities for genetic prediction models tailored

to specific health conditions and populations, facilitating the progress of precision medicine.

PGS models vary in performance across training sources such that it would be desirable to

compare the performance of array versus WGS genotype using PGS results from other study

settings. For example, it would be valuable to compute PGS using the PGS catalog[43] by applying

the existing scoring files (with variants, effect alleles, and allelic information) on our target data in

All of Us, comparing the performance for array versus WGS genotypes. However, the PGC

Catalog's software implementation currently only supports imputed array-based genotypes but

not WGS data. If the *All of Us* array data is imputed in the future, or if WGS data becomes well-

supported by the calculator, we can compare the reproducibility of PGS from our model to existing

scores. For future work, it would also be interesting to benchmark PGS models that employ

functionally informed fine-mapping methods[44]. Fine-mapping aims to identify causal variants for

complex traits[45], and we expect that these methods would be better suited for sequenced

genomes than arrays which "tag" the causal effects. This also means that including rarer but

functionally mapped variants into PGS calculation as well as GWAS construction using WGS is

highly desirable.

To conclude, this study evaluates the performance of PGS with variants discovered from arrays

and WGS. The advantage of using either genotype discovery approach depends on several

factors. Array-PGS exhibit higher predictive accuracy than WGS-PGS for less polygenic traits

when variants are clumped. The correlation between the number of variants clumped and

prediction performance differs across populations. On the other hand, WGS-PGS outperformed

array-PGS for most traits with higher polygenicity when using all variants for prediction, while

readjusting effect size estimates based on LD. We hope this study provides researchers with a

foundation for selecting an optimal genotype calling platform and polygenic score method,

considering diverse populations and traits.

Methods

GWAS summary statistics QC

The multi-ancestry meta-analyzed GWAS summary statistics for six continuous traits—height,

DBP, leukocyte, RBC, HDL, and TC—and four binary traits—asthma, breast cancer, colorectal

cancer, and T2D—were downloaded from Pan-UKBB. A summary table of the selected

phenotypes, including sample sizes by population, is provided in **Table S1**. Each summary

statistic was lifted over from hg19 to hg38 to harmonize with the genome build of the target

genotypes in *All of Us*. Variants in all summary statistics were filtered to retain only biallelic

SNPs. The reference and alternate alleles were swapped when necessary to match the strand

orientation in the target dataset, and the effect size signs were reversed accordingly. For

quantitative traits, only high-quality samples (denoted with the suffix "hq"), effect sizes, and *P*

values were used.

Heritability estimation

Heritability for the 10 Pan-UKBB phenotypes was estimated using LD Score Regression

(LDSC)[46]. Given that EUR constitutes 95% of the total samples in the Pan UKBB GWAS meta-

analysis, we downloaded 1kGP EUR LD scores as a representative reference from LDSC. To

match the SNP IDs to the rsIDs in the EUR LD scores, the GWAS summary statistics were

annotated with dbSNP rsIDs v155 using the R package *SNPlocs.Hsapiens.dbSNP155.GRCh37*.

The observed-scale heritability was then computed using the formatted summary statistics.

***All of Us* phenotype curation**

For the 10 phenotypes with GWAS summary statistics available from pan-UKBB, we curated the

corresponding phenotypes in the *All of Us* following the methodology outlined in Tsuo *et al*[47].

We curated the quantitative traits based on concept IDs, and binary traits using PheCode map

v1.2, which facilitate the mapping of ICD codes into their corresponding phecodes. For

quantitative phenotypes, we harmonized their units by adopting the most frequently observed

unit as the reference standard. We further removed those individuals with values exceeding 5

standard deviations from the mean. Subsequently, we performed inverse-rank normal

transformation to ensure normalization.

Target sample selection

Samples with both genotyped array and WGS data were selected. In total, 95,562 individuals

had both types of data in *All of Us* V6. Samples were excluded if more than 10% of genotypes

were missing. Related samples were removed based on a kinship score > 0.1. Samples

predicted to be of EUR (European, composed of Finnish and non-Finnish European), AMR

(Latino/admixed American), or AFR (African) ancestry were selected based on an auxiliary

genetically predicted ancestry file provided in *All of Us*. Briefly, the ancestry labels were inferred

using the prediction probabilities from a random forest classifier, which was trained on the 16-

dimenional PCA space of reference HGDP and 1kGP samples and autosomal variants, which

obtained from gnomAD[14]. A summary table of sample sizes for the 10 curated phenotypes is

provided in **Table S2**.

Target variant QC

The QC criteria were identical for both array and WGS variants in *All of Us* V6. First, only

autosomal variants were retained. Variants with a call rate lower than 90% were excluded.

Indels were removed, and only common biallelic SNPs with a MAF > 0.01 were retained. QC of

the 1,824,517 array variants resulted in 975,876 SNPs, while QC of the 702,574,937 WGS

variants resulted in 8,996,707 SNPs. For the analysis of HDL in AFR, we further excluded

common SNPs with a MAF < 0.01 in the AFR population to evaluate PGS performance. We did

not impute array variants in *All of Us* due to the high computational cost associated with cloud-

based analysis. *All of Us* genotype data is released unimputed, such that this is expected to be

standard practice for users of this particular dataset. *All of Us* array data is genotyped with the

Global Diversity Array, which was designed to integrate highly optimized multiethnic variants

with a genome-wide scaffold, incorporating WGS data from over 1,000 individuals of African

and/or American ancestry, reflecting the genetic diversity of participants in the *All of Us*

Research Program. As such, comparing polygenic prediction performance across ancestral

groups using array and WGS data from *All of Us* is particularly relevant.

LD clumping

All 3,202 samples from five continental populations in 1kGP Phase 3 were used as the

reference panel for LD calculation in C+T. Samples with first- and second-degree relatives were

removed. Reference variants were filtered to retain common biallelic SNPs (MAF > 0.01).

Clumping was performed to remove SNPs that were highly correlated based on the LD pattern

from the QC'd 1kGP reference panel, retaining only independent significant SNPs. Variants in

the ten GWAS summary statistics were clumped using PLINK, with the flags –clump-p1 1, –

clump-r2 0.1, and –clump-kb 250. The number of array or WGS variants for each trait after

clumping is provided in **Table S3**.

C+T construction

For C+T, variants for the 10 traits were clumped according to the LD in the 1kGP reference

panel. PGS for each trait were computed using the following equation:

477
$$PGS_i = \sum_{j=1}^{M} x_{ij}\beta_j$$

where X represents the dosage of alternate alleles {0, 1, 2} from the genotype matrix, β denotes

the effect size estimates, i indexes the individual, j indexes the variant, and M is the total number

of variants used for the calculation (i.e. number of clumped SNPs). The best PGS for each

population was determined through 10-fold cross-validation (1 fold for validation and 9 folds for

testing) with different sets of variants passing corresponding p-value thresholds: 1, 0.5, 1e-1, 1e-

2, 1e-3, 1e-4, 1e-5, 1e-6, 1e-7, and 1e-8. The PGS for the best thresholds were then evaluated

using R^2 for continuous traits or Nagelkerke's R^2 for binary traits. R^2 is the proportion of variance

explained by the full model relative to the null model, calculated using linear regression.

Nagelkerke's R^2 was computed via logistic regression by comparing the likelihoods of the null and

full models, adjusting for the overall fit to obtain a value indicating the proportion of variance

explained by the PGS in the context of the full model. The null model included age, male sex,

female sex, and the first 16 principal components as predictors, while the full model included all

variables from the null model in addition to PGS.

PRS-CS construction

We prepared the LD reference panel from two sources: 1. A precomputed EUR LD panel

constructed using UKBB data, restricted to 1,120,696 HapMap3 variants, which was

downloaded from the PRS-CS GitHub repository. 2. A genome-wide EUR LD panel constructed

using the 1kGP and HGDP joint call set[48]. To generate this LD panel, we downloaded

precomputed EUR LD blocks based on the GRCh38 genome from LDblocks_GRCh38[49]. We

then computed the LD matrices for each LD block using PLINK, with a total of 7,330,169 post-

QC (bi-allelic SNPs with MAF >0.5%) genome-wide variants from the VCF of 664 unrelated

EUR samples in the 1kGP and HGDP joint call set. The LD matrices across 22 chromosomes

were saved in HDF5 format, which is compatible with PRS-CS. To run PRS-CS, we did not set

the global shrinkage parameter phi and allowed the program to automatically search for the

optimal value. After obtaining posterior effect sizes generated from PRS-CS-auto, we computed

PGS for each target individual by aggregating the product of their genotypes weighted by the

updated effect sizes, as shown in the equation below:

505
$$PGS_i = \sum_{j=1}^{M} x_{ij}\beta_{j,posterior}$$

PGS performance was then evaluated using R^2 for continuous traits and Nagelkerke's R^2 for

binary traits, as described in the C+T section.

Declaration of interests

A.R.M. has received speaker fees from Novartis. Other authors declare no competing interests.

Acknowledgements

We gratefully acknowledge *All of Us* participants for their contributions, without whom this

research would not have been possible. We also thank the National Institutes of Health's *All of*

Us Research Program for making available the participant genotype and phenotype data

examined in this study. We thank Aishi Ayyanathan for her assistance in generating the QC'd

sample list used in this study. This work was supported by NIH grants K01MH121659 and

R01HG012869 to E.G.A.

Author contributions

Y-S.L. analyzed the data, interpreted the results, and drafted the manuscript. T.T. analyzed the

data and interpreted the results. Y.W. curated *All of Us* phenotypes. B.P. and A.R.M. provided

critical comments. E.G.A designed and supervised the study and revised the manuscript. All

authors approved the final manuscript.

Web resources

Pan-UKBB Downloads page, https://pan.ukbb.broadinstitute.org/downloads

EUR LD scores, https://zenodo.org/records/8182036

1kGP Phase 3 reference panels, https://www.cog-genomics.org/plink/2.0/resources

UKBB EUR LD panel for PRS-CS, https://github.com/getian107/PRScs

Data and code availability

The GWAS summary statistics used in this study were downloaded from the Pan UKBB

Downloads page. Individual genotype data were obtained from the *All of Us* Research Program

Controlled Tier Dataset V6. EUR LD scores from 1kGP, used for heritability estimation, were

downloaded from the zenodo web resources describe above. The 1kGP Phase 3 reference panels

used for C+T were downloaded from PLINK resources. The EUR reference LD panel, constructed

using UKBB data for PRS-CS, was downloaded from the PRS-CS GitHub repository. All code

used for this analysis is available at https://github.com/Atkinson-Lab/PGS_Array_WGS.

References

1. Konuma, T., and Okada, Y. (2021). Statistical genetics and polygenic risk score for precision

medicine. Inflamm. Regen. *41*, 18.

2. Choi, S.W., Mak, T.S.-H., and O'Reilly, P.F. (2020). Tutorial: a guide to performing polygenic

risk score analyses. Nat. Protoc. *15*, 2759–2772.

3. Wang, Y., Tsuo, K., Kanai, M., Neale, B.M., and Martin, A.R. (2022). Challenges and

opportunities for developing more generalizable polygenic risk scores. Annu. Rev. Biomed. Data

Sci. *5*, 293–320.

4. Ding, Y., Hou, K., Xu, Z., Pimplaskar, A., Petter, E., Boulier, K., Privé, F., Vilhjálmsson, B.J.,

Olde Loohuis, L.M., and Pasaniuc, B. (2023). Polygenic scoring accuracy varies across the

genetic ancestry continuum. Nature *618*, 774–781.

5. Fitipaldi, H., and Franks, P.W. (2023). Ethnic, gender and other sociodemographic biases in

genome-wide association studies for the most burdensome non-communicable diseases: 2005-

2022. Hum. Mol. Genet. *32*, 520–532.

6. Sirugo, G., Williams, S.M., and Tishkoff, S.A. (2019). The missing diversity in human genetic

studies. Cell *177*, 26–31.

7. Martin, A.R., Kanai, M., Kamatani, Y., Okada, Y., Neale, B.M., and Daly, M.J. (2019). Clinical

use of current polygenic risk scores may exacerbate health disparities. Nat. Genet. *51*, 584–

591.

8. Ikegawa, S. (2012). A short history of the genome-wide association study: where we were

and where we are going. Genomics Inform. *10*, 220–225.

9. Cross, B., Turner, R., and Pirmohamed, M. (2022). Polygenic risk scores: An overview from

bench to bedside for personalised medicine. Front. Genet. *13*, 1000667.

10. Yeung, J.M., Sham, P.C., Chan, A.S., and Cherny, S.S. (2008). OpenADAM: an open

source genome-wide association data management system for Affymetrix SNP arrays. BMC

Genomics *9*, 636.

11. Xing, C., Huang, J., Hsu, Y.-H., DeStefano, A.L., Heard-Costa, N.L., Wolf, P.A., Seshadri,

S., Kiel, D.P., Cupples, L.A., and Dupuis, J. (2016). Evaluation of power of the Illumina

HumanOmni5M-4v1 BeadChip to detect risk variants for human complex diseases. Eur. J. Hum.

Genet. *24*, 1029–1034.

12. Infinium Global Screening Array-24 Kit | Population-scale genetics.

13. Infinium Global Diversity Array-8 Kit | Multiethnic human genotyping.

14. All of Us Research Program Genomics Investigators (2024). Genomic data in the All of Us

Research Program. Nature *627*, 340–346.

15. Infinium Asian Screening Array | Genotyping of East Asian populations.

16. content, C. A powerful array for genetic studies focused on African populations.

17. H3Africa Consortium, Rotimi, C., Abayomi, A., Abimiku, A., Adabayeri, V.M., Adebamowo,

C., Adebiyi, E., Ademola, A.D., Adeyemo, A., Adu, D., et al. (2014). Enabling the genomic

revolution in Africa. Science *344*, 1346–1348.

18. 1000 Genomes Project Consortium, Auton, A., Brooks, L.D., Durbin, R.M., Garrison, E.P.,

Kang, H.M., Korbel, J.O., Marchini, J.L., McCarthy, S., McVean, G.A., et al. (2015). A global

reference for human genetic variation. Nature *526*, 68–74.

19. Naito, T., and Okada, Y. (2024). Genotype imputation methods for whole and complex

genomic regions utilizing deep learning technology. J. Hum. Genet. *69*, 481–486.

20. McMahon, A., Lewis, E., Buniello, A., Cerezo, M., Hall, P., Sollis, E., Parkinson, H., Hindorff,

L.A., Harris, L.W., and MacArthur, J.A.L. (2021). Sequencing-based genome-wide association

studies reporting standards. Cell Genomics *1*,.

21. Brlek, P., Bulić, L., Bračić, M., Projić, P., Škaro, V., Shah, N., Shah, P., and Primorac, D.

(2024). Implementing whole genome sequencing (WGS) in clinical practice: advantages,

challenges, and future perspectives. Cells *13*,.

22. Wendl, M.C., and Wilson, R.K. (2009). The theory of discovering rare variants via DNA

sequencing. BMC Genomics *10*, 485.

23. Wheeler, M.M., Stilp, A.M., Rao, S., Halldórsson, B.V., Beyter, D., Wen, J., Mihkaylova,

A.V., McHugh, C.P., Lane, J., Jiang, M.-Z., et al. (2022). Whole genome sequencing identifies

structural variants contributing to hematologic traits in the NHLBI TOPMed program. Nat.

Commun. *13*, 7592.

24. Appadurai, V., Bybjerg-Grauholm, J., Krebs, M.D., Rosengren, A., Buil, A., Ingason, A.,

Mors, O., Børglum, A.D., Hougaard, D.M., Nordentoft, M., et al. (2023). Accuracy of haplotype

estimation and whole genome imputation affects complex trait analyses in complex biobanks.

Commun. Biol. *6*, 101.

25. Martin, A.R., Atkinson, E.G., Chapman, S.B., Stevenson, A., Stroud, R.E., Abebe, T.,

Akena, D., Alemayehu, M., Ashaba, F.K., Atwoli, L., et al. (2021). Low-coverage sequencing

cost-effectively detects known and novel variation in underrepresented populations. Am. J.

Hum. Genet. *108*, 656–668.

26. Chat, V., Ferguson, R., Morales, L., and Kirchhoff, T. (2021). Ultra Low-Coverage Whole-

Genome Sequencing as an Alternative to Genotyping Arrays in Genome-Wide Association

Studies. Front. Genet. *12*, 790445.

27. Petter, E., Ding, Y., Hou, K., Bhattacharya, A., Gusev, A., Zaitlen, N., and Pasaniuc, B.

(2023). Genotype error due to low-coverage sequencing induces uncertainty in polygenic

scoring. Am. J. Hum. Genet. *110*, 1319–1329.

28. Kim, S., Shin, J.-Y., Kwon, N.-J., Kim, C.-U., Kim, C., Lee, C.S., and Seo, J.-S. (2021).

Evaluation of low-pass genome sequencing in polygenic risk score calculation for Parkinson's

disease. Hum Genomics *15*, 58.

29. Karczewski, K.J., Gupta, R., Kanai, M., Lu, W., Tsuo, K., Wang, Y., Walters, R.K., Turley,

P., Callier, S., Baya, N., et al. (2024). Pan-UK Biobank GWAS improves discovery, analysis of

genetic architecture, and resolution into ancestry-enriched effects. MedRxiv.

30. Wang, Y., Kanai, M., Tan, T., Kamariza, M., Tsuo, K., Yuan, K., Zhou, W., Okada, Y.,

BioBank Japan Project, Huang, H., et al. (2023). Polygenic prediction across populations is

influenced by ancestry, genetic architecture, and methodology. Cell Genomics *3*, 100408.

31. Ge, T., Chen, C.-Y., Ni, Y., Feng, Y.-C.A., and Smoller, J.W. (2019). Polygenic prediction via

Bayesian regression and continuous shrinkage priors. Nat. Commun. *10*, 1776.

32. Stoler, N., and Nekrutenko, A. (2021). Sequencing error profiles of Illumina sequencing

instruments. NAR Genom. Bioinform. *3*, lqab019.

33. Wall, J.D., Tang, L.F., Zerbe, B., Kvale, M.N., Kwok, P.-Y., Schaefer, C., and Risch, N.

(2014). Estimating genotype error rates from high-coverage next-generation sequence data.

Genome Res. *24*, 1734–1739.

34. Sleep, J.A., Schreiber, A.W., and Baumann, U. (2013). Sequencing error correction without

a reference genome. BMC Bioinformatics *14*, 367.

35. Visscher, P.M., Yang, J., and Goddard, M.E. (2010). A commentary on "common SNPs

explain a large proportion of the heritability for human height" by Yang et al. (2010). Twin Res.

Hum. Genet. *13*, 517–524.

36. Fatumo, S., Chikowore, T., Choudhury, A., Ayub, M., Martin, A.R., and Kuchenbaecker, K.

(2022). A roadmap to increase diversity in genomic studies. Nat. Med. *28*, 243–250.

37. Kachuri, L., Chatterjee, N., Hirbo, J., Schaid, D.J., Martin, I., Kullo, I.J., Kenny, E.E.,

Pasaniuc, B., Polygenic Risk Methods in Diverse Populations (PRIMED) Consortium Methods

Working Group, Witte, J.S., et al. (2024). Principles and methods for transferring polygenic risk

scores across global populations. Nat. Rev. Genet. *25*, 8–25.

38. Kullo, I.J., Lewis, C.M., Inouye, M., Martin, A.R., Ripatti, S., and Chatterjee, N. (2022).

Polygenic scores in biomedical research. Nat. Rev. Genet. *23*, 524–532.

39. Montinaro, F., Busby, G.B.J., Pascali, V.L., Myers, S., Hellenthal, G., and Capelli, C. (2015).

Unravelling the hidden ancestry of American admixed populations. Nat. Commun. *6*, 6596.

40. Bryc, K., Durand, E.Y., Macpherson, J.M., Reich, D., and Mountain, J.L. (2015). The genetic

ancestry of African Americans, Latinos, and European Americans across the United States. Am.

J. Hum. Genet. *96*, 37–53.

41. Atkinson, E.G., Maihofer, A.X., Kanai, M., Martin, A.R., Karczewski, K.J., Santoro, M.L.,

Ulirsch, J.C., Kamatani, Y., Okada, Y., Finucane, H.K., et al. (2021). Tractor uses local ancestry

to enable the inclusion of admixed individuals in GWAS and to boost power. Nat. Genet. *53*,

195–204.

42. Metzker, M.L. (2010). Sequencing technologies - the next generation. Nat. Rev. Genet. *11*,

31–46.

43. Lambert, S.A., Wingfield, B., Gibson, J.T., Gil, L., Ramachandran, S., Yvon, F., Saverimuttu,

S., Tinsley, E., Lewis, E., Ritchie, S.C., et al. (2024). Enhancing the Polygenic Score Catalog

with tools for score calculation and ancestry normalization. Nat. Genet. *56*, 1989–1994.

44. Weissbrod, O., Kanai, M., Shi, H., Gazal, S., Peyrot, W.J., Khera, A.V., Okada, Y., Biobank

Japan Project, Martin, A.R., Finucane, H.K., et al. (2022). Leveraging fine-mapping and

multipopulation training data to improve cross-population polygenic risk scores. Nat. Genet. *54*,

450–458.

45. Pasaniuc, B., and Price, A.L. (2017). Dissecting the genetics of complex traits using

summary association statistics. Nat. Rev. Genet. *18*, 117–127.

46. Bulik-Sullivan, B., Loh, P.-R., Finucane, H.K., Ripke, S., Yang, J., Schizophrenia Working

Group of the Psychiatric Genomics Consortium, Patterson, N., Daly, M.J., Price, A.L., and

Neale, B.M. (2015). LD Score regression distinguishes confounding from polygenicity in

genome-wide association studies. Nat. Genet. *47*, 291–295.

47. Tsuo, K., Shi, Z., Ge, T., Mandla, R., Hou, K., Ding, Y., Pasaniuc, B., Wang, Y., and Martin,

A.R. (2024). All of Us diversity and scale improve polygenic prediction contextually with greatest

improvements for under-represented populations. BioRxiv.

48. Koenig, Z., Yohannes, M.T., Nkambule, L.L., Zhao, X., Goodrich, J.K., Kim, H.A., Wilson,

M.W., Tiao, G., Hao, S.P., Sahakian, N., et al. (2024). A harmonized public resource of deeply

sequenced diverse human genomes. Genome Res. *34*, 796–809.

49. MacDonald, J., Harrison, T., Bammler, T., Mancuso, N., and Lindstroem, S. (2022). An updated

map of GRCh38 linkage disequilibrium blocks based on European ancestry data. BioRxiv.