DeorphaNN: Virtual screening of GPCR peptide agonists using AlphaFold-predicted active-state complexes and deep learning embeddings

Larissa Ferguson[1,*], Sébastien Ouellet[2], Elke Vandewyer[3], Christopher Wang[2,4], Zaw Wunna[1,5], Tony K.Y. Lim[6], William R. Schafer[1,3, §], Isabel Beets[3, §]

[1] Neurobiology Division, MRC Laboratory of Molecular Biology, Cambridge, United Kingdom

[2] Independent Researcher, Ottawa, Ontario, Canada

[3] Department of Biology, KU Leuven, Leuven, Belgium

[4] Current affiliation: University College London, United Kingdom

[5] Current affiliation: University of Leeds, United Kingdom

[6] Department of Pharmacology, University of Cambridge, Cambridge, United Kingdom.

[§] Senior authors

[*] Corresponding Author

ORCID: LF (0000-0003-4274-8634), SO (0000-0002-3098-4907), TKYL (0000-0003-1843-0060), WRS (0000-0002-6676-8034), IB (0000-0002-0968-4360)

KEYWORDS

G protein-coupled receptors (GPCRs), AlphaFold, deorphanization, peptide agonists, neuropeptides, peptide hormone, protein representations, active-state structures, protein embeddings, structural bioinformatics

ABSTRACT

Peptide-activated G protein-coupled receptors (GPCRs) regulate critical physiological processes such as metabolism, neural signalling, and endocrine function through their interaction with neuropeptides and peptide hormones. Despite their importance, identifying endogenous peptide agonists for GPCRs remains challenging, particularly for orphan receptors without known ligands. Recent advances in deep learning-based protein structure prediction, exemplified by AlphaFold (AF), have shown application beyond structural modelling, including protein-protein interaction prediction. Given that GPCR-peptide agonist interactions represent a specialized form of protein-protein interaction, we leveraged a dataset of experimentally validated agonist and non-agonist GPCR-peptide interactions from *Caenorhabditis elegans* to evaluate AF-Multimer's ability to distinguish agonist-bound complexes. When modelling GPCR-peptide complexes, AF-Multimer confidence metrics partially discriminate agonist from non-agonist interactions, with improved discrimination achieved by utilizing AF-Multistate-derived active-state templates. We further investigated whether embeddings from the hidden layer of AF-Multimer's neural network could distinguish agonist from non-agonist complexes. Feature performance analysis reveals that AF-Multimer's pair representations outperform single representations, with distinct subregions of the pair representation providing complementary predictive signals. Building on these insights, we developed DeorphaNN, a graph neural network integrating active-state GPCR-peptide structural predictions, interatomic interactions, and deep learning embeddings to prioritize GPCR-peptide agonist interactions. DeorphaNN generalizes across datasets derived from different species, including annelids and humans, and successfully uncovered peptide agonists for two orphan GPCRs. DeorphaNN offers a novel computational resource to accelerate deorphanization by prioritizing GPCR-peptide agonist candidates for AI-guided experimental validation.

INTRODUCTION

G protein-coupled receptors (GPCRs) are a large and diverse family of membrane proteins critical for cellular signalling, defined by their characteristic seven-transmembrane domain structure. A key class of GPCR agonists includes small peptides, such as neuropeptides and peptide hormones, which regulate physiological functions ranging from homeostasis and metabolism[1] to complex behaviours like sleep, mechanosensation, and learning[2–5]. Peptide-activated GPCRs typically couple extracellular ligand binding to the regulation of intracellular signal transducers, mainly G proteins and arrestins[6]. However, identifying endogenous GPCR-peptide interactions remains a challenge, and many GPCRs are still "orphan" receptors without cognate agonists. Phylogenetic analyses have proven effective for predicting agonists of conserved peptide GPCRs across divergent phyla[7–11], but are less effective for GPCRs without clear orthologues. Large-scale experimental screens that systematically evaluate extensive libraries of putative bioactive peptides derived through peptidomic analysis[12] or computational tools[13–15] have advanced peptide agonist discovery and GPCR deorphanization[9,11,15,16], but these approaches are resource-intensive given that animal genomes typically encode dozens to over 100 peptide GPCRs alongside hundreds of bioactive peptides[9,15–17].

Computational prediction methods can address these limitations by prioritizing high-probability GPCR agonist candidates for experimental validation. Given the therapeutic

importance of GPCRs, numerous machine learning tools have been developed for *in silico*
screening of small molecule GPCR ligands. For example, AiGPro uses a multi-task
framework combining protein representations and SMILES strings to predict agonist and
antagonist activities against human GPCRs[18]. DeepGPCR employs graph convolutional
networks to classify small molecule-GPCR interactions[19], while other models predict half-
maximal effective concentration (EC_{50}) values for chemical-GPCR pairs[20]. Structure-based
docking tools, which model molecular interactions using physics-based simulations, have
also proven effective for small molecule ligand discovery[21,22].

Despite advances in machine learning applications and docking tools for identifying small
molecule ligands for GPCRs, computational tools for *in silico* peptide agonist screening
remain underdeveloped. This gap persists partly because peptides—larger, more flexible
ligands than small molecules—pose unique challenges for computational modelling[23]. While
docking methods can predict binding poses of peptide ligands of GPCRs[24], they struggle to
identify functional agonists[25]. This limitation highlights the need for next-generation
computational tools specifically designed to address the unique structural and mechanistic
complexities of GPCR-peptide agonist interactions.

Recent advances in protein structure prediction tools, including AlphaFold2 (AF2), are
rapidly reshaping computational structure-based discovery of protein complexes and
interactions. The AF2 algorithm[26] predicts protein structure by implicitly learning biophysical
relationships between residues through a combination of coevolutionary data and deep
learning techniques[27]. These biophysical properties, encoded as statistical patterns in AF2's
protein representations, enable applications beyond structural modelling, including prediction
of ligand-binding sites[28], protein function[29], and recombinant protein expression[30]. The
development of AF-Multimer[31], an extension of AF2, has allowed accurate prediction of
multimeric complexes, including peptide-protein interactions[32,33]. Additionally, system-wide
experimental screens are expanding our knowledge of GPCR-peptide interactions across
diverse animal species, providing high-quality datasets for training machine learning models.
In *Caenorhabditis elegans*, we recently constructed a comprehensive resource of over 400
GPCR-peptide agonist pairs and numerous non-agonist pairs through screening > 55,000
GPCR-peptide interactions[9]. Together, these advances—generalizable AF2-derived protein
representations, AF-Multimer's peptide-protein docking capabilities, and high-quality GPCR-
peptide interaction data—provide a foundation for developing computational methods to
predict peptide agonists for GPCRs.

In this study, we harness AF-Multimer-derived structural predictions and hidden layer protein
representations to develop computational methods for classifying agonist and non-agonist
GPCR-peptide interactions. Using a system-wide, experimentally validated *C. elegans*
dataset of GPCR-peptide agonist and non-agonist pairs[9], we evaluate AF-Multimer
confidence metrics as indicators of agonist activity, revealing their modest discriminative
capability. This capability is enhanced when active-state GPCR-peptide complexes—
modelled using templates derived from AF-Multistate[34]—are utilized to align receptors with
activation-associated binding conformations. Next, we analyze AF-Multimer's hidden layer
protein representations and find that pair representations outperform single representations
in distinguishing agonists. We find that subregions within the pair representations contribute
distinct, complementary predictive signals, highlighting the importance of multi-modal feature
integration.

Building on these insights, we developed DeorphaNN, a graph neural network (GNN) that
integrates AF-Multimer-derived structural predictions, interatomic interactions, and protein
representations to classify agonist interactions. We demonstrate that this pipeline
generalizes across datasets derived from different species, including *Platynereis* and human
datasets. Experimental validation of top-ranked peptide agonists—prioritized by
DeorphaNN—identifies endogenous peptide ligands of two orphan *C. elegans* GPCRs,
demonstrating DeorphaNN's potential for enhancing conventional screening and
accelerating the deorphanization of peptide-activated GPCRs.

RESULTS

Dataset preprocessing

We leveraged a previously published dataset that employed a high-throughput CHO $G\alpha_{16}$-
mediated calcium signalling assay to screen peptide agonist activity across 161 putative
peptide-activated GPCRs from *C. elegans*[9]. We only included GPCRs that showed
concentration-dependent activation by at least one peptide, as a lack of activity could have
been due to factors such as non-functional expression, misfolding, or failure to couple with
$G\alpha_{16}$, rather than the absence of a true agonist. Because AF-Multimer is unable to account
for post-translational modifications, pyroglutamated and amidated residues were not
included in peptide sequences. Following additional filtering—such as removal of short
peptides (< 3 residues) and redundant GPCR and peptide sequences (see Methods)—our
final dataset contained 65 GPCRs (derived from 55 genes) and 339 unique peptides
(derived from 93 genes) (**Figure 1A**). Combining each GPCR with each peptide ("GPCR-
peptide complex") yielded 20,035 pairs, 457 of which were experimentally confirmed agonist
matches[9]. The median number of agonists per GPCR in the dataset is 3 and ranges from 1-
61 (**Figure 1B**). For 38 of the 65 GPCRs, agonist peptides are derived from a single peptide
encoding gene, with the specific gene varying across receptors (**Supplemental Figure 1A**).
Peptides range in size from 3 residues to 37 residues, with a median length of 11 residues
(**Supplemental Figure 1B**). The names and primary amino acid sequences of all GPCRs
and peptides used in this study are provided in **Supplemental Data 1**.

AF-Multimer positions peptides in GPCR binding pocket with minimal discrimination

We modelled each GPCR-peptide complex using AF-Multimer to evaluate whether the
outputs could distinguish agonists from non-agonists. As experimentally determined
structures show that peptide agonists typically interact with the helical cavity ("orthosteric
binding pocket") and extracellular loops of GPCRs[35], we hypothesized that AF-Multimer
would predominantly model agonist peptides in a similar manner, while non-agonist peptides
might be modelled in less physiologically relevant locations (**Figure 1C**). To investigate this
across diverse GPCR structures, we defined the putative GPCR binding pocket as residues
within ±5 positions from the DeepTMHMM[36]-predicted extracellular-membrane boundary.
We then computed the minimum peptide-to-pocket residue distance to classify peptides as
being "inside" or "outside" the GPCR binding pocket, using a 12.5 Å cutoff. On average, <
5% of peptides per GPCR were predicted to be further than 12.5 Å from the nearest binding
pocket residue, though this varied by GPCR (**Figure 1D**). Across the dataset, only one
agonist peptide was modelled outside of the binding pocket of its respective GPCR, while
approximately 3.4% of non-agonist peptides were modelled outside the binding pocket
(**Figure 1E**). Due to the prevalence of peptides positioned in the binding pocket irrespective

of ligand class, this feature alone does not provide a reliable basis for distinguishing between
agonist and non-agonist GPCR-peptide complexes.

AF-Multimer confidence metrics partially discriminate peptide agonists from non-
agonists

We next evaluated the ability of AF-Multimer confidence metrics (interface pTM [ipTM],
predicted local distance difference test [pLDDT], and predicted aligned error [PAE]) to
discriminate peptide agonists from non-agonists. The ipTM is a metric that assesses the
accuracy of the interface between proteins in the predicted multimeric complex and is given
as a single number per multimer, ranging from 0 (low accuracy) to 1 (high accuracy)[31]. The
pLDDT is a measure of confidence output as a per-residue score ranging from 0 (low
confidence) to 100 (high confidence). Since the transmembrane regions of GPCRs are
typically predicted with high confidence by AF2, we focused on confidence metrics of the
peptide. pLDDT was averaged across peptide residues to yield a single aggregated "peptide
pLDDT" score for each GPCR-peptide multimer. Lastly, the PAE quantifies the expected
positional error of each residue in a pairwise alignment with every other residue, output as a
2D array with values ranging from 0 Å (low positional error) to a cap at 31.75 Å (high
positional error). Per-residue PAE scores for the peptide aligned on the GPCR binding
pocket residues were averaged to yield the "pocket PAE" score. For each GPCR-peptide
complex, we selected the model from the five AF-Multimer outputs with the highest ipTM,
highest peptide pLDDT, or lowest pocket PAE, depending on the specific metric being
analyzed.

We evaluated the predictive capability of each metric using mean average precision (mAP).
For each GPCR, average precision (AP) measures how agonists rank relative to non-
agonists. mAP is then calculated by averaging these AP scores across all receptors,
ensuring that GPCRs with few agonists contribute equally to the metric. This approach
avoids biases inherent in methods that assign disproportionately higher weight to receptors
with many agonists and reduces sensitivity to class imbalance inherent in the dataset.
Furthermore, by prioritizing agonists at the top of the ranked peptide list, AP better reflects
practical screening scenarios. Analysis of the AP for AF-Multimer confidence metrics
(peptide pLDDT, ipTM, and pocket PAE) revealed their ability to discriminate agonists from
non-agonists (**Figure 1F, Supplemental Figure 1C-D**). Peptide pLDDT significantly
outperformed ipTM and pocket PAE, establishing it as the most reliable indicator of GPCR-
peptide agonist interactions among the tested metrics.

Active-state GPCR-peptide complexes enhance the ability of peptide pLDDT to
discriminate agonists

AF2 is inherently biased towards modelling GPCRs in an inactive conformation[34], likely due
to having been exposed to predominantly inactive-state GPCR structures during training. In
contrast, agonist binding stabilizes the active conformation of GPCRs[37]. Therefore, we
hypothesized that biasing the GPCR in each GPCR-peptide complex toward an active
conformation would preferentially improve the confidence of AF-Multimer predictions for
agonists.

To model active-state GPCR-peptide complexes, we generated predicted active-state GPCR
structures using AF-Multistate[34] and refined them for use as templates (**Figure 2A**). First, we
trimmed extracellular regions from the template, as these domains mediate ligand binding[35].
This allows AF-Multimer to model peptide interactions without interference from pre-defined

extracellular structures. Second, we preserved the transmembrane helices, as
conformational shifts to the active state are driven by their displacement[38–40]. Third, we
removed low-confidence residues in the intracellular domain (involved in G-protein
interactions), preventing these regions from distorting structural predictions of active-state
GPCR-peptide complexes.

Active-state templates enhance discrimination of agonist and non-agonist GPCR-peptide
interactions. **Figure 2B** illustrates an example where modelling a GPCR-peptide agonist
complex with an active-state template increases peptide pLDDT. In contrast, **Figure 2C**
shows the same peptide modelled with a GPCR for which it is not an agonist. Here, the
active-state template does not alter peptide pLDDT. These differences in peptide pLDDT
between agonist and non-agonist complexes improve the ranking of agonists. Active-state
templates increase mAP values compared to template-free modelling (**Figure 2D**) by
increasing peptide pLDDT for agonists relative to non-agonists (**Figure 2E**). Additionally, AF-
Multimer positioned a greater proportion of non-agonist peptides outside of the binding
pocket when using active-state templates (**Figure 2F**). In contrast, using active-state
templates did not alter the number of agonist peptides modelled outside of the binding
pocket (data not shown). These findings—improved agonist peptide pLDDT and increased
exclusion of non-agonist peptides from the binding pocket—demonstrate that active-state
GPCR templates improve discrimination between agonist and non-agonist complexes.
Consequently, we employed active-state templates for all subsequent analyses.

Pair representations outperform single representations in discriminating GPCR-
peptide agonists

In the process of predicting the 3D structure of proteins, AF2 generates "single" and "pair"
representations that are transformed and updated in the EvoFormer block of the algorithm[26].
Each single representation is a matrix in $\mathbb{R}^{\{n \times 256\}}$ where n is the number of residues in the
GPCR-peptide complex; similarly, each pair representation is a tensor in $\mathbb{R}^{\{n \times n \times 128\}}$,
providing pairwise residue-level relationships (**Figure 3A**). These representations can be
collected from AF2 as the final hidden layer embeddings of its neural network.

We applied local pooling to residue subregions in each representation to identify features
useful for classifying GPCR-peptide agonists. For single representations, we averaged
residue regions corresponding to the GPCR, the binding pocket, or the peptide, producing
three different 256-dimensional feature vectors. Similarly, for pair representations, we
averaged residue embeddings involving the same regions and additionally the pairwise
intersection of the binding pocket and peptide residues ("bp:peptide"), yielding four distinct
128-dimensional feature vectors.

To evaluate the relative importance of features across subregions of the single and pair
representations, we employed random forest classifiers trained using stratified group 10-fold
cross-validation. Grouping by GPCR gene ensures that GPCRs are not split across
training/validation folds, thereby mitigating data leakage and preventing overfitting to GPCR-
specific structural patterns. Additionally, stratifying by agonist class helps reduce class
imbalance. Our analysis demonstrates that features derived from the peptide subregions (in
both single and pair representations) outperform those from GPCR and binding pocket
subregions as measured by receiver operating characteristic (ROC) (**Figure 3B**) and
precision-recall (PR) (**Figure 3C**) area under the curve (AUC). While pair representations
averaged over GPCR residues or binding pockets significantly outperformed single

representations from the same regions in ROC-AUC and PR-AUC, peptide pair and single
representations showed no significant difference in these metrics. However, our dataset
exhibits significant variation in agonist distribution: some promiscuous GPCRs have many
agonists, while most receptors have few (**Figure 1B**). Metrics like ROC-AUC and PR-AUC
weight each GPCR-agonist complex equally, which disproportionately prioritizes
promiscuous GPCRs in evaluation. To address this, we used the recommender system
metric AP, which is computed per GPCR gene such that each gene contributes equally
regardless of agonist count or the number of GPCR isoforms derived from that gene. Using
leave-one-group-out analysis, we show that peptide pair representations achieve higher AP
scores than single representations (**Figure 3D**).

Distinct subregions of pair representations capture complementary information
relevant to successful classification of GPCR-peptide agonists

Our analysis of different subregions in single and pair representations revealed that pair
representations provide valuable information for predicting GPCR-peptide agonists. To
further investigate this, we trained leave-one-group-out random forest models on three key
subregions of the pair representations: (1) the bp:peptide subregion (pairwise residues
between the binding pocket and the peptide), (2) the peptide subregion, and (3) the binding
pocket subregion.

Models trained on the binding pocket subregion exhibited significantly lower AP scores
compared to models trained on the bp:peptide or peptide subregions (**Figure 3E**). However,
despite these lower scores, binding pocket-trained models demonstrated unique
prioritization capabilities for certain agonists that eluded models trained on other subregions
(**Figure 3F**). Notable examples include the GPCRs FRPR-15, GNRR-3, and NPR-3, where
binding pocket features proved particularly informative. Similarly, peptide-trained models
showed superior performance for some GPCRs, while bp:peptide-trained models were more
effective for others. This pattern of variable performance across subregions suggests that
features from different subregions are complementary rather than universally optimal for all
GPCRs.

Integration of multimodal GPCR-peptide features for prioritizing agonist interactions

Given the complementary nature of features from different subregions, we generated graph
representations of GPCR-peptide complexes (**Figure 4A**) to leverage the ability of GNNs to
model complex relational data (e.g., residue interactions).

The graph representations consist of two distinct sets of nodes: GPCR residue nodes and
peptide residue nodes. To define intermolecular edges between these nodes, we use
Arpeggio[41], a computational tool designed to identify biophysically meaningful interatomic
interactions in protein structures by analysing spatial and physicochemical relationships
(e.g., hydrogen bonds, ionic interactions, cation-π interactions, etc.) (**Figure 4B**). Only
GPCR residues directly connected to peptide residues via Arpeggio-identified interactions
(or within one degree of such interactions) are selected as nodes, ensuring the graphs focus
on biophysically relevant regions of each GPCR. In contrast, all peptide residues are
included as nodes, as the smaller size of peptides enables their inclusion without excessive
computational burden. Additionally, intramolecular connectivity is preserved by connecting
nodes with edges based on their primary sequences.

GPCR nodes are loaded with embeddings derived by residue-specific pooling of the pair
representation's GPCR subregion, while peptide nodes are loaded with embeddings

generated similarly from the peptide subregion (**Figure 4C**). Specifically, for each residue i,
we average the i-th row and the i-th column across all features of the respective subregion
matrix, yielding a 128-dimensional embedding that captures residue-level structural and
interaction information from the pair representation. Edges between GPCR and peptide
residues are loaded with pairwise interaction embeddings. This design ensures that node
embeddings encode residue-specific information, incorporating both local and global context
from the pair representation, while interaction edges encode intermolecular residue-residue
interaction context.

Impact of graph structure and edge embeddings on GNN performance

To assess how graph structure and edge features influence performance, we conducted an
ablation study (**Figure 4D**). First, we replaced Arpeggio-defined interaction edges with
distance-based edges (residues ≤ 6 Å apart), resulting in a significant reduction in AP when
evaluated via shuffle-groups-out cross-validation (11 splits). Next, we removed pairwise
interaction embeddings from Arpeggio-defined edges, which similarly decreased
performance (**Figure 4D**). Interestingly, when both changes were combined—using
distance-based edges and omitting edge features—the model outperformed either single
ablation alone, although this combined ablation still achieved significantly lower AP than the
complete graph structure (Arpeggio edges with edge features).

Distance-based edges, while capturing spatial proximity, may introduce non-functional
contacts that create noise when paired with pairwise interaction embeddings, likely because
they lack the physicochemical specificity inherent in Arpeggio-defined interactions.
Conversely, while Arpeggio edges provide biologically relevant connections, the model
cannot effectively make use of this connectivity without the context provided by pairwise
interaction embeddings. The complete graph structure, which combines Arpeggio-defined
edges with edge features, outperformed all ablated versions, suggesting a synergistic effect
of biophysically meaningful edges and interaction-aware features. This framework enables
the GNN, DeorphaNN, to learn complex relational patterns that achieve significantly higher
AP scores than a peptide pLDDT-based approach (**Figure 4E**). Importantly, DeorphaNN can
prioritize agonists that are overlooked by peptide pLDDT (**Figure 4F**), demonstrating its
ability to identify agonists independently of pLDDT-based prioritization.

Validation on phylogenetically diverse data and comparison to state-of-the-art

To assess whether DeorphaNN captures conserved mechanisms of GPCR-peptide agonism
rather than species-specific patterns, we evaluated its performance on a dataset from the
bilaterian marine annelid, *Platynereis dumerilii*[11]. This dataset contains 18 GPCRs and 122
peptides that were tested in a similar experimental pipeline as the *C. elegans* training
dataset (high-throughput CHO Gα$_{16}$-mediated calcium signalling assay). We utilized
DeorphaNN to rank *Platynereis* peptides for each GPCR based on predicted agonist
potential. The mAP across all *Platynereis* GPCRs was significantly greater than the baseline
expected with random ranking (**Figure 5A**), demonstrating that DeorphaNN generalizes to
non-*C. elegans* datasets.

To assess DeorphaNN's generalization to human GPCR-peptide interactions, we utilized a
literature-curated dataset of experimentally confirmed agonist interactions across species[42].
While this dataset includes human GPCR-agonist pairs, it lacks non-agonist interactions. To
address this gap, we generated synthetic non-agonist GPCR-peptide pairs using a
dissimilarity-based approach inspired by principles from prior work[42]. Specifically, we

leveraged ESM-2[43] language model embeddings to quantify peptide dissimilarity. By
calculating the Euclidean distance between each peptide's ESM-2 representation and that of
the cognate agonists, we selected peptides with a distance exceeding an empirical
threshold—chosen to ensure at least 3 non-agonists per GPCR.

To validate the biological relevance of these synthetic pairs, we trained a model using the
DeorphaNN framework on the human dataset (augmented with synthetic non-agonist
interactions) and tested its performance on the *C. elegans* dataset, which contained no
synthetic data (**Figure 5B**). This model achieved scores significantly higher than the random
baseline, confirming that the human dataset—which combines confirmed agonist pairs with
ESM-2-guided synthetic non-agonists—reliably captures real-world interaction patterns and
supports the augmented dataset's utility for benchmarking.

We then benchmarked DeorphaNN (trained on *C. elegans* data) on the augmented human
dataset, achieving a mAP of 0.72—significantly higher than the random baseline of 0.30
(**Figure 5C**). For comparison, we evaluated SpatialPPIv2, a state-of-the-art model designed
for protein-protein interaction prediction that leverages large language models and graph
attention networks to capture structural patterns[44]. On the same augmented human dataset,
SpatialPPIv2 achieved a mAP of 0.33, not significantly different from random ranking.
DeorphaNN significantly outperformed SpatialPPIv2, demonstrating greater accuracy in
predicting GPCR-peptide agonist interactions. This difference highlights that our specialized
GNN—which integrates structural predictions and interaction data—captures biologically
relevant features specific to GPCR-peptide agonism more effectively than general protein-
protein interaction models.

Discovery of novel peptide agonists for orphan GPCRs identified by virtual screening

Some peptide agonists were identified after the system-wide experimental screen of GPCR-
peptide interactions in *C. elegans*. Indeed, peptidomics and comparative genomics studies
have since expanded the number of peptides known in *C. elegans* beyond those included in
the training dataset[45–47], providing an opportunity to reassess *C. elegans* GPCRs with a
broader set of candidate ligands. The receptor NPR-34, an ortholog of the elevenin peptide
receptor family, was not found to have agonist-induced activity with any of the peptides in
the training dataset, but subsequent experiments demonstrated that this receptor is activated
by a *C. elegans* peptide (SNET-1-1) related to the elevenin peptide family[9]. This agonist
ranks first out of 364 candidates (339 peptides from the training dataset plus 25 recently
identified peptides [**Supplemental Data 1**]) by DeorphaNN's predictions (**Table 1**). Similarly,
the peptide NLP-73-3 was present in the training dataset but did not activate SEB-2 in the
original screen because the synthetic peptide lacked a post-translational modification
(disulfide bridge) important for receptor activation; however, when synthesized with this
modification, NLP-73-3 robustly activated SEB-2[9]. Indeed, NLP-73-3 is ranked first among
all candidate peptides for SEB-2 by DeorphaNN (**Table 1**).

We next applied DeorphaNN to two orphan *C. elegans* GPCRs, NPR-44/H23L24.4 and
NPR-33/F31B9.1, and tested their highest-ranked candidate agonists. For NPR-44, we
observed robust activation by NLP-69-1 (EC$_{50}$ value of 231.7 nM), ranked 5th out of 364
peptides by DeorphaNN (**Table 1, Figure 6A, Supplemental Data 3**). In addition, NPR-33
was potently activated by NLP-70-2 (EC$_{50}$ value of 76.3 nM), the highest-ranked peptide
(**Table 1, Figure 6B, Supplemental Data 3**). No response was seen with any of the
peptides in cells transfected with an empty vector control (**Supplemental Figure 2A**). Given
that GPCRs are often activated by multiple peptides within the same peptide-encoding gene

(**Supplemental Figure 1A**), we also tested NLP-70-1 (ranked 156/364 by DeorphaNN),
another putative peptide encoded by the *nlp-70* gene. Although we detected receptor
activation, NLP-70-1's EC_{50} value (1.16 µM; **Figure 6C**) is considerably higher than that of
NLP-70-2. This suggests DeorphaNN may prioritize agonists with specific interaction
patterns that correlate with higher potency. Indeed, the majority of agonist interactions in the
C. elegans dataset exhibit high potency ($EC_{50} < 500$ nM)[9], which may explain why lower-
potency agonists like NLP-70-1 were ranked lower by DeorphaNN.

DISCUSSION

In this study, we present DeorphaNN, a GNN-based pipeline for predicting GPCR-peptide
agonist interactions *in silico* that offers a scalable strategy for GPCR deorphanization.
Previous studies have shown that pLDDT from AlphaFold predictions correlate with
interaction affinity[31,32,48], consistent with our findings that pLDDT partially discriminate
agonists from non-agonists. However, affinity alone is insufficient to determine agonist
function[35,49]. While affinity is a prerequisite for agonism, it does not capture additional
mechanisms required for functional activation, such as intrinsic efficacy[50]—the propensity of
a ligand to induce conformational changes in the GPCR that activate downstream G protein
signalling.

Agonist binding induces conformational changes in the GPCR that drive conserved
transmembrane (TM) rearrangements, a hallmark of receptor activation[38,51,52]. A key feature
of this process is the outward movement of TM6[53], facilitated by kinking at conserved motifs
and disruption of ionic interactions between TM3 and TM6/7[54–56]. These rearrangements
reconfigure the surface of the orthosteric binding pocket[57,58], enhancing affinity for
agonists[59]. To capitalize on this mechanism, DeorphaNN incorporates active-state structural
templates generated using AF-Multistate[34]. This enables the modelling of GPCR-peptide
complexes in their active conformations, leveraging AF-Multimer's ability to prioritize
peptides that both bind and stabilize the active-state binding pocket.

DeorphaNN builds on AF-Multimer by analyzing patterns in the predicted active-state
complex to predict whether bound peptides can activate receptors. Agonists activate GPCRs
through interactions with key "toggle switch" residues in the binding pocket[60,61]. This
activation is thought to require two distinct types of intermolecular interactions: "anchor"
interactions that provide stability for ligand binding, and "driver" interactions that directly
engage with toggle switches to induce GPCR conformational changes[62–64]. To enable
pattern recognition of these interactions, we engineered DeorphaNN to utilize Arpeggio-
defined edges—capturing interatomic interactions[41]—and AF pairwise embeddings—
encoding implicit biophysical relationships between residues[27]. By integrating these features,
DeorphaNN learns to distinguish agonists from non-agonists, likely through patterns
corresponding to the anchor and driver interactions essential for receptor activation and
intrinsic efficacy. In contrast, SpatialPPIv2—a state-of-the-art model for predicting general
protein-protein interactions[44]—lacks this context, explaining its inferior performance in
differentiating agonist from non-agonist interactions (**Figure 5C-D**).

Despite being trained on a relatively small number of GPCR-agonist pairs from *C. elegans*,
DeorphaNN's predictions seem to generalize across species. This success reflects the
effective application of inductive transfer learning principles, which have revolutionized fields
like natural language processing and computer vision by enabling models pretrained on
large datasets to be fine-tuned for specialized tasks with limited data[65,66]. In our work,

DeorphaNN leverages the AF2 algorithm, which was pretrained on approximately 170,000 protein structures from diverse species[26], and adapts it for the specialized task of GPCR-peptide agonism prediction. The model's ability to predict agonist interactions in phylogenetically distinct species such as *Platynereis dumerilii* and humans suggests that the implicit biophysical principles learned by AF2 were successfully transferred to this specialized task.

Compared to existing methods, DeorphaNN represents a significant advancement in GPCR-peptide agonism prediction. PD-incorporated SVM, a sequence-based approach, predicts peptide agonists for GPCRs using a support vector machine trained on peptide descriptors that represent sequence patters of 1-5 residues encoded into numeric arrays[42]. GPCRVS employs deep neural networks, gradient boosting machines, and AutoDock Vina to predict compound activity, selectivity, and binding affinity for small molecules and peptides, but is restricted to GPCRs within its training data and can only effectively screen N-terminal fragments of peptides (six residues or smaller)[67]. In contrast, DeorphaNN integrates structural predictions from AF-Multimer, deep learning-derived protein representations, and intermolecular interactions data, enabling it to learn from three-dimensional structural relationships and biophysical interaction patterns that are not captured by primary sequence alone. Trained on biologically relevant peptide sizes (3-37 residues) and demonstrating generalization to non-*C. elegans* GPCRs, DeorphaNN provides a more comprehensive approach to GPCR-peptide agonism prediction across diverse receptors.

Despite its advances, DeorphaNN does not uncover all GPCR-peptide agonist interactions. Several factors likely contribute to this limitation. First, as the training dataset was derived from a single experimental screen, the accuracy of the dataset is inherently tied to the limitations of that screen. For example, while the promiscuous $G\alpha_{16}$ subunit enables many GPCRs to signal through the PLCβ pathway, the effectiveness of this signalling can be ligand-specific[68], potentially resulting in misclassified negative interactions. In addition, some peptides may be misclassified for highly promiscuous receptors, as not all peptides from the same precursor gene were tested against these receptors for agonist-induced activity. Second, while the dataset includes a variety of GPCR-peptide agonist interactions, it is not exhaustive, creating potential blind spots for interactions that are dissimilar to those in the training dataset. Third, DeorphaNN's performance depends on AF2's ability to accurately predict GPCR-peptide complexes. Inaccurate structural predictions may fail to capture the true nature of GPCR-peptide relationships, impacting DeorphaNN's effectiveness. Indeed, AF2-predicted GPCR structures show deviations in ligand-binding pockets and extracellular domains compared to experimentally determined structures[69,70]. Additionally, AF2 cannot account for post-translational modifications of GPCRs and peptides. For GPCRs, extracellular post-translational modifications such as tyrosine sulfation, glycosylation, and proteolytic cleavage may alter ligand binding[71]; for peptides, post-translational modifications such as C-terminal amidation or pyroglutamation are often important for agonist activity[35]. Although direct interactions between GPCRs and the C-terminal amidated group of peptide ligands have not yet been identified[35], amidation has been shown to influence biological activity[72], and the omission of such post-translational modifications in AF2 predictions may result in lost interaction information. However, with the advent of newer models such as AlphaFold3[73], Chai-1[74], and Boltz-1[75]—which can account for post-translational modifications and demonstrate higher modelling accuracy—these limitations may be addressed in future work.

In this study, we demonstrate how deep learning methods can enhance the identification of
functional GPCR-ligand relationships, using DeorphaNN to identify agonists for two
previously orphan GPCRs in *C. elegans*. Our results demonstrate that DeorphaNN's
predictive capabilities extend beyond this model organism, suggesting its potential to aid in
deorphanization efforts of both orphan GPCRs and orphan peptides. Beyond facilitating the
discovery of novel signalling pathways and potential therapeutic targets, DeorphaNN may
significantly accelerate drug discovery efforts, as recent advances in machine learning-
based synthetic peptide design have produced tools for generating synthetic ligands for
GPCRs[76,77]. DeorphaNN complements all of these efforts, prioritizing promising candidate
peptide agonists for experimental validation and reducing the need for exhaustive screening.

MATERIALS AND METHODS

Datasets

The *C. elegans* training dataset was derived from a previously published system-wide
screen using a CHO $G\alpha_{16}$-mediated calcium signalling assay to assess endogenous peptide
agonist activity across *C. elegans* GPCRs[9]. To accommodate AF-Multimer's limitations
regarding post-translational modifications, we preprocessed peptide sequences by removing
C-terminal glycine residues for amidated peptides and N-terminal glutamine residues for
pyroglutamated peptides. Peptides containing disulfide bridges were not changed. After
removing duplicate sequences and peptides shorter than 3 residues, 339 unique peptides
remained. GPCRs that lacked any concentration-dependent agonist responses in the screen
were excluded, reducing the likelihood that an observed lack of agonist activity was the
result of experimental limitations. Additionally, we excluded the GPCR DMSR-8-1, which has
the same agonist interaction profile as the other DMSR-8 isoform (DMSR-8-2) and only
differs in sequence by an addition of four N-terminus residues. This filtering process resulted
in a final training dataset comprising 65 unique GPCRs derived from 55 genes. The full list of
GPCRs and peptides included in the *C. elegans* training dataset is provided in
Supplemental Data 1.

The *Platynereis dumerilii* dataset used for cross-species validation was derived from a
previously published report[11]. We processed all peptides with modified residues as above
and omitted peptides with D-amino acids, resulting in 122 peptides. We similarly omitted
GPCRs that had no confirmed agonists among the included peptides, resulting in 18
receptors and 23 agonist interactions.

For the human dataset, we utilized a previously published list of GPCR-peptide agonist
interactions compiled across diverse species, including vertebrates and invertebrates[42]. We
limited our analysis to agonist interactions involving human GPCRs, while using peptides
from all species (excluding those longer than 50 residues) to augment the dataset with
synthetic non-agonist interactions. Specifically, we generated ESM2-150M[43] embeddings for
each peptide and identified, for each GPCR, peptides with Euclidean distances > 3.9 from
known agonists, ensuring at least 3 putative non-agonists per GPCR. This process yielded
an augmented dataset containing 345 agonist and 3370 non-agonist GPCR-peptide pairs
across 82 human GPCRs.

In all datasets, we omitted GPCRs that were not predicted by DeepTMHMM to have the
characteristic GPCR structure (seven transmembrane domains, with an extracellular N-
terminal and an intracellular C-terminal). The full list of GPCRs and peptides included in the
validation datasets (*Platynereis* and human) are provided in **Supplemental Data 2**.

AlphaFold2

Primary amino acid sequences for each GPCR-peptide complex were input together
(GPCR:peptide) into AF-Multimer[26,31] using local ColabFold v1.5.5[78] on a high-performance
computing cluster. All modelling settings were left at default
(model_type=alphafold2_multimer_v3, num_recycles=20, recycle_early_stop_tolerance=0.5,
pairing_strategy=greedy, max_msa=auto), resulting in the generation of 5 predicted
structures and corresponding confidence metrics. Hidden layer protein representations
(single and pair) were collected.

For confidence metric analyses, we utilized the model with the highest ipTM, highest peptide
pLDDT, or lowest pocket PAE, depending on the metric being analysed. To determine
whether the peptide was modelled within the binding pocket, we carried out analysis on the
predicted structure with the highest peptide pLDDT, measuring the minimum distance of
peptide to binding pocket residues after averaging the location of all atoms in each residue.

For all protein representation analyses, representations across all five AF-Multimer models
were averaged to prevent algorithms from learning patterns specific to the different AF-
Multimer models.

To bias AF-Multimer predictions towards GPCR active-state conformations, we first
generated active-state GPCR templates using AF2-Multistate[34]. This approach leverages
state-annotated GPCR databases to guide predictions with a restricted MSA protocol. The
top ranked active-state structures were processed by trimming intracellular residues with
pLDDT values below 70 and all extracellular residues, based on DeepTMHMM[36]
annotations. These processed structures served as GPCR-specific templates in subsequent
AF-Multimer predictions for each GPCR-peptide pair, generating state-biased predictions.
MSA reduction was not necessary as the templates were derived from the same sequence
as the target GPCRs[79], and retaining the full MSA preserves coevolutionary signals that are
vital for driving accurate inter-protein contact predictions[80].

Mean Average Precision (mAP)

547 Ranking performance was quantified according to recommendation system metrics[81], using
548 average precision (AP) computed across all peptides (*N*) per GPCR or GPCR gene. For
549 each receptor, AP aggregates precision at every rank containing an agonist:

$$AP = \frac{\sum_k^N \left(\frac{\text{agonists in top } k}{k}\right) \times rel@k}{total\ agonists}$$

551 where $rel@k$ equals 1 if the k-th ranked peptide is relevant (i.e. an agonist) and 0 otherwise.
552 Mean average precision (mAP) averages AP equally across all GPCRs.

553 To establish a random baseline, we randomized peptide rankings 100 times per GPCR or
554 GPCR family and computed the AP. The average of the 100 APs was then used as the
555 random baseline AP.

Supervised learning algorithms

We implemented random forest classifiers using scikit-learn[82] with default hyperparameters,
leveraging their ability to perform implicit feature selection and assess feature importance.
To maintain consistency across all cross-validation splits, we used identical random seed
and data partitions. For Figures 3B and 3C, we employed stratified group 10-fold cross-
validation with the same random seed. Grouping by GPCR was performed to minimize
leakage of receptor-specific information between folds. Isoforms from the same GPCR gene
were treated as a single unit, ensuring they appear together (55 unique GPCR genes), and
class distribution was balanced by stratification. For Figures 3D and 3E, we employed leave-
one-group-out cross-validation. Reported APs are an average of 5 different random seeds.

Arpeggio

The top-ranked GPCR-peptide structure according to peptide pLDDT was examined.
Peptides that exhibited a minimum distance greater than 12.5 Å from the binding pocket
were excluded from further analysis. The position of each residue is defined by averaging
the position of each residue atom. Structures were relaxed by Amber[83] and analysed with
Arpeggio[41] to identify interatomic interactions between the GPCR and peptide. Specifically,
we identified hydrophobic interactions, polar bonds, weak polar bonds, hydrogen bonds,
weak hydrogen bonds, ionic bonds, aromatic ring interactions, van der Waals' forces, and
amide group interactions.

Graph construction

Graphs were constructed from GPCR-peptide interaction data obtained from AlphaFold2
structural predictions and pair representations. Each graph represents a GPCR-peptide
complex, with nodes corresponding to individual residues. All peptide residues were included
as nodes, while GPCR residues were included if they directly interacted with peptide
residues or were within one degree of such interactions. Nodes were connected by two
types of edges: intramolecular edges connecting nodes according to primary sequence, and
intermolecular edges connecting GPCR and peptide nodes according to Arpeggio-identified
interactions. For Figure 4D, spatial proximity-based edges (< 6 Å) were also utilized,
computed by defining the residue's position as the average position of the atoms that make
up the residue.

Node features were derived using pair representations averaged over 5 models for each
residue position. First, we processed the tensor $\boldsymbol{P} \in \mathbb{R}^{n \times n \times 128}$—where n is the total residue
count in the GPCR-peptide complex—to extract three sub-tensors:

589
$$\boldsymbol{P}^{\text{GPCR}} \in \mathbb{R}^{n_{GPCR} \times n_{GPCR} \times 128}$$

590
$$\boldsymbol{P}^{\text{pep}} \in \mathbb{R}^{n_{pep} \times n_{pep} \times 128}$$

591
$$\boldsymbol{P}^{\text{int}} = \frac{1}{2}\left(\left(\boldsymbol{P}^{\text{GPCR,pep}} \in \mathbb{R}^{n_{GPCR} \times n_{pep} \times 128}\right) + \left(\boldsymbol{P}^{\text{pep, GPCR}} \in \mathbb{R}^{n_{pep} \times n_{GPCR} \times 128}\right)^{T}\right)$$

592 where n_{GPCR} and n_{pep} are residues of the GPCR and peptide, respectively.

593 We derived per-residue embeddings for GPCR and peptide nodes by applying cross-axis
594 pooling independently to sub-tensors, $\boldsymbol{P}^{\mathrm{GPCR}}$ and $\boldsymbol{P}^{\mathrm{pep}}$. For each residue i in the sub-tensor
595 $X \in \{\mathrm{GPCR}, \mathrm{pep}\}$, we computed its embedding by averaging within each of the 128 features
596 across the i-th row and the i-th column while correcting for (i, i) duplication:

$$z_i^X = \frac{\left(\sum_{k=1}^{n_X} P_{k,i,:}^X + \sum_{k=1}^{n_X} P_{i,k,:}^X\right) - P_{i,i,:}^X}{2n_X - 1}$$

598 Intermolecular edge features were derived from the interaction region of the pair
599 representations ($\boldsymbol{P}^{\mathrm{int}}$), with each intermolecular edge loaded with a 128-dimensional feature
600 vector representing the interaction between the residue pairs connected by that edge.
601 Intramolecular edges were assigned a uniform feature vector, computed as the mean-pooled
602 representation of all intermolecular edge features across the graph.

Model architecture and training

The GNN architecture is based on the Graph Attention Network (GAT) framework,
specifically utilizing the GATv2Conv[84] layer implementation from PyTorch Geometric. The
network begins with a Batch Normalization layer to standardize input features, ensuring
stable training dynamics. This is followed by a GATv2Conv layer with 10 attention heads, a
dropout rate of 0.5, and 64 hidden channels. The attention mechanism allows the model to
dynamically weigh the importance of neighbouring nodes differently when aggregating
information, enabling it to focus on relevant structural and interaction patterns within the
graph.

After the convolutional layer, a rectified linear unit (ReLU)[85] activation function introduces
non-linearity to the model. For graph-level representation learning, a global mean pooling
operation aggregates node embeddings across the entire graph, producing a fixed-size
vector representation regardless of graph size. This pooled representation is then passed
through a final linear layer with a dropout rate of 0.5 for regularization before being fed into a
softmax function for classification. The model is trained using the AdamW optimizer[86] with a
learning rate of 0.0005 and employs CrossEntropyLoss[87] with label smoothing to mitigate
overfitting and improve generalization. During training, graphs are batched and processed
using PyTorch Geometric's DataLoader, with edge features incorporated where applicable.

For each validation fold, the training set was subsampled to maintain a balance between
positive and negative examples. Specifically, for each positive example (agonist GPCR-
peptide complex), four negative examples (non-agonist GPCR-peptide complex) were
randomly selected, creating a balanced training set with a 1:4 ratio of positive to negative
samples. The model selection was based on validation performance using group shuffle-split
cross-validation, with early stopping to prevent overfitting. In this approach, the dataset was
divided into groups based on GPCR families, and multiple random splits were generated
where each split maintained a specified proportion of groups in the training and validation
sets. This method ensures that the model is evaluated on previously unseen GPCR families
while maintaining biological relevance in the validation process. The final model for each fold
was chosen based on the highest validation average precision score achieved during
training. Training was performed for 30 epochs, with the model evaluated periodically on the
validation set to monitor convergence and generalization performance.

The final predictions reported were generated using an ensemble of 10 GNNs trained via bootstrap aggregating, with each model trained on a distinct 90% bootstrap sample of the training data. The ensemble outputs were aggregated to produce the final prediction scores.

Aequorin-based GPCR activation assay

An aequorin-based calcium mobilization assay was used to assess GPCR activation following peptide application, as previously described[9]. In brief, reverse pharmacology screening was performed using CHO-K1 cells expressing mitochondrial-targeted apo-aequorin and promiscuous human $G\alpha_{16}$. CHO cells were transfected with pcDNA3.1 plasmids containing the GPCR of interest and harvested two days after transfection. BSA served as a negative control for peptide-evoked calcium responses; ATP activates an endogenous receptor in CHO cells and was used as a positive control. Maximum calcium responses for normalization were obtained by lysing cells at the end of the assay.

Statistical analysis

Statistical analysis was performed in GraphPad Prism version 10.2.2 for macOS (GraphPad Software, San Diego, CA). All statistical tests were two-tailed.

RESOURCE AVAILABILITY

Lead Contact

Requests for further information and resources should be directed to and will be fulfilled by the lead contact, Larissa Ferguson (LariFerg@gmail.com).

Materials Availability

This study did not generate new unique reagents.

Data and Code Availability

All datasets utilized in this study are available as Supplemental Materials and in a Hugging Face repository at https://huggingface.co/datasets/lariferg/DeorphaNN. The DeorphaNN code is available at https://github.com/Zebreu/DeorphaNN.

ACKNOWLEDGEMENTS

We thank Jake Grimmett, Toby Darling, and Ivan Clayson of LMB Scientific Computing. Additional thanks to members of the Schafer lab for helpful discussions. Z.W. acknowledges support from the Max Perutz Fund as part of the GenerationResearch project. W.R.S. acknowledges support from the Medical Research Council (MRC) core grant MC-A023-5PB91 and the Research Foundation – Flanders (FWO) grant G050825N. I.B. acknowledges support from the KU Leuven Research Council grant C16/19/003, the Research Foundation – Flanders (FWO) grant G036524N, and the Baillet Latour Fund.

AUTHOR CONTRIBUTIONS

L.F., S.O., T.K.L., W.R.S., and I.B. conceptualized the work; L.F., S.O., and T.K.L developed methodology; L.F., S.O., and T.K.L. performed formal analysis; L.F. and T.K.L. contributed to visualization; S.O., L.F., and C.W. developed software; L.F., S.O., E.V., C.W., Z.W.

conducted investigation and experiments; L.F. wrote the original manuscript draft; T.K.L.,
I.B., S.O., W.R.S., and C.W. reviewed and edited the manuscript; W.R.S., I.B., and L.F.
supervised the project. W.R.S. and I.B. provided funding and infrastructure.

DECLARATION OF INTERESTS

The authors declare no competing interests.

DECLARATION OF GENERATIVE AI AND AI-ASSISTED TECHNOLOGIES IN THE
WRITING PROCESS

During the preparation of this work, ChatGPT and KIMI.ai were used to improve readability.
After using these tools/services, the authors reviewed and edited the content as needed and
take full responsibility for the content of the publication.

FIGURES

Figure 1: AF-Multimer structures and confidence metrics exhibit limited ability to
discriminate between agonist and non-agonist GPCR-peptide interactions

(**A**) 65 GPCRs and 339 endogenous peptides (22 035 GPCR-peptide pairs) from *C. elegans* were
modelled using AF2-Multimer. (**B**) Frequency distribution of the number of agonists per GPCR in the
dataset. Most GPCRs have few agonists (median = 3), though a small number of promiscuous
GPCRs account for the majority of agonist interactions. (**C**) Example AF-Multimer predicted
structures. Left: FLP-34-4, an agonist for the GPCR, NPR-11-1, is modelling in the orthosteric binding
pocket. Right: NLP-36-1, a non-agonist for NPR-11-1, is modelled outside of the binding pocket. The
GPCR is shown in pink, binding pocket residues (defined as ±5 residues from the extracellular-
membrane boundary) in yellow, and peptides in blue. (**D**) The percentage of peptides modelled
outside the binding pocket for each GPCR ranges from 0 – 24.5%, with a mean of 3.4% (±4.4%

SD).(**E**) 99.8% of agonists are modelled within the GPCR binding pocket, compared to 96.6% of non-
agonists. (**F**) Peptide pLDDT significantly outperforms ipTM, pocket PAE, and random ranking in
distinguishing agonists from non-agonists (Friedman test with multiple comparisons with FDR
correction using the method of Benjamini, Krieger, and Yekutieli, * q < 0.05). Error bars indicate mean
± SEM.

Figure 2: Active-state templates enhance AF-Multimer's discrimination of agonist and non-agonist GPCR-peptide interactions

(**A**) Predicted active-state structures were generated for each GPCR using AF-Multistate. After trimming all extracellular regions and low confidence (pLDDT < 70) intracellular regions, these templates were then used in AF-Multimer to model GPCR-peptide complexes. (**B**) Representative agonist complex: GPCR CKR-1-1 is modelled with agonist peptide NLP-12-1 without (left) and with (right) an active-state template. The use of an active-state template improved peptide pLDDT. (**C**) Representative non-agonist complex: GPCR FRPR-18-2 is modelled with non-agonist NLP-12-1 (the same peptide shown in B) with (left) and without (right) an active-state template. The use of an active-state template does not alter peptide pLDDT. (**D**) Average precision (AP) of agonist peptides ranked by peptide pLDDT significantly improved when using active-state templates (mAP: 0.36 vs. 0.32 without templates; Wilcoxon signed-rank test, $p < 0.05$). Error bars indicate mean ± SEM. (**E**) The improvement in peptide pLDDT with active state templates was significantly greater for agonists compared to non-agonists (Welch's t-test, $p < 0.0001$). Error bars represent mean ± SEM. (**F**) Active-state templates increased the percentage of peptides modelled outside the GPCR binding pocket (mean: 5.5% ±0.6% SEM vs. 3.4% ±0.6% without templates; paired t-test, $p < 0.0001$).

Figure 3: Subregions of AF-Multimer pair representations provide complementary information for classifying agonist and non-agonist peptides

(**A**) Schematic illustration of feature extraction from AF-Multimer representations. Single representations ($\mathbb{R}^{\{n \times 128\}}$) and pair representations ($\mathbb{R}^{\{n \times n \times 128\}}$) were processed by aggregating features via local pooling over predefined subregions: peptide residues (blue outlines), GPCR residues (purple outlines), binding pocket residues (orange outlines), and the pairwise interaction of binding pocket and peptide residues ("bp:peptide"; yellow outlines; pair representations only). (**B**) Pair representations significantly outperform single representations for GPCR and binding pocket subregions, and peptide subregions outperform GPCR and binding pocket subregions. Random forest models were evaluated by ROC-AUC in 10-fold cross validation. Two-way repeated measures ANOVA with Geisser-Greenhouse correction shows significant interaction between the representation type and the subregion used F (1.387, 12.49) = 10.22, p = 0.0044). Multiple comparisons comparing each group to every other group corrected by the FDR method of Benjamini, Krieger, and Yekutieli reveals that peptide subregion performance exceeded that of GPCR or binding pocket subregions, but did not show a significant difference between single and pair representations (* q < 0.05). (**C**) PR-

AUC analysis mirrors ROC-AUC results. A two-way repeated measures ANOVA with Geisser-
Greenhouse correction was conducted to investigate the effects of representation type and subregion
on PR-AUC. A significant main effect was found for representation type ($F_{(1.000, 9.000)}$ = 13.76, p =
0.0048) and subregion ($F_{(1.408, 12.67)}$ = 15.91, p = 0.0008). The interaction between representation
type and subregion was not significant ($F_{(1.889, 17.00)}$ = 1.758, p = 0.203). Multiple comparisons
comparing each group to every other group corrected by the FDR method of Benjamini, Krieger, and
Yekutieli reveals that peptide subregion performance exceeded that of GPCR or binding pocket
subregions, but did not show a significant difference between single and pair representations (* q <
0.05). (**D**) A more in-depth evaluation using leave-one-group-out cross-validation (GPCR gene
families as groups) reveals that random forest models trained on peptide pair representations
significantly outperform single representations (** p < 0.01, Wilcoxon matched-pairs signed rank test).
The average precision (AP) was calculated for each GPCR gene. Error bars denote mean ± SEM. (**E**)
Leave-one-group-out analysis revealed that random forest models trained on peptide and bp:peptide
regions outperformed models trained on the binding pocket subregion (* q < 0.05, Friedman test with
multiple comparisons corrected by the FDR method of Benjamini, Krieger, and Yekutieli). (**F**) Heatmap
of AP values from (E) illustrates that different GPCR gene families benefit from features provided by
different subregions.

751
Figure 4: DeorphaNN integrates predicted active state complexes, interatomic
interactions, and protein representations to prioritize GPCR-peptide agonists

(**A**) Graph representations of GPCR-peptide complexes. Intra-protein edges are defined by primary
sequence, while inter-protein edges are defined by Arpeggio. Peptide residues (all included) and
GPCR residues (those directly connected to peptides via Arpeggio-identified interactions or within one
degree of such interactions) serve as nodes. (**B**) AF-Multimer predicted structures are analyzed by
Arpeggio, which identifies biophysically meaningful interatomic interactions (e.g., hydrogen bonds,
ionic interactions). Arpeggio interactions are used to define intermolecular edges between GPCR and
peptide residue nodes. (**C**) AF-Multimer pair representations are split into GPCR, peptide, and

interaction subregions. Residue-specific pooling of GPCR and peptide subregions generates 128-

dimensional embeddings for respective nodes. Interaction edges are annotated with pairwise

interaction embeddings from the interaction subregion. (**D**) Arpeggio-defined edges and use of

interaction edge features synergistically improve model performance as determined by shuffle-

groups-out cross-validation with 11 splits. Two-way repeated measures ANOVA with Geisser-

Greenhouse correction shows significant interaction between the use of edge features (no features

vs. pairwise interaction embeddings), and method of drawing edges (distance-based cutoff vs.

Arpeggio) ($F(1, 10) = 28.75$, $p = 0.0003$). Multiple comparisons comparing all groups, corrected by the

FDR method of Benjamini, Krieger, and Yekutieli, reveal that loss of edge features and/or Arpeggio

defined edges significantly reduces model performance (* $q < 0.05$). Error bars indicate mean ± SEM.

(**E**) DeorphaNN outperforms peptide pLDDT in agonist prediction (Wilcoxon matched-pairs signed-

rank test, *** $p < 0.001$). Error bars indicate mean ± SEM. (**F**) Heatmap of AP values demonstrates

that DeorphaNN identifies agonists missed by peptide pLDDT across various GPCR families

Figure 5: DeorphaNN generalizes to non-*C. elegans* datasets

(**A**) DeorphaNN, trained on *C. elegans* data, prioritizes peptide agonists for GPCRs from *Platynereis dumerilii* significantly better than random ranking. (Wilcoxon matched-pairs signed rank test, ** p < 0.01). (**B**) A human GPCR-peptide agonist dataset was augmented with ESM-2-guided synthetic non-agonist pairs. Its representativeness was evaluated by training a DeorphaNN model on this augmented dataset and assessing its performance on the *C. elegans* dataset, which contains no synthetic data. Model performance was significantly greater than random ranking (Wilcoxon matched-pairs signed-rank test, **** p < 0.0001). (**C**) DeorphaNN (trained on the *C. elegans* dataset) significantly outperforms SpatialPPIv2 and random ranking on human GPCR-peptide agonist prioritization. Statistical significance was determined using the Friedman test with Dunn's correction (**** p < 0.0001). Error bars indicate mean ± SEM. (**D**) Heatmap for the per-GPCR AP values from (C), illustrating that DeorphaNN prioritizes agonists overlooked by SpatialPPIv2.

792
Figure 6: DeorphaNN-guided identification and experimental validation of agonists for
two *C. elegans* GPCRs
(**A**) Concentration-response curve showing calcium mobilization in CHO cells co-expressing the
GPCR NPR-44, $G\alpha_{16}$, and the calcium indicator aequorin upon stimulation with the peptide NLP-69-1.
Responses are shown relative to 100% activation after normalization to the total calcium response.
EC_{50} = 231.7 nM (95% CI: 153.6 nM - 309.7 nM), n = 6. (**B**) Concentration-response curve of the
GPCR NPR-33 to the peptide, NLP-70-2. EC_{50} = 76.3 nM (95% CI: 50.3 nM - 128 nM), n = 6. (**C**)
Concentration-response curve of the GPCR NPR-33 to the peptide NLP-70-1. EC_{50} = 1.16 µM (95%
CI: 1.00 µM - 1.38 µM), n = 6.

802
803
804 **TABLES**
805
806 Table 1: GPCR-peptide agonist pairs identified by DeorphaNN

GPCR	GPCR Uniprot ID	Peptide	Peptide sequence	Rank by DeorphaNN	Source
NPR-34	G5EDR6	SNET-1-1	LDCRKFSFAPACRGIML	1/364	Beets et al.[9]
SEB-2	P30650	NLP-73-3	NRQCLLNAGLSQGCDFSDLL HAQTQARKFMSFAGP	1/364	Beets et al.[9]
NPR-44	Q9N5L5	NLP-69-1	LHRIGGNIVM	5/364	This paper
NPR-33	O62189	NLP-70-2	WYDWQNVPHALQQ	1/364	This paper
		NLP-70-1	WYEWNNDMEIT	156/364	This paper

SUPPLEMENTAL INFORMATION

<u>Supplemental Figures 1-2</u>

<u>Supplemental Data 1</u>: An excel file with the names and primary sequences of all GPCRs and
peptides in the *C. elegans* training dataset, and a list of the experimentally validated agonist
pairs.

<u>Supplemental Data 2</u>: An excel file with the names and primary sequences of all GPCRs and
peptides in the validation datasets (*Platynereis* and human), with agonist pairs labelled.

<u>Supplemental Data 3</u>: An excel file with DeorphaNN predictions (ranked) for SEB-2, NPR-34,
NPR-44, and NPR-33 with 364 *C. elegans* peptides

REFERENCES

1. Atkins, N. *et al.* Functional Peptidomics: Stimulus- and Time-of-Day-Specific Peptide

Release in the Mammalian Circadian Clock. *ACS Chem. Neurosci.* **9**, 2001–2008 (2018).

2. Bhat, U. S., Shahi, N., Surendran, S. & Babu, K. Neuropeptides and Behaviors: How

Small Peptides Regulate Nervous System Function and Behavioral Outputs. *Front. Mol.*

Neurosci. **14**, 786471 (2021).

3. De Fruyt, N., Yu, A. J., Rankin, C. H., Beets, I. & Chew, Y. L. The role of neuropeptides

in learning: Insights from C. elegans. *Int. J. Biochem. Cell Biol.* **125**, 105801 (2020).

4. Jékely, G. *et al.* The long and the short of it – a perspective on peptidergic regulation of

circuits and behaviour. *J. Exp. Biol.* **221**, jeb166710 (2018).

5. Chew, Y. L. *et al.* An Afferent Neuropeptide System Transmits Mechanosensory Signals

Triggering Sensitization and Arousal in C. elegans. *Neuron* **99**, 1233-1246.e6 (2018).

6. Lorente, J. S. *et al.* GPCR drug discovery: new agents, targets and indications. *Nat. Rev.*

Drug Discov. (2025) doi:10.1038/s41573-025-01139-y.

7. Jékely, G. Global view of the evolution and diversity of metazoan neuropeptide signaling.

Proc. Natl. Acad. Sci. **110**, 8702–8707 (2013).

8. Hsueh, A. J. W. & Feng, Y. Discovery of polypeptide ligand-receptor pairs based on their

co-evolution. *FASEB J.* **34**, 8824–8832 (2020).

9. Beets, I. *et al.* System-wide mapping of peptide-GPCR interactions in C. elegans. *Cell*

Rep. **42**, 113058 (2023).

10.   Mirabeau, O. & Joly, J.-S. Molecular evolution of peptidergic signaling systems in

bilaterians. *Proc. Natl. Acad. Sci.* **110**, (2013).

11.   Bauknecht, P. & Jékely, G. Large-Scale Combinatorial Deorphanization of

Platynereis Neuropeptide GPCRs. *Cell Rep.* **12**, 684–693 (2015).

12.   Schulz-Knappe, P., Hans-Dieter, Z., Heine, G., Jurgens, M. & Schrader, M.

Peptidomics The Comprehensive Analysis of Peptides in Complex Biological Mixtures.

Comb. Chem. High Throughput Screen. **4**, 207–217 (2012).

13.   Ma, Y. *et al.* Identification of antimicrobial peptides from the human gut microbiome

using deep learning. *Nat. Biotechnol.* **40**, 921–931 (2022).

14.   Teufel, F. *et al.* DeepPeptide predicts cleaved peptides in proteins using conditional

random fields. *Bioinformatics* **39**, btad616 (2023).

15.   Foster, S. R. *et al.* Discovery of Human Signaling Systems: Pairing Peptides to G

Protein-Coupled Receptors. *Cell* **179**, 895-908.e21 (2019).

16.   Thiel, D. *et al.* Large-scale deorphanization of Nematostella vectensis neuropeptide G

protein-coupled receptors supports the independent expansion of bilaterian and cnidarian

peptidergic systems. *eLife* **12**, RP90674 (2024).

17.   Jékely, G. & Yuste, R. Nonsynaptic encoding of behavior by neuropeptides. *Curr.*

Opin. Behav. Sci. **60**, 101456 (2024).

18.   Brahma, R., Moon, S., Shin, J.-M. & Cho, K.-H. AiGPro: a multi-tasks model for

profiling of GPCRs for agonist and antagonist. *J. Cheminformatics* **17**, 12 (2025).

19.   Zhang, H. *et al.* Revolutionizing GPCR–ligand predictions: DeepGPCR with

experimental validation for high-precision drug discovery. *Brief. Bioinform.* **25**, bbae281

(2024).

20.   Huang, W.-C., Lin, W.-T., Hung, M.-S., Lee, J.-C. & Tung, C.-W. Decrypting orphan

GPCR drug discovery via multitask learning. *J. Cheminformatics* **16**, 10 (2024).

21.   Ballante, F., Kooistra, A. J., Kampen, S., De Graaf, C. & Carlsson, J. Structure-Based

Virtual Screening for Ligands of G Protein–Coupled Receptors: What Can Molecular

Docking Do for You? *Pharmacol. Rev.* **73**, 1698–1736 (2021).

22.   Luttens, A. *et al.* Rapid traversal of vast chemical space using machine learning-

guided docking screens. *Nat. Comput. Sci.* (2025) doi:10.1038/s43588-025-00777-x.

23.   Ciemny, M. *et al.* Protein–peptide docking: opportunities and challenges. *Drug*

Discov. Today **23**, 1530–1537 (2018).

24.   Badaczewska-Dawid, A. E., Kmiecik, S. & Koliński, M. Docking of peptides to

GPCRs using a combination of CABS-dock with FlexPepDock refinement. *Brief.*

Bioinform. **22**, bbaa109 (2021).

25.   Ciancetta, A. *et al.* A Multi-Angle Approach to Predict Peptide-GPCR Complexes:

The N/OFQ-NOP System as a Successful AlphaFold Application Case Study. *J. Chem.*

Inf. Model. **64**, 8034–8051 (2024).

26.   Jumper, J. *et al.* Highly accurate protein structure prediction with AlphaFold. *Nature*

596, 583–589 (2021).

27.   Roney, J. P. & Ovchinnikov, S. State-of-the-Art Estimation of Protein Model

Accuracy Using AlphaFold. *Phys. Rev. Lett.* **129**, 238101 (2022).

28.   Gazizov, A., Lian, A., Goverde, C., Ovchinnikov, S. & Polizzi, N. F. AF2BIND:

Predicting ligand-binding sites using the pair representation of AlphaFold2. Preprint at

https://doi.org/10.1101/2023.10.15.562410 (2023).

29.   Hu, M. *et al.* Exploring evolution-aware & -free protein language models as protein

function predictors. Preprint at https://doi.org/10.48550/arXiv.2206.06583 (2022).

30.   Ouellet, S., Ferguson, L., Lau, A. Z. & Lim, T. K. Y. CysPresso: a classification

886   model utilizing deep learning protein representations to predict recombinant expression of

887   cysteine-dense peptides. *BMC Bioinformatics* **24**, 200 (2023).

888   31.   Evans, R. *et al.* Protein complex prediction with AlphaFold-Multimer. *bioRxiv*

889   2021.10.04.463034 (2022) doi:10.1101/2021.10.04.463034.

890   32.   Tsaban, T. *et al.* Harnessing protein folding neural networks for peptide–protein

891   docking. *Nat. Commun.* **13**, 176 (2022).

892   33.   Johansson-Åkhe, I. & Wallner, B. Improving peptide-protein docking with

893   AlphaFold-Multimer using forced sampling. *Front. Bioinforma.* **2**, 959160 (2022).

894   34.   Heo, L. & Feig, M. Multi-state modeling of G-protein coupled receptors at

895   experimental accuracy. *Proteins Struct. Funct. Bioinforma.* **90**, 1873–1885 (2022).

896   35.   Tikhonova, I. G., Gigoux, V. & Fourmy, D. Understanding Peptide Binding in Class

897   A G Protein-Coupled Receptors. *Mol. Pharmacol.* **96**, 550–561 (2019).

898   36.   Jeppe Hallgren, A. K., Konstantinos D. Tsirigos, Mads D. Pedersen, José Juan

899   Almagro Armenteros, Paolo Marcatili, Henrik Nielsen & Winther, O. DeepTMHMM

900   predicts alpha and beta transmembrane proteins using deep neural networks. (2022)

901   doi:https://doi.org/10.1101/2022.04.08.487609.

902   37.   Lopez-Balastegui, M. *et al.* Relevance of G protein-coupled receptor (GPCR)

903   dynamics for receptor activation, signalling bias and allosteric modulation. *Br. J.*

904   *Pharmacol.* bph.16495 (2024) doi:10.1111/bph.16495.

905   38.   Zhou, Q. *et al.* Common activation mechanism of class A GPCRs. *eLife* **8**, e50279

906   (2019).

907   39.   Latorraca, N. R., Venkatakrishnan, A. J. & Dror, R. O. GPCR Dynamics: Structures

908   in Motion. *Chem. Rev.* **117**, 139–155 (2017).

40.　Weis, W. I. & Kobilka, B. K. The Molecular Basis of G Protein-Coupled Receptor

Activation. *Annu. Rev. Biochem.* **87**, 897–919 (2018).

41.　Jubb, H. C. *et al.* Arpeggio: A Web Server for Calculating and Visualising

Interatomic Interactions in Protein Structures. *J. Mol. Biol.* **429**, 365–371 (2017).

42.　Shiraishi, A. *et al.* Repertoires of G protein-coupled receptors for Ciona-specific

neuropeptides. *Proc. Natl. Acad. Sci. U. S. A.* **116**, 7847–7856 (2019).

43.　Lin, Z. *et al.* Evolutionary-scale prediction of atomic-level protein structure with a

language model. *Science* **379**, 1123–1130 (2023).

44.　Hu, W. & Ohue, M. SpatialPPIv2: Enhancing protein–protein interaction prediction

through graph neural networks with protein language models. *Comput. Struct. Biotechnol.*

J. **27**, 508–518 (2025).

45.　McKay, F. M. *et al.* In silico analyses of neuropeptide-like protein (NLP) profiles in

parasitic nematodes. *Int. J. Parasitol.* **52**, 77–85 (2022).

46.　Van Bael, S. *et al.* A *Caenorhabditis elegans* Mass Spectrometric Resource for

Neuropeptidomics. *J. Am. Soc. Mass Spectrom.* **29**, 879–889 (2018).

47.　Koziol, U. *et al.* De novo discovery of neuropeptides in the genomes of parasitic

flatworms using a novel comparative approach. *Int. J. Parasitol.* **46**, 709–721 (2016).

48.　Chang, L. & Perez, A. Ranking Peptide Binders by Affinity with AlphaFold**.

Angew. Chem. Int. Ed. **62**, e202213362 (2023).

49.　Roche, D., Gil, D. & Giraldo, J. Mechanistic analysis of the function of agonists and

allosteric modulators: reconciling two-state and operational models. *Br. J. Pharmacol.*

169, 1189–1202 (2013).

50.　Clarke, W. P. & Bond, R. A. The elusive nature of intrinsic efficacy. *Trends*

Pharmacol. Sci. **19**, 270–276 (1998).

51.   Venkatakrishnan, A. J. *et al.* Diverse activation pathways in class A GPCRs converge

near the G-protein-coupling region. *Nature* **536**, 484–487 (2016).

52.   Tehan, B. G., Bortolato, A., Blaney, F. E., Weir, M. P. & Mason, J. S. Unifying

Family A GPCR Theories of Activation. *Pharmacol. Ther.* **143**, 51–60 (2014).

53.   Rasmussen, S. G. F. *et al.* Crystal structure of the β2 adrenergic receptor–Gs protein

complex. *Nature* **477**, 549–555 (2011).

54.   Ballesteros, J. A. *et al.* Activation of the β2-Adrenergic Receptor Involves Disruption

of an Ionic Lock between the Cytoplasmic Ends of Transmembrane Segments 3 and 6. *J.*

Biol. Chem. **276**, 29171–29177 (2001).

55.   Shi, L. *et al.* β2 Adrenergic Receptor Activation. *J. Biol. Chem.* **277**, 40989–40996

(2002).

56.   Venkatakrishnan, A. J. *et al.* Molecular signatures of G-protein-coupled receptors.

Nature **494**, 185–194 (2013).

57.   Liu, F. *et al.* GPCR-BSD: a database of binding sites of human G-protein coupled

receptors under diverse states. *BMC Bioinformatics* **25**, 343 (2024).

58.   Liessmann, F., Künze, G. & Meiler, J. Improving the Modeling of Extracellular

Ligand Binding Pockets in RosettaGPCR for Conformational Selection. *Int. J. Mol. Sci.*

24, 7788 (2023).

59.   Warne, T., Edwards, P. C., Doré, A. S., Leslie, A. G. W. & Tate, C. G. Molecular

basis for high-affinity agonist binding in GPCRs. *Science* **364**, 775–778 (2019).

60.   Filipek, S. Molecular switches in GPCRs. *Curr. Opin. Struct. Biol.* **55**, 114–120

(2019).

61.   Hauser, A. S. *et al.* GPCR activation mechanisms across classes and

macro/microscales. *Nat. Struct. Mol. Biol.* **28**, 879–888 (2021).

62.   Zhang, M. *et al.* G protein-coupled receptors (GPCRs): advances in structures,

mechanisms and drug discovery. *Signal Transduct. Target. Ther.* **9**, 88 (2024).

63.   Nussinov, R. & Tsai, C.-J. Unraveling structural mechanisms of allosteric drug action.

Trends Pharmacol. Sci. **35**, 256–264 (2014).

64.   Nussinov, R., Tsai, C.-J. & Liu, J. Principles of Allosteric Interactions in Cell

Signaling. *J. Am. Chem. Soc.* **136**, 17692–17701 (2014).

65.   Howard, J. & Ruder, S. Universal Language Model Fine-tuning for Text

Classification. Preprint at https://doi.org/10.48550/arXiv.1801.06146 (2018).

66.   Panda, A., Panigrahi, D., Mitra, S., Mittal, S. & Rahimi, S. Transfer Learning Applied

to Computer Vision Problems: Survey on Current Progress, Limitations, and

Opportunities. Preprint at https://doi.org/10.48550/ARXIV.2409.07736 (2024).

67.   Latek, D., Prajapati, K., Dragan, P., Merski, M. & Osial, P. GPCRVS - AI-driven

Decision Support System for GPCR Virtual Screening. *Int. J. Mol. Sci.* **26**, 2160 (2025).

68.   Kostenis, E. Is Gα16 the optimal tool for fishing ligands of orphan G-protein-coupled

receptors? *Trends Pharmacol. Sci.* **22**, 560–564 (2001).

69.   Karelina, M., Noh, J. J. & Dror, R. O. How accurately can one predict drug binding

modes using AlphaFold models? *eLife* **12**, RP89386 (2023).

70.   He, X. *et al.* AlphaFold2 versus experimental structures: evaluation on G protein-

coupled receptors. *Acta Pharmacol. Sin.* **44**, 1–7 (2023).

71.   Goth, C. K., Petäjä-Repo, U. E. & Rosenkilde, M. M. G Protein-Coupled Receptors in

the Sweet Spot: Glycosylation and other Post-translational Modifications. *ACS Pharmacol.*

Transl. Sci. **3**, 237–245 (2020).

72.   Eipper, B. A., Stoffers, D. A. & Mains, R. E. The Biosynthesis of Neuropeptides:

Peptide alpha-Amidation. *Annu. Rev. Neurosci.* **15**, 57–85 (1992).

73. Abramson, J. *et al.* Accurate structure prediction of biomolecular interactions with AlphaFold 3. *Nature* **630**, 493–500 (2024).

74. Chai Discovery *et al.* Chai-1: Decoding the molecular interactions of life. *bioRxiv* 2024.10.10.615955 (2024) doi:10.1101/2024.10.10.615955.

75. Wohlwend, J. *et al.* Boltz-1: Democratizing Biomolecular Interaction Modeling. Preprint at https://doi.org/10.1101/2024.11.19.624167 (2024).

76. Xue, Y. *et al.* State-specific Peptide Design Targeting G Protein-coupled Receptors. Preprint at https://doi.org/10.1101/2024.11.27.625792 (2024).

77. Pacesa, M. *et al.* BindCraft: one-shot design of functional protein binders. Preprint at https://doi.org/10.1101/2024.09.30.615802 (2024).

78. Mirdita, M. *et al.* ColabFold: making protein folding accessible to all. *Nat. Methods* **19**, 679–682 (2022).

79. Wu, F., Jing, X., Luo, X. & Xu, J. Improving protein structure prediction using templates and sequence embedding. *Bioinformatics* **39**, btac723 (2023).

80. Ovchinnikov, S., Kamisetty, H. & Baker, D. Robust and accurate prediction of residue–residue interactions across protein interfaces using evolutionary information. *eLife* **3**, e02030 (2014).

81. Jadon, A. & Patil, A. A Comprehensive Survey of Evaluation Techniques for Recommendation Systems. Preprint at https://doi.org/10.48550/ARXIV.2312.16015 (2023).

82. Pedregosa, F. *et al.* Scikit-learn: Machine learning in Python. *J. Mach. Learn. Res.* **12**, 2825–2830 (2011).

83. Hornak, V. *et al.* Comparison of multiple Amber force fields and development of improved protein backbone parameters. *Proteins Struct. Funct. Bioinforma.* **65**, 712–725 (2006).

84.   Brody, S., Alon, U. & Yahav, E. How Attentive are Graph Attention Networks?

Preprint at https://doi.org/10.48550/ARXIV.2105.14491 (2021).

85.   Agarap, A. F. Deep Learning using Rectified Linear Units (ReLU). Preprint at

https://doi.org/10.48550/ARXIV.1803.08375 (2018).

86.   Loshchilov, I. & Hutter, F. Decoupled Weight Decay Regularization. Preprint at

https://doi.org/10.48550/ARXIV.1711.05101 (2017).

87.   Mao, A., Mohri, M. & Zhong, Y. Cross-Entropy Loss Functions: Theoretical Analysis

and Applications. Preprint at https://doi.org/10.48550/ARXIV.2304.07288 (2023).

1014

1015

1016