`AdDeam`: A Fast and Scalable Tool for Estimating and Clustering Reference-Level Damage Profiles

Louis Kraft[1,*], Thorfinn Sand Korneliussen[2], Peter Wad Sackett[1], and Gabriel Renaud[1,*]

[1]Section for Bioinformatics, Department of Health Technology, Technical University of Denmark, Kongens Lyngby, Denmark

[2]Section for GeoGenetics, Globe Institute, University of Copenhagen, Copenhagen K, Denmark

[*]Correspondence: lokraf@dtu.dk, gabriel.reno@gmail.com

March 20, 2025

Abstract

Motivation

DNA damage patterns, such as increased frequencies of C→T and G→A substitutions at fragment ends, are widely used in ancient DNA studies to assess authenticity and detect contamination. In metagenomic studies, fragments can be mapped against multiple references or *de novo* assembled contigs to identify those likely to be ancient. Generating and comparing damage profiles to identify samples or contigs that are likely to stem from modern contaminants, however, can be both tedious and time-consuming. Although tools exist for estimating damage in single reference genomes and metagenomic datasets, none efficiently cluster damage patterns.

Results

To address this methodological gap, we developed `AdDeam`, a tool that combines rapid damage estimation with clustering for streamlined analyses and easy identification of potential contaminants or outliers. Our tool takes aligned aDNA fragments from various samples or contigs as input, computes damage patterns, clusters them and outputs representative damage profiles per cluster, a probability of each sample of pertaining to a cluster as well as a PCA of the damage patterns for each sample for fast visualisation. We evaluated `AdDeam` on both simulated and empirical datasets. `AdDeam` effectively distinguishes different damage levels, such as UDG-treated samples, sample-specific damages from specimens of different time periods, and can also distinguish between contigs containing modern or ancient fragments, providing a clear framework for aDNA authentication and facilitating large-scale analyses. The software is publicly available at https://github.com/LouisPwr/AdDeam.

1 Keywords

Ancient DNA, Damage Estimation, Ancient Metagenomics, Clustering

2 Introduction

Validating the authenticity of ancient DNA (aDNA) samples is essential to ensure the reliability of scientific conclusions in evolutionary and archaeological studies[1, 2]. The authentication process relies on the characteristic molecular alterations that occur in DNA molecules. Two primary processes lead to the breakdown and chemical alteration of aDNA: hydrolytic mechanisms cause the degradation of DNA molecules thus resulting in shorter fragments[3, 4], and deamination converts cytosines into uracil molecules. During DNA sequencing, these alterations are interpreted as base substitutions[5]. This phenomenon, known as "damage", occurs predominantly at the ends of aDNA fragments. In double-stranded aDNA library preparation [6], this leads to elevated frequencies of C→T substitutions at the 5′ end and G→A substitutions at the 3′ end[5, 7]. In contrast, for single-stranded aDNA library preparation [8, 9], only C→T substitutions at the 5′ end are observable. Base substitutions can be partially or nearly completely removed through wet-lab protocols using uracil-DNA glycosylase (UDG) treatment. Full UDG treatment excises uracil residues from aDNA fragments, effectively eliminating damage signatures. While this improves sequence accuracy, it also results in shorter fragment lengths[10]. Partial UDG treatment leaves some uracil residues intact, preserving a limited number of damage sites for authentication[11]. As a result, full UDG treatment produces fragments with no observable damage patterns, whereas partial UDG treatment retains minimal damage signatures.

Damage patterns are used to determine whether the DNA being extracted from fossils or ancient environments is indeed ancient in origin[12, 5, 3]. Modern contaminants can contribute DNA and therefore, their DNA fragments will not display such damage patterns[13, 14, 15, 16, 17, 18, 19]. In addition, the levels of damage are informative about the conditions in which DNA was preserved[20]. When several samples of eukaryotic species like humans are sequenced, researchers routinely screen multiple extractions and determine which carry damage patterns and at which level to determine authenticity[21, 22, 23]. This involves aligning the aDNA fragments to a single reference from the eukaryotic species in question. In the case of metagenomic studies involving *de novo* assembly, damage patterns are used to determine which contigs are likely to be ancient by aligning the aDNA fragments back to the assembly[24, 25, 26, 27, 28]. A contig where the aligned fragments do not display damage patterns is more likely to be a modern contaminant[29]. Furthermore, aDNA fragments from microbes can be aligned to multiple reference genomes and damage patterns are used to determine which species are likely to be present and *bona fine* aDNA[30, 31, 32, 33].

Regardless of which, researchers in aDNA are faced with the task of inspecting large numbers of damage pattern plots to identify outliers.

Several bioinformatic tools have been developed to generate damage profiles from alignment files. Traditional tools such as `mapDamage`[34, 35], `PMDtools`[36], and `DamageProfiler` [37] focus primarily on analysing damage patterns for single reference species. The tool `aRchaic` [38] clusters damage patterns to estimate a "grade of membership" for all aligned reads in k damage profiles relative to a single reference, such as the human genome. It can distinguish between samples with no damage, full-UDG, half-UDG, and full damage. However, it assumes a single known reference (e.g., Homo sapiens) and is not suited for metagenomic datasets, where distinguishing damage patterns across multiple references is essential. Although no longer actively maintained, `aRchaic` remains unique in its approach to clustering reads by damage profiles.

More recently, tools tailored for metagenomic datasets have been developed. `pyDamage`[29] uses likelihood ratio models for contig-level analysis, while `metaDamage`[39] facilitates damage estimation through BLAST-based alignment against external databases. `metaDMG`[40] enables comprehensive assessments of damage at both the global metagenome and taxonomic levels.

Pipelines such as `aMeta` [41] and `HOPS` [42] provide automated and reproducible workflows to identify and authenticate ancient microbial species and pathogens. `aMeta` uses `PMDtools` [36] internally, while `HOPS` employs the `MALT` [43, 44] suite, which combines a BLAST-like alignment strategy with ancient damage estimation.

While researchers involved in eukaryotic projects can use traditional tools like `mapDamage` [35, 34] or `DamageProfiler` [37], they are still faced with the daunting task of screening the damage plots of several extractions. Despite this, software tools aimed at metagenomics are not applicable to such projects. On the other hand, researchers involved in ancient metagenomics, then need to screen assembled contigs or potential reference genomes of microbes that could be present. Such researchers do not have a tool to rapidly cluster damage patterns and visualize them. A tool that would allow researchers to quickly visualize damage patterns across multiple samples would save the aDNA community a lot of time.

To address these needs, we present `AdDeam`, a versatile tool designed for rapid damage estimation and clustering of aDNA profiles. `AdDeam` combines two key functions: (1) efficiently generating damage profiles from BAM files and (2) applying a clustering algorithm to group similar damage profiles into k clusters while providing visualizations of both individual profiles and cluster representatives. It is designed to handle large collections of BAM files as input from any reference type (e.g., bacterial, human, or other genomes) as well as BAM files containing alignments to multiple references, such as contigs or grouped reference genomes. It outputs the degree of assignment of the samples or contigs to each cluster and reports the damage profile for each cluster.

Unlike existing tools that either report damage profiles [34, 35, 36, 37, 39, 41, 42, 40], classify sequences as ancient or modern [29], or assume a single known reference [38], AdDeam offers versatility in handling BAM files representing either a single reference or multiple references for metagenomic analysis. While aRchaic [38] similarly clusters fragments based on their damage patterns, it does so only for a single predefined reference, without distinguishing between multiple references within a dataset. This limitation makes it unsuitable for metagenomic applications. Moreover, the tool is no longer maintained and, despite extensive attempts, could not be installed on our servers, further restricting its usability.

AdDeam processes single or multiple BAM files in two modes. First, a classic mode for analysing multiple BAM files from different samples aligned to the same reference genome. This mode is useful for determining if certain human extractions have damage in the fragments aligned to the human reference. Second, a meta mode for fragments aligned to multiple contigs of a metagenomic assembly contained within a single BAM file. This mode is aimed at researchers who wish to determine which contigs are potentially modern in origin.

By using a Gaussian Mixture Model (GMM) algorithm, AdDeam clusters similar damage profiles, offering both quantitative assessments and intuitive visualizations of damage profile similarities. This makes AdDeam particularly suited for organizing aDNA studies involving multiple samples or datasets with sequences from numerous species, where alignment files often span many references.

We demonstrated AdDeam's ability to accurately cluster damage profiles using simulated data and tested its performance on empirical datasets. For the latter, AdDeam was applied to profile metagenomic samples against a set of reference taxa and to cluster contigs derived from *de novo* assembly based on their damage patterns. AdDeam offers researchers an efficient and standardized approach to contextualize and authenticate aDNA damage patterns in large-scale studies or across multiple projects, saving time and facilitating downstream analyses.

3   Materials and Methods

In this manuscript, we distinguish between fragments and reads as follows: fragments represent the sequences of degraded aDNA molecules. In paired-end sequencing, each fragment is sequenced from both ends, producing two corresponding reads. Reads are individual observations of the same fragment. However, by trimming adapters and merging paired-end reads, one can reconstruct the most likely sequence representing the original fragment [45]. Consequently, we consistently refer to aDNA fragments when discussing trimmed and merged sequences, such as those used for alignment to a reference.

AdDeam consists of two subsequent stages: 1) generating damage profiles from BAM files either

for each sample in classic mode or per contig in meta mode 2) clustering these based on their similarity into k clusters, where k is user-defined. By default, clustering is performed for $k = 2, 3,$ and 4. Please note that step 2 is performed independently of the mode chosen be it classic or meta. Finally, `AdDeam` outputs a comprehensive report in PDF format as well as tab-separated files for convenient downstream analysis. The workflow of `AdDeam` is illustrated in Figure 1.

Figure 1: Overview of the two modes of the `AdDeam` workflow: classic mode and meta mode. In classic mode (left), multiple BAM files, each representing different samples mapped to a reference genome (e.g., human), are processed with `bam2prof`, a lightweight C++ program included with `AdDeam`, to generate individual damage profiles. These profiles are then clustered using the GMM algorithm, assigning each sample a probability of belonging to each of the k (in this example $k = 2$) clusters. In meta mode (right), one (or more) BAM file containing the original aDNA fragments aligned to a reference containing the assembled contigs is processed. The `bam2prof` program generates damage profiles for each reference within the BAM file, and GMM clustering (shown for $k = 3$) assigns probabilities for each contig's cluster membership to identify contigs that could potentially be modern in origin. We provide the inferred damage profiles for the different clusters.

3.1 Stage 1: Damage Profile Generation

We employ `bam2prof`, a tool written in C++, originally developed by Gabriel Renaud and Thorfinn Korneliussen (https://github.com/grenaud/bam2prof), to generate damage profiles from BAM files containing aDNA alignments. `bam2prof` iterates over all alignments and calculates the ratio

of observed C→T and G→A mismatches per position. Building upon the original implementation, we have extended the functionality with several key features:

Classic mode

Generates a single damage profile per BAM file. This function may be used to analyse a set of BAM files that are aligned to either a single reference genome, regardless of whether the reference genome is of bacterial or eukaryotic origin (i.e., human genome with multiple chromosomes), as illustrated in Figure 1, CLASSIC MODE panel.

Meta mode

Produces individual damage profiles for each reference sequence within a BAM file, enabling analysis of damage patterns with each record (be it a contig, scaffold or chromosome) in a reference. This mode is particularly useful for samples where aDNA fragments have been aligned to a database containing multiple reference genomes, such as prokaryotic genomes in metagenomic studies. The result is one damage profile per record in the reference. Additionally, this mode is especially interesting for metagenome assemblies, allowing fragments used for assembly to be aligned back to the resulting contigs, producing a damage profile for each contig (see Figure 1, META MODE panel).

Fast profile generation from large BAM files

As metagenomic datasets can contain high volumes of short-read DNA sequences, the resulting BAM files can become large and time-intensive to analyse. To accelerate damage profile generation for large datasets, we introduced an iterative convergence check. This approach allows users to specify an interval size (n) and a precision threshold (d) to balance accuracy and computational efficiency. The algorithm processes each reference iteratively, evaluating substitution frequencies after every n fragments. If the frequencies stabilize within the specified precision threshold d—meaning they have not changed by more than d—further iterations are skipped. Both parameters are user-adjustable, with the default behaviour ensuring that all alignments are fully processed. Our experience showed that substitution frequencies typically stabilize after processing 10 million fragments.

Python Wrapper for Parallel Processing of Multiple Input Files

To facilitate efficient high-throughput analysis, we developed a Python wrapper around `bam2prof` that enables the parallel processing of multiple BAM files across multiple threads. This wrapper can be invoked with the command:

```
172     addeam-bam2prof.py -i inputBams.txt -o outputDir
```

173 where `inputBams.txt` is a file listing the input BAM files, and `outputDir` specifies the directory

174 for outputting the generated damage profiles. All parameters available for the compiled `bam2prof`

175 program are also supported by the wrapper script and passed on accordingly.

3.2   Stage 2: Clustering of Damage Profiles into k clusters

The damage profiles generated by `bam2prof` for a single sample are stored as two tab-delimited

text files: one representing the substitution rates at the 5' end of the DNA fragments and the other

for the 3' end. In these files, rows correspond to the first nucleotide positions from each end (5' or

3'), and columns capture substitution rates for all 12 possible mismatches at each position.

We prepare the profiles for clustering by combining the damage rates. By default, `bam2prof`

considers only 5 positions away from the 5' and 3' end which get converted into a feature vector

of length p and therefore, by default, $p = 10$. Specifically, the first five elements of this vector

capture the C→T substitution frequencies at positions 1 through 5 from the 5' end, whereas the

last five elements represent G→A substitution frequencies at positions 5 through 1 from the 3'

end. This approach focuses on substitution patterns that are informative for identifying aDNA,

condensing each profile into a single line vector where one line represents a sample (or contig in

meta mode). To improve separation during clustering, all values in the vector are transformed

using the logarithm of the substitution frequencies. The logarithm scale is useful as a jump from

0% damage to 15% should be more noticeable than a 15% to 30% jump in damage rates. The

logarithm space makes smaller values, thus likely to be a contaminant, more salient.

By concatenating the vectors from all profiles, we construct an $m \times p$ matrix X, where each row

represents one of m samples and each column corresponds to one of the ten informative positions p

(five for C→T and five for G→A). This matrix serves as input for clustering the damage patterns

using a GMM algorithm implemented using `scikit-learn`[46]. Unlike deterministic clustering

algorithms such as k-means, which assign each sample to a single cluster, the GMM algorithm

assigns probabilities to each sample of belonging to every cluster, reflecting the model's uncertainty

in classification. This probabilistic approach allows samples to have partial membership across

clusters, capturing cases where certain samples do not clearly belong to a single cluster. These

ambiguous samples can then be further analysed downstream. However, the number of clusters,

k, must be specified by the user in advance, as it is an inherent parameter of the GMM algorithm.

The GMM algorithm is a probabilistic model that assumes data are generated from a mixture

of k Gaussian distributions. Each cluster is represented as a Gaussian distribution with its own

mean and covariance structure, which together define the shape and orientation of the cluster.

In our application, the number of Gaussian components, k, is specified by the user, with default values of $k = 2, 3$, and 4. For each chosen k, the GMM estimates the parameters of each Gaussian distribution to best fit the observed data, which in this case are the damage profiles.

The likelihood of observing a sample $\vec{x}$ under the GMM is defined as:

$$P(\vec{x}) = \sum_{j=1}^{k} \pi_j \mathcal{N}(\vec{x}|\boldsymbol{\mu}_j, \boldsymbol{\Sigma}_j) \tag{1}$$

where π_j are the mixing coefficients, $\boldsymbol{\mu}_j$ are the mean vectors, and $\boldsymbol{\Sigma}_j$ are the covariance matrices of the Gaussian components. Here, $\mathcal{N}(\vec{x}|\boldsymbol{\mu}_j, \boldsymbol{\Sigma}_j)$ represents the probability density function of the multivariate Gaussian distribution for component j, parametrised by its mean vector $\boldsymbol{\mu}_j$ and covariance matrix $\boldsymbol{\Sigma}_j$. Each Gaussian component represents a potential cluster in the data, with its own probability distribution. Instead of using $\boldsymbol{\mu}_j$ directly as the damage profile, we compute a weighted representative pattern for each cluster by averaging the damage patterns of all samples, weighted by their cluster probabilities. This allows researchers to scan k damage profiles rather than hundreds or thousands.

In `AdDeam`, we initialize the means systematically:

- For $k = 2$, we set $\boldsymbol{\mu}_1$ to the minimum values and $\boldsymbol{\mu}_2$ to the arithmetic mean of minimum and maximum values in linear space.

- For $k = 3$, we add a third mean, $\boldsymbol{\mu}_3$, set to the maximum values.

- For $k > 3$, additional means are distributed evenly between minimum and maximum values using linear interpolation.

During the development of `AdDeam`, we explored different covariance structures for the GMM algorithm and found that a spherical covariance structure worked best. This structure assumes that each cluster's covariance matrix is isotropic, meaning that clusters have the same spread in all directions, forming spherical shapes in multi-dimensional space. An advantage of this approach is its computational efficiency, as it requires estimating fewer parameters compared to more flexible structures like a full covariance matrix. The model is optimized using the Expectation-Maximization algorithm, which iteratively maximizes the likelihood of the observed data under the model, assigning each sample a probability-based cluster membership.

When working with low-coverage metagenomic data, damage profiles can be less reliable if generated from references with minimally aligned fragments[39]. Hence, the Python script that runs the clustering first pre-filters the damage profiles based on the number of assigned fragments, ensuring that only reliable profiles are included in the analysis. Erroneous mappings or low-read evidence

can reduce the accuracy of damage profiles, potentially leading to incorrect clustering outcomes. To address this, we included an option to exclude profiles generated from references with fewer than a specified threshold of aligned fragments (by default, 1000) from the clustering process.

3.3 Output and Visualisation

After clustering the damage profiles, each sample is assigned probabilities indicating its membership in each of the k clusters. However, some samples may exhibit nearly uniform probability distributions across multiple clusters, making their classification ambiguous.

To aid interpretation and identify potential outliers, we include a visualization step that projects the clustered damage profiles into a lower-dimensional space using Principal Component Analysis (PCA). Analogous to clustering in logarithmic space, we also perform the PCA on the logarithm of the substitution frequencies. The two most significant principal components are plotted, with each sample colour-coded according to its highest GMM cluster assignment. This provides an intuitive way to assess cluster separation and detect samples with uncertain assignments.

Additionally, we generate probability plots illustrating each sample's cluster membership probabilities and compute representative damage profiles for each identified cluster as weighted averages based on GMM assignment probabilities.

For downstream analysis, all results, including sample identifiers, mapped read counts, cluster assignment probabilities, and Euclidean distances to GMM cluster centers in PCA space, are exported as tab-separated files.

3.4 Generation of Simulated Data

To properly assess the clustering performance, we generated simulated sequencing reads where the ground truth—the true damage level of each sample—was known. Logically, all samples with the same simulated damage profile should be assigned to the same cluster. Moreover, the inferred damage profiles of the cluster should be similar to the original damage profile used for generating the samples of this cluster.

In empirical samples, damage levels vary between references, even among those that are expected to cluster together relative to other observable damage levels (e.g., one species may display 30% damage at the first position while another shows 27% or 35%). To simulate this empirical heterogeneity, we created three pools of 1,000 similar damage profiles corresponding to no damage, mid damage [47], and high damage [48]. Using 290 bacterial reference genomes, we simulated reads for each genome at all three damage levels by randomly sampling from the respective pools, resulting

in a total of 870 datasets.

We simulated sequencing reads with `gargammel`[49] at an average coverage of 4X per genome. The resulting reads were then trimmed and merged using `leeHom`[50] with the `--ancientdna` parameter before being mapped to their respective reference genomes using `bwa aln`[51] with the parameters -n 0.01 -o 2 -l 1024 [52]. After alignment, we processed the BAM files with `samtools`[53] to sort them and add MD flags, which annotate mismatches relative to the reference.

We then processed these alignments using `AdDeam` in classic mode to generate damage profiles, resulting in 870 BAM files (290 per damage level). To better approximate empirical scenarios, we employed a non-uniform distribution of samples in our clustering analysis, using 290 samples with no damage, 145 samples with mid damage, and 29 samples with high damage. The damage profiles used for simulation and those estimated from the simulated data are shown in the Supplementary Material, Section "Simulated Datasets: Additional Information", Figure S1.

We focus on this simulation to demonstrate the feasibility of our clustering approach. As there are no existing tools that purport to cluster damage parameters in such as way, direct benchmarking is difficult. Most available methods either generate damage profiles or classify the probability that, for example, a contig is ancient [34, 35, 36, 37, 39, 41, 42, 40, 29], but they do not cluster damage profiles which is one of the core functionality of `AdDeam`. While `aRchaic` [38] could also perform clustering, it does so under the assumption of a single predefined reference, without distinguishing between multiple references within a BAM file. As a result, it cannot capture damage variation across multiple references, which is crucial in metagenomic studies. Additionally, `aRchaic` is no longer maintained, and despite extensive efforts, we were unable to install it successfully.

4   Results

4.1   Clustering of Simulated Damage Profiles

The damage patterns used for simulating ancient reads served as the ground truth, exhibiting distinct substitution rate intervals for no damage, mid-damage, and high damage (see details in section 3.4). However, the estimated damage profiles generated by `bam2prof` inevitably deviate from this ground truth due to alignment biases. These biases arise because not all fragments are perfectly mapped to the reference, leading to overlapping damage rate intervals after estimation. This effect is further detailed in Supplementary Material, Section "Simulated Datasets: Additional Information", and Figure S1.

In order to evaluate `AdDeam`'s ability to correctly cluster similar damage patterns, we used simulated datasets in which the ground truth damage levels were known to us but not to the algorithm.

After running `AdDeam`'s clustering module, we compared its output with the ground truth. From a simulated dataset of 890 samples, we selected a subset comprising 290 samples with no damage, 145 samples with mid damage, and 29 samples with high damage to reflect the empirical heterogeneity of damage patterns. In total, 464 samples were analysed.

Figure **2**, upper panel "Ground Truth of Simulation" illustrates the distribution of samples across the three damage levels that were simulated and subsequently used as input for `AdDeam`.

Figure 2: Clustering of simulated damage profiles. Upper panel: Ground truth distribution of samples across the three simulated damage levels used as input for `AdDeam`. The damage plots above the bars illustrate the range of substitution rates that individual samples within each damage level carry. Lower panel left: GMM algorithm clustering results for $k = 2$ and $k = 3$. For $k = 2$, no-damage profiles form one cluster, while mid- and high-damage profiles are combined into a second cluster. For $k = 3$, all profiles are correctly assigned to their respective categories. Lower panel right: PCA of damage profiles for $k = 3$. The plot reveals three distinct clusters, with colour-coding derived from the GMM algorithm.

On the left side of Figure **2**, "Output 1: Gaussian Mixture Model Cluster Assignment," the automatically generated clustering results for $k = 2$ and $k = 3$ are shown.

For $k = 2$, AdDeam grouped all no-damage profiles into a single cluster, while mid- and high-damage profiles were combined into a second cluster. Due to the use of the logarithm scale, this binary classification effectively distinguished between the presence and absence of damage patterns. Representative damage profiles for each cluster are also provided. The representative profile for the no-damage cluster closely aligns with the expected near-zero substitution frequencies. The representative profile for the combined mid- and high-damage cluster is more similar to the mid-damage profile. This results from the cluster being dominated by 145 mid-damage profiles, compared to only 29 high-damage profiles, making the representative profile weighted accordingly.

For $k = 3$, AdDeam successfully assigned all profiles to their correct categories. The representative profiles for the three clusters were distinct and aligned with the expected patterns of no-damage, mid-damage, and high-damage.

On the right side of Figure 2, "Output 2: Principal Component Analysis of Damage Profiles in Regard to Output 1" presents a PCA plot of the clustering results for $k = 3$. The plot reveals three distinct clusters, visually apparent from the data point distributions and supported by colour coding from the GMM algorithm. No-damage, mid-damage, and high-damage profiles each form separate clusters. The uniform colour within each group indicates perfect consistency in the classification since each cluster only contains samples of the same simulated ground truth of damage. This colour-coded PCA plot is automatically generated by AdDeam and provided to the user.

4.2 Empirical Analysis: Mapping Ancient Metagenomic Fragments to Core Oral Microbiome Genera

In order to evaluate AdDeam's ability to cluster damage patterns in empirical datasets, we analysed fragments from 49 ancient metagenome datasets originally presented by Fellows Yates *et al.*[30]. These datasets were selected because key characteristics such as sample age and UDG treatment were known, providing metrics to validate AdDeam's clustering performance. The samples, which were extracted from dental calculus, were obtained from various species, including howler monkeys, gorillas, chimpanzees, Neanderthals, ancient modern humans, and present-day modern humans.

We mapped the 49 samples against the reference genomes of four bacterial species: *Tannerella forsythia*, *Porphyromonas gingivalis*, *Treponema denticola*, and *Fretibacterium fastidiosum*. These species were chosen because they were described as "core genera" in the study by Fellows Yates *et al.*[30], which defines a core genus as one found in at least two-thirds of the populations within a given host genus. These bacteria are highly prevalent across all host genera in the source study, including *Alouatta* (Howler monkey), *Gorilla*, *Pan troglodytes* (Chimpanzee), and *Homo Sapiens*. In modern humans, they are strongly associated with periodontal disease [30], and analysing

³³⁹ their ancient genomes provides valuable insights into the evolution of the oral microbiome and its
³⁴⁰ relationship to host health.

³⁴¹ Therefore, the damage profiles for these four core genera species are of particular interest: their
³⁴² presence can be confidently inferred if ancient damage patterns are observed, and the effectiveness of
³⁴³ UDG treatment can be assessed, ensuring the removal of base substitutions crucial for downstream
³⁴⁴ analyses.

³⁴⁵ The BAM files containing the alignments of the 49 samples were analysed using `AdDeam` in "classic
³⁴⁶ mode", which means that a single damage profile was reported for the four "core genera". Figure
³⁴⁷ **3** shows the clustering results for $k = 4$, and Table 1 presents the metadata associated with
³⁴⁸ the samples, including cluster assignment, sample source, sample age, and UDG treatment. We
³⁴⁹ saw that $k = 4$ provided a clear separation of the different samples. The left panel displays the
³⁵⁰ probability assignment of each sample to a cluster. The uniform colour of each bar indicates that
³⁵¹ all samples were assigned to a cluster with probabilities close to 100%. The right panel shows the
³⁵² representative damage patterns for each cluster.

Figure 3: Clustering results for 49 samples aligned against the genomes of four bacterial species that represent the "core genera" of oral microbiomes. A single damage profile was obtained per sample using the alignments to these four genomes which are usually present in oral microbiome. Left: Probability assignments to each cluster ($k = 4$). Right: Representative damage profiles for each cluster. `AdDeam` was run in "classic mode", generating a single damage profile for all four bacterial species.

Cluster Assigned	Sample codes	Sample Source	Period	UDG Treated
1	DJA (1x)	Gorilla	20th century	yes
1	EBO (1x)	Gorilla	20th century	yes
1	OME (1x)	Howler Monkey	20th-21st century	no
1	OME (3x)	Howler Monkey	20th-21st century	yes
1	OAK (2x)	Modern human	Later Stone Age	yes
1	TAF (1x)	Modern human	Later Stone Age	yes
1	ECO (2x)	Modern human	Mesolithic	yes
1	FUM (1x)	Neanderthal	Middle Palaeolithic	yes
1	PES (1x)	Neanderthal	Middle Palaeolithic	yes
1	EMN (1x)	Modern human	Upper Palaeolithic	yes
2	DJA (5x)	Chimpanzee	20th century	no
2	EBO (6x)	Chimpanzee	20th century	no
2	OME (3x)	Howler Monkey	20th-21st century	no
3	OAK (3x)	Modern human	Later Stone Age	no
3	TAF (4x)	Modern human	Later Stone Age	no
3	FUM (3x)	Neanderthal	Middle Palaeolithic	no
3	PES (1x)	Neanderthal	Middle Palaeolithic	no
3	EMN (1x)	Modern human	Upper Palaeolithic	no
3	ECO (1x)	Modern human	Mesolithic	no
4	OAK (1x)	Modern human	Later Stone Age	no
4	TAF (2x)	Modern human	Later Stone Age	no
4	ECO (5x)	Modern human	Mesolithic	no

Table 1: Overview of sample information and cluster assignments. The table includes sample codes, sources, time periods, and whether the samples were UDG-treated.

Clusters 1 and 2 exhibit representative damage profiles close to zero (cluster 1) and with minimal damage (maximum 5%) for cluster 2. In contrast, the representative profiles for clusters 3 and 4 display more pronounced damage patterns. Cluster 3 shows damage around 30% at the first position, while cluster 4 shows high damage with over 40% at the first position.

To provide additional context, Table 1 presents an overview of the samples assigned to each cluster. The table includes the cluster assignment, sample codes from Fellows Yates *et al.* [30], sample sources, the period they originate from, and whether the samples were UDG-treated or not.

The table reveals that cluster 1 primarily contains all UDG-treated samples from all time periods, with a single exception. This exception is a sample from a howler monkey (*Alouatta*) dated to the 20th-21st century. The damage profile of this outlier shows exceptionally low substitution frequencies, consistent with the UDG-treated samples. This explains its assignment to cluster 1. The output files of AdDeam including the damage profiles of all samples are accessible at https://github.com/LouisPwr/AdDeamAnalysis.

Cluster 2 consists exclusively of non-UDG-treated samples from relatively modern time periods (20th-21st century). In contrast, clusters 3 and 4 only include samples from older periods, specifically the Mesolithic, Upper Paleolithic, Middle Paleolithic, and Later Stone Age.

4.3 Empirical Analysis: Clustering Damage Profiles from Assembled Contigs

As described in the Introduction `AdDeam` can generate damage profiles for individual records (i.e contigs, scaffolds or chromosomes) in a reference genome using `bam2prof`. This feature enables an interesting use case: clustering damage profiles derived from multiple reference sequences, such as those obtained through *de novo* assembly of ancient metagenomes. The fragments can be realigned to the contigs and determine which are potential contaminants.

To explore this, we analysed a co-assembly strategy by combining one modern sample (Sample ID VLC) and two ancient samples (Sample IDs TAF and EMN) all from Fellows Yates *et al.* [30]. The combined dataset was assembled using `MEGAHIT`[54] and the resulting contigs were filtered to have lengths of at least 10,000 bp. The original fragments which were used for assembly were then mapped to these contigs, and the alignment files were analysed using `AdDeam`. The ENA accession numbers included in the FASTQ headers of each sample enabled us to trace which fragments originated from each sample. Therefore, we could determine for each cluster the fraction of sample-specific fragments that aligned to the contigs. This helped us inferring the composition of the contigs, showing whether they were mostly assembled from modern or ancient fragments.

The results of this analysis are shown in Figure 4. The left panel displays a PCA plot, where contigs are clustered into three groups ($k = 3$) based on their damage profiles. To validate whether the contigs clustered together match the composition of the reads from which they were assembled, we counted the fragments aligning to contigs in each cluster and calculated the fraction coming from each sample (VLC for modern, TAF for Later Stone Age, and EMN for Upper Paleolithic). The right panel of Figure 4 shows that contigs in cluster 1 have mapped almost exclusively modern fragments ($\geq 99\%$), contigs in cluster 3 have mapped almost exclusively ancient fragments, and contigs in cluster 2 represent a mix of both. These results align with the representative damage patterns shown.

The PCA plot in Figure 4 also shows that some contigs between cluster 1 and 2 are not clearly assigned to a single cluster by the GMM. These contigs are represented by lighter gradient colours, representing lower probabilities of cluster membership. This uncertainty in cluster assignment is consistent with their intermediate positions in the PCA plot, where these data points visually appear between cluster 1 and 2.

4.4 Runtime

We measured the runtime of `AdDeam` for each processing step. For a BAM file containing 1,770 references (contigs) and a total of 48,312,572 mapped fragments, the `bam2prof` module generated

Figure 4: Classifying contigs based on their damage profiles from co-assembled fragments of modern and ancient sources. Three samples from Fellows Yates *et al.* [30] were merged and assembled using `MEGAHIT`[54]. Fragments were mapped to contigs that are over 10,000 bp in length, followed by analysis with `AdDeam` to generate damage reports. The results demonstrate the ability to differentiate between modern and ancient contigs. Clustering analysis (k=3) was applied to the VLC (21st century), TAF (Later Stone Age), and EMN (Upper Palaeolithic) datasets. The PCA plot is based on damage profiles from contigs over 10,000 bp, with clusters coloured according to the clustering results. The legend next to each cluster shows the representative damage profile (in order) and the proportion of sample-specific fragments aligning to the contigs in each cluster (Modern: VLC, Ancient (LSA): TAF, Ancient (UP): TAF).

all 1,770 damage profiles in under 43 seconds. The clustering module completed clustering for $k = 2, 3$, and 4 in 1 minutes and 17 seconds, while running in quiet mode (i.e., with reduced visual output, beneficial for larger datasets) reduced the execution time to 25 seconds. The metrics were measured on a Intel(R) Xeon(R) Platinum 8462Y+ server with a "Processor Base Frequency" of 2.10 GHz and a "Max Turbo Frequency" of 4.10 GHz. The maximum memory usage was less than 400 Mb. Both damage profile generation and clustering utilized a single thread only. The `addeam-bam2prof.py` wrapper offers a `-hpc` option that redirects commands to a file, which can then be executed on HPC clusters that often use queueing systems.

5   Discussion

We developed `AdDeam`, a versatile and user-friendly tool for estimating DNA damage and clustering damage profiles. Designed to streamline the analysis and comparison of damage patterns, `AdDeam` fills a methodological gap when working with large datasets, such as those containing numerous samples or alignment files with multiple references.

`AdDeam` consists of two Python scripts: `addeam-bam2prof.py` and `addeam-cluster.py`. The first script is a wrapper to allow parallelization of `bam2prof`, a small single-threaded program written in C++ for rapid and efficient damage estimation. The latter script, `addeam-cluster.py`, applies

a Python-based GMM algorithm to group samples/references based on their damage profiles. The GMM assigns probabilities for each reference to belong to one of k clusters, where k can be user-defined. `AdDeam` generates comprehensive visualizations, including cluster membership probabilities, representative damage profiles for each cluster, and a PCA plot.

The GMM algorithm employed in `AdDeam` does not inherently determine the optimal number of clusters (k) for a given dataset. Instead, the algorithm requires the user to specify a predefined number of clusters. While the theoretical number of clusters in a dataset can vary widely, `AdDeam` addresses this limitation by running the clustering algorithm for multiple values of k (e.g., 2, 3, and 4) by default and reporting the results for each. Given the efficiency of the GMM implementation, running the clustering for several values of k is computationally feasible. This approach provides flexibility in interpretation: for instance, $k = 2$ is often sufficient to distinguish between damaged and undamaged samples, while higher values of k (e.g., $k = 3$ or $k = 4$) can reveal additional layers of variation in damage profiles, if present. Since `AdDeam` is split into two commands—`addeam-bam2prof.py` for generating damage profiles and `addeam-cluster.py` for clustering—users can easily experiment with different values of k without rerunning `addeam-bam2prof.py`.

We demonstrated `AdDeam`'s ability to accurately cluster similar damage profiles using simulated and empirical datasets. For the latter, we applied `AdDeam` to aDNA authentication in 47 metagenomic samples, effectively distinguishing UDG-treated from non-UDG-treated samples. Additionally, we showed that `AdDeam` can classify assembled contigs by damage levels, thereby identifying contigs with similar damage patterns.

Ancient metagenomic studies can greatly benefit from *de novo* assembly for taxonomic and functional annotation, but ultra-high and heterogeneous damage patterns can hinder this process. The novel damage-aware assembler `CarpeDeam` [55] addresses this issue but currently applies a single global damage pattern, which may not capture the damage variability in ancient datasets. `AdDeam` can facilitate assembly by clustering reference-level damage profiles from BAM files and subsequently enabling the extraction of fragments with similar damage patterns to improve assembly accuracy.

Overall, `AdDeam` significantly enhances the workflow of aDNA studies by streamlining the time-consuming process of sample authentication and organization. Damage authentication of numerous samples or metagenomic datasets is often labour-intensive, typically requiring the generation of multiple damage plots and their manual interpretation. As publicly accessible aDNA datasets continue to grow, including million-year-old specimens with highly variable damage patterns [23, 56], the need for efficient and versatile screening tools becomes ever more critical.

Unlike tools such as `pydamage` [29], `metadamage` [39] or `mapDamage` [35, 34], which estimate probabilities for whether a reference is actually damaged, `AdDeam` focuses on efficiently reporting damage

profiles as directly interpreted from BAM files, enabling large-scale analysis of aDNA damage patterns while maintaining computational efficiency. Future updates may incorporate aforementioned probabilistic damage assessments, particularly by further examining low-coverage alignments. However, at present, `AdDeam` allows users to control the robustness of the analysis by specifying a minimum number of aligned fragments per reference, ensuring flexibility in filtering.

6 Declarations

Data Availability

The analysed datasets in this publication are accessible on Zenodo under the DOI: `10.5281/zenodo.15052427`.

Code Availability

The software is publicly available at `https://github.com/LouisPwr/AdDeam`. All analysis scripts are available at `https://github.com/LouisPwr/AdDeamAnalysis`.

Software Versions

bwa==0.7.17-r1188

samtools=1.13

MEGAHIT=v1.2.9

numpy==2.1.3

pandas==2.2.3

matplotlib==3.9.2

scikit-learn==1.5.3

PyPDF2>=2.0.0

scipy==1.14.1

Competing Interests

The authors declare no competing interests.

Acknowledgements

We would like to acknowledge that this research and the PhD scholarships of Louis Kraft were funded by the Novo Nordisk Data Science Investigator grant number NNF20OC0062491. We thank the Technical University of Denmark's Department of Health Technology for additional funding. L.K. acknowledges the use of OpenAI/ChatGPT and Anthropic/Claude to proofread the manuscript.

Author Contributions

G.R. conceived the project. L.K. and G.R. designed and developed the method. G.R. and T.S.K. developed the C++ version of `bam2prof`. L.K. modified `bam2prof`. L.K. implemented the method and tested it. L.K. conducted all tests.

Funding

Funding for this research was provided by a Novo Nordisk Data Science Investigator grant number NNF20OC0062491 (GR). This funding source provided the salaries for LK. Additional funding for computational resources was provided by the Department for Health Technology at DTU. The funders had no role in study design, data collection and analysis, decision to publish, or preparation of the manuscript.

References

[1] R. E. Green, A. W. Briggs, J. Krause, K. Prüfer, H. A. Burbano, M. Siebauer, M. Lachmann, and S. Pääbo, "The Neandertal genome and ancient DNA authenticity," The EMBO Journal, vol. 28, p. 2494–2502, Aug. 2009.

[2] C. Der Sarkissian, I. M. Velsko, A. K. Fotakis, Å. J. Vågene, A. Hübner, and J. A. Fellows Yates, "Ancient Metagenomic Studies: Considerations for the Wider Scientific Community," mSystems, vol. 6, 12 2021.

[3] M. Hofreiter, D. Serre, H. N. Poinar, M. Kuch, and S. Pääbo, "Ancient DNA," Nature Reviews Genetics, vol. 2, p. 353–359, May 2001.

[4] S. Pääbo, "Ancient DNA: extraction, characterization, molecular cloning, and enzymatic amplification.," Proceedings of the National Academy of Sciences, vol. 86, p. 1939–1943, Mar. 1989.

[5] A. W. Briggs, U. Stenzel, P. L. F. Johnson, R. E. Green, J. Kelso, K. Prüfer, M. Meyer, J. Krause, M. T. Ronan, M. Lachmann, and S. Pääbo, "Patterns of damage in genomic DNA sequences from a Neandertal," Proceedings of the National Academy of Sciences, vol. 104, p. 14616–14621, 9 2007.

[6] A. W. Briggs and P. Heyn, Preparation of Next-Generation Sequencing Libraries from Damaged DNA, p. 143–154. Humana Press, Dec. 2011.

[7] J. Dabney, M. Meyer, and S. Paabo, "Ancient DNA Damage," Cold Spring Harbor Perspectives in Biology, vol. 5, p. a012567–a012567, 5 2013.

[8] M.-T. Gansauge, T. Gerber, I. Glocke, P. Korlević, L. Lippik, S. Nagel, L. M. Riehl, A. Schmidt, and M. Meyer, "Single-stranded DNA library preparation from highly degraded DNA usingT4DNA ligase," Nucleic Acids Research, p. gkx033, Jan. 2017.

[9] J. D. Kapp, R. E. Green, and B. Shapiro, "A Fast and Efficient Single-stranded Genomic Library Preparation Method Optimized for Ancient DNA," Journal of Heredity, vol. 112, p. 241–249, Mar. 2021.

[10] A. W. Briggs, U. Stenzel, M. Meyer, J. Krause, M. Kircher, and S. Pääbo, "Removal of deaminated cytosines and detection of in vivo methylation in ancient DNA," Nucleic Acids Research, vol. 38, p. e87–e87, Dec. 2009.

[11] N. Rohland, E. Harney, S. Mallick, S. Nordenfelt, and D. Reich, "Partial uracil–DNA–glycosylase treatment for screening of ancient DNA," Philosophical Transactions of the Royal Society B: Biological Sciences, vol. 370, p. 20130624, Jan. 2015.

[12] M. Hofreiter, V. Jaenicke, D. Serre, A. von Haeseler, and S. Pääbo, "DNA sequences from multiple amplifications reveal artifacts induced by cytosine deamination in ancient DNA," Nucleic Acids Research, vol. 29, pp. 4793–4799, Dec. 2001.

[13] M. Richards, B. Sykes, and R. Hedges, "Authenticating DNA Extracted From Ancient Skeletal Remains," Journal of Archaeological Science, vol. 22, p. 291–299, Mar. 1995.

[14] M. L. Sampietro, M. T. P. Gilbert, O. Lao, D. Caramelli, M. Lari, J. Bertranpetit, and C. Lalueza-Fox, "Tracking down Human Contamination in Ancient Human Teeth," Molecular Biology and Evolution, vol. 23, p. 1801–1807, June 2006.

[15] J. Krause, A. W. Briggs, M. Kircher, T. Maricic, N. Zwyns, A. Derevianko, and S. Pääbo, "A Complete mtDNA Genome of an Early Modern Human from Kostenki, Russia," Current Biology, vol. 20, p. 231–236, Feb. 2010.

[16] O. Handt, M. Krings, R. H. Ward, and S. Pääbo, "The retrieval of ancient human DNA sequences," American Journal of Human Genetics, vol. 59, pp. 368–376, Aug. 1996.

[17] C. Warinner, A. Herbig, A. Mann, J. A. Fellows Yates, C. L. Weiß, H. A. Burbano, L. Orlando, and J. Krause, "A robust framework for microbial archaeology," Annual Review of Genomics and Human Genetics, vol. 18, pp. 321–356, Aug. 2017.

[18] F. M. Key, C. Posth, J. Krause, A. Herbig, and K. I. Bos, "Mining metagenomic data sets for ancient DNA: Recommended protocols for authentication," Trends in Genetics, vol. 33, pp. 508–520, Aug. 2017.

[19] G. Renaud, V. Slon, A. T. Duggan, and J. Kelso, "Schmutzi: estimation of contamination and endogenous mitochondrial consensus calling for ancient DNA," Genome Biology, vol. 16, Oct. 2015.

[20] S. Sawyer, J. Krause, K. Guschanski, V. Savolainen, and S. Pääbo, "Temporal Patterns of Nucleotide Misincorporations and DNA Fragmentation in Ancient DNA," PLOS ONE, vol. 7, p. e34131, Mar. 2012.

[21] D. Pandey, M. Harris, N. R. Garud, and V. M. Narasimhan, "Leveraging ancient DNA to uncover signals of natural selection in Europe lost due to admixture or drift," Nature Communications, vol. 15, Nov. 2024.

[22] M. E. Allentoft, M. Sikora, A. Fischer, K.-G. Sjögren, A. Ingason, R. Macleod, A. Rosengren, B. Schulz Paulsson, M. L. S. Jørkov, M. Novosolov, J. Stenderup, T. D. Price, M. Fischer Mortensen, A. B. Nielsen, M. Ulfeldt Hede, L. Sørensen, P. O. Nielsen, P. Rasmussen, T. Z. T. Jensen, A. Refoyo-Martínez, E. K. Irving-Pease, W. Barrie, A. Pearson, B. Sousa da

Mota, F. Demeter, R. A. Henriksen, T. Vimala, H. McColl, A. Vaughn, L. Vinner, G. Renaud, A. Stern, N. N. Johannsen, A. D. Ramsøe, A. J. Schork, A. Ruter, A. B. Gotfredsen, B. Henning Nielsen, E. Brinch Petersen, E. Kannegaard, J. Hansen, K. Buck Pedersen, L. Pedersen, L. Klassen, M. Meldgaard, M. Johansen, O. C. Uldum, P. Lotz, P. Lysdahl, P. Bangsgaard, P. V. Petersen, R. Maring, R. Iversen, S. Wåhlin, S. Anker Sørensen, S. H. Andersen, T. Jørgensen, N. Lynnerup, D. J. Lawson, S. Rasmussen, T. S. Korneliussen, K. H. Kjær, R. Durbin, R. Nielsen, O. Delaneau, T. Werge, K. Kristiansen, and E. Willerslev, "100 ancient genomes show repeated population turnovers in Neolithic Denmark," Nature, vol. 625, p. 329–337, Jan. 2024.

[23] K. H. Kjær, M. Winther Pedersen, B. De Sanctis, B. De Cahsan, T. S. Korneliussen, C. S. Michelsen, K. K. Sand, S. Jelavić, A. H. Ruter, A. M. A. Schmidt, K. K. Kjeldsen, A. S. Tesakov, I. Snowball, J. C. Gosse, I. G. Alsos, Y. Wang, C. Dockter, M. Rasmussen, M. E. Jørgensen, B. Skadhauge, A. Prohaska, J. Å. Kristensen, M. Bjerager, M. E. Allentoft, E. Coissac, A. Rouillard, A. Simakova, A. Fernandez-Guerra, C. Bowler, M. Macias-Fauria, L. Vinner, J. J. Welch, A. J. Hidy, M. Sikora, M. J. Collins, R. Durbin, N. K. Larsen, and E. Willerslev, "A 2-million-year-old ecosystem in Greenland uncovered by environmental DNA," Nature, vol. 612, pp. 283–291, 12 2022.

[24] H. P. Hodgins, P. Chen, B. Lobb, X. Wei, B. J. M. Tremblay, M. J. Mansfield, V. C. Y. Lee, P.-G. Lee, J. Coffin, A. T. Duggan, A. E. Dolphin, G. Renaud, M. Dong, and A. C. Doxey, "Ancient Clostridium DNA and variants of tetanus neurotoxins associated with human archaeological remains," Nature Communications, vol. 14, Sept. 2023.

[25] P. Rozwalak, J. Barylski, Y. Wijesekara, B. E. Dutilh, and A. Zielezinski, "Ultraconserved bacteriophage genome sequence identified in 1300-year-old human palaeofaeces," Nature Communications, vol. 15, 1 2024.

[26] M. Klapper, A. Hübner, A. Ibrahim, I. Wasmuth, M. Borry, V. G. Haensch, S. Zhang, W. K. Al-Jammal, H. Suma, J. A. Fellows Yates, J. Frangenberg, I. M. Velsko, S. Chowdhury, R. Herbst, E. V. Bratovanov, H.-M. Dahse, T. Horch, C. Hertweck, M. R. González Morales, L. G. Straus, I. Vilotijevic, C. Warinner, and P. Stallforth, "Natural products from reconstructed bacterial genomes of the Middle and Upper Paleolithic," Science, vol. 380, p. 619–624, 5 2023.

[27] J. C. Brealey, H. G. Leitão, T. van der Valk, W. Xu, K. Bougiouri, L. Dalén, and K. Guschanski, "Dental Calculus as a Tool to Study the Evolution of the Mammalian Oral Microbiome," Molecular Biology and Evolution, vol. 37, p. 3003–3022, 5 2020.

[28] M. C. Wibowo, Z. Yang, M. Borry, A. Hübner, K. D. Huang, B. T. Tierney, S. Zimmerman, F. Barajas-Olmos, C. Contreras-Cubas, H. García-Ortiz, A. Martínez-Hernández, J. M. Luber,

P. Kirstahler, T. Blohm, F. E. Smiley, R. Arnold, S. A. Ballal, S. J. Pamp, J. Russ, F. Maixner, O. Rota-Stabelli, N. Segata, K. Reinhard, L. Orozco, C. Warinner, M. Snow, S. LeBlanc, and A. D. Kostic, "Reconstruction of ancient microbial genomes from the human gut," Nature, vol. 594, p. 234–239, 5 2021.

[29] M. Borry, A. Hübner, A. B. Rohrlach, and C. Warinner, "PyDamage: automated ancient damage identification and estimation for contigs in ancient DNA de novo assembly," PeerJ, vol. 9, p. e11845, July 2021.

[30] J. A. Fellows Yates, I. M. Velsko, F. Aron, C. Posth, C. A. Hofman, R. M. Austin, C. E. Parker, A. E. Mann, K. Nägele, K. W. Arthur, J. W. Arthur, C. C. Bauer, I. Crevecoeur, C. Cupillard, M. C. Curtis, L. Dalén, M. Díaz-Zorita Bonilla, J. C. Díez Fernández-Lomana, D. G. Drucker, E. Escribano Escrivá, M. Francken, V. E. Gibbon, M. R. González Morales, A. Grande Mateu, K. Harvati, A. G. Henry, L. Humphrey, M. Menéndez, D. Mihailović, M. Peresani, S. Rodríguez Moroder, M. Roksandic, H. Rougier, S. Sázelová, J. T. Stock, L. G. Straus, J. Svoboda, B. Teßmann, M. J. Walker, R. C. Power, C. M. Lewis, K. Sankara-narayanan, K. Guschanski, R. W. Wrangham, F. E. Dewhirst, D. C. Salazar-García, J. Krause, A. Herbig, and C. Warinner, "The evolution and changing ecology of the African hominid oral microbiome," Proceedings of the National Academy of Sciences, vol. 118, 5 2021.

[31] A. Fernandez-Guerra, G. Borrel, T. O. Delmont, B. Elberling, A. M. Eren, S. Gribaldo, A. Jochheim, R. A. Henriksen, K.-U. Hinrichs, T. S. Korneliussen, M. Krupovic, N. K. Larsen, R. Laso-Pérez, M. W. Pedersen, V. K. Pedersen, K. K. Sand, M. Sikora, M. Steinegger, I. Veseli, L. Wörmer, L. Zhao, M. Žure, K. Kjær, and E. Willerslev, "A 2-million-year-old microbial and viral communities from the Kap København Formation in North Greenland," Cold Spring Harbor Laboratory, 6 2023.

[32] D. Bozzi, S. Neuenschwander, D. I. Cruz Dávalos, B. Sousa da Mota, H. Schroeder, J. V. Moreno-Mayar, M. E. Allentoft, and A.-S. Malaspinas, "Towards predicting the geographical origin of ancient samples with metagenomic data," Scientific Reports, vol. 14, Sept. 2024.

[33] M. A. Spyrou, K. I. Bos, A. Herbig, and J. Krause, "Ancient pathogen genomics as an emerging tool for infectious disease research," Nature Reviews Genetics, vol. 20, p. 323–340, 4 2019.

[34] A. Ginolhac, M. Rasmussen, M. T. P. Gilbert, E. Willerslev, and L. Orlando, "mapDamage: testing for damage patterns in ancient DNA sequences," Bioinformatics, vol. 27, p. 2153–2155, June 2011.

[35] H. J
'onsson, A. Ginolhac, M. Schubert, P. L. F. Johnson, and L. Orlando, "mapDamage2.0: fast

approximate Bayesian estimates of ancient DNA damage parameters," <u>Bioinformatics</u>, vol. 29, p. 1682–1684, Apr. 2013.

[36] P. Skoglund, B. H. Northoff, M. V. Shunkov, A. P. Derevianko, S. Pääbo, J. Krause, and M. Jakobsson, "Separating endogenous ancient DNA from modern day contamination in a Siberian Neandertal," <u>Proceedings of the National Academy of Sciences</u>, vol. 111, p. 2229–2234, Jan. 2014.

[37] J. Neukamm, A. Peltzer, and K. Nieselt, "DamageProfiler: fast damage pattern calculation for ancient DNA," <u>Bioinformatics</u>, vol. 37, p. 3652–3653, Apr. 2021.

[38] H. Al-Asadi, K. K. Dey, J. Novembre, and M. Stephens, "Inference and visualization of DNA damage patterns using a grade of membership model," <u>Bioinformatics</u>, vol. 35, p. 1292–1298, 9 2018.

[39] R. Everett and B. Cribdon, "MetaDamage tool: Examining post-mortem damage in sedaDNA on a metagenomic scale," <u>Frontiers in Ecology and Evolution</u>, vol. 10, 1 2023.

[40] C. Michelsen, M. W. Pedersen, A. Fernandez-Guerra, L. Zhao, T. C. Petersen, and T. S. Korneliussen, "metaDMG – A Fast and Accurate Ancient DNA Damage Toolkit for Metagenomic Data," <u>Cold Spring Harbor Laboratory</u>, 12 2022.

[41] Z. Pochon, N. Bergfeldt, E. Kırdök, M. Vicente, T. Naidoo, T. van der Valk, N. E. Altınışık, M. Krzewińska, L. Dalén, A. Götherström, C. Mirabello, P. Unneberg, and N. Oskolkov, "aMeta: an accurate and memory-efficient ancient metagenomic profiling workflow," <u>Genome Biology</u>, vol. 24, Oct. 2023.

[42] R. Hübler, F. M. Key, C. Warinner, K. I. Bos, J. Krause, and A. Herbig, "HOPS: automated detection and authentication of pathogen DNA in archaeological remains," <u>Genome Biology</u>, vol. 20, Dec. 2019.

[43] A. Herbig, F. Maixner, K. I. Bos, A. Zink, J. Krause, and D. H. Huson, "MALT: Fast alignment and analysis of metagenomic DNA sequence data applied to the Tyrolean Iceman," <u>Cold Spring Harbor Laboratory</u>, Apr. 2016.

[44] Å. J. Vågene, A. Herbig, M. G. Campana, N. M. Robles García, C. Warinner, S. Sabin, M. A. Spyrou, A. Andrades Valtueña, D. Huson, N. Tuross, K. I. Bos, and J. Krause, "Salmonella enterica genomes from victims of a major sixteenth-century epidemic in Mexico," <u>Nature Ecology & Evolution</u>, vol. 2, p. 520–528, Jan. 2018.

[45] A. Lien, L. P. Legori, L. Kraft, P. W. Sackett, and G. Renaud, "Benchmarking software tools for trimming adapters and merging next-generation sequencing data for ancient DNA," <u>Frontiers in Bioinformatics</u>, vol. 3, Dec. 2023.

[46] F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay, "Scikit-learn: Machine Learning in Python," Journal of Machine Learning Research, vol. 12, pp. 2825–2830, 2011.

[47] I. Olalde, M. E. Allentoft, F. Sánchez-Quinto, G. Santpere, C. W. K. Chiang, M. DeGiorgio, J. Prado-Martinez, J. A. Rodríguez, S. Rasmussen, J. Quilez, O. Ramírez, U. M. Marigorta, M. Fernández-Callejo, M. E. Prada, J. M. V. Encinas, R. Nielsen, M. G. Netea, J. Novembre, R. A. Sturm, P. Sabeti, T. Marquès-Bonet, A. Navarro, E. Willerslev, and C. Lalueza-Fox, "Derived immune and ancestral pigmentation alleles in a 7, 000-year-old Mesolithic European," Nature, vol. 507, p. 225–228, Jan. 2014.

[48] T. Günther, H. Malmström, E. M. Svensson, A. Omrak, F. Sánchez-Quinto, G. M. Kılınç, M. Krzewińska, G. Eriksson, M. Fraser, H. Edlund, A. R. Munters, A. Coutinho, L. G. Simões, M. Vicente, A. Sjölander, B. Jansen Sellevold, R. Jørgensen, P. Claes, M. D. Shriver, C. Valdiosera, M. G. Netea, J. Apel, K. Lidén, B. Skar, J. Storå, A. Götherström, and M. Jakobsson, "Population genomics of Mesolithic Scandinavia: Investigating early postglacial migration routes and high-latitude adaptation," PLOS Biology, vol. 16, p. e2003703, Jan. 2018.

[49] G. Renaud, K. Hanghøj, E. Willerslev, and L. Orlando, "gargammel: a sequence simulator for ancient DNA," Bioinformatics, vol. 33, p. 577–579, 11 2016.

[50] G. Renaud, U. Stenzel, and J. Kelso, "leeHom: adaptor trimming and merging for Illumina sequencing reads," Nucleic Acids Research, vol. 42, p. e141–e141, 8 2014.

[51] H. Li and R. Durbin, "Fast and accurate short read alignment with Burrows–Wheeler transform," Bioinformatics, vol. 25, p. 1754–1760, May 2009.

[52] A. Oliva, R. Tobler, A. Cooper, B. Llamas, and Y. Souilmi, "Systematic benchmark of ancient DNA read mapping," Briefings in Bioinformatics, vol. 22, Apr. 2021.

[53] H. Li, B. Handsaker, A. Wysoker, T. Fennell, J. Ruan, N. Homer, G. Marth, G. Abecasis, and R. Durbin, "The Sequence Alignment/Map format and SAMtools," Bioinformatics, vol. 25, p. 2078–2079, 6 2009.

[54] D. Li, C.-M. Liu, R. Luo, K. Sadakane, and T.-W. Lam, "MEGAHIT: an ultra-fast single-node solution for large and complex metagenomics assembly via succinct de Bruijn graph," Bioinformatics, vol. 31, p. 1674–1676, 1 2015.

[55] L. Kraft, J. Söding, M. Steinegger, A. Jochheim, P. W. Sackett, A. Fernandez-Guerra, and G. Renaud, "CarpeDeam: ADe NovoMetagenome Assembler for Heavily Damaged Ancient Datasets," Cold Spring Harbor Laboratory, Aug. 2024.

[56] T. van der Valk, P. Pečnerová, D. Díez-del Molino, A. Bergström, J. Oppenheimer, S. Hartmann, G. Xenikoudakis, J. A. Thomas, M. Dehasque, E. Sağlıcan, F. R. Fidan, I. Barnes, S. Liu, M. Somel, P. D. Heintzman, P. Nikolskiy, B. Shapiro, P. Skoglund, M. Hofreiter, A. M. Lister, A. Götherström, and L. Dalén, "Million-year-old DNA sheds light on the genomic history of mammoths," Nature, vol. 591, p. 265–269, Feb. 2021.