Cellular porosity in dentin exhibits complex network characteristics with spatio-temporal fluctuations

L. Chatelain[1], N. Tremblay[2], E. Vennat[3], E. Dursun[4,5], D. Rousseau[6]* & A. Gourrier[1]*

[1] Univ. Grenoble Alpes, CNRS, LIPhy, Grenoble F-38000, France

[2] CNRS, Univ. Grenoble Alpes, Grenoble-INP, Gipsa-lab, Grenoble, France

[3] Université Paris-Saclay, CentraleSupélec, ENS Paris-Saclay, CNRS, LMPS - Laboratoire de Mécanique Paris-Saclay, 91190, Gif-sur-Yvette, France

[4] Université Paris Cité, U1333 Santé Orale, INSERM, Dental School, Montrouge, France

[5] AP-HP, Service de médecine bucco-dentaire, Hôpitaux Universitaires Henri Mondor, Créteil, France

[6] Laboratoire Angevin de Recherche en Ingénierie des Systèmes (LARIS), UMR INRAe-IRHS, Université d'Angers, 62 Avenue Notre Dame du Lac, 49000 Angers, France

* corresponding authors

Abstract

According to the current hydrodynamic theory, teeth sensitivity is mediated by odontoblast cell processes which can be activated by fluid flow in the pericellular space of bulk dentin. To better understand the possible spatial extent of such phenomena, we investigated the topology and connectivity of dentinal porosity of a healthy human tooth. Using confocal fluorescence microscopy, we modeled the porosity as a spatial graph with edges representing dentinal tubules or lateral branches and nodes defining their connections. A large fraction of porosity channels in crown dentin was found to be interconnected, with 47 % of nodes linked in a single component over a millimetric distance from the dentin-enamel junction (DEJ). However, significant differences in network topology were also observed. A sharp transition in connectivity from 83 % to 43 % occurred at 300 μm from the DEJ, which corresponds to an early stage of tooth formation. This was reflected in all graph metrics investigated, in particular the network resilience which dropped by a factor 2. To test the robustness of our observations, an in-depth analysis of potential remaining biases of the graph extraction was conducted. Most graph metrics considered were found to be within a 10 % precision range from a manually annotated ground truth. However, path metrics, which characterize transport properties, proved very sensitive to network defects. Residual errors were classified in 4 topological classes and their relative importance estimated from statistical and physical graph attack simulations in a broad experimental range. Our modeling thus provides a practical framework to estimate the interpretability of calculated graph metrics for a given experimental microscopy setup and image processing pipeline. Overall, this study shows that dentin porosity exhibits typical characteristics of a complex network and quantitatively emphasize the importance of the smallest lateral branches. Our results could be used to model fluid flow more accurately in order to better understand mechanosensing by odontoblasts in dentin.

Keywords: teeth sensitivity, odontoblast, tubules, lateral branches, mechanosensing, biological network, spatial graph, graph topology, connectivity

Statement of significance

Dental pain is believed to be triggered by external stimuli affecting cells located in the central pulp cavity and which extend throughout dentin, the bulk of the tooth. Pain sensing therefore strongly depends on the spatial distribution and connectivity of those cells and surrounding porosity. Previous studies have mainly focused on the first aspect. Using graph theory, we show that dentinal porosity constitutes a densely connected network which is very far from a widespread view of a parallel array of sensors. Our work also provides a computational framework to estimate the precision and interpretability of network analysis in dentin. We thus show that the mechanosensing response to stimulated zones under localized mechanical/temperature stresses could be more complex than currently envisaged.

CRediT's

L. Chatelain: Investigation, Data Curation, Formal Analysis, Software, Visualization, Writing – original draft.

N. Tremblay: Supervision, Software, Validation, Writing – review & editing.

E. Vennat: Resources, Validation, Writing – review & editing.

E. Dursun: Resources, Validation, Writing – review & editing.

D. Rousseau: Conceptualization, Methodology, Supervision, Writing – review & editing.

A. Gourrier: Project administration, Funding acquisition, Conceptualization, Methodology, Resources, Supervision, Software, Writing – review & editing.

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

I. Introduction

Tooth sensitivity is thought to be primarily mediated by odontoblast cells which form a dense sensory complex with unmyelinated nerve fibers in the central pulp cavity [1, 2]. Since odontoblasts are deeply buried inside the pulp cavity of the tooth, their mechanosensing capacity mostly depends on their ability to probe their spatial environment within the bulk formed by dentin mineralized tissue. To this end, odontoblasts extend a single long cytoplasmic process through dentin, from the pulp to the interface with the enamel capping layer apparent in the buccal cavity [3]. This cellular process has a diameter in the micron range but can extend radially over distances larger than 1 mm in human adult molars [4]. It is also known to regularly branch into thinner (0.1-0.5 µm), shorter and more tortuous secondary processes that either connect to neighboring cells, or stop at short distances [3]. Since these secondary processes often interconnect [5, 6], cell-cell communication or activation by dentinal fluid flow could be possible at regular intervals along the main process. According to the current mechanotransduction theory, mechanical pressure applied on the tooth surface induce pericellular dentinal fluid displacements, mechanically activating odontoblasts which send a biochemical response that ultimately trigger electrical pulses in neighboring nerves, thus conveying information to the central nervous system [7-9]. The overall topology and connectivity of odontoblasts and their processes therefore appear to be key determinants of the mechanosensing capacity of teeth.

Given the apparent importance of odontoblastic lateral branching and its possible role in pain signaling, recognized from an early stage, Kaye and Herold [5], Holland [10] and Mjör and Norhal [11] (amongst others) performed detailed histological and statistical characterizations of those secondary processes. However, despite the importance of their contributions, a global understanding of intercellular communication or dentinal fluid flow on a large scale yet remains to be established. With this in mind, we recently revisited this question focusing on 3D imaging of dentin cellular porosity close to the dentin-enamel junction (DEJ) in crown dentin [12]. Using

confocal fluorescence microscopy, we further refined the branching classification proposed by

Mjör and Norhal and revealed that secondary processes interconnecting odontoblasts might

be much more frequent than previously thought, even in regions far away from the DEJ.

Depending on the spatial extent of secondary processes, odontoblasts could thus form a much

more complex network than described so far, which motivates further study of its topology.

Topology analysis based on graph theory forms the basis of complex networks studies, an

active area of research with applications in many scientific fields [13]. In biomedical research,

various complex networks have been identified and investigated, in particular vascular

networks in multiple organs (retina [14, 15], liver [16, 17], kidney [18, 19] and lung [20] amongst

others), pulmonary airways [21, 22] and bone porosity networks [23]. But the field to which

graph theory contributed the most is undoubtedly neuroscience. Connectomics, the analysis

of structure-function relationships, currently forms a cornerstone of brain functional studies

[24]. It is worthwhile pointing out that all these applications relate to transport pathways within

organs and could therefore be related to much broader transport network studies [25]. The

success of graphs essentially resides in their apparent mathematical simplicity: a collection of

nodes connected by edges, and their flexibility: nodes and edges can represent very diverse

objects and their relationships. Depending on the imaging or analytical modality used to

measure brain function, nodes can represent different regions, tissues and even cells [26].

Modeling brain function by taking the ensemble of cells of the brain and their interconnection

is currently considered as the ultimate goal of connectomics [27]. The complexity of such tasks

therefore stems from the gigantic number of nodes and edges to be considered which can

lead to extremely challenging mathematics and numerical/computational dilemmas.

Inspired by connectomic brain analysis, a series of seminal studies were performed on the

bone osteocyte lacuno-canalicular network (LCN) by Weinkamer et al. [23]. Bone can be

considered as the closest system to dentin because the tissue essentially consists of the same

structural building block, mineralized collagen fibrils [28-30]. More importantly, osteocytes and

odontoblasts both appear to play a key mechanosensory role [31, 32], although, arguably,

osteocytes have a stronger impact on the tissue structure and thus biomechanical adaptation,

due to their implication in bone remodeling. Using graph representations with nodes as

osteocytes and edges as canaliculi, Weinkamer et al. laid the ground for advanced numerical

3D fluid flow simulations in the LCN of full osteons sections, thus providing important biological

insights that couldn't otherwise be obtained experimentally [33, 34] and also highlighted small-

world properties [35], i.e. nodes in the network are in close proximity despite their large amount

and limited direct links. Despite numerous experimental evidence of tubules interconnections

by branches in dentin and its apparent proximity to bone in this respect [36], graph theory

hasn't been used yet to study odontoblast or dentinal porosity connectivity. Such analysis

could, however, provide valuable information concerning intra- or extra-cellular

communication between odontoblasts. Overall, the mechanosensing mechanisms of teeth

could therefore be more complex than currently considered in the literature.

One possible explanation for this gap in our current knowledge of dentin function may reside

in the fact that secondary processes are difficult to image with sufficient resolution over large

volumes compatible with connectivity analysis. Transmission electron microscopy (TEM) [37,

38] and, to a lesser extent, confocal laser scanning microscopy (CLSM) [4, 39, 40] provided

in-depth insight into cellular components structure, albeit on a relatively local scale. To gain a

more global perspective of cellular organization, scanning electron microscopy (SEM) was

also heavily used to image dentinal porosity, thus providing indirect information of

odontoblastic process connectivity [11, 41, 42]. However, SEM studies were performed on 2D

surfaces such that 3D interpretation can only be achieved qualitatively through complex slicing

of dentin samples in different orientations. Nevertheless, SEM provided sufficient spatial

resolution to image the finest odontoblastic branches which hasn't been demonstrated using

X-ray tomography methods so far. As a result, the spatial distribution and connectivity of

primary and secondary odontoblast processes are still poorly quantified. Analyzing the

dentinal porosity using fluorescence confocal microscopy in 3D was recently shown to provide

an indirect but accurate 3D visualization of the odontoblast topology [12]. This procedure forms

the basis of virtually all connectomic studies performed in the bone field to this date [33-35,

43].Such that all network topology analysis of cells in mineralized tissues published so far rely

on the precision of the visualization using confocal fluorescence microscopy and of the graph

extraction procedure. Because of the sensitivity of graph analysis to experimental microscopy

conditions and image processing biases, a rigorous assessment of the experimental

conditions seems mandatory, but was rarely performed, if ever.

The objective of the present study is to perform a first quantification of odontoblast connectivity

in the vicinity of the DEJ, considering dentin porosity as a network. We first describe an image

processing pipeline to extract a graph description of dentinal porosity that can be used for 3D

connectivity analysis. In a second step, we examine different classes of graph metrics that

best describe the cellular porosity network. We then provide an in-depth estimation of potential

residual errors arising from the proposed pipeline and from intrinsic CSLM limitations, thus

emphasizing the importance of fine odontoblastic branches that physically bridge tubules

during tissue formation. Finally, we analyze the spatial fluctuation of the network in relation to

well-known histological odontoblast characteristics.

168 II. Materials and methods

169 II.1. Data acquisition

170 II.1.1. Sample preparation

Figure 1: **Methods summary.** a) Transmission light microscopy of the sample section imaged with confocal laser scanning microscopy (CLSM) in the area indicated by a red rectangle (width: 200 µm, height: 900 µm). E: Enamel, D: Dentin, P: Pulp cavity. Scale bar: 2 mm. b) 3D rendering of the resulting image stack. c-f) Image processing pipeline of the image stack: c) original image, d) vesselness filtering result, e) porosity segmentation with its skeleton in red, f) cleaned graph. Displayed images are a maximum intensity projection (MIP) of 51.2 x 51.2 x 20 µm volumes. Scale bar: 10 µm.

This study was performed using a healthy human third molar from a 23 years old woman obtained on 19/02/2018 with informed oral consent of the patient, in accordance with the ethical guidelines laid down by French law (agreement IRB 00006477 and n° DC-2009-927, Cellule Bioéthique DGRI/A5). Immediately after extraction, the tooth was cleaned from food impurities with an ultrasound bath and disinfected in a Chloramine-T (0.5% - 5g/L) solution. The tooth was then fixed in a 70 % ethanol for 48 hours and subsequently embedded in an athermal curing epoxy resin (EPOFIX, Struers) to facilitate handling and cutting. Thin slices of 300 µm in thickness were cut in the mesio-distal plane (Fig.1a) using a diamond saw with water lubrication (Struers E0D15 mounted on a Presi Mecatome T210). The sections were cleaned with water from cutting residues and reduced to 200 µm in thickness by polishing

191   (Presi Minitech 233) with SiC paper up to P4000 grade (EU grade, Struers). Finally, the sample

192   was stained for 72 h in a glycerol solution with 0.02 wt% Rhodamine B at room temperature

193   and sealed in the same solution between two glass cover slides.

II.1.2. Confocal fluorescence imaging

Confocal image stacks were acquired in the period 26/02/2018 to 09/03/2018 with a Leica

TCS SP8 microscope, using a 40x/1.3NA oil immersion lens. A wavelength of 561 nm (LED

laser DPSS 561) was used to excite Rhodamine B fluorescence which was collected in a

range of 567-636 nm with a hybrid detector. The acquisitions were performed on the polished

surface of crown dentin up to 900 μm from the DEJ in the direction of the pulp (cf Fig.1a-b).

The scanning was performed using 26-52 μW laser power with a linear increase in depth to

compensate for scattering and absorption with a pixel dwell time of 300 ns and a line average

of 3 acquisitions. The scan consisted of a mosaic of 5 overlapping stacks of $205.5{\times}205.5~\mu m^2$

images with a pixel size of 100 nm, collected over 20.65 μm in depth with 350 nm sampling,

forming a $934.4{\times}205.5{\times}20.65~\mu m^3$ volume. The resulting experimental dataset was thus

$2055{\times}9344{\times}59$ voxels in shape with $100{\times}100{\times}350~nm^3$ voxel size.

II.2. Processing pipeline: from 3D image stacks to graphs

Three different graphs are considered in this study and described in more details in the

following sections:

• The generated graph: coarse graph automatically generated from the raw image stack

following the image processing pipeline.

• The cleaned graph: semi-automatically generated. This is a "cleaned" version of the

generated graph after systematically correcting generic errors.

• The ground truth (GT) graph: generated by manual annotation of the data to correct

remaining errors.

II.2.1. Porosity segmentation

All calculations were performed on a computer equipped with an Intel Xeon 1270 CPU (3.40 GHz 16) and 64 Gb of RAM. Data processing was done using custom Python code (based on the numpy [44], scipy [45] or scikit-image [46] libraries unless specified otherwise). The raw mosaic volume was first cropped to remove the enamel region and the intensity level of the stack of images was adjusted by histogram equalization, to account for the decrease of intensity in depth due to scattering and absorption. The dataset was then resliced in Z (in-depth direction) by a factor of 3.5 (with bicubic interpolation) to obtain isotropic voxels of $100\times100\times100$ nm^3. The final dataset size was thus $8196\times2055\times206$ voxels.

Since all dentinal porosity appears in the form of tubes with varying diameter, a morphological multiscale 3D vesselness filter was applied to enhance vessel structures in the image [47]. The filter is based on the eigenvalues of the Hessian of the image that can help in assessing the structure shapes locally. Tubular features are identified as locations with two strong eigenvalues (cross-section plane) and a small one (along the vessel axis). The implementation from Jerman [48] was used with parameters σ (set of scales for the hessian) in the range 1-5 pixels in steps of 0.05 (corresponding to 2.36-11.78 pixels FWHM, or 0.236-1.178 µm) and τ = 0.5. The filtered volumetric porosity was then segmented using hysteresis thresholding with thresholds determined using a 3-class multi-Otsu method. Remaining noise was removed from the final binary porosity mask through a sequence of morphological opening (3 voxel diameter ball footprint), removal of isolated voxels clusters (either black or white, of size less than 256 voxels with 26-connectivity) and final median filtering (3 voxels side length cubic window).

II.2.2. Topological graph extraction

The skeleton of the smoothed 3D binary mask was obtained with a topology preserving thinning process (Lee's method [49]) to reduce the vessels down to their centerlines. A

multigraph in the format defined in the NetworkX library [50] was extracted from the skeleton via the sknw Python library [51]. The generated graphs have nodes at branching and end points and edges representing the vessels. Multiple node and edge attributes were also created in the process. Each node and edge first have an attribute corresponding to the list of associated voxels positions to retain the skeleton information in the graph. Then, the node center of gravity (defined by 1 to 3 skeleton voxels) was added as an attribute. For the edges, a "weight" attribute was also created, corresponding to the arc length of the edge (sum of the pairwise distances in "pts").

II.2.3. Graph cleaning

In a first step, the generated graph was filtered to remove undesired artifacts and topological errors. The algorithm developed for this cleaning is detailed in S1 Appendix Fig.S1a. The terms "artifacts" correspond here to elements in the graph that don't correspond to our biological knowledge of dentin porosity. This includes multi-edges (different edges associated to the same pair of nodes), self-loops (edges whose ends are linked to the same node) and nodes of degree equal to 2 (nodes with two edges). The second step consisted in removing "errors" defined as sets of nodes and edges that do not correspond to real porosity vessels and branching points. The removals of both spurious edges and edge bridges are considered, two types of errors described in more detail below (III.1.). The cleaning of spurious edges concerns the removal of terminal edges (edges with at least one node of degree 1) based on a threshold over the "bulge size" parameter defined in [52]. The cleaning of a specific kind of edge, defined as "edge bridges" in III.3.1, is based on local orientation of the edge and its neighbors (see S1 Appendix Fig.S1b for more details). The graph was thus cleaned from "artifacts" and "errors" through several iterations until no changes were detected.

II.2.4. Ground truth creation

The graph obtained after the automatic cleaning step was further corrected via a manual

annotation in two sub-volumes of interest (ROI) of 1000×1000×206 voxels region. The

manually corrected graphs are considered in the following as "ground truth graphs". The

annotation was done with FIJI [53] in the form of markers. 3D image representations where

the graph was superposed to the original image stack were used to visually compare the

resulting graph with the acquired 3D volume. Annotation markers were then exported and

used in Python scripts to apply the modifications. Three types of graph corrections were

considered: deletion (node or edge), creation of a missing straight edge, creation of a node

and creation of an edge with a broken line path.

II.2.5. Graph representation

275   The software Gephi [54] was used to display the graphs. The Fig.4.b,e representation was

276   obtained using the node positions, and the one for Fig.4.c,f is based on the use of multiple

277   predefined layouts (OpenOrd, Force Atlas and Noverlap).

II.3. Network analysis

II.3.1. Graph metrics

280   Because graphs representing cellular and porosity networks in bone and teeth are essentially

281   spatial graphs, we use the corresponding terminology for graph metrics proposed by

282   Barthélemy et al. [55], a reference review on the topic. A limited subset of the metrics

283   described by the authors was selected to account for different categories of information.

Graph descriptors

285   N: Total number of nodes

286   E: Total number of edges

287   $\langle k \rangle$: Mean degree: average number of node neighbors

288   γ: The gamma index, $\gamma = \frac{2E}{N(N-1)}$ \qquad (1)

The number of nodes **N** and of edges **E** are the most fundamental network properties. The mean node degree **<k>** and gamma index **ɣ** (Eq. 1) respectively represent the average number of neighbors a node possesses and the probability of having an edge between two randomly selected nodes. Altogether, these metrics provide a basic understanding of the graph's size and sparsity.

Connectivity metrics

S: Relative size (node fraction) of the largest component, $S = \frac{N^*}{N}$ (2)

K: Number of connected components

FS: Fault sensitivity, fraction of edges in the largest component whose removal would break the component in two

where the symbol * denotes a calculation on the largest connected component (in number of nodes) of the graph.

Tubules and branches cut at the borders of the imaged volume are represented by edges which may appear disconnected, giving rise to small connected components. The relative size of the largest component **S** (Eq. 2) therefore allows assessing the proportion of nodes forming the connected core of the graph. The number of connected components **K** (Eq. 6) is used to evaluate how fragmented the graph is. The robustness of the network can be further explored with the fault sensitivity **FS** (Eq. 3), the probability to create a new component when removing an edge at random. Note that this metric was defined as fault tolerance in Barthélemy et al. [55] but we find this terminology misleading since it somewhat represents the "intolerance" to defects.

Path-based and distance-based measures

W: Total edge length, $W = \sum_{e \in E} w_e$ (3)

$\langle w \rangle$: Mean edge length $\langle w \rangle = \frac{W}{E} = \frac{1}{E}\sum_{e \in E} w_e$ (4)

$\langle l \rangle$: Weighted average shortest path length, $\langle l \rangle = \frac{1}{N^*(N^*-1)}\sum_{(i,j) \in E^*} l(i,j)$ (5)

D: Diameter, $D = \max\limits_{(i,j) \in E^*} l(i,j)$ (6)

DI: Average detour index, $DI = \frac{1}{N^*(N^*-1)}\sum_{(i,j) \in E^*} \frac{l(i,j)}{d(i,j)}$ (7)

where W, $\langle w \rangle$, $\langle l \rangle$ and D are in µm, with w_e the length of edge e, $l(i,j) = \min\limits_{paths(i \rightarrow j)} |path|$ and $d(i,j)$ respectively the shortest route length and the Euclidean distance between two nodes.

For a spatial graph where edges represent physical paths, the evaluation of weighted distances provide valuable insight to the transport properties of the network. The total edge length W (Eq. 3) is the global path quantity, while the mean edge length $\langle w \rangle$ (Eq. 4) give a basic estimate of the spacing between nodes. The weighted shortest path length $l(i,j)$ corresponds to the minimum route distance (in µm) between two nodes. The weighted average path length $\langle l \rangle$ (Eq. 5) and diameter D (Eq. 6) (the longest shortest path) yield intuitive measures of node proximity in the graph. In this study, only nodes from the largest component (hence the star symbols) were considered to avoid biases from other smaller components. The average detour index DI [Eq. 7], which is the mean ratio of the shortest path length (or route length) to the Euclidean distance for each pair of nodes, also provides a valuable measure of the network travel efficiency.

Figure 2: **Graph metrics summary.** a) **Graph descriptors**. *k* is the degree of the node

highlighted in red. b) **Connectivity metrics**. Highlighted nodes in green show the largest

connected component containing *N** nodes. *FS* is the ratio of edges (in red) which removal

would lead to disconnections. c) **Distance metrics**. All components but the principal one are

faded out to indicate that, in this study, the distance metrics are computed only in the principal

component. Displayed numbers correspond to edge lengths. The edges highlighted in red

represent the shortest path between two highlighted nodes. The shortest path in this example

is the longest in the graph, meaning that its length corresponds to the graph diameter *D*. The

detour index of this specific path is 1.21 (ratio between the route length in red and the

Euclidean distance in dashed green). The graph detour index (*DI*) is the average of the detour

index of all shortest paths in the principal component.

II.3.2. Assessing the robustness of the chosen graph metrics

For each identified possible type of error on the graph (see section III.3.1 and table 3) and

each graph metric, two simulations were performed starting from the ground truth graphs:

random modifications, akin to widely performed "graph attacks" [56] and targeted "physics- or

biology-informed" modifications which makes use of the spatial graph attributes as described

below.

Node disconnections

Physical model: nodes of degree superior or equal to 3 are selected and their edge

of smallest diameter is disconnected by removing a few voxels next to the node

(according to the diameter at the node position).

Random model: for every node of degree superior or equal to 3, an edge is randomly

removed

Edge bridges

Physical model: edges are added where vessels are close to each other, based on a

distance threshold. For every edge voxel, compute the Euclidean distances to all other

voxels (from different edges) and keep the shortest. The distances are weighted such

that x and y length are multiplied by 3.5 to be representative of the dimensions of the

instrument's PSF, meaning that bridges tend to be aligned along the z axis. Bridges

are detected as the pairs of voxels with shortest distance, sorted by increasing length

and added in this order up to a certain threshold during the simulation.

Random model: edges are added between randomly picked edge voxels (previously

created bridges excluded).

Missing edges

Physical model: based on the intensity value of each voxel, edges of the graph are

erased where their diameter is below a given threshold, leading to disconnections,

splitting in several pieces or complete removal. During the simulation, this threshold is

linearly increased from 0 to the maximum diameter value in the graph by steps of 50

nm (half a pixel length).

Random model: edges are randomly removed until none remain in the graph.

III. Results

III.1. Morphology of the dentinal porosity network

In contrast to the enamel region (cropped for the analysis), where the only visible features are cracks stained by RhB, a dense packing of elongated tubular structures is visible in the confocal fluorescence stack of stained dentin with variable intensity but high contrast (Fig.3). Those correspond to open cellular porosity infiltrated by the fluorescent solution, which was abundantly described in 2D by SEM at higher resolution [57, 58] and confocal microscopy [37, 39].

The largest bright vessels, which are roughly aligned along the radial DEJ/pulp direction (vertically in Fig.3), are known as "tubules". The thinner and more tortuous one, regularly branching out from tubules, are generally referred to as "branches" [11]. Those either branch out to some distance in the dentin matrix or fully extend to connect other tubules (Fig.3.f-g). Some branches also extend radially over large distances (Fig.2.h). Rotating the 3D volume by 90° about the X axis (Fig.3.i-j) allows observing the tubules in cross-section, as often done in SEM studies to evaluate tubule density and diameters. The tubules and branches appear elongated along the Z axis because of the axial anisotropic point-spread-function (PSF) of the confocal microscope.

The DEJ chronologically corresponds to the onset of dentinogenesis during which odontoblast synthesizes the dentinal tissue. Interestingly, the two regions taken at 150 μm and 700 μm distances to the DEJ shown respectively in Fig.3b,c and Fig.3d,e exhibit relatively distinct topological characteristics. First, tubules appear wavy close to the DEJ and straighter at longer distances. Secondly, the density of tubules increases far from the DEJ and they appear much blurrier in the images due to optical aberrations. Third, the number of branches seems to decline far from the DEJ and they are fainter, i.e. the overall contrast decreases. Those observations are in perfect agreement with the literature (see e.g. [5, 11, 12, 59]).

Figure 3: Acquired image stack visualization. a) First slice of the image stack. The red and blue boxes show respectively the ROI 1 and 2. The dotted green line highlight the different regions, marked by the letters D: dentin and E: Enamel. Yellow dotted lines indicate the location of the orthogonal cuts (in the XZ plane) displayed in f) and g). Scale bar: 50µm. b) ROI 1 first slice. c) ROI 1 maximum intensity projection (MIP). d) ROI 2 first slice. e) ROI 2 MIP. b-e) Scale bar: 10µm. f-h) MIP over a limited number of slices (respectively 10, 9 and 17 slices) in sub-regions of ROIs. Scale bar: 5µm. i) XZ orthogonal cut far from the enamel. j) XZ orthogonal cut close to the enamel. i-j) Scale bar: 10µm. All images were contrasted (different values were used for each ROI) to enhance the visual perception of the structures.

III.2. Topological graph characteristics

III.2.1 Initial estimation from extracted graphs

It is well known that many artifacts can result from the graph extraction process [52, 60] which typically requires removing nodes and/or edges. However, there are no universal rules for graph cleaning, such that corrections ultimately rely on expert user input and their implementation in computing libraries. Furthermore, removal of nodes and/or edges may not have an equal impact on each type of graph metrics. Table 1 summarizes our observations on the differences between the initial computed metrics presented in II.3 on the generated graph and the corrected cleaned graph based on a set of custom rules described in II.2 and S1 Appendix Fig.S1.

First, it can be noticed that the cleaned graph is very sparse, as evidenced by the close number of nodes N and edges E (~ 35 k). This derives from the fact that ~ 80 % of the nodes have a degree (number of neighbors) of 1 (end of branch) or 3 (tubule/branch connection) (S3 Appendix Fig.S3), which results in low mean degree $<k>$ ~ 2 and gamma index γ values ~ 5.10^{-5}. Secondly, the graph's edges are relatively short: $<w>$ is around 6 µm for a graph diameter D of 1017 µm. However, the cumulative edge length W is over 0.2 meters, which is

consequent when compared to the total sample volume (3.2×10^{-3} mm^3) and is indicative of a

relatively high linear edge density of tubules and branches ($\sim 6.8 \times 10^5$ mm/mm^{-3}). Third, the

largest graph component **S** comprises more than half the graph nodes, the remaining being

scattered in about **K** $\sim$ 6000 minor components with size varying from 0–1% of the total

number of nodes. This can at least partly be explained by the finite extent of the image stack,

with many isolated nodes or groups of nodes found at or near the boundary which originate

from branches or tubules outside the acquisition volume. Finally, the graph seems to have a

low resilience as the fault sensitivity **FS** is over 0.6, meaning that a limited number of edges

are essential to reach all nodes. The low clustering coefficient (**C** $\sim$ 0.02) also points to a low

probability of alternative deviation passing by immediate neighbors of an edge's endpoints.

Interestingly, while the effect of graph cleaning has a massive influence on the number of

nodes (-58 %) and edges (-62 %), the impact on other metrics seems rather limited for some

and quite critical for others. The main degree remains close to **<k>** $\sim$ 2 because most of the

errors were node groups with a degree 1 and a degree 3 (called "spurious edges", discussed

below in III.3.1). Similarly, the total edge length **W** remains higher than 0.2 meters and the

largest graph component **S** still contains > 50 % of graph nodes. This indicates that most of

the edges removed were typically spurious edges of short length. As a result, the average

length **<w>** nearly doubles. Because **N** and **E** are roughly divided by 2, **γ** doubles as it depends

linearly on **E**, but quadratically on **N**. Also, the increase in **K** shows that some erroneous edges

were connecting components that shouldn't be, but this didn't affect the graph resilience as

FS only slightly decreases.

Metric	Full graph		ROI 1					ROI 2				
	Generated	Cleaned	Generated		Cleaned		GT	Generated		Cleaned		GT
N	92226	38755	8294	(+185%)	3683	(+26%)	2915	3613	(+259%)	1187	(+18%)	1006
E	93621	35995	9361	(+219%)	4142	(+42%)	2925	3314	(+301%)	790	(-5%)	827
$\langle k \rangle$	2.03	1.86	2.29	(+9%)	2.33	(+10%)	2.11	1.86	(+6%)	1.42	(-19%)	1.75
γ ($\cdot 10^4$)	0.22	0.48	2.77	(-62%)	6.34	(-13%)	7.25	5.17	(-71%)	11.99	(-31%)	17.45
$\langle w \rangle$	2.59	6.07	2.56	(-63%)	5.22	(-25%)	6.95	2.81	(-74%)	11.24	(+5%)	10.75
W ($\cdot 10^{-3}$)	239.5	218.6	24.8	(+10%)	23.2	(+3%)	22.5	9.6	(-4%)	10.1	(+0%)	10.1
$\langle l \rangle$	265	311	108	(-23%)	122	(-14%)	141	49	(-72%)	44	(-75%)	173
D	1108	1017	289	(-22%)	318	(-14%)	372	144	(-76%)	174	(-72%)	611
DI	2.37	2.39	2.00	(-20%)	2.27	(-9%)	2.50	1.82	(-45%)	1.69	(-49%)	3.33
S	0.56	0.50	0.93	(+11%)	0.85	(+2%)	0.83	0.05	(-87%)	0.03	(-94%)	0.43
K	5727	6197	173	(-23%)	202	(-11%)	226	400	(+94%)	405	(+97%)	206
FS	0.68	0.61	0.41	(-24%)	0.36	(-33%)	0.54	0.96	(+10%)	0.95	(+9%)	0.87

Table 1: Graph analysis of the two ROIs. The values for different metrics are compared between the generated, cleaned and ground truth (GT). *N*: number of nodes, *E*: number of edges, *<k>* mean degree, *γ*: edge density, *<w>*: mean edge length (in μm), *W*: edge length total sum (in μm), *<l>*: average shortest path (in μm), *D*: diameter (in μm), *DI*: detour index, *S*: relative size of the largest component, *K*: number of connected components, *FS,*: fault sensitivity. Values between parentheses are the relative differences between the generated or cleaned graph and the GT.

III.2.2 Ground truth comparison

The previous observations are based on the assumption that most errors on the graph have indeed been corrected during the cleaning step. This is typically a non-trivial task that relies on one's ability to identify artifacts and define sufficiently precise correction rules. In order to verify the efficiency of this step, two regions of interest (ROI) were selected (Fig.3-4) and manually corrected to create ground truth (GT) graphs. ROI 1 was chosen close to the DEJ (~ 150 μm) while ROI 2 is at a further distance (700 μm).

Table 1 provides a comparative summary of the relative errors between the generated or cleaned graphs and GT for the two ROIs. Overall, the cleaning efficiency is relatively high with respect to the number of nodes and edges, albeit with substantial differences between ROIs. As expected, the initially generated **N** and **E** are reduced by a factor of ~ 2 (ROI 1) – 3 (ROI 2) resulting in a 10 % error for ROI 2, which seems reasonable at first sight, while ROI 1 retains

a 24 % and 30 % excess *N* and *E*, respectively, which may appear insufficiently precise.

However, the relative impact of cleaning is much less pronounced in ROI 2, where all paths

and resilience metrics are rarely affected and retain relatively high error rates, while most

metrics improve in ROI 1. The resulting cleaned graphs metrics are all within 15 % error of the

GT for ROI 1 except the average edge length *<w>* (-25 %) and *FS* (-33 %), while for ROI 2,

the only metrics under 15 % error are *<w>*, *W* and *FS*, all others being above 70 % except

<k> (-19 %) and *γ* (-31 %) which are somewhat in between. So, overall, the impact of cleaning

on connectivity analysis is clearly much more efficient in ROI 1 than ROI 2 where many results

may seem unreliable.

The analysis confirms our initial visual perception of a greater vessel density near the DEJ

(ROI 1), with higher values for *N*, *E* and *W*, and higher connectivity shown by higher *<k>* (less

end points of degree 1, more vessel connections of degree 3) and *S*, resulting in a lower *FS*.

The high *FS* value in ROI 2 emphasizes the overall fragility of the network. The relative size

of the largest component *S* and the number of connected components *K* indicate that the

generated and cleaned graphs are heavily fragmented in comparison to the GT in ROI 2 while

being very close in ROI 1. This implies that in ROI 2, metrics focusing on this largest

component only describe a small part of the topology as apparent in Fig.4. The similar GT

values for the number of components *K* in both ROIs suggest that the effect of artificial vessels

pruning   at   the   imaged   volume   borders   is   the   same   in   both   cases.

Those observations allow better quantifying the important differences in structures in each

region. In ROI 2, tubules are connected by a few branches only, thus defining an irregular,

sparse 3D grid (Fig.4f). Branches in ROI 1 tend to connect more often, leading to a more

complex structure providing multiple alternative paths, which has a direct impact on distance-

based metrics (*<l>*, *D* and *Dl*). For instance, the large *D* value in ROI 2 (611.3 μm), which is

about 6 times the length of the ROI in X or Y, could be explained by the need to travel further

along a given tubule to reach the few available bridges allowing to hop onto another tubule. In

ROI 1, *D* is smaller because a greater number of bridges are available, thus requiring lesser

distance to be traveled along tubules and the same logic goes for *<l>* and *DI*. Nevertheless, it

is worthwhile noting that *DI* values are rather high in both regions (2.50-3.33), meaning that

the transport distance separating two given nodes is 2 to 3 times higher than the Euclidean

distance. In comparison, Giacomin *et al.* computed the detour index (or circuity in the study)

of metropolitan road networks in the US in [61], and obtained an average value of 1.339 (with

a maximum of 1.467. Although these networks are 2D planar, whereas ours are in 3D, the

obtained values of 2.5 and 3.33 are indicative of poor transport efficiency.

Figure 4: Ground truth graph visualization. a) MIP of ROI 1 region in the original image;

scale bar 20 μm. Ground truth graph in ROI 1, shown in b) with spatially localized nodes or in

c) with a "Force Atlas" representation (cf II.3.4) highlighting the different components. d), e) f)

same representations for ROI 2. Colors indicate the different components, with red associated

with the largest one.

III.2.3 Interpretability of local topological changes

The comparison of the (cleaned) extracted graph for the whole data set to two GTs showed

that there are potentially different levels of errors remaining in different ROIs after cleaning (as

compared to the GTs). However, the comparison of the two ROIs also reveals quite different

topologies in each data set. Our ability to identify topological differences therefore depends

on those relative differences. To verify this, we calculated a "*spatial-to-error differences ratio*"

as the ratio of the maximum difference between the cleaned graph and the GT (Δ(Cle)) and

the difference between the ROIs GT (Δ(GT1/2)) (in Table 2). Under this definition, a ratio < 1

would indicate that the remaining errors in the cleaned graph are sufficiently low to accurately

detect topological changes in the whole volume (providing that ROI 1 and 2 represent extreme

values), while a ratio > 1 prevents concluding with sufficient certainty.

The results in table 2 show that the smallest uncertainty ratio (highest confidence) for the

cleaned graph is obtained for the total edge length sum **W** (0.06). This ratio is remarkably low

compared to those of all other metrics (> 0.37), therefore **W** should be considered as a key

measure for local analysis. **N**, **E**, **γ**, **<w>** and **FS** should also prove reliable since their

uncertainty ratio is < 0.5–0.6. The mean degree **<k>** will also be considered as its ratio remains

< 1 and so could **S** which is close to 1, but all other metrics (**<l>**, **D**, **DI**, **K**) should be discarded.

Metric	$\Delta(Gen)$	$\Delta(Cle)$	$\Delta(GT_{1/2})$	$\frac{\Delta(Gen)}{\Delta(GT_{1/2})}$	$\frac{\Delta(Cle)}{\Delta(GT_{1/2})}$
N	5379	768	1909	2.82	**0.40**
E	6436	1217	2098	3.07	**0.58**
$\langle k \rangle$	0.18	0.33	0.36	**0.50**	**0.92**
γ	12.28	5.46	10.20	1.20	**0.54**
$\langle w \rangle$	79.4	17.4	37.9	2.09	**0.46**
W	2.35	0.73	12.41	**0.19**	**0.06**
$\langle l \rangle$	1247	1295	321	3.89	4.04
D	4673	4372	2397	1.95	1.82
DI	1.51	1.64	0.83	1.82	1.98
S	0.377	0.406	0.402	**0.94**	1.01
K	194	199	20	9.70	9.95
FS	0.13	0.18	0.33	**0.39**	**0.55**

Table 2: Comparison between remaining graph errors and topological differences.

Δ*(Gen)* and Δ*(Cle)* are respectively the maximum between the two ROIs of the absolute

difference between the generated graph or cleaned graph and the GT. Δ*(GT1/2)* is the

absolute difference between ROI 1 and ROI 2. The ratio between Δ*(Gen)* (or Δ*(Cle)*) and

Δ*(GT1/2)* indicates how important is the error bias when computing the metric on the

generated/cleaned graph in comparison to the ROIs variations (the lower the better).

III.3. Modeling the sources of errors and assessing their impact

Previous results provide important insights on the metrics sensitivity to remaining errors,

allowing to identify which ones are most reliable. However, our analysis is only valid for our

imaging setup and graph extraction pipeline and results may vary for other experimental

conditions. To assess the generalizability of our observations and better quantify the impact

of different parametrization, we computed the evolution of graph metrics under an increasing

amount of each type of errors taken independently.

III.3.1 Nature and classification of the sources of errors

During the manual correction of the cleaned graphs, repeating error patterns were observed

which led to their categorization in 4 classes: *spurious edges*, *nodes disconnections, missing*

edges and *edge bridges*. The characteristic features and type of applied corrections are

described in table 3 and Fig.5-7. *Spurious edges* were found to be the most common type of

error in the graph, equally distributed between the two ROIs but were almost entirely

automatically corrected during the cleaning procedure: 1656 in ROI 1, 1094 in ROI 2,

corresponding to a decrease of almost 50% of **N** and **E**. *Nodes disconnections*, on the other

hand, couldn't be entirely corrected during the cleaning step. This was the least common error

among the four types but was equally distributed in both ROIs (~50 in each). *Missing edges*

were also not fully corrected in the cleaning step. This was the second most common error

during manual correction in ROI 2 (~100 added edges) but was very rare in ROI 1. On the

opposite, *Edge bridges* was the second-most common type of error in ROI 1 but were very

scarce in ROI 2: 2190 bridges were detected and removed during the cleaning step (448 in

ROI 1, 15 in ROI 2), but an extra 50 % had to be manually corrected in the GT.

Name	Characteristics	Possible origin	Correction
Spurious edges	The simplest type of artifact, in the form of short edges (l<2µm) with a node of degree 1 stemming from a tubule.	Commonly known artifacts resulting from the skeletonization of rough (pixelated) vessel surfaces [62].	Removal of the edge and its two nodes (which also fuses two edges on the tubule).
Missing edges	Correspond to (at least parts of) branches with weak intensity or low contrast in the raw images.	Typical results from insufficient excitation laser power or low fluorescent dye concentration (e.g. small vessel or blocked diffusion). The segmentation parameters may also be another source.	Adding an edge between the existing end nodes.
Node disconnections	Disconnections which often appears at branch/tubule junctions.	Well known artifacts of vesselness filters which tend to under-perform at intersections [63].	Adding an edge from the node tip of the disconnecting branch to the tubule edge, followed by the concatenation of the branch and the created edge.
Edge bridges	Artificial junctions between two crossing non-connecting branches.	Mainly arise from small branches connecting due to the enlargement of tubules or branches by the instrument PSF [16]. Possible enlargements of voxels by filtering is also possible, although less likely.	Removal of the connecting edge followed by the application of the 2-degree nodes correction (as described in II.2.3.) to its ends.

Table 3: Characteristics and correction rules of the four classes of identified defects.

III.3.2 Simulation of errors

Using the ground truth in the two ROIs, we simulated two types of error models: *random*

modifications, akin to widely performed "*graph attacks*" [56] and targeted "*physics- or biology-*

informed" modifications which make use of the spatial graph attributes, as described in II.2.

The main difference between the two models essentially resides in their interpretability:

random attacks are mostly focused on graph topology by targeting nodes or edges, while the

physics based simulation may alter nodes or parts of edges by thresholding their attributes

depending on a physical parameter related to imaging. All results can be found in S3–S5

Appendices Fig.S3-S5 and are summarized in Fig.5-7 below. In order to facilitate the

comparison between the random and physical models, additional graphs were added in the

middle row of Fig. 6b,7b representing the correspondence between the physical parameters

and the fraction of affected edges.

Since *spurious edges* were almost entirely corrected during the cleaning step, we will only

consider the three remaining types in the following discussion. From a very general

perspective, all results obtained for *nodes disconnections* and *edge bridges* with the random

model and those based on physics using the intermediate representation appear to be very

close or, at least, follow the same tendencies. A notable exception is <*w*> which follows an

inverse trend in both models. In the case of *missing edges*, the two models don't necessarily

yield the same results, so both will have to be examined separately in this case. Also, for all

considered type of error and metrics, ROI 1 and 2 curves are distinct but their relative evolution

can basically follow three different scenario: 1) they can diverge or follow similar trends but

never intersect (e.g. Fig.6b); 2) they can start with opposite trends and intersect at a point of

confusion (black dashed line) which is often found at a relatively low level of error (e.g. <*l*> in

Fig.5b,7b) or 3) they converge after a critical error level beyond which both curves are

indistinguishable (e.g. *S*, *FS* in Fig.5b,7b). However, each type of error simulation exhibits

different patterns which must be described separately:

Node disconnections: this simulation (Fig.5 and S3 Appendix Fig.S3) assesses the impact

of improper branching connections, a typical artifact of the vesselness filter. The **random**

model simply fully deletes a fraction of edges randomly, so **N** and **E** decrease linearly. The

physical model only disconnects a portion of nodes with degree 3, starting with the smallest

diameter branches, such that N and E remain constant up to the maximum fraction of affected

nodes (30 %) corresponding to the total number of nodes of degree 3 found in the graph. At

the end, nodes of degree 0 are removed, and edges connected to degree 2 nodes are

concatenated and the node removed as well. As a result, $<k>$ naturally drops while the

average edge length $<w>$ increases in both models due to the edges being merged. Naturally,

the total edge length W decreases.

This type of defect evidently results in a quick degradation of the graph integrity with a very

high fragmentation ($S < 0.1$) for only ~10 % of edges removed in the least connected region

(ROI 2) and 20-30 % for the most connected one (ROI 1) as shown in Fig.4b. Interestingly,

this leads to very different behaviors of path metrics in the two regions: in the least connected

one (ROI 2), the average shortest paths $<l>$ rapidly decreases as parts of the main component

get disconnected (decreasing S). In the most connected region (ROI 1), $<l>$ increases due to

longer detours needed to overcome the disconnections, as long as the main component still

contains $S \sim 40$ % of edges. It reaches a peak after the removal of ~ 20% of the graph nodes

after which it drops. D logically follows a similar trend and so does DI, although the reason for

this is less clear.

Unlike the physical model, the random model doesn't target thinner vessels and is more likely

to remove tubules. For that reason, the connectivity metrics S and FS are affected at much

lower values in ROI 1 (Fig.5b). This emphasizes the fact that tubules are more important than

branches for the connectivity in ROI 1.

Figure 5: Node disconnections error simulations. a) Schematic representation of the random and physical simulations. b) Simulation results for selected metrics (all results available in S3 Appendix Fig.S3). The red and blue curves correspond respectively to the ROI 1 and 2.

Edge bridges: this simulation (Fig.6 and S4 Appendix Fig.S4) models connections between

branches that were often corrected manually in the ground truth. Connections are either added

between edges chosen randomly (*random model*) or if their relative minimum distance is

smaller than a threshold parameter (*physical model*). The fundamental difference between

the two models is that the first can connect edges at long distances while the second connects

edges at short, increasing distances. This results in opposite trends for the mean edge length

<w>, but all other metrics exhibit the same behavior in the two models.

Figure 6: Edge bridges error simulations. a) Schematic representation of the random and physical simulations. b) Simulation results for selected metrics (all results available in S4 Appendix Fig.S4). The red and blue curves correspond respectively to the ROI 1 and 2. Because of the high spatial edge density in ROI 1, N and E increase more rapidly than in ROI 2. Consequently, most metrics rise ($<k>$, W, S) or drop (γ, $<l>$, D, DI, K, FS) more steeply in ROI 1 than ROI 2. Interestingly, all remain virtually unaffected below ~ 1 µm, indicating that typical distances between vessels are at least greater than this value. Also, all values seem

to remain stable beyond ~ 7 µm in ROI 1 and ~ 9-10 µm in ROI 2, indicating a typical maximum

distance between tubules.

Missing edges: this simulation (Fig.7 and S5 Appendix Fig.S5) aims to emulate branches

which are visible in the data but appear fragmented in the segmented data, thus also

fragmenting the graph. It yields the strongest differences between the random and physical

models. The ***random model*** is close to this used for edge disconnections (regardless of their

degree in this case), so the results follow the same trends within the 0-30 % equivalent range.

Removing fractions of edges based on their minimum image intensity attribute as done in the

physical model, on the other hand, yields a different behavior. N and E exhibit no change

until a critical intensity of ~ 25, then increase sharply to a maximum of 50 for ROI 2 and 75 for

ROI 1 after which they decrease exponentially. This can be understood by the fact that the

weakest signal from the branches mostly lie within the 25-50 intensity range, after which, most

branches (60 % of edges) have been removed and tubules progressively disappear. Because

of the highest edge density in ROI 1, the effect is more pronounced in this region.

Figure 7: Missing edges error simulations. a) Schematic representation of the random and physical simulations. b) Simulation results for selected metrics (all results available in S5 Appendix Fig.S5). The red and blue curves correspond respectively to the ROI 1 and 2.

In all graph simulations (Fig.5b-7b), the first value on the y axis always corresponds to the GT and the dashed lines show the amount of errors reported during the manual correction (x axis), as well as the associated error value on the cleaned graph (Err$_{CG}$) (y axis). In addition, the

region corresponding to a 10 % error from the GT value is indicated by shaded areas to

highlight an acceptable error rate. This value is somewhat arbitrary, but approximately

corresponds to an upper limit of the minimum percentage error between the cleaned graph

and the ground truth in ROI 1 and ROI 2 (table 1) for the metrics which expressiveness was

found to be < 1 (table 2).

All Err_{CG} values for nodes disconnections fall within this 10 % error range except for **D** and **S**

in ROI 2 (Fig.5b). More importantly, those values are always lower than the confusion points

of the metrics (at least for the physical model). Altogether, this indicates that our cleaning

graph pipeline for this level of imaging quality is sufficiently robust against nodes disconnection

errors. The situation is more delicate for *branch bridges*, where Err_{CG} for <*l*> in ROI 1 is located

beyond the confusion point in the physical model representation. Furthermore, Err_{CG} values

mostly fall on the initial plateau region of ROI 2, but not in ROI 1. Since the metrics are very

sensitive to this type of error (sharp increase or decrease following the initial plateau), a slight

increase in bridge length (physical model) or fraction of affected edges (random model) results

in a significant change in metric value. So clearly, all metrics are highly sensitive to this type

of error, which is more problematic in densely connected regions. The situation is reversed for

missing edges, for which all metrics fall on a stable initial plateau within 10 % error rates for

ROI 1 and out of range for ROI 2 (Fig.7b). More problematic, some Err_{CG} values calculated for

ROI 2 (<*l*>, **D**) are beyond the point of confusion, such that their interpretation is opposite to

that made from GT values. Therefore, this error is clearly more critical for less connected

regions.

	Highly connected region (ROI1)	Less connected region (ROI2)
Node disconnections	−	−
Branch bridges	++	− −
Missing edges	− −	++

Table 4: relative importance of error type as a function of network topology.

III.4. Spatial graph fluctuations over the full volume

Based on the previous analysis of the ground truths in ROI 1 and ROI 2, where topological differences were evidenced and thoroughly quantified, it was found that a number of metrics could safely be used to analyze the global cleaned graph (*N*, *E*, *γ*, $<k>$, $<w>$, *W*, *S* and *FS*), while others ($<l>$, *D*, *DI*, *K*) were found to be insufficiently precise in the absence of a ground truth.

To emphasize the spatial changes in network topology as a function of distance to DEJ, we provide coarse-grained maps of the analyzed volume in Fig.8 and S6 Appendix Fig.S6. All metrics emphasize a transition between two zones comprising the two studied ROIs at an approximate distance of 300 µm from the DEJ indicated by a dashed line in Fig.8. Although local fluctuations can be observed in both zones, they mostly lie within the uncertainty level, so cannot be interpreted. Not all metrics have the same contrast between the two areas. For instance, *N*, *W*, *FS* and $<w>$ in (Fig 8.b-e) have strong variations. $<w>$ highlight the small edge length near the DEJ caused by a greater number of branches, despite a small underestimation (ROI 2 has higher values). Now, shortest path-based metrics such as $<l>$ (S6 Appendix Fig.S6c) appear noisy, without the expected smooth variations (due to the 50% overlap of the sliding window). This is probably because the computing of such metrics is not adapted for

small subgraphs like our window size (25 x 25 x 20.6µm).

The number of nodes **N** and edges **E** are the most basic graph descriptors and provide a first

information of the graph size to be expected. The average degree $\langle k \rangle$ completes this

information, although in our case, fluctuations mostly arise from the distributions of nodes of

degree 1 (end nodes) and 3 (branching). Note that all metrics don't have the same contrast

between the two areas. For instance, **N**, **W**, **FS** and **$\langle w \rangle$** in (Fig 8.b-e) exhibit strong variations.

$\langle w \rangle$ highlight the small edge length near the DEJ caused by a greater number of branches,

despite a small underestimation (ROI 2 has higher values). Also, shortest path-based metrics

such as **$\langle l \rangle$** (S6 Appendix Fig.S6c) appear noisier. This is most likely due to the size of the

sliding window used to calculate the metrics maps (25 x 25 x 20.6µm) which may appear too

small to fully capture path characteristics in a simple way. Taken together, those simple metric

maps provide useful insight into the network characteristics.

Figure 8: Spatial graph fluctuations. a) Maximum intensity projection of the image stack,

shown as a spatial reference. Scale bar 50 µm. b) number of nodes (N), c) total edge length

(W), d) Fault sensitivity (FS), e) mean edge length ($\langle$ w $\rangle$) and f) mean degree ($\langle$ k $\rangle$). Top and

bottom squares indicate respectively the ROI 1 and ROI 2. Approximate distance from DEJ to

transition zone indicated by dashed lines: 300 μm.

IV. Discussion

Our first aim, in this study, was to show that dentin cellular porosity indeed forms a complex

spatial network. In this healthy 23 years old female molar, we observed two topologically

distinct regions within the first 300 μm from the DEJ and beyond. A denser branching area

can be observed close to the DEJ, which corroborates previous SEM and optical imaging

studies. At further distances, fewer branches were still observed which proved important for

the global network connectivity. Those simple histological observations are reflected by the

most basic graph characteristics, such as branching type (node degree <k>), inter-distance or

length (mean edge length <w>) which all clearly highlight this transition.

However, our graph analysis provides a much clearer view of the overall network connectivity:

e.g. 83 % of nodes were found to be connected in the main component of ROI 1, compared

to 43 % in ROI 2 (*S* in table 1), as illustrated in Fig.4. Although those differences are highly

significant, the fact that both regions are strongly interconnected is, as such, an important

result which tends to indicate that tubules cannot be considered independently from a

functional point of view. This observed porosity may or may not contain odontoblastic

processes (not visualized in our study). If they do, the observed interconnections directly

represent a path to inter-cellular connectivity evidenced by TEM [6]. Otherwise, they are simply

filled with physiological fluid, in which case fluid flow through these interconnections could

favor collective odontoblasts activation through shear stresses according to the main

mechanosensing theory [1]. Either way, the observed topological connectivity should have a

direct consequence on mechanosensing which should be different between the two regions,

in accordance with well-known increase in pain sensitivity in coronal dentin close to the DEJ.

The total edge length W is also a very important quantity in spatial graphs as it provides a

direct measure of the "cost", in a general sense, associated with the network [55]. For cellular

networks, it represents the metabolic cost of maintaining the cells alive and connected. In

mineralized tissues, maintaining the pericellular space (or the tubular porosity if the main

process has retracted) also requires additional cellular activity to prevent unwanted tissue

formation and mineralization [64]. Again, a marked difference can be observed between the

two regions, with only half the value in ROI 2 compared to ROI 1 (0.101 and 0.22 m

respectively in table 1). The fault sensitivity FS also provides a useful quantification of how

fragile the network is, should a connection (tubule or branch) disappear. It is therefore

inversely proportional to the resilience of the network. With values close to 0.4 close to the

DEJ and 0.9 beyond 300 µm, the network strength appears different in the two zones (Fig.6):

quite resilient close to the DEJ and more fragile after the transition zone. Because the network

resilience is a critical factor for long-lived cells, such analysis clearly emphasizes the

usefulness of graph analysis.

Although the analysis of a single sample prevents drawing definite biological conclusions, this

first study allowed examining a basic set of common classes of graph metrics and testing their

sensitivity in the specific context of dentin cellular porosity networks. In doing so, we

thoroughly analyzed the impact of potential artifacts that may arise from confocal fluorescence

microscopy or subsequent image processing to extract the network graph. A first important

result is that certain types of metrics were found to be highly prone to residual errors in the

graph. This is the case for nearly all path metrics, <l>, D and DI, which are particularly sensitive

to edge bridges and missing edges, with typical values of final cleaned graph beyond the point

of confusion, which basically results in opposite interpretation of the relative values in ROI 1

and 2 compared to the ground truth (Fig.6-7). This is somewhat problematic since those

metrics are important quantities to understand the efficiency of transport in graphs.

Our simulations of the relative importance of different types of errors based on a physical

parameter allows a much finer interpretation of the impact of errors in possibly very different

experimental conditions than reported for this study. For instance, *branch bridges* essentially

characterize the impossibility to distinguish neighboring branches or tubules that may not be

physically connected but appear so due to a lack of imaging resolution or improper segmenting

with low intensity thresholding. The optical point-spread-function (PSF) used in our study was

typically ~ 300 nm in the imaging plane and ~ 700 nm axially. This yielded a typical value of

branching in our graphs of 1.2 µm which would correspond to the distance between two

branches of 500 nm diameter separated by the axial PSF. This is observed to have a strong

effect on all metrics of ROI 1, which is denser and thus more prone to such artifacts. But this

PSF is actually obtained in close to optimal conditions, with a close index matching between

sample and mounting media and high-quality oil objective of 1.3 NA. So, improving these

measuring conditions would be difficult with a standard confocal microscopy setup and

possibly require super-resolution microscopy, which may prove very tedious. In fact, since

many measurements of cellular networks in mineralized tissues are often performed in PBS

with water objectives of much lower NA, we anticipate that many results could be obtained

with worse performance than ours. A simple increase in axial PSF of 700 nm to 1 µm would

result in a ~ 10 % apparent increase of connectivity S in ROI 1 and 2 or an equivalent loss in

fault sensitivity.

The case of *missing edges* is potentially even worse. Such artifacts typically result from

imperfect tubule or branch fluorescent staining due to lack of dye diffusion in remote or partly

occluded cellular porosity, yielding very low intensity values in the acquired images. Imperfect

segmentation is unavoidable in such cases. Such loss of information is very often observed in

published studies of the lacuno-canalicular network in bone (see e.g. [34, 43]). In regions of

low connection density, this may easily result in a 25-50 % error or higher on virtually all graph

metrics (e.g. with a threshold of 30-50 on ROI 2 in Fig.7). It should be noted here that this

reasoning is not limited to confocal fluorescence microscopy. Resolution limitations and low

signal/background ratio is an inherent problem to any imaging modality, although each would

have its own set of advantages/disadvantages. For example, X-ray CT has isotropic

resolution, which is a strong advantage over optical methods and may decrease edge bridges

with equivalent in-plane resolution. But this would require achieving spatial resolutions in the

~ 100 nm range which has not yet been demonstrated with laboratory sources for dentin

imaging. Our own experience shows that a proper imaging of dentinal branches with X-ray CT

requires advanced synchrotron phase contrast imaging, which cannot be put on the same

level as widespread confocal microscopy.

Similarly, image processing is clearly an important potential source of improvement. For

instance, should the PSF be accurately estimated (which is difficult with strongly aberrating

mineralized tissues), image deconvolution could probably reduce the amount of *edge bridges*.

Another non-negligible source of error are *nodes disconnections*. Those are a very well-known

artifact of vesselness filtering which tends to under-perform in branching areas [63]. Although

we used the best known version of this filter, more advanced correction rules could be applied,

e.g. as geodesic voting which was successfully implemented by Peyrin *et al.* for bone studies

[65]. Supervised or unsupervised deep-learning models could also prove useful for such

purposes, but because they would require user annotation or input, those methods would still

require benchmarking.

Altogether, we wish to stress that such error estimation was rarely published before, at least

for cellular networks in mineralized tissues. Our study not only shows that this is absolutely

mandatory to discuss any observed topological fluctuation which could otherwise be at the

statistical noise level, but also that it provides quite deep insights into experimental and image

processing aspects that need to be considered and might be improved.

V. Conclusion

In this study, we investigated the topology of cellular porosity in crown dentin of a young female adult molar and showed that it exhibits characteristic features of a complex network even at millimetric distances from the dentin-enamel junction. We defined nodes as connections between tubules surrounding the main odontoblastic process and lateral branches formed by thinner secondary processes and edges as portions of those processes. We were thus able to show that a very large fraction of odontoblasts in the measured volume could be interconnected to some degree. This could have strong biological consequences in terms of cell-cell interactions, spatial extent of stimulated zones under localized mechanical/temperature stresses that may induce a more complex mechanosensing response than currently envisaged in clinical practice. Based on the examination of basic network features, such as node degree or edge lengths, we were also able to quantify the transition between the well-known highly branched region in the immediate vicinity of the DEJ from this further away. Interestingly, all more advanced network characteristics such as shortest paths or node fraction in the main connected component were found to be sensitive to this topological transition area. Moreover, the network resilience was found to strongly differ in the two regions. However, our in-depth evaluation of potential artifacts arising from the experimental image acquisition and post-processing showed that some graph metrics were very sensitive to such bias. This particularly concerns metrics measuring possible paths in the network, which ultimately relate to possible information transfer pathways between cells. We further classified the nature of encountered errors that couldn't be fully corrected automatically during image processing and simulated their specific impact on the network characteristics. Our modeling also provides a useful framework for other experimental conditions that may be encountered in confocal microscopy studies and image processing of cellular networks in dentin or other mineralized tissues and, possibly, other types of networks.

Acknowledgements

This research has been supported by the Human Frontier Science Program Research Grant RGP0023/2021. We thank Pr. Ariane Bernal (Sorbonne Univ, Univ Paris Cite, Ctr Rech Cordeliers, Inserm, U1138, Equipe Physiopathol Orale Mol, Paris) for valuable discussions concerning odontoblast development.

References

1. Magloire H, Maurin J-C, Couble ML, Shibukawa Y, Tsumura M, Thivichon-Prince B, et al. Topical Review. Dental Pain and Odontoblasts: Facts and Hypotheses. Journal of orofacial pain. 2010;24:335-49.

2. Solé-Magdalena A, Martínez-Alonso M, Coronado CA, Junquera LM, Cobo J, Vega JA. Molecular basis of dental sensitivity: The odontoblasts are multisensory cells and express multifunctional ion channels. Annals of Anatomy - Anatomischer Anzeiger. 2018;215:20–9.

3. Holland GR. The Odontoblast Process: Form and Function. Journal of Dental Research. 1985;64:499–514.

4. Byers MR, Sugaya A. Odontoblast processes in dentin revealed by fluorescent Di-I. Journal of Histochemistry & Cytochemistry. 1995;43:159–68.

5. Kaye H, Herold RC. Structure of human dentine—I. Archives of Oral Biology. 1966;11:355–IN11.

6. Carda C, Peydró A. Ultrastructural patterns of human dentinal tubules, odontoblasts processes and nerve fibres. Tissue and Cell. 2006;38:141–50.

7. Magloire H, Couble ML, Thivichon-Prince B, Maurin JC, Bleicher F. Odontoblast: a mechano-sensory cell. Journal of Experimental Zoology Part B: Molecular and Developmental Evolution. 2009;312B:416–24.

8. Aminoshariae A, Kulild JC. Current Concepts of Dentinal Hypersensitivity. Journal of
Endodontics. 2021;47:1696–702.

9. Fu X, Kim HS. Dentin Mechanobiology: Bridging the Gap between Architecture and
Function. International Journal of Molecular Sciences. 2024;25:5642.

10. Holland GR, editor An ultrastructural survey of cat dentinal tubules. J Anat (1976), 122,
1, pp 1-13; 1976.

11. Mjör IA, Nordahl I. The density and branching of dentinal tubules in human teeth.
Archives of oral biology. 1996;41:401-12.

12. Vennat E, Wang W, Genthial R, David B, Dursun E, Gourrier A. Mesoscale porosity at
the dentin-enamel junction could affect the biomechanical properties of teeth. Acta
Biomaterialia. 2017;51:418-32.

13. Newman M. Networks: Oxford University Press; 2010 March.

14. Akita K, Kuga H. A computer method of understanding ocular fundus images. Pattern
Recognition. 1982;15:431–43.

15. Azegrouz H, Trucco E, editors. Max-Min Central Vein Detection in Retinal Fundus
Images. 2006 International Conference on Image Processing; 2006 October: IEEE.

16. Soler L, Delingette H, Malandain G, Montagnat J, Ayache N, Koehl C, et al. Fully
Automatic Anatomical, Pathological, and Functional Segmentation from CT Scans for
Hepatic Surgery. Computer Aided Surgery. 2001;6:131–42.

17. Selle D, Preim B, Schenk A, Peitgen HO. Analysis of vasculature for liver surgical
planning. IEEE Transactions on Medical Imaging. 2002;21:1344–57.

18. Kaczmarek E. Visualisation and modelling of renal capillaries from confocal images.
Medical & Biological Engineering & Computing. 1999;37:273–7.

19. Espinoza-Valdez A, Femat R, Ordaz-Salazar FC. A model for renal arterial branching
based on graph theory. Mathematical Biosciences. 2010;225:36–43.

20. Ukil S, Reinhardt JM. Anatomy-Guided Lung Lobe Segmentation in X-Ray CT Images.
IEEE Transactions on Medical Imaging. 2009;28:202–14.

21. Tschirren J, Hoffman EA, McLennan G, Sonka M, editors. Branchpoint labeling and
matching in human airway trees. Medical Imaging 2003: Physiology and Function:
Methods, Systems, and Applications; 2003 May: SPIE.

22. Schmidt A, Zidowitz S, Kriete A, Denhard T, Krass S, Peitgen H-O. A digital reference
model of the human bronchial tree. Computerized Medical Imaging and Graphics.
2004;28:203–11.

23. Weinkamer R, Kollmannsberger P, Fratzl P. Towards a Connectomic Description of
the Osteocyte Lacunocanalicular Network in Bone. Current Osteoporosis Reports.
2019;17:186–94.

24. Bullmore ET, Bassett DS. Brain Graphs: Graphical Models of the Human Brain
Connectome. Annual Review of Clinical Psychology. 2011;7:113–40.

25. Gastner MT, Newman MEJ. The spatial structure of networks. The European Physical
Journal B - Condensed Matter and Complex Systems. 2006;49:247–52.

26. Bullmore ET, Fornito A, Zalesky A. Fundamentals of Brain Network Analysis: Elsevier;
2016.

27. Shibata S, Komaki Y, Seki F, Inouye MO, Nagai T, Okano H. Connectomics:
comprehensive approaches for whole-brain mapping. Microscopy. 2014;64:57–67.

28. Currey JD. Bones: Princeton University Press; 2006 July.

29. Zaslansky P, Friesem AA, Weiner S. Structure and mechanical properties of the soft
zone separating bulk dentin and enamel in crowns of human teeth: Insight into tooth
function. Journal of Structural Biology. 2006;153:188–99.

30. Fratzl P. Collagen Structure and Mechanics: Springer Science+Business Media, LLC;
2008.

31. Bonewald LF. The amazing osteocyte. Journal of Bone and Mineral Research.
2011;26:229–38.

32. Couve E, Osorio R, Schmachtenberg O. The Amazing Odontoblast. Journal of dental
research. 2013;92:765–72.

33. van Tol AF, Roschger A, Repp F, Chen J, Roschger P, Berzlanovich A, et al. Network
architecture strongly influences the fluid flow pattern through the lacunocanalicular
network in human osteons. Biomechanics and Modeling in Mechanobiology.
2020;19:823–40.

34. Kerschnitzki M, Kollmannsberger P, Burghammer M, Duda GN, Weinkamer R,
Wagermaier W, et al. Architecture of the osteocyte network correlates with bone
material quality. Journal of Bone and Mineral Research. 2013;28:1837–45.

35. Kollmannsberger P, Kerschnitzki M, Repp F, Wagermaier W, Weinkamer R, Fratzl P.
The small world of osteocytes: connectomics of the lacuno-canalicular network in
bone. New Journal of Physics. 2017;19:073019.

36. Lu Y, Xie Y, Zhang S, Dusevich V, Bonewald LF, Feng JQ. DMP1-targeted Cre
Expression in Odontoblasts and Osteocytes. Journal of Dental Research.
2007;86:320–5.

37. Yoshiba K, Yoshiba N, Ejiri S, Iwaku M, Ozawa H. Odontoblast processes in human
dentin revealed by fluorescence labeling and transmission electron microscopy.
Histochemistry and Cell Biology. 2002;118:205–12.

38. Nalla RK, Porter AE, Daraio C, Minor AM, Radmilovic V, Stach EA, et al. Ultrastructural
examination of dentin using focused ion-beam cross-sectioning and transmission
electron microscopy. Micron. 2005;36:672–80.

39. Grötz KA, Duschner H, Reichert TE, de Aguiar EG, Götz H, Wagner W.
Histotomography of the odontoblast processes at the dentine-enamel junction of
permanent healthy human teeth in the confocal laser scanning microscope. Clinical
Oral Investigations. 1998;2:21–5.

40. Ma J, Wang Z, Shen Y, Haapasalo M. A New Noninvasive Model to Study the
Effectiveness of Dentin Disinfection by Using Confocal Laser Scanning Microscopy.
Journal of Endodontics. 2011;37:1380–5.

41. Sigal MJ, Pitaru S, Aubin JE, Cate ART. A combined scanning electron microscopy
and immunofluorescence study demonstrating that the odontoblast process extends

to the dentinoenamel junction in human teeth. The Anatomical Record. 1984;210:453–62.

42. Szabó J, Trombitás K, Szabó I. The odontoblast process and its branches in human teeth observed by scanning electron microscopy. Archives of Oral Biology. 1984;29:331–3.

43. Repp F, Kollmannsberger P, Roschger A, Kerschnitzki M, Berzlanovich A, Gruber GM, et al. Spatial heterogeneity in the canalicular density of the osteocyte network in human osteons. Bone Reports. 2017;6:101–8.

44. Harris CR, Millman KJ, van der Walt SJ, Gommers R, Virtanen P, Cournapeau D, et al. Array programming with NumPy. Nature. 2020;585:357–62.

45. Virtanen P, Gommers R, Oliphant TE, Haberland M, Reddy T, Cournapeau D, et al. SciPy 1.0: fundamental algorithms for scientific computing in Python. Nature Methods. 2020;17:261–72.

46. van der Walt S, Schönberger JL, Nunez-Iglesias J, Boulogne F, Warner JD, Yager N, et al. scikit-image: image processing in Python. PeerJ. 2014;2:e453.

47. Frangi AF, Niessen WJ, Vincken KL, Viergever MA. Multiscale vessel enhancement filtering. Wells WM, Colchester A, Delp S, editors. Berlin, Heidelberg: Springer Berlin Heidelberg; 1998. 130–7 p.

48. Jerman T, Pernuš F, Likar B, Špiclin Ž, editors. Beyond Frangi: an improved multiscale vesselness filter. SPIE Proceedings; 2015 March: SPIE.

49. Lee T-C, Kashyap RL, Chu CN. Building Skeleton Models via 3-D Medial Surface Axis Thinning Algorithms. CVGIP Graph Model Image Process. 1994;56:462-78.

50. Hagberg A, Swart P, Chult D, editors. Exploring Network Structure, Dynamics, and Function Using NetworkX2008 June.

51. Xiaolong Y, Charles NC. Skeleton Network. [software] 2017. Available from: https://github.com/Image-Py/sknw

52. Drees D, Scherzinger A, Hägerling R, Kiefer F, Jiang X. Scalable robust graph and

feature extraction for arbitrary vessel networks in large volumetric datasets. BMC

Bioinformatics. 2021;22.

53. Schindelin J, Arganda-Carreras I, Frise E, Kaynig V, Longair M, Pietzsch T, et al. Fiji:

an open-source platform for biological-image analysis. Nature Methods. 2012;9:676–

82.

54. Bastian M, Heymann S, Jacomy M, editors. Gephi: An Open Source Software for

Exploring and Manipulating Networks. 2009 March: Association for the Advancement

of Artificial Intelligence (AAAI).

55. Barthélemy M. Spatial networks. Physics Reports. 2011;499:1–101.

56. Albert R, Barabási A-L. Statistical mechanics of complex networks. Reviews of Modern

Physics. 2002;74:47–97.

57. Kontakiotis EG, Tsatsoulis IN, Filippatos CG, Agrafioti A. A quantitative and diametral

analysis of human dentinal tubules at pulp chamber ceiling and floor under scanning

electron microscopy. Australian Endodontic Journal. 2014;41:29–34.

58. Giudice GL, Cutroneo G, Centofanti A, Artemisia A, Bramanti E, Militi A, et al. Dentin

Morphology of Root Canal Surface: A Quantitative Evaluation Based on a Scanning

Electronic Microscopy Study. BioMed Research International. 2015;2015:1–7.

59. Zaslansky P, Zabler S, Fratzl P. 3D variations in human crown dentin tubule

orientation: A phase-contrast microtomography study. Dental Materials. 2010;26:e1–

e10.

60. Sled JG, Marxen M, Henkelman RM, editors. Analysis of microvasculature in whole

kidney specimens using micro-CT. SPIE Proceedings; 2004 October: SPIE.

61. Giacomin DJ, Levinson DM. Road network circuity in metropolitan areas. Environment

and Planning B: Planning and Design. 2015;42:1040–53.

62. Soille P. Morphological Image Analysis: Springer Berlin Heidelberg; 2004.

63. Jerman T, Pernus F, Likar B, Spiclin Z. Enhancement of Vascular Structures in 3D and

2D Angiographic Images. IEEE Transactions on Medical Imaging. 2016;35:2107–18.

64. Bleicher F, Richard B, Thivichon-Prince B, Farges J-C, Carrouel F. Odontoblasts and

Dentin Formation: Elsevier; 2015. 379–95 p.

65. Peyrin F, Pacureanu A, Zuluaga MA, Dong P, Langer M, editors. 3D X-ray CT imaging

of the bone Lacuno-Canalicular Network. 2012 9th IEEE International Symposium on

Biomedical Imaging (ISBI); 2012 May: IEEE.

1043