OpDetect: A convolutional and recurrent neural network classifier for precise and sensitive operon detection from RNA-seq data

Rezvan Karaji[1], Lourdes Peña-Castillo[1,2,*]

1 Department of Computer Science, Memorial University of Newfoundland, St. John's, NL, Canada
2 Department of Biology, Memorial University of Newfoundland, St. John's, NL, Canada

* lourdes@mun.ca

Abstract

An operon refers to a group of neighbouring genes belonging to one or more overlapping transcription units that are transcribed in the same direction and have at least one gene in common. Operons are a characteristic of prokaryotic genomes. Identifying which genes belong to the same operon facilitates understanding of gene function and regulation. There are several computational approaches for operon detection; however, many of these computational approaches have been developed for a specific target bacterium or require information only available for a restricted number of bacterial species. Here, we introduce a general method, OpDetect, that directly utilizes RNA-sequencing (RNA-seq) reads as a signal over nucleotide bases in the genome. This representation enabled us to employ a convolutional and recurrent deep neural network architecture which demonstrated superior performance in terms of recall, f1-score and AUROC compared to previous approaches. Additionally, OpDetect showcases species-agnostic capabilities, successfully detecting operons in a wide range of bacterial species and even in *Caenorhabditis elegans*, one of few eukaryotic organisms known to have operons. OpDetect is available at
`https://github.com/BioinformaticsLabAtMUN/OpDetect`.

Author summary

The most recent operon definition highlights the complexity of bacteria gene regulation: 1) Operons consist of one or more overlapping transcription units; 2) genes in an operon might be involved in multiple metabolic pathways; 3) operons might have internal promoters that might be differentially regulated; and 4) not all genes in an operon might be cotranscribed. Most of these characteristics were not considered in the initial operon definition. However, that initial operon definition guided the development of several existing operon detection computational tools which are based, for example, on functional annotations. In this work, we develop a species-agnostic, data-driven, machine learning-based approach for operon detection that allows detected operons to have all the characteristics mentioned above. Our method (OpDetect) directly uses RNA-seq read counts from up to six samples to identify pairs of adjacent genes belonging to the same operon. OpDetect outperforms four state-of-the-art approaches for operon detection and is general enough to be able to accurately detect operons in *Caenorhabditis elegans*, one of few eukaryotic organisms known to have operons.

Introduction

Bacteria are involved in the survival and functioning of all plants and animals, including humans [1]. Understanding bacterial gene function and regulation is essential to decipher how bacteria interact with other organisms and the environment. Operons, fundamental to bacterial genome organization and gene regulation, play a critical role in bacterial molecular functions. An operon refers to a group of neighbouring genes that are regulated by one or more overlapping transcription units [2]. These overlapping transcription units are transcribed in the same direction and have at least one gene in common. Transcription units are DNA regions that encompass the area from a promoter, where transcription is initiated, to a terminator, which marks the end of transcription [2]. Thus, genes in a transcription unit are transcribed as a single mRNA. Genes belonging to the same operon are typically, but not necessarily, functionally related or involved in the same metabolic pathways [2–5]. Operon detection is the task of identifying genes belonging to the same operon, which contributes to the mapping of regulatory networks. This will lead to a better understanding of gene functionality and regulation in bacterial genomes [4,6].

Several machine learning-based tools have recently been developed for operon detection in bacterial genomes. These tools utilize various computational approaches. Operon-mapper [7] utilizes computational algorithms grounded in the Prokaryotic Operon Database (ProOpDB) [8,9]. It employs a two-layer neural network that incorporates intergenic distances and gene functional relationship scores from STRING [10]. Its training and evaluation was done in *Escherichia coli* and *Bacillus subtilis*. For RNA-seq data analysis and bacterial operon prediction, Rockhopper [11] adopts a Naïve Bayes model that integrates intergenic distances and gene expression levels from RNA-seq data. The training and evaluation of Rockhopper's model was done on *E. coli*, *B. subtilis*, and *Helicobacter pylori*. Operon Finder [12] is a web service that builds upon Operon Hunter [4]. Operon Hunter introduces a distinct approach by adapting, using transfer learning, ResNet18 [13] on visual comparative genome representations of six species with experimentally confirmed operons in the Operon DataBase (ODB) [14]. Comparative genomic images were obtained via the Compare Region Viewer service from PATRIC [15]. OperonSEQer [16] uses a voting system that combines six machine learning algorithms. Based on RNA-seq reads, OperonSEQer extracts Kruskal-Wallis statistics and p-values to evaluate gene pairs and intergenic regions for differences in read coverage. OperonSEQer is trained on computationally-obtained operon labels from MicrobesOnline [17] for eight different organisms.

While all these computational techniques have significantly advanced operon detection, there are still some opportunities for improvement. First, some of these tools rely on features from external sources, these features are often available only for extensively studied organisms. This affects the applicability of such models to lesser-studied bacterial genomes, which comprise the vast majority of bacteria [18]. Second, some models have been trained on computationally derived labels, potentially leading to mimicry of another algorithm's decisions. Third, some models have been trained and evaluated in the same organisms, which could lead to data leakage. These last two issues might cause that reported performances are overestimated. In this work, we have developed a tool to address these issues. Our approach, OpDetect, relies solely on genome sequence and RNA-seq data, which are available for a broad range of bacteria. It was trained on experimentally verified operon labels, and evaluated on an independent set of organisms not used for training. Additionally, we focus on creating an organism-agnostic operon detection model capable of adapting to different species and effectively identifying operons across various conditions. We comparatively assessed the performance of OpDetect with that of Operon-mapper, OperonFinder, OperonSEQer

and Rockhopper. Our results show that OpDetect outperforms these other four approaches in terms of recall, f1-score and the area under the ROC curve (AUROC).

Materials and methods

Data

This study utilizes genome sequences, RNA-seq data, and operon annotations as primary data sources. Thus, we collected data for organisms that have operon annotations in OperonDB and RNA-seq data publicly available. The genome sequence and annotation files are obtained from the RefSeq [19] database. RNA-seq data for up to six samples of each organism are sourced from the Sequence Read Archive (SRA) [20] and the European Nucleotide Archive (ENA) [21]. Operon annotations are obtained from OperonDB version 4 (ODB) [14]. This curated database, available at `https://operondb.jp/`, contains experimentally known operons. Detailed information on organisms and their accession codes for genome sequences and RNA-seq data is available in Table 1. We selected seven bacterial organisms to be used for training purposes and another seven organisms for independent validation (six bacteria and one eukaryote). This selection was based on data availability: Those bacterial organisms with more annotated gene pairs were used for training.

Data Preparation Commands

The initial steps in processing the data involve trimming and filtering the raw sequencing data in FASTQ format. This process is performed using Fastp (version 0.23.1) [34]. The trimmed and filtered FastQ files are then aligned to the reference genomes using HISAT2 (version 2.2.1) [35], and the read coverage for each genome base is extracted using SAMtools (version 1.17) [36] and BEDtools (version 2.30.0) [37]. Complete commands for these steps are provided in OpDetect's GitHub repository.

Feature Representation

The feature representation used in this study draws inspiration from signal processing techniques, particularly the work of [38] in classifying human activities using signals from wearable sensors. However, instead of analyzing signals over time, we focus on the RNA-seq read counts across nucleotide bases in a genome. In our case, the different sensors correspond to multiple RNA-seq samples of the same organism. This perspective allows us to leverage signal processing advancements for our task, operon detection.

By adopting this representation, we aim to maximize the utilization of information from RNA-seq data. Previous approaches such as OperonSEQer often relied on statistical analyses of RNA-seq data, which by summarizing the data with statistics removed potential informative patterns from the input data. Our feature representation enables us not only to use nucleotide-level signals but also to combine them with primary sequence features, such as gene length, gene borders, and intergenic distances. Another advantage of our feature representation is the compatibility of the final dataset's shape with convolutional neural network architectures.

The features in our model are derived from read counts per genome base, paired with operon labels obtained from ODB. The read counts for each gene are grouped based on genome annotations, allowing the extraction of gene-specific vectors. These vectors are then paired for consecutive genes, and intergenic region read counts are assembled into a vector for each gene pair. The process is repeated for up to six samples for each organism. All vectors are resampled to a fixed size of 150. Following resampling, scaling transforms the read counts to a range of 0 to 1, akin to treating gene pairs as images.

Training				
Organism		**RNA-seq**		
Name (Phylum)	**Genome**	**Study**	**Samples**	**Ref**
B. subtilis subsp. subtilis str. 168 (Bacillota)	NC_000964.3	GSE179533	SRR15049591 SRR15049592 SRR15049593	[22]
		E-MTAB-10658	ERR6156944 ERR6156945 ERR6156946	[23]
Corynebacterium glutamicum ATCC 13032 (Actinomycetota)	NC_006958.1	GSE120924	SRR7977557 SRR7977561 SRR7977565	[24]
		E-MTAB-8070	ERR3380462 ERR3380465 ERR3380468	[25]
E. coli K-12 substr. MG1655 (Pseudomonadota)	NC_000913.2	GSE65642	SRR1787590 SRR1787592 SRR1787594	[26]
		GSE114917	SRR7217927 SRR7217928 SRR7217929	[27]
Helicobacter pylori 26695 (Campylobacterota)	GCA_000008525	GSE94268	SRR5217496	[28]
Legionella pneumophila str. Paris (Pseudomonadota)	NC_006368.1	E-MTAB-4095	ERR1157043 ERR1157044 ERR1157045	[29]
Listeria monocytogenes EDG-e (Bacillota)	NC_003210.1	GSE152295	SRR11998208 SRR11998211 SRR11998214 SRR11998217 SRR11998220 SRR11998223	[30]
Mycoplasmoides pneumoniae M129 (Mycoplasmatota)	NC_000912.1	E-MTAB-8537	ERR3672190 ERR3672191 ERR3672192 ERR3672193	[31]

Validation				
Organism		**RNA-seq**		
Photobacterium profundum SS9 (Pseudomonadota)	NC_006370.1, NC_006371.1	GSE38259	SRR500950 SRR500951	[32]
Agrobacterium fabrum str. C58 (Pseudomonadota)	NC_003062, NC_003063	GSE173921	SRR14432343 SRR14432344 SRR14432345	NA
Borreliella burgdorferi B31 (Spirochaetota)	NC_001318.1	GSE152295	SRR11997800 SRR11997801 SRR11997802	[30]
Bradyrhizobium diazoefficiens USDA 110 (Pseudomonadota)	NC_004463.1	GSE163004	SRR13238987 SRR13238988 SRR13238989	[33]
Pseudomonas aeruginosa PAO1 (Pseudomonadota)	NC_002516.2	GSE152295	SRR11998427 SRR11998428 SRR11998429	[30]
Yersinia pestis CO92 (Pseudomonadota)	NC_003143.1	PRJNA384395	SRR5489122 SRR5489125	NA
C. elegans (Nematoda)	GCF_000002985.6	GSE149300	SRR11605370 SRR11605378 SRR11605385	NA

Table 1. Data used in this study.

Separate channels are constructed for each part of the gene pairs: the first gene, intergenic region, and the second gene. This approach, reminiscent of RGB channels in images, allows the treatment of each vector as an independent entity within the feature representation. Additionally, this representation naturally encodes the length and borders of each segment (i.e., gene, intergenic region, gene). The final shape of each gene pair's vector is (150, 6, 3), reflecting the fixed size input vector, number of samples, and number of channels. Operon labels, assigned based on ODB annotations, distinguish gene pairs within the same operon (label 1) or not (label 0), with label 2 indicating insufficient experimental evidence for operon relationship determination. We introduced label 2 to account for the fact that lack of annotation is not the same as knowing that two genes are not within the same operon. Label 2 is given to pairs of genes not in the ODB operon annotations (default label 0) where both genes are absent from the ODB annotations. Gene pairs labeled as 2 are excluded from the training data. The number of instances (gene pairs) for each label in our training data is provided in Table 2.

Label	Operon(**1**)	Non-operon(**0**)	Unknown(**2**)
Number of gene pairs	6345	4030	9828

Table 2. The number of instances (gene pairs) per label class in our training data. Labels 0 and 1 are used to train the model, making the final size of training data 10375 gene pairs.

Machine Learning Model

CNN-LSTM is the deep learning architecture we adapted from [38]. It combines Convolutional Neural Networks CNNs and Long Short-Term Memory LSTM recurrent neural networks [39] to capture spatial and temporal dependencies in the data. The CNN-LSTM architecture that is utilized in this study includes a CNN, a Lambda, an LSTM, an Attention, and a Dense layer, respectively (Table 3). The CNN layer acts as a feature detector, extracting spatial patterns from the input data. A Lambda layer facilitates a smooth transition to the LSTM layer by reshaping the CNN layer output. The LSTM layer captures sequential dependencies, utilizing its memory to predict future steps. An Attention layer enhances focus on relevant data regions. To prevent overfitting, dropout regularization is applied. The Dense layer processes information for the final binary output.

Layer	Output Shape	No. parameters
Input Layer	(None, 150, 6, 3)	0
Conv2D	(None, 146, 1, 64)	5,824
Lambda	(None, 146, 64)	0
LSTM	[(None, 146, 64), (None, 64), (None, 64)]	33,024
Self Attention	[(None, 1024), (None, 6, 146)]	2,560
Lambda	(None, 1024)	0
Dense	(None, 2)	2,050

Table 3. CNN-LSTM architecture. (None, 150, 6, 3) in the input layer specifies that the CNN model can accept input data with variable batch sizes (None), where each sample has a length of 150 elements (fixed size input vector), a height of 6 rows (number of samples), and a width of 3 columns (number of vectors). The Lambda layer is used to adjust the shape of the output from the CNN layer to input for the LSTM layer.

Software and Packages

The feature representation pipeline and machine learning model in this study were developed using Python (version 3.10.13). The list of used packages along with their versions is presented in S1 Table. OpDetect code is available at `https://github.com/BioinformaticsLabAtMUN/OpDetect`.

Training the Model

We trained our model using the data shown in Table 2. To prevent overfitting when optimizing the hyperparameters, 10-fold grid-search cross-validation was employed, averaging results across folds. The hyperparameters listed in Table 4 were selected to achieve a high AUROC. AUROC is a metric used to evaluate the performance of binary classification models. The AUROC can be interpreted as an estimate of the probability that a random positive instance will be predicted to have a higher likelihood to belong to the positive class (operon) than a random negative instance. The specifications for the attention layer in this model are exactly as defined in [38]. We use the default threshold of 0.5 to classify gene pairs as operons. To support the reproducibility of the machine learning method of this study, the machine learning summary table is included in S2 Tableas per DOME recommendations [40].

Hyperparameter	Value	Hyperparameter	Value	Hyperparameter	Value
Batch size	32	Epoch	100	Dropout rate	0.4
Kernel size	(5, 6)	CNN filters	64	LSTM units	64
Optimizer	Adam	Learning rate	0.001		
Loss function	Categorical cross entropy	Early stopping Metric	AUROC	Early stopping patience	10

Table 4. Hyperparameters used in our final CNN-LSTM model.

Evaluation Metrics

To evaluate our model's effectiveness in operon detection, we consider the F1-score. The F1-score is defined as:

$$\text{F1-score} = \frac{2 \times \text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}} \tag{1}$$

where recall is the proportion of positive instances predicted to be positive, and precision is the proportion of predicted positive instances which are actually positive. However, due to limited 0-label instances in five of the seven validation organisms, f1-score calculation can be based on very few (less than 10) negative instances and hence unreliable. To overcome this, we also assessed the performance of our model using recall. In the cases where there were more than 10 negative instances, we also utilized the AUROC, and visualized the ROC curve to observe the trade-off between the True Positive Rate (TPR) or recall, and the False Positive Rate (FPR) at various classification thresholds.

Results and Discussion

Cross-validation results

For the aggregated training data of seven organisms (Table 1, top half), the performance of OpDetect over 10-fold cross-validation is shown in Table 5.

Performance metric	Mean value	90% Confidence interval
Recall	88.94%	[88.17%, 89.70%]
f1-score	89.50%	[88.74%, 90.25%]
Accuracy	90.18%	[89.47%, 90.88%]
AUROC	0.889	[0.882, 0.897]

Table 5. OpDetect's 10-fold cross-validation results. The 90% confidence interval suggests that the model's performance metric is 90% probable to be within this range.

Comparative assessment

We evaluated the performance of OpDetect on identifying pairs of genes belonging to the same operon on seven organims (Table 1, bottom half) and compared its performance with that of Operon-mapper, OperonFinder, OperonSEQer and Rockhopper. The number of operons and non-operons collected for these seven organisms is provided in Table 6. Collected data are incomplete, as we only used experimentally-confirmed operons in ODB and we implemented a strict approach to label gene pairs as non-operons. In other words, there are actual operons and also non-operons missing from our data. This has implications during the evaluation of the methods; for example, a predicted operon might in fact be an operon (i.e., the prediction is correct) but it will be considered a false positive because that operon has not been experimentally-confirmed. To test the generalizability of OpDetect, we included in our validation data *B. burgdorferi*'s data and *C. elegans*'s data. *B. burgdorferi* belongs to a phylum (Spirochaetota) not present in our training data and *C. elegans* is one of the few eukaryotes known to have operons [41].

Organism	No. of Operons (P)	No. of Non-operons (N)
C. elegans	1184	56
P. profundum	676	87
P. aeruginosa	67	3
B. diazoefficiens	15	2
B. burgdorferi	20	0
A. fabrum	14	0
Y. pestis	6	0

Table 6. Number of gene pairs belonging to the same operon (P) and not belonging to the same operon (N) per organism in our validation data.

During the comparative assessment, we faced some challenges with some of the tools included in the evaluation. These challenges were: i) Due to their size, we were unable to load the genome of *C. elegans* to the Operon-mapper website for prediction. As a result, we do not possess predictions of *C. elegans* operons from Operon-mapper. ii) Due to the reliance of Operon Finder on external data sources, the predictions generated by this method are restricted to the organisms that are available within those specific sources. Consequently, we were unable to obtain predictions from Operon Finder for *Y. pestis* CO92, *B. diazoefficiens* USDA 110, and *C. elegans*. iii) OperonSEQer predicted as belonging to the same operon gene pairs from different strands, whereas it is known that genes within the same operon must be located on the same strand [42]. Moreover, OperonSEQer was unable to predict labels for gene pairs with a read depth coverage below certain average read counts. Specifically, OperonSEQer failed to predict 181, 19 and 1 gene pairs for *C. elegans*, *P. profundum* and *P. aeruginosa*, respectively. OperonSEQer performance metrics in these organisms might be affected by the missed predictions. The results of our comparative assessment are provided in Table 7. Fig. 1 shows the ROC curves for *C. elegans* and *P. profundum*.

These results indicate that OpDetect can reliably identify operons even in an eukaryote (*C. elegans*) while Rockhopper and OperonSEQer, the two other tools which can predict *C. elegans*'s operons, are close to the random classifier performance (Fig. 1,

		F1-score			
Organism	Operon-mapper	Rockhopper	Operon Finder	OperonSEQer	OpDetect
C. elegans	NA	10.7%	NA	35.5%	88.0%
P. profundum SS9	58.0%	39.9%	91.3%*	95.8%	94.9%

		Recall			
Organism	Operon-mapper	Rockhopper	Operon Finder	OperonSEQer	OpDetect
C. elegans	NA	5.7%	NA	21.6%	80%
P. profundum SS9	42.2%	25.4%	89.5%*	97%	95.9%
P. aeruginosa PAO1	59.7%	52.2%	94%	91%	97%
B. diazoefficiens USDA 110	66.7%	20%	NA	78.6%	93.3%
B. burgdorferi B31	25%	30%	85%	75%	100%
A. fabrum str. C58.	14.3%	35.7%	92.9%	85.7%	100%
Y. pestis CO92	100%	100%	NA	100%	100%
Average $\pm$ s.d.	51.3 ± 31.1	38.4 ± 30.7	90.3 ± 4.0	78.4 ± 26.7	95.2 ± 7.2

Table 7. F1-scores for the two validation organisms with more than 10 non-operon labels, *C. elegans* and *P. profundum* SS9, and recalls for all seven validation organisms. The highlighted numbers in the tables represent the best performance per organism. The mean recall for Operon-mapper and Operon Finder was calculated excluding the missing values. * indicates that the target organism is included in the training data of the corresponding method.

Fig 1. ROC curve for *C. elegans* (left) and *P. profundum* SS9 (right). Diagonal dotted line indicates a random classifier and top dashed line indicates a perfect classifier.

left) for this organism. For *P. profundum*, the predictive performance of OperonSEQer and OpDetect is comparable, with OperonSEQer achieving the highest F1-score (Table 7) and OpDetect obtaining the highest AUROC (Fig. 1, right). Additionally, OpDetect achieves the highest average recall with the second-smallest standard deviation, suggesting that OpDetect's recall is consistent for a wide range of organisms.

Assessing the effect of data leakage

When we performed our comparative assessment, we noticed that, in one case, one of the methods included in the comparative assessment had data from the corresponding validation organism in its training data (Table 7). This is a form of data leakage. Data leakage refers to the introduction of information in the training data (about the target function or about the test data) that should not be legitimately available to learn from. Data leakage usually causes an overestimation of a model's predictive performance. Data leakage is a widespread problem in machine learning applications [43], including machine learning-based bioinformatics [44]. Thus, we decided to quantify the effect of having the target organism in the training data. To do this, we evaluated all the methods in the training data and included two versions of OpDetect: i) one where we

trained OpDetect and assessed its performance using cross-validation on data that ²⁰⁸ included the target organism (data leakage-affected version). In this version, gene pairs ²⁰⁹ of the target organism were randomly partitioned into training and testing. Thus, ²¹⁰ individual gene pairs were not in the training and testing data simultaneously; and ii) ²¹¹ another version we retrained excluding all gene pairs of the target organism (data ²¹² leakage-free version). This means that we re-trained OpDetect for each of the training ²¹³ organisms so that we could have a data leakage-free version for each organism in our ²¹⁴ training data. Note that excluding the target organism from the training of the other ²¹⁵ methods was not possible since we used their pre-trained models. ²¹⁶

Table 8 presents the F1-scores and AUROCs for each method on the training ²¹⁷ organisms. "OpDetect NE" refers to OpDetect without excluding the examined ²¹⁸ organism from the training process (i.e., affected by data leakage). The ROC curves for ²¹⁹ these organisms can be found in S1-7 Figures. For OpDetect, data leakage on average ²²⁰ inflates by 2% both performance metrics, and this overestimation of predictive ²²¹ performance can be as high as 6%. This highlights the need to ensure a strict separation ²²² of training and testing/validation data when assessing the generalizability of machine ²²³ learning-based models. ²²⁴

OpDetect outperforms all other methods in terms of average F1-score and average ²²⁵ AUROC and, considering only data leakage-free methods per organism, OpDetect is the ²²⁶ method that achieves the highest F1-score in all seven bacteria and the highest AUROC ²²⁷ in six of the seven bacteria (Table 8). ²²⁸

F1-scores

Organism	Operon-mapper	Rockhopper	Operon Finder	OperonSEQer	OpDetect	OpDetect NE
E. coli	49%*	73%*	86%*	89%*	85%	91%*
C. glutamicum	50%	12%	79%*	81%	86%	89%*
L. monocytogenes	57%	20%	92%*	45%	97%	98%*
L. pneumophila	56%	28%	86%*	90%	94%	96%*
H. pylori	59%	14%*	90%	93%	97%	97%*
B. subtilis	57%*	74%*	90%*	89%*	93%	95%*
M. pneumoniae	63%	42%	48%	85%	90%	91%*
Average ± s.d.	56 ± 5%	38 ± 26%	82 ± 15%	82 ± 17%	92 ± 5%	94 ± 3%

AUROC

Organism	Operon-mapper	Rockhopper	Operon Finder	OperonSEQer	OpDetect	OpDetect NE
E. coli	0.65*	0.78*	0.87*	0.86*	0.85	0.91*
C. glutamicum	0.64	0.53	0.81*	0.73	0.86	0.90*
L. monocytogenes	0.68	0.56	0.88*	0.63	0.88	0.91*
L. pneumophila	0.63	0.57	0.77*	0.72	0.80	0.77*
H. pylori	0.69	0.54*	0.87	0.85	0.84	0.84*
B. subtilis	0.68*	0.79*	0.87*	0.86*	0.84	0.88*
M. pneumoniae	0.69	0.62	0.64	0.74	0.79	0.83*
Average ± s.d.	0.67 ± 0.03	0.63 ± 0.11	0.82 ± 0.09	0.77 ± 0.09	0.84 ± 0.03	0.86 ± 0.05

Table 8. F1-scores and AUROCs achieved on the training organisms. * indicates that the target organism is included in the training data of the corresponding method (i.e., data leakage has occurred). "OpDetect NE" refers to OpDetect without excluding the examined organism from the training process (i.e., affected by data leakage). The highlighted numbers in the tables represent the best performance per organism achieved without data leakage.

OpDetect achieves stable and accurate operon prediction for a wide range of organisms

Figs. 2 and 3 show the distribution of F1-scores and AUROCs achieved by the five methods in the seven training organisms and the two validation organisms with more than 10 non-operon labels (Tables 1 and 6). For these analyses, we used the OpDetect data leakage-free result (Table 8). OpDetect has less spread in its performance in terms of F1-score and AUROC than the other methods (Figs. 2 and 3). Furthermore, most of its F1-scores are above 90% (Fig. 2). This indicates that OpDetect is able to balance precision and recall.

Fig 2. Violin plots of the F1-scores achieved by each method in the seven training organisms and the two validation organisms with more than 10 non-operon labels. We used OpDetect data leakage-free result (Table 8). For each method, calculations excluded their missing results. That is, for Operon-mapper and Operon Finder the distribution is on eight organisms instead of nine, as these two methods could not predict operons in *C. elegans*. Red dots indicate the average F1-score per method.

Fig 3. Violin plots of the F1-scores achieved by each method in the seven training organisms and the two validation organisms with more than 10 non-operon labels. We used OpDetect data leakage-free result (Table 8). For each method, calculations excluded their missing results. That is, for Operon-mapper and Operon Finder the distribution is on eight organisms instead of nine, as these two methods could not predict operons in *C. elegans*. Red dots indicate the average AUROC per method. Horizontal dashed line indicates the AUROC of a random classifier.

We employed the Friedman non-parametric statistical test that is suitable for comparing multiple classifiers over multiple datasets to assess the statistical significance of AUROC differences between the methods [45]. To do this, we ranked each model based on the AUROC obtained on all seven training organisms and two validation organisms, *C. elegans* and *P. profundum* SS9. The model with the highest AUROC was

assigned rank one, while ties received the same rank. Missing values were ranked four. The Friedman test yielded a p-value of 0.0002, indicating that the mean AUROC obtained by certain classifiers significantly deviates from the others. To find out which models differ in terms of AUROC, we used several pairwise post hoc tests as recommended in [46]; namely, Quade, Miller, Nemenyi, and Siegel post hoc tests. All statistical tests were carried out in R (version 4.4.2) using the packages PMCMRplus (version 1.9.12) [47] and scmamp (version 0.3.2) [48].

We observed that three groups of classifiers with similar ranks emerged, as illustrated in Fig. 4. OpDetect's ranks are comparable to those of Operon Finder and OperonSEQer. All pairwise post hoc tests agreed that OpDetect's AUROC ranks are statistically better (adjusted p-value < 0.05) than those of Operon-mapper and Rockhopper. The other statistical difference consistently found was between Operon Finder and Rockhopper. Although Operon Finder showed the second-best performance in terms of AUROC and F1-score overall, it is limited to making predictions for specific species due to its reliance on features obtained from external data sources. For example, Operon Finder could predict only four out of seven species in our validation data (Table 7).

Fig 4. Critical Difference plot for AUROC, over seven training organisms and two validation organisms. Classifiers that do not show significant differences according to the Nemenyi test at a significance level of 0.05 are connected with a horizontal line. The methods with the best performance are to the right.

Conclusion

In this work, we introduce OpDetect, a species-agnostic method for operon identification from RNA-seq data. OpDetect is, in fact, the only method we evaluated capable of precise and sensitive identification of operons in an eukaryote, *C. elegans*. OpDetect has the following advantages: i) By exclusively relying on genome annotations and RNA-seq data, OpDetect makes operon detection accessible for more species. ii) By using a new feature representation for RNA-seq data, inspired by signal processing methods, OpDetect could use a CNN-LSTM architecture. This architecture captures both spatial and sequential dependencies in the RNA-seq data. iii) By using experimentally evaluated operons and conservatively labelling non-operons, we reduced the number of potentially mislabeled gene pairs in OpDetect training data. It is well-known in machine learning that the cleaner the training data the better the generated model. iv) OpDetect outperforms four state-of-the-art operon prediction methods in terms of F1-score and AUROC. For future work, we propose exploring the inclusion of promoter and terminator data, as they have been reported to have a significant influence on operon detection [5]. Finally, based on our results on assessing the effect of data leakage,

we recommend having a strict partition of organisms for training and validation of machine learning-based methods to avoid overestimating their generalizability.

Supporting information

S1 Table. List of Python packages with their versions used to develop OpDetect.

S2 Table. Data, Optimization, Model and Evaluation (DOME) Information.

S1-7 Figures. ROC curves for the seven training organisms showing the effect of data leakage.

Acknowledgments

We thank Gavin Hull for his assistance in optimizing OpDetect's hyperparameters. This research was partially enabled by the computing infrastructure provided by Acenet (ace-net.ca) and the Digital Research Alliance of Canada (alliancecan.ca). This work was supported by funds from an NSERC Discovery Grant to L.P-C. and a graduate fellowship from Memorial University School of Graduate Studies to R.K.

References

1. Rappuoli R, Young P, Ron E, Pecetta S, Pizza M. Save the microbes to save the planet. A call to action of the International Union of the Microbiological Societies (IUMS). One Health Outlook. 2023;5(1):5. doi:10.1186/s42522-023-00077-2.

2. Mejía-Almonte C, Busby SJW, Wade JT, van Helden J, Arkin AP, Stormo GD, et al. Redefining fundamental concepts of transcription initiation in bacteria. Nature Reviews Genetics. 2020;21(11):699–714. doi:10.1038/s41576-020-0254-8.

3. Osbourn AE, Field B. Operons. Cellular and Molecular Life Sciences. 2009;66(23):3755–3775. doi:10.1007/s00018-009-0114-3.

4. Assaf R, Xia F, Stevens R. Detecting operons in bacterial genomes via visual representation learning. Scientific Reports. 2021;11(1):1–10. doi:10.1038/s41598-021-81169-9.

5. Conway T, Creecy JP, Maddox SM, Grissom JE, Conkle TL, Shadid TM, et al. Unprecedented high-resolution view of bacterial operon architecture revealed by RNA sequencing. mBio. 2014;5(4). doi:10.1128/mBio.01442-14.

6. Creecy JP, Conway T. Quantitative bacterial transcriptomics with RNA-seq. Current Opinion in Microbiology. 2015;23:133–140. doi:10.1016/j.mib.2014.11.011.

7. Taboada B, Estrada K, Ciria R, Merino E. Operon-mapper: A web server for precise operon identification in bacterial and archaeal genomes. Bioinformatics. 2018;34(23):4118–4120. doi:10.1093/bioinformatics/bty496.

8. Taboada B, Ciria R, Martinez-Guerrero CE, Merino E. ProOpDB: Prokaryotic operon database. Nucleic Acids Research. 2012;40(D1):627–631. doi:10.1093/nar/gkr1020.

9. Taboada B, Verde C, Merino E. High accuracy operon prediction method based on STRING database scores. Nucleic Acids Research. 2010;38(12). doi:10.1093/nar/gkq254.

10. Jensen LJ, Kuhn M, Stark M, Chaffron S, Creevey C, Muller J, et al. STRING 8 - A global view on proteins and their functional interactions in 630 organisms. Nucleic Acids Research. 2009;37(SUPPL. 1):412–416. doi:10.1093/nar/gkn760.

11. Tjaden B. A computational system for identifying operons based on RNA-seq data. Methods. 2020;176(April 2019):62–70. doi:10.1016/j.ymeth.2019.03.026.

12. Tomar TS, Dasgupta P, Kanaujia SP. Operon Finder: a deep learning-based web server for accurate prediction of prokaryotic operons. Journal of Molecular Biology. 2022; p. 167921.

13. He K, Zhang X, Ren S, Sun J. Deep Residual Learning for Image Recognition. In: 2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR); 2016. p. 770–778.

14. Okuda S, Yoshizawa AC. ODB: A database for operon organizations, 2011 update. Nucleic Acids Research. 2011;39(SUPPL. 1):552–555. doi:10.1093/nar/gkq1090.

15. Wattam AR, Abraham D, Dalay O, Disz TL, Driscoll T, Gabbard JL, et al. PATRIC, the bacterial bioinformatics database and analysis resource. Nucleic Acids Research. 2014;42(D1):581–591. doi:10.1093/nar/gkt1099.

16. Krishnakumar R, Ruffing AM. OperonSEQer: A set of machine-learning algorithms with threshold voting for detection of operon pairs using short-read RNA-sequencing data. PLoS Computational Biology. 2022;18(1):1–18. doi:10.1371/journal.pcbi.1009731.

17. Dehal PS, Joachimiak MP, Price MN, Bates JT, Baumohl JK, Chivian D, et al. MicrobesOnline: an integrated portal for comparative and functional genomics. Nucleic acids research. 2010;38(suppl_1):D396–D400.

18. Jensen PA. Ten species comprise half of the bacteriology literature, leaving most species unstudied. bioRxiv. 2025;doi:10.1101/2025.01.04.631297.

19. Haft DH, DiCuccio M, Badretdin A, Brover V, Chetvernin V, O'Neill K, et al. RefSeq: An update on prokaryotic genome annotation and curation. Nucleic Acids Research. 2018;46(D1):D851–D860. doi:10.1093/nar/gkx1068.

20. Leinonen R, Sugawara H, Shumway obotINSDC Martin. The Sequence Read Archive. Nucleic Acids Research. 2010;39(suppl-1):D19–D21. doi:10.1093/nar/gkq1019.

21. Leinonen R, Akhtar R, Birney E, Bower L, Cerdeno-Tárraga A, Cheng Y, et al. The European nucleotide archive. Nucleic acids research. 2010;39(suppl_1):D28–D31.

22. Jiang Z, Wang C, Wu Z, Chen K, Yang W, Deng H, et al. Enzymatic deamination of the epigenetic nucleoside N6-methyladenosine regulates gene expression. Nucleic Acids Research. 2021;49(21):12048–12068. doi:10.1093/nar/gkab1124.

23. Patrick Faßhauer JS, Busche T. RNAseq of *Bacillus subtilis* wildtype and cspB-cspD deletion mutant reveals that the lack of the cold shock proteins CspB and CspD affects the expression of about 20% of all genes; 2021. https://www.ebi.ac.uk/biostudies/arrayexpress/studies/E-MTAB-10658.

24. Keppel M, Hünnefeld M, Filipchyk A, Viets U, Davoudi CF, Krüger A, et al. HrrSA orchestrates a systemic response to heme and determines prioritization of terminal cytochrome oxidase expression. Nucleic Acids Research. 2020;48(12):6547–6562. doi:10.1093/nar/gkaa415.

25. Matthias Ruwe TB, Kalinowski J. Transcriptional analysis of regulatory effects in *Corynebacterium glutamicum* and a derived (p)ppGpp0 mutant strain; 2019. `https://www.ebi.ac.uk/biostudies/arrayexpress/studies/E-MTAB-8070`.

26. Kim D, Seo SW, Gao Y, Nam H, Guzman GI, Cho BK, et al. Systems assessment of transcriptional regulation on central carbon metabolism by Cra and CRP. Nucleic Acids Research. 2018;46(6):2901–2917. doi:10.1093/nar/gky069.

27. Guyet A, Dade-Robertson M, Wipat A, Casement J, Smith W, Mitrani H, et al. Mild hydrostatic pressure triggers oxidative responses in Escherichia coli. PLoS ONE. 2018;13(7):1–19. doi:10.1371/journal.pone.0200660.

28. Kumar S, Karmakar BC, Nagarajan D, Mukhopadhyay AK, Morgan RD, Rao DN. N4-cytosine DNA methylation regulates transcription and pathogenesis in Helicobacter pylori. Nucleic Acids Research. 2018;46(7):3429–3445. doi:10.1093/NAR/GKY126.

29. Charpentier X. RNAseq profiling of a lpp1663 mutant compared to its isogenic parent *Legionella pneumophila* strain Paris; 2020. `https://www.ebi.ac.uk/biostudies/arrayexpress/studies/E-MTAB-4095`.

30. Avican K, Aldahdooh J, Togninalli M, Mahmud AKMF, Tang J, Borgwardt KM, et al. RNA atlas of human bacterial pathogens uncovers stress dynamics linked to infection. Nature Communications. 2021;12(1). doi:10.1038/s41467-021-23588-w.

31. Luis Serrano MLS Raul Burgos, Weber M. RNA-seq of Lon and FtsH conditional mutants of *Mycoplasma pneumoniae* under depleting and inducing conditions; 2020. `https://www.ebi.ac.uk/biostudies/arrayexpress/studies/E-MTAB-8537`.

32. Campanaro S, Pascale FD, Telatin A, Schiavon R, Bartlett DH, Valle G. The transcriptional landscape of the deep-sea bacterium Photobacterium profundum in both a toxR mutant and its parental strain. BMC Genomics. 2012;13(1):1. doi:10.1186/1471-2164-13-567.

33. Differentiation B, Symbiotic S, Nicoud Q, Lamouche F, Chaumeret A, Balliau T, et al. Bradyrhizobium diazoef fi ciens USDA110 Nodulation of Aeschynomene afraspera Is Associated with Atypical Terminal. mSystems. 2021;6(3):1–19.

34. Chen S, Zhou Y, Chen Y, Gu J. Fastp: An ultra-fast all-in-one FASTQ preprocessor. Bioinformatics. 2018;34(17):i884–i890. doi:10.1093/bioinformatics/bty560.

35. Kim D, Paggi JM, Park C, Bennett C, Salzberg SL. Graph-based genome alignment and genotyping with HISAT2 and HISAT-genotype. Nature Biotechnology. 2019;37(8):907–915. doi:10.1038/s41587-019-0201-4.

36. Danecek P, Bonfield JK, Liddle J, Marshall J, Ohan V, Pollard MO, et al. Twelve years of SAMtools and BCFtools. GigaScience. 2021;10(2). doi:10.1093/gigascience/giab008.

37. Quinlan AR, Hall IM. BEDTools: a flexible suite of utilities for comparing genomic features. Bioinformatics. 2010;26(6):841–842. doi:10.1093/bioinformatics/btq033.

38. Singh SP, Sharma MK, Lay-Ekuakille A, Gangwar D, Gupta S. Deep ConvLSTM with Self-Attention for Human Activity Decoding Using Wearable Sensors. IEEE Sensors Journal. 2021;21(6):8575–8582. doi:10.1109/JSEN.2020.3045135.

39. Goodfellow I, Bengio Y, Courville A. Deep Learning. MIT Press; 2016.

40. Walsh I, Fishman D, Garcia-Gasulla D, Titma T, Pollastri G, ELIXIR Machine Learning Focus Group, et al. DOME: recommendations for supervised machine learning validation in biology. Nat Methods. 2021;18(10):1122–1127. doi:10.1038/s41592-021-01205-4.

41. Blumenthal T. Operons in eukaryotes. Brief Funct Genomic Proteomic. 2004;3(3):199–211. doi:10.1093/bfgp/3.3.199.

42. Ermolaeva MD, White O, Salzberg SL. Prediction of operons in microbial genomes. Nucleic acids research. 2001;29(5):1216–1221.

43. Kapoor S, Narayanan A. Leakage and the reproducibility crisis in machine-learning-based science. Patterns (N Y). 2023;4(9):100804. doi:10.1016/j.patter.2023.100804.

44. Bernett J, Blumenthal DB, Grimm DG, Haselbeck F, Joeres R, Kalinina OV, et al. Guiding questions to avoid data leakage in biological machine learning applications. Nat Methods. 2024;21(8):1444–1453. doi:10.1038/s41592-024-02362-y.

45. Demšar J. Statistical comparisons of classifiers over multiple data sets. The Journal of Machine learning research. 2006;7:1–30.

46. García S, Fernández A, Luengo J, Herrera F. Advanced nonparametric tests for multiple comparisons in the design of experiments in computational intelligence and data mining: Experimental analysis of power. Information Sciences. 2010;180(10):2044–2064. doi:https://doi.org/10.1016/j.ins.2009.12.010.

47. Pohlert T. PMCMRplus: Calculate Pairwise Multiple Comparisons of Mean Rank Sums Extended; 2024. Available from: `https://CRAN.R-project.org/package=PMCMRplus`.

48. Calvo B, Santafe G. scmamp: Statistical Comparison of Multiple Algorithms in Multiple Problems. The R Journal. 2016;8(1):248–256.