UITOTO: a new software for molecular diagnoses in species descriptions

Ambrosio Torres*[a], Leshon Lee[a,b], Amrita Srivathsan[a], and Rudolf Meier[a]

[a]*Center for Integrative Biodiversity Discovery, Leibniz Institute for Evolution and Biodiversity Science, Museum für Naturkunde, Invalidenstraße 43, 10115 Berlin, Germany;* [b]*Lee Kong Chian Natural History Museum, National University of Singapore, 2 Conservatory Dr, Singapore, 117377.*
Corresponding author: atorresgalvis@gmail.com

Abstract

Millions of species remain undescribed, requiring molecular and morphological diagnoses. However, no efficient software reliably derives and tests —state-specific and contrastive— molecular diagnoses. UITOTO addresses this gap by identifying, testing, and visualizing Diagnostic Molecular Combinations (DMCs). The software uses a weighted random sampling algorithm based on the Jaccard Index for building candidate DMCs. It then selects DMCs with the highest specificity stability, meeting user-defined thresholds for exclusive character states. If multiple optimal DMCs exist, it derives a majority-consensus DMC. UITOTO includes a validation module for testing DMCs against aligned or unaligned sequences. A user-friendly Shiny App GUI with an additional module for customizable publication-quality DMC visualizations is also available online and in RStudio. We assess UITOTO's performance by comparing its DMCs to those derived from a recent software (MOLD) for three large empirical datasets: i) genus *Megaselia* (69 species, 2,229 training and 30,289 testing barcodes); ii) family Mycetophilidae, (118 species, 1,456 training and 60,349 testing barcodes); and iii) European Lepidoptera (49 species, 591 training and 21,483 testing barcodes). Based on several classification metrics (*e.g.*, Accuracy, F1 Score), UITOTO's DMCs are more reliable, because MOLD's DMCs tend to be too short to be species-specific. Overall, we demonstrate that the biggest challenge for generating molecular and morphological diagnoses are the same. This is balancing specificity and length. Short diagnoses often lack specificity, while excessively long DMCs are often so specific that they do not accommodate intraspecific variation. We thus provide guidelines for generating molecular diagnoses, including detailed instructions for using UITOTO.

Introduction

Humans have always been interested in classifying and understanding diversity, relationships, and organization of the entities surrounding them (Llorente-Bousquets, 1990). For biological objects, this urge to classify was formalized hundreds of years ago and has recently become particularly important because biodiversity loss is one of the 10 most pressing problems of humanity for the next 10 years (World Economic Forum, 2025). Descriptive taxonomy forms the basis of these activities by delimiting distinct biological units as species. Scientists then utilize such basic units (*i.e.*, species) across various research fields, including ecological and evolutionary studies. The principles applied to the classification and designation of new taxa have evolved throughout time to incorporate newly accessible information, approaches, and regulations that enable scientists to communicate effectively about biodiversity in a standardized way (Llorente-Bousquets, 1990; Renner, 2016; Braby *et al.*, 2024). Since Linnaeus (1758), descriptive taxonomy has emphasized the importance of diagnostic features. Diagnoses are critical for accurately distinguishing species from their closest relatives based on their unique combinations of (traditionally) morphological characteristics and anatomical comparisons. Specifically, this process involves identifying homologous and distinctive features (*i.e.*, primary homology hypotheses: see Richter, 2005; Agnarsson & Coddington, 2008).

With the advent of integrative taxonomy, DNA sequences—along with other sources of information such as chromosome mapping, biochemical profiling, ecological data, and phylogeography—has begun to play a crucial role in taxonomic practice, providing a more comprehensive understanding of species boundaries (Meier, 2008; Ahrens *et al*., 2024; Janzen *et al*., 2017; Maltsev & Erst, 2023). However, despite advancements in DNA sequencing methods, the use of precise molecular diagnoses remains uncommon (Brower, 2010; Renner, 2016; Meier *et al*., 2022; Ahrens, 2024), although the International Commission on Zoological Nomenclature (ICZN) has recently emphasized the need for more rigorous criteria in species diagnoses for future editions of bionomenclature codes (Rheindt *et al*., 2023). The ICZN advocates that species diagnoses should be state-specific (explicitly incorporate detailed information on the character states of distinguishing molecular sites) and contrastive (comparing these states with those from similar species). Such guidelines aim to enhance taxonomic standards and ensure that all diagnoses, including those based on DNA, are appropriately contextualized by fulfilling these two ideal properties of diagnoses (Renner, 2016; Rheindt *et al*., 2023; Ahrens, 2024; Braby *et al*., 2024). In practical terms, a contrastive diagnosis should highlight distinguishing characters or character states by directly comparing at least one other species (*e.g.*, New Species 1 differs from Species 2 in two nucleotides at positions 25 and 69). In addition, state-specific diagnoses require the author not only to identify a distinguishing character but also to specify its character state (*e.g.*, New Species 1 has an Adenine [A] nucleotide at position 25 and a Guanine [G] at position 69, in contrast to Species 2, which has a Thymine [T] at position 25 and a Cytosine [C] at position 69) (see also Rheindt *et al.*, 2023). For this purpose, researchers could employ a Diagnostic Molecular Combination (DMC): a group of unique molecular character states that identify a particular species (analogous to a group of diagnostic morphological traits used in traditional taxonomy). To interpret the positions of these character states, a reference sequence must also be specified (e.g., the sequence of the holotype). Thus, following the previous example, one could express the DMC of the holotype of Species 1 as "`[25: A; 69: G]`", which is contrastable by using sequence alignments including other species.

Many approaches to generating molecular diagnosis fail to meet this gold standard (*i.e.*, contrastiveness and state-specificity) (Rheindt *et al.*, 2023). For instance, Sharkey *et al.* (2021) utilized consensus barcodes as taxonomic diagnoses. However, they neither indicate the diagnostic positions nor do they mention the states of the relevant positions (*i.e.*, nucleotides) (Fedosov *et al.*, 2022; Meier *et al.*, 2022; Rheindt *et al.*, 2023). Overall, this is akin to providing a fuzzy composite image of photographs of the same structure from several specimens. The structure may be potentially diagnostic, but the diagnostic features are not highlighted. This is undesirable and should be replaced with methods that generate robust DMCs that can be tested across diverse taxonomic contexts. This need has been addressed through the recent development of software and methods such as Cladistic Haplotype Aggregation (CHA. Brower, 1999), `Spider` (Brown *et al*., 2012); `BLOG` (Weitschek *et al*., 2013); `FASTACHAR` (Merckelbach & Borges, 2020); `QUIDDICH` (Kühn & Hasse, 2020); `DeSignate` (Hütter *et al*., 2020), `MOLD` (Fedosov *et al*., 2022), and `CAOS-R` (Sarkar *et al*., 2008; Bergmann, 2024). Two recent reviews have summarized the current state-of-the-art (Fedosov *et al*., 2022; Brower & DeSalle, 2024), so that we here opted to show particularly important differences in a table (Table 1). We would argue that all methods exhibit some undesirable properties that may explain why they are rarely used in species descriptions. For example, they all lack rigorous tools for DMC verification and may thus generate DMCs that are not species-specific. Furthermore, the existing software is neither user-friendly due to non-intuitive interfaces nor sufficiently efficient to yield DMCs for large numbers of species diagnosed based on thousands of sequences.

The main challenge with generating diagnoses, morphological or molecular, is the inherent trade-off between specificity and inclusivity. This also applies to Diagnostic Molecular Combinations (DMCs) (Fedosov *et al*., 2022; Rheindt *et al*., 2023). If a diagnosis is too specific or excessively detailed (*e.g.*, very long DMCs), it may fail to encompass intraspecific variability which can be extensive once spatial and temporal sampling increases for species. Conversely, if a diagnosis is too general or lacks sufficient characters (*e.g.*, very short DMCs), it may fit multiple species. Statistically and computationally, this trade-off translates into the need to manage the risks for false negatives (excluding specimens belonging to a species) and false positives (including specimens from another species). Brower (1999), Lim *et al*. (2012), and Fedosov *et al*. (2022) were, of course, well aware of these challenges and implemented algorithmic solutions that increased the reliability of the DMCs (see Fedosov *et al*., 2022). However, upon testing competing software packages, we found that they were still generating unreliable DMCs when analyzing datasets utilized in high-throughput taxonomy. These datasets typically contain data for hundreds of species that need to be diagnosed based on tens of thousands of sequences across different genera (see the Results and Discussion section below). Yet, such datasets are becoming more common as species discovery is scaled up to allow for holistic biodiversity monitoring (Amorim *et al*., 2024; Meier *et al*., 2024). Such large datasets will also become particularly common as the vast number of undescribed species in dark taxa are described (Srivathsan *et al*., 2019, 2023; Caruso *et al*., 2024).

Here, we introduce UITOTO, a user-friendly R package (R Core Team, 2024) specifically developed to tackle the challenges associated with finding, testing, and visualizing reliable Diagnostic Molecular Combinations (DMCs) in high-throughput taxonomy. We demonstrate that UITOTO produces reliable DMCs for most of the species in three different large empirical datasets: i) European Lepidoptera, with 49 species, 591 barcodes for training, and 21,483 for testing (Dincă *et al.*, 2021); ii) family Mycetophilidae (Diptera: Bibionomorpha), with 118 species, 1,456 barcodes for training (Amorim *et al.*, 2024), and 60,349 for testing (Ratnasingham & Hebert, 2007); and iii) genus *Megaselia* (Diptera: Phoridae), with DMCs for 69 species (Lee, 2023), comprising 2,229 barcodes in the training dataset and 30,289 in the testing dataset. This includes even many difficult species where balancing DMC length and specificity is particularly difficult. For these, we provide guidelines and instructions for running UITOTO.

Materials and Methods

1. Description of the UITOTO R package

UITOTO (**U**ser **I**n**T**erface for **O**ptimal molecular diagnoses in high-throughput **T**ax**O**nomy) is an R package (R Core Team, 2024) suitable for all major operating systems that facilitates the discovery, testing, and visualization of optimal Diagnostic Molecular Combinations (DMCs) from datasets with thousands of sequences. The name UITOTO is a tribute to the indigenous Uitoto (also Huitoto or Witoto) people of the Colombian-Peruvian Amazon, whose deep understanding of biodiversity and commitment to preserving their natural environment in the face of the challenges they face (deforestation, illegal mining, loss of land, etc.) inspired the first author in advancing biodiversity research. UITOTO can be downloaded from its GitHub repository (at https://github.com/atorresgalvis/UITOTO) or directly installed by entering the following commands into the R console:

```
install.packages("devtools")
library(devtools)
devtools::install_github("atorresgalvis/UITOTO")
```

The software requires the pre-installation of some additional R packages such as Biostrings (Pagès *et al.*, 2024), DECIPHER (Wright, 2016), dplyr (Wickham *et al.*, 2023), ggplot2 (Wickham, 2016), readr (Wickham *et al.*, 2024), SeqinR (Charif & Lobry, 2007), shiny (Chang *et al.*, 2024), shinyjs (Attali, 2021), and shinyWidgets (Perrier *et al.*, 2024). Therefore, we recommend following the instructions of the UITOTO repository in GitHub. In addition to the conventional command-driven interface, UITOTO features a user-friendly Shiny app (Chang *et al.*, 2024) accessible online (Figure 1. https://atorresgalvis.shinyapps.io/MolecularDiagnoses/) or locally in RStudio (Posit team, 2023). The UITOTO repository in GitHub also includes a comprehensive user manual that introduces the three main modules:

a)

b)

Figure 1. a) UITOTO Shiny app home page. Available at https://atorresgalvis.shinyapps.io/MolecularDiagnoses/. b) Module "Visualization of DMCs" of the Shiny app. See also the GitHub repository of UITOTO at https://github.com/atorresgalvis/UITOTO

Module 1: Identification of Diagnostic Molecular Combinations (DMCs)

This is the core module of `UITOTO` and responsible for identifying optimal DMCs. Users can start the DMC searches by activating "Find Diagnostic Molecular Combinations (DMCs)" in the `UITOTO Shiny` app. Alternatively, they can use the `OpDMC` function included in the package. This method assigns a weight to each site based on the Jaccard index of similarity, which measures the number of sequences that differ from the query taxon (*e.g.*, sequences of a new taxon) for the nucleotide at this site (Jaccard, 1908). The function then employs a Weighted Random Sampling approach to construct candidate combinations for DMCs. Sites with higher uniqueness values are then more likely to be included in the candidate DMCs (Figure 2). Fedosov *et al.*, (2022) also use in `MOLD` the Jaccard index of similarity to measure the uniqueness (in their terms, "score") of the sites. However, it does not use a Weighted Random Sampling approach for building the candidate combinations. Instead, "*The scores are then ranked in descending order and the user defines how many of the top-ranking sites are used for assembling a draft combination*" (Fedosov *et al.*, 2022). This approach could present a potential problem when dealing with multiple ties, as several sites could have the same weights (or scores), and as a consequence, some sites with high uniqueness values might not be sampled at all if they fall below the user-defined threshold.

User input required is the minimum number of exclusive character states (*i.e.*, nucleotides) to select optimal combinations from candidate DMCs. For example, specifying a minimum of two exclusive character states means that an optimal DMC must differ by at least two sites from the DMC of all other species (Figure 2). This criterion ensures significant differentiation from other taxa while using a higher number may invalidate a DMC when additional intraspecific sequence variability is found in the future. This approach is analogous to the well-known Bremer support measure used in phylogenetic inference, which quantifies the number of extra steps required to break a tree node (Bremer, 1994). For the purposes of molecular diagnoses, `UITOTO` applies a similar principle by considering the number of extra nucleotide matches needed to break the specificity of a DMC (Figure 2).

Next, the software identifies those sites that are most frequently included in DMCs that meet the preceding criterion of having a minimum number of exclusive character states. These sites are then used to build one final majority-consensus DMC for each species, which is confirmed to meet the user-specified exclusivity criterion. As output, `UITOTO` generates a CSV file containing the final identified DMCs. In addition, it randomly selects one of the optimal combinations as an alternative DMC for each species. Users can adjust various settings to control the DMC search process, including the number of candidate DMCs to test (*i.e.*, iterations), the minimum required length for the DMCs, and the DMC minimum number of exclusive characters states (see the instructions in the GitHub repository and the package manual).

Figure 2. The fundamental algorithmic process utilized by UITOTO to identify optimal Diagnostic Molecular Combinations (DMCs). The queries represent the entities to be diagnosed, such as new species to be described.

Module 2: Verification of DMCs and their use for specimen identification

The verification tool allows the user to test DMCs against user-supplied data from private or public databases. This tool is also accessible via both the `Shiny` app's graphical interface (under the module "Taxonomic verification and identification using DMCs for aligned and unaligned sequences") and the command-line version, which integrates three different functions included in the package: `ALnID`, `Identifier`, and `IdentifierU`.

The `Identifier` function compares DMCs against a set of sequences and identifies those that match the DMCs. It generates a detailed output file that highlights which sequence is a match. In contrast, the `ALnID` function employs dynamic programming (a variation of the Needleman & Wunsch [1970] algorithm for global alignment) from the `R` package `DECIPHER` (Wright, 2016) to align unaligned sequences from a FASTA file with the sequences used to derive the DMCs. It then operates similarly to the previously described `Identifier` function. Lastly, the `IdentifierU` function employs an alignment-free approach, using a dynamic sliding window to iteratively compare DMCs with different parts of individual sequences. This function allows users to set a mismatch threshold and thus to enhance flexibility in taxonomic identification and verification (see the available instructions in the GitHub repository and the package manual).

Such a testing module for DMCs is only included in `UITOTO` and is essential for evaluating the reliability of the DMCs via cross-validation. By comparing the identified specimens with known taxonomic assignments, users can validate the accuracy and robustness of each DMC. This validation process aids in refining and optimizing the selection criteria for DMCs, ensuring their efficacy across diverse datasets and taxonomic groups.

Module 3: Visualization of DMCs

This module enables users to generate detailed and customizable publication-quality DMC comparisons through interactive features available in the "Visualization of DMCs" module. It is accessible via the graphical user interface of the package (*i.e.*, the `UITOTO Shiny` app) and enhances the interpretation and communication of DMCs dispersed over long DNA sequences (Figure 1b).

2. Performance test of `UITOTO` versus `MOLD`

Test data sets

- For the first case, we used a published DNA barcode library that covers 97% of the 459 species of European Lepidoptera (hereafter, *European Butterflies*. Dincă *et al.*, 2021). We extracted the data for the 49 United Kingdom (UK) butterflies species and then derived the DMCs (591 aligned Cytochrome Oxidase I [COI] sequences. Called the "*European butterflies training dataset*"). To assess the performance of the DMCs based on UK data, we used all European data ("*European butterflies testing dataset*") comprising 21,483 unaligned sequences of the butterfly species presented in the rest of Europe. The barcode lengths ranged from 113 to 1,498 base pairs (bp) (mean = 656 bp).

- The second dataset is from a recently published monograph of Mycetophilidae (Diptera: Bibionomorpha) from Singapore (Amorim *et al.*, 2024) that delimits 120 species. To identify the DMCs, we used a dataset comprising 1,456 aligned COI

minibarcodes of 118 species (313 bp: called the "*Mycetophilidae training dataset*"). We evaluated the resulting DMCs against a dataset of 60,349 unaligned Mycetophilidae sequences from The Barcode of Life Data System (BOLD; Ratnasingham & Hebert, 2007: "*Mycetophilidae testing dataset*"). The length of the sequences in the latter ranged from 498 to 658 base pairs (mean = 605).

- The third study describes 69 new species of the genus *Megaselia* (Diptera: Phoridae) from Sentosa Island, Singapore (Lee, 2023). DMCs are proposed based on 2,229 aligned COI sequences (hereafter, the "*Megaselia training dataset*"). To evaluate the reliability of the DMCs for the 69 new species, we employed an additional dataset of 30,289 aligned Phoridae sequences from other parts of Singapore and Indonesia (hereafter, the "*Megaselia testing dataset*"). Both datasets consisted of minibarcodes with a length of 313 base pairs.

This selection of datasets allows us to evaluate UITOTO's performance and robustness across different taxonomic and methodological challenges. For instance, the European butterflies dataset, a nearly complete, well-studied, and curated barcode library, provides a particularly rigorous test case. By deriving DMCs from the UK species and evaluating them against the broader European dataset, we simulate the effects of increased sequencing effort, which not only reveals greater intraspecific variability but also introduces sequences from additional species. This expansion can challenge the specificity of DMCs in two ways: increased intraspecific variability may cause them to lose their ability to recognize conspecific specimens, while the inclusion of more species may lead to erroneous recognition of heterospecifics. In contrast, the Mycetophilidae and *Megaselia* datasets exemplify large-scale species descriptions for incompletely known faunas, where barcode libraries are still expanding. These datasets allow us to assess how UITOTO performs in newly described taxa with varying degrees of taxonomic uncertainty. Additionally, our testing strategy incorporates both aligned and unaligned sequences, reflecting the reality of publicly available barcode data, which often vary greatly in length and require complex alignment procedures.

Obtaining Diagnostic Molecular Combinations (DMCs)

To assess the performance of UITOTO, we compared it to MOLD (Fedosov *et al.*, 2022) and indirectly to BLOG (Weitschek *et al.*, 2013). The latter became necessary because it was not discussed in Fedosov *et al.* (2022), which mostly showed that MOLD outperformed DeSignate (Hütter *et al.*, 2020) for medium- and high-complexity datasets (Fedosov *et al.*, 2022). To assess whether BLOG would have fared better when compared with MOLD, we generated MOLD and BLOG DMCs for our third dataset (*Megaselia*) using the default settings (available at https://github.com/SashaFedosov/MolD/blob/master/MolD_parameters.txt and http://dmb.iasi.cnr.it/blog.php, respectively). We found that MOLD greatly outperformed BLOG (see Supplementary Table S1, Supplementary Material online) so that we dropped BLOG from our tests of UITOTO.

For our performance evaluation of MOLD and UITOTO, we obtain DMCs from UITOTO by varying the search settings in the OpDMD function (see above and the package manual). All searches treated gaps as missing data and employed 50,000 iterations (number of candidate DMCs to prove) and a refinement strength of 0.33. The refinement strength, which ranges from 0 to 1, controls the proportion of sub-combinations —from each optimal DMC— that the function tests. The higher the refinement strength, the greater the likelihood of identifying

shorter DMCs (though this also increases the computational time). Each run had its own set of defined parameters to control the minimum length of the DMCs (**MnLen**) and their minimum number of exclusive character states (**exclusive**. See Figure 2). Therefore, the basic command we used can be summarized as follows:

```
OpDMC("Alignment.fasta", "Queries.csv", iter = 50000, MnLen =
2, exclusive = 2, RefStrength = 0.33, OutName =
"OutputFile.csv", GapsNew = FALSE)
```

In total, we conducted seven searches. For three of these, we fixed the minimum length of the DMCs to six (*i.e.*, **MnLen = 6**) and varied the number of exclusive character states to two, three, and four (*i.e.*, **exclusive = 2, 3**, and **4**, respectively). For the remaining three searches, we retained the same number of exclusive character state settings (*i.e.*, **exclusive = 2, 3**, and **4**, respectively) but allowed the **MnLen** to vary freely; i.e., the minimum possible length of a DMC obtained with **exclusive = 2** was also two. When the user sets an **exclusive** value higher than the **MnLen** value, the function automatically adjusts **MnLen** to match the **exclusive** value, thus also allowing the minimum length to vary freely. Finally, we conducted one search with a minimum length of ten (*i.e.*, **MnLen = 10**) and set the number of exclusive character states to four (*i.e.*, **exclusive = 4**).

The Supplementary Material online contains the scripts we used in this study. It also provides detailed instructions for identifying the DMCs in UITOTO (ScriptSearchDMC.R). For comparison with MOLD, we used the default settings of this software, which are identical to those used in Fedosov *et al*. (2022: section 2.3.1). While it is true that MOLD allows for adjusting additional parameters, when it comes to DMC length, the software only allows setting a maximum length while it does not permit specifying a minimum length or a minimum number of exclusive character states. In contrast, UITOTO allows fine-tuning both parameters, providing greater flexibility in optimizing DMCs. This is a major advantage, because our results demonstrate that MOLD tends to produce short DMCs (see Discussion and Conclusions section below) lacking specificity. Consequently, even if MOLD's available settings were adjusted, this would not lead to a significant improvement in DMC quality, as its optimization criteria inherently favor shorter DMCs.

Testing the reliability of DMCs

To test the reliability of the DMCs, we used two UITOTO functions depending on whether the test sequences were aligned (Identifier) or unaligned (ALnID). The Identifier function was applied to the *Megaselia* test dataset while the two other data sets were analyzed with AlnID, because they included unaligned sequences. The latter function first aligns the sequences of the testing dataset with those used to derive the DMCs (*i.e.*, those from the training dataset) and then operates similarly to the Identifier function. In all cases, we conducted the cross-validation analyses using two different tolerances: one allowing up to one mismatch between the DMCs and the sequences and the other with zero tolerances for mismatches (see the script ScriptIdentification.R in the Supplementary Material online). For clarity and conciseness, we present only the results allowing for up to one mismatch, as the zero-tolerance scenario produced qualitative the same patterns across all three datasets examined (see Supplementary Table S2, Supplementary Material online).

To summarize the results, we developed the R function ConfuClass (provided in the Supplementary Material online as ConfuClass.R). It processes the output files from the

`ALnID` and `Identifier` functions to generate confusion matrices and classification metrics, including precision, recall, specificity, accuracy, and F1 score (see below for the equations). The `ConfuClass` function detects when sequences to be identified contain missing data at the DMCs sites and excludes them from the calculations. Additionally, if no query species sequences were present in the testing datasets (used to assess the performance of the DMCs), only the "Specificity" metric was evaluated, as the number of true positives and false negatives could not be determined. These metrics, commonly used in machine learning techniques (*e.g.*, discriminant analysis) and deep learning, provide valuable insights into the effectiveness of classification models (Figure 3). "Recall" refers to the proportion of correctly identified specimens out of all the specimens that belong to a particular species. For example, a recall of 50% indicates that the DMC was only able to assign a species label to half of the test specimens from the species. "Precision" indicates the proportion of specimens that was identified to have been correctly identified, i.e., long diagnoses tend to suffer from low recall but have high precision. "Specificity" refers to the proportion of specimens correctly identified as not belonging to a particular species, i.e., it indicates how well a DMC can avoid false positives for a given species. DMCs with high recall often have low specificity because they are so general that they assign the same species-label to multiple species. Finally, the F1 score combines precision and recall into a single metric. In our case, the metrics are calculated for each DMC corresponding to an individual species, ensuring a tailored assessment of the performance for each species (see the file `ScriptConfuClassi.R` in the Supplementary Material online).

Figure 3. Comparison of the performance of commonly used metrics (F1 Score, Recall, Precision, Accuracy, and Specificity) in classification techniques, applied to a hypothetical dataset of 69 specimens across four species. Green silhouettes: correctly identified specimens; red silhouettes: misidentified specimens; gray silhouettes: unclassified specimens. Insect silhouette images sourced from https://www.phylopic.org/.

In evaluating the performance of the software packages, we focus on **F1** and **accuracy** as they summarize the performance values obtained across all metrics. However, detailed results for all metrics are available in the Supplementary Material online (Supplementary Tables S2-S3).

Additionally, it is worth noting that the F1 Score is arguably preferable over accuracy for datasets where a few species are very common and have a lot of sequences while most are only represented by 1-2 barcodes. The F1 Score is less sensitive to such imbalances (*i.e.*, a high probability of having many more true negatives than true positives). For example, the DMC for species A in Figure 3 performs particularly well. This is expressed by the F1 score, while Accuracy for species A and B is very similar although the DMC for species B leads to 9 false positives.

- Recall = True Positives / (True Positives + False Negatives)
- Precision = True Positives / (True Positives + False Positives)
- Specificity = True Negatives / (True Negatives + False Positives)
- Accuracy = (Recall + Specificity) / 2
- F1 Score = 2 * (Precision * Recall) / (Precision + Recall)

Results

The F1 Score results across the European butterflies, Mycetophilidae, and *Megaselia* datasets revealed two patterns (Figure 4): i) the Diagnostic Molecular Combinations (DMCs) generated by `UITOTO` (see the values below) were generally more reliable than those obtained from `MOLD` (F1Score average = 0.20–0.63), and ii) longer DMCs consistently produced higher F1 Scores across all analyses. Specifically, we observed that F1 Scores increased with both parameters we used for controlling DMC lengths in `UITOTO`. The highest F1 Scores were obtained by setting a fixed Minimum Length (`MnLen`) of DMCs to ten nucleotides (on average 0.72–0.97), followed by a `MnLen` of six nucleotides (on average 0.56–0.94), with the lowest F1 Scores resulting when we allowed the `MnLen` to vary freely (on average 0.09–0.92). Additionally, we observed a positive correlation between the number of exclusive character states (*i.e.*, `exclusive`) and F1, a pattern particularly evident when we allowed the `MnLen` to vary freely (Figure 4; see also Supplementary Tables S2-S3, Supplementary Material online).

The use of Accuracy as evaluation criterion yielded somewhat different results (Supplementary Information S1, Supplementary Material online). As shown in Figure 3 (compare species A and B), Accuracy carries a low penalty for generating false positives (assigning the wrong specimens to a species). Not surprisingly, short DMCs thus then to have higher Accuracy values. Despite this, the generally short DMCs of `MOLD` did not consistently outperform those generated by `UITOTO` (see Supplementary Tables S2-S3, Supplementary Material online). Instead, the Accuracy values of `MOLD` (on average 0.956–0.992) were comparable to or even lower than those obtained with `UITOTO` when the `MnLen` was allowed to vary freely (0.897–0.996) or set to short lengths by specifying a low number of exclusive character states (*e.g.*, 0.880–0.988 with `exclusive = 2`). This is particularly pronounced for European butterflies and *Megaselia* datasets (Supplementary Table S3, Supplementary Material online).

Regarding the remaining metrics, we observe that short DMCs also favor Recall, while longer DMCs tend to yield higher Precision and Specificity (Supplementary Information S2-S4, Supplementary Material online. See also Figure 3). Overall, the performance of the DMCs from the Mycetophilidae dataset was less satisfying than those observed for the European butterflies and *Megaselia* datasets (Figure 4; Supplementary Information S1-S4 and Supplementary Tables S2-S3, Supplementary Material online). We suspect that this is due to high intraspecific sequence variability in the delimited species (Amorim *et al.*, 2024; Meier *et*

al., 2025). It is important to note that the performance of DMCs from different groups (such as *Megaselia*, Mycetophilidae, and European butterflies) cannot be directly compared. As mentioned in the Discusion and Conclusions section, the inclusion of sequences in the training and testing datasets must consider the specific characteristics and scope of each dataset, as intraspecific and interspecific variations can differ among groups. However, we briefly compared the overall performance of DMCs across these three groups to highlight the subtleties involved in identifying optimal DMCs through the use of software like UITOTO.

Discussion and Conclusions

Our empirical tests based on three datasets with different properties reveal that UITOTO produces more reliable Diagnostic Molecular Combinations (DMCs) than the currently available software such as MOLD (Fedosov *et al*., 2022) and BLOG (Weitschek *et al*., 2013). Note that the three different datasets represented different challenges. The European butterfly dataset has dense coverage of species and intraspecific variability and is best suited to test whether molecular diagnoses are feasible for a taxonomically very well-known taxon like European butterflies. In contrast, the *Megaselia* (Phoridae) and the mycetophilid datasets represent poorly known "dark taxa" with more than 90% of the species-level diversity being undescribed. One dataset pertains to a taxon with low intraspecific sequence variability (*Megaselia*), while the other is characterized by high intraspecific variability (Amorim *et al.*, 2024; Meier *et al.*, 2025). Yet, UITOTO seems to be doing comparatively well for all three datasets. This is because MOLD tends to generate short DMCs, which enhances the detection of query species but also leads to a significant number of false positives (*i.e.*, erroneous species identifications or incorrect taxonomic assignments. See Figure 3). For example, the DMCs obtained by MOLD for *Megaselia* ranged in length from two to six sites (average = 3.5). This was similar to what was found with UITOTO when the MnLen was allowed to vary freely (DMCs ranged from two to five sites; average = 3.1). However, using UITOTO for deriving DMCs with two exclusive states yielded DMC with a length of 3-8 sites (average = 4.6), which increased to 5-11 sites (average = 4.6) when requiring four exclusive states.

This preference for shorter DMCs results in considerably lower F1 Scores for MOLD, while UITOTO's longer DMCs yield higher F1 Scores, presumably being better at balancing precision, specificity, and recall (see Figure 3). This also leads to better results when identifying sequences using DMCs (Figure 4). Since MOLD only allows for setting maximum lengths of the DMCs (which can lead to excessively short DMCs, as mentioned above), its performance could theoretically be improved by incorporating a parameter to control the minimum DMC length. However, MOLD would still lack the option to define the number of exclusive character states in each species-specific DMC. This feature directly assesses the DMC performance while MOLD uses simulations to generate sequences with introduced mutations to test the robustness of the DMCs. In addition, the ability to set the number of exclusive sites indirectly controls DMC length (*e.g.*, a DMC with four exclusive character states cannot have fewer than four sites). The dual control over specificity and length takes place simultaneously with the generation of DMC candidates, reducing the likelihood of false positives and false negatives. Additional benefits of UITOTO are the verification module that evaluates the reliability of DMCs and the visualization module for obtaining publication-ready diagnoses (also unavailable in the new version of MOLD at https://itaxotools.org/index.html).

Figure 4. F1 Score of the Diagnostic Molecular Combinations (DMCs) from MOLD and UITOTO for the three datasets. Each point represents a query species. Due to overlap, the blue numbers indicate the number of species with values greater than (>) 0.99, while the red numbers indicate those with values less than (<) 0.10. The number of exclusive character states and MnLen (minimum length of the DMCs) are settings available in UITOTO (*i.e.*, not applicable for MOLD).

The new features of UITOTO address the challenge of managing the trade-off between overly detailed diagnoses that may exclude some specimens and overly general ones that might include non-members, thereby hopefully avoiding the generation of unreliable DMCs (see Figures 3–4). However, we reiterate a crucial point: users must test multiple settings during the DMC searches to achieve optimal DMCs. For example, one could start by using four exclusive character states, and ten nucleotides as the minimum DMC length, since these settings often yield better outcomes. Subsequently, for some species, it may be necessary to explore other settings to capture genetic variation more effectively. For example, we observed that optimal DMCs (*i.e.*, high F1 Scores) were hard to achieve for the Mycetophilidae (Figure 4). This should not surprise because we observed high intraspecific variability in Mycetophilidae. Indeed, taxonomists are used to the fact that morphological diagnoses have to reflect different levels of intraspecific variability in different taxa. This is the same for DMCs. Different settings should be explored and are needed especially for 'recalcitrant' species with high intraspecific variability and low differentiation to closely related species. Amorim *et al*. (2024) achieved optimal DMCs for their new Mycetophilidae species using this

strategy (mean F1 Score = 0.92; mean accuracy = 0.99). In addition, all of our analyses point to the need to combine DMCs obtained from COI with diagnostic markers from other character systems (e.g., morphology, other genes). Indeed, it is well known that some species share DNA barcodes (Meier, 2008) but it seems likely that species with high intraspecific COI variability and low interspecific differentiation may not have DMCs.

To rigorously derive DMCs, we therefore introduced a cross-validation module. It reveals that certain species belonging to the *Megaselia* and European Butterflies datasets yielded DMCs with low F1 Scores (*e.g.*, < 0.75). A detailed analysis using the Basic Local Alignment Search Tool (BLAST. Camacho *et al.*, 2009) revealed that this was particularly common for those species with high intraspecific variability and small barcode gaps—defined here as the difference between the distributions of inter- and intraspecific genetic identities or distances (see Figure 5). Note, however, that in some cases the identification and classification of unknown sequences based on DMCs remains effective. In fact, we identified several species, where BLAST failed to yield identification at a reasonably identity threshold (*e.g.*, 99%), while DMC-based methods still delivered a high F1 Score (see Figure 5). This highlights that the currently well entrenched habit of identifying specimens with BLAST should be complemented with specimen identification with DMCs.

Figure 5. Comparison of classification results from Diagnostic Molecular Combinations (DMCs) and the Basic Local Alignment Search Tool (BLAST. Camacho *et al.*, 2009). The performance of the

DMCs was evaluated using the F1 Score, while `BLAST` performance was assessed by the percentage of identical nucleotides between two sequences (identity percentage).

Overall, our data highlight the importance of sampling. Reliable DMCs will be elusive when the sequence diversity in the training dataset is artificially low due to insufficient sampling. This is analogous to morphological diagnoses whose accuracy are heavily dependent on sampling for variable species or species that have many close relatives. This is one reason why we recommend to also use sequences from non-query taxa as part of the testing datasets rather than relying solely on sequences of the queried species (as suggested by Weitschek *et al*., 2013). Dense taxon sampling helps with mitigating the risk of obtaining DMCs that yield false positives with poorly designed DMCs that were constructed using too few sequences. For example, including species from other genera within the tribe or family to which your query species belong will strengthen the test.

Most of the issues discussed here will be familiar and uncomfortable territory for all taxonomists with extensive experience in generating diagnoses. There are no standards for the number of characters that should be included in a morphological diagnosis of a new species. Furthermore, new species with numerous closely related congeners are likely to be diagnosed with more characters (=exclusive states) than species belonging to highly distinct monotypic genera. In this sense, it may be challenging to set an appropriate number of exclusive character states, but this challenge is unavoidable. For example, if a species has several close relatives, one could start by testing a higher number of exclusive character states compared to those used for monotypic genera. In addition, one could consider using a percentage-based approach, where the number of exclusive character states reflects the percentage difference needed to distinguish species—such as 1% or 3%. However, this raises questions about the appropriate percentage to select, similar to the challenge in integrative taxonomy when delimiting species (e.g., should one use 1% or 3% genetic divergence? How about 5%?). Our advice is thus to test various settings for each species and evaluate the optimality of the DMCs based on performance metrics like accuracy and F1 Score. This approach allows researchers to make informed decisions without relying on a universal standard for the number of exclusive character states. Importantly, finding DMCs with higher F1 Scores under different settings imply these DMCs are better at balancing precision and recall. Such DMCs should be preferred because a large number of false positives adds to the workload of taxonomists which then have to remove big amounts of incorrectly identified specimens. Conversely, false negatives require only 'unidentified' specimens be reviewed, allowing researchers to focus on a manageable subset of sequences struggling with identification.

We believe that `UITOTO` currently provides the most robust and intuitive platform for identifying, testing, and visualizing DMCs for taxonomy. The `Shiny` app interface integrated into our package extends beyond traditional command-line tools, offering a user-friendly way to perform complex analyses and generate high-quality visualizations without needing coding knowledge. This flexibility supports a broad range of empirical and theoretical studies and addresses the need for effective molecular diagnostics across diverse taxonomic contexts, ensuring transparency and reproducibility.

Acknowledgments

We sincerely thank Vivan Feng, Duniesky Ríos-Tamayo, Liliya Serbina, and Ronniel Pedales for their valuable suggestions and thoughtful feedback on the early versions of this article.

References

Agnarsson, I., Coddington, J.A. (2008). Quantitative tests of primary homology. *Cladistics*, 24(1), 51–61. https://doi.org/10.1111/j.1096-0031.2007.00168.x

Ahrens, D., Fabrizi, S., Šipek, P., Lago, P.K. (2013). Integrative analysis of DNA phylogeography and morphology of the European rose chafer (*Cetonia aurata*) to infer species taxonomy and patterns of postglacial colonisation in Europe. *Molecular Phylogenetics and Evolution*, 69(1), 83–94. https://doi.org/10.1016/j.ympev.2013.05.016

Ahrens, D. (2024). Species diagnosis and DNA taxonomy. In: DeSalle, R. (eds) DNA barcoding. Methods in Molecular Biology, vol 2744. Humana, New York, NY. https://doi.org/10.1007/978-1-0716-3581-0_2

Amorim, D.S., Oliveira, S.S., Balbi, M.I.P.A., Ang, Y., Torres, A., Yeo, D., Srivathsan, A., Meier, R. (2024). An integrative taxonomic treatment of the Mycetophilidae (Diptera: Bibionomorpha) from Singapore reveals 115 new species on 730 km². *Integrative Systematics: Stuttgart Contributions to Natural History*, *in press*.

Attali, D. (2021). `shinyjs`: easily improve the user experience of your Shiny apps in seconds. R package version 2.1.0. https://CRAN.R-project.org/package=shinyjs

Bergmann, T. (2024). `CAOS-R`: character-based barcoding. In: DeSalle, R. (eds) DNA Barcoding. Methods in Molecular Biology, vol 2744. Humana, New York, NY. https://doi.org/10.1007/978-1-0716-3581-0_22

Braby, M.F., Hsu, Y-F., Lamas, G. (2024). How to describe a new species in zoology and avoid mistakes. *Zoological Journal of the Linnean Society*, *in press*. https://doi.org/10.1093/zoolinnean/zlae043

Bremer, K. (1994). Branch support and tree stability. *Cladistics*, 10(3), 295–304. https://doi.org/10.1111/j.1096-0031.1994.tb00179.x

Brower, A.V.Z. (1999). Delimitation of phylogenetic species with DNA sequences: a critique of Davis and Nixon's population aggregation analysis. *Systematic Biology*, 48(1), 199–213. http://www.jstor.org/stable/2585276

Brower, A.V.Z. (2010). Alleviating the taxonomic impediment of DNA barcoding and setting a bad precedent: names for ten species of 'Astraptes fulgerator' (Lepidoptera: Hesperiidae: Eudaminae) with DNA-based diagnoses. *Systematics and Biodiversity*, 8(4), 485–491. https://doi.org/10.1080/14772000.2010.534512

Brower, A.V.Z., DeSalle, R. (2024). DNA Barcodes in Taxonomic Descriptions. In: DeSalle, R. (eds) DNA Barcoding. Methods in Molecular Biology, vol 2744. Humana, New York, NY. https://doi.org/10.1007/978-1-0716-3581-0_5

Brown, S.D.J., Collins, R.A., Boyer, S., Lefort, M.-C., Malumbres-Olarte, J., Vink, C.J., Cruickshank, R.H. (2012). `Spider`: an R package for the analysis of species identity and evolution, with particular reference to DNA barcoding. *Molecular Ecology Resources*, 12(3), 562–565. https://doi.org/10.1111/j.1755-0998.2011.03108.x

Camacho, C., Coulouris, G., Avagyan, V., Ma, N., Papadopoulos, J., Bealer, K., Madden, T.L. (2009). `BLAST+`: architecture and applications. *BMC Bioinformatics*, 10, 421. https://doi.org/10.1186/1471-2105-10-421

Caruso, V., Hartop, E., Chimeno, C., Noori, S., Srivathsan, A., Haas, M., Lee, L., Meier, R., Whitmore, D. (2024). An integrative framework for dark taxa biodiversity assessment at scale: A case study using *Megaselia* (Diptera, Phoridae). *Insect Conservation and Diversity*, 17(6), 968–987. https://doi.org/10.1111/icad.12762

Chang, W., Cheng, J., Allaire, J., Sievert, C., Schloerke, B., Xie, Y., Allen, J., McPherson, J., Dipert, A., Borges, B. (2024). `Shiny`: web application framework for R. R package version 1.8.1.1, https://CRAN.R-project.org/package=shiny

Charif, D., Lobry, J. (2007). `SeqinR 1.0-2`: a contributed package to the `R` project for statistical computing devoted to biological sequences retrieval and analysis. In Bastolla, U., Porto, M., Roman, H., Vendruscolo, M. (eds.), Structural approaches to sequence evolution: Molecules, networks, populations, series Biological and Medical Physics, Biomedical Engineering, 207–232. Springer Verlag, New York. ISBN : 978-3-540-35305-8.

Dincă, V., Dapporto, L., Somervuo, P., Vodă, R., Cuvelier, S., Gascoigne-Pees, M., Huemer, P., Mutanen, M., Hebert, P. D. N., Vila, R. (2021). High resolution DNA barcode library for European butterflies reveals continental patterns of mitochondrial genetic diversity. *Communications Biology*, 4, 315. https://doi.org/10.1038/s42003-021-01834-7

Fedosov, A., Achaz, G., Gontchar, A., Puillandre, N. (2022). `MOLD`, a novel software to compile accurate and reliable DNA diagnoses for taxonomic descriptions. *Molecular Ecology Resources*, 22(5), 2038–2053. https://doi.org/10.1111/1755-0998.13590

Hütter, T., Ganser, M.H., Kocher, M., Halkic, M., Agatha, S., Augsten, N. (2020). `DeSignate`: detecting signature characters in gene sequence alignments for taxon diagnoses. *BMC Bioinformatics*, 21, 151. https://doi.org/10.1186/s12859-020-3498-6

Jaccard, P. (1908). Nouvelles recherches sur la distribution florale. *Bulletin de la Société vaudoise des Sciences Naturelles*. 44, 223–270.

Janzen, D.H., Burns, J.M., Cong, Q., Hallwachs, W., Dapkey, T., Manjunath, R., Hajibabaei, M., Hebert, P.D.N., Grishin, N.V. (2017). Nuclear genomes distinguish cryptic species suggested by their DNA barcodes and ecology. *Proceedings of the National Academy of Sciences*, 114(31), 8313–8318. https://doi.org/10.1073/pnas.1621504114

Kühn, A.L., Haase, M. (2020). `QUIDDICH`: QUick IDentification of DIagnostic CHaracters. *Journal of Zoological Systematics and Evolutionary Research*, 58, 22–26. https://doi.org/10.1111/jzs.12347

Lee, L. (2023). Experimental Integrative Taxonomy: Tackling dark taxa in the tropics (Master's Thesis). National University of Singapore.

Lim, G.S., Balke, M., Meier, R. (2012). Determining species boundaries in a world full of rarity: singletons, species delimitation methods. *Systematic Biology*, 61(1), 165–169. https://doi.org/10.1093/sysbio/syr030

Linnaeus, C. (1758). Systema Naturae per regna tria naturae, secundum classes, ordines, genera, species, cum characteribus, differentiis, synonymis, locis. Tomus I. Editio decima, reformata. Holmiae: Laurentius Salvius.

Llorente-Bousquets, J. (1990). La búsqueda del método natural. Fondo de Cultura Económica, México, D.F.

Maltsev, Y., Erst, A. (2023). Recent advances in the integrative taxonomy of Plants. *Plants*, 12(24): 4097. https://doi.org/10.3390/plants12244097

Meier, R. (2008). DNA sequences in taxonomy: opportunities and challenges. In: Wheeler, Q.D. (eds) The new taxonomy. CRC Press, Boca Ratón, FL. https://doi.org/10.1201/9781420008562-11

Meier, R., Blaimer, B.B., Buenaventura, E., Hartop, E., von Rintelen, T., Srivathsan, A., Yeo, D. (2022). A re-analysis of the data in Sharkey *et al*.'s (2021) minimalist revision reveals that BINs do not deserve names, but BOLD Systems needs a stronger commitment to open science. *Cladistics*, 38(2), 264–275. https://doi.org/10.1111/cla.12489

Meier, R., Hartop, E., Pylatiuk, C., Srivathsan, A. (2024). Towards holistic insect monitoring: species discovery, description, identification and traits for all insects. *Philosophical Transactions of the Royal Society B,* 379, 20230120. https://doi.org/10.1098/rstb.2023.0120

Meier, R., Lawniczak, M.K.N., Srivathsan, A. (2025). Illuminating entomological dark matter with DNA barcodes in an era of Insect decline, deep learning, and genomics. *Annual Review of Entomology,* 70, 185–204. https://doi.org/10.1146/annurev-ento-040124-014001

Merckelbach, L.M., Borges, L.M.S. (2020). Make every species count: `FASTACHAR` software for rapid determination of molecular diagnostic characters to describe species. *Molecular Ecology Resources*, 20(6), 1761–1768. https://doi.org/10.1111/1755-0998.13222

Needleman, S., Wunsch, C. (1970). A general method applicable to the search for similarities in the amino acid sequence of two proteins. *Journal of Molecular Biology*, 48(3), 443–453. https://doi.org/10.1016/0022-2836(70)90057-4

Pagès, H., Aboyoun, P., Gentleman, R., DebRoy, S. (2024). `Biostrings`: efficient manipulation of biological strings. R package version 2.70.3. https://bioconductor.org/packages/Biostrings

Perrier, V., Meyer, F., Granjon, D. (2024). `shinyWidgets`: custom inputs widgets for Shiny. R package version 0.8.6. https://CRAN.R-project.org/package=shinyWidgets

Posit team (2023). RStudio: integrated development environment for R. Posit Software, PBC, Boston, MA. http://www.posit.co/

R Core Team (2024). `R`: a language and environment for statistical computing. R Foundation for Statistical Computing, Vienna, Austria. https://www.R-project.org/

Ratnasingham, S., Hebert, P.D. (2007) BOLD: The Barcode of Life Data System (http://www.barcodinglife.org). *Molecular Ecology Notes*, 7(3), 355–364. https://doi.org/10.1111/j.1471-8286.2007.01678.x

Rheindt, F.E., Bouchard, P., Pyle, R.L., Welter-Schultes, F., Aescht, E., Ahyong, S.T., Ballerio, A., Bourgoin, T., Ceríaco, L.M.P., Dmitriev, D., Evenhuis, N., Grygier, M.J., Harvey, M.S., Kottelat, M., Kluge, N., Krell, F.T., Kojima, J.I., Kullander, S.O., Lucinda, P., Lyal, C.H.C., Scioscia, C.L., Whitmore, D., Yanega, D., Zhang, Z-Q., Zhou, H-Z., Pape, T. (2023). Tightening the requirements for species diagnoses would help integrate DNA-based descriptions in taxonomic practice. *PLoS Biology*, 21(8), e3002251. https://doi.org/10.1371/journal.pbio.3002251

Renner, S.S. (2016). A return to Linnaeus's focus on diagnosis, not description: the use of DNA characters in the formal naming of species. *Systematic Biology*, 65(6), 1085–1095. https://doi.org/10.1093/sysbio/syw032

Richter, S. (2005). Homologies in phylogenetic analyses—concept and tests. *Theory in Biosciences*. 124, 105–120. https://doi.org/10.1007/BF02814479

Sarkar, I.N., Planet, P.J., Desalle, R.O.B. (2008). CAOS software for use in character-based DNA barcoding. *Molecular Ecology Resources*, 8(6), 1256–1259. https://doi.org/10.1111/j.1755-0998.2008.02235.x

Srivathsan, A., Hartop, E., Puniamoorthy, J., Lee, W.T., Narayanan-Kutty, S., Kurina, O., Meier, R. (2019). Rapid, large-scale species discovery in hyperdiverse taxa using 1D MinION sequencing. *BMC Biology,* 17, 96. https://doi.org/10.1186/s12915-019-0706-9

Srivathsan, A., Ang, Y., Heraty, J.M., Hwang, W.S., Jusoh W.F.A., Narayanan-Kutty, S., Puniamoorthy, J., Yeo, D., Roslin, T., Meier, R. (2023). Convergence of dominance and neglect in flying insect diversity. *Nature Ecology and Evolution*, 7, 1012–1021. https://doi.org/10.1038/s41559-023-02066-0

Weitschek, E., van Velzen, R., Felici, G., Bertolazzi, P. (2013). BLOG 2.0: a software system for character–based species classification with DNA Barcode sequences: what it does, how to use it. *Molecular Ecology Resources*, 13(6), 1043–1046. https://onlinelibrary.wiley.com/doi/10.1111/1755-0998.12073

Wickham, H. (2016). `ggplot2`: elegant graphics for data analysis. Springer-Verlag, New York.

Wickham, H., François, R., Henry, L., Müller, K., Vaughan, D. (2023). `dplyr`: A Grammar of Data Manipulation. R package version 1.1.4. https://CRAN.R-project.org/package=dplyr

Wickham, H., Hester, J., Bryan, J. (2024). `readr`: read rectangular text data. R package version 2.1.5. https://CRAN.R-project.org/package=readr

World Economic Forum. (2025). The Global Risks Report 2025: A World Divided. https://www.weforum.org/reports/the-global-risks-report-2025

Wright, E.S. (2016). Using `DECIPHER` v2.0 to analyze big biological sequence data in R. *The R Journal*, 8(1), 352–359.

Software	References	DMCs identification	Taxonomic identification	Diagnosis visualization	GUI	Online access	Tree-based analysis	Source
UITOTO	This study	Yes	Yes	Yes	Yes	Yes	No	https://github.com/atorresgalvis/UITOTO
CAOS / CAOS-R	Sarkar *et al*., 2008 / Bergmann, 2024	No*	Yes**	No	No	No	Yes	https://github.com/JuliaHealth/CAOS.jl/ https://github.com/M0rph3u2x/CAOS-R
MOLD	Fedosov *et al*., 2022	Yes	No	No	Yes	Yes	No	https://github.com/SashaFedosov/MolD
DeSignate	Hütter *et al*., 2020	Yes	No	Yes	Yes	Yes	Yes / No	https://github.com/DatabaseGroup/DeSignate
QUIDDICH	Kühn & Hasse, 2020	No*	No	No	No	No	No	https://cran.r-project.org/package=quiddich
FASTACHAR	Merckelbach & Borges, 2020	No*	No	No	Yes	No	No	https://github.com/smerckel/FastaChar
BLOG	Weitschek *et al.*, 2013	Yes	Yes	No	Yes	No	No	http://dmb.iasi.cnr.it/blog-downloads.php
Spider	Brown *et al.*, 2012	No*	No	No	No	No	No	https://cran.r-project.org/web/packages/spider/

Table 1. General comparison of available software tools for molecular diagnosis in taxonomy. The table indicates the available functionalities in each one of the software. *Tools specifically designed to identify single nucleotide characters (rather than combinations of characters) for diagnosing species. These tools typically aim to detect apomorphic characters, which are diagnostic sites where all sequences of a query taxon (*e.g.*, a new species) have nucleotide(s) not found in any member of the remaining taxa. However, such diagnostic characters are seldom present for every taxon in the analyzed alignments, especially in high-throughput taxonomy where hundreds of species and thousands of sequences are involved. **These tools use the identified nucleotide diagnostic characters and apply a hybrid approach combining elements of decision trees and distance methods for taxonomic identification. GUI = Graphical User Interface; DMCs = Diagnostic Molecular Combinations.