1

Trial-level Representational Similarity Analysis

Shenyang Huang[1*], Cortney M. Howard[1*], Paul C. Bogdan[1], Ricardo Morales-Torres[1],

Matthew Slayton[1], Roberto Cabeza[1], Simon W. Davis[1,2]

[1]Department of Psychology & Neuroscience, Duke University, Durham NC 27708

[2]Department of Psychological & Brain Sciences, Indiana University, Bloomington IN 47405

*These authors contributed equally; order was decided based on a coin flip.

Corresponding Author:

Simon W. Davis

Department of Psychological & Brain Sciences

Indiana University

Bloomington, IN 47405

swd4@iu.edu

COI: The authors declare no conflicts of interest.

Abstract

Neural representation refers to the brain activity that stands in for one's cognitive experience, and in cognitive neuroscience, a prominent method of studying neural representations is representational similarity analysis (RSA). While there are several recent advances in RSA, the classic RSA (cRSA) approach examines the structure of representations across numerous items by assessing the correspondence between two representational similarity matrices (RSMs): usually one based on a theoretical model of stimulus similarity and the other based on similarity in measured neural data. However, because cRSA cannot weigh the contributions of individual trials (RSM rows/columns), it is fundamentally limited in its ability to assess subject-, stimulus-, and trial-level variances that all influence representation. Here, we formally introduce trial-level RSA (tRSA), an analytical framework that estimates the strength of neural representation for singular experimental trials and evaluates hypotheses using multi-level models. First, we verified the correspondence between tRSA and cRSA in quantifying the overall representation strength across all trials. Second, we compared the statistical inferences drawn from both approaches using simulated data that reflected a wide range of scenarios. Compared to cRSA, the multi-level framework of tRSA was both more theoretically appropriate and significantly sensitive to true effects. Third, using real fMRI datasets, we further demonstrated several issues with cRSA, to which tRSA was more robust. Finally, we presented some novel findings of neural representations that could only be assessed with tRSA and not cRSA. In summary, tRSA proves to be a robust and versatile analytical approach for cognitive neuroscience and beyond.

Introduction

Since the start of any systematic examination of the mind, the concept of *representation* has provided a link between the external world and the content of mental life (Brentano, 1874). Current perspectives in cognitive science have defined representations as brain activity patterns that convey some behaviorally relevant content, which could be sensory perception, memory, concept knowledge, or social relations (Kriegeskorte & Diedrichsen, 2019). One of the central approaches for evaluating information represented in the brain is representational similarity analysis (RSA), an analytical approach that queries the representational geometry of the brain in terms of its alignment with the representational geometry of some cognitive model (Kriegeskorte et al., 2008; Kriegeskorte & Kievit, 2013), or, in some cases, compares the representational geometry of two neural systems (e.g., Kriegeskorte et al., 2008) or two model systems (Sucholutsky et al., 2023). The RSA approach has demonstrated utility across many domains of cognitive neuroscience research, such as visual perception (Jozranjbar et al., 2023), episodic memory (Xue, 2018), concept knowledge (Bauer & Just, 2019), social information (Freeman et al., 2018), and cognitive control (Freund, Etzel, et al., 2021). Despite its proven success, classic RSA approach, henceforth cRSA, has several limitations in efficacy across various experimental scenarios, due to its inability to reflect the proper multi-level variance structure within the data. Recently, methodological advancements have addressed many known limitations in cRSA. For example, cross-validated distance measures have improved the reliability of representational dissimilarities in the presence of noise and trial imbalance (Diedrichsen et al., 2021; Nili et al., 2014; Walther et al., 2016). Bayesian approaches such as pattern component modeling (Diedrichsen et al., 2018) have extended representational approaches to accommodate continuous stimulus features or temporal variation. Further, model comparison RSA strategies (Diedrichsen et al., 2021) and generalization techniques across stimuli and participants (Schütt et al., 2023) have improved sensitivity and inference. Nevertheless, a common feature shared across most of improvements is that they require stimuli repetition to examine the representational structure. This requirement limits their ability to probe brain-behavior questions at the level of individual events. In this paper, we present an advancement termed trial-level RSA, or tRSA, which addresses these limitations in cRSA and may be utilized in paradigms with or without repeated stimuli.

A typical implementation of cRSA involves four main steps (see **Figure 1**). First, brain activity responses to a series of N trials are compared against each other (typically using Pearson's r) to form an $N \times N$ representational similarity matrix, or RSM_{brain}. Second, a

hypothesis of how this brain system ought to respond — a cognitive model — is created in the

form of a model RSM, or RSM_{model}. This RSM_{model} can be created based on objective features of

the stimuli (e.g., image brightness, category membership), subject ratings or behaviors (e.g.,

pleasantness, memory success), or outputs from computational models (e.g., neuron activations

in artificial neural networks, semantic embeddings from large language models). Third, values

from the lower (or equivalently, upper) triangular parts of both RSM_{brain} and RSM_{model} are

retrieved, vectorized, and compared. This RSM_{brain}-RSM_{model} comparison focuses on the

similarity between the two representational geometries, which is typically measured by

Spearman's rank correlation (Kriegeskorte et al., 2008) but alternatives have also been

proposed (Bobadilla-Suarez et al., 2020; Diedrichsen et al., 2021; Walther et al., 2016). This

similarity measure is often referred to as a first-level RSA score or *representational strength*[1].

Fourth, once the above procedures are completed for each subject and condition, the first-level

measures of representation are submitted to a second-level hypothesis testing for statistical

inferences — often using general linear models such as t-test and ANOVA. One notable feature

of cRSA is that the representational geometries are compared to one another in their entireties

in step 3, and this step produces as a single measure of representational strength collapsing

across all experimental trials. In other words, cRSA estimates cannot be interpreted for specific

experimental trials or stimuli; rather, they only reflect how strongly the studied neural system

represents for the entire set of items, limiting the realm of possible research questions. Most

critically, as trial-level information is collapsed in cRSA, multiple sources of variance become

intractable, yet these ignored variances could render subsequent second-level analyses

susceptible to erroneous inferences.

---

[1] *Representational geometry* usually refers to the structure of similarities among repeated presentations of the same stimulus in the neural data (as captured in the brain RSM) and is often estimated utilizing a model comparison approach, whereas *representational strength* is a derived measure that quantifies how strongly this geometry aligns with a hypothesized model RSM. In other words, geometry characterizes the pattern space itself, while representational strength reflects the degree of correspondence between that space and the theoretical model under test.

Figure 1. Representational Similarity Analysis (RSA). *Steps for classic RSA (cRSA) and trial-level RSA (tRSA). **A)** Neural Representational Similarity Matrix (RSM_{brain}) is generated by correlating multi-voxel activity patterns across all trials within a Region of Interest (ROI), reflecting similarity between neural responses. **B)** Model Representational Similarity Matrix (RSM_{model}) is constructed by correlating of-interest stimulus properties across all trials. **C)** First-Level cRSA (top) and tRSA (bottom). For cRSA, the lower triangular parts (black outline) of RSM_{brain} and RSM_{model} are compared, producing a single summary statistic (e.g., Spearman's rho) across all trials. For tRSA, representational similarity values from RSM_{brain} and RSM_{model} for the same trial (e.g., tennis ball; red dashed outline) are compared, producing a single representational strength estimate for that trial. **D)** Second-Level analysis for cRSA and tRSA. In cRSA, subject-level r values are submitted to a one-sample t-test to assess whether the values reliably exceed zero. In tRSA, a linear random effects model with random effects for subject and stimulus is fit, and hypothesis testing determines whether the estimated intercept is significantly greater than zero.*

A behavioral or neural measure in a single experimental trial consists of meaningful

variances from four distinct sources: *condition-level* (experimental task manipulations such as

cognitive load and emotional valence)*, subject-level* (individual differences in perceptual acuity,

prior knowledge, or other cognitive faculties)*, stimulus-level* (features of the stimuli with

behavioral or neural relevance)*,* and *trial-level* (physiological and nuisance variables affecting

measurement). Notably, the distinction between condition-level and stimulus level is not always

clear as researchers may manipulate stimulus-level features themselves. In these cases, what

researchers ultimately consider condition-level and stimulus-level will depend on their specific

research questions. For example, researchers intending to study generalized object

representation may consider object category a stimulus-level feature, while researchers

interested in if/how object representation varies by category may consider the same category

variable condition-level.

To explain the variance in behavioral or neural measures, the appropriate statistical

model should reflect said multi-level variance structure. However, the cRSA approach only does

so imperfectly with three major limitations, which we detail below.

First, the heterogeneity of subject- and/or condition-level variances in real datasets

adversely impacts the sensitivity and reliability of cRSA. One of the fundamental assumptions of

general linear models (step 4 of cRSA; see **Figure 1D**) is *homoscedasticity* or homogeneity of

variance — that is, all residuals should have equal variance. This assumption is often violated in

real datasets. The variance of first-level cRSA scores depends largely on the number of

observations (see **Figure 2**), but this trial count can be highly variable across subjects or

conditions, resulting in *heteroscedasticity*. This issue is prevalent in studies where trials are

selected and grouped based on subject behavior, such as in memory or attention tasks. In those

cases, treating cRSA scores obtained from 100 trials and those obtained from 20 trials as

having equal variance would violate the homoscedasticity assumption and lead to unreliable

results. One suggested remedy of the issue is equating the number of trials via random

subsampling conditions with more trials (Dimsdale-Zucker & Ranganath, 2018); however, this

solution comes with the cost of not making full use of the rich information from those low-

variance conditions and may not be ideal when the number of trials is highly unbalanced.

Second, cRSA is unable to model stimulus-level variance. Many studies present

subjects with a fixed set of stimuli, which are supposedly samples representative of some

broader category. In this case, using cRSA brings about two issues. For one, stimuli can vary in

a wealth of properties. Object images, for example, vary in terms of image complexity, concept

frequency, and memorability, all of which can affect both behavior and neural activity in

important and systematic ways (Bainbridge et al., 2017; Hovhannisyan et al., 2021; Naspi et al.,

2021). To mitigate this issue, one might explicitly manipulate the distribution of relevant stimulus

properties or cross-validate cRSA results on subsets of stimuli (Freund, Bugg, et al., 2021).

Nevertheless, neither solution could address the second issue, which is the fact that the same

stimuli are presented to multiple subjects. To properly address this stimulus-level dependence in

the data and generalize the results beyond the fixed stimulus set, one must model stimulus

identity as random effects, for the very same reason subjects are specified as random effects

(Chen et al., 2021; Yarkoni, 2022). However, this solution is not accessible for cRSA since its

current implementation stipulates the collapsing of stimulus information across trials (step 3 of

cRSA; see **Figure 1C**). While other approaches such as pattern component

modeling(Diedrichsen et al., 2018) and encoding models (Naselaris et al., 2011) are well-suited

to analyzing variables that vary continuously on a trial-by-trial or moment-by-moment basis,

these frameworks address different inferential goals. Specifically, pattern component modeling
and encoding models focus on estimating variance components or predicting activation from
features, while cRSA is designed to evaluate representational geometry. Thus, cRSA as well as
our proposed approach address a problem setting distinct from pattern component modeling
and encoding models.
158

Figure 2. Trial count influences the reliability of correlations. *The spread of correlation estimates (y-axis) varies nonlinearly with the number of observations, or trial count (x-axis). Trial count ranges from 10 to 200 with increments of 1. For each trial count, observations were drawn from a bivariate normal distribution with the given ground truth Pearson correlation, and their empirical Pearson correlation coefficient was computed. Ten random samples were drawn for each trial count and ground truth combination. Both ground truth and estimated values in the scatter plots are Fisher-transformed (z).*

Third, cRSA is not well-suited for testing the influence of stimulus-level or trial-level
properties on neural representations. For example, it may be desirable to explicitly test or
control for how certain stimulus-level properties (e.g., memorability) or trial-level recordings (e.g.,
cardiac cycle, pupil dilation) affect neural representations (Critchley & Garfinkel, 2018; van der
Wel & van Steenbergen, 2018). One strategy to analyze the effects of those stimulus- or trial-
level continuous variables is to discretize them into categories (e.g., low vs. medium vs. high);
however, discretization inevitably leads to a loss of information, reduced statistical power, and
potentially misleading outcomes (Cohen, 1983; MacCallum et al., 2002). Alternatively, one could
construct additional RSMs for the covariates and then compare all RSMs using a partial

correlation or multiple regression framework, yet the statistical interpretations become much less straightforward after the conversion. For instance, even though a univariate random variable v, such as pleasantness ratings, can be conveniently converted to an RSM using pairwise distance metrics (Weaverdyck et al., 2020), the very same RSM would also be derived from the opposite random variable $-v$, leaving uncertain of the directionality (or if representation is strongest for pleasant or unpleasant items) of any findings with the RSM (see also Bainbridge & Rissman, 2018).

Here, we propose an original method for evaluating the neural representation of information at the level of individual experimental trials: *trial-level RSA* or *tRSA*. In this approach, instead of deriving a single measure of the similarity between RSM_{model} and RSM_{brain}, we compute a series of similarity measures on a trial-by-trial (row-by-row or column-by-column) basis (Davis et al., 2021). For instance, the representational strength in the first trial is calculated as the similarity between the first row of RSM_{model} and the first row of RSM_{brain} (see **Figure 1C**). While several extensions of RSA have addressed key limitations in noise sensitivity, stimulus variance, and modeling (e.g., Diedrichsen et al., 2021; Schütt et al., 2023), our tRSA approach introduces a new methodological step by estimating representational strength at the trial level. This accounts for the multi-level variance structure in the data, affords generalizability beyond the fixed stimulus set, and allows one to test stimulus- or trial-level modulations of neural representations in a straightforward way. Critically, in single-presentation designs, a "trial" refers to one stimulus presentation, and corresponds to a row or column in the RSM. In studies with repeated stimuli, these rows are often called "conditions" and may reflect aggregated patterns across trials. tRSA is compatible with both cases: whether rows represent individual trials or averaged trials that create "conditions", tRSA estimates are computed at the row level. We assessed the efficacy of tRSA in comparison with cRSA using data from simulations representing a wide range of possible experimental scenarios (Experiment 1) and data from an extant real fMRI study (Experiment 2). In both experiments, our results demonstrated enhanced sensitivity, robustness, and flexibility with analyzing neural representations using the tRSA approach. Data is available upon request to the corresponding author and our simulations and example tRSA code is available at https://github.com/electricdinolab.

Methods

Experiment 1: cRSA and tRSA comparisons in simulated data

Experiment 1 consisted of three main parts. First, we validated the similarity between tRSA and cRSA results in assessing the general representational strength across all trials. In other words, we established that tRSA can carry out the main purpose of cRSA. Second, we compared the statistical inferences generated by each approach in a set of synthetic within-subject studies with two conditions. Third, we demonstrated tRSA's unique capability of assessing continuous modulators of representational strength in a set of synthetic scenarios. A host of parameters were varied to ensure the robustness of the comparisons in all three parts, such as the trial count, subject sample size, and effect size. All analyses were done in R 4.4.1 (R Core Team, 2024).

Estimating overall representational strength

We simulated *activity patterns*, from which RSMs were derived. Specifically, assuming an experiment with n trials and q measurement channels (e.g., voxels), we sampled a set of $n \cdot q$ values from a univariate standard normal distribution $N(0,1)$, and another set of $n \cdot q$ values from a univariate normal distribution $N(0, \sigma^2)$. Both vectors were rearranged into matrices of n rows and q columns, yielding a *ground truth activity* pattern and a *noise* pattern. The summation of these two patterns yielded a *measured* pattern. Two RSMs were then generated from the ground truth pattern (RSM_{model}) and the measured pattern (RSM_{brain}) using Pearson's correlation, with which cRSA and tRSA were conducted separately. This set of procedures was repeated for 10,000 iterations with different random samples. The following parameter values were used for reported results: $q = 500, n \in \{10, 15, 20, 25, 30, 40, 50, 100\}, \sigma^2$ ranging from 0.8 to 2.0 with increments of 0.2.

We next assessed the correspondence between tRSA and cRSA in the presence of discrete conditions, which is often seen in real studies. Assuming a simple experimental design with two conditions, A and B, consisting of n_A and n_B trials, respectively, we generated a ground truth activity pattern with $n_A + n_B$ rows and m columns in the same way as before. Then, we generated two sets of noise patterns, which were controlled by parameters σ_A and σ_B, respectively, one for each condition. The measured pattern was again computed as the summation of ground truth and noise. cRSA was conducted separately for trials in each condition. Critically, tRSA was conducted in an *across-condition* fashion: we generated RSMs with all $n_A + n_B$ trials, obtained $n_A + n_B$ tRSA values as previously described, and then split the

values into two sets based on the condition each trial belonged to. Finally, as before, we

computed the average of tRSA values separately for Conditions A and B to allow comparisons

with cRSA values. This set of procedures was repeated for 10,000 iterations with different

random samples. We assessed the influence of three factors: sample size, balance, and noise

level, with the following parameter values: $q = 500, n_A, n_B \in \{20, 80, 320\}, \sigma_A, \sigma_B \in \{1, 2\}$.

Of note, tRSA could conceivably also be conducted in a *within-condition* fashion,

whereby one would generate two separate sets of RSMs according to condition, i.e., one set of

$n_A \times n_A$ RSMs for Condition A and another set of $n_B \times n_B$ RSMs for Condition B, and then

compute the two sets of *within-condition* tRSA values separately. We hereby advocate for the

use of *across-condition* tRSA — which we have used in previous studies (Davis et al., 2021;

Howard et al., 2024; S. Huang, Howard, et al., 2024; Naspi et al., 2023) — over within-condition

tRSA. Comparisons of the statistical properties of within-condition and across-condition tRSA

approaches are discussed in **Appendix 2**.

<u>Statistical inferences from tRSA and cRSA</u>

Modeling discrete conditions

The essential theoretical advantage of tRSA over cRSA is that representational strength can be

estimated at the level of experimental trials, which would allow us to properly capture the multi-

level variance structure in the data. To demonstrate this benefit, four sources of variances were

hypothesized: condition, subject, stimulus, and trial. Condition-level variance denotes the effect

of experimental conditions or manipulations on representation, with each condition receiving its

own noise-level parameter $s_{cond,k}$. This is the focal effect of interest for this simulation.

Additionally, subject-level variance denotes individual differences in the quality of representation

across m subjects, with each subject receiving one's own noise-level parameter $s_{subj,i}$. A within-

subject design is common in real experiments and is thus assumed here, where each subject

received all experimental conditions. Stimulus-level variance denotes the diversity of stimuli that

may result in some being represented more strongly than others, with each stimulus receiving

its own noise level parameter $s_{stim,j}$. The subject-level and stimulus-level variances were fully

crossed, i.e., all subjects were assumed to view all stimuli exactly once (condition

counterbalanced) during the experiment. Finally, trial-level variance denotes random

fluctuations in the signal across the experiment and is controlled by a single noise-level

parameter s_{trial}. Therefore, for a given event of subject i responding to stimulus j in condition k,

we computed its noise level as:

$\sigma_{ijk} = \max(s_{subj,i} + s_{stim,j} + s_{cond,k} + s_{trial}, 0.01).$

Notably, this multi-level variance structure replaced the fixed noise parameters σ_A, σ_B,

while all other procedures remained the same as the previous simulation. The entire set of

procedures was repeated for 10,000 iterations. The base simulation parameters were as follows:

• Experimental design: $q = 500, m = 40, n_A = n_B = 100$, and

• Multi-level variance: $s_{cond} \in \{1, 1.2\}, s_{subj} \sim N(0, 0.5^2), s_{stim} \sim N(0, 0.2^2), s_{trial} = 2$.

To assess the robustness of RSA methods in different situations that could occur in real

data, we introduced a number of variations to the base design:

• Number of subjects: $m \in \{10, 20, 40, 80, 160, 320\}$.

• Trial count per subject: $n_{trial} \in \{20, 30, 46, 70, 100, 250, 220, 330, 500\}$.

• Trial count ratio: $n_A \in \{20, 40, 60, \ldots, 180\}, n_B = 200 - n_A$.

• Variance in trial count ratio across subjects: $\sigma_n \in \{0, 1, 2, 4, 8, 16, 32, 64, 128\}$. Actual trial

counts were drawn from a truncated normal distribution,

$n_A \sim truncN(100, \sigma_n, 10, 190), n_B = 200 - n_A$.

• Effect size: condition-level noise $s_{cond,A/B} \in \{1.00, 1.05, 1.10, \ldots, 1.30\}$. Greater

differences in the condition-level noise correspond to larger condition effects.

Following data generation, condition-level representational strength was estimated using

cRSA and trial-level representational strength was estimated using tRSA. We focused on the

statistical inferences of the effect of conditions, namely b_{B-A}. To this end, cRSA estimates were

submitted to a paired-sample t-test. Critically, tRSA estimates were submitted to a mixed-effects

model which is statistically appropriate for modeling the hierarchical structure of the data, where

observations are nested within both subjects and stimuli (Baayen et al., 2008; Chen et al., 2021).

Specifically, a linear mixed-effects model with a fixed effect of condition (which estimates the

average effect across the entire sample, capturing the overall effect of interest) and random

effects of both subjects and stimuli (which model variations due to differences between

individual subjects and items, allowing generalization beyond the sample) were fitted to tRSA

estimates via the `lme4 1.1-35.3` package in R (Bates et al., 2015), and p-values were

estimated using Satterthwaites's method via the `lmerTest 3.1-3` package (Kuznetsova et al.,

2017).

Given data generated with $s_{cond,A} = s_{cond,B}$, the correct inference should be a failure to

reject the null hypothesis of $b_{B-A} = 0$; any significant ($p < 0.05$) result in either direction was

considered a false positive (spurious effect, or Type I error). Given data generated with $s_{cond,A} >$

$s_{cond,B}$, the inference was considered correct if it rejected the null hypothesis of $b_{B-A} = 0$ and

yielded the expected sign of the estimated contrast ($b_{B-A} > 0$). A significant result with the

reverse sign of the estimated contrast ($b_{B-A} < 0$) was considered a Type I error, and a

nonsignificant ($p \geq 0.05$) result was considered a false negative (failure to detect a true effect,

or Type II error). Error rates were computed for each RSA method and were compared against

the null hypothesis of equal proportions between methods.

Modeling continuous modulators

In addition to discrete experimental conditions, we also simulated data reflecting scenarios in

which representational strength varies continuously with some modulator. For example, one

may be interested in the effects of continuous variables such as image complexity and

memorability (stimulus-level) or reaction time (trial-level). In this case, s_{trial} was no longer a

constant throughout the experiment but a trial-level variable. For a given event of subject i

responding to stimulus j in trial k, we computed its noise level as:

$\sigma_{ijk} = \max(s_{subj,i} + s_{stim,j} + s_{trial,k}, 0.01)$.

To capture the effect of this trial-level variable, we generated a random variable

$v_{measured}$ that reflects a trial-level measurement with construct validity

$r_{val} = Cor(v_{measured}, s_{trial})$, which was restricted to be a nonpositive value. When $r_{val} = 0$,

$v_{measured}$ carries no information of the underlying s_{trial} and should not predict trial-level

representational strength. When $r_{val} < 0$, $v_{measured}$ is inversely related to trial-level noise and

should positively predict trial-level representational strength. The entire set of procedures was

repeated for 10,000 iterations. The base simulation parameters were as follows:

• Experimental design: $q = 500, m = 40, n = 200$, and

• Variance structure: $r_{val} \in \{0, -0.1\}, s_{subj} \sim N(0, 0.5^2), s_{stim} \sim N(0, 0.2^2), s_{trial} = 2$.

As before, we introduced a number of variations, as follows:

• Number of subjects: $m \in \{10, 20, 40, 80, 160, 320\}$.

• Number of trials per subject: $n_{trial} \in \{20, 30, 46, 70, 100, 250, 220, 330, 500\}$.

• Variance in the number of trials per subject: $\sigma_n \in \{0, 20, 40, \ldots, 160\}$. Actual trial counts

were drawn from a truncated normal distribution, $n \sim truncN(n, \sigma_n, 20, n)$.

• Effect size: $r_{val} \in \{-0.10, -0.09, \ldots, 0.00\}$. More negative values of r_{val} should result in

greater representational strength.

Following data generation, two conditions were created for each subject based on a

median split (A=low $v_{measured}$, B=high $v_{measured}$), and we tested cRSA and tRSA models as

described in the previous simulation, focusing on b_{B-A}. Furthermore, we additionally modeled

trial-level representational strength as a function of $v_{measured}$ directly, using a linear mixed-

effects model of tRSA estimates with a fixed effect of $v_{measured}$ and random effects of both

subjects and stimuli. Given data generated with $r_{val} = 0$, the correct inference should be a

failure to reject the null hypothesis of $b = 0$ in both discrete and continuous models; any

significant ($p < 0.05$) result in either direction was considered a false positive or Type I error.

Given data generated with $r_{val} < 0$, the inference was considered correct if it rejected the null

hypothesis of $b = 0$ and yielded the expected sign of the estimated contrast or slope $b > 0$. A

significant result with the reverse sign of the estimated contrast or slope ($b < 0$) was considered

a Type I error, and a nonsignificant ($p \geq 0.05$) result was considered a false negative or Type II

error. Error rates were computed for each RSA method and were compared against the null

hypothesis of equal proportions between methods.

Experiment 2: cRSA and tRSA comparisons in fMRI data

Experiment 2 proceeded in 3 steps. First, we assessed how the impact of subject-level variance

in heterogeneity of trial ratios amongst two critical conditions ("Hits" and "Misses") can lead to

biased estimates of representational strength. Second, we examined the impact of modeling

trial-level variance on both representational strength during Object Naming, as well as

Mnemonic Strength during a memory retrieval task. Lastly, stimulus-level estimates of

representational strength were related to object memorability — an analysis that is not directly

accessible to cRSA.

<u>Data acquisition</u>

Participants

A pre-existing dataset was analyzed to evaluate tRSA. Main study findings have been reported

elsewhere (S. Huang et al., 2025). A total of 38 adults, aged 18 to 30, participated in this study

on a voluntary basis and received monetary compensation for their time. Eligibility criteria

required participants to be native or fluent English speakers, with no history of significant

neurological or psychiatric conditions, and not taking medications that could affect cognitive

function or cerebral blood flow (except for antihypertensive agents). All participants provided

written informed consent before the start of the study. Six participants did not complete the

study and were excluded from the analysis. Additionally, two participants were excluded from

the Memory Retrieval analyses due to poor memory performance. The final sample included 32

participants (21 women and 11 men) for the Object Perception task and 30 participants (19

women and 11 men) for the Memory Retrieval task.

 Experimental design

An expansive outline of the study design for the tasks described below can be found in (S.

Huang et al., 2025); here we briefly review relevant details pertinent to our application of trial-

level RSA for a subset of that data. Data from two experimental datasets were used, including

an Object Perception dataset and a Memory dataset (**Figures 7A and 8A**). In the Object

Perception task, participants were shown images of 114 unique everyday objects on a white

background. The corresponding label presented underneath each object and participants were

asked to rate how well the label described the object on a four-point scale. The main purposes

of this rating task was to make sure that participants assess the meaning of the objects and to

verify that these objects are indeed familiar to them (mean rating = 3.59). The objects were

presented for 4 seconds, followed by a jittered fixation cross with an average duration of 4

seconds. In the memory task, a Memory Encoding session took place at least 7 days after

Object Perception. During Encoding, participants viewed images of 114 unique real-world

scenes along with the 114 objects they had seen in session 1. In each trial, participants were

shown a scene image for 3 seconds, followed by a jittered empty box indicating the continuation

of the trial, which lasted for an average of 3 seconds, and finally an object image for 4 seconds.

During the object presentation, participants rated "how likely it is to find the object in the scene"

on a 4-point scale (1 = "very unlikely," 2 = "somewhat unlikely," 3 = "somewhat likely," 4 = "very

likely"). Each trial was separated by a jittered fixation cross with an average duration of 4

seconds. Memory Retrieval consisted of three scanning runs, each with 38 trials, lasting

approximately 9 minutes and 12 seconds. Memory Retrieval consisted of three scanning runs,

each with 38 trials, lasting approximately 9 minutes and 12 seconds (within-run comparisons

were later excluded from RSA analyses). Memory Retrieval took place one day after Memory

Encoding and involved testing participants' memory of the objects seen in the Encoding phase.

Neural data during the Encoding phase has been reported elsewhere. In the main Memory

Retrieval task, participants were presented with 144 labels of real-world objects, of which 114

were labels for previously seen objects and 30 were unrelated novel distractors. Participants

performed old/new judgements, as well as their confidence in those judgements on a four-point

scale (1 = Definitely New, 2 = Probably New, 3 = Probably Old, 4 = Definitely Old). In a

subsequent Perceptual Memory Retrieval task participants were shown 126 images of real-

world objects (96 old images, 18 were different exemplar images of old objects, and 12 images

of unrelated novel objects). Participants were asked to determine whether the image was old,

similar, or new. All analyses in the current study pertained to fMRI data from Object Perception

and the main Memory Retrieval tasks, as well as behavioral data from the Perceptual Memory

Retrieval task.

MRI data were collected using a 3T GE MR750 Scanner equipped with an 8-channel head coil

at the Brain Imaging and Analysis Center (BIAC) at Duke University. Each MRI session began

with a localizer scan, during which 3-plane (straight axial/coronal/sagittal) faster spin echo

images were obtained. A high-resolution T1-weighted (T1w) structural scan was then acquired,

consisting of 96 axial slices parallel to the AC-PC plane, with voxel dimensions of 0.9 × 0.9 ×

1.9 mm³. This was followed by blood-oxygenation-level-dependent (BOLD) functional scans

using a whole-brain gradient-echo echo planar imaging sequence (repetition time = 2000 ms,

echo time = 30 ms, field of view = 192 mm, 36 oblique slices with voxel dimensions of 3 x 3 x 3

mm³). Task instructions and stimuli were delivered using the PsychToolbox program (Kleiner et

al., 2007) and projected onto a mirror at the back of the scanner bore. Participants responded

using a four-button fiber-optic response box. To reduce scanner noise, participants wore

earplugs, and MRI-compatible lenses were provided when necessary to correct vision. Foam

padding was placed inside the head coil to minimize head movement.

<u>Data analysis</u>

MRI data preprocessing

fMRIPrep 23.0.1 (Esteban et al., 2019, 2023) was used to preprocess structural and functional

MRI data, as well as generating text descriptions of preprocessing details, which were

condensed below. T1w structural images collected across all MRI sessions for the same

participant were corrected for intensity non-uniformity with `N4BiasFieldCorrection` (Tustison et

al., 2010) from ANTs 2.3.3 (Avants et al., 2011). The T1w-reference was skull-stripped with a

Nipype implementation of the `antsBrainExtraction.sh` workflow from ANTs, using

OASIS30ANTs as target template. Brain tissue segmentation of cerebrospinal fluid (CSF),

white-matter (WM), and gray-matter (GM) was performed on the brain-extracted T1w using

`fast` from FSL (Zhang et al., 2001). An anatomical T1w-reference map was computed after

registration of T1w images using `mri_robust_template` from FreeSurfer 7.3.2 (Reuter et al.,

2010). Brain surfaces were reconstructed using `recon-all` from FreeSurfer 7.3.2 (Dale et al.,

1999), and the brain mask estimated previously was refined with a custom variation of the

method to reconcile ANTs-derived and FreeSurfer-derived segmentations of the cortical gray-

matter of Mindboggle (Klein et al., 2017). Volume-based spatial normalization to the ICBM 152

Nonlinear Asymmetrical template version 2009c standard space was performed through

nonlinear registration with `antsRegistration` from ANTs 2.3.3, using brain-extracted versions of

both T1w reference and the T1w template.

BOLD functional data across all sessions and runs were preprocessed collectively. A

reference volume and its skull-stripped version were generated using a custom methodology of

fMRIPrep. Head-motion parameters with respect to the BOLD reference were estimated,

followed by spatiotemporal filtering using `mcflirt` from FSL (Jenkinson et al., 2002). BOLD runs

were slice-time corrected to 0.972s (0.5 of slice acquisition range 0s-1.94s) using `3dTshift`

from AFNI (Cox & Hyde, 1997). The BOLD time-series were resampled onto their original,

native space by applying the transforms to correct for head-motion. The BOLD reference was

then co-registered to the T1w reference using boundary-based registration via `bbregister` from

FreeSurfer (Greve & Fischl, 2009). Co-registration was configured with six degrees of freedom.

Confounding time-series calculated based on the preprocessed BOLD included: root mean

square displacement (RMSD) between frames (Jenkinson et al., 2002), absolute sum of relative

framewise displacement (FD) (Power et al., 2014), and the derivative of root mean square

variance over voxels (DVARS) (Power et al., 2014), as well as global signals extracted within

CSF, WM, and the whole-brain mask. Additionally, a set of physiological regressors were

extracted to allow for component-based noise correction (CompCor) (Behzadi et al., 2007).

Principal components were estimated after high-pass filtering the preprocessed BOLD time-

series (using a discrete cosine filter with 128s cut-off) for the two CompCor variants: temporal

(tCompCor) and anatomical (aCompCor). tCompCor components were calculated from the top

2% variable voxels within the brain mask. For aCompCor, three probabilistic masks (CSF, WM

and combined CSF+WM) were generated in anatomical space. For each CompCor

decomposition, the k components with the largest singular values that cumulatively explained at

least 50% of variance across the nuisance mask (CSF, WM, combined, or temporal) were

retained. The BOLD time-series were resampled into standard space with a spatial resolution of

$2 \times 2 \times 2$ mm^3 or $97 \times 115 \times 97$ voxels. First, a reference volume and its skull-stripped version

were generated using a custom methodology of fMRIPrep. All resamplings can be performed

with a single interpolation step by composing all the pertinent transformations (i.e., head-motion

transform matrices, susceptibility distortion correction when available, and co-registrations to

anatomical and output spaces). Gridded (volumetric) resamplings were performed using

`antsApplyTransforms` (ANTs), configured with Lanczos interpolation to minimize the smoothing

effects of other kernels (Lanczos, 1964). Non-gridded (surface) resamplings were performed

using `mri_vol2surf` (FreeSurfer).

Single-trial modeling

Neural activity in gray matter (GM) voxels for each object presentation event was estimated

using first-level least squares separate general linear models (Mumford et al., 2012) constructed

with SPM12 (Friston et al., 2006) and custom MATLAB scripts. Subject-specific GM masks were

generated by binarizing the fMRIPrep-derived probabilistic masks with a threshold set to

exclude voxels with 80% probability of CSF or WM. Each model included a regressor for the

event of interest along with a regressor for all other objects. Both regressors were convolved

with the canonical double-Gamma hemodynamic response function, including their temporal

and dispersion derivatives to account for variations in the timing of the peak response.

Covariates of no interest included global signal, WM signal, CSF signal, FD, DVARS, RMSD,

and six motion parameters related to translation and rotation. A high-pass temporal filter with a

cutoff of 128 seconds was applied, and the AR(1) model was used to correct for autocorrelation.

These first-level models yielded regression coefficients (betas) that estimated voxel-level neural

activity corresponding to a single trial. Trials with FD greater than 1mm either before or during

the trial were excluded (range: 0-28). Additionally, runs with more than 25% motion trials were

excluded. In total, 1 Object Perception run, and 3 Memory Retrieval runs were excluded.

Behavioral Analyses

Trials for which participants gave no response in the Object Perception (mean 5) or the main

Memory Retrieval (mean 4) were excluded from all analyses involving fMRI data at Perception

and Memory Retrieval tasks respectively. As our primary behavioral measure, we assessed the

memory performance for the object labels. Participants demonstrated variability in their ability to

distinguish between old and new objects, as well as in their decision criteria, making direct

comparisons of raw responses challenging. To address these biases, we performed a receiver-

operating characteristics (ROC) analysis using `yardstick 1.3.1` (Kuhn et al., 2024) in R. This

analysis allowed us to categorize Hit and Miss trials by determining whether counting only "4"

responses or both "3" and "4" responses as "old" yielded the best decision outcome (i.e., closest

to 100% true positive and 0% false positive). The outcome of this analysis was then used to

compute the sensitivity index (d') of recognition. Adjusted hit rates were used to determine

adherence to the task and sufficient fMRI data during Memory Retrieval.

Behavioral analyses categorized each trial during Memory Retrieval as either a "Hit" or
"Miss" for the purpose of categorizing the conditions in the fMRI data. This analysis determined
whether counting only "4" responses or both "3" and "4" responses as "old" produced the most
accurate decision outcome (i.e., closest to 100% true positive and 0% false positive). In total,
data from 8 participants were adjusted to consider only "4" responses as "hit" trials. The results
were then used to calculate the sensitivity index (d') of recognition within each subjective
congruency condition and the corrected hit rate. Participants with post-adjustment hit rates
below 40% were considered to have low adherence to the task and were excluded from all
subsequent analyses. The number of included trials per participant for perception (mean = 110),
ROC values (mean = 0.78), the count of hit trials (mean =76) as well as the corrected hit rate
(mean = 0.70), are detailed in **Appendix 3** **Table 4**.

Neural Representational Similarity Matrices

Models for neural pattern similarity (RSM_{brain}) were constructed using both the Object Perception
study and the main Memory Retrieval task. Twenty six regions from the Human Brainnetome
Atlas (Fan et al., 2016), focusing on eight areas within the lateral occipital cortex (LOC), 14
areas within the inferior temporal cortex (ITC), and four areas in the inferior parietal cortex (IPL,
combining IPL sub regions into lateral posterior and anterior regions), as these regions are
critically involved in visual representations during object perception and memory retrieval (Davis
et al., 2021; Favila et al., 2020; Howard et al., 2024; Long & Kuhl, 2021). For each of these 26
regions, we constructed similarity matrices of voxel activation patterns across stimuli with
custom scripts in MATLAB and SPM12 (Friston et al., 2006). This was done by vectorizing the
voxel-level activation values within each region and calculating their correlations using
Pearson's r, excluding all within-run comparisons. While each cell in a RSM_{model} reflects the
similarity in stimulus properties, each cell in the 114×114 RSM_{brain} represents the similarity in
activation patterns across different stimuli (**Figure 1A**).

Model Representational Similarity Matrix

The C2 layer of the Hierarchical Model of object recognition (HMAX) was used to capture visual
similarity between the 114 objects. The PsyTorch implementation of the HMAX model was used
and contains four sequential stages, each with their own output: S1, C1, S2, and C2. The S1
layer applies Gabor filters to the input image across multiple scales and orientations. The Gabor
filters capture edge-like features such as bars and gratings. The output consists of feature maps
that highlight these basic visual components. Following the S1 layer, the C1 layer performs local

max pooling over the S1 feature maps. This operation introduces some degree of invariance to

position and scale. By selecting the maximum response within localized regions, the C1 layer

reduces the spatial resolution while retaining the most salient features. The stages S2 and C2

build upon this foundation using similar pooling mechanisms. Specifically, S2 units pool

information from the C1 stage using linear filters and function as radial basis functions,

responding most strongly to specific prototype input patterns. These prototypes are derived from

random fragments extracted from a set of natural images, independent of the stimuli used in this

study. The C2 layer then pools outputs from S2 units using a MAX operation, which provides a

degree of position and scale tolerance, allowing for robust representation of visual objects. This

global pooling results in a feature vector that is highly invariant to position and scale, capturing

the presence of complex features regardless of their location in the input image. The C2 layer's

output serves as a compact representation of the visual input (Kriegeskorte et al., 2008;

Riesenhuber & Poggio, 1999, 2002; Serre et al., 2005, 2007; Sufikarimi & Mohammadi, 2020).

Features from the C2 layer of the HMAX model were used to create the model RSM.

Pairwise similarity between images was computed using Pearson's correlation coefficient (r),

measuring the relationship between their C2 feature vectors. These values were organized into

a 114×114 RSM, where each cell represented the similarity between two images. The resulting

RSM_{model} provided a structured representation of visual similarity, with higher correlations

indicating shared complex features (**Figure 1B**).

Classic Representational Similarity Analysis (cRSA)

We conducted cRSA using data from both the Object Perception dataset and the Memory

Retrieval dataset. For Object Perception, we estimated participants' classic representational

strength in each of the 26 regions of interest by calculating Spearman's rho between the

RSM_{brain} and the RSM_{model}, while excluding within-run comparisons and the diagonal cells of the

matrices (see **Figure 1C, Top**). We then assessed the strength and reliability of visual

representations across participants using one-sample t-tests (testing Fisher-transformed rho > 0)

for each of the 26 regions, applying a false discovery rate (FDR) correction with a threshold of q

= 0.05.

To evaluate cRSA's performance in detecting differences in representational strength

between conditions, we analyzed data from the main Memory Retrieval task, focusing on old

items. An RSM_{brain} for each of the 26 regions of interest was parsed into two separate RSMs:

one containing data from "Hit" trials and the other from "Miss" trials. Similarly, the model RSMs

were split based on participant responses. We then calculated Spearman's rhos for the Hit and

Miss conditions by correlating RSM$_{brain}$ and RSM$_{model}$, again excluding within-run comparisons

and the diagonal cells of the matrices. These subject-specific representational strength

measures were subsequently Fisher-transformed and analyzed using paired-sample t-tests.

Regions showing significantly higher representational strength for Hit trials compared to Miss

trials, after FDR correction with q < 0.05, were identified as *mnemonic representation regions*.

To assess the impact of unbalanced trial counts on mnemonic representational strength,

we calculated a Contrast Variance Factor (CVF) for each participant in regions showing

evidence of mnemonic representation (p < 0.05, uncorrected). The participant contrast score

was determined by subtracting the Miss representational strength ($R_{i,M}$) from the Hit

representational strength ($R_{i,H}$).

$$D_i \; = \; R_{i,H} \; - \; R_{i,M}$$

564   Next, we computed the mean difference $\bar{D}$ across all participants:

$$\bar{D} = \frac{1}{N}\sum_{i}^{N} D_i$$

565   To quantify how much each participant's mnemonic representational strength in each

566 ROI deviated from the mean (thus inflating the contrast variance), we calculated the normalized

567 absolute difference between the participant contrast score (D_i) and the average contrast score

568 ($\bar{D}$):

$$CVF_i = \frac{|D_i - \bar{D}|}{\bar{D}}$$

569   Finally, to evaluate the influence of unbalanced trial counts on the variance factor, we

570 correlated the participant CVF averaged across regions with the ratio of Hit trial count ($N_{i,H}$) to

571 Miss trial count ($N_{i,M}$).

$$Ratio_i = \frac{N_{i,H}}{N_{i,M}}$$

Trial-Level Representational Similarity Analysis (tRSA)

The tRSA approach used the same model and neural RSMs from the Object Perception dataSET

and the main Memory Retrieval dataset as described above. However, instead of correlating the

two matrices in their entirety, correlations were computed on a row-by-row basis, excluding

within-run similarities and the diagonal cells of the matrices (see **Figure 1C, Bottom**). The trial-

level estimates from both phases were then fitted to a series of mixed-effects models using the

`lme4` package in R (R Core Team, 2024) with restricted maximum likelihood methods. These

fitted models were then evaluated using the Akaike Information Criterion (AIC) to determine the

optimal random effect structure (Meteyard & Davies, 2020; Park et al., 2020). To further validate

model selection (Matuschek et al., 2017), models were refit using maximum likelihood

estimation and subjected to model selection via log-likelihood ratio tests (LRTs). The average

AICs and the results of the LRTs are reported in **Appendix 3 Table 5**. Restricted maximum

likelihood models with the selected random effects structure were further analyzed using the

`lmerTest` package. Denominator degrees of freedom were estimated using Satterthwaite's

method (Satterthwaite, 1946), and fixed effects were tested using t-tests with an alpha level of

0.05, corrected for false discovery rate (FDR) to account for multiple comparisons.

To estimate tRSA representational strength, trial-level estimates from the Object

Perception dataset were fit to a mixed-effects model with random intercepts for Participant and

Stimulus. Estimated intercepts (b > 0) were used to identify representational regions. For

detecting tRSA mnemonic representations in the main Memory Retrieval task, instead of

constructing separate Hit and Miss RSMs, row-wise correlations were performed across all trials

in the matrices (i.e., across-condition tRSA). This approach allows for trial-level estimates of

representational strength that can be subsequently categorized as "Hit" or "Miss" and analyzed

using a series of mixed-effects models. The model for mnemonic representation data included

the fixed effect of Memory Success (Hit vs. Miss trials) and random intercepts for Participant

and Stimulus.

Examining continuous modulators of representation

The capacity of tRSA in examining stimulus-level variance modulating representation was

assessed. For each item, a memorability score was calculated as the average response across

participants (on a scale of 1-4 for the main Memory Retrieval and 1-3 for Perceptual Retrieval),

normalized by the maximum possible value (4 for main retrieval and 3 for perceptual retrieval).

This approach produced two stimulus-specific continuous variables indicating the overall

confidence with which each item would be recalled. We refer to these measures as Conceptual

Memorability and Item Memorability (perceptual). The Item Memorability measure was used as

an of-interest fixed effect for trial-level representational strength estimates from the Object

Perception dataset. Additional fixed nuisance variables included Conceptual Memorability, fMRI

run, and trial-level reaction time. Random intercepts for Participant and Stimulus were also

included.

Results

Experiment 1: cRSA and tRSA comparisons in simulated data

Basic statistical properties of tRSA estimates

We simulated activity patterns from which RSMs were then derived and used to estimate representational strength. Notably, while it is difficult to fix the ground truth representational strength, we manipulated the statistical dependence between the activity patterns — and by extension, between RSM_{brain} and RSM_{model} — by injecting varying levels of measurement noise (σ^2). Simulations indicated that increasing measurement noise indeed reduced estimates of representational strength by both cRSA and tRSA (see **Figure 3A**). Also as expected, greater trial counts led to more stable estimates for both methods. Most importantly, a strong positive correlation between cRSA and tRSA estimates can be observed even in the "noisiest" simulation (i.e., $n = 10, \sigma^2 = 2$; Intercept $b_0 = 0.00$, SE = 0.01, t = 0.33, p = 0.74; Slope $b_{cRSA} = 1.00$, SE = 0.02, t = 64.95, p < 0.001). These results demonstrated the close numerical correspondence between tRSA and cRSA in estimating the overall representational strength of a given system across all trials.

Discrete conditions

Oftentimes, researchers are interested in not only representational strength *per se*, but also how representation *changes* with other factors like experimental manipulations (e.g., "easy" vs. "hard"), behavioral performance (e.g., "remembered" vs. "forgotten"), or some combination. Analyzing these differences with cRSA entails partitioning the data to generate separate condition-specific RSMs. Subsequently, an intuitive version of *within-condition* tRSA can be computed using those RSMs, and its estimates would closely track cRSA estimates, as we have demonstrated in the previous section. Instead, we advocate for *across-condition* tRSA: full RSMs are used for computing trial-level representational strength, and the estimates are then split by conditions as necessary. For a direct comparison of *within-* and *across-condition* tRSA, see **Appendix 2**.

A

B

C

Figure 3. Correspondence between classic and trial-level RSA. A) *Scatter plots of overall representational strength estimates, based on simulated activity patterns, produced by cRSA (x-axis) and tRSA (y-axis). Trial count (n) and measurement noise level (σ^2) were both varied. 50 iterations were performed for each parameter combination. Solid slopes indicate where tRSA equaled cRSA ($y = x$). **B)** Histograms of overall representational strength estimates, based on simulated activity patterns for two separate conditions, produced by cRSA (gray) and across-condition tRSA (orange). Each histogram depicted 10,000 iterations. Trial counts were varied; for example, "20 : 80" means that Condition A contained 20 trials and Condition B contained 80 trials, which was an unbalanced scenario. Effect sizes were also varied, such that the ground truth representational strength would be equal between conditions ("A = B") or stronger in Condition B ("A < B"). **C)** Histograms of condition differences in representational strength values in **B**.*

Here, we examined the correspondence of *across-condition* tRSA with cRSA in a wide

range of scenarios where data can be meaningfully split into two subsets. Specifically, we

assessed the influence of three important factors that may vary widely across studies: *raw trial*

counts, *balance of trial counts*, and *effect sizes*. Because cRSA was performed separately for

each condition, changes in the trial count or effect size of Condition B had no influence on cRSA

estimates for Condition A. However, they indeed affected estimates obtained from *across-*

condition tRSA, where all experimental trials were used for representational strength estimation.

Specifically, all else being equal, increasing the trial count in Condition B from 20 to 80 or from

80 to 320 improved the reliability of tRSA estimates in Condition A (see **Figure 3B, Rows 1 and**

3). Additionally, increasing the noise level for Condition A to be higher than that for Condition B

led to reduced tRSA estimates in Condition B as well. These effects were also reflected in the

condition difference in tRSA estimates (see **Figure 3C**). Moreover, it is critical to note that tRSA

appeared to be more reliable than cRSA in almost all simulated scenarios, especially in terms of

the estimated difference between conditions. These findings suggest that tRSA may be more

sensitive to true effects and at lower risk of false positives, i.e., reduced Type II and Type I error

rates in formal statistical tests.

Contrasting conditions

Figure 4. Testing condition differences in representational strength with varying effect sizes. *The effect size of the condition difference in representation was manipulated by changing the noise level in each condition in small increments, with higher noise levels corresponding to lower ground truth representational strengths. When the noise level was the same for both conditions, Type I error rates (red) were computed as the proportion of significant contrasts across 10,000 iterations, regardless of sign of the estimate. Otherwise, proportions were computed separately for effects of the correct sign (+, or B>A; blue) and of the incorrect sign (-, or B<A). Asterisks indicate the significance level of the test of equal proportions between simulation results from cRSA (left) and tRSA (right). Significance annotation: *** p < 0.001, ** p < 0.01, * p < 0.05.*

The next set of simulations compared across-condition tRSA to cRSA in terms of

statistical inferences, focusing on the difference in representational strength between two

conditions as a typical effect of interest in many empirical studies. We implemented the

condition differences by altering two condition-level noise parameters, where more noise would

result in lower representational strength. The statistical significance of the condition difference

b_{B-A} was estimated by a paired-sample t-test for cRSA and by a linear mixed-effects model for

tRSA, using a threshold of α = 0.05. Depending on whether the two conditions ought to have the

same quality of representation, outcomes were classified as true positives, true negatives, false

positives (Type I error), or false negatives (Type II error). The performance of cRSA and tRSA

were quantified with their specificity (better avoids false positives, 1 - Type I error rate) and

sensitivity (better avoids false negatives 1 - Type II error rate).

We first examined how cRSA and tRSA performed with effects of different sizes, under a

base within-subject experimental design consisting of 40 subjects and 200 unique stimuli

randomly and evenly split between two conditions. Across 10,000 simulations, cRSA and tRSA

were comparable in terms of specificity, with both Type I error rates neighboring around the

nominal 5% (see **Figure 4**, diagonal cells in red). As the true condition difference increased, the

sensitivity of both methods also increased accordingly. Importantly, tRSA were significantly

more sensitive to true effects than cRSA in a range of simulated scenarios, consistent with our

hypothesis (see **Figure 4**, off-diagonal cells in blue; asterisks indicate where tRSA was

statistically more sensitive then cRSA).

We further probed the robustness of cRSA and tRSA across datasets that varied in

several important experimental design factors, namely the number of participants, trial counts

per participant, and the balance of trial counts. In terms of specificity, our simulations did not

suggest an effect of those manipulated factors, as the proportions of significant contrasts

yielded by both cRSA and tRSA did not significantly deviate from the nominal alpha level of 5%.

Tests of significant contrast proportions reported by cRSA and by tRSA also failed to reject the

null hypothesis of equal proportions ($p > 0.05$), suggesting similarly acceptable Type I error

rates of both approaches (see **Figure 5, Left**).

In terms of sensitivity, our simulations revealed large impacts of all manipulated

parameters. Increasing the number of subjects or the trial count per subject improved the

sensitivity of true effects, benefiting both cRSA and tRSA substantially. Tests comparing the

sensitivity of tRSA and cRSA suggested an advantage of tRSA at small-to-medium sample

sizes of up to at least 40 subjects, and at medium trial counts of between 100 and 220 trials per

subject (see **Figure 5A-B, Right**). We additionally tested variabilities in trial counts that may

occur in real experiments. In one set of simulations, the total trial count was fixed at 200 but the

ratio of trial counts between conditions varied consistently across subjects (i.e., systematic

imbalance; **Figure 5C**). In another set of simulations, while trial counts were kept approximately

equal between conditions *on average*, subject-specific ratios varied (**Figure 5D**). In both

scenarios, increasing heterogeneity in trial counts resulted in substantially reduced sensitivity for

cRSA. This result was expected: the reliability of cRSA estimates depends largely on trial

counts (**Figure 2**), which violated the homoscedasticity assumption of the subsequent paired-

sample t-test. In the meantime, with trial-level estimates of representational strength from tRSA,

the subsequent mixed-effects models were able to properly handle this variance in trial count.

Indeed, our simulations validated that tRSA was more robust to extreme scenarios and always

significantly outperformed cRSA in sensitivity (see **Figure 5C-D, Right**).

Figure 5. Testing condition differences in representational strength with varying designs. *The robustness of cRSA and tRSA were assessed in several variations of a base experimental design consisting of 40 subjects and 200 unique stimuli (randomly and evenly split into two sets). Simulations varied in* **A)** *number of subjects,* **B)** *trial count per subject,* **C)** *the ratio of trial counts between two conditions (with a fixed total), and* **D)** *the variance of trial count ratios across participants (even split overall). In each simulation, the statistical significance of the condition difference in representational strength was determined by a paired-sample t-test for cRSA and a linear mixed-effects model for tRSA, with α = 0.05. The proportion of significant contrasts was computed across 10,000 iterations. Type I error rates were computed regardless of the direction of the contrast. Type II error rates were computed only for the correct contrast (i.e., B > A). Error bars indicate standard errors. In the left column, dashed horizontal lines mark the nominal α level of 0.05, and dotted horizontal lines mark the critical values beyond which the estimated proportion would be significantly different from α. Asterisks indicate the significance of the deviation in error rates between cRSA and tRSA results, *** p < 0.001, ** p < 0.01, * p < 0.05.*

 Continuously varying effects

A crucial advantage of tRSA over cRSA is that this approach offers a straightforward way to

model representational strength as a function of stimulus- or trial-level measures, such as image

complexity and subjective familiarity. While these measures could be discretized into a much

smaller number of bins (e.g., "low" and "high"), they are better treated as continuous variables to

preserve meaningful variance. To simulate these scenarios, we simulated a trial-level

measurement variable $v_{measured}$ that hypothetically tracks trial-level variability s_{trial} with

construct validity $r_{val} = Cor(v_{measured}, s_{trial})$. With higher construct validity, $v_{measured}$ becomes

more predictive of trial-level variability in noisiness and, therefore, representational strength. To

perform cRSA, trials were post-hoc split into two conditions by performing a median split on

$v_{measured}$ for each participant. Statistical inferences were again drawn for the difference in

representational strength between the two conditions, using both cRSA and tRSA$_{discrete}$. In

addition, we also assessed the performance of tRSA$_{continuous}$, where representational strength

was directly predicted by the measured continuous variable $v_{measured}$ without discretization.

Specificity and sensitivity were first examined for datasets with various effect sizes.

Across 10,000 iterations, cRSA had a Type I error rate (i.e., when $r_{val} = 0$) close to the nominal

rate of 5%, while both tRSA$_{discrete}$ and tRSA$_{continuous}$ showed significantly improved specificity (see

Figure 6A). As construct validity and effect size of the trial-level measurement increased (i.e.,

more negative r_{val}), sensitivity expectedly improved for all methods. Relative to cRSA,

tRSA$_{continuous}$ appeared to show slightly lower sensitivity for small effects (e.g., $r_{val} = -0.01$),

though it was also more conservative than cRSA with a lower chance of declaring significance

in the incorrect direction (B<A). Moreover, tRSA$_{continuous}$ was the most sensitive method for

moderate effects (e.g., $r_{val} = -0.04$). We further probed the robustness of cRSA and tRSA

across datasets that varied widely in the number of subjects and trial counts. Overall, we

observed that the Type I error rates were stable around the nominal 5% for cRSA, as expected.

However, both tRSA$_{discrete}$ and tRSA$_{continuous}$ demonstrated significantly enhanced specificity

across all manipulations (see **Figure 6B-D, Left**). Sensitivity expectedly improved for all three

approaches with increasing subject numbers and trial counts and hit the ceiling with enough

samples, though tRSA$_{continuous}$ significantly outperformed other methods at smaller sample sizes,

such as 10 participants with 200 trials each or 40 participants with 30 trials each (see **Figure**

6B-C, Right). Additionally, we simulated scenarios in which subject-level trial counts were

variable (e.g., missingness, exclusions), resulting in not only a reduction of total sample size but

also additional variance in any subject-level estimates. The sensitivity of cRSA dropped

substantially with this change because cRSA does not account for such variance, while tRSA-

based inferences were minimally impacted (see **Figure 6D, Right**).

Figure 6. Testing continuous modulations of representational strength with varying designs. *The robustness of cRSA and tRSA were assessed in several variations of a base experimental design consisting of 40 subjects and 200 unique stimuli presented once for each subject. Simulations varied in **A)** the true effect size of representational strength, **B)** number of subjects, **C)** trial count per subject, and **D)** the variance of trial count across subjects (assuming a fixed total). Three statistical tests were performed in each simulation: a paired-sample t-test on the difference between "high" and "low" conditions (median-split of $v_{measured}$) for cRSA, a linear mixed-effects model on the same condition difference for tRSA$_{discrete}$, and a linear mixed-effects model on the effect of continuous variable $v_{measured}$ for tRSA$_{continuous}$. Statistical significance was determined with α = 0.05. The proportion of significant results was computed across 10,000 iterations. Type I error rates were computed regardless of the sign of the estimate. Type II error rates were computed only for the correct sign (+). Error bars indicate standard errors. In the left column for **B** through **D**, dashed horizontal lines mark the nominal α level of 0.05, and dotted horizontal lines mark the critical values beyond which the estimated proportion would be significantly different from α. Asterisks indicate the significance level of the test of equal proportions between each tRSA approach and cRSA, *** p < 0.001, ** p < 0.01, * p < 0.05.*

<u>Summary of Experiment 1</u>

Collectively, our simulations offered three key insights into the commonalities and distinctions between our novel tRSA and the commonly implemented cRSA approaches. First, when the goal is to quantify the overall representational strength of the entire set of trials, tRSA produces estimates highly similar to those generated by cRSA. In other words, little information is lost in performing the trial-level computations (**Figure 3**). Second, tRSA is robust to variances that cRSA is agnostic to, such as imbalances in trial count between conditions and variability in trial count ratios across subjects. In almost all cases tRSA significantly outperformed cRSA in sensitivity (**Figure 5**). This outcome was expected, as the collapsing of trials in cRSA inevitably leads to the loss of important information regarding meaningful variances from other levels; tRSA is capable of properly modelling the multi-level variance structure. Third, tRSA is uniquely advantageous when neural representations are to be linked to continuous variables, rather than discrete conditions. The voided need for post-hoc discretization prevents additional loss of meaningful variance from the modulators, and $tRSA_{continuous}$ demonstrated significantly enhanced specificity and sensitivity over cRSA in a wide range of scenarios (**Figure 6**).

Experiment 2: cRSA and tRSA comparison in fMRI data

<u>Trial-level RSA estimates for Perceptual and Mnemonic Processing</u>

The first goal of Experiment 2 was to compare the results from tRSA and cRSA approaches obtained from real fMRI data. We used fMRI data collected when participants implicitly named 114 colored images of everyday objects in a white background (Object Perception; see **Figure 7A**). Estimates of regional representational strength in the tRSA models were compared with mean cRSA values across participants, for each region of interest. Unsurprisingly, the tRSA model estimates and the cRSA mean correlation values demonstrated similar distributions (**Figure 7B**) and were highly correlated (**Figure 7C**). Critically, however, the two approaches yielded different results in terms of statistically significant regions. Specifically, the cRSA approach identified four significant regions in the LOC during Object Perception, whereas the tRSA approach identified two additional regions within the LOC (**Table 1**, **Figure 7D**, and **Figure 7E**). This discrepancy indicated the ability of tRSA to more accurately and robustly identify representational regions.

768
Figure 7. tRSA outperforms cRSA in identifying representational regions during object perception. A)
Visualization of the Object Perception Task. The fMRI task required participants to view 114 labeled objects and rate
how well the labels describe the objects on a scale of 1 to 4 (mean 3.59). B) Density plots (y-axis) of regional
representational strengths (x-axis) for tRSA (model estimates, dark) and cRSA (mean correlation values, light).
Regions with significant representational strength greater than zero (q < 0.05) are highlighted in red. C) Scatter plot
showing the correlation between regional representational strengths from tRSA (model estimates, y-axis) and cRSA
(mean correlation values, x-axis). Regions with significant tRSA representation are highlighted in red, and those
significant in cRSA are outlined in red. The representational strength measures are highly correlated across regions (r
= 0.98, p < 0.001). D) Bar graph of t-statistics for each of the 26 regions of interest. Representation t-statistics (y-axis)
from cRSA (light) and tRSA (dark) across 26 regions of interest (x-axis). Regions significant after FDR correction (q <
0.05) are highlighted in red. E) Brain regions with significant representation. Regions in light red were identified by the
tRSA and cRSA. Regions in dark red were identified by the tRSA method only.

Table 1. Representation regions identified by cRSA and tRSA.

REGION	SubArea	Coordinates (x, y, z)	cRSA					tRSA				
			Mean	SE	t Values	p	q	coeff	SE	t Values	p	q
LEFT IPL	A40c, caudal area 40(PFm)	-56, -49, 38	-0.002	0.006	-0.276	0.785	0.887	0.000	0.005	-0.039	0.969	0.980
RIGHT IPL	A40c, caudal area 40(PFm)	57, -44, 38	0.000	0.008	0.053	0.958	0.992	0.001	0.006	0.199	0.843	0.914
LEFT IPL	A39rv, rostroventral area 39(PGa)	-47, -65, 26	0.012	0.009	1.273	0.212	0.394	0.010	0.007	1.461	0.154	0.307

RIGHT IPL	A39rv, rostroventral area 39(PGa)	53, -54, 25	0.012	0.008	1.511	0.141	0.333	0.013	0.007	1.901	0.066	0.215
LEFT ITC	A20iv, intermediate ventral area 20	-45, -26, -27	0.002	0.007	0.352	0.727	0.859	0.003	0.005	0.533	0.598	0.777
LEFT ITC	A20r, rostral area 20	-43, -2, -41	-0.011	0.007	-1.383	0.178	0.357	-0.006	0.006	-1.027	0.314	0.510
LEFT ITC	A20il, intermediate lateral area 20	-56, -16, -28	-0.011	0.006	-1.722	0.095	0.309	-0.008	0.005	-1.587	0.123	0.278
RIGHT ITC	A20iv, intermediate ventral area 20	46, -14, -33	-0.010	0.007	-1.385	0.176	0.357	-0.008	0.005	-1.563	0.128	0.278
RIGHT ITC	A20r, rostral area 20	40, 0, -43	0.005	0.006	0.781	0.442	0.676	0.002	0.005	0.419	0.679	0.824
RIGHT ITC	A20il, intermediate lateral area 20	55, -11, -32	-0.011	0.007	-1.642	0.111	0.320	-0.009	0.006	-1.660	0.107	0.277
LEFT ITC	A37elv, extreme lateroventral area37	-51, -57, -15	-0.003	0.007	-0.470	0.642	0.859	0.000	0.006	0.025	0.980	0.980
LEFT ITC	A37vl, ventrolateral area 37	-55, -60, -6	0.003	0.007	0.418	0.679	0.859	0.007	0.005	1.331	0.193	0.358
LEFT ITC	A20cl, caudolateral of area 20	-59, -42, -16	0.013	0.008	1.569	0.127	0.329	0.011	0.006	1.728	0.094	0.271
LEFT ITC	A20cv, caudoventral of area 20	-55, -31, -27	0.006	0.009	0.657	0.516	0.746	0.005	0.007	0.765	0.450	0.651
RIGHT ITC	A37elv, extreme lateroventral area37	53, -52, -18	-0.006	0.007	-0.807	0.426	0.676	-0.002	0.006	-0.354	0.726	0.824
RIGHT ITC	A37vl, ventrolateral area 37	54, -57, -8	0.000	0.007	0.010	0.992	0.992	0.002	0.006	0.350	0.729	0.824
RIGHT ITC	A20cl, caudolateral of area 20	61, -40, -17	0.000	0.008	-0.019	0.985	0.992	0.005	0.007	0.696	0.492	0.673
RIGHT ITC	A20cv, caudoventral of area 20	54, -31, -26	0.007	0.007	0.983	0.333	0.577	0.008	0.006	1.233	0.227	0.393
LEFT LOC	mOccG, middle occipital gyrus	-31, -89, 11	0.021	0.011	2.015	0.053	0.196	0.022	0.009	2.345	0.023	0.086
LEFT LOC	V5/MT+, area V5/MT+	-46, -74, 3	**0.032**	**0.010**	**3.126**	**0.004**	**0.033**	**0.030**	**0.009**	**3.440**	**0.002**	**0.010**
LEFT LOC	OPC, occipital polar cortex	-18, -99, 2	-0.004	0.010	-0.393	0.697	0.859	0.008	0.010	0.772	0.442	0.651
LEFT LOC	iOccG, inferior occipital gyrus	-30, -88, -12	0.024	0.009	2.560	0.016	0.067	**0.027**	**0.009**	**3.115**	**0.003**	**0.013**
RIGHT LOC	mOccG, middle occipital gyrus	34, -86, 11	**0.038**	**0.009**	**4.082**	**0.000**	**0.004**	**0.038**	**0.008**	**4.533**	**0.000**	**0.001**

RIGHT LOC	V5/MT+, area V5/MT+	48, -70, -1	0.026	0.006	4.139	0.000	0.004	0.024	0.006	3.933	0.000	0.004
RIGHT LOC	OPC, occipital polar cortex	22, -97, 4	0.025	0.010	2.573	0.015	0.067	**0.030**	**0.010**	**3.128**	**0.003**	**0.013**
RIGHT LOC	iOccG, inferior occipital gyrus	32, -85, -12	0.028	0.009	3.018	0.005	0.033	0.029	0.009	3.334	0.001	0.010

Subject-level variance not accounted for by cRSA

The second goal of Experiment 2 was to demonstrate the utility of tRSA in accounting for the

heterogeneity in subject-level variance. In the main Memory Retrieval task, experimental trials

were categorized as "Hit" or "Miss" based on participants' memory success, and the exact

number of trials in each condition varied widely across participants (**Figure 8A, Bottom**).

Importantly, the difference in the number of trials had a strong impact on the estimation of

representational strength (see **Figure 2**). Participants with fewer trials in a given condition

exhibited a noticeably wider distribution of representational strength values across ROIs in that

condition, indicating that trial count was a substantial source of across-subject variance indeed

(see **Figure 8B**). Moreover, trial count was also negatively associated with the standard

deviation of representational strengths across ROIs, for both Hit trials (rho = -0.37, p = 0.043)

and Miss trials (rho = -0.71, p < 0.001). However, this subject-level variance is often not

accounted for in subsequent group-level t-test or ANOVA, which assumes that each participant

contributes equally reliable estimates (i.e., homoscedasticity). Indeed, CVFs were much higher

for participants with more extreme Hit to Miss trial counts (rho = 0.45, p = 0.016; see **Figure 8C**).

This issue of neglected heteroscedasticity remains when conditional contrasts (e.g., Hit

minus Miss) are computed. Given the nonlinear relationship between trial counts and the

reliability of correlations (see **Figure 2**), a more extreme trial imbalance (e.g., 100 Hits and 10

Misses, versus 70 Hits and 40 Misses) would also lead to a less reliable estimate of the

difference. To demonstrate this issue in real fMRI data, we computed the CVF for each

participant, measuring how much their Hit-Miss contrast in representational strength estimates

deviated from the group mean. Indeed, CVFs were much higher for participants with more

extreme Hit to Miss trial counts (rho = 0.45, p = 0.016; see **Figure 8C**). Critically, the two

participants with Hit to Miss ratios < 1 were excluded from this correlation (since in those cases

we would expect an increased CVF), but their data points are included in the corresponding

figure for transparency.

Figure 8. Unmodeled within- and between-participant variance in cRSA for mnemonic representations. A) *Top: Visualization of the main memory task. Participant recognition and judgement confidence was tested for 144 concepts (114 "old", 30 "new").* **Bottom:** *Stacked bar plots with the number of "Hit" (blue) and "Miss" (gray) trials (y-axes) for each participant (x-axis). Participants were sorted by their hit to miss ratio in descending order.* **B)** *Density plots of cRSA representational strength (y-axes) across the 26 ROIs (x-axes) for Hits (blue) and Misses (gray) for each participant, sorted by descending Hit-to-Miss count ratio. The Hit-to-Miss ratios were displayed in the top-left corner of each subplot, with the font color transitioning from blue (indicating more Hits) to gray (indicating more Misses).* **C)** *Scatter plot illustrating the influence of the Hit-to-Miss ratio (x-axis) on the participant CVFs (y-axis). The Spearman's correlation was significant, with a coefficient of 0.45 and a p-value of 0.016. Two participants are marked X and were excluded from this correlation as their Hit-to Miss ratio is less than 1.* **D)** *Density plots (y-axis) of cRSA representational strength across participants for Hits (blue) and Misses (gray).* **E)** *Regions exhibiting significant cRSA mnemonic representation (Hits > Misses). Regions highlighted in blue were significant after FDR correction with q < 0.05. Regions in gray were significant at p < 0.05 but did not survive FDR correction.*

Additionally, the distributions of representational strengths for Hits and Misses across participants were unequal. Since most participants had more Hit trials than Miss trials (Hit-to-Miss Ratio mean = 3.7, median = 3.1), the distribution of representational strength values was broader for misses compared to hits (**Figure 8D**). Ultimately, results from cRSA revealed significant mnemonic representation in one right LOC region and one right anterior ITC region, with two additional ITC regions showing trend-level significance (**Table 2**, **Figure 8E**); these outcomes were revisited in comparison to the tRSA approach below. Together, these results demonstrate that cRSA failed to model the across-subject variance in real fMRI data, which stemmed from the inevitable variability in trial count ratios affecting the reliability of each participant's cRSA contrast estimates. The violation of statistical assumptions challenged the interpretability of standard t-tests in detecting representational regions.

<u>Subject-level variance accounted for by tRSA</u>

We also sought to assess how the tRSA approach would improve the estimates of

representational strength for memory success. The mixed-effects models used to test tRSA

mnemonic representations supporting retrieval identified four significant mnemonic

representation regions: one in the right LOC and three in the right ITC (**Table 2**, **Figure 9A**, and

Figure 9B). While the t-statistics for tRSA and cRSA showed a correlation across ROIs (**Figure**

9C), the tRSA approach, which produced trial-level estimates of representational strength, was

able to detect mnemonic representation regions that the cRSA approach did not. This result

demonstrated the enhanced sensitivity of tRSA in identifying subtle differences in

representational strength. Moreover, a region in the LOC, initially considered a mnemonic

representation region by the cRSA method — largely due to data from participants with low miss

trial counts (**Appendix 3 Table 4**) — was correctly excluded from being classified as such by

tRSA (**Figure 9A**, **Figure 9B**). This result highlighted tRSA's improved specificity in the

identification of true mnemonic representation regions by reducing potential biases introduced

by variances in trial counts that went neglected by cRSA.

Figure 9. tRSA outperforms cRSA in detecting mnemonic representations. A) *Bar graph of t Statistics for each*
of the 26 regions of interest. Mnemonic representation t-statistics (y-axis) from cRSA (light) and tRSA (dark) across
26 regions of interest (x-axis). Regions that are significant after FDR correction (q < 0.05) are highlighted in blue. ***B)***
Brain regions with significant mnemonic representation identified by tRSA are shown in blue. The region that was
significant in cRSA but not in tRSA is depicted in light blue. ***C)*** *Scatter plot of t-statistics calculated from tRSA (y-axis)*
and cRSA (x-axis), showing a significant Pearson correlation (r = 0.49, p = 0.010). Significant tRSA regions are
highlighted in blue. Significant cRSA regions are outlined in light blue.

Table 2. Mnemonic representation regions identified by cRSA and tRSA.

			cRSA					tRSA				
REGION	SubArea	Coordinates	Mean	SE	t Values	p	q	coeff	SE	t Values	p	q

		(x, y, z)										
LEFT IPL	A40c, caudal area 40(PFm)	-56, -49, 38	0.011	-0.012	0.967	0.341	0.617	-0.003	0.005	-0.583	0.560	0.661
RIGHT IPL	A40c, caudal area 40(PFm)	57, -44, 38	0.006	-0.002	0.325	0.747	0.747	0.002	0.005	0.445	0.656	0.742
LEFT IPL	A39rv, rostroventral area 39(PGa)	-47, -65, 26	0.020	-0.011	1.418	0.167	0.546	0.008	0.005	1.842	0.066	0.213
RIGHT IPL	A39rv, rostroventral area 39(PGa)	53, -54, 25	0.007	-0.015	1.048	0.303	0.607	0.005	0.005	1.024	0.306	0.612
LEFT ITC	A20iv, intermediate ventral area 20	-45, -26, -27	0.010	-0.014	1.250	0.221	0.546	0.004	0.005	0.764	0.445	0.661
LEFT ITC	A20r, rostral area 20	-43, -2, -41	-0.022	-0.044	0.894	0.379	0.617	0.005	0.005	1.081	0.280	0.606
LEFT ITC	A20il, intermediate lateral area 20	-56, -16, -28	0.003	-0.011	0.498	0.623	0.704	-0.003	0.005	-0.599	0.549	0.661
RIGHT ITC	A20iv, intermediate ventral area 20	46, -14, -33	0.002	-0.011	0.555	0.584	0.690	**0.013**	**0.005**	**2.678**	**0.007**	**0.048**
RIGHT ITC	A20r, rostral area 20	40, 0, -43	*0.015*	*-0.051*	*3.289*	*0.003*	*0.039*	**0.014**	**0.005**	**2.704**	**0.007**	**0.048**
RIGHT ITC	A20il, intermediate lateral area 20	55, -11, -32	0.003	-0.020	1.203	0.239	0.546	0.009	0.005	1.886	0.059	0.213
LEFT ITC	A37elv, extreme lateroventral area37	-51, -57, -15	0.024	0.007	0.903	0.374	0.617	0.001	0.005	0.285	0.776	0.841
LEFT ITC	A37vl, ventrolateral area 37	-55, -60, -6	0.012	-0.007	0.825	0.416	0.636	-0.006	0.005	-1.272	0.203	0.481
LEFT ITC	A20cl, caudolateral of area 20	-59, -42, -16	0.014	0.030	-0.727	0.473	0.683	0.004	0.005	0.783	0.434	0.661
LEFT ITC	A20cv, caudoventral of area 20	-55, -31, -27	0.021	-0.016	1.582	0.125	0.541	0.001	0.005	0.147	0.883	0.918
RIGHT ITC	A37elv, extreme lateroventral area37	53, -52, -18	0.006	-0.019	1.265	0.216	0.546	0.009	0.005	1.978	0.048	0.213
RIGHT ITC	A37vl, ventrolateral area 37	54, -57, -8	0.001	-0.013	0.664	0.512	0.684	0.003	0.005	0.663	0.508	0.661
RIGHT ITC	A20cl, caudolateral of area 20	61, -40, -17	0.008	-0.036	2.137	0.041	0.268	0.008	0.005	1.767	0.077	0.223
RIGHT ITC	A20cv, caudoventral of area 20	54, -31, -26	0.013	-0.031	2.353	0.026	0.222	**0.014**	**0.005**	**3.043**	**0.002**	**0.048**

Region		Coordinates										
LEFT LOC	mOccG, middle occipital gyrus	-31, -89, 11	0.030	-0.001	1.169	0.252	0.546	0.003	0.004	0.661	0.509	0.661
LEFT LOC	V5/MT+, area V5/MT+	-46, -74, 3	0.022	0.013	0.451	0.655	0.710	0.003	0.005	0.740	0.459	0.661
LEFT LOC	OPC, occipital polar cortex	-18, -99, 2	0.028	-0.004	1.294	0.206	0.546	0.000	0.004	-0.035	0.972	0.972
LEFT LOC	iOccG, inferior occipital gyrus	-30, -88, -12	0.001	0.010	-0.393	0.697	0.725	0.004	0.005	0.783	0.433	0.661
RIGHT LOC	mOccG, middle occipital gyrus	34, -86, 11	0.016	0.000	0.642	0.526	0.684	0.004	0.004	0.860	0.390	0.661
RIGHT LOC	V5/MT+, area V5/MT+	48, -70, -1	0.009	-0.037	1.995	0.056	0.289	**0.013**	**0.005**	**2.867**	**0.004**	**0.048**
RIGHT LOC	OPC, occipital polar cortex	22, -97, 4	0.026	-0.062	3.461	0.002	0.039	0.008	0.005	1.875	0.061	0.213
RIGHT LOC	iOccG, inferior occipital gyrus	32, -85, -12	0.005	-0.004	0.556	0.583	0.690	0.006	0.004	1.411	0.158	0.412

Estimations of continuous modulators

Our final goal was to assess the utility of tRSA in testing hypotheses regarding continuous
modulators of representational strength. Here, we focused on the effect of item memorability, a
stimulus-level variable (see **Figure 10A**). The tRSA approach successfully detected continuous,
stimulus-level modulation of representational strength during Object Perception, when
participants were engaged in basic-level naming of color objects displayed on a white
background; notably, no memory task was engaged before or during this phase of the
experiment. Four regions within the LOC showed significant modulation by Perceptual
Memorability, a measure based on average responses in the Perceptual Retrieval task (see
Table 3 and Figure 10B). While not the explicit focus of this analysis, the analyses also
identified significant effects of the nuisance variables, Conceptual Memorability, and reaction
time in five regions of interest (**Appendix 3, Table 6**) within the LOC. These regions are often
associated with processing the constituent categories or visual features of an object (Tyler et al.,
2013), and consistent with the view that the memorability of images can be predicted by
statistical properties of semantic features (Bainbridge, 2022; Hovhannisyan et al., 2021; Kramer
et al., 2023). Critically, memorability is a robust stimulus property that is consistent across
participants and paradigms(Bainbridge, 2022). Moreover, object memorability effects have been
replicated using a variety of methods aside from tRSA, including univariate analyses and
representational analyses of neural activity patterns where trial-level neural activity pattern
estimates are correlated directly with object memorability (Slayton et al., 2025).

Figure 10. tRSA captures stimulus-level modulations on representation. A) *Distribution of Item Memorability.*
Density plot of memorability values demonstrates a wide distribution of memorability scores (i.e., the average
confidence of remembering a particular item). This stimulus-level variance is an underexplored target of
representational analyses. **B)** *Cortical representational effects of Memorability. Relationship between item-level*
Memorability and representational strength, as assessed with tRSA, for each of the 26 regions of interest. Trial-level
representational strength estimates from Object Perception were significantly modulated by a continuous, stimulus-
level measure of Item Memorability in four regions (blue). The t-statistics for this modulation were plotted (y-axis)
across regions of interest (x-axis).

Table 3. Continuous modulation in tRSA.

REGION	SubArea	Coordinates (x, y, z)	coeff	SE	t Values	p	q
LEFT IPL	A40c, caudal area 40(PFm)	-56, -49, 38	-0.036	0.072	-0.496	0.620	0.949
RIGHT IPL	A40c, caudal area 40(PFm)	57, -44, 38	0.038	0.069	0.547	0.584	0.949
LEFT IPL	A39rv, rostroventral area 39(PGa)	-47, -65, 26	-0.015	0.068	-0.227	0.820	0.949
RIGHT IPL	A39rv, rostroventral area 39(PGa)	53, -54, 25	-0.001	0.071	-0.018	0.986	0.986
LEFT ITC	A20iv, intermediate ventral area 20	-45, -26, -27	0.044	0.071	0.621	0.534	0.949
LEFT ITC	A20r, rostral area 20	-43, -2, -41	0.025	0.079	0.315	0.752	0.949
LEFT ITC	A20il, intermediate lateral area 20	-56, -16, -28	0.068	0.072	0.955	0.340	0.949
RIGHT ITC	A20iv, intermediate ventral area 20	46, -14, -33	-0.013	0.074	-0.177	0.860	0.949
RIGHT ITC	A20r, rostral area 20	40, 0, -43	-0.046	0.078	-0.587	0.558	0.949

RIGHT ITC	A20il, intermediate lateral area 20	55, -11, -32	0.021	0.071	0.290	0.771	0.949
LEFT ITC	A37elv, extreme lateroventral area37	-51, -57, -15	0.029	0.071	0.409	0.682	0.949
LEFT ITC	A37vl, ventrolateral area 37	-55, -60, -6	0.105	0.075	1.405	0.160	0.694
LEFT ITC	A20cl, caudolateral of area 20	-59, -42, -16	-0.014	0.068	-0.201	0.841	0.949
LEFT ITC	A20cv, caudoventral of area 20	-55, -31, -27	-0.027	0.069	-0.389	0.698	0.949
RIGHT ITC	A37elv, extreme lateroventral area37	53, -52, -18	-0.073	0.071	-1.022	0.307	0.949
RIGHT ITC	A37vl, ventrolateral area 37	54, -57, -8	0.011	0.070	0.156	0.876	0.949
RIGHT ITC	A20cl, caudolateral of area 20	61, -40, -17	-0.003	0.072	-0.038	0.970	0.986
RIGHT ITC	A20cv, caudoventral of area 20	54, -31, -26	-0.036	0.072	-0.506	0.613	0.949
LEFT LOC	mOccG, middle occipital gyrus	-31, -89, 11	**0.255**	**0.080**	**3.166**	**0.002**	**0.012**
LEFT LOC	V5/MT+, area V5/MT+	-46, -74, 3	**0.258**	**0.071**	**3.614**	**0.000**	**0.008**
LEFT LOC	OPC, occipital polar cortex	-18, -99, 2	**0.276**	**0.089**	**3.113**	**0.002**	**0.012**
LEFT LOC	iOccG, inferior occipital gyrus	-30, -88, -12	0.019	0.083	0.223	0.823	0.949
RIGHT LOC	mOccG, middle occipital gyrus	34, -86, 11	0.201	0.082	2.456	0.014	0.073
RIGHT LOC	V5/MT+, area V5/MT+	48, -70, -1	0.089	0.077	1.149	0.251	0.931
RIGHT LOC	OPC, occipital polar cortex	22, -97, 4	**0.277**	**0.089**	**3.107**	**0.002**	**0.012**
RIGHT LOC	iOccG, inferior occipital gyrus	32, -85, -12	0.040	0.083	0.485	0.628	0.949

Summary of Experiment 2

Three key takeaways from Experiment 2 mirrored those from Experiment 1. First, while access
to ground truths was not possible with empirical fMRI datasets, results from tRSA and cRSA
approaches showed a relatively high degree of correspondence as before (**Figure 7C**).

Nonetheless, modeling trial-level estimates from tRSA showed improved sensitivity to neural

representations in the Object Perception dataset, as the tRSA model was able to weigh study

subjects with different numbers of trials appropriately (**Figure 7D**). Second, in the Memory

Retrieval dataset, participants had unbalanced and heterogenous distributions of trial counts in

two conditions ("Hits" and "Misses"), as expected with any psychological task focusing on

subject performance (**Figure 8A**). tRSA's improved characterization can be seen in multiple

empirical outcomes: tRSA was able to detect mnemonic representation regions that the cRSA

approach missed (improved; sensitivity **Figure 9B**), and afforded more appropriate weighting of

participant's contrast estimates while maintaining similar outcome statistics as cRSA (**Figure**

9C). Third, tRSA supported the investigation of research questions that cannot be readily

addressed with cRSA, namely the trial- or stimulus-level modulations of representational

strength. We demonstrated this point using Item Memorability — a stable stimulus property that

is thought to contribute to memory independently of task context, experimental context, or

individual differences. Representational strength in several regions in the ventral stream varied

continuously with stimulus-level memorability (**Figure 10B**). Moreover, model-fits became the

strongest when the models also incorporated trial-level variables such as fMRI run and reaction

time (**Appendix 3 Table 6**). These findings showed that the representational strength estimates

produced by tRSA indeed captured the multi-level variance structure in the data and that tRSA

can be implemented to study item-specific or trial-level modulators of representational strength

effectively.

Discussion

This paper formally presents tRSA — a novel technique for evaluating the strength of neural

representation at the level of individual experimental trials. The performance of tRSA was

evaluated and compared to that of cRSA using both simulations (Experiment 1) and empirical

fMRI datasets (Experiment 2). Three principal insights can be drawn from these analyses. First,

tRSA produces highly similar estimates of *overall* representational strength as cRSA such this

new approach comes with little cost in efficacy. Second, tRSA is robust to subject-level

variances that would be neglected by cRSA, namely the trial count differences across subjects.

With both simulations and empirical datasets, tRSA demonstrated enhanced sensitivity over

cRSA in detecting true effects. Third, tRSA provides an opportunity to examine continuous

modulators of representational strength with decent specificity and sensitivity. With the empirical

fMRI dataset, we demonstrated that tRSA was able to detect significant associations between

representational strength and item-level memorability, as well as trial-level nuisance variables.

Below we discuss the methodological and conceptual implications of the tRSA approach for the

field of cognitive neuroscience and beyond.

Similarities between cRSA and tRSA

Since the advent of cRSA, the method has been widely implemented in studies of neural

representations with great success (Dimsdale-Zucker & Ranganath, 2018; Kriegeskorte et al.,

2008). Our first and foremost objective was to ensure that our novel tRSA technique produces

estimates of representational strength that are comparable to cRSA. This objective was

achieved in both Experiment 1 (simulations) and Experiment 2 (real fMRI data). Simulations

suggested that tRSA and cRSA estimates reacted in very similar ways to manipulations of the

number of subjects, trial counts, and noise level. Although tRSA and cRSA both aim to quantify

representational strength, they differ in how they operationalize this concept. cRSA summarizes

the correspondence between RSMs as a single measure, such as the matrix-wise Spearman

correlation. In contrast, tRSA computes such correspondence for each trial, enabling estimates

at the level of individual observations. This flexibility allows trial-level variability to be modeled

directly, but also introduces subtle differences in what is being measured. Nonetheless, our

simulations showed that, although numerical differences occasionally emerged—particularly

when comparing between-condition tRSA estimates to within-condition cRSA estimates—the

magnitude of divergence was small and did not affect the outcome of downstream statistical

tests. Analyses with real fMRI datasets corroborated their correspondence, showing highly

similar distributions of estimated representational strength across the brain. These results

confirm that our novel tRSA approach performs at least no worse than cRSA. In other words,

researchers can confidently replace their existing cRSA analyses with the tRSA framework, not

having to be concerned about the loss of information or inferior statistical performance. It is also

important to note that some prior work has examined similarly fine-grained representations in

time-resolved neuroimaging data, such as the temporal generalization method introduced by

King et al. (King et al., 2019). Their approach trains classifiers at each time point and tests them

across all others, resulting in a temporal generalization matrix that reflects decoding accuracy

over time. While such matrices share some structural similarity with RSMs, they do not involve

correlating trial-level pattern vectors with model RSMs nor do their second-level models include

trial-wise, subject-wise, and item-wise variability simultaneously. In general, our analyses with

both simulations and real fMRI datasets demonstrated several important advantages of tRSA

over cRSA in a wide range of scenarios.

Methodological significance

Statistically, tRSA is designed to properly capture the multi-level variance structure in the data,
yielding improved specificity and sensitivity. An important motivation of ours for devising this
novel tRSA technique accords with a steady emergence in many scientific fields that advocates
for proper treatments of the multi-level variance structure in the data (Dedrick et al., 2009;
Winter & Grice, 2021; Yarkoni, 2022). As laid out in the Introduction, we argue that (at least)
four independent sources of variance contribute to how strongly a given neural system
represents a single event (e.g., looking at an image of "basketball"): condition-level, subject-
level, stimulus-level, and trial-level.

Subject-level variance was a major focus of analysis in both Experiments. Research
subjects are samples (ideally, random and representative) drawn from some population of
interest. Barring quantifiable individual differences that may be relevant to the cognitive
functions being studied (e.g., age, education, personality traits), subjects are considered to vary
randomly around the population-level mean, which is often the focus of analysis. In cRSA,
subject-level estimates of representational strength or condition differences are typically entered
into a general linear model where homoscedasticity is assumed (e.g., t-test). However, this
assumption is easily violated due to heterogeneity in subject-level trial counts, resulting in
unreliable model outputs. Indeed, artificially induced variability in trial counts led to catastrophic
reductions in the sensitivity of cRSA (Experiment 1). Empirical studies that select trials based on
subjective performance or expect to have extensive missingness or exclusions must be wary of
this problem, as we demonstrated the same issue of cRSA using real fMRI data from an
episodic memory study (Experiment 2). Critically, tRSA proved to be more robust to this subject-
level heteroscedasticity issue in both Experiments, for trial count information was available to
the subsequent models with subjects entered as random factors (Yarkoni, 2022).

Stimulus-level variance was another focus of our investigations. A major advantage of
RSA over multivariate pattern classification techniques is that it allows the use of "condition-rich"
experimental designs with large and diverse collections of stimuli, so long as meaningful
hypotheses can be constructed in the form of an RSM_{model} (Kriegeskorte et al., 2008). For
instance, using an RSM_{model} based on human similarity judgments, past work has implemented
RSA on neuroimaging data collected with nearly two thousand unique natural object images
(THINGS database; Hebart et al., 2023). Various stimulus properties have also been the target
of neural representation research, such as the real-world size of objects (T. Huang et al., 2022),
the geographical location of landmarks (Morton et al., 2021), or more abstractly, visual and

semantic features of naturalistic images (Devereux et al., 2018; Jozwik et al., 2023; Naspi et al.,

2021). Despite such prevalent appreciation for the neurocognitive relevance of stimulus

properties, cRSA often does not account for the fact that the same stimulus (e.g., "basketball")

is seen by multiple subjects and produces statistically dependent data an issue addressed by

Schütt et al. (2023), who developed cross validation and bootstrap methods that explicitly model

dependence across both subjects and stimulus conditions. With tRSA, this issue is at least

partially addressed by modeling stimulus identity as random effects, resulting in generalizability

and reliability (Chen et al., 2021; Yarkoni, 2022). Admittedly, a complete resolution of this

stimulus-as-fixed-effect fallacy would require stimulus information to be incorporated in any

preceding procedures, including first-level models of fMRI data (Westfall et al., 2017); while

beyond the scope of the current paper, these relevant analytical pipelines may be integrated for

a full solution of the fallacy. Furthermore, as demonstrated in Experiment 2, tRSA supports the

straightforward investigation of how representational strength varies with stimulus-level

properties such as memorability. With the flexibility of tRSA, future studies may freely explore

other interesting stimulus-level research questions.

Of note, in the current paper, we only examined experimental designs where each

unique stimulus is presented once, i.e., no repetitions. Repetitions are sometimes included as

targets to which participants should respond, in order to promote engagement level (Allen et al.,

2022; Chang et al., 2019; Lahner et al., 2024). Additionally, some preprocessing or modeling

procedures use repetitions to improve the accuracy of their estimates of neural activity

responses and representations (Charest et al., 2018; Prince et al., 2022), though the

effectiveness of this approach may depend on various other factors (Ritchie et al., 2021).

Importantly, repetitions have been found to robustly induce neural activity adaptation or

repetition suppression in task-relevant brain regions (Barron et al., 2016; Grill-Spector et al.,

2006), and this phenomenon has profound impacts on multi-voxel activity patterns as well

(Mazurchuk et al., 2023). While beyond the scope of the current paper, we briefly mention two

possible treatments of stimulus repetitions in implementing tRSA. For one, repetitions can be

collapsed in first-level models of brain recordings for more reliable estimations of stimulus-

specific neural activations; in this case, any subsequent analyses including tRSA can simply

proceed as if individual stimuli are only presented once. Alternatively, repetitions can also be

kept as separate events for which individual tRSA estimates are assigned; this option allows

one to probe the stability of neural representations across time and repetitions. In either case,

our tRSA approach can flexibly suit the various goals of research.

Trial-level variance refers to the effect on the estimations of neural representations by

factors that vary from trial to trial. For example, attention level fluctuates during the task and

changes the fidelity of neural representations (Aly & Turk-Browne, 2016; Rothlein et al., 2018).

Like stimulus-level variance, trial-level variance is not accounted for by cRSA as the comparison

of RSMs collapses across trials. In our simulations, we demonstrated that tRSA can indeed

capture trial-level variance and reliably estimate its effect on representational strength

(Experiment 1). In a real fMRI dataset, we found that reaction time, a trial-level nuisance

variable, also had statistically significant effects on representational strength (Experiment 2). In

addition, past research has found that pure physiological changes in pupillary size, cardiac

rhythm, and respiration may also influence both neural and cognitive processes (Critchley &

Garfinkel, 2018; van der Wel & van Steenbergen, 2018). While a portion of those effects could

be due to the incomplete removal of artifacts during signal preprocessing, some physiological

changes may also have intriguing neurocognitive relevance that is worth exploring in future

studies.

1050

Conceptual significance

Fundamentally, approaching RSA at the level of individual trials is an advancement in terms of

not only *methodology* (discussed above) but also *conceptualization*. The notion of *neural*

representation, albeit used more broadly than the phrase is intended to, emphasizes the link

between the representee (contents being represented, such as stimuli or memories) and its

representative (alternative format of the content, such as neural activity) (Baker et al., 2022;

Favela & Machery, 2023; Vilarroya, 2017). Collapsing trial-level information in its formulation,

cRSA could only indicate the quality of a *kind* of representation or the *overall* representational

strength across events. Instead, tRSA provides a measure that directly corresponds to the

conceptualization of representation, with each trial or event receiving its own estimated

representational strength. This level of analysis is consistent with previous studies that focused

on quantifying the similarity of multi-voxel activity patterns across different trials (S. Huang, Faul,

et al., 2024; Wing et al., 2020; Yu et al., 2024) and at different stages of memory (Ritchey et al.,

2013; Shao et al., 2023). As such, tRSA provides a versatile tool for inquiring about many

different brain-behavior relationships at an appropriate level of analysis and with straightforward

interpretations (Becker et al., 2024; Howard et al., 2024; Morales-Torres et al., 2024; Naspi et

al., 2023; Pacheco-Estefan et al., 2024). Notably, tRSA is not limited to neuroimaging data; past

research has also implemented this approach to perform item-specific analyses on behavioral

data (Walsh & Rissman, 2023).

At a broader level, the tRSA approach also engenders a host of other innovative

techniques. While a number of studies have addressed the validity of measuring

representational geometry using designs with multiple repetitions, a conceptual benefit of the

tRSA approach is the reliance on a regression framework that engenders the testing of

competing *conceptual* models of stimulus representation (e.g., taxonomic vs. encyclopedic

semantic features, as in Davis et al., 2021). The emerging research on representational

connectivity focuses on the intersection of representational information and functional

connectivity analyses, and seeks to uncover new multivariate views on how concepts are

distributed across the brain (Anzellotti & Coutanche, 2018). Using the tRSA approach, trial-level

representational strength values from any pair of brain regions may be correlated to yield their

model-based representational connectivity (S. Huang, De Brigard, et al., 2024; Karimi-

Rouzbahani et al., 2022). Trial-level representational strength values may also be combined

with other trial-level measures of neural activity such as univariate activation to probe diverse

inter-regional interactions that are theoretically motivated (S. Huang, Howard, et al., 2024).

1084

1085   Methodological considerations

While linear mixed-effects modeling offers a powerful framework for analyzing representational

similarity measures, it is critical that researchers carefully construct and validate their models. In

our simulations, we designed our model RSM to be the "true" RSM for demonstration purposes.

However, researchers should always consider if their models match the goals of their analysis,

including 1) constructing the random effects structure that will converge in their dataset and 2)

testing their model fits against alternative structures (Meteyard & Davies, 2020; Park et al., 2020)

and 3) considering which effects should be considered random or fixed depending on their

research question. An effect is fixed when the levels represent the specific conditions of

theoretical interest (e.g., *task condition*) and the goal is to estimate and interpret those

differences directly. In contrast, an effect is random when the levels are sampled from a broader

population (e.g., *subjects*) and the goal is to account for their variability while generalizing

beyond the sample tested. Note that the same variable (e.g., *stimuli*) may be considered fixed or

random depending on the research questions.

Additionally, the multi-level structure of RSA measures introduces potential

dependencies across subjects, stimuli, and trials, which can violate assumptions of

independence if not properly modeled. In the present study, we used a model that included

random intercepts for both subjects and stimuli, which accounts for variance at these levels and

improves the generalizability of fixed-effect estimates. Still, there is a potential for systematic

dependence across trials within a subject. To ensure that the model assumptions were satisfied, we conducted a series of diagnostic checks on an exemplar ROI (right LOC; middle occipital gyrus) in the Object Perception dataset, including visual inspection of residual distributions and autocorrelation (Appendix 3, Figure 13). These diagnostics supported the assumptions of normality, homoscedasticity, and conditional independence of residuals. In addition, we conducted permutation-based inference, similar to prior improvements to cRSA (Nili et al., 2014), using a nested model comparison to test whether the mean similarity in this ROI was significantly greater than zero. The observed likelihood ratio test statistic fell in the extreme tail of the null distribution (Appendix 3, Figure 14), providing strong nonparametric evidence for the reliability of the observed effect. We emphasize that this type of model checking and permutation testing is not merely confirmatory but can help validate key assumptions in RSA modeling, especially when applying mixed-effects models to neural similarity data. Researchers are encouraged to adopt similar procedures to ensure the robustness and interpretability of their findings. Further, while analyses here were largely employed to be comparable with cRSA, researchers should consider taking advantage of the flexibility of the mixed-effects models and include co variates of non-interest (run, trial order, etc.).

Additionally, we note that while our proposed tRSA framework provides a flexible and statistically principled approach for modeling trial-level representational strength, we acknowledge that there are alternative methods for addressing trial-level variability in RSA. In particular, the use of cross-validated distance metrics (e.g., crossnobis distance) has become increasingly popular for controlling differences in measurement noise variance and accounting for possible covariance structures across trials (Walther et al., 2016). These metrics offer several advantages, including unbiased estimation of representational dissimilarities under Gaussian noise assumptions and improved generalization to unseen data. However, cross-validated distances are conceptually distinct from the approach taken here: whereas cross-validation aims to correct for noise-related biases in representational dissimilarity matrices, our trial-level RSA method focuses on estimating and modeling the variability in representation strength across individual trials using mixed-effects modeling. Rather than proposing a replacement for cross-validated RSA, tRSA adds a complementary tool to the methodological toolkit—one that supports hypothesis-driven inference about condition effects and trial-level covariates, while leveraging the full structure of the data.

Conclusion

We present a comprehensive overview and diagnostics of a trial-level approach to representational similarity analysis, termed tRSA. With both simulations and real fMRI datasets, we have demonstrated that tRSA properly captures the multi-level variance structure in the data, shows improved and robust specificity and sensitivity, and offers flexible modeling options. We believe that tRSA is an important advancement of the generic RSA implementation, both methodologically and conceptually, and we hope that this innovation provides a versatile and useful tool for digging deeper into the fascinating complexity of cognition.

Acknowledgement

This study was supported by the National Institutes of Health grant numbers: R01-AG066901, R21-AG058161, and R01-AG075417.

Appendices

Appendix 1. Row-wise correlations

We explored the statistical properties of computing row-wise correlations, which is a critical step in tRSA. Assuming an experimental design with $n = 200$ trials, we sampled $n(n-1)/2 = 19900$ pairs of values from a bivariate normal distribution, with their Pearson correlation fixed at some given value via the `MASS 7.3-60.2` package (Venables et al., 2002) in R. The two vectors were rearranged as the lower triangular part of two $n \times n$ matrices, and the upper triangular parts were filled out accordingly to yield two symmetric matrices M and S. With each pair of matrices, the Fisher-transformed Pearson correlation coefficient of the lower triangular parts of the two matrices is equal to the ground truth parameter z. We computed row-wise Pearson correlations for row vectors $M_{i\cdot}$ and $S_{i\cdot}$, barring entries on the diagonal (see **Figure 1C, Bottom**). Fisher transformation of correlation coefficients was applied such that the distribution of values is more approximately normal (Silver & Dunlap, 1987). This set of procedures was repeated for 10,000 iterations, for each ground truth parameter z ranging from -0.2 to 0.6 with increments of 0.1.Our simulations indicated that the average of row-wise correlations numerically approximates the overall correlation. Specifically, the estimates centered around zero when it was the ground truth; as the magnitude of the ground truth increased, there appeared to be a bias toward slightly larger magnitudes. Despite this, the spread of estimates derived from the row-wise method remained small, with a constrained range of [0.599, 0.604] around the ground truth of 0.600 (see **Appendix 11 Figure 11**).

Appendix 1 Figure 11. Row-wise correlations. Histograms of the mean of row-wise correlation values. Each histogram depicted 10,000 iterations. In each iteration, two symmetrical matrices with a fixed ground truth Pearson correlation coefficient were randomly generated, and the mean of row-wise correlation coefficients were computed as the estimate. Dashed vertical lines indicate the ground truth parameter, and solid vertical lines indicate the mean of estimates.

Note that a limitation of this simulation is that the symmetric matrices were randomly

generated without being guaranteed to be mathematically valid similarity matrices (i.e., positive

semidefinite). For example, $[[1, 1, 1], [1, 1, -1], [1, -1, 1]]$ is symmetric but is not a valid

correlation RSM, since it is impossible to satisfy $a = b = c$ (row 1) and $a = b = -c$ (row 2)

unless $a = b = c = 0$, in which case the Pearson correlation is undefined. Similarly, RSMs using

distance metrics such as Euclidean distance must satisfy the triangle inequality, i.e., $d_{xy} +$

$d_{xz} \geq d_{yz}$. Moreover, it is difficult to implement the multi-level variance structure directly on

RSMs; rather, those variances are theorized to operate directly on the underlying *activity*

patterns.

Appendix 2. Comparing across-condition and within-condition tRSA

Given discrete experimental conditions, tRSA could be formulated either within each condition

or across all conditions. In *within-condition* tRSA, one would generate condition-specific RSMs,

e.g., one set of $n_A \times n_A$ RSMs for Condition A and another set of $n_B \times n_B$ RSMs for Condition B,

and compute the two sets of *within-condition* tRSA values separately. These tRSA estimates

are then subjected to subsequent analysis. In *across-condition* tRSA, RSMs are generated

across all trials in all conditions, and tRSA estimates are computed as if there were no multiple

conditions. Then, tRSA estimates are categorized based on the condition they belong to in any

subsequent analysis.

We advocate for the use of across-condition tRSA for its enhanced statistical reliability

over within-condition tRSA. One major limitation of within-condition tRSA is its vulnerability to

small and variable trial counts. Suppose that a condition contains n trials, cRSA would use

$n(n-1)/2$ observations to compute its estimate, whereas within-condition tRSA could only use

$n-1$ observations. This effective sample size could turn out to be fairly small and variable in

practice (see **Figure 8A, Bottom**), resulting in unreliable estimates (see **Figure 2**). On the

contrary, across-condition tRSA suffers much less from this issue, since most experiments

should have been designed to have an adequate total trial count.

Another theoretical advantage of across-condition tRSA is that it better corresponds to

tRSA$_{continuous}$, i.e., analyses in which trial-level representational strength estimates are

hypothesized to be modulated by some continuous variable such as memorability or reaction

time. In both across-condition tRSA and tRSA$_{continuous}$, full RSMs are used to estimate

representational strength before any discrete condition effect or continuous modulation effect is

assessed.

Appendix 2 Figure 12 below summarizes the differences between within-condition and

across-condition tRSA outcomes in a series of simulations. Notably, while within-condition tRSA

estimates showed better numerical correspondence with cRSA estimates, they are less reliable

than across-condition tRSA, as evidenced by the wider spread of estimates.

1208

Appendix 2 Figure 12. **Comparing across-condition and within-condition tRSA**. *Each cell depicts descriptive statistics of different RSA methods from 10,000 simulations. Cells differ in raw trial counts (20, 80, or 320 in a given condition), balance of trial counts between conditions (balanced or unbalanced), and effect (A = B, A > B, or A < B). In each cell, the top scatter plots depict condition-level tRSA estimates (y-axis; blue, within-condition; orange, across-condition) against cRSA estimates (x-axis), whereas the bottom scatter plots depict the standard deviations of trial-level representational strength estimates from across-condition tRSA (y-axis) and within-condition tRSA (x-axis).*

1209

1210

Appendix 3. Supporting data and results for Experiment 2

1211

1212 *Appendix 3 Figure 13.*

1213

Figure 13. Exemplar model checks Experiment 2 Object Perception in right LOC (middle
occipital gyrus). A) QQ Plot of Residuals. B) Histogram of Residuals. C) Residuals vs Fitted
Values. D) Autocorrelation Function (ACF) Plot. These diagnostic plots were generated to
evaluate whether the linear mixed-effects model satisfied key statistical assumptions. The
model was fit to an exemplar region of interest (ROI) with subject and stimulus modeled as
random intercepts. Residuals were extracted from the fitted model and plotted using base R
functions. The QQ plot (A) and histogram (B) indicate that residuals are approximately normally
distributed. The residuals vs. fitted values plot (C) shows no clear patterns or funneling,
suggesting homoscedasticity and no evidence of model misspecification. Finally, the ACF plot
(D) displays no significant autocorrelation, supporting the assumption that residuals are
independent after accounting for the specified random effects structure.

1225

 Exemplar Permutation Testing

To test whether the mean representational strength in the ROI right LOC (middle
occipital gyrus) was significantly greater than zero, we used a permutation-based likelihood ratio
test implemented via the `permlmer` function. This test compares two nested linear mixed-
effects models fit using the `lmer` function from the lme4 package, both including random
intercepts for Participant and Stimulus ID to account for between-subject and between-item
variability.
The null model excluded a fixed intercept term, effectively constraining the mean
similarity to zero after accounting for random effects:
ROI ~ 0 + (1 | Participant) + (1 | Stimulus)
The full model included the same random effects structure but allowed the intercept to
be freely estimated:
ROI ~ 1 + (1 | Participant) + (1 | Stimulus)
By comparing the fit of these two models, we directly tested whether the average
similarity in this ROI was significantly different from zero. Permutation testing (1,000
permutations) was used to generate a nonparametric p-value, providing inference without
relying on normality assumptions.
The full model, which estimated a nonzero mean similarity in the right LOC (middle
occipital gyrus), showed a significantly better fit to the data than the null model that fixed the
mean at zero ($\chi^2(1) = 17.60$, $p = 2.72 \times 10^{-5}$). The permutation-based p-value obtained from
permlmer confirmed this effect as statistically significant ($p = 0.0099$), indicating that the mean
similarity in this ROI was reliably greater than zero. These results support the conclusion that
the right LOC contains representational structure consistent with the HMAXc2 RSM. A density
plot of the permuted likelihood ratio tests is plotted along with the observed likelihood ratio test
in Appendix 3 Figure 14.

1251

"Appendix 3 Figure 14. Permutation-based likelihood ratio test (LRT) comparing models with

and without a fixed intercept in the right LOC (middle occipital gyrus). The x-axis shows the

distribution of LRT statistics obtained from 1,000 permutations under the null hypothesis that the

mean similarity is zero. The blue line represents the null distribution of permuted LRT values,

and the red vertical line indicates the observed LRT statistic from the original model comparison

$(\chi^2 = 17.60)$. The observed value falls in the extreme tail of the null distribution, yielding a

permutation-based p-value of 0.0099, indicating that the mean similarity in this ROI is

significantly greater than zero."

1260

1261

1262

1263 *Appendix 3 Table 4. Behavioral results. Bold indicates participants excluded from Conceptual Retrieval Analyses.*

Participant	Gender	Response Trials at Perception	ROC	Count of Hits	Hit Rate
1	M	114	0.84	84	0.74
2	W	114	0.73	82	0.78
3	**W**	105	**0.70**	**32**	**0.36**

4	W	112	0.93	94	0.82
5	W	114	0.95	85	0.76
6	W	96	0.74	84	0.79
7	W	108	0.93	99	0.88
8	W	114	0.56	76	0.75
9	M	113	0.81	89	0.78
10	M	101	0.79	64	0.80
11	M	101	0.93	78	0.80
12	W	113	0.66	53	0.50
13	M	114	0.87	89	0.78
14	W	103	0.69	35	0.39
15	M	114	0.84	75	0.66
16	W	114	0.67	51	0.45
17	**W**	**113**	**0.35**	**26**	**0.30**
18	W	114	0.83	75	0.66
19	W	114	0.90	100	0.88
20	W	114	0.71	68	0.60
21	W	114	0.89	80	0.70
22	W	114	0.90	99	0.89
23	W	113	0.83	93	0.82
24	W	110	0.70	64	0.62
25	M	114	0.87	84	0.74
26	M	95	0.62	71	0.75
27	M	114	0.75	81	0.71
28	M	109	0.95	100	0.88
29	W	106	0.72	81	0.79
30	W	114	0.92	95	0.86

31	M	114	0.74	79	0.69
32	W	109	0.62	50	0.50

1264

1265

1266 *Appendix 3 Table 5. Model selection using 3 criteria: Akaike information criterion (AIC), Bayesian information criterion*
1267 *(BIC), and log-liklihood ratio testing (LRT).*

REGION	SubArea	Coordinates (x, y, z)	(1+adjHvM|Subject + (1+adjHvM|StimID)			(1+adjHvM|Subject)+(1|StimID)			(1|Subject)+(1|StimID)		
			AIC	BIC	LRT pvalue	AIC	BIC	LRT pvalue	AIC	BIC	LRT pvalue
LEFT IPL	A40c, caudal area 40(PFm)	-56, -49, 38	-4778	-4724	-	-4781	-4739	0.555	-4784	-4754	0.600
RIGHT IPL	A40c, caudal area 40(PFm)	57, -44, 38	-4632	-4578	-	-4614	-4571	0.000	-4639	-4608	1.000
LEFT IPL	A39rv, rostroventral area 39(PGa)	-47, -65, 26	-4907	-4852	-	-4910	-4867	0.674	-4914	-4883	0.819
RIGHT IPL	A39rv, rostroventral area 39(PGa)	53, -54, 25	-4765	-4710	-	-4768	-4726	0.909	-4772	-4742	0.969
LEFT ITC	A20iv, intermediate ventral area 20	-45, -26, -27	-4786	-4731	-	-4790	-4747	1.000	-4788	-4758	0.079
LEFT ITC	A20r, rostral area 20	-43, -2, -41	-4188	-4134	-	-4187	-4145	0.117	-4191	-4161	0.858
LEFT ITC	A20il, intermediate lateral area 20	-56, -16, -28	-4808	-4753	-	-4806	-4764	0.064	-4809	-4779	0.663
RIGHT ITC	A20iv, intermediate ventral area 20	46, -14, -33	-4526	-4472	-	-4529	-4487	0.623	-4533	-4502	0.716
RIGHT ITC	A20r, rostral area 20	40, 0, -43	-3940	-3886	-	-3942	-3901	0.510	-3944	-3914	0.337
RIGHT ITC	A20il, intermediate lateral area 20	55, -11, -32	-4554	-4500	-	-4558	-4516	0.982	-4562	-4532	0.974
LEFT ITC	A37elv, extreme lateroventral area37	-51, -57, -15	-4920	-4865	-	-4924	-4881	1.000	-4924	-4894	0.214
LEFT ITC	A37vl, ventrolateral area 37	-55, -60, -6	-4946	-4891	-	-4949	-4907	0.875	-4953	-4923	0.875
LEFT ITC	A20cl, caudolateral of area 20	-59, -42, -16	-5003	-4949	-	-5005	-4962	0.297	-5007	-4977	0.476
LEFT ITC	A20cv, caudoventral of area 20	-55, -31, -27	-4867	-4812	-	-4871	-4828	0.996	-4873	-4843	0.413
RIGHT ITC	A37elv, extreme lateroventral area37	53, -52, -18	-4933	-4878	-	-4935	-4892	0.301	-4936	-4906	0.352
RIGHT ITC	A37vl, ventrolateral area 37	54, -57, -8	-4875	-4821	-	-4877	-4835	0.366	-4881	-4850	0.865
RIGHT ITC	A20cl, caudolateral of area 20	61, -40, -17	-4617	-4563	-	-4619	-4576	0.291	-4623	-4592	0.966
RIGHT ITC	A20cv, caudoventral of area 20	54, -31, -26	-4683	-4628	-	-4685	-4642	0.293	-4688	-4657	0.679
LEFT LOC	mOccG, middle occipital gyrus	-31, -89, 11	-5123	-5068	-	-5127	-5084	0.941	-5128	-5097	0.259
LEFT LOC	V5/MT+, area V5/MT+	-46, -74, 3	-4820	-4765	-	-4824	-4782	0.996	-4827	-4797	0.631
LEFT LOC	OPC, occipital polar cortex	-18, -99, 2	-5046	-4991	-	-5049	-5006	0.595	-5052	-5022	0.818
LEFT LOC	iOccG, inferior occipital gyrus	-30, -88, -12	-4959	-4904	-	-4962	-4919	0.516	-4966	-4935	0.929

REGION	SubArea	Coordinates (x, y, z)									
RIGHT LOC	mOccG, middle occipital gyrus	34, -86, 11	-5265	-5210	-	-5269	-5227	1.000	-5271	-5241	0.440
RIGHT LOC	V5/MT+, area V5/MT+	48, -70, -1	-4879	-4824	-	-4881	-4839	0.382	-4883	-4852	0.279
RIGHT LOC	OPC, occipital polar cortex	22, -97, 4	-4995	-4940	-	-4989	-4946	0.007	-4991	-4961	0.472
RIGHT LOC	iOccG, inferior occipital gyrus	32, -85, -12	-5126	-5071	-	-5126	-5083	0.144	-5129	-5098	0.618
		% Selected	4%	0%	8%	0%	0%	0%	96%	100%	92%

1268

1269

1270 *Appendix 3 Table 6. Significant nuisance effects in memorability model.*

REGION	SubArea	Coordinates (x, y, z)	Conceptual Memorability					Reaction Time				
			Mean	SE	t Values	p	q	coeff	SE	t Values	p	q
LEFT IPL	A40c, caudal area 40(PFm)	-56, -49, 38	0.077	0.060	1.274	0.203	0.659	0.005	0.004	1.369	0.171	0.869
RIGHT IPL	A40c, caudal area 40(PFm)	57, -44, 38	-0.053	0.057	-0.931	0.352	0.773	0.007	0.004	1.731	0.084	0.869
LEFT IPL	A39rv, rostroventral area 39(PGa)	-47, -65, 26	-0.019	0.056	-0.341	0.733	0.866	0.005	0.004	1.433	0.152	0.869
RIGHT IPL	A39rv, rostroventral area 39(PGa)	53, -54, 25	-0.039	0.059	-0.666	0.506	0.773	0.010	0.004	2.482	0.013	0.869
LEFT ITC	A20iv, intermediate ventral area 20	-45, -26, -27	-0.052	0.059	-0.876	0.381	0.773	0.004	0.004	1.101	0.271	0.869
LEFT ITC	A20r, rostral area 20	-43, -2, -41	-0.051	0.065	-0.780	0.436	0.773	-0.004	0.004	-0.846	0.397	0.869
LEFT ITC	A20il, intermediate lateral area 20	-56, -16, -28	-0.053	0.060	-0.893	0.372	0.773	0.004	0.004	0.889	0.374	0.869
RIGHT ITC	A20iv, intermediate ventral area 20	46, -14, -33	0.017	0.061	0.278	0.781	0.867	0.002	0.004	0.556	0.578	0.869
RIGHT ITC	A20r, rostral area 20	40, 0, -43	0.029	0.065	0.444	0.657	0.854	0.000	0.004	0.016	0.987	0.869
RIGHT ITC	A20il, intermediate lateral area 20	55, -11, -32	-0.053	0.059	-0.887	0.375	0.773	0.002	0.004	0.439	0.661	0.869
LEFT ITC	A37elv, extreme lateroventral area37	-51, -57, -15	-0.044	0.059	-0.750	0.453	0.773	0.004	0.004	1.050	0.294	0.869
LEFT ITC	A37vl, ventrolateral area 37	-55, -60, -6	-0.043	0.062	-0.682	0.495	0.773	-0.003	0.004	-0.627	0.531	0.869
LEFT ITC	A20cl, caudolateral of area 20	-59, -42, -16	0.009	0.057	0.165	0.869	0.869	0.002	0.004	0.529	0.597	0.869
LEFT	A20cv, caudoventral of	-55, -31, -27	0.032	0.057	0.550	0.582	0.797	0.001	0.004	0.218	0.827	0.869

ITC	area 20											
RIGHT ITC	A37elv, extreme lateroventral area37	53, -52, -18	0.034	0.059	0.580	0.562	0.797	0.000	0.004	0.015	0.988	0.869
RIGHT ITC	A37vl, ventrolateral area 37	54, -57, -8	-0.012	0.059	-0.210	0.834	0.867	-0.007	0.004	-1.662	0.097	0.869
RIGHT ITC	A20cl, caudolateral of area 20	61, -40, -17	0.022	0.060	0.366	0.714	0.866	-0.001	0.004	-0.137	0.891	0.869
RIGHT ITC	A20cv, caudoventral of area 20	54, -31, -26	0.013	0.060	0.221	0.825	0.867	-0.004	0.004	-0.909	0.363	0.869
LEFT LOC	mOccG, middle occipital gyrus	-31, -89, 11	**-0.233**	**0.067**	**-3.473**	**0.001**	**0.005**	**0.015**	**0.005**	**3.199**	**0.001**	**0.033**
LEFT LOC	V5/MT+, area V5/MT+	-46, -74, 3	**-0.193**	**0.059**	**-3.241**	**0.001**	**0.006**	**0.008**	**0.004**	**2.093**	**0.036**	**0.033**
LEFT LOC	OPC, occipital polar cortex	-18, -99, 2	**-0.259**	**0.074**	**-3.516**	**0.000**	**0.005**	**0.017**	**0.005**	**3.359**	**0.001**	**0.033**
LEFT LOC	iOccG, inferior occipital gyrus	-30, -88, -12	-0.054	0.069	-0.779	0.436	0.773	0.011	0.005	2.371	0.018	0.869
RIGHT LOC	mOccG, middle occipital gyrus	34, -86, 11	**-0.224**	**0.068**	**-3.286**	**0.001**	**0.006**	**0.015**	**0.005**	**3.361**	**0.001**	**0.033**
RIGHT LOC	V5/MT+, area V5/MT+	48, -70, -1	-0.089	0.064	-1.388	0.165	0.614	0.006	0.004	1.311	0.190	0.869
RIGHT LOC	OPC, occipital polar cortex	22, -97, 4	**-0.296**	**0.074**	**-3.987**	**0.000**	**0.002**	**0.014**	**0.005**	**2.867**	**0.004**	**0.033**
RIGHT LOC	iOccG, inferior occipital gyrus	32, -85, -12	-0.099	0.069	-1.439	0.150	0.614	0.012	0.005	2.610	0.009	0.869

1271

1272

1273

References

Allen, E. J., St-Yves, G., Wu, Y., Breedlove, J. L., Prince, J. S., Dowdle, L. T., Nau, M., Caron,

B., Pestilli, F., Charest, I., Hutchinson, J. B., Naselaris, T., & Kay, K. (2022). A massive

7T fMRI dataset to bridge cognitive neuroscience and artificial intelligence. *Nature*

Neuroscience, *25*(1), 116–126. https://doi.org/10.1038/s41593-021-00962-x

Aly, M., & Turk-Browne, N. B. (2016). Attention Stabilizes Representations in the Human

Hippocampus. *Cerebral Cortex*, *26*(2), 783–796. https://doi.org/10.1093/cercor/bhv041

Anzellotti, S., & Coutanche, M. N. (2018). Beyond Functional Connectivity: Investigating

Networks of Multivariate Representations. *Trends in Cognitive Sciences*, *22*(3), 258–269.

https://doi.org/10.1016/j.tics.2017.12.002

Avants, B. B., Tustison, N. J., Song, G., Cook, P. A., Klein, A., & Gee, J. C. (2011). A

reproducible evaluation of ANTs similarity metric performance in brain image registration.

NeuroImage, *54*(3), 2033–2044. https://doi.org/10.1016/j.neuroimage.2010.09.025

Baayen, R. H., Davidson, D. J., & Bates, D. M. (2008). Mixed-effects modeling with crossed

random effects for subjects and items. *Journal of Memory and Language*, *59*(4), 390–

412. https://doi.org/10.1016/j.jml.2007.12.005

Bainbridge, W. A. (2022). Memorability: Reconceptualizing memory as a visual attribute. In

Visual memory (pp. 173–187). Routledge. https://doi.org/10.4324/9781003158134-11

Bainbridge, W. A., Dilks, D. D., & Oliva, A. (2017). Memorability: A stimulus-driven perceptual

neural signature distinctive from memory. *NeuroImage*, *149*, 141–152.

https://doi.org/10.1016/j.neuroimage.2017.01.063

Bainbridge, W. A., & Rissman, J. (2018). Dissociating neural markers of stimulus memorability

and subjective recognition during episodic retrieval. *Scientific Reports*, *8*(1), 8679.

https://doi.org/10.1038/s41598-018-26467-5

Baker, B., Lansdell, B., & Kording, K. P. (2022). Three aspects of representation in

neuroscience. *Trends in Cognitive Sciences*, *26*(11), 942–958.

https://doi.org/10.1016/j.tics.2022.08.014

Barron, H. C., Garvert, M. M., & Behrens, T. E. J. (2016). Repetition suppression: A means to

index neural representations using BOLD? *Philosophical Transactions of the Royal*

Society B: Biological Sciences, *371*(1705), 20150355.

https://doi.org/10.1098/rstb.2015.0355

Bates, D., Mächler, M., Bolker, B., & Walker, S. (2015). Fitting Linear Mixed-Effects Models

Using lme4. *Journal of Statistical Software*, *67*(1), 1–48.

Bauer, A. J., & Just, M. A. (2019). Neural Representations of Concept Knowledge. In G. I. de

Zubicaray & N. O. Schiller (Eds.), *The Oxford Handbook of Neurolinguistics* (p. 0).

Oxford University Press. https://doi.org/10.1093/oxfordhb/9780190672027.013.21

Becker, M., Sommer, T., & Cabeza, R. (2024). *Neural Mechanisms of Creative Problem*

Solving—From Representational Change to Memory Formation (p. 2023.06.13.544774).

bioRxiv. https://doi.org/10.1101/2023.06.13.544774

Behzadi, Y., Restom, K., Liau, J., & Liu, T. T. (2007). A component based noise correction

method (CompCor) for BOLD and perfusion based fMRI. *NeuroImage*, *37*(1), 90–101.

https://doi.org/10.1016/j.neuroimage.2007.04.042

Bobadilla-Suarez, S., Ahlheim, C., Mehrotra, A., Panos, A., & Love, B. C. (2020). Measures of

Neural Similarity. *Computational Brain & Behavior*, *3*(4), 369–383.

https://doi.org/10.1007/s42113-019-00068-5

Brentano, F. (1874). *Psychology From an Empirical Standpoint*. Routledge.

Chang, N., Pyles, J. A., Marcus, A., Gupta, A., Tarr, M. J., & Aminoff, E. M. (2019). BOLD5000,

a public fMRI dataset while viewing 5000 visual images. *Scientific Data*, *6*(1), 49.

https://doi.org/10.1038/s41597-019-0052-3

Charest, I., Kriegeskorte, N., & Kay, K. N. (2018). GLMdenoise improves multivariate pattern

analysis of fMRI data. *NeuroImage*, *183*, 606–616.

https://doi.org/10.1016/j.neuroimage.2018.08.064

Chen, G., Padmala, S., Chen, Y., Taylor, P. A., Cox, R. W., & Pessoa, L. (2021). To pool or not

to pool: Can we ignore cross-trial variability in FMRI? *NeuroImage*, *225*, 117496.

https://doi.org/10.1016/j.neuroimage.2020.117496

Cohen, J. (1983). The cost of dichotomization. *Applied Psychological Measurement*, *7*(3), 249–

253. https://doi.org/10.1177/014662168300700301

Cox, R. W., & Hyde, J. S. (1997). Software tools for analysis and visualization of fMRI data.

NMR in Biomedicine, *10*(4–5), 171–178. https://doi.org/10.1002/(SICI)1099-

1492(199706/08)10:4/5%253C171::AID-NBM453%253E3.0.CO;2-L

Critchley, H. D., & Garfinkel, S. N. (2018). The influence of physiological signals on cognition.

Current Opinion in Behavioral Sciences, *19*, 13–18.

https://doi.org/10.1016/j.cobeha.2017.08.014

Dale, A. M., Fischl, B., & Sereno, M. I. (1999). Cortical Surface-Based Analysis: I. Segmentation

and Surface Reconstruction. *NeuroImage*, *9*(2), 179–194.

https://doi.org/10.1006/nimg.1998.0395

Davis, S. W., Geib, B. R., Wing, E. A., Wang, W.-C., Hovhannisyan, M., Monge, Z. A., &

Cabeza, R. (2021). Visual and Semantic Representations Predict Subsequent Memory

in Perceptual and Conceptual Memory Tests. *Cerebral Cortex*, *31*(2), 974–992.

https://doi.org/10.1093/cercor/bhaa269

Dedrick, R. F., Ferron, J. M., Hess, M. R., Hogarty, K. Y., Kromrey, J. D., Lang, T. R., Niles, J.

D., & Lee, R. S. (2009). Multilevel Modeling: A Review of Methodological Issues and

Applications. *Review of Educational Research*, *79*(1), 69–102.

https://doi.org/10.3102/0034654308325581

Devereux, B. J., Clarke, A., & Tyler, L. K. (2018). Integrated deep visual and semantic attractor

neural networks predict fMRI pattern-information along the ventral object processing

pathway. *Scientific Reports*, *8*(1), Article 1. https://doi.org/10.1038/s41598-018-28865-1

Diedrichsen, J., Berlot, E., Mur, M., Schütt, H. H., Shahbazi, M., & Kriegeskorte, N. (2021).

Comparing representational geometries using whitened unbiased-distance-matrix

similarity (No. arXiv:2007.02789). arXiv. https://doi.org/10.48550/arXiv.2007.02789

Diedrichsen, J., Yokoi, A., & Arbuckle, S. A. (2018). Pattern component modeling: A flexible

approach for understanding the representational structure of brain activity patterns.

NeuroImage, *180*(Pt A), 119–133. https://doi.org/10.1016/j.neuroimage.2017.08.051

Dimsdale-Zucker, H. R., & Ranganath, C. (2018). Representational Similarity Analyses:

A Practical Guide for Functional MRI Applications. In D. Manahan-Vaughan (Ed.),

Handbook of Behavioral Neuroscience (Vol. 28, pp. 509–525). Elsevier.

https://doi.org/10.1016/B978-0-12-812028-6.00027-6

Esteban, O., Markiewicz, C. J., Blair, R. W., Moodie, C. A., Isik, A. I., Erramuzpe, A., Kent, J. D.,

Goncalves, M., DuPre, E., Snyder, M., Oya, H., Ghosh, S. S., Wright, J., Durnez, J.,

Poldrack, R. A., & Gorgolewski, K. J. (2019). fMRIPrep: A robust preprocessing pipeline

for functional MRI. *Nature Methods*, *16*(1), Article 1. https://doi.org/10.1038/s41592-018-

0235-4

Esteban, O., Markiewicz, C. J., Goncalves, M., Provins, C., Salo, T., Kent, J. D., DuPre, E., Ciric,

R., Pinsard, B., Blair, R. W., Poldrack, R. A., & Gorgolewski, K. J. (2023). *fMRIPrep: A*

robust preprocessing pipeline for functional MRI (Version 23.0.1) [Computer software].

Zenodo. https://doi.org/10.5281/zenodo.11123262

Fan, L., Li, H., Zhuo, J., Zhang, Y., Wang, J., Chen, L., Yang, Z., Chu, C., Xie, S., Laird, A. R.,

Fox, P. T., Eickhoff, S. B., Yu, C., & Jiang, T. (2016). The Human Brainnetome Atlas: A

New Brain Atlas Based on Connectional Architecture. *Cerebral Cortex*, *26*(8), 3508–

3526. https://doi.org/10.1093/cercor/bhw157

Favela, L. H., & Machery, E. (2023). Investigating the concept of representation in the neural

and psychological sciences. *Frontiers in Psychology*, *14*.

https://doi.org/10.3389/fpsyg.2023.1165622

Favila, S. E., Lee, H., & Kuhl, B. A. (2020). Transforming the Concept of Memory Reactivation.

Trends in Neurosciences, *43*(12), 939–950. https://doi.org/10.1016/j.tins.2020.09.006

Freeman, J. B., Stolier, R. M., Brooks, J. A., & Stillerman, B. S. (2018). The neural

representational geometry of social perception. *Current Opinion in Psychology*, *24*, 83–

91. https://doi.org/10.1016/j.copsyc.2018.10.003

Freund, M. C., Bugg, J. M., & Braver, T. S. (2021). A Representational Similarity Analysis of

Cognitive Control during Color-Word Stroop. *Journal of Neuroscience*, *41*(35), 7388–

7402. https://doi.org/10.1523/JNEUROSCI.2956-20.2021

Freund, M. C., Etzel, J. A., & Braver, T. S. (2021). Neural Coding of Cognitive Control: The

Representational Similarity Analysis Approach. *Trends in Cognitive Sciences*, *25*(7),

622–638. https://doi.org/10.1016/j.tics.2021.03.011

Friston, K. J., Ashburner, J. T., Kiebel, S. J., Nichols, T. E., & Penny, W. D. (Eds.). (2006).

Statistical parametric mapping: The analysis of functional brain images (1st ed.).

Academic Press.

Greve, D. N., & Fischl, B. (2009). Accurate and robust brain image alignment using boundary-

based registration. *NeuroImage*, *48*(1), 63–72.

https://doi.org/10.1016/j.neuroimage.2009.06.060

Grill-Spector, K., Henson, R., & Martin, A. (2006). Repetition and the brain: Neural models of

stimulus-specific effects. *Trends in Cognitive Sciences*, *10*(1), 14–23.

https://doi.org/10.1016/j.tics.2005.11.006

Hebart, M. N., Contier, O., Teichmann, L., Rockter, A. H., Zheng, C. Y., Kidder, A., Corriveau, A.,

Vaziri-Pashkam, M., & Baker, C. I. (2023). THINGS-data, a multimodal collection of

large-scale datasets for investigating object representations in human brain and

behavior. *eLife*, *12*, e82580. https://doi.org/10.7554/eLife.82580

Hovhannisyan, M., Clarke, A., Geib, B. R., Cicchinelli, R., Monge, Z., Worth, T., Szymanski, A.,

Cabeza, R., & Davis, S. W. (2021). The visual and semantic features that predict object

memory: Concept property norms for 1,000 object images. *Memory & Cognition*, *49*(4),

712–731. https://doi.org/10.3758/s13421-020-01130-5

Howard, C. M., Huang, S., Hovhannisyan, M., Cabeza, R., & Davis, S. W. (2024). Differential

Mnemonic Contributions of Cortical Representations during Encoding and Retrieval.

Journal of Cognitive Neuroscience, 1–29. https://doi.org/10.1162/jocn_a_02227

Huang, S., Bogdan, P. C., Howard, C. M., Gillette, K., Deng, L., Welch, E., McAllister, M. L.,

Giovanello, K. S., Davis, S. W., & Cabeza, R. (2025). Cortico-hippocampal interactions

underlie schema-supported memory encoding in older adults. *Cerebral Cortex*, *35*(8).

https://doi.org/10.1093/cercor/bhaf211

Huang, S., De Brigard, F., Cabeza, R., & Davis, S. W. (2024). Connectivity analyses for task-

based fMRI. *Physics of Life Reviews*, *49*, 139–156.

https://doi.org/10.1016/j.plrev.2024.04.012

Huang, S., Faul, L., Parikh, N., LaBar, K. S., & De Brigard, F. (2024). Counterfactual thinking

induces different neural patterns of memory modification in anxious individuals. *Scientific*

Reports, *14*(1), 10630. https://doi.org/10.1038/s41598-024-61545-x

Huang, S., Howard, C. M., Hovhannisyan, M., Ritchey, M., Cabeza, R., & Davis, S. W. (2024).

Hippocampal Functions Modulate Transfer-Appropriate Cortical Representations

Supporting Subsequent Memory. *Journal of Neuroscience*, *44*(1).

https://doi.org/10.1523/JNEUROSCI.1135-23.2023

Huang, T., Song, Y., & Liu, J. (2022). Real-world size of objects serves as an axis of object

space. *Communications Biology*, *5*(1), 1–12. https://doi.org/10.1038/s42003-022-03711-

3

Jenkinson, M., Bannister, P., Brady, M., & Smith, S. (2002). Improved Optimization for the

Robust and Accurate Linear Registration and Motion Correction of Brain Images.

NeuroImage, *17*(2), 825–841. https://doi.org/10.1006/nimg.2002.1132

Jozranjbar, B., Kristjánsson, Á., Starrfelt, R., Gerlach, C., & Sigurdardottir, H. M. (2023). Using

representational similarity analysis to reveal category and process specificity in visual

object recognition. *Cortex*, *166*, 172–187. https://doi.org/10.1016/j.cortex.2023.05.012

Jozwik, K. M., Kietzmann, T. C., Cichy, R. M., Kriegeskorte, N., & Mur, M. (2023). Deep Neural

Networks and Visuo-Semantic Models Explain Complementary Components of Human

Ventral-Stream Representational Dynamics. *Journal of Neuroscience*, *43*(10), 1731–

1741. https://doi.org/10.1523/JNEUROSCI.1424-22.2022

Karimi-Rouzbahani, H., Woolgar, A., Henson, R., & Nili, H. (2022). Caveats and Nuances of

Model-Based and Model-Free Representational Connectivity Analysis. *Frontiers in

Neuroscience*, *16*. https://www.frontiersin.org/article/10.3389/fnins.2022.755988

King, M. L., Groen, I. I. A., Steel, A., Kravitz, D. J., & Baker, C. I. (2019). Similarity judgments

and cortical visual responses reflect different properties of object and scene categories

in naturalistic images. *NeuroImage*, *197*, 368–382.

https://doi.org/10.1016/j.neuroimage.2019.04.079

Klein, A., Ghosh, S. S., Bao, F. S., Giard, J., Häme, Y., Stavsky, E., Lee, N., Rossa, B., Reuter,

M., Neto, E. C., & Keshavan, A. (2017). Mindboggling morphometry of human brains.

PLOS Computational Biology, *13*(2), e1005350.

https://doi.org/10.1371/journal.pcbi.1005350

Kleiner, M., Brainard, D., & Pelli, D. (2007). What's new in Psychtoolbox-3? *Perception*, *36*(14),

1–16.

Kramer, M. A., Hebart, M. N., Baker, C. I., & Bainbridge, W. A. (2023). The features underlying

the memorability of objects. *Science Advances*, *9*(17), eadd2981.

https://doi.org/10.1126/sciadv.add2981

Kriegeskorte, N., & Diedrichsen, J. (2019). Peeling the Onion of Brain Representations. *Annual*

Review of Neuroscience, *42*(1), 407–432. https://doi.org/10.1146/annurev-neuro-

080317-061906

Kriegeskorte, N., & Kievit, R. A. (2013). Representational geometry: Integrating cognition,

computation, and the brain. *Trends in Cognitive Sciences*, *17*(8), 401–412.

https://doi.org/10.1016/j.tics.2013.06.007

Kriegeskorte, N., Mur, M., & Bandettini, P. A. (2008). Representational similarity analysis—

Connecting the branches of systems neuroscience. *Frontiers in Systems Neuroscience*,

2. https://doi.org/10.3389/neuro.06.004.2008

Kuhn, M., Vaughan, D., & Hvitfeldt, E. (2024). *yardstick: Tidy Characterizations of Model*

Performance (Version 1.3.1) [Computer software].

https://github.com/tidymodels/yardstick

Kuznetsova, A., Brockhoff, P. B., & Christensen, R. H. B. (2017). lmerTest Package: Tests in

Linear Mixed Effects Models. *Journal of Statistical Software*, *82*(13).

https://doi.org/10.18637/jss.v082.i13

Lahner, B., Dwivedi, K., Iamshchinina, P., Graumann, M., Lascelles, A., Roig, G., Gifford, A. T.,

Pan, B., Jin, S., Ratan Murty, N. A., Kay, K., Oliva, A., & Cichy, R. (2024). Modeling

short visual events through the BOLD moments video fMRI dataset and metadata.

Nature Communications, *15*(1), 6241. https://doi.org/10.1038/s41467-024-50310-3

Lanczos, C. (1964). Evaluation of Noisy Data. *Journal of the Society for Industrial and Applied*

Mathematics Series B Numerical Analysis, *1*(1), 76–85. https://doi.org/10.1137/0701007

Long, N. M., & Kuhl, B. A. (2021). Cortical Representations of Visual Stimuli Shift Locations with

Changes in Memory States. *Current Biology.* https://doi.org/10.1016/j.cub.2021.01.004

MacCallum, R. C., Zhang, S., Preacher, K. J., & Rucker, D. D. (2002). On the practice of

dichotomization of quantitative variables. *Psychological Methods*, *7*(1), 19–40.

https://doi.org/10.1037/1082-989X.7.1.19

Matuschek, H., Kliegl, R., Vasishth, S., Baayen, H., & Bates, D. (2017). Balancing Type I error

and power in linear mixed models. *Journal of Memory and Language*, *94*, 305–315.

https://doi.org/10.1016/j.jml.2017.01.001

Mazurchuk, S., Conant, L. L., Tong, J.-Q., Binder, J. R., & Fernandino, L. (2023). Stimulus

repetition and sample size considerations in item-level representational similarity

analysis. *Language, Cognition and Neuroscience*, *0*(0), 1–12.

https://doi.org/10.1080/23273798.2023.2232903

Meteyard, L., & Davies, R. A. I. (2020). Best practice guidance for linear mixed-effects models in

psychological science. *Journal of Memory and Language*, *112*, 104092.

https://doi.org/10.1016/j.jml.2020.104092

Morales-Torres, R., Wing, E. A., Deng, L., Davis, S. W., & Cabeza, R. (2024). Visual

Recognition Memory of Scenes Is Driven by Categorical, Not Sensory, Visual

Representations. *Journal of Neuroscience*, *44*(21).

https://doi.org/10.1523/JNEUROSCI.1479-23.2024

Morton, N. W., Zippi, E. L., Noh, S. M., & Preston, A. R. (2021). Semantic Knowledge of

Famous People and Places Is Represented in Hippocampus and Distinct Cortical

Networks. *Journal of Neuroscience*, *41*(12), 2762–2779.

https://doi.org/10.1523/JNEUROSCI.2034-19.2021

Mumford, J. A., Turner, B. O., Ashby, F. G., & Poldrack, R. A. (2012). Deconvolving BOLD

activation in event-related designs for multivoxel pattern classification analyses.

NeuroImage, *59*(3), 2636–2643. https://doi.org/10.1016/j.neuroimage.2011.08.076

Naselaris, T., Kay, K. N., Nishimoto, S., & Gallant, J. L. (2011). Encoding and decoding in fMRI.

NeuroImage, *56*(2), 400–410. https://doi.org/10.1016/j.neuroimage.2010.07.073

Naspi, L., Hoffman, P., Devereux, B., Thejll-Madsen, T., Doumas, L. A. A., & Morcom, A. (2021).

Multiple dimensions of semantic and perceptual similarity contribute to mnemonic

discrimination for pictures. *Journal of Experimental Psychology: Learning, Memory, and*

Cognition, *47*(12), 1903–1923. https://doi.org/10.1037/xlm0001032

Naspi, L., Stensholt, C., Karlsson, A. E., Monge, Z. A., & Cabeza, R. (2023). Effects of Aging on

Successful Object Encoding: Enhanced Semantic Representations Compensate for

Impaired Visual Representations. *Journal of Neuroscience*, *43*(44), 7337–7350.

https://doi.org/10.1523/JNEUROSCI.2265-22.2023

Nili, H., Wingfield, C., Walther, A., Su, L., Marslen-Wilson, W., & Kriegeskorte, N. (2014). A

Toolbox for Representational Similarity Analysis. *PLOS Computational Biology*, *10*(4),

e1003553. https://doi.org/10.1371/journal.pcbi.1003553

Pacheco-Estefan, D., Fellner, M.-C., Kunz, L., Zhang, H., Reinacher, P., Roy, C., Brandt, A.,

Schulze-Bonhage, A., Yang, L., Wang, S., Liu, J., Xue, G., & Axmacher, N. (2024).

Maintenance and transformation of representational formats during working memory

prioritization. *Nature Communications*, *15*(1), 8234. https://doi.org/10.1038/s41467-024-

52541-w

Park, J., Cardwell, R., & Yu, H.-T. (2020). Specifying the Random Effect Structure in Linear

Mixed Effect Models for Analyzing Psycholinguistic Data. *Methodology*, *16*(2), Article 2.

https://doi.org/10.5964/meth.2809

Power, J. D., Mitra, A., Laumann, T. O., Snyder, A. Z., Schlaggar, B. L., & Petersen, S. E.

(2014). Methods to detect, characterize, and remove motion artifact in resting state fMRI.

NeuroImage, *84*, 320–341. https://doi.org/10.1016/j.neuroimage.2013.08.048

Prince, J. S., Charest, I., Kurzawski, J. W., Pyles, J. A., Tarr, M. J., & Kay, K. N. (2022).

Improving the accuracy of single-trial fMRI response estimates using GLMsingle. *eLife*,

11, e77599. https://doi.org/10.7554/eLife.77599

R Core Team. (2024). *R: A Language and Environment for Statistical Computing* (Version 4.4.1)

[Computer software]. R Foundation for Statistical Computing. https://www.R-project.org/

Reuter, M., Rosas, H. D., & Fischl, B. (2010). Highly accurate inverse consistent registration: A

robust approach. *NeuroImage*, *53*(4), 1181–1196.

https://doi.org/10.1016/j.neuroimage.2010.07.020

Riesenhuber, M., & Poggio, T. (1999). Hierarchical models of object recognition in cortex.

Nature Neuroscience, *2*(11), 1019–1025. https://doi.org/10.1038/14819

Riesenhuber, M., & Poggio, T. (2002). Neural mechanisms of object recognition. *Current

Opinion in Neurobiology*, *12*(2), 162–168. https://doi.org/10.1016/S0959-4388(02)00304-

5

Ritchey, M., Wing, E. A., LaBar, K. S., & Cabeza, R. (2013). Neural Similarity Between

Encoding and Retrieval is Related to Memory Via Hippocampal Interactions. *Cerebral

Cortex*, *23*(12), 2818–2828. https://doi.org/10.1093/cercor/bhs258

Ritchie, J. B., Lee Masson, H., Bracci, S., & Op de Beeck, H. P. (2021). The unreliable influence

of multivariate noise normalization on the reliability of neural dissimilarity. *NeuroImage*,

245, 118686. https://doi.org/10.1016/j.neuroimage.2021.118686

Rothlein, D., DeGutis, J., & Esterman, M. (2018). Attentional Fluctuations Influence the Neural

Fidelity and Connectivity of Stimulus Representations. *Journal of Cognitive

Neuroscience*, *30*(9), 1209–1228. https://doi.org/10.1162/jocn_a_01306

Satterthwaite, F. E. (1946). An Approximate Distribution of Estimates of Variance Components.

Biometrics Bulletin, *2*(6), 110–114. https://doi.org/10.2307/3002019

Schütt, H. H., Kipnis, A. D., Diedrichsen, J., & Kriegeskorte, N. (2023). Statistical inference on

representational geometries. *eLife*, *12*, e82566. https://doi.org/10.7554/eLife.82566

Serre, T., Oliva, A., & Poggio, T. (2007). A feedforward architecture accounts for rapid

categorization. *Proceedings of the National Academy of Sciences*, *104*(15), 6424–6429.

https://doi.org/10.1073/pnas.0700622104

Serre, T., Wolf, L., & Poggio, T. (2005). Object recognition with features inspired by visual

cortex. *2005 IEEE Computer Society Conference on Computer Vision and Pattern*

Recognition (CVPR'05), *2*, 994–1000 vol. 2. https://doi.org/10.1109/CVPR.2005.254

Shao, X., Li, A., Chen, C., Loftus, E. F., & Zhu, B. (2023). Cross-stage neural pattern similarity

in the hippocampus predicts false memory derived from post-event inaccurate

information. *Nature Communications*, *14*(1), Article 1. https://doi.org/10.1038/s41467-

023-38046-y

Silver, N. C., & Dunlap, W. P. (1987). Averaging correlation coefficients: Should Fisher's z

transformation be used? *Journal of Applied Psychology*, *72*, 146–148.

https://doi.org/10.1037/0021-9010.72.1.146

Slayton, M., Howard, C. M., Huang, S., Hovhannisyan, M., Cabeza, R., & Davis, S. W. (2025).

Semantic Dimensions Support the Cortical Representation of Object Memorability.

Journal of Cognitive Neuroscience, 1–27. https://doi.org/10.1162/jocn.a.60

Sufikarimi, H., & Mohammadi, K. (2020). Role of the secondary visual cortex in HMAX model for

object recognition. *Cognitive Systems Research*, *64*, 15–28.

https://doi.org/10.1016/j.cogsys.2020.07.001

Tustison, N. J., Avants, B. B., Cook, P. A., Zheng, Y., Egan, A., Yushkevich, P. A., & Gee, J. C.

(2010). N4ITK: Improved N3 Bias Correction. *IEEE Transactions on Medical Imaging*,

29(6), 1310–1320. IEEE Transactions on Medical Imaging.

https://doi.org/10.1109/TMI.2010.2046908

Tyler, L. K., Chiu, S., Zhuang, J., Randall, B., Devereux, B. J., Wright, P., Clarke, A., & Taylor, K.

I. (2013). Objects and Categories: Feature Statistics and Object Processing in the

Ventral Stream. *Journal of Cognitive Neuroscience*, *25*(10), 1723–1735.

https://doi.org/10.1162/jocn_a_00419

van der Wel, P., & van Steenbergen, H. (2018). Pupil dilation as an index of effort in cognitive

control tasks: A review. *Psychonomic Bulletin & Review*, *25*(6), 2005–2015.

https://doi.org/10.3758/s13423-018-1432-y

Venables, W. N., Ripley, B. D., & Venables, W. N. (2002). *Modern applied statistics with S* (4th

ed). Springer.

Vilarroya, O. (2017). Neural Representation. A Survey-Based Analysis of the Notion. *Frontiers*

in Psychology, *8*. https://doi.org/10.3389/fpsyg.2017.01458

Walsh, C. R., & Rissman, J. (2023). Behavioral representational similarity analysis reveals how

episodic learning is influenced by and reshapes semantic memory. *Nature*

Communications, *14*(1), Article 1. https://doi.org/10.1038/s41467-023-42770-w

Walther, A., Nili, H., Ejaz, N., Alink, A., Kriegeskorte, N., & Diedrichsen, J. (2016). Reliability of

dissimilarity measures for multi-voxel pattern analysis. *NeuroImage*, *137*, 188–200.

https://doi.org/10.1016/j.neuroimage.2015.12.012

Weaverdyck, M. E., Lieberman, M. D., & Parkinson, C. (2020). Tools of the Trade Multivoxel

pattern analysis in fMRI: A practical introduction for social and affective neuroscientists.

Social Cognitive and Affective Neuroscience, *15*(4), 487–509.

https://doi.org/10.1093/scan/nsaa057

Westfall, J., Nichols, T. E., & Yarkoni, T. (2017). Fixing the stimulus-as-fixed-effect fallacy in

task fMRI. *Wellcome Open Research*, *1*, 23.

https://doi.org/10.12688/wellcomeopenres.10298.2

Wing, E. A., Geib, B. R., Wang, W.-C., Monge, Z., Davis, S. W., & Cabeza, R. (2020). Cortical

Overlap and Cortical-Hippocampal Interactions Predict Subsequent True and False

Memory. *Journal of Neuroscience*, *40*(9), 1920–1930.

https://doi.org/10.1523/JNEUROSCI.1766-19.2020

Winter, B., & Grice, M. (2021). Independence and generalizability in linguistics. *Linguistics*,

59(5), 1251–1277. https://doi.org/10.1515/ling-2019-0049

Xue, G. (2018). The Neural Representations Underlying Human Episodic Memory. *Trends in*

Cognitive Sciences, *22*(6), 544–561. https://doi.org/10.1016/j.tics.2018.03.004

Yarkoni, T. (2022). The generalizability crisis. *Behavioral and Brain Sciences*, *45*, e1.

https://doi.org/10.1017/S0140525X20001685

Yu, C., Huang, S., Howard, C. M., Hovhannisyan, M., Clarke, A., Cabeza, R., & Davis, S. W.

(2024). Subsequent Memory Effects in Cortical Pattern Similarity Differ by Semantic

Class. *Journal of Cognitive Neuroscience*, 1–12. https://doi.org/10.1162/jocn_a_02238

Zhang, Y., Brady, M., & Smith, S. (2001). Segmentation of brain MR images through a hidden

Markov random field model and the expectation-maximization algorithm. *IEEE*

Transactions on Medical Imaging, *20*(1), 45–57. https://doi.org/10.1109/42.906424

1611

1612

1613