A language network in the individualized functional connectomes of over 1,000 human brains doing arbitrary tasks

Cory Shain[1] and Evelina Fedorenko[2]

[1]Department of Linguistics, Stanford University, cashain@stanford.edu, **Corresponding author**

[2]Department of Brain & Cognitive Sciences, MIT, evelina9@mit.edu

Abstract

A century and a half of neuroscience has yielded many divergent theories of the neurobiology of language. Two factors that likely contribute to this situation include (a) conceptual disagreement about language and its component processes, and (b) intrinsic inter-individual variability in the topography of language areas. Recent functional magnetic resonance imaging (fMRI) studies of small numbers of intensively scanned individuals have argued that a language-selective brain network emerges bottom-up from correlations (individualized functional connectomics, iFC) in task-free (e.g., rest) or task-regressed activation timecourses. Here we test this hypothesis at scale and evaluate its practical utility for task-agnostic language localization: we apply iFC separately to each of 1,957 (fMRI) scanning sessions (1,199 unique brains), each consisting of diverse tasks. We find that iFC indeed reveals a largely left-hemisphere-dominant frontotemporal network that is more stable within individuals than between them, robust to the granularity of the parcellation, and selective for language. These results support the hypothesis that this network is a key structure in the functional organization of the adult brain and show that it can be recovered retrospectively from arbitrary imaging data, with implications for neuroscience, neurosurgery, and neural engineering.

Introduction

Language holds a special place in the study of the human mind and brain. It is a species-specific and species-universal acquired behavior of extraordinary complexity (1), it is intricately linked with human intelligence (2) and social coordination (3), and it is the inaugural domain of cognitive neuroscience (4). Language is also a strong candidate for neural specialization: it can be selectively impaired by developmental disorders (5), brain injury (6), or neurodegeneration (7), with far-reaching consequences for quality of life (8). But despite a century and a half of intensive research, substantial disagreement remains about which brain areas are implicated in language or its component processes and what computations those areas support (9–22).

Two factors likely contribute to this situation. The *first factor* is theoretical disagreement about the construct of language itself and its place in the mind and brain (1, 9, 23–30). It is difficult to synthesize across experiments that disagree fundamentally in how they construe their object of study, given that theoretical precommitments become embedded in task designs. For example, a commonly used task for operationalizing language processing is to compare responses to sentences and responses to lists of pronounceable nonwords (20, 31). However, critics of different theoretical persuasions have argued both that this task is too broad (e.g., that it fails to isolate syntax (32)) and too narrow (e.g., that it fails to include phonological processing (33); cf. (34)). We raise this example not to delve into the particulars of these debates, but to illustrate the difficulty of pursuing a cumulative neurobiology of language in the presence of core disagreements about how language should be conceptualized and studied. The *second factor* is growing evidence that language areas—similar to other areas in the association cortex—are weakly "tethered" to macroanatomical structure (e.g., sulcal/gyral landmarks or coordinates in a template brain) across individuals (10, 31, 35–38). The widely-targeted question of which brain regions support which language functions (12, 13, 15–17, 20, 39, 40) may therefore be ill-posed

at the population level, which is the level that standard analytic approaches focus on. One solution
to weak structure-function tethering is to identify language regions within individuals using an
independent "localizer" task (31, 41–45). Over a decade of work across many labs has shown
that diverse language localizers convergently identify a frontotemporal network with strikingly
language-selective tuning and distributed sensitivity to a range of linguistic properties (for review,
see Ref. (10)). But such studies rely even more fundamentally on the construct and test validity
of the localizer task(s). Using a task to localize putative functions (task-based localization) thus
accounts for individual variability but pushes functional assumptions deeper into the analysis.

A promising opportunity to skirt both of these issues in studies of the brain's functional
organization (46) comes from functional connectomics (FC), the study of structured covariation in
activity between brain areas (47–50), typically using functional magnetic resonance imaging
(fMRI). Historically, FC analyses have been performed at the group level (49, 51–54). Motivated
in part by the concern above about individual variability in functional organization, recent FC
research has moved from studying group-level functional connectomes to individualized ones
(iFC) (55–63). In the process, an intriguing finding has emerged: iFC methods seem to recover a
network with expected topography (in most people, falling primarily in previously documented
frontal and temporal regions with a left-hemisphere bias) that is selective for language (64–67)
and closely matches the topography of the language network previously identified and
characterized using task-based localization (10).

However, to-date, iFC studies of language have involved relatively small numbers (*n* < 20) of
intensively-scanned participants, and inferences about the population drawn from few individuals
can be tenuous. Moreover, the bulk of this evidence is derived from a single task state (resting
state)—though see Ref. (66). Therefore, claims from iFC about e.g., the existence, topography,
and functional properties of a language network would benefit from a larger and more diverse
sample of individuals and task states (68–70). Further, on the practical side, any form of data
collection that is strictly for localization purposes (including resting state scanning) shortens the
time available for the main experiment(s) in the scanning session, and, like localizer tasks, resting
state iFC cannot be applied retrospectively to task-only datasets that have already been collected.
These considerations limit the practical utility of iFC for functional localization. However, these
limitations would be removed if the language network could be detected in *arbitrary* fMRI data,
irrespective of task contents. Several lines of prior evidence support this possibility. First, iFC
appears to be highly conserved across task states (71–73). Second, the language network as
identified using task contrasts exhibits stable connectivity between rest and task (74, 75). And
third, iFC studies have directly shown striking recovery of the same frontotemporal language
network using task-based iFC (76) in samples of two (64) and fifteen (66) individuals.

In this study, we pushed this insight towards both scale and generality. Towards *scale*, we applied
iFC methods to every fMRI session collected in the Fedorenko lab between 2007 and 2024
(excluding data from studies of people with brain lesions or an established diagnosis of a
neurodevelopmental disorder, such as autism), a total of 1,957 sessions from 1,199 unique brains
(see **Materials and Methods**). This dataset includes two orders of magnitude more individuals
than any prior iFC study of language, thereby increasing our ability to make inferences about
human brain organization. Towards *generality*, we explored whether a language network is

detectable in iFC parcellations under the most general conditions we can simulate: only having
access to fMRI timecourses, with no knowledge of the task, from a single scanning session, using
fully automated analyses.

To foreshadow our key results, we found that iFC reliably recovers a network (LangFC) with
strikingly similar properties to prior findings using task localization (10). In, particular, LangFC (a)
shows expected topography, distinct from other brain networks, (b) is selective for language, (c)
emerges across task states, (d) differs in function from nearby networks, (e) is robust to the
granularity of the parcellation, (f) is stable within individuals and variable between them, (g) can
be identified efficiently, and (h) reproduces localizer task-based results. This finding has
implications for neuroscience, neurosurgery, and neural engineering (see **Discussion**).

Results

Drawing on prior FC work that parcellates the brain into distributed networks of strongly functionally connected (covarying in activity over time) areas (51, 64, 65, 77), we developed a simple and fast automated procedure (schematized in **Fig 1**) for computing individualized probabilistic assignments of small-scale volumetric brain regions (2mm isotropic voxels) to functionally-labeled networks. The approach is based purely on low-frequency fluctuations over time in blood oxygen-level dependent (BOLD) measures recorded by fMRI, without reference to task contents. For maximum simplicity and generality, we did not apply task regression (i.e., residualizing the task structure out of the timecourses, see **Discussion**). Evidence from our study (**SI C**) and other recent work (66) suggests that a language network with qualitatively similar functional properties also emerges under task regression.

Our parcellation procedure for a single scanning session was as follows. *First*, we computed a binary connectivity matrix R per session (65). To do so, we computed a V x 1,000 correlation matrix between the timecourses (times of repetition or TRs, usually corresponding to 2s of data in this study) in V three-dimensional voxels in the gray matter volume and the average timecourses in 1,000 parcels of a prior atlas (53). R was then computed by binarizing against the 90th percentile across the whole matrix, following Ref. (65). Parcellation results were robust to many of these design choices (**SI D**), generalized to a qualitatively different template-matching method (**SI E**), and generalized across both rest- and task-based iFC in direct comparisons (**SI F**). *Second*, assuming a fixed number of networks k, we clustered the voxels into networks by applying k-means to R. Because k-means is sensitive to initial conditions, we derived a *probabilistic parcellation* by computing 100 different clusterings from 100 random initializations. These sampled clusterings are not commensurable: the network boundaries can differ, and even if boundaries are identical, the assignment of labels (1, …, k) to networks is random. To address this, in our *third* step, we greedily aligned the clusterings into a common space. To do so, we sorted the clusterings by their mean squared error (best to worst) and initialized the parcellation to the best clustering. We then incrementally modified the parcellation at each subsequent clustering by first using linear sum assignment (78) to optimize the spatial alignment between the clustering and the current state of the parcellation and then updating the parcellation with a moving average. This procedure yields a probabilistic whole-brain map for each of the k networks. In each map, the value in each gray matter voxel represents the probability of belonging to the corresponding network. *Fourth*, we extracted 16 functionally labeled networks from the parcellation based on spatial correlation to population-level reference atlases for 16 putative networks proposed by prior work, namely, the Language Atlas (LanA) derived from language localizer task contrasts in a large cohort (79), plus the spatial priors for 15 functional networks derived task-independently in a different sample of participants (65): language (LANG), frontoparietal A and B (FPN-A/B), default A and B (DN-A/B), cingulo-opercular (CG-OP), salience/parietal memory (SAL/PMN), dorsal attention A and B (dATN-A/B), auditory (AUD), premotor posterior-parietal rostral (PM-PPr), somatomotor A and B (SMOT-A/B), and visual central and peripheral (VIS-C/P).

Because the optimal k is unknown and may vary between individuals, we optimized k for each session by running the entire procedure above independently for k = 10, 20, …, 200 and selecting

the value of *k* that maximized the average spatial correlation between the labeled iFC networks
and their corresponding reference atlases. To avoid *post hoc* selection of results, the final
parcellation for a session was computed by resampling a new parcellation at the chosen value of
k. Importantly, we were not selecting for a particular functional profile for any network: the
optimization of *k* is based only on the average spatial similarity to the 16 reference atlases and is
therefore independent of any task contrasts available for that participant.

These iFC-derived functional networks were then analyzed with respect to diverse properties,
including their responses to key contrasts (*t*-statistic) during a set of tasks that were frequently
attested in the dataset and spanned a range of cognitive processes: language (reading and
listening), theory of mind (verbal and nonverbal), executive functions (spatial working memory),
numerical cognition, music perception, and high-level visual perception. Given our focus on
language, a key contrast of interest was the *sentences vs. nonwords* (S-N) contrast in a heavily-
studied and widely-used reading-based localizer task for language (31). Therefore, all runs used
to estimate the S-N contrast for an individual were excluded from the parcellation procedure,
ensuring data independence. iFC and task contrasts were compared using two quantitative
measures: (a) Fisher-transformed spatial correlation between an iFC-derived network and the
task contrast *t*-map—denoted z(r), and (b) the average *t*-value of the task contrast within an iFC-
derived network, weighted by the voxelwise probability of network membership. These measures
are complementary: z(r) captures overall *spatial similarity* to the task-evoked response (thus
penalizing spatial deviation from the topography of a task contrast, including false negatives: task-
responsive areas that fall outside the network), whereas the *t*-value captures the *strength* of the
task-evoked response within the network (thus primarily penalizing false positives: task-
unresponsive areas that fall into the network).

Detailed methods for parcellation and analysis are provided in **Materials and Methods**.

Figure 1: Schematic of our analysis procedure for a single participant. Voxelwise blood oxygen-level dependent
(BOLD) timecourses are correlated with average timecourses in each of 1,000 anatomical parcels (53) to produce a
correlation matrix (functional connectome), which is then binarized (in the schematic, black dots correspond to the 10%
of the strongest voxel-to-voxel correlations). Voxel clusterings (parcellations) are sampled by repeatedly applying *k*-
means to the voxelwise patterns of functional connectivity. These samples are then greedily aligned using linear sum
assignment (78) and averaged to produce probabilistic assignments of voxels to (unlabeled) networks. Interpretable
labels are then assigned to a subset of the networks in the parcellation by finding the most spatially correlated network
in the parcellation to each of a set of reference atlases. For details, see **Materials and Methods**.

176
Figure 2: A. Individual-level LangFC networks that are labeled relative to LANG (light) and LanA (dark) are spatially
similar to the LANG and LanA reference atlases (this is expected given that these atlases are used to label LangFC).
Similarity to the other reference atlases is low, with weak similarity to two networks (DMN-B and AUD) that are known
to abut language areas within individuals. **B.** Within individuals, LangFC is nearly identical whether labeled using LANG
or LanA, and spatially dissimilar from other FC-derived networks. **A-B.** Error intervals represent standard errors of the
mean (SEMs), which in some cases are too small to be visible given the size of our sample. **C.** The LANG and LanA
reference atlases used to automatically label LangFC from the data-driven parcellation, alongside both the group
average in our study of binarized ($p > 0.5$) LangFC and an estimate of LangFC's "periphery", with faint trends highlighted
with white ellipses in the left temporoparietal area and the right superior temporal sulcus (see **Materials and Methods**).
The LANG and LanA atlases are broadly similar, as is the group average of LangFC. The periphery is faint but tends
to fall in right-hemisphere homotopes of language areas, as well as a left-hemisphere area posterior to temporal
language areas, consistent with prior task-based evidence (80). **D.** LangFC (blue) vs. task t-maps (sentences vs.
nonword lists or S-N, red) in the 10 participants with the highest S-N contrast stability between even and odd runs.
Overlap is shown in magenta, and opacity reflects magnitude ($0.2 < p < 0.8$ for LangFC, $1 < t < 4$ for S-N). LangFC
overlaps substantially with the S-N contrast (and tends to be contained within it) and follows inter-individual variation in
the topography of task activations.

LangFC Shows Expected Topography, Distinct from Other Brain Networks

We first compared the topography of our individualized LangFC estimates both to population-level expected topographies (reference atlases) of several key networks and to other iFC-derived networks in the same individual. Unsurprisingly, LangFC has a similar spatial distribution (**Fig 2A**) to the reference atlases used to label it (LANG and LanA, **Fig 2C**). More noteworthy is the fact that it has low or negative spatial correlation with the other fourteen reference atlases, indicating that LangFC was generally well separated from population-level expected topographies of networks that have been previously associated with nonlinguistic functions. When comparing LangFC to the set of iFC-derived networks in the same individual instead of reference atlases, this spatial separation is substantially enhanced (**Fig 2B**): LangFC is nearly identical within individuals whether labeled relative to LANG (65) or LanA (79), with weak or negative spatial correlation to other iFC-defined networks in the same individual. Note that, due to our probabilistic network definitions, different iFC networks can in principle overlap spatially; the fact that they generally do not is a contingent outcome. The finding of similar LangFC outcomes regardless of reference atlas (LANG or LanA) is noteworthy given that the LANG and LanA reference atlases differ meaningfully: although they are visually similar (**Fig 2B**), their z(r) to each other is only 0.37, and thus they could in principle systematically pick out different networks in the parcellation. But, in practice, LANG and LanA references picked out the same network in 58% of sessions in our study, and in the remaining sessions they identified networks with a similar degree of spatial similarity—average z(r)=0.39±0.01 SEM—to the similarity between the LANG and LanA reference atlases themselves.

The two most topographically similar networks to LangFC are AUD and DMN-B, both of which are known to abut temporal language regions within individuals (67, 81). In addition, when we consider an "extended" LangFC (82) composed of multiple iFC subnetworks whose union maximizes spatial similarity to the reference atlas (LANG or LanA, see **Materials and Methods**), we find (**Fig 2C**, bottom) that LangFC's periphery tends to fall both in right hemisphere homotopes of language areas and in left-hemisphere areas posterior to temporal language areas. This finding is consistent with previous task-based reports about the distribution of the language network's "periphery" (80, 82) or "weak shadow" (83).

Consistent with prior claims (64), LangFC (**Fig 2C**, bottom) systematically includes areas in the middle frontal / superior precentral gyri as well as dorsomedial frontal areas that fall outside of traditional theoretical models of language neurobiology (13), while also excluding temporoparietal areas that are often included in language neuroscience studies (20, 84). The inclusion of temporoparietal areas in language studies is likely because these areas often register responses to meaningful language, as reflected by their presence in the task-derived LanA atlas (**Fig 2B**, bottom). But prior work has reported that language-responsive temporoparietal areas differ functionally from the language network in several respects and are thus arguably not part of the network (64, 80), a claim that finds support from our iFC results.

LangFC also shows the left-hemisphere bias abundantly attested in prior work on language in the human brain (4, 10, 13, 40, 64, 85–91), as can be seen qualitatively in **Fig 2D** and **SI A**. We

quantified this impression by computing a *laterality index* (LI) defined as the ratio of the
interhemispheric difference to the interhemispheric sum in some measurement (92), thus ranging
from -1 (fully right-lateralized) to 1 (fully left-lateralized). We found comparable degrees of strong
left-hemisphere bias across participants (averaging across sessions within participants) in
LangFC (number of voxels exceeding p=0.5 of belonging to LangFC in the parcellation,
LI=0.61±0.01SEM) and the reading localizer task contrast (number of voxels exceeding t=5 in the
sentences–nonwords contrast, LI=0.60±0.01SEM).

Figure 3: A. FCLang is more spatially similar to language vs. other contrasts (top) and likewise has a stronger average
response to language vs. other contrasts (bottom), whether parcellated from all runs (left) or from nonlinguistic runs
only (right). The larger z(r) and *t* values for verbal theory of mind can be explained by linguistic confounds in the task
(80). **B.** Other iFC networks show a different functional profile. AUD only shows a strong response in an auditory task,
FPN-A (which corresponds to the Multiple Demand (MD) network; (65)) doubly dissociates from LangFC (positive

response to executive and numerical tasks and negative response to language tasks), and DN-B (which corresponds
to the Theory of Mind (ToM) network; (65)) responds most strongly to theory of mind tasks and shows the default
network's signature task negativity (strong deactivation under demand during executive and numerical tasks). **C.** The
language network is stable over a large range of parcellation granularities, with little decrease in the number of voxels
(sum of LangFC probabilities) or change in spatial similarity to the reading localizer contrast map (S-N) beyond about
50 networks. **All panels:** Error intervals represent standard errors of the mean (SEMs), which in some cases are too
small to be seen given the size of our sample.

LangFC Is Selective for Language

The individualized spatial distributions of LangFC and the S-N contrast—which are derived from
independent data—are highly overlapping (especially in superior temporal, inferior and middle
frontal, and dorsomedial frontal areas), as shown qualitatively in a sample of participants (**Fig 2D**,
see **SI A** for exhaustive results) and quantitatively across participants (**Fig 3A**). LangFC is
spatially correlated—high z(r), **Fig 3A** top—with contrasts evoked by language tasks but not tasks
targeting theory of mind, executive functions, numerical cognition, music, or high-level visual
processing. Likewise, the contrasts themselves—*t*-values, **Fig 3A** bottom—are large for language
tasks but not the other tasks. The only nonlinguistic task that evokes a substantial response in
LangFC is the verbal theory of mind task, but this task is reading-based (and thus mediated by
language comprehension, unlike its non-verbal counterpart) and has been shown in prior work to
be confounded with dimensions of linguistic complexity that are independently known to drive
responses in language areas (80).

LangFC is also more functionally selective than the reference atlases used to label it: it has higher
z(r) and *t*-value for language tasks than LANG (filled vs. unfilled dotted bars in **Fig 2A**). Although
LangFC has comparable z(r) in language tasks to the LANA atlas, it is more functionally selective
(higher *t*-value, filled vs. unfilled solid bars in **Fig 2A**). LanA therefore tends to capture the spatial
distribution of language task responses reasonably well (likely by virtue of being more
continuously-valued and covering a greater spatial extent than LANG, **Fig 2C**), but it does so at
the expense of functional selectivity. Only LangFC—which is individualized—both captures the
spatial distribution of task responses and reliably excludes functionally irrelevant areas. Moreover,
in supplementary analyses (**SI B**), we found that our approach to labeling LangFC from among
the set of networks in the parcellation was on par with an "oracle" setting that directly selected the
network most similar to the participant's reading language localizer contrast map. This outcome
suggests that our labeling approach nears the participant-specific optimum for this dataset. The
importance of identifying language areas within individual brains evidenced here aligns with prior
claims of weak structure-function tethering for language across individuals (35, 36, 38).

LangFC Emerges Across Task States

Fig 3A shows evidence that functionally relevant stimulation (language) is not needed to identify
LangFC: even when we parcellate only based on tasks that involved no language in input or
response (e.g., a spatial working memory task or a face perception task; see **Materials and**
Methods for details about the nonlinguistic tasks), we recover a variant of LangFC ("Nonlinguistic
Runs"). The recovered network is qualitatively similar in spatial distribution and functional profile
to LangFC derived from all runs to the exclusion of the S-N task contrast ("All Runs"), albeit with

some degradation in the selectivity of the network's correspondence to language task contrasts.
Note that this is a conservative test: in the nonlinguistic condition, we are not only excluding
functionally relevant data, but we are also parcellating on less than a third of the data on average
(mean 581 timepoints, rather than 1,854), which can harm parcellation quality (see e.g., Ref. (65)
and this study, **LangFC Can Be Identified Efficiently**). In supplementary analyses (**SI C**), we
found similar estimates of LangFC regardless of whether we regressed out the task structure.
These findings converge to suggest that LangFC connectivity is strong enough to enable good
recovery of the network across diverse task states.

LangFC Differs in Function from Nearby Networks

LangFC's (language-selective) functional profile is different from the functional profiles of
networks known to be spatially adjacent to language areas within individual brains (**Fig 3B**),
including the auditory network (AUD), fronto-parietal network A (FPN-A, sometimes called the
multiple demand (MD) network (93, 94)), and default network B (DN-B, sometimes called the
theory of mind (ToM) network (95)). AUD only shows a substantial response to the listening-based
language localizer, which contrasts intact speech with unintelligibly degraded speech (41).
Although this contrast is generally effective for localizing high-level language areas, it does not
perfectly match acoustic features across conditions, and therefore activates nonlinguistic auditory
areas, including speech-selective areas (96, 97), to some extent (67). AUD shows only a weak
response to a music task, plausibly because many auditory areas, including speech-processing
areas, are not sensitive to music structure (e.g., Ref. (97)) and thus respond similarly in both the
typical and structure-scrambled conditions. FPN-A shows a strong response to working memory
and math tasks and weak or negative responses to all other tasks. Its response is anticorrelated
with the language localizer task, which is a known property of this network, to the point that the
reverse contrast (nonwords vs. sentences) can be used as an MD network localizer (98). FPN-A
and LangFC thus doubly dissociate with respect to their language vs. executive/numerical task
responses. DN-B shows little response to language tasks, is strongly activated by theory of mind
tasks, and is strongly deactivated by executive/numerical tasks. All of these properties are
expected based on prior characterization of DN-B's function (65, 66, 99–101).

LangFC Is Robust to the Granularity of the Parcellation

We found (**Fig 3C**) that the size and shape of LangFC converged to a stable configuration around
a granularity of approximately 50 networks in the parcellation and remained stable over a range
of up to 200 networks, considerably more than the 15 networks used in recent iFC studies of
language (65, 66). Despite the increasing granularity of the parcellation, LangFC did not
appreciably fractionate, but instead retained a stable count of about 2,000 voxels on average
(computed as the sum of LangFC probabilities across the gray matter volume) and a stable
degree of spatial similarity to the S-N contrast within individuals. This result reinforces prior claims
that the language network is tightly functionally integrated, rather than showing sharp network-
internal functional divides (10).

Figure 4: A. Both LangFC and the S-N contrast *t*-maps are more similar (a) between sessions within individuals vs. (b) between individuals, indicating substantial individual variability in structure-function tethering for language. LangFC is similarly stable whether considering the whole brain (whole) or only six left-hemisphere regional masks (masked), whereas S-N is more stable under masking, at least within individuals. **B.** The matrix of pairwise z(r) between LangFC as estimated from different numbers of runs (1, 2, 5, 10, 25, and 50) shows that LangFC stability increases with the number of runs used for parcellation. LangFC estimates from larger numbers of runs (especially 5 or more, bottom right of the plot) have greater Fisher-averaged correlation with each other. **C.** LangFC shows a language-selective profile of task responses (see **Fig 2** for task labels) even when estimated from a single run (left), but its functional selectivity is enhanced by parcellating on more data (right), especially in the strength of the network's language task response (*t*-value).

LangFC Is Stable Within Individuals and Variable Between Them

We found (**Fig 4A**) that both LangFC and the *t*-maps for the S-N task contrast were stable within individuals across scanning sessions but variable between individuals, consistent with prior reports (36, 64). Moreover, within individuals, we found that LangFC was more stable than the S-N contrast when evaluated across the entire brain, suggesting that the iFC approach successfully "cleans up" some of the noisy parts of task-based maps (see **SI A**). However, when restricting the analysis to six left-hemisphere fronto-temporal regional masks used in prior work (36), we found that S-N contrasts became more stable than LangFC, although LangFC remained stable. Thus, relative to a localizer task, LangFC seems to provide less noisy localization at the whole brain level, but slightly noisier localization within brain areas likely to contain the "core" language network (82).

LangFC Can Be Identified Efficiently

To assess how much data within an individual is needed to identify LangFC, we ran a secondary analysis of the subset of the participants in the dataset (n=53) who had at least 50 runs (on

average, at least 5 hours of imaging data) in total across all scanning sessions. We parcellated
each individual based only on the first m runs, $m \in \{1, 2, 5, 10, 25, 50\}$ (when $m = 50$, mean
9,311±151SEM TRs). We found (**Fig 4B**) that increasing the number of runs helped stabilize the
LangFC estimate, consistent with prior work (65): LangFC estimates based on larger numbers of
runs (especially 5 or more) are more spatially similar to each other. Nonetheless, LangFC is
already functionally selective even when estimated from a single run (mean 198±8SEM TRs, **Fig**
4C, left), although selectivity becomes more pronounced with more data (**Fig 4C**, right). These
results suggest that LangFC can be identified to a reasonable approximation even with little data,
but that parcellation quality will likely benefit from additional data when available. Importantly, if
task-agnostic iFC is being applied retrospectively, it requires no data beyond the data already
being collected for the main experiment(s).

LangFC Reproduces Localizer Task-Based Results

We have confirmed that iFC recovers a language selective network with favorable characteristics across a range of measures of reliability, stability, and efficiency. These results suggest that iFC can be used instead of task-based localization to identify the language network within individuals. We put this suggestion to direct test by using LangFC as a drop-in replacement for the S-N *t*-map in a reanalysis of a prior study in the lab that used task-based localization (102). In brief, the experiment was a reading study in which participants read variable-length (1- to 12-word) "chunks" that formed either complete phrases (real-words condition), "syntactic prose" in which real words were replaced with plausible nonwords (Jabberwocky condition), or partial syntactic phrases (non-constituents condition; see the original study for additional details). In one analysis of the study, the top 10% of voxels with the largest S-N *t*-value within individuals were identified for each of the six regional parcels shown in **Fig 5A**, resulting in individualized *functional regions of interest* (fROIs). In the original study, it was found that task-based functional localization dramatically increased signal strength for the key effects (**Fig 5B**) relative to group-level ROIs (**Fig 5D**). When we instead functionally localized based on LangFC (**Fig 5C**), we largely recovered the favorable sensitivity properties of task-based localization, especially in (e.g., inferior frontal) regions where sensitivity suffers most in group-level analyses (103). Quantitatively, when we looked across the six regions in this analysis, we found a small but significant decrease in the slope of the length effect in the real-word conditions from iFC relative to direct task-based localization (mean=0.39, *t*=2.4, *p*=0.02) but a larger significant increase in this same slope from iFC relative to the anatomical group-level parcels (mean=0.60, *t*=5.1, *p*<0.001). This result supports the practical feasibility of using LangFC to find language areas in individual brains and study their response properties, including potentially in retrospective analyses of existing data and in participant populations for whom additional task-based localizer scans would be burdensome.

Discussion

We have argued that contradictory theoretical precommitments and widespread reliance on group-based functional mapping present barriers to progress in language neuroscience, and we have evaluated the potential of individualized functional connectomics (iFC) to skirt these issues and offer a path forward (46). In so doing, we have built on prior evidence to this effect (64–67) while going substantially beyond it in scale and generality, simulating widely-applicable conditions across diverse practical needs in functional neuroimaging (access only to arbitrary functional timecourses from a single scanning session) in the largest sample we could obtain (nearly 1,200 participants). Similar to other work (104, 105), we used an entirely automated process for parcellating individual brains into interpretably labeled networks with no task supervision. This design enabled our core contribution: we assessed at scale the extent to which recent claims that a network for language is a key unit of human brain organization (10)—which to date are based heavily on task fMRI, though see refs (64–67)—hold up under weaker assumptions. In this respect, our focus is primarily on the nature of human brain organization rather than on methodological approaches to studying this organization: we are not advocating a particular approach to functional brain parcellation and indeed expect, and show empirically, that the qualitative pattern generalizes across methods (**SI D** and **E**). Nonetheless, our claims have important practical implications because they support the use of iFC to identify the language network within individuals in a broad range of both prospective and retrospective settings, including the unfortunately common case where the task parameters associated with a given run (e.g., in an open dataset) are missing, incomplete, or poorly documented.

Specifically, we found that iFC systematically yielded a network with broadly similar topography to expectations established by prior work (in most brains, the network was left-lateralized and fell primarily in the temporal and frontal lobes). We further found that this network was selective for language, different in functional tuning (even doubly dissociating) from networks closely adjacent to it, robust to parcellation granularity (suggesting tight functional integration across the network), stable across scanning sessions within individuals, and variable between individuals. This picture of the neurobiology of language—which amounts to an iFC-based recapitulation of the picture advocated in a recent position paper based largely on task data (10)—diverges from standard theorizing in language neuroscience, which attempts to assign specific linguistic functions to macroanatomically defined regions or pathways in the brain (12, 13, 15, 19, 20, 106–110). Instead, we find iFC evidence convergent with prior claims (36) that the stable trait-level topography of language areas differs substantially between brains (**Fig 4A**). It follows from this that the question of which (macroanatomical) regions support which (linguistic) functions is ill-posed, at least for the population as a whole, which might partially underlie ongoing confusion about the basic neurobiology of language (11). We have emphasized the left-dominance and frontotemporal distribution of LangFC merely in order to highlight continuities between our findings and those of decades of prior research in language neurobiology. But in so doing, we do not intend to imply that the language network is exclusively left-lateral or exclusively frontotemporal. Even within our own cohort we find qualitative evidence (**SI A**) of both (a) substantial individual variability in lateralization of both task and LangFC topographies (90, 111) and (b) LangFC and task topographies that frequently extend into other parts of the brain, consistent with recent

arguments (112–114). Quantifying and explaining these observations fall outside our present
goals, and we leave them to future work.

Our finding that LangFC is highly selective for language (**Fig 3A**) is a truly contingent outcome of
our analyses that converges both with recent iFC work (64–67) and with task-based studies (80,
98, 101, 115–117). We did not seek (and could not in principle have sought) this result in the
design of our procedure, given that nothing constrains the functional connectome to show any
particular task tuning. This finding is therefore strong independent confirmation of the hypothesis
that an integrated frontotemporal network for language is a key unit of adult brain organization,
independently of how language is construed theoretically or operationalized experimentally by
researchers. In other words, iFC offers language neuroscientists a theory-external explanatory
target in the brain, much as the discovery of the default network(s) has done for the functions that
they support (47, 99, 100, 118). It follows from this that the term "language network" is demoted
from definitional to descriptive: it refers to a brain network with independent existence that could
instead be called e.g., "the frontotemporal network" without loss of accuracy. Such a label would
belie the network's strikingly language-selective tuning, and we therefore have continued to
include "language" in our terminology. But our claims about this network would not be
fundamentally altered by future nuances in our understanding of its function, such as recent
evidence that this network is also engaged to some extent by nonverbal event semantics (119,
120).

Our findings also bear indirectly on influential claims that distinct linguistic subfunctions (e.g.,
processing of phonology, words, syntax, and sentence meaning) are implemented by different
macroanatomically-defined (e.g., inferior frontal vs. posterior temporal) regions (12, 13, 20, 106).
Any such sharp divisions have proven difficult to replicate within individuals (31, 102, 121–123),
and our findings converge with recent iFC work (64–67) in suggesting a reason why: the entire
network is tightly functionally integrated, as revealed by the fact that it is parcellated out of the
functional connectome as a single unit. We furthermore have shown that this is not merely an
artifact of choosing a particular parcellation granularity: even when the iFC approach has 200
networks to work with (and thus plenty of opportunity to fractionate the language network into
component networks or regions, if they existed), it prefers to keep LangFC intact (**Fig 3C**). This
result reduces the plausibility of any claims about sharp network-internal functional subdivisions
at scales detectable using fMRI: any claimed subdivisions would need to explain how the
activations across the putative divide are so highly correlated. This finding of course does not
obviate questions about how the network implements different linguistic subprocesses. It simply
encourages a reorientation away from macroanatomical divisions and toward other possible types
of differentiation, including structure at finer spatial scales (124, 125), in time (126), in the core
vs. periphery (82), in cortical gradients (127), and in distributed patterns of activation (128).

Beyond these findings and their bearing on theoretical questions about the neurobiology of
language, we investigated the practical utility of iFC methods for language network identification
in plausible real-world conditions in which individual-participant datasets are small or task
information is unavailable or unreliable, leaving only the possibility of parcellating directly on
timecourses with unknown task content, without the task regression (76) commonly used in other
iFC work (64, 66, 72). Although task regression is known to improve the ability to estimate the

resting state functional connectome from task data (76), the goal of iFC-based language
localization is not to simulate rest but instead to identify the language network under minimal
assumptions. We found that iFC showed favorable stability and efficiency characteristics that
support its practical utility for functional localization: LangFC is topographically similar to language
task contrasts in unseen data, is robust to the presence or absence of functionally relevant
stimulation, and remains spatially and functionally similar with or without task regression in direct
comparisons. Moreover, we found that LangFC can be identified to a good approximation even
from only a single functional run, while also measurably benefiting from additional data when
available. Finally, we showed that LangFC works well as a drop-in replacement for localizer task
contrast maps in an existing functional localization toolchain (129, 130). Together, these results
suggest a wide domain of practical applications for iFC as a theory-neutral language localization
method. Retrospective iFC unlocks thousands of hours of existing fMRI datasets for individualized
functional analysis, even if those datasets lack the localizer task contrasts that would otherwise
be a prerequisite. It also could support such analyses in studies facing practical constraints on
data quantity, such as participant populations with low tolerance for extended scanning (42). In
addition, iFC has potential as a technique to identify eloquent cortex prior to surgical resection
(131–134), to select sensor placements for neural speech prostheses (135–137), or to select sites
for language-related brain stimulation (138).

Our study has several limitations, some of which are plausible targets for future work. *First*, our
automated methods may introduce noise either in the mapping from the functional connectome
to a parcellation or in the labeling of LangFC. Errors in parcellation may arise because we have
used a parcellation method (*k*-means) that can converge to local optima (this issue also holds of
other widely-used parcellation methods, including independent components analysis and
dictionary learning). We have mitigated (but not eliminated) this issue by sampling and aligning
many parcellations with different random seeds. Errors in labeling may arise if an individual's
language network is successfully parcellated but happens not to be the most spatially similar
network to the reference atlas used to label LangFC. We have chosen to accept the possibility of
such errors for this study in order to achieve scale and minimize researcher influence on results.
But both of these steps can be replaced by manual expert checks of both the continuous functional
connectome (seed-based analysis) and the topographic plausibility of candidate LangFC
networks. Previous iFC studies have demonstrated that automatic and manual approaches to
identifying the language network tend to align closely (64, 65). Nonetheless, in smaller scale
studies, identification of LangFC based on expert review of the functional connectome is always
available.

Second, we have only explored a single basic approach to FC parcellation (*k*-means), without
engaging with significant recent efforts to increase the quality and sophistication of FC parcellation
methods (104, 138–141). We have done so for strictly practical reasons (we needed fast methods
to work at this scale of data), but we expect that our results provide a conservative picture of the
utility of iFC for language localization that will be surpassed by integrating with ongoing technical
advances in the field.

Third, although we have advocated the use of LangFC for task-agnostic language localization,
we are not advocating a wholesale abandonment of localizer tasks. Even if iFC is used (rather

than localizer tasks) for selective analysis, it is valuable to have localizer task data in order to
validate LangFC estimates. Without such validation, there would be no direct confirmation of
LangFC's functional tuning within an individual, and results would need to be interpreted more
cautiously. In other words, two lines of evidence are better than one: while we have shown that
iFC is now essentially always available for language localization (given that it can be reliably
estimated from arbitrary task states), additional task data when available can improve confidence
in the localization by providing independent convergent evidence. Moreover, localizer tasks
provide an estimate of the strength of response during language processing; such estimates can
be useful for comparison with other experimental conditions, and also constitute a neural marker
(reliable over time; Ref. (36)) for investigations of brain-behavior or brain-genetic relationships
across individuals. Thus, for studies targeting language for which it is feasible to collect a localizer
task, doing so can still have value, whereas for studies in which language localization is lower
priority and/or running additional localizer tasks is infeasible, we have shown that iFC can usually
serve as a strong stand-in.

Fourth, we have not engaged with (and cannot speak to) more nuanced questions about the
functional connectome itself, including widespread interest in (a) its dynamics (142–152) and (b)
its multivariate interactions (153–156). Our approach assumes based on prior evidence that much
of the functional connectome is stationary (72) and that networks can be recovered from
univariate voxel-level timecourses (65), and we leverage these assumptions to identify stable
language-relevant brain areas within individuals. But we leave open the possibility that e.g.,
functional connectivity can vary over time and between task states in ways that meaningfully bear
on the brain basis of language. The existence of reliable iFC methods for language neuroscience
opens up a new window onto these questions for future work.

Materials and Methods

fMRI Data Acquisition and Preprocessing

All structural and functional data were collected on a whole-body 3 Tesla Siemens scanner with a 32-channel head coil at the Athinoula A. Martinos Imaging Center at the McGovern Institute for Brain Research at MIT. Because our dataset covers the entire fMRI acquisition history of a neuroscience lab (see **fMRI Session Selection**), it includes data collected over a long timespan for diverse projects with diverse goals (including unpublished pilot studies), and thus the acquisition parameters vary. There were two large-scale changes in equipment and/or lab-standard acquisition parameters, one in 2021, and one in 2022. Typical scan parameters in each of these three time periods are given in **Table 1**. Detailed scan parameters for each run in the dataset are provided in our Stanford Digital Repository dataset (**URL**).

	~2021 and before	~2021 to ~2022	~2022 to present
Scanner Model	Siemens Trio	Siemens Prisma	Siemens Prisma
T1 (structural) parameters	176 sagittal slices with 1 mm isotropic voxels (TR = 2,530 ms, TE = 3.3 ms, TI = 900 ms, flip = 9 degrees).	208 sagittal slices with 0.85 mm isotropic voxels (TR = 1,800 ms, TE = 2.37 ms, TI = 900 ms, flip = 8 degrees)	208 sagittal slices with 0.85 mm isotropic voxels (TR = 1,800 ms, TE = 2.37 ms, TI = 900 ms, flip = 8 degrees)
T2* (functional) parameters	EPI sequence with a 90° flip angle and using GRAPPA with an acceleration factor of 2; with the following parameters: thirty-three 4 mm thick near-axial slices acquired in an interleaved order (with 10% distance factor), with an in-plane resolution of 2.1 mm × 2.1 mm, FoV in the phase encoding (A >> P) direction 200 mm and matrix size 96 × 96, TR = 2000 ms and TE = 30 ms	SMS EPI sequence with a 90° flip angle and using a slice acceleration factor of 2, with the following acquisition parameters: fifty-two 2 mm thick near-axial slices acquired in the interleaved order (with 10% distance factor), 2 mm × 2 mm in-plane resolution, FoV in the phase encoding (A >> P) direction 208 mm and matrix size 104 × 104, TR = 2,000 ms, TE = 30 ms, and partial Fourier of 7/8	SMS EPI sequence with a 90° flip angle and using a slice acceleration factor of 3, with the following acquisition parameters: seventy-two 2 mm thick near-axial slices acquired in the interleaved order (with 10% distance factor), 2 mm × 2 mm in-plane resolution, FoV in the phase encoding (F >> H) direction 208 mm and matrix size 104 × 104, TR = 2,000 ms, TE = 30 ms, and partial Fourier of 7/8
Number of runs	42,277	8,753	5,330

Table 1: Typical MRI acquisition parameters used in this study. Counts in "number of runs" are provided for
convenience and include near-matches to these typical configurations. Precise parameters for each run in the dataset
are provided in our Stanford Digital Repository dataset (**URL**).

fMRI data were analyzed using SPM12 (release 7487), CONN EvLab module (release 19b), and
other custom MATLAB scripts. Each participant's functional and structural data were converted
from DICOM to NIFTI format. All functional scans were coregistered and resampled using the 4th
degree B-spline interpolation to the first scan of the first session (157). Potential outlier scans
were identified from the resulting subject-motion estimates as well as from BOLD signal indicators
using default thresholds in CONN preprocessing pipeline (5 standard deviations above the mean
in global BOLD signal change, or framewise displacement values above 0.9 mm; (158)).
Functional and structural data were independently normalized into a common space (the Montreal
Neurological Institute [MNI] template; IXI549Space) using SPM12 unified segmentation and
normalization procedure (159) with a reference functional image computed as the mean functional

data after realignment across all timepoints omitting outlier scans. The output data were
resampled to a common bounding box between MNI-space coordinates (-90, -126, -72) and (90,
90, 108), using 2mm isotropic voxels and 4th degree B-spline interpolation for the functional data,
and 1mm isotropic voxels and trilinear interpolation for the structural data. BOLD signal in each
voxel of each run was then denoised by residualizing against variables controlling for the effect
of slow linear drifts, subject-motion parameters, signals originating in white matter and
cerebrospinal fluid, and potential outlier scans. Last, the functional data were smoothed spatially
using spatial convolution with a 4 mm FWHM Gaussian kernel.

Tasks and Materials

The task fMRI runs in our dataset come from a large and diverse set of published and unpublished
experiments. Since most of these tasks are not of interest (and documenting them fully would
amount to an exhaustive history of research conducted in the Fedorenko lab), here we restrict our
presentation to a subset of key tasks and materials: those that we directly use in this study either
to compute task contrasts or to select or exclude runs for parcellation. These tasks were selected
because they have been used relatively frequently and cover a spectrum of targeted cognitive
processes (e.g., language, social cognition, and high-level vision). In our Stanford Digital
Repository dataset (**URL**), we provide metadata on which of the following experimental tasks
apply to which fMRI sessions.

In general, a given participant did not complete all of these tasks, so we only evaluated
participants with respect to tasks they did complete. When possible, we used task contrasts
derived from the same session used for parcellation. Otherwise, if a task contrast was available
in a different session, we used those data (this is why identical task maps sometimes recur in
participants with repeated scans in **Fig S1**). If no task contrast was available for a participant, they
were omitted from evaluation on that contrast. For some tasks, our dataset includes minor variants
in parameters like timing, item lists, and the presence of additional conditions not used in these
analyses. For ease of comparison between task types, here we treat these variants as equivalent.

High-level descriptions of the key tasks used in this study are as follows (readers are referred to
the citations for additional motivation and methods detail).

Language (reading)

601   Participants read sequences presented one word at a time on a screen in two conditions: a
602   *sentences* condition in which the sequence formed a meaningful sentence, and a perceptually
603   matched *nonwords* condition in which the sequence formed a list of pronounceable pseudowords
604   (31).

Language (Listening)

606   Participants listened to audio recordings in two conditions: *intelligible* speech in a familiar
607   language, and *unintelligible* degraded versions of these recordings (41).

Theory of Mind (Verbal)

Participants read vignettes presented one at a time in two conditions: a *false belief* condition and a *false photo* condition (95). The false belief items described a scenario in which a character has a false belief. The false photo items described previous states of the world that are no longer true (e.g., an object that has since been removed). Although careful attention was paid in the design of these items to match the conditions on multiple linguistic dimensions, subsequent work has found that the false belief items are higher in multiple measures of linguistic complexity that are known to modulate language regions, and thus that language network responses to this task do not necessarily reflect theory of mind processing (80).

Theory of Mind (Nonverbal)

Participants viewed a silent animated film (the Pixar short *Partly Cloudy*) which has been proposed as a naturalistic theory of mind localizer (160). The film was coded for time intervals that depict (a) mental state content, (b) physical events, (c) non-mentalizing social interactions, and (d) characters experiencing physical pain, and these interval codes were used as regressors to estimate the task contrast (response to *mental* segments over *physical* segments).

Executive (Working Memory)

Participants viewed sequences of marked squares on a grid and were tasked with keeping track of all marked locations, assessed at the end of the sequence using a two-alternative forced choice (98). Items occurred in two conditions: easy (4 locations) and hard (8 locations).

Numerical (Math)

Participants saw a number and were tasked with computing its cumulative sum with a sequence of three additional numbers (98). The addends occurred in two conditions: easy (magnitude 2-4) and hard (magnitude 6-8).

Music

Participants listened to tonal melodies in two conditions, an *intact* condition in which the melody followed typical Western tone sequences and rhythm, and a *scrambled* condition in which these melodies' tones and rhythms were randomly scrambled (116).

High-Level Visual Perception

Participants viewed 3-second silent video clips in 5 conditions: faces, body parts, objects, scenes, and randomly scrambled objects (161).

fMRI Session Selection

We parcellated every admissible fMRI scan of neuroanatomically typical individuals in the history of the Fedorenko lab as of August 27th, 2024. Inclusion was defined as generously as was feasible. A small percentage of sessions (26 out of 1,983) were excluded for the following reasons:

1. There were missing or corrupt data or metadata, preventing timecourse extraction (11 sessions).

2. There were no functional runs from an all-anatomical scan (1 session).

3. There were no functional runs remaining after exclusion of language localizer runs (14 sessions). This situation arose because we have a privileged interest in evaluating the parcellation against an extensively studied reading-based language localizer (sentences vs. nonword lists) contrast—which is often used to identify the language network (10, 31)—and are following a design in which runs from the localizer task are entirely held out from parcellation to ensure the independence of this critical task. This requirement is conservative and not strictly necessary; in fact, we found that LangFC is recovered from reading localizer runs even when the task structure is regressed out (**SI C**). Runs for the other experimental tasks we examined (described in **Tasks and Materials** below, e.g., the hard vs. easy contrast from the spatial working memory task) were not held out from parcellation, because holding out all contrasts requires either (a) substantial loss of source data for parcellation if removing all evaluation tasks simultaneously, since the evaluation tasks make up a large portion of the available data, or (b) re-parcellating the brain based on different subsets of data for each contrast, which is infeasible (given that we are searching over many parcellation granularities in a large dataset, each complete set of parcellations takes weeks on our compute cluster and requires terabytes of storage).

The remaining dataset contains 1,957 sessions—each typically containing about an hour (1,854±12SEM TRs, TR=2s) of fMRI data—recorded from a total participant population of 1,199 individuals (the difference between the number of sessions and the number of individuals is due to repeated scanning of some individuals). To avoid biasing results, no additional quality controls or filters were applied. Each session's data was parcellated separately, even when the participant had completed other sessions. This allowed us to assess the stability of parcellations across sessions within an individual (see **LangFC Is Stable Within Individuals and Variable Between Them**) and ensured that our results were representative of the expected performance of our proposed method for a typical cognitive neuroscience experiment (in which each participant may only have one scanning session).

Parcellation and Evaluation Procedure

We identified and functionally evaluated putative language regions using a five-step procedure within each session of fMRI data in our study: sampling, alignment, labeling, aggregation, and evaluation. The essence of this procedure is schematized in **Fig 1**. Our general purpose codebase for volumetric parcellation of fMRI timecourses in NIFTI format, largely built on the *nilearn* (162)

and *scikit learn* (163) Python packages, is available open source:
https://github.com/coryshain/parcellate. We have additionally released a separate reproduction
codebase for all analyses specific to this study: https://github.com/coryshain/langlocFC. Although
many of the design choices described below are motivated by considerations of performance,
efficiency, or precedent set by prior work, we found in direct comparisons that most of them had
little impact on results, supporting the robustness of the parcellations to diverse implementation
details (**SI D**).

We have released all parcellation configuration files and results in the Stanford Digital Repository
(**URL**), along with the preprocessed timecourses that were used as input to the parcellation.

Sampling

Gray matter voxels from all available functional runs after exclusions (see **fMRI Session**
Selection) were individually bandpassed between 0.01 and 0.1Hz, detrended, and z-scored,
voxelwise (64). The resulting timecourses were concatenated into a single sequence, and the
time dimension was reduced to 200 principal components (PCs). Primarily for computational
reasons, the resulting 200-dimensional vector for each of the V voxels was then correlated with
the average vector within each of 1,000 parcels in a previously published atlas (53), resulting in
a V × 1,000 connectivity matrix (in our case, V=134,713, so the use of parcels for spatial
downsampling gives large memory savings without harming results, see **SI 3**). Following prior
work (65), the connectivity matrix was then binarized at a quantile threshold of 0.9.

The resulting matrix served as input to an iterative parcellation procedure in which voxels'
connectivity patterns were clustered into *k* networks using *k*-means under 100 random
initializations. This both mitigates the sensitivity of *k*-means to initial conditions and provides an
opportunity to quantify uncertainty about voxel assignments to networks, in hopes of capturing
core-periphery distinctions when relevant (164). This results in a sample of 100 clusterings
(discrete parcellations) of the gray matter volume. However, aggregating over this sample is
challenging due to the arbitrariness of the cluster labels assigned by *k*-means. Therefore, we
include an alignment step, described below.

Alignment

We used a greedy approach to align the 100 sampled parcellations into a common set of
networks. We first sorted the samples in ascending order (best to worst) according to the mean
squared error of their cluster centroids to the data (a measure of clustering quality). We then
initialized the probabilistic parcellation using the best sample. For each subsequent sample, we
found the optimal spatial alignment (measured as Pearson correlation over the gray matter
volume) to the current state of the probabilistic parcellation using linear sum assignment (78) and
updated the probabilistic parcellation using a moving average with the newly aligned sample. The
result is a set of *k* probabilistic (and potentially spatially overlapping) assignments of voxels to
networks, with 0 indicating that a voxel was never assigned to the network and 1 indicating that
the voxel was always assigned to the network. Each network in the final probabilistic parcellation
was then min-max normalized.

Labeling

Interpretable labels were heuristically assigned to a subset of the networks in the probabilistic parcellation based on spatial similarity (Pearson correlation in the gray matter volume) to a set of (non-individualized) reference atlases (65, 79). For each reference atlas, the most spatially similar individualized network in the parcellation was selected and assigned the corresponding functional label (e.g., LANG, DN-B, FPN-A, etc.). The assignments could be many-to-one, in that the same network could be chosen by multiple reference atlases (in practice, for sufficiently granular parcellations, this was rare).

Aggregation

We wanted both to explore the influence of the choice of the number of networks k and allow k to vary as needed between individuals. Thus, for this study, we placed all three of the preceding steps (sampling, alignment, and labeling) under a loop over values of k from 10 to 200 in increments of 10, resulting in 20 parcellations (at different k) per scanning session. We defined the optimal k for a session to be the value that maximized the average spatial similarity between the reference atlases and their corresponding labeled iFC counterparts. We chose to select on correspondence to the reference atlases in order to avoid any bias toward a particular pattern of functional tuning (as would be the case if we e.g., selected on similarity to language task responses). In order to avoid *post hoc* selection of results, we refitted the parcellation using the chosen value of k to produce our final parcellation for the participant.

Evaluation

As described in **Results**, we applied two key analyses of functional tuning to all labeled networks in the parcellation, for all available tasks within our critical set for which we had data for the participant: z(r), a measure of spatial similarity between the network and the distribution of task responses, and mean *t*-value, a weighted sum across the gray matter volume of the voxelwise *t*-values for a given contrast, weighted by their iFC-estimated probability of belonging to the network in question.

Additional Analyses

Here we describe all remaining methods used for secondary analyses in this study.

LangFC Periphery (Fig 2C)

To identify the LangFC "periphery" (visualized at the group level in **Fig 2C**), we developed a procedure for finding a union of subnetworks in our probabilistic parcellation that maximized overall spatial similarity (Pearson correlation) to the reference atlas. To do so, in each individual, we started with LangFC labeled relative to a reference atlas (LanA), and we used a greedy approach in which we iteratively identified the next most similar network to the reference atlas and added it to the union (by definition, the first of these networks is LangFC) as long as doing so increased spatial similarity between the union and the reference atlas. This greedy approach is computationally efficient at the expense of global optimality, since we did not exhaustively

maximize spatial similarity over the power set of networks in the parcellation. Our stopping
criterion guarantees that there will always be at least one network (LangFC) in the union, and
possibly (but not necessarily) more. A voxel's probability of belonging to the union is equal to its
probability of belonging to at least one of the component subnetworks, that is, the probability of
at least one success under a Poisson-binomial distribution (165) parameterized by the
membership probabilities for each subnetwork in the union. Union membership was used to
create a new probabilistic atlas representing the probability of belonging to an iFC-based
extended language network (82). To identify the LangFC "periphery" in an individual, we
discretized both LangFC and extended LangFC (p > 0.5) and selected all voxels belonging to
extended LangFC but not LangFC. These boolean maps per participant were then averaged
across all participants in stereotactic space to produce the probabilistic atlas visualized at the
bottom of **Fig 2C**, which provides an iFC-based measure of the topographic tendencies in the
language network's periphery.

Nonlinguistic Runs (Fig 3A)

To produce the "nonlinguistic runs" analyses on the right side of **Fig 3A**, we re-parcellated all
sessions that contained at least one of a number of tasks that we identified as nonlinguistic, in
the sense that no language was present in the stimulus and no overt or covert language response
was requested. These tasks included the spatial working memory task, nonverbal theory of mind
task, music task, and visual perception tasks described in **Tasks and Materials**. They also
included resting state scans, silent movie watching, various non-linguistic visual perception tasks
(e.g., motion perception, action perception), abstract symbolic rule induction tasks, and
nonspeech auditory perception tasks. We have uploaded a table of all nonlinguistic tasks and
brief descriptions to the Stanford Digital Repository (**URL**). We cannot of course rule out the
possibility that some participants e.g., engaged in inner speech during the task (166–168), except
to note that some of these tasks (spatial working memory and math) occur frequently among our
nonlinguistic runs and elicit weak or negative responses in language areas (**Fig 3A**), suggesting
that covert language is not used pervasively in order to support these types of thought (24).

Variability Between and Within Individuals (Fig 4A)

To measure within- and between-individual variation as reported in **Fig 4A**, we used the following
procedures.

Between-individual variation was computed by taking both the LangFC topographies on the one
hand and the reading localizer task maps on the other from all sessions in our main analysis,
averaging these across sessions as needed in cases where the same person participated in
multiple sessions. We then computed the between-individual spatial correlation by averaging
across the lower triangle of the (1,199 x 1,199) participant-wise Fisher-transformed correlation
matrix.

Within-individual variation was computed by finding all participants with at least two sessions (305
participants, 1,063 sessions, 3.5 sessions per participant on average) and computing session-
wise Fisher-transformed spatial correlation matrices between LangFC topographies on the one

hand and between reading localizer task maps on the other, independently for each individual.
The resulting Fisher correlations were then averaged to provide an estimate of typical stability
between runs within an an individual.

Partial Reproduction of Shain et al. (2024)

795 For reliable comparison to task-based localization in Ref. (102), we exactly matched their
796 procedure for defining functional regions of interest (fROIs) with one change: we replaced the S-
797 N localizer task *t*-maps with LangFC probabilistic maps. The resulting procedure was as follows,
798 for each participant:

1. Mask the brain volume with each of six regional parcels from a prior study (20): left pars orbitalis (LIFGorb), left pars triangularis (LIFGtri), left temporal pole (LTP), left anterior temporal sulcus (aSTS), left posterior temporal sulcus (pSTS), and left temporoparietal junction (LTPJ).
2. Within each regional mask, identify the subset of voxels with the top 10% probability of belonging to LangFC according to that participant's probabilistic network estimate. This top-10% subset of voxels defines the fROI for each of the six regional masks.
3. Within the fROI, compute the average effect size for each contrast of interest—see Ref. (102) for contrast definitions.

The fact that LangFC defines valid network membership probabilities (unlike e.g., a task *t*-map)
offers principled alternatives to the design above, such as taking a weighted average over the
entire gray matter volume (as in **Fig 3A**) or selection by absolute thresholding (e.g., $p > 0.5$, i.e.,
more likely than not to belong to LangFC). Such approaches could have advantages, including
the possibility of discovering areas that fall outside the regional masks, or application to
participants with different brain anatomy relative to template spaces derived from typical adults
(e.g., children or individuals with brain lesions). We leave validation of alternative localization
criteria to future work.

Acknowledgments

We would like to acknowledge the Athinoula A. Martinos Imaging Center at the McGovern Institute
for Brain Research at MIT, and its support team (Steve Shannon and Atsushi Takahashi). We are
also indebted to the many past and current members of the Fedorenko lab (including
undergraduates, research assistants, graduate students, and postdocs) for the countless hours
they collectively invested in gathering, preprocessing, and analyzing the data that made this study
possible. We would also like to thank Anya Ivanova and Randy Buckner for their valuable input,
and Atsushi Takahashi and Alex Fung for help in retrieving acquisition sequence details for this
dataset. In addition, EF was supported by NIH awards DC016607 and DC016950 from NIDCD,
and NS121471 from NINDS, and research funds from the McGovern Institute for Brain Research,
the Department of Brain and Cognitive Sciences, the Simons Center for the Social Brain, and
MIT's Quest for Intelligence.

References

1.   M. D. Hauser, N. Chomsky, W. T. Fitch, The Faculty of Language: What Is It, Who Has It,
and How Did It Evolve? *Science* **298**, 1569–1579 (2002).

2.   S. Dehaene, F. Al Roumi, Y. Lakretz, S. Planton, M. Sablé-Meyer, Symbols and mental
programs: a hypothesis about human singularity. *Trends Cogn. Sci.* **26**, 751–766 (2022).

3.   H. H. Clark, *Using language* (Cambridge university press, 1996).

4.   P. Broca, Remarques sur le siège de la faculté du langage articulé, suivies d'une
observation d'aphémie (perte de la parole). *Bull. Memoires Soc. Anat. Paris* **6**, 330–357
(1861).

5.   D. V. M. Bishop, M. J. Snowling, P. A. Thompson, T. Greenhalgh, C. Consortium,
CATALISE: A Multinational and Multidisciplinary Delphi Consensus Study. Identifying
Language Impairments in Children. *PLOS ONE* **11**, e0158753 (2016).

6.   H. Goodglass, *Understanding aphasia* (Academic Press, 1993).

7.   M.-M. Mesulam, Primary progressive aphasia. *Ann. Neurol.* **49**, 425–432 (2001).

8.   R. Chapey, *et al.*, Life Participation Approach to Aphasia: A Statement of Values for the
Future. *ASHA Lead. Arch.* **5**, 4–6 (2000).

9.   S. Aliko, B. Wang, S. L. Small, J. I. Skipper, The entire brain, more or less, is at work:
'Language regions' are artefacts of averaging. [Preprint] (2023). Available at:
https://www.biorxiv.org/content/10.1101/2023.09.01.555886v2 [Accessed 8 September
2024].

10. E. Fedorenko, A. A. Ivanova, T. I. Regev, The language network as a natural kind within
the broader landscape of the human brain. *Nat. Rev. Neurosci.* **25**, 289–312 (2024).

11. E. Fedorenko, N. Kanwisher, Neuroimaging of Language: Why Hasn't a Clearer Picture
Emerged? *Lang. Linguist. Compass* **3**, 839–865 (2009).

12. A. D. Friederici, *Language in Our Brain* (MIT Press, 2017).

13. N. Geschwind, The Organization of Language and the Brain. *Science* **170**, 940–944
(1970).

14. Y. Grodzinsky, The Picture of the Linguistic Brain: How Sharp Can It Be? Reply to
Fedorenko & Kanwisher. *Lang. Linguist. Compass* **4**, 605–622 (2010).

15. P. Hagoort, On Broca, brain, and binding: a new framework. *Trends Cogn. Sci.* **9**, 416–
423 (2005).

16. P. Hagoort, The meaning-making mechanism(s) behind the eyes and between the ears.
Philos. Trans. R. Soc. B Biol. Sci. **375**, 20190301 (2019).

17. G. Hickok, The functional neuroanatomy of language. *Phys. Life Rev.* **6**, 121–143 (2009).

18. A. G. Huth, W. A. de Heer, T. L. Griffiths, F. E. Theunissen, J. L. Gallant, Natural speech
reveals the semantic maps that tile human cerebral cortex. *Nature* **532**, 453 (2016).

19. W. Matchin, G. Hickok, The Cortical Organization of Syntax. *Cereb. Cortex* **30**, 1481–
1498 (2020).

20. C. Pallier, A.-D. Devauchelle, S. Dehaene, Cortical representation of the constituent
structure of sentences. *Proc. Natl. Acad. Sci.* **108**, 2522–2527 (2011).

21. P. Tremblay, A. S. Dick, Broca and Wernicke are dead, or moving past the classic model
of language neurobiology. *Brain Lang.* **162**, 60–71 (2016).

22. S. J. Forkel, P. Hagoort, Redefining language networks: connectivity beyond localised
regions. *Brain Struct. Funct.* **229**, 2073–2078 (2024).

23. N. Bourguignon, S. L. Bue, An emergentist account of language in the brain – seeking
neural synergies behind human uniqueness. [Preprint] (2024). Available at:
https://osf.io/36s9m [Accessed 3 November 2024].

24. E. Fedorenko, S. T. Piantadosi, E. A. F. Gibson, Language is primarily a tool for
communication rather than thought. *Nature* **630**, 575–586 (2024).

25. W. T. Fitch, M. D. Martins, Hierarchical processing in music, language, and action:
Lashley revisited. *Ann. N. Y. Acad. Sci.* **1316**, 87–104 (2014).

26. J. A. Fodor, *Modularity of Mind* (MIT Press, 1983).

27. J. L. McClelland, M. St. John, R. Taraban, Sentence comprehension: A parallel
distributed processing approach. *Lang. Cogn. Process.* **4**, SI287–SI335 (1989).

28. M. Tomasello, *Constructing a language: A usage-based theory of language acquisition*
(Harvard University Press, 2003).

29. R. Levy, Expectation-based syntactic comprehension. *Cognition* **106**, 1126–1177 (2008).

30. N. D. Goodman, M. C. Frank, Pragmatic Language Interpretation as Probabilistic
Inference. *Trends Cogn. Sci.* **20**, 818–829 (2016).

31. E. Fedorenko, P.-J. Hsieh, A. Nieto-Castañón, S. Whitfield-Gabrieli, N. Kanwisher, New
method for fMRI investigations of language: defining ROIs functionally in individual
subjects. *J. Neurophysiol.* **104**, 1177–1194 (2010).

32. W. Matchin, Lexico-semantics obscures lexical syntax. *Front. Lang. Sci.* **2** (2023).

33. W. W. Graves, *et al.*, An inclusive multivariate approach to neural localization of language
components. *Brain Struct. Funct.* **229**, 1243–1263 (2024).

34. T. I. Regev, *et al.*, High-level language brain regions process sublexical regularities.
Cereb. Cortex **34**, bhae077 (2024).

35. M. A. Frost, R. Goebel, Measuring structural–functional correspondence: Spatial
variability of specialised brain regions after macro-anatomical alignment. *NeuroImage* **59**,

1369–1381 (2012).

36.   K. Mahowald, E. Fedorenko, Reliable individual-level neural markers of high-level
899   language processing: A necessary precursor for relating neural variability to behavioral
900   and genetic variability. *NeuroImage* **139**, 74–93 (2016).

901   37.   S. Mueller, *et al.*, Individual Variability in Functional Connectivity Architecture of the
902   Human Brain. *Neuron* **77**, 586–595 (2013).

903   38.   B. Vázquez-Rodríguez, *et al.*, Gradients of structure–function tethering across neocortex.
904   *Proc. Natl. Acad. Sci.* **116**, 21219–21227 (2019).

905   39.   S. E. Petersen, P. T. Fox, M. I. Posner, M. Mintun, M. E. Raichle, Positron emission
906   tomographic studies of the cortical anatomy of single-word processing. *Nature* **331**, 585–
907   589 (1988).

908   40.   C. J. Price, A review and synthesis of the first 20 years of PET and fMRI studies of heard
909   speech, spoken language and reading. *NeuroImage* **62**, 816–847 (2012).

910   41.   T. L. Scott, J. Gallée, E. Fedorenko, A new fun and robust version of an fMRI localizer for
911   the frontotemporal language system. *Cogn. Neurosci.* **8**, 167–176 (2017).

912   42.   J. J. Lee, T. L. Scott, T. K. Perrachione, Efficient functional localization of language
913   regions in the brain. *NeuroImage* **285**, 120489 (2024).

914   43.   K. Elin, *et al.*, A New Functional Magnetic Resonance Imaging Localizer for Preoperative
915   Language Mapping Using a Sentence Completion Task: Validity, Choice of Baseline
916   Condition, and Test–Retest Reliability. *Front. Hum. Neurosci.* **16** (2022).

917   44.   O. A. Olulade, *et al.*, The neural basis of language development: Changes in lateralization
918   over age. *Proc. Natl. Acad. Sci.* **117**, 23477–23483 (2020).

919   45.   T. van Kerkoerle, *et al.*, Brain mechanisms of reversible symbolic reference: a potential
920   singularity of the human brain. [Preprint] (2023). Available at:
921   https://www.biorxiv.org/content/10.1101/2023.03.04.531109v1 [Accessed 5 May 2023].

922   46.   B. B. Biswal, *et al.*, Toward discovery science of human brain function. *Proc. Natl. Acad.*
923   *Sci.* **107**, 4734–4739 (2010).

924   47.   B. Biswal, F. Zerrin Yetkin, V. M. Haughton, J. S. Hyde, Functional connectivity in the
925   motor cortex of resting human brain using echo-planar mri. *Magn. Reson. Med.* **34**, 537–
926   541 (1995).

927   48.   M. D. Fox, M. E. Raichle, Spontaneous fluctuations in brain activity observed with
928   functional magnetic resonance imaging. *Nat. Rev. Neurosci.* **8**, 700–711 (2007).

929   49.   B. T. Thomas Yeo, *et al.*, The organization of the human cerebral cortex estimated by
930   intrinsic functional connectivity. *J. Neurophysiol.* **106**, 1125–1165 (2011).

931   50.   K. J. Friston, C. D. Frith, P. F. Liddle, R. S. J. Frackowiak, Functional Connectivity: The
932   Principal-Component Analysis of Large (PET) Data Sets. *J. Cereb. Blood Flow Metab.*

933   (1993). https://doi.org/10.1038/jcbfm.1993.4.

934   51.   J. D. Power, *et al.*, Functional Network Organization of the Human Brain. *Neuron* **72**,
935   665–678 (2011).

936   52.   G. Doucet, *et al.*, Brain activity at rest: a multiscale hierarchical functional organization. *J.*
937   *Neurophysiol.* **105**, 2753–2763 (2011).

938   53.   A. Schaefer, *et al.*, Local-Global Parcellation of the Human Cerebral Cortex from Intrinsic
939   Functional Connectivity MRI. *Cereb. Cortex* **28**, 3095–3114 (2018).

940   54.   M. F. Glasser, *et al.*, A multi-modal parcellation of human cerebral cortex. *Nature* **536**,
941   171–178 (2016).

942   55.   E. M. Gordon, *et al.*, Precision Functional Mapping of Individual Human Brains. *Neuron*
943   **95**, 791-807.e7 (2017).

944   56.   C. Gratton, *et al.*, Defining Individual-Specific Functional Neuroanatomy for Precision
945   Psychiatry. *Biol. Psychiatry* **88**, 28–39 (2020).

946   57.   C. J. Lynch, *et al.*, Rapid Precision Functional Mapping of Individuals Using Multi-Echo
947   fMRI. *Cell Rep.* **33**, 108540 (2020).

948   58.   R. J. M. Hermosillo, *et al.*, A precision functional atlas of personalized network
949   topography and probabilities. *Nat. Neurosci.* **27**, 1000–1013 (2024).

950   59.   L. A. Moore, *et al.*, Towards personalized precision functional mapping in infancy.
951   *Imaging Neurosci.* **2**, 1–20 (2024).

952   60.   Z. Cui, *et al.*, Linking Individual Differences in Personalized Functional Network
953   Topography to Psychopathology in Youth. *Biol. Psychiatry* **92**, 973–983 (2022).

954   61.   A. K. Labonte, *et al.*, Precision Functional Mapping to Advance Developmental Psychiatry
955   Research. *Biol. Psychiatry Glob. Open Sci.* **4**, 100370 (2024).

956   62.   S. H. Siddiqi, *et al.*, Precision functional MRI mapping reveals distinct connectivity
957   patterns for depression associated with traumatic brain injury. *Sci. Transl. Med.* **15**,
958   eabn0441 (2023).

959   63.   C. M. Sylvester, *et al.*, Individual-specific functional connectivity of the amygdala: A
960   substrate for precision psychiatry. *Proc. Natl. Acad. Sci.* **117**, 3808–3818 (2020).

961   64.   R. M. Braga, L. M. DiNicola, H. C. Becker, R. L. Buckner, Situating the left-lateralized
962   language network in the broader organization of multiple specialized large-scale
963   distributed networks. *J. Neurophysiol.* **124**, 1415–1448 (2020).

964   65.   J. Du, *et al.*, Organization of the human cerebral cortex estimated within individuals:
965   networks, global topography, and function. *J. Neurophysiol.* **131**, 1014–1082 (2024).

966   66.   J. Du, *et al.*, Within-Individual Precision Mapping of Brain Networks Exclusively Using
967   Task Data. *Neuron* **113**, 4069-4083.e6 (2025).

67. J. J. Salvo, N. L. Anderson, R. M. Braga, Intrinsic functional connectivity delineates
transmodal language functions. [Preprint] (2024). Available at:
https://www.biorxiv.org/content/10.1101/2024.12.20.629770v1 [Accessed 2 March 2025].

68. E. S. Finn, Is it time to put rest to rest? *Trends Cogn. Sci.* **25**, 1021–1032 (2021).

69. R. L. Buckner, J. L. Vincent, Unrest at rest: Default activity and spontaneous network
correlations. *NeuroImage* **37**, 1091–1096 (2007).

70. A. M. Morcom, P. C. Fletcher, Does the brain have a baseline? Why we should be
resisting a rest. *NeuroImage* **37**, 1073–1082 (2007).

71. E. S. Finn, *et al.*, Functional connectome fingerprinting: identifying individuals using
patterns of brain connectivity. *Nat. Neurosci.* **18**, 1664–1671 (2015).

72. C. Gratton, *et al.*, Functional Brain Networks Are Dominated by Stable Group and
Individual Factors, Not Cognitive or Daily Variation. *Neuron* **98**, 439-452.e5 (2018).

73. F. M. Krienen, B. T. T. Yeo, R. L. Buckner, Reconfigurable task-dependent functional
coupling modes cluster around a core functional architecture. *Philos. Trans. R. Soc. B
Biol. Sci.* **369**, 20130526 (2014).

74. I. Blank, N. Kanwisher, E. Fedorenko, A functional dissociation between language and
multiple-demand systems revealed in patterns of BOLD signal fluctuations. *J.
Neurophysiol.* **112**, 1105–1118 (2014).

75. S. Malik-Moraleda, *et al.*, An investigation across 45 languages and 12 language families
reveals a universal language network. *Nat. Neurosci.* **25**, 1014–1019 (2022).

76. D. A. Fair, *et al.*, A method for using blocked and event-related fMRI data to study "resting
state" functional connectivity. *NeuroImage* **35**, 396–405 (2007).

77. R. L. Buckner, F. M. Krienen, B. T. T. Yeo, Opportunities and limitations of intrinsic
functional connectivity MRI. *Nat. Neurosci.* **16**, 832–837 (2013).

78. D. F. Crouse, On implementing 2D rectangular assignment algorithms. *IEEE Trans.
Aerosp. Electron. Syst.* **52**, 1679–1696 (2016).

79. B. Lipkin, *et al.*, Probabilistic atlas for the language network based on precision fMRI data
from >800 individuals. *Sci. Data* **9**, 529 (2022).

80. C. Shain, A. Paunov, X. Chen, B. Lipkin, E. Fedorenko, No evidence of theory of mind
reasoning in the human language network. *Cereb. Cortex* **33**, 6299–6319 (2023).

81. B. Deen, K. Koldewyn, N. Kanwisher, R. Saxe, Functional organization of social
perception and cognition in the superior temporal sulcus. *Cereb. Cortex* **25**, 4596–4609
(2015).

82. L. R. Chai, M. G. Mattar, I. A. Blank, E. Fedorenko, D. S. Bassett, Functional Network
Dynamics of the Language System. *Cereb. Cortex* **26**, 4148–4159 (2016).

83. K. C. Martin, *et al.*, A Weak Shadow of Early Life Language Processing Persists in the

Right Hemisphere of the Mature Brain. *Neurobiol. Lang. Camb. Mass* **3**, 364–385 (2022).

84. C. Shain, I. A. Blank, M. van Schijndel, W. Schuler, E. Fedorenko, fMRI reveals
language-specific predictive coding during naturalistic sentence comprehension.
Neuropsychologia **138** (2020).

85. C. Wernicke, "The Symptom Complex of Aphasia" in *Proceedings of the Boston*
Colloquium for the Philosophy of Science 1966/1968, Boston Studies in the Philosophy of
Science., R. S. Cohen, M. W. Wartofsky, Eds. (Springer Netherlands, 1969), pp. 34–97.

86. N. Geschwind, W. Levitsky, Human Brain: Left-Right Asymmetries in Temporal Speech
Region. *Science* **161**, 186–187 (1968).

87. T. Rasmussen, B. Milner, The role of early left-brain injury in determining lateralization of
cerebral speech functions. *Ann. N. Y. Acad. Sci.* **299**, 355–369 (1977).

88. R. Rajimehr, A. Firoozi, H. Rafipoor, N. Abbasi, J. Duncan, Complementary hemispheric
lateralization of language and social processing in the human brain. (2021).
https://doi.org/10.21203/rs.3.rs-808005/v1.

89. A. M. Galaburda, Human Brain: Cytoarchitectonic Left-Right Asymmetries in the
Temporal Speech Region. *Arch. Neurol.* **35**, 812 (1978).

90. A. R. Bradshaw, Z. V. J. Woodhead, P. A. Thompson, D. V. M. Bishop, Investigation into
inconsistent lateralisation of language functions as a potential risk factor for language
impairment. *Eur. J. Neurosci.* **51**, 1106–1121 (2020).

91. S. M. Wilson, *et al.*, Recovery from aphasia in the first year after stroke. *Brain* **146**, 1021–
1039 (2023).

92. M. L. Seghier, Laterality index in functional MRI: methodological issues. *Magn. Reson.*
Imaging **26**, 594–601 (2008).

93. J. Duncan, The multiple-demand (MD) system of the primate brain: Mental programs for
intelligent behaviour. *Trends Cogn. Sci.* **14**, 172–179 (2010).

94. J. Duncan, M. Assem, S. Shashidhara, Integrated intelligence from distributed brain
activity. *Trends Cogn. Sci.* (2020).

95. R. Saxe, N. Kanwisher, People thinking about thinking people: The role of the temporo-
parietal junction in "theory of mind." *NeuroImage* **19**, 1835–1842 (2003).

96. T. Overath, J. H. McDermott, J. M. Zarate, D. Poeppel, The cortical analysis of speech-
specific temporal structure revealed by responses to sound quilts. *Nat. Neurosci.* **18**,
903–911 (2015).

97. S. Norman-Haignere, N. G. Kanwisher, J. H. McDermott, Distinct Cortical Pathways for
Music and Speech Revealed by Hypothesis-Free Voxel Decomposition. *Neuron* **88**,
1281–1296 (2015).

98. E. Fedorenko, J. Duncan, N. Kanwisher, Broad domain generality in focal regions of

frontal and parietal cortex. *Proc. Natl. Acad. Sci.* **110**, 16616–16621 (2013).

99.   R. Saxe, L. J. Powell, It's the Thought That Counts: Specific Brain Regions for One
1042   Component of Theory of Mind. *Psychol. Sci.* **17**, 692–699 (2006).

1043   100.   R. L. Buckner, L. M. DiNicola, The brain's default network: updated anatomy, physiology
1044   and evolving insights. *Nat. Rev. Neurosci.* **20**, 593–608 (2019).

1045   101.   A. M. Paunov, *et al.*, Differential Tracking of Linguistic vs. Mental State Content in
1046   Naturalistic Stimuli by Language and Theory of Mind (ToM) Brain Networks. *Neurobiol.*
1047   *Lang.* **3**, 413–440 (2022).

1048   102.   C. Shain, *et al.*, Distributed Sensitivity to Syntax and Semantics throughout the Language
1049   Network. *J. Cogn. Neurosci.* 1–43 (2024). https://doi.org/10.1162/jocn_a_02164.

1050   103.   E. Fedorenko, I. A. Blank, Broca's Area Is Not a Natural Kind. *Trends Cogn. Sci.* **24**, 270–
1051   284 (2020).

1052   104.   R. Kong, *et al.*, Spatial Topography of Individual-Specific Cortical Networks Predicts
1053   Human Cognition, Personality, and Emotion. *Cereb. Cortex* **29**, 2533–2551 (2019).

1054   105.   R. Kong, *et al.*, Individual-Specific Areal-Level Parcellations Improve Functional
1055   Connectivity Prediction of Behavior. *Cereb. Cortex* **31**, 4477–4500 (2021).

1056   106.   G. Hickok, D. Poeppel, The cortical organization of speech processing. *Nat. Rev.*
1057   *Neurosci.* **8**, 393–402 (2007).

1058   107.   I. Bornkessel-Schlesewsky, M. Schlesewsky, Reconciling time, space and function: A
1059   new dorsal–ventral stream model of sentence comprehension. *Brain Lang.* **125**, 60–76
1060   (2013).

1061   108.   S. M. Frankland, J. D. Greene, An architecture for encoding sentence meaning in left mid-
1062   superior temporal cortex. *Proc. Natl. Acad. Sci.* **112**, 11732–11737 (2015).

1063   109.   J. Brennan, L. Pylkkänen, The time-course and spatial distribution of brain activity
1064   associated with sentence processing. *NeuroImage* 1–10 (2012).
1065   https://doi.org/10.1016/j.neuroimage.2012.01.030.

1066   110.   D. K. Bemis, L. Pylkkänen, Simple composition: a magnetoencephalography investigation
1067   into the comprehension of minimal linguistic phrases. *J. Neurosci. Off. J. Soc. Neurosci.*
1068   **31**, 2801–2814 (2011).

1069   111.   B. Mazoyer, *et al.*, Gaussian Mixture Modeling of Hemispheric Lateralization for
1070   Language in a Large Sample of Healthy Individuals Balanced for Handedness. *PLOS*
1071   *ONE* **9**, e101165 (2014).

1072   112.   A. Wolna, *et al.*, The extended language network: Language-responsive brain areas
1073   whose contributions to language remain to be discovered. [Preprint] (2025). Available at:
1074   https://www.biorxiv.org/content/10.1101/2025.04.02.646835v3 [Accessed 4 February
1075   2026].

113. C. Casto, *et al.*, The cerebellar components of the human language network. *Neuron*
(2026). https://doi.org/10.1016/j.neuron.2025.12.030.

114. A. LeBel, A. M. D'Mello, A seat at the (language) table: incorporating the cerebellum into
frameworks for language processing. *Curr. Opin. Behav. Sci.* **53**, 101310 (2023).

115. A. A. Ivanova, *et al.*, Comprehension of computer code relies primarily on domain-general
executive brain regions. *eLife* **9**, e58906 (2020).

116. X. Chen, *et al.*, The human language system, including its inferior frontal component in
"Broca's area," does not support music perception. *Cereb. Cortex* **33**, 7904–7929.

117. E. Fedorenko, M. K. Behr, N. Kanwisher, Functional specificity for high-level linguistic
processing in the human brain. *Proc. Natl. Acad. Sci.* (2011).

118. M. E. Raichle, *et al.*, A default mode of brain function. *Proc. Natl. Acad. Sci.* **98**, 676–682
(2001).

119. A. A. Ivanova, *et al.*, The Language Network Is Recruited but Not Required for Nonverbal
Event Semantics. *Neurobiol. Lang.* **2**, 176–201 (2021).

120. Y. Sueoka, *et al.*, The Language Network Reliably "Tracks" Naturalistic Meaningful
Nonverbal Stimuli. *Neurobiol. Lang.* **5**, 385–408 (2024).

121. I. Blank, Z. Balewski, K. Mahowald, E. Fedorenko, Syntactic processing is distributed
across the language system. *NeuroImage* **127**, 307–323 (2016).

122. I. A. Blank, E. Fedorenko, No evidence for differences among language regions in their
temporal receptive windows. *NeuroImage* **219**, 116925 (2020).

123. E. Fedorenko, I. A. Blank, M. Siegelman, Z. Mineroff, Lack of selectivity for syntax relative
to word meanings throughout the language network. *Cognition* **203**, 104348 (2020).

124. M. K. Leonard, *et al.*, Large-scale single-neuron speech sound encoding across the depth
of human cortex. *Nature* **626**, 593–602 (2024).

125. T. I. Regev, *et al.*, Neural populations in the language network differ in the size of their
temporal receptive windows. *Nat. Hum. Behav.* **8**, 1924–1942 (2024).

126. L. Gwilliams, J.-R. King, A. Marantz, D. Poeppel, Neural dynamics of phoneme
sequences reveal position-invariant code for content and order. *Nat. Commun.* **13**, 6606
(2022).

127. A. Samara, J. Eilbott, D. S. Margulies, T. Xu, T. Vanderwal, Cortical gradients during
naturalistic processing are hierarchical and modality-specific. *NeuroImage* **271**, 120023
(2023).

128. C. Caucheteux, A. Gramfort, J.-R. King, Disentangling syntax and semantics in the brain
with deep networks in *Proceedings of the 38th International Conference on Machine
Learning*, (PMLR, 2021), pp. 1336–1348.

129. R. Gao, A. A. Ivanova, funROI: A Python package for functional ROI analyses of fMRI

data. *figshare* (2025). Available at:
https://figshare.com/articles/code/funROI_A_Python_package_for_functional_ROI_analys
es_of_fMRI_data/28120967/1 [Accessed 22 March 2025].

130. A. Nieto-Castañón, E. Fedorenko, Subject-specific functional localizers increase
sensitivity and functional resolution of multi-subject analyses. *NeuroImage* **63**, 1646–1669
(2012).

131. C. F. A. Benjamin, *et al.*, Presurgical language fMRI: Clinical practices and patient
outcomes in epilepsy surgical planning. *Hum. Brain Mapp.* **39**, 2777–2785 (2018).

132. E. Diachek, V. L. Morgan, S. M. Wilson, Adaptive Language Mapping Paradigms for
Presurgical Language Mapping. *Am. J. Neuroradiol.* (2022).
https://doi.org/10.3174/ajnr.A7629.

133. M. Karami, *et al.*, Presurgical Language Mapping in Patients With Intractable Epilepsy: A
Review Study. *Basic Clin. Neurosci.* **12**, 163–176 (2021).

134. R. Kreidenhuber, X. De Tiège, S. Rampp, Presurgical Functional Cortical Mapping Using
Electromagnetic Source Imaging. *Front. Neurol.* **10** (2019).

135. F. R. Willett, *et al.*, A high-performance speech neuroprosthesis. *Nature* **620**, 1031–1036
(2023).

136. N. S. Card, *et al.*, An Accurate and Rapidly Calibrating Speech Neuroprosthesis. *N. Engl.*
J. Med. **391**, 609–618 (2024).

137. A. B. Silva, *et al.*, A bilingual speech neuroprosthesis driven by cortical articulatory
representations shared between languages. *Nat. Biomed. Eng.* 1–15 (2024).
https://doi.org/10.1038/s41551-024-01207-5.

138. R. Hermosillo, *et al.*, Convergence of individualized functional neural networks and
structural connectivity in subdural prefrontal cortical stimulation. *Brain Stimul. Basic*
Transl. Clin. Res. Neuromodulation **18**, 422 (2025).

139. P. Jain, A. Chakraborty, R. Hafiz, A. K. Sao, B. Biswal, Enhancing the network specific
individual characteristics in rs-fMRI functional connectivity by dictionary learning. *Hum.*
Brain Mapp. **44**, 3410–3432 (2023).

140. Z. Luo, *et al.*, Frequency-specific segregation and integration of human cerebral cortex:
An intrinsic functional atlas. *iScience* **27** (2024).

141. W. Qiu, L. Ma, T. Jiang, Y. Zhang, Unrevealing Reliable Cortical Parcellation of Individual
Brains Using Resting-State Functional Magnetic Resonance Imaging and Masked Graph
Convolutions. *Front. Neurosci.* **16** (2022).

142. E. A. Allen, *et al.*, Tracking Whole-Brain Connectivity Dynamics in the Resting State.
Cereb. Cortex N. Y. NY **24**, 663–676 (2014).

143. M. W. Cole, T. Ito, C. Cocuzza, R. Sanchez-Romero, The Functional Relevance of Task-
State Functional Connectivity. *J. Neurosci.* **41**, 2684–2702 (2021).

144.   J. Gonzalez-Castillo, P. A. Bandettini, Task-based dynamic functional connectivity:
Recent findings and open questions. *NeuroImage* **180**, 526–533 (2018).

145.   S. Heitmann, M. Breakspear, Putting the "dynamic" back into dynamic functional
connectivity. *Netw. Neurosci.* **02**, 150–174 (2018).

146.   R. Hindriks, *et al.*, Can sliding-window correlations reveal dynamic functional connectivity
in resting-state fMRI? *NeuroImage* **127**, 242–256 (2016).

147.   R. M. Hutchison, *et al.*, Dynamic functional connectivity: Promise, issues, and
interpretations. *NeuroImage* **80**, 360–378 (2013).

148.   N. Leonardi, D. Van De Ville, On spurious and real fluctuations of dynamic functional
connectivity during rest. *NeuroImage* **104**, 430–436 (2015).

149.   D. J. Lurie, *et al.*, Questions and controversies in the study of time-varying functional
connectivity in resting fMRI. *Netw. Neurosci.* **4**, 30–69 (2020).

150.   A. T. Phan, W. Xie, J. I. Chapeton, S. K. Inati, K. A. Zaghloul, Dynamic patterns of
functional connectivity in the human brain underlie individual memory formation. *Nat.*
Commun. **15**, 8969 (2024).

151.   M. Salehi, *et al.*, There is no single functional atlas even for a single individual: Functional
parcel definitions change with task. *NeuroImage* **208**, 116366 (2020).

152.   J. M. Shine, *et al.*, The Dynamics of Functional Brain Networks: Integrated Network
States during Cognitive Task Performance. *Neuron* **92**, 544–554 (2016).

153.   S. Anzellotti, M. N. Coutanche, Beyond Functional Connectivity: Investigating Networks of
Multivariate Representations. *Trends Cogn. Sci.* **22**, 258–269 (2018).

154.   K. Yoo, *et al.*, Multivariate approaches improve the reliability and validity of functional
connectivity and prediction of individual behaviors. *NeuroImage* **197**, 212–223 (2019).

155.   P. A. Valdés-Sosa, *et al.*, Estimating brain functional connectivity with sparse multivariate
autoregression. *Philos. Trans. R. Soc. B Biol. Sci.* **360**, 969–981 (2005).

156.   A. Basti, H. Nili, O. Hauk, L. Marzetti, R. N. Henson, Multi-dimensional connectivity: a
conceptual and mathematical review. *NeuroImage* **221**, 117179 (2020).

157.   Karl. J. Friston, *et al.*, Spatial registration and normalization of images. *Hum. Brain Mapp.*
3, 165–189 (1995).

158.   A. Nieto-Castanon, *Handbook of functional connectivity Magnetic Resonance Imaging*
methods in CONN (Hilbert Press, 2020).

159.   J. Ashburner, K. J. Friston, Unified segmentation. *NeuroImage* **26**, 839–851 (2005).

160.   N. Jacoby, E. Bruneau, J. Koster-Hale, R. Saxe, Localizing Pain Matrix and Theory of
Mind networks with both verbal and non-verbal stimuli. *NeuroImage* **126**, 39–48 (2016).

161.   D. Pitcher, D. D. Dilks, R. R. Saxe, C. Triantafyllou, N. Kanwisher, Differential selectivity

for dynamic versus static information in face-selective cortical regions. *NeuroImage* **56**, 2356–2363 (2011).

162. Nilearn contributors, nilearn. https://doi.org/10.5281/zenodo.8397156.

163. F. Pedregosa, *et al.*, Scikit-learn: Machine Learning in Python. *Mach. Learn. PYTHON*.

164. D. S. Bassett, *et al.*, Task-Based Core-Periphery Organization of Human Brain Dynamics. *PLOS Comput. Biol.* **9**, e1003171 (2013).

165. Y. Hong, On computing the distribution function for the Poisson binomial distribution. *Comput. Stat. Data Anal.* **59**, 41–51 (2013).

166. B. Alderson-Day, C. Fernyhough, Inner speech: Development, cognitive functions, phenomenology, and neurobiology. *Psychol. Bull.* **141**, 931–965 (2015).

167. C. Fernyhough, A. M. Borghi, Inner speech as language process and cognitive tool. *Trends Cogn. Sci.* **27**, 1180–1193 (2023).

168. A. Morin, B. Uttl, B. Hamper, Self-Reported Frequency, Content, and Functions of Inner Speech. *Procedia - Soc. Behav. Sci.* **30**, 1714–1718 (2011).

169. E. M. Gordon, T. O. Laumann, B. Adeyemo, S. E. Petersen, Individual Variability of the System-Level Organization of the Human Brain. *Cereb. Cortex* **27**, 386–399 (2017).

170. J. M. Teo, *et al.*, Probabilistic template matching for detecting resting-state functional MRI language network in brain tumor patients. *Med. Phys.* **52**, e70138 (2025).

171. A. Dworetsky, *et al.*, Probabilistic mapping of human functional brain networks identifies regions of high group consensus. *NeuroImage* **237**, 118164 (2021).

172. J. Tuominen, K. Specht, L. Vaisvilaite, P. Zeidman, An information-theoretic analysis of resting-state versus task fMRI. *Netw. Neurosci.* **7**, 769–786 (2023).