TRUHiC: A TRansformer-embedded U-2 Net to enhance Hi-C data for 3D chromatin structure characterization

Chong Li[1,2*], Mohammad Erfan Mowlaei[1,2*], Human Genome Structural Variation Consortium (HGSVC), HGSVC Functional Analysis Working Group, Vincenzo Carnevale[2,3], Sudhir Kumar[1,2,4], Xinghua Shi[1,2#]

[1]Department of Computer and Information Sciences, College of Science and Technology, Temple University, Philadelphia, PA, US

[2]Institute for Genomics and Evolutionary Medicine, Temple University 1925 N. 12th Street, 19122, PA, USA

[3]Institute for Computational Molecular Science, Temple University 1925 N. 12th Street, 19122, PA, USA

[4]Department of Biology, College of Science and Technology, Temple University, Philadelphia, PA, USA.

Abstract:

High-throughput chromosome conformation capture sequencing (Hi-C) is a key technology for studying the three-dimensional (3D) structure of genomes and chromatin folding. Hi-C data reveals important patterns of genome organization such as topologically associating domains (TADs) and chromatin loops with critical roles in transcriptional regulation and disease etiology and progression. However, the relatively low resolution of existing Hi-C data often hinders robust and reliable inference of 3D structures. Hence, we propose *TRUHiC*, a new computational method that leverages recent state-of-the-art deep generative modeling to augment low-resolution Hi-C data for the characterization of 3D chromatin structures. Applying *TRUHiC* to publically available Hi-C data for human and mice, we demonstrate that the augmented data significantly improves the characterization of TADs and loops across diverse cell lines and species. We further present a pre-trained *TRUHiC* on human lymphoblastoid cell lines that can be adaptable and transferable to improve chromatin characterization of various cell lines, tissues, and species.

Keywords: Hi-C, 3D genome, deep learning, transformer, super-resolution

---

*These authors contributed equally to this work
#Corresponding author(s). Email: mindyshi@temple.edu

1 Introduction

The technology of high-throughput chromosome conformation capture sequencing (Hi-C) has emerged as a pivotal approach for studying three-dimensional (3D) genome organization[1]. This technology builds upon the principles of chromatin conformation capture assay (3C) and enables researchers to explore the interactions of chromatin across the entire genome. The analysis of Hi-C data at desired resolutions would facilitate a comprehensive understanding of genome-wide chromatin structures, such as A/B compartments[1], topologically associating domains (TADs)[2] and chromatin loops[3], thereby shedding light on the essential functions of the 3D genome[2]. Nevertheless, biologically meaningful identification of fine-grained structural features, especially TADs and loops, necessitates higher resolution or read depth of Hi-C sequencing. Achieving this resolution demands costly high-coverage deep sequencing to ensure sufficient read depth for accurately capturing chromatin interaction frequencies[4]. Consequently, many existing Hi-C datasets present relatively low resolution, defined by larger genomic bins divided from the genome due to cost constraints limiting their utility in discerning finer chromatin structures[5,6]. This issue has prompted the development of computational methods for Hi-C data enhancement in an attempt to leverage existing low-resolution Hi-C data to infer corresponding high-resolution Hi-C data for various genomic downstream analyses.

The computational enhancement of Hi-C data shares conceptual similarities with the image super-resolution task in computer vision[7,8]. Hi-C sequencing reads are typically transformed into contact matrices that can be visualized as image-like heatmaps, suggesting a potential application of super-resolution techniques (Figure 1a). However, directly applying image-based super-resolution methods to Hi-C contact maps is less effective due to the unique structural properties of Hi-C contact matrices. Unlike natural images, Hi-C contact matrices are inherently symmetric around the diagonal and contain biologically meaningful constraints, such as sparsity in long-range interactions and high variability across genomic regions. The number of rows and columns in a Hi-C matrix corresponds to the length of the genome divided by the resolution (bin size, smaller bin size of fixed genomic intervals)[9]. Key 3D chromatin features such as TADs are visually represented as triangular regions with elevated signal intensity on the heat maps, and chromatin loops are depicted as concentrated focal points (Figure 1a)[10]. Thus, developing specialized Hi-C resolution enhancement methods that incorporate biological domain knowledge is essential for accurately reconstructing high-resolution Hi-C contact maps.

Various deep learning methods have been developed to address the resolution enhancement challenge, predominantly based on two architectures: convolutional

neural networks (CNNs) and generative adversarial networks (GANs), as well as their
variants. Existing CNN-based methods include *HiCPlus*[5], *HiCNN*[7] and *HiCNN2*[8], *SRHiC*[11],
and *DFHiC*[12], while current GAN-based methods contain *hicGAN*[6], *DeepHiC*[13], *HiCSR*[14],
VEHiCLE[15], and *EnHiC*[16], accompanied with an integrated CNN and GAN-based model
termed *HiCARN*[17]. These methods differ in terms of the loss function and model
architecture that led to varying performances. *HiCPlus* pioneered the use of CNN
architecture with mean squared error (MSE) loss, while *HiCNN* introduced a deeper
convolutional network. *hicGAN* was the first to incorporate a GAN framework to
generate high-resolution contact maps conditioned on low-resolution inputs. *HiCNN2*
proposed three customized CNN architectures, and *SRHiC* later combined ResNet[18] and
WDSR arrchitectures[19]. Subsequent models such as *DeepHiC* and *HiCSR* introduced
multiple loss components to improve performance. *VEHiCLE* employed a variational
autoencoder within a conditional GAN framework, while *EnHiC*[20] addressed the issue of
image artifacts through a novel decomposition and reconstruction block. *HiCARN*
employed a lightweight Cascading Residual Network (CARN)[21], and the latest method,
DFHiC, integrated peripheral genomic information through their implementation of
convolution layers. Beyond these, genome graph-based approaches have recently
emerged to infer genome sequences from Hi-C reads and generate more accurate Hi-C
contact matrices[22].
90
The aforementioned methods primarily adopt an image super-resolution approach,
where the Hi-C matrix is segmented, independently processed for resolution
enhancement, and then reassembled. However, this approach does not fully account for
the biological significance of Hi-C contact matrices, where interaction intensities are
inherently tied to the hierarchical nature of 3D chromatin organization. Existing methods
rely heavily on convolutional layers. Convolution layers can effectively model local
patterns but fall short in capturing long-range chromatin interactions and global
structural context. As a result, enhanced contact maps often lack structural coherence
and biological fidelity. These limitations underscore the need for new approaches
capable of integrating both local and global dependencies. Transformer-based
approaches have achieved major breakthroughs in computer vision and natural
language processing. However, the quadratic computational cost of the attention
mechanism makes it prohibitive to apply it directly to image-like inputs with thousands
of features. A solution is to use CNNs to capture local patterns and reduce the
dimensionality of the input before using transformer blocks[23]. Based on these
principles, we propose a novel Hi-C data resolution enhancement approach (*TRUHiC*)
that integrates a customized and lightweight CNN-based U-2 Net architecture
empowered by a transformer block. This hybrid architecture leverages the strengths of
both convolutional and attention-based mechanisms. The U-2 Net's deeply nested
structure is well-suited for capturing fine-grained, multi-scale local features in contact

maps while maintaining a low computational overhead, an important consideration for high-throughput genomic data. At the same time, the transformer block enables the model to effectively capture long-range dependencies and complex interaction patterns, which are essential for reconstructing 3D genome organization. To the best of our knowledge, this is one of the first methods[24] to harness the transformer's attention mechanism for capturing global chromatin interaction patterns from low-resolution Hi-C contact matrices. Understanding these interactions at a finer scale is crucial for improving 3D genome reconstruction and enabling more accurate downstream biological interpretations. We demonstrate that our method outperforms state-of-the-art techniques in both contact map generation and chromatin structure identification, as evidenced by superior evaluation scores across multiple experiments.

Furthermore, existing models, which are typically trained on artificially low-resolution datasets, often experience a dramatic drop in performance when applied to biological replications. To overcome this limitation[25], we propose *TRUHiC-LCL, a* cell-line-specific *(CLS)* model for lymphoblastoid cell lines (LCLs) trained on a large real LCL-specific Hi-C dataset (n=43). This approach addresses limitations in existing methods by mitigating biases that arise from training on limited and artificial low-resolution datasets and providing a genome-wide representation of chromatin interactions. As a result, the model improves adaptability to real-world applications and enhances chromatin structure inference. To promote accessibility and further advance Hi-C data analysis, we have released both TRUHiC and TRUHiC-LCL as open-source frameworks, which surpass existing methods and enable broader applications in 3D genome research.

2 Results

2.1 Super-resolution reconstruction of Hi-C contact maps from downsampled low-resolution Hi-C data

TRUHiC takes low-resolution Hi-C contact maps as the input and attempts to augment their resolution. The architecture of *TRUHiC* (see Figure 5) is based on the U-2 Net, and we equipped it with a transformer block to enable the resulting models to capture both short- and long-range interactions among the genomic regions and make context-aware predictions. We use low-resolution contact maps as the input and train the model in a supervised manner to predict the respective high-resolution contact maps. Also, we leverage mean absolute error (MAE) and signal-to-noise ratio (SNR) in our loss function with equal weights. To rigorously assess *TRUHiC*'s performance in reconstructing high-resolution Hi-C contact maps, we trained the model on chromosomes 1-17 of the GM12878 cell line and tested the resulting model on chromosomes 18-22 with a down-

sampled rate of 1/16 (see Methods for downsampling details). For a comprehensive
comparison with existing models, including *DFHiC*, *HiCNN2*, and *HiCARN*, we applied
identical data preprocessing to that of *TRUHiC* to ensure the exact same data input is
used to train and evaluate every method. Next, we saved each model for the
subsequent experiments in this subsection and subsections 2.2 and 2.4. To
comprehensively evaluate the quality of the enhanced Hi-C contact maps, we employed
multiple image quality assessment metrics that capture different aspects of
reconstruction fidelity (see Methods for details), including Peak Signal-to-Noise Ratio
(PSNR), Signal-to-Noise Ratio (SNR), Spearman correlation coefficient (SPC), Pearson
correlation coefficient (PCC), Structural Similarity Index Measure (SSIM), Mean
Squared Error (MSE), Jaccard Index (JI), F1 scores, and GenomeDISCO Scores
(GDS)[26]. These metrics were calculated to compare the enhanced low-resolution Hi-C
matrices generated by *TRUHiC* against the competing methods. As summarized in
Table 1, *TRUHiC* consistently outperforms the other enhancement methods across all
metrics in the test set.

All enhancement models, including *TRUHiC*, were trained on an 80GB A100 NVidia
GPU, and the training time and memory consumption for each model on the Hi-C
dataset with an input size of 40*40 are summarized in Supplementary Table S1.
TRUHiC demonstrates a balanced trade-off between computational speed and memory
efficiency compared to competing methods.*TRUHiC* does not require any additional
data normalization and denormalization and uses the raw data directly. In contrast,
DeepHiC and *HiCARN* need additional data normalization and denormalization
procedures, as they described in their papers. However, during experiments, we
observed that *DeepHiC* and *HiCARN* performed better on raw data. Therefore, all
competing models in this study were trained and evaluated on the raw Hi-C data to
ensure a fair comparison.
174

Cell line	Method	PSNR⬆	SNR⬆	SPC⬆	PCC⬆	GDS⬆	SSIM⬆	MSE⬇
GM12878	HiCNN2	25.1040	102.8193	0.6304	0.6890	0.9112	0.5452	226.2458
	HiCARN1	25.1686	102.7036	0.6388	0.6961	0.9106	0.5428	247.7091
	HiCARN2	25.4459	106.3763	0.6484	0.7039	0.9112	0.5410	269.0648
	DFHiC	26.0993	115.1918	0.6841	0.7315	0.9212	0.5663	193.4211
	TRUHiC	**26.2321**	**117.2548**	**0.6922**	**0.7381**	**0.9217**	**0.5777**	**177.3425**

175 **Table 1. Comparison of vision metrics results averaged across test chromosomes (18-22)**
176 **for each enhancement method.** The arrows in each column indicate whether a higher (⬆) or
177 lower (⬇) value is better, and the best score for each metric is bolded.
178
179
180 **2.2 Hi-C structural features reconstruction from downsampled low-resolution Hi-C**
181 **data**
182
To assess the effectiveness of *TRUHiC* in recognizing important 3D chromatin
structures, namely TADs and loops, we employed two widely used tools: *Insulation*
scores (IS)[27] and *HiCCUPs*[28]. *IS* is primarily developed to detect TAD boundaries, with
the regions between the two adjacent significant boundaries defined as TAD regions.
HiCCUPS identifies chromatin loops by detecting enriched pixels, where contact
frequencies within a pixel are compared to surrounding regions to determine significant
looping interactions. We applied these methods to both high-resolution (HR) Hi-C
datasets and enhanced contact maps generated by different models. To quantify the
consistency of TAD predictions, we calculated the Jaccard Index (JI) and F1 score
between the detected TAD boundaries in HR and enhanced datasets. The results for
chromosomes 18-22 in the GM12878 cell line are summarized in Figure 1b - d and
Table 2. The analysis reveals that *TRUHiC* consistently generates TAD boundaries with
higher similarity to the high-resolution dataset compared to the competing methods.
Unlike *HiCNN2* and *HiCARN*, *TRUHiC* does not overestimate the number of detected
TAD boundaries, maintaining consistency with the HR dataset and indicating its
effectiveness in preserving the integrity of chromatin structure.
199
200
201
202
203 a.

205   b.

206
207
208   c.   d.

209
Figure 1. The performance comparison of the *TRUHiC* and its competing methods. **a).** A
Hi-C contact map visualizing chromatin interactions, with TAD boundaries outlined in yellow and
chromatin loops marked with black circles. The hierarchical organization of chromatin
interactions is depicted, highlighting the structural features that contribute to genome
organization. A zoomed-in region of the Hi-C contact map displays a representative interaction
frequency (IF) matrix, where each value quantifies the frequency of interactions between
genomic loci. Higher IF values indicate stronger chromatin interactions. **b).** Visualization of the
result in the genomic region Chr 21: 44,560,001-45,550,000, where *TRUHiC* identified the most
consistent TAD boundary locations to the real high-resolution data, compared to the competing
methods. Yellow rectangles highlight TAD boundary locations detected in both the HR Hi-C
contact map and the enhanced maps, while dashed yellow rectangles indicate TAD boundary
locations present in the HR Hi-C contact map but missing in the enhanced maps. Black
rectangles indicate erroneously detected TAD boundaries that are absent in the HR Hi-C
contact map but appear in the enhanced maps. **c-d).** Comparison of the number of TAD
boundaries and sizes of TADs detected using *IS* on chromosome 21 of the GM12878 cell line

recovered by different methods for down-sampled low-resolution Hi-C data. The results for other
test chromosomes are presented in Supplementary Figures S1 and S2.
227
228
We applied *HiCCUPs* to the original HR Hi-C matrices, downsampled low-resolution
matrices, and enhanced-resolution matrices generated by *TRUHiC* and other competing
methods to identify chromatin loops. We aimed to recover a higher number of true
positive chromatin loops while maintaining structural integrity across test chromosomes.
The results, presented in Figure 2, illustrate the number of loops identified by *HiCCUPs*
for each method compared to the original loop calls in the HR matrices, with the
overlapping sections indicating shared loop interactions. Additional results for other
chromosomes can be found in Supplementary Figure S3. As expected, significantly
fewer reliable loops can be detected from the low-resolution Hi-C data. Notably,
TRUHiC outperformed competing methods across all test chromosomes by retaining
the highest ratio of recovered significant chromatin loops over identified spurious loops.
240

241
Figure 2. Comparison of chromatin loops detected on chromosome 20 of the GM12878
cell line. The numbers of chromatin loops are obtained by running *HiCCUPs* on the Hi-C data
recovered by different enhancement methods from down-sampled low-resolution Hi-C data.
Each blue circle represents the total number of loops detected in the high-resolution (HR) Hi-C
datasets, while the corresponding pink circle represents the loops identified on the HiC data
from the downsampled sample (Figure 2.a) and on the enhanced Hi-C data using each method
(Figures 2b-2f). The overlapping section indicates the intersections of blue and pink circles and
thus represents loops that are true positives resulting from each enhancement method. The
results for other cell lines are shown in Supplementary Figure S4.
251

We calculated the Jaccard Index (JI) and F1 score to assess the consistency of the
TAD boundary and loop calls. Specifically, the JI measures the similarity between two
sets by calculating the intersection ratio counting (at least one bp overlap) and the
union, using the following formula:

$$JI = \frac{length(intersection)}{length(Union) - length(Intersection)} .$$ (1)

For TAD boundaries, we considered two regions identical if they shared at least a one
base pair (bp) overlap. For loop calls, we defined two loops as matching if their
positions fell within the range of +/- 5 kb. The F1 score was computed as follows[29]:

$$F1\ score = \frac{TP}{TP + \frac{1}{2}(FP + FN)} ,$$ (2)

where we defined true positives (TP) as predicted loops that fall within the spatial range
of +/- 5 kb around the loops identified in the ground truth. False positives (FP) refer to
predicted loops that fall outside this flanking window. False negatives (FN) are ground-
truth loops that lack a corresponding predicted match within the same range. True
negatives were not considered in the calculation, as they represent the majority of the
genomic space and provide limited meaningful information.

We further evaluate the quality of loop calling for each method by calculating the
proportion of CCCTC-binding factor (CTCF) validate loop anchors (see Methods for
details). Prior studies have shown that the majority of loop anchor loci are bound by the
insulator protein CTCF, along with cohesin subunits RAD21 and SMC3[3]. Therefore, we
expect that our model will be able to predict a higher proportion of loop anchors that can
be validated as CTCF-supported loop anchors co-occurring with CTCF, RAD21, and
SMC3 ChIP-seq peaks. We applied this to the LR, *TRUHiC,* and other competing
methods and reported the validated loop ratio in Table 2. Note that the comparative JI
and F1 scores of the TAD boundary for LR align with the theoretical basis of the IS
algorithm, which was initially designed for detecting TAD features in low-resolution Hi-C
data. While IS demonstrates relative robustness across different data resolutions, our
method achieves discernible improvements across all aspects, further reinforcing its
effectiveness.

Cell line	Method	TAD boundary JI↑	TAD boundary F₁↑	Loop JI↑	Loop F₁↑	Validated loop anchor ratio (%)↑
	LR	0.2771	0.4262	0.1564	0.2740	70.8700
	HiCNN2	0.2796	0.4304	0.2538	0.4415	68.5920

GM12878	HiCARN1	0.2870	0.4388	0.2654	0.4515	68.2800
	HiCARN2	0.3015	0.4568	0.2617	0.4446	72.8980
	DFHiC	0.3324	0.4944	0.2775	0.4655	77.1280
	TRUHiC	**0.3479**	**0.5122**	**0.2992**	**0.4920**	**77.3360**

Table 2. Comparison of TAD boundaries and chromatin loops detected by different
models on test chromosomes (18-22) in GM12878 cell line. The number shows the average
value among the five test chromosomes. The arrows in each column indicate whether a higher
(⬆) or lower value (⬇) is better, and the best-performing score in each category is highlighted in
bold. Additionally, the higher validated loop anchor ratio in LR is attributed to the small number
of loops detected in the LR data, where the majority of the identified loops successfully passed
validation. The results for each test chromosome are summarized in Supplementary Tables S2-
S5.

During the experiments, we questioned the extent to which vision metrics correlate with
biologically meaningful feature metrics. While prior studies have reported visual metrics,
we did not find compelling discussions on why such metrics are specifically important
for the Hi-C enhancement task. Commonly used vision metrics such as SPC, PCC,
SNR, SSIM, and PSNR are widely employed for image quality assessment; however,
their direct relevance to biological features, such as chromatin loops and TADs, remains
unexplored. To investigate this, we computed R^2 scores between various visual metrics
and biological feature metrics we obtained from the above experiments to determine
which visual assessments best reflect biologically significant structures in Hi-C data
(Figure 3).

Our analysis revealed that PSNR, SNR, SPC, PCC, GDS, and SSIM exhibit strong
correlations with TAD boundary feature metrics (R^2 scores 0.85-0.88), suggesting that
these visual measures effectively benefit hierarchical chromatin organization
identification. Likewise, SSIM and GDS correlated well with loop-based metrics (R^2
scores 0.73-0.81), indicating their utility in evaluating fine-scale structural features. In
contrast, PSNR, SNR, SPC, and PCC showed only moderate correlations with loop-
based metrics (R^2 scores 0.53-0.71), whereas MSE showed no association with any
biological metrics (R^2 scores = 0.01), underscoring its limitations in assessing structural
fidelity. These findings underscore the importance of selecting biologically relevant
evaluation metrics when developing and benchmarking Hi-C data enhancement models.

313
314

Figure 3. Correlations between vision quality metrics and biological feature metrics. The plots display R^2 scores quantifying the relationships between selected vision metrics on the X-axis (PSNR, GDS, SSIM, and MSE) and biological feature matrices on the Y-axis (F1 score) for chromatin loops. The full results are shown in Supplementary Figure S5.

2.3 Performance assessment at different levels of data sparsity.

To evaluate the robustness of our method under varying levels of data sparsity, we extended our analysis beyond the 1/16 downsampled dataset by randomly down-sampling the high-resolution (10 kb) GM12878 cell line Hi-C data. We used 1/50 and 1/100 downsampling ratios, resulting in progressively lower resolution datasets (500 kb and 1 Mb, respectively), allowing us to assess *TRUHiC*'s performance relative to competing methods under different sparsity conditions. All models were retrained separately for each downsampled dataset and subsequently tested on chromosomes 18-22 using the same evaluation metrics: PSNR, SNR, SPC, PCC, GDS, SSIM, MSE, and biologically relevant metrics for TAD boundary and loop detection. The results, summarized in Supplementary Tables S6 and S7, demonstrate that *TRUHiC* predominantly outperforms other models at down-sampling rates of 1/50 and 1/100. As expected, increasing the down-sampling rate led to a decline in enhancement

336 performance across all models due to the greater loss of structural information at higher
337 sparsity levels.
338
339
340 **2.4 Generalization across different cell types and species**
341
We aimed to assess *TRUHiC*'s capability in enhancing low-resolution Hi-C data across
multiple human cell lines (K562, IMR90, and NHEK), as well as a mouse cell line
(CH12-LX), to benchmark model generalization across different cell types and species.
These datasets were originally processed at the same resolution as GM12878 (10 kb)
and were subsequently downsampled by 1/16 to a 160 kb resolution. In this experiment,
the pre-trained GM12878 models from Subsection 2.1 were directly applied to enhance
different down-sampled Hi-C data from the three additional human cell lines and the
mouse line. The test chromosomes for the human cell lines remained the same as
GM12878 (18-22), while chromosomes 16-19 were selected as the test set for the
mouse cell line. To evaluate the models' effectiveness, we used the previously
established evaluation metrics, which are outlined in Supplementary Table S8. We
observed that *TRUHiC* achieved higher performance scores compared to the competing
methods in three of these cell lines (K562, IMR90, and CH12-LX) while maintaining
competitiveness in the remaining human cell line (NHEK).

To further investigate the capability of *TRUHiC* to identify TADs and loops, we
employed the same TAD and loop callers, *IS* and *HiCCUPs,* to detect these two
features on the test chromosomes across different cell lines. As shown in
Supplementary Table S9, *TRUHiC* achieved higher JI values, indicating a greater
number of true positive TAD boundaries and loops while maintaining consistently lower
false positive rates across all cell lines and species compared to other methods. These
results demonstrate *TRUHiC*'s comparative generalization power across different cell
lines and species.
364
365 **2.5 Enhancing resolution in experimentally sparse Hi-C data**
366
We applied our primary pre-trained *TRUHiC* model, trained on GM12878 with 1/16
downsampled rate, to an actual low-resolution Hi-C data GM12329, obtained from
HGSVC2, with a contact map resolution of approximately 18 kb. This sample had been
excluded from the previous research studies[30] due to its low sequencing quality, which
resulted in the detection of only 158 chromatin loops at 10 kb resolution. To
comprehensively evaluate its performance, we assessed all 3D genome structure
features and all the reproducibility scores of GM12329 at a genome-wide scale. After
enhancement with *TRUHiC*, we identified 4,177 chromatin loops across all autosomes,
with all 158 loops originally detected in the data also present. We further compared it

with the recently released integrative TAD catalog in lymphoblastoid cell lines[30]. The
results of this experiment, presented in Supplementary Table S10, showcase that
TRUHiC outperforms the competing methods in accurately identifying loops and TAD
boundaries in real-world Hi-C data as well.
380
However, we observed a decline in performance across all evaluation metrics for
GM12329 compared to our primary results on the downsampled GM12878 dataset. This
finding is consistent with a recent study assessing the generalizability of deep learning-
based Hi-C resolution improvement methods, which reported that existing deep learning
approaches struggle to generalize to experimentally derived sparse Hi-C datasets, with
performance reductions of up to 57%[25]. These results highlight a critical limitation in
current deep learning frameworks and underscore the need for improved strategies to
enhance model generalizability. While our proposed *TRUHiC* framework outperforms
existing methods, addressing its robustness on real sparse data remains an important
direction in which we investigate further in Subsection 2.6 (CLS model).
391
392 **2.6 Towards robust Hi-C data enhancement using a cell line-specific (CLS) model**
393
Beyond our primary experiment using a 1/16 downsampled ratio, we generated four
additional replicates of data with the same 1/16 downsampling ratio using different
random seeds, constituting a total of five low-resolution datasets (Supplementary Figure
S6) to try to mimic more diverse data distribution observed in real-world Hi-C
experiments. We trained *TRUHiC* and other competing models on each of these five
datasets separately (the primary dataset plus four replicates) and observed inconsistent
prediction performance across different replicates and methods (Supplementary Tables
S11 and S12). We argue that these fluctuations in model performance arise from
inherent variations in the input Hi-C data distributions. Statistical analysis supports this
hypothesis, as indicated by a significant Kruskal-Wallis Test *p-value* (< 0.05) followed by
a Kolmogorov-Smirnov Test p-value for pairwise comparisons (Supplementary Table
S13). To address this issue, we propose a distinctive model training strategy that
integrates a diverse set of real Hi-C data rather than relying solely on a single
downsampled sample. This approach is inspired by recent advancements in
foundational models, which have demonstrated the effectiveness of large-scale data
aggregation in various domains, such as natural language processing[31–35] and
computational biology[36–42].
Lymphoblastoid cell lines (LCLs) are widely studied in large-scale genomic research
and are of particular importance for functional genomic and pharmacogenetics studies
in humans[43–46]. As a model system, LCLs enable scientists to study gene regulation,
genetic variation, and disease mechanisms at the population level using a consistent
cell type that can be easily expanded from small blood samples. Given their

significance, a cell line-specific (CLS) model tailored for enhancing Hi-C data in LCLs is
of great importance to the research community. Despite the merits a foundational model
trained on diverse species and cell lines presents, a CLS model is better suited to
capture the unified chromatin interaction patterns specific to the same cell line[47,48]. That
is, a CLS model is inherently biased toward the distinct structural patterns unique to a
specific cell line, which could be otherwise lost in favor of more common patterns across
species and cell lines in a foundational model.

Instead of pooling Hi-C data at the matrix level, as done in Li et al.'s study[30], our
proposed CLS modeling paradigm learns hierarchical chromatin interaction patterns
from multiple independent biological samples during training, enabling it to generalize
across diverse Hi-C datasets. Our CLS model framework is built upon the *TRUHiC*
architecture and is trained on a large-scale dataset of HGSVC Hi-C data from Li et al.'s
study[30] (Figure 4a). To systematically assess model scalability, we designed two
hierarchical training sets: a small dataset consisting of 10 unique HGSVC biological
samples (training set S) and another large dataset including an expanded set of 43
HGSVC biological samples, with GM12878 excluded (training set L). Both models were
evaluated using a test set comprising three biological sample data (GM11168,
GM13977, and GM18951) from Harris et al. 's study[49], ensuring that none of these
samples were included in any of the training sets.

Due to computational constraints, the initial model training was conducted on
chromosome 22. As shown in Supplementary Tables S14, S15 and Figure 4b, the
model trained on training set L yielded significantly improved performance across all
vision and biological feature evaluation metrics compared to the model trained on
smaller training set S. These findings support our hypothesis regarding the
effectiveness of our CLS-model framework, *TRUHiC-LCL*, demonstrating that a CLS-
model trained on the whole genome Hi-C data could even more effectively capture
complex chromatin interaction patterns present in real Hi-C datasets, surpassing the
limitations of single-sample training approaches. In this study, we release the pre-
trained chromosome 22 *TRUHiC-LCL* model trained on the training set L with 43 Hi-C
samples, providing an open-access resource for future applications in Hi-C data
enhancement and chromatin structure characterization.

a.

448
449   b.

Figure 4. The training strategy of building an LCL cell line-specific (CLS) model and
performance comparison of *TRUHiC-LCL* and *DFHiC-LCL* on chromosome 22. a).** This
schematic illustrates our proposed approach for developing a Hi-C CLS model (*TRUHiC-LCL*)
by aggregating diverse real Hi-C datasets from HGSVC (Li et al., 2024, n=43). We train an LCL-
model with two hierarchical training sets: Training Set S (small, n=10) and Training Set L (large,
n=43, GM12878 is excluded). The left panel represents training using chromosome 22, while
the right panel shows the potential to extend this framework to whole-genome training
(chromosomes 1-22), demonstrating the scalability of *TRUHiC-LCL* for constructing a Hi-C
foundation model that enhances data consistency and generalizability across multiple biological
samples. **b).** The figure presents F1 scores for TAD boundary and loop identification using a
small training set S (10 samples) and a large training set L (43 samples) across three real Hi-C
samples (GM11168, GM13977, and GM18951). Performance is compared between the state-

463 of-the-art *DFHiC* model and our *TRUHiC* framework. *TRUHiC* consistently outperformed *DFHiC*
464 across both training sample sizes and demonstrated further improvements as the training set
465 increased.

466
467

3 Discussion

Recent advances in chromosome conformation capture technologies like Hi-C have
provided critical insights into chromatin folding and genome organization. However, the
resolution of Hi-C data is often constrained by the sequencing depth and experimental
limitations, making it challenging to accurately detect TADs and chromatin loops. To
address this, we proposed *TRUHiC*, a computational framework designed to
significantly enhance low-resolution Hi-C data with high fidelity. Expanding on this, we
introduced *TRUHiC-LCL*, a lymphoblastoid cell line (LCL) specific model trained on
enriched Hi-C datasets aimed at improving generalizability and robustness across
different sequencing depths and experimental conditions for LCL Hi-C data. We provide
a pre-trained *TRUHiC-LCL* model based on HGSVC data, specifically for chromosome
22 of LCLs, developed within our constraints of computational limitations. We anticipate
that these models will be further enhanced with regard to their robustness and
performance in the future by incorporating additional LCL Hi-C data from consortia such
as HGSVC[50], HPRC[51], and the 4D nucleome project[52], as well as studies like Harris et
al.[49]. Moreover, our open-access framework is adaptable and enables researchers to
train and finetune their own CLS models and extend the approach to whole-genome Hi-
C data in various cell lines, tissues, and species, facilitating broader applications in
chromatin structure analysis.

Our experimental results support the idea and demonstrate the feasibility of building a
foundational model for Hi-C data using our approach. By leveraging existing Hi-C
datasets, this method enables the enhancement of low-resolution data, providing a
scalable framework for understanding chromatin architecture in species with limited
genomic resources. We anticipate the approaches demonstrated in this study will be
transferable to future extensions to build foundation models with massive Hi-C data
when available, with abundant opportunities to be applied to various applications across
diverse organisms other than human cell lines, such as plants and agriculturally
important species like soybeans. However, significant challenges remain in the
development of such generalized models that await future explorations.

One key limitation is the availability of high-quality, diverse Hi-C datasets for training.
Currently, *TRUHiC* has been primarily trained on GM12878, a well-characterized human

cell line. Though *TRUHiC-LCL* has been trained on a large scale of LCL Hi-C data, the
reliance introduces a potential bias in performance, as the model may become overly
tailored to the specific chromatin features of the dataset of that single cell line, limiting
its generalizability. To improve model robustness, the inclusion of Hi-C data from
additional cell types and species is critical. A more diverse training set would reduce
bias and enhance the model's ability to generalize across different chromatin
architectures, such as those found in plant genomes or organisms with unique genomic
configurations.

The performance discrepancy observed when applying the model to different datasets
further underscores this limitation. A biased training data may result in reduced
accuracy when used on species or conditions with chromatin features that deviate
significantly from those of GM12878. Overcoming this challenge requires efforts to
collect more Hi-C data, particularly high-resolution datasets from diverse backgrounds,
to create a more comprehensive training set across different biological contexts. Future
work should thus focus on expanding training datasets in both diversity and volume to
reduce bias and enhance the model's generalizability. Additionally, it is essential to
explore how the model performs across datasets with varying resolutions and
experimental protocols to help identify and address potential discrepancies. Coupling
Hi-C data with complementary multi-omics datasets, such as ATAC-seq, ChIP-seq, and
RNA-seq, could also enhance the model's ability to link chromatin structure with gene
regulation and functional outcomes, providing deeper insights into genome organization
and transcriptional regulation. With a continued expansion of training datasets and
continued model refinement, this method has the potential to advance our
understanding of chromatin architecture across a wide range of organisms and
biological contexts. Ultimately, it could contribute to accurate reconstructions of three-
dimensional genome organization, facilitating new insights into gene regulation,
epigenetics, and genome function.

4 Materials and methods

4.1 Materials

We utilized a published high-resolution Hi-C dataset of human cell type GM12878, three
additional different human cell types, K562, NHEK, and IMR90, and one mouse cell
type CH12-LX from the GEO database (accession number GSE63525)[3] and a recent
study that integrated human cell type from 44 individuals[30]. To generate low-resolution
Hi-C data, we applied a random down-sampling approach to the raw sequencing reads
of each cell line using down-sampling rates ranging from 1/16 to 1/100, with the primary

sampling rate set as 1/16. We trained our model using both high-resolution and low-
resolution Hi-C data. These diverse sampling rates enable us to assess the model's
performance across different levels of raw reads sequencing depth. Both high-resolution
and the corresponding low-resolution Hi-C matrices were partitioned into 40 × 40 non-
overlapping blocks of 10 kb resolution with no normalization method applied
(normalization set to NONE). We followed established practices in Hi-C super-resolution
methodologies to preserve only small fragments where the genomic distance between
two loci is < 2Mb, considering the typical average genomic distance of TADs to be < 1
Mb[5,6,12,13,15]. Chromosomes 1-17 comprised our training set, and chromosomes 19-22
constituted our test set. We split the training set into training and validation data
following a 9.5:0.5 ratio during the training process of our model and all competing
methods to have an identical and fair training regiment.

547
4.2 *TRUHiC* architecture

TRUHiC is a computational framework designed to enhance the resolution of Hi-C
matrices through supervised training. The overall architecture of *TRUHiC* is portrayed in
Figure 5. The backbone of the *TRUHiC* is a U-2 Net architecture, the successor of U-
Net architecture. A U-Net[53] is an auto-encoder based model that has skip connections
from the encoder layers to the respective decoder layers. A U-2 Net[54] is a U-Net in
which layers are replaced by U-Nets-like blocks, termed ReSidual U-blocks (RSU).
More specifically, a U-2 Net uses RSU-L and RSU-4F blocks. RSU-L blocks use a
CNN-based symmetric U-Net architecture with L-1 encoder/decoder convolutional
layers in addition to the pooling and upsampling operations. RSU-4F blocks are used as
the bridge of the U-2 Net, as well as pre and post-bridge blocks, using dilated
convolutions. In the originally proposed U-2 Net framework, the encoder/decoder has
four RSU-L blocks and one RSU-F block, and another RSU-F block is used as the
bridging block between the encoder and the decoder. Another characteristic of the U-2
Net architecture is the presence of auxiliary outputs from the bridging block and each
decoder block.

We customized the U-2 Net architecture for the Hi-C enhancement task by refining
several key components to optimize performance and computational efficiency. At a
high level, we reduced the number of encoder/decoder RSU-L blocks to two, which
simplifies the network while retaining sufficient capacity to extract essential features. In
our design, the encoder/decoder blocks play a critical role in capturing multi-scale
information and reducing their number, which lowers computational complexity without
significantly compromising performance. Additionally, we introduced a direct skip
connection from the input to the outputs, inspired by the DFHiC model[12]. This
connection helps preserve pixel-level details. To further improve feature representation,

we replaced the traditional RSU-4F bridging block with a customized multi-head
self-attention gating mechanism[55] embedded within a transformer block (Supplementary
Figure S7). This self-attention module mainly regulates channel-wise information
through fully connected layers, thereby enhancing the quality of the generated feature
maps. We also applied weighting to each auxiliary output. Specifically, the loss from
each auxiliary output is multiplied by *1/e^x*, where *x* is the index of the auxiliary output,
starting at one for the final RSU-L block and ending at four for the transformer block. For
example, the auxiliary output from the RSU-4F block is weighted by $1/e^3$. This approach
prevents earlier layers from being forced to generate a fully refined prediction and
instead allows them to reinforce the final output effectively. Finally, to preserve spatial
resolution, a critical aspect for accurate Hi-C data enhancement, we removed the
maximum pooling and upsampling operations from the RSU-L blocks (Supplementary
Figure S7). Furthermore, we applied both L1 and L2 regularizations to the convolution
layers to mitigate overfitting and improve the model's generalization capabilities.

Additionally, we altered the loss function to include two terms as follows:

$$L(y, \widehat{y}) = MAE(y, \widehat{y}) + \frac{1}{SNR(y,\widehat{y}) + \varepsilon},$$ (3)

where MAE denotes the mean absolute error, and SNR is the signal-to-noise ratio,
defined in Equation (6). We use the LAMB optimizer[56] and early stopping. Also, we
implement a learning rate reduction strategy upon loss plateau to enhance convergence
stability.

593
Figure 5. Overview of the *TRUHiC* architecture. We customized the U-2 Net architecture in
several ways. A skip connection was added from the input to the output of the model. We
replaced the U-Net bridge block in the model with (customized) multi-head self-attention gating
wrapped up in a transformer block. We also removed MaxPooling and UpSampling layers to
prevent the loss of information due to data compression. Additionally, auxiliary outputs have a
weighted loss contribution. *TRUHiC* takes the low resolution of the Hi-C contact map as the
input and generates the super-resolution Hi-C contact map as the output. A detailed illustration
of RSU_L, RSU_4F, and Transformer blocks can be found in Supplementary Figure S6.
602
603

4.3 Identification of TAD boundaries and loops

We used the *Insulation Score* (*IS*) method to identify TAD boundaries in this study,
which was originally designed to detect TAD boundaries and quantify the boundary
strength of Hi-C data with limited resolution. For all the experiments with GM12878
data, the Hi-C data were mapped to the hg19 human reference genome, and the KR
normalized contact matrix at 10 kb resolution was used to compute the insulation scores
and boundary scores (BS). TAD boundaries were identified using the *FAN-C* toolkit
(version 0.9.26b2) with a minimum boundary score cut-off value of 0.20, specifying a
100 kb window size, as referenced in the 4DN domain calling protocol[52,57]. For the

experiments of sample GM12329, we used the hg38 human reference genome and
applied SCALE normalization to the predicted contact map at 10 kb resolution. For the
TRUHiC-LCL model, we selected the 5 kb resolution to be consistent with the protocol
of the integrative TAD catalog described in Li et al.'s study[30].

The *IS* method operates by defining a sliding window along the diagonal of the Hi-C
matrix and summing contacts within this window. Regions with low insulation scores
(corresponding to high boundary scores) act as insulating boundaries and are identified
as TAD boundaries. In contrast, regions with high insulation scores (low boundary
scores) typically fall within TAD domains and are referred to as TAD regions, which
represent the genomic intervals between the adjacent TAD boundaries in this study.
TADs with a size larger than 2 Mb were excluded from the analysis, and sex
chromosomes X and Y were removed from all analyses due to sex-based variability in
the samples. *Juicebox* software and the *FAN-C* toolkit in Python 3.7 were used to
visualize insulation scores, TAD boundaries, and respective boundary scores.

Chromatin loops (and loop anchors) of the experiments of samples GM12878 and
GM12329 were identified by *HiCCUPS* (GPU) at 10 kb resolution, and the loops of three
real samples enhanced by the *TRUHiC-LCL* model were detected at 5 kb resolution.
The data alignment and matrix normalization procedures for the experiments with the
GM12878 sample, actual samples, and *TRUHiC-LCL* followed the same approach as
described in TAD boundary identification. The Jaccard Index was computed using the
bedtools jaccard command, and the F1 score was calculated based on the equation
provided in the previous section and implemented using our custom Python script.
635
636 **4.4 CTCF loop anchor validation with ChIP-seq datasets**
637
ChIP-Seq experimental datasets for CTCF, RAD21, and SMC3 for each cell line were
obtained from Rao et al.'s study[3]. For each loop anchor, we expanded its region by ± 5
kb flanking windows and merged overlapping or adjacent intervals into a single larger
interval. A loop anchor was classified as CTCF-supported if its expanded regions fully
contained CTCF ChIP-Seq peak, RAD21 ChIP-Seq peak, and SMC3 ChIP-Seq peak
simultaneously. In cases where RAD21 or SMC3 ChIP-Seq data were unavailable for a
given cell type, a loop anchor was considered CTCF-supported if the expanded anchor
overlapped with CTCF and either SMC3 or RAD21 peaks. If only CTCF ChIP-Seq data
were available, the loop anchor was required to show a direct overlap with a CTCF
ChIP-Seq peak to be classified as CTCF-supported. The validated loop anchor ratio
was calculated as the percentage of CTCF-supported loop anchors among the total
unique loop anchors. We reported this value as a matrix to evaluate the accuracy of
loop calling across different methods. The validation experiment was not performed for
the CH12-LX cell line due to the absence of corresponding ChIP-Seq datasets provided

in Rao et al.'s study. A detailed list of CTCF ChIP-Seq datasets used in this analysis is
provided in Supplementary Table S16.
654

4.5 Baseline Models

We selected *HiCNN2*, *HiCARN1*, *HiCARN2*, and *DFHiC* methods for benchmarking our
proposed method. While pre-trained model weights for a number of the mentioned
methods are publicly available, we opted to train them all from scratch to ensure fair and
consistent evaluations. Each model was implemented using its official source code to
maintain fidelity to the original methods. In the case of *DFHiC*, we re-implemented the
code in Tensorflow 2.14 and added improvements to it for scheduling the learning rate
to prevent premature loss convergence. For the *HiCNN2* and *HiCARN* (*HiCARN1* and
HiCARN2) methods, we used the source Pytorch implementations without any major
changes other than cleaning up the code and adding command line arguments for ease
of training and inference. We are providing the implementations of these models on our
repository at https://github.com/shilab/TRUHiC for better reproducibility of the results.
668

4.6 Evaluation metrics

To assess the performance of our model and the quality of the generated enhanced Hi-
C samples, we considered the output as an image and employed various evaluation
metrics, which include Mean Squared Error (MSE), Structural Similarity Index (SSIM),
Peak Signal-to-Noise Ratio (PSNR), Signal-to-Noise Ratio (SNR), Spearman
Correlation Coefficient (SPC), Pearson Correlation Coefficient (PCC) and
GenomeDISCO Scores (GDS).

Firstly, MSE is used to calculate the average squared difference between the model-
predicted Hi-C matrix and the real high-resolution Hi-C matrix, which can effectively
capture the average discrepancy at the pixel level. SSIM score evaluates the structural
similarity between the enhanced output and the ground truth Hi-C matrix, with higher
scores indicating greater preservation of structural integrity. Furthermore, we used both
PSNR and SNR to measure the quality of the reconstructed Hi-C contact maps.
Specifically, SNR quantifies the ratio of signals relative to background noise, whereas
PSNR measures the ratio of the maximum possible signal power to the power of
corrupting noise in the enhanced contact matrix and the target real high-resolution
matrix. The higher both values are, the more unwanted noise is removed. PSNR and
SNR are formulated in Equations (5 and 6), respectively. We employ SPC and PCC to
evaluate the correlation between the predicted Hi-C matrix and the actual Hi-C matrix
along the matrix diagonal. Additionally, we used a concordance measure named
GenomeDISCO, which was developed to assess the similarity between a pair of contact

maps received from 3C experiments. We provide the equations for these metrics as
follows[15]:

$$MSE = \frac{1}{n^2} \Sigma_{i,j}(H_{ij} - E_{ij})^2$$
(4)

$$PSNR = 10log_{10}(\frac{MAX^2}{MSE})$$ (5)

$$SNR = \frac{\Sigma_{i,j} E_{i,j}}{\sqrt{\Sigma_{i,j} (H_{i,j}-E_{i,j})^2}}$$ (6)

$$SSIM = \frac{(2\mu_H \mu_E + C_1^2) + (2\sigma_{HE} + C_2^2)}{(\mu_H^2 + \mu_E^2 + C_1^2) + (\sigma_H^2 + \sigma_E^2 + C_2^2)}, \quad C_1 = 0.01 \text{ and } C_2 = 0.03$$
(7)

$$SPC = \frac{\Sigma_{i=1} (rH_i - rH)(rE_i - E)}{\sqrt{\Sigma_{i=1} (rH_i-rH)^2} \sqrt{\Sigma_{i=1} (rE_i-rE)^2}}$$ (8)

$$PCC = \frac{\Sigma_{i=1} (H_i - \mu_H)(E_i - \mu_E)}{\sqrt{\Sigma_{i=1} (H_i-\mu_H)^2} \sqrt{\Sigma_{i=1} (E_i-\mu_E)^2}}$$
(9)

where H_{ij} is the pixel in the real HR Hi-C matrix and E_{ij} is the pixel in the enhanced Hi-
C matrix. MAX denotes the maximum possible value in samples, while μ and
σ correspond to the mean and variance, respectively. σ_{HE} is the covariance of H and
E, and r is rank. Mean, variance, and covariance in the SSIM formula are calculated
using a Gaussian filter, and C_1 and C_2 are constants used to stabilize the calculations.
We used the SSIM implementation provided in *DeepHiC*.
707
708
4.7 Data and Code Availability

The GM12878, K562, IMR90, NHEK, and CH12-LX datasets supporting this study are
publicly accessible in the GEO database under accession number GSE63525, available
at https://www.ncbi.nlm.nih.gov/geo/query/acc.cgi?acc=GSE63525. The raw
sequencing Hi-C data generated by HGSVC2 discussed in this study can be
downloaded directly at the following link:
https://ftp.1000genomes.ebi.ac.uk/vol1/ftp/data_collections/HGSVC2/working/20230515
_Shi_hic_files/. Our *TRUHiC* method, along with the competing methods, the pre-
trained *TRUHiC-LCL* model for chromosome 22, and all original code for the statistical
analysis and pipeline implementation, have been deposited on GitHub

https://github.com/shilab/TRUHiC and are publicly available as of the date of
publication.

Funding

723 This work is partially supported by the US National Science Foundation (DBI 1750632)
724 and the National Institutes of Health (R35-GM139540-04, U24HG007497,
725 R01GM093290).

Acknowledgment

727 This research includes calculations carried out on HPC resources supported in part by
728 the National Science Foundation through major research instrumentation grant number
729 1625061 and by the US Army Research Laboratory under contract number W911NF-
730 16-2-0189. We thank Rohan Alibutud for his feedback on the project and diligent
731 proofreading.

Human Genome Structural Variation Consortium (HGSVC)

The members of the Human Genome Structural Variation Consortium (HGSVC) are
Hufsah Ashraf, Peter A. Audano, Olanrewaju Austine-Orimoloye, Parithi Balachandran,
Anna O. Basile, Christine R. Beck, Marc Jan Bonder, Marta Byrska-Bishop, Mark J.P.
Chaisson, Zechen Chong, André Corvelo, Jonathan Crabtree, Scott E. Devine, Peter
Ebert, Jana Ebler, Evan E. Eichler (Co-Chair), Mark B. Gerstein, Bida Gu, Lisbeth A
Guethlein, Pille Hallast, William T. Harvey, Patrick Hasenfeld, Alex R. Hastie, Mir
Henglin, Kendra Hoekzema, PingHsun Hsieh, Sarah Hunt, Matthew Jensen, Miriam K.
Konkel, Jan O. Korbel (Co-Chair), Jennifer Kordosky, Youngjun Kwon, Peter M.
Lansdorp, Charles Lee (Co-Chair), Wan-Ping Lee, Alexandra P. Lewis, Chong Li,
Jiadong Lin, Mark Loftus, Glennis A. Logsdon, Tobias Marschall (Co-Chair), Gianni V.
Martino, Ryan E. Mills, Yulia Mostovoy, Mohammad Erfan Mowlaei, Katherine M.
Munson, Giuseppe Narzisi, Andy Pang, David Porubsky, Timofey Prodanov, Keon
Rabbani, Tobias Rausch, Xinghua Shi, Yuwei Song, Arda Söylev, Likhitha Surapaneni,
Michael E. Talkowski, Vasiliki Tsapalou, Feyza Yilmaz, DongAhn Yoo, Xuefang Zhao,
Weichen Zhou, and Michael C. Zody.

HGSVC Functional Analysis Working Group

The members of the Human Genome Structural Variation Consortium (HGSVC) functional analysis working group are Anna O. Basile, Christine R. Beck, Marta Byrska-Bishop, Marc Jan Bonder, Mark J.P. Chaisson, Ken Chen, Evan E. Eichler, Matthew Jensen, Yunzhe Jiang**,** Kwondo Kim, Miriam K. Konkel, Jan O. Korbel (Co-Chair), Charles Lee, Chong Li, Jiaqi Li, Yang I. Li, Qingnan Liang, Glennis A. Logsdon, Tobias Marschall, Gianni V. Martino, Ryan E. Mills, Nicholas Moskwa, Yulia Mostovoy, Mark Gerstein, Lingbin Ni, Pille Hallast, Wolfram Höps, Daniel Ben-Isvy, Carolyn Paisie, Bernardo Rodriguez-Martin, Xinghua Shi (Co-Chair), Oliver Stegle, Sabriya Syed, Michael E. Talkowski, Yukun Tan, Alex Yenkin, DongAhn Yoo, Xuefang Zhao, Weichen Zhou, and Michael C. Zody.

References

1. Lieberman-Aiden, E. *et al.* Comprehensive mapping of long-range interactions reveals folding principles of the human genome. *Science* **326**, 289–293 (2009).

2. Dixon, J. R. *et al.* Topological domains in mammalian genomes identified by analysis of chromatin interactions. *Nature* **485**, 376–380 (2012).

3. Rao, S. S. P. *et al.* A 3D map of the human genome at kilobase resolution reveals principles of chromatin looping. *Cell* **159**, 1665–1680 (2014).

4. Bonev, B. *et al.* Multiscale 3D Genome Rewiring during Mouse Neural Development. *Cell* **171**, 557–572.e24 (2017).

5. Zhang, Y. *et al.* Enhancing Hi-C data resolution with deep convolutional neural network HiCPlus. *Nat. Commun.* **9**, 750 (2018).

6. Liu, Q., Lv, H. & Jiang, R. hicGAN infers super resolution Hi-C data with generative adversarial networks. *Bioinformatics* **35**, i99–i107 (2019).

780 7. Liu, T. & Wang, Z. HiCNN: a very deep convolutional neural network to better

781   enhance the resolution of Hi-C data. *Bioinformatics* **35**, 4222–4228 (2019).

782 8. Liu, T. & Wang, Z. HiCNN2: Enhancing the resolution of Hi-C data using an

783   ensemble of convolutional neural networks. *Genes (Basel)* **10**, 862 (2019).

784 9. Yardımcı, G. G. Software tools for visualizing Hi-C data. *Genome Biology* **18**, 1–9

785   (2017).

786 10. Merkenschlager, M. & Nora, E. P. CTCF and Cohesin in Genome Folding and

787   Transcriptional Gene Regulation. *Annual review of genomics and human genetics*

788   **17**, (2016).

789 11. Li, Z. & Dai, Z. SRHiC: A Deep Learning Model to Enhance the Resolution of Hi-C

790   Data. *Front Genet* **11**, 353 (2020).

791 12. Wang, B., Liu, K., Li, Y. & Wang, J. DFHiC: a dilated full convolution model to

792   enhance the resolution of Hi-C data. *Bioinformatics* **39**, (2023).

793 13. Hong, H. *et al.* DeepHiC: A generative adversarial network for enhancing Hi-C data

794   resolution. *PLoS Comput. Biol.* **16**, e1007287 (2020).

795 14. Dimmick, M. C., Lee, L. J. & Frey, B. J. HiCSR: a Hi-C super-resolution framework

796   for producing highly realistic contact maps. *bioRxiv* 2020.02.24.961714 (2020)

797   doi:10.1101/2020.02.24.961714.

798 15. Highsmith, M. & Cheng, J. VEHiCLE: a Variationally Encoded Hi-C Loss

799   Enhancement algorithm for improving and generating Hi-C data. *Sci. Rep.* **11**, 8880

800   (2021).

801 16. Hu, Y. & Ma, W. EnHiC: learning fine-resolution Hi-C contact maps using a

802   generative adversarial framework. *Bioinformatics* **37**, i272–i279 (2021).

17. Hicks, P. & Oluwadare, O. HiCARN: resolution enhancement of Hi-C data using

cascading residual networks. *Bioinformatics* **38**, 2414–2421 (2022).

18. He, K., Zhang, X., Ren, S. & Sun, J. Deep Residual Learning for Image

Recognition. (2015).

19. Yu, J. *et al.* Wide Activation for Efficient and Accurate Image Super-Resolution.

(2018).

20. Shi, W. *et al.* Real-Time Single Image and Video Super-Resolution Using an

Efficient Sub-Pixel Convolutional Neural Network. (2016).

21. Ahn, N., Kang, B. & Sohn, K.-A. Fast, Accurate, and Lightweight Super-Resolution

with Cascading Residual Network. (2018).

22. Shen, Y., Yu, L., Qiu, Y., Zhang, T. & Kingsford, C. Improving Hi-C contact matrices

using genome graphs. *bioRxiv* 2023.11.08.566275 (2023)

doi:10.1101/2023.11.08.566275.

23. Hassani, A. *et al.* Escaping the Big Data Paradigm with Compact Transformers.

(2021).

24. HiCTF:A Transformer Model for enhancing Hi-C data resolution.

https://dl.acm.org/doi/10.1145/3637732.3637780 doi:10.1145/3637732.3637780.

25. Murtaza, G., Jain, A., Hughes, M., Wagner, J. & Singh, R. A Comprehensive

Evaluation of Generalizability of Deep Learning-Based Hi-C Resolution

Improvement Methods. *Genes* **15**, 54 (2023).

26. Ursu, O. *et al.* GenomeDISCO: a concordance score for chromosome conformation

capture experiments using random walks on contact map graphs. *Bioinformatics*

34, 2701–2707 (2018).

27. Crane, E. *et al.* Condensin-driven remodelling of X chromosome topology during

dosage compensation. *Nature* **523**, 240–244 (2015).

28. A 3D Map of the Human Genome at Kilobase Resolution Reveals Principles of

Chromatin Looping. *Cell* **162**, 687–688 (2015).

29. Fang, T. *et al.* Enhancing Hi-C contact matrices for loop detection with Capricorn: a

multiview diffusion model. *Bioinformatics* **40**, i471–i480 (2024).

30. Li, C. *et al.* An integrative TAD catalog in lymphoblastoid cell lines discloses the

functional impact of deletions and insertions in human genomes. *Genome Res* **34**,

2304–2318 (2024).

31. Longpre, S. *et al.* A large-scale audit of dataset licensing and attribution in AI.

Nature Machine Intelligence **6**, 975–987 (2024).

32. Myers, D. *et al.* Foundation and large language models: fundamentals, challenges,

opportunities, and social impacts. *Cluster Computing* **27**, 1–26 (2023).

33. Bommasani, R. *et al.* On the Opportunities and Risks of Foundation Models.

(2021).

34. Zhou, C. *et al.* A Comprehensive Survey on Pretrained Foundation Models: A

History from BERT to ChatGPT. (2023).

35. Recent Advances in Natural Language Processing via Large Pre-trained Language

Models: A Survey. *ACM Computing Surveys* (2023) doi:10.1145/3605943.

36. Wang, X. *et al.* A generalizable Hi-C foundation model for chromatin architecture,

single-cell and multi-omics analysis across species. *bioRxiv* 2024.12.16.628821

(2024) doi:10.1101/2024.12.16.628821.

37. Cui, H. *et al.* scGPT: toward building a foundation model for single-cell multi-omics

using generative AI. *Nat Methods* **21**, 1470–1480 (2024).

38. Chen, Z., Wei, L. & Gao, G. Foundation models for bioinformatics. *Quantitative*

Biology **12**, 339–344 (2024).

39. Zhang, S. *et al.* Applications of transformer-based language models in

bioinformatics: a survey. *Bioinform Adv* **3**, vbad001 (2023).

40. Liu, J. *et al.* Large language models in bioinformatics: applications and

perspectives. *ArXiv* (2024).

41. Moor, M. *et al.* Foundation models for generalist medical artificial intelligence.

Nature **616**, 259–265 (2023).

42. Vorontsov, E. *et al.* A foundation model for clinical-grade computational pathology

and rare cancers detection. *Nature Medicine* **30**, 2924–2935 (2024).

43. Scheinfeldt, L. B. *et al.* Genetic and genomic stability across lymphoblastoid cell

line expansions. *BMC Research Notes* **11**, 1–5 (2018).

44. Thomas, S. M. *et al.* Reprogramming LCLs to iPSCs Results in Recovery of Donor-

Specific Gene Expression Signature. *PLOS Genetics* **11**, e1005216 (2015).

45. Çalışkan, M., Pritchard, J. K., Ober, C. & Gilad, Y. The Effect of Freeze-Thaw

Cycles on Gene Expression Levels in Lymphoblastoid Cell Lines. *PLOS ONE* **9**,

e107166 (2014).

46. *Human Lymphoblastoid Cell Lines in Pharmacogenomics*. 89–110 (Academic

Press, 2014).

47. Li, Y., Zeng, M., Zhang, F., Wu, F.-X. & Li, M. DeepCellEss: cell line-specific

essential protein prediction with attention-based interpretable deep learning.

Bioinformatics **39**, (2023).

48. Tan, J. *et al.* Cell-type-specific prediction of 3D chromatin organization enables

high-throughput in silico genetic screening. *Nature Biotechnology* **41**, 1140–1150

(2023).

49. Harris, H. L. *et al.* Chromatin alternates between A and B compartments at kilobase

scale for subgenic organization. *Nature Communications* **14**, 1–17 (2023).

50. Logsdon, G. A. *et al.* Complex genetic variation in nearly complete human

genomes. *bioRxiv* (2024) doi:10.1101/2024.09.24.614721.

51. Liao, W.-W. *et al.* A draft human pangenome reference. *Nature* **617**, 312–324

(2023).

52. Dekker, J. *et al.* The 4D nucleome project. *Nature* **549**, 219–226 (2017).

53. Ronneberger, O., Fischer, P. & Brox, T. U-Net: Convolutional Networks for

Biomedical Image Segmentation. (2015).

54. U2-Net: Going deeper with nested U-structure for salient object detection. *Pattern

Recognition* **106**, 107404 (2020).

55. Oktay, O. *et al.* Attention U-Net: Learning Where to Look for the Pancreas. (2018).

56. You, Y. *et al.* Large Batch Optimization for Deep Learning: Training BERT in 76

minutes. in *International Conference on Learning Representations* (2019).

57. Kruse, K., Hug, C. B. & Vaquerizas, J. M. FAN-C: a feature-rich framework for the

analysis and visualisation of chromosome conformation capture data. *Genome Biol.*

21, 303 (2020).