# Development of Replay–DMN Coordination Predicts Entorhinal Grid Codes

Luoyao Pang[1,2#], Yukun Qu[1,2#], Jianxin Ou[1,2], Shuqi Wu[1,2], Yuejia Luo[1,3],

Chetan Gohil[4,5], Mark Woolrich[4,5], Tim Behrens[5,6,7], Yunzhe Liu[1,2*]

1. State Key Laboratory of Cognitive Neuroscience and Learning, IDG/McGovern Institute for Brain Research, Beijing Normal University, Beijing, China

2. Chinese Institute for Brain Research, Beijing, China

3. School of Psychology, Center for Brain Disorders and Cognitive Science, Shenzhen University, Shenzhen, China

4. Oxford Centre for Human Brain Activity (OHBA), University of Oxford, Oxford, UK

5. Wellcome Centre for Integrative Neuroimaging, University of Oxford, Oxford, UK

6. Wellcome Centre for Human Neuroimaging, UCL, London, UK

7. Sainsbury Wellcome Centre for Neural Circuits and Behaviour, UCL, London, UK

# These authors contributed equally

* Correspondence: yunzhe.liu@bnu.edu.cn (Y.L.)

# Abstract

Replay has been implicated in organising experiences into cognitive maps offline, yet how this process evolves through development remains unclear. We studied 106 participants (ages 8–25) who learned a hidden two-dimensional (2D) structure and then underwent magnetoencephalography (MEG) during a map-based inference task and subsequent rest, allowing us to detect spontaneous replay. Younger participants relied more on replay alone to represent the 2D associations, whereas older participants showed increasingly precise alignment between replay and the default mode network (DMN), particularly when replay events were timed to the DMN theta (2–6 Hz) trough. This alignment further predicted grid-cell-like codes in the entorhinal cortex, previously identified in the same cohort using fMRI. Resting-state fMRI indicated that DMN connectivity also strengthened with age, which explained reduced reliance on replay and faster inference across development. These findings illuminate a developmental progression where replay shifts from an isolated hippocampal process to a coordinated hippocampal–DMN mechanism. This shift may underpin maturing grid-like schema representations, offering insight into how children gradually build internal knowledge structures for flexible inference.

**Keywords:** replay, default mode network (DMN), cognitive map, grid code, development

## 1 Introduction

Neural replay, in which activity patterns reflecting past experiences re-emerge during rest or sleep, is classically associated with memory consolidation and hippocampal sharp-wave ripples (Carr et al., 2011; Diba & Buzsáki, 2007; Skaggs & McNaughton, 1996). In rodents, it appears to stitch together experiences into new associations (Barron et al., 2020). In humans, replay has also been observed (Liu et al., 2019; Schuck & Niv, 2019) and seems more flexible (Liu et al., 2019; Schwartenbeck et al., 2023). An intriguing line of research suggests that replay helps form internal representations or cognitive maps that support flexible behaviour (Behrens et al., 2018; Whittington et al., 2022), a core component of biological intelligence. It is crucial to know how it develops. Although rodent studies show replay is present even before weaning and gradually becomes more extended and structured (Farooq & Dragoi, 2019; Muessig et al., 2019), little is known about how it develops in humans or about its functional implications for cognition.

Replay is thought to integrate experiences by forging local links between related items (Barron et al., 2020), forming associative maps directly from experiences (Stachenfeld et al., 2017), or by embedding these experiences within a broader schema (Ou et al., 2025; Xiao et al., 2025). These task schemas (Piaget, 1952; Tolman, 1948) enable inferences beyond direct experiences in both physical and conceptual spaces (Constantinescu et al., 2016; Doeller et al., 2010; Park et al., 2021). They are characterised by grid-cell-like codes in the entorhinal cortex (EC) in a two-dimensional (2D) space. However, it remains unclear whether and how replay evolves through development, and how it relates to the entorhinal grid code.

A recent fMRI study by Qu et al. (2024) of 203 subjects, aged 8 to 25, showed that children's inference ability improves with age and is accompanied by increasingly pronounced grid-cell-like activity in the EC. In younger participants who had not formed a clear grid-based schema, the hippocampus appeared to play a larger role, suggesting heavier reliance on hippocampal mechanisms before shifting to an EC grid-like schema. These findings raise the question of whether replay underlies this transition.

This transition may require coordination with broader cortical processes rather than the hippocampus alone. Research in human adults and animals indicates that replay often coincides with activity in the default mode network (DMN), particularly when sharp-wave ripples in the hippocampus synchronise with DMN activation (Higgins et al., 2021; Kaplan et al., 2016; Norman et al., 2021; Swanson et al., 2025; Vaz et al., 2020). During development, the DMN undergoes substantial maturation, including enhanced connectivity in key hubs such as the posterior cingulate cortex (PCC) (Fair et al., 2008; Supekar et al., 2010). It also displays increased specialisation and integration across regions, including privileged links with the hippocampus (Ezama et al.,

2021; Olsen et al., 2017; Ward et al., 2014) and stronger internal connections (Fair et al., 2009; Supekar et al., 2010). These observations suggest that replay might shift from a local hippocampal event to a more coordinated hippocampal–DMN process as the brain matures.

We investigated how replay and replay–DMN coordination evolve from childhood to adulthood, and whether such coordination predicts entorhinal grid code. One hundred and six participants aged 8 to 25 years learned pairwise object relationships in a hidden 2D structure, then underwent magnetoencephalography (MEG) during a map-based inference task and subsequent rest, allowing us to detect spontaneous replay. We identified replay of task-related experiences during post-task rest (Liu et al., 2021) and employed hidden Markov modelling to track transient DMN activation in the same resting period (Higgins et al., 2021). We then tested whether replay–DMN alignment predicted subsequent grid-like coding in the EC, identified previously in the same set of participants (Qu et al., 2024).

Our findings revealed a developmental shift from stronger replay in younger participants to more selective replay–DMN alignment in older participants, particularly when replay coincided with the DMN theta trough. This alignment was linked to stronger DMN activation in resting-state MEG and to the previously observed grid-like signals in the EC. These results suggest that replay transitions from an isolated hippocampal process to a more coordinated hippocampal–DMN mechanism, potentially facilitating the formation of schema-based knowledge for flexible inference.

**Results**

**Age-related improvement in map-based inference**

All participants underwent extensive off-scan behavioural training, before MEG scanning (**Figure 1A**; see

Methods for details and Qu et al., 2024). During this training, they learned the adjacent rank order (differing

by one rank) of 25 objects in terms of attack and defence power, arranged in a hidden $5 \times 5$ 2D grid. Through

repeated pairwise comparisons along each dimension, participants gradually acquired the power hierarchy of

the objects. Only those who reached at least 80% accuracy on all pairwise relationships proceeded to the

subsequent experiment. This thorough training ensured that participants of all ages fully understood the task,

minimised fatigue during scanning, and controlled for other age-related confounds (see also **Supplementary**

**Note 1**).

Following this training, participants performed an inference task and completed pre- and post-task resting-

state scans under MEG (**Figure 1B**). The pre-task rest occurred before the inference task, and the post-task

rest immediately after. These sessions enabled us to assess how the inference task affected neural replay during

rest and how replay changed with age. After the MEG session, participants underwent fMRI scanning, which

included a resting-state fMRI for linking with MEG replay measures, followed by an fMRI-scanned inference

task reported in detail in Qu et al. (2024), where a robust grid-like code in the EC was identified.

In the MEG-scanned inference task, participants were presented with two randomly selected objects and asked

to infer which had higher power in a cued dimension (attack or defence). Each object appeared on screen for

1.5 s, separated by a 0.4–0.6 s interval. After both objects were shown, a decision cue indicated which

dimension to compare, and participants had up to 2 s to select the object with the higher rank on that dimension

(**Figure 1B**). This procedure required them to make inferences beyond the pairs directly learned during training,

potentially relying on an internal 2D map of the task space.

In total, 106 participants aged 8–25 years took part in the MEG experiment. After excluding those with random

behaviour or excessive head movement, 98 participants (mean $\pm$ SEM age: $16.40 \pm 0.64$ years) remained in the

final analysis (see **Supplementary Table 1**). Behaviourally, inference accuracy positively correlated with age

($r = 0.219$, $p = 0.030$), indicating that older participants made more correct inferences, and reaction time

negatively correlated with age ($r = -0.259$, $p = 0.010$), suggesting faster responses among older participants.

Notably, memory accuracy after training was not significantly associated with age ($r = 0.074$, $p = 0.471$), and

the correlations between age and both accuracy and reaction time in the inference task remained significant

when controlling for memory accuracy. The Advanced Progressive Matrices (APM) test, a standard IQ measure of reasoning, also improved significantly with age ($r = 0.505$, $p < 0.001$), and was significantly associated with inference performances (see **Supplementary Figure 1B**). These results demonstrate that as individuals mature, they become both more accurate and more efficient at complex inferences, in line with typical age-related gains in reasoning skills.

These improvements in inference ability may emerge as the 2D schema representation in the EC becomes more robust (Qu et al., 2024). However, it remains unclear whether the neural processes supporting this form of advanced knowledge organisation also mature with age. We hypothesised that spontaneous neural replay during rest is crucial to this development. In the sections that follow, we examine whether and how replay transitions across ages, including its coordination with the DMN (**Figure 1C**).

**Figure 1. Overview of experimental design and analysis.**

(**A**) Behavioural training. Prior to scanning, participants completed an off-scan training protocol in which they memorised pairwise associations between 25 objects based on their attack or defence power. Participants were unaware of the underlying 5 × 5 2D structure and believed they were performing a simple memory task. Only those achieving at least 80% accuracy on all pairwise relationships proceeded to the neuroimaging sessions (see also Methods).

(**B**) MEG acquisition. Participants first underwent a five-minute resting-state scan (eyes open). They then performed a map-based inference task, in which each trial presented two objects (1.5 s each) separated by a 0.4–0.6 s interval. After the second object, a decision cue indicated the dimension (attack or defence) to be

compared, and participants had up to 2 s to choose the object with the higher rank. No feedback was given. This inference task was immediately followed by another five-minute resting-state scan, again with eyes open.

(**C**) Data analysis and hypothesis. MEG recordings from the resting-state scans were used to quantify neural replay of experiences and its relationship with dynamic activity across different resting-state networks, with a focus on the DMN. We investigated whether replay events aligned with DMN activation and whether this alignment changed with development. We further assessed the functional relevance of replay–DMN alignment by testing its relationship to grid-like code in the EC measured in fMRI (Qu et al., 2024).

**Stronger replay for representing 2D map in younger individuals**

We next examined neural replay patterns across ages. We first validated that the neural recording was not confounded by age-related factors. In developmental neuroscience studies such as this, potential confounds can arise from smaller head size in younger subjects (Brookes et al., 2018) or greater head movement in children (Wehner et al., 2008). For instance, smaller heads place the brain farther from the sensors, lowering the signal-to-noise ratio (SNR), while excessive movement degrades signal quality and introduces noise, along with other age-related factors. To address these issues, we evaluated the effects of head size and head movement on signal strength across our cohort (see Methods for details) and found they did not pose significant problems (see **Supplementary Note 1**). Moreover, we accounted for head size and head movement in all subsequent neural analyses to ensure the robustness of our results.

The replay detection pipeline begins with the neural decoding of stimuli during their visual presentation in the inference task (**Figure 2A**). Specifically, we trained object-specific decoders using task-evoked MEG data from all planar channels. For example, the decoder for the target object "book" showed higher predicted probabilities for "book" than for other decoders, indicating successful identification (**Figure 2B**). Decoding accuracy was highest when training and testing occurred at the same time point (**Figure 2C**). Across participants, cross-validated decoding accuracy peaked at around 300 ms after stimulus onset (one-sample $t$-test vs. chance, $t(97) = 12.622$, $p < 0.001$; **Figure 2D**). No significant correlation was observed between participant age and the timing of this peak ($r = -0.176$, $p = 0.08$). We therefore trained and tested decoders at the 300 ms peak for all subsequent analyses and for all subjects. Decoding accuracy at 300 ms was positively correlated with age ($r = 0.255$, $p = 0.011$; **Figure 2E**), and this relationship remained significant when controlling for head motion ($r = 0.220$, $p = 0.043$), head size ($r = 0.242$, $p = 0.016$), memory ($r = 0.245$, $p = 0.016$) and task ($r = 0.202$, $p = 0.047$) performances. These findings suggest that older participants demonstrated more distinct and robust neural representations of the objects during the task.

Using these decoders, we transformed resting-state MEG data into time series of reactivation probabilities for each object. We defined replay events as sequential patterns of object reactivation, quantified by the "sequenceness" measure from the temporally delayed linear modelling (TDLM) method (Liu et al., 2021). As in Ou et al. (2025), we classified replay experiences as either "1D replay", reflecting separate consolidation along a single dimension (for instance, "watch → tomato"), or "2D replay", reflecting adjacency on the hidden 2D map (for instance, "watch → scissors"; see also **Figure 2F**). If both 1D and 2D replays occurred,

participants would be consolidating each dimension separately. By contrast, if only 2D replay exists, as similar with Ou et al. (2025), it suggests replay represented a unified 2D map.

We found no evidence of 1D replay in pre-task or post-task rest (see **Supplementary Figure 2**). However, 2D replay did emerge during post-task rest (**Figure 2F–G**). Across all subjects, 2D replay was stronger than chance at 50–70 ms lags, controlling for multiple comparisons (**Figure 2G**). Across both pre-task and post-task rest, 2D replay peaked at a 50 ms lag, and we focused on this lag for all further analyses. Notably, 2D replay was significantly higher during post-task rest than during pre-task rest (paired-sample $t$-test, $t(97) = 3.065$, $p = 0.003$), suggesting that participants organised the inferred information into a 2D map after performing the inference task. Moreover, the increase in 2D replay from pre-task to post-task rest was negatively correlated with age ($r = -0.300$, $p = 0.003$; **Figure 2I**), and this relationship persisted after controlling for head movement ($r = -0.261$, $p = 0.017$), head size ($r = -0.306$, $p = 0.002$), memory ($r = -0.302$, $p = 0.003$) and task ($r = -0.304$, $p = 0.002$) performances. Younger participants thus displayed greater reliance on replay to represent the 2D map, whereas older participants engaged in less replay.

Because replay often associates with hippocampal ripples, we also checked whether 2D replay co-occurred with ripple-band (80–120 Hz) power increases. Indeed, 2D replay was accompanied by stronger ripple-band power compared to baseline (paired-sample $t$-test, $t(97) = 6.189$, $p < 0.001$; see also **Supplementary Figure 3**). Using generalised eigendecomposition (Ohki et al., 2024), we extracted a ripple-related component, and time-frequency analysis revealed increased high-frequency power around replay onset (**Figure 2H**). Across participants, this ripple power increase was negatively correlated with age ($r = -0.242$, $p = 0.016$), again indicating heavier replay engagement in younger participants. Taken together, these findings suggest that as individuals mature, they become less dependent on replay during rest for constructing the 2D map, possibly reflecting a shift toward more efficient, stable representations.

**Figure 2. Neural decoding accuracy and task-induced replay across ages.**

**(A)** Pipeline of neural replay analysis. Neural decoders were trained for each object using task-evoked MEG

data. These decoders were then applied to resting-state MEG data, transforming the raw neural signals into

time series of reactivation probability, which reflect the likelihood that neural activity corresponds to a specific

object at a given time. Replay was quantified by assessing the sequential activation patterns among objects.

Specifically, for a given time lag $\Delta t$, the reactivation probability of one object was used to predict the future

reactivation probability of all other objects. This resulted in empirical transition matrices, representing

observed transition probabilities between objects. Replay sequenceness was then defined as the regression

coefficient $\beta_{replay}$ obtained by comparing these empirical transition matrices with hypothesised transition

matrix. Statistical significance was determined by comparing $\beta_{replay}$ from empirical transitions to those from

randomly permuted transition matrices ($\beta_{permuted}$).

**(B)** Example of neural decoding. Object-specific neural decoders were trained and tested at every 10 ms

interval from stimulus onset to 800 ms, using task-evoked MEG data in sensor space. The example illustrates

the predicted probabilities for the object "book", decoded by 25 different decoders trained at 300 ms post-

stimulus onset. The probability predicted by the "book" decoder (black line) is higher than those predicted by

other decoders. The inset shows the sensor distribution and beta weights for the "book" decoder.

**(C)** Decoding accuracy across training and testing time points. Decoding accuracy was highest when training and testing were conducted at the same time point.

**(D)** Decoding accuracy over time. Cross-validation results showed that peak decoding accuracy was achieved at 300 ms post-stimulus onset. Error bars represent the group SEM. This peak was used as the basis for selecting neural decoders to detect replay during rest.

**(E)** Correlation between decoding accuracy and age. Decoding accuracy (with decoders trained at 300 ms) showed a significant positive correlation with age. The solid line represents the best-fitting line across participants, and the shaded area indicates the 95% confidence interval. Each dot represents an individual participant.

**(F)** Example 2D replay sequences. 2D replay is characterised by the sequential reactivation of nearby objects on the hidden 2D map. Representative 2D replay sequences from a younger and an older participant demonstrate that, in both cases, the activation of a starting object at time $t$ is followed by adjacent objects after a 50 ms interval. 2D replay was more pronounced in younger participants compared to older participants.

**(G)** 2D replay during rest. 2D replay during post-task rest was significantly higher than expected by chance (black dashed line indicates the permutation threshold) at time lags of 50–70 ms. Additionally, post-task replay was significantly higher than pre-task replay at the 50 ms lag. Error bars represent the group SEM. '**' for $p < 0.01$. See also **Supplementary Figure 2**.

**(H)** Extraction of ripple component. A neural component associated with ripple activity was extracted using a generalised eigendecomposition method (Ohki et al., 2024). Epoching this component around replay events revealed increased high-frequency power during replay, indicating replay-related modulation of ripple-band activity.

**(I)** Age-related decline in task-induced 2D replay. The change in 2D replay from pre-task to post-task rest (post minus pre) was negatively correlated with age, indicating a decline in task-induced replay in older participants. The solid line represents the best-fitting line across participants, and the shaded area indicates the 95% confidence interval. Each dot represents an individual participant.

**Distinct temporal and spectral characteristics of the DMN remain stable across ages**

Beyond replay processes, resting-state cortical dynamics also shape how the brain organises information during rest (Tambini et al., 2010). To investigate how replay–DMN coordination evolves from childhood to adulthood, we first needed to detect activation of RSNs from MEG data and examine their intrinsic dynamics. We used the TDE-HMM method (Vidaurre et al., 2018; see Methods for details). This approach models neural activity as latent states, each defined by a unique covariance matrix describing power and cross-spectra across brain regions. Parameters are estimated through Bayesian inference, yielding both state covariances and activation time-courses.

Specifically, the raw MEG data were reconstructed into source space (**Figure 3A**), parcellated into 38 regions of interest (**Supplementary Table 2**), and the resulting time series were input into TDE-HMM (Gohil et al., 2024). We then estimated power and coherence maps for each inferred state (see also **Supplementary Figure 4A**) and identified known brain networks based on their spatial patterns. To group similar states, we reordered state labels by their transition probabilities (**Supplementary Figure 4B, C**). Ultimately, we identified 12 RSNs. RSN state 1 corresponded to the DMN, primarily involving the medial prefrontal cortex (mPFC) and posterior cingulate cortex (PCC), a pattern robustly replicated across multiple datasets (van Es et al., 2023). RSN state 2 corresponded to the visual network (VIS), covering the occipital lobe. These two states are highlighted because of their temporal coordination with replay identified in prior literature (Higgins et al., 2021; Ji & Wilson, 2007) and in subsequent analyses. Activation probability time series were generated for each state, and the mutually exclusive nature of these states allowed us to produce a deterministic activation time series.

We then summarised the temporal and spectral characteristics of these RSNs. Temporally, we used the state activation time series to calculate fractional occupancy (the proportion of time spent in each state) and mean interval time (the average duration between consecutive state visits). Among all states, the DMN showed the lowest fractional occupancy and the longest mean interval (**Figure 3B**). Spectrally, for each state, we computed mean power and mean coherence across all brain regions and frequencies. The DMN exhibited the highest overall power and coherence, with peaks in the delta/theta and alpha bands (**Figure 3C, D**), and these patterns were replicated in factorised frequency bands (see **Supplementary Figure 4D**). Together, these observations highlight the distinctiveness of DMN relative to other RSNs across all subjects, including children, consistent with previous findings in adults (Higgins et al., 2021).

Notably, none of these general DMN properties correlated with age (**Figure 3E**). The temporal measures, including fractional occupancy, mean interval time, mean lifetime (average duration of state activation), switching rate (average number of state activations), and Fano factor (temporal irregularity), showed no significant relationships with age (all $p > 0.1$). Likewise, the spectral measures, including power ($r = 0.088$, $p = 0.387$) and coherence ($r = -0.061$, $p = 0.551$), also did not correlate with age. This suggests that the fundamental temporal and spectral characteristics of the DMN remain stable across development.

**Figure 3. Distinct temporal and spectral characteristics properties of the DMN remain stable across ages.**
**(A)** Identification of 12 RSNs using the TDE-HMM. Post-task resting-state MEG time series from all planar MEG channels were reconstructed into source space via an LCMV beamformer projection, with individual structural MRI coregistration to improve spatial resolution. The reconstructed data were then parcellated into 38 predefined regions of interest (see **Supplementary Table 2**). The HMM transformed these time series into probabilities of RSN-state activation. The model estimated covariance matrices (characterising the power spectrum within RSN states) and transition probabilities (describing dynamics between RSN states). RSN states were labelled based on their minimised distance. Thresholded power maps for state 1 (left, red, DMN) and state 2 (right, yellow, VIS) are presented. See also **Supplementary Figure 4A**.

**(B)** Temporal characteristics of RSN-state activation. RSN states are mutually exclusive, with one state having the highest activation probability at each time point, which can be used to generate binarised state activation

time series. This allows fractional occupancy and mean interval for each RSN state to be quantified. The DMN exhibited the lowest occupancy, and the longest intervals compared to other RSN states, with all paired-sample $t$-tests $p < 0.001$ after family-wise error correction. Violin plots display these distributions, with internal boxplots marking medians and quantiles across participants.

**(C)** Spectral characteristics of RSN-state activation. The DMN demonstrated the highest power and coherence across frequencies, featuring peaks in the delta/theta and alpha bands.

**(D)** Relationship between RSN power and coherence. Scatterplot showing the wideband, subject-averaged power and coherence per state. Each dot represents a value from specific brain regions in source-space data. The DMN maintained high power and coherence concurrently, distinguishing it from other RSN states.

**(E)** No significant relationship between general DMN characteristics and age. Key temporal (fractional occupancy, mean interval) and spectral (power, coherence) characteristics of the DMN showed no significant correlation with age. Dots represent observed correlation values across participants, with error bars indicating 95% confidence intervals. See **Supplementary Table 3** for correlation statistics.

**Replay–DMN alignment grows with age to support schema-based knowledge**

We next asked whether replay interacts with RSN activity, particularly the DMN, and how such replay–DMN coordination evolves through development. We also examined whether this alignment underpins grid-like schema representations in the EC, testing our central question of how replay transitions from direct associations to aligning new experiences with existing schemas.

Consistent with studies in adults (Higgins et al., 2021), we found that replay events were temporally aligned with increases in DMN activation across all participants (see **Figure 4A** for a representative example). At the group level, we observed a transient increase in activation probability in both the DMN and the VIS around replay events, peaking approximately 30 ms after replay onset (**Figure 4B**). Sign-flipping permutation tests confirmed the significance of these increases ($p < 0.001$; see Methods for details).

Next, we investigated whether replay-aligned DMN activation correlates with age. We defined replay-aligned DMN activation as the baseline-corrected DMN activation probability, centred on replay onsets (see Methods for details). For each participant, we extracted replay-aligned DMN activation at the group-level peak. We observed a significant positive correlation between age and replay-aligned DMN activation ($r = 0.281$, $p = 0.005$; **Figure 4C**), which persisted after controlling for head movement ($r = 0.316$, $p = 0.004$), head size ($r = 0.287$, $p = 0.004$), memory ($r = 0.277$, $p = 0.006$) and task ($r = 0.253$, $p = 0.012$) performances. Thus, as individuals mature, the coupling between replay events and DMN activity becomes stronger. Notably, this relationship was absent in other RSNs, including the VIS (see **Supplementary Figure 5A** for control analysis of the VIS), and was significantly stronger for the DMN than for the VIS, as confirmed by Steiger's $Z$-test ($Z = 2.546$, $p = 0.011$).

This strengthened replay–DMN coordination appears to facilitate aligning newly replayed content with pre-existing schemas. To support this idea, we examined a subset of participants ($N = 85$) who completed both the MEG task and a subsequent fMRI-based map inference task (Qu et al., 2024). In those subjects, we identified grid-like codes in the EC using fMRI, reflecting a 2D schematic representation of the task space. The strength of the EC grid-like code was significantly above chance (one-sample $t$-test, $t(84) = 4.197$, $p < 0.001$) and positively correlated with age ($r = 0.226$, $p = 0.038$), confirming earlier results (Qu et al., 2024). Crucially, in the same participants, replay-aligned DMN activation predicted the strength of the EC grid-like code ($r = 0.243$, $p = 0.025$; **Figure 4D**). An exploratory mediation analysis indicated that replay-aligned DMN activation during rest may mediate the relationship between age and grid-like code strength (indirect effect, $p = 0.069$).

To probe the neural mechanism underpinning this developmental shift, we explored how replay becomes increasingly coordinated with large-scale cortical dynamics. One potential mechanism is phase-based timing in the theta band, which has been linked to hippocampal–cortical communication and memory integration (Heusser et al., 2016; Fujisawa & Buzsáki, 2011). We hypothesised that the stronger replay–DMN alignment seen in older participants reflects more precise timing of replay relative to the ongoing theta rhythms, allowing more effective embedding of replayed content. We therefore analysed the theta phase (2–6 Hz, derived by non-negative matrix factorisation, Higgins et al., 2021; see also **Supplementary Figure 4D**) at which replay events occurred for each participant. Among all source-space regions, the PCC, a core DMN node, showed the highest theta power, so we focused on that region.

To address sign ambiguity in source-space MEG data (Vidaurre et al., 2016), we applied a sign-flipping procedure based on the power of theta troughs and peaks (see Methods for details) and validated it using a replay event-related phase-amplitude coupling analysis (see **Supplementary Figure 6**). We found a significant correlation between age and the replay event phase (circular-linear correlation, $\rho = 0.300$, $p = 0.012$), demonstrating that older participants had replay events more aligned with the theta trough.

We further characterised this developmental transition by splitting participants at the median age. Younger participants (age $<$ 15) had replay onsets near the theta peak, whereas older participants (age $\geq$ 15) were more aligned with the theta trough (**Figure 4E**). A Watson-Williams test confirmed that mean replay phases differed significantly between groups ($F(1, 96) = 36.013$, $p < 0.001$; **Figure 4F**, left), and a Rayleigh test showed that only older participants exhibited significant phase locking of replay events to the theta trough ($z = 7.547$, $p < 0.001$). Younger participants displayed no significant phase locking ($z = 1.473$, $p = 0.230$; **Figure 4F**, right).

To confirm that global theta oscillations alone did not drive the observed phase alignment, we conducted a control analysis by randomly shuffling decoder weights (see Methods for details). This generated random reactivations unrelated to actual replay, allowing us to test whether such random events would align with the theta trough. We found no correlation between age and replay phases derived from shuffled decoders (circular-linear correlation, $\rho = 0.159$, $p = 0.290$), indicating that the observed phase alignment is specific to genuine replay events rather than general theta dynamics.

Importantly, in older participants, replay events closer to the theta trough were accompanied by stronger DMN activation (circular-linear correlation, $\rho = 0.395$, $p = 0.022$), suggesting a functional role for theta phase in

coordinating replay–DMN interactions. This effect did not appear in younger participants ($\rho = 0.198$,

$p = 0.384$).

Overall, these findings reveal that replay–DMN alignment becomes increasingly synchronised with age, with

theta-phase locking emerging as a key mechanism. As subjects mature, replay events are timed more precisely

to the theta trough, leading to stronger DMN engagement and potentially more effective embedding of new

information into established grid-like schema representation.

**Figure 4. Replay–DMN alignment becomes stronger and more synchronised with age.**

**(A)** Example of replay–DMN alignment. An example from Subject 33 (196.8 s to 202.4 s) illustrates the

temporal coupling between replay and DMN activation. Replay quantifies the extent to which strong

reactivation of one object is immediately followed by strong reactivation of subsequent objects. The black line

represents the summed reactivation probability across all possible object transitions, with peaks marking replay

onsets. The inset shows reactivation probability after epoching around replay onsets, revealing a peak at time

$t$, followed by a secondary increase at $t + \Delta t$. The red line represents DMN activation. Their alignment

demonstrates how replay events (red inverted triangles) were consistently accompanied by DMN activation

(red colour).

**(B)** Changes in RSN-state activation around replay events. Replay events accompanied by a transient increase

in RSN-state activation, particularly in the DMN and VIS. This increase was observed from −0.2 s to 0.3 s

relative to replay onset (dashed black line), peaking around 30 ms after replay onset (dashed red line). Significance bars indicate time windows where RSN-state activation was significantly modulated by replay events ($p < 0.001$, permutation tests).

**(C)** Replay-aligned DMN activation positively correlates with age. The solid line represents the best-fitting line across participants, and the shaded area indicates the 95% confidence interval. Each dot represents an individual participant.

**(D)** Replay-aligned DMN activation positively correlates with grid-like code in the EC. Grid like code in EC was found in Qu et al. (2024) with the same set of participants using fMRI (see Methods for details). The solid line represents the best-fitting line across participants, and the shaded area indicates the 95% confidence interval. Each dot represents an individual participant.

**(E)** Theta phase coupling of replay events varies with age. Replay events became more phase-locked to the trough of theta oscillations with age. Participants were split into two groups based on median age for visualisation. In younger participants (age $< 15$, green), replay events were distributed across all phases, whereas in older participants (age $\geq 15$, blue), replay events were preferentially clustered in the theta trough. Each dot represents the mean theta phase of replay onsets for a participant.

**(F)** Stronger replay-aligned DMN activation occurs at the theta trough. Replay events showed a significant difference in phase distribution between younger and older participants (left panel, Watson-Williams test). Error bars represent the group SEM. Further analysis revealed that in younger participants, replay events were not systematically locked to specific theta phases (right panel, Rayleigh test). In contrast, in older participants, there was a significant clustering of replay events in the theta trough. More importantly, stronger replay-aligned DMN activation was observed when replay events occurred in the theta trough. Each dot represents the mean theta phase of replay onsets for a participant. '***' for $p < 0.001$.

**Age-related strengthening of DMN connectivity reduces replay reliance and improves inference**

Building on our observation that replay–DMN alignment becomes more pronounced and precisely timed with age, we examined whether broader connectivity features of the DMN contribute to these developmental changes. Specifically, we tested whether resting-state functional connectivity (rsFC) within the DMN, measured via fMRI, might support neural replay (observed in MEG) and inference performance.

Although the general temporal and spectral properties of the DMN from MEG-based analyses were stable across ages, earlier work has reported that rsFC within the DMN increases with development (Fair et al., 2009; Fan et al., 2021), potentially reflecting adaptive changes that facilitate memory processes (Sestieri et al., 2011; Xia et al., 2022). It is possible that age-related strengthening of DMN rsFC leads to more efficient representations of the cognitive map and thereby decreases reliance on replay mechanisms.

To test this idea, we employed connectome-based predictive modelling (CPM) (Scheinost et al., 2019; Shen et al., 2017) to determine whether rsFC within the DMN, derived from resting-state fMRI, could predict changes in 2D replay measured by MEG (**Figure 5A**; see Methods for details). Specifically, we constructed individual rsFC matrices by correlating the average BOLD signals from each voxel in the DMN, as defined by the Schaefer 400 atlas (Schaefer et al., 2018). We then performed leave-one-out cross-validation (LOOCV) at the participant level, applying feature selection within each training set to build a linear model predicting 2D replay strength in the left-out participant.

Our results showed that DMN rsFC significantly predicted the task-induced replay (Spearman's $\rho = 0.275$, $p = 0.007$; **Figure 5B**). Permutation tests supported the statistical significance of this prediction ($p = 0.034$). In contrast, rsFC within the VIS did not predict replay sequenceness (Spearman's $\rho = -0.031$, $p = 0.766$, see **Supplementary Figure 5B**), and the difference between DMN and VIS predictions was statistically significant (Steiger's $Z = 2.221$, $p = 0.026$). Further analysis of whole-brain rsFC revealed that connectivity within and across the DMN contributed most strongly to the predictive model (see **Supplementary Figure 5C**). Feature selection in CPM revealed specific DMN rsFC connections that robustly predicted 2D replay; averaging these connections yielded a summary index of DMN rsFC, which showed a significant positive correlation with age ($r = 0.313$, $p = 0.002$). This finding is consistent with earlier reports that DMN connectivity strengthens with development.

Finally, we conducted mediation analyses to determine whether DMN rsFC could explain the relationship between age, task-induced replay, and inference efficiency. We found that DMN rsFC fully mediated the age-

related reduction in 2D replay (indirect effect size, $d = -0.206$, 95% CI $[-0.314, -0.099]$, $p < 0.001$; **Figure 5C**, left panel). Thus, as DMN connectivity increases with age, it reduces reliance on replay for representing the 2D map. DMN rsFC also partially mediated the age-related improvement in inference efficiency, reflected in faster reaction times (indirect effect size, $d = -0.102$, 95% CI $[-0.200, -0.028]$, $p = 0.033$; **Figure 5C**, right panel). This suggests that greater DMN connectivity promotes more efficient inferential behaviour.

To rule out potential age-related confounds such as task engagement, fatigue, head motion, head size, or processing speed, we performed thorough complementary analyses, none of which explained the observed relationships (see **Supplementary Note 1** and **Supplementary Figures 7–10** for details). In summary, by integrating MEG and fMRI data, our results show that age-related increases in DMN connectivity, together with more precise replay–DMN alignment, are crucial for reducing reliance on replay alone and enhancing inference abilities.

**Figure 5. Age-related strengthening of DMN connectivity reduces replay reliance and improves inference.**

**(A)** Connectome-based predictive modelling of rsFC for predicting task-induced 2D replay. Resting-state fMRI data were used to construct rsFC matrices by correlating averaged BOLD signals from each voxel within the DMN, defined by the Schaefer 400 atlas. LOOCV was performed at the participant level, with feature selection conducted within the training set ($N - 1$ participants). A linear regression model was then built to predict the 2D replay strength of the left-out participant. Model performance was evaluated by the Spearman

correlation between predicted and observed replay values, with permutation tests (10,000 iterations) used to assess statistical significance.

**(B)** DMN rsFC predicts MEG-based task-induced 2D replay. The predicted replay strength positively correlated with the actual replay. The solid line denotes the best-fitting line across participants, and the shaded area shows the 95% confidence interval. Each dot represents one validation data point. Permutation tests further validated the significance.

**(C)** Mediating analysis of the DMN rsFC in fMRI. The strength of DMN rsFC fully mediated the age-related decrease in 2D replay (left panel) and partially mediated the age-related improvement in inference efficiency, reflected by faster reaction times (right panel). Insets show the spatial distribution of robust features (selected with frequency above 0.9) contributing to the predictive model.

## Discussion

Our study provides novel insights into developmental changes in neural replay and its coordination with the DMN. Specifically, younger participants showed a stronger reliance on replay during post-task rest, whereas older participants demonstrated increasingly precise replay–DMN coordination, which predicts EC grid-like code. These results indicate a gradual shift from replay alone towards more selective replay events timed to large-scale cortical dynamics.

In general, there are two ways of representing relational information (Behrens et al., 2018). One involves constructing a direct associative map, such as a successor representation derived by tracking experiences (Barron et al., 2020; Stachenfeld et al., 2017). The other approach entails aligning new experiences with a pre-existing schema, allowing more rapid assimilation (Tse et al., 2007; van Buuren et al., 2014). Recent work suggests that hippocampal replay can support both modes of map formation (Bakermans et al., 2025; Evans & Burgess, 2019; Ou et al., 2025). Consistent with this, children with less coherent grid schemas rely more on hippocampal mechanisms (Qu et al., 2024). Our finding that younger participants depended more on replay to represent the 2D map aligns with this view. In our context, replay integrates experiences into a 2D cognitive map, rather than simply repeating learned sequences. This suggests that younger participants may use replay to stabilise inferred relationships when schematic representations are still developing. Critically, this effect is not driven by changes in decoding accuracy, which in fact increased with age, likely reflecting more refined sensory representations in older individuals (Fandakova et al., 2019). Thus, replay may compensate for underdeveloped schematic frameworks in younger participants.

A key finding is that replay, although less strong in older participants, becomes more tightly aligned with DMN activity. This stronger replay–DMN synchrony predicts grid-like schema representations in the EC, implying that synchronising replay with the DMN facilitates the incorporation of reactivated experience content into higher-order schemas (Kaefer et al., 2022; Masís-Obando et al., 2022). Physiologically, older participants show more precise replay timing at the DMN theta trough, which we localised to the PCC. This region has well-documented structural and functional connectivity with the hippocampus and medial temporal lobe (Andrews-Hanna et al., 2010; Greicius et al., 2009) and acts as a hub for integrating memory-related signals and coordinating top-down influences across cortical networks (Alexander et al., 2023; Goddard et al., 2022). Recent studies further demonstrate that this PCC related cortical activity is time-locked to hippocampal ripples during sleep (Pedrosa et al., 2022; Swanson et al., 2025), suggesting that hippocampal–cortical interactions are modulated, in part, by ongoing cortical oscillations. Consistent with this, the theta trough is associated with

heightened excitability for hippocampal–cortical communication (Buzsáki & Draguhn, 2004; Fuentemilla et al., 2010; Sirota et al., 2008), potentially enabling more effective integration of replayed content into distributed cortical networks. It is also noteworthy that human theta rhythms are generally slower than those in rodents. In the present study, we defined theta as 2–6 Hz based on the spectral decomposition of resting-state cortical activity, and replay aligned with DMN theta rather than hippocampal theta (Kragel et al., 2020; Solomon et al., 2019), indicating a more network-level form of memory integration (Kaefer et al., 2022). Future work should clarify how replay and cortical theta coupling emerge at the neuronal-circuit level (Fernández-Ruiz et al., 2017; Xiao et al., 2024).

DMN resting-state functional connectivity also increases with age, explaining the observed developmental reduction in replay reliance and the improvement in inference efficiency. While the temporal and spectral features of the DMN appeared stable in our MEG analyses, fMRI-based connectivity measures showed an age-related rise in DMN cohesiveness, potentially providing a scaffold for integrating reactivated information into pre-existing knowledge structures (Xiao et al., 2025). Taken together, these findings suggest a broader interplay of hippocampal replay, cortical maturation, and temporal coordination that supports schema-based inference over development.

These results have broad implications for learning and memory development. Younger individuals' reliance on replay to stabilise new information points to the potential value of structured replay-based strategies, such as active recall or spaced repetition (Antony et al., 2017; Karpicke & Roediger, 2008; Wiklund-Hörnqvist et al., 2021). In contrast, older individuals with stronger DMN connectivity and more precise replay–DMN timing may benefit more from schema-focused approaches that leverage abstract reasoning (Aghayan Golkashani et al., 2021; Ramey et al., 2024; van Kesteren et al., 2012). Further investigation of individual differences in replay usage and DMN connectivity could refine educational strategies tailored to developmental stages.

In conclusion, our study highlights a developmental trajectory in which reliance on replay progressively transforms into an integrated replay–DMN mechanism, featuring precise theta phase alignment and enhanced DMN connectivity. This shift underlies the formation of grid schema representations and supports more efficient inferential reasoning. By elucidating how replay matures with age, we provide a mechanistic framework for understanding cognitive development and propose avenues for interventions aimed at optimising learning and memory consolidation across development.

## 1 Methods

## 2 Participants

The study comprised multiple sessions, including off-scan behavioural training, MEG scanning, and MRI

scanning. A total of 106 right-handed participants aged 8–25 years (mean ± SEM: 16.45 ± 0.61 years; 51

females, see also **Supplementary Table 1**) were recruited after qualifying in the training session. All

participants had normal or corrected-to-normal vision and reported no neurological disorders, brain injuries,

or developmental disabilities.

After the MEG scanning session, data from 98 participants were retained for analysis; eight were excluded due

to random behaviour or excessive head movement. The final sample for MEG analyses had similar

demographics (mean ± SEM: 16.40 ± 0.64 years; 49 females). Behavioural data and resting-state MEG data

from these 98 participants were used for all subsequent analyses. Of these, 96 participants completed the

resting-state fMRI scanning session. Following the resting-state fMRI scanning session, 85 participants who

completed the MEG experiment also took part in a task fMRI study probing the grid-like code of the 2D

knowledge map through development, as detailed in Qu et al. (2024).

Prior to participation, informed consent was obtained from all participants or their guardians, along with two

scanning safety checklists. The study adhered to the Declaration of Helsinki and was approved by the

Institutional Review Board of the Faculty of Psychology at Beijing Normal University (ethics number:

IRB_A_0051_2021002). Participants received monetary compensation upon completing the experiment.

Children were encouraged to participate through laboratory visits and developmental guidance.

## 20 Experimental design

The experiment consisted of three main sessions: off-scan behavioural training, MEG scanning, and MRI

scanning.

In the off-scan training session, participants underwent extensive behavioural training to learn a cognitive map.

Twenty-five objects were arranged in an unseen 5 × 5 2D grid, representing two attributes: attack power (AP)

and defence power (DP). Participants learned the power levels of each object along these two dimensions

separately through pairwise comparisons. For example, in a learning trial for the attack power dimension, two

objects (e.g., a key and a telescope) were presented simultaneously, and participants chose the object with

higher power. They gradually learned the true sequence through trial-and-error iterations. Importantly, the paired objects differed by one power level, resulting in 100 unique pairs for each dimension.

From the participants' perspective, the learned relationships could be represented as multiple one-dimensional (1D) sequences for each dimension or as a single integrated 2D map combining both dimensions. The learning order of the two dimensions and key-press assignments was balanced between participants. Extensive training over multiple days ensured that participants reached at least 80% accuracy, qualifying them for the subsequent scanning sessions. The overall training performance is summarised in **Supplementary Note 1**, while detailed descriptions of the training procedure can be found in Qu et al., 2024.

The MEG scanning session involved a five-minute pre-task rest, a map-based inference task, and a five-minute post-task rest. During the map-based inference task, participants were asked to infer which of two randomly selected objects had higher power in either the attack or defence dimension. Although this inference could be made using either 1D or 2D representations, utilising the integrated 2D map was expected to be more efficient. The task required participants to compare objects that were not directly adjacent in the learned sequences, encouraging the utilisation of the 2D map structure.

In each trial (**Figure 1B**), two objects were presented sequentially on the screen for 1.5 s each, with an inter-stimulus interval of 0.4–0.6 s. After both objects were shown, a decision cue indicated the dimension (attack or defence) for comparison. Participants had up to 2 s to respond by choosing the object with higher power on the cued dimension. An inter-trial interval of 0.4–0.6 s followed each response. The task consisted of 240 trials, divided into eight blocks (four blocks for each dimension). The inference order of the two dimensions and key-press assignments was balanced between participants, and object locations were counterbalanced within participants.

The MRI scanning session included T1-weighted structural imaging and a five-minute resting-state fMRI scan. Participants were instructed to keep their eyes open during all resting-state scans. Following these sessions, most participants proceeded to task-based fMRI scanning, which included additional cognitive map tasks detailed in Qu et al. (2024). These tasks involved more complex inferences requiring integration across dimensions and learning relationships with newly introduced objects.

Throughout the experiment, tasks were framed within a "monster tournament" storyline to engage participants and facilitate understanding. Clear instructions were provided, and participants confirmed their comprehension before entering the scanner. Post-scan debriefings ensured that all participants, including the youngest, had

understood and completed the tasks as intended. The MEG and resting-state fMRI sessions lasted approximately one hour per participant. Also, care was taken to ensure that all participants, including the youngest, fully understood the tasks, minimized fatigue during scanning, and controlled for other age-related confounding factors (see also **Supplementary Note 1**).

**MEG Data acquisition and preprocessing**

MEG data were collected using an Elekta Neuromag TRIUX system (Elekta, Helsinki, Finland), which comprises a sensor array of 102 magnetometers and 204 planar gradiometers. Data were sampled at a rate of 1000 Hz. Participants were seated comfortably in a magnetically shielded room to minimise environmental noise and artefacts. Head position was continuously monitored using head-position indicator coils, allowing for real-time tracking relative to the sensor array. The MEG scanning session began and ended with five-minute resting-state periods, interleaved with eight task runs, each lasting approximately three minutes.

MEG data preprocessing followed established protocols (Higgins et al., 2021; Liu et al., 2021), with adjustments made to accommodate the computational requirements of different analyses. Initial preprocessing involved the use of MaxFilter software (Elekta) to correct for head movement artefacts and reduce external noise through signal-space separation. A 0.5 Hz high-pass filter was applied to remove slow drifts, and notch filters were used to eliminate power line interference. The data were then down-sampled to 400 Hz.

Automated algorithms were employed to identify bad segments and channels. Independent component analysis (ICA) was performed on concatenated task and rest data to identify and remove artefactual components based on spatial topography, frequency spectra, and temporal patterns. After artefact removal, the data were further processed according to the specific requirements of subsequent analyses.

For replay detection, the preprocessed data were down-sampled to 100 Hz to reduce computational load while preserving temporal resolution sufficient for replay analysis.

For resting-state network modelling using the HMM, the data were coregistered with individual structural MRI scans to enable precise source localisation. The coregistered data were down-sampled to 250 Hz and bandpass-filtered between 1–45 Hz to focus on frequencies relevant to resting-state networks (Gohil et al., 2024). Source reconstruction was performed using a linearly constrained minimum variance (LCMV) beamformer, and the reconstructed signals were parcellated (taking the first principal component) into 38 predefined regions of interest (ROIs) based on the Harvard-Oxford atlas (Colclough et al., 2016; see **Supplementary Table 2**). To correct for source leakage, symmetric orthogonalisation was applied (Colclough et al., 2015). Dipole sign

ambiguity in the source-reconstructed data was resolved using a greedy algorithm that optimised lagged partial

correlations across time lags (Vidaurre et al., 2016), ensuring consistent signal alignment across participants.

**MRI Data Acquisition and Preprocessing**

MRI data were acquired using a Siemens Prisma 3 T MRI scanner with a 32-channel head coil. T1-weighted

structural images were collected using a 3D magnetisation-prepared rapid acquisition gradient echo sequence

with the following parameters: repetition time (TR) = 2.53 s, echo time (TE) = 2.98 ms, flip angle = 7°, field of

view (FoV) = 256 mm, slice thickness = 1 mm, and voxel size = $0.5 \times 0.5 \times 1$ mm³. Functional images were

acquired using a gradient-echo echo-planar imaging sequence (Ogawa et al., 1990) with TR = 3 s, TE = 30 ms,

flip angle = 90°, FoV = 192 mm, slice thickness = 3 mm, and voxel size = $3 \times 3 \times 3$ mm³. The five-minute

resting-state scan captured 100 whole-brain volumes. We acquired images with a 30° tilt relative to the

anterior-posterior commissure line to minimize signal loss in the orbitofrontal cortex (Weiskopf et al., 2006).

MRI data were preprocessed using fMRIPrep (version 20.2.7; Esteban et al., 2019), ensuring standardised and

reproducible results. Preprocessing steps included skull-stripping, bias-field correction, and spatial

normalisation to the MNI152NLin2009cAsym template at 2 mm resolution for the structural images.

Functional data preprocessing involved motion correction, slice-timing correction, and coregistration with T1-

weighted images. Spatial distortion correction was performed using the SyN-based susceptibility distortion

correction method. Confound regressors, including head motion estimates and signals from cerebrospinal fluid

and white matter, were calculated for later denoising. Outputs were generated in standard MNI space for group-

level analyses.

**Replay detection**

Replay detection was conducted using a temporally delayed linear modelling (TDLM) approach adapted from

Liu et al. (2021). The procedure involved two main steps: neural decoding to identify object-specific neural

patterns during the task, and detection of replay sequences during rest based on these patterns (**Figure 2A**).

In the neural decoding step, object-specific decoders were trained using task MEG data, as no independent

functional localiser was implemented. The task comprised 240 trials, with each object presented approximately

19 times. Sparse logistic regression classifiers with L1 regularisation were employed to identify neural patterns

corresponding to each object. Data from all MEG planar channels were epoched from stimulus onset to 800 ms

and used for decoding, with 10 ms time bin.

To determine the optimal time point for classifier training, a five-fold cross-validation was conducted, assessing classification accuracy at every 10 ms interval. Classifiers trained and tested at the same time point (i.e., along the diagonal of the temporal generalisation matrix) showed peak accuracy at 300 ms after stimulus onset (**Figure 2D**). Consequently, object-specific classifiers were retrained on the full task dataset at this time point for subsequent replay detection.

The trained classifiers were then applied to the resting-state MEG data to obtain object reactivation probability time series. Replay was defined as the sequential reactivation of specific objects in patterns reflecting the learned relationships. Two types of replay were investigated: two-dimensional (2D) replay and one-dimensional (1D) replay. In 2D replay, sequential reactivation occurred among objects adjacent on the 2D map, capturing the integrated representation of both dimensions (**Supplementary Figure 2A**). In contrast, 1D replay involved sequential reactivation along a single dimension (attack or defence), excluding neighbours on the 2D map to distinguish from 2D replay.

Replay quantification involved applying general linear regression to model the reactivation probabilities of objects at time $t + \Delta t$, based on the reactivation at time $t$, across all time points, with equation (1).

$$X_j(t + \Delta t) = \sum_{i=1}^{n} X_i(t) * \beta_{i,j} + C \qquad (1)$$

$X_j(t + \Delta t)$ is the reactivation probability of object $j$, at time $t_0 + \Delta t$, $X_i(t)$ is the reactivation probability of object $i$, at time $t$. $\beta_{i,j}$ represents the empirical transition matrix capturing observed transitions (with shape $N_{object} \times N_{object}$), and $C$ is a constant term.

The empirical transition matrix was predicted from the hypothesised transition matrices while controlling for confounds such as autocorrelation and mean activity. Each hypothesised matrix represented every possible transition permitted in either 2D or 1D replay and used binary entries to mark transferable transitions (set to one) and non-transferable transitions (set to zero). For instance, in **Figure 2F**, the transition "watch → scissors" is given a value of one, whereas "watch → tomato" is given a value of zero in the hypothesised 2D replay matrix. The complete equation for modelling the empirical matrix is provided below.

$$\beta = \sum_{r=1}^{r} Z(r) * T_r \qquad (2)$$

where $T_r$ represented hypothesised transition matrices, and $Z(r)$ was beta coefficient, representing the strength of alignment between empirical and hypothesised transitions, were interpreted as replay sequenceness.

To assess statistical significance, non-parametric permutation tests were employed. Hypothesised transition matrices were shuffled 1,000 times by randomly reassigning ones and zeros, and the prediction of the shuffled matrices to the empirical transition matrix was repeated, yielding a null distribution of replay sequenceness values. Replay sequenceness exceeding the 95th percentile of this null distribution was considered significant. Candidate time lags ranging from 10 ms to 600 ms in 10 ms increments were evaluated to identify the optimal replay speed, with corrections applied for multiple comparisons across time lags.

**Resting-state network modelling**

Resting-state networks were characterised using a time-delay embedded hidden Markov model (TDE-HMM) approach (Higgins et al., 2021; Vidaurre et al., 2018; Gohil et al., 2024). This method models brain activity as a sequence of latent states, each associated with distinct spectral and spatial properties.

At each time point $t$, the observed data $Y_t$ are assumed to be generated by a latent state $\theta_t$, with the probability $p(Y_t \mid \theta_t)$. The latent states evolve according to a Markov process, with transition probabilities $p(\theta_t \mid \theta_{t-1})$, which describe state transitions. This differs from the transition matrix used for replay quantification, which models reactivation probabilities between objects. The observation model uses time-embedded data vectors $vec(Y_{t-l:t+l})$, where $l$ defines the embedding window (set to $l = 7$), and $vec$ denotes vectorisation. Dimensionality reduction via principal component analysis (PCA) is applied for computational efficiency, retaining the top 80 components. Each state's observation model is characterised by a multivariate normal distribution with state-specific mean $m_k$ and covariance $C_k$, capturing both power spectra and coherence patterns, with equation (3).

$$p(vec(Y_{t-l:t+l}) \mid \theta = k) \sim \mathcal{N}(m_k, C_k) \tag{3}$$

Bayesian inference with stochastic gradient variational Bayes was employed to estimate model parameters, optimising both the observation model and transition probabilities. The model was trained five times with random initialisations to avoid local minima, selecting the solution with the lowest free energy.

The trained model provided activation probability time series for 12 RSN states, their spectral properties, and the transition probability matrix. RSN states were reordered based on minimising distances between states with

high transition probabilities. The most probable sequence of RSN states (Viterbi path) was computed,

assuming mutual exclusivity of states.

Temporal properties such as fractional occupancy, mean interval time, mean lifetime, switching rate, and Fano

factor were calculated for each RSN state. Spectral analyses involved computing mean power and coherence

across frequencies, with spatial distributions visualised for each state (**Supplementary Figure 4A**).

**Replay-aligned RSN-state activation**

To investigate whether replay events coincided with RSN-state activation, replay onset times were identified,

and RSN-state activation around these events was analysed.

Replay onsets were defined as times when the strong reactivation of one object was immediately followed by

the strong reactivation of the subsequent object in the sequence. Among all candidate time lags, the one

yielding the highest replay sequenceness was selected as the optimal time lag. Using the identified time lag,

we constructed the reactivation matrix $X$ and its time-shifted version $X(\Delta t)$. The original reactivation matrix

$X$ was then multiplied by the hypothesised transition matrix $T_r$, representing the expected unscrambled

sequences. Next, the $X \times T_r$ was element-wise multiplied with the time-shifted matrix $X(\Delta t)$, yielding a

matrix with each column corresponding to an object and each row representing a time point in the resting-state

data. To capture the strength of replay over time, we summed the values across columns, producing a long

vector $R$, with each element indicating the replay strength at a specific moment. We then applied a threshold

to $R$, selecting only values above the 99th percentile to define significant replay moments. To further ensure

temporal independence between replay events, we imposed a minimum gap between consecutive replay onsets,

ensuring that each onset was preceded by at least 100 ms without replay activity. Specifically,

$$21 \quad R_t = \sum_{i}^{n} (X \times T_r)_{ti} \circ X(\Delta t)_{ti} \tag{4}$$

Using the identified replay onsets and the activation probability time series for each RSN state, replay-aligned

RSN-state activation was analysed at the participant level. For each participant, the activation probability time

series of each RSN state was baseline-corrected by subtracting the average activation probability across all

time points within the session. This ensured that positive values reflected higher-than-average activation

probabilities, while negative values indicated lower-than-average activation probabilities. The corrected time

series was segmented into epochs centred around replay events, with a window spanning from 0.5 s before to

0.5 s after each event (0.2 s before to 0.3 s after for visualisations in **Figure 4**). The RSN-state activation

probabilities were averaged across these epochs for each participant. The mean of these averaged values across participants was computed to quantify the expected increase or decrease in RSN-state activation probability in response to replay events. To assess the statistical significance of replay-aligned RSN-state activation, a permutation-based approach was employed. Specifically, the sign of the activation probabilities was randomly flipped across trials 5,000 times to generate a null distribution. The observed mean activation probability was then compared against this null distribution to determine whether it exceeded the chance level. Statistical significance was set at $p < 0.001$.

**Grid-like code**

We applied representation similarity analysis (RSA) to examine grid-like neural representations (Bellmund et al., 2016; Kriegeskorte et al., 2008; the method used in this study is detailed in Qu et al., 2024). First, we built a model representational dissimilarity matrix (RDM) based on the angular differences between inferred directions, assuming that grid-like patterns would show greater similarity at specific angles (0–15° and 45–60°) due to the periodic nature of grid codes. Pairs of directions within these angles were considered similar (assigned a value of zero), while other pairs were marked as dissimilar (assigned a value of one). Next, we ran a whole-brain searchlight analysis. For each voxel, we estimated activity patterns by modelling separate regressors for each direction during the GLM analysis. We then calculated a neural RDM within a searchlight sphere around each voxel by measuring correlation distances between these patterns. Finally, we compared the model RDM to the neural RDM using Pearson's correlation, transformed these correlation values to $z$-scores, and mapped them back to the central voxel of each sphere for further analysis.

**Theta phase locking**

To investigate theta phase locking of replay events and its relationship with age and DMN properties, we extracted theta phases at replay onset from the source-space MEG data for each ROI. Using non-negative matrix factorisation (NNMF), we separated the frequency range of 1–45 Hz into four distinct bands, as illustrated in **Supplementary Figure 4D**. The theta band was defined as 2–6 Hz. The data utilised for constructing the Hidden Markov Model were filtered to the theta band and subsequently Hilbert transformed to obtain a time series of phases.

Source-space MEG data can exhibit sign ambiguity, resulting in uncertainty in phase estimation (Vidaurre et al., 2016). To mitigate this issue, we applied a sign-flipping procedure based on the premise that high gamma power is greater at the theta trough than at the theta peak (Canolty et al., 2006). The high gamma band was

defined as 80–120 Hz, corresponding to observed ripple band power increases (**Figure 2H**) and consistent with previous studies (Heusser et al., 2016). Following phase adjustment, we analysed the theta phases at replay onset.

A potential confound is that the global theta signal, representing activity across sensor space, could artificially inflate decoding accuracy at the theta peak and trough (Vidaurre et al., 2021). This might falsely suggest that replay events cluster around these phases even without true alignment. To address this, we conducted a control analysis by shuffling the decoder weights 1,000 times and using the shuffled decoders to decode the original resting-state MEG data. The resulting reactivation time series from the shuffled decoders were then used to identify replay onsets. This approach effectively disrupted the relationship between replay events and the true data while preserving the statistical structure of original signal. Replay onsets identified from the shuffled data did not show significant phase alignment with age, confirming that the observed replay onset phase alignment is not driven by global theta signal effects.

**Event-related phase-amplitude coupling**

Phase-amplitude coupling (PAC) was assessed to explore interactions between theta phase and gamma amplitude during replay events. PAC was computed using the Gaussian-Copula Mutual Information (GCMI) method (Combrisson et al., 2020; Ince et al., 2017), a non-parametric approach estimating mutual information between phase and amplitude components while accounting for their marginal distributions.

High-frequency gamma amplitudes (80–120 Hz) were extracted using bandpass filtering and the Hilbert transform. Theta phases (2–6 Hz) were obtained using overlapping 1 Hz steps to minimise frequency-specific artefacts. PAC values were calculated for each trial and participant.

Statistical significance was determined using an amplitude-shuffling procedure, generating a null distribution of PAC values by randomly reordering amplitude time series 200 times per trial. Observed PAC values were converted to $z$-scores, and group-level $t$-tests assessed significance across participants. Regions showing significant PAC ($p < 0.05$) were identified.

**Connectome-based predictive modelling**

Connectome-based predictive modelling (Scheinost et al., 2019; Shen et al., 2017) was employed to assess whether resting-state functional connectivity within the DMN could predict task-induced 2D replay sequenceness.

Using preprocessed fMRI data, BOLD time series from 400 brain regions (including 91 regions within the DMN) were extracted based on the Schaefer atlas (Schaefer et al., 2018). Pearson correlations between time series of each pair of regions were calculated and Fisher $z$-transformed to create individual rsFC matrices.

Leave-one-out cross-validation (LOOCV) was used to train and validate the predictive model. In each iteration, data from one participant were held out as the test set, and the remaining data formed the training set. Feature selection within the training set identified rsFC edges significantly correlated with replay sequenceness ($p < 0.001$). The sum of strengths of positively and negatively correlated edges served as predictors in a linear regression model.

Predicted replay sequenceness values were generated for each left-out participant. Model performance was evaluated using Spearman's correlation between predicted and actual replay sequenceness. Permutation tests with 10,000 iterations assessed the statistical significance by comparing model performance to a null distribution generated by shuffling replay sequenceness values. Statistical significance was established if the $p$-value from the permutation tests was less than 0.05.

**Mediation analysis**

To investigate whether DMN rsFC mediated the relationships between age, task-induced replay sequenceness, and inference efficiency, mediation analyses were conducted following standard procedures (Preacher & Hayes, 2004). The analysis aimed to determine whether the effect of the independent variable (e.g., age) on the dependent variable (e.g., replay sequenceness or inference efficiency) could be explained, in whole or in part, by the mediator variable (e.g., DMN rsFC).

Bootstrapping methods with 5,000 resamples were employed to generate 95% bias-corrected confidence intervals for the indirect effects, allowing for robust estimation of mediation effects without reliance on normality assumptions. All variables were mean-centred prior to analysis to facilitate interpretation, and standardised coefficients were reported to enable comparison across variables. An indirect effect was considered significant if its confidence interval did not include zero, indicating a reliable mediation effect. Statistical significance for individual paths in the mediation model was determined at the $p < 0.05$ level.

**Statistical analysis**

Statistical analyses were conducted using Python, employing the scipy.stats and statsmodels libraries for hypothesis testing and statistical modelling. Throughout the study, two-tailed $p$-values were used. Corrections

for multiple comparisons were applied where appropriate to control the family-wise error rate, particularly in analyses involving multiple time points or ROIs.

Correlation analyses were performed using Pearson's correlation coefficient ($r$) for normally distributed data and Spearman's rank correlation coefficient ($\rho$) for non-parametric data or when assessing monotonic relationships. These analyses examined relationships between variables such as age, decoding accuracy, replay sequenceness, and DMN rsFC.

For replay detection, non-parametric permutation tests were employed to assess the statistical significance of replay sequenceness. Hypothesised transition matrices were shuffled 1,000 times to generate null distributions, and corrections for multiple comparisons were applied across the range of time lags assessed (10 ms to 600 ms in 10 ms increments). Replay sequenceness exceeding the 95th percentile of the maximum values from the null distributions was considered statistically significant.

To evaluate replay-aligned RSN-state activation and phase-amplitude coupling, permutation-based approaches were used. For RSN-state activation, the sign of activation probabilities was randomly flipped across trials 5,000 times to create a null distribution, and statistical significance was set at $p < 0.001$. For PAC analysis, an amplitude-shuffling procedure with 200 repetitions per trial generated null distributions, and observed PAC values were converted to $z$-scores for statistical testing. Within-subject and group-level statistics were calculated, with significance determined at $p < 0.05$.

Circular statistics were employed for analyses involving angular data, such as theta phase locking. The Rayleigh test was used as a one-sample test for non-uniformity of circular data, assessing whether replay events occurred preferentially at specific phases. The Watson-Williams test served as a circular analogue of the two-sample $t$-test, comparing mean phases between age groups. Circular-linear correlation coefficients were calculated to assess relationships between angular variables and linear variables like age.

In the connectome-based predictive modelling, model performance was evaluated using Spearman's correlation between predicted and actual values of task-induced replay sequenceness. Permutation tests with 10,000 iterations assessed the robustness of the predictive models by comparing the observed performance to that expected by chance. Statistical significance was established if the $p$-value from the permutation tests was less than 0.05.

For mediation analyses, bootstrapping methods with 5,000 resamples were used to estimate indirect effects and generate 95% bias-corrected confidence intervals. An indirect effect was considered significant if the

confidence interval did not include zero. Variables were mean-centred, and standardised coefficients were reported to facilitate comparison across variables.

To compare the strength of two dependent correlation coefficients (i.e., correlations sharing one variable), Steiger's $Z$-test was used. This test assessed whether the difference between two correlations was statistically significant. For example, between age and replay–DMN alignment versus age and replay–VIS alignment. All comparisons were two-tailed, and statistical significance was set at $p < 0.05$.

## Acknowledgment

Conceptualisation, Y.L., Y.Q., L.P., and T.B.; Investigation, L.P., Y.Q., J.O., S.W., Y.L., C.G., M.W, and T.B.; Writing — Original Draft, L.P., Y.L.; Writing — Review & Editing, Y.L., L.P., Y.Q., T.B. This study is supported by the National Science and Technology Innovation 2030 Major Program (2022ZD0205500), the National Natural Science Foundation of China (32271093), the Beijing Natural Science Foundation (Z230010, L222033), and the Fundamental Research Funds for the Central Universities.

## Conflict of interest

The authors have indicated they have no potential conflicts of interest to disclose.

## Data availability

MEG, fMRI and behavioural data that support the conclusions in this study will be available on http://zenodo.org/uploads/14177579 upon publication.

## Code availability

The analysis code will be publicly available on https://gitlab.com/liu_lab/replay_development upon publication.

# References

Aghayan Golkashani, H., Leong, R. L. F., Wong, K. F., & Chee, M. W. L. (2021). Schema-driven memory benefits boost transitive inference in older adults. *Psychology and aging*, *36*(4), 463–474.

Alexander, A. S., Place, R., Starrett, M. J., Chrastil, E. R., & Nitz, D. A. (2023). Rethinking retrosplenial cortex: Perspectives and predictions. *Neuron*, *111*(2), 150–175.

Andrews-Hanna, J. R., Reidler, J. S., Sepulcre, J., Poulin, R., & Buckner, R. L. (2010). Functional-anatomic fractionation of the brain's default network. *Neuron*, *65*(4), 550–562.

Antony, J. W., Ferreira, C. S., Norman, K. A., & Wimber, M. (2017). Retrieval as a Fast Route to Memory Consolidation. *Trends in cognitive sciences*, *21*(8), 573–576.

Bakermans, J. J. W., Warren, J., Whittington, J. C. R., & Behrens, T. E. J. (2025). Constructing future behavior in the hippocampal formation through composition and replay. *Nature neuroscience*, 10.1038/s41593-025-01908-3.

Barron, H. C., Reeve, H. M., Koolschijn, R. S., Perestenko, P. V., Shpektor, A., Nili, H., Rothaermel, R., Campo-Urriza, N., O'Reilly, J. X., Bannerman, D. M., Behrens, T. E. J., & Dupret, D. (2020). Neuronal Computation Underlying Inferential Reasoning in Humans and Mice. *Cell*, *183*(1), 228–243.e21.

Behrens, T. E., Muller, T. H., Whittington, J. C., Mark, S., Baram, A. B., Stachenfeld, K. L., & Kurth-Nelson, Z. (2018). What is a cognitive map? Organizing knowledge for flexible behavior. *Neuron*, *100*(2), 490–509.

Bellmund, J. L., Deuker, L., Navarro Schröder, T., & Doeller, C. F. (2016). Grid-cell representations in mental simulation. *Elife*, *5*, e17089.

Brookes, M. J., Groom, M. J., Liuzzi, L., Hill, R. M., Smith, H. J. F., Briley, P. M., Hall, E. L., Hunt, B. A. E., Gascoyne, L. E., Taylor, M. J., Liddle, P. F., Morris, P. G., Woolrich, M. W., & Liddle, E. B. (2018). Altered temporal stability in dynamic neural networks underlies connectivity changes in neurodevelopment. *NeuroImage*, *174*, 563–575.

Buysse, D. J., Reynolds, C. F., 3rd, Monk, T. H., Berman, S. R., & Kupfer, D. J. (1989). The Pittsburgh Sleep Quality Index: a new instrument for psychiatric practice and research. *Psychiatry research*, *28*(2), 193–213.

Buzsáki, G., & Draguhn, A. (2004). Neuronal oscillations in cortical networks. *Science*, *304*(5679), 1926–1929.

Canolty, R. T., Edwards, E., Dalal, S. S., Soltani, M., Nagarajan, S. S., Kirsch, H. E., Berger, M. S., Barbaro, N. M., & Knight, R. T. (2006). High gamma power is phase-locked to theta oscillations in human neocortex. *Science*, *313*(5793), 1626–1628.

Carr, M. F., Jadhav, S. P., & Frank, L. M. (2011). Hippocampal replay in the awake state: a potential substrate for memory consolidation and retrieval. *Nature neuroscience*, *14*(2), 147–153.

Colclough, G. L., Brookes, M. J., Smith, S. M., & Woolrich, M. W. (2015). A symmetric multivariate leakage correction for MEG connectomes. *Neuroimage*, *117*, 439–448.

Colclough, G. L., Woolrich, M. W., Tewarie, P. K., Brookes, M. J., Quinn, A. J., & Smith, S. M. (2016). How reliable are MEG resting-state connectivity metrics? *Neuroimage*, *138*, 284–293.

Combrisson, E., Nest, T., Brovelli, A., Ince, R. A. A., Soto, J. L. P., Guillot, A., & Jerbi, K. (2020). Tensorpac: An open-source Python toolbox for tensor-based phase-amplitude coupling measurement in electrophysiological brain signals. *PLoS computational biology*, *16*(10), e1008302.

Constantinescu, A. O., O'Reilly, J. X., & Behrens, T. E. J. (2016). Organizing conceptual knowledge in humans with a gridlike code. *Science*, *352*(6292), 1464–1468.

Diba, K., & Buzsáki, G. (2007). Forward and reverse hippocampal place-cell sequences during ripples. *Nature neuroscience*, *10*(10), 1241–1242.

Doeller, C. F., Barry, C., & Burgess, N. (2010). Evidence for grid cells in a human memory network. *Nature*, *463*(7281), 657–661.

Esteban, O., Markiewicz, C. J., Blair, R. W., Moodie, C. A., Isik, A. I., Erramuzpe, A., Kent, J. D., Goncalves, M., DuPre, E., Snyder, M., et al. (2019). fMRIPrep: A robust preprocessing pipeline for functional MRI. *Nature Methods*, *16*(1), 111–116.

Evans, T., & Burgess, N. (2019). Coordinated hippocampal-entorhinal replay as structural inference. *Advances in Neural Information Processing Systems*, *32*.

Ezama, L., Hernández-Cabrera, J. A., Seoane, S., Pereda, E., & Janssen, N. (2021). Functional connectivity of the hippocampus and its subfields in resting-state networks. *European Journal of Neuroscience*, *53*(10), 3378–3393.

Fair, D. A., Cohen, A. L., Dosenbach, N. U., Church, J. A., Miezin, F. M., Barch, D. M., Raichle, M. E., Petersen, S. E., & Schlaggar, B. L. (2008). The maturing architecture of the brain's default network. *Proceedings of the National Academy of Sciences of the United States of America*, *105*(10), 4028–4032.

Fair, D. A., Cohen, A. L., Power, J. D., Dosenbach, N. U., Church, J. A., Miezin, F. M., Schlaggar, B. L., & Petersen, S. E. (2009). Functional brain networks develop from a "local to distributed" organization. *PLoS Computational Biology*, *5*(5), e1000381.

Fandakova, Y., Leckey, S., Driver, C. C., Bunge, S. A., & Ghetti, S. (2019). Neural specificity of scene representations is related to memory performance in childhood. *NeuroImage*, *199*, 105–113.

Fan, F., Liao, X., Lei, T., Zhao, T., Xia, M., Men, W., Wang, Y., Hu, M., Liu, J., Qin, S., Tan, S., Gao, J. H., Dong, Q., Tao, S., & He, Y. (2021). Development of the default-mode network during childhood and adolescence: A longitudinal resting-state fMRI study. *NeuroImage*, *226*, 117581.

Farooq, U., & Dragoi, G. (2019). Emergence of preconfigured and plastic time-compressed sequences in early postnatal development. *Science*, *363*(6423), 168–173.

Fernández-Ruiz, A., Oliva, A., Nagy, G. A., Maurer, A. P., Berényi, A., & Buzsáki, G. (2017). Entorhinal-CA3 Dual-Input Control of Spike Timing in the Hippocampus by Theta-Gamma Coupling. *Neuron*, *93*(5), 1213–1226.

Fuentemilla, L., Penny, W. D., Cashdollar, N., Bunzeck, N., & Düzel, E. (2010). Theta-coupled periodic replay in working memory. *Current biology*, *20*(7), 606–612.

Fujisawa, S., & Buzsáki, G. (2011). A 4 Hz oscillation adaptively synchronizes prefrontal, VTA, and hippocampal activities. *Neuron*, *72*(1), 153–165.

Goddard, E., Contini, E. W., & Irish, M. (2022). Exploring Information Flow from Posteromedial Cortex during Visuospatial Working Memory: A Magnetoencephalography Study. *The Journal of neuroscience*, *42*(30), 5944–5955.

Gohil, C., Huang, R., Roberts, E., van Es, M. W. J., Quinn, A. J., Vidaurre, D., & Woolrich, M. W. (2024). osl-dynamics, a toolbox for modeling fast dynamic brain activity. *Elife*, *12*, RP91949.

Greicius, M. D., Supekar, K., Menon, V., & Dougherty, R. F. (2009). Resting-state functional connectivity reflects structural connectivity in the default mode network. *Cerebral cortex*, *19*(1), 72–78.

Heusser, A. C., Poeppel, D., Ezzyat, Y., & Davachi, L. (2016). Episodic sequence memory is supported by a theta–gamma phase code. *Nature neuroscience*, *19*(10), 1374–1380.

Higgins, C., Liu, Y., Vidaurre, D., Kurth-Nelson, Z., Dolan, R., Behrens, T., & Woolrich, M. (2021). Replay bursts in humans coincide with activation of the default mode and parietal alpha networks. *Neuron*, *109*(5), 882–893.

Ince, R. A., Giordano, B. L., Kayser, C., Rousselet, G. A., Gross, J., & Schyns, P. G. (2017). A statistical framework for neuroimaging data analysis based on mutual information estimated via a gaussian copula. *Human brain mapping*, *38*(3), 1541–1573.

Ji, D., & Wilson, M. A. (2007). Coordinated memory replay in the visual cortex and hippocampus during sleep. *Nature neuroscience*, *10*(1), 100–107.

Johnson, B. W., & He, W. (2019). MEG studies on the connectivity of brain networks in children. *Magnetoencephalography: From signals to dynamic cortical networks*, 733–756.

Kaefer, K., Stella, F., McNaughton, B. L., & Battaglia, F. P. (2022). Replay, the default mode network and the cascaded memory systems model. *Nature Reviews Neuroscience*, *23*(10), 628–640.

Kaplan, R., Adhikari, M. H., Hindriks, R., Mantini, D., Murayama, Y., Logothetis, N. K., & Deco, G. (2016). Hippocampal sharp-wave ripples influence selective activation of the default mode network. *Current Biology*, *26*(5), 686–691.

Karpicke, J. D., & Roediger, H. L., 3rd (2008). The critical importance of retrieval for learning. *Science*, *319*(5865), 966–968.

Kragel, J. E., VanHaerents, S., Templer, J. W., Schuele, S., Rosenow, J. M., Nilakantan, A. S., & Bridge, D. J. (2020). Hippocampal theta coordinates memory processing during visual exploration. *Elife*, *9*, e52108.

Kriegeskorte, N., Mur, M., & Bandettini, P. (2008). Representational similarity analysis - connecting the branches of systems neuroscience. *Frontiers in systems neuroscience*, *2*, 4.

Liu, Y., Dolan, R. J., Higgins, C., Penagos, H., Woolrich, M. W., Ólafsdóttir, H. F., Barry, C., Kurth-Nelson,

Z., & Behrens, T. E. (2021). Temporally delayed linear modelling (TDLM) measures replay in both animals

and humans. *Elife*, *10*, e66917.

Liu, Y., Dolan, R. J., Kurth-Nelson, Z., & Behrens, T. E. J. (2019). Human Replay Spontaneously Reorganizes

Experience. *Cell*, *178*(3), 640–652.e14.

Masís-Obando, R., Norman, K. A., & Baldassano, C. (2022). Schema representations in distinct brain networks

support narrative memory during encoding and retrieval. *Elife*, *11*, e70445.

Muessig, L., Lasek, M., Varsavsky, I., Cacucci, F., & Wills, T. J. (2019). Coordinated Emergence of

Hippocampal Replay and Theta Sequences during Post-natal Development. *Current biology*, *29*(5), 834–

840.e4.

Norman, Y., Raccah, O., Liu, S., Parvizi, J., & Malach, R. (2021). Hippocampal ripples and their coordinated

dialogue with the default mode network during recent and remote recollection. *Neuron*, *109*(17), 2767–2780.e5.

Ogawa, S., Lee, T. M., Nayak, A. S., & Glynn, P. (1990). Oxygenation-sensitive contrast in magnetic

resonance image of rodent brain at high magnetic fields. *Magnetic resonance in medicine*, *14*(1), 68–78.

Ohki, T., Chao, Z. C., Takei, Y., Kato, Y., Sunaga, M., Suto, T., Tagawa, M., & Fukuda, M. (2024).

Multivariate sharp-wave ripples in schizophrenia during awake state. *Psychiatry and clinical neurosciences*,

*78*(9), 507–516.

Olsen, G. M., Ohara, S., Iijima, T., & Witter, M. P. (2017). Parahippocampal and retrosplenial connections of

rat posterior parietal cortex. *Hippocampus*, *27*(4), 335–358.

Ou, J., Qu, Y., Xu, Y., Xiao, Z., Behrens, T., & Liu, Y. (2025). Replay builds an efficient cognitive map offline

to avoid computation online. *bioRxiv*, 2025.01.08.632067.

Park, S. A., Miller, D. S., & Boorman, E. D. (2021). Inferences on a multidimensional social hierarchy use a

grid-like code. *Nature neuroscience*, *24*(9), 1292–1301.

Pedrosa, R., Nazari, M., Mohajerani, M. H., Knöpfel, T., Stella, F., & Battaglia, F. P. (2022). Hippocampal

gamma and sharp wave/ripples mediate bidirectional interactions with cortical networks during sleep.

*Proceedings of the National Academy of Sciences of the United States of America*, *119*(44), e2204959119.

Pfeiffer, B. E., & Foster, D. J. (2013). Hippocampal place-cell sequences depict future paths to remembered

goals. *Nature*, *497*(7447), 74–79.

Piaget, J. (1952). The origins of intelligence in children. *International University*.

Preacher, K. J., & Hayes, A. F. (2004). SPSS and SAS procedures for estimating indirect effects in simple

mediation models. *Behavior research methods, instruments, & computers*, *36*(4), 717–731.

Qu, Y., Ou, J., Pang, L., Wu, S., Luo, Y., Behrens, T. E., & Liu, Y. (2024). Development of Non-Spatial Grid-

Like Neural Codes Predicts Inference and Intelligence. *bioRxiv*, 2024.11.20.624569.

Ramey, M. M., Yonelinas, A. P., & Henderson, J. M. (2024). How schema knowledge influences memory in

older adults: Filling in the gaps, or leading memory astray?. *Cognition*, *250*, 105826.

Schaefer, A., Kong, R., Gordon, E. M., Laumann, T. O., Zuo, X.-N., Holmes, A. J., Eickhoff, S. B., & Yeo, B. T. (2018). Local-global parcellation of the human cerebral cortex from intrinsic functional connectivity MRI. *Cerebral Cortex*, *28*(9), 3095–3114.

Scheinost, D., Noble, S., Horien, C., Greene, A. S., Lake, E. M., Salehi, M., Gao, S., Shen, X., O'Connor, D., Barron, D. S., et al. (2019). Ten simple rules for predictive modeling of individual differences in neuroimaging. *NeuroImage*, *193*, 35–45.

Schuck, N. W., & Niv, Y. (2019). Sequential replay of nonspatial task states in the human hippocampus. *Science*, *364*(6447), eaaw5181.

Schwartenbeck, P., Baram, A., Liu, Y., Mark, S., Muller, T., Dolan, R., Botvinick, M., Kurth-Nelson, Z., & Behrens, T. (2023). Generative replay underlies compositional inference in the hippocampal-prefrontal circuit. *Cell*, *186*(22), 4885–4897.e14.

Sestieri, C., Corbetta, M., Romani, G. L., & Shulman, G. L. (2011). Episodic memory retrieval, parietal cortex, and the default mode network: functional and topographic analyses. *The Journal of neuroscience*, *31*(12), 4407–4420.

Shen, X., Finn, E. S., Scheinost, D., Rosenberg, M. D., Chun, M. M., Papademetris, X., & Constable, R. T. (2017). Using connectome-based predictive modeling to predict individual behavior from brain connectivity. *Nature Protocols*, *12*(3), 506–518.

Sirota, A., Montgomery, S., Fujisawa, S., Isomura, Y., Zugaro, M., & Buzsáki, G. (2008). Entrainment of neocortical neurons and gamma oscillations by the hippocampal theta rhythm. *Neuron*, *60*(4), 683–697.

Solomon, E. A., Stein, J. M., Das, S., Gorniak, R., Sperling, M. R., Worrell, G., Inman, C. S., Tan, R. J., Jobst, B. C., Rizzuto, D. S., & Kahana, M. J. (2019). Dynamic Theta Networks in the Human Medial Temporal Lobe Support Episodic Memory. *Current biology*, *29*(7), 1100–1111.e4.

Skaggs, W. E., & McNaughton, B. L. (1996). Replay of neuronal firing sequences in rat hippocampus during sleep following spatial experience. *Science*, *271*(5257), 1870–1873.

Stachenfeld, K. L., Botvinick, M. M., & Gershman, S. J. (2017). The hippocampus as a predictive map. *Nature neuroscience*, *20*(11), 1643–1653.

Supekar, K., Uddin, L. Q., Prater, K., Amin, H., Greicius, M. D., & Menon, V. (2010). Development of functional and structural connectivity within the default mode network in young children. *Neuroimage*, *52*(1), 290–301.

Swanson, R. A., Chinigò, E., Levenstein, D., Vöröslakos, M., Mousavi, N., Wang, X. J., Basu, J., & Buzsáki, G. (2025). Topography of putative bi-directional interaction between hippocampal sharp-wave ripples and neocortical slow oscillations. *Neuron*, *113*(5), 754–768.e9.

Tambini, A., Ketz, N., & Davachi, L. (2010). Enhanced brain correlations during rest are related to memory for recent experiences. *Neuron*, *65*(2), 280–290.

Tolman, E. C. (1948). Cognitive maps in rats and men. *Psychological Review*, *55*(4), 189.

Tse, D., Langston, R. F., Kakeyama, M., Bethus, I., Spooner, P. A., Wood, E. R., Witter, M. P., & Morris, R. G. (2007). Schemas and memory consolidation. *Science*, *316*(5821), 76–82.

van Buuren, M., Kroes, M. C., Wagner, I. C., Genzel, L., Morris, R. G., & Fernández, G. (2014). Initial investigation of the effects of an experimentally learned schema on spatial associative memory in humans. *The Journal of neuroscience*, *34*(50), 16662–16670.

van Es, M. W., Higgins, C., Gohil, C., Quinn, A. J., Vidaurre, D., & Woolrich, M. W. (2023). Large-scale cortical networks are organized in structured cycles. *bioRxiv*, 2023-07.

van Kesteren, M. T., Ruiter, D. J., Fernández, G., & Henson, R. N. (2012). How schema and novelty augment memory formation. *Trends in neurosciences*, *35*(4), 211–219.

Vaz, A. P., Wittig, J. H., Jr, Inati, S. K., & Zaghloul, K. A. (2020). Replay of cortical spiking sequences during human memory retrieval. *Science*, *367*(6482), 1131–1134.

Vidaurre, D., Cichy, R. M., & Woolrich, M. W. (2021). Dissociable Components of Information Encoding in Human Perception. *Cerebral cortex*, *31*(12), 5664–5675.

Vidaurre, D., Hunt, L. T., Quinn, A. J., Hunt, B. A., Brookes, M. J., Nobre, A. C., & Woolrich, M. W. (2018). Spontaneous cortical activity transiently organises into frequency specific phase-coupling networks. *Nature Communications*, *9*(1), 2987.

Vidaurre, D., Quinn, A. J., Baker, A. P., Dupret, D., Tejero-Cantero, A., & Woolrich, M. W. (2016). Spectrally resolved fast transient brain states in electrophysiological data. *NeuroImage*, *126*, 81–95.

Ward, A. M., Schultz, A. P., Huijbers, W., Van Dijk, K. R., Hedden, T., & Sperling, R. A. (2014). The parahippocampal gyrus links the default-mode cortical network with the medial temporal lobe memory system. *Human Brain Mapping*, *35*(3), 1061–1073.

Wehner, D. T., Hämäläinen, M. S., Mody, M., & Ahlfors, S. P. (2008). Head movements of children in MEG: quantification, effects on source estimation, and compensation. *NeuroImage*, *40*(2), 541–550.

Whittington, J. C. R., McCaffary, D., Bakermans, J. J. W., & Behrens, T. E. J. (2022). How to build a cognitive map. *Nature neuroscience*, *25*(10), 1257–1272.

Wiklund-Hörnqvist, C., Stillesjö, S., Andersson, M., Jonsson, B., & Nyberg, L. (2021). Retrieval practice facilitates learning by strengthening processing in both the anterior and posterior hippocampus. *Brain and behavior*, *11*(1), e01909.

Xia, Y., Xia, M., Liu, J., Liao, X., Lei, T., Liang, X., Zhao, T., Shi, Z., Sun, L., Chen, X., et al. (2022). Development of functional connectome gradients during childhood and adolescence. *Science Bulletin*, *67*(10), 1049–1061.

Xiao, Q., Lu, M., Zhang, X., Guan, J., Li, X., Wen, R., Wang, N., Qian, L., Liao, Y., Zhang, Z., Liao, X., Jiang, C., Yue, F., Ren, S., Xia, J., Hu, J., Luo, F., Hu, Z., & He, C. (2024). Isolated theta waves originating from the midline thalamus trigger memory reactivation during NREM sleep in mice. *Nature communications*, *15*(1), 9231.

1    Xiao, Z., Wang, X., Zhang, J., Ou, J., He, L., Qu, Y., Hu, X., Behrens, T., & Liu, Y. (2025). Human
2    hippocampal ripples predict the alignment of experience to a grid-like schema. *bioRxiv*, 2025.01.08.632069.

# Supplementary Information

**Supplementary Figure 1. Task performances in map-based inference and general reasoning ability.**

**(A)** Accuracy (left) and reaction time (right) in the map-based inference task showed no difference between the attack (AP) and defence (DP) dimensions. Error bars represent the group SEM. 'ns' for non-significant.

**(B)** Relationship between reasoning ability and map-based inference task performance: Accuracy positively correlated with the Advanced Progressive Matrices (APM) score (left), while reaction time negatively correlated with the APM score (right). The solid line represents the best-fitting line across participants, and the shaded area indicates the 95% confidence interval. Each dot represents an individual participant.

**Supplementary Figure 2. No 1D replay detected in post-task rest.**

**(A)** An illustration of 2D replay. 2D replay starts from the object in the red frame and targets the blacked objects. In 2D replay, these targets are adjacent to the starting object in the 2D space formed by the AP and DP dimensions.

**(B)** Illustrations of three types of 1D replay: 1D replay of the attack power dimension (left), defence power dimension (middle), and the combination of both (right). In 1D replay, target objects are one level away from the starting object in either the AP or DP dimension, excluding stimuli that are neighbours in the 2D map, to distinguish from 2D replay.

**(C)** Unlike 2D replay, replay sequenceness for all types of 1D replay fell below the permutation threshold (dashed black line). No replay of 1D was observed. The shaded area represents the group SEM.

**Supplementary Figure 3. Increased high-frequency band power around replay events.**

High-frequency power increase associated with replay events. Left: The onset of replay events is associated

with an increase in high-frequency power relative to the global average (mean ± SEM over participants). Right:

Replay-aligned power was computed by taking 100 ms windows of data around identified replay onsets. The

averaged replay-aligned power in the 80–120 Hz band is significantly higher than the baseline. '***' for

$p < 0.001$.

**Supplementary Figure 4. The broadband power and phase-locking network properties of all RSN states.**

**(A)** Visualisation of RSN states. Twelve RSN states were identified from the post-task resting MEG time series, using the HMM with time-delayed embedding (Vidaurre et al., 2018). Each RSN state corresponds to a distinct power distribution and phase-locking pattern between ROIs. The power maps (sagittal view) and the phase-locking maps of each RSN state are plotted in each cell. The power maps were normalised across all states by subtracting the mean, and the phase-locking maps were thresholded using a Gaussian mixture model.

**(B)** RSN-state transition probability matrix. This matrix illustrates the likelihood of transitioning from one state at time $t$ (horizontal axis) to another state at time $t + 1$ (vertical axis). Each entry represents a specific transition probability.

**(C)** Replay-aligned RSN-state activation positively correlated with its transition probability from the DMN for all other RSN states.

**(D)** Spectral factorisation. Using non-negative matrix factorisation, the 1–45 Hz frequency range was decomposed into four bands: theta (2–6 Hz), alpha (6–12 Hz), beta (12–32 Hz), and gamma (32–45 Hz).

**Supplementary Figure 5. Control analysis on the relationships between the VIS and replay.**

**(A)** In contrast to the DMN, replay-aligned VIS activation was not correlated with age. 'ns' for non-significant.

**(B)** Unlike the DMN, the VIS rsFC failed to predict replay, showing no significant correlation between

predicted and actual replay sequenceness. The solid line represents the best-fitting line across participants,

and the shaded area indicates the 95% confidence interval. Each dot represents an individual participant.

'ns' for non-significant.

**(C)** Distribution of robust features in the valid predictive model using whole-brain rsFC, with features within

and across the DMN contributing more to the prediction.

Supplementary Figure 6. Event-related phase-amplitude coupling of replay.

**(A)** ERPAC analysis in the PCC. Event-related phase-amplitude coupling (ERPAC) of replay events was analysed in the PCC. The heat map shows Gaussian-Copula PAC values (Combrisson et al., 2020; Ince et al., 2017), across theta phases and high-frequency amplitudes (see Methods for details). A significant coupling between theta phase and gamma amplitude is observed. '*' for $p < 0.05$.

**(B)** Spatial distribution and phase dependency. Top: Spatial distribution of ROIs, with regions showing significant ERPAC of theta phase and gamma amplitude coloured according to their t-test values at the group level. Bottom: Gamma power changes with theta phase in the PCC around replay events, showing higher amplitude at the theta trough compared to the theta peak.

**Supplementary Figure 7. Replication of main effects in younger participants.**

**(A)** Decoding accuracy over time. Cross-validation results revealed that peak decoding accuracy was achieved
at 300 ms post-stimulus onset, consistent with findings in the full sample. Error bars represent the group
SEM.
**(B)** 2D replay during rest. 2D replay during post-task rest was significantly higher than expected by chance
(black dashed line indicates the permutation threshold) at time lags of 50–70 ms. Additionally, post-task
replay was significantly higher than pre-task replay at the 50 ms lag, replicating the replay effects observed
in the full sample. Error bars represent the group SEM. '**' for $p < 0.01$.
**(C)** Changes in RSN-state activation around replay events. Replay events accompanied by a transient increase
in RSN-state activation, particularly in the DMN and VIS, replicating the temporal profile observed in the
full sample. This increase was observed from −0.2 s to 0.3 s relative to replay onset (dashed black line),
peaking around 30 ms after replay onset (dashed red line).

**Supplementary Figure 8. Distribution of training sessions across age groups.**

**(A)** Total number of training sessions required to reach memory criterion (accuracy ≥ 80%) across all phases,
plotted by age (8–25 years). Error bars represent the group SEM.

**(B)** Number of sessions completed in each training phase: single-dimension training for dimension 1 and
dimension 2, intermixed training, and final review. Error bars represent the group SEM.

**(C)** Interaction between age groups (children: 8–13; adolescents: 14–17; adults: 18–25) and phases, indicating
that children struggled most during the intermixed phase. Error bars represent the group SEM.

**Supplementary Figure 9. Age-related and temporal stability of behavioural performance.**

**(A)** Behavioural performance across age groups. Behavioural performance in the inference task was analysed

across different age groups. All groups performed significantly above chance level, demonstrating active

task engagement. Error bars represent the group SEM.

**(B)** Performance stability over task runs. Behavioural performance of participants aged 8–13 was examined

across runs of the inference task. Accuracy remained stable over time, while reaction time showed changes,

suggesting possible familiarity effects rather than fatigue. Error bars represent the group SEM.

**Supplementary Figure 10. Control analyses of head motion and head size.**

**(A)** Controlling for head motion. The correlations between age and decoding accuracy (left), task-induced 2D replay sequenceness (middle), and replay-aligned DMN activation (right) remained significant after controlling for mean head motion during the corresponding MEG scanning sessions.

**(B)** Controlling for head size effects. The correlations between age and decoding accuracy (left), task-induced 2D replay sequenceness (middle), and replay-aligned DMN activation (right) remained significant after controlling for the mean lead field norms.

## Supplementary Note 1. Control analyses of age-related confounding factors

To ensure the robustness of our findings, we conducted comprehensive control analyses to account for potential age-related confounding factors.

### Main effects across age group

We assessed whether the main effects of replay and DMN activation were influenced by participant age by dividing participants into younger (age < 15) and older (age ≥ 15) groups. For pre-task and post-task 1D replay, as well as pre-task 2D replay, no significant effects were observed in either group. Post-task 2D replay showed significant results in both groups. Notably, the increase in 2D replay from pre-task to post-task was significant also in the younger group (paired $t$-test, $p < 0.01$) but not in the older group. This supports our interpretation that younger participants required more replay to consolidate the cognitive map. The general properties of the DMN and replay-aligned DMN activation were consistently replicated across both age groups. **Supplementary Figure 7** illustrates that the observed effects are not solely driven by older participants.

### Training procedure

All participants completed a three-stage training procedure prior to the formal experiment to ensure full memorisation of 200 pairwise relationships, as described in Qu et al. (2024). The first stage was single dimension learning, participants learned one-rank relationships separately for each dimension until reaching at least 80% accuracy. The second was intermixed learning, trials from both dimensions were intermixed, and incorrectly recalled pairs were relearned until performance again exceeded 80%. In the final review stage, all learned pairs were revisited across three days to stabilise memory before the formal experiment. See **Supplementary Figure 8** and **Supplementary Table 4** for training sessions across age groups and training phases. This adaptive procedure accommodated age-related differences in learning speed while enforcing a uniform memory accuracy criterion. Although the number of training sessions required to reach criterion was significantly correlated with age, $r = -0.483$, $p < 0.001$, memory performance after training did not show a significant association with the number of training sessions, $r = -0.087$, $p = 0.405$, nor with age, $r = 0.074$, $p = 0.471$. Moreover, all main correlations reported in the present study remained significant after controlling for individual differences in memory performance, suggesting that the observed age-related changes were not driven by differences in memory accuracy.

### Task engagement

To ensure active task engagement, we set a stringent pre-scanning memory criterion, allowing participants to proceed to scanning sessions only after achieving at least 80% accuracy in pairwise comparisons during training. Inference accuracy for all participants exceeded the 50% chance level. **Supplementary Figure 9A** shows behavioural performance across age groups, confirming that all groups performed significantly above chance (one-sample $t$-tests, $p < 0.001$). Children aged 8–13 performed comparably to other age groups, indicating effective task engagement.

### Fatigue effect

We examined potential fatigue effects in youngest children aged 8–13 by analysing behavioural performance across the eight runs of the inference task (**Supplementary Figure 9B**). Repeated measures ANOVA revealed no significant differences in accuracy across runs ($F(7, 294) = 1.796$, $p = 0.112$), indicating stable performance.

Reaction time showed significant changes across runs ($F(7, 294) = 5.868$, $p < 0.001$), suggesting familiarity effects rather than fatigue.

## Head motion

Head motion is a common concern in developmental neuroimaging studies (Wehner et al., 2008). We calculated mean head motion for each participant during task and rest periods. After controlling for head motion, the correlations between age and decoding accuracy (partial $r = 0.220$, $p = 0.043$), task-induced 2D replay (partial $r = -0.261$, $p = 0.017$), and replay-aligned DMN activation (partial $r = 0.316$, $p = 0.004$) remained significant (**Supplementary Figure 10A**). This indicates that head motion did not confound our results.

## Head size effects

Head size is a known confound in neurodevelopmental MEG studies due to the fixed sensor geometry of the MEG helmet (Johnson & He, 2019), which can result in smaller brains being farther from the sensors, leading to lower signal strength and SNR in younger participants (Brookes et al., 2018). To assess the potential impact of head size on our results, we followed Brookes et al. (2018), and simulated lead fields for a single source in 38 cortical regions for each participant and examined the correlation between lead field norms (as a proxy for signal strength) and age. No significant linear or non-linear relationship was found between the averaged lead field norms and age (all $p > 0.1$), and the inclusion of lead field norms as a regressor of no interest did not alter the primary results (**Supplementary Figure 10B**). This indicates that head size had no measurable confounding effect on our analyses.

## Processing speed

To ensure that younger participants were not disadvantaged by processing speed, we set a decision time limit of 2 seconds, based on pilot testing with children and adults. Behavioural data confirmed that all participants responded well within this limit (one-sample $t$-test against 2 seconds: $t(97) = -102.630$, $p < 0.001$), including children aged 8–13 ($t(42) = -81.179$, $p < 0.001$). Thus, differences in processing speed did not account for our findings.

## Non-linear age-related development hypothesis

As suggested in Brookes et al. (2018), we compared three candidate models to test whether nonlinear models provided a better fit for variables significantly correlated with age: a linear model $y = a_1 x + a_2$; a non-linear monotonic model $y = -\frac{b_1}{x} + b_2$; a quadratic model $y = c_1 x^2 + c_2 x + c_3$. The linear models of inference accuracy, decoding accuracy, task-induced 2D replay, replay-aligned DMN activation and grid-like code consistently outperformed the non-linear and quadratic alternatives, as indicated by higher adjusted R-squared values and lower Bayesian Information Criterion (BIC) scores. For temporal and spectral characteristics of the DMN that did not show a significant linear association with age, neither the non-linear monotonic model nor the quadratic model provided a significant improvement in fit. These results suggest that linear relationships adequately describe our data, with no substantial evidence supporting nonlinear age effects.

**Socioeconomic status (SES)**

Due to privacy concerns, valid SES data were available for only 51 participants. Analysis revealed a significant negative correlation between age and SES (Spearman's $\rho = -0.326$, $p = 0.019$), indicating higher SES in younger participants. However, none of the key variables in our study showed significant correlations with SES (all $p > 0.1$), suggesting that SES did not influence our results.

**Time of day**

All MEG scanning sessions were conducted in the morning, between 10:00 am and 12:00 pm, to control for potential diurnal variations in brain activity and cognitive performance.

**Sleep quality**

Participants were instructed to have adequate rest the night before scanning. Sleep quality was assessed using the Pittsburgh Sleep Quality Index (PSQI, Buysse et al., 1989). None of the participants scored above the cutoff of 10.

1 **Table S1**. Descriptive statistics of demographic variables (N = 106).

| | Total | Group Age < 15 (N = 53) | Age >= 15 (N = 53) | t-test |
|---|---|---|---|---|
| **Female** | 51 | 22 | 29 | |
| **Male** | 55 | 31 | 24 | |
| **Age** | $16.45 \pm 0.61$ | $10.75 \pm 0.20$ | $22.15 \pm 0.27$ | $23.79^{***}$ |
| **APM** | $25.21 \pm 0.64$ | $22.10 \pm 0.60$ | $28.25 \pm 0.54$ | $5.25^{***}$ |

2  '***' for independent-sample $t$-test $p < 0.001$.

1 **Table S2**. MNI coordinates for the 38 ROIs in the source space.

| Region of interest | Hemisphere | MNI coordinates | | | Hemisphere | MNI coordinates | | |
|---|---|---|---|---|---|---|---|---|
| | | *x* | *y* | *z* | | *x* | *y* | *z* |
| Cuneal Cortex | L | −10 | −87 | 23 | R | 10 | −87 | 23 |
| Lateral Occipital Cortex inferior division | L | −37 | −77 | −5 | R | 37 | −77 | −5 |
| Subcallosal Cortex | L | −53 | −10 | 29 | R | 54 | −10 | 29 |
| Planum Temporale | L | −54 | −22 | 6 | R | 55 | −22 | 7 |
| Postcentral Gyrus | L | −38 | −26 | 57 | R | 38 | −26 | 57 |
| Superior Parietal Lobule | L | −23 | −61 | 54 | R | 23 | −61 | 54 |
| Middle Temporal Gyrus temporoocipital part | L | −47 | −67 | 9 | R | 47 | −67 | 9 |
| Lateral Occipital Cortex superior division | L | −36 | −74 | 37 | R | 36 | −74 | 38 |
| Superior Temporal Gyrus anterior division | L | −51 | −6 | −17 | R | 51 | −5 | −17 |
| Sensorimotor Cortex | L | −11 | −29 | 65 | R | 11 | −29 | 65 |
| Supramarginal Gyrus posterior division | L | −56 | −47 | 34 | R | 56 | −47 | 34 |
| Inferior Frontal Gyrus pars triangularis | L | −42 | 30 | 12 | R | 43 | 30 | 12 |
| Occipital Pole | L | −20 | −94 | 7 | R | 21 | −94 | 7 |
| Middle Frontal Gyrus | L | −23 | 10 | 56 | R | 23 | 10 | 56 |
| Superior Frontal Gyrus | L | −15 | 37 | 47 | R | 15 | 37 | 47 |
| Frontal Lobe | L | −32 | 52 | −5 | R | 33 | 52 | −5 |
| Middle Temporal Gyrus temporoocipital part | L | −58 | −48 | −1 | R | 58 | −47 | −1 |
| Frontal Lobe | L | −21 | 55 | 20 | R | 21 | 55 | 20 |
| Posterior Cingulate Cortex | M | 0 | −60 | 34 | | | | |
| Medial Prefrontal Cortex | M | 0 | 45 | 10 | | | | |

Table S3. Pair-wise correlations across all key variables (N = 98).

| | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **1. Age** | | | | | | | | | | | | | | | |
| **2. Inference ACC** | 0.219 * | | | | | | | | | | | | | | |
| **3. Inference RT (log)** | −0.259 ** | −0.585 *** | | | | | | | | | | | | | |
| **4. APM** | 0.505 *** | 0.416 *** | −0.321 ** | | | | | | | | | | | | |
| **5. Decoding ACC** | 0.255 * | 0.305 ** | −0.212 * | 0.263 * | | | | | | | | | | | |
| **6. 2D replay (Pre)** | 0.167 | −0.107 | 0.017 | 0.14 | 0.025 | | | | | | | | | | |
| **7. 2D replay (Post)** | −0.172 | −0.11 | 0.148 | −0.075 | −0.054 | 0.370 *** | | | | | | | | | |
| **8. 2D replay (Post vs. Pre)** | −0.300 ** | −0.017 | 0.127 | −0.187 | −0.071 | −0.470 *** | 0.646 *** | | | | | | | | |
| **9. DMN occupancy** | 0.187 | 0.102 | −0.121 | 0.022 | −0.041 | −0.016 | 0.072 | 0.081 | | | | | | | |
| **10. DMN interval** | −0.13 | 0.025 | 0.059 | −0.042 | 0.088 | 0.023 | 0 | −0.018 | −0.819 *** | | | | | | |
| **11. DMN power** | 0.088 | 0.127 | −0.095 | −0.005 | −0.013 | −0.009 | 0.12 | 0.122 | 0.794 *** | −0.607 *** | | | | | |
| **12. DMN coherence** | −0.061 | 0.063 | 0.011 | −0.047 | 0.071 | −0.015 | 0.049 | 0.059 | −0.753 *** | 0.921 *** | −0.490 *** | | | | |
| **13. Replay-aligned DMN activation** | 0.281 ** | 0.171 | −0.187 | 0.097 | 0.046 | −0.007 | −0.048 | −0.039 | 0.875 *** | −0.671 *** | 0.749 *** | −0.679 *** | | | |
| **14. Replay-aligned VIS activation** | −0.075 | 0.155 | −0.141 | 0.077 | 0.121 | 0.202 * | −0.116 | −0.276 ** | −0.171 | 0.041 | −0.068 | −0.051 | −0.042 | | |
| **15. fMRI DMN rsFC** | 0.398 *** | 0.202 * | −0.314 ** | 0.278 ** | 0.225 * | 0.210 * | −0.403 *** | −0.565 *** | −0.066 | 0.018 | −0.115 | −0.043 | 0.082 | 0.179 | |

'***' for Pearson correlation $p < 0.001$, '**' for $p < 0.01$, and '*' for $p < 0.05$.

1    **Table S4**. Training sessions for each age group and learning phase (N = 98).

| Age group | Single-Dim | Intermixed | Review | All phases |
|---|---|---|---|---|
| **Children (8–13)** | 3.50 ± 0.53 | 10.98 ± 1.61 | 2.17 ± 0.11 | 20.14 ± 2.16 |
| **Adolescents (14–17)** | 1.50 ± 0.28 | 3.90 ± 0.96 | 2.00 ± 0.32 | 8.90 ± 1.02 |
| **Adults (18–25)** | 1.18 ± 0.06 | 3.68 ± 0.34 | 1.90 ± 0.09 | 7.95 ± 0.32 |
| **All participants** | 2.26 ± 0.26 | 7.00 ± 0.82 | 2.03 ± 0.07 | 13.56 ± 1.15 |

2    Values are mean ± SEM. Single-Dim values are averaged across AP and DP dimensions.