Panalyze: automated virus pangenome variation graph construction, analysis and annotation

Chandana Tennakoon[1,*], Thibaut Freville[1] and Tim Downing[1,*]
[1]Pirbright Institute, Surrey, UK
*To whom correspondence should be addressed

Subject Section: Genome Analysis

Abstract

Motivation: Constructing and studying pangenome variation graphs (PVG) supports new insights into viral genomic diversity. This is because such pangenomes are less prone to reference bias, which affects mutation detection. Interpreting the information arising from this is challenging, so automating these processes to allow exploratory investigations for PVG optimisation is essential. Moreover, existing methods do not scale well to the smaller virus genome sizes and to facilitate analysis in laptop environments. To address this, we developed an easily deployable pipeline to facilitate the rapid creation of virus PVGs that applies a broad range of analyses to these PVGs.
Results: We present panalyze, a scalable and unbiased virus PVG construction, analysis and annotation tool implemented in NextFlow and containerised in Docker. Panalyze uses NextFlow to efficiently complete tasks across multiple compute nodes and in diverse high-performance computing environments. Panalyze can also operate on a single thread on a standard laptop, and analyse sequences lengths are of any size. We illustrate how Panalyze works and the valuable outputs it can generate using a range of common viral pathogens.

Availability: Panalyze is released under a MIT open-source license, available on GitHub with documentation accessible at https://github.com/downingtim/Panalyze/.

Contact: Chandana.tennakoon@pirbright.ac.uk, tim.downing@pibright.ac.uk

Supplementary information: Supplementary data are available online.

Keywords: Comparative Genomics, Genome analysis, Genome annotation, Genome evolution Genomics.

1. Introduction

Pangenome variation graphs (PVGs) offer new insights into genome evolution over short and long scales. A PVG is a sequence graph whose nodes represent sequences and whose edges represent connections observed in data (Hein 1989) such that a genome can be decoded by traversing a series of paths (Garrison et al 2018). PVGs combat reference allele bias by allowing reads to map to the most similar combination of paths in a PVG, instead of a single haplotype (Paten et al 2018). Reference bias is not obviated by using a consensus reference sequence or by using a multi-sample reference (Chen et al 2021, Chen et al 2024). This affects the chance of a read mapping to a location, impacting mutation detection, phylogenetic analyses, and associated inferences in pathogens (Valiente-Mulor 2017) particularly at variable regions that are often strongly associated with phenotypic changes (Haga et al 2024). This results in unaligned reads, missed mutations, poorer inferences, and less precise evolutionary models (Baaijens et al 2017, Hickey et al 2020). Novel pathogen isolates genetically distinct from known references will be characterised less accurately (Boehm et al 2021, Garrison 2023). In viruses, although genome assembly can be effective, extreme AT/GC content, host/vector contamination, short output contig lengths, and repetitiveness all contribute to incomplete and

biased genomes (Alser et al 2021, Lischer et al 2017). Moreover, contigs often need to be aligned to existing databases either as sequences or k-mers, or an existing unavoidably-biased scaffold may be used as a reference (Bradley et al 2019, Ondov et al 2016).

Little work on viral PVGs has been completed (Downing 2025): only one study has yet been published: in this, PVGs helped recover >8% of sequence that failed to align to known linear reference genomes (Duchen et al 2024). A PVG can efficiently represent the diversity of multiple viral strains and so act as a better reference structure than a single linear reference. This means reads can map to different parts of the haplotypes represented in the PVG, which reduces the effect of known mutations and improves mutation discovery (Paten et al 2017, Rakocevic et al 2018). This circumvents the issue of reference genetic distance, improves alignment quality, and may permit more accurate genetic reconstruction of the sample collection (Garrison et al 2023, Moshiri et al 2022). Thus, there is a need for PVG creation and analysis to explore parameter spaces and optimise processes for viral PVGs.

There are many tools available for PVG creation and analysis. Most of these are developed with eukaryotic genome sizes in mind. These may require minimum sequence lengths larger than a typical virus genome length. Moreover, many of these tools are hard to install due to complex installation procedures, assume numerous dependencies, have steps requiring root access. Thus, it would be beneficial to have a curated set of pre-installed tools that can be easily deployed to automate PVG construction, analysis and annotation for small genome sizes. An existing tool, nf-core/pangenome (Heumos et al 2024) achieves this for larger eukaryotic genome sizes, but does not work for genomes <5 Kb long, has limited analysis options, and requires a minimum number of computer server threads. However, the smaller genome sizes of viruses means that their PVG analysis is possible on a laptop.

To address these issues, we present Panalyze, a scalable and rapid virus PVG construction, analysis and annotation tool operating in NextFlow v24.10.3 (Di Tommaso et al 2017) and containerised in Docker (Merkel 2014). Panalyze wraps a series of tools to allow sequence retrieval, PVG creation, phylogenetic analysis, PVG visualisation using multiple methods, PVG size calculation, PVG feature summarisation using different tools, PVG openness analysis, VCF generation, BUSCO gene detection, PVG community detection and PVG annotation. Panalyze focuses on constructing PVGs for smaller (viral) genomes and on supporting the interpretation and analysis of PVGs. Panalyze can automatically: download data of interest, align it, make a phylogeny, compute additional PVG metrics, identify BUSCO genes, annotate the PVG and compare inter-sample genome coordinates. Panalyze can use cluster nodes efficiently in a scalable manner that can be implemented on a single thread on a laptop or using many threads on a computer server. It also resolves the issue of complex installations and dependencies using Docker. We illustrate how Panalyze can work effectively for segmented, DNA and RNA viruses.

2. Methods

2.1 Pipeline overview

Panalyze has two entry points: a pre-existing FASTA file, or a search query from the user (Figure 1A). The latter seeks all complete genomes or genomic sequences matching the query in the Nucleotide database (Sayers et al 2021). The sequences are aligned with Mafft v7.453 (Katoh & Standley 2013) using automatic optimisation and default parameters. Evolutionary relationships are reconstructed using RAxML-NG (Randomised Axelerated Maximum Likelihood) v1.2.0 (Kozlov et al 2019) with a GTR (general time reversible) model and gamma substitution rate heterogeneity. Other models can be selected with modeltest-ng (Darriba et al 2020). Phylogenies are mid-pointed rooted and visualised using R v4.3.2 (R Core Team 2025)

packages ape v5.7-1 (Paradis & Schliep 2019), ggtree v3.8.2 (Yu et al 2017), phangorn v2.11.1 (Schliep 2011), Rcpp v1.0.11 (Eddelbuettel et al 2024b), RcppArmadillo v0.12.6.6.0 (Eddelbuettel et al 2024a), phytools v2.0-3 (Revell 2024) and treeio v1.24.3 (Wang et al 2020).

Panalyze creates PVGs using the pangenome graph builder (PGGB) v0.7.2-27 pipeline (Garrison et al 2024), which initiates all-to-all alignment with WFMASH v0.14.0-0 (Guarracino et al 2021) subject to a threshold of 90% identity per Kb (Figure 1B). PGGB keeps all paths and was used to reconstruct the input haplotypes directly. PGGB creates the PVG using SEQWISH (Garrison & Guarracino 2023) using a k-mer of 19 bp and a window size of 27 bp, and then sorts and orders it to produce a progressively linearised PVG based on partial order alignment with SMOOTHXG v0.7.0. This also removes erroneous redundant nodes (Garrison & Guarracino 2023). To allow analysis of a region < 1.5 Kb in size, we pad the sequences with nucleotides to a minimum length of 1.5 Kb. Once a PVG is built, we break the PVG into single-nucleotide nodes, retaining the original topology. Then we remove the nodes belonging to the padded sequences. Finally, we collapse this pruned PVG so that consecutive unitigs are collapsed into a contig. Multiqc v1.14 (Ewels et al 2016) collates PGGB metrics. The PVGs are generated in Graphical Fragment Assembly (GFA) format version 1. Panalyze does not use PVG pruning, chunking or lacing because virus PVGs are small. These PVGs are converted with the convert function in variation graph (VG) v1.43.0 (Garrison et al 2018), indexed with VG's autoindex function. The corresponding FASTA file is indexed with SAMtools (Li 2009).

Next, a range of PVG analyses are applied. GFASTATS v1.3.6 (Formenti 2022), and ODGI (optimized dynamic genome/graph implementation) v0.8.3 (Guarracino et al 2022) produce PVG summary statistics. Visualisations are created with ODGI (Guarracino et al 2022) (Figure 1) and PGGB (Garrison et al 2023). The number of bases in the PVG comes from ODGI (Guarracino et al 2022). A VCF is produced by GFAUTIL v0.3.2 (Fischer 2021). The relative differences between the sequences' coordinate systems is computed by GFAUTIL and visualised with ggplot2 v2_3.4.4 (Wickham 2016). PVG openness is computed firstly by Panacus v0.2.3 (Parmigiani et al 2024) using the nodes in the PVG with default coverage thresholds that included all segments, secondly with k-mers using Pangrowth (Parmigiani et al 2024), which also estimates the core PVG size, and thirdly with sequences extracted from PVG nodes using ODGI's heaps function using 1,000 simulations (Guarracino et al 2022). Three methods are used to ensure consistency of openness estimates. PVG communities are created by PGGB (Garrison et al 2023) where the number of clusters can be determined by the user and the file names are indexed using fastix. This PVG community data is parsed, visualised and pairwise alignment format (PAF) files are generated for input to PAFGNOSTIC to numerically summarise PVG properties. A tabular PVG annotation file is generated using Prokka (Seeman 2014) for visualisation with Bandage (Wick et al 2015). Optional analyses include determining key gene presence-absence via BUSCO (Manni et al 2021). Additionally, the presence-absence variation (PAV) can be determined by ODGI (Guarracino et al 2022) and visualised, but should only be used for smaller or less diverse datasets due to the compute time required.

2.2 Testing the workflow

To illustrate that Panalyze's PVG analysis approach was broadly applicable to all virus genomes, a range of test datasets were analysed (Table 1). Firstly, we applied it to a set of 121 lumpy skin disease virus (LSDV) genomes, representing large DNA viruses (taking 114 CPU hours, 78 minutes to complete). Secondly, we evaluated Panalyze's performance on 15 porcine respiratory coronavirus (PRCV) genomes, representing small ssRNA viruses (6.7 CPU hours, 6.8 minutes). We repeated this on (ssRNA) 18 FMDV serotype C genomes (2.0 CPU hours, 2.6 minutes), and 441 FMDV serotype O genomes (353 CPU hours, 518 minutes). Thirdly, we evaluated its effectiveness in interpreting a segmented ssRNA virus, Rift Valley fever virus (RVFV), whose genome has three segments (S in 15 CPU hours / 7.1 minutes, M in 18 CPU hours / 10.3 minutes, L in

593 CPU hours, 553 minutes). Fourthly, we demonstrate the scalability of Panalyze by applying it to 2,358 mpox genomes (23 CPU hours, 249 minutes).

Fig. 1. A representation of Panalyze's workflow processes (right)**.** Users can either (A) retrieve sequences of interest via the DOWNLOAD process to get FASTA input for (B), or curate a sample set and start the pipeline at (B). (B) MAKE_PVG will take the FASTA to make the PVG, before running analyses, including: getting PVG metrics with the ODGI and GFAstat processes, visualisations with VIZ1 and VIZ2, genome lengths with GETBASES, creating PAFs with PAFGNOSTIC, community detection with COMMUNITIES and annotation. Other processes are on mutation detection: determining VCFs with VCF_FROM_GFA, VCF_PROCESS to infer mutation rates, getting PAVS with PAVS, and visualising the PAVs with PAVS_plot. Users can implement openness analyses using Panacus, Pangrowth and ODGI, HEAPS and HEAPS_Vizualize. Users can (optionally) identify Busco genes with BUSCO. (C) A region at 135-140 Kb from a 121-sample LSDV PVG visualised using viz in ODGI where each genome shown is a coloured bar and the PVG topology is shown as the genomic coordinates the x-axis (black lines). (D) A region at 136-138 Kb of the same PVG visualised with viz in VG. (E) A region in the same PVG visualised using SequenceTubeMap, showing one minor (22 samples from Clade 1) and one major (99 samples from Clades 1.2 and 2) extended haplotype at LD144 (encoding a kelch-like protein at 135,541-137,208 bp) and LD145 (encoding an ankyrin repeat protein at 137,232-139,136). (F) A phylogeny based on this region showing the two main divergent haplotypes.

Virus pangenome graphs

Virus	Region	Samples	Scaffold (bp)	Length (bp)	Nodes	Edges	Openness
LSDV	Genome	121	150,524	156,966	7,203	9,827	1.88
LSDV 5' end	7.5 Kb	132	7,500	8,954	790	1,037	1.80
LSDV 3' end	5 Kb	132	5,001	7,198	443	572	1.64
GTPV	Genome	6	150,350	163,590	7,523	10,235	1.92
SPPV	Genome	31	149,834	151,742	3,136	4,354	1.04
FMDV A	Genome	142	8,028	15,793	13,102	21,235	0.81
MPOX	Genome	2,358	197,051	280,783	32,387	46,230	0.60
PRCV	Genome	15	27,660	32,086	7,559	10,233	1.13
FMDV O	Genome	441	8,178	16,879	14,064	22,993	0.99
FMDV C	Genome	18	8,148	10,779	5,959	8,359	1.14
RVFV	S segment	414	1,690	2,739	1,738	2,495	0.97
RVFV	M segment	302	3,885	6,182	3,639	5,091	0.93
RVFV	L segment	306	6,399	9,092	5,528	7,677	0.99

Table 1. Properties of selected virus PVGs. The Scaffold refers to the average scaffold size, which was from GFAstats such that the total length refers to the sum of the sequence lengths of the nodes in the PVG from ODGI. FMDV A stands for FMDV serotype A. FMDV C stands for FMDV serotype C. FMDV O stands for FMDV serotype O. Openness was estimated using the alpha values from Panacus.

We repeated the analyses of the same sets of viral genomes using the nf-core/pangenome pipeline (Heumos et al 2024) for comparison with Panalyze using the same sets of viral genomes. The nf-core/pangenome pipeline version tested setup, environment and implementation was cloned locally and required at least 12 nodes. Metrics were extracted for the pruned PVGs to ensure consistency of comparisons. Panalyze and the nf-core/pangenome pipeline provided identical results and the the nf-core/pangenome pipeline was faster overall. However, the RVFV segments S and M were too small to be assessed by nf-core/pangenome. In addition, Panalyze performs a wide range of PVG analysis and visualisations absent in nf-core/pangenome.

To run Panalyze on laptop environments, we created two instances of virtual machines on laptops. The high-resource instance had four cores with 8 GB RAM and the low-resource one had a single core with 4 GB RAM. We used a test dataset of 800 bp from the RVFV S segment for eight genomes.

3. Results

We created PVGs for large DNA (LSDV, mpox, GTPV, SPPV), small ssRNA (PRCV, FMDV) and segmented RNA (RVFV) viruses using Panalyze to illustrate its broad applicability to different virus types, as well as levels of diversity, sequence sizes and sample sizes (Table 1). The varied relative rate of nodes and edges compared to the sample sizes and average genome lengths illustrate how different the levels of sequence variability were. To illustrate the unusual patterns of variation in certain viral genomes, we extracted a portion of the LSDV PVG at which there are 15 mutations spanning two genes (Figure 1E). Phylogenetic reconstruction shows divergent haplotypes: selecting a single representative reference sequence for this region would bias downstream analyses.

We modelled the rate of discovery of new mutations as a function of the number of samples added to the PVGs, estimated with Panacus calculation of alpha. We observed that RVFV's segments had a slightly open PVG, whereas PRCV and the FMDV serotypes had slightly closed ones, which contrasted with the closed

LSDV PVG and the open mpox PVG (Table 1). Similar values were observed with Panacus. Our estimate of gamma for LSDV's PVG (Panacus 0.04) was comparable to a previous estimate of 0.05 derived from a gene-based pangenome (Xie et al 2024).

4. Discussion

We present Panalyze, a scalable, portable, adaptable pipeline for virus PVG construction, analysis and annotation. It runs in NextFlow (Di Tommaso et al 2017) inside Docker (Merkel 2014) containers and is designed in a modular fashion. This allows Nextflow's process management to improve thread allocation and accelerate task completion. Panalyze is written in domain-specific language (DSL) 2 and wraps a range of existing PVG tools to interpret PVGs rapidly to support exploration and optimisation. The selection of tools to run can be specified using a configuration file. Panalyze-generated PVGs uses PGGB and then runs a series of tasks to interpret this PVG using numerical, visual, graphical and other summaries for users to examine. This automation facilitates deeper engagement with complex datasets. Notably, it can analyse genomic regions of any size. Additionally, it can run on a scalable number of threads (from one to many), allowing it to be run locally on a laptop as well as on a HPC server. We demonstrate here how Panalyze can be applied to diverse specimens, including large DNA viruses, small ssRNA viruses, and segmented ones.

Although there are emerging tools for PVG construction, analysis and annotation for smaller genomes, no tool has yet bridged these nor automated them in Nextflow. Panalyze addresses this in a user-oriented reproducible manner. We hope that Panalyze can help the virus research community progress from using linear reference genomes to more accurate PVGs generated from more representative datasets. Moreover, we expect that superior PVG methods will underpin better novel or recombinant sample characterisation as well as routine PVG analysis and mutation detection. Consequently, Panalyze supports virus evolutionary and epidemiological genomics.

Acknowledgements

We acknowledge comments and ideas from Dr. Caroline Wright (Pirbright Institute) and Dr. Lidia Dykes (Pirbright Institute).

Funding

This work was supported by the Pirbright Institute's Bioinformatics STP resources and funding from UK Research and Innovation (UKRI) Biotechnology and Biological Sciences Research Council (BBSRC) grants BBS/E/PI/230002A, BBS/E/PI/230002B, BBS/E/PI/230002C, BBS/E/PI/23NB0003 and BBS/E/PI/23NB0004.

Conflicts of Interest

The authors declare no conflicts of interest.

References

Alser M, et al. Technology dictates algorithms: recent developments in read alignment. Genome Biol. 2021 22(1):249. doi: 10.1186/s13059-021-02443-7

Baaijens JA, Aabidine AZE, Rivals E, Schönhuth A. De novo assembly of viral quasispecies using overlap graphs. Genome Res. 2017 27(5):835-848. doi: 10.1101/gr.215038.116

Virus pangenome graphs

Boehm E, Kronig I, Neher RA, Eckerle I, Vetter P, Kaiser L; Geneva Centre for Emerging Viral Diseases. Novel SARS-CoV-2 variants: the pandemics within the pandemic. Clin Microbiol Infect. 2021 27(8):1109-1117. doi: 10.1016/j.cmi.2021.05.022

Bradley P, den Bakker HC, Rocha EPC, McVean G, Iqbal Z. Ultrafast search of all deposited bacterial and viral genomic data. Nat Biotechnol. 2019 37(2):152-159. doi: 10.1038/s41587-018-0010-1

Chen NC, Paulin LF, Sedlazeck FJ, Koren S, Phillippy AM, Langmead B. Improved sequence mapping using a complete reference genome and lift-over. Nat Methods. 2024 21(1):41-49. doi: 10.1038/s41592-023-02069-6.

Chen NC, Solomon B, Mun T, Iyer S, Langmead B. Reference flow: reducing reference bias using multiple population genomes. Genome Biol. 2021 22(1):8 doi: 10.1186/s13059-020-02229-3.

Darriba D, Posada D, Kozlov AM, Stamatakis A, Morel B, Flouri T. ModelTest-NG: A New and Scalable Tool for the Selection of DNA and Protein Evolutionary Models. Mol Biol Evol. 2020 37(1):291-294. doi: 10.1093/molbev/msz189

Di Tommaso P, Chatzou M, Floden EW, Barja PP, Palumbo E, Notredame C. Nextflow enables reproducible computational workflows. Nat Biotechnol. 2017 35(4):316-319. doi: 10.1038/nbt.3820.

Downing T. Approaches to studying virus pangenome variation graphs. ArXiv 2025 https://doi.org/10.48550/arXiv.2412.05096

Duchen D, Clipman S, Vergara C, Thio CL, Thomas DL, Duggal P, Wojcik GL. A hepatitis B virus (HBV) sequence variation graph improves sequence alignment and sample-specific consensus sequence construction for genetic analysis of HBV. PLoS One. 2024 19(4):e0301069. doi: 10.1371/journal.pone.0301069

Eddelbuettel D, Balamuta JB. Extending R with C++: A Brief Introduction to Rcpp. 2018 https://doi.org/10.1080/00031305.2017.1375990

Eddelbuettel D, Sanderson C. RcppArmadillo: Accelerating R with high-performance C++ linear algebra. 2014. Computational Statistics and Data Analysis 10.1016/j.csda.2013.02.005

Ewels P, Magnusson M, Lundin S, Käller M. MultiQC: summarize analysis results for multiple tools and samples in a single report. Bioinformatics. 2016 32(19):3047-8. doi: 10.1093/bioinformatics/btw354.

Formenti G, Abueg L, Brajuka A, Brajuka N, Gallardo-Alba C, Giani A, Fedrigo O, Jarvis ED. Gfastats: conversion, evaluation and manipulation of genome sequences using assembly graphs. Bioinformatics. 2022 38(17):4214-4216. doi: 10.1093/bioinformatics/btac460

Garrison E, et al Variation graph toolkit improves read mapping by representing genetic variation in the reference. Nat Biotechnol. 2018 36(9):875-879. doi: 10.1038/nbt.4227

Garrison E, et al. Building pangenome graphs. Nat Methods. 2024 21(11):2008-2012. doi: 10.1038/s41592-024-02430-3

Garrison E, Guarracino A. Unbiased pangenome graphs. Bioinformatics. 2023 39(1):btac743. doi: 10.1093/bioinformatics/btac743

Guarracino A, Heumos S, Nahnsen S, Prins P, Garrison E. ODGI: understanding pangenome graphs. Bioinformatics. 2022 38(13):3319–26. doi: 10.1093/bioinformatics/btac308.

Guarracino A, Mwaniki N, Marco-Sola S, Garrison E. wfmash: whole-chromosome pairwise alignment using the hierarchical wavefront algorithm. 2021 https://github.com/ekg/wfmash.

Haga IR, et al. Sequencing and Analysis of Lumpy Skin Disease Virus Whole Genomes Reveals a New Viral Subgroup in West and Central Africa. Viruses. 2024 16(4):557. doi: 10.3390/v16040557

Hein J. A new method that simultaneously aligns and reconstructs ancestral sequences for any number of homologous sequences, when the phylogeny is given. Mol Biol Evol. 1989 6(6):649-68. doi: 10.1093/oxfordjournals.molbev.a040577.

Hickey G, Heller D, Monlong J, Sibbesen JA, Sirén J, Eizenga J, Dawson ET, Garrison E, Novak AM, Paten B. Genotyping structural variants in pangenome graphs using the vg toolkit. Genome Biol. 2020 21(1):35. doi: 10.1186/s13059-020-1941-7

Virus pangenome graphs

Heumos S, Heuer ML, Hanssen F, Heumos L, Guarracino A, Heringer P, Ehmele P, Prins P, Garrison E, Nahnsen S. Cluster-efficient pangenome graph construction with nf-core/pangenome. Bioinformatics. 2024 40(11):btae609. doi: 10.1093/bioinformatics/btae609.

Katoh K, Standley DM. MAFFT: iterative refinement and additional methods. Methods Mol Biol. 2014 1079:131-46. doi: 10.1007/978-1-62703-646-7_8.

Kozlov AM, Darriba D, Flouri T, Morel B, Stamatakis A. RAxML-NG: a fast, scalable and user-friendly tool for maximum likelihood phylogenetic inference. Bioinformatics. 2019 35(21):4453-4455. doi: 10.1093/bioinformatics/btz305.

Li H, Handsaker B, Wysoker A, Fennell T, Ruan J, Homer N, Marth G, Abecasis G, Durbin R; 1000 Genome Project Data Processing Subgroup. The Sequence Alignment/Map format and SAMtools. Bioinformatics. 2009 25(16):2078-9. doi: 10.1093/bioinformatics/btp352.

Lischer HEL, Shimizu KK. Reference-guided de novo assembly approach improves genome reconstruction for related species. BMC Bioinformatics. 2017 18(1):474. doi: 10.1186/s12859-017-1911-6

Manni M, Berkeley MR, Seppey M, Simão FA, Zdobnov EM. BUSCO Update: Novel and Streamlined Workflows along with Broader and Deeper Phylogenetic Coverage for Scoring of Eukaryotic, Prokaryotic, and Viral Genomes. Mol Biol Evol. 2021 38(10):4647-4654.

Merkel, D. 2014. Docker: lightweight linux containers for consistent development and deployment. Linux Journal, 2014(239), 2. doi: https://10.5555/2600239.2600241

Moshiri N, Fisch KM, Birmingham A, DeHoff P, Yeo GW, Jepsen K, Laurent LC, Knight R. The ViReflow pipeline enables user friendly large scale viral consensus genome reconstruction. Sci Rep. 2022 12(1):5077. doi: 10.1038/s41598-022-09035-w.

Ondov BD, Treangen TJ, Melsted P, Mallonee AB, Bergman NH, Koren S, Phillippy AM. Mash: fast genome and metagenome distance estimation using MinHash. Genome Biol. 2016 17(1):132. doi: 10.1186/s13059-016-0997-x.

Paradis E, Schliep K. ape 5.0: an environment for modern phylogenetics and evolutionary analyses in R. Bioinformatics. 2019 35(3):526-528. doi: 10.1093/bioinformatics/bty633.

Parmigiani L, Garrison E, Stoye J, Marschall T, Doerr D. Panacus: fast and exact pangenome growth and core size estimation. Bioinformatics. 2024 40(12):btae720. doi: 10.1093/bioinformatics/btae720.

Paten B, Eizenga JM, Rosen YM, Novak AM, Garrison E, Hickey G. Superbubbles, Ultrabubbles, and Cacti. J Comput Biol. 2018 25(7):649-663. doi: 10.1089/cmb.2017.0251.

R Core Team (2025). R: A language and environment for statistical computing. R Foundation for Statistical Computing, Vienna, Austria. URL https://www.R-project.org/

Rakocevic G, et al Fast and accurate genomic analyses using genome graphs. Nat. Genet. 2019 51, 354–362.

Revll LJ. phytools 2.0: an updated R ecosystem for phylogenetic comparative methods (and other things). PeerJ 12:e16505 https://doi.org/10.7717/peerj.16505

Sayers EW, et al. Database resources of the National Center for Biotechnology Information. Nucleic Acids Res. 2021 49(D1):D10-D17. doi: 10.1093/nar/gkaa892.

Schliep KP. phangorn: phylogenetic analysis in R. Bioinformatics. 2011 27(4):592-3. doi: 10.1093/bioinformatics/btq706.

Seemann T. Prokka: rapid prokaryotic genome annotation. Bioinformatics. 2014 30(14):2068-9. doi: 10.1093/bioinformatics/btu153.

Valiente-Mullor C, et al. One is not enough: On the effects of reference genome for the mapping and subsequent analyses of short-reads. PLoS Comput Biol. 2021 17(1):e1008678. doi: 10.1371/journal.pcbi.1008678.

Wang LG, et al. Treeio: An R Package for Phylogenetic Tree Input and Output with Richly Annotated and Associated Data. Mol Biol Evol. 2020 37(2):599-603. doi: 10.1093/molbev/msz240.

Wick RR, Schultz MB, Zobel J, Holt KE. Bandage: interactive visualization of de novo genome assemblies. Bioinformatics. 2015 31(20):3350-2. doi: 10.1093/bioinformatics/btv383.

Virus pangenome graphs

Wickham H. 2016. ggplot2: Elegant Graphics for Data Analysis. Springer-Verlag New York. ISBN 978-3-319-24277-4, https://ggplot2.tidyverse.org.

Xie S, Cui L, Liao Z, Zhu J, Ren S, Niu K, Li H, Jiang F, Wu J, Wang J, Wu J, Song B, Wu W, Peng C. Genomic analysis of lumpy skin disease virus asian variants and evaluation of its cellular tropism. NPJ Vaccines. 2024 9(1):65. doi: 10.1038/s41541-024-00846-8.

Yu G, Smith D, Zhu H, Guan Y, Lam TT. ggtree: an R package for visualization and annotation of phylogenetic trees with their covariates and other associated data. 2017. Methods in Ecology and Evolution, 8, 28-36. doi:10.1111/2041-210X.12628.

(A)

optional — DOWNLOAD: get genomes — ALIGN: Mafft alignment — Get FASTA file
TREE: Construct phylogeny

(B)

MAKE_PVG: using PGGB
- ODGI: get odgi PVG stats
- GFAstat: get key PVG metrics
- VIZ: visualise PVG
- VIZ2: get large-scale PVG image
- GETBASES: get genome lengths
- PATH_FROM_GFA: get sample names
- PAFGNOSTIC: get region matches
- COMMUNITIES: identify groups in network
- Annotate_Position: annotate PVG for visualisation

FASTA file

Get mutations
- VCF_FROM_GFA: get VCF data
- VCF_PROCESS: get SNP rates
- PAVS: get number of PAVs
- PAVS_plot: Visualise PAV rates

PVG openness estimate
- OPENNESS_PANACUS: Get PVG growth rate
- OPENNESS_PANGROWTH: Get PVG growth rate
- HEAPS: Get PVG growth rate from odgi
- HEAPS_Visualize: Show odgi PVG growth rate

optional — BUSCO: get BUSCO genes

(C)

(D)

(E)

(F)

Clade 1.2

Clade 2

Clade 1.1

0.003