Assessing scoring metrics for AlphaFold2 and AlphaFold3 protein complex predictions

Luca R. Genz[1,2,3], Sanjana Nair[1,3] and Maya Topf*[1,3,4]

[1]Leibniz-Institut für Virologie (LIV), [2]Universität Hamburg, [3]Centre for Structural Systems Biology (CSSB) and [4]Universitätsklinikum Hamburg Eppendorf (UKE), Hamburg, Germany

*To whom correspondence should be addressed.

Correspondence: Maya Topf; maya.topf@cssb-hamburg.de; +49 040 8998 87660

1. Abstract

Abstract: The recent breakthroughs in AI-driven protein structure prediction have revolutionized structural biology, unlocking new possibilities to model complex biomolecular interactions. We evaluated widely-used scoring metrics for assessing such models predicted by ColabFold with templates, ColabFold without templates, and AlphaFold3. We benchmarked the optimal cutoffs for these assessment scores using a set of 325 heterodimeric high-resolution protein structures and their predictions. Our results show that ColabFold with templates and AlphaFold3 perform similarly and both outperform ColabFold without templates. Furthermore, interface-specific scores are found to be more reliable for evaluating protein complex predictions compared to the corresponding global scores. Notably, ipTM and *model confidence* achieve the best performance in distinguishing correct from incorrect predictions. Based on our results, we developed a weighted combined score, C2Qscore, to improve model quality assessment, which was used to analyze dimers from large assemblies solved by cryoEM. This revealed potential limitations of the

assessment scores when multiple configurations of heterodimers are possible. C2Qscore has been integrated as a tool into our ChimeraX plug-in PICKLUSTER v2.0, facilitating interactive access to the scoring metrics. The plug-in is freely available for download from the ChimeraX Toolshed and https://gitlab.com/topf-lab/pickluster-v2.0.git. This study provides insights into the strengths and weaknesses of current scores and offers guidance for improving protein complex model assessment.

Keywords: Protein complex modeling; Interface scoring; Scoring metrics; AlphaFold3; ColabFold, protein structure prediction; ChimeraX plug-in

Impact of this work: This study evaluates the effectiveness of current scoring metrics used to assess computationally generated structural models of protein complexes, which are crucial for understanding cellular functions. By analyzing the performance of these metrics and comparing different prediction methods, we aim to enhance the reliability and accuracy of such models. Our findings provide valuable insights for researchers utilizing computational approaches to study biological processes and have potential applications in biomedical research.

2. Introduction

Protein complexes are fundamental to various cellular processes, performing diverse functions in vivo (Schulz and Schirmer 2013). To understand the mechanisms of protein complex formation and macromolecular recognition, the precise identification and characterization of protein-protein interfaces is a crucial step (Xue et al. 2015). High-resolution structural data obtained from experimental methods such as X-ray crystallography and cryogenic-electron microscopy (cryo-EM) offer insights into these interfaces (Smyth and Martin 2000; Namba and Makino 2022). However, these are resource-intensive techniques and present challenges for large-scale structure determination (Xue et al. 2015). Recent advancements in AI-based protein structure prediction, particularly AlphaFold2, have mitigated these challenges by enabling large-scale structure predictions sometimes even with accuracies comparable to those of experimental methods (Jumper et al. 2021; Evans et al. 2022). This progress was recognized with the 2024 Nobel Prize in Chemistry. AlphaFold2's successor, AlphaFold3, further advanced the field by allowing the prediction of protein complexes with lipids, nucleic acids and other ligands (Abramson et al. 2024).

Beyond predicting the structures of protein complexes, it is equally important to assess the accuracy of these predictions to ensure confidence in the models which is crucial for downstream analyses, such as functional studies, protein engineering, and drug design (Baker and Sali 2001). However, evaluating the quality of predictions without a reference structure is challenging. The progress in the protein structure prediction field has led to the development of various methods for accessing model accuracy, with increasing emphasis on evaluating protein complexes (Studer et al. 2023). CASP (Critical Assessment of Structure Prediction), a community-wide experiment designed to track advancements in the structure prediction field, introduced the Estimation of

Model Accuracy (EMA) category already in CASP7 to address this need (Cozzetto et

al. 2007).

To date, numerous prediction-based evaluation metrics have been proposed, most of

which are machine learning-based (Studer et al. 2023 Oct 19). The graph neural

network (GNN)-based scoring method, VoroIF-GNN (VoroIF) (Olechnovič and

Venclovas 2023), emerged as one of the top performing scores in assessing interface

quality in the CASP15 EMA iteration, ranking alongside ModFOLDdockR and

ModFOLDdock (Edmunds et al. 2023) and VoroMQA (Olechnovič and Venclovas

2019). VoroIF uses Voronoi tessellation to derive interface graphs, providing a

detailed, contact-based accuracy estimate for the entire interface. The VoroIF

interface-specific score is calculated as the average score of interface residues

(Average-VoroIF-GNN-residue-pCAD score), which is then adjusted for structural

completeness based on the ratio of atoms in the model to atoms in the target.

Another commonly used metric for evaluating the quality of protein structure

predictions is the predicted DockQ score (pDockQ) (Bryant et al. 2022). This score is

derived by calculating the number of interfacial contacts and the average quality of

interacting residues, which are then fitted to a sigmoid function of the DockQ score

(Basu and Wallner 2016). Its more recent iteration, pDockQ2 (Zhu et al. 2023), was

specifically developed for the assessment of multimeric protein complexes.

To our knowledge, to date only Yin et al. (Yin et al. 2022) have conducted a systematic

assessment of scores that evaluate AlphaFold2 multimeric predictions, using a

relatively small benchmark set of 152 heterodimeric protein complexes. In their

analysis, they compared the performance of AlphaFold2 to the protein-docking

algorithm ZDOCK (Pierce et al. 2011). Evaluated metrics included the predicted Local

Distance Difference Test (pLDDT) (Jumper et al. 2021), an interface-specific version

of pLDDT, predicted Template Modeling score (pTM) (Jumper et al. 2021), an

interface-specific Pairwise Alignment Error (PAE) (Evans et al. 2022), among other

metrics, and these were compared against the interface Root Mean Square Deviation

(I-RMSD) (Lensink and Wodak 2013; Basu and Wallner 2016). Furthermore, most of

the current evaluation metrics, including pDockQ, VoroIF, and others, have been

applied in isolation and were evaluated prior to the development of AlphaFold3.

In this study, we focused on the quality of the interface, by providing a comprehensive

comparison and evaluation of commonly used scores for assessing predictions of

heterodimeric protein complexes. We evaluated predictions from both

AlphaFold2/ColabFold (Mirdita et al. 2022) (with and without templates) and

AlphaFold3. We compared different scores, with DockQ as ground truth, including:

interface predicted Local Distance Difference Test (ipLDDT) (Genz et al. 2023), pTM,

interface pTM (ipTM) (Evans et al. 2022), *model confidence* (Evans et al. 2022),

interface PAE (iPAE) (Evans et al. 2022; Genz et al. 2023), pDockQ2 (Zhu et al. 2023),

and VoroIF. The individual scores were merged into one score, trained on predictions

for 325 heterodimeric high-resolution structures from the Protein Data Bank (PDB) and

tested on an independent dataset of predictions for X-ray crystallographic structures

and dimers from larger assemblies derived from cryoEM. The score has been

integrated as a tool into our ChimeraX plug-in PICKLUSTER v2.0 (Genz et al. 2023),

providing users with interactive access to scoring metrics as a valuable analytical tool.

3.   Results

3.1. Benchmarking the prediction accuracy of ColabFold with templates,

ColabFold template free and AlphaFold3

To evaluate the capability of ColabFold and AlphaFold3 in generating high-quality

predictions of structural models, a comparative analysis was performed using a

benchmark set. We focused exclusively on heterodimeric complexes rather than homodimeric ones, as AlphaFold2 generally performs better on homomeric interfaces (Evans et al. 2022; Zhu et al. 2023). By selecting heterodimers, we aimed to introduce greater diversity and a more challenging evaluation setting. Starting with 1,381 complexes, a filtering process (See Methods, Suppl. Fig. 1) reduced the number of target structures to 397. Among these, 72 cases were identified in which the biological assembly (BA) assigned in the PDB is different from the asymmetric unit (AU), resulting in predictions resembling only one of the two. This caused issues during evaluation with DockQ, as DockQ was used to align the AU with the predicted model, leading to artificially low scores that do not reflect the prediction quality in these specific cases. To address this, only templates with the assigned dimeric BA identical to the AU were included in the benchmark set, resulting in a final set of 325 target structures. Predictions were generated using ColabFold with templates (CF-T) and with the template-free (CF-F) option, and the AlphaFold3 web server (AF3). All predictions were performed with three recycles followed by relaxation (Hornak et al. 2006), producing five predictions per target structure. DockQ and individual prediction-based scores were calculated for a total of 1,612 models in the CF-T and 1,614 models in the CF-F set. In the AF3 set, scores were obtained for 1,595 models.

Using CAPRI (Critical Assessment of PRediction of Interactions) criteria for DockQ ("DockQ classification", Methods) revealed that CF-T (52.5%) and AF3 (50.3%) had the highest proportion of 'high' quality models (DockQ > 0.8), making it the largest fraction for both prediction methods (Fig. 1A).

Of the three prediction methods, the CF-F set contained the lowest proportion of 'high' quality models at 34.7% with the largest fraction consisting of models of 'medium' quality.

Analyzing the models classified as 'incorrect' using DockQ (DockQ ≤ 0.23) showed

that AF3 had the lowest percentage of incorrect models at 13.5%. In contrast, the CF-

T and CF-F sets exhibited significantly higher proportions of incorrect models, at

17.5% and 22.2%, respectively.

Further investigation of the composition of the 'incorrect' fraction revealed that AF3

showed the highest percentage of cases where all five models of the prediction were

classified as incorrect (83.7%) (Fig. 1B) CF-F revealed a significantly smaller

proportion of cases where all five models of the prediction were classified as incorrect

(75.4%) and the CF-T set had the lowest percentage of those (69.5%).

Considering only the 'high' quality fraction, CF-T predictions appear to be the most

accurate. However, if models classified as 'acceptable', 'medium' and 'high' quality

according to the CAPRI criteria are all considered correct (as opposed to the 'incorrect'

fraction), then AF3 predictions are superior, as they exhibit the lowest number of

incorrect models. This detailed analysis of the quality of the predicted models suggests

AlphaFold3 and ColabFold with templates as the most reliable predictors. Additionally,

it demonstrates that compared to ColabFold, AlphaFold3 predictions are more

consistent in regards to whether a model is correct or incorrect. This is indicated by

the significantly higher proportion of cases where all five models in a prediction were

classified as incorrect and the lowest proportion where only one model is incorrect.

Fig. 1. Quality distributions and overlap of DockQ classifications (5 levels) across models predicted by CF-T, CF-F, and AF3. **A:** Quality assessment of the three sets based on DockQ classification criteria. **B:** Breakdown of the incorrect fraction from A, categorizing cases where all five models of a template are classified as incorrect, followed by cases with 4, 3, 2, and those with only one model classified as incorrect. **C:** Venn diagram of the 'correct' fraction ('acceptable', 'medium', 'high' are combined). The fraction of only CF-T predicting models of a specific quality are shown in blue, CF-F in green, and AF3 in orange. When two prediction methods agree, the fraction is represented in gray, and when all three prediction methods agree, it is shown in light gray. **D:** Venn diagram of the 'incorrect' fraction. Colors are as in (C).

Moreover, the consensus of prediction quality across the three datasets (CF-T, CF-F

and AF3) was analyzed by comparing models of the same rank (Fig. 1C, D, Suppl.

Fig. 2). When the 'high', 'medium' and 'acceptable' quality fractions are combined

(considered 'correct' based on CAPRI criteria), the models predicted by the three

different methods are comparable in terms of quality in 81.8% of cases (Venn diagram

in Fig. 1C). The highest proportion (6.4%) of uniquely correct predictions was observed

for AF3, suggesting that running AlphaFold3 may enhance the likelihood of generating

reliable models. However, Venn diagrams illustrating just high-quality models (based

on CAPRI criteria) reveal that only 50.3% of the cases were consistent across all three

datasets (Suppl. Fig. 2). Notably, for high-quality models only, the highest proportion

(14.9%) of predictions when only one method was able to achieve such results was

observed for CF-T. This suggests that using ColabFold with templates may increase

the likelihood of generating high-quality models. The Venn diagram shows that CF-F

had the highest proportion of incorrect predictions (17.9%) based on CAPRI criteria

(Fig. 1D), consistent with its highest proportion of incorrect models in the benchmark

set (Fig. 1A). The acceptable fraction showed the lowest agreement (17.6%) between

the three prediction methods (Suppl. Fig. 2), suggesting that in cases where

predictions are near the threshold for incorrect predictions (DockQ ≤ 0.23), running all

three methods and comparing results may yield the most optimal outcome.

3.2. Distributions and correlations of individual prediction-based scores

In order to evaluate the effectiveness of the raw assessment scores (ipLDDT, iPAE,

pTM, ipTM, *model confidence*, pDockQ2 and VoroIF, Suppl. Tab. 1) in predicting the

quality of the models, these scores were calculated for each model in the three distinct

datasets: CF-T, CF-F and AF3. Given the variability in defining the interface based on

different distance cutoffs and different types of atoms and positions, the impact of the

distance parameter on ipLDDT and iPAE was investigated (see Methods). The results

indicated no substantial difference in interface detection or ipLDDT and iPAE

calculations across the various distance parameters (Suppl. Fig. 3). This suggests that

the distance parameter has a marginal influence on these scores.

Consequently, a heavy atom distance cutoff of 5 Å was adopted for the definition of

the interface and the calculation of the ipLDDT and the iPAE in agreement with the

interface threshold used by AlphaFold to define the interface (Evans et al. 2022).

Subsequently, the empirical distributions of the scores and the correlation between the

scores were analyzed (Fig. 2, Supp Fig. 4,5). A common trend across these

distributions was the predominance of high scores (low scores for iPAE and PAE),

suggesting a generally high quality of the prediction sets, consistent with the findings

discussed in 3.1.

As expected, *model confidence* exhibited the highest correlation with ipTM across all

three datasets, which is the dominant component of the former. Conversely, pDockQ2

demonstrated the lowest correlation with other scores. Overall, the global scores

pLDDT and PAE, had a lower correlation with all other scores. In contrast, the

interface-specific scores, ipLDDT and iPAE, had a higher correlation with other scores.

This could be due to the interface specificity of most of the other scores (except pTM).

Overall, the individual prediction-based scores were in good agreement with our

observation that these datasets comprised a high proportion of high-quality models.

Moreover, the described trends were consistent across all three datasets (CF-T, CF-

F and AF3) (Fig. 2, Supp Fig. 4,5).

Fig. 2: Distribution and correlation of the individual scores (pLDDT, PAE, ipLDDT, iPAE, pTM, ipTM, *model confidence* (mc), pDockQ2 and VoroIF) for the CF-T dataset. The lower-left section displays the pairwise correlation between the scores. The diagonal shows the distribution of each raw score within the benchmark set. The upper-right section provides the PCC between the scores with red indicating high and blue low PCCs.

3.3. Correlation of individual prediction-based scores with DockQ

To evaluate the effectiveness of individual scores in assessing the quality of the predicted models in the three datasets, PCC between these scores and DockQ were calculated. The results were consistent across CF-T, CF-F, and AF3, with mean PCCs of 0.68, 0.72, and 0.64 (averaged over the individual scores), respectively. However, Wilcoxon signed-rank test showed that only the differences between CF-F and AF3 were statistically significant (p-value of 0.004). These findings suggest that the scores were more effective in evaluating models generated by ColabFold without templates than by AF3. Notably, despite the generally lower quality of models in the CF-F dataset (Fig 1A) compared to CF-T and AF3, the assessment scores performed best for these

models (Fig. 3A). ipTM and *model confidence* showed the highest correlations with

DockQ across all datasets, recommending these scores as the primary metrics for the

protein complex model assessment when only a single score is to be used regardless

of the prediction method.

Furthermore, the interface-specific scores, ipLDDT and iPAE, outperformed their

global versions, pLDDT and PAE, as they exhibited a significantly higher correlation

with the DockQ. The third least correlated score was pDockQ2, which remained only

mildly correlated with DockQ across all datasets. Fig 3B (i, ii, and iii), provides

examples to demonstrate that the ipTM and DockQ indicate high quality models, but

pDockQ2 indicates the opposite: for targets PDB: 6UKA (predicted by CF-T) and PDB:

5ZZA (predicted by CF-F), although DockQ implies a high-quality model and ipTM is

high (0.88, 0.82), pDockQ2 is very low (0.01, 0.01). Finally, a similar situation is

observed for a model produced by AF3: for target PDB: 7O4Q, ipTM is high (0.82) and

pDockQ2 is significantly lower (0.30).

Fig. 3: Quality of the individual scores and representative structural predictions with scores. **A:** PCC of the individual scores (pLDDT, PAE, ipLDDT, iPAE, pTM, ipTM, *model confidence*, pDockQ2 and VoroIF) with DockQ. The color bar is a gradient from blue to red indicating low to high correlation, respectively for CF-T, CF-F and AF3. **B(i):** CF-T prediction (blue, interface: red) and target structure (PDB: 6UKA) (gray, interface: dark red). **B(ii):** CF-F prediction (green, interface: red) and target structure (PDB: 5ZZA) (gray, interface: dark red). **B(iii):** AF3 prediction (orange, interface: red) and target structure (PDB: 7O4Q) (gray, interface: dark red).

3.4. Determinants of high- and low-quality models

The individual scores provide only the absolute values without any established thresholds, thus limiting their application for binary classification of the model as correct or incorrect. To address this limitation, we performed Receiver Operating Characteristic (ROC) curve analyses for each score, allowing the determination of cutoffs based on (Melo and Sali 2007) (see Methods).

For defining the ground truth, models labelled as 'incorrect' by DockQ classification

were defined as incorrect models, while those falling into the 'acceptable', 'medium',

and 'high' DockQ categories were considered as "correct" predictions. Using ROC

curves, optimal thresholds were derived for each dataset (Fig. 4A).

Additionally, Area Under the Curve (AUC) (Fig. 4B), accuracy and precision (Suppl.

Table 2) were calculated to assess the ability of the thresholds to distinguish between

models of low and high accuracy as designated by DockQ (see Methods). While the

precision values of all three datasets was similarly high, the AUC and accuracy values

for the AF3 dataset were lower than those for CF-T and CF-F. This result is consistent

with Section 3.3, which shows comparatively lower PCC for AF3. Among the scores

evaluated, pDockQ2 consistently exhibited the lowest AUC (Fig. 4B) and also

accuracy (Suppl. Table 2) across all three datasets, in agreement with the distributions

shown in Fig. 3. Considering the low correlation of pDockQ2 with DockQ (Fig. 3) its

threshold determination is less reliable. This is especially clear for the CF-F dataset,

where the threshold is below 0.1. On the other hand, the highest AUC (Fig. 4B) and

accuracy (Suppl. Table 2) values were observed for the ipTM and *model confidence*

scores, in agreement with the findings of Section 3.3.

To assess AF3 models, there were guidelines for the cutoffs of ipTM in the frequently

asked questions of the AlphaFold Server (Accessed October 29, 2024.

https://alphafoldserver.com/faq). ipTM > 0.8 indicates high-quality predictions, ipTM

< 0.6 suggests likely failed predictions, and ipTM in 0.6 - 0.8 range falls into a "gray

zone" where predictions could be correct or incorrect.

However, the importance of providing a specific cutoff to separate correct from

incorrect models arises when the model's ipTM falls within the gray zone. In all three

examples shown in Fig. 4C, the ipTM scores fall within the gray zone defined in

AlphaFold server, yet the outcomes vary significantly. In Fig. 4C (i and iii), the

predictions by CF-T (target PDB: 7PPZ) and AF3 (target PDB: 6MM8) do not pass the

ipTM corresponding cutoffs (0.70 and 0.75, respectively) and are categorized as

'incorrect' based on DockQ scores. In contrast, Fig. 4C(ii) shows a CF-F prediction

(target PDB: 7BZK) for which the ipTM score surpasses our cutoff of 0.65, with the

DockQ score classifying this prediction as of 'high' quality. Therefore, for the subset of

structures of CF-T, CF-F and AF3 with ipTM values in the range of 0.6-0.8, we

evaluated the accuracy with cutoffs determined by ROC analyses (CF-T: 0.7; CF-F:

0.65; AF3: 0.75, Fig. 4B). This allowed us to differentiate between correct and incorrect

models even in the gray zone with accuracies of 0.81, 0.87 and 0.63 for CF-T, CF-F

and AF3, respectively (Suppl. Table 3).

A

Binary classification correct vs. incorrect			
Score	CF-T	CF-F	AF3
ipLDDT	80.0	80.0	85.0
iPAE	5.00	9.00	6.00
pTM	0.80	0.80	0.75
ipTM	0.70	0.65	0.75
mc	0.75	0.70	0.70
pDockQ2	0.35	0.05	0.45
VoroIF	0.65	0.65	0.60

B

CF-T

ipLDDT (AUC = 0.92)
iPAE (AUC = 0.94)
pTM (AUC = 0.89)
ipTM (AUC = 0.95)
mc (AUC = 0.95)
pDockQ2 (AUC = 0.84)
VoroIF (AUC = 0.90)
Diagonal

CF-F

ipLDDT (AUC = 0.94)
iPAE (AUC = 0.96)
pTM (AUC = 0.90)
ipTM (AUC = 0.96)
mc (AUC = 0.96)
pDockQ2 (AUC = 0.86)
VoroIF (AUC = 0.92)
Diagonal

AF3

ipLDDT (AUC = 0.90)
iPAE (AUC = 0.94)
pTM (AUC = 0.90)
ipTM (AUC = 0.95)
mc (AUC = 0.95)
pDockQ2 (AUC = 0.82)
VoroIF (AUC = 0.85)
Diagonal

C

(i) ipTM: 0.65
DockQ: 0.10

(ii) ipTM: 0.66
DockQ: 0.83

(iii) ipTM: 0.67
DockQ: 0.19

Fig. 4: ROC curves, determined cutoffs and example predictions. **A:** Determined thresholds

for the scores distinguishing correct ('high', 'medium', 'acceptable' DockQ) and incorrect

('incorrect' DockQ) models for CF-T, CF-F and AF3. **B:** ROC-curves and AUC of the raw

scores (ipLDDT, iPAE, pTM, ipTM, *model confidenc*e, pDockQ2 and VoroIF) for CF-T, CF-F

and AF3. The binary classification is based on the DockQ classification correct ('high',

'medium', 'acceptable' DockQ) and incorrect ('incorrect' DockQ) **C(i):** CF-T prediction (blue,

interface: red) and target structure (PDB: 7PPZ) (gray, interface: dark red). **C(ii):** CF-F

prediction (green, interface: red) and target structure (PDB: 7BZK) (gray, interface: dark red).

C(iii): AF3 prediction (orange, interface: red) and target structure (PDB: 6MM8) (gray, interface: dark red).

3.5. Combined scoring and testing

In addition to evaluating the individual scores and their discriminatory power, a combined score was developed to improve the assessment of predicted protein complex models. Various approaches were tested to establish a combined score (See Methods). Given that *model confidence* and pDockQ2 are computed by combining other evaluated scores, these scores were excluded.

A linear regression-based model for the combination of all scores (ipLDDT, iPAE, pTM, ipTM, and VoroIF) was consistently identified as the best-performing (based on PCC) combined score across all three datasets (CF-T, CF-F and AF3), and referred to as C2Qscore (Combined Complex Quality score). This score was selected for further analyses (Suppl. Table 4, for weights, bias and maxima see Suppl. Tab. 5-7). Wilcoxon signed-rank test indicated that C2Qscore provided a statistically significant improvement compared to the unweighted combination of the individual scores (Suppl. Table 8).

Finally, ROC curve analysis was conducted to determine a cutoff for differentiating between correct models and incorrect ones (Suppl. Table 9). This analysis yielded a cutoff of 0.56 (AUC: 0.95) for models predicted using ColabFold with templates, 0.52 (AUC: 0.96) for models predicted without templates, and 0.65 (AUC: 0.94) for models predicted by AF3.

To further assess the performance of C2Qscore, it was tested on an independent dataset of 40 recently released structures of heterodimeric protein complexes determined by X-ray crystallography (resolution better than 3 Å). DockQ and all prediction-based scores (including the combined ones) were calculated for 160

models for CF-T, 159 models for CF-F, and 185 models for AF3. The cutoffs defined

in Sections 3.4 and 3.5 were applied to all scores to calculate the accuracy and

precision (Fig. 5). C2Qscore demonstrated an improvement in model classification

over the unweighted score (simple average of the individual scores) for CF-T

(Δaccuracy: +0.01) and AF3 (Δaccuracy: +0.03) and individual scores (Supp. Fig. 6).

For CF-F, the unweighted combined score and C2Qscore showed equal performance

(Δaccuracy: 0.0), though C2Qscore provided a clearer separation between incorrect

and correct models compared to the unweighted score.

Fig. 5: Unweighted combined score and C2Qscore for the X-ray crystallography test set for

CF-T, CF-F and AF3. True positives and true negatives are plotted in dark green and false

positives and false negatives in dark red. The in Section 3.5 determined cutoffs are shown as

dotted lines in the plots.

3.6. Evaluating the scores on dimers from larger assemblies

Next, we evaluated the performance of the unweighted combined score and C2Qscore

on a dataset of dimers derived from assemblies of higher order (≥ trimeric). This

evaluation aimed to assess the performance of the prediction methods and the scoring

approaches on dimers, without prior knowledge of the biological context. The cutoffs

determined in Section 3.5 were applied. This set included a total of 156 dimeric target

structures derived from cryoEM assemblies at resolutions higher than 2.3 Å.

Here, as before, the performance of C2Qscore was similar to the unweighted score,

showing a mild improvement (statistically insignificant) in model classification based

on DockQ only for CF-T (Δaccuracy: 0.01), while a mild decrease in performances of

CF-F (Δaccuracy: -0.02) and AF3 (Δaccuracy: -0.01) (Fig. 6, Supp. Fig. 7). The scoring

of these models had a higher percentage of false negatives across all datasets

compared to the X-ray test set (Fig. 5, Fig. 6A, Supp. Fig. 7).

To understand the general decrease in accuracy compared to the X-ray test set, we

further analyzed the cryoEM models by investigating the distribution of DockQ and

C2Qscore in relation to the number of possible configurations of the dimeric complex

derived from large assemblies. In some cases, the target chains of a dimer, which is

part of a larger complex, has homologous counterparts within the assembly forming

different configurations (Fig. 6B). Since AlphaFold2 and AlphaFold3 only accept the

sequence as input, one cannot know in advance which of the available configurations

correspond to the predicted structure. Fig. 6C depicts the dimeric complex formed by

the chains D and I of the large assembly with PDB-code 9ESY. Chain I is homologous

to chain A in the assembly, which also interacts with chain D, resulting in two possible

configurations for the target complex. The CF-T prediction closely resembles the dimer

formed by chains A and D (DockQ 0.74), but because DockQ is calculated for the

complex formed by chains I and D, DockQ is very low (0.01). In contrast, C2Qscore

for this prediction is relatively high, at 0.72.

In a typical prediction scenario, where no ground truth is available, the number of

potential configurations of a complex is unknown. Therefore, it is crucial to assess the

reliability of the scores when various spatial arrangements for two chains to form a

dimer ("configuration") exist. To address this, we used the "large assembly set" and

analyzed the DockQ and C2Qscore versus the number of configurations per target

dimer for the entire "large assembly" set. The dataset was filtered to include only those

templates for which more than one dimeric configuration exist, specifically those with

two or three configurations. Furthermore, the predictions were required to be classified

as correct based on DockQ (DockQ $\geq$ 0.23) for one of the existing configurations. It is

important to note that the presented DockQ scores (Fig. 6B) correspond to the

alignment between the target structure and the prediction. This, by definition, will result

in low DockQ values in cases where the prediction closely resembles one of the

alternative configurations but is compared to the target configuration.

For cases with two potential configurations of the dimer (n=55) the DockQ showed a

bimodal distribution, featuring very high and very low scores (Fig. 6B). However, the

C2Qscore distribution differed significantly, with many models scored with very high

or medium-to-high scores. For cases involving three possible configurations in CF-T

(n=33), the DockQ score peaked at low scores (due to more "different" configuration

from the target), while the distribution of the C2Qscore was spread in the entire range

of values. Similar trends were observed in the CF-F and AF3 dataset (Suppl. Fig. 8).

These findings suggest that both AF2 and AF3 struggle to differentiate between

probability and certainty when multiple configurations of a dimer are present. As a

result, lower scores (medium-to-high or lower) may be assigned to highly accurate

predictions, making the scores less reliable. This could explain the general decrease

in accuracy of the models in the large assembly set compared to the X-ray test set.

Fig. 6: A: Unweighted combined score and C2Qscore for the large assembly test set for CF-T. True positives and true negatives are plotted in dark green (upper right and lower left) and false positives and false negatives in dark red (upper left and lower right). The cutoffs we determined based on the benchmark set are shown in light blue. **B:** Distribution of DockQ and C2Qscore for CF-T cases of two (n=55) or three (n=33) potential configurations, for which the prediction resembles one of the configurations. **C:** CF-T prediction superposed on the large assembly (PDB: 9ES7; chains D&I). The prediction (blue), the target chains D (green), I (purple) and the homologue of chain I, chain A (gold), are highlighted on the assembly (gray). The interface of chain D and I (red, top, target) and chain D and A (hot pink, bottom, other possible configurations) are shown. The DockQ for the alignment of the prediction with the complex D-I and D-A and C2Qscore for the prediction are reported.

3.7. C2Qscore as a tool

The algorithm for calculating the C2Qscore for AlphaFold2/ColabFold and AlphaFold3 models has been integrated as a tool into our ChimeraX plug-in PICKLUSTER v2.0 (Pettersen et al. 2021; Genz et al. 2023). The new PICKLUSTER v2.0 identifies and clusters protein interfaces based on distance, providing a targeted approach for their

analysis. It offers access to a range of scoring metrics, including the following scores

analyzed in this work: pLDDT, PAE, ipLDDT, iPAE, pTM, ipTM, and *model confidence*.

Here, PICKLUSTER v2.0 has been updated to support predictions generated by

AlphaFold3, and the newly developed C2Qscore has been integrated as a feature in

the user-interface.

4.   Discussion

In this study, we presented a comprehensive evaluation of commonly used scores for

assessing protein complex models and compared three prediction methods:

ColabFold with templates (CF-T), ColabFold without templates (CF-F), and

AlphaFold3 (AF3). Using a benchmark set of 325 heterodimeric, high-resolution target

structures from the PDB, we analyzed the ability of these methods to produce accurate

models based on the CAPRI DockQ classifications. We also assessed the

effectiveness of the following scores: ipLDDT, iPAE, pTM, ipTM, *model confidence*,

pDockQ2 and VoroIF, in distinguishing correct from incorrect predictions.

Overall, we found that ipTM and *model confidence* consistently show the highest PCC

with DockQ, highest AUC for classifying models as correct or incorrect and high

accuracies across all datasets (CF-T, CF-F, and AF3), suggesting these scores as the

most reliable ones to assess heterodimeric protein complex models with both

ColabFold and AlphaFold3.

Furthermore, in general the interface-specific scores, ipLDDT and iPAE, showed

higher PCCs with DockQ than their global counterparts, pLDDT and PAE, consistent

with the findings of (Yin et al. 2022). This highlights the importance of interface-specific

metrics for assessing protein complex models.

Interestingly, our results reveal that also iPAE exhibits a high PCC with DockQ, ranking

just below ipTM and *model confidence*. Additionally, we observe a strong correlation

between PAE and pTM, and between iPAE and ipTM. This can be attributed to the method used to compute ipTM and pTM, both of which are derived from the PAE matrix (Evans et al. 2022). However, during this process, the values within the PAE matrix are weighted, such that residue pairs with lower PAE values contribute more significantly to ipTM and pTM. When averaged across the entire structure, this weighting effect is diminished.

Importantly , the cutoffs we define for differentiating correct from incorrect models using ipTM fall into the gray zone thresholds proposed by the AlphaFold web server (Accessed October 29, 2024, https://alphafoldserver.com/faq). However, while AlphaFold's ipTM gray zone leaves model quality open to interpretation, our cutoffs offer a practical guide, helping users to assess the reliability of protein complex models based on the chosen structure prediction method and settings. In this study, we establish a new, high-accuracy cutoff specifically for ColabFold, not only for ipTM but for all scoring metrics, to better differentiate between correct and incorrect models.

Notably, the determination of cutoffs was also effective for AF3, though with lower accuracy compared to CF-T and CF-F. Along with lower AUC, accuracy values and lowest mean PCC between the individual scores and DockQ, these findings suggest an overall weaker performance of assessment scores for AlphaFold3 compared ColabFold. This may be due to the differences in the network architecture and confidence estimation of AlphaFold3 compared to AlphaFold2-multimer (Abramson et al. 2024).

According to our benchmark, CF-T and AF3 produce similarly reliable predictions. This contrasts with the findings of (Abramson et al. 2024), which reported that AlphaFold3 improved protein complex accuracy compared to AlphaFold-multimer (v.2.3), the

version employed in ColabFold v.1.5.2 (which is also the version used in this work

(CF-T)).

Not surprisingly, our results show that as the prediction quality (DockQ) decreases,

the agreement among the prediction methods also declines. Interestingly, this

suggests that for cases of lower prediction quality, in particular when the scores are

around the "acceptable" zone, using multiple prediction methods and comparison of

the results may be beneficial.

We analyzed our benchmark for cases where the asymmetric unit (AU) differed from

the biological assembly (BA) in the PDB. Interestingly, in such instances, we observed

that all three methods could predict either the AU or the BA with high confidence, but

without prior knowledge, it would not be possible to determine which outcome reflects

the correct structure. This scenario becomes particularly problematic when the

predicted AU is correct based on scoring metrics but does not correspond to the

functional BA, potentially leading to false interpretations in subsequent experiments.

Such cases underline the importance of cautious interpretation of predictions,

particularly in scenarios where the biological relevance of the AU and BA is unclear

(Schweke et al. 2023).

To improve the ability of assessing protein complex models, we developed a combined

score, C2Qscore (Combined Complex Quality score) based on a linear regression

model that included ipLDDT, iPAE, pTM, ipTM and VoroIF. C2Qscore improved the

ability to assess model quality, particularly for CF-T and AF3 model predictions tested

on a X-ray crystallography dataset, where it outperformed the unweighted combination

of the individual scores.

Testing of C2Qscore on the 'large assembly' dataset revealed an increased

percentage of false negatives and a reduced classification accuracy across all

prediction methods compared to the X-ray test set. This suggests that when multiple

configurations of a dimer are possible, AlphaFold2 and AlphaFold3 may give lower

scores (medium-to-high rather than high) to highly accurate models, compromising the

reliability of the scores.

Finally, it is important to note that this study focused exclusively on protein pairs that

are known to interact, using the scoring metrics to evaluate the quality of the predicted

complexes. Other studies have applied these scores to determine whether a protein

pair interacts or not (Schweke et al. 2023). The latter approach should be used with

caution, as studies have shown that ipTM is sensitive to variations in sequence

constructs, leading to different ipTM scores despite unchanged predicted interface

contacts (Bret et al. 2024; Pándy-Szekeres et al. 2024). This suggests that while a

high ipTM score indicates confidence in the prediction, a low score does not

necessarily imply that protein pairs do not interact and scores in the grey zone may or

may not imply interaction. Tools like PPIscreenML (Mischley et al. 2024) may provide

potential solutions to address this challenge.

5.   Conclusion

Our study shows both the strengths and limitations of individual commonly used

assessment scores for evaluating heterodimeric protein complex models produced by

ColabFold with and without templates and by AlphaFold3. Our PICKLUSTER v2.0

plug-in enables the usage of these scores in an interactive and easy manner. Overall,

we recommend ipTM and *model confidence* for general use due to their high

correlation with DockQ. However, the interpretation of the scores needs to be

performed carefully, particularly for AlphaFold3 models. Notably, our analysis was

conducted exclusively on heterodimeric protein complex models without the

consideration of multiple interfaces. Further research should investigate the

transferability of the results to higher-order complexes. Moreover, exploring different

interfaces could reveal how scores perform in situations where interface regions differ

significantly in quality. With AlphaFold3 also enabling the prediction of protein-ligand,

protein-lipid, and protein-nucleotide interactions, future research could focus on

scoring metrics for these types of complexes. This also includes complexes involving

antibodies, which were excluded from the analysis in this work. Refining scoring

methods and expanding their applicability to diverse complex types and interface

characteristics will be for computational protein complex modeling to reach its full

potential.

6. Methods

6.1. Generation of the benchmark dataset (Suppl. Fig. 1)

PDB entries were initially filtered to include hetero-dimeric complexes with a release

date after 30.04.2018 (last date used in the AlphaFold training set), a release data

before 06.11.2023, and a refinement resolution ≤3.0 Å. The entries were grouped by

a sequence identity of >30% using PDB default settings (MMseqs2 (Steinegger and

Söding 2017)). The asymmetric unit of representative structures from groups that

satisfied the specified criteria were downloaded from the PDB, yielding a total of 1,381

complexes.

In the subsequent step, interacting complexes were defined as two chains having at

least three residues from each chain interacting with residues of the other chain, with

heavy atom distance cutoff of 5 Å, using PICKLUSTER (Genz et al. 2023). Non-

interacting complexes, as well as any chain with less than 50 residues, were filtered

out using the PICKLUSTER pipeline. This process resulted in a total of 580 protein

complexes.

In the next step, a PDB search and a manual analysis were conducted in order to filter

out entries containing antibodies or nanobodies. Subsequently, to ensure that the

dimers could be classified as heterodimeric complexes, homology within the

complexes was assessed by application of CD-HIT (Fu et al. 2012) with a 30%

sequence identity threshold, resulting in 397 complexes. Moreover, only templates for

which one BA assigned in the PDB equaled the AU were included in the benchmark

set, resulting in 325 target complex structures in the final benchmark set.

X-ray crystallography test set

The X-ray crystallography test set (X-ray test set) was curated following the same

pipeline as for the benchmark set, with only slight adjustments to the selection criteria

(Suppl. Fig. 1). Target structures present in the benchmark set were excluded from

the X-ray test set, resulting in 40 target complex structures in the X-ray test set.

Large assembly test set

The set of dimers from larger assemblies ("large assembly test set") was curated

following the protocol established for the benchmark set (Suppl. Fig. 1), with the

following modifications to the selection criteria: the dimers were derived from higher-

order assemblies ($\geq$ trimeric) with a resolution $\leq$2.3 Å resolved by cryoEM. A stricter

resolution cutoff was implemented compared to the original benchmark set due to the

potential variability in local resolution relative to the reported global resolution in

structures resolved by cryoEM (Vilas et al. 2020). To ensure the non-redundancy of

dimers derived from the same larger assembly, the homology of the dimers was

evaluated using CD-HIT (Fu et al. 2012) with a 30% sequence identity threshold,

resulting in 156 dimeric target structures included in the large assembly test set.

6.2. Model generation

Three AI-based structure prediction approaches were used: CF-F, CF-T and AF3, to create three corresponding datasets.

For the CF-F dataset structural models were predicted from sequence using local ColabFold v1.5.2 (Mirdita et al. 2022). Default parameters were applied for multiple sequence alignment (MSA) generation (MSA mode: mmseqs_uniref_env) and three recycles were performed. For each template, five models were generated, all of which were included in the dataset. Relaxation was performed to all five models.

For the CF-T dataset structural models were predicted using the same criteria as for the CF-F dataset. The only difference was the activation of the template option.

For the AF3 dataset structural models were predicted using the AlphaFold3 web server (https://alphafoldserver.com/) (Abramson et al. 2024) with default settings, which includes the usage of templates.

6.3. Model preparation

For the assessment of the model quality with DockQ, after prediction with ColabFold or AlphaFold3 residues were renumbered according to the template residue numbering, utilizing the fix_numbering.pl script provided in the DockQ package. An in-house Python script was employed to rename chain identifiers in the models, ensuring alignment between the template and the model chains.

AF3 models were initially predicted in mmCIF format, and to enable for the assessment with DockQ, they were converted into PDB format with a Python script that uses the *Biopython (Cock et al. 2009)* package.

6.4. Reference-based score

DockQ v1.0 (Basu and Wallner 2016) (https://github.com/bjornwallner/DockQ) (https://github.com/bjornwallner/DockQ) was used to evaluate the quality of the

predicted models, by comparing the predicted models of a complex against the native

complex structure. The score combines the criteria from the CAPRI competition

(Lensink and Wodak 2013) into a single value. Scores range from 0 to 1, with 1

indicating a perfect match between the interface of the predicted model and that of the

native complex structure. Threshold values of 0.23, 0.49, and 0.8 were used to

categorize predictions as acceptable, medium, and high quality respectively,

according to CAPRI standards. DockQ scores were determined by comparing the

predicted models of a complex against the native complex structure. DockQ v1.0 was

installed according to https://github.com/bjornwallner/DockQ.

6.5. Prediction-based scores

The scores used for assessment of models are: pLDDT (predicted local difference

distance test) (Jumper et al. 2021), PAE (predicted alignment error) (Evans et al.

2022), ipLDDT (interface pLDDT) (Jumper et al. 2021; Genz et al. 2023), iPAE

(interface PAE) (Evans et al. 2022; Genz et al. 2023), pTM (predicted TM-score)

(Jumper et al. 2021), ipTM (interface pTM) (Evans et al. 2022), *model confidence*

(Evans et al. 2022), pDockQ2 (Zhu et al. 2023) and VoroIF (VoroIF-GNN) (Olechnovič

and Venclovas 2023 Jul 21). The details about each score, including the range, what

it measures and whether it is interface specific or not, are provided in Supp. Table. 1.

6.6. Performance metrics

To measure the overall performance of scores over the different datasets we used a

number of approaches:

Pearson correlation coefficient: The Pearson correlation coefficient (PCC) gives an

indication of the strength of the linear relationship between two datasets. The PCC

ranges from -1 to +1 with 0 indicating no correlation and correlations of -1/+1 implying

an exact linear relationship. The PCC only detects linear dependencies between the

datasets. Positive values indicate a correlation whilst negative values imply anti-

correlation (Benesty et al. 2009).

The PCC was calculated using the stats package provided in the *SciPy* v1.11.3 Python

package (Virtanen et al. 2020).

ROC-curves and AUC: To identify the best performing cutoff for the scores, a Receiver

Operator Curve (ROC) analysis was conducted. The optimal cutoff for the score was

determined by maximizing the separation between correctly and incorrectly assessed

models, calculated through the True Positive Rate (TPR) and False Positive Rate

(FPR), which were plotted as the ROC curve. The best performing cutoff was identified

as the point with the maximum distance from the diagonal in the ROC curve (Melo and

Sali 2007). For each point on the ROC curve, the cutoff values were incrementally

increased depending on the score type (pLDDT/ipLDDT: 5; iPAE/PAE: 1; all other

scores: 0.05). The Area Under the Curve (AUC) was calculated to quantify the

accuracy of the metric being evaluated, where an AUC of 0.5 indicates random

performance, and an AUC of 1 represents perfect discrimination. Both the ROC curves

and AUCs were computed using a Python script utilizing the metrics module from the

Scikit-learn v1.3.0 Python package (Pedregosa et al. 2011).

Accuracy: Accuracy is defined as the ratio of (TP+TN)/(TP+TN+FP+FN), where TP

represents the number of true positives, TN the number of true negatives, FP the

number of false positives and FN denotes the number of false negatives. The metric

is used to evaluate the performance of a model, indicating how frequently the model

makes correct predictions. It is determined by comparing the number of correct

predictions to the total number of predictions made by the model. The metric is

expressed as a value between 0 and 1, with 1 indicating the optimal outcome. The

accuracy provides an overall measure of the reliability of a model (Powers 2020).

Precision: Precision is defined as the ratio TP/(TP+FP). Precision quantifies the

proportion of correctly identified positive samples out of all samples predicted as

positive. It therefore reflects the ability of the classifier to avoid falsely classifying

negative samples as positive. A precision value of 1 indicates perfect performance,

with no false positives, while a value of 0 represents the worst outcome, with all

predicted positives being incorrect. Precision shows how often a model is correct when

predicting the target class (Powers 2020).

Wilcoxon signed rank (WSR) test: The WSR test is a nonparametric test procedure for

the evaluation of the significance of paired data (Woolson 2005). This non-parametric

test was chosen due to its ability to compare matched data without assuming

normality. The p-value was calculated to determine the significance of the observed

difference. A significance threshold of $p < 0.05$ was applied. The WSR test was

implemented using the stats package provided in the *SciPy* Python package (Virtanen

et al. 2020).

6.7. Influence of the distance threshold for the definition of the interface on

the scores

To determine the interface PAE (iPAE) and interface pLDDT (ipLDDT), the interface

was defined as residues with less than 5Å (Evans et al. 2022) distance between heavy

atoms (non-hydrogen atoms) of the two chains in the heterodimeric structure, which

was calculated with PICKLUSTER (Genz et al. 2023).

To investigate the impact of the distance parameter on ipLDDT and iPAE, we chose

to do this analysis on the dataset generated using CF-T, which had 1,612 models in

total. We then computed ipLDDT and iPAE on these models using distance thresholds

in a range of 5 to 9Å (1Å steps).

6.8. Linear and Lasso regression

Linear regression was tested as the first approach for a weighted combined score. It

fits a linear model with coefficients by minimizing the residual sum of squares between

the target values in the datasets and the ones predicted by the approximation of the

linear model. A Lasso regression model was evaluated as the second approach to

define a weighted combined score. This approach uses a linear model that is fitted

under the assumption that only few of the coefficients are non-zero. Therefore, it

identifies the most relevant features and reduces the number of input variables.

Linear and Lasso regression were performed by using the linear_model package

provided in the *Scikit-learn* Python package (Pedregosa et al. 2011).

6.9. Combined scoring

To enable a combined score, both ipLDDT and iPAE were normalized between 0 and

1, representing the optimal outcome. Subsequently, various approaches were tested

to establish a combined score demonstrating superior model assessment capacity.

Given that *model confidence* and pDockQ2 are computed by combining other

evaluated scores, these scores were excluded.

In the first approach we selected the best combination of scores (ipLDDT, iPAE, pTM,

ipTM, and VoroIF) based on PCC with DockQ as the evaluation criterion. All possible

combinations without repetition of equally weighted scores within each set were

tested, and PCCs were computed for each. In the second approach we employed

linear regression, applied to both the full combination of scores and the best-

performing combination identified in the first approach. Finally, Lasso regression was

tested as an approach for improvement over using individual scores.

7. Acknowledgments and Funding

We thank the Topf group, especially Thomas Mulvaney, Karen Manalastas-Cantos

and Natan Nagar, for discussions and valuable feedback. This work was supported by

the cooperation of Leibniz Institute of Virology Strategic Incentive Program and the

Leibniz ScienceCampus InterACt (funded by the BWFGB Hamburg and the Leibniz

Association), the BMBF Computational Life Sciences project (ASPIRE, 031L028), the

Landesforschungsförderung Hamburg (HamburgX) and DFG CRC1648.

Conflict of interest: none declared.

8. References

Abramson J, Adler J, Dunger J, Evans R, Green T, Pritzel A, Ronneberger O, Willmore L,
Ballard AJ, Bambrick J, et al. 2024. Accurate structure prediction of biomolecular interactions
with AlphaFold 3. Nature. 630(8016):493–500.

Baker D, Sali A. 2001. Protein structure prediction and structural genomics. Science.
294(5540):93–96.

Basu S, Wallner B. 2016. DockQ: A Quality Measure for Protein-Protein Docking Models.
PLoS One. 11(8):e0161879.

Benesty J, Chen J, Huang Y, Cohen I. 2009. Pearson Correlation Coefficient. In: Noise
Reduction in Speech Processing. Berlin, Heidelberg: Springer Berlin Heidelberg. p. 1–4.

Bret H, Gao J, Zea DJ, Andreani J, Guérois R. 2024. From interaction networks to
interfaces, scanning intrinsically disordered regions using AlphaFold2. Nat Commun. 15.
doi:10.1038/s41467-023-44288-7. https://www.nature.com/articles/s41467-023-44288-7.

Bryant P, Pozzati G, Elofsson A. 2022. Improved prediction of protein-protein interactions
using AlphaFold2. Nat Commun. 13(1):1265.

Cock PJA, Antao T, Chang JT, Chapman BA, Cox CJ, Dalke A, Friedberg I, Hamelryck T,
Kauff F, Wilczynski B, et al. 2009. Biopython: freely available Python tools for computational
molecular biology and bioinformatics. Bioinformatics. 25(11):1422–1423.

Cozzetto D, Kryshtafovych A, Ceriani M, Tramontano A. 2007. Assessment of predictions in
the model quality assessment category. Proteins. 69 Suppl 8(S8):175–183.

Edmunds NS, Alharbi SMA, Genc AG, Adiyaman R, McGuffin LJ. 2023 Jun 14. Estimation of
model accuracy in CASP15 using the ModFOLDdock server. Proteins.

doi:10.1002/prot.26532. http://dx.doi.org/10.1002/prot.26532.

Evans R, O'Neill M, Pritzel A, Antropova N, Senior A, Green T, Žídek A, Bates R, Blackwell
S, Yim J, et al. 2022. Protein complex prediction with AlphaFold-Multimer.
bioRxiv.:2021.10.04.463034. doi:10.1101/2021.10.04.463034. [accessed 2022 Sep 5].
https://www.biorxiv.org/content/biorxiv/early/2022/03/10/2021.10.04.463034.

Fu L, Niu B, Zhu Z, Wu S, Li W. 2012. CD-HIT: accelerated for clustering the next-
generation sequencing data. Bioinformatics. 28(23):3150–3152.

Genz LR, Mulvaney T, Nair S, Topf M. 2023. PICKLUSTER: a protein-interface clustering
and analysis plug-in for UCSF ChimeraX. Bioinformatics. 39(11):btad629.

Hornak V, Abel R, Okur A, Strockbine B, Roitberg A, Simmerling C. 2006. Comparison of
multiple Amber force fields and development of improved protein backbone parameters.
Proteins. 65(3):712–725.

Jumper J, Evans R, Pritzel A, Green T, Figurnov M, Ronneberger O, Tunyasuvunakool K,
Bates R, Žídek A, Potapenko A, et al. 2021. Highly accurate protein structure prediction with
AlphaFold. Nature. 596(7873):583–589.

Lensink MF, Wodak SJ. 2013. Docking, scoring, and affinity prediction in CAPRI. Proteins.
81(12):2082–2095.

Mariani V, Biasini M, Barbato A, Schwede T. 2013. lDDT: a local superposition-free score for
comparing protein structures and models using distance difference tests. Bioinformatics.
29(21):2722–2728.

Melo F, Sali A. 2007. Fold assessment for comparative protein structure modeling. Protein
Sci. 16(11):2412–2426.

Mirdita M, Schütze K, Moriwaki Y, Heo L, Ovchinnikov S, Steinegger M. 2022. ColabFold:
making protein folding accessible to all. Nat Methods. 19(6):679–682.

Mischley V, Maier J, Chen J, Karanicolas J. 2024. PPIscreenML: Structure-based screening
for protein-protein interactions using AlphaFold. doi:10.7554/elife.98179.1.
http://dx.doi.org/10.7554/elife.98179.1.

Namba K, Makino F. 2022. Recent progress and future perspective of electron
cryomicroscopy for structural life sciences. Microscopy (Oxf). 71(Supplement_1):i3–i14.

Olechnovič K, Venclovas Č. 2019. VoroMQA web server for assessing three-dimensional
structures of proteins and protein complexes. Nucleic Acids Res. 47(W1):W437–W442.

Olechnovič K, Venclovas Č. 2023 Jul 21. VoroIF-GNN: Voronoi tessellation-derived protein-
protein interface assessment using a graph neural network. Proteins.
doi:10.1002/prot.26554. http://dx.doi.org/10.1002/prot.26554.

Pándy-Szekeres G, Taracena Herrera LP, Caroli J, Kermani AA, Kulkarni Y, Keserű GM,
Gloriam DE. 2024. GproteinDb in 2024: new G protein-GPCR couplings, AlphaFold2-
multimer models and interface interactions. Nucleic Acids Res. 52(D1):D466–D475.

Pedregosa F, Varoquaux G, Gramfort A, Michel V, Thirion B, Grisel O, Blondel M, Louppe G,
Prettenhofer P, Weiss R, et al. 2011. Scikit-learn: Machine Learning in Python. J Mach Learn
Res. abs/1201.0490:2825–2830.

Pettersen EF, Goddard TD, Huang CC, Meng EC, Couch GS, Croll TI, Morris JH, Ferrin TE.

2021. UCSF ChimeraX: Structure visualization for researchers, educators, and developers.
Protein Sci. 30(1):70–82.

Pierce BG, Hourai Y, Weng Z. 2011. Accelerating protein docking in ZDOCK using an
advanced 3D convolution library. PLoS One. 6(9):e24657.

Powers DMW. 2020. Evaluation: from precision, recall and F-measure to ROC,
informedness, markedness and correlation. arXiv [csLG]. http://arxiv.org/abs/2010.16061.

Schulz GE, Schirmer RH. 2013. Principles Protein Structure. Berlin/Heidelberg, Germany:
Springer Science & Business Media.

Schweke H, Xu Q, Tauriello G, Pantolini L, Schwede T, Cazals F, Lhéritier A, Fernandez-
Recio J, Rodríguez-Lumbreras LA, Schueler-Furman O, et al. 2023. Discriminating
physiological from non-physiological interfaces in structures of protein complexes: A
community-wide study. Proteomics. 23(17):e2200323.

Smyth MS, Martin JH. 2000. X ray crystallography. Mol Pathol. 53(1):8–14.

Steinegger M, Söding J. 2017. MMseqs2 enables sensitive protein sequence searching for
the analysis of massive data sets. Nat Biotechnol. 35(11):1026–1028.

Studer G, Tauriello G, Schwede T. 2023 Oct 19. Assessment of the assessment-All about
complexes. Proteins. doi:10.1002/prot.26612. http://dx.doi.org/10.1002/prot.26612.

Varadi M, Anyango S, Deshpande M, Nair S, Natassia C, Yordanova G, Yuan D, Stroe O,
Wood G, Laydon A, et al. 2022. AlphaFold Protein Structure Database: massively expanding
the structural coverage of protein-sequence space with high-accuracy models. Nucleic Acids
Res. 50(D1):D439–D444.

Vilas JL, Heymann JB, Tagare HD, Ramirez-Aportela E, Carazo JM, Sorzano C. 2020. Local
resolution estimates of cryoEM reconstructions. Curr Opin Struct Biol. 64:74–78.

Virtanen P, Gommers R, Oliphant TE, Haberland M, Reddy T, Cournapeau D, Burovski E,
Peterson P, Weckesser W, Bright J, et al. 2020. SciPy 1.0: fundamental algorithms for
scientific computing in Python. Nat Methods. 17(3):261–272.

Woolson RF. 2005. Wilcoxon Signed-Rank Test. In: Encyclopedia of Biostatistics.
Chichester, UK: John Wiley & Sons, Ltd.
https://onlinelibrary.wiley.com/doi/abs/10.1002/0470011815.b2a15177.

Xue LC, Dobbs D, Bonvin AMJJ, Honavar V. 2015. Computational prediction of protein
interfaces: A review of data driven methods. FEBS Lett. 589(23):3516–3526.

Yin R, Feng BY, Varshney A, Pierce BG. 2022. Benchmarking AlphaFold for protein complex
modeling reveals accuracy determinants. Protein Sci. 31(8):e4379.

Zhang Y, Skolnick J. 2004. Scoring function for automated assessment of protein structure
template quality. Proteins. 57(4):702–710.

Zhu W, Shenoy A, Kundrotas P, Elofsson A. 2023. Evaluation of AlphaFold-Multimer
prediction on multi-chain protein complexes. Bioinformatics. 39(7):btad424.