All spectral frequencies of neural activity reveal semantic representation in the human

anterior ventral temporal cortex

Saskia L. Frisby[1], Ajay D. Halai[1], Christopher R. Cox[2], Alex Clarke[3], Akihiro Shimotake[4,5],

Takayuki Kikuchi[6], Takeharu Kuneida[6,7], Yoshiki Arakawa[6], Ryosuke Takahashi[4], Akio Ikeda[8],

Riki Matsumoto[4,9], Timothy T. Rogers[10], & Matthew A. Lambon Ralph[1]

[1] MRC Cognition and Brain Sciences Unit, University of Cambridge, Cambridge, UK

[2] Department of Psychology, Louisiana State University, Baton Rouge, USA

[3] Department of Psychology, University of Warwick, Warwick, UK

[4] Department of Neurology, Kyoto University Graduate School of Medicine, Kyoto, Japan

[5] Clinical Research Center, National Hospital Organization Utano Hospital, Kyoto, Japan

[6] Department of Neurosurgery, Kyoto University Graduate School of Medicine, Kyoto, Japan

[7] Department of Neurosurgery, Ehime University Graduate School of Medicine, Ehime, Japan

[8] Department of Epilepsy, Movement Disorders and Physiology; Kyoto University Graduate

School of Medicine; Kyoto; Japan

[9] Division of Neurology, Kobe University Graduate School of Medicine, Kusunoki-cho, Kobe,

Japan

[10] Department of Psychology, University of Wisconsin–Madison, Madison, USA

Keywords: electrocorticography, ECoG, intracranial electrophysiology, time-frequency

analysis, semantic representation, decoding, multivariate pattern analysis

Abstract:

Intracranial electrophysiology offers a unique insight into the nature of information

representation in the brain – it can be used to disentangle information encoded in local

neuronal activity (gamma and high gamma frequencies) from information encoded via long-

range interactions (lower frequencies). We used regularised logistic regression to decode

animacy from time-frequency power and phase extracted from electrocorticography (ECoG)

grid electrode data recorded on the surface of human vATL. Power in gamma (30 – 60 Hz)

and high gamma (42 – 200 Hz) produced reliable decoding, indicating that semantic

information is indeed expressed by local populations in vATL. However, power from a wide

range of frequencies (4 – 200 Hz) produced significantly higher decoding accuracy and also

exhibited the same rapidly-changing dynamic code previously observed when decoding

voltage. These findings support the theory that semantic information is encoded by a local

vATL "hub" that interacts with distributed cortical "spokes".

1. Introduction

Semantic cognition is our ability to understand and respond in a meaningful way to objects that we see, language that we hear, events that we experience, and any other stimuli in our environment. The ventral anterior temporal lobes (vATLs) play a critical role in such abilities (Lambon Ralph et al., 2017; Patterson et al., 2007; Rogers et al., 2004), but it remains unclear *how* neural activity in these regions encodes semantic information. Electrocorticography (ECoG) grid electrode data are a rare and informative resource, sensitive to activity at a wide range of frequencies including very high-frequency activity thought to indicate local neuronal activity (Başar-Eroglu et al., 1996; Bressler, 1990; Merker, 2013; Nir et al., 2007). Although prior work has shown that surface voltages express information about stimulus animacy (is it an animal or not?; Y. Chen et al., 2016; Rogers et al., 2021), voltages are a conflation of high- and lower-frequency activity; therefore, apparent representation of semantic information by the vATL may actually reflect incoming signals from more remote areas. We address these questions by applying regularised logistic regression — a multivariate decoding procedure that makes minimal assumptions about the nature of neural representations (Cox & Rogers, 2021; Frisby et al., 2023) — to time-frequency power and phase extracted from a large sample of ECoG data (n = 18).

Extensive prior work suggests that the vATLs serve as a representational "hub", interacting with multiple "spokes" that each encode modality-specific information about the environment. By virtue of these interactions, and over the course of learning and development, the vATLs come to express transmodal conceptual similarity structure and enable generalisation of knowledge across items and contexts (Lambon Ralph et al., 2010, 2017; Patterson et al., 2007; Rogers et al., 2004). The "hub-and-spoke" model is supported by convergent evidence from neuropsychology (Hodges & Patterson, 2007), positron emission tomography (PET; Devlin et al., 2000), distortion-corrected functional magnetic resonance imaging (fMRI; Binney et al., 2010; Halai et al., 2014; Visser et al., 2010), magnetoencephalography (MEG; Mollo et al., 2017), neuro-computational simulations (L. Chen et al., 2017; Rogers et al., 2004, 2021), transcranial magnetic stimulation (TMS; Pobric et al., 2007, 2010a, 2010b), invasive cortical stimulation mapping (Lüders et al., 1991; Matoba et al., 2024), and ECoG (Halgren et al., 2006; Nobre & McCarthy, 1995; Sato et al., 2021; Shimotake et al., 2015).

Multivariate decoding approaches have only recently been applied to ECoG data in an attempt to characterise, not simply where and when task-related changes in neuronal activity occur, but what information those changes represent. Most of these analyses have focused on voltage (Y. Chen et al., 2016; Cox et al., 2024; Liu et al., 2009; Nagata et al., 2022; Rogers et al., 2021, cf. Clarke, 2020; Rupp et al., 2017; Wang et al., 2011). However, voltage reflects a blend of activity at different frequencies and, while gamma (> 30 Hz) and high gamma (> ~60 Hz) activity is thought to reflect local neuronal activity (Başar-Eroglu et al., 1996; Bressler, 1990; Merker, 2013; Nir et al., 2007), activity at lower frequencies may reflect transmission of information over varying cortical distances (Canolty & Knight, 2010; Lachaux et al., 2012), which may be important for assembling the spatially-distributed representations posited by the hub-and-spoke model.

The first aim of this paper was to clarify the role of time-frequency power and phase in semantic representation in the vATL and to relate this to voltage findings (Y. Chen et al., 2016; Cox et al., 2024; Liu et al., 2009; Nagata et al., 2022; Rogers et al., 2021) and to other sources of evidence (Lambon Ralph et al., 2017). The dataset consisted of ECoG data collected from a large cohort of patients (n = 18) while they named line drawings of animate and inanimate objects. ECoG offers excellent spatial and temporal resolution and the use of grid electrodes on the cortical surface offers much greater coverage than can be obtained with cortical depth electrodes — important for detecting semantic representations that may be distributed across space (Merker, 2013; Rogers et al., 2021). Crucially for this study, intracranial methods are necessary for revealing high gamma activity that is blocked by the skull and scalp when using noninvasive methods such as EEG or MEG (Lachaux et al., 2012; Parvizi & Kastner, 2018).

We used regularised logistic regression to decode information from time-frequency power and phase – a method that, unlike decoding methods that have previously been applied to ECoG time-frequency data (Clarke, 2020; Rupp et al., 2017; Wang et al., 2011) makes very few assumptions about the properties of the underlying code (Frisby et al., 2023). Regularised regression can detect representations whether individual populations or frequencies encode pieces of information separately, or whether the relationship between information and neural activity can be understood only by considering multiple populations and/or frequencies simultaneously (Frisby et al., 2023). Since it relies on parameter fitting

rather than simple correlations, it is resistant to false positives and false negatives

associated with purely correlational approaches (Cox et al., 2024).

We tested whether animacy (a) can be decoded from time-frequency power and/or

phase; (b) if so, from which frequency ranges and at what timepoints; and (c) how these

results relate to decoding of voltage. These analyses therefore allowed us to determine

whether time-frequency- and voltage-based decoding offer similar or different conclusions

about the timecourse of semantic representation in the vATL. Decoding accuracy in gamma

and high gamma ranges (independently of other ranges) allowed us to determine whether

semantic information is encoded by local neural activity within the vATL.

The second aim of this paper was to assess whether the dynamic and nonlinear

changes to semantic representation observed in voltage decoding (Rogers et al., 2021) also

arise within or across frequency ranges. Dynamic change in representation can be measured

via the *temporal generalisation* of a decoding model (Carlson et al., 2013; Cichy et al., 2014;

Contini et al., 2017; King & Dehaene, 2014; Rogers et al., 2021). The model is fitted to neural

data at a given timepoint, then is assessed at other timepoints. If a classifier shows above-

chance hold-out accuracy when fitted to timepoint A, and also shows above-chance

accuracy when used to decode at timepoint B, we can conclude that information is encoded

similarly at both timepoints. Conversely, if a classifier trained and succeeding in timepoint A

then fails when tested on timepoint B, and if the reverse pattern also holds (a model trained

on B succeeds on B but fails on A), this suggests that the target information is encoded by

different neural patterns at different timepoints. That is, such a pattern suggests dynamic

change in neural representation of the target information.

When applied to ECoG voltage data, this technique revealed four interesting

characteristics of the semantic code in the vATL (Rogers et al., 2021):

1. Classifiers fitted and tested at overlapping 50 ms windows showed reliable

decoding from about 100ms post stimulus onset through the remainder of the processing

window (1650ms), suggesting that animacy is *constantly decodable* from the moment

stimulus-driven activity reaches the vATL until the response.

2. Classifiers trained at a given window generalised to temporal neighbours (both

preceding and succeeding), but not to temporally remote windows; that is, voltage-based

neural decoding showed *local temporal generalisation*, suggesting a dynamically-changing

neural code for animacy.

3. The width of the temporal generalisation window for a given classifier was quite narrow early in stimulus processing but widened over time, indicating that dynamic change to the voltage-based code is initially quite rapid but slows with further processing.

4. The direction of the neural code — whether an increase in voltage at a particular electrode signified increased or decreased probability that the stimulus is animate — changed over the course of processing, so that voltage deflections might signify different things at different timepoints at the same electrode.

Together these properties suggest that, while information about animacy is expressed in voltage throughout stimulus processing, the precise way that this information is encoded changes rapidly and nonlinearly, with change slowing as the system settles into a steady state. Moreover, these patterns mirrored those observed in a recurrent deep neural network model of semantic processing, suggesting that such models may offer a useful way of thinking about representational dynamics in real neural systems (Rogers et al., 2021).

The second goal of this paper was to assess whether these properties (constant decodability, local temporal generalisation, widening generalisation window, and change in code direction) are observed when decoding time-frequency power or phase information, across ranges or within each range considered independently. Answers to these questions could clarify whether these dynamic characteristics of representation arise from rapid local activity (i.e., driven by gamma/high gamma) and/or from more remote input (driven by lower frequencies).

1. Results

1.1. Relative decoding accuracy using spectral frequency power or phase vs. voltage

The ECoG data were collected from 6 - 52 subdural grid electrodes implanted over the ventral anterior temporal lobe (vATL) in 18 patients. The patients named line drawings of animals and inanimate objects that were used in prior work and matched for age of acquisition, concreteness, word frequency, and familiarity (Dilkina & Lambon Ralph, 2012). Time-frequency power and phase were extracted using complex Morlet wavelet convolution (see Methods). Classifiers were fitted using LASSO regularisation (Tibshirani, 1996) and

assessed using ten-fold cross-validation. The classifiers were trained either on frequency

features (vectors of power or phase values extracted from multiple frequencies from

multiple electrodes at a single timepoint) or on voltage features (vectors of voltage values

extracted from multiple electrodes from a 50 ms window centred on the timepoint of

interest). Separate classifiers were trained for timepoints between 0 and 1650 ms in 10 ms

time steps (0 ms, 10 ms, 20 ms, …). Each classifier was tested on every possible timepoint.

We first tested whether it was possible to decode the animacy of the stimuli using

time-frequency power and/or phase and whether decoding performance was comparable to

voltage (Rogers et al., 2021). We compared classifiers trained on frequency features of

power or phase at 60 frequencies, logarithmically spaced between 4 and 200 Hz, to

classifiers trained on voltage features. Figure 1A shows the results. Time-frequency power

showed an almost identical decoding profile to voltage – hold-out accuracy rose to around

0.7 at 200 ms post stimulus onset and remained significantly above chance (0.5) throughout

the time window. At no point was it possible to decode animacy from classifiers trained on

phase.

Next, to disentangle the role of local neural activity versus distal input, we trained

classifiers on frequency features composed only of power or phase values from one

frequency range - theta (4 – 7 Hz), alpha (12 – 18 Hz), beta (13 – 30 Hz), gamma (30 – 60 Hz)

and high gamma (42 – 200 Hz). Figure 1B shows the decoding profile in each range. For

power, the patterns were almost indistinguishable, showing the same rise to about 0.6 and

remaining above chance for most of the time window of interest. On the assumption that

gamma and high gamma frequencies represent local neural activity, these results confirmed

that local neural activity in the vATL expresses semantic information. However, we found

that power in every range was sufficient, and no range was necessary, for above-chance

decoding. For phase, decoding was rarely above chance, with the exception of weak

decoding using theta data in the window 0 - 500 ms. The remaining analyses therefore

focused on characterising semantic information encoded in time-frequency power.

Figure 1C shows hold-out accuracy for classifiers trained on power within a single

range compared to accuracy for classifiers trained on power at all 60 frequencies. For each

range there was a time window during which decoding on all frequencies reached its peak

and decoding on a single range performed significantly less well. This indicated that no

individual range contains sufficient information to enable decoding accuracy comparable to

accuracy based on all frequencies. To investigate which combination of frequencies enabled

such successful decoding, we inspected the coefficients on each frequency. Figure 1D shows

these averaged across electrodes for one example patient (similar plots for all patients are

shown in Supplementary Materials S1, Figure S1; plots showing coefficients on individual

electrodes for the one sample patient are shown in Supplementary Materials S1, Figure S2).

Throughout the time window, frequencies across the whole range were selected by the

classifier and thus contributed to decoding performance. This is evidence that the vATL

represents semantic information via a *transfrequency* code, by which we mean that

frequencies within the theta, alpha, beta, gamma and high gamma ranges all contribute to

information representation.

Figure 1: Semantic decoding with time-frequency power and phase. (A) Mean and 95%
confidence interval of the hold-out accuracy for classifiers trained on power or phase
frequency features for all frequencies between 4 and 200 Hz (blue) or on voltage features
(brown). Coloured dots indicate a significant difference between classifier accuracy and
chance (0.5, one-sample t-test with probabilities adjusted to control the false-discovery rate
at α = 0.05). Black dots indicate a significant difference between accuracies at a given
timepoint (paired t-tests with probabilities adjusted to control the false-discovery rate at α =
0.05). (B) Mean and 95% confidence interval of the hold-out accuracy for classifiers trained
on frequency features composed only of power or phase values from a given range - theta
(4 – 7 Hz, red), alpha (12 – 18 Hz, orange), beta (13 – 30 Hz, yellow), gamma (30 – 60 Hz,
light green) and high gamma (42 – 200 Hz, dark green). Coloured dots indicate a significant

difference between classifier accuracy and chance (0.5, one-sample t-test with probabilities adjusted to control the false-discovery rate at α = 0.05). (C) Mean and 95% confidence interval of the hold-out accuracy for classifiers trained on frequency features composed only of power or phase values from a given range compared to classifiers trained on frequency features including all frequencies between 4 and 200 Hz. Coloured dots indicate a significant difference between classifier accuracy and chance; black dots indicate a significant difference between accuracies. (D) Feature selection of each frequency at each timepoint (averaged across electrodes) for classifiers trained on frequency feature vectors including all frequencies between 4 and 200 Hz for a single patient. Features with a nonzero coefficient are shown in colour.

1.2. Does the time-frequency semantic code change dynamically?

Our second question was whether the time-frequency code changes dynamically over stimulus processing in a manner similar to the voltage code. The preceding results show that time-frequency power exhibits one property also observed in voltage, namely constant decodability - animacy can be decoded from whole-spectrum power, and from power within each frequency range independently, from about 100-200ms post onset until about the mean onset of naming (1190ms in the subset of patients analysed by Rogers et al., 2021). Next, we applied the method of temporal generalisation to investigate whether time-frequency power, like voltage, shows (a) local temporal generalisation, indicating a changing neural code, and (b) a widening generalisation window, indicating rapid initial change that slows over time (Rogers et al., 2021).

Figure 2A shows the generalisation profile of classifiers trained on power at all frequencies (left) and those trained on voltage (right). The diagonal of each matrix indicates the hold-out accuracy of classifiers trained and tested at the same timepoint. Points closer to the diagonal indicate how well a classifier generalises to neighbouring timepoints, while points far from the diagonal indicate how well it generalises to timepoints further away. Local temporal generalisation is signified by better decoding close to the diagonal. In these plots, the most saturated colours indicate classifier accuracies statistically indistinguishable from the best-performing classifier at the same timepoint. Increasingly desaturated colours indicate accuracies that are reliably worse than the best-performing classifier at increasingly strict significance thresholds. Horizontal black bars indicate classifiers that did not exceed chance performance even when evaluated on held-out stimuli from the training timepoint.

The superimposed squares on each plot provide illustrative referents for evaluating

whether the temporal generalisation pattern signifies a dynamically changing code. If

classification accuracy is significantly higher for the two on-diagonal corners than the two

off-diagonal corners, this signifies that (a) the neural signal reliably encodes semantic

information at the two timepoints but (b) the signal changes in nature – whatever features

of the signal support the good performance at the training timepoint are not present at the

more remote testing points. This pattern is clearly observed for both voltage and whole-

spectrum power (Figure 2A), indicating that the transfrequency semantic code exhibits

dynamic properties similar to voltage.

When decoding from each range separately, however, the local generalisation

pattern was less clear overall, and arguably present only in lower frequency ranges (theta,

alpha, and beta; Figure 2B). Gamma and high gamma showed a different pattern: classifiers

fitted at a given timepoint generalised approximately equally well to all prior timepoints

back to the first timepoint where decoding was reliable (about 100-200ms post stimulus

onset). That is, classifiers trained on gamma and high gamma showed excellent *retrograde*

generalisation. This pattern yields the vertical "edge" clearly evident in the high gamma

matrix, and blurrier but still present in the gamma matrix. The classifiers also generalised to

future timepoints, but with performance often tailing off for more remote future timepoints

— that is, they showed diminishing *anterograde* generalisation.

Together these observations suggest two interesting things about the semantic code

as expressed within and across different frequency ranges. First, whatever information a

classifier trained on gamma or high gamma power exploits at its own training timepoint

must also be present in the signal at all earlier time points, all the way back to the first

moment semantic information appears (producing good retrograde generalisation).

However, information exploited by a classifier at its training timepoint may *not* be present in

the signal at future timepoints, suggesting that these features "drop out" over the course of

stimulus processing, producing a graded drop-off in anterograde generalisation. Second, the

dynamically-changing pattern observed in the transfrequency code may be carried

predominantly by lower frequency information.

Figure 2: Temporal generalisation of classifiers. For each test time, the train time (vertical dimension) of the best classifier, plus the train times of other classifiers that perform statistically indistinguishably from the best (p > 0.05, paired t-test with probabilities adjusted to control the false-discovery rate at α = 0.05), are shown in the most saturated colour. Progressively desaturated colours show the train time of classifiers exhibiting a significant difference from the best classifier (p < 0.05, p < 0.01, p < 0.005). Timepoints where classifiers trained at that timepoint do not perform significantly better than chance even when tested at the training timepoint (0.5, one-sample t-test with probabilities adjusted to control the false-discovery rate at α = 0.05) are shown in black. Local temporal generalisation is indicated by significantly better performance on timepoints at or near the train time (the diagonal shown on each plot) than at more remote timepoints. The squares highlight cases where hold-out accuracies at two training timepoints (the two corners on the diagonal) are both significantly better than when the same classifiers are used to decode more remote timepoints (the two off-diagonal corners). (A) Results for classifiers trained on power frequency features for all frequencies between 4 and 200 Hz (blue) or on voltage features (brown). (B) Results for classifiers trained on power frequency features from a single range - theta (4 – 7 Hz, red), alpha (12 – 18 Hz, orange), beta (13 – 30 Hz, yellow), gamma (30 – 60 Hz, light green) and high gamma (42 – 200 Hz, dark green).

303
Figure 3: Width of generalisation window. Classifiers trained on power frequency features
for all frequencies between 4 and 200 Hz (shades of blue) or on voltage features (shades of
brown) were grouped into ten clusters via agglomerative hierarchical clustering (see
Methods). The "timecourses" show the mean hold-out accuracy for classifiers within each
cluster at each timepoint. Lines are solid where there was a significant difference between
classifier accuracy and chance (0.5, one-sample t-test with probabilities adjusted to control
the false-discovery rate at α = 0.05) and dashed where there is no significant difference.
Coloured bars show the grouped timepoints in each cluster. Statistics supporting this
pattern are reported in Supplementary Materials 1, Figure S4).

We decided to focus subsequent analyses on frequency ranges in which a dynamic

code was most clearly observed, namely voltage and whole-spectrum power. We next

assessed whether the window of above-chance temporal generalisation widened over time,

consistent with an overall slowing of representational change. To this end, we grouped the

classifiers into ten clusters based on similarity in their temporal decoding profiles (see

Methods). That is, classifiers that show similar patterns of prediction accuracy across all test

timepoints were clustered together, and we computed the mean accuracy profile over time

for each cluster. Figure 3 shows the result. Classifiers trained earlier showed a sharper rise

and fall in accuracy, whereas classifiers trained later exhibited a wider window of

generalisation (similar plots for classifiers trained on separate frequency ranges are shown

in Supplementary Materials 1, Figure S3; statistics supporting this claim are reported in

Supplementary Materials 1, Figure S4). Thus both voltage and trasnfrequency power show a

slowing of dynamic representational change over the course of stimulus processing.

Finally, we assessed whether the observed dynamic change was accompanied by
change in the apparent code direction—that is, whether an increase in voltage or in power
predicted a greater likelihood that the stimulus is an animal at some points in time, and a
greater likelihood that it is inanimate at others. Change in code direction is another hallmark
of nonlinear representational change (Rogers et al., 2021). To see this, we aggregated the
classifier coefficients across patients for each timepoint and plotted these on the cortical
surface. Specifically, at each cortical location, we first calculated the number of electrodes
across patients that had a non-zero coefficient, then computed the proportion of these
having a negative coefficient (since animals were coded as 0 and inanimate objects as 1, a
negative coefficient means that an increase in voltage or power is associated with increased
probability that the stimulus is an animal). Figure 4 shows these proportions at 4 different
timepoints post stimulus onset, for classifiers trained on whole-spectrum power (top) or
voltage (bottom). Warm colours indicate areas and timepoints where most selected
electrodes have negative coefficients, while cool colours indicate areas and timepoints
where most selected electrodes have positive coefficients. Green shades indicate areas and
timepoints where selected electrodes have a mixture of positive and negative coefficients.
We also animated the coefficient change over time, with videos for classifiers trained on all
frequencies, individual frequency ranges, and voltage available at
https://github.com/slfrisby/ECoG_LASSO/.
For both voltage and power, changes in code direction were observed. For voltage,
for instance, the anterior-most part of the ventral temporal lobe was uniformly positive at
200ms and uniformly negative at 600ms. By 1000ms, midway between the anterior and
posterior extent of coverage, coefficients showed a medial-to-lateral change in direction,
suggesting that voltage increases signify animals in the more medial portion and non-
animals in the more lateral portion. Whole-spectrum power also showed changes in code
direction over time; for instance, in Figure 4, the medial anterior portion of ventral temporal
cortex showed a negative relationship between power and animacy at 400ms, but a positive
relationship by 1000ms. At 1000ms, the transfrequency coefficients also showed a medial-
to-lateral change, with increased power signifying animals all along the medial extent of the
coverage area, but showing a more mixed pattern across the more lateral extent.

Figure 4: Change in code direction. Coefficients for classifiers trained on power frequency features for all frequencies between 4 and 200 Hz, or on voltage features, are projected onto the ventral surface of the left hemisphere. Time is shown relative to stimulus onset. Colours indicate the proportion of classifier coefficients at that location with the same sign (see Methods). Warm colours indicate that coefficients are mostly negative across patients (since animals were coded as 0 and inanimate objects as 1, a negative coefficient indicates that an increase in power is associated with increased probability that the stimulus is animate); cool colours indicate that coefficients are mostly positive across patients (an increase in power is associated with increased probability that the stimulus is inanimate); green shades indicate that the region was selected in multiple patients but that the sign of the coefficient is not consistent across patients.

2. Discussion

While it has long been clear that the vATLs play an important role in human semantic cognition (Lambon Ralph et al., 2017; Patterson et al., 2007; Rogers et al., 2004), precisely *how* neural populations encode such information remains uncertain. Recent

studies applying multivariate decoding to voltages recorded from the cortical surface

suggest that semantic information is expressed in a rapidly-changing code (Rogers et al.,

2021), but, with respect to uncovering local neural representations, such studies remain

limited, since voltages can be influenced by a variety of sources both local and remote. The

current work instead applied multivariate decoding to a time-frequency decomposition of

ECoG data, with two results that advance our understanding of the vATL semantic code in

important ways. First, information about animacy is expressed by power in all frequencies

simultaneously - it appears within each range considered independently, and jointly across

all ranges, for most of the duration of stimulus processing. Moreover, decoding accuracy

was reliably better when models were fitted to all frequencies simultaneously compared to

each individual range; and classifiers fitted to the whole spectrum always selected features

from all frequency ranges no matter which timepoint they were trained on. This result

strongly suggests conjoint encoding of semantic information across the power spectrum

(Frisby et al., 2023). Second, decoding from both power and voltage revealed characteristics

of dynamic representational change: constant decodability, local temporal generalisation, a

widening generalisation window, and changes in code direction. This is likely to be driven by

low frequencies – gamma and high gamma classifiers showed a contrasting pattern of

excellent retrograde generalisation back to the earliest successful decoding timepoint, but

anterograde generalisation that diminished for more remote timepoints.

394   Assuming that the frequency of activity is inversely related to the distance over

which information is being transmitted (Canolty & Knight, 2010; Lachaux et al., 2012), our

results are consistent with the claim that both local neuronal activity within the vATL

(reflected in gamma and/or high gamma power) and distal inputs to the region (reflected in

theta, alpha and beta) encode semantic information. These findings therefore agree with

multiple univariate studies that variously associate theta (Hermes et al., 2014), alpha (Clarke

et al., 2018), beta (Abel et al., 2015; Sato et al., 2021), gamma and high gamma (Arya, 2019;

Cervenka et al., 2013; Chan et al., 2011; Crone et al., 2001; Crone & Hao, 2002; Edwards et

al., 2010; Forseth et al., 2018; Kojima et al., 2013; Nakai et al., 2017, 2019; Snyder et al.,

2023; Tanji, 2005; Wang et al., 2011) with semantic tasks. One interpretation of our results

is that information is represented redundantly in multiple frequencies. A second possibility

is that, since the brain exhibits properties of a dynamical system (Jones et al., 2015; Yuste,

2015), rhythmic patterns may be an epiphenomenon of normal functioning or even of

epileptiform activity (Drane et al., 2008; Hamberger, 2007; Henry et al., 1998). Therefore,

some frequency ranges may represent information not in a "strong" sense (meaning that

the brain uses time-frequency power to represent information for downstream

computation) but in a "weak" sense (meaning that time-frequency power is decodable but

is not used as the principal means of representation; Watrous et al., 2015).

However, the finding that classifiers trained on whole-spectrum power outperform

those trained on a single frequency range and select features from across the frequency

spectrum (Figures 1C and 1D) supports a more nuanced conclusion. Classifiers trained with

LASSO regularisation prefer sparse solutions, in which only a small subset of features receive

nonzero coefficients. If the information in the different frequency ranges were redundant, a

classifier would not assign nonzero coefficients to many features that spanned the

frequency range. Instead, these results support the notion of *transfrequency* representation

– information is encoded *across* multiple frequency ranges (sometimes called frequency

"multiplexing", Watrous et al., 2015). Some previous univariate studies have proposed

specific roles that different frequency ranges may play - abstraction from multiple episodic

experiences (Sauseng & Klimesch, 2008), binding multiple features of an item (Merker,

2013; Sauseng & Klimesch, 2008; Stryker, 1989; Tallon-Baudry & Bertrand, 1999; von der

Malsburg, 1995), encoding semantic similarity (Solomon et al., 2019; Spiers, 2020), and

enabling retrieval independent of sensory modality (Sauseng & Klimesch, 2008) in a way

that is appropriate for the context (Halgren et al., 2015; Jackson, 2021; Klimesch, 2012;

Marko et al., 2019). However, on the simple assumption that the frequency of activity is

inversely related to transmission distance, the notion of transfrequency representation is

highly consistent with the hub-and-spoke model (Lambon Ralph et al., 2017; Patterson et

al., 2007; Rogers et al., 2004). According to this model, neither the vATL "hub" nor the

modality-specific "spokes" are individually sufficient for full semantic cognition – rather,

information is encoded conjointly in multiple regions and in the interactions between them

(Frisby et al., 2023).

This study was the first to investigate whether activity in different frequency

ranges exhibits the same pattern of dynamic representational change seen in voltage

(Rogers et al., 2021). Although dynamic change was clearly evident when decoding whole-

spectrum power, gamma and high gamma showed a different pattern – excellent retrograde

generalisation and diminishing anterograde generalisation. The good retrograde

generalisation indicates that features exploited by a classifier at its training timepoint must

also be present, and must signify the same information in the same way, for all preceding

timepoints (up to the earliest successful timepoint). That is, this part of the code must be

relatively *static* over processing from the earliest arrival of perceptual signals up to the time

where the classifier is fitted. Conversely, the diminishing anterograde generalisation

indicates that features exploited by a classifier at its training timepoint eventually fall away

at future timepoints.

Figure 5 illustrates in schematic form what such a decoding pattern might suggest

about how animacy is encoded in high-frequency activity (and thus, by inference, in local

neural activity). Each curve represents a hypothetical response to animate stimuli in the

gamma or high gamma range for one electrode over time. Every electrode shows increased

gamma power for animate stimuli from early in processing, but the timecourse of this

change differs between electrodes. Where gamma increases most strongly early in

processing, it also diminishes most rapidly; where gamma increases are smaller initially,

they persist longer. Since the LASSO penalty prefers to assign features the smallest

coefficients possible, models fitted with LASSO regularisation will select whichever

electrodes show the strongest response at the training tinepoint. Thus models fitted to the

earliest timepoints will select the red electrodes, those fitted slightly later will select the

orange ones, etc. Generalisation to future timepoints will diminish as the gamma power

decreases on the selected electrodes, producing diminishing anterograde generalisation.

Because all electrodes carry useful signal from the onset, however, each classifier

generalises successfully to all prior time points, producing good retrograde generalisation.

The generalisation pattern is thus consistent with the view that animacy is encoded in the

local activity of many neural populations, some responding strongly but then quickly

diminishing, and other initially responding less strongly but persisting for a longer duration.

Figure 5: Hypothesised semantic code in gamma and/or high gamma producing full
retrograde generalisation and limited anterograde generalisation. Each curve represents the
hypothesised gamma/high gamma response to animate stimuli by one electrode. Where
curves are above the grey horizontal line, they encode information about animacy. All
electrodes encode animacy from early in processing, but models regularised with the LASSO
penalty will place coefficients on whichever electrode has the strongest response at a given
timepoint. The saturated parts of the coloured horizontal bars thus indicate which electrode
is selected by a classifier at each timepoint. The desaturated parts indicate the
generalisation profile of the resulting classifier. Electrodes that show the strongest
responses early on diminish in power most rapidly, limiting anterograde generalisation.
Because all electrodes carry information about animacy from the onset of the signal,
however, all classifiers generalise well to the beginning of the processing window.
478
479

Finally, the current work carries important implications for interpreting other

sources of information about semantic representation. Noninvasive methods such as EEG

and MEG cannot discern activity within high gamma frequencies because it is blocked by the

skull and the scalp. The current work suggests that dynamic representational change is

mainly observed in lower frequency ranges that are more readily measurable via these

other techniques—thus the comparatively static code revealed in high frequency ranges

may be obscured in other imaging modalities. Additionally, the current work highlights

circumstances in which representations in neural activity differ in their nature from

representations observed in neuro-computational models (which exhibit the dynamic

properties observed in voltage and transfrequency power, not the comparatively static code

observed in high frequencies). Further work should explore the circumstances under which

representational properties in brains and machines converge and diverge (Cox et al., 2015).

2.1. Conclusion

To summarise, we have shown that it is possible to decode semantic information

from every frequency range between theta and high gamma. Although individual frequency

ranges contained enough information to drive decoding above chance, decoding from the

whole frequency spectrum at once produced the highest decoding accuracy, equivalent to

using voltage. Decoding from the whole frequency spectrum also revealed the same set of

dynamic properties observed in voltage; however decoding of high-frequency ranges alone

showed a qualitatively different pattern, suggesting that local firing activity expresses a

more static semantic code. Together these results provide an important step toward

understanding how neural systems encode semantic information.

504
505
506   3. Methods
507
508   3.1. Patients
509
19 patients participated in the study (labelled 01-22 to enable comparison with

previous work; Y. Chen et al., 2016; Cox et al., 2024; Rogers et al., 2021; Shimotake et al.,

2015). Of these 19 patients, one was later excluded because too many trials were

contaminated with artefacts (see Preprocessing – ECoG), leaving 18 patients for decoding.

For one further patient (Patient 20), no exact MNI coordinates were available for their

electrodes. This patient was included in the analyses, but excluded from visualisation (see

Experimental Questions). All patients were native speakers of Japanese. Information about

patients' age, sex, handedness, and clinical presentation is summarised in Table 1.

Each patient was implanted with subdural electrodes arranged in grids or strips for

presurgical monitoring (mean 91 electrodes, range 56 – 128 electrodes per patient). 16

patients had electrodes implanted in the left hemisphere, of which 10 – 52 electrodes

(mean 27 electrodes) were within grids or strips that covered the vATL (where grids or strips

included both electrodes that covered ventral anterior temporal cortex and electrodes that

covered lateral or posterior temporal cortex, the whole grid or strip was included in the

analysis). In the remaining 3 patients, with electrodes implanted in the right hemisphere, 6 –

28 electrodes (mean 20 electrodes) were within grids or strips that covered the vATL. Grids

in which no electrodes covered the vATL were excluded from analysis. Electrodes that were

included in the analysis are shown in Figure 6. The electrodes were platinum, with a

recording diameter of 2.3 mm and an inter-electrode distance of 1 cm (ADTECH, WI). Three

patients were also implanted with depth electrodes (sEEG), but these were not included in

the analysis.

All patients gave written informed consent and the study was approved by the ethics

committee of the Kyoto University Graduate School of Medicine (#C533).

	Patient 01	Patient 02	Patient 03	Patient 04
Age, sex, handedness	22, M, R	29, M, R&L	17, F, R	38, F, R
WAIS-R/WAIS-III* (VIQ, PIQ, TIQ)	70, 78, 69	72, 78, 72	67, 76, 69	84, 97, 89
WMS-R (verbal, visual, general, attention, delayed recall)	99, 64, 87, 91, 82	99, 92, 97, 87, 83	51, <50, <50, 81, 56	75, 111, 83, 62, 53
WAB	95.6	96	97.2	98.5
WADA	Left	Bilateral	Left	Left
Age of seizure onset	16	10	12	29
Seizure type	FAS→FIAS, FBTCS	FAS→FIAS	FAS→FIAS	FAS→FIAS
Ictal ECoG onset	aMTG	PHG	PHG	PHG
MRI	L basal frontal cortical dysplasia, L anterior temporal arachnoid cyst	L posterior temporal cortical atrophy	L temporal tip arachnoid cyst	L HS/HA
Pathology	FCD type I	FCD type IIIa	Palmini FCD type IB	FCD type IIa
	Patient 05	Patient 06	Patient 07	Patient 08
Age, sex, handedness	55, M, R	34, M, L	41, F, R	27, F, R
WAIS-R/WAIS-III* (VIQ, PIQ, TIQ)	105, 99, 103	55, **, 44	72, 83, 75	106, **, 105
WMS-R (verbal, visual, general, attention, delayed recall)	71, 117, 84, 109, 72	52, <50, <50, 55, <50	83, 111, 89, 94, 82	112, 114, 114, 81, 100
WAB	98	88	97.3	99.6
WADA	Left	Left	Right	Left
Age of seizure onset	55	12	19	16
Seizure type	FIAS (once)	FAS→FIAS	FAS→FIAS	FAS→FIAS
Ictal ECoG onset	None	R parietal lobe/pMTG	PHG	ventral anterior temporal
MRI	L medial temporal lobe low-grade glioma	R parietal cerebral atrophy & contusion, R hippocampal sclerosis/atrophy	L HS/HA, L parieto-occipital perinatal infarction	R medial temporal cyst
Pathology	Diffuse astrocytoma	Post-traumatic change(parietal)/ scar(temporal)/ HS	FCD type I	FCD type I
	Patient 09	Patient 10	Patient 11	Patient 12
Age, sex, handedness	51, M, R	38, F, R	29, F, R	40, M, L

WAIS-R/WAIS-III* (VIQ, PIQ, TIQ)	73, 97, 83	109, 115, 112	62, 80, 67	93, 105, 98
WMS-R (verbal, visual, general, attention, delayed recall)	80, 101, 85, 91, 91	71, 79, 70, 90, 58	64, 94, 68, 79, 79	74, 94, 77, 110, 96
WAB	89.6	96.9	95.8	99
WADA	Left	Left	Left	Right
Age of seizure onset	43	28	12	6
Seizure type	FIAS	FAS→FIAS	FAS→FIAS	FAS→FIAS
Ictal ECoG onset	mITG	SMG	PHG	PHG
MRI	L temporal cavernoma	L parietal operculum tumour	L HS	R HS/HA
Pathology	Arteriovenous malformation	Oligoastrocytoma	non-neoplastic brain tissue	FCD type IIIa

	Patient 13	Patient 14	Patient 15	Patient 20
Age, sex, handedness	22, M, R	42, M, R	35, M, R	23, F, R
WAIS-R/WAIS-III* (VIQ, PIQ, TIQ)	86, 79, 81	96, 84, 90	82, 86, 82	67, 82, 71
WMS-R (verbal, visual, general, attention, delayed recall)	55, 79, 53, 90, 54	73, 85, 73, 103, 76	75, 89, 75, 92, 81	78, 119, 86, 82, 64
WAB	97.4	99.9	99.2	94.2
WADA	Left	Left	Left	Bilateral
Age of seizure onset	14	27	20	15
Seizure type	FAS→FIAS	FAS→FIAS	FIAS	FIAS
Ictal ECoG onset	PHG	PHG	PHG	IPL/SMG
MRI	L HS/HA	L HS	L HS/HA	No apparent lesion
Pathology	FCD type IIIa	FCD type IIIa	FCD type IIIa	FCD type I

	Patient 21	Patient 22
Age, sex, handedness	40, M, R	28, F, R
WAIS-R/WAIS-III* (VIQ, PIQ, TIQ)	86, 97, 90	80, 69, 72
WMS-R (verbal, visual, general, attention, delayed recall)	111, 113, 113, 87, 109	77, 89, 77, 121, 73
WAB	92.2	100
WADA	Left	Left
Age of seizure onset	30	12
Seizure type	FIAS	FIAS
Ictal ECoG onset	aMTG	PHG
MRI	No apparent lesion	L HS/HA
Pathology	FCD type I	FCD type IIIa

Table 1: Patient characteristics. Abbreviations: WAIS-R – Wechsler Adult Intelligence Scale (1991), WAIS-III - Wechsler Adult Intelligence Scale (1997), VIQ – Verbal IQ, PIQ – Performance IQ, TIQ – full-scale IQ, WMS-R – Wechsler Memory Scale (1987), WAB – Western Aphasia Battery, FAS – focal aware seizure, FIAS – focal impaired awareness seizure, FBTCS – focal to bilateral tonic-clonic seizure, aMTG – anterior middle temporal gyrus, PHG – parahippocampal gyrus, pMTG – posterior middle temporal gyrus, mITG – medial inferior temporal gyrus, SMG - supramarginal gyrus, ITG – inferior temporal gyrus, IPL – intraparietal lobule, HS – hippocampal sclerosis, HA – hippocampal atrophy, FCD – focal cortical dysplasia. * - The WAIS-R was used to test patients 01-06 and the WAIS-III was used to test other patients. ** - missing score.

Figure 6: Electrode locations for all patients. Electrodes are overlaid on an MNI template (MNI152NLin2009cAsym).

3.2. Stimuli, task, and acquisition

Stimuli were the same 100 line drawings used previously (Y. Chen et al., 2016; Rogers et al., 2021; Shimotake et al., 2015) – 50 animals and 50 nonliving items including buildings, tools, musical instruments and other household objects (Morrison et al., 1997; https://github.com/slfrisby/ECoG_LASSO/tree/main/data_info/stimuli/). There were no significant differences between the categories with respect to age of acquisition, visual complexity, concreteness, familiarity, word frequency, name agreement and non-semantic visual structure (Barry et al., 1997; Rogers et al., 2021). MATLAB r2010a was used to display stimuli on a PC screen.

There were four runs per patient, collected in a single session. Within each run, each stimulus was presented once in a random order. Stimuli were presented for 5 seconds each, with no break between stimuli.

Patients were instructed to name each picture as quickly and accurately as possible. Data for nine patients were recorded at 2000 Hz (with a low-pass filter of 600 Hz) and data for ten patients were recorded at 1000 Hz (with a low-pass filter of 300 Hz). Time of naming onset was measured. Responses and eye fixation were monitored via video.

3.3. Data analysis

3.3.1. Preprocessing – structural MRI

A clinical MPRAGE T$_1$-weighted anatomical scan was acquired before and after electrode

implantation. The location of each electrode was identified on each 2D slice of the post-

surgical scan. *fnirt* in FSL (https://fsl.fmrib.ox.ac.uk/fsl/fslwiki/; Jenkinson et al., 2012; Smith

et al., 2004) was used to coregister the electrode positions to the pre-surgical scan and then

to MNI space (MNI152NLin2009cAsym). The position of each electrode was then manually

adjusted to the surface.

3.3.2.   Preprocessing – ECoG

Preprocessing was performed using in-house MATLAB (r2023b) code, composed of

functions from EEGLAB (2023.1; https://eeglab.org/; Delorme & Makeig, 2004) and available

at https://github.com/slfrisby/ECoG_LASSO/ . First, the CleanLine EEGlab plugin (v2.0;

https://github.com/sccn/cleanline; Delorme, 2023; Mitra & Bokil, 2007) was used to

remove line noise at 60 Hz and the harmonics 120 and 180 Hz, without scanning for exact

line noise frequencies and with a sliding window step size of 2 (all other parameters were

set as defaults). CleanLine uses a multitaper fast Fourier transform to identify and remove

sinusoidal noise and, though it removes noise less completely than traditional notch-

filtering, is less disruptive to the overall frequency structure of the data. Data were then

filtered using *eegfilt* (EEGLAB). The low cutoff was set to 0.5 Hz (to remove slow drifts;

Delorme, 2023) and the high cutoff set to 300 Hz (for consistency across patients - some

data were recorded at 1000 Hz using equipment that imposed a low-pass filter at 300 Hz).

Channels that lay below the seizure onset zone (identified in the clinical examinations) or

with poor contact (identified by visual inspection) were removed. Data were epoched

between -1000 and 3000 ms relative to stimulus onset and baseline-corrected using the

mean response across trials between -200 and -1 ms. Data from the nine patients recorded

at 2000 Hz was then down-sampled to match the ten patients recorded at 1000 Hz by

boxcar averaging pairs of neighbouring timepoints. A common average reference was

applied using *reref* (EEGLAB).

Addressing artefacts in the data was a five-step process. First, the mean voltage for

each channel was calculated over timepoints and trials. Any trial that contained a value

more extreme than 10 standard deviations from the mean was rejected. Second, all trials

were inspected individually and any that appeared to contain obvious interictal epileptiform

activity, muscle activity, "electrode pop" or other artefacts were rejected. Since repeated

presentations of the same stimulus were to be averaged it was important to check whether

there was at least one good trial for each stimulus. One patient lacked any good trials for 18

stimuli (7 animate, 11 inanimate) and so was excluded from further analysis (and does not

appear in Table 1). Another lacked any good trials for 3 stimuli (1 animate, 2 inanimate) –

because of the small and relatively balanced number of missing stimuli, we included this

patient. For the next steps an independent component analysis (ICA) was conducted using

runica (EEGLAB) extracting *n* components, where *n* was 75% of the total number of good

electrodes (Clarke, 2020). For the third artefact rejection step, the SASICA EEGLAB plugin

(https://github.com/dnacombo/SASICA/; Chaumon et al., 2015) was used to identify ICA

components with weak autocorrelation, which is characteristic of muscle activity.

Components identified by SASICA were inspected and, in order to minimise rejection of

signal-carrying data, rejected if the channel appeared to contain only autocorrelated noise

and no neural activity. Fourth, SASICA was used to highlight components with focal trial

activity (i.e., activity in only a few trials, characteristic of muscle activity), "electrode pop" or

other artefacts. Rather than rejecting the component across all trials, the atypical trials were

identified via visual inspection and only those trials were removed. The ICA was then re-run

and the process repeated until no components contained significant focal trial activity. Fifth,

the possibility of microsaccade artefacts in the data was assessed (Clarke, 2020; Jerbi et al.,

2009; Kovach et al., 2011; Yuval-Greenberg et al., 2008). The independent component

activations were filtered for activity in the frequency range associated with microsaccades

(20 – 190 Hz). The activations were then convolved with a saccade-related potential

template and the number of microsaccades per second was calculated (Craddock et al.,

2016). Since every component contained very few microsaccades (< 0.000012

microsaccades per second) and no component obviously contained more microsaccades

than any other, no components were rejected based on this assessment.

630   Time-frequency power and phase were extracted using complex Morlet wavelet

convolution (Bertrand et al., 1994), implemented with *timefreq* (EEGLAB). Power values

were extracted from every trial between 0 and 1650 ms in 10 ms time steps and between 4

and 200 Hz in 60 logarithmically-spaced frequency steps. A 5-cycle wavelet was used at 4 Hz,

increasing to a 15-cycle wavelet at 200 Hz (Clarke, 2020). Power values were then averaged

across repeated presentations of the same stimulus and any missing trials were interpolated

with the median power value across all trials. Decibel normalisation was performed using

the mean power across trials between -300 and -100 ms (calculated separately for each

electrode and frequency) – a gap before stimulus onset was used to mitigate the effect of

temporal leakage of trial activity into the baseline during wavelet convolution. Since phase

values cannot be averaged (Cohen, 2014), preprocessed trials were averaged across

repeated presentations of the same stimulus before phase values were extracted using the

same time and frequency steps used for the extraction of power. As a comparison,

preprocessed voltage was averaged over repeated presentations of the same stimulus.

The impact of preprocessing decisions on decoding results is explored in

Supplementary Materials 2. In summary, decoding of semantic structure (animacy) with

spectral frequency features remains unchanged after each step in this extensive and careful

cleaning.

3.3.3.   Multivariate classification

650   3.3.3.1.   Decoding approach

Logistic regression classifiers were trained to discriminate animate from inanimate

stimuli using *glmnet* in R (Friedman et al., 2010). For power and phase, frequency feature

vectors were created for each stimulus at each timepoint (0 ms, 10 ms, 20 ms, …) by

concatenating power or phase values for all electrodes for all frequencies in a range of

interest. Voltage feature vectors were created for each stimulus at each timepoint by

concatenating voltage values for all electrodes in a 50 ms window centred on the timepoint

of interest. The voltage feature vectors therefore reflected activity around the timepoint of

interest – but note that so did frequency feature vectors, since Morlet wavelet convolution

takes activity at neighbouring timepoints into account. These vectors were provided as input

to the classifiers. Each classifier was trained on vectors generated at a single timepoint for a

single patient.

The classifiers used LASSO (L1) regularisation (Tibshirani, 1996), which applies a

penalty that scales with the sum of the absolute values of the coefficients and thus

produces solutions in which many features receive coefficients of zero. This approach was

selected because it can be used to assess whether the same electrodes or frequencies are

used to represent information at different timepoints. If the information used by a classifier

trained at timepoint A is present at timepoint B, the classifier will perform well at timepoint

B; other units, that may be in different states at the two timepoints, will receive coefficients

of zero and therefore will not affect classifier performance (Rogers et al., 2021).

Classifier accuracy was assessed using 10-fold cross-validation. In each outer loop, 10

out of 100 stimuli (5 animate, 5 inanimate) were held out. The remaining 90 stimuli were

used to search a range of 100 values (0.2 – 0.002, logarithmically spaced) for the

regularisation parameter that resulted in the smallest mean squared error. This process was

implemented using *cv.glmnet* (glmnet) with parallel model fitting implemented with foreach

(https://cran.r-project.org/web/packages/foreach/index.html; all other parameters were

set as defaults). A model with the best regularisation parameters was tested on the 10

stimuli in the outer loop hold-out set. The same model was tested on the same 10 stimuli at

all other timepoints. The process was then repeated 10 times with different final hold-out

sets. This process yielded both a main timecourse of decoding accuracy (i.e., mean accuracy,

over folds, of classifiers tested on the timepoint at which they were trained) and a

generalisation matrix in which the y-coordinate of a cell is the time at which the classifier

was trained and the x-coordinate is the time at which the classifier was tested. Finally, a

single classifier was trained at every timepoint using all 100 stimuli for training. The accuracy

of these classifiers was not evaluated – they were used only for inspection of coefficients.

To assess group-level performance, the timecourses of decoding accuracy and the

generalisation matrices were averaged across patients.

3.3.3.2.   Experimental questions

We first assessed whether power, phase and voltage each contained sufficient

information to enable decoding. We therefore created both voltage feature vectors and

frequency feature vectors of power and phase data (separately) using all 60 frequencies

between 4 and 200 Hz and used these as input to classifiers. We compared each group-

average timecourse to chance (0.5) using one-tailed, one-sample t-tests. We compared

power and voltage, and phase and voltage, using paired t-tests. Probabilities were adjusted

to control the false-discovery rate at α = 0.05 (Benjamini & Hochberg, 1995). We confirmed

that near-identical patterns of results were obtained in the 8 patients with left-hemisphere

electrodes previously analysed by (Rogers et al., 2021), the 7 patients with left-hemisphere

electrodes analysed for the first time in this work, and the 3 patients with right-hemisphere

electrodes (Supplementary Materials 1, Figure S5). Having done so, we combined all

patients into a single group for all subsequent analyses.

We next investigated whether there were differences in decoding performance

between power and phase within different frequency ranges. We therefore divided the 60

frequencies into theta (4 – 7 Hz, 11 frequencies), alpha (12 – 18 Hz, 7 frequencies), beta (13

– 30 Hz, 13 frequencies), gamma (30 – 60 Hz, 10 frequencies) and high gamma (42 – 200 Hz,

19 frequencies) ranges. We constructed frequency vectors of power and phase data using

only power or phase at frequencies within each range and used these as input to separate

classifiers. We compared each group-average timecourse to chance and then compared

each range to the timecourse of decoding using all 60 frequencies.

We then tested whether, if either power or phase data contained sufficient

information to enable decoding, the power or phase code exhibited the same distributed,

dynamic properties identified by Rogers et al., 2021 in both the voltage data (for the first

subset of patients) and the computational hub-and-spoke model. We tested for these

properties using both frequency vectors constructed using all 60 frequencies and vectors

constructed using only frequencies within each range. Constant decodability had already

been assessed by one-sample t-tests of each group-average timecourse against chance.

To assess local temporal generalisation we inspected the group-average

generalisation matrices generated by testing each classifier at every possible timepoint. To

test whether the patterns observed were statistically significant, we identified the best-

performing classifier at each timepoint and then conducted paired t-tests to assess whether

classifiers trained at every other possible timepoint performed equally well. Probabilities

were adjusted to control the false-discovery rate at $\alpha = 0.05$ (Benjamini & Hochberg, 1995).

To assess the shape of the generalisation window over time we computed the

pairwise cosine distance between each row of the generalisation matrix, then applied

agglomerative hierarchical clustering using *hclust* (native R) and cut the tree to create 10

clusters. We selected this cluster number to make these results comparable to those of

Rogers et al. (2021). We averaged the timecourses of classifiers within each cluster and

inspected performance over time (again, probabilities were adjusted to control the false-

discovery rate). To quantify the patterns observed we took classifiers trained every 50 ms

(i.e., 0 ms, 50 ms, 100 ms …; this ensured that, for classifiers trained on voltage, consecutive

50 ms windows did not overlap and were therefore independent). We calculated the area

under the curve between each timecourse and a horizontal line at chance (0.5) and fitted a piecewise linear regression to the area values using the *segmented* library in R, using *selgmented* with the Bayesian Information Criterion to determine the number and location of breakpoints to produce the best model given the number of free parameters.

To assess and visualise changes in code direction we first took the classifiers trained on all data at each timepoint and then (separately for every electrode, every patient and every timepoint) calculated the mean classifier coefficient within each frequency range (or over all 60 frequencies, or over the 50 ms within each window in the case of voltage). These mean classifier coefficients were converted to one NIFTI volume per patient and per timepoint, at 2.5 mm isotropic resolution in MNI space (MNI152NLin2009cAsym), using SPM12 (https://www.fil.ion.ucl.ac.uk/spm/) implemented in MATLAB r2023b. One patient (Patient 20) was excluded from this analysis because no MNI coordinates were available for their electrodes. Other patients were missing MNI coordinates from only a subset of electrodes; we included those patients in the analysis but ignored coefficients on the electrodes with missing coordinates. We projected coefficients in each volume to the pial surface (fsaverage template; Dale et al., 1999; Fischl et al., 1999) using *-volume-to-surface-mapping* with trilinear interpolation and smoothed them on the surface at 6 mm FWHM using *–metric-smoothing* in Connectome Workbench 1.5.0. We calculated the proportion of negative coefficients that each vertex received (since animals were coded as 0 and inanimate objects as 1, a negative coefficient indicates that an increase in power is associated with increased probability that the stimulus is animate). We plotted these proportions on the pial surface using *plot_surf_stat_map* in *nilearn* 0.10.3 implemented in Python 3.9. Finally, we animated the results – ffmpeg 5.1.6 (https://ffmpeg.org/) was used to concatenate plots of coefficients at successive timepoints with a frame rate of 10 (10 times slower than real time) and motion interpolation.

Data and code availability: We are unable to share raw data for this study because the patients did not provide informed consent to do so. However, matrices containing power, phase and voltage features (columns) for each stimulus (rows) will be made available upon peer review and acceptance. Code is available at https://github.com/slfrisby/ECoG_LASSO/ .

CRediT statement: Saskia L. Frisby – Conceptualisation, Methodology, Formal Analysis, Data

Curation, Writing – Original Draft, Writing – Review & Editing, Visualisation; Ajay D. Halai –

Conceptualisation, Methodology, Formal Analysis, Writing – Review & Editing, Supervision;

Christopher R. Cox – Conceptualisation, Writing – Review & Editing; Alex Clarke – Formal

Analysis, Writing – Review & Editing; Akihiro Shimotake – Investigation, Data Curation,

Writing – Review & Editing, Supervision; Takayuki Kikuchi – Investigation, Data Curation,

Methodology; Takeharu Kuneida – Investigation, Data Curation, Methodology; Yoshiki

Arakawa – Investigation, Data Curation, Methodology; Ryosuke Takahashi – Investigation;

Akio Ikeda – Investigation, Data Curation, Methodology; Riki Matsumoto – Investigation,

Methoology, Writing – Review & Editing; Timothy T. Rogers – Conceptualisation,

Methodology, Writing – Review & Editing; Supervision; Funding Acquisition; Matthew A.

Lambon Ralph - Conceptualisation, Methodology, Writing – Review & Editing; Supervision;

Funding Acquisition.

Acknowledgements: This work was supported by an MRC Career Development Award

(MR/V031481/1) to A.D.H., by Grants-in-Aid for Scientific Research (KAKENHI 23KK0146,

22H02945) to R.M., and by an Advanced European Research Council (ERC) award (GAP

670428-30 BRAIN2MIND_NEUROCOMP), MRC programme grant (MR/R023883/1), and

intramural funding (MC_UU_00005/18) to M.A.L.R. We would like to thank the patients who

so selflessly participated in this study.

Competing interests: A. I. belongs to the Department of Epilepsy, Movement Disorders and

Physiology, an Industry-Academia Collaboration Course, supported by a grant from Eisai

Corporation, Nihon Kohden Corporation, Otsuka Pharmaceutical Co., and UCB Japan Co.

References

Abel, T. J., Rhone, A. E., Nourski, K. V., Kawasaki, H., Oya, H., Griffiths, T. D., Howard, M. A.,
& Tranel, D. (2015). Direct physiologic evidence of a heteromodal convergence
region for proper naming in human left anterior temporal lobe. *Journal of
Neuroscience, 35*(4), 1513–1520. https://doi.org/10.1523/JNEUROSCI.3387-14.2015
Arya, R. (2019). Similarity of spatiotemporal dynamics of language-related ECoG high-
gamma modulation in Japanese and English speakers. *Clinical Neurophysiology:*

Official Journal of the International Federation of Clinical Neurophysiology, *130*(8),

1403–1404. https://doi.org/10.1016/j.clinph.2019.05.006

Barry, C., Morrison, C. M., & Ellis, A. W. (1997). Naming the Snodgrass and Vanderwart

pictures: Effects of age of acquisition, frequency, and name agreement. *The*

Quarterly Journal of Experimental Psychology Section A, *50*(3), 560–585.

https://doi.org/10.1080/783663595

Başar-Eroglu, C., Strüber, D., Schürmann, M., Stadler, M., & Başar, E. (1996). Gamma-band

responses in the brain: A short review of psychophysiological correlates and

functional significance. *International Journal of Psychophysiology*, *24*(1–2), 101–112.

https://doi.org/10.1016/S0167-8760(96)00051-7

Benjamini, Y., & Hochberg, Y. (1995). Controlling the false discovery rate: A practical and

powerful approach to multiple testing. *Journal of the Royal Statistical Society, Series*

B (Statistical Methodology), *57*(1), 289–300.

Bertrand, O., Bohorquez, J., & Pernier, J. (1994). Time-frequency digital filtering based on an

invertible wavelet transform: An application to evoked potentials. *IEEE Transactions*

on Biomedical Engineering, *41*(1), 77–88. IEEE Transactions on Biomedical

Engineering. https://doi.org/10.1109/10.277274

Binney, R. J., Embleton, K. V., Jefferies, E., Parker, G. J. M., & Lambon Ralph, M. A. (2010).

The ventral and inferolateral aspects of the anterior temporal lobe are crucial in

semantic memory: Evidence from a novel direct comparison of distortion-corrected

fMRI, rTMS, and semantic dementia. *Cerebral Cortex*, *20*(11), 2728–2738.

https://doi.org/10.1093/cercor/bhq019

Bressler, S. L. (1990). The gamma wave: A cortical information carrier? *Trends in*

Neurosciences, *13*(5), 161–162. https://doi.org/10.1016/0166-2236(90)90039-D

Canolty, R. T., & Knight, R. T. (2010). The functional role of cross-frequency coupling. *Trends*

in Cognitive Sciences, *14*(11), 506–515. https://doi.org/10.1016/j.tics.2010.09.001

Carlson, T., Tovar, D. A., Alink, A., & Kriegeskorte, N. (2013). Representational dynamics of

object vision: The first 1000 ms. *Journal of Vision*, *13*(10), 1–1.

https://doi.org/10.1167/13.10.1

Cervenka, M. C., Corines, J., Boatman-Reich, D. F., Eloyan, A., Sheng, X., Franaszczuk, P. J., &

Crone, N. E. (2013). Electrocorticographic functional mapping identifies human

cortex critical for auditory and visual naming. *NeuroImage*, *69*, 267–276.

https://doi.org/10.1016/j.neuroimage.2012.12.037

Chan, A. M., Baker, J. M., Eskandar, E., Schomer, D., Ulbert, I., Marinkovic, K., Cash, S. S., &

Halgren, E. (2011). First-pass selectivity for semantic categories in human

anteroventral temporal lobe. *Journal of Neuroscience*, *31*(49), 18119–18129.

https://doi.org/10.1523/JNEUROSCI.3122-11.2011

Chaumon, M., Bishop, D. V. M., & Busch, N. A. (2015). A practical guide to the selection of

independent components of the electroencephalogram for artifact correction.

Journal of Neuroscience Methods, *250*, 47–63.

https://doi.org/10.1016/j.jneumeth.2015.02.025

Chen, L., Lambon Ralph, M. A., & Rogers, T. T. (2017). A unified model of human semantic

knowledge and its disorders. *Nature Human Behaviour*, *1*(3), 0039.

https://doi.org/10.1038/s41562-016-0039

Chen, Y., Shimotake, A., Matsumoto, R., Kunieda, T., Kikuchi, T., Miyamoto, S., Fukuyama,
H., Takahashi, R., Ikeda, A., & Lambon Ralph, M. A. (2016). The 'when' and 'where' of
semantic coding in the anterior temporal lobe: Temporal representational similarity
analysis of electrocorticogram data. *Cortex*, *79*, 1–13.
https://doi.org/10.1016/j.cortex.2016.02.015

Cichy, R. M., Pantazis, D., & Oliva, A. (2014). Resolving human object recognition in space
and time. *Nature Neuroscience*, *17*(3), 455–462. https://doi.org/10.1038/nn.3635

Clarke, A. (2020). Dynamic activity patterns in the anterior temporal lobe represents object
semantics. *Cognitive Neuroscience*, *11*(3), 111–121.
https://doi.org/10.1080/17588928.2020.1742678

Clarke, A., Devereux, B. J., & Tyler, L. K. (2018). Oscillatory dynamics of perceptual to
conceptual transformations in the ventral visual pathway. *Journal of Cognitive
Neuroscience*, *30*(11), 1590–1605. https://doi.org/10.1162/jocn_a_01325

Cohen, M. X. (2014). *Analyzing Neural Time Series Data: Theory and Practice*. MIT Press.

Contini, E. W., Wardle, S. G., & Carlson, T. A. (2017). Decoding the time-course of object
recognition in the human brain: From visual features to categorical decisions.
Neuropsychologia, *105*, 165–176.
https://doi.org/10.1016/j.neuropsychologia.2017.02.013

Cox, C. R., & Rogers, T. T. (2021). Finding distributed needles in neural haystacks. *Journal of
Neuroscience*, *41*(5), 1019–1032. https://doi.org/10.1523/JNEUROSCI.0904-20.2020

Cox, C. R., Rogers, T. T., Shimotake, A., Kikuchi, T., Kunieda, T., Miyamoto, S., Takahashi, R.,
Matsumoto, R., Ikeda, A., & Lambon Ralph, M. A. (2024). Representational similarity
learning reveals a graded multidimensional semantic space in the human anterior
temporal cortex. *Imaging Neuroscience*, *2*, 1–22.
https://doi.org/10.1162/imag_a_00093

Cox, C. R., Seidenberg, M. S., & Rogers, T. T. (2015). Connecting functional brain imaging and
Parallel Distributed Processing. *Language, Cognition and Neuroscience*, *30*(4), 380–
394. https://doi.org/10.1080/23273798.2014.994010

Craddock, M., Martinovic, J., & Müller, M. M. (2016). Accounting for microsaccadic artifacts
in the EEG using independent component analysis and beamforming.
Psychophysiology, *53*(4), 553–565. https://doi.org/10.1111/psyp.12593

Crone, N. E., Boatman, D., Gordon, B., & Hao, L. (2001). Induced electrocorticographic
gamma activity during auditory perception. *Clinical Neurophysiology*, *112*(4), 565–
582. https://doi.org/10.1016/S1388-2457(00)00545-9

Crone, N. E., & Hao, L. (2002). Functional dynamics of spoken and signed word production: A
case study using electrocorticographic spectral analysis. *Aphasiology*, *16*(9), 903–
927. https://doi.org/10.1080/02687030244000383

Dale, A. M., Fischl, B., & Sereno, M. I. (1999). Cortical surface-based analysis: I.
Segmentation and surface reconstruction. *NeuroImage*, *9*(2), 179–194.
https://doi.org/10.1006/nimg.1998.0395

Delorme, A. (2023). EEG is better left alone. *Scientific Reports*, *13*(1), 2372.
https://doi.org/10.1038/s41598-023-27528-0

880 Delorme, A., & Makeig, S. (2004). EEGLAB: An open source toolbox for analysis of single-trial
881   EEG dynamics including independent component analysis. *Journal of Neuroscience*
882   *Methods*, *134*(1), 9–21. https://doi.org/10.1016/j.jneumeth.2003.10.009

883 Devlin, J. T., Russell, R. P., Davis, M. H., Price, C. J., Wilson, J., Moss, H. E., Matthews, P. M., &
884   Tyler, L. K. (2000). Susceptibility-induced loss of signal: Comparing PET and fMRI on a
885   semantic task. *NeuroImage*, *11*(6), 589–600.
886   https://doi.org/10.1006/nimg.2000.0595

887 Dilkina, K., & Lambon Ralph, M. A. (2012). Conceptual structure within and between
888   modalities. *Frontiers in Human Neuroscience*, *6*.
889   https://doi.org/10.3389/fnhum.2012.00333

890 Drane, D. L., Ojemann, G. A., Aylward, E., Ojemann, J. G., Johnson, L. C., Silbergeld, D. L.,
891   Miller, J. W., & Tranel, D. (2008). Category-specific naming and recognition deficits in
892   temporal lobe epilepsy surgical patients. *Neuropsychologia*, *46*(5), 1242–1255.
893   https://doi.org/10.1016/j.neuropsychologia.2007.11.034

894 Edwards, E., Nagarajan, S. S., Dalal, S. S., Canolty, R. T., Kirsch, H. E., Barbaro, N. M., &
895   Knight, R. T. (2010). Spatiotemporal imaging of cortical activation during verb
896   generation and picture naming. *NeuroImage*, *50*(1), 291–301.
897   https://doi.org/10.1016/j.neuroimage.2009.12.035

898 Fischl, B., Sereno, M. I., & Dale, A. M. (1999). Cortical surface-based analysis: II. Inflation,
899   flattening, and a surface-based coordinate system. *NeuroImage*, *9*(2), 195–207.
900   https://doi.org/10.1006/nimg.1998.0396

901 Forseth, K. J., Kadipasaoglu, C. M., Conner, C. R., Hickok, G., Knight, R. T., & Tandon, N.
902   (2018). A lexical semantic hub for heteromodal naming in middle fusiform gyrus.
903   *Brain*, *141*(7), 2112–2126. https://doi.org/10.1093/brain/awy120

904 Friedman, J., Hastie, T., & Tibshirani, R. (2010). Regularization paths for generalized linear
905   models via coordinate descent. *Journal of Statistical Software*, *33*(1).
906   https://doi.org/10.18637/jss.v033.i01

907 Frisby, S. L., Halai, A. D., Cox, C. R., Lambon Ralph, M. A., & Rogers, T. T. (2023). Decoding
908   semantic representations in mind and brain. *Trends in Cognitive Sciences*, *27*(3),
909   258–281. https://doi.org/10.1016/j.tics.2022.12.006

910 Halai, A. D., Welbourne, S. R., Embleton, K., & Parkes, L. M. (2014). A comparison of dual
911   gradient-echo and spin-echo fMRI of the inferior temporal lobe. *Human Brain*
912   *Mapping*, *35*(8), 4118–4128. https://doi.org/10.1002/hbm.22463

913 Halgren, E., Kaestner, E., Marinkovic, K., Cash, S. S., Wang, C., Schomer, D. L., Madsen, J. R.,
914   & Ulbert, I. (2015). Laminar profile of spontaneous and evoked theta: Rhythmic
915   modulation of cortical processing during word integration. *Neuropsychologia*, *76*,
916   108–124. https://doi.org/10.1016/j.neuropsychologia.2015.03.021

917 Halgren, E., Wang, C., Schomer, D. L., Knake, S., Marinkovic, K., Wu, J., & Ulbert, I. (2006).
918   Processing stages underlying word recognition in the anteroventral temporal lobe.
919   *NeuroImage*, *30*(4), 1401–1413. https://doi.org/10.1016/j.neuroimage.2005.10.053

920 Hamberger, M. J. (2007). Cortical language mapping in epilepsy: A critical review.
921   *Neuropsychology Review*, *17*(4), 477–489. https://doi.org/10.1007/s11065-007-
922   9046-6

Henry, T. R., Buchtel, H. A., Koeppe, R. A., Pennell, P. B., Kluin, K. J., & Minoshima, S. (1998).
Absence of normal activation of the left anterior fusiform gyrus during naming in left
temporal lobe epilepsy. *Neurology*, *50*(3), 787–790.
https://doi.org/10.1212/WNL.50.3.787
Hermes, D., Miller, K. J., Vansteensel, M. J., Edwards, E., Ferrier, C. H., Bleichner, M. G., van
Rijen, P. C., Aarnoutse, E. J., & Ramsey, N. F. (2014). Cortical theta wanes for
language. *NeuroImage*, *85*, 738–748.
https://doi.org/10.1016/j.neuroimage.2013.07.029
Hodges, J. R., & Patterson, K. (2007). Semantic dementia: A unique clinicopathological
syndrome. *The Lancet Neurology*, *6*(11), 1004–1014. https://doi.org/10.1016/S1474-
4422(07)70266-1
Jackson, R. L. (2021). The neural correlates of semantic control revisited. *NeuroImage*, *224*,
117444. https://doi.org/10.1016/j.neuroimage.2020.117444
Jenkinson, M., Beckmann, C. F., Behrens, T. E. J., Woolrich, M. W., & Smith, S. M. (2012). FSL.
NeuroImage, *62*(2), 782–790. https://doi.org/10.1016/j.neuroimage.2011.09.015
Jerbi, K., Freyermuth, S., Dalal, S., Kahane, P., Bertrand, O., Berthoz, A., & Lachaux, J.-P.
(2009). Saccade related gamma-band activity in intracerebral EEG: Dissociating
neural from ocular muscle activity. *Brain Topography*, *22*(1), 18–23.
https://doi.org/10.1007/s10548-009-0078-5
Jones, M. N., Willits, J., & Dennis, S. (2015). In J. R. Busemeyer, Z. Wang, J. T. Townsend, & A.
Eidels (Eds.), *Models of Semantic Memory*. Oxford University Press.
https://doi.org/10.1093/oxfordhb/9780199957996.013.11
King, J.-R., & Dehaene, S. (2014). Characterizing the dynamics of mental representations:
The temporal generalization method. *Trends in Cognitive Sciences*, *18*(4), 203–210.
https://doi.org/10.1016/j.tics.2014.01.002
Klimesch, W. (2012). Alpha-band oscillations, attention, and controlled access to stored
information. *Trends in Cognitive Sciences*, *16*(12), 606–617.
https://doi.org/10.1016/j.tics.2012.10.007
Kojima, K., Brown, E. C., Matsuzaki, N., Rothermel, R., Fuerst, D., Shah, A., Mittal, S., Sood,
S., & Asano, E. (2013). Gamma activity modulated by picture and auditory naming
tasks: Intracranial recording in patients with focal epilepsy. *Clinical Neurophysiology*,
124(9), 1737–1744. https://doi.org/10.1016/j.clinph.2013.01.030
Kovach, C. K., Tsuchiya, N., Kawasaki, H., Oya, H., Howard, M. A., & Adolphs, R. (2011).
Manifestation of ocular-muscle EMG contamination in human intracranial
recordings. *NeuroImage*, *54*(1), 213–233.
https://doi.org/10.1016/j.neuroimage.2010.08.002
Lachaux, J.-P., Axmacher, N., Mormann, F., Halgren, E., & Crone, N. E. (2012). High-
frequency neural activity and human cognition: Past, present and possible future of
intracranial EEG research. *Progress in Neurobiology*, *98*(3), 279–301.
https://doi.org/10.1016/j.pneurobio.2012.06.008
Lambon Ralph, M. A., Jefferies, E., Patterson, K., & Rogers, T. T. (2017). The neural and
computational bases of semantic cognition. *Nature Reviews Neuroscience*, *18*(1), 42–
55. https://doi.org/10.1038/nrn.2016.150

Lambon Ralph, M. A., Sage, K., Jones, R. W., & Mayberry, E. J. (2010). Coherent concepts are
computed in the anterior temporal lobes. *Proceedings of the National Academy of*
Sciences, *107*(6), 2717–2722. https://doi.org/10.1073/pnas.0907307107
Liu, H., Agam, Y., Madsen, J. R., & Kreiman, G. (2009). Timing, timing, timing: Fast decoding
of object information from intracranial field potentials in human visual cortex.
Neuron, *62*(2), 281–290. https://doi.org/10.1016/j.neuron.2009.02.025
Lüders, H., Lesser, R. P., Hahn, J., Dinner, D. S., Morris, H. H., Wylie, E., & Godoy, J. (1991).
Basal temporal language area. *Brain*, *114*(2), 743–754.
https://doi.org/10.1093/brain/114.2.743
Marko, M., Cimrová, B., & Riečanský, I. (2019). Neural theta oscillations support semantic
memory retrieval. *Scientific Reports*, *9*(1), 17667. https://doi.org/10.1038/s41598-
019-53813-y
Matoba, K., Matsumoto, R., Shimotake, A., Nakae, T., Imamura, H., Togo, M., Yamao, Y.,
Usami, K., Kikuchi, T., Yoshida, K., Matsuhashi, M., Kunieda, T., Miyamoto, S.,
Takahashi, R., & Ikeda, A. (2024). Basal temporal language area revisited in Japanese
language with a language function density map. *Cerebral Cortex*, *34*(6), bhae218.
https://doi.org/10.1093/cercor/bhae218
Merker, B. (2013). Cortical gamma oscillations: The functional key is activation, not
cognition. *Neuroscience & Biobehavioral Reviews*, *37*(3), 401–417.
https://doi.org/10.1016/j.neubiorev.2013.01.013
Mitra, P., & Bokil, H. (2007). *Observed Brain Dynamics*. Oxford University Press.
https://doi.org/10.1093/acprof:oso/9780195178081.001.0001
Mollo, G., Cornelissen, P. L., Millman, R. E., Ellis, A. W., & Jefferies, E. (2017). Oscillatory
dynamics supporting semantic cognition: MEG evidence for the contribution of the
anterior temporal lobe hub and modality-specific spokes. *PLOS ONE*, *12*(1),
e0169269. https://doi.org/10.1371/journal.pone.0169269
Morrison, C. M., Chappell, T. D., & Ellis, A. W. (1997). Age of acquisition norms for a large set
of object names and their relation to adult estimates and other variables. *The*
Quarterly Journal of Experimental Psychology Section A, *50*(3), 528–559.
https://doi.org/10.1080/027249897392017
Nagata, K., Kunii, N., Shimada, S., Fujitani, S., Takasago, M., & Saito, N. (2022).
Spatiotemporal target selection for intracranial neural decoding of abstract and
concrete semantics. *Cerebral Cortex*, *32*(24), 5544–5554.
https://doi.org/10.1093/cercor/bhac034
Nakai, Y., Jeong, J., Brown, E. C., Rothermel, R., Kojima, K., Kambara, T., Shah, A., Mittal, S.,
Sood, S., & Asano, E. (2017). Three- and four-dimensional mapping of speech and
language in patients with epilepsy. *Brain*, *140*(5), 1351–1370.
https://doi.org/10.1093/brain/awx051
Nakai, Y., Sugiura, A., Brown, E. C., Sonoda, M., Jeong, J., Rothermel, R., Luat, A. F., Sood, S.,
& Asano, E. (2019). Four-dimensional functional cortical maps of visual and auditory
language: Intracranial recording. *Epilepsia*, *60*(2), 255–267.
https://doi.org/10.1111/epi.14648
Nir, Y., Fisch, L., Mukamel, R., Gelbard-Sagiv, H., Arieli, A., Fried, I., & Malach, R. (2007).
Coupling between Neuronal Firing Rate, Gamma LFP, and BOLD fMRI Is Related to

Interneuronal Correlations. *Current Biology*, *17*(15), 1275–1285. https://doi.org/10.1016/j.cub.2007.06.066

Nobre, A., & McCarthy, G. (1995). Language-related field potentials in the anterior-medial temporal lobe: II. Effects of word type and semantic priming. *The Journal of Neuroscience*, *15*(2), 1090–1098. https://doi.org/10.1523/JNEUROSCI.15-02-01090.1995

Parvizi, J., & Kastner, S. (2018). Promises and limitations of human intracranial electroencephalography. *Nature Neuroscience*, *21*(4), 474–483. https://doi.org/10.1038/s41593-018-0108-2

Patterson, K., Nestor, P. J., & Rogers, T. T. (2007). Where do you know what you know? The representation of semantic knowledge in the human brain. *Nature Reviews Neuroscience*, *8*(12), 976–987. https://doi.org/10.1038/nrn2277

Pobric, G., Jefferies, E., & Lambon Ralph, M. A. (2007). Anterior temporal lobes mediate semantic representation: Mimicking semantic dementia by using rTMS in normal participants. *Proceedings of the National Academy of Sciences*, *104*(50), 20137–20141. https://doi.org/10.1073/pnas.0707383104

Pobric, G., Jefferies, E., & Lambon Ralph, M. A. (2010a). Amodal semantic representations depend on both anterior temporal lobes: Evidence from repetitive transcranial magnetic stimulation. *Neuropsychologia*, *48*(5), 1336–1342. https://doi.org/10.1016/j.neuropsychologia.2009.12.036

Pobric, G., Jefferies, E., & Lambon Ralph, M. A. (2010b). Category-specific versus category-general semantic impairment induced by transcranial magnetic stimulation. *Current Biology*, *20*(10), 964–968. https://doi.org/10.1016/j.cub.2010.03.070

Rogers, T. T., Cox, C. R., Lu, Q., Shimotake, A., Kikuchi, T., Kunieda, T., Miyamoto, S., Takahashi, R., Ikeda, A., Matsumoto, R., & Lambon Ralph, M. A. (2021). Evidence for a deep, distributed and dynamic code for animacy in human ventral anterior temporal cortex. *eLife*, *10*, e66276. https://doi.org/10.7554/eLife.66276

Rogers, T. T., Lambon Ralph, M. A., Garrard, P., Bozeat, S., McClelland, J. L., Hodges, J. R., & Patterson, K. (2004). Structure and deterioration of semantic memory: A neuropsychological and computational investigation. *Psychological Review*, *111*(1), 205–235. https://doi.org/10.1037/0033-295X.111.1.205

Rupp, K., Roos, M., Milsap, G., Caceres, C., Ratto, C., Chevillet, M., Crone, N. E., & Wolmetz, M. (2017). Semantic attributes are encoded in human electrocorticographic signals during visual object recognition. *NeuroImage*, *148*, 318–329. https://doi.org/10.1016/j.neuroimage.2016.12.074

Sato, N., Matsumoto, R., Shimotake, A., Matsuhashi, M., Otani, M., Kikuchi, T., Kunieda, T., Mizuhara, H., Miyamoto, S., Takahashi, R., & Ikeda, A. (2021). Frequency-dependent cortical interactions during semantic processing: An electrocorticogram cross-spectrum analysis using a semantic space model. *Cerebral Cortex*, *31*(9), 4329–4339. https://doi.org/10.1093/cercor/bhab089

Sauseng, P., & Klimesch, W. (2008). What does phase information of oscillatory brain activity tell us about cognitive processes? *Neuroscience & Biobehavioral Reviews*, *32*(5), 1001–1013. https://doi.org/10.1016/j.neubiorev.2008.03.014

Shimotake, A., Matsumoto, R., Ueno, T., Kunieda, T., Saito, S., Hoffman, P., Kikuchi, T.,
Fukuyama, H., Miyamoto, S., Takahashi, R., Ikeda, A., & Lambon Ralph, M. A. (2015).
Direct exploration of the role of the ventral anterior temporal lobe in semantic
memory: Cortical stimulation and local field potential evidence from subdural grid
electrodes. *Cerebral Cortex*, *25*(10), 3802–3817.
https://doi.org/10.1093/cercor/bhu262
Smith, S. M., Jenkinson, M., Woolrich, M. W., Beckmann, C. F., Behrens, T. E. J., Johansen-
Berg, H., Bannister, P. R., De Luca, M., Drobnjak, I., Flitney, D. E., Niazy, R. K.,
Saunders, J., Vickers, J., Zhang, Y., De Stefano, N., Brady, J. M., & Matthews, P. M.
(2004). Advances in functional and structural MR image analysis and implementation
as FSL. *NeuroImage*, *23*, S208–S219.
https://doi.org/10.1016/j.neuroimage.2004.07.051
Snyder, K. M., Forseth, K. J., Donos, C., Rollo, P. S., Fischer-Baum, S., Breier, J., & Tandon, N.
(2023). Critical role of the ventral temporal lobe in naming. *Epilepsia*, *64*(5), 1200–
1213. https://doi.org/10.1111/epi.17555
Solomon, E. A., Lega, B. C., Sperling, M. R., & Kahana, M. J. (2019). *Hippocampal theta codes*
for distances in semantic and temporal spaces. 10.
Spiers, H. J. (2020). The hippocampal cognitive map: One space or many? *Trends in Cognitive*
Sciences, *24*(3), 168–170. https://doi.org/10.1016/j.tics.2019.12.013
Stryker, M. P. (1989). Is grandmother an oscillation? *Nature*, *338*(6213), 297–298.
https://doi.org/10.1038/338297a0
Tallon-Baudry, C., & Bertrand, O. (1999). Oscillatory gamma activity in humans and its role in
object representation. *Trends in Cognitive Sciences*, *3*(4), 151–162.
https://doi.org/10.1016/S1364-6613(99)01299-1
Tanji, K. (2005). High-frequency -band activity in the basal temporal cortex during picture-
naming and lexical-decision tasks. *Journal of Neuroscience*, *25*(13), 3287–3293.
https://doi.org/10.1523/JNEUROSCI.4948-04.2005
Tibshirani, R. (1996). Regression shrinkage and selection via the lasso. *Journal of the Royal*
Statistical Society: Series B (Methodological), *58*(1), 267–288.
https://doi.org/10.1111/j.2517-6161.1996.tb02080.x
Visser, M., Jefferies, E., & Lambon Ralph, M. A. (2010). Semantic processing in the anterior
temporal lobes: A meta-analysis of the functional neuroimaging literature. *Journal of*
Cognitive Neuroscience, *22*(6), 1083–1094. https://doi.org/10.1162/jocn.2009.21309
von der Malsburg, C. (1995). Binding in models of perception and brain function. *Current*
Opinion in Neurobiology, *5*(4), 520–526. https://doi.org/10.1016/0959-
4388(95)80014-X
Wang, W., Degenhart, A. D., Sudre, G. P., Pomerleau, D. A., & Tyler-Kabara, E. C. (2011).
Decoding semantic information from human electrocorticographic (ECoG) signals.
Annual International Conference of the IEEE Engineering in Medicine and Biology
Society. IEEE Engineering in Medicine and Biology Society. Annual International
Conference, *2011*, 6294–6298. https://doi.org/10.1109/IEMBS.2011.6091553
Watrous, A. J., Fell, J., Ekstrom, A. D., & Axmacher, N. (2015). More than spikes: Common
oscillatory mechanisms for content specific neural representations during perception

and memory. *Current Opinion in Neurobiology*, *31*, 33–39.

https://doi.org/10.1016/j.conb.2014.07.024

Yuste, R. (2015). From the neuron doctrine to neural networks. *Nature Reviews*

Neuroscience, *16*(8), 487–497. https://doi.org/10.1038/nrn3962

Yuval-Greenberg, S., Tomer, O., Keren, A. S., Nelken, I., & Deouell, L. Y. (2008). Transient

induced gamma-band response in eeg as a manifestation of miniature saccades.

Neuron, *58*(3), 429–441. https://doi.org/10.1016/j.neuron.2008.03.027

1103