1 **IL4Pred2: Prediction of Interleukin-4 Inducing Peptides in Human and Mouse**

2 **Ritu Tomer, Naman Kumar Mehta, Shivani Malik, Shipra Jain and Gajendra P. S. Raghava\***

3 Department of Computational Biology, Indraprastha Institute of Information Technology, Okhla Phase 3, New

4 Delhi-110020, India.

5
6
7 **Mailing Address of Authors**

8
9 Ritu Tomer: ritut@iiitd.ac.in                    ORCID ID: https://orcid.org/0000-0002-6171-8660

10 Naman Kumar Mehta: namanm@iiitd.ac.in          ORCID ID: https://orcid.org/0009-0009-0244-2826

11 Shivani Malik: shivanim@iiitd.ac.in            ORCID ID: https://orcid.org/0009-0002-3005-3069

12 Shipra Jain: shipra@iiitd.ac.in                ORCID ID: https://orcid.org/0000-0002-7045-5188

13 Gajendra P. S. Raghava (GPSR): raghava@iiitd.ac.in ORCID ID: https://orcid.org/0000-0002-8902-2876

14
**\*Corresponding Author**

Prof. Gajendra P. S. Raghava

Department of Computational Biology

Indraprastha Institute of Information Technology, Delhi

Okhla Industrial Estate, New Delhi, India

Phone:011-26907444

Email: raghava@iiitd.ac.in

Website: http://webs.iiitd.edu.in/raghava/

*Abstract*

In 2013, our group developed IL4pred, a host-independent method for predicting interleukin-4 (IL-4) inducing peptides, which has been widely used by the scientific community. In this study, we present a second-generation method, IL4Pred2, which is a host-specific approach designed to predict IL-4 inducing peptides separately for human and mouse hosts. All models were trained, tested, and benchmarked on experimentally validated data obtained from the IEDB. We employed a wide range of state-of-the-art techniques for prediction, including similarity-based approaches, machine learning, deep learning methods, and large language models. Our best model achieved highest AUC 0.80 with MCC 0.45 for human and AUC 0.82 with MCC 0.50 for mouse on independent set of main datasets. All models were trained, test and optimized on training dataset. We validate our final model on an independent dataset which is not used in training or hyperparameter optimization of models. In this study, we developed models on three types of datasets called Main, Alternate1 and Alternate2 for predicting IL-4 inducing peptides. This abstract show performance of our models on Main dataset, performance of models on other datasets have been discussed in manuscript. One of the major objectives of this study is to facilitate research community in the area of immunotherapy and vaccine development. Thus, we developed, a web server and standalone software IL4pred2 for predicting, designing and scanning IL-4 inducing peptides in proteins (https://webs.iiitd.edu.in/raghava/il4pred2/ and https://github.com/raghavagps/il4pred2 ).

*Keywords:* Cytokines, T-Helper epitopes, MHC binders, AI based models, Subunit vaccine

 ***Introduction:***

Interleukin-4 (IL-4)  plays a critical role in various biological and immunoregulatory functions. It regulates a

wide range of cells that include B-/T- lymphocytes, NK cells, monocytes, dendritic cells, basophils, mast cells,

and fibroblasts [1–5]. It drives the differentiation of T-helper cells and promotes the growth of CD8+ T cells [6].

Its receptors appear on many cell types, primarily of hematopoietic origin [7, 8]. Researchers also refer to IL-4

as B cell growth factor-1 (BCGF-1) or B cell stimulatory factor-1 (BSF-1) [5, 9]. It also regulates the growth

and differentiation of hematopoietic stem cells [1]. IL-4 activates the JAK/STAT signaling cascade, which leads

to inflammation and hypersensitivity [10]. As illustrated in Figure 1, IL-4 is a key mediator of type 2 immunity.

Recent studies have identified its therapeutic role in multiple myeloma, cancer, psoriasis, mucormycosis, and

arthritis [11–14]. Current therapies for asthma and atopic dermatitis work by blocking IL-4 activity. In contrast,

IL-4 has shown therapeutic benefits in animal models of spinal cord injury, stroke, and multiple sclerosis [15].

**Fig 1: Schematic representation of role of IL4 cytokine in biological systems.**

Identifying peptides or antigenic regions capable of inducing IL-4 is, therefore, crucial for designing IL-4-based

immunotherapies. Although experimental methods can detect IL-4 inducing peptides with high precision, they

remain expensive, labor-intensive, and time-consuming. This highlights the need to develop efficient

computational approaches for predicting and designing IL-4 inducing peptides. Over the years, researchers have

developed several computational methods to predict cytokine-inducing peptides for a wide range of cytokines,

which include IL-6, IL-7, IL-10, IL-13, interferon-gamma, and TNF-alpha [16–21]. In 2013, our group was the

first to introduce IL4Pred, a method for predicting IL-4 inducing peptides [22]. IL4Pred has been widely used

and cited by researchers to identify and experimentally validate IL-4 inducing peptides. In the past decade,

several new methods have emerged for IL-4 prediction, including Meta-IL4 and PLM-IL4 [6, 23].

One of the major limitations of existing methods is their reliance on limited data available at the time of development. Another key drawback is their host-independent nature; these methods use a single model for all hosts. These method assuming all methods have same immune response for an antigen, which is not universally true. To address these limitations, we developed a second-generation method, IL4Pred2, which builds separate models for human and mouse to predict IL-4 inducing peptides. In addition, datasets used in this study have maximum and latest information from available sources. In this study, we retrieved experimentally validated peptides from the IEDB database to construct our datasets. Generating a positive set of IL-4 inducing peptides was straightforward, as such data are readily available in IEDB. However, constructing an appropriate negative dataset that is acceptable to the scientific community remains a significant challenge. To overcome this, we created three distinct datasets for each host, termed *Main*, *Alternate1*, and *Alternate2*. Each dataset includes a positive set of experimentally validated IL-4 inducing MHC class II binders; 845 for human and 560 for mouse. The negative set in each case contains an equal number of peptides that are not known to induce IL-4. Specifically, the Main dataset includes a mixture of MHC class II binders and non-binders as negatives; Alternate1 uses only MHC class II binders; and Alternate2 uses only MHC class II non-binders. Further details are provided in the Materials and Methods section, while the rationale for using multiple datasets is discussed in the Discussion section. We developed a wide range of models for each dataset and for both human and mouse hosts. These models are intended to aid in identifying potential antigens for immunotherapy and vaccine design [24].

### Materials & Methods

In this study, we made an effort to classify IL4-inducing peptides based on different hosts for which we have followed the below given methodology.

**Fig 2:** The figure depicts the overall architecture of the study.

*1.1. Dataset and Preprocessing*

In this study, we developed models for human and mouse host, thus we create separate datasets for each host.

We extract data from IEDB for creating datasets, IEDB contain experimentally validated peptides. For each

host, we created three datasets termed as Main, Alternate1 and Alternate2 (**Please refer Supplementary Figure**

**S1**). In all three datasets, positive dataset is same that is IL-4 inducing MHC II binding peptides (**Table 1**). We

have taken different type of data to create negative dataset in three datasets. The negative dataset of Main

dataset contains MHC Class II binders and MHC non-binders. We also make sure that none of the peptide in

negative dataset have ability to induce IL-4.  In case of Alternate1 dataset, our negative contains MHC Class II

binders which do not induce IL-4. In case of Alternate2 dataset, our dataset contains MHC Class II non-binders

which does not induce IL-4.

We have selected MHC-class II non-binders by considering there $IC_{50}$ values. As given in previous studies,

MHC class II binding affinities were categorized based on their $IC_{50}$ values, as good binders ($IC_{50} \leq$ 1000 nM),

weak binders ($IC_{50}$ 1,000– 10,000 nM), and non-binders ($IC_{50} >$ 10000 nM) [25, 26]. In present study, we have

flagged the peptides with $IC_{50}$ value more than 1000 nM as MHC class II non-binders. Further, we preprocessed

extracted data by removing redundant peptide sequences and applying length filter. We choose the length range

based on maximum sequence coverage. The detailed data statistics of all three models for both hosts can be seen

in **Table 1**.

**Table 1: The table shows the number of peptides in different datasets for human and mouse.**

| Human | | | | | | |
|---|---|---|---|---|---|---|
| **Data Type** | **Main Dataset** | | **Alternate1 Dataset** | | **Alternate2 Dataset** | |
| | **Positive** | **Negative** | **Positive** | **Negative** | **Positive** | **Negative** |
| **Unique peptide** | 900 | 1389 | 900 | 534 | 900 | 1855 |
| **Length (9-22)** | 845 | 1333 | 845 | 516 | 845 | 1817 |
| **Final Data** | 845 | 845 | 845 | 516 | 845 | 845 |
| **Mouse** | | | | | | |
| **Data Type** | **Main Dataset** | | **Alternate1 Dataset** | | **Alternate2 Dataset** | |
| | **Positive** | **Negative** | **Positive** | **Negative** | **Positive** | **Negative** |
| **Unique peptide** | 660 | 1787 | 660 | 905 | 660 | 882 |
| **Length (9-22)** | 560 | 1547 | 560 | 698 | 560 | 849 |
| **Final Data** | 560 | 560 | 560 | 560 | 560 | 560 |

*1.2. Feature Extraction*

We have deployed Pfeature tool to extract the peptide-based features from the dataset sequences [27]. Using this

method, we have generated a total of 9189 feature vectors for every given sequence of our data. In addition to

this, we have also computed composition-based features separately such as AAC, DPC and TPC to develop

machine learning based models over single composition-based features.

*1.3. Alignment based prediction methods*

**a)** *BLAST:* BLAST tool is widely used for annotating and aligning peptide/ protein sequences [28–30]. In this

study, we have implemented this tool to identify similarity of a query sequence with IL4 inducing peptides

by aligning it to a manually curated database of IL4 inducing and non-inducing interleukins sequences. We deployed the BLASTshortP (version 2.9.0), a method designed for annotating short peptides, based on the resemblance among the sequences. In order to run this tool, we first created a repository of IL4 inducing and non-inducing peptides of training dataset. Then, each sequence in the validation dataset was searched against it. In this approach, we employed the top BLAST hit approach. In this method, a peptide sequence was classified as an inducing or non-inducing peptide based on the top match peptide label, using various E-value cutoffs ranging from $10^{-1}$ to $10^{-6}$. For example, if the query sequence hits a IL4 inducing peptide, then the sequence was categorized as IL4 inducing, otherwise, vice versa. The performance was evaluated using different E-value cutoffs.

b) *Identification of Motifs*: In the present study, we scanned exclusive conserved patterns in positive and negative peptide sequences using MERCI – Motif EmeRging and with Classes Identification and MEME (Multiple Em for Motif Elicitation) suits tools such as MEME-MAST (Motif Alignment and Search Tool) [31–33]. These two are widely used tools for motif discovery in each set of sequences. These tools aid in discovering exclusive patterns/ motifs and their occurrences that can distinguish between IL4 inducing and non-inducing peptides.

### 1.4. Alignment-free prediction methods

a) *Machine learning models:* With the aim to screening the IL4 inducing and non-inducing peptides, we deployed various widely used machine learning models such as Decision Tree, Random Forest, Logistic Regression, XGBoost (Extreme Gradient Boosting), K-Nearest Neighbors, Gaussian Naive Bayes, Extra Tree and Support Vector Classifier [21, 34]. To implement these machine learning algorithms, we deployed sklearn, a python-based machine learning library.

b) *Feature Selection*

In this study, we applied several widely known feature selection techniques such as Support Vector Classifier with L1 regularization (SVC-L1), Minimum Redundancy Maximum Relevance (mRMR), and Sequential Feature Selection (SFS). SVC-L1 is a type of Support Vector Machine with linear kernel, penalized with L1 regularization (also known as Lasso regularization) [35]. MRMR aims to extract features that have high relevance to the target variable with minimum redundancy with each other [36]. SFS is based on a greedy search algorithm that selects features sequentially [37].

c) *Statistical method for feature reduction*

In addition to the popular feature selection techniques, we have also applied mean based univariate analysis to select relevant features. In this step we have implemented the mean based univariate approach, by applying a student T-test. It enables us to compare the mean difference of the feature set between the inducing and non-inducing peptides. We ranked the features with significant p-values ($p<0.05$) and higher mean difference among both classes. Using these ranked features, we developed ML models using top 100, 150, 200, 250 feature sets.

d) *Deep learning models:* In present study, we have implemented 1D Convolutional Neural Networks (1D CNN) and TabNet for screening of IL4 inducing peptides. The 1D CNN extracts spatial patterns from peptide sequences encoded using one-hot representation [38, 39]. TabNet, designed for tabular

data, leverages feature transformer blocks to model complex relationships and attentive transformers for feature selection, ensuring interpretability through sparse regularization [40]. While 1D CNN processes sequence-based information, TabNet focuses on tabular features like physicochemical properties.

e) **Reinforcement learning**

In this study, we have also implemented the LLM (large language model) for the classification of IL4 inducing and non-inducing peptides. We utilized ProtBERT which is a transformed based Bert model and has been pretrained on a large pool of protein sequences in a self-supervised fashion [41]. We extracted embeddings from the pretrained model, and which represented the amino acid sequences. These embeddings encode biochemical and structural features of peptides, such as similarities, motifs, and functional relationships, learned during pretraining on large protein sequence datasets. Post that we fine-tuned the ProtBERT model on a labelled dataset and varied epoch values (3 to 7) to record the performance parameters.

### 1.5. Cross validation

In order to maintain the machine learning standards, we randomly split all datasets created as 80% training data and 20% independent validation dataset. In addition to this, we have implemented a 5-fold cross validation technique over our training dataset, to ensure robustness and to prevent overfitting of our model. Using this technique, we have divided our training data (i.e. 80% of dataset) into five subsets, in which four are used as training and one as testing dataset [18, 21, 42]. This process is iterated five times so that each subset is used as a testing subset. Post that the best model is implemented on an independent validation set (i.e. 20% of dataset) for evaluating the machine learning based classification model performance.

### 1.6. Performance evaluation

The efficacy of our machine learning based prediction models developed for the prediction of IL4 inducing and non-inducing peptides, we calculated widely used evaluation parameters in literature [22, 43]. In the present study, we implemented both threshold-dependent parameters such as sensitivity (Sens), specificity (Spec) and accuracy (Acc) and independent parameters such as Area Under the Receiver Operating Characteristic (AUROC) curve to measure the performance of the models. These parameters were calculated using the following equations:

$$Sensitivity = \frac{TP}{TP+FN} * 100 \tag{1}$$

$$Specificity = \frac{TN}{TN+FP} * 100 \tag{2}$$

$$Accuracy = \frac{TP+TN}{TP+FP+TN+FN} * 100 \tag{3}$$

$$MCC = \frac{(TP*TN) - (FP*FN)}{\sqrt{(TP+FP)(TP+FN)(TN+FP)(TN+FN)}} \tag{4}$$

Where, FP is false positive, FN is false negative, TP is true positive, and TN is true negative.

### 1.7. Ensemble approach

In present study, we have developed an ensemble method that integrates machine learning models with traditional sequence-based approaches to enhance predictive performance. Specifically, we combined the top-performing machine learning models with alignment-based techniques, such as BLAST, as well as motif-based methods, including MEME-MAST and MERCI. By leveraging the complementary nature of these approaches, we intend to capture evolutionary relationships through sequence alignment and functional motifs through pattern recognition, ultimately leading to combined prediction model. Using this we developed ensemble approach using 3 methods: 1) BLAST mapped IL4 inducing peptides based on similarity hits then ML model was used to predict the non-mapped peptides. 2) MERCI based motif sequence patterns were identified in the validation dataset and then, ML model predicted the non-identified peptides. 3) Similarly, combined MEME MAST motifs with ML model prediction results.

*Results***:**

*1.    Preliminary analysis*

*1.1.    Positional Analysis*

In this study, we did positional analysis to understand the amino acids preferences at specific positions in our main dataset between IL4-inducing and IL4 non-inducing peptides for human and mouse dataset. Two sample logo positional analysis depicts the dominance and relative occurrence of a particular amino acid in the sequence [44]. It is vital to note that the first eight positions in the logo depicts the eight N-terminal residues, and the last eight depicts the eight C-terminal residues. It is evident from **Figure 3.1**, that in human host lysine (K), isoleucine (I) and tyrosine (Y) are found to be predominant at multiple positions in IL4 inducing peptides. Lysine is often present at $1^{st}$, $4^{th}$, $5^{th}$, $8^{th}$, $9^{th}$, $10^{th}$, $13^{th}$ and $18^{th}$ position. Whereas proline (P), glycine (G), leucine (L) and aspartic acid (D) amino acids are in abundance in the non-inducing peptides. Proline is often present at $1^{st}$, $5^{th}$, $7^{th}$, $8^{th}$, $9^{th}$, $13^{th}$, $15^{th}$ and $18^{th}$ position.

In contrast, in mouse host certain amino acids are found to be confined at a particular position. In this data, glycine (G) at $1^{st}$ and $4^{th}$, proline (P) at $3^{rd}$, $5^{th}$, $6^{th}$, $8^{th}$, $12^{th}$, $13^{th}$, $16^{th}$ and $17^{th}$, phenylalanine (F) at $4^{th}$ and $5^{th}$ and tyrosine (Y) are found to be present at $6^{th}$, $8^{th}$ and $17^{th}$ position in IL4 inducing peptides, and leucine (L) is found to be prominent at $1^{st}$, $5^{th}$, $6^{th}$, $9^{th}$, $13^{th}$, $14^{th}$, $17^{th}$ and $18^{th}$ position in IL4 non-inducing peptides.

**Fig 3.1: This figure represents two-sample logo positional analysis for IL4 Inducing and Non-inducing**

**peptides in human and mouse host.**

We have also performed positional analysis to understand the amino acids preferences at specific positions in

IL4-inducing peptides of human and mouse. Here, we observed that amino acids leucine (L) is abundant at 1[st],

8[th], 13[th], 14[th], 17[th] and 18[th] position, methionine (M) is found at 4[th] AND 6[th] position and cysteine is present at

11[th] and 16[th] position in human IL4-inducers while serine (S), glutamine (Q), proline (P), asparagine (N) and

glycine (G) residues are abundant at specific positions in mouse IL4-inducing peptides.

**Fig 3.2: This figure represents two-sample logo positional analysis between IL4 Inducing peptides of**

**human and mouse host.**

*1.2.  Compositional Analysis*

In present study, we performed a compositional analysis of peptide dataset to capture the amino acid

composition molecular insights as IL4 inducing peptides. We observed that in humans' Glutamic acid,

Isoleucine, Lysine and Tyrosine amino acid residues were found in abundance in IL4 inducing peptides,

whereas Aspartic acid, phenylalanine, histidine, Leucine, Proline, Asparagine and Threonine were reported in

higher frequency in non-inducing peptides.  As depicted in **Figure 4.1**, amino acid composition trends in mouse

host were not like humans.  In mouse, Proline, Serine and Tyrosine average amino acid composition were higher

in IL4 inducing peptides, whereas Cysteine, Histidine, Isoleucine, Leucine, Methionine and Arginine are on

abundant side in non-inducing peptides.

**Figure 4.1: This figure depicts IL4 inducing and non-inducing peptides amino acid composition in human and mouse hosts.**

To understand the difference between human and mouse specific IL4 inducing peptides, we performed average compositional analysis between IL4 inducing peptides of human and mouse hosts. As we hypothesized that there is difference between composition of human and mouse data. Here, we can clearly see that the average amino acid composition of cysteine, phenylalanine, leucine and methionine residues are significantly higher in human IL4-inducing peptides while average amino acid composition of glycine and proline residues are abundant in mouse data. The same trend can also be seen in amino acid positional analysis between human and mouse IL4-inducing peptides.

**Figure 4.2: This figure shows amino acid composition of IL-4 inducing peptides in human and mouse.**

*1.3.    Mean based analysis*

In order to capture the mean-based differentiation among feature pool, we ranked them based on their higher

mean difference between IL4 inducing and non-inducing peptides with significant p-value. As observed from

**Table 2** that in human host, Pseudo Amino Acid Composition (PAAC) feature emerged on top with a difference

of 0.34, whereas composition enhanced transition and distribution (CeTD) based features appeared on top with

difference of 0.36 in mouse dataset. The complete list of features with significant p-value and their ranks can be

referred in **Supplementary Table S1**.

**Table 2: The table depicts top 5 features which have maximum difference in positive and negative**

**peptides**

| Main Dataset of Human | | | | Main Dataset of Mouse | | | |
|---|---|---|---|---|---|---|---|
| **Feature** | **Pos_avg** | **Neg_avg** | **Diff** | **Feature** | **Pos_avg** | **Neg_avg** | **Diff** |
| PAAC1_lam1 | 0.17 | -0.17 | 0.34 | CeTD_100_p_VW1 | 0.18 | -0.18 | 0.36 |
| SOC1_SC1 | 0.16 | -0.16 | 0.32 | CeTD_50_p_VW1 | 0.18 | -0.18 | 0.36 |
| CeTD_12_PO | -0.15 | 0.15 | -0.30 | SER_P | -0.17 | 0.17 | -0.34 |
| SER_K | -0.14 | 0.14 | -0.28 | PAAC1_L | -0.17 | 0.17 | -0.34 |
| QSO1_G_P | -0.14 | 0.14 | -0.28 | APAAC1_L | -0.17 | 0.17 | -0.34 |

**Note:** Diff: Difference between Positive mean and Negative Mean;

*1.4.    Single based feature performance*

In present study, we performed Logistic regression-based analysis to understand the efficacy of single feature to

discriminate IL4 inducing and non-inducing peptides. As evident from **Table 3**, we observed that PAAC1_lam1

feature reported the maximum AUC as 0.59 for human host. Few of these features were also observed in the top

5 list of highest significant mean difference list. Whereas composition enhanced transition and distribution-

based features (CeTD_100_p_VW1, CeTD_50_p_VW1) reported the maximum AUC as 0.61 and 0.60 respectively for the mouse host which are also observed in the list of top 5 highly significant mean difference list. Please refer **Supplementary Table S2** for the detailed list.

**Table 3: Single feature-based performance of top 5 features where models were developed using logistic regression.**

| Main Dataset (Human) | | | | | |
|---|---|---|---|---|---|
| **Feature** | **Sens** | **Spec** | **ACC** | **AUC** | **MCC** |
| PAAC1_lam1 | 53.85 | 55.15 | 54.51 | 0.59 | 0.09 |
| SOC1_SC1 | 57.92 | 55.88 | 56.88 | 0.58 | 0.14 |
| CeTD_13_SA | 62.75 | 50.94 | 56.73 | 0.58 | 0.14 |
| AAC_K | 55.35 | 55.15 | 55.25 | 0.57 | 0.11 |
| SER_K | 55.35 | 55.15 | 55.25 | 0.57 | 0.11 |
| Main Dataset (Mouse) | | | | | |
| **Feature** | **Sens** | **Spec** | **ACC** | **AUC** | **MCC** |
| CeTD_100_p_VW1 | 60.71 | 56.43 | 58.57 | 0.61 | 0.17 |
| CeTD_50_p_VW1 | 60.71 | 56.43 | 58.57 | 0.60 | 0.17 |
| CeTD_75_p_VW1 | 60.71 | 56.43 | 58.57 | 0.60 | 0.17 |
| AAC_L | 58.57 | 51.43 | 55.00 | 0.60 | 0.10 |
| SER_L | 58.57 | 51.43 | 55.00 | 0.60 | 0.10 |

**Note:** Sens: Sensitivity; Spec: Specificity; ACC: Accuracy; AUC: Area under curve; MCC: Mathew's correlation coefficient.

### 2. *Alignment based prediction methods*

Alignment-based methods rely on the similar patterns or presence of specific motifs in sequences. These types of methods have higher specificity but low sensitivity. In this study, we used following alignment or similarity-based methods.

### 2.1. *BLAST*

In this approach, we preform BLAST search of peptides in independent dataset against peptides in training dataset. We mapped hits at several e-values ranging from $1e^{-1}$ to $1e^{-6}$. The query sequence was classified as IL4 inducer if its top hit was positive and as IL4 non-inducer if its top hit was from negative data. The detailed list of hits achieved by BLAST on human and mouse main validation data is shown below in **Table 4**.

**Table 4: The performance of BLAST at different cut-off value.**

| Human Host (Main Dataset) | | | | Mouse Host (Main Dataset) | | | |
|---|---|---|---|---|---|---|---|
| **E-value** | **T_hits** | **CP_hits** | **CN_hits** | **E-value** | **T_hits** | **CP_hits** | **CN_hits** |

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| **1.00E-01** | 557 | 89 | 59 | **1.00E-01** | 197 | 30 | 29 |
| **1.00E-02** | 458 | 75 | 41 | **1.00E-02** | 164 | 28 | 27 |
| **1.00E-03** | 331 | 60 | 31 | **1.00E-03** | 126 | 22 | 20 |
| **1.00E-04** | 207 | 48 | 21 | **1.00E-04** | 80 | 14 | 12 |
| **1.00E-05** | 126 | 36 | 12 | **1.00E-05** | 39 | 9 | 6 |
| **1.00E-06** | 66 | 25 | 3 | **1.00E-06** | 18 | 7 | 1 |

**Note: T_hits: Total hits found; CP_hits: correct positive hits; CN_hits: correct negative hits.**

### 2.2. Motif analysis

We performed comprehensive motif analysis using two established tools—MERCI and MEME-MAST— to identify signature sequence patterns associated with IL-4 inducing and non-inducing peptides. Motifs were first extracted from the training dataset and then scanned across independent validation datasets from both humans and mouse to evaluate their presence and relevance. The top 10 motif hits identified by each tool, along with corresponding correct and incorrect classification outcomes, are summarized in **Table 5.** Detailed motif coverage and occurrence for the MERCI tool, along with ensemble method results, are provided in **Supplementary Table S3.1**. Similarly, comprehensive motif coverage and ensemble results for MEME-MAST analysis can be found in **Supplementary Table S3.2**.

**Table 5: The list of Motif hits obtained using MERCI & MEME MAST on Human and Mouse validation datasets.**

| Host | Classification Method | Number of K motifs | IL-4 inducing | | | IL-4 Non-inducing | | |
|---|---|---|---|---|---|---|---|---|
| | | | motif | Correct | Incorrect | motif | Correct | Incorrect |
| **MERCI** | | | | | | | | |
| **Human** | None | 10 | 5 | 7 | 1 | 0 | 0 | 0 |
| **Mouse** | None | 10 | 1 | 1 | 0 | 3 | 6 | 3 |
| **MEME-MAST** | | | | | | | | |
| Host | E-value | Mini-site | Number of K motifs | IL-4 inducing | | | IL-4 Non-inducing | | |
| | | | | motif | Correct | Incorrect | motif | Correct | Incorrect |
| **Human** | 0.05 | 10 | 50 | 14 | 30 | 8 | 10 | 15 | 12 |
| **Mouse** | 0.05 | 10 | 10 | 4 | 6 | 3 | 7 | 5 | 2 |

### 3. Alignment free approach

### 3.1. Machine learning based classifiers

In this study, we have applied several machine learning-based algorithms on composition-based features including amino acid composition (AAC), di-peptide composition (DPC) and tri-peptide composition (TPC). As evident in **Table 6**, for human host Extra tree classifier developed over AAC feature outperformed all and achieved 0.76 as AUC score. In addition to this, Random Forest classifier developed using DPC feature reported highest AUC as 0.70 with balanced sensitivity and specificity for mouse host. Detailed results on training and validation dataset can be referred in **Supplementary Table S4.**

317 **Table 6: The performance of top machine learning based models developed using different type of**
318 **compositional features on independent dataset.**

| Human Dataset (Main data) | | | | | | |
|---|---|---|---|---|---|---|
| **Model** | **Feature** | **Sens** | **Spec** | **ACC** | **AUC** | **MCC** |
| **ET** | **AAC** | 71.43 | 62.18 | 67.16 | 0.76 | 0.34 |
| **ET** | **DPC** | 70.33 | 66.67 | 68.64 | 0.76 | 0.37 |
| **SVC** | **TPC** | 65.39 | 67.31 | 66.27 | 0.74 | 0.33 |
| Mouse Dataset (Main data) | | | | | | |
| **Model** | **Feature** | **Sens** | **Spec** | **ACC** | **AUC** | **MCC** |
| **RF** | **AAC** | 64.57 | 61.86 | 63.39 | 0.68 | 0.26 |
| **RF** | **DPC** | 65.35 | 60.83 | 63.39 | 0.70 | 0.26 |
| **SVC** | **TPC** | 64.57 | 70.10 | 66.96 | 0.69 | 0.34 |

**Note:** Sens: Sensitivity; Spec: Specificity; ACC: Accuracy; AUC: Area under curve; MCC: Mathew's
correlation coefficient.

*3.2.  Feature Selection*

In order to develop a robust model, we applied popular feature selection techniques like SVC-L1, mRMR
and SFS techniques to extract important features from the 9189-feature pool generated using Pfeature.
We selected 149 features from SVC-L1, 50 from mRMR and 17 from SFS techniques for human host.
Similarly, we extracted 97 features from SVC-L1, 50 from mRMR and 17 from SFS techniques for
mouse host. We developed machine learning classifiers using these selected features. As depicted in
**Table 7**, we observed highest AUC as 0.79 using Extra Tree classifier developed SVC-L1 feature
selection technique for human host and 0.72 using Random Forest classifier developed SVC-L1 feature
selection technique for mouse host. Detailed performance evaluation metrics for training data can be
referred in **Supplementary Table S5.**

**Table 7: The performance of top machine learning based models developed on selected features**
**obtained from different techniques.**

| Method | Model | No of selected features | Human host | | | | |
|--------|-------|--------------|------|------|------|------|------|
| | | | Sens | Spec | ACC | AUC | MCC |
| SVC-L1 | ET | 149 | 73.08 | 69.23 | 71.3 | 0.79 | 0.42 |
| mRMR | XGB | 50 | 67.03 | 56.41 | 62.13 | 0.68 | 0.24 |
| SFS | LR | 17 | 61.54 | 58.33 | 0.60 | 0.63 | 0.20 |

| Method | Model | No of features | Mouse host | | | | |
|--------|-------|--------------|------|------|------|------|------|
| | | | Sens | Spec | ACC | AUC | MCC |
| SVC-L1 | RF | 116 | 69.29 | 60.83 | 65.63 | 0.72 | 0.30 |
| mRMR | XGB | 50 | 65.35 | 58.76 | 62.5 | 0.67 | 0.24 |
| SFS | LR | 17 | 56.69 | 64.95 | 0.60 | 0.60 | 0.21 |

335 **Note:** Sens: Sensitivity; Spec: Specificity; ACC: Accuracy; AUC: Area under curve; MCC: Mathew's
336 correlation coefficient.
337
In addition to these feature selection techniques, we also performed the mean based univariate analysis to
rank significant features among IL4 inducing and non-inducing peptides. The top ranked 100, 150, 200
and 300 features with significant p-values were selected and used to implement machine learning based
classifiers. As evident in **Table 8,** we achieved a maximum AUC as 0.80 with MCC of 0.45 over top 300
features for human host while over top 300 features for mouse host we achieved AUC of 0.82 with MCC
of 0.50 using Multilayer Perceptron (MLP) based machine learning classifier. See **Supplementary Table**
**S6** for detailed results over training and validation set.
345
346 **Table 8: The performance of top machine learning based models developed using different number**
347 **of features selected using univariate analysis.**

| Human host | | | | | | |
|--------|-------|------|------|------|------|------|
| Feature | Model | Sens | Spec | ACC | AUC | MCC |
| Top_100 | ET | 0.71 | 0.71 | 71 | 0.76 | 0.41 |
| Top_150 | RF | 0.70 | 0.69 | 70 | 0.76 | 0.39 |
| Top_200 | ET | 0.71 | 0.68 | 70 | 0.76 | 0.39 |
| Top_250 | MLP | 0.75 | 0.69 | 72 | 0.76 | 0.44 |
| Top_300 | MLP | 0.75 | 0.7 | 73 | 0.80 | 0.45 |
| Mouse host | | | | | | |
| Feature | Model | Sens | Spec | ACC | AUC | MCC |
| Top_100 | GNB | 0.65 | 0.69 | 67 | 0.71 | 0.34 |

| | | | | | | |
|---|---|---|---|---|---|---|
| **Top_150** | **GNB** | 0.63 | 0.72 | 67 | 0.72 | 0.35 |
| **Top_200** | **ET** | 0.72 | 0.65 | 69 | 0.73 | 0.37 |
| **Top_250** | **MLP** | 0.69 | 0.7 | 69 | 0.76 | 0.38 |
| **Top_300** | **MLP** | 0.74 | 0.76 | 75 | 0.82 | 0.50 |

**Note:** Sens: Sensitivity; Spec: Specificity; ACC: Accuracy; AUC: Area under curve; MCC: Mathew's correlation coefficient.

### 3.3. *Deep learning-based classifiers*

In present study, deep learning-based classifiers have been deployed for the screening of IL4 inducing and non-inducing peptides. We have implemented 1D CNN and TabNet for classifying among both groups. As shown in **Table 9**, RRI (Repetitive Residue Information) feature reported the maximum AUC score as 0.66 for human host, whereas TPC feature achieved higher AUC score as 0.64 for mouse host using CNN classifier. **Supplementary Table S7** can be referred for performance score for training and testing dataset for both deep learning-based classifier methods.

**Table 9: The performance of deep learning-based models developed using different types of residue compositions and evaluated on independent dataset (main dataset).**

| Human host | | | | | | |
|---|---|---|---|---|---|---|
| **Model** | **Feature** | **Sens** | **Spec** | **ACC** | **AUC** | **MCC** |
| **AAC** | CNNClassifier | 0.61 | 0.55 | 0.58 | 0.61 | 0.16 |
| **DPC** | CNNClassifier | 0.65 | 0.53 | 0.59 | 0.62 | 0.18 |
| **DPC_LEN** | CNNClassifier | 0.57 | 0.67 | 0.62 | 0.65 | 0.24 |
| **RRI** | CNNClassifier | 0.65 | 0.61 | 0.63 | 0.66 | 0.26 |
| **TPC** | CNNClassifier | 0.66 | 0.56 | 0.62 | 0.65 | 0.22 |
| **AAC** | TabNetClassifier | 0.44 | 0.6 | 0.51 | 0.51 | 0.04 |
| **DPC** | TabNetClassifier | 0.84 | 0.18 | 0.54 | 0.45 | 0.03 |
| **DPC_LEN** | TabNetClassifier | 0.35 | 0.74 | 0.53 | 0.58 | 0.09 |
| **RRI** | TabNetClassifier | 0.65 | 0.39 | 0.53 | 0.53 | 0.05 |
| **TPC** | TabNetClassifier | 0.03 | 0.95 | 0.45 | 0.53 | 0.06 |
| Mouse host | | | | | | |
| **Model** | **Feature** | **Sens** | **Spec** | **ACC** | **AUC** | **MCC** |
| **AAC** | CNNClassifier | 0.55 | 0.58 | 0.56 | 0.54 | 0.13 |
| **DPC** | CNNClassifier | 0.51 | 0.57 | 0.54 | 0.59 | 0.08 |
| **DPC_LEN** | CNNClassifier | 0.54 | 0.68 | 0.60 | 0.63 | 0.22 |
| **RRI** | CNNClassifier | 0.57 | 0.45 | 0.52 | 0.52 | 0.02 |
| **TPC** | CNNClassifier | 0.55 | 0.62 | 0.58 | 0.64 | 0.17 |
| **AAC** | TabNetClassifier | 0.50 | 0.58 | 0.54 | 0.56 | 0.08 |
| **DPC** | TabNetClassifier | 0.35 | 0.68 | 0.49 | 0.49 | 0.03 |
| **DPC_LEN** | TabNetClassifier | 0.01 | 0.98 | 0.43 | 0.51 | 0.05 |

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| **RRI** | TabNetClassifier | 0.54 | 0.52 | 0.53 | 0.53 | 0.05 |
| **TPC** | TabNetClassifier | 0.01 | 0.98 | 0.43 | 0.51 | 0.05 |

**Note:** Sens: Sensitivity; Spec: Specificity; ACC: Accuracy; AUC: Area under curve; MCC: Mathew's correlation coefficient.

### 3.4. Large Language model

In this study, we have implemented pretrained protBERT large language model for classification of IL4 inducing and non-inducing peptide groups. As shown in **Table 10**, we observed the maximum AUC as 0.72 using fine-tuned model while AUC of 0.75 achieved feature embeddings extracted from finetuned protBERT model for human host at an epoch value of 5. For the mouse host, the highest AUC of 0.66 was achieved at epoch 7 for both the fine-tuned model and feature embeddings. Refer **Supplementary Table S8** for performance matrix for all models.

**Table 10: The performance of protein language model protBERT and machine learning models**

| Epochs | Feature | Model | Human host | | | | |
|---|---|---|---|---|---|---|---|
| | | | **Sens** | **Spec** | **ACC** | **AUC** | **MCC** |
| **3** | **Sequence** | **Finetuned** | 0.79 | 0.50 | 65.98 | 0.72 | 0.31 |
| | **Embedding** | **RF** | 0.72 | 0.69 | 71.00 | 0.75 | 0.41 |
| **5** | **Sequence** | **Finetuned** | 0.56 | 0.73 | 64.20 | 0.69 | 0.30 |
| | **Embedding** | **ET** | 0.70 | 0.67 | 69.00 | 0.72 | 0.37 |
| **7** | **Sequence** | **Finetuned** | 0.65 | 0.69 | 67.46 | 0.70 | 0.35 |
| | **Embedding** | **ET** | 0.69 | 0.63 | 66.00 | 0.71 | 0.32 |
| Epochs | Feature | Model | Mouse host | | | | |
| | | | **Sens** | **Spec** | **ACC** | **AUC** | **MCC** |
| **3** | **Sequence** | **Finetuned** | 0.57 | 0.63 | 60.27 | 0.60 | 0.21 |
| | **Embedding** | **ET** | 0.60 | 0.59 | 59.00 | 0.62 | 0.18 |
| **5** | **Sequence** | **Finetuned** | 0.69 | 0.52 | 62.05 | 0.63 | 0.22 |
| | **Embedding** | **ET** | 0.64 | 0.60 | 62.00 | 0.64 | 0.23 |
| **7** | **Sequence** | **Finetuned** | 0.55 | 0.67 | 60.71 | 0.66 | 0.22 |
| | **Embedding** | **ET** | 0.61 | 0.62 | 61.00 | 0.66 | 0.22 |

**developed using embedding of protBERT on independent dataset (main dataset).**

**Note:** Sens: Sensitivity; Spec: Specificity; ACC: Accuracy; AUC: Area under curve; MCC: Mathew's correlation coefficient.

### 3.5. Ensemble/Hybrid Approach

*3.5.1.*    **BLAST**

For hybrid method, we merged the similarity-based prediction classifiers and machine learning

algorithms. The BLAST hit results were merged with the best performing machine learning based

classifier labels. We observed the maximum AUC score as 0.76 with MCC of 0.38 at an e-value of $1e^{-6}$

for with maximum correct hits for human host, whereas the highest AUC score reported in mouse host

is 0.71 with MCC of 0.29 at an e-value of $1e^{-6}$. Detailed performance matrix can be referred in

**Supplementary Table S9.**

*3.5.2.*    **Motif**

In this approach, we extracted exclusive motifs/ recurring patterns found in IL4 inducing and non-

inducing peptides training dataset using MERCI & MEME tools. Then we searched for these patterns

in independent validation dataset peptides and reported their presence. If a positive motif is found in

query peptide, then it is marked as IL4 inducing peptide and +0.5 value is assigned and 0 if no match

found. Finally, we combine predicted labels of best machine learning model with motif score. For

MERCI tool we reported the maximum AUC as 0.80 with MCC of 0.45 for human host and AUC as

0.80 with MCC of 0.50 for mouse host by specifying maximum frequency of 10 positive motifs in

MERCI tool using default parameter. Detailed motif coverage and occurrence list with ensemble

method results for MERCI tool can be referred in **Supplementary Table S3.1**. Similarly, for MEME-

MAST tool ensemble method we have achieved maximum AUC as 0.70 with MCC of 0.31 for human

host and AUC as 0.70 with MCC of 0.28 for mouse host with p-value 0.05 respectively. Complete

motif coverage with ensemble approach results for MEME-MAST tool can be referred in

**Supplementary Table S3.2.**

*3.6.*    **Summary**

*3.6.1.*    ***Summary of Main Model***

***Human Host***

In our main model, we have used 845 IL4-inducing, MHC class-II binders as positive dataset while for

negative data we combine 845 IL4 non-inducing, MHC class-II binders as well as non-binders. Both

positive and negative datasets are completely different as we preprocess the data to remove any

redundancy. This dataset is then used for classification purpose. We have applied different approaches

such as alignment-based approach (BLAST & Motif) and alignment free approach (ML, DL, LLM) to

classify between IL4-inducing and non-inducing peptides. Using the alignment-based approach

"BLAST", we got 126 hits which covers 54 sequences out of 338 sequences of validation set. For motif

search we used MERCI software, here we obtained 5 motifs using default parameters which covers

only 8 sequences out which 1 sequence got incorrect hit, while using MEME MAST we got 14 motifs

covering 38 sequences with 8 incorrect hits. Then we move forward to utilize, alignment free

approaches. Firstly, we extracted 9189 composition-based features such as amino acid composition

(AAC), dipeptide composition (DPC) and tripeptide composition (TPC) features. Then we applied

different ML-based classifiers on composition-based features, in this task we found that extra tree

classifier outperforms over other and achieved a highest AUC of 0.76 on AAC and DPC features. Then

we applied different feature selection techniques such as svc-l1, mrmr, sfs, and mean based univariate

analysis on all composition-based features. In this process, we obtained highest AUC of 0.80 on top 300 features selected using mean based univariate feature selection technique. We have also applied DL based classifiers such as CNN and TabNET on composition-based features and achieved AUC of 0.66 using CNN classifier on RRI feature. After that, we have also applied large language protbert model, where we achieved highest AUC of 0.72 on finetune model and AUC 0.75 on embeddings extracted using finetune model.

In last, we have developed hybrid models by combining alignment based and alignment free approaches. By combining BLAST hits with best ML scores, we achieved an AUC 0.76, by combining MERCI hits with best ML scores, we obtained an AUC of 0.80 while using MEME MAST hits with ML scores, we achieved AUC of 0.70. Here, our hybrid approach using motif hits by MERCI and best ML scores achieved highest AUC 0.80 which is similar to our best ML performance i.e; AUC of 0.80 on top 300 features selected using mean based univariate feature selection technique. We have incorporated our best model in the webserver, standalone, github package and pypi package.

### *Mouse Host*

In our main model, we have used 560 IL4-inducing, MHC class-II binders as positive dataset while for negative data we combine 560 IL4 non-inducing, MHC class-II binders as well as non-binders. Both positive and negative datasets are completely different as we preprocess the data to remove any redundancy. This dataset is then used for classification purpose. We have applied different approaches such as alignment-based approach (BLAST & Motif) and alignment free approach (ML, DL, LLM) to classify between IL4-inducing and non-inducing peptides. Using the alignment-based approach "BLAST", we got 18 hits which covers 11 sequences out of 224 sequences of validation set. For motif search we used MERCI software, here we obtained 1 motif using default parameters which covers only 1 sequence, while using MEME MAST we got 4 motifs covering 9 sequences with 3 incorrect hits. Then we move forward to utilize, alignment free approaches. Firstly, we extracted 9189 composition-based features such as amino acid composition (AAC), dipeptide composition (DPC) and tripeptide composition (TPC) features. Then we applied different ML-based classifiers on composition-based features, in this task we found that random forest classifier outperforms over other and achieved a highest AUC of 0.70 on DPC feature. Then we applied different feature selection techniques such as svc-l1, mrmr, sfs, and mean based univariate analysis on all composition-based features. In this process, we obtained highest AUC of 0.82 on top 300 features selected using mean based univariate feature selection technique. We have also applied DL based classifiers such as CNN and TabNET on composition-based features and achieved AUC of 0.64 using CNN classifier on TPC feature. After that, we have also applied large language protbert model, where we achieved highest AUC of 0.66 on finetune model as well as on embeddings extracted using finetune model.

In last, we have developed hybrid models by combining alignment-based and alignment-free approaches. By combining BLAST hits with the best ML scores, we achieved an AUC of 0.71; by combining MERCI hits with the best ML scores, we obtained an AUC of 0.80. While using MEME MAST hits with ML scores, we achieved an AUC of 0.70. Here, our hybrid approach using motif hits by MERCI and best ML scores achieved the highest AUC of 0.80, which is less than our best ML

performance, i.e., an AUC of 0.82 on the top 300 features selected using the mean-based univariate feature selection technique. We have incorporated our best model in the webserver, standalone, GitHub package and Pypi package.

### 3.6.2. Summary of Alternate1 and Alternate2 Models

#### Human Host

The alternate1 & alternate2 model, we have used 845 IL4-inducing, MHC class-II binder peptides as positive data while 516 IL4 non-inducing, MHC class-II binder peptides as negative data for alternate1 and 845 IL4 non-inducing, MHC class-II non binder peptides as negative data. Both positive and negative datasets are completely different as we preprocess the data to remove any redundancy. We follow the same workflow on alternate1 and alternate2 models for classification which we follow in main model.

In alternate1 model, our best model was developed using DPC feature that obtained highest AUC 0.82 using extra tree classifier on validation set. While in alternate2 model, highest AUC 0.85 was achieved on validation set using top 300 features selected using mean based univariate analysis.

#### Mouse Host

The alternate1 & alternate2 model, we have used 560 IL4-inducing, MHC class-II binder peptides as positive data while 560 IL4 non-inducing, MHC class-II binder peptides as negative data for alternate1 and 560 IL4 non-inducing, MHC class-II non binder peptides as negative data. Both positive and negative datasets are completely different as we preprocess the data to remove any redundancy. We follow the same workflow on alternate1 and alternate2 models for classification which we follow in main model.

In alternate1 model, our best model was developed using top 300 features selected using mean based univariate analysis that obtained highest AUC 0.82 using logistic regression classifier on validation set. While in alternate2 model, AAC feature achieved highest AUC 0.88 on validation set using random forest classifier on validation set. We have incorporated our best models in webserver, standalone, github package and pypi package.

### Web Server:

In order to serve the scientific community, we provided an easy-to-use web-based interface to our users (http://webs.iiitd.edu.in/raghava/il4pred2/). IL4Pred2 web server would aid our fellow researchers, to easily scan and predict the IL4 inducing peptides. This online tool has been designed using a responsive HTML template which facilitates web page compatibility among various devices such as mobile, tablets and desktops. This web interface comprises three major modules known as: "Predict", "Design", and "Protein Scan". Standalone version of this tool can be accessed using "https://webs.iiitd.edu.in/raghava/il4pred2/download.php" and is also available at GitHub "https://github.com/raghavagps/il4pred2".

### Benchmarking with exiting methods

It is essential to compare recently developed approaches with those that already exist to assess the application and limitation of our method. In past, researchers made efforts to predict IL-4 inducing peptides. The first method was developed by Dhanda et al, in 2013 to predict IL-4 inducing peptides and achieved a maximum

accuracy of 75.76% and MCC of 0.51 by utilizing amino acid pairs and motif information [22]. After that in
2023, Hassan et al, developed another method named "Meta-IL4" based on ensemble approach. This method
utilized amphiphilic pseudo-amino acid composition (APAAC) feature to predict IL-4 inducing peptides and
reported highest accuracy of 90.70%. Recently, a new method named as "Plm-Il4" has been developed by Liu et
al, using ESM-2 based model achieved accuracy of 93% [23]. The major limitation of all the methods is that
they have been developed using experimental IL-4 inducing data irrespective of their host. To overcome this
limitation, we have developed a host specific method to classify IL4-inducing peptides using human and mouse
as host. In the present study, the compositional analysis of human and mouse host shown a major difference in
average amino acid composition. The amino acid residue leucine is shown to be higher average composition in
Human host while glycine and proline has higher average amino acid composition in Mouse host as shown in
**Figure 4.2**.

We have performed a benchmarking study of IL4pred-2 method using validation dataset and newly added data,
which is not present in previous methods, to calculate the performance over other methods. Here, we have
observed that the main validation dataset of Human and Mouse host on hybrid model (SVM and motif) of
IL4pred achieved an accuracy of 75% and 79% on both human and mouse data while it obtained an accuracy of
50% and 63% using newly added data on human and mouse. The Plm-Il4 achieved accuracy of 61% and 66%
on validation data of human and mouse and accuracy of 64% and 81% on newly added data of human and
mouse (**see Table 11.1**). The above defined models performed well on validation data of IL4pred2 as these
methods already trained on around 60% same positive and 51% same negative dataset of IL4pred2.

We have also performed a reverse analysis of IL4pred-2 human model performance evaluation on IL4pred-2
mouse model and vice versa. This analysis was performed to validate our hypothesis that human model not
working well on mouse data and mouse model does not work well on human data due to their different amino
acid composition. Here, we have observed that main validation dataset of human achieved only 0.50 AUC using
main model of mouse host. It can be clearly seen that mouse model is unable to discriminate between il4-
inducing data of human host. Then we check performance of mouse main validation data on human main model
and achieved an AUC of 0.58 (**see Table 11.2**). These finding clearly support our hypothesis about different
models for human and mouse hosts. Previously, we had already shown that discrimination between hosts in
another method which is designed for discovering interferon-gamma inducing peptides in human and mouse
[45]. The above explained results are shown in **Table 11**, for detailed results please refer **Supplementary Table**
**S10**.

**Table 11.1: This table depicts the benchmarking accuracy of validation data of IL4pred2 over different**
**methods.**

| Method | Human Data | | | Mouse Data | | |
|---|---|---|---|---|---|---|
| | Main | Alt 1 | Alt 2 | Main | Alt 1 | Alt 2 |
| IL4pred (validation data) | 75 | 83 | 64 | 79 | 81 | 67 |
| IL4pred (newly added data) | 50 | 60 | 49 | 63 | 78 | 48 |
| Plm-Il4 (validation | 61 | 62 | 68 | 66 | 61 | 59 |

| | | | | | |
|---|---|---|---|---|---|
| **data)** | | | | | |
| **Plm-Il4 (newly added data)** | 64 | 68 | 63 | 81 | 60 | 62 |

**Note:** Alt 1: Alternate1; Alt 2: Alternate2;

**Table 11.2: This table depicts the benchmarking performance of validation data of IL4pred2 over different methods.**

| Mouse Model | Human Independent Data |
|---|---|
| **Main AUC** | 0.50 |
| **Alternate1 AUC** | 0.49 |
| **Alternate2 AUC** | 0.62 |
| **Human Model** | **Mouse Independent Data** |
| **Main AUC** | 0.58 |
| **Alternate1 AUC** | 0.52 |
| **Alternate2 AUC** | 0.60 |

*Discussion:*

In the era of peptide therapeutics, IL4 based drugs and therapeutics plays a pivotal role in disease prevention. As it originates from T helper 2 cells along with other cytokines, it helps in inhibiting $T_{H1}$-like and $T_H17$-mediated inflammatory processes and act as anti-inflammatory cytokine. It also plays important role in tissue regeneration and the host's defense against parasites [46]. Although, it had also been found in the development of cancer, autoimmune disorders, and allergy diseases [15]. Research on IL-4's potential in immunotherapy and disease modulation is continuing, and given its wide immunological impact, it continues to be a prospective therapeutic target for several diseases [47]. Abrocitinib, Dupilumab, Upadacitinib, Tofacitinib are the few U.S. Food and Drug Administration, and the European Medicines Agency approved therapies which targets IL-4/IL-13 signaling. These drugs targets IL-4Rα receptor, and/or molecules of JAK1, JAK3 and used for treatment purposes of atopic dermatitis, severe asthma, chronic sinusitis, nasal polyps and rheumatoid arthritis [15].

In this study, we tried to develop a host specific prediction method where we used two hosts: Human and Mouse. We have gathered experimentally validated MHC-class II binding IL-4 inducing peptides of Human and Mouse host for prediction task. Each host method consists of three different models depending on nature of IL4 non-inducing peptides. Firstly, we have performed preliminary analysis using main dataset of human and mouse hosts. The positional and compositional analysis amino acid residues shows that leucine is abundant in human host while glycine and proline are abundant in mouse host. We have also implemented alignment-based approaches such as BLAST and Motif (MERCI and MEME) and alignment free approaches such as machine learning based classifiers, deep learning-based classifiers and large language models for classification and prediction of IL-4 inducing peptides. The classification task is completely dependent on most relevant feature. To extract important features, we have performed different feature selection techniques such as SVC-L1, mRMR, SFS, LR-based and univariate (mean-based) feature selection method. As we have prepared three different datasets for each host, different features were used to develop models on individual datasets. Human and Mouse main model is developed using top 300 composition-based selected features from univariate feature

selection method. We have obtained 0.80 AUC with 0.45 MCC on human main model while 0.82 AUC with
0.50 MCC on mouse main model. The best models of all the three datasets for both hosts are incorporated in
webserver and standalone packages.

Most of the existing studies utilized single dataset for developing prediction model for this type of studies. This
raised an obvious question, why we used three types of datasets for building models. In all three datasets,
positive dataset is identical that contain IL-4 inducing peptides extracted from IEDB. The major challenge is to
choose a negative dataset which is acceptable by the scientific community. In Alterante1 dataset, we have
considered MHC class II binders which don't induce IL-4 as the negative set. This dataset contains
experimentally confirmed IL-4 inducing and IL-4 non-inducing MHC class II binding peptides. The majority of
existing studies generally use this type of dataset for model building. Model built on the Alternate1 dataset is
intended to differentiate between IL-4-inducing and IL-4 non-inducing MHC Class II binders. This model is
most helpful if the user knows that their peptide is an MHC Class II binder, but it will fail if peptide is non-
binder. To offer different solutions, we have introduced Alternate2 dataset that contain non-MHC Class II
binders as the negative set. Model built on this dataset is useful for separating IL-4 inducing peptides from non-
MHC Class II binders. But can't differentiate between MHC Class II binders which do or don't induce IL-4. In
real-world, most of time user have no idea whether given peptide an MHC Class II binder or not. Then model
built on above datasets will be failed. To overcome above drawbacks, we have proposed a dataset called Main
dataset. This dataset contains both MHC binders and non-binders as negative dataset, all of which are
experimentally confirmed IL-4 non-inducing peptides. This model is most appropriate for scenarios in which the
user does not have any information regarding whether their peptide is an MHC binder or not. To sum up, we
trained our models on three different datasets to cater to different ranges of user requirements under different
scenarios.

*Conclusion:*
In this study, we have attempted a systemic approach for benchmarking the existing methods for scanning and
predicting the IL4 inducing peptides available in public domain. The aim of this study was to expedite the time-
consuming process and higher precision involved in designing novel drug adjuvant and immunotherapies
revolving around IL4 cytokine. Although generating an immune response via inducing a cytokine/ interleukin in
disease patients is a complex and challenging problem, we hope that this tool would aid in identifying peptide-
based therapeutics against various disease states.

*Acknowledgments*
Authors are thankful to the Department of Science and Technology (DST-INSPIRE), University Grants
Commission (UGC), Department of Biotechnology (DBT), and the Department of Computational Biology,
IIITD New Delhi for fellowships, financial support, infrastructure and facilities. We would like to acknowledge
that Figures were created using BioRender.com**.**

*Data Availability Statement*
All the datasets used in this study are available at the "il4pred2" webserver,
https://webs.iiitd.edu.in/raghava/il4pred2/download.html.

*Preprint*

The preprint is available at biorxiv https://doi.org/10.1101/2025.04.23.650150.

*Funding Source*

The current work has been supported by the Department of Biotechnology (DBT) grant BT/PR40158/BTIS/137/24/2021.

*Author Contributions*

RT and GPSR collected and processed the datasets. RT, NM and GPSR implemented the algorithms and developed the prediction models. RT, NM and GPSR analyzed the results. RT created the front-end user interface and back end of the webserver. RT, SJ and GPSR penned the manuscript. SM prepared the figures and pypi package for the manuscript. RT, NM, SM, SJ and GPSR reviewed the manuscript. GPSR conceived and coordinated the project. All authors read and approved the final manuscript.

*Conflict of Interest Statement*

The authors declare no conflicts of interest.

*Reference*

1. Jansen JH, Fibbe WE, Willemze R, Kluin-Nelemans JC (1990) Interleukin-4. A regulatory protein. Blut 60:269–274. https://doi.org/10.1007/BF01736226

2. Chomarat P, Banchereau J (1997) An update on interleukin-4 and its receptor. Eur Cytokine Netw 8:333–344

3. Yoshimoto T, Bendelac A, Watson C, et al (1995) Role of NK1.1+ T cells in a TH2 response and in immunoglobulin E production. Science 270:1845–1847. https://doi.org/10.1126/science.270.5243.1845

4. Seder RA, Paul WE, Dvorak AM, et al (1991) Mouse splenic and bone marrow cell populations that express high-affinity Fc epsilon receptors and produce interleukin 4 are highly enriched in basophils. Proc Natl Acad Sci U S A 88:2835–2839. https://doi.org/10.1073/pnas.88.7.2835

5. Brown MA, Pierce JH, Watson CJ, et al (1987) B cell stimulatory factor-1/interleukin-4 mRNA is expressed by normal and transformed mast cells. Cell 50:809–818. https://doi.org/10.1016/0092-8674(87)90339-4

6. Hassan MT, Tayara H, Chong KT (2023) Meta-IL4: An ensemble learning approach for IL-4-inducing peptide prediction. Methods 217:49–56. https://doi.org/10.1016/j.ymeth.2023.07.002

7. Luzina IG, Keegan AD, Heller NM, et al (2012) Regulation of inflammation by interleukin-4: a review of "alternatives". J Leukoc Biol 92:753–764. https://doi.org/10.1189/jlb.0412214

8. Paul WE (2015) History of interleukin-4. Cytokine 75:3–7. https://doi.org/10.1016/j.cyto.2015.01.038

9. Howard M, Farrar J, Hilfiker M, et al (1982) Identification of a T cell-derived b cell growth factor distinct from interleukin 2. J Exp Med 155:914–923. https://doi.org/10.1084/jem.155.3.914

10. Kelly-Welch AE, Hanson EM, Boothby MR, Keegan AD (2003) Interleukin-4 and interleukin-13 signaling connections maps. Science 300:1527–1528. https://doi.org/10.1126/science.1085458

11.  Rocken M, Racke M, Shevach EM (1996) IL-4-induced immune deviation as antigen-specific therapy

for inflammatory autoimmune disease. Immunol Today 17:225–231. https://doi.org/10.1016/0167-

5699(96)80556-1

12.  Ghoreschi K, Thomas P, Breit S, et al (2003) Interleukin-4 therapy of psoriasis induces Th2 responses

and improves human autoimmune disease. Nat Med 9:40–46. https://doi.org/10.1038/nm804

13.  Lubberts E, Joosten LA, Chabaud M, et al (2000) IL-4 gene therapy for collagen arthritis suppresses

synovial IL-17 and osteoprotegerin ligand and prevents bone erosion. J Clin Invest 105:1697–1710.

https://doi.org/10.1172/JCI7739

14.  Tomer R, Patiyal S, Kaur D, et al (2024) Genome-based solutions for managing mucormycosis. Adv

Protein Chem Struct Biol 139:383—403. https://doi.org/10.1016/bs.apcsb.2023.11.014

15.  Gartner Y, Bitar L, Zipp F, Vogelaar CF (2023) Interleukin-4 as a therapeutic target. Pharmacol Ther

242:108348. https://doi.org/10.1016/j.pharmthera.2023.108348

16.  Dhall A, Patiyal S, Sharma N, et al (2021) Computer-aided prediction and design of IL-6 inducing

peptides: IL-6 plays a crucial role in COVID-19. Brief Bioinform 22:936–945.

https://doi.org/10.1093/bib/bbaa259

17.  Nagpal G, Usmani SS, Dhanda SK, et al (2017) Computer-aided designing of immunosuppressive

peptides based on IL-10 inducing potential. Sci Rep 7:42851. https://doi.org/10.1038/srep42851

18.  Jain S, Dhall A, Patiyal S, Raghava GPS (2022) IL13Pred: A method for predicting immunoregulatory

cytokine IL-13 inducing peptides. Comput Biol Med 143:105297.

https://doi.org/10.1016/j.compbiomed.2022.105297

19.  Gupta S, Mittal P, Madhu MK, Sharma VK (2017) IL17eScan: A Tool for the Identification of Peptides

Inducing IL-17 Response. Front Immunol 8:1430. https://doi.org/10.3389/fimmu.2017.01430

20.  Dhanda SK, Vir P, Raghava GPS (2013) Designing of interferon-gamma inducing MHC class-II

binders. Biol Direct 8:30. https://doi.org/10.1186/1745-6150-8-30

21.  Dhall A, Patiyal S, Choudhury S, et al (2023) TNFepitope: A webserver for the prediction of TNF-alpha

inducing epitopes. Comput Biol Med 160:106929. https://doi.org/10.1016/j.compbiomed.2023.106929

22.  Dhanda SK, Gupta S, Vir P, Raghava GPS (2013) Prediction of IL4 inducing peptides. Clin Dev

Immunol 2013:263952. https://doi.org/10.1155/2013/263952

23.  Liu R, Yan S, Zhang Z, et al (2025) PLM-IL4: Enhancing IL-4-inducing peptide prediction with protein

language model. Comput Biol Chem 118:108448. https://doi.org/10.1016/j.compbiolchem.2025.108448

24.  Ansari HR, Flower DR, Raghava GPS (2010) AntigenDB: an immunoinformatics database of pathogen

antigens. Nucleic Acids Res 38:D847-53. https://doi.org/10.1093/nar/gkp830

25.  Harrison LC, Honeyman MC, Trembleau S, et al (1997) A peptide-binding motif for I-A(g7), the class

II major histocompatibility complex (MHC) molecule of NOD and Biozzi AB/H mice. J Exp Med

185:1013–1021. https://doi.org/10.1084/jem.185.6.1013

26.  Rajapakse M, Schmidt B, Feng L, Brusic V (2007) Predicting peptides binding to MHC class II

molecules using multi- objective evolutionary algorithms. BMC Bioinformatics 8:459.

https://doi.org/10.1186/1471-2105-8-459

27.  Pande A, Patiyal S, Lathwal A, et al (2023) Pfeature: A Tool for Computing Wide Range of Protein

Features and Building Prediction Models. J Comput Biol 30:204–222.

https://doi.org/10.1089/cmb.2022.0241

28.    Altschul SF, Gish W, Miller W, et al (1990) Basic local alignment search tool. J Mol Biol 215:403–410.

https://doi.org/10.1016/S0022-2836(05)80360-2

29.    Sharma N, Patiyal S, Dhall A, et al (2021) AlgPred 2.0: an improved method for predicting allergenic

proteins and mapping of IgE epitopes. Brief Bioinform 22:. https://doi.org/10.1093/bib/bbaa294

30.    Sharma N, Naorem LD, Jain S, Raghava GPS (2022) ToxinPred2: an improved method for predicting

toxicity of proteins. Brief Bioinform 23:. https://doi.org/10.1093/bib/bbac174

31.    Bailey TL, Boden M, Buske FA, et al (2009) MEME SUITE: tools for motif discovery and searching.

Nucleic Acids Res 37:W202-8. https://doi.org/10.1093/nar/gkp335

32.    Bailey TL, Johnson J, Grant CE, Noble WS (2015) The MEME Suite. Nucleic Acids Res 43:W39-49.

https://doi.org/10.1093/nar/gkv416

33.    Vens C, Rosso M-N, Danchin EGJ (2011) Identifying discriminative classification-based motifs in

biological sequences. Bioinformatics 27:1231–1238. https://doi.org/10.1093/bioinformatics/btr110

34.    Tomer R, Patiyal S, Dhall A, Raghava GPS (2023) Prediction of celiac disease associated epitopes and

motifs in a protein   . Front. Immunol.   14

35.    Zhu J, Rosset S, Hastie T, Tibshirani R (2003) 1-norm support vector machines. In: Proceedings of the

17th International Conference on Neural Information Processing Systems. MIT Press, Cambridge, MA,

USA, pp 49–56

36.    Peng H, Long F, Ding C (2005) Feature selection based on mutual information: criteria of max-

dependency, max-relevance, and min-redundancy. IEEE Trans Pattern Anal Mach Intell 27:1226–1238.

https://doi.org/10.1109/TPAMI.2005.159

37.    Whitney AW (1971) A Direct Method of Nonparametric Measurement Selection. IEEE Trans Comput

C–20:1100–1103. https://doi.org/10.1109/T-C.1971.223410

38.    Kiranyaz S, Avci O, Abdeljaber O, et al (2021) 1D convolutional neural networks and applications: A

survey. Mech Syst Signal Process 151:107398.

https://doi.org/https://doi.org/10.1016/j.ymssp.2020.107398

39.    Li Z, Liu F, Yang W, et al (2022) A Survey of Convolutional Neural Networks: Analysis, Applications,

and Prospects. IEEE Trans neural networks Learn Syst 33:6999–7019.

https://doi.org/10.1109/TNNLS.2021.3084827

40.    Arik SÖ, Pfister T (2021) TabNet: Attentive Interpretable Tabular Learning. Proc AAAI Conf Artif

Intell 35:6679–6687. https://doi.org/10.1609/aaai.v35i8.16826

41.    Elnaggar A, Heinzinger M, Dallago C, et al (2021) ProtTrans: Towards Cracking the Language of

Life{\textquoteright}s Code Through Self-Supervised Learning. bioRxiv.

https://doi.org/10.1101/2020.07.12.199554

42.    Kumar N, Patiyal S, Choudhury S, et al (2023) DMPPred: a tool for identification of antigenic regions

responsible for inducing type 1 diabetes mellitus. Brief Bioinform 24:.

https://doi.org/10.1093/bib/bbac525

43.    Kaur H, Raghava GPS (2003) A neural-network based method for prediction of gamma-turns in

proteins from multiple sequence alignment. Protein Sci 12:923–929. https://doi.org/10.1110/ps.0241703

44.    Vacic V, Iakoucheva LM, Radivojac P (2006) Two Sample Logo: a graphical representation of the

717             differences between two sets of sequence alignments. Bioinformatics 22:1536–1537.

718             https://doi.org/10.1093/bioinformatics/btl151

719    45.    Dhall A, Patiyal S, Raghava GPS (2024) A hybrid method for discovering interferon-gamma inducing

720             peptides in human and mouse. Sci Rep 14:26859. https://doi.org/10.1038/s41598-024-77957-8

721    46.    Choi P, Reiser H (1998) IL-4: role in disease and regulation of production. Clin. Exp. Immunol.

722             113:317–319

723    47.    Iwaszko M, Bialy S, Bogunia-Kubik K (2021) Significance of Interleukin (IL)-4 and IL-13 in

724             Inflammatory Arthritis. Cells 10:. https://doi.org/10.3390/cells10113000

728