# Title: Normal Breast Tissue (NBT)-Classifiers: Advancing Compartment Classification in Normal Breast Histology

Siyuan Chen[1†], Mario Parreno-Centeno[1†], Graham Booker[1], Gregory Verghese[1,2,3], Fathima Sumayya Mohamed[1], Salim Arslan[4], Pahini Pandya[4], Aasiyah Oozeer[2,5], Marcello D'Angelo[5], Rachel Barrow[2,6], Rachel Nelan[2,6], Marcelo Sobral-Leite[7], Fabio de Martino[8], Cathrin Brisken[8,9], Matthew J. Smalley[10], Esther H. Lips[7], Cheryl Gillett[2,5], Louise J. Jones[2,6], Christopher R.S. Banerji[1,11,12], Sarah E. Pinder[13], Anita Grigoriadis[1,2,3,*]

**Authors affiliations**

[1] Cancer Bioinformatics, School of Cancer & Pharmaceutical Sciences, Faculty of Life Sciences and Medicine, King's College London, London, UK.

[2] PharosAI, London, UK.

[3] The Breast Cancer Now Research Unit, School of Cancer and Pharmaceutical Sciences, Faculty of Life Sciences and Medicine, King's College London, London, UK.

[4] Panakeia Technologies, London, UK.

[5] King's Health Partners Cancer Biobank, King's College London, London, UK.

[6] Centre for Tumour Biology, Barts Cancer Institute, Queen Mary University of London, London, UK.

[7] Division of Molecular Pathology, Netherlands Cancer Institute, Amsterdam, the Netherlands.

[8] Swiss Institute for Experimental Cancer Research, School of Life Sciences, Ecole Polytechnique Fédérale de Lausanne, Lausanne, Switzerland.

[9] The Breast Cancer Now Toby Robins Research Centre, The Institute of Cancer Research, London, UK.

[10] European Cancer Stem Cell Research Institute, School of Biosciences, Cardiff University, Cardiff, UK.

[11] The Alan Turing Institute, London, UK.

[12] University College London NHS Trust, London, UK.

[13] School of Cancer & Pharmaceutical Sciences, Faculty of Life Sciences and Medicine, King's College London, London, UK.

† These authors contributed equally

* **Corresponding author**

Professor Anita Grigoriadis, Cancer Bioinformatics, School of Cancer and Pharmaceutical

Sciences, Faculty of Life Sciences and Medicine, King's College London, Innovation Hub,

Cancer Centre at Guy's Hospital, London SE1 9RT, UK, (+44) 20 7188 2360,

anita.grigoriadis@kcl.ac.uk

**Keywords:** normal breast tissue, tissue type classification, convolutional neural network (CNN)

**Abstract**

Cancer research emphasises early detection, yet quantitative methods for normal tissue

analysis remain limited. Digitised haematoxylin and eosin (H&E)-stained slides enable

computational histopathology, but artificial intelligence (AI)-based analysis of normal breast

tissue (NBT) in whole slide images (WSIs) remains scarce. We curated 70 WSIs of NBTs from

multiple sources and cohorts with pathologist-guided manual annotations of epithelium, stroma,

and adipocytes (https://github.com/cancerbioinformatics/OASIS). We developed robust

convolutional neural network (CNN)-based, patch-level classification models, named *NBT-*

*Classifiers*, to tessellate and classify NBTs at different scales. Across three external cohorts,

*NBT-Classifiers* trained on 128 x 128 µm and 256 x 256 µm patches achieved AUCs of

0.98–1.00. The model learned independent normal features different from those of

precancerous and cancerous epithelium, which were further visualised using two explainable AI

techniques. When integrated into an end-to-end preprocessing pipeline, *NBT-Classifiers*

facilitate efficient downstream analysis within peri-lobular regions. *NBT-Classifiers* provide

robust compartment-specific analytical tools and enhance our understanding of NBT

appearances, which serve as valuable reference points for identifying premalignant changes

and guiding early breast cancer prevention strategies.

**Introduction**

Normal breast tissue (NBT) research is gaining momentum for the early detection of breast

cancer[1]. The epithelium, organised into ducts and lobules, also referred to as terminal duct-

lobular units (TDLUs), is of primary importance, as these structures are where most

physiological processes and pathological alterations occur[2]. Apart from the epithelium, recent

evidence suggests that the stroma, particularly the peri-lobular stroma, may also harbour

precursor alterations and have a crucial role in breast cancer progression[3-6]. Therefore, in-depth

histopathological research into these structures, especially in women with varying breast cancer

risk, holds promise for detecting early signs of cancer initiation in breast tissues that appear

"normal". This is particularly significant for women at higher breast cancer risk, such as germline

*BRCA1/2* mutation (*gBRCA1/2m*) carriers[7].

Histopathology remains the gold standard for diagnosing cancer, relying on microscopic

examination to detect tissue abnormalities. In routine practice, pathologists first survey the

entire tissue section on a glass slide before focusing on pathological regions at higher

magnification for more detailed assessment. Whole slide images (WSIs) enable the hierarchical

storage of microscopic histological images scanned at multiple magnifications[8]. Their ease of

management and ability to facilitate rapid sharing have led to their growing integration into

clinical workflows[9], as well as driving advancements in digital image analysis using platforms

such as QuPath[10]. This shift has led to the recent growth of computational pathology (CPath), a

rapidly evolving field that leverages artificial intelligence (AI) and deep learning, particularly

convolutional neural networks (CNNs) and the latest vision transformer (ViT)-based foundation

models[11], for high-throughput analysis of large-scale WSI datasets[12-14].

Automatically classifying tissue and decomposing individual tissue compartments into smaller

pieces, namely patches, are crucial WSI pre-processing steps. Numerous CNN-based models

have been developed for breast cancer[15], including approaches that classify tissue

compartments within normal tissues adjacent to tumours, such as HistoROI[16]. In contrast, few

studies have specifically focused on normal breast tissues in those individuals without

malignancy, with prior efforts primarily aimed at detecting and quantifying lobules[17-22] or

assessing overall tissue composition[23,24]. Nonetheless, none of these approaches has been

specifically designed to provide patch-level tissue classifications on digitised WSIs of NBTs.

Moreover, all these studies typically relied on a single source of NBTs, which may limit the

generalisability of the resulting models[25]. Specifically, NBTs are heavily underrepresented in

large annotated WSI databases. A recent literature review[26] summarised publicly available

breast haematoxylin and eosin (H&E) WSI datasets from 2015 to 2023, identifying 17 datasets

comprising a total of 10,385 breast H&E WSIs. Of these, only two contain NBTs (350 female

normal breast WSIs), and just one (44 WSIs) includes manual annotations. Thus, there is a

clear need for a universal patch-level classification model for NBTs, developed on a curated

dataset that captures real-world variability and is supported by ground-truth manual annotations.

We present CNN-based *NBT-Classifiers* to classify patches of epithelium, stroma and

adipocytes at two different scales. We provide pathologist-guided manually annotated NBTs on

digitised WSIs, sourced from five cohorts, including NBTs from healthy women without high-risk

germline mutations who underwent reduction surgery or core biopsy, *gBRCA1/2m* carriers who

underwent a risk-reducing mastectomy, as well as contralateral and ipsilateral NBTs from breast

cancer patients. *NBT-Classifiers* achieved robust performance across three external cohorts by

leveraging normal-specific features, which were further validated by explainable AI-based

approaches[27,28]. Additionally, an end-to-end framework was integrated, outputting pseudo

patch-level annotations of target regions, including lobules and their microenvironment.

Collectively, *NBT-Classifiers* provide a primary tool for studying different tissue compartments at

sub-tissue level on large-scale digitised images in the context of normal breast tissue.

## Results

### Optimisation of *NBT-Classifiers*

In practice, pixel-level annotated digitised histological image datasets of NBTs are scarce[26].

Furthermore, the biological heterogeneity of NBTs from diverse sources is often overlooked

when assembling such datasets. To address this, we collected in total 70 digitised formalin-fixed,

paraffin-embedded (FFPE), H&E-stained images (n=70 patients) of NBTs from various sources,

including core biopsies of healthy donors (non-*gBRCA1/2m* carriers, n=12 WSIs), women

undergoing reduction mammoplasties (non-*gBRCA1/2m* carriers, n=30 WSIs), *gBRCA1/2m*

carriers undergoing risk-reducing mastectomy (n=21 WSIs), and contralateral or ipsilateral

normal tissues from breast cancer patients (n=7 WSIs) (**Fig. 1a**, **Supplementary Table 1**,

**Methods**). These NBT WSIs were sourced from five distinct patient cohorts: the King's Health

Partners Cancer Biobank (KHP) in London (UK), the Netherlands Cancer Institute (NKI) in

Amsterdam (Netherlands), the Barts Cancer Institute (BCI) in London (UK), the École

Polytechnique Fédérale de Lausanne (EPFL) in Lausanne (Switzerland), and the publicly

available Susan G. Komen Tissue Bank (SGK)[29] (**Fig. 1b**). Patient age ranged from 16 to 74

years. Collectively, these digitised images capture both technical variability (differences in H&E-

staining and scanning) and biological diversity (variations in tissue sources and a broad patient

age range) within NBTs. Due to their greater data diversity, WSIs from the NKI and BCI cohorts

were used for model training and optimisation, while WSIs from the KHP, EPFL, and SGK

cohorts were held out for external validation. Expert manual annotations of epithelium, stroma,

and adipocytes were performed under the supervision of a consultant pathologist (SEP) using

QuPath v0.3.0 (**Fig. 1c**, **1d**, **Supplementary Fig. 1**, **Methods**). The pathology-guided annotated

WSIs of NBTs are available in the nOrmal breASt tISsue Dataset (OASIS) repository,

accessible at https://github.com/cancerbioinformatics/OASIS.

NBTs inherently exhibit a hierarchical organisation. Within the epithelium, structures ranging

from individual epithelial cells, through to larger islands of acini, and then lobules, can be

captured at fields of view (FOVs) of 64 × 64 µm, 128 × 128 µm, and 256 × 256 µm

(**Supplementary Fig. 2**). Therefore, we aimed to train models enabling tissue classification at

different scales to offer greater analytical flexibility for downstream analysis. To train these

models, we generated patch-level datasets using QuPath v0.3.0 for the NKI and BCI cohorts.

These datasets consisted of non-overlapping patches with sizes of 224 × 224, 512 × 512, and

1024 × 1024 pixels, all extracted at a resolution of 0.25 µm/pixel (**Supplementary Table 2**,

**Methods**).

In the training pipeline (**Fig. 1c**), patches were subjected to stain normalisation to minimise

cohort variability (**Supplementary Fig. 3**, **Methods**). The model employs a pre-trained CNN

backbone for feature extraction, with a trainable classification head that predicts the probabilities

of epithelium, stroma, and adipocytes (**Supplementary Fig. 4**, **Methods**). Given the critical role

of stain normalisation[30] and the selection of CNN backbone[31], we initially performed three-fold

cross-validation experiments to optimise these parameters (**Methods**). The stain normalisation

methods evaluated included Reinhard[32], Vahadane[33], Macenko[34], and StainGAN[35]

(**Supplementary Fig. 5**, **Methods**). For the CNN backbones, we tested MobileNet[36],

ResNet50[37], DenseNet[38], and InceptionV3[39], using weights pre-trained on ImageNet[40]. These

experiments were conducted using patch-level datasets containing non-overlapping 512 × 512-

pixel patches from the NKI and BCI cohorts, with patches sampled in a class-balanced manner

to ensure equal representation of tissue types (**Supplementary Fig. 6-7**, **Methods**). The
combination of Reinhard stain normalisation and the MobileNet backbone yielded the best
overall performance (**Fig. 1e**, **Supplementary Table 3**).

Configured with Reinhard stain normalisation and the MobileNet backbone, we trained models
using class-balanced, non-overlapping patches of 224 × 224, 512 × 512, and 1024 × 1024
pixels from the NKI and BCI cohorts (**Supplementary Fig. 6-7**, **Methods**). The models trained
on larger FOVs generally achieved higher accuracies (**Fig. 1f**, **Supplementary Table 3**), while
the 224 × 224-pixel model exhibited the lowest accuracy and was more prone to misclassifying
epithelium (**Supplementary Fig. 8**). Due to the suboptimal performance of the 224 × 224-pixel
model, we proceeded to retrain two final versions of the *NBT-Classifier*: one using 512 × 512-
pixel patches and the other using 1024 × 1024-pixel patches.

***NBT-Classifiers* demonstrate strong generalisability underpinned by interpretable tissue**
**representations**

We then evaluated the optimised *NBT-Classifiers* on the external KHP, EPFL, and SGK cohorts
using receiver operating characteristic (ROC) analysis (**Methods**). The class-specific area
under the curve (AUC) values were 0.98 for epithelium, 0.98 for stroma, and 1.00 for adipocytes
across all cohorts (**Fig. 2a**), with cohort-specific AUCs showing some variation (**Supplementary**
**Fig. 9**). The 1024px-based *NBT-Classifier* achieved similarly robust class-specific AUCs of 0.99
for epithelium, 0.98 for stroma, and 1.00 for adipocytes (**Fig. 2b**), with slight variations across
cohort-specific AUCs (**Supplementary Fig. 10**). For both 512px- and 1024px-based *NBT-*
*Classifiers*, we observed no bias in the accuracy concerning patient age in external cohorts or
source of the NBT (**Supplementary Fig. 11**, **Methods**).

To dissect the underlying learned representations, we first visualised the feature representations
from the last hidden layer of both models using t-distributed Stochastic Neighbour Embedding
(t-SNE)[41] (**Methods**). Patches predicted as epithelium, stroma, and adipocytes formed well-
separated visual clusters (**Fig. 2c, Supplementary Fig. 12a**) that closely mirrored their
respective histology (**Fig. 2d**, **Supplementary Fig. 12b**, **Methods**). We then examined the
specific histological patterns driving class-specific predictions using class activation mapping
(CAM)[27] and gradient-weighted class activation mapping (Grad-CAM)[28] (**Supplementary Fig.**

**13**, **Methods**). Both methods consistently highlighted biologically meaningful regions—epithelial

cellular contents, collagen fibres, and adipocyte membranes—corresponding to the three tissue

classes (**Fig. 2e**, **Supplementary Fig. 14a**, **14b**). When applied to a larger, representative

region (5120 × 5120 pixels, 0.25 µm/pixel) encompassing all three tissue compartments, these

characteristic patterns were coherently captured across non-overlapping patches, preserving

spatial continuity (**Fig. 2f**). Notably, these patterns were reproducible across all cohorts

(**Supplementary Fig. 15a**), including images scanned at 20x magnification from the SGK cohort

(**Supplementary Fig. 15b**). When comparing the predictions with ground-truth annotations,

most misclassifications occurred at the boundaries between class-specific visual clusters where

histological features are less distinct (**Supplementary Fig. 12c**, **Supplementary Fig. 16a**).

Correspondingly, the confidence of model's predictions, approximated by the probability

associated with the predicted tissue class, was notably lower at these boundaries

(**Supplementary Fig. 16b**). We then applied CAM and Grad-CAM to assess patches with low-

confidence predictions. The resulting heatmaps for all three tissue classes showed that the

model's attention was proportionally distributed across mixed tissue regions (**Supplementary**

**Fig. 17**). This suggests that the misclassifications are not due to a bias in the model's innate

judgement, but rather to ambiguity in the testing patches where tissue classes are less clearly

defined. Together, these analyses demonstrate the strong generalisability of the *NBT-Classifiers*,

underpinned by interpretable and biologically grounded representations of normal breast tissue

architecture.

**Training exclusively on normal tissue enables learning of distinctive features in the**

**normal breast**

Because there are no CNN models trained exclusively on normal breast tissue, we

benchmarked the 1024px-based *NBT-Classifier* against HistoROI[16], a ResNet18-based[37] model

trained on mixed breast tissue WSIs, ranging from histologically normal, noncancerous,

precancerous, to cancerous tissues[42,43], to classify epithelium, stroma, adipocytes, along with

lymphocytes, miscellaneous tissues, and artefacts (**Methods**). HistoROI demonstrated

comparable AUCs for epithelium (0.99 vs 0.99), while performance was lower for stroma (0.97

vs 0.98) and adipocytes (0.95 vs 1.00) (**Fig. 3a**, DeLong's test, P<0.0001, **Methods**). This

performance gap was more pronounced in accuracy metrics: HistoROI achieved 80%, 91%, and

72% for epithelium, stroma, and adipocytes, respectively, lower than the 87%, 94%, and 96%

attained by the *NBT-Classifier* (**Supplementary Fig. 18**).

The fundamental difference between the 1024px-based *NBT-Classifier* and HistoROI lies in

their training datasets: HistoROI was developed using mixed breast tissues, while *NBT-*

*Classifiers* were trained exclusively on normal breast tissue. This raised the question: could

*NBT-Classifiers* capture unique architectural features of normal breast tissue, distinguishing it

from abnormal tissues? To test this hypothesis, we curated a patch dataset using the same

dataset employed to develop the HistoROI model[16,42,43] (**Methods**). In total, 56,000 1024 ×

1024-pixel patches were extracted at 40x magnification for evaluation of both the *NBT-Classifier*

and HistoROI. The dataset comprised 8,000 patches per class across the following categories:

normal (peri-tumoral, N), benign (pathological benign, PB; usual ductal hyperplasia, UDH),

precancerous (flat epithelial atypia, FEA; atypical ductal hyperplasia, ADH), and cancerous

(ductal carcinoma in situ, DCIS; invasive carcinoma, IC). Of these, 96.14% were predicted as

epithelium by the *NBT-Classifier*, indicating good generalisability on external datasets. Notably,

the epithelium probability distributions were shifted for normal breast tissue compared with

pathological categories. In contrast, the mixed-tissue-based HistoROI exhibited substantial

overlap between the two classes (**Fig. 3b**). ROC analysis further demonstrates that the *NBT-*

*Classifier* outperforms HistoROI in discriminating normal breast epithelium from abnormal tissue

(**Fig. 3c**, DeLong's test, $P < 0.0001$). Importantly, differences between normal and

precancerous or cancerous epithelium were consistently better captured by the *NBT-Classifier*

(**Fig. 3d**). When applying Grad-CAM to patches of normal epithelium, we observed differences

in the resolution and granularity of attention due to the distinct CNN architectures used

(MobileNet[44] for *NBT-Classifiers* and ResNet18[37] for HistoROI). Beyond these architectural

differences, HistoROI showed limited recognition of entire normal lobules, with attention

misaligned and incomplete, whereas the normal-specific *NBT-Classifier* provided more

comprehensive and well-aligned coverage of normal epithelium (**Fig. 3e**). Together, these

findings suggest that the *NBT-Classifier* captures normal-specific features, in contrast to the

more general epithelial features learned by models trained on mixed-breast-tissue datasets.

**Slide-level tissue compartment classification and visualisation**

*NBT-Classifiers* are patch-level tissue classification models that, once trained on annotated

patches, can be applied to entire WSIs. To demonstrate this, we performed whole-slide tissue

classification on a representative WSI using both the 512px- and 1024px-based *NBT-Classifiers*.

The results were then converted and imported into QuPath v0.3.0 for interactive histological

inspection (**Fig. 4a**, **4b**, **Methods**). Heatmaps generated by both models showed strong

alignment between predicted tissue classes and the underlying histology at different scales. For

a larger tissue region (5120 × 5120 pixels, 0.25 µm/pixel), we created a smoother heatmap by

using predicted tissue class probabilities (**Methods**). This high-resolution heatmap effectively

delineated individual lobules and segmented tissue compartments with smooth transitions (**Fig.**

**4c**). Additionally, we analysed six other regions from tissue across different patient age groups,

all of which demonstrated similarly strong performance (**Supplementary Fig. 19**). These results

highlight the potential of this approach as a foundation for more advanced downstream image

analyses, such as lobule detection.

Among all patches used for external validation, 98.2% had probabilities greater than 0.7, and 84%

had probabilities greater than 0.99 (**Fig. 4d**). We then examined the spatial distribution of

patches predicted with varying confidence in the same WSI example. Patches with confidence

above 0.7 covered most tissue regions, while those with scores above 0.99 covered only partial

regions, with gaps primarily at the boundaries between tissue compartments and within large

lobules (**Fig. 4e**). These low-confidence patches in large lobules may explain the reduced

accuracy of the 224px-based *NBT-Classifier*, as the smaller patch size tends to capture more

intra-lobular stroma, leading to a higher rate of misclassification of epithelium as stroma.

Furthermore, the varying spatial localisation of model confidence could serve as a valuable

metric for capturing spatial and histological variations within each tissue compartment, making it

particularly useful for patch selection in slide-level analysis, such as multiple-instance learning

(MIL)[16,45].

**End-to-end pipeline for analysing large-scale WSIs of NBT**

Building on the demonstrated utility of the proposed *NBT-Classifiers*, we integrated the models

into an end-to-end WSI pre-processing pipeline (**Fig. 5a**). This generates tissue classification

results that facilitate large-scale digital image analysis within target sub-tissue regions in the

normal breast, such as lobules and their microenvironment, and supports the patch selection

process for more advanced deep learning frameworks, such as MIL[16,45]. The pipeline begins

with HistoQC[46] to detect foreground tissue regions (**Supplementary Fig. 20**, **Methods**). Once

identified, the region is tessellated into non-overlapping patches, which are then analysed by the

corresponding *NBT-Classifier* to predict tissue classes. This produces a whole slide tissue class

heatmap, from which lobules and their peri-lobular regions within a specified range can be

detected and localised (**Fig. 5b**, **Methods**). For frameworks such as MIL[16,45], patches from

target tissue regions can be selectively balanced and treated as a hyperparameter to optimise

performance during training (**Fig. 5a**). Besides, the pipeline outputs a binary mask that localises

individual lobules on each WSI and can be directly imported into QuPath v0.3.0 as pseudo

lobule annotations (**Fig. 5c**). Within each lobule, QuPath v0.3.0's built-in nuclei detection and

advanced spatial analysis tools, such as Delaunay triangulation, can be utilised for object-level

lobule quantification. Additionally, the original patch-level classifications of the target regions

(lobules and peri-lobular areas) can be exported and loaded into QuPath v0.3.0 where digital

image analyses, such as texture analysis can be performed, across the slide at the patch level

(**Fig. 5d**). These approaches build upon the previous efforts of standardised quantifications of

TDLUs[17-21], aiming at expanding interpretation of lobules as well as their direct

microenvironment, which might unlock novel biomarkers that are indicative of breast cancer

precursors. The pipeline performed robustly across WSIs with varying staining at both 40x and

20x magnification (**Supplementary Fig. 21**), offering flexibility for studies involving

heterogeneous datasets. The source code running this pipeline is available at:

https://github.com/cancerbioinformatics/NBT-Classifier and

https://hub.docker.com/repository/docker/siyuan726/nbtclassifier.

## Discussion

AI-driven WSI analysis has given rise to groundbreaking advancements in histopathology[13]. In

breast research, while the research frontier remains largely focused on breast cancer,

histologically normal tissues are significantly underrepresented among millions of digitised WSIs,

with few applications specifically designed for facilitating in-depth morphological characterisation

of NBTs[17-24]. To address this gap, we compiled high-quality, manually annotated WSIs of NBTs,

sourced from women with varying breast cancer risk across multiple institutions. Through

extensive optimisation and external validation, we developed robust *NBT-Classifiers* capable of

processing WSIs at different scales and performing patch-level tissue classification of epithelium,

stroma, and adipocytes. To the best of our knowledge, *NBT-Classifiers* represent the first deep

learning-based CPath models specifically trained to classify tissue compartments within normal

breast tissue (from individuals without any lesions).  Building on this, we integrated an end-to-

end WSI pre-processing pipeline to ensure objective and reproducible tessellation and patch

selection from biologically important regions, such as lobules and their microenvironment. The

outputs are compatible with QuPath v0.3.0, one of the most widely used digital image analysis

platforms and can be seamlessly integrated with deep learning-based CPath frameworks such

as MIL[16,45]. Our models (https://github.com/cancerbioinformatics/NBT-Classifier and

https://hub.docker.com/repository/docker/siyuan726/nbtclassifier) and datasets

(https://github.com/cancerbioinformatics/OASIS) are publicly available, whereby the latter will be

a highly valuable resource for training pathology foundation models as they provide rich

histology data of normal breast.

To establish fundamental tissue classification tools for NBTs, particularly as a primary step for

downstream analyses, ensuring generalisability, robustness, and adaptability is essential.

Achieving this requires a diverse and representative WSI dataset, ground-truth manual

annotations, and seamless compatibility with downstream analytical frameworks. Previous NBT

studies have typically relied on a single data source, such as benign breast biopsies[17-19,23],

healthy donors[20,22], or reduction mammoplasties[21]. Only one exception[24] incorporated NBTs

from both risk-reducing mastectomy and reduction mammoplasty specimens (*gBRCA1/2m*

status unknown). However, these datasets do not capture the diverse origins of NBTs, which

may exhibit varying predispositions to cancer initiation and distinct histological manifestations. In

contrast, a key strength of our work is the incorporation of a broad spectrum of NBT variations,

including differences in patient age, breast cancer risk, H&E staining protocols, and scanning

platforms.

In the generation of AI, manual annotations should not be overlooked when developing

supervised applications, especially in highly expert histopathological domains[47]. Our fully

pathologist-supervised ground-truth likely explains the slightly better performance in stroma and

adipocytes classification compared to HistoROI[16], which employed human-in-the-loop

annotations. Among the previous NBT research, three studies provide manual annotations, yet

their sample sizes and annotation levels vary (**Supplementary Table 4**). We expanded on this

by providing detailed annotation of lobules, stroma and adipocytes that displayed biological

variations. Moreover, we demonstrated that *NBT-Classifiers*, trained exclusively on histologically

normal breast tissue, learn distinctive, normal-specific features. Their outputs reflect the degree

of similarity to truly normal epithelium, whereas models trained on mixed breast tissues capture

more general epithelium features. The comparable performance observed in the mix-breast-

tissue model might largely arise from the relative similarity of epithelium to other tissue

compartments, making the prediction effectively an approximation rather than a normal-specific

assessment. This distinction is critical, as a classifier that is grounded in the unique

characteristics of normal breast tissue offers a more robust foundation for future applications in

early detection, positioning it as a screening tool for identifying pathological deviations in

gigapixel WSIs of histologically normal breast tissue.

Performing patch-level analysis within key regions of NBTs, such as lobules and their

microenvironment, is essential for detecting early cancer precursors. Prior NBT studies have

focused on well-established cancer risk biomarkers, such as TDLU involution[17-20], immune

infiltration in lobular regions[21], alterations in tissue composition[22,23], and fibroglandular density[24].

In addition to these visible pathological biomarkers, recent studies have highlighted greater

predictive potential within NBTs at the single-cell level[48-51]. Given the extensive validation of

genotype-phenotype links in various CPath studies focused on cancer[52-54], analysing sub-tissue

regions at the cellular and sub-cellular level shows significant promise for NBTs as well. In this

context, the ability to adapt to broader downstream pathomics feature extraction tools, such as

QuPath-based digital image analysis, or deep learning-driven CPath frameworks, opens new

opportunities for evaluating high-throughput histopathological measurements. This, in turn,

provides insights into localised histological markers that may signal the earliest stages of breast

cancer initiation. Building upon this, advanced techniques such as spatial transcriptomics[55] and

spatial proteomics[56] could uncover the underlying molecular mechanisms driving these

histological changes. By linking molecular data with histological features, a deeper

understanding of how early molecular alterations contribute to the development of breast cancer

can be achieved.

One limitation of this study is the diversity of the external validation cohorts, which may not fully

capture the spectrum of variations in NBTs, such as contralateral tissues or those from risk-

reducing mastectomies. Future work will systematically evaluate the model's performance

particularly across diverse demographic groups and healthcare settings, with a specific focus on

ensuring equitable generalisability in underrepresented populations. Another limitation lies in the

annotation scope, which included only subsets of tissue types. Consequently, regions like

artefacts, necrosis and blood vessels were misclassified as epithelium when applying the *NBT-*

*Classifiers* to whole WSIs. Including these regions as additional classes could improve

classification accuracy. While expert annotation remains essential due to the histological

complexity of NBTs, strategies to improve efficiency, such as AI-powered annotation platforms

or carefully guided crowdsourcing approaches[47], could help scale the process. Biological assays

or molecular markers[21] could further support the generation of more precise, cell-level ground-

truth annotations. In addition, ViT-based foundation models were not evaluated, as the near-

perfect AUCs achieved suggest that the semantic distinctions between epithelium, stroma, and

adipocytes were sufficiently pronounced for capture by conventional CNNs. Additionally, while

ViTs excel at capturing global context, their patch-based architecture and multi-head attention

often produce coarse or fragmented saliency maps, limiting interpretability at the cellular and

sub-tissue level[57,58]. In contrast, CNNs, with their locality and translation-invariance biases,

generate more granular and biologically intuitive explanations that align with pathologists'

reasoning[59]. Thus, although CNNs may lack some global context, their explainability was critical

for our goal of visualising distinct, plausible patterns in normal breast tissue. Future work could

explore whether transformer-based backbones provide additional performance gains or improve

generalisability. Lastly, due to out-of-distribution effects between training and testing data,

domain shift was observed in features extracted from both *NBT-Classifiers*, as well as HistoROI

(**Supplementary Fig. 22**), suggesting stain normalisation cannot fully address the variations in

data distributions across cohorts. Recent studies indicate that even foundation models[60,61]

trained on large and diverse datasets do not always avoid domain shift[62,63]. In future work,

domain generalisation techniques could be applied to improve the models, enabling them to

learn domain-invariant features and reduce cohort-specific biases[30,64].

In summary, we present deep learning-based *NBT-Classifiers* for patch-level tissue type

classification in NBTs. These have the potential to enhance our understanding of how various

NBT components contribute to both benign and malignant breast pathology and lay the

groundwork for the development of more advanced deep learning models and spatial-defined

molecular large-scale analyses in the future.

**Methods**

**Patient cohorts**

In this study, NBTs were obtained from the following sources: core biopsies of healthy donors
(non-*gBRCA1/2m* carriers, n=12 WSIs); women undergoing reduction mammoplasties (non-
*gBRCA1/2m* carriers, n=30 WSIs); *gBRCA1/2m* carriers undergoing risk-reducing mastectomy
(n=21 WSIs); and contralateral or ipsilateral normal tissues from breast cancer patients (n=7
WSIs). A total of 70 digitised formalin-fixed, paraffin-embedded (FFPE), haematoxylin and eosin
(H&E)-stained WSI were collected across five cohorts: the King's Health Partners Cancer
Biobank (KHP) in London (UK) (n=16 WSIs), the Netherlands Cancer Institute (NKI) in
Amsterdam (Netherlands) (n=16 WSIs), the Barts Cancer Institute (BCI) in London (UK) (n=16
WSIs), the École Polytechnique Fédérale de Lausanne (EPFL) in Lausanne (Switzerland) (n=10
WSIs), and the public Susan G. Komen Tissue Bank (SGK) (n=12 WSIs)[29]. Patient age ranged
from 16 to 74 years. WSIs from the KHP, BCI, and EPFL cohorts were scanned on Hamamatsu
NanoZoomer scanners whilst WSIs from the NKI cohort were scanned on MIRAX scanners, all
at 40x magnification (0.25 µm/pixel). WSIs from the SGK cohort were downloaded from the
virtual tissue bank (https://virtualtissuebank.iu.edu/query/), having been scanned at 20x
magnification[29].

To develop *NBT-Classifiers*, we used the NKI and BCI cohorts. These included samples of
NBTs from reduction mammoplasties (n=4 patients, non-*gBRCA1/2m* carriers), risk-reducing
mastectomies in *gBRCA1/2m* mutation carriers (n=21 patients, no cancer at surgery), and
contralateral or ipsilateral NBTs from breast cancer patients (n=7 patients). The remaining WSIs
from the KHP, EPFL and SGK cohorts were used for external validation. These included NBTs
from reduction mammoplasties (n=26 patients, non-*gBRCA1/2m* carriers) and core biopsies
from healthy donors (n=12 patients, non-*gBRCA1/2m* carriers). Detailed information on
individual slides can be found in **Supplementary Table 1** and is available at the OASIS
repository (https://github.com/cancerbioinformatics/OASIS).

**Manual annotation**

Expert manual annotations of epithelium, stroma, and adipocytes were performed for each WSI
under the supervision of a consultant pathologist (SEP) using QuPath v0.3.0[10]. To improve the

efficiency of the annotation process, we adopted a hybrid strategy: lobular boundaries were
precisely delineated to annotate epithelium, while stroma and adipocytes were annotated using
rectangular boxes of comparable size, randomly sampled from various regions throughout the
NBT, to ensure a balanced representation of tissue classes during training (**Fig. 1c**, **1d**,
**Supplementary Fig. 1**). The pathology-guided annotated WSIs of NBTs are available in the
nOrmal     breASt     tISsue     Dataset     (OASIS)     repository,     accessible     at
https://github.com/cancerbioinformatics/OASIS.

### Patch-level datasets for training

To train models classifying NBTs at different scales, we used QuPath v0.3.0 to extract labelled
patches from the NKI and BCI cohorts. These datasets consisted of non-overlapping patches
with sizes of 224 × 224, 512 × 512, and 1024 × 1024 pixels, all extracted at a resolution of 0.25
µm/pixel (**Supplementary Table 2**). Only patches with their centres located within the
annotated regions were extracted and inherited the labels from the pixel-level manual
annotations. The patch extraction was performed using Groovy scripts in QuPath v0.3.0. The
script     is     available     at:     https://github.com/cancerbioinformatics/NBT-
Classifier/blob/main/patching_qupath.groovy.
448

### Stain normalisation

450   In experiments optimising the stain normalisation method, we used the same reference image
451   when implementing the Reinhard, Macenko, and Vahadane method, which is available at:
452   https://github.com/cancerbioinformatics/NBT-Classifier/blob/main/data/he.jpg.

### Architecture of *NBT-Classifiers*

The *NBT-Classifiers* leverage transfer learning, each employing a pre-trained CNN backbone to
extract visual features from image patches, followed by a trainable classification head for tissue
class prediction (**Supplementary Fig. 4**). Specifically, the feature maps from the last
convolutional layer of each CNN backbone were transformed into a single-dimensional vector
using a global average pooling layer. The reduced visual features serve as input to the

subsequent classification module, which consists of two densely connected layers. The first

dense layer linearly transforms the input features into a 1024-dimensional representation,

followed by a second dense layer that reduces it to 512 dimensions, both employing the "ReLU"

activation function. To mitigate overfitting, a Dropout layer with a rate of 50% is applied between

these layers. The final output layer maps the 512-dimensional representation to a 3-dimensional

feature, using a "Softmax" activation function to predict the probability distribution across the

three tissue classes. The class with the highest probability is assigned as the predicted tissue

class (0: epithelium, 1: stroma, 2: adipocytes).

### 469　Three-fold cross-validation

*NBT-Classifiers* were trained and optimised through three-fold cross-validation. To ensure

methodological consistency and fair comparison across experiments, a single fixed partition of

the data was applied throughout all analyses. In each fold, patches were split at the WSI level:

20 WSIs for training (10 from each cohort), 4 WSIs for internal validation (2 from each cohort),

and 8 WSIs for internal testing (4 from each cohort).

For experiments optimising the stain normalisation method and CNN backbone, patch-level

datasets containing non-overlapping 512 × 512-pixel patches from the NKI and BCI cohorts

were used. To ensure class balance, 250 patches per tissue class were randomly sampled from

each WSI. For experiments optimising *NBT-Classifiers* on patches of different FOVs, non-

overlapping patches of 224 × 224, 512 × 512, and 1024 × 1024 pixels from the NKI and BCI

cohorts were used. To ensure class balance, 150 patches per tissue class were randomly

sampled from each WSI (**Supplementary Fig. 6-7**, **Supplementary Table 2**).

For training patches, six data augmentation techniques were employed, including horizontal

flipping, random rotation within the range of -40 degrees to 40 degrees, random shifts, random

shear transformations, random zoom in/out, and random shifts of the channel values within the

range of [0, 10], to enhance model's robustness and regularise the algorithm. The weights of the

CNN backbones were all frozen, and the densely connected layers in the classification head

were initialised by the Xavier normal initializer and set to be trainable. We used categorical

cross-entropy as the loss function and Adam optimizer with a learning rate of 1e-5. The batch

size was 16 and we trained each model for 50 epochs. The best model was selected according

to the highest validation accuracy, reflecting the overall multi-class classification performance,

and was then saved for further testing.

**External validation**

For cohorts used for external validation (KHP, EPFL and SGK), we extracted non-overlapping

patches with a size of 512 × 512 and 1024 × 1024 pixels at a resolution of 0.25 µm/pixel for the

KHP and EPFL cohorts. For the SGK cohort, scanned at 20x magnification, we extracted non-

overlapping patches with a size of 256 × 256 and 512 × 512 pixels at a resolution of 0.5

µm/pixel (**Supplementary Table 2)**. All patches were normalised using the Reinhard method

and patches from SGK were resized to match the dimension of the corresponding *NBT-*

*Classifier*. For each patch, each *NBT-Classifier* outputs probabilities of epithelium, stroma and

adipocytes and the tissue class with the highest predicted probability was assigned as the final

class prediction. The primary statistical endpoint was the area under the receiver operating

characteristic curve (AUROC). The secondary statistical endpoint was class-specific accuracy.

Accuracy was determined by comparing the ground-truth labels with the class assigned the

highest predicted probability. We report both the overall accuracy as well as individual

accuracies in each KHP, EPFL and SGK cohort.

**Confounder analysis**

We evaluated whether the *NBT-Classifiers* exhibited any bias towards potential confounders

such as patient age and the source of NBTs. For a fair comparison, we sampled 15 patients

from a total of 38 patients across three external cohorts, ensuring balanced representation

across three age groups, namely "premenopausal years" <45 years: 5 patients; "menopausal

years" 45–55 years: 5 patients; "postmenopausal years" >55 years: 5 patients. We sampled 30

patients from a total of 32 patients across NKI and BCI cohorts to include equal representation

across three NBT sources: reduction mammoplasty (10 patients), risk-reducing mastectomy (10

patients), and NBTs from breast cancer patients (10 patients). To mitigate class imbalance, 500

patches per tissue class per WSI were randomly sampled when using the 512px-based model

and 250 patches per class per WSI were sampled when using the 1024px-based model. These

experiments were repeated three times.

**Implementation of HistoROI**

HistoROI[16] is a CNN-based tissue classification model trained on WSIs of histologically normal,
noncancerous, precancerous, and cancerous breast tissue from the public BReAst Carcinoma
Subtyping (BRACS) dataset (https://research.ibm.com/haifa/Workshops/BRIGHT/,
https://www.bracs.icar.cnr.it/)[42,43]. The model classifies epithelium, stroma, and adipocytes,
along with lymphocytes, miscellaneous tissues, and artefacts. It processes 256 × 256-pixel
patches at a resolution of 1 µm/pixel, capturing the same field of view (FOV) as 1024 × 1024-
pixel patches at 0.25 µm/pixel. To ensure a fair comparison, we resized the 1024 × 1024-pixel
patches extracted from WSIs in three external cohorts and applied Reinhard stain normalisation
before using them with HistoROI[16].

**Analysis of epithelium patches from BReAst Carcinoma Subtyping (BRACS) database**
**and analysis**

To evaluate the ability of *NBT-Classifier* and HistoROI to discriminate between histologically
normal, precancerous, and cancerous epithelium, we systematically curated a patch dataset
from the public BRACS database[42,43] that was used to develop the HistoROI model. Specifically,
region of interest (ROI) images (scanned at 40x, available at: https://www.bracs.icar.cnr.it/)
encompassing peri-tumoral normal breast tissue (N), atypical ductal hyperplasia (ADH), ductal
carcinoma in situ (DCIS), and invasive carcinoma (IC) were tessellated into patches compatible
with both models. We then randomly sampled 8,000 patches per class and applied both
classifiers to obtain epithelium probabilities and feature representations. The distributional
differences in epithelium probabilities between the normal class (N) and each pathological class
(ADH, DCIS, IC) were assessed using the Wilcoxon rank-sum test, followed by Bonferroni
correction for multiple comparisons. The code is available at:
https://github.com/cancerbioinformatics/NBT-
Classifier/blob/main/notebooks/BRACS_analyses.ipynb.

**Visual assessment of feature representations**

We performed t-distributed Stochastic Neighbour Embedding (t-SNE)[41] to visualise the output of
features from the layer before the final output layer, of each *NBT-Classifier* in a 2-dimensional
space. To facilitate the inspection of the corresponding histology of the features, we randomly
selected 500 H&E patches from each ground-truth tissue class (epithelium, stroma, adipocytes)
and projected them onto the t-SNE plot based on their coordinates. The code for this
visualisation is available at: https://github.com/cancerbioinformatics/NBT-
Classifier/blob/main/vis_features.ipynb.

**CAM and Grad-CAM visualisation**

To enhance model interpretability, we applied Class activation mapping (CAM)[27] and Gradient-
weighted Class activation mapping (Grad-CAM)[28]. These techniques generate activation
heatmaps that highlight the spatial regions most important to the model's predictions for any
given input image, utilising the final convolutional layer of the MobileNet backbone weighted by
importance scores. Based on their distinct mechanisms (**Supplementary Fig. 13**), CAM
typically generates more localised heatmaps that highlight areas relevant to the final
classification. In contrast, Grad-CAM may produce more diffuse or generalised heatmaps in
some instances, due to its reliance on gradients to capture the model's learning dynamics. Once
the activation heatmaps were computed, we applied bicubic interpolation to match their
dimensions to those of the original H&E images. The resulting smoothed heatmaps were
overlaid onto the digitised H&E images to visualise the high-attention histological structures
corresponding to each particular tissue class prediction. The source code is available at:
https://github.com/cancerbioinformatics/NBT-Classifier/blob/main/vis_CAMs.ipynb.

**Foreground tissue detection**

Given that WSIs often contain substantial non-tissue regions, including white background and
artefacts such as coverslip edges, excluding these regions is essential for reducing the model's
inference time. We employed HistoQC[46], a WSI quality control software, to automatically
generate binary masks that highlight the artefact-free foreground tissue regions on each WSI

(**Supplementary Fig. 20**), ensuring that only tissue-containing regions are included in
downstream tissue classification analyses.

**Whole slide tissue classification**

When using the 512px-based *NBT-Classifier*, the detected foreground tissue regions are divided
into non-overlapping patches with a fixed size of 128 × 128 μm to account for variations in the
micron per pixel (mpp) values across different scanners. These patches are then resized to 512
× 512 pixels to match the input dimensions of the model. When using the 1024px-based *NBT-*
*Classifier*, the detected foreground region is divided into non-overlapping patches with a fixed
size of 256 × 256 μm and resized to 1024 × 1024 pixels. Each *NBT-Classifier* outputs both
probabilities of epithelium, stroma and adipocytes and the final class prediction for each patch,
along with the original coordination on the slide.

**Whole slide visualisation of tissue classification results**

To visualise the whole slide tissue classification in a single image, we arranged the class
predictions of patches according to their corresponding coordinates on the slide to create a
heatmap. For interactive histological inspection, the tissue class heatmap can be exported as a
JSON file and imported into the QuPath v0.3.0 platform. Additionally, we generated smoother
tissue class heatmaps by upscaling the predicted probability matrix through interpolation. The
visualisation method is available at: [https://github.com/cancerbioinformatics/NBT-](https://github.com/cancerbioinformatics/NBT-)
[Classifier/blob/main/NBT_pipeline.ipynb](https://github.com/cancerbioinformatics/NBT-Classifier/blob/main/NBT_pipeline.ipynb).

**Lobule detection**

To detect individual lobules with their surrounding peri-lobular regions (adjustable), the epithelial
layer in the whole slide tissue class heatmap is extracted and enlarged by a factor of 32. Then,
connected component analysis is applied to identify groups of connected foreground pixels
(filled with a value of 1) as distinct objects. Through manual examination, we observed that
lobules empirically are covered by more than two epithelium patches, approximately 500,000
pixels and 0.25 μm/pixel. Therefore, we removed foreground objects (filled with a value of 1)
smaller than 400,000 pixels and filled "holes" (filled with a value of 0) smaller than 400,000

pixels inside each detected foreground object. For slides scanned at 20x magnification, the

threshold is adjusted to 250,000 pixels. This step reduces noise and increases the robustness

for lobule localisation. This method outputs a binary mask highlighting individual lobules and an

optional surrounding stroma within a pre-defined range. The mask can be converted into a

JSON file and imported into QuPath v0.3.0 for downstream digital image analyses. The source

code is available at: https://github.com/cancerbioinformatics/NBT-

Classifier/blob/main/NBT_pipeline.ipynb.

**Deep learning implementation**

All deep learning experiments were implemented with TensorFlow2 in Python on two NVIDIA

A100 GPUs from the high-performance computing cluster of King's Computational Research,

Engineering, and Technology Environment (CREATE).

**Statistical analysis**

To compare distributions between two groups, we performed pairwise Wilcoxon tests, applying

Bonferroni correction for multiple comparisons. A p-value of < 0.05 was considered statistically

significant. DeLong's test was employed to compare the AUCs between different classifiers,

assessing the significance of performance differences[65,66].

**Data availability**

WSIs involved in this study are stored at the OASIS repository:

https://github.com/cancerbioinformatics/OASIS, which currently can be accessed upon request.

**Code availability**

The implementation code involved in this study can be found at:

https://github.com/cancerbioinformatics/NBT-Classifier, including Python codes for

implementing *NBT-Classifiers* and the pre-processing pipeline, and QuPath v0.3.0 scripts for

tessellation and importing pseudo annotations.

**Acknowledgements**

The authors wish to acknowledge the support of the King's Health Partners Cancer Biobank in London, the Netherlands Cancer Institute in Amsterdam, the Barts Cancer Institute in London, and the École Polytechnique Fédérale de Lausanne in Lausanne, Switzerland and Aasiyah Oozeer, Marcello D'Angelo, Rachel Barrow, Rachel Nelan, Marcelo Sobral-Leite, Fabio de Martino for material collection.

The authors would like to thank all members of the Cancer Bioinformatics team at King's College London (London, UK) for their helpful suggestions. We thank the Breast Cancer Research Trust, Breast Cancer Now (and their legacy charity Breakthrough Breast Cancer), the Medical Research Council (MRC) [MR/X012476/1], Cancer Research UK [CRUK/07/012, KCL-BCN-Q3], CRUK City of London Centre Award [CTRQQR-2021/100004], and the UK Government through the Research Venture Catalyst award, Department for Science, Innovation, and Technology for funding this project. Siyuan Chen is funded by a China Scholarship Council PhD scholarship. The funders had no role in study design, data collection and analysis, decision to publish, or preparation of the manuscript. During the preparation of this work, the author(s) used Grammarly (free version) and ChatGPT (version 2) to correct some grammatical errors and enhance the overall readability of the manuscript. After using this tool/service, the authors reviewed and edited the content as needed and take(s) full responsibility for the content of the publication.

**Author Contributions**

**Conceptualisation**: Anita Grigoriadis, Sarah Pinder, Siyuan Chen, Mario Parreno-Centeno, Christopher R.S. Banerji. **Data curation**: Siyuan Chen, Graham Booker. **Formal analysis**: Siyuan Chen, Mario Parreno-Centeno. **Funding acquisition**: Anita Grigoriadis. **Investigation**: Anita Grigoriadis, Sarah Pinder, Siyuan Chen, Mario Parreno-Centeno, Christopher R.S. Banerji. **Methodology**: Siyuan Chen, Mario Parreno-Centeno, Christopher R.S. Banerji, Gregory Verghese, Salim Arslan. **Project administration**: Anita Grigoriadis. **Resources**: Cheryl Gillett, Louise J. Jones, Esther H. Lips, Cathrin Brisken, Aasiyah Oozeer, Marcello D'Angelo, Rachel Barrow, Rachel Nelan, Marcelo Sobral-Leite, Fabio de Martino. **Software**: Siyuan Chen, Mario Parreno-Centeno. **Supervision**: Anita Grigoriadis, Sarah Pinder, Christopher R.S. Banerji. **Validation**: Fathima Sumayya Mohamed. **Visualisation**: Siyuan Chen. **Writing – original draft**: Siyuan Chen. **Writing– review & editing**: Anita Grigoriadis, Sarah Pinder, Christopher R.S.

665 Banerji, Esther H. Lips, Cathrin Brisken, Louise J. Jones, Matthew J. Smalley, Gregory

666 Verghese, Fathima Sumayya Mohamed, Graham Booker, Siyuan Chen, Mario Parreno-Centeno,

667 Salim Arslan, Pahini Pandya.

**Competing interests**

670 Anita Grigoriadis, Louise J. Jones and Greg Verghese are Co-Founders of PharosAI. Salim

671 Arslan and Pahini Pandya and employed by Panakeia Technology, UK. All other authors

672 declare no relevant conflict of interest.

**Reference**

1.    Salim M, Liu Y, Sorkhei M, et al. AI-based selection of individuals for supplemental MRI in
population-based breast cancer screening: the randomized ScreenTrustMRI trial. *Nature Medicine* 2024;
30: 2623-2630. DOI: 10.1038/s41591-024-03093-5.
2.    Henson DE and Tarone RE. Involution and the etiology of breast cancer. *Cancer* 1994; 74: 424-
429.
3.    Conklin MW, Eickhoff Jc Fau - Riching KM, Riching Km Fau - Pehlke CA, et al. Aligned collagen
is a prognostic signature for survival in human breast carcinoma.
4.    Li HA-O, Bera KA-O, Toro P, et al. Collagen fiber orientation disorder from H&E images is
prognostic for early stage breast cancer: clinical trial validation.
5.    Provenzano PP, Eliceiri KW, Campbell JM, et al. Collagen reorganization at the tumor-stromal
interface facilitates local invasion. *BMC Med* 2006; 4: 38. 20061226. DOI: 10.1186/1741-7015-4-38.
6.    Gadaleta E, Thorn GJ, Ross-Adams H, et al. Field cancerization in breast cancer. *The Journal of
Pathology* 2022; 257: 561-574. https://doi.org/10.1002/path.5902. DOI: https://doi.org/10.1002/path.5902.
7.    Kuchenbaecker KB, Hopper JL, Barnes DR, et al. Risks of breast, ovarian, and contralateral
breast cancer for BRCA1 and BRCA2 mutation carriers. *Jama* 2017; 317: 2402-2416.
8.    Ferreira R, Moon B, Humphries J, et al. The virtual microscope. In: *Proceedings of the AMIA
Annual Fall Symposium* 1997, p.449. American Medical Informatics Association.
9.    Pantanowitz L, Sharma A, Carter AB, et al. Twenty Years of Digital Pathology: An Overview of
the Road Travelled, What is on the Horizon, and the Emergence of Vendor-Neutral Archives. *Journal of
Pathology Informatics* 2018; 9: 40. DOI: https://doi.org/10.4103/jpi.jpi_69_18.
10.    Bankhead P, Loughrey MB, Fernández JA, et al. QuPath: Open source software for digital
pathology image analysis. *Scientific Reports* 2017; 7: 16878. DOI: 10.1038/s41598-017-17204-5.
11.    Lipkova J and Kather JN. The age of foundation models. *Nat Rev Clin Oncol* 2024; 21: 769-770.
DOI: 10.1038/s41571-024-00941-8.
12.    Cooper M, Ji Z and Krishnan RG. Machine learning in computational histopathology: Challenges
and opportunities. *Genes* 2023; 62: 540 - 556.
13.    Hosseini MS, Bejnordi BE, Trinh VQ-H, et al. Computational Pathology: A Survey Review and
The Way Forward. *arXiv preprint arXiv:230405482* 2023.
14.    Song AH, Jaume G, Williamson DF, et al. Artificial intelligence for digital and computational
pathology. *Nature Reviews Bioengineering* 2023; 1: 930-949.

15.     Zhu Z, Wang SH and Zhang YD. A Survey of Convolutional Neural Network in Breast Cancer.
*Comput Model Eng Sci* 2023; 136: 2127-2172. DOI: 10.32604/cmes.2023.025484.
16.     Patil A, Diwakar H, Sawant J, et al. Efficient quality control of whole slide pathology images with
human-in-the-loop training. *Journal of Pathology Informatics* 2023; 14: 100306.
17.     Wetstein SC, Onken AM, Luffman C, et al. Deep learning assessment of breast terminal duct
lobular unit involution: Towards automated prediction of breast cancer risk. *PLoS One* 2020; 15:
e0231653. 20200415. DOI: 10.1371/journal.pone.0231653.
18.     de Bel T, Litjens G, Ogony J, et al. Automated quantification of levels of breast terminal duct
lobular (TDLU) involution using deep learning. *NPJ Breast Cancer* 2022; 8: 13. 20220119. DOI:
10.1038/s41523-021-00378-7.
19.     Kensler KH, Liu EZF, Wetstein SC, et al. Automated Quantitative Measures of Terminal Duct
Lobular Unit Involution and Breast Cancer Risk. *Cancer Epidemiol Biomarkers Prev* 2020; 29: 2358-2368.
20200911. DOI: 10.1158/1055-9965.Epi-20-0723.
20.     Ogony J, de Bel T, Radisky DC, et al. Towards defining morphologic parameters of normal
parous and nulliparous breast tissues by artificial intelligence. *Breast Cancer Res* 2022; 24: 45. 20220711.
DOI: 10.1186/s13058-022-01541-z.
21.     Apou G, Schaadt NS, Naegel B, et al. Detection of lobular structures in normal breast tissue.
*Comput Biol Med* 2016; 74: 91-102. 20160511. DOI: 10.1016/j.compbiomed.2016.05.004.
22.     Abubakar M, Klein A, Fan S, et al. Host, reproductive, and lifestyle factors in relation to
quantitative histologic metrics of the normal breast. *Breast Cancer Res* 2023; 25: 97. 20230815. DOI:
10.1186/s13058-023-01692-7.
23.     Ish JL, Abubakar M, Fan S, et al. Outdoor air pollution and histologic composition of normal
breast tissue. *Environ Int* 2023; 176: 107984. 20230519. DOI: 10.1016/j.envint.2023.107984.
24.     Heydarlou H, Hodson LJ, Dorraki M, et al. A Deep Learning Approach for the Classification of
Fibroglandular Breast Density in Histology Images of Human Breast Tissue. *Cancers (Basel)* 2025; 17
20250128. DOI: 10.3390/cancers17030449.
25.     Stacke K, Eilertsen G, Unger J, et al. Measuring Domain Shift for Deep Learning in
Histopathology. *IEEE J Biomed Health Inform* 2021; 25: 325-336. 20210205. DOI:
10.1109/jbhi.2020.3032060.
26.     Tafavvoghi M, Bongo LA, Shvetsov N, et al. Publicly available datasets of breast histopathology
H&E whole-slide images: A scoping review. *Journal of Pathology Informatics* 2024; 15: 100363. DOI:
https://doi.org/10.1016/j.jpi.2024.100363.
27.     Zhou B, Khosla A, Lapedriza A, et al. Learning deep features for discriminative localization. In:
*Proceedings of the IEEE conference on computer vision and pattern recognition* 2016, pp.2921-2929.
28.     Selvaraju RR, Cogswell M, Das A, et al. Grad-CAM: visual explanations from deep networks via
gradient-based localization. *International journal of computer vision* 2020; 128: 336-359.
29.     Sherman ME, Figueroa JD, Henry JE, et al. The Susan G. Komen for the Cure Tissue Bank at
the IU Simon Cancer Center: A Unique Resource for Defining the "Molecular Histology" of the Breast.
*Cancer Prevention Research* 2012; 5: 528-535. DOI: 10.1158/1940-6207.CAPR-11-0234.
30.     Jahanifar M, Raza M, Xu K, et al. Domain generalization in computational pathology: survey and
guidelines. *arXiv preprint arXiv:231019656* 2023.
31.     Voon W, Hum YC, Tee YK, et al. Performance analysis of seven Convolutional Neural Networks
(CNNs) with transfer learning for Invasive Ductal Carcinoma (IDC) grading in breast histopathological
images. *Scientific Reports* 2022; 12: 19200. DOI: 10.1038/s41598-022-21848-3.
32.     Reinhard E, Adhikhmin M, Gooch B, et al. Color transfer between images. *IEEE Computer
Graphics and Applications* 2001; 21: 34-41. DOI: 10.1109/38.946629.
33.     Vahadane A, Peng T, Sethi A, et al. Structure-Preserving Color Normalization and Sparse Stain
Separation for Histological Images. *IEEE Trans Med Imaging* 2016; 35: 1962-1971. 20160427. DOI:
10.1109/tmi.2016.2529665.

34.     Macenko M, Niethammer M, Marron JS, et al. A method for normalizing histology slides for
quantitative analysis. In: *2009 IEEE International Symposium on Biomedical Imaging: From Nano to*
*Macro* 28 June-1 July 2009 2009, pp.1107-1110.
35.     Kang H, Luo D, Feng W, et al. StainNet: A Fast and Robust Stain Normalization Network. *Front*
*Med (Lausanne)* 2021; 8: 746307. 20211105. DOI: 10.3389/fmed.2021.746307.
36.     Howard AG. Mobilenets: Efficient convolutional neural networks for mobile vision applications.
*arXiv preprint arXiv:170404861* 2017.
37.     He K, Zhang X, Ren S, et al. Deep residual learning for image recognition. In: *Proceedings of the*
*IEEE conference on computer vision and pattern recognition* 2016, pp.770-778.
38.     Huang G, Liu Z, Van Der Maaten L, et al. Densely connected convolutional networks. In:
*Proceedings of the IEEE conference on computer vision and pattern recognition* 2017, pp.4700-4708.
39.     Szegedy C, Vanhoucke V, Ioffe S, et al. Rethinking the inception architecture for computer vision.
In: *Proceedings of the IEEE conference on computer vision and pattern recognition* 2016, pp.2818-2826.
40.     Deng J, Dong W, Socher R, et al. Imagenet: A large-scale hierarchical image database. In: *2009*
*IEEE conference on computer vision and pattern recognition* 2009, pp.248-255. Ieee.
41.     Van der Maaten L and Hinton G. Visualizing data using t-SNE. *Journal of machine learning*
*research* 2008; 9.
42.     BReAst Carcinoma Subtyping (BRACS), https://www.bracs.icar.cnr.it/background/.
43.     Brancati N, Anniciello AM, Pati P, et al. BRACS: A Dataset for BReAst Carcinoma Subtyping in
H&E Histology Images. *Database* 2022; 2022: baac093. DOI: 10.1093/database/baac093.
44.     Howard AG, Zhu M, Chen B, et al. Mobilenets: Efficient convolutional neural networks for mobile
vision applications. *arXiv preprint arXiv:170404861* 2017.
45.     Yamashita R, Long J, Longacre T, et al. Deep learning model for the prediction of microsatellite
instability in colorectal cancer: a diagnostic study. *Lancet Oncol* 2021; 22: 132-141. DOI: 10.1016/s1470-
2045(20)30535-0.
46.     Janowczyk A, Zuo R, Gilmore H, et al. HistoQC: An Open-Source Quality Control Tool for Digital
Pathology Slides. *JCO Clin Cancer Inform* 2019; 3: 1-7. DOI: 10.1200/cci.18.00157.
47.     Montezuma D, Oliveira SP, Tolkach Y, et al. Annotation Practices in Computational Pathology: A
European Society of Digital and Integrative Pathology (ESDIP) Survey Study. *Lab Invest* 2024; 105:
102203. 20241129. DOI: 10.1016/j.labinv.2024.102203.
48.     Reed AD, Pensa S, Steif A, et al. A single-cell atlas enables mapping of homeostatic cellular
shifts in the adult human breast. *Nature Genetics* 2024; 56: 652-662. DOI: 10.1038/s41588-024-01688-9.
49.     Kumar T, Nee K, Wei R, et al. A spatially resolved single-cell genomic atlas of the adult human
breast. *Nature* 2023; 620: 181-191. 20230628. DOI: 10.1038/s41586-023-06252-9.
50.     Sun S, Brazhnik K, Lee M, et al. Single-cell analysis of somatic mutation burden in mammary
epithelial cells of pathogenic BRCA1/2 mutation carriers. *J Clin Invest* 2022; 132. DOI: 10.1172/jci148113.
51.     Pal B, Chen Y, Vaillant F, et al. A single-cell RNA expression atlas of normal, preneoplastic and
tumorigenic states in the human breast. *Embo j* 2021; 40: e107333. 20210505. DOI:
10.15252/embj.2020107333.
52.     Anaya J, Sidhom JW, Mahmood F, et al. Multiple-instance learning of somatic mutations for the
classification of tumour type and the prediction of microsatellite status. *Nat Biomed Eng* 2024; 8: 57-67.
20231102. DOI: 10.1038/s41551-023-01120-3.
53.     Naik N, Madani A, Esteva A, et al. Deep learning-enabled breast cancer hormonal receptor status
determination from base-level H&E stains. *Nature communications* 2020; 11: 5727.
54.     El Nahhas OSM, Loeffler CML, Carrero ZI, et al. Regression-based Deep-Learning predicts
molecular biomarkers from pathology slides. *Nature Communications* 2024; 15: 1253. DOI:
10.1038/s41467-024-45589-1.

55.    Caputo A, Vipparthi K, Bazeley P, et al. Spatial Transcriptomics Suggests That Alterations Occur
in the Preneoplastic Breast Microenvironment of BRCA1/2 Mutation Carriers. *Mol Cancer Res* 2024; 22:
169-180. DOI: 10.1158/1541-7786.Mcr-23-0489.
56.    Trujillo KA, Heaphy Cm Fau - Mai M, Mai M Fau - Vargas KM, et al. Markers of fibrosis and
epithelial to mesenchymal transition demonstrate field cancerization in histologically normal tissue
adjacent to breast tumors.
57.    Jo S, Jang G and Park H. GMAR: Gradient-Driven Multi-Head Attention Rollout for Vision
Transformer Interpretability. *arXiv preprint arXiv:250419414* 2025.
58.    Chowdhury A, Paul D, Mai Z, et al. Prompt-CAM: Making Vision Transformers Interpretable for
Fine-Grained Analysis. In: *Proceedings of the Computer Vision and Pattern Recognition Conference* 2025,
pp.4375-4385.
59.    Oh S, Kim N and Ryu J. Analyzing to discover origins of CNNs and ViT architectures in medical
images. *Scientific Reports* 2024; 14: 8755. DOI: 10.1038/s41598-024-58382-3.
60.    Chen RJ, Ding T, Lu MY, et al. A general-purpose self-supervised model for computational
pathology. *arXiv preprint arXiv:230815474* 2023.
61.    Lu MY, Chen B, Williamson DFK, et al. A visual-language foundation model for computational
pathology. *Nature Medicine* 2024; 30: 863-874. DOI: 10.1038/s41591-024-02856-4.
62.    Gustafsson FK and Rantalainen M. Evaluating Computational Pathology Foundation Models for
Prostate Cancer Grading under Distribution Shifts. *arXiv preprint arXiv:241006723* 2024.
63.    Song AH, Chen RJ, Ding T, et al. Morphological prototyping for unsupervised slide representation
learning in computational pathology. In: *Proceedings of the IEEE/CVF Conference on Computer Vision
and Pattern Recognition* 2024, pp.11566-11578.
64.    Yun J, Hu Y, Kim J, et al. Enhancing Whole Slide Pathology Foundation Models through Stain
Normalization. *arXiv e-prints* 2024: arXiv: 2408.00380.
65.    DeLong ER, DeLong DM and Clarke-Pearson DL. Comparing the areas under two or more
correlated receiver operating characteristic curves: a nonparametric approach. *Biometrics* 1988; 44: 837-
845.
66.    Sun × and Xu W. Fast Implementation of DeLong's Algorithm for Comparing the Areas Under
Correlated Receiver Operating Characteristic Curves. *IEEE Signal Processing Letters* 2014; 21: 1389-
1393. DOI: 10.1109/LSP.2014.2337313.
831

**Figures**

**Figure 1. Dataset overview and optimisation of *NBT-classifiers*. a** Schematic illustrating the

sources of normal breast tissues (NBTs) used in the study. **b** Barplot depicting the distribution of

whole slide images (WSIs) used for training and external validation. WSIs from the NKI and BCI

cohorts were used for model training, while those from the KHP, EPFL, and SGK cohorts were

reserved for external validation. Each bar represents the patient age associated with a single

WSI, with colours indicating the NBT source. **c** Schematic of the manual annotation process and

the training pipeline. Epithelium, stroma, and adipocytes are annotated in red, green, and blue,

respectively. Scale bar, 2 mm. Annotations were tessellated into non-overlapping patches,

followed by class-balanced sampling and stain normalisation for training each *NBT-Classifier*.

Each model uses a CNN backbone with a classification head that predicts three tissue classes:

0 (epithelium), 1 (stroma), and 2 (adipocytes). **d** Magnified images of single annotations for

epithelium, stroma, and adipocytes (from left to right). Scale bars, 100 µm. **e** Barplot of 3-fold

cross-validation (CV) performance for models trained with and without different stain

normalisation methods and CNN backbones. Experiments were conducted on patches

tessellated at 512 × 512 pixels (0.25 µm/pixel). The yellow line in each box represents the

median internal test accuracy, with whiskers extending to the minimum and maximum values.

The best-performing combination is highlighted with a red arrow. **f** Barplot showing test

accuracies during 3-fold cross-validation for models trained on different patch sizes. Patches

were tessellated at 0.25 µm/pixel resolution and processed using the Reinhard stain

normalisation method and the MobileNet backbone. The results for 224 × 224 (green, 224px),

512 × 512 (blue, 512px), and 1024 × 1024 (light brown, 1024px) pixel patches are coloured

differently. The upper, middle, and lower lines of each boxplot represent the test accuracies

during 3-fold cross-validation.

**Figure 2.** *NBT-Classifiers* **demonstrate high generalisability based on robust normal breast features. a** Tissue-specific ROC curves showing the external performance of the 512px-based *NBT-Classifier*. True positive rate (TPR) is plotted against false positive rate (FPR) at different thresholds for epithelium, stroma, and adipocytes, indicated in red, green, and blue, respectively. The corresponding area under the curve (AUC) values are presented in the legend. **b** Tissue-specific ROC curves showing the external performance of the 1024px-based *NBT-Classifier*. **c** t-SNE visualisation of the 512px-based *NBT-Classifier's* predictions. Features for epithelium, stroma, and adipocytes are indicated in red, green, and blue, respectively. **d** t-SNE visualisation of H&E-stained patches of the same samples shown in panel b. For each predicted tissue class (epithelium, stroma, and adipocytes), 500 patches were randomly sampled and overlaid onto the plot based on their coordinates. **e** Class activation mapping (CAM) visualisation for the 512px-based *NBT-Classifier*. Examples of epithelium, stroma, and adipocytes patches (512 × 512 pixels, 0.25 µm/pixel) are shown in the first column. For each example, the original CAM heatmap, resized heatmap and heatmap overlaid on the original H&E patch image are shown on the right, with the predicted probabilities for epithelium, stroma, and adipocytes displayed at the top. Scale bar, 25 µm. **f** CAM heatmaps overlaid on a selected

874    region. The region was divided into non-overlapping 512 × 512-pixel patches, for which CAM

875    heatmaps were generated based on the predicted tissue class. The heatmaps were then

876    resized and overlaid to highlight high-attention structures in each patch. Scale bar, 250 µm.

**Figure 3. *NBT-Classifiers* capture features unique to normal breast epithelium. a** Tissue-specific ROC curves comparing the external performance of the 1024px-based *NBT-Classifier* and HistoROI in classifying stroma and adipocytes. AUC values for each model and tissue type are listed in the legend. Differences in AUC were evaluated using DeLong's test. **b** Distribution of epithelial probability scores for normal versus abnormal breast tissues. Panels show probability density estimates for the 1024px-based *NBT-Classifier* (top) and HistoROI (bottom). Abnormal□=□ADH, DCIS, FEA, IC, PB, and UDH lesions. **c** ROC curves for normal versus abnormal tissue classification using *NBT-Classifier* and HistoROI. Corresponding AUC values are indicated in the figure. DeLong's test, p < 0.0001. **d** Barplots showing AUC values for normal tissue versus precancerous (FEA, ADH) and cancerous lesions (DCIS, IC) using *NBT-Classifier* and HistoROI. **e** Grad-CAM visualisation of regions of high attention contributing to epithelium predictions. For a representative epithelium patch (1024 × 1024 pixels, extracted at 40× magnification), Grad-CAM was applied to both the 1024px-based *NBT-Classifier* and HistoROI. For each model, the Grad-CAM heatmap and corresponding H&E overlay are shown.

**Figure 4. Visualisation of whole slide tissue classification. a-b** QuPath v0.3.0 visualisation of whole slide tissue class predictions by the 512px- (**a**) and 1024-based (**b**) *NBT-Classifiers*. The original tissue class predictions of the entire WSI were converted into JSON files and imported into QuPath v0.3.0 as pseudo patch-level annotations, shown in the right images. Epithelium, stroma, and adipocytes are represented in red, green, and blue, respectively. Scale bar, 2 mm. Magnified regions are displayed on the right. Scale bar, 400 µm. **c** Tissue probability heatmaps of a representative region. A 5120 × 5120-pixel region containing mixed tissue components (left) was selected and tessellated into non-overlapping 512 × 512-pixel patches. For each patch, the probabilities of epithelium, stroma, and adipocytes were predicted using the 512px-based *NBT-Classifier* and mapped to the red (R), green (G), and blue (B) channels, respectively, to generate a tissue probability heatmap (middle). The heatmap was then resized and overlaid onto the H&E image to facilitate comparison with the corresponding histological patterns (right). Scale bar, 250 µm. **d** Pie chart illustrating the distribution of the 512px-based

907    *NBT-Classifier's* confidence in the predicted tissue class. **e** Visualisation of patches predicted

908    with varying confidence. The top image shows patches classified with a confidence higher than

909    0.7, while the bottom image shows patches classified with a confidence higher than 0.99.

**Figure 5. Approaches facilitating downstream WSI analysis of NBTs. a** Proposed WSI pre-processing pipeline for NBTs. From left to right, the images depict an input WSI (scale bar, 2 mm), detected foreground tissue regions, whole slide tissue classifications (red: epithelium, green: stroma, blue: adipocytes), identified lobular regions, balanced-sampled patches, and stain-normalised patches. **b** Magnified example of a detected lobular region. The tissue class mask was generated by the 512px-based *NBT-Classifier*, resized, and overlaid onto the H&E image. The red box highlights the detected lobule, while the yellow box outlines the lobular region, with a 250 µm (adjustable) width between the two boxes, as indicated by the white arrows. **c** Example demonstrating generated pseudo lobule annotations and downstream nuclei spatial analysis in QuPath v0.3.0. The first image displays a binary mask of detected lobules, which were imported as pseudo-lobule annotations (highlighted in red) in QuPath v0.3.0, as shown in the second image. Scale bar, 2 mm. Within QuPath v0.3.0, nuclei segmentation was performed using StarDist, followed by Delaunay spatial analysis to quantify various graph properties of each lobule, such as the number of nuclei within the graph. The third image visualises the variation in the number of nuclei (indicated by the colour bar) across Delaunay graphs constructed for lobules within a magnified region. Scale bar, 1 mm. The last image presents an example of a Delaunay graph constructed from a magnified lobule. Scale bar, 100 µm. **d** Example of pseudo patch-level tissue class annotations within detected lobular regions and downstream texture analysis in QuPath v0.3.0. The middle image displays pseudo patch-

level annotations of the epithelium (red) and peri-lobular stroma (green) in QuPath v0.3.0, which

were subsequently analysed separately using Haralick texture features. The left image

visualises the variation in the Inverse Difference Moment (F4) across epithelium patches, while

the right image shows the variation in the Angular Second Moment (F0) across stroma patches.

Scale bar, 2 mm. Magnified patch examples with low and high F4 and F0 values are displayed

on the side.