Human gloss perception reproduced by tiny neural networks

Takuma Morimoto[1, 2*], Arash Akbarinia[1], Katherine R. Storrs[3], Jacob R. Cheeseman[1], Hannah E. Smithson[2], Karl R. Gegenfurtner[1], and Roland W. Fleming[1]

1: Department of Psychology, Justus-Liebig-Universität Gießen, Germany

2: Department of Experimental Psychology, University of Oxford, Oxford, UK

3: School of Psychology, University of Auckland, New Zealand

*Corresponding author: Takuma Morimoto

Email: takuma.morimoto@psy.ox.ac.uk

Keywords: human vision, material perception, convolutional neural networks, online experiment

Abstract (200/200 words)

A key goal of visual neuroscience is to explain how our brains infer object properties like colour, curvature, or gloss. Here, we used machine learning to identify computations underlying human gloss judgments from object images—traditionally considered a particularly challenging inference. We rendered thousands of object images—varying in lighting, shape, and viewpoint—and crowdsourced perceptual reflectance estimates for each image. Curiously, participants' judgments were highly consistent with one another, yet systematically deviated from reality. We compared the responses with neural networks trained on two different learning objectives: one set trained to estimate physical reflectance ('ground-truth networks') and another to mimic the human responses ('human-like networks'). By reducing network size, we identified the minimum computations needed for each objective. While estimating physical reflectance required deep networks, shallow networks—with as few as three layers—accurately replicated human judgments. Remarkably, even a miniscule 'network' with just a single filter could predict human judgments better than the best ground-truth network. The human-like networks also captured known gloss illusions outside the training range. These results suggest human gloss judgments rely on simpler, more general-purpose computations than previously thought, and also demonstrate the extraordinary power of using 'tiny' but interpretable neural networks to uncover functional computations in human brains.

Introduction

In daily life, we encounter materials with a wide range of visual qualities, like metal, cloth, or plastic [1]. In a brief glance, we can judge their colour, lightness, shape, glossiness, translucency and other appearance characteristics. We can infer associated physical properties, such as weight, softness, or roughness, and even their states, such as whether they are wet or dry, clean or dirty, solid or melting

[2]. Humans use visually sampled information about materials to guide our behaviors, e.g. lifting heavy
objects slowly or plucking ripe berries gently.

Among the various material properties that we can perceive visually, gloss is the most extensively
studied [3]. Gloss estimation is widely considered a quintessential, challenging perceptual inference [3-
5] as it involves not only distinguishing highlights and reflections from other features (e.g., bumps or
surface markings) but also pooling and interpreting the reflections to arrive at a global estimate of the
surface's reflectance. Past studies have proposed various cues the visual system may use to determine
the glossiness of an object's surface, including the skewness of the luminance histogram [6-9], the
luminance gradient [10], the standard deviation of luminance over a surface [11], and various image
metrics derived from specular reflection patterns [12,13]. One significant challenge is that an object with
specific material properties can differ substantially in visual appearance, depending on factors such as
shape, lighting, and viewpoint. To characterise how the visual system addresses this challenge, many
studies have measured gloss perception across a wide variety of viewing conditions [14-29]. Yet, no
single model fully captures human gloss perception across these diverse factors.

In the present study, we aim to identify biologically plausible, *image-computable* models that can
account for human gloss judgments across a broad set of images. Our focus is specifically on
understanding the perceptual computations that support judgments of gloss *from images*. While this is
not equivalent to gloss perception in real-world, dynamic viewing, image-based judgments provide a
tractable and meaningful way to investigate the visual information and representations that correlate
with perceived gloss.

'Tiny' neural networks as interpretable data-driven models. One persistent challenge for traditional
cue-based approaches is that researchers must somehow invent candidate visual cues in advance to
evaluate their efficacy. This can be a hurdle when the cues the visual system relies on may be too
complex or abstract to formulate. Recent studies have taken a data-driven approach, seeking deep
learning models that mirror the pattern of human gloss judgments [30,31]. Our approach differs
fundamentally by aiming to create human-like convolutional neural networks (CNNs) by directly training
them on human perceptual data. We gathered gloss judgments from hundreds of human observers for
thousands of object images in an online experiment. Through optimization, the CNNs spontaneously
acquired a set of filters useful for reproducing human-like gloss judgments, without manual feature
selection. This allows exploration of a much larger search space, not limited by the experimenter's
imagination. We then systematically adjusted the depth of the CNNs to understand the computational
power required to predict human gloss judgments, aiming to make them as shallow as possible to
increase interpretability [32-34]. We then interrogated the mechanisms that emerged within the
networks. This allows for a data-driven, hypothesis-free approach to discovering the computations
underlying human perception across diverse viewing conditions [35].

Figure 1 summarizes our approach. We generated 3,888 images from the full combination of 36 lighting environments, 36 object geometries, and 3 viewpoints. Using an online crowd-sourced experiment, each image was assigned a perceived gloss value based on human gloss judgments ('human labels'), first averaged across two repetitions per observer and then averaged across at least three observers. The observer's task was to adjust the specular reflectance parameter of a reference object until the test and reference objects appeared to have the same glossiness. The quality of the data was confirmed through laboratory-based validation experiments (see **Supporting Information, SI**). We then trained two sets of CNNs with various depths: one on images with human labels ('human-like networks') and another on images with physical ground-truth labels ('ground-truth networks'). To ensure that the networks learned only the gloss computation—rather than tasks such as image segmentation—we trained them on images where the object was shown against a uniform gray background (sRGB = [127, 127, 127]). Finally, we compared the performance of the two sets of CNNs and examined the internal computations of the human-like networks to gain insights into mechanisms that reproduce human gloss judgements.

Figure 1. Schematic of our approach. a The scenes contained an object with a glossy surface (Ward reflectance model [36, 37], surface roughness fixed at 0.05). Random specular reflectance values and body colors were applied. The full set of 3,888 images was rendered by combining 36 shapes, 36 lighting environments, and 3 random viewpoints per shape-lighting pair (36 × 36 × 3). **b Left**: Design of online experiment. The 3,888 images were randomly assigned to 54 sets of 72 images plus 12 additional images shared across sets to evaluate variation among observers. Two image sets were also tested in a lab-based experiment (see **Supplementary Information**), to validate the online data quality. At least three observers were recruited for each set. **Right:** stimulus configuration for the asymmetric gloss

matching task. By moving a slider, observers adjusted the gloss (i.e., Pellacini's c [38]) of the reference
object to match the perceived gloss level between the two objects. **c** For cross-validation, the 3,888
images were split such that each validation set consisted of a block of either three novel shapes (3
shapes × 36 lighting environments × 3 viewpoints = 324 images) or three novel lighting environments
(36 shapes × 3 lighting environments × 3 viewpoints = 324 images), which were excluded from the
corresponding training set. There were 12 such shape-based splits and 12 lighting-based splits,
resulting in 24 unique, non-overlapping combinations of training (3,564 images) and validation (324
images) datasets. We trained CNNs with varying numbers of intermediate layers using images labeled
by human gloss judgments ('human-like networks') or by physical ground-truth labels ('ground-truth
networks'), where each 'label' consisted of a continuous value of perceived gloss or physical specular
reflectance. Gloss levels predicted by the networks were compared against human responses. The
trained networks were analyzed to understand the computational mechanisms that emerged within
them.

Our findings suggest that relatively shallow CNN architectures with as few as three convolutional layers
are sufficient to predict human gloss judgments approximately as well as individual human judgments
predict one another, while inferring the physical ground-truth requires far more complex computations
for equivalent accuracy. Indeed, we find that even a single convolutional kernel can predict human
perception better than the best of the ground-truth networks. Analysis of the emergent filters in the
human-like networks showed that a filter combining a Gaussian blob and oriented ridges can effectively
extract image features predictive of human gloss judgments. This insight indicates that what seems to
be a complex visual task, such as judging material properties, may be resolved through a set of simple
computations that are also used for other visual tasks.

120
Results
Perceptual experiments. Each gray circle in **Figure 2a** represents one of the 3,888 test images. The
axes display ground-truth specular reflectance values and observer settings (averaged over observers).
Notably, the average observer settings significantly deviate from the ground-truth reflectance of the
objects. The histogram of Pearson's correlation coefficients for each of the 295 observers shows a
median correlation value of 0.46, with no observer exceeding 0.75 (**Figure 2b**). This indicates that gloss
judgements deviated from ground truth in informative ways, likely due to the broader range of viewing
conditions than in many earlier studies.

129
However, crucially these gloss judgments were highly consistent both within and across observers
(**Figures 2c** and **2d**). Intra-observer correlations were calculated between sessions 1 and 2 for each
observer over 84 images (Figure 2c). Each inter-observer correlation was computed over 84 images
between one observer and the average of the rest who judged the same set (left plot in Figure 2d), or
between one observer and another for all possible observer pairs (295*294*0.5 = 43,365 pairs), over
12 common images (right plot). This confirms that the large deviation from the physical ground-truth
was not due to random variation in observer judgments. On the contrary, observers made highly
systematic and consistent patterns of agreement and disagreement with physical reflectance in gloss

estimation. A separate, lab-based experiment validated that the online data are of comparable quality

(SI, Figure S4).

Each grid in **Figure 2e** shows eight example images in each pair of physical ground-truth and observer

settings (low, mid and high). Images in the diagonal arrays (low-low, mid-mid, high-high) display objects

where ground-truth and human judgments agree. Images in the top left and bottom right grids (low-high,

high-low) highlight interesting cases where human judgments and physical ground-truth disagree

substantially. Such images effectively provide different objectives for networks trained on physical

ground-truth versus human judgments. Although human judgments do correlate somewhat with ground-

truth, there is also sufficient consistent deviation from physical ground-truth to allow us to capture the

key idiosyncratic computational signatures of human gloss perception.

Figure 2. Summary of behavioural results. a Each data point shows a specific stimulus image, and

the plot includes data on all 3,888 images. The horizontal and vertical axes show physical ground-truth

reflectance values and observer settings (perceived gloss) averaged over observers. **b** Histogram of

human vs. ground-truth correlation. The plot shows the distribution of Pearson's correlation coefficients

between each observer's settings and the corresponding ground-truth values. **c** Histogram of within-
observer correlations. For each observer, Pearson's correlation coefficient was computed between
session 1 and session 2 to quantify the intra-observer variability. **d** Histogram of correlation across
observers. For the left plot, the correlation was computed between one observer and the average across
all other observers across 72 images unshared across image sets. For the right plot, the correlation
was computed over 12 images for every pair of observers (i.e. (295×294)/2 = 43,365 pairs). **e** Each grid
shows 8 example images. The horizontal and vertical positions in the grid show the physical specular
reflectance assigned to each object and observer settings (perceived gloss level). The number of
images in each grid is shown at the right bottom of each grid.

Computational Models. Figure 3 compares observers and candidate models based on their
correlation to the physical ground-truth (x-axis) and human judgments (y-axis). The upper left half of
the plot (pale blue region) indicates human-like models. The other half (pale pink region) indicates
models that correlate more closely with the physical ground-truth. Each dark green circle represents an
individual observer, where the y-axis shows the correlation to the average of the rest of the observers
who judged the same 72 images. Thus, in this plot, we are seeking models positioned close to this
distribution of green circles.

Gray diamonds show models based on luminance statistics models (mean, median, first quartile, third
quartile, minimum, maximum, standard deviation, skewness, kurtosis), which are positioned far from
the human distribution. When these cues are combined using multiple linear regression fit to predict
human responses, the correlation with human responses increases (indicated by the gray star symbol).
Light green downward triangles show models that use sharpness, coverage and sub-band contrast
computed from specular reflection images [12]. These models correlate more with physical ground-truth
than with human observers and therefore do not effectively capture human perception in our task.
Combining these cues yielded no improvement (the light-green star symbol).

The blue triangles and squares show CNNs trained on human responses with one and three
convolutional layers, respectively. The number next to each symbol shows the number of kernels in
each convolutional layer. As expected, the deeper networks, such as three-layer with 64 kernels, came
closer to approximating the mean glossiness judgments across all observers (black cross). Yet it is
extremely intriguing and noteworthy that a CNN with only one kernel (single-kernel model) comes close
to the edge of the human distribution, with a correlation coefficient of 0.64. Given the correlation
coefficient across observers was around 0.85, this very light model reaches 75.3% of this performance
ceiling and indeed approximates human perception better than any of the models trained on physical
ground-truth labels that we tested.

In contrast to the CNNs trained on human labels, the networks trained on physical ground-truth labels,
shown by magenta symbols, struggle to achieve such impressive performance. Although trained to
recover physical labels, some physical ground-truth networks are positioned near human-like networks,

and even the three-layer models fall in the blue half of the plot. To predict physical labels effectively, more complex architectures were required. A ResNet18 (magenta rightward triangle) was needed to cross the diagonal unity line, highlighting the computational challenges involved in estimating physical ground-truth. Using additional training images rendered using novel lighting environments and object shapes, the network's ability to predict ground-truth substantially improved, as shown by orange symbols. Three-layer models with 64 kernels (orange square) still show a limited correlation below 0.70, even with an additional 3.8×10^5 images. A ResNet18 trained with these additional images shows a correlation around 0.9 to ground-truth, but importantly, the correlation to human responses is below 0.5. The intriguing aspect of this observation is that it suggests that human strategies for estimating material properties such as specular reflectance are unlikely to rely on complex computations that aim to recover physical parameters, as suggested by inverse optics approaches. Instead, it appears that humans use relatively simple computations to intuit complex material properties. Having established that lean neural network models can be trained to approximate human responses, we next sought to analyse the inner workings of these networks as a means to gain insights into the computations underlying human gloss judgements.

Figure 3. Summary of computational model behaviours. Dark green circles show individual human observers (N=295), where the x-axis and the y-axis show the correlation over 74 images to the physical ground-truth and the correlation to the average of the rest of the observers, respectively. Other data points show candidate computational models. Gray diamonds show low level luminance image statistics models, and the gray star shows a multiple regression model based on the luminance statistics (best fit to human data). Light green downward triangles show models based on statistics computed from specular reflection images (sharpness, coverage, and sub-band contrast), and the light green star symbol shows a multiple regression based on the specular metrics (best fit to human data). Triangles and squares show one-layer models with different kernel numbers (1, 2, 4 and 9; 9, 16, 32 and 64), where blue symbols refer to the networks trained on images labeled by observer judgments and pink symbols show networks trained on images labeled by physical ground-truth labels. The magenta

rightward triangle shows ResNet18 trained on physical ground-truth label. Orange symbols represent
CNNs trained with additional images, generated using novel shapes and lighting conditions not included
in the 3,888 images. Orange squares correspond to the three-layer model with 64 filters, and orange
rightward triangles show ResNet18. The orange numbers on the plot show the number of additional
images used.

Analysis of single-kernel models. As shown in **Figure 4a**, the single-kernel model first applies a
15×15×3 convolution to the input image, followed by max pooling and the addition of a bias term to
predict a gloss level. To evaluate the variability of the emergent kernel, we analyzed 24 networks trained
as part of the cross-validation process.
233
We found that the emerging kernels were highly consistent across the 24 networks (panel **b**). Their
typical spatial structure consisted of a bright central blob surrounded by a darker region, which is well
suited for detecting highlights based on their characteristic spatial intensity profiles. Notably, the bright
region often exhibits a yellowish tint, while the surrounding area appears bluish. This mirrors the typical
color relationship between direct illumination (such as sunlight) and indirect illumination (such as
skylight) in natural scenes, allowing the kernels to exploit hue differences for highlight detection. It is
also notable that each blob is abutted by one or two brownish diagonal ridges—typically consisting of
an orange upper region, a dark middle region and blueish lower region—presumably positioned to
detect oriented, lower-contrast highlights. These ridges are bands of positive weights running at
approximately 45° or 135°, which enable the kernel to respond strongly to local intensity changes at
similar angles. As a result, the kernels can detect diagonal boundaries and curvatures typical of
specular highlights on curved surfaces, as well as capture how highlights spread or extend in specific
directions.
247
Panel **c** shows the chromatic distribution of an example kernel in $L^*a^*b^*$ color space. To obtain these
coordinates, we converted the sRGB values of each kernel pixel to $L^*a^*b^*$ using a D65 white point
(X=95.0, Y=100, Z=108.9). The resulting distribution is tightly clustered along the CIE daylight locus,
where natural illuminant colors typically fall [39]. As illustrated in Figure S1c, the environmental
illuminations used in this study exhibit a similar distribution, which directly influences the color of
specular highlights as reflections of incident light. This suggests that the filters exploit this regularity to
help extract specular reflections from object surfaces. To test this, we generated 3,888 new images with
lighting environments in which pixel colors were rotated by +90 degrees in the a^*b^* plane, while L^*
(lightness) remained constant. All other rendering parameters matched the main dataset. As shown in
panel **d**, the chromatic distribution of the resulting kernel also rotated by roughly 90 degrees, confirming
that the kernel's chromatic properties are shaped by the chromatic illumination statistics of the training
environment.
260
As shown in panel **e**, we found that the spatial properties of the bright blob and accompanying ridges
can be represented by a two-dimensional (2D) Gaussian function, a type of receptive field observed as
early as retinal ganglion cells [40] and one-dimensional (1D) oriented Gaussian ridges, respectively.

The 2D Gaussian has five free parameters: amplitude (a_g), x-center coordinate (x_{g0}), y-center coordinate
(y_{g0}), standard deviations along the x-axis (σ_{gx}) and y-axis (σ_{gy}). Each 1D Gaussian ridge has five free
parameters: amplitude (a_{Rk}), x-center coordinate (x_{Rk0}), y-center coordinate (y_{Rk0}), standard deviations
(σ_{Rk}) and orientation (φ_{Rk}), where k represents ridge 1 or 2.
268
Panel **f** shows the fitted parameters for each function across the 24 kernels displayed in panel b,
excluding x_{Rk0} and y_{Rk0}. The 2D Gaussian blobs exhibited high amplitude values (0.5–1.0) and standard
deviations indicating a slight vertical elongation. Among the 24 kernels, 9 were fitted with two ridges.
The amplitudes (a_{Rk}) of these ridges were consistently lower than those of the Gaussian blobs, typically
ranging from 0.2 to 0.3, and σ_{Rk} values were similar between ridges. The orientation parameter (φ_{Rk})
clustered clearly around 45° and 135°. When two ridges were present, they were separated by 90°,
indicating a systematic orientation preference in the filter.
276
To intuitively grasp the filter's selectivity, we examined the top 60 image regions most strongly activating
the single-kernel model. The orientation preference of the kernel is clearly reflected, as many regions
contain diagonal specular highlights. However, it is noteworthy that the kernel also produces strong
responses to circular bright blobs and other highlight shapes, demonstrating that its selectivity is not
limited to oriented features. This highlights the kernel's robust ability to detect a broad range of specular
highlight patterns, from elongated streaks to more compact, blob-like structures.
283
284   We emphasize that the strong orientation selectivity of the kernel is unlikely to be merely an artifact of
285   our training imageset. Oriented specular highlights are frequently observed in everyday materials, as
286   demonstrated by examples taken from the Flickr Material Database (FMD) [41] (see panel **h**). This
287   pattern is thus characteristic of real-world surfaces, not just synthetic images. Further validation of the
288   single-kernel model's performance on real-world photographs is presented below (see **Figure 8**).
289
In summary, the kernels observed within the tiniest CNN are composite filters that encode multiple
fundamental visual features, including luminance and chromatic contrast, orientation, and shape. This
allows them to capture both the presence and geometric structure of specular highlights, supporting
robust extraction of highlights across a range of different geometries. Although such a simple filter was
far from the best of the models we tested for predicting human gloss judgments, it is striking that its
correlation coefficient reaches 75.3 percent of the upper-limit set by inter-observer consistency, yet is
highly interpretable, yielding insights into key features that observers likely rely on to make their gloss
matches.
298
299

Figure 4. Analysis of single-kernel models. a Computational steps of the single-kernel model. The input image is convolved with a 15 × 15 × 3 kernel, the resulting activation map is max-pooled to a single value, and a bias term is applied to produce the gloss prediction. **b** Consistency check across 24 networks trained in cross-validation. Although they were trained on different (but overlapping) datasets with different random weight initializations, all networks developed a similar pattern of kernels, with a bright blob located at various positions, superimposed on straight elongated, diagonally-oriented yellow-black-blue ridges. **c** Analysis of chromatic tuning of the kernel. The sRGB color of each pixel in an example kernel was converted to the $L^*a^*b^*$ color coordinates, and their a^*b^* distribution is shown. We found that kernel colors are closely aligned along the daylight locus, likely reflecting the typical color of specular highlights seen in training images (see example image at the bottom). **d** Chromatic distribution of an emergent kernel from a network trained on a new set of 3,888 images under 90° gamut-rotated environmental illuminations. The kernel clearly adapts to the chromatic statistics of specular highlights present in the training data. **e** Fitting a two-dimensional Gaussian filter and one or two Gaussian ridges to the kernel's spatial intensity distribution. For simplicity, fitting was performed on the luminance image after mean subtraction. The bright blob region is well approximated by the 2D Gaussian filter. The diagonal stripe pattern is captured by a 1D Gaussian ridge, and the residual component is also shown. The difference in scale between the two components is indicated by the colorbars. **f.** Distribution of the fitted parameters for the 2D Gaussian components and ridges across the 24 kernels shown in panel b.

319 **g.** The top 60 image regions that most strongly activated the example kernel. While diverse specular
320 reflection geometries are captured, there is a clear preference for diagonal highlights. **h.** Examples of
321 oriented specular highlights detected by the example kernel in real material photographs.
322
323 **Analysis of three-layer models.** Panel **a** illustrates the computation flow of the example three-layer
324 model with 64 kernels. The model processes the input image through multiple layers of convolution,
325 pooling, normalization, and non-linear activation, ultimately using linear regression to predict the gloss
326 value. The leftmost images show nine example kernels in the first convolutional layer, which show
327 Gaussian blobs with different spatial scales, contrasts, color tunings, and polarities.
328
We examined this three-layer network, the best of all the models we tested, to see how glossiness is
coded within the network and how the representation progressively changes over layers. We first
extracted activation maps after each convolutional layer (marked by stars) and aggregated the signals
over the map using max pooling for the first layer and average pooling for the third layer. This resulted
in 64 scalar values per layer, which were plotted on a 2-dimensional plane using t-distributed stochastic
neighbor embedding (t-SNE; panel **b**). For comparison, we performed the same analysis using the raw
pixel values of the input image.
336
Results revealed that in pixel space, objects are primarily clustered by their geometry (not shown here).
In the first layer, object images are already roughly grouped into glossy and matte categories, with some
glossy objects misclassified as matte and vice versa. The second and third layers only slightly refine
this representation. However, the overall representation does not change drastically from the first layer.
This suggests that the first convolutional layer most strongly contributes to gloss judgments, with
subsequent layers making small adjustments to improve predictions, perhaps by separating overall
luminance level (e.g., albedo) and glossiness, as well as arranging objects by their shape characteristics
(note the bulbous-spiky organisation [42, 43] in the layer 3 representation)
345
346 Taken together with the analysis of the single-kernel network, these observations suggest our gloss
347 judgments can be predicted well by a combination of well-known, low-level filtering mechanisms within
348 the visual system.
349

Figure 5. Analysis of a three-layer model with 64 kernels trained on images with human labels.
a In the first convolutional layer, the input image was convolved by a set of 64 kernels, 9 of which (7 by 7 pixels) we visualize on the left side. In the second and third convolutional layer, activation maps from the first convolutional layer were further convolved by the two sets of kernels subsequently and average pooling was taken for each of 64 activation maps from the third convolutional layer. Between convolutional layers 2 and 3, batch normalization and/or ReLU are applied. There were skip connections between layers to bypass the information if beneficial. Then the pooled features were used as input for a linear regression model, which predicted gloss level. **b** Example of internal representation in a three-layer network model. We fed the network images it had not seen during training and extracted activation maps from each convolutional layer. The maps were aggregated by max pooling (layers 1 and 2) or average pooling (final layer) over the entire map, then used as inputs for t-distributed stochastic neighbor embedding (t-SNE) to project onto a two-dimensional plane. The bottom two figures show

363 representations from the first and third convolutional layers. For comparison, we also performed t-SNE
364 analysis on the same images in the pixel space (leftmost plot), where matte and glossy objects are not
365 separated and objects are primarily clustered by shape (not shown here).
366

367 **Evaluation of model generalization across supplementary image sets.**
368 We conducted four additional generalization tests using (i) object images with manipulated specular
369 highlights, (ii) an additional set of 42,120 rendered images, (iii) real-world photographs, and (iv) textured
370 object images, as detailed below.
371

Gloss illusion caused by manipulated specular highlights. Surprisingly, given the simplicity of the
internal representations, we also found that the human-like networks predicted a number of known gloss
effects [8, 44, 45] as shown in **Figure 6**. For instance, the networks accurately anticipated the decrease
in perceived glossiness when the specular highlight is rotated (panel **a**), moved horizontally (panel **b**),
when surface roughness increases (panel **c**), and when the underlying specular reflectance weakens
(panel **d**). The decrease was steeper for the three-layer models compared to the one-layer model.
Notably, these modified images were not included in the training dataset, demonstrating the models'
ability to generalize beyond the training range. It is straightforward that perceived gloss decreases when
surface roughness or specular contrast decreases, as this correlates with a decrease in local intensity
of the specular component. It is somewhat surprising, however, that even a single-kernel model can
predict the decrease in gloss level for rotation and translations. The spatial pattern of the receptive field
suggests the filter utilizes the local spatial intensity profile of the specular highlight region. For a typical
glossy object, this local intensity profile likely arises from the combined contribution of both specular
highlights and diffuse components when they are correctly aligned [46]. When only the specular
component shifts from the original position independently of the diffuse component, this geometrical
regularity collapses, leading to a decrease in the filter output. However, we recognize this is not always
the case. Out of 3,888 test images, 790 images (about 20%) actually showed an overall increase in
gloss levels due to highlight rotation. Nevertheless, it is intriguing that simple models can detect
seemingly complex inconsistencies of highlight position. It suggests that while there is surely some
degree of coupling between mid-level representations of shape, material and lighting [5, 9,12,13, 46-
48], a significant portion of gloss perception may actually be accounted for by more basic mechanisms.

Figure 6. Evaluation of single-kernel and three-layer network models for three known perceptual effects. The dark blue circles and blue diamonds show model responses for the one-layer model and three-layer models, respectively. **a** Effect of rotating specular structure. The top image shows the original image where no manipulation was applied. The rotation 0 indicates the original image. **b** Effect of horizontally translating specular reflection. The translation 0 indicates the original image. **c** Effect of changing surface roughness level. The surface roughness 0.05 indicates the original image. **d** Effect of changing surface contrast level. The surface roughness 100% indicates the original image. Contrast was manipulated by changing Pellacini's c.

Additional rendered images. Serrano et al. [49] generated 42,120 images from 9 lighting environments (**Figure 7a**), 9 object geometries (panel **b**), and 520 bidirectional reflectance distribution functions. For each image, they collected ratings of various perceptual attributes including glossiness through crowdsourcing, providing an excellent validation set for our models. We tested our single-kernel model and three-layer model with 64 kernels, both trained on all 3,888 images. To prepare the input, we used object masks to exclude non-object regions, filling them with a mid-gray color (sRGB = [127, 127, 127]), and then fed the resulting images into our models to generate gloss predictions.

Panel **c** shows Pearson's correlation between the single-kernel model predictions and human gloss ratings. The single-kernel model, despite its minimal architecture, achieves a correlation of 0.63 and 0.64 across lighting environments and shapes, respectively, performing comparably to our own dataset (r = 0.64). In contrast, the three-layer model shown in panel **d**, which outperforms the single-kernel

model on our own data (r = 0.82), shows a correlation of 0.53 and 0.65. Similarly, the deep ResNet-52 gloss model by Serrano et al., when applied to our 3,888 images, shows a weak correlation of 0.29 (not shown), highlighting a curious trade-off between model complexity and generalization. Clearly human perception does not suffer from such generalisation limits, yet this likely relates to our vastly larger visual diets.

Figure 7. Results of a generalization test using Serrano dataset. a, b Nine lighting environments and shapes used to render images. **c** Pearson's correlation coefficient between the model response of the single-kernel model trained by all 3,888 images and perceptual rating measured in crowd-source experiment [49] for each lighting and shape. Each bar shows the correlation across 4,680 images. **d** The case for a three-layer model trained by all 3,888 images, which shows slightly lower generalization ability compared to the single-kernel model.

Real-world photographs.

We further evaluated generalization to real-world photographs of everyday materials using 183 images compiled from multiple sources, including the Flickr Material Database (FMD) [41], visuo-haptic studies by Baumgartner et al. [50, 51], an fMRI study by Jacobs et al. [52], and a perceptual material classification study by Wiebel et al. [53]. The dataset covers a diverse range of material categories, such as metal, glass, plastic, fur and leather, fluids, and fabric. All images had been consistently judged as either matte or glossy by all eight observers in a previous study [11].

Figure 8a shows the predictions of the single-kernel model and the three-layer model, plotted on the x-axis and y-axis, respectively. The classification accuracy, based on the threshold indicated by the dashed lines in the plot, was 91.9% for the single-kernel model (d' = 2.79) and 71.9% for the three-layer model (d' = 1.08). This again demonstrates the superior generalization performance of the simpler model. Notably, the misclassified images lie close to the category boundary, with a mean distance of 0.0079, which corresponds to approximately 7 % of the model's prediction range.

This result is intriguing in that even a simple filter-based model can capture the diverse patterns of

specular reflection found across different real-world materials (panel **b**) with high accuracy, while

remaining robust against being misled by the texture patterns present in many matte images (panel **c**).

Interestingly, the three-layer model, which performed well on our own dataset, showed reduced

accuracy in this test. This suggests that even relatively shallow models, such as those with only three

layers, can be prone to overfitting, pointing to the often-overlooked value of using simpler computational

strategies.

Together with the results on manipulated specular highlights and Serrano's 42,120 images, this

validation shows that the single-kernel model achieves an effective balance between simplicity and

performance, making it a strong candidate for gloss computation across diverse image sets.

Figure 8. Generalization performance on real-world material photographs. **a** Scatter plot

comparing model responses for each image labeled as either matte or glossy based on behavioral data

from a previous study [11]. The x-axis represents the single-kernel model, and the y-axis represents

the three-layer model. Green and pink circles show images consistently rated as matte and glossy,

respectively, by all eight observers. The dotted lines indicate the optimal category boundaries that

achieve the highest classification accuracies: 91.9% for the single-kernel model and 71.9% for the

three-layer model. **b** Example images correctly classified as glossy by the single-kernel model. **c**

Example images correctly classified as matte.

Textured objects. In our main image set, all object surfaces had uniform base colors. However, real-

world surfaces can sometimes have high-contrast textures, which our filter-based model may

misinterpret as specular reflections.

Thus, as shown in **Figure 9a**, we tested the single-kernel model's response to objects from a subset of

the original dataset (1,296 images) with added surface textures. When the texture had the same

luminance as the surrounding body color and introduced only chromatic contrast, the predicted gloss

level remained stable (panel **b**, left). However, when the texture's luminance was increased to 1.5 times

that of the body color, the model often misinterpreted it as a specular highlight, leading to a systematic

increase in predicted glossiness (panel **b**, right).

However, if textured objects had been included in our training data, the model could have learned to

suppress responses to texture and become more selectively tuned to specular highlights. To test this,

we retrained the model using paired images from the original and textured datasets assigning the same

gloss labels to each pair, and examined the filters that emerged (panel **c**, upper). In the two-kernel

model, one excitatory kernel similar to the original emerged, along with a second inhibitory kernel (panel

c, lower). The model predicts glossiness as a weighted sum of the responses from these two filters.

Notably, the inhibitory kernel showed strong selectivity to texture (Figure 9d), effectively functioning as

a texture-canceling filter that counteracts misclassification driven by texture contrast. We found that the

two-filter network suppressed the systematic increase in predicted glossiness for textured surfaces

(panel **e**). Our high-contrast textures included sharp spatial variations in both chromaticity and

luminance. The colorful suppression kernel that emerged is specifically tuned to respond strongly to

spatial chromatic variation, such as that found in textures. In contrast, specular highlights typically

appear as smooth luminance gradients in low-saturation yellow-blue or white regions, which elicit only

a weak response from this kernel. The network improves its selectivity for specular highlights by

offsetting texture-driven activation in the excitatory kernel with the inhibitory kernel's response.

Thus, while texture poses a challenge, our results suggest that this issue can be mitigated by

incorporating additional filters and exposure to textured objects in the training set. Naturally, if the

texture exhibits spatial structures that more closely resemble specular highlights, suppression becomes

more difficult—not only for our model, but likely for any model, and potentially even for human

observers. Nonetheless, this illustrates how a data-driven approach can uncover a concrete

computational solution to a long-standing challenge in the field. In real-world viewing, motion cues

further assist in distinguishing surface texture from specular highlights by revealing differences in their

relative motion patterns [54].

Figure 9. Evaluation of model responses to textured objects. a Two types of textures were applied to a subset of the original dataset: low- and high-contrast textures, each with either equal luminance or 1.5 times higher luminance relative to the body color. **b** Model responses to the original image set (x-axis) versus the textured image set (y-axis), shown separately for low-contrast textures (left) and high-contrast textures (right). **c** A model with two kernels was trained on a new dataset containing both uniform and textured objects. The model convolves the input image with two kernels, applies max pooling to the activation maps, and predicts glossiness by taking a weighted sum of the max-pooled values plus a bias term. **d** Example activation maps of the inhibitory kernel. The cyan square highlighted by an arrow indicates the image region that produced the highest activation in the double-kernel model. **e** The double-kernel model reduces the increase in predicted glossiness caused by texture patterning.

Discussion

This study is inspired by a fundamental question in behavioral neuroscience: what neural computations enable material perception from highly variable sensory inputs across different contexts? We address this by leveraging CNNs to replicate human-like judgments of object gloss from images and explore the internal computational strategies of these networks, in a data-driven, hypothesis-neutral approach that contrasts with traditional cue-based methods. The motivation is that tasks such as material perception might be too complex for intuitive identification of underlying mechanisms, whereas CNNs excel at finding statistical regularities in training datasets. We used this tool to guide our search for biologically plausible computations that underlie human gloss perception.

This approach identified a clear contrast between the computational demands required to develop human-like CNNs and physical ground-truth CNNs, suggesting that human gloss judgments from object

images likely do not involve sophisticated inverse optics computations. This notion has been suggested
by others [1], but what is new here is the identification of specific filters and the depth of computation
required to predict human gloss perception and physical reflectance parameters. In particular, the
effectiveness of a filter with a bright blob and ridges is intriguing, directly supporting the idea that gloss
perception relies, to a nontrivial extent, on relatively simple image features, as suggested by Motoyoshi
et al. [6]. Much as cone photoreceptors provide foundational signals for color perception and other
visual functions, bright blob and ridge detectors may serve as a key component of gloss perception,
and perhaps other distal perceptual attributes too [55-57]. While we certainly are not suggesting that
the human gloss perception is based *exclusively* on low-level filters, it is intriguing that when a large
population is asked to judge gloss under diverse conditions, they resort to strategies that can be well
approximated by such measurements. We would caution against interpreting our findings as suggesting
the human visual system contains 'gloss detector' receptive fields resembling the kernels that emerged
in our models. Representations in the human visual system have to underpin far more tasks than just
gloss perception. Instead, we see the emerging kernels as a tool to identify the relevant *image*
information that observers draw on to perform the gloss match task. Yet the combination of controllable
computer-generated training sets, large-scale human perceptual data, and deep learning with small,
interpretable models seems like a promising avenue for unravelling the computations underlying other
'mid-level' visual inferences.
544
One key aspect of our approach is the use of large-N psychophysical experiments. Since numerous
distal factors such as shape, lighting, and reflectance properties are involved in generating a single
object image, covering a wide range of stimulus space—ideally, comparable to the diversity of natural
images—is critical to capture visual behaviors with sufficient resolution. Conversely, when we used only
a small number of shapes or lighting environments, we found that perceptual gloss judgments correlated
well with physical ground-truth in many cases (**Figures S2 and S3**). This correlation is not inherent to
our perceptual judgment but is influenced by the stimulus set. Recent studies have made significant
efforts to collect extensive human judgment data across a large number of images [58, 59]. To
understand visual mechanisms, we must account for both successes and errors in perception, and
large-scale measurement helps capture these diagnostic behavioral patterns. Although careful data
curation and validation are essential to this approach, it offers a powerful data-driven framework for
exploring the complex mechanisms underlying human perception and behavior. Combining our
approach with unsupervised learning can help reduce the cost of collecting labeled images [60-62].
558
Our validation results highlight the generalization challenges inherent to complex models. While deep
learning has addressed many problems in visual perception, it remains uncertain whether such models
capture the mechanisms underlying human vision [63]. A key strength of our approach is its capacity to
systematically explore specific filter designs and their combinations, enabling a more comprehensive
search through the space of low-level computations. Our results may provide insight into long-standing
questions in vision science, specifically whether complex perceptual systems like material perception
originate from low-level visual processes [64].

One outcome of this study is the creation of a publicly available database containing 3,888 images.

While many databases exist for labeled objects, those focusing on material properties are less common.

Each image is annotated with full stimulus parameters, including physical ground-truth labels and

perceptual labels from at least three different observers. We expect this dataset to be useful in multiple

disciplines such as vision science, cognitive neuroscience, and computer vision. In addition, the

availability of perceptual labels is useful for industrial applications, such as predicting the perceived

glossiness of car paint, enhancing the presentation of jewelry, or achieving specific visual impressions

in artworks.

To conclude, our study has provided a novel data-driven perspective on the computational mechanisms

in human gloss judgements using large-scale perceptual measurement and CNN-based modeling. We

found a relatively simple and biologically plausible linear model that predicts the idiosyncrasies of

human gloss constancy, but also several established perceptual gloss effects beyond the training range,

as well as gloss perception for real-world object photographs.

Materials and Methods

Stimuli

The detailed procedure for stimulus generation is explained in our previous study [65]. All reference and

test images were generated using the physically-based rendering software Mitsuba v 0.6 [66]. All

images contained a single object at the center of the scene, to which we applied diffuse and specular

reflectance using the Ward reflectance model [36, 37] with a fixed surface roughness level of 0.05. The

specular reflectance value was randomly sampled from zero (matte) to 0.0999 (highly glossy). We

applied image-based environmental illumination to the scene, with the camera set at the same height

as the object and pointing directly at it. The asymmetric gloss matching task required a matching object

whose physical specular reflectance parameter could be continuously adjusted by observers. For this,

we used Pellacini's c [38], a perceptually-linear characterization of Ward specular reflectance

associated with the object to render a set of images, instead of making changes in image space. A total

of 3,888 test images were generated by combining 36 lighting environments, 36 object shapes, and 3

random viewpoints. For each test image, a random body color was used, with fixed lightness at 50, and

random chroma and hue between 8-26 and 0-360 degrees in the L*a*b* perceptually-uniform color

space [67], respectively. A full list of object shapes and environmental illuminations is shown in **Figure**

S1.

To generate the textured object images used for validation, we selected 12 object geometries with

smooth, continuous surfaces suitable for texture mapping from the original set of 36 geometries. We

then created 1,296 images by applying achromatic blob textures with either the same luminance as the

body color or 1.5 times higher (Figure 9a).

All images were generated at 512×512 pixels in XYZ format. After converting the raw XYZ image to a

linear monitor RGB format, each image was normalized using the 97th percentile pixel value. These

scaled linear RGB images were then gamma-corrected using the standard sRGB formula. This spatial

resolution of 512×512 pixels was used for the psychophysical experiment while this was reduced to

224×224 pixels for the network's inputs to shorten the training time.

For the online experiment, a total of 3,888 images were divided into 54 independent sets. Twelve

common images were added to each set to evaluate the consistency of observer responses. At least

three observers were recruited for each set. For two of these sets, we recruited 21 and 23 observers to

validate the online data with a lab-based experiment (see **SI**).

Experiment

The main experiment was conducted online using PsychoPy (version 2022.1.4) [68] and hosted on an

online platform Pavlovia. Observers were recruited via Prolific and compensated 12 euros per hour.

Before participating, they downloaded and read an information sheet explaining the procedure and

signed a digital consent form. A validation experiment was conducted in the laboratory (detailed in SI,

Figure S4).

Observers and Ethics

A total of 467 observers participated in the online experiment, with data from 295 analyzed (see

exclusion criteria in a later section). Observers had normal or corrected-to-normal visual acuity and

normal color vision (self-report). Their age ranged from 19 to 65 (mean 41.4; S.D. 12.4). The observer

group comprised 159 females and 136 males. Informed consent forms were in English, so only English-

speaking observers were recruited for the online experiment. No language criteria were applied for the

laboratory experiment. No observer was informed of the experiment's purpose. The study was approved

by the local ethics committee at Justus Liebig University Giessen, following the Helsinki Declaration

(sixth revision, 2008).

Procedure and task

Observers were instructed to turn off the room lights and sit at arm's length from the display during the

experiment. Observers viewed the screen binocularly. Before the experiment, observers completed a

size calibration using a bank card [69] to ensure the stimulus image appeared at the correct size. In

each trial, a test image was shown on the left and a reference image on the right. The task of observers

was to move a slider under the reference image to match its perceived glossiness with the test image.

The reference image stayed the same in all parameters except Pellacini's c, while the test image varied

between trials in terms of shape, color, viewpoint and lighting environment (asymmetric matching

[70,71]). After completing the size calibration, the observers received on-screen instructions: "Adjust

the gloss level of the right 'reference' object using the slider until it matches the gloss level of the left

'target' object." The slider's starting position was randomized for each trial, excluding edge values,

which were reserved for catch trials used to detect autoresponders. The first three trials were practice

rounds to help observers get used to the task. After practice, they adapted for one minute to a uniform

white screen (sRGB = [127, 127, 127]). Each observer was randomly assigned to one of 54 image sets,

each containing a set comprising 84 images (72 unique to the set and 12 common images). Each

session consisted of 84 trials, and all observers completed 2 sessions, totaling 168 trials. To detect

autoresponders, each session included a catch trial in which no stimuli were shown; instead, a text

screen instructed observers to move the slider to the left edge before proceeding to the next trial. The

order of stimulus presentation was randomized. Median time across 295 observers to complete the

experiment was 13.7 mins (4.89 sec per trial).

Exclusion criteria

For quality control, we set two exclusion criteria. First, observers who failed either of the catch trials

were excluded. Second, observers who completed each trial too quickly were excluded; this was

indicated by a mean response time shorter than the mean minus two standard deviations of laboratory-

based experiments. We continued our experiments until at least 3 observers passed these criteria for

each image set. This exclusion process resulted in 295 out of 467 observers (63.2%) being included in

the final analysis.

Computational Modeling

Fitting of single-kernel models.

To quantitatively describe the spatial structure of the filters developed in network models, we modeled

them as the sum of a two-dimensional (2-D) Gaussian $G(x,y)$ and multiple oriented ridge functions $R_k(x,$

$y)$ as defined in equation (1):

$$M(x,y) = G(x,y) + \sum_{k=1}^{n} R_k(x,y)$$

667 $\qquad\qquad$ (1)

668 The 2-D axis-aligned Gaussian function was defined as equation (2):

$$G(x,y) = a \cdot \exp\left(-\left[\frac{(x-x_0)^2}{2\sigma_x^2} + \frac{(y-y_0)^2}{2\sigma_y^2}\right]\right)$$

669 $\qquad\qquad$ (2)

670 where a is amplitude, (x_0,y_0) is the center, and σ_x, σ_y are the standard deviations along each axis.

672 Each oriented ridge was defined as equation (3):

$$R_k(x,y) = a_{R_k} \cdot \exp\left(-\frac{[(x-x_{0,R_k})\sin\varphi_{R_k} - (y-y_{0,R_k})\cos\varphi_{R_k}]^2}{2\sigma_{R_k}^2}\right)$$

$\qquad\qquad$ (3)

where a_{Rk} is amplitude, $(x_{0,Rk}, y_{0,Rk})$ is the ridge center, σ_{Rk} is the width perpendicular to the ridge,

and φ_{Rk} is the orientation. The index k takes values 1 and 2.

We converted each kernel from sRGB to XYZ and used the Y (luminance) channel for fitting to simplify

the analysis. Optimization was performed using MATLAB's lsqcurvefit function. The functions were fitted

sequentially: first the primary ridge, then the secondary ridge, and finally the 2D Gaussian. If a second

ridge component was not identified through the optimization, only a single ridge was fitted to the kernel.

Luminance statistics models.

The Y (luminance) channel from raw XYZ images was extracted. We implemented nine models to

determine glossiness using the mean, median, standard deviation (std.), skewness, kurtosis, first

quartile (Q1), third quartile (Q3), and the minimum and maximum pixel luminance values within the

object region of each test image, excluding the surrounding region from these calculations.

Specular reflection models.

We computed three metrics—coverage, sharpness, and contrast—derived from the specular reflection

component of each image, inspired by an influential prior study [12]. Each model involved free

parameters, which were optimized to align most closely with human gloss judgments. For each test

image, we rendered a version of the object containing only the specular component by setting the diffuse

reflectance to zero, and converted the resulting image to a luminance image. To extract direct specular

reflections and exclude secondary and higher-order interreflections, we selected only those pixels

whose intensities exceeded a certain percentage ($k\%$) of the maximum intensity in the specular image.

The value of k was selected from the set {0, 1, 3, 5, 10, 20, 40}. Based on this thresholded highlight

image, we computed the three metrics. Coverage was defined as the proportion of the object's region

occupied by highlights. Sharpness was calculated using spatial convolution to detect regions with rapid

luminance changes [72]. For contrast, rather than using the raw highlight image, we applied a Gaussian

band-pass filter to decompose the image into seven spatial frequency sub-bands, with cutoff ranges of

1.5–3.0, 3.0–6.0, 6.0–12.0, 12.0–24.0, 24.0–48.0, 48.0–96.0, and 96.0–192.0 cycles per image. This

approach follows previous findings suggesting that certain frequency channels contribute more

significantly to gloss perception [73]. We then computed the root-mean-square contrast, equivalent to

the standard deviation of pixel intensities, for each sub-band image, as well as for an aggregated image

across all frequency bands. Unlike coverage and sharpness, which each depend on a single parameter,

the sub-band contrast metric includes two free parameters: the pixel intensity threshold k and the spatial

frequency band. These parameters were optimized separately for each metric to determine the values

that best correlated with human gloss judgments.

Manipulation of the pattern of specular reflection

First, for each of the 3,888 test images, the diffuse and specular components were rendered separately.

We then manipulated the specular reflection in three different ways (rotation, translation and roughness)

before combining it with the diffuse component. The strength of the specular reflectance was set to a

maximum value for all images (0.0999 in the Ward reflectance model, equivalent to 0.1487 in Pellacini's

c) to clearly observe the effect of highlight manipulation.

For rotated specular reflection, we rotated the specular component from -90 to +90 degrees in 30-

degree steps, using the image center as the rotation axis. For translation, we shifted the specular

component horizontally from -30 to 30 pixels in 10-pixel steps relative to the image size of 224×224

pixels. After these manipulations, a mask was applied to remove any specular reflection extending

beyond the object region. For surface roughness, we rendered the specular component with varying

roughness values of ε (0.001), 0.05, 0.10, 0.15, and 0.20. For surface contrast, we adjusted the strength

of the specular component between 0, 0.0372, 0.0743, 0.1115, and 0.1487 in Pellacini's c unit. Then,

we combined these manipulated specular images with the diffuse image.

All manipulated and original images were input to CNNs, and the proportional change in predicted gloss

level relative to the non-manipulated image was computed.

Network architectures

We used a ResNet architecture for two reasons. First, it has proven effective in solving object

recognition tasks [74], which are highly relevant to our visual task. Second, it consists of several stages,

each with a flexible number of convolutional layers, allowing us to systematically adjust architectural

complexity.

The one-layer model consists of a single convolutional layer, followed by max pooling and a regression

layer to predict continuous gloss values. It does not include non-linear operations such as rectified linear

unit (ReLU) or batch normalization. The three-layer model begins with a convolutional layer followed by

max pooling, then two additional convolutional layers, batch normalization, and ReLU with a skip

connection that allows the input to bypass the signals from the previous layer if beneficial. This is

followed by average pooling, and finally, a regression layer.

In the first convolutional layer, the kernel size was 15 × 15 pixels for the one-layer model and 7 × 7

pixels for the three-layer model, determined through preliminary exploration of suitable architectures.

The number of kernels varied between 1, 2, 4, and 9 for the one-layer model, and 9, 16, 32, and 64 for

the three-layer model. Networks were trained for 90 epochs until reaching a performance plateau,

starting with an initial learning rate of 0.01, which decreased by a factor of 10 every 30 epochs. We

used the Adam optimizer and mean absolute error as the evaluation function. Model training was

conducted on a DGX A100 system (four NVIDIA A100 GPUs each with 80GB video memory, Dual AMD

Rome 7742 CPU, 128 cores total, 2.25 GHz base) running Ubuntu 22.04 LTS. While each individual

model was lightweight, the system enabled efficient parallel training of many networks required for

cross-validation.

Training and validation procedure

Our evaluation procedure consists of two independent sets of cross-validation. In the first set, networks

were trained on 33 lighting environments (3,564 images) and tested on 3 novel lighting environments

(324 images). This process was repeated 12 times until all lighting environments were used as test

sets. In the second set, networks were trained on 33 shapes (3,564 images) and tested on the 3 novel

lighting environments (324 images). Again, this was repeated 12 times until all shapes were used as

test sets. Thus, each network architecture underwent 24 unique training and testing pairs, resulting in

24 trained models. The correlation coefficient reported in Figure 3 is the average value across these 24

networks, each computed from 324 test images. Luminance statistics models and specular reflection

models were evaluated in the same way for consistency, although no fitting was involved for the
luminance statistics models.

For each training session, the 3,564 images were augmented to 320,760 images through horizontal
flipping and random size cropping, ensuring that 80% of the object region was preserved. This
conservative augmentation approach was chosen because certain manipulations, such as vertical
flipping, may disrupt the geometrical regularity in natural environments, potentially affecting the
representativeness of gloss judgments.

Acknowledgments

The authors thank Ana Serrano for providing the associated data for the rendered image dataset, and
Matteo Toscani for providing the real-world photographs used to validate our models. We also thank
Annika Zentel for her assistance with data collection in the laboratory-based experiment. TM was
supported by a Sir Henry Wellcome Postdoctoral Fellowship from Wellcome Trust (218657/Z/19/Z).
This research was also supported by "The Adaptive Mind," funded by the Excellence Program of the
Hessian Ministry of Higher Education, Science, Research, by the DFG SFB-TRR-135 "Cardinal
Mechanisms of Perception" (project No. 222641018, TPs C1 and C2), and by a Marsden Fast Start
Grant to KS from the Royal Society of New Zealand (project MFP-UOA2109), and European Research
Council Advanced Grant Color3.0 (project number 884116) to KRG and European Research Council
Advanced Grant STUFF (project number 101098225) to RWF. For the purpose of open access, the
author has applied a CC BY public copyright license to any Author Accepted Manuscript version arising
from this submission.

Data availability

784 We will upload all 3,888 images and corresponding observer responses used in this study to Zenodo
785 upon acceptance. Each image will be provided in ".png" format using the sRGB color space, along
786 with: (i) full rendering parameters, including object shape, physical diffuse and specular reflectance,
787 viewpoint, object rotation angle, and environmental illumination; and (ii) perceptual labels from at least
788 three observers, provided in a tabulated ".csv" file.

Code availability

791 We will publicly release the MATLAB code used for analysis and for reproducing the figures presented
792 in this study upon acceptance.

References

795 1. Fleming RW. Material perception. Annu Rev Vis Sci. 2017;3:365-388.

796 2. Nishida S. Image statistics for material perception. Curr Opin Behav Sci. 2019;30:94-
797 99.

798 3. Chadwick A, Kentridge R. The perception of gloss: A review. Vision Res.
799 2015;109(Part B):221-235.

4. Blake A, Bülthoff H. Does the brain know the physics of specular reflection? Nature. 1990 Jan;343(6254):165-168.

5. Anderson BL. Mid-level vision. Curr Biol. 2020;30(3):R105–R109.

6. Motoyoshi I, et al. Image statistics and the perception of surface qualities. Nature. 2007;447:206-209.

7. Sharan L, et al. Image statistics for surface reflectance perception. J Opt Soc Am A. 2008;25:846-865.

8. Anderson BL, Kim J. Image statistics do not explain the perception of gloss and lightness. J Vis. 2009;9:10.

9. Kim J, Anderson BL. Image statistics and the perception of surface gloss and lightness. J Vis. 2010;10:3.

10. Sawayama M, Nishida SY. Material and shape perception based on two types of intensity gradient information. PLoS Comput Biol. 2018;14:e1006061.

11. Wiebel C, Toscani M, Gegenfurtner KR. Statistical correlates of perceived gloss in natural images. Vis Res. 2015;115B:175-187.

12. Marlow PJ, Kim J, Anderson BL. The perception and misperception of specular surface reflectance. Curr Biol. 2012;22:1909-1913.

13. Marlow PJ, Anderson BL. Generative constraints on image cues for perceived gloss. J Vis. 2013;13:2.

14. Fleming RW, Dror RO, Adelson EH. Real-world illumination and the perception of surface reflectance properties. J Vis. 2003;3:347-368.

15. Zhang F, de Ridder H, Barla P, Pont S. A systematic approach to testing and predicting light-material interactions. J Vis. 2019;19:11.

16. Zhang F, de Ridder H, Barla P, Pont S. Effects of light map orientation and shape on the visual perception of canonical materials. J Vis. 2020;20:13.

17. Gigilashvili D, Islam AJ. The role of shape in modeling gloss. Proc 30th Color Imaging Conf. 2022;271-276.

18. Gigilashvili D, Thomas J, Pedersen M, Hardeberg JY. On the appearance of objects and materials: Qualitative analysis of experimental observations. J Int Colour Assoc. (JAIC) 2021;27:26-55.

19. Vangorp P, Laurijssen J, Dutre P. The influence of shape on the perception of material reflectance. ACM Trans Graph. 2007;26:77.

20. Chen B, Wang C, Piovarči M, Seidel HP, Didyk P, Myszkowski K, Serrano A. The effect of geometry and illumination on appearance perception of different material categories. Vis Comput. 2021;37:2975–2987.

21. Wendt G, Faul F, Ekroll V, Mausfeld R. Disparity, motion, and color information improve gloss constancy performance. J Vis. 2010;10:7.

22. Adams WJ, Kucukoglu G, Landy MS, Mantiuk RK. Naturally glossy: Gloss perception, illumination statistics, and tone mapping. J Vis. 2018;18:4.

839   23. Honson V, et al. Effects of shape, roughness and gloss on the perceived reflectance
840   of colored surfaces. Front Psychol. 2020;11:485.

841   24. Cheeseman JR, Ferwerda J, Morimoto T, Fleming R. Gloss discrimination: Towards
842   an image-based perceptual model. PsyArXiv. 2024.
843   https://doi.org/10.31234/osf.io/anx4q

844   25. Wijntjes MWA, Pont SC. Illusory gloss on Lambertian surfaces. J Vis. 2010;10(9):13.

845   26. Radonjić A, Cottaris NP, Brainard DH. The relative contribution of color and material
846   in object selection. PLoS Comput Biol. 2019;15(4):e1006950.

847   27. Norman JF, Todd JT, Phillips F. Effects of illumination on the categorization of shiny
848   materials. J Vis. 2020;20(5):2.

849   28. Ho YX, Landy MS, Maloney LT. Conjoint measurement of gloss and surface texture.
850   Psychol Sci. 2008;19(2):196–204.

851   29. Doerschner K, Maloney LT, Boyaci H. Perceived glossiness in high dynamic range
852   scenes. J Vis. 2010;10(9):11.

853   30. Prokott KE, Tamura H, Fleming RW. Gloss perception: Searching for a deep neural
854   network that behaves like humans. J Vis. 2021;21:14.

855   31. Tamura H, Prokott KE, Fleming RW. Distinguishing mirror from glass: A "big data"
856   approach to material perception. J Vis. 2022;22:4.

857   32. Goncalves NR, Welchman AE. "What Not" detectors help the brain see in depth. Curr
858   Biol. 2017;27:1403-1412.e8.

859   33. Rideaux R, Welchman AE. But still it moves: Static image statistics underlie how we
860   see motion. J Neurosci. 2020;40:2538-2552.

861   34. Rideaux R, Welchman AE. Exploring and explaining properties of motion processing
862   in biological brains using a neural network. J Vis. 2021;21:11.

863   35. Anderson BL, Storrs KR, Fleming RW (2023). Where do the hypotheses come from?
864   Data-driven learning in science and the brain. Behavioral and Brain Sciences. 46:
865   e386.

866   36. Ward GJ. Measuring and modeling anisotropic reflection. Proc 19th Annu Conf
867   Comput Graph Interact Tech. 1992;265-272.

868   37. Geisler-Moroder D, Dür A. A new ward BRDF model with bounded albedo. Comput
869   Graph Forum. 2010;29(4):1391–1398.

870   38. Pellacini F, Ferwerda JA, Greenberg DP. Toward a psychophysically-based light
871   reflection model for image synthesis. Proc 27th Annu Conf Comput Graph Interact
872   Tech (SIGGRAPH '00). 2000;55-64.

873   39. Judd DB, et al. (1964) Spectral distribution of typical daylight as a function of
874   correlated color temperature. J Opt Soc Am 54:1031–1040.

875   40. Young RA. The Gaussian derivative model for spatial vision: I. Retinal mechanisms.
876   Spatial Vis. 1987;2(4):273–293.

877   41. Sharan L, Rosenholtz R, Adelson EH (2014) Accuracy and speed of material
878   categorization in real-world images. J Vis 14(9):Article 12.

42. Bao, P., She, L., McGill, M., & Tsao, D. Y. (2020). A map of object space in primate
inferotemporal cortex. Nature, 583(7814), 103-108.
43. Morgenstern, Y., Hartmann, F., Schmidt, F., Tiedemann, H., Prokott, E., Maiello, G., &
Fleming, R. W. (2021). An image-computable model of human visual shape similarity.
PLoS computational biology, 17(6), e1008981.
44. Beck, J., & Prazdny, S. (1981). Highlights and the perception of glossiness.
Perception & Psychophysics.
45. Todd, J. T., Norman, J. F., & Mingolla, E. (2004). Lightness constancy in the presence
of specular highlights. Psychological Science, 15(1), 33-39.
46. Marlow P, Kim J, Anderson BL. The role of brightness and orientation congruence in
the perception of surface gloss. J Vis. 2011;11(9):16. doi:10.1167/11.9.16.
47. Marlow PJ, Todorović D, Anderson BL. Coupled computations of three-dimensional
shape and material. Curr Biol. 2015;25(6):R221–R222.
48. Anderson BL, Marlow PJ. Perceiving the shape and material properties of 3D
surfaces. Trends Cogn Sci. 2023;27(1):98–110.
49. Serrano A, et al. The effect of shape and illumination on material perception: Model
and applications. ACM Trans Graph. 2021;40:4.
50. Baumgartner E, Wiebel CB, Gegenfurtner KR. Visual and haptic representations of
material properties. Multisens Res. 2013;26(5):429-55.
51. Baumgartner E, Wiebel CB, Gegenfurtner KR. A comparison of haptic material
perception in blind and sighted individuals. Vision Res. 2015 Oct;115(Pt B):238-45.
52. Jacobs RH, Baumgartner E, Gegenfurtner KR. The representation of material
categories in the brain. Front Psychol. 2014 Mar 12;5:146.
53. Wiebel CB, Valsecchi M, Gegenfurtner KR. The speed and accuracy of material
recognition in natural images. Atten Percept Psychophys. 2013 Jul;75(5):954-66.
54. Doerschner K, Fleming RW, Yilmaz O, Schrater PR, Hartung B, Kersten D. Visual
motion and the perception of surface material. Curr Biol. 2011 Dec 6;21(23):2010-6.
55. Lowe DG. Distinctive image features from scale-invariant keypoints. Int J Comput Vis.
2004;60(2):91–110.
56. Akbarinia A, Parraga CA. Colour constancy beyond the classical receptive field. IEEE
Trans Pattern Anal Mach Intell. 2017;39(4):830–845.
57. Akbarinia A, Parraga CA. Feedback and surround modulated boundary detection. Int
J Comput Vis. 2018;126(6):583–603.
58. Sawayama M, Dobashi Y, Makoto M, Hosokawa K, Koumura T, Saarela TP,
Olkkonen M, Nishida S. Visual discrimination of optical material properties: A large-
scale study. J Vis. 2022;22:17.
59. Lagunas M, Malpica S, Serrano A, Garces E, Gutierrez D, and Masia B. A similarity
measure for material appearance. ACM Trans Graph. 2019;38:Article 135.
60. Storrs KR, Anderson BL, Fleming RW. Unsupervised learning predicts human
perception and misperception of gloss. Nat Hum Behav. 2021;5:1402-1417.

61. Guerrero-Viu J, Subias JD, Serrano A, Storrs KR, Fleming RW, Masia B and Gutierrez D. Predicting Perceived Gloss: Do Weak Labels Suffice?. Comput Graph Forum. 2024;43:e15037.

62. Liao C, Sawayama M, Xiao B. Unsupervised learning reveals interpretable latent representations for translucency perception. PLoS Comput Biol. 2023;19(2):e1010878.

63. Bowers, J. S., Malhotra, G., Dujmović, M., Llera Montero, M., Tsvetkov, C., Biscione, V., … Blything, R. (2023). Deep problems with neural network models of human vision. Behavioral and Brain Sciences, 46, e385.

64. Adelson EH. On seeing stuff: the perception of materials by humans and machines. Proc SPIE 4299, Human Vision and Electronic Imaging VI. 2001;1-12.

65. Morimoto T, Akbarinia A, Storrs K, et al. Color and gloss constancy under diverse lighting environments. J Vis. 2023;23(7):8, 1–25.

66. Jakob W. Mitsuba: Physically based renderer. Retrieved from https://www.mitsuba-renderer.org/ (2010).

67. Carter EC, Schanda J, Hirschler R, Jost S, Luo MR, Melgosa M, Ohno Y, Pointer MR, Rich DC, Viénot F, Whitehead L, Wold JH. CIE 015:2018 Colorimetry. 4th ed. 2018.

68. Peirce JW, Gray JR, Simpson S, et al. PsychoPy2: experiments in behavior made easy. Behav Res Methods. 2019. https://doi.org/10.3758/s13428-018-01193-y

69. Li Q, Joo SJ, Yeatman JD, et al. Controlling for Participants' Viewing Distance in Large-Scale, Psychophysical Online Experiments Using a Virtual Chinrest. Sci Rep. 2020;10:904. https://doi.org/10.1038/s41598-019-57204-1

70. Arend L, Reeves A. Simultaneous color constancy. J Opt Soc Am A. 1986;3:1743-1751.

71. Brainard DH, Wandell BA. Asymmetric color matching: How color appearance depends on the illuminant. J Opt Soc Am A. 1992;9:1433-1448.

72. Vu CT, Phan TD, Chandler DM. S3: A spectral and spatial measure of local perceived sharpness in natural images. IEEE Trans Image Process. 2012;21:934-945.

73. Boyadzhiev I, Bala K, Paris S, Adelson E. Band-sifting decomposition for image-based material editing. ACM Trans Graph. 2015;34:1-16.

74. He K, Zhang X, Ren S, Sun J. Deep Residual Learning for Image Recognition. Proc IEEE Conf Comput Vis Pattern Recognit (CVPR). 2016;770-778. doi: 10.1109/CVPR.2016.90.

Supplementary Information

Object geometries and lighting environments.

To generate test images, we selected 36 three-dimensional meshes of everyday objects from Evermotion (https://evermotion.org) and 36 image-based illumination maps from various databases, including the Debevec database [1], Southampton-York Natural Scenes [2], and Freebies (https://hdrmaps.com/freebies/; accessed May 2021), as shown in panels A and B of **Figure S1**. For a reference image, we chose an Uffizi light probe, as in a previous study [3], and generated the geometry of a bumpy sphere using the 3D modeling software Blender (version 2.79b). These lightings and shapes were selected to cover a wide range of characteristics, with different complexities, which we thought is key to identifying unique human behaviors that decorrelate from physical reflectances. Panel C shows the chromatic distribution of each lighting environment. There is a tendency for pixel colors to spread along the vertical blue-yellow axis, known as a daylight locus [4].

Figure S1. Object geometries, lighting environments and their chromatic statistics. a, b Object geometries and lighting environments selected to generate test images. They were selected to be as diverse as possible. **c** Chromatic distribution of each lighting environment in L*a*b* color space. We randomly sampled 10% of pixels to reflect the density of distribution. The black cross symbols show mean chromaticity and black curve shows daylight locus. The white point was set to D65. The layout is the same as panel b.

Observer settings for each lighting environment and shape.

Figures S2 and **S3** show mean observer settings compared to the physical ground-truth, grouped by each lighting environment and each shape, respectively. Each data point represents one image, with each plot containing 108 images (36 lighting environments or 36 shapes × 3 viewpoints). The aim of this analysis is to determine whether a specific lighting environment or shape consistently induces high or low gloss levels. For lighting environments, although correlations between human settings and physical ground-truth vary between 0.40 and 0.68, observer setting patterns were generally similar, with no noteworthy trends. In contrast, there are clearer differences across shapes. Shapes ranked high tend to be round, presumably because they generate highly visible specular reflections, while flat objects ranked low tend to produce low perceived gloss. This is visually intuitive, as specular highlights for the flat objects are widely spread on their surfaces and not easily visible. Overall, these findings show that when focusing on a particular shape or lighting environment, perceived gloss somewhat correlates with the underlying physical specular reflectance. It is the use of diverse shapes and lighting environments that decorrelates human responses from the physical ground-truth labels in our behavioural data.

Figure S2. Average observer settings compared to physical ground-truth for images grouped by lighting environment. All images for each specific lighting environment were included in each panel, resulting in 108 data points (36 shapes × 3 viewpoints). The upper right value shows Pearson's correlation coefficient, used to rank each panel. The vertical error bar represents ±S.E. across observers.

Figure S3. Average observer settings for images grouped by object shapes. Each plot contains 108 images (36 lighting environments × 3 viewpoints).

Laboratory experiment

Motivation. Our main experiment was conducted online to effectively collect a large number of perceptual labels. However, there are general concerns with online experiments [5], such as the lack of monitor calibration, absence of an experimenter, and lack of verbal communication, which may affect task comprehension. To assess the quality of the online data, we conducted a validation experiment in a controlled laboratory environment as follows.

Observers and ethics. Twenty observers (13 females and 7 males) were recruited. Observers' age
ranged from 18 to 36 and mean ± standard deviation was 23.4±4.06 years. All observers had normal
or corrected-to-normal visual acuity and normal color vision, screened using Ishihara Pseudo-
isochromatic color plates [6]. Informed consent was obtained before the experiment. Before the
experiment, the experimenter explained the task of the experiment to the observers. All procedures
were approved by the local ethics committee at Justus Liebig University Giessen.
1022
1023 **Test images.** We used two of the image sets that had been shown in the main experiment to 21 and
1024 23 online observers. Each set contained 72 images, excluding 12 common images. All lab-based
1025 observers judged all images from both sets.
1026
Apparatus. Images were displayed on a 24-inch LCD monitor (ColorEdge CG2420, 1920×1200 pixels,
frame rate 60 Hz; EIZO, Ishikawa, Japan) that allows for 10 bits per color channel (red, green, and
blue). Gamma correction and spectral calibration were performed using measurements from a
spectroradiometer (CS-2000; KONICA MINOLTA, Inc., Tokyo, Japan). The code to run the experiment
was prepared in MATLAB using custom functions as well as functions provided in PsychToolbox-3 [7].
A chin rest was used to maintain the viewing distance.
1033
Procedures. The experiment was conducted in a dark room. Observers placed their forehead and chin
on the chinrest, to keep the viewing distance constant at 49 cm from the LCD monitor. Observers viewed
the monitor binocularly. In each session observers completed 144 trials (72×2 images), and all
observers completed 2 sessions, totaling 288 trials. The images were presented in a random order.
Otherwise, the experimental procedure and the task of the observer were identical to the online
experiment. Median response time was 6.18 sec per trial across — longer than in the online experiment
(4.89 sec per trial).
1041
Results. Panel **a** in **Figure S4** compares observer settings between laboratory and online experiments,
where each data point represents the average across all observers. In both image sets, we found a
near-perfect correlation. These very high correlations likely result from averaging data from a large
number of observers. We also created a histogram of correlations for all possible pairs of individual
observers (panel **b**). In this plot, we observed that the median correlation was higher than 0.8, which is
not dramatically lower than the within-observer correlation shown in panel **c**. In summary, these
comparisons demonstrate excellent consistency between online and laboratory-based experiments,
suggesting that online data collection may be feasible for certain research questions and visual tasks.
1050

1051

1052

1053 **Figure S4. Comparison between online and offline results. a** Laboratory experiment data plotted
1054 against online experiment data, with each data point representing the average across observers. **b**
1055 Histogram of correlations across individual observers between laboratory and online experiments. The
1056 median is shown in magenta. **c** Histogram of within-observer correlations computed between sessions
1057 1 and 2 over 144 images.

1058

CNN-based models that takes the surrounding context information into account
We removed the surrounding context from each image, set background pixels to mid-gray
(R=G=B=128), and used the resulting images to train the CNN-based models presented in the main
text. This decision was made because our shallow network model lacks the computational capacity to
effectively segregate the background from the object while also predicting gloss levels. However, the
surrounding context might contain useful information that could help CNNs better predict human
responses. To explore this possibility, we added an additional stream to our existing models,
incorporating information from the surrounding region into the regression layer at the end to determine
gloss levels.

1068

Figure S5 illustrates the architectures of such models and their performance in predicting human
responses for the one-layer model (panel **a**) and the three-layer model (panel **b**). The results indicate
that including context information in the network stream results in no performance improvement for both
models (two-tailed paired t-test; $t(23)=0.572$, $p = 0.573$ for one-layer model; $t(23)=0.55$, $p = 0.588$ for
three-layer model), suggesting that the surrounding context does not provide significant additional
information. It is possible that useful cues are present but not captured by the networks. Nevertheless,
this observation aligns with past empirical evidence that observers do not rely on surrounding contextual
information when judging surface glossiness [8].

1077

1078

1079

Figure S5. Testing whether surrounding context provides useful information for predicting

human responses. a The left network illustrates the architecture of a one-layer model with an additional

stream for processing surrounding context. The circles indicate the correlation coefficient with human

responses, averaged across 24 networks when no surrounding context was used, as reported in the

main text (Figure 3). The diamonds show the results when surrounding context was included. **b** The

same analysis for a three-layer network. Lines indicate performance changes for each of 24 networks.

In both cases, including surrounding context information resulted in little performance improvement.

1087

1088 **SI References**

1089

1. Debevec P (1998) Rendering synthetic objects into real scenes: Bridging traditional
and image-based graphics with global illumination and high dynamic range
photography. SIGGRAPH 98 Proc 25th Annu Conf Comput Graph Interact Tech 189–
198.
2. Adams WJ, et al. (2016) The Southampton-York Natural Scenes (SYNS) dataset:
Statistics of surface attitude. Sci Rep 6:35805.
3. Morimoto T, Akbarinia A, Storrs K, Cheeseman JR, Smithson HE, Gegenfurtner KR,
Fleming RW (2023) Color and gloss constancy under diverse lighting environments. J
Vis 23(7):8, 1–25.
4. Judd DB, et al. (1964) Spectral distribution of typical daylight as a function of
correlated color temperature. J Opt Soc Am 54:1031–1040.
5. Rodd JM (2024) Moving experimental psychology online: How to obtain high quality
data when we can't see our participants. J Mem Lang 134:Article 104472.
6. Ishihara S (1973) The series of plates designed as a test for colour-blindness
(Kanehara Shuppan Co. Ltd., Tokyo, Japan).
7. Brainard DH. (1997) The Psychophysics Toolbox. Spat Vis. 10(4):433-6.
8. Motoyoshi I, Matoba H (2012) Variability in constancy of the perceived surface
reflectance across different illumination statistics. Vis Res 53:30–39.

1108