Multiscale Probabilistic Modeling: A Bayesian Approach to Augment Mechanistic Models of Cell Signaling with Machine-Learning Predictions of Binding Affinity

Holly A. Huber[a] and Stacey D. Finley[a,b,c]

[a]Department of Biomedical Engineering, University of Southern California, Los Angeles, CA 90089, USA

[b]Department of Quantitative and Computational Biology, University of Southern California, Los Angeles, CA 90089, USA.

[c]Mork Family Department of Chemical Engineering and Materials Science, University of Southern California, Los Angeles, CA 90089, USA.

Corresponding Author: Stacey D. Finley, email - sfinley@usc.edu

Abstract

Computational models in systems biology are often underdetermined—that is, there is little data

relative to the complexity and size of the model. The lack of data is primarily due to limits in our

ability to observe specific biological systems and restricts the utility of computational models.

However, there are a growing number of experimental databases in biology. While these

databases provide more observations, they often do not have observations that match the

system of interest exactly. For example, database measurements might be collected at different

experimental conditions or on a different scale compared to the system of interest. Here, we

investigate what information can be gleaned from generalizing databases across these

differences in the context of modeling a specific system – cell signaling. Ultimately, our goal is to

better determine models of specific systems, thereby increasing their utility. To do this, we

propose a novel, multiscale, probabilistic framework. We use this framework to integrate

measurements of protein structure from the Protein Data Bank and measurements of amino

acid sequence from the Universal Protein Resource into the parameter inference of cell

signaling models. Then, we quantify exactly what information is gained from these

measurements when modeling cell signaling. We choose to investigate the utility of these

databases in the context of dynamic cell signaling models because experimental measurements

of the variables of interest, protein dynamics, are still quite limited. We find that we can

successfully integrate measurements from these databases to significantly improve parameter

estimation of signaling models. The impact of sequence and structure measurements on model

predictions depends on the sensitivity of the prediction to perturbations in the parameter values.

Overall, this study demonstrates that measurements of protein structure and amino acid

sequence can be leveraged to better inform parameters in models of cell signaling.

Author Summary

Computational models of cell signaling have provided mechanistic insights into complex

biological systems, including in physiological and disease settings. Accurate and predictive

modeling critically depends on the precise estimation of model parameters, which is often

hindered by the limited availability of experimental data. In this study, we present a novel

multiscale probabilistic inference framework that broadens the scope of data types that can be

leveraged for parameter estimation for models of cell signaling. The framework integrates a

machine learning pipeline with a generalizable parameter inference approach, enabling the use

of experimental data across scales. Specifically, we demonstrate that incorporating protein

amino acid sequence and 3D structural data enhances parameter estimation compared to

traditional measurements such as protein concentrations over time. Improving parameter

estimation increases the robustness and applicability of cell signaling models. Ultimately, our

framework facilitates use of a broader range of data and supports the development of predictive

computational models that increase our understanding of cell signaling.

1 Introduction

The application of computational modeling to biological systems has generated a substantial surge in discoveries and insights into these systems; however, especially as systems become more complex, accurately determining computational models remains challenging (1). For example, it can be challenging to parameterize systems biology models, as we often do not have direct measurements of model parameters. Instead, parameters must be inferred using noisy, partial observations of the system of interest. For instance, a system of ordinary differential equations (ODEs) may be used to model intracellular signaling (2). Such mechanistic models are useful, having been applied to optimize CAR-T cell therapies or elucidate control mechanisms of cellular responses (3,4). However, we rarely have observations of all the model parameters— such as binding affinities or protein shuttling rates. Instead, these parameters must be inferred using observations of the model variables: protein concentrations over time. Timeseries measurements of protein concentrations are often sparse, limited to relative concentrations, and noisy. When such measurements are used for parameter estimation, these limitations can result in significant uncertainty in the model predictions, which limits the applicability of the model (5).

To overcome this limitation, in this work we propose a novel, multiscale, probabilistic modeling framework that expands the experimental measurements that may be integrated into the parameter estimation of cell signaling models. Figure 1 illustrates this framework. We hypothesize that despite differences in scale, measurements of protein structure and amino acid sequence can still facilitate the parameter inference of ODE models of cell signaling. To overcome this difference in scale, our framework includes a user-friendly machine learning (ML) pipeline that predicts binding affinity parameters of cell signaling models using sequence or structure. To

integrate these affinity parameter
predictions into the estimation of signaling
models, our framework also includes a
generalizable Bayesian inference
approach. This probabilistic approach to
parameter estimation allows us to formally
quantify the information gained from
augmenting traditional experimental
measurements for parameter estimation of
cell signaling modes, such as protein
concentration dynamics, with
measurements of sequence and structure.

Figure 1. Multiscale Probabilistic Modeling Framework. Starting with the same range of possible parameter values—prior distribution—for the ODE model of cell signaling, we integrate data from different scales into our Bayesian parameter inference using a ML pipeline. We perform inference using two data sets. One dataset comprises only concentration dynamics. The other comprises concentration dynamics as well as amino acid sequence and protein structure. We may then compare the difference between the plausible parameter values—posterior distribution—with, (a), and without, (b), measurements of sequence and structure.

We use measurements of protein structure
and amino acid sequence to augment our
cell signaling model parameter inference.
While experimental observations are still
limited for the parameters and variables of signaling models, there have been significant
breakthroughs in the ability to measure other biological variables. For example, researchers have
been able to collect many more measurements of protein structure and amino acid sequence.
This has resulted in rich databases such as the Protein Data Bank (PDB) and Universal Protein
Resource (UniProt) (6,7). Thus, we propose augmenting timeseries measurements of protein
concentrations with more plentiful data on sequence and structure.

Our proposed multiscale, probabilistic framework leverages a ML pipeline to integrate
measurements of sequence and structure into the parameter inference of cell signaling models.
Integrating such data into the parameter estimation is non-trivial because the data are not
observations of variables or parameters of the biological system being modeled. Indeed, amino
acid sequences and protein structures are on a different scale than the protein concentrations
modeled in cell signaling. To overcome this challenge, we propose a ML pipeline that predicts the
binding affinity parameters of cell signaling models using sequence and structure. We then
compare these predicted parameters to the model parameters. ML models have been leveraged
to similarly predict the parameters of models of cellular metabolism and steady-state signaling

(8,9) (10). We note that the latter study on steady state signaling was tested on only one protein

in the system, limiting the generalizability of the results. Excitingly, ours is the first such approach

tested on dynamic signaling models. Furthermore, we aim to increase the generalizability of our

results by presenting an expanded sample size.

Ultimately, we want to use our proposed framework to evaluate how much information is gained

from adding sequence and structure measurements to our signaling model parameter inference.

Despite interest in generalizing large datasets using ML models, there are a limited number of

studies quantifying how much information is being gained from augmenting measurements

traditionally used to calibrate systems biology models. For example, only recently has the limited

applicability of the ML model used to predict parameters of cellular metabolism models outside of

the ML model's training data set been revealed (11). To fill this important gap, our proposed

framework also comprises a generalizable Bayesian inference approach.

Bayesian inference is an established means to quantify the information gained from data. For

example, one particularly relevant study used it to quantify the information gained from absolute

measurements in the context of cell signaling models, which typically only leverage relative

measurements for parameter inference (12). Importantly, Bayesian inference characterizes the

posterior distribution, which is the distribution of plausible model parameters given a particular

dataset. Inference begins by defining a prior distribution, the distribution of plausible model

parameters given prior information. For example, the prior might formalize the fact that physical

parameters can only be positive. The inference approach then proceeds by incorporating

experimental datasets. To quantify the information gained from a particular dataset, one can

compare the distribution of plausible parameter values before and after integrating data using

statistical distance metrics. One common distance metric used to quantify the difference between

distributions is Kullback Leibler (KL) divergence (13). The more the posterior distribution changes,

the larger the KL divergence becomes, indicating that more information is gained from the data.

KL divergence has been applied in experimental design and hypothesis generation (14–16). Here,

we use it to quantify the information gained from incorporating experimental observations of

sequence or structure into the parameter inference of cell signaling models.

Overall, we are proposing a novel, multiscale, probabilistic modeling framework that enables data

integration across scales and quantifies the benefit of this integration (Figure 1). We use an ML

pipeline to integrate multiscale data (amino acid sequence and protein structure) into the

probabilistic, Bayesian parameter inference problem of ODE models of intracellular signaling. This

probabilistic inference allows us to quantify the information gained from augmenting parameter

inference with sequence and structure.

We test our approach on two, well characterized ODE models of cell signaling: Epidermal Growth

Factor Receptor (EGFR) and G-Protein Coupled Receptor (GPCR) signaling. Not only are these

models well-established; they are also biologically significant. In the case of EGFR signaling, this

model represents dynamics upstream of the most well-studied pathway in cell signaling: MAPK

(17). In the second case, modeling GPCR signaling is important as GPCR's are considered a

prime drug target due to their ubiquity and targetability. In fact, around a third of drugs approved

by the U.S. Food and Drug Administration (FDA) target this protein (18).

To understand what information is gained from using sequence or structure in the parameter

inference of GPCR and EGFR signaling, we compare the results of two parameter inference

approaches. In what we will refer to as the "baseline approach", only the published data reported

for the EGFR or GPCR model is used to infer model parameters. In the "augmented approach",

the reported data is used together with data from PDB or UniProt. Data from PDB and UniProt is

integrated using our multiscale probabilistic framework. Throughout the paper, we refer to these

two datasets as y_{BASE} and y_{AUG}. We ultimately compare the predictions and posterior inferred

using y_{AUG} to the predictions and posterior inferred using y_{BASE}. We perform this comparison

using KL divergence, an information theoretic distance enabled by our probabilistic framework, to

quantify the information gained from augmenting the baseline data. Ultimately, we answer the

question of what information can be gained from protein structure and amino acid sequence in

the context of dynamic models of cell signaling.

2 Approach and Results

2.1 Machine Learning K_D Predictor Pipeline

146 To leverage the large quantities of data on amino sequence and protein structure in the context

147 of cell signaling models, we must translate the information in a sequence or structure to a scale

148 that is meaningful for cell signaling—that is, on the scale of protein concentrations. Further, this

149 translation approach should be easy to use to complement existing modeling approaches for cell

150 signaling. We developed a ML pipeline for this task (Figure 2).

Figure 2. ML Pipeline to predict K_D. K_D is predicted using an SVM regression model, PPI-Affinity. PPI-Affinity needs the complex structure as an input. If the structure exists, it may be extracted from PDB. If it does not exist, the structure may instead be predicted using AlphaFold 3. AlphaFold 3 only needs amino acid sequences, which are typically available. The predicted K_D is the same K_D that characterizes reversible, bimolecular binding reactions comprising cell signaling models.

Upon reviewing the literature, we found that there exist several ML models that translate the

information in an amino acid sequence and/or structure to a scale that is meaningful for cell

signaling (19–22). Specifically, there are several ML models that predict protein binding affinity,

K_D, in units of concentration, from structure or sequence. We can then relate this predicted K_D to

the parameters of the ODE model, which are the unbinding (k_b) and binding (k_f) rates governing

the reaction, by using the definition of K_D: the ratio of the unbinding rate to the binding rate. These

ML models are generally limited to bimolecular, reversible binding reactions. However, this is not

a limitation in the context of cell signaling models, which are often comprised of such reactions.

This is because even when the product of the reaction contains more than two proteins, the

process usually involves a series of bimolecular reactions (23).

We found two ML models with convenient webservers for making K_D predictions: Prodigy and

PPI-Affinity (19,24). We moved forward with PPI-Affinity, a support vector machine (SVM)

regression model, as it shows modest improvements on Prodigy's performance. Further, it

performs comparably to more complicated K_D predictors, like those based on deep learning

models (19). PPI-Affinity requires the structure of the bound protein complex as an input; however,

only a fraction of experimentally available protein structures are complexes. Instead, most

structures available are for monomer proteins. Thus, we sought an alternative input to PPI-Affinity

to use in cases where the protein structure is not available.

Excitingly, AlphaFold (AF3), the latest iteration of the Nobel-prize winning, deep learning model

AlphaFold, is designed to predict the structures of biomolecular interactions, including protein

complexes (25). Although AF3 needs amino acid sequences of the binding partners to predict this

structure, the amino acid sequence of a given protein of an intracellular signaling network is often

known. AF3 is also hosted on a webserver, making predictions straightforward.

Altogether, the compatibility between signaling models and ML models, recent breakthroughs in

predicting the structure of biomolecular interactions, and attention towards the useability of ML

models enabled us to chain together existing ML models into one, user-friendly pipeline for

incorporating amino acid sequence and protein structure into cell signaling models (Figure 2).

2.2 Test Case on Uninformative Prior

Before incorporating predictions from our ML pipeline into the parameter inference, we first tested

its ability to accurately predict K_D for the ten binding reactions present in the ODE test cases. For

each of the ten binding reactions, we predicted K_D using our proposed ML pipeline. We compared

the accuracy of these predictions to an uninformed K_D prediction. To generate this uninformed

prediction, we sampled our Bayesian prior ten times. This prior is log-uniform, and has been used

as an uninformative distribution for

parameter inference in systems biology (12).

Thus, it is well suited for representing an

uninformed K_D prediction. More details

about this prior may be found in the Materials

and Methods.

We calculate the absolute error of the ML

pipeline predictions and prior samples with

respect to the experimentally-derived K_D

values reported in the GPCR and EGFR

publications (26,27). Since we are

concerned with order-of-magnitude changes

in K_D, this error is calculated after a log10

transformation of the ML pipeline prediction

and reported K_D values. Figure 3a shows

how the ML pipeline's performance

compares to the uninformed prediction's

Figure 3. ML Pipeline performance. Cyan, EGFR reaction; pink, GPCR reaction. Circles, K_D predicted using predicted structure; triangles, K_D predicted using experimental structure. (a) Mann-Whitney test comparing absolute error of structure-informed K_D prediction with a random sample from a log-uniform distribution. n=10 binding reactions. *p-value< 0.05. Black horizontal line, sample mean. (b) Spearman's rank correlation between error of K_D prediction and AlphaFold 3 confidence metric, ranking score. n=9 binding reactions that were predicted using a predicted structure, given there was no experimental structure.

performance. The ML pipeline's predictions have a significantly lower absolute error than the uninformed prediction. One of these K_D predictions was made with an experimental structure. Interestingly, it resulted in only the fifth smallest error.

We also tested whether the confidence metrics provided by the ML models that comprise the pipeline were indicative of the pipeline's overall performance. To do this, we calculated the Spearman correlation between the error of the ML pipeline's prediction and each confidence metric—the applicability domain (AD) for PPI-Affinity and the ranking score for AlphaFold 3. More details on these metrics can be found in the Materials and Methods. In the case of AF3, we test on only nine of the binding reactions. This is because for one of the reactions, there is an experimental structure. Thus, there was no need to use AlphaFold to predict the structure. We found that PPI-Affinity's AD metric was not significantly associated with the overall pipeline's

Figure 4. Parameter inference with and without data augmentation. Cyan, EGFR results; pink, GPCR results. All parameter samples were log-transformed prior to analysis. *p-value < 0.05 (a) 90% quantiles of marginal posterior distributions of binding parameters. Light cyan line, prior; medium cyan line, baseline posterior; dark cyan line, augmented posterior; black horizontal line, reported parameter value. (b) KL divergence, in bits, from baseline posterior to augmented posterior. Values are grouped by parameter function. (c) Mean absolute error (M.A.E.) of parameter samples. Mean taken with respect to each posterior distribution. Error calculated with respect to the values reported in the literature. Light cyan points, baseline; dark cyan points, augmented; black horizontal line, median M.A.E.

212 performance (Supplementary Information Figure S1a). However, we did find that AlphaFold 3's

213 ranking score was significantly correlated with the pipeline's performance (Figure 3b).

2.3 Test Case on EGFR and GPCR Signaling: Parameters

Next, we infer the Bayesian posterior distributions of the ODE model parameters using y_{BASE} or

y_{AUG}. Details on this inference can be found in the Materials and Methods. We analyze the

posterior samples after a log10 transformation, as we want to compare order-of-magnitude

changes in the parameters. The quantiles of the resulting marginal posterior distributions of the

unbinding and binding rates are shown in Figure 4a. After checking that both inferences

recapitulate the training data (Supplementary Information Figure S3), we analyzed the resulting

posterior distributions. To measure the information gained from using the augmented dataset

compared to the baseline dataset, we compute the KL divergence from the posterior estimated

with y_{BASE} to the posterior estimated with y_{AUG}. The resulting KL divergences are shown in Figure

4b. Interestingly, the most information is

gained on the rate of protein unbinding.

Figure 4c plots the mean absolute log error

the parameter estimates with and without

data augmentation. Error is calculated with

respect to the experimentally derived

reported values from the published papers.

Excitingly, we see that the information in

y_{AUG} improves the parameter estimates,

especially in the case of the unbinding

rates, where the improvement is

statistically significant.

Figure 5. Performance on test set. (a) Predictions for EGFR test set, the percent of phosphorylated signaling protein SHC from 0-120 seconds. (b) Predictions for GPCR test set, the amount of ligand bound receptor 60 seconds post-stimulation, at different ligand doses, relative to 1000 nM of ligand. Cyan, EGFR; pink, GPCR. Shaded region, 90% quantiles of baseline approach; patterned region, 90% quantiles of augmented approach; dotted line, median prediction of augmented approach; dashed line, median prediction of augmented approach; black dots, experimental data with reported error.

2.4 Test Case on EGFR and GPCR Signaling: Predictions

Figure 5 shows the difference in the

medians and 90% quantiles of the test

predictions generated by sampling the

augmented posterior compared to the

baseline posterior. The test/train split is detailed in the Materials and Methods. While we see some

differences at middle timepoints of the EGFR test set (Figure 5a) and at certain doses of the

GPCR test set (Figure 5b), overall the predictions are not qualitatively different. Further, in the

case of GPCR, at no point does the difference between the medians of the two approaches

become greater than the reported experimental error. In other words, the difference in the

predictions between the two approaches falls within the error of the test set. In the case of EGFR,

the difference between the medians does approach the level of the reported error. However, we

note the unusually small scale of this reported error, which is +/- 1% change in phosphorylated

SHC protein.

When we investigate the medians and 90% quantiles for other outputs besides the test set, we

observe larger differences in the predictions. For example, if we consider the timeseries of

receptor-bound ligand, RL, of GPCR at times other than 60 seconds post-stimulation, we see

greater differences between both the quantiles and medians (Figure 6a). Similarly, several

species comprising EGFR signaling show larger differences in the predicted median and 90

percent quantiles. (Supplementary Information Figure S2).

2.5 Local Sensitivity Analysis

To investigate what leads to changes in some, but not all, ODE model predictions, we conducted

a local perturbation analysis of both the GPCR and EGFR outputs to model parameters. We

perturbed the maximum likelihood parameter values of the baseline case by 5% and used the

local sensitivity at the maximum likelihood to calculate the projected change in an output from this

perturbation. We analyzed 360 outputs for GPCR and 345 outputs for EGFR. These outputs

correspond to five model species at eight timepoints and nine doses and 23 model species at five

timepoints and three doses, respectively for the two test cases. Doses and timepoints match

experimental conditions. However, we exclude timepoint zero because the sensitivity of the initial

concentrations to any parameter is zero. More details about the local sensitivity analysis may be

found in the Materials and Methods section.

Next, we calculated the Spearman correlation between the change in the median prediction of an

output and the sensitivity of that output to perturbations of either unbinding rates, binding rates,

or non-binding parameters. The resulting Spearman coefficients for both EGFR and GPCR are

shown in Figure 6b. Both test cases display a positive and significant correlation with the

 sensitivity to perturbation of unbinding rates. In the case of GPCR, the correlation decreases from

Figure 6 Local sensitivity analysis. (a) GPCR timeseries prediction of ligand-bound receptor, (RL), after 1 nM ligand stimulation. Units, molecules. Shaded region, 90% quantiles of baseline approach; patterned region, 90% quantiles of augmented approach; dotted line, median prediction of augmented approach; dashed line, median prediction of augmented approach. Difference between median prediction of baseline approach and median prediction of augmented approach, *Δ* median, indicated with black arrow. (b) Spearman correlation between *Δ* median and change in output due to 5% perturbation of either unbinding, binding, or non-binding parameters. Cyan, EGFR; pink, GPCR. *p-value< 0.05. n = 345 for EGFR; corresponding to 345 prediction outputs from 3 doses, 23 species, and 5 timepoints. n = 360 for GPCR; corresponding to 360 prediction outputs from 9 doses, 5 species, and 8 timepoints. Doses and timepoints match experimental observations. (c) Scatter plots illustrating relationship between perturbation and the *Δ* median prediction for GPCR. (d) Scatter plots illustrating relationship between perturbation to a type of parameter and the *Δ* median prediction for EGFR.

unbinding to binding to non-binding parameters. This decreasing correlation was clear visually

(Figure 6c). Interestingly, this is the case despite the sensitivity to perturbations being around an

order of magnitude lower for unbinding rates than the other parameter types. In the case of EGFR,

there is a significant positive correlation for all parameter types.

2.6 Investigation of Machine Learning Prediction Confidence

Given the significant correlation between the confidence of the protein structure prediction and

absolute error of the predicted K_D, (Figure 3b) we investigated whether weighing our data

integration by the confidence of the predicted structure could improve our results. More details on

how we implemented this confidence weight can be found in the Materials and Methods.

However, considering the confidence of the protein structure prediction did not significantly

change most of the results of our parameter inference with and without data augmentation

(Supplementary Information Figure S4). As in Figure 4, data augmentation provided the most

information on unbinding rates. y_{AUG} also consistently improved parameter estimates of unbinding

rates compared to y_{BASE}.

Predictions of the test data were similarly unchanged qualitatively (Supplementary Information

Figure S5). As in Figure 5, the predictions with and without data augmentation were similar. One

quantitative difference did emerge. When structure confidence was considered, the difference

between median predictions for the EGFR test data was no longer greater than the reported error.

2.7 Robustness of Results to Changes in Prior Distribution

The prior distribution for each binding parameter is representative of a non-informative

characterization of our knowledge of binding and unbinding rates. However, we also wanted to

explore how the results might change given a more informative or less informative prior. To do

so, we increased or decreased the upper and lower bounds of the prior distributions of all

parameters by one order of magnitude. The results were qualitatively consistent across these

changes in the prior (Supplementary Information Figures S6, S7, S8, and S9). Further, they were

mostly quantitatively consistent as well; only a few quantitative differences emerged. In the case

of the more informative prior, the difference between median predictions for the EGFR test data

was no longer greater than the reported error (Supplementary Information Figure S7a). In the

case of the less informative prior, the information gained from data augmentation was no longer

significantly different between the unbinding and binding rates (Supplementary Information Figure
S8b). This was because more information was gained for binding rates. Interestingly, this did not
result in a corresponding significant change in the mean absolute error for binding rates.

3 Discussion

Computational models of biological systems generate insights beyond what experiments alone
can offer. However, they also present their own challenges. Our work here explores the potential
of augmenting the conventional measurements used for parameter inference in models of
intracellular signaling. Ultimately, our goal was to reduce uncertainty in parameters for better
model determination. To do this, we proposed a multiscale, probabilistic modeling framework. We
first develop a ML pipeline for incorporating the new, multiscale measurements into parameter
inference. Then, we conduct a thorough quantification of the information gained from these new
measurements using a Bayesian framework.

We use amino acid sequence and protein structure measurements from UniProt and PDB,
respectively, to augment the published datasets of two test cases: EGFR and GPCR signaling.
The published datasets include partial, relative measurements of protein concentration and
protein co-localization over time. We chose the EGFR and GPCR models as our test cases
because both are well-established and biologically significant. Taken together, these models offer
a comprehensive test of our approach. For example, EGFR provides a test of a moderately sized
model, while GPCR provides a test of a minimal model. In addition, our ML pipeline can make K_D
predictions using sequence or structure. EGFR provides a test of predictions using sequence,
while GPCR provides a test of predictions using structure.

Predictions from the GPCR and EGFR models occur on the scale of protein concentrations. To
make measurements of sequence and structure applicable to the parameter estimation of these
models, we needed to convert the measurements to the same scale as the GPCR and EGFR
models. Excitingly, we were able to integrate two, user-friendly ML models, PPI-Affinity and
AlphaFold 3, into one pipeline to do this (19,25). This pipeline uses sequence or structure to
predict the binding affinity, K_D, of a given bimolecular, reversible reaction in a cell signaling model.
We find that this ML pipeline outperforms an uninformative prior when predicting the K_D. Thus, it
is appropriate to use when no experimental measurements exist for K_D. Importantly, this pipeline

is generalizable to other dynamic signaling models. It is limited only by access to amino acid

sequence and comprises two, user-friendly web servers.

Interestingly, we found that our pipeline's performance did not significantly benefit from using an

experimental protein complex structure, rather than predicted complex structure, when predicting

K_D. The binding affinity between GPCR and its ligand was predicted using an experimental

structure. However, the error of this prediction was not smaller than all the other K_D prediction

errors. PPI-Affinity was trained using complex structure and K_D pairs from the PDBbind database.

Although the GPCR structure was within the applicability domain of PPI-Affinity, it seems that the

ligand-bound GPCR complex was not included in this training set. This could explain the lack of

improvement we see. We also note the small sample size (n=1) of experimental structures we

tested, which limits the certainty of this result.

We incorporate the K_D's that we predict using the ML pipeline into the likelihood that we use in

our signaling model's parameter inference. We combined this likelihood of the predicted K_D and

the likelihood of the data reported in the original publications to form an augmented dataset, y_{AUG}.

This augmented dataset is ultimately informed by the experimental data on sequence or structure

that we use to predict K_D. We then compared the posteriors and predictions inferred with y_{AUG} to

the posteriors and predictions inferred using only the original data, y_{BASE}, our baseline dataset.

Overall, augmenting our data with data on sequence or structure provides more information on

rates of protein unbinding compared to using only the original data. This was consistent across

both the EGFR test case and GPCR test case. Further, the information gained from sequence or

structure tends to push the unbinding rate towards the rates reported in the original publications.

These reported rates were all taken from experiments, rather than fit to data (26,27). Our results

offer an understanding of when our approach is useful: in the case of underdetermined rates of

protein unbinding. We have confidence in this recommendation of utility, since the results were

consistent even with a more informative or less informative prior distribution. In practice, it is

helpful to use our approach to constrain unbinding rates, as these rates tend to vary over a larger

range than binding rates (23).

When we investigate how predictions change due to the data augmentation, the results are less

clear. We first find that augmenting the baseline data set does not fundamentally change the

predictions of our test data for either test case. However, we do see more substantial changes for

other outputs besides the test data. We thus investigated when predictions inferred with y_{BASE} will

differ from predictions inferred with y_{AUG}. As our approach changes unbinding parameter rates,

intuitively, one would then expect to see differences in predictions for outputs influenced by

unbinding rates. Thus, we investigated the relationship between the local sensitivity of an output

to unbinding rates, binding rates, and non-binding parameters. When we analyzed the GPCR

model, there emerged a striking, significant, positive and linear correlation between changes in a

prediction and the local sensitivity of that prediction to perturbations in the unbinding rate. A

significant positive correlation also emerged with the EGFR model. However, this relationship was

similar across unbinding rates, binding rates, and nonbinding parameters. The different results

from the two test cases may be a function of the complexity of the models. While GPCR is a

minimal model comprised of eight parameters, EGFR is a more moderately sized model

comprised of 50 parameters. It is thus plausible that the relationship between sensitivity and

predictions is impacted by higher-order interactions between parameters in the case of EGFR

(28). These interactions would not be captured by the local sensitivity analysis we conduct here.

There was a significant negative correlation between AlphaFold 3's confidence metric and the

error of the K_D prediction. Based on this, we investigated weighing the likelihood of K_D by

AlphaFold's confidence. Interestingly, incorporating confidence in this way did not significantly

improve or change our results. This could be explained by the fact that we were conservative

when balancing the influence of data augmentation against the influence of the baseline data. For

example, weighing by confidence, which was scaled from [0,1] decreased the influence of

predicted K_D's. An interesting future direction could be investigating other probabilistic

frameworks for incorporating AlphaFold's confidence into parameter inference.

We acknowledge some limitations of our study. We test our ML pipeline on only the 10 binding

reactions reported in our test cases. We could test our pipeline with more reactions from

databases of paired structures and affinities, like PDBbind (29). We chose to focus only on binding

affinities reported in the context of ODE models as these affinities are known to recapitulate

intracellular protein dynamics. Future work could investigate how our ML pipeline could be even

more specialized to binding reactions occurring inside the cell. For example, future work could

take in to account the crowded intra-cellular environment (30). With future improvements to the

ML pipeline in mind, we developed a Bayesian framework for incorporating $\widehat{K}_D$ that can evolve

with our pipeline. For example, we use the error reported by PPI-Affinity to weigh the predicted

K_D likelihood against the likelihood of the conventional experimental measurements. This weight

can be adjusted as that error improves.

There are also ML models that use amino acid sequence to predict binding affinity. In theory, we

could use one of these models instead of our pipeline. However, in practice, we found that there

were no such models hosted on convenient webservers. Even more limiting was the prohibitively

large RAM these models needed to make a prediction for the relatively large signaling protein

complexes we are interested in here (20). We instead focus on more user-friendly models, both

in terms of RAM and implementation.

In conclusion, we have developed a multiscale, probabilistic framework to show that it is viable to

use measurements of amino acid sequence and protein structure to augment parameter inference

in the context of dynamic signaling models. Experimental data on protein structure and amino

acid sequence consistently adds information on the unbinding rate parameters of these signaling

models. This improves parameter estimation and thus model determination. In the future, our

framework has the potential to synergize with breakthroughs in ML and data collection. As ML

models better predict binding affinities, our framework can better constrain signaling models. As

databases of protein structure and amino acid sequence grow, our framework will generalize to

more binding reactions.

4 Materials and Methods

4.1 ODE models of intracellular signaling

We base our investigation on two ODE models: a 50 parameter, 23 species model of EGFR

signaling and an eight parameter, seven species model of GPCR signaling (26,27). In the case

of EGFR signaling, a combination of mass action and Michaelis Menten kinetics is used to

describe cell signaling events such as protein binding and phosphorylation. In the case of GPCR

signaling, mass action kinetics are used to describe cell signaling events such as protein binding,

activation, and degradation. Binding reactions are of particular interest to our study: in the case

of EGFR, 18 parameters characterize nine binding reactions, while in the case of GPCR, two

parameters characterize one binding reaction.

The EGFR model simulates signaling up to 120 seconds, while the GPCR model simulates

signaling up to 600 seconds. We use the reported initial species pools to initialize the model

simulations. We simulate both models with the Julia package *DifferentialEquations.jl* (31).

Because our model parameter values can vary across a wide range, the solution may be stiff.

Thus, we want to choose an ODE solver that can handle stiffness. In addition, we need a solver

that performs well given a higher-than-default accuracy requirement. This is due to the nature of

our state variable: protein concentration. The accuracy of a particular problem is specified by

the absolute and relative tolerances. The relative tolerance (rtol) is set based on the number of

significant digits required for the model output, plus 1 (32,33). We note that the upper bound on

the number of significant digits is between 15 and 17, as this is the maximum number of

significant digits stored by a Float64 type variable, which we use here. In our case, we deem 5

significant digits sufficient for our problem and set the rtol to $10^{-(5+1)}$. The absolute tolerance

(atol) is set based on the absolute value of the model output that may be deemed insignificant

(32,33). In our case, we deem a protein concentration of 10^{-5} nM, or less than 1 protein/cell, as

insignificant. A rtol of 10^{-6} and atol of 10^{-5} are more as stringent as the default tolerances for

most scientific computation, 10^{-3} and 10^{-6}, respectively (32,34). Based on our requirements, we

choose to use *DifferentialEquation.jl*'s QNDF solver, which is equivalent to Matlab's ode15s

solver (34). It is a stiff solver that can handle medium tolerances; thus, it meets our problem's

requirements (32,34,35).

4.2 Data Augmentation

Given an ODE model, $M(\cdot)$, and experimental data, y, our objective is to infer the model

parameters, θ. In this work, we propose augmenting the published data for each system, y_{BASE},

with predicted K_D values, $\widehat{K}_D$. Equation (1) shows how the augmented dataset, y_{AUG} incorporates

additional data into y_{BASE}. We predict K_D using experimental observations of amino acid

sequences from UniProt, y_{FASTA}, or protein structures from PDB, y_{PDB}. y_{BASE} , y_{FASTA} and y_{PDB}

are defined in detail in the subsequent sections.

$$y_{AUG} = \left[y_{BASE}, \widehat{K}_D(y_{PDB} \lor y_{FASTA})\right] \tag{1}$$

446   Throughout the paper, we refer to $\widehat{K}_D(y_{PDB}, y_{FASTA})$ as simply predicted K_D, for conciseness and

447   clarity.

4.3 Experimental measurements of EGFR and GPCR signaling

Both ODE models report experimental measurements of the system of interest. That is, measurements of in vitro protein dynamics, which correspond to the predictions of the ODE models (Figure 7). Note that we are not pooling data across systems, but, for simplicity, we will refer to each data set as y_{BASE}. In the context of the EGFR model, y_{BASE} are measurements of EGFR signaling dynamics (Figure 7a) and in the context of the GPCR model, y_{BASE} are measurements of GPCR signaling dynamics (Figure 7b). We extracted the data and errors with Plot Digitizer (36) .

Eight outputs of EGFR are observed, and we show three of these outputs as a representative sample in Figure 7a. These include the percent of phosphorylated receptor at various ligand dosages as well as the percent of phosphorylation of two intracellular proteins at various ligand

Figure 7. Baseline data set (y_{BASE}). (a) Training data for EGFR parameter inference. (b) Test data for EGFR parameter inference. (c) Training data for GPCR parameter inference. (d) Test data for GPCR parameter inference. Cyan or pink lines, simulations using reported parameter values for EGFR and GPCR, respectively; black markers, reported experimental data points for a particular dose; black error bars, reported standard error.

dosages. Further observations include the percent of an intracellular protein bound with another

intracellular protein and the receptor. The original work does not fit parameters to data, so we

must decide our test/train data split. We choose to reserve measurements of one of the

intracellular proteins, SHC, as our test data. We choose SHC due to its clinical relevance, as this

signaling species has been shown as an important marker in various cancers (37). Furthermore,

the published model predictions do not quantitatively match the experimental measurements of

SHC (37). Ideally, incorporating data on protein structure will improve our predictions for this

experimentally relevant target. Thus, we use the data for SHC to test our model predictions.

Three outputs of GPCR signaling are observed, all of which are shown in Figure 7b. These include

levels of active G-protein at various ligand dosages as well as levels of the ligand-bound receptor

at various ligand dosages. As in the original work, we use the two G-protein data sets as training

data. We reserve data on the bound receptor for testing.

Both models also report binding parameter values derived from experiments or physical bounds,

rather than fit to the data. We use these reported values as a test of the binding parameter values

themselves.

4.4 Experimental measurements from UniProt and PDB Databases

We augment y_{BASE} with amino acid sequences or structures of the proteins that are involved in

binding for each system. Given two proteins that are binding, we first searched for any structures

of the bound complex in PDB. One such structure exists, describing GPCR bound to alpha

pheromone, PDB structure 7QBI (38,39). This structure corresponds to the single binding reaction

in the GPCR model and is formatted as a PDB file. This measurement comprises y_{PDB}.

If no such structure was found, as was the case for the nine EGFR binding reactions, we extracted

the canonical amino acid sequences of the individual proteins, as FASTA files, from UniProt. They

are extracted UniProt sequences P01133 (EGF), P29353 (SHC1), P19174 (PLCG1), Q07889

(SOS1), P62995 (GRB2), and P00533 (EGFR). These measurements comprise y_{FASTA}.

4.5 ML pipeline to predict K_D

Figure 2 provides an overview of the ML pipeline used to predict K_D using amino acid sequence

(y_{FASTA}) or protein structure (y_{PDB}). Given either the sequences of the binding proteins or the

structure of the bound complex, our objective is to predict the binding affinity, K_D, in units of

concentration, for a specific bimolecular binding reaction. We can then relate this predicted K_D to

the parameters of the ODE model, which are the unbinding (k_b) and binding (k_f) rates governing

this reaction, by using the definition of K_D: the ratio of the unbinding rate to the binding rate.

If the bound complex structure is available, we can use a support vector machine (SVM)

regression model, PPI-Affinity, to predict ΔG, the free energy change in kcal/mol (19). PPI-Affinity

uses a feature vector derived from the complex structure to make its prediction of ΔG. We then

convert ΔG to K_D, given a gas constant and absolute temperature (40,41). If the bound complex

is not available, we use a deep-learning model, AlphaFold 3, to predict the complex structure

given the amino acid sequences of the individual proteins. If the complex is comprised of identical

subunits, we extract the smallest subunit (21). We then use this predicted structure as in input to

PPI-Affinity to predict K_D.

Both PPI-Affinity and AlphaFold 3 provide confidence metrics for their predictions. AlphaFold

provides a 'ranking score' for each predicted structure. This score ranges from [-100, 1.5] with -

100 representing low confidence. The ranking score is a function of various features of the protein

structure, such as the fraction of the predicted structure that is disordered and the interface

predicted template modeling (ipTM) score (25). Both the ranking score and ipTM are significantly

correlated with the performance of the ML pipeline (Figure 3b and Supplementary Information

Figure S1b). Conveniently, ipTM is scaled between [0,1], with zero representing low confidence.

We take advantage of this property when considering AlphaFold 3 confidence in our Bayesian

framework, detailed next. In the case of PPI-Affinity, it is noted whether each K_D prediction is

within the applicability domain of the training dataset (19). We found that the accuracy of

predictions was more dependent on ranking score than applicability domain.

4.6 Bayesian inference

The objective of Bayesian inference is to find the posterior distribution, $p(\theta|y)$, which is defined

using Bayes rule:

513
$$p(\theta|y) = \frac{p(y|\theta)p(\theta)}{p(y)}$$

While we often know the likelihood of the data given model parameters, $p(y|\theta)$, and the prior

probability of parameters, $p(\theta)$ we usually do not know the probability of the data $p(y)$. Thus, we

must approximate this distribution knowing $p(\theta|y)$ up to a proportionality constant. While there

are various distribution approximation methods for this problem, the most powerful are Markov-

Chain Monte Carlo (MCMC) approximations, because our initial guess of $p(\theta|y)$ does not need

to be particularly close to the reality. These algorithms generate correlated samples of the

posterior, which we may use to simulate our model.

To generate these samples for our ODE models, we use a Julia implementation of the affine

invariant ensemble MCMC sampler from the package *AffineInvariantMCMC.jl* (42). Like all

MCMC algorithms, the affine-invariant ensemble sampler algorithm constructs a Markov chain

that is used to sample the posterior distribution. To better navigate the parameter space, this

algorithm initializes an ensemble of samplers that propose the next sample based on the location

of another sampler in the ensemble. Because all our parameter values are restricted to positive

values and are often described on a logscale rather than linear scale, we conduct sampling in a

log-transformed parameter space (43,44). Further discussion of the convergence diagnostics of

the samples to the posterior may be found in the Supplementary Information.

4.7 Prior

The prior encodes our assumptions, ideally derived from empirical knowledge, about parameters.

Here, we choose to define independent, log-uniform priors. If the parameter is a binding rate, we

limit the distribution to [10^{-4} nM^{-1}s^{-1}, 100 nM^{-1}s^{-1}]; for an unbinding rate, we limit the distribution to

[10^{-6} s^{-1}, 100 s^{-1}]. This is in line with prior distributions for binding rates in the literature and

database values (12,45). For non-binding parameters, we limit the distributions to +/- two orders

of magnitude above and below the reported parameter value.

4.8 Likelihood

Recall that our augmented data, y, is comprised of two categories, y_{BASE} and predicted K_D, $\widehat{K}_D$.

Both y_{BASE} and $\widehat{K}_D$ represent vectors of data points. For example, in the case of EGFR, y_{BASE} is

a vector of 42 points, corresponding to seven different outputs observed at six timepoints each,

while $\widehat{K}_D$ is a vector of nine predicted affinities for the nine binding reactions of the model.

We assume that each data point is independent from the rest. Next, we assume that a data point

in y_{BASE}, y_{BASE}^{j}, is normally-distributed, given the ODE model prediction and experimental error for

data point j. For example, if j indicates the amount of active G-protein 300 seconds after

stimulation, then we use the model's prediction for active G-protein 300 seconds after stimulation

as the mean of the likelihood distribution and the reported error of this measurement as the

deviation of the likelihood distribution.

Finally, we assume that a data point in $\widehat{K}_D$, $\widehat{K}_D^{k}$, is log-normally distributed, given the ratio of the

unbinding and binding reaction rates for that data point and standard error of the SVM regression

model, PPI-Affinity. For example, if $\widehat{K}_D^{k}$ is the predicted binding affinity of a receptor binding a

ligand, then we will use the rate of receptor ligand unbinding divided by rate of receptor ligand

binding as the mean of the likelihood distribution and the standard error as the deviation. This

standard error is on the scale of one order of magnitude change in $\widehat{K}_D$.

For parts of the investigation, we augment this likelihood term to account for AlphaFold3's

confidence. Specifically, we weigh the log-likelihood of a given $\widehat{K}_D^{k}$ by AlphaFold 3's interface

predicted template modeling (ipTM) score, which represents the confidence of $\widehat{K}_D^{k}$ scaled from

zero to one. This likelihood formulation is known as a power prior. Power priors consist of raising

the likelihood, or a term in the likelihood, to a discounting factor. This controls the amount of

information taken from certain data (46,47). When the log likelihood is evaluated, the product of

likelihoods becomes a sum, and the discount factor(s) become weight(s) on the terms of this sum.

Further details on our likelihood distribution are included in the Supplementary Information.

4.9 Log Transformation of Parameters for Analysis

We note that analyses of the model parameters, and therefore posteriors, are done after a log10-

transformation of the parameter samples. The reason for this is threefold. First, log-transformation

tends to bring biochemical parameters like K_D towards a Normal distribution, which is desirable

for most statistical analyses (43). Second, by comparing order-of-magnitude changes in

parameters, we can compare parameters of different scales. Finally, we are concerned with order-

of-magnitude changes in K_D, as it has been shown that changes less than this do not significantly

influence model predictions (48).

4.10 Quantifying information gained using KL divergence

We use KL divergence between marginal posterior distributions to quantify the information gained

from augmenting our data with experimental measurements of amino acid sequence and protein

structure. Specifically, we calculate the KL divergence from the marginal probability of parameter

θ_i given only the baseline data, $q(\theta_i|y_{BASE})$, to the marginal posteriors estimated with the

augmented data, $p(\theta_i|y_{AUG})$:

576
$$D_{KL}(P||Q) = \int_0^\infty p(\theta_i|y_{AUG}) \log \frac{p(\theta_i|y_{AUG}):}{q(\theta_i|y_{BASE})}$$

Given posterior samples, we use a univariate kernel density estimate and Monte Carlo integration

to approximate a divergence for each marginal posterior (15).

4.11 Sensitivity Analysis and Perturbation Analysis

We compute the local sensitivity of a model prediction with respect to model parameters using

Julia's *ForwardDiff.jl* packages (49–51). Given the local nature of this analysis, parameters are

not log-transformed. *ForwardDiff.jl* approximates the derivative of an output with respect to a

model parameter using forward mode automatic differentiation. We use forward mode automatic

differentiation as it is recommended for ODE's with less than 100 parameters (49). We take the

local sensitivity with respect to the posterior parameter set that maximizes the likelihood of the

baseline training data.

To calculate the projected change in an output due to a 5% change in a particular parameter, we

multiple the local sensitivity by 5% of the maximum likelihood parameters. We take the absolute

value of the resulting perturbation. We then need to down select one perturbation value for each

type of parameter: unbinding, binding, or non-binding. In the case of GPCR, this is trivial for

unbinding and binding rates, as there is only one unbinding parameter and one binding parameter.

For the other cases, GPCR non-binding parameters and all EGFR parameters, we take the

maximum resulting perturbation.

4.12 Statistical Analyses

All statistical analyses, Mann Whitney U test and Spearman rank correlation, were carried out

using Prism 10.4.0 or a combination of Julia's *HypothesisTests.jl* package and *StatsBase.jl*

packages.

4.13 Code Availability

Code is available at: https://github.com/FinleyLabUSC/structure_informed_cell_signaling.

5 Acknowledgements

The authors thank members of the Finley research group for critical comments and suggestions. This work was partially supported by the National Cancer Institute of the National Institutes of Health grant 1U01CA27580 and National Science Foundation award 2410753.

6 References

1. Puniya BL, Verma M, Damiani C, Bakr S, Dräger A. Perspectives on computational modeling of biological systems and the significance of the SysMod community. Zhu S, editor. Bioinforma Adv. 2024 Jan 5;4(1):vbae090.

2. Ingalls BP. Mathematical modeling in systems biology: an introduction. Cambridge, Massachusetts: MIT Press; 2013. 408 p.

3. Nandagopal N, Santat LA, LeBon L, Sprinzak D, Bronner ME, Elowitz MB. Dynamic Ligand Discrimination in the Notch Signaling Pathway. Cell. 2018 Feb 8;172(4):869-880.e19.

4. Rohrs JA, Siegler EL, Wang P, Finley SD. ERK Activation in CAR T Cells Is Amplified by CD28-Mediated Increase in CD3ζ Phosphorylation. iScience [Internet]. 2020 Apr 24 [cited 2025 Mar 27];23(4). Available from: https://www.cell.com/iscience/abstract/S2589-0042(20)30207-8

5. MacLean AL, Rosen Z, Byrne HM, Harrington HA. Parameter-free methods distinguish Wnt pathway models and guide design of experiments. Proc Natl Acad Sci U S A. 2015 Mar 3;112(9):2652–7.

6. UniProt: the Universal Protein Knowledgebase in 2025 | Nucleic Acids Research | Oxford Academic [Internet]. [cited 2025 May 16]. Available from: https://academic.oup.com/nar/article/53/D1/D609/7902999?login=false

7. Berman HM, Westbrook J, Feng Z, Gilliland G, Bhat TN, Weissig H, et al. The Protein Data Bank. Nucleic Acids Res. 2000 Jan 1;28(1):235–42.

8.   Yu H, Deng H, He J, Keasling JD, Luo X. UniKP: a unified framework for the prediction of
enzyme kinetic parameters. Nat Commun. 2023 Dec 11;14(1):8211.

9.   Li F, Yuan L, Lu H, Li G, Chen Y, Engqvist MKM, et al. Deep learning-based kcat prediction
enables improved enzyme-constrained model reconstruction. Nat Catal. 2022
Aug;5(8):662–72.

10. Zaballa VD, Hui EE. Systems-Structure-Based Drug Design [Internet]. arXiv; 2024 [cited
2025 Mar 27]. Available from: http://arxiv.org/abs/2410.10108

11. Kroll A, Lercher MJ. DLKcat cannot predict meaningful kcat values for mutants and
unfamiliar enzymes. Biol Methods Protoc. 2024 Jan 1;9(1):bpae061.

12. Thijssen B, Dijkstra TMH, Heskes T, Wessels LFA. Bayesian data integration for quantifying
the contribution of diverse measurements to parameter estimates. Bioinforma Oxf Engl.
2018 Mar 1;34(5):803–11.

13. Kullback S, Leibler RA. On Information and Sufficiency. Ann Math Stat. 1951 Mar;22(1):79–
86.

14. Lomeli LM, Iniguez A, Tata P, Jena N, Liu ZY, Van Etten R, et al. Optimal experimental
design for mathematical models of haematopoiesis. J R Soc Interface. 2021
Jan;18(174):20200729.

15. Huber HA, Georgia SK, Finley SD. Systematic Bayesian Posterior Analysis Guided by
Kullback-Leibler Divergence Facilitates Hypothesis Formation. J Theor Biol. 2022
Nov;111341.

16. George A, Zuckerman DM. From Average Transient Transporter Currents to Microscopic
Mechanism—A Bayesian Analysis. J Phys Chem B. 2024 Feb 29;128(8):1830–42.

17. Glont M, Arankalle C, Tiwari K, Nguyen TVN, Hermjakob H, Malik-Sheriff RS. BioModels
Parameters: a treasure trove of parameter values from published systems biology models.
Robinson P, editor. Bioinformatics. 2020 Nov 1;36(17):4649–54.

18. Eiger DS, Pham U, Gardner J, Hicks C, Rajagopal S. GPCR systems pharmacology: a
different perspective on the development of biased therapeutics. Am J Physiol - Cell
Physiol. 2022 May 1;322(5):C887–95.

19. Romero-Molina S, Ruiz-Blanco YB, Mieres-Perez J, Harms M, Münch J, Ehrmann M, et al.
PPI-Affinity: A Web Tool for the Prediction and Optimization of Protein–Peptide and Protein–
Protein Binding Affinity. J Proteome Res. 2022 Aug 5;21(8):1829–41.

20. Zheng F, Jiang X, Wen Y, Yang Y, Li M. Systematic investigation of machine learning on
limited data: A study on predicting protein-protein binding strength. Comput Struct
Biotechnol J. 2024 Dec;23:460–72.

21. Zhou Z, Yin Y, Han H, Jia Y, Koh JH, Kong AWK, et al. ProAffinity-GNN: A Novel Approach
to Structure-Based Protein–Protein Binding Affinity Prediction via a Curated Data Set and
Graph Neural Networks. J Chem Inf Model. 2024 Dec 9;64(23):8796–808.

22. Vangone A, Bonvin AM. Contacts-based prediction of binding affinity in protein–protein
complexes. Levitt M, editor. eLife. 2015 Jul 20;4:e07454.

23. Pollard TD. A Guide to Simple and Informative Binding Assays. Mol Biol Cell. 2010
Dec;21(23):4061–7.

24. Xue LC, Rodrigues JP, Kastritis PL, Bonvin AM, Vangone A. PRODIGY: a web server for
predicting the binding affinity of protein–protein complexes. Bioinformatics. 2016 Dec
1;32(23):3676–8.

25. Abramson J, Adler J, Dunger J, Evans R, Green T, Pritzel A, et al. Accurate structure
prediction of biomolecular interactions with AlphaFold 3. Nature [Internet]. 2024 May 8 [cited
2024 May 15]; Available from: https://www.nature.com/articles/s41586-024-07487-w

26. Kholodenko BN, Demin OV, Moehren G, Hoek JB. Quantification of Short Term Signaling by
the Epidermal Growth Factor Receptor. J Biol Chem. 1999 Oct;274(42):30169–81.

27. Yi TM, Kitano H, Simon MI. A quantitative characterization of the yeast heterotrimeric G
protein cycle. Proc Natl Acad Sci. 2003 Sep 16;100(19):10764–9.

28. Monsalve-Bravo GM, Lawson BAJ, Drovandi C, Burrage K, Brown KS, Baker CM, et al.

Analysis of sloppiness in model simulations: Unveiling parameter uncertainty when

mathematical models are fitted to data. Sci Adv. 2022 Sep 23;8(38):eabm5952.

29. Liu Z, Li Y, Han L, Li J, Liu J, Zhao Z, et al. PDB-wide collection of binding data: current

status of the PDBbind database. Bioinformatics. 2015 Feb 1;31(3):405–12.

30. Grassmann G, Miotto M, Desantis F, Di Rienzo L, Tartaglia GG, Pastore A, et al.

Computational Approaches to Predict Protein–Protein Interactions in Crowded Cellular

Environments. Chem Rev. 2024 Apr 10;124(7):3932–77.

31. Rackauckas C, Nie Q. DifferentialEquations.jl – A Performant and Feature-Rich Ecosystem

for Solving Differential Equations in Julia. J Open Res Softw [Internet]. 2017 May 25 [cited

2025 Mar 27];5(1). Available from:

https://openresearchsoftware.metajnl.com/articles/10.5334/jors.151

32. Shampine LF, Gladwell I, Thompson S. Solving ODEs with MATLAB. Cambridge ; New

York: Cambridge University Press; 2003. 263 p.

33. Brenan KE, Campbell SL, Petzold LR. Numerical solution of initial-value problems in

differential-algebraic equations. Philadelphia: Society for Industrial and Applied

Mathematics; 1996. 256 p. (Classics in applied mathematics).

34. Rackauckas C, Nie Q. DifferentialEquations.jl – A Performant and Feature-Rich Ecosystem

for Solving Differential Equations in Julia. J Open Res Softw. 2017 May 25;5(1):15.

35. The MathWorks, Inc. Choose an ODE Solver [Internet]. The MathWorks Inc.; 2023.

Available from: https://www.mathworks.com/help/matlab/math/choose-an-ode-solver.html

36. PlotDigitizer: Version 3.1.6 [Internet]. 2025. Available from: https://plotdigitizer.com

37. Guo Z, Cai C, Zhou K, Song L, Wang X, Chen D, et al. SHC1 serves as a prognostic and

immunological biomarker in clear cell renal cell carcinoma: a comprehensive bioinformatics

and experimental analysis. Sci Rep. 2024 Aug 30;14(1):20150.

38. Velazhahan V, Ma N, Vaidehi N, Tate CG. Activation mechanism of the class D fungal
GPCR dimer Ste2. Nature. 2022 Mar;603(7902):743–8.

39. Velazhahan V, Tate CG. Structure of the GPCR dimer Ste2 in the active-like state bound to
agonist. 2021.

40. Kastritis PL, Moal IH, Hwang H, Weng Z, Bates PA, Bonvin AMJJ, et al. A structure-based
benchmark for protein–protein binding affinity. Protein Sci. 2011 Mar;20(3):482–91.

41. Ruiz-Blanco YB, Paz W, Green J, Marrero-Ponce Y. ProtDCal: A program to compute
general-purpose-numerical descriptors for sequences and 3D-structures of proteins. BMC
Bioinformatics. 2015 May 16;16(1):162.

42. Goodman J, Weare J. Ensemble samplers with affine invariance. Commun Appl Math
Comput Sci. 2010 Jan 31;5(1):65–80.

43. Bar-Even A, Noor E, Savir Y, Liebermeister W, Davidi D, Tawfik DS, et al. The moderately
efficient enzyme: evolutionary and physicochemical trends shaping enzyme parameters.
Biochemistry. 2011 May 31;50(21):4402–10.

44. Lubitz T, Liebermeister W. Parameter balancing: consistent parameter sets for kinetic
metabolic models. Bioinformatics. 2019 Oct 1;35(19):3857–8.

45. Tötsch N, Hoffmann D. Bayesian Data Integration Questions Classic Study on Protease
Self-Digest Kinetics. ACS Omega. 2020 Jun 30;5(25):15162–8.

46. Carvalho LM, Ibrahim JG. On the normalized power prior. Stat Med. 2021;40(24):5251–75.

47. Ibrahim JG, Chen MH, Gwon Y, Chen F. The Power Prior: Theory and Applications. Stat
Med. 2015 Dec 10;34(28):3724–49.

48. Soltis AR, Saucerman JJ. Robustness portraits of diverse biological networks conserved
despite order-of-magnitude parameter uncertainty. Bioinformatics. 2011 Oct
15;27(20):2888–94.

49. Ma Y, Dixit V, Innes MJ, Guo X, Rackauckas C. A Comparison of Automatic Differentiation
and Continuous Sensitivity Analysis for Derivatives of Differential Equation Solutions. In:

2021 IEEE High Performance Extreme Computing Conference (HPEC) [Internet]. Waltham,

MA, USA: IEEE; 2021 [cited 2025 Apr 3]. p. 1–9. Available from:

https://ieeexplore.ieee.org/document/9622796/

50. Revels J, Lubin M, Papamarkou T. Forward-Mode Automatic Differentiation in Julia

[Internet]. arXiv; 2016 [cited 2025 May 15]. Available from: http://arxiv.org/abs/1607.07892

51. Dixit VK, Rackauckas C. GlobalSensitivity.jl: Performant and Parallel Global Sensitivity

Analysis with Julia. J Open Source Softw. 2022 Aug 17;7(76):4561.