Click-qPCR: an ultra-simple tool for interactive qPCR data analysis

Authors

Azusa Kubota[1,*], Atsushi Tajima[1]

[1]Department of Bioinformatics and Genomics, Graduate School of Advanced Preventive Medical

Sciences, Kanazawa University, Kanazawa, Japan

*Corresponding author:

Azusa Kubota, Master of Med. Sci.

Department of Bioinformatics and Genomics, Graduate School of Advanced Preventive Medical

Sciences, Kanazawa University, 13-1 Takara-machi, Kanazawa 920-8640, Japan

Fax: +81-76-234-4249; Phone: +81-76-265-2715

E-mail: kubotaexperiments@gmail.com

Abstract

Real-time quantitative PCR (qPCR) is a pivotal technique for analyzing gene expression and DNA copy number variation. However, the limited availability of easy-to-use software tools remains a significant challenge for experimental biologists without programming expertise. To address this issue, we developed Click-qPCR, a user-friendly, web-based Shiny application that requires no local installation. Click-qPCR streamlines ΔCq and $\Delta\Delta$Cq calculations using user-uploaded CSV data files. The application allows users to dynamically select genes and groups, and to perform Welch's *t*-tests for pairwise comparisons and one-way ANOVA with Dunnett's post-hoc test for multi-group comparisons. Results are immediately visualized as interactive bar plots (mean $\pm$ SD with individual data points) and can be downloaded as publication-quality images, along with statistical summaries. Click-qPCR enables researchers to efficiently process, interpret, and visualize their qPCR data regardless of programming experience, thereby accelerating data processing and improving the accessibility of routine analysis. The Shiny application of Click-qPCR is freely available at https://kubo-azu.shinyapps.io/Click-qPCR/. The source code and user guide for Click-qPCR are openly available on GitHub at https://github.com/kubo-azu/Click-qPCR.

Keywords: Quantitative real-time PCR (qPCR), Gene expression analysis, Copy number variation analysis, Bioinformatics, Shiny web application.

Background

Real-time quantitative PCR (qPCR) is a cornerstone experiment in molecular biology, offering a highly sensitive and widely adopted method for profiling gene expression levels [1]. Its application currently spans diverse research areas, ranging from basic biological investigations to clinical diagnostics. In addition to assessing mRNA expression, relative qPCR is a robust method for detecting DNA copy number variations (CNVs), making it a common and effective technique. Although qPCR encompasses both absolute and relative quantification strategies, relative quantification is more commonly used in practice. This preference largely stems from the inherent complexities and specific requirements of absolute quantification, which often limit its utility to specialized applications, such as virus quantification. The $\Delta\Delta Cq$ method, which is common for relative quantification, robustly compares mRNA transcript levels and CNVs. This comparison relies on a two-step normalization: first against a stable reference gene, and then against a control or calibrator sample [2]. This normalization process is crucial for accurately interpreting biological changes in gene expression and CNV analysis.

Despite its widespread adoption and critical importance for relative gene expression and CNV analysis, the $\Delta\Delta Cq$ method often presents significant hurdles for researchers, particularly those in wet-lab environments, in terms of accessing and utilizing appropriate analysis software. Many existing software solutions are proprietary and commercially licensed, platform-specific, or demand a level of computational proficiency and programming knowledge that can be a barrier for many experimental biologists. For instance, spreadsheet-based qPCR analysis is often error-prone and

time-consuming for multiple genes, while advanced statistical software can be unnecessarily

complex for routine tasks.

Recognizing these limitations, we developed Click-qPCR. Unlike many existing solutions,

which may require local software installation, command-line operations, or a foundational

understanding of programming environments, Click-qPCR is a fully web-based application that

requires no setup beyond a standard internet browser. This tool is designed to provide a

user-friendly, intuitive, and readily accessible web-based platform specifically designed for the

rapid and interactive analysis of qPCR data. Its focus on operational simplicity and immediate

visual feedback makes Click-qPCR ideal for researchers, students, and technicians with limited

bioinformatics experience.

Implementation

The Click-qPCR application was developed using the R programming language [3] and the Shiny

framework [4] to provide an interactive web interface. It relies on several publicly available R

packages from the CRAN repository for its functionality. The application is platform-independent

and can be run on any operating system with a standard R installation. Alternatively, users are

required to have the following packages installed, which can be obtained using install.packages():

-   shiny: Provides the core framework for the interactive web application [4]

-   dplyr: Utilized for data manipulation, filtering, and summarization operations [5]

-   tidyr: Assists in reshaping and tidying datasets for analysis [6]

-    ggplot2: Handles graphical rendering of bar plots and error bars [7]

-    DT: Integrates dynamic, interactive HTML tables for summary output display [8]

-    RColorBrewer: Used for selecting and applying color palettes to the plots [9]

-    fontawesome: Enables the use of 'Font Awesome' icons within the user interface [10]

-    multcomp: For performing the Dunnett's post-hoc test [11]

The application's modular design supports both ΔCq-based relative quantification and $\Delta\Delta$Cq

analysis workflows. All components are reactive and update automatically in response to user input,

enhancing the fluidity and intuitiveness of the analytical experience. The graphical overview of

Click-qPCR is in Figure 1.

Input and user interface

Click-qPCR employs a streamlined, tab-based interface comprising "Preprocessing and ΔCq

Analysis", "$\Delta\Delta$Cq Analysis", "ΔCq ANOVA (Dunnett's post-hoc)", "$\Delta\Delta$Cq ANOVA (Dunnett's

post-hoc)", and "Diagnostics" sections. The analysis process begins on the "Preprocessing and ΔCq

Analysis" tab, where a tidy CSV file containing four essential columns of sample, group, gene, and

Cq is uploaded. A template file and an example dataset are available for download to facilitate

proper formatting. Data loading is implemented as a deliberate two-step process. Upon file selection,

the first 10 rows are displayed in a sidebar preview. The file is formally loaded and validated by

clicking the "Load File" button.

Within the "Preprocessing and ΔCq Analysis" tab, one or more comparisons can be defined by

checking the "Enable multiple reference genes" box. This mode is available to follow the MIQE 2.0

guidelines about the number of reference genes [12]. Reference and target genes are selected via the

drop-down menus, and experimental group pairs are specified for comparison. Additional

comparison sets can be added via the "Add" button and deleted via the "Remove" button. The

"Reset All" button restores the application to its initial state. In the "ΔΔCq Analysis" tab, the

reference gene from the main analysis is retained automatically. A single target gene, a base

(control) group, and one or more treatment groups are selected to compute fold changes relative to

the base group.

For multi-group comparisons, users can navigate to the "ΔCq ANOVA (Dunnett's post-hoc)"

tab. Here, they select a single target gene, a control group, and two or more treatment groups. After

running the analysis, the results are presented as relative expression ($2^{-\Delta Cq}$). The same statistical

results can also be visualized as fold-change ($2^{-\Delta\Delta Cq}$) on the dedicated "ΔΔCq ANOVA (Dunnett's

post-hoc)" tab.

Data processing and statistical analysis

For the ΔCq analysis, users can select one or multiple reference genes. The ΔCq value for each

sample is calculated using the Cq of the target gene against the mean Cq of the selected reference

gene(s). Relative expression is calculated as:

$$\Delta Cq = Cq_{target} - Cq_{reference}$$

$$Relative\ expression = 2^{-\Delta Cq}$$

109   Welch's *t*-tests are performed on the log2-transformed ΔCq values for each specified group pair.

110   Cases with zero variance are identified, and "Zero variance" is reported in place of a test statistic. In

111   the $\Delta\Delta$Cq analysis, ΔCq values are first obtained as above. The $\Delta\Delta$Cq and fold change values are

112   computed as:

$$\Delta\Delta Cq = \Delta Cq_{treatment} - \Delta Cq_{control}$$

$$Fold\ change = 2^{-\Delta\Delta Cq}$$

Statistical significance between treatment and control group is determined using Welch's *t*-tests on

ΔCq values.

For comparing three or more groups, the application performs a one-way analysis of variance

(ANOVA) followed by Dunnett's post-hoc test to compare each treatment group against a single

control group. This analysis is performed on the relative expression ($2^{-\Delta Cq}$) values.

Visualization and output

The application adjusts plot width to accommodate the number of bars, introducing a horizontal

scrollbar when necessary. Plot height is similarly expanded based on the number of significance

brackets, ensuring adequate spacing between them. All analysis modes generate high-quality bar

plots, displaying mean ± standard deviation (SD) with individual data points overlaid via jitter plots.

Statistical comparisons are annotated with significance brackets. Significance levels are denoted as

$p < 0.05$ (*), $p < 0.01$ (**), $p < 0.001$ (***), and *ns* otherwise. A corresponding summary table

provides mean, SD, sample size (N), *p*-value, and the assigned significance symbol. Download

options include three buttons:

-    The "Download Plot" button outputs a PNG file with custom width, height, and DPI specified

via sliders.

-    The "Save Displayed Size" button outputs an on-screen plot PNG file.

-    The " Download Stats" button generates a CSV file containing the on-screen summary table

data.

Reproducibility and diagnostics

An embedded example dataset and a downloadable template CSV file are provided to support

reproducibility. The "Diagnostics" tab allows verification for core functions in any execution

environment. Time-stamped downloads facilitate record-keeping. Upon clicking the "Run

Diagnostics" button, the application uses the built-in dataset (similar to the template CSV file

contents) to test three functions:

-    First, the sample data loading step confirms successful file loading.

-    Second, the ΔCq analysis validation step confirms that ΔCq calculation and *t*-tests detect the

expected difference.

-    Third, the ΔΔCq analysis validation step confirms that ΔΔCq (fold change) calculation and

t-tests detect the expected difference.

-    Fourth, the ANOVA and Dunnett's test validation step confirms that the multi-group

comparison functionality is operating correctly.

If all tests return "Passed" status, the application's calculation and statistical processing capabilities

are considered verified.

Use case

Click-qPCR is designed to streamline relative quantification analysis for researchers working with

qPCR data, particularly those without a strong background in programming or statistics. The tool is

intended for diverse user groups including:

-    Experimental biologists conducting small- to medium-scale gene expression studies

-    Technical staff responsible for routine data analysis in core facilities

-    Undergraduate and graduate students learning about qPCR and statistical evaluation

-    Collaborative research groups where ease of data sharing and reproducibility are essential

Limitations

While Click-qPCR provides an accessible and efficient platform for relative quantification analysis,

several limitations should be noted:

-    About assumption of normality: The app performs Welch's t-tests without explicitly confirming

equal variances.

- Normalization with multiple reference genes: The application now supports normalization using

the geometric mean of multiple reference genes, enhancing the robustness of the analysis.

However, automated methods for identifying the most stable reference genes, such as geNorm

[13], Normfinder [14], and BestKeeper [15], can be conducted outside this tool.

- Simplified statistical options: The app does not offer a correction for multiple comparisons (e.g.,

Bonferroni correction or FDR), which may be relevant when analyzing many target genes

simultaneously.

- No support for technical replicates handling: The input format assumes that users have averaged

technical replicates. Raw Cq values across technical replicates must be prepared in advance.

Concluding remarks

Click-qPCR is a web-based application designed to facilitate the rapid and reproducible analysis of

qPCR data. In contrast to conventional tools that require programming skills or complex local

installations, it is accessible directly through a web browser, enabling use by researchers, students,

and technical staff with limited bioinformatics experience. The application supports multiple

primary workflows of relative expression analysis: ΔCq analysis for direct group comparisons using

Welch's *t*-tests, ANOVA with Dunnett's post-hoc test for multi-group comparisons, and $\Delta\Delta$Cq

analysis for calculating fold changes relative to a control group. It generates publication-ready

visualizations and includes a dedicated Diagnostics tab for verification of core computational

functions. By integrating a guided interface, flexible export options, and reproducibility-oriented

features, Click-qPCR enables efficient processing of qPCR datasets and promotes transparent

reporting of gene expression analyses.

Declarations

Availability of source code and requirements

- Project name: Click-qPCR

- Project home page: https://kubo-azu.shinyapps.io/Click-qPCR/ (Shiny);

https://github.com/kubo-azu/Click-qPCR (R source code)

- Operating System(s): Platform Independent

- Programming language: R

- License: MIT

Data availability

The template CSV file for Click-qPCR can be found in the Supplementary information and at

https://github.com/kubo-azu/Click-qPCR/blob/main/Click-qPCR_template.csv.

Acknowledgments

Writing - original draft: AK. Writing - review and Editing: AT. Conceptualization: AK and AT.

Software: AK. Funding Acquisition: AK. Supervision: AT.

This work was supported by JST SPRING, Grant Number JPMJSP2135. The authors thank Dr.

Yasuhito Shimada and Dr. Liqing Zang for their constructive feedback, which contributed to the

improvement of Click-qPCR.

207   Competing interests

208   The authors declare that they have no competing interests.

210   Ethical considerations

211   The authors declare that ethical approval was not required for this type of research.

References

References

1. Harshitha R and Arunraj DR. Real-time quantitative PCR: A tool for absolute and relative

quantification. Biochem Mol Biol Educ. 2021;49 5:800-12. https://doi.org/10.1002/bmb.21552.

2. Livak KJ and Schmittgen TD. Analysis of relative gene expression data using real-time

quantitative PCR and the $2^{-\Delta\Delta CT}$ Method. Methods. 2001;25 4:402-8.

https://doi.org/10.1006/meth.2001.1262.

3. R Core Team. R: A Language and Environment for Statistical Computing. R Foundation for

Statistical Computing, Vienna, Austria. (2024). Version 4.4.2. https://www.R-project.org/.

4. Chang, W., Cheng, J., Allaire, J.J., Sievert, C., Schloerke, B., Xie, Y., Allen, J., McPherson, J.,

Dipert, A., & Borges, B. shiny: Web Application Framework for R. CRAN. (2024). Version

1.10.0. https://CRAN.R-project.org/package=shiny.

5. Wickham, H., François, R., Henry, L., Müller, K., & Vaughan, D. dplyr: A Grammar of Data

Manipulation. (2023). Version 1.1.4. https://dplyr.tidyverse.org.

6. Wickham, H. ggplot2: Elegant Graphics for Data Analysis. Springer-Verlag New York. (2016).

ISBN: 978-3-319-24277-4. https://ggplot2.tidyverse.org.

7. Wickham, H., Vaughan, D., & Girlich, M. tidyr: Tidy Messy Data. (2024). Version

1.3.1. https://tidyr.tidyverse.org.

8. Xie, Y., Cheng, J., & Tan, X. DT: A Wrapper of the JavaScript Library 'DataTables'. (2024).

Version 0.33. https://github.com/rstudio/DT.

9. Neuwirth,   E.   RColorBrewer: ColorBrewer   Palettes.   (2022).   Version

1.1-3. https://CRAN.R-project.org/package=RColorBrewer.

10. Iannone, R. fontawesome: Easily Work with 'Font Awesome' Icons. (2024). Version

0.5.3. https://github.com/rstudio/fontawesome.

11. Hothorn, T., Bretz, F., & Westfall, P. (2008). Simultaneous inference in general parametric

models. Biom J, 50(3), 346-363. https://doi.org/10.1002/bimj.200810425.

12. Bustin, S. A., Ruijter, J. M., van den Hoff, M. J. B., Kubista, M., Pfaffl, M. W., Shipley, G. L.,

Tran, N., Rodiger, S., Untergasser, A., Mueller, R., Nolan, T., Milavec, M., Burns, M. J.,

Huggett, J. F., Vandesompele, J., & Wittwer, C. T. (2025). MIQE 2.0: Revision of the Minimum

Information for Publication of Quantitative Real-Time PCR Experiments Guidelines. Clin

Chem. https://doi.org/10.1093/clinchem/hvaf043.

13. Vandesompele J, De Preter K, Pattyn F, Poppe B, Van Roy N, De Paepe A, et al. Accurate

normalization of real-time quantitative RT-PCR data by geometric averaging of multiple

internal   control   genes.   Genome   Biol.   2002;3   7:Research0034.

https://doi.org/10.1186/gb-2002-3-7-research0034.

14. Andersen CL, Jensen JL and Ørntoft TF. Normalization of real-time quantitative reverse

transcription-PCR data: a model-based variance estimation approach to identify genes suited for

normalization, applied to bladder and colon cancer data sets. Cancer Res. 2004;64 15:5245-50.

https://doi.org/10.1158/0008-5472.CAN-04-0496.

15. Pfaffl MW, Tichopad A, Prgomet C and Neuvians TP. Determination of stable housekeeping

genes, differentially regulated target genes and sample integrity: BestKeeper--Excel-based tool

using   pair-wise   correlations.   Biotechnol   Lett.   2004;26   6:509-15.

https://doi.org/10.1023/B:BILE.0000019559.84305.47.

Figure 1. Graphical overview of the Click-qPCR application.