1

Disentangling objects' contextual associations from perceptual and

conceptual attributes using time-resolved neural decoding

Ariel H. Kim*[,1,2], Genevieve L. Quek*[,1,3], Denise Moerel*[,1,3], Olivia Gorton[1],

Thomas A. Carlson[1]

[1] The School of Psychology, University of Sydney, Sydney, Australia

[2] Faculty of Medicine, Dentistry and Health Sciences, The University of Melbourne,

Melbourne, Australia

[3] The MARCS Institute for Brain, Behaviour and Development,

Western Sydney University, Sydney, Australia

*Shared first author

Corresponding Author: G. Quek (g.quek@westernsydney.edu.au)

Acknowledgements:

This project was partially funded by an Australian Research Council Discovery Project grant

(DP200101787) awarded to T. A. Carlson

25   **Abstract**

Humans effortlessly relate what they see to what they know, drawing on

existing knowledge of objects' perceptual, conceptual, and contextual attributes while

searching for and recognising objects. While prior studies have investigated the

temporal dynamics of perceptual and conceptual object properties in the neural

signal, it remains unclear whether and when contextual associations are uniquely

represented. In this study, we used representational similarity analysis on

electroencephalography (EEG) data to explore how the brain processes the

perceptual, conceptual, and contextual dimensions of object knowledge over time.

Using human similarity judgments of 190 naturalistic object concepts presented as

either as images or words, we constructed separate behavioural models of objects'

perceptual, conceptual, and contextual properties. We correlated these models with

neural patterns from two EEG datasets, one publicly available and one newly

collected, both recorded while participants passively viewed the same object stimuli.

Across both datasets, we found that perceptual features dominated the early EEG

response to object images, while conceptual features emerged later. Contextual

associations were also reflected in neural patterns, but their explanatory power

largely overlapped with that of conceptual models, suggesting limited unique

representation of objects' contextual attributes under passive viewing conditions.

These results highlight the brain's integration of perceptual and conceptual

information when processing visual objects. By combining high temporal resolution

EEG with behaviourally derived models, this study advances our understanding of

how distinct dimensions of object knowledge are encoded in the human brain.

Relating what we see to what we know is an essential cognitive function for

humans, enabling us to draw on prior experience to successfully detect, recognise

and interact with objects in the world. Doing so requires rapid and reliable evaluation

of the similarity between incoming sensory information and stored representations

(Clarke & Tyler, 2015; Edelman, 1998; Kok et al., 2013; Nosofsky, 1986). Despite its

ubiquity, this process of comparison is inherently complex, as objects themselves are

defined by a myriad of both observable visual properties (e.g., colour, surface,

texture, global shape, etc.) and more abstract, conceptual attributes (e.g., biological

status, action affordances, abstract qualities) (Clarke et al., 2013; Clarke & Tyler,

2015; Grootswagers et al., 2019b; Hebart et al., 2020; Teichmann et al., 2026). As

such, objects can be both similar *and* different to one another, depending on the

dimension under consideration. For example, an alligator and a rabbit are at once

both vastly disparate – one is large, scaly, and dangerous; the other small, fluffy, and

cute – and yet fundamentally similar – both animals that breathe, eat, and reproduce.

Recent largescale efforts to characterise the multidimensional nature of object

representations have uncovered a host of dimensions that underlie human

judgements of similarity both across (Hebart et al., 2019, 2020; Teichmann et al.,

2026) and within overarching object categories (Almeida et al., 2023). Findings

suggest that both perceptual and conceptual attributes serve to structure object

representations in the human visual system. Identified perceptual dimensions capture

intrinsic properties of objects' visual appearance (e.g., roundness, elongation, colour,

flatness, shininess, texture), where conceptual dimensions encompass both

taxonomic category (e.g., animal, vehicle, plant), as well as higher-level, semantically

rich aspects of object meaning (e.g., associations of value, heat, disgust).

Disentangling how perceptual and conceptual object properties emerge in time-

resolved M/EEG neural responses has been a focus within existing work on the

temporal unfolding of visual object processing (Bankson et al., 2018; Carlson et al.,

2013; Clarke & Tyler, 2015; Contini et al., 2017; Giari et al., 2020; Grootswagers et

al., 2019b; Isik et al., 2014; Wardle et al., 2016). This is important, since perceptual

and conceptual object attributes often covary: Think of a *HAMMER* and a *FORK*,

which are similar in terms of not only material composition, size, and shape, but also

function, affordance and taxonomic status (graspable tools). As a collective, these

studies suggest that perceptual features give rise to early, stimulus-locked activity

patterns – reflecting rapid encoding of objects' visual features – where

representations of conceptual properties tend to emerge comparatively later in the

neural time course, suggesting a temporal cascade from early perceptual analysis to

later semantic integration (Bankson et al., 2018; Carlson et al., 2013; Clarke & Tyler,

2015; Grootswagers et al., 2019b; Proklova et al., 2019; Teichmann et al., 2026).

Notably, neural representations of conceptual features also show greater variability

across individuals, potentially reflecting differences in experience, familiarity, or

conceptual organisation (Teichmann et al., 2026).

In addition to their inherent perceptual and conceptual features, object

knowledge also comprises contextual attributes, defined by objects' predictable

associations with certain environments (e.g., a toothbrush in a bathroom, a knife on a

countertop). A wealth of prior work has shown that contextual associations between

objects and surrounding scenes influence how we search for and recognise objects

(Bar, 2004; Biederman et al., 1973; Davenport & Potter, 2004; Ganis & Kutas, 2003;

Oliva & Torralba, 2007; Võ et al., 2019), with scene context even serving to

disambiguate neural representations for degraded objects that are otherwise

unrecognisable (Brandman & Peelen, 2017; Wischnewski & Peelen, 2021). Context-

based facilitation also arises at the inter-object level, with observers recognising

objects more efficiently when they are contextualised by second, related object

(Auckland et al., 2007; Bar & Ullman, 1996; Davenport, 2007; Green & Hummel,

2006; Kaiser et al., 2019; Kaiser et al., 2014; Quek et al., 2025). Moreover, violations

of canonical contextual associations seem to elicit reliable neural signals even when

observers are not explicitly attending to congruity between the elements (Mudrik et

al., 2010, 2014; Quek & Peelen, 2020), suggesting that representations of contextual

object attributes may be evoked automatically during object processing.

Where prior work characterising the neural timecourse of individual object

dimensions does encompass aspects of objects' contextual attributes (e.g.,

'outdoors-related', 'bathroom-/wetness related', Hebart et al., 2023), to date no study

has explicitly aimed at *dissociating* time-resolved representations of contextual object

knowledge from their perceptual and conceptual counterparts. Understanding the

degree of temporal overlap in the processing of these three classes of object features

is central to the interpretation of inter-object contextual facilitation effects, which are

underpinned by both conceptual and contextual associations between simultaneously

presented objects (e.g., *teacup* and *saucer* are both food/drink related and typically

encountered in the same surrounding context). The present study addressed this gap

by examining the extent to which behaviourally-derived models encompassing

objects' perceptual characteristics, conceptual attributions, and contextual

associations predict unique variance in the unfolding neural response to object

images reflected in EEG data.

To explore the intersection between processing of objects' contextual,

perceptual, and conceptual features, we adapted the "odd-one-out" task used by

Hebart et al. (2020) to capture subjective similarity judgments among triplets of object

concepts. Crucially, rather than eliciting purely intuitive judgements of object

similarity, here we imposed specific task instructions designed to selectively weight a

particular object dimension. Different groups of online observers made triplet

similarity judgements for the same 190 object concepts in terms of *i)* objects'

observable perceptual properties (e.g., size, colour, shape, etc.), *ii)* their conceptual

attributes (e.g., function, use, affordance), or *iii)* their contextual associations (e.g.,

where the object would likely be found). These dimension-specific judgments were

then used to construct models that isolated perceptual, conceptual, or contextual

structure of objects. Our overarching goal was to examine the extent to which each of

these behaviourally-derived object dimension models explained unique variance in

the dynamically evolving representational structure of visual object processing. To

this end, we correlated our object dimension models with two high-temporal

resolution EEG datasets recorded in separate participant samples viewing the same

object images under orthogonal task conditions. These included both a publicly

available EEG dataset (referred to as Experiment 1; (Grootswagers et al., 2022) and

a newly acquired dataset (referred to as Experiment 2) which differed in presentation

rate and the number of object image repetitions.

Secondarily, we also aimed to investigate how different presentation

modalities would differentially capture subjective similarity between objects'

perceptual, conceptual, and contextual dimensions. Thus, we derived object

dimension models based on both image and word-label versions of our 190 object

concepts. This represents a departure from previous studies that have typically

modelled object dimensions based on behavioural responses to object images alone

(e.g., Cichy et al., 2019; Giari et al., 2020). Here we predicted that similarity

judgments using word labels would capture object dimensions in a more abstract

form, whereas judgments based on images would inherently be more visually-driven,

even if participants were asked specifically to consider conceptual or contextual

object properties. By using both abstractly derived (word-based models) and

perceptually derived (image-based models) object dimensions to understand neural

responses to objects, we aimed to further delineate the contributions of perceptual

and conceptual dimensions to neural responses. Our analysis measured the degree

to which the representational structure of object dimensions, as perceived by

individuals, aligned with the dynamically evolving representational structure of visual

object processing in the brain.

2. MATERIALS AND METHOD

The current study consisted of three parts: (1) collection of behavioural data,

(2) analysis of both pre-collected EEG data (Experiment 1) and newly acquired EEG

data (Experiment 2), and (3) Representational Similarity Analysis using data from (1)

and (2).

2.1 Stimuli

To investigate how different dimensions of human similarity judgments are

reflected in the neural processing of visual objects, we took advantage of the

THINGS stimulus database (Hebart et al., 2023; Hebart et al., 2019). This open-

source database consists of 1,854 object concepts systematically sampled from a

wide range of concrete nouns that can be visually depicted and labelled in American

English. These object concepts correspond to basic-level categories such as *dog,*

car, spaghetti, and *foot.* Each concept is associated with a word label and includes

exemplar images that showcase the objects embedded within naturalistic scenes.

These exemplar images capture the objects in diverse colours, shapes, angles,

positions, lighting conditions, and other visual characteristics, creating a rich and

varied visual context for each object concept. Additionally, each concept belonged to

one of the 27 high-level categories defined by THINGS, which represent broader

superordinate categories such as vehicles, animals, food, and body parts (Figure

1A).

Since it was infeasible to derive six separate models for the full set of object

concepts in the THINGS database, here we focused on a subset of 190 object

concepts spanning the top 25 high-level categories identified in the original THINGS

database (*food, animal, clothing, tool, sports equipment, vegetable, vehicle, musical*

instrument, fruit, body part, dessert, toy, container, part of car, weapon, bird,

furniture, kitchen tool, office supply, kitchen appliance, plant, insect, home décor,

medical equipment, electronic device). From these high-level categories, we selected

7-8 concepts per category, which resulted in 190 object concepts in total, each of

which was represented by 10 exemplar images and a word label. This resulted in a

final stimulus set of 1900 images (used in behavioural and EEG data collection) and

190 words (used in behavioural data collection only).

2.2 Behavioural Data Collection

The goal of our behavioural data collection was to model functionally-derived

similarity in our set of 190 objects' perceptual, conceptual, and contextual attributes.

To this end, we tasked different groups of observers with evaluating similarity among

triplets of object concepts along one of those three dimensions. Separate models

were derived for the same 190 object concepts represented by 1) images and 2)

object labels (i.e., words). Similarity judgements from each task were converted into a

representational dissimilarity matrix (RDM) to create six behavioural model RDMs, to

be subsequently related to neural RDM series based on EEG data recorded in a
different set of participants viewing image versions of same 190 object concepts.

2.2.1 Participants

A total of 695 undergraduate students at the University of Sydney, Australia,
were recruited to take part in the online behavioural study in exchange for course
credit. Each participant took part in only one of the six behavioural tasks, and each
task had a different number of participants: Perceptual-image task (n=128),
Conceptual-image task (n=101), Contextual-image task (n=116), Perceptual-word
task (n=113), Conceptual-word task (n=119) and Contextual-word task (n=118). All
participants were aged over 18 years; no further demographic information was
collected. All participants provided informed consent prior to commencing the
experimental task.

2.2.2 Behavioural Task Paradigm

We collected behavioural similarity judgements for our 190 object concepts
using an adapted version of the "triplet odd-one-out task" from Hebart et al. (2020), in
which observers evaluate the similarity across three object concepts on each trial. In
Hebart et al.'s original version of this task, observers saw three object images per
trial, and simply selected the object they intuitively felt is the 'odd-one-out', which
implies that the other two objects were more similar. In our adapted version of this
task, we instructed online observers to consider triplets of object concepts with
respect to either their *Perceptual*, *Conceptual,* or *Contextual* features, selecting the
two objects that were most similar along the specified dimension. The task
instructions were worded differently depending on the type of similarity judgement
required for each task (see Figure 1B). In the *Perceptual* condition, the instructions

were: *"Select the two items that are most similar in <u>appearance</u> to each other. It may*

be helpful to think about: What size is this item? What colour is this item? What

shape is this item?". In the *Conceptual* condition, the prompt was: "*Select the two*

items that are most <u>conceptually similar</u> to each other. It may be helpful to think

about: What is this item used for? How would I interact with this item? What functions

does this item have in the real world?". In the *Contextual* condition, participants were

shown: "*Select the two items that you would be most likely to <u>find together</u> in the real*

world. It may be helpful to think about: Where would I normally find this item?". These

instructions were designed to constrain observers' similarity judgements to the

specific dimension of interest, with the understanding that the same trio of objects

could be evaluated differently depending on the dimension under consideration (e.g.,

a hammer and a fork are similar in terms of both their perceptual AND conceptual

attributes, but less so in their contextual associations).

To reinforce these instructions and thus reduce the risk of participants

applying inconsistent or unintended criteria, we reiterated the object dimension the

participant should (and should not) attend to across two worked demonstration trials.

As one example, in the contextual condition, participants were shown *PARROT,*

CHICK, and *TRACTOR*, and instructed: "Remember to choose the items that <u>go</u>

<u>together</u> in the real world. Don't make the mistake of choosing items that are similar

concepts! The correct answer is **chick** and **tractor**, which could both be found on a

farm. Don't get distracted by **chick** and **parrot** being similar concepts (both birds)!".

After examining these demonstration trials, participants completed five practice trials

that were individually tailored to each version of the task, and included explicit

feedback about the selected pair of objects. For example, selecting *ELEPHANT* and

BEAR on a perceptual similarity practice trial resulted in the feedback text: "That was

an easy one! An elephant and a bear both have four legs, a tail, eyes, etc.".

Conversely, selecting *ELEPHANT* and *BAMBOO* resulted in: "Hmm I'm not so sure

about that one. They don't really share many visual features".

Participants were assigned to either a *word* or *image* format of the task (see

Figure 2A), and were assigned to only *one* of the three dimensions to judge object

similarity. Thus, there were six different triplet similarity tasks with unique participant

samples (Perceptual-word, Conceptual-word, Contextual-word, Perceptual-image,

Conceptual-image, and Contextual-image). In the word task, three words were

randomly drawn from the bank of 190 labels that corresponded to the names of 190

object concepts (i.e., three distinct object concept labels per trial). In the image task,

we selected three different object concepts at random, and presented the first

exemplar image for each after shuffling the set of 10 exemplars. Participants in the

word version of the task completed 250 trials; participants in the image task

completed 170 trials. This difference was due to a practical constraint, since images

took longer to load in the online study. Alongside the experimental trials, each triplet

similarity task also included 5 attention-check trials, designed to probe whether the

participants were correctly attending to the instructed dimension. These trials were

tailored for each version of the behavioural experiment, such that each trial had an

obvious answer with respect to the instructed object dimension (e.g., a perceptual

similarity attention-check trial would contain *MOTH, DRAGONFLY*, and *DIRTBIKE*).

The total testing time in both versions was approximately 30 minutes.

Note that for all six triplet similarity tasks, each participant was tested with only

a subset of the possible triplet combinations from the 190 objects, as testing all

112,835 possible combinations per participant was practically unfeasible. The large

number of possible combinations also meant that, even across all participants, we

were unable to obtain results from all triplet combinations. However, previous studies

have shown that testing a subset of triplet combinations still provides sufficient

coverage to infer most of the pairwise dissimilarities between objects, which is

necessary for constructing the model RDM (e.g., Hebart et al., 2020; Moerel et al.,

2024). The number of trials collected from each task were as follows: Perceptual-

image task = 21,760, Conceptual-image task = 17,170, Contextual-image task =

19,720, Perceptual-word task = 28,250, Conceptual-word task = 29,750 and

Contextual-word task = 29,500. Although these represented only a fraction of the

total possible trials, each trial provides dissimilarity information about three objects

(i.e., A-B, A-C, and B-C), allowing for three pairwise comparisons within a single trial.

Thus, a relatively small amount of trials was still able to cover a large number of

unique object pairs. All behavioural data and relevant analysis code can be accessed

at: https://osf.io/jy284/.

Figure 1. A. Stimuli were 190 object concepts from the THINGS database (Hebart et

al., 2019). Each was represented by 10 exemplar images; there were 7-8 object

concepts from each of the top 25 high-level categories identified in the original

Hebart paper (2019). **B.** Overview of the triplet similarity behavioural task(s). Each

participant was assigned to either a WORD or IMAGE version of the task, and

instructed to evaluate triplets of object concepts along one of three objects dimension

(fixed across the experiment). Thus, the participant samples for each combination of

Stimulus Type and Similarity Type were non-overlapping. **C.** An example of the Rapid

Serial Visual Presentation (RSVP) paradigm used in the two EEG experiments that

differed in their image presentation rate (i.e., 3.33 Hz vs. 10 Hz). All images in this

figure have been replaced with visually similar images from the public domain.

2.3 EEG Data Collection

The current study employed two EEG datasets recorded in response to the

same set of 1900 object images, covering 190 concepts. In Experiment 1, we took

advantage of a pre-existing, publicly available dataset from Grootswagers et al.

(2022), comprising 64 channel EEG recordings obtained in 50 observers as they

viewed a rapid stream of object images presented at a rate of 10 Hz (image duration

= 50 ms; ISI = 50 ms; 1 repetition per image, see Figure 1C). Acquisition details for

this Experiment 1 neural dataset are provided in Grootswagers et al. (2022). In

Experiment 2, we acquired a novel dataset for this study, comprising 128 channel

EEG recordings obtained in 20 observers as they viewed object images appearing at

a rate of 3.33 Hz (image duration = 100 ms; ISI = 200 ms; 3 repetitions per image,

see Figure 1C). The sections below provide detailed acquisition information

pertaining to this Experiment 2 dataset (example dataset available at:

https://osf.io/jy284/).

2.3.1 Participants

Twenty undergraduate students (15 females and one non-binary individual) from the University of Sydney participated in Experiment 2 in exchange for course credit (mean age = 21.85 years, SD = 4.55, age range = 18-34). All participants reported normal or corrected-to-normal vision and normal colour vision, and had no history of psychological or neurological disorders. All but one reported being right-handed. Verbal and written informed consent was obtained from all participants before the experiment, and the study was approved by the Human Ethics Committee of the University of Sydney (ethics ID 2019/340). One participant was excluded from the results due to a technical error in the EEG data, resulting in a final sample of 19 participants.

2.3.2 Experimental Design and Procedure

Experiment 2 was modelled on the paradigm employed by Grootswagers et al. (2022) to collect the EEG dataset comprising Experiment 1. Where their paper presented multiple exemplars of all 1,854 object concepts from the THINGS dataset (Hebart et al., 2019), here participants viewed a rapid stream of object images representing our selected subset of 190 concepts used in the behavioural experiment. We modified the image presentation rate used by Grootswagers et al. (2022) from 10 Hz to 3.33 Hz (see Figure 1C), on the rationale that a slower presentation rate might enable better capture of not only visual and perceptual processing of objects but also activation of more abstract and semantic information (Carlson et al., 2013; Contini et al., 2017). We selected the first 10 unique images for

each per concept, and each of the 1900 object images appeared three times of the

course of the full experiment.

Participants sat in a dimly lit room at a distance of ~60 cm before a 1920 x

1080 pixel computer monitor. After being set up for EEG recording, they rested their

hands on a button box and were instructed to maintain their gaze on a small,

centrally-displayed black and white bullseye while images were flashing in the

background. Participants were instructed to remain still and minimise eye and head

movements during the stimulus presentation. Stimuli were presented on a uniform

background using the PsychoPy toolbox in Python (Peirce et al., 2019), and were

256 by 265 pixels (approximately 6.25 by 6.25 degrees of visual angle) in size. The

task of the participants was to press the button whenever the bullseye turned red

(colour changes lasted 100 ms and occurred at random intervals 2-4 times per

block). The purpose of this task was to increase attention and engagement. Before

the start of the experiment, a practice trial was conducted to ensure that participants

understood the task requirements.

All 190 object concepts were presented in a randomised order within each

individual sequence; at a rate of 3.33 Hz, this meant that a single sequence lasted 57

seconds. There were 10 exemplar images for each object concept, with each

exemplar presented three times across the entire experiment (i.e., 30 sequences in

total). This resulted in a total of 5,700 stimulus presentations per participant (190

concepts x 10 exemplars x 3 repetitions). Participants were encouraged to take

sufficient breaks between sequences to mitigate screen fatigue. The progress of the

experiment was indicated on the screen between sequences by displaying the

number of the upcoming sequence (e.g., "2/30", "18/30"). The entire experiment,

including breaks, took approximately 35 minutes.

361   *2.3.3 EEG Recording and Preprocessing*

During the stimulus presentation, participants' brain activity was continuously

recorded using a BrainVision ActiChamp system at a sampling rate of 1000 Hz. The

standard 128-channel EEG cap (Brain Products; GmbH, Herrsching, Germany) was

fitted to the participants, corresponding to the 10-20 international system of electrode

locations (Oostenveld & Praamstra, 2001). We applied electrolyte gel to keep the

impedances below 10 kΩ, and the electrodes were referenced to FCz.

The offline preprocessing of EEG data was performed using the EEGLAB

toolbox in MATLAB (Delorme & Makeig, 2004). A Hamming windowed FIR filter was

applied with a low-pass filter of 100 Hz and a high-pass filter of 0.1 Hz. The data

were then re-referenced to the average reference and downsampled to a rate of 250

Hz. Epochs were created for each stimulus presentation from -100 ms to 800 ms

relative to the stimulus onset. No further preprocessing steps were taken.

374   **2.4 Representational Similarity Analysis**

To assess whether the behavioural data of object similarity judgements could

explain the dynamics of neural representational structure over time, we used

Representational Similarity Analysis (RSA; Kriegeskorte et al., 2008). We created

Representational Dissimilarity Matrices (RDMs), which capture the dissimilarity

between pairs of experimental stimuli based on their representational patterns. For

the behavioural data, RDMs were generated from participants' similarity judgments of

objects, with one RDM created for each of six triplet similarity tasks. As for the neural

data, RDMs reflected the similarity or dissimilarity in the neural activation patterns

evoked by each pair of the 190 concepts.

384   *2.4.1 Behavioural model RDMs*

Before creating the behavioural model RDMs, we firstly removed any

participants who made an incorrect selection on more than 3 of the 5 attention-check

trials, on the rationale that they were not correctly attending to the instructed object

dimension. This resulted in the following final participant samples: Perceptual-image

task (n = 114), Conceptual-image task (n = 100), Contextual-image task (n = 108),

Perceptual-word task (n = 98), Conceptual-word task (n = 105) and Contextual-word

task (n = 103). Following this, we constructed 6 RDMs based on the six different

triplet tasks. These RDMs were constructed at the level of object concepts, with cells

reflecting the pairwise dissimilarity between objects' selection rates (ranging between

0 and 1). This value was computed from the triplet similarity task data, by calculating

the proportion in which two objects were chosen together out of all the instances

when they were shown together in a triplet. A value of 1 indicated extreme

dissimilarity, meaning that the two objects were never chosen together, while a value

of 0 indicated extreme similarity, meaning the objects were always chosen together.

As outlined above, because we presented only a subset of the total possible triplet

combinations in our behavioural tasks, some cells of these RDMs had no dissimilarity

score, indicating that the respective object pairs were never shown together in a

triplet. The proportion of missing dissimilarity values in the six behavioural model

RDMs were as follows: Perceptual-word = 1.65%, Conceptual-word = 0.52%,

Contextual-word = 0.60%, Perceptual-image = 1.69%, Conceptual-image = 7.89%,

and Contextual-image = 6.22%.

We inspected the validity of our behaviourally-derived models by correlating

them with binary models representing ground truth object properties. These included

models of high-level category, naturalness, animacy, outdoor/indoor association and

real-world size (smaller or larger than a shoebox). Each object pair was given a

binary value of either 0 or 1, indicating identicality or difference in the given object

dimension (Figure 2B). As is clear in Figure 2C, there were significant correlations

among most of our models, with the strongest correlations emerging between the

Conceptual-word and Naturalness models (r = .53, p<.00001), and the Conceptual-

image and Naturalness models (r = .48, p < .00001). Notably, strong correlations

were evident between the image and word versions of each similarity judgement

task, reflected in the clustering of these models when visualised using 2D

multidimensional scaling (Figure 2D).

Figure 2. A) Behavioural RDMs derived from each of the 6 behavioural triplet similarity tasks. Non-overlapping groups of online observers saw either triplets of object-images or object-names and had to select the pair with the highest conceptual similarity, contextual similarity, or perceptual similarity. B) Binary models for the 190 object concepts. C) Intercorrelation matrix for the six behavioural RDMs and the binary models. Stars indicate correlations significant at p < .001, FDR corrected. D)

Model similarity reflected in 2D multidimensional scaling. Note the close proximity of

word/image versions for each object similarity dimension.

2.4.2 Experiment 2 Neural RDMs

We subjected the preprocessed EEG data from Experiment 2 to RSA to

produce an RDM series reflecting time-resolved pairwise dissimilarity between all 190

object-concepts. Decoding accuracy served to index the degree of dissimilarity

between object concepts' neural activation patterns, with higher decoding accuracy

taken to reflect more dissociable object representations. In line with previous studies

(e.g., Grootswagers et al., 2019), we ran the decoding analysis on preprocessed

EEG data collected from all 128 channel voltages, using the CoSMoMVPA MATLAB

toolbox (Oosterhof et al., 2016). A linear discriminant analysis (LDA) classifier was

used to identify the decision boundary that could best differentiate the brain activation

patterns evoked by objects. We implemented a leave-one-sequence-out cross-

validation procedure, wherein the classifier was trained iteratively on all sequences of

EEG data except one, which was kept aside to serve as the test data. We repeated

this process for all sequences to ensure that every sequence was used for testing.

During training, the classifier was tasked with distinguishing the neural activity

patterns evoked by pairs of object objects and classifying them into two categories.

This process was performed for every possible pairwise combination of the 190

object concepts shown in that sequence. The classifier underwent training and

testing at each timepoint in the epoch between -100 and 800 ms. This process was

repeated for each participant, resulting in one time-varying neural RDM per

participant for each time-point.

2.4.3 Experiment 1 Neural RDMs

To create corresponding RDMs based on the pre-existing EEG dataset for Experiment 1, we applied the same pre-processing and analysis steps described above for Experiment 2 to the raw data from Grootswagers et al. (2022). This EEG dataset consisted of EEG recordings from 50 participants presented with 1,854 THINGS concepts. Four participants were excluded from the analysis due to poor signal quality or equipment failure, resulting in data from 46 participants. From this original dataset, we extracted the data pertaining to the first 10 images of the 190 object concepts, aligning with the concepts and stimuli used in our behavioural study and the collection of new EEG data in Experiment 2. We used the same epoch length described for Experiment 2 (-100 ms to 800 ms relative to stimulus onset, or 225 time-points). We then used pairwise decoding with a leave-one-sequence-out cross-validation procedure to obtain an RDM for each participant and timepoint in the epoch.

2.4.5 Correlation between Behavioural Model RDMs and EEG Neural RDMs

To examine the degree to which our behaviourally-derived RDMs could account for unique variance in the neural responses elicited by images of those same object concepts, we correlated each of the six behavioural RDMs with the time-varying neural RDM from Experiment 1 and Experiment 2. For this analysis, we grouped the behavioural models by whether they were derived from image-based or word-based similarity judgements. Thus, four sets of partial correlation analyses were conducted: (1) Experiment 1 neural RDM with three image model RDMs (i.e., Perceptual-image, Conceptual-image, Contextual-image), (2) Experiment 1 neural

RDM with three word model RDMs (i.e., Perceptual-word, Conceptual-word,

Contextual-word), (3) Experiment 2 neural RDM with three image model RDMS, and

(4) Experiment 2 neural RDM with three word model RDMs.

In each case, we were interested in quantifying the unique variance in the

neural RDM that a given model RDM could explain while controlling for the other

models in that set. Within each analysis and at each timepoint, we used MATLAB's

partialcorr function to obtain Spearman's rank correlation coefficients between the

neural RDM and a given model RDM while partialling out the variance explained by

the other two model RDMs within the same task modality. This procedure serves to

regress out variance shared with competing models from both the model predictions

and the neural data. The resultant correlation between these residuals serves to

capture the model's independent explanatory power, rather than variance attributable

to shared structure between models. Notably, we computed partial correlations at the

level of the RDMs (model to neural), rather than at the level of EEG signals or

stimulus-wise classification accuracies. Due to the lack of behavioural data for one

object ('spatula'), we excluded it and only correlated 189 objects in both the neural

and model RDMs. Additionally, as some cells in the model RDMs did not have

dissimilarity scores, we used a geometric reconstruction method to complete these

missing dissimilarity scores (Moerel & Grootswagers, 2025) before using them in the

correlation analysis. For detailed information on this analysis, see the publicly shared

analysis code available here: https://osf.io/jy284/.

Finally, we calculated difference scores between the resultant partial

correlation values associated with each model using a simple arithmetic subtraction.

For example, difference scores were calculated between the partial correlations of

the perceptual and conceptual models within the same task (i.e., Perceptual-image

minus Conceptual-image; Perceptual-word minus Conceptual-word), and between

image and word modalities within the same similarity dimension (i.e., Perceptual-

image minus Perceptual-word; Conceptual-image minus Conceptual-word).

2.5 Statistical Inference

We evaluated evidence for positive correlations between the behavioural

models and the two EEG dataset using Bayesian hypothesis testing that considered

evidence supporting the alternative hypothesis (i.e., H_a) over the null hypothesis (i.e.,

H_0). In this context, we report Bayes factors (BFs) which assess the likelihood of a

partial correlation (H_a) as compared to no partial correlation (H_0), given the set of

obtained correlation values across participants at each time point. Specifically, we

defined H_a as the existence of a positive partial correlation between the neural and

model RDMs (i.e., as the dissimilarity between two stimuli increases in the neural

RDM, the dissimilarity in the behavioural model RDM also tends to increase), while

H_0 posited that the partial correlation between neural and model RDMs was zero (i.e.,

no relationship between the dissimilarity of two stimuli in the neural RDM and the

model RDM). In general, a BF greater than 1 indicates evidence in favour of H_a, while

a BF less than 1 suggests evidence in favour of H_0. We interpreted BF thresholds as

follows: BF > 10 was considered strong evidence, and BF > 3 was considered weak

evidence in favour of H_a. Conversely, BF < 1/10 indicated strong evidence, and BF <

1/3 indicated weak evidence in favour of H_0. When 1/3 < BF < 3, this was interpreted

as insufficient evidence for either hypothesis. We used a threshold of BF > 3 to

calculate the onset time of above chance correlations. We required at least two

consecutive BFs > 3 for the onset, an isolated BF at a single time point, meeting the

threshold of 3 or 1/3 but without consecutive BFs reaching these thresholds, was

treated as inconclusive evidence for either hypothesis.

BFs were calculated using the Bayes Factor package in R (Morey et al., 2015)

. The null hypothesis was defined using a point null (Morey & Rouder, 2011) and we

applied a half-Cauchy prior for the alternative hypothesis to conduct a directional test

to test for positive partial correlations. The prior range for the alternative hypothesis

was defined from d = 0.5 to d = ∞ to exclude small effects between the interval of d =

0 and d = 0.5, as these have been shown to occur at chance under the null

hypothesis (Teichmann et al., 2022). The prior width was set to a medium (r = 0.707),

which is the default setting in the BayesFactor R package.

3. RESULTS

We first examined whether brain activity during passive viewing of rapid object

image streams could be explained by our behavioural models of objects' perceptual,

conceptual, and contextual attributes. We separated the models by the modality they

were derived from – i.e., whether similarity judgements were made for object-labels

(words) or object images. Within each model grouping, we computed partial

correlations between the perceptual, conceptual, and contextual models and time-

resolved EEG data, with the aim of identifying timepoints where each model uniquely

explained variance in the EEG signal (i.e., beyond what was captured by the other

models).

3.1 Correlating the behavioural models with the Experiment 1 neural

RDM

Figure 3 shows the partial correlations between the Experiment 1 EEG dataset

(acquired at a 10 Hz image presentation rate) and the three object dimension models

derived from the image-based triplet similarity task (Figure 3A) and the word-based

triplet similarity task (Figure 3B). We observed partial correlation between the

Experiment 1 neural RDM and the Perceptual-image model beginning 108 ms after

stimulus onset and peaking at 192 ms. There was also a comparatively later partial

correlation with the Conceptual-image model beginning from 184 ms, which coincides

with its peak at 188 ms. There was evidence for no positive partial correlation with

the Contextual-image model.

For the word-based object dimension models, we found evidence for a partial

correlation with the Perceptual-word model and Experiment 1 EEG RDM starting

from 124 ms, which coincides with its peak. The Conceptual-word model also

correlated with this EEG dataset from 176 ms, with a distinct single peak occurring at

196 ms. From this, we inferred that the Conceptual-word model had a later

correlation onset and peak compared to the Perceptual-word model, mirroring the

pattern observed in the image models. Furthermore, compared to the image models,

the word models generally had a later onset and peak of partial correlation (see

Table 1 for correlation onsets and peaks for each model). Finally, there was either

insufficient evidence or evidence of no partial correlation between the Contextual-

word model and the Experiment 1 EEG RDM.

Figure 3. Partial Correlations Between Behavioural Models and two EEG

Datasets. Partial correlations (Spearman's ρ) were calculated between the EEG

neural RDMs from two datasets (reflected in columns) and the six behavioural model

RDMs grouped by modality (reflected in rows). Partial correlations were computed at

each time point from stimulus onset by removing the variance explained by the other

two models within the same modality from each model's full correlation. Shaded

areas represent standard errors. Time (ms) is relative to the stimulus onset at 0 ms.

The logarithmic scale of Bayes factors (BFs) below each plot indicates the strength of

evidence for two opposing hypotheses at each individual timepoint. BF>1 were

represented by circles filled with the corresponding plot colour and denote evidence

for alternative hypothesis (i.e., positive or negative correlation), BF≈1 were

represented by white circles, which indicate insufficient evidence for either

hypotheses, and BF<1 were represented by grey circles and indicate evidence for

null hypothesis (i.e., zero-correlation). Topographies above each panel depict Bayes

Factors associated with a spatial searchlight analysis for each model's partial

correlation. For all models, the strongest contributions are evident over posterior

electrodes. This suggests that eye-movements (reflected in frontal channel activity)

are unlikely to have made a substantial contribution to the model performances.

3.2 Correlating the behavioural models with the Experiment 2 neural

RDM

The right column of Figure 3 shows the partial correlations between the

Experiment 2 EEG dataset (acquired at a 3.33 Hz image presentation rate) and the

behavioural models derived from the image-based triplet similarity task (Figure 3C)

and the word-based triplet similarity task (Figure 3D). For the image-based models,

we found evidence of a partial correlation between this neural RDM and the

Perceptual-image mode beginning 108 ms after stimulus onset and peaking at 204

ms. The Conceptual-image model displayed a correlation onset of 160 ms, reaching

its peak at 220 ms. Notably, we also found modest evidence of a partial correlation

between the Contextual-image model and Experiment 2 neural RDM, starting from

384 ms and peaking at 732 ms. These results show that the correlation onset of the

Conceptual-image model occurred relatively later compared to the Perceptual-image

model, but the peak correlation occurred around a similar time for both models. In

contrast, the modest unique contribution of the Contextual-image model arose rather

later during the neural response.

Figure 3D shows the partial correlations between Experiment 2 neural RDM

and the three models derived from word-based similarity judgements. The

Perceptual-word model's partial correlation started from 120 ms and peaked at 368

ms, while the Conceptual-word model correlated with EEG from 176 ms with a single

distinct peak at 212 ms. For the Contextual-word model, we found either evidence for

no correlation, or else insufficient evidence to support either outcome.

Experiment 1						Experiment 2					
Image-task			Word-task			Image-task			Word-task		
Per-cept	Con-cept	Con-text	Per-cept	Con-cept	Con-text	Per-cept	Con-cept	Con-text	Per-cept	Con-cept	Con-text
108 ms	184 ms	N.E.	124 ms	176 ms	N.E.	108 ms	160 ms	384 ms	120 ms	176 ms	N.E.
192 ms	188 ms	N.E.	124 ms	196 ms	N.E.	204 ms	220 ms	732 ms	368 ms	212 ms	N.E.

610 **Table 1. Partial Correlation Onsets and Peaks**. The time points (ms)

611 corresponding to correlation onsets (top row) and peaks (bottom row) were identified

612 using Bayes Factors (BFs) cut-offs (see Methods for details). N.E. denotes no

613 evidence.

3.3. Summary of EEG Datasets

In summary, the object dimension models that uniquely explained the dynamic

neural representation of the stimuli were largely consistent across both EEG

datasets. Specifically, the perceptual and conceptual models, whether derived from

image-based or word-based similarity judgements, consistently accounted for the

neural response to object images in both Experiment 1 and 2. Evidence for a unique

contribution from the contextual models was comparatively much weaker – indeed,

the only unique contribution we observed was from the Contextual-image model to

the Experiment 2 neural dataset. In this case, explanatory power both arose and

peaked at relatively at late time points (384 ms and 732 ms respectively). All other

statistical analyses provided insufficient evidence or evidence of no partial correlation

between the contextual models and EEG.

From these results, we concluded that the pattern observed in Experiment 2

reflected a 'scaled-up' version of that seen for Experiment 1, with similar timings of

correlation onsets and peak time points in the perceptual and conceptual models.

This is likely due to the threefold increase in image repeats in Experiment 2, which

enable a higher signal-to-noise ratio than the single image presentations that

characterised Experiment 1. Given the high consistency of findings across the two

EEG datasets, and considering the enhanced power provided by Experiment 2, our

subsequent analyses focused exclusively on the neural data acquired in Experiment

2. Within this dataset, we pursued a series of more focused analysis questions

detailed below.

3.4 Perceptual versus Conceptual models in explaining neural responses

In Figure 4A, we examined the relative contributions of the perceptual and

conceptual models to explaining the neural representational structure of the neural

RDM from Experiment 2 by subtracting the partial correlation of the conceptual model

from the perceptual model, separately for each task modality. A two-tailed Bayesian

t-test was used to compare the resulting difference profile to zero.

When we compared the Perceptual-image model with the Conceptual-image

model, their difference score exceeded zero during an early time window (108-140

ms), indicating that the Perceptual-image model provided a better explanation of the

neural response to object images than the Conceptual-image model during this early

phase. Outside this window, there was either no evidence or insufficient evidence of

a difference between the two models, suggesting that both models performed equally

well at explaining EEG during this period.

Comparing the performance of the Perceptual-word with the Conceptual-word

model, only a few isolated time points showed evidence of a difference. Since no two

or more consecutive time points showed such evidence, we concluded that there was

limited evidence of difference between the Perceptual-word and Conceptual-word

models, indicating that both models provided comparably good explanations of the

EEG data across all time points.

Figure 4. Spearman's ρ differences contrasting the predictive power for various behavioural models. (A) Perceptual – Conceptual partial correlation differences calculated for each modality (i.e., Image or Word) separately. **(B)** Image – Word partial correlation differences calculated for each similarity dimension (i.e., Perceptual or Conceptual) separately. Shaded areas indicate standard error. Lower panels are log-scaled Bayes Factors testing difference scores ≠ 0.

In Figure 4B, we compared the modality in which the triplet similarity task was

presented (i.e., image vs. word) within the same object dimension (i.e., perceptual or

conceptual). When comparing the two perceptual models, we observed that the

Perceptual-image model had a greater unique explanation of EEG neural response

compared to the Perceptual-word model, during the period of 112 to 332 ms,

although included a few time points that showed insufficient evidence. In contrast,

there was no sustained evidence of a difference between the Conceptual-image and

Conceptual-word models. Note that while the image-based and word-based

conceptual models appeared to explain the neural data equally well, this need not

imply that these two models captured the *same* conceptual information about objects

(for further details on this, see Figure S1 in Supplementary Materials).

Overall, our analysis of the difference between the model performances

suggests that: (1) the Perceptual-image model outperformed the Conceptual-image

model at early time points; (2) the Perceptual-image model was better predictor of the

(image-derived) EEG responses compared to the Perceptual-word model across a

broad time window; (3) there was limited evidence of a difference in explanatory

power between the Perceptual-word and Conceptual-word models, as well as the

Conceptual-image and Conceptual-word models.

3.5 Do Contextual models play any role in explaining the neural response

to objects?

In a final analysis, we focused specifically on the models of objects' contextual

attributes, which thus far show comparatively weaker capacity to predict the neural

response to object images (Contextual-image model correlating with the Experiment

2 neural RDM at isolated late time points; see Figure 3C and Table 1). At this stage,

it remains unclear whether behaviourally derived models of objects' contextual

associations lack explanatory power altogether, or if their explanatory power is simply

not unique, due to shared variance with the perceptual and/or conceptual models. To

examine this, we calculated the partial correlations between each contextual model

and the Experiment 2 neural RDM while partialling out the perceptual and conceptual

models in separate analyses. As a baseline, we also calculated the full correlation

between each contextual model and the neural RDM (i.e., without removing shared

variance with any other model). In doing so, we aimed to determine whether the

contextual model considered in isolation could account for any variance in the EEG

data, and if so, clarify the extent to which this variance overlapped with that explained

by the perceptual and conceptual models individually.

Figure 5. Full and Partial Correlations for the Contextual Models based on **(A)** Image-task and **(B)** Word task. The lines were temporally smoothed with a kernel of 3 samples (12 ms) for visibility. Below each plot, Bayes factors (BFs) appear for the full correlation (top), partial correlation controlling for the perceptual model within the

same modality (middle) and partial correlation controlling for the conceptual model

within the same modality (bottom). The Bayes factors (BFs) were based on

unsmoothed data.

Figure 5A shows the full and partial correlations of the Contextual-image

model with EEG. We found evidence that the Contextual-image model did correlate

with the EEG data when no other models were taken into account (onset at 120 ms

and peaking at 244 ms). When the variance explained by the Perceptual-image

model was partialled out, we retained evidence of a partial correlation between the

Contextual-image model and EEG from 140 ms onwards. When the covariate was

changed to be the Conceptual-image model, we retained evidence of a partial

correlation between the Contextual-image model and EEG during the late time

window from 384 ms. This would suggest that the Conceptual-image model shared a

similar amount of variance with the Contextual-image model, and that when variance

accounted for by each were taken into consideration, the Contextual-image model

retained little unique explanatory power.

Figure 5B shows the full and partial correlations of the Contextual-word model

with EEG. Evidence indicated that the Contextual-word model began correlating with

EEG at 184 ms. When the Perceptual-word model was included as a covariate and

partialled out from the full correlation, the correlations were mostly preserved, with a

shifted onset of 196 ms. This suggested minimal shared variance between the

Contextual-word and the Perceptual-word models. However, when the covariate was

switched to the Conceptual-word model, there was no longer any evidence

supporting the Contextual-word model's unique explanatory power, in contrast to the

results when the Perceptual-word model was partialled out. In general, these findings

suggest that the contextual models shared relatively more variance with the

conceptual models than the perceptual models, particularly in the case of word-based

models. While the contextual models do explain variance in the EEG data, they do

not provide unique explanatory power beyond what is captured by the conceptual

models.

4. DISCUSSION

This study investigated how contextual, perceptual, and conceptual object

attributes contribute to the neural responses evoked by visual objects. We used

representational similarity analysis (RSA) to correlate two EEG datasets recorded

during the passive viewing of object images with behavioural models based on

similarity judgements of objects' perceptual, conceptual, or contextual properties.

Separate behavioural models were derived for image and word label versions of the

objects. Our findings revealed that behavioural similarity judgements along the

perceptual and conceptual dimensions accounted for independent aspects of the

neural response to object images. Our results underscore the robustness of object

representations in the human brain, as the temporal dynamics of perceptual and

conceptual object feature models' explanatory power were consistent across both

word-based and image-based models, and across EEG datasets with differing signal-

to-noise ratios due to differences in presentation rate, stimulus repetition, and inter-

stimulus interval. Notably, there was no evidence that contextual object attributes

captured by in our behavioural models were meaningfully related to the neural

response elicited by object images over and above what could be explained by the

perceptual and conceptual models.

A perceptual-conceptual continuum of object features across both image and word modalities

A key finding from our study is that the perceptual features of objects deemed relevant by human observers dominated the early stages of the neural response to object images, with conceptual aspects of objects better explaining a later stage processing. Information about objects' perceptual attributes emerged as early as approximately 100 ms after stimulus onset, while conceptual information was reflected in the neural response to object images from approximately 160 ms onwards. This pattern was consistent regardless of the image presentation rate, and evident using models derived from both the image and word modalities, although onsets were slightly later for the Perceptual-word compared to image models (see Table 1). These findings largely align with established object recognition literature that has identified early processing of lower level visual features (such as object shape and colour) followed by abstract conceptual attributes (such as object category) (Carlson et al., 2013; Cichy et al., 2014; Contini et al., 2017, 2020; Grootswagers et al., 2019a, 2019b; Teichmann et al., 2026).

We found that perceptual similarity between object images uniquely explained EEG neural response from approximately 100 ms after stimulus onset, peaking at approximately 200 ms for both Experiment 1 and 2. This is in line with previous studies that have compared behavioural models of perceived visual similarity to EEG responses to visual stimuli (Cichy et al., 2019; Wardle et al., 2016). Cichy and colleagues found the unique emergence of visual features such as colour and shape at 82 ms and 183 ms respectively, peaking at 82-117 ms and 183-202 ms. Similarly, Wardle et al. found that the perceived similarity of artificial shapes explained neural response from as early as 50 ms, with the highest correlation observed at 150 ms.

Although variations in experimental designs and stimuli make direct comparisons of

correlation onsets and peaks between studies challenging (Contini et al., 2017), our

findings are consistent with the broader agreement that visual features underlying

behaviour are processed within the first 200 ms of visual object recognition (Carlson

et al., 2013; Cichy et al., 2014; Contini et al., 2017). While we cannot determine

which specific visual features participants focused on when evaluating objects'

perceptual similarity, the Perceptual-image model demonstrated the earliest time

point of unique correlation among all behavioural models, which suggest that

participants likely relied on lower-level properties of objects such as colour or shape

to guide their similarity judgements. The temporal dynamics associated with

conceptual attributes of object images observed here also concord with extant

findings. In our case, the Conceptual-image model uniquely explained the EEG

response from approximately 160 ms onwards, peaking around 200 ms, a relatively

later onset but similar peak compared to the Perceptual-image model. The partly

overlapping time points of correlation between the perceptual and conceptual image

models highlight the dynamic evolution of representations in the brain, transitioning

from lower-level perceptual to higher-level semantic properties over the first 200 ms

after stimulus onset (Bankson et al., 2018; Clarke et al., 2013, 2015).

The inclusion of word-based models of object dimensions enabled us to

inspect the relative contribution of perceptual, conceptual, and contextual object

properties to the neural response while controlling for category-nonspecific visual

features of individual stimulus images. Here we found that the Perceptual-word

model held unique explanatory power for our neural data from approximately 120 ms

after stimulus onset. This suggests that perceptual object properties accessible via

object labels alone are represented during the early stages of visual object

805 perception, a finding that may be underpinned by mental imagery. Specifically, when

806 participants in our behavioural   perceptual similarity task read a word like

807 "AIRPLANE", they may well have activated this concepts' associated visual features

808 (e.g., shape, colour) in their minds to help guide their judgement of this object-

809 concept's similarity with the other concepts on that trial (Pearson et al., 2015).

810 Research on mental imagery indicates that imagining a visual stimulus activates the

811 visual cortex, engaging similar neural mechanisms to those involved in perceiving an

812 actual object (Kosslyn et al., 1995; Mechelli et al., 2004; O'Craven & Kanwisher,

813 2000). At the same time, vivid visual imagery is certainly not required to do the word-

814 based perceptual similarity task – judgements in this case could also be based on

815 internally constructed representations of the object-labels. Regardless of underlying

816 processes that behavioural participants used, it remains the case that visual

817 processing of objects as early as 120 ms following stimulus onset could be explained

818 by the perceptual properties that online participants used when considering the

819 similarity of object-labels. Consistent with this is the finding that the word-based

820 Perceptual model's correlation onset and peak arose later than those for the image-

821 based Perceptual model, which suggests that the specific perceptual properties

822 tapped by object-label similarity judgements are somewhat more abstract than those

823 tapped by image-based judgements.

824  The relatively later onset of the Conceptual-word model's explanation of EEG

825 (approximately 180 ms after stimulus onset) further suggests that the specific

826 abstract/semantic features of objects that observers access via object labels are

827 represented in the neural response to objects somewhat later than their

828 stereotypically-associated visual features. Taken together, these results suggest that

829 reading object-labels can activate both perceptual and conceptual object knowledge,

but in a different manner to when observers encounter an object image, extracting

visual features from the stimuli and derive their conceptual meaning.

A unique aspect of our study is its direct comparison of behaviourally-derived

object dimension models based on judgements elicited by word and image versions

of the same object concepts. Our findings suggest there is significant overlap in the

object knowledge accessed via object image and word labels, in that both contribute

to explaining the neural activity involved in visual object recognition. However, there

appears to be a trend where lexically-accessed visual and conceptual features

explain neural processes at later time points compared to image-derived object

knowledge for the perceptual models. In demonstrating that lexically-accessed

perceptual and conceptual features can also explain the neural responses to visual

objects, we add to an existing literature that has mostly relied on object images to

generate behavioural object dimension models (Cichy et al., 2019; Giari et al., 2020).

The findings here are some of the first to capture how presentation modality (word vs.

image) differentially activates object knowledge within the same dimension, with

object labels facilitating access to semantic aspects of object that are less visually

confounded than those elicited by object images (Giari et al., 2020). Precedent for

our approach does exist in terms of neural responses, with Giari and colleagues.

measuring neural responses for image and word versions of the same objects with

EEG.   Specifically,   they   compared   conceptual   object   similarity   with   the

representational structure of MEG responses elicited by both pictures and words, to

delineate the time course of higher-level semantic processing evoked by reading

object labels (which are not subject to the visual-conceptual covariance present in

object images). Several factors distinguish our study from that of Giari et al.: where

they   used   a   category-typicality   rating   task   during   MEG   recording   to   activate

conceptual object representations, the neural representations of objects in our data

were acquired under passive viewing conditions. That is, we deliberately did not

direct attention to object features, but rather engaged participants in an orthogonal

fixation colour change detection task that rendered the objects task-irrelevant. That

we find evidence of conceptual processing using both an orthogonal task and a faster

presentation rate than Giari et al. (100 ms vs. 400 ms) highlights the rapid and

automatic nature of object concept activations during visual perception.

Interpretation considerations

While the partial correlation values we report here are relatively small in

absolute magnitude, within a multivariate decoding framework, decoding accuracy

and correlation strength are understood to depend strongly on multivariate analysis

choices (e.g., trial averaging, cross-validation scheme, and representational format),

and therefore do not map straightforwardly onto classical effect size measures such

as Cohen's d (e.g., Allefeld & Haynes, 2014; Combrisson & Jerbi, 2015; Dubois et al.,

2015; Hebart & Baker, 2018). Indeed, even accuracies or correlations close to

chance can carry meaningful information if they are reliable and generalise across

participants and timepoints (Christophel et al., 2015). In the present case, our

purpose was to assess whether various behavioural models explained variance in

time-resolved EEG representational structure i) above chance and ii) relative to other

models. In this context, small but reliable correlations are expected, particularly given

the noisy nature of single-trial EEG data and the fact that we correlate neural RDMs

against high-level behavioural models rather than stimulus labels. It is compelling to

find that even in this context, the evidence supporting the unique predictive power of

our models is very strong, with Bayes Factors exceeding 100,000 in some cases (see

Figure 3).

Additionally, it is also relevant to consider what role eye movements could

have played in explaining our results (Linde-Domingo & Spitzer, 2024; Mostert et al.,

2018; Quax et al., 2019). Happily, the current design limits participants' opportunity to

make meaningful saccades via a combination of very short presentation durations,

parafoveal stimulus presentation, and a focal orthogonal task. Nevertheless, we

cannot completely exclude the possibility that there could be a systematic

relationship between participants' eye movements or blinks and the perceptual,

conceptual, or contextual properties of our visual stimuli. Yet the results of our

channel-based searchlight analysis would argue against this possibility: the dominant

contribution to all our models arises at posterior sensors (where we expect visual

neural responses to be strongest), rather than frontal electrodes that might hint at

eye-movement-related activity.

Contrasting perceptual and conceptual models within each modality

When comparing the performance of different models based on object

dimension or modality against the EEG neural data, we found that the Perceptual-

image model outperformed the Conceptual-image model at early time points

(approximately 100-140 ms after stimulus onset). The early dominance of the

Perceptual-image model over the Conceptual-image model further supports our

findings from the individual partial correlations of the behavioural models across the

two modalities and EEG datasets, indicating that perceptual features are processed

earlier than conceptual features. There was limited evidence of a difference in

explanatory power between the Perceptual-word and Conceptual-word models.

However, this still suggests a general pattern of later processing of conceptual

features compared to perceptual features, consistent with the Perceptual-image and

Conceptual-image models. Taken together, this suggests that for image-derived

behavioural models, perceptual features explain EEG data better than conceptual

features. The same was not true for the word-based models, where we observed a

trend for the Conceptual-word model explaining the neural responses better than the

Perceptual-word model, although not reaching the threshold for evidence. Future

studies could explore the factors contributing to this modality-specific distinction,

particularly in how perceptual and conceptual features are evoked differently by

pictorial and lexical stimuli, which could offer more insights into the temporal

dynamics of perceptual and conceptual feature integration in the brain.

Contrasting image- and word-based models within each object
dimension

The superior fit of the Perceptual-image model compared to the Perceptual-

word model across a broad time range of approximately 100-330 ms suggests that

perceptual features evoked by directly viewing object images better explain the EEG

than those evoked by reading word labels. As discussed earlier, reading word labels

requires a degree of mentalisation to evoke perceptual features, which may vary

significantly across participants. The variability likely limits the explanatory power of

the Perceptual-word model compared to the Perceptual-image model. In contrast,

there was no evidence that the two conceptual models based on different modalities

differed in their explanatory power. Moreover, incorporating the Conceptual-word and

Conceptual-image models into a single analysis did not reduce either model's partial

correlation to zero (Figure S1 in Supplementary Materials), raising the possibility that

the two captured somewhat distinct elements of objects' conceptual attributes. This

could reflect different ways of accessing conceptual knowledge: image-cued

activation may involve processing visual features to retrieve associated conceptual

attributes, while word-cued activation relies on lexical processing to access the

conceptual knowledge of the object stored in the brain.

Contextual object associations do not uniquely predict neural responses

to objects

In contrast to the relatively clear connection between the perceptual and

conceptual models and the neural data, we found only fleeting evidence that the

models of objects' contextual associations uniquely explained the neural response to

object images. This evidence was limited to Experiment 2 neural dataset, and

corresponded to timepoints from 384 ms onwards. The minimal explanatory power of

the contextual models was surprising given that prior studies have found that

observers are highly sensitive to violations of object context (Bar, 2004; Biederman et

al., 1973; Davenport & Potter, 2004; Ganis & Kutas, 2003; Mudrik et al., 2010; Mudrik

et al., 2014; Oliva & Torralba, 2007; Quek & Peelen, 2020; Võ et al., 2019), and

recognise objects more efficiently when they appear alongside related objects

(Auckland et al., 2007; Bar & Ullman, 1996; Davenport, 2007; Green & Hummel,

2006; Kaiser et al., 2014, 2019; Quek et al., 2025). As such, we might well have

expected information about objects' contextual associations might well be carried in

the evoked responses to object images.

One possible explanation for the lack of unique explanatory power for our

contextual attribute models concerns the overlap in conceptual and contextual

features of our selected 190 object concepts. Indeed, although both the Contextual-

word and Contextual-image model *did* predict neural responses when considered in

isolation (i.e., without other models as covariates), they lost most of their explanatory

power when the conceptual model from the same modality was included as a

covariate. Previous studies have found that the parahippocampal cortex encodes the

contextual representation of objects, specifically how certain objects tend to co-occur

with one another within a context (Aminoff et al., 2013; Bar, 2004). Martin and

colleagues also found in their fMRI-RSA analysis that conceptual representations

were activated in parahippocampal cortex when participants were engaged in a task

that evoked conceptual features (Martin et al., 2018). In line with their findings, our

results also seem to demonstrate that objects that tend to occur in the same context

often share many conceptual features but can be visually distinct (e.g., a toothbrush

and toothpaste). Our study also extends this further by demonstrating that in time-

resolved whole-brain EEG response to object images, contextual features, whether

derived from images or words, were not uniquely processed by the brain on top of

conceptual features; rather, they were processed as part of conceptual processing.

Another, non-mutually-exclusive possibility is that contextual associations between

object concepts are represented most strongly when two (or more) objects are

encountered simultaneously (as has often been the case in prior studies examining

contextual relations between objects). Future studies seeking to disentangle the

neural timecourse of contextual object knowledge from its perceptual and conceptual

counterparts might exploit such multi-object processing paradigms (Quek et al., 2025;

Quek & Peelen, 2020), in which the strength of conceptual and contextual object

associations could be strictly orthogonalised.

Conclusion

Our study demonstrates the brain's robust and cascaded integration of

perceptual and conceptual features in forming object representations. Using RSA to

correlate EEG responses with behavioural models, we found that perceptual features

dominate early neural responses, while conceptual features emerge later. These

findings were consistent across different behavioural task modalities and EEG

datasets. Notably, although contextual associations between objects did meaningfully

predict the structure of neural object representations, this explanatory power

overlapped significantly with models of conceptual object features. By using

functionally relevant models of different object dimensions, this work provides insight

into how these dimensions are generally represented when observers look at objects.

Together, these findings contribute to our understanding of the brain's dynamic

processing of visual objects.

5. REFERENCES

Almeida, J., Fracasso, A., Kristensen, S., Valério, D., Bergström, F., Chakravarthi, R., . . . Walbrin, J. (2023). Neural and behavioral signatures of the multidimensionality of manipulable object processing. *Communications Biology, 6*(1), 940. doi:10.1038/s42003-023-05323-x

Aminoff, E. M., Kveraga, K., & Bar, M. (2013). The role of the parahippocampal cortex in cognition. *Trends in Cognitive Sciences, 17*(8), 379-390. doi:10.1016/j.tics.2013.06.009

Auckland, M. E., Cave, K. R., & Donnelly, N. (2007). Nontarget objects can influence perceptual processes during object recognition. *Psychonomic Bulletin & Review, 14*(2), 332-337.

Bankson, B. B., Hebart, M. N., Groen, I. I. A., & Baker, C. I. (2018). The temporal evolution of conceptual object representations revealed through models of behavior, semantics and deep neural networks. *Neuroimage, 178*, 172-182. doi:https://doi.org/10.1016/j.neuroimage.2018.05.037

Bar, M. (2004). Visual objects in context. *Nature Reviews Neuroscience, 5*(8), 617.

Bar, M., & Ullman, S. (1996). Spatial Context in Recognition. *Perception, 25*(3), 343-352. doi:10.1068/p250343

Biederman, I., Glass, A. L., & Stacy, E. W. (1973). Searching for objects in real-world scenes. *Journal of Experimental Psychology, 97*(1), 22-27. doi:10.1037/h0033776

Brandman, T., & Peelen, M. V. (2017). Interaction between Scene and Object Processing Revealed by Human fMRI and MEG Decoding. *Journal of Neuroscience, 37*(32), 7700-7710. doi:10.1523/jneurosci.0582-17.2017

Carlson, T., Tovar, D. A., Alink, A., & Kriegeskorte, N. (2013). Representational

dynamics of object vision: the first 1000 ms. *Journal of Vision, 13*(10), 1.

Cichy, R. M., Kriegeskorte, N., Jozwik, K. M., van den Bosch, J. J. F., & Charest, I.

(2019). The spatiotemporal neural dynamics underlying perceived similarity for

real-world   objects.   *Neuroimage,   194*,   12-24.

doi:https://doi.org/10.1016/j.neuroimage.2019.03.031

Cichy, R. M., Pantazis, D., & Oliva, A. (2014). Resolving human object recognition in

space and time. *Nature Neuroscience, 17*(3), 455-462. doi:10.1038/nn.3635

Clarke, A., Taylor, K. I., Devereux, B., Randall, B., & Tyler, L. K. (2012). From

Perception to Conception: How Meaningful Objects Are Processed over Time.

Cerebral Cortex, 23(1), 187-197. doi:10.1093/cercor/bhs002

Clarke, A., & Tyler, L. K. (2015). Understanding What We See: How We Derive

Meaning From Vision. *Trends in Cognitive Sciences, 19*(11), 677-687.

doi:10.1016/j.tics.2015.08.008

Contini, E. W., Goddard, E., Grootswagers, T., Williams, M., & Carlson, T. (2020). A

humanness dimension to visual object coding in the brain. *Neuroimage*,

117139. doi:https://doi.org/10.1016/j.neuroimage.2020.117139

Contini, E. W., Wardle, S. G., & Carlson, T. A. (2017). Decoding the time-course of

object recognition in the human brain: From visual features to categorical

decisions.   *Neuropsychologia,   105*,   165-176.

doi:https://doi.org/10.1016/j.neuropsychologia.2017.02.013

Davenport, J. L. (2007). Consistency effects between objects in scenes. *Memory &*

Cognition, 35(3), 393-401. doi:10.3758/bf03193280

Davenport, J. L., & Potter, M. C. (2004). Scene Consistency in Object and

1035   Background Perception. *Psychological Science, 15*(8), 559-564.

1036   doi:10.1111/j.0956-7976.2004.00719.x

1037   Delorme, A., & Makeig, S. (2004). EEGLAB: an open source toolbox for analysis of

1038   single-trial EEG dynamics including independent component analysis. *Journal*

1039   *of Neuroscience Methods, 134*(1), 9-21.

1040   doi:https://doi.org/10.1016/j.jneumeth.2003.10.009

1041   Edelman, S. (1998). Representation is representation of similarities. *Behavioral and*

1042   *Brain Sciences, 21*(4), 449-467. doi:10.1017/S0140525X98001253

1043   Ganis, G., & Kutas, M. (2003). An electrophysiological study of scene effects on

1044   object identification. *Brain Research: Cognitive Brain Research, 16*(2), 123-

1045   144. doi:10.1016/s0926-6410(02)00244-6

1046   Giari, G., Leonardelli, E., Tao, Y., Machado, M., & Fairhall, S. L. (2020).

1047   Spatiotemporal properties of the neural representation of conceptual content

1048   for words and pictures – an MEG study. *Neuroimage, 219*, 116913.

1049   doi:https://doi.org/10.1016/j.neuroimage.2020.116913

1050   Green, C., & Hummel, J. E. (2006). Familiar interacting object pairs are perceptually

1051   grouped. *Journal of Experimental Psychology: Human Perception and*

1052   *Performance, 32*(5), 1107.

1053   Grootswagers, T., Robinson, A. K., & Carlson, T. (2019a). The representational

1054   dynamics of visual objects in rapid serial visual processing streams.

1055   *Neuroimage, 188*, 668-679.

1056   doi:https://doi.org/10.1016/j.neuroimage.2018.12.046

Grootswagers, T., Robinson, A. K., Shatek, S. M., & Carlson, T. A. (2019b).

Untangling featural and conceptual object representations. *Neuroimage, 202*,

116083.

Grootswagers, T., Wardle, S. G., & Carlson, T. (2017). Decoding dynamic brain

patterns from evoked responses: A tutorial on multivariate pattern analysis

applied to time series neuroimaging data. *Journal of Cognitive Neuroscience,*

29(4), 677-697. doi:10.1162/jocn_a_01068

Grootswagers, T., Zhou, I., Robinson, A. K., Hebart, M. N., & Carlson, T. A. (2022).

Human EEG recordings for 1,854 concepts presented in rapid serial visual

presentation streams. *Scientific Data, 9*(1), 3. doi:10.1038/s41597-021-01102-

7

Hebart, M. N., Contier, O., Teichmann, L., Rockter, A. H., Zheng, C. Y., Kidder, A., . .

. Baker, C. I. (2023). THINGS-data, a multimodal collection of large-scale

datasets for investigating object representations in human brain and behavior.

eLife, 12, e82580. doi:10.7554/eLife.82580

Hebart, M. N., Dickter, A. H., Kidder, A., Kwok, W. Y., Corriveau, A., Van Wicklin, C.,

& Baker, C. I. (2019). THINGS: A database of 1,854 object concepts and more

than 26,000 naturalistic object images. *PloS One, 14*(10), e0223792.

doi:10.1371/journal.pone.0223792

Hebart, M. N., Zheng, C. Y., Pereira, F., & Baker, C. I. (2020). Revealing the

multidimensional mental representations of natural objects underlying human

similarity judgements. *Nature Human Behaviour, 4*(11), 1173-1185.

doi:10.1038/s41562-020-00951-3

Isik, L., Meyers, E. M., Leibo, J. Z., & Poggio, T. (2014). The dynamics of invariant

object recognition in the human visual system. *Journal of Neurophysiology,*

111(1), 91-102. doi:10.1152/jn.00394.2013

Kaiser, D., Quek, G. L., Cichy, R. M., & Peelen, M. V. (2019). Object Vision in a

Structured World. *Trends in Cognitive Sciences, 23*(8), 672-685.

doi:10.1016/j.tics.2019.04.013

Kaiser, D., Stein, T., & Peelen, M. V. (2014). Object grouping based on real-world

regularities facilitates perception by reducing competitive interactions in visual

cortex. *Proceedings of the National Academy of Sciences of the United States*

of America, 111(30), 11217-11222.

Kok, P., Brouwer, G. J., van Gerven, M. A. J., & de Lange, F. P. (2013). Prior

Expectations Bias Sensory Representations in Visual Cortex. *The Journal of*

Neuroscience, 33(41), 16275-16284. doi:10.1523/jneurosci.0742-13.2013

Kosslyn, S. M., Thompson, W. L., Klm, I. J., & Alpert, N. M. (1995). Topographical

representations of mental images in primary visual cortex. *Nature, 378*(6556),

496-498. doi:10.1038/378496a0

Kriegeskorte, N., Mur, M., & Bandettini, P. (2008). Representational Similarity

Analysis – Connecting the Branches of Systems Neuroscience. *Frontiers in*

Systems Neuroscience, 2, 4. doi:10.3389/neuro.06.004.2008

Martin, C. B., Douglas, D., Newsome, R. N., Man, L. L. Y., & Barense, M. D. (2018).

Integrative and distinctive coding of visual and conceptual object features in

the ventral visual stream. *eLife, 7*, e31873. doi:10.7554/eLife.31873

Mechelli, A., Price, C. J., Friston, K. J., & Ishai, A. (2004). Where Bottom-up Meets

Top-down: Neuronal Interactions during Perception and Imagery. *Cerebral*

Cortex, 14(11), 1256-1265. doi:10.1093/cercor/bhh087

Moerel, D., & Grootswagers, T. (2025). Reconstruction of Partial Dissimilarity
Matrices for Cognitive Neuroscience. *arXiv preprint arXiv:2506.00484*.

Moerel, D., Psihoyos, J., & Carlson, T. A. (2024). The Time-Course of Food
Representation in the Human Brain. *The Journal of Neuroscience, 44*(26),
e1101232024. doi:10.1523/jneurosci.1101-23.2024

Morey, R. D., & Rouder, J. N. (2011). Bayes factor approaches for testing interval null
hypotheses. *Psychological Methods, 16*(4), 406-419. doi:10.1037/a0024377

Morey, R. D., Rouder, J. N., Jamil, T., & Morey, M. R. D. (2015). Package
'bayesfactor'. In.

Mudrik, L., Lamy, D., & Deouell, L. Y. (2010). ERP evidence for context congruity
effects during simultaneous object–scene processing. *Neuropsychologia,*
48(2), 507-517.

Mudrik, L., Shalgi, S., Lamy, D., & Deouell, L. Y. (2014). Synchronous contextual
irregularities affect early scene processing: Replication and extension.
Neuropsychologia, 56, 447-458.
doi:https://doi.org/10.1016/j.neuropsychologia.2014.02.020

Nosofsky, R. M. (1986). Attention, similarity, and the identification-categorization
relationship. *Journal of Experimental Psychology: General, 115*(1), 39-61.
doi:10.1037//0096-3445.115.1.39

O'Craven, K. M., & Kanwisher, N. (2000). Mental Imagery of Faces and Places
Activates Corresponding Stimulus-Specific Brain Regions. *Journal of Cognitive*
Neuroscience, 12(6), 1013-1023. doi:10.1162/08989290051137549

Oliva, A., & Torralba, A. (2007). The role of context in object recognition. *Trends in*
Cognitive Sciences, 11(12), 520-527.
doi:https://doi.org/10.1016/j.tics.2007.09.009

Oostenveld, R., & Praamstra, P. (2001). The five percent electrode system for high-

resolution EEG and ERP measurements. *Clinical Neurophysiology, 112*(4),

713-719. doi:https://doi.org/10.1016/S1388-2457(00)00527-7

Oosterhof, N. N., Connolly, A. C., & Haxby, J. V. (2016). CoSMoMVPA: Multi-Modal

Multivariate Pattern Analysis of Neuroimaging Data in Matlab/GNU Octave.

Frontiers in Neuroinformatics, 10. doi:10.3389/fninf.2016.00027

Pearson, J., Naselaris, T., Holmes, E. A., & Kosslyn, S. M. (2015). Mental Imagery:

Functional Mechanisms and Clinical Applications. *Trends in Cognitive*

Sciences, 19(10), 590-602. doi:10.1016/j.tics.2015.08.003

Peirce, J., Gray, J. R., Simpson, S., MacAskill, M., Höchenberger, R., Sogo, H., . . .

Lindeløv, J. K. (2019). PsychoPy2: Experiments in behavior made easy.

Behavior Research Methods, 51(1), 195-203. doi:10.3758/s13428-018-01193-

y

Proklova, D., Kaiser, D., & Peelen, M. V. (2019). MEG sensor patterns reflect

perceptual but not categorical similarity of animate and inanimate objects.

Neuroimage,   193,   167-177.

doi:https://doi.org/10.1016/j.neuroimage.2019.03.028

Quek, G. L., & Peelen, M. V. (2020). Contextual and Spatial Associations Between

Objects Interactively Modulate Visual Processing. *Cerebral Cortex, 30*(12),

6391-6404. doi:10.1093/cercor/bhaa197

Quek, G. L., Theodorou, A., & Peelen, M. V. (in press). The timecourse of inter-object

contextual facilitation. *Cortex*. doi:10.1101/2023.05.30.542965

Teichmann, L., Hebart, M. N., & Baker, C. I. (2025). Dynamic representation of

multidimensional object properties in the human brain. *bioRxiv*.

doi:10.1101/2023.09.08.556679

Teichmann, L., Moerel, D., Baker, C., & Grootswagers, T. (2022). An Empirically

Driven Guide on Using Bayes Factors for M/EEG Decoding. *Aperture Neuro*.

doi:10.52294/ApertureNeuro.2022.2.MAOC6465

Võ, M. L. H., Boettcher, S. E. P., & Draschkow, D. (2019). Reading scenes: how

scene grammar guides attention and aids perception in real-world

environments. *Current Opinion in Psychology, 29*, 205-210.

doi:https://doi.org/10.1016/j.copsyc.2019.03.009

Wardle, S. G., Kriegeskorte, N., Grootswagers, T., Khaligh-Razavi, S.-M., & Carlson,

T. A. (2016). Perceptual similarity of visual patterns predicts dynamic neural

activation patterns measured with MEG. *Neuroimage, 132*, 59-70.

doi:https://doi.org/10.1016/j.neuroimage.2016.02.019

Wischnewski, M., & Peelen, M. V. (2021). Causal neural mechanisms of context-

based object recognition. *eLife, 10*, e69736. doi:10.7554/eLife.69736

1168