Human intention inference with a large language model can enhance

brain-computer interface control: A proof-of-concept study

Authors

Shue Shiinoki[1], Seitaro Iwama[2], Junichi Ushiba[2*]

[1] Graduate School of Science and Technology, Keio University, Kanagawa, Japan

[2] Department of Biosciences and Informatics, Faculty of Science and Technology, Keio

University, Kanagawa, Japan

*Correspondence

Junichi Ushiba, Ph.D.

Department of Biosciences and Informatics, Faculty of Science and Technology, Keio

University, 3-14-1 Hiyoshi, Kouhoku-ku, Yokohama, Kanagawa 223-8522, Japan.

Tel/Fax: +81-45-566-1678.

Email: ushiba@bio.keio.ac.jp

Abstract

Brain-computer interface (BCI) control enables direct communication between the brain and external devices. However, BCI control accuracy with intention inferred from non-invasive modalities is limited, even when using data-driven approaches to tailor neural decoders. In this study, we propose a knowledge-driven framework for inferring human intention, leveraging large language models (LLMs) as an alternative to conventional data-driven approaches. We developed a neural decoder that integrates neural and oculomotor signals with contextual information using an LLM agent. Its feasibility was tested in a real-world BCI task to control a computer application. The LLM-based decoder achieved an average accuracy of 79% for responders (11 out of 20) in inferring the intention to select arbitrary posts in a social networking service. Ablation analyses revealed that integration of contextual information, multimodal signals, and empirical knowledge is critical for decoding accuracy. This study demonstrates the feasibility of a neural decoding framework using an LLM, paving the way for improved performance in BCI-driven external device operation for patients with disability.

Keywords

Brain-Computer Interface; Neural Decoding; Context Inference; Large Language Model; Motor Imagery

Highlights

- Large language models can infer human intent from neural and oculomotor signals integrated with screen context.

40 • The proposed model performed with higher accuracy compared with data-driven

41   approaches.

42 • Ablation analyses revealed that integrating contextual information, multi-modal signals,

43   and empirical knowledge is critical for decoding accuracy.

Introduction

A brain-computer interface (BCI) that can bypass human motor pathways to express user

volition has been desired for augmented alternative communication[1–5]. To achieve this, a

computational model, namely a neural decoder, is employed to infer user intentions

embedded in real-time acquired neural signals[6–8]. The decoder plays a critical role in a

BCI system, as the decoded results, transformed into device control, need to be accurate

enough to reconstruct user intentions. The accuracy from noninvasive modalities has

been significantly increased over the decades owing to the development of statistics and

machine learning algorithms[9,10].

One of the representative approaches to enhance the BCI performance is deep

learning, which is a data-driven representation learning from minimally preprocessed

neural signals[8,11,12]. A variety of network structures, such as a recurrent neural network or

a convolutional neural network (CNN), have been proposed to extract features from

neural signals[13,14] without prior knowledge and assumptions about models. The CNN-

based models have demonstrated consistently high performance, leading to the

development of derivative models aimed at improving accuracy, generalization across

various tasks, and generalization across subjects[8,11,14–19].

Despite astonishing demonstrations using deep learning technology harnessing its

high generalization performance and superior accuracy in various fields, such as image

processing or sound recognition[20–22], no such breakthroughs have been achieved in

neural decoding, especially when using low-fidelity neural measurements represented by

scalp electroencephalogram (EEG) as a readout of human cortical activities. It would be

because the limited length of experimental time makes it impractical to collect a dataset

covering a vast data space, which is essential to learn a data representation generalizable

across datasets, calling for a method to alleviate the fully data-driven nature of existing

approaches.

An alternative approach for data-driven model training is to incorporate knowledge-

driven signal observation. For instance, in the Bayesian framework, the prior knowledge

can be used for initiating the training from a better probability distribution. Further, a more

flexible embedding of prior knowledge can be achieved via a large language model (LLM)

as a processing block for inference. LLM can be a suitable solution for situations with

limited neural training data since it contains neurophysiological knowledge usable for

decoding as a supplement to the input signals. Indeed, LLMs have demonstrated human-

level, exceptional knowledge-driven reasoning abilities in recommendation systems[23],

lifelong learning[24], and autonomous driving tasks[25,26]. For instance, in autonomous driving

tasks, LLM systems mimicking human-like decision-making based on common-sense

and past experiences have achieved highly generalized autonomous driving through

causal reasoning, outperforming existing reinforcement learning-based methods[25,26].

Here, we propose a multimodal decoding system for decoding motor intentions and

operation targets from EEG and eye movements based on knowledge-driven reasoning

using LLM. We tested its effectiveness in BCI control in a real-world scenario. Participants

operated the BCI during the use of social networking service to evaluate the feasibility of

the system. The performance of the LLM decoders was compared among models that

partially knocked out the input and knowledge, with data-driven models, and with

analyses on the discrimination results. We hypothesized that the LLM-based BCI decoder

is achieved by the integration of the observation of multimodal signals, instructions for

decoding, and a small number of training data derived from the participants.

Results

Decoder architecture

In this proof-of-concept study, we propose a decoder framework that can integrate EEG

and oculomotor signals, contextual information, knowledge, and a few samples of data

useful for EEG decoding, which were all integrated and fed into an LLM agent during BCI

operation (Fig.1, Supplementary Movie). The LLM agent was instructed to reason out

which content shown in the PC display the user selected. All input data were transformed

into texts using modules designed for an LLM agent to refer to based on the instruction.

The LLM agent employs the "chain of thought" process for human intention

inference, a methodology that has been successfully applied in other fields, such as

autonomous driving. In this study, we utilized the ReAct framework[25,27] to facilitate

reasoning based on the common knowledge embedded in the LLM, integrating logical

reasoning with information extracted from acquired signals, as well as physiological and

heuristic knowledge provided as prompts. The React framework addresses the final

decision-making problem (i.e., determining where the user is paying attention or whether

they intend to press a button) by iteratively selecting an action based on inferred results,

observing the outcomes of that action, and then reasoning about those outcomes.

To achieve this, the system leveraged multiple information sources as agent tools

(candidate actions), including references to action intention choices, EEG feature

calculations, the number of solid viewpoints in each tweet display area, and the spatial

distribution of solid viewpoints. Additionally, environmental data such as tweet and button

coordinates, UI information, and physiological knowledge were incorporated as prior

information (Fig. 1b). The prompts were generated from text data with integration of those

describing EEG decoding knowledge (See Supplementary Information), and those

describing the few-shot EEG datasets acquired before the BCI operation, and they were

passed to an LLM agent. The model performs the reasoning according to a defined format

and finally outputs the operation commands.

The proposed decoder is feasible to infer the user intention

Before the formal evaluation of decoder accuracy, the signal quality of EEG and eye gaze

signals was visually inspected. For the EEG signals, the temporal, spatial, and spectral

information of EEG used for neural decoding was extracted by spatio-spectral

decomposition (SSD) algorithm[28] to visualize time-frequency representations

(Supplementary Fig. 1). For the eye gaze signal, we visualized scan path maps indicating

sequences of fixations on displays.

First, we asked if the proposed LLM decoder was able to perform neural decoding.

We stratified participants based on the responsiveness of scalp EEG signals: the subjects

were grouped into responder and non-responder groups. The responders were selected

based on SMR-ERD magnitude (Fig. 2a). We evaluated decoding accuracy of action and

target selection (i.e, both "push like" or "read" selection and the tweet selection), and that

of action detection alone. The results showed that the responder group was superior to

the non-responder group in both overall decoding and action decoding alone (Fig. 2b and

Supplementary Fig. 2a, *t*-test, $p < 0.05$, Cohen's d = 2.86, 2.94), suggesting that the

proposed decoding approach is feasible for the two groups and dependent on

responsiveness of SMR-ERD.

Next, we examined the influence of action decoding accuracy on target decoding

accuracy to evaluate the interaction of the two decoding procedures. To this aim, target

decoding accuracy was compared between trials in which motor intention was correctly

or incorrectly detected. We found that target decoding accuracy was significantly more

accurate when motor intention was correctly detected (Fig. 2c, Paired *t*-test, $p < 0.05$,

Cohen's d = 1.88). Moreover, when target selection was correct, action decoding

accuracy was also significantly higher (Supplementary Fig. 2b, Paired *t*-test, $p < 0.05$,

Cohen's d = 1.58). Therefore, our findings suggest that successful motor intention

decoding is associated with higher target decoding accuracy.

Multimodal signal input, prior knowledge, and few-shot information are necessary for

effective decoding

In the present study, multimodal data, namely neural and oculomotor movements, were

used in an integrated manner for human intention inference. We examined the

contribution of each modality to the decoding performance. First, we conducted an

ablation study for input modalities (Fig. 3a). The prompt was modified to perform the same

inference as the original model. A repeated measures analysis of variance (rmANOVA)

revealed that there was a significant decline in the overall decoding accuracy (Main effect:

F = 3.45, $p < 0.05$; Post-hoc pair-wise *t*-test, EEG (+), Gaze (+) and EEG (+), Gaze (-): *t*

= 3.3, $p < 0.05$, Cohen's d = 1.04, EEG (+), Gaze (+) and EEG (-), Gaze (+): *t* = 2.4, $p <$

0.05, Cohen's d = 0.77), indicating that the decoder with both signals was significantly

more accurate than a single decoder for both eye movements and EEG.

Next, we analyzed the impact of two factors on decoding performance: empirical

knowledge of EEG decoding, provided in the prompts as essential knowledge for

decoding, and few-shot data of EEG features from the first few trials, included as past

decoding experience (Fig. 3b). To examine whether knowledge can substitute for

experience and whether performance is maintained even with a small amount of few-shot

data when knowledge is provided, a two-way rmANOVA was conducted. The independent

variables were the presence of empirical knowledge and the amount of few-shot data,

while the dependent variable was accuracy. The results showed significant main effects

for both factors, but not interaction. Post-hoc tests indicated that when heuristic

knowledge was included in the prompt, performance was significantly higher for 0-shot,

1-shot, 5-shot, and 10-shot conditions (Paired t-test, $p<0.05$, Cohen's d = 1.08, 0.98, 0.55,

0.39, Bonferroni correction for multiple comparisons). Here, the number of "shots" refers

to the number of trials provided, with each trial containing four sample data points.

Furthermore, 10-shot decoding performed significantly better than both 0-shot and 5-shot

conditions (Paired t-test, $p < 0.05$, Cohen's d = 1.84, 0.60, Bonferroni correction for

multiple comparisons).

Comparison with other data-driven decoder architectures

The decoding performance of the knowledge-driven approach was examined in

comparison with data-driven methods. Here, we compared the performance with that of

CNN and Light Gradient Boosting Machine (Light GBM). The basic type of input for the

CNN-based EEG decoder is raw data. However, for the comparison, the CNN model also

received SMR-ERD data as input for the LLM in the study.

We compared decoding performance among multiple CNN model and the

proposed knowledge-driven model (Fig. 4a). We compared the accuracy of the LLM

decoder which uses 10 trials of data from the same subject as few-shot prompts with

several versions of EEGNet[17] trained on varying amounts of data: Fine-tuning (10 trials):

Trained from scratch using 10 trials of data from the same subject, matching the number

of trials used in the LLM decoder. Fine-tuning (50 trials): Trained with 50 trials (i.e., 5

sessions) of data from the same subject. Pretraining + Fine tuning (pretrained + 10 trials):

First pre-trained on 500 trials from other subjects, then fine-tuned using 10 trials from the

same subject as in the test. The 10-shot LLM decoder showed significantly higher

accuracy for the CNN 5 sessions and the CNN 1 session (Paired t-test, $p < 0.05$, Cohen's

d = 1.23, 1.09). This suggests that the performance of the LLM decoder is comparable to

that of a CNN decoder with pre-training + finetuning.

To further validate the superiority of the LLM over decision tree-based prediction,

we also constructed a model using LightGBM[29] with the same ERD features used as

inputs to the LLM. We then compared the decoding accuracy of the 10-shot LLM decoder

with that of the LightGBM model trained on data from 5 sessions and 1 session (Fig. 4b).

The results showed that the 10-shot LLM was significantly more accurate than the 1-

session Light GBM. (Paired t-test, $p < 0.05$, Cohen's d = 1.5).

Discussion

In the present study, we investigated whether the LLM-based neural decoder architecture

is feasible and capable of inferring human movement intention and its target. Through the

performance evaluation and ablation analyses, we demonstrate that the proposed LLM-

based neural decoder effectively infers human movement intentions and target selections

by integrating neural and oculomotor signals with contextual and empirical knowledge.

Specifically, the decoder achieved significantly higher accuracy for responders, with

successful motor intention decoding closely linked to improved target selection. Ablation

analyses revealed that multimodal signal integration, empirical knowledge, and few-shot

learning all significantly contributed to decoding performance, with knowledge-driven

inference mitigating the limitations of limited training data. These results support the

feasibility of an LLM-driven approach for enhancing BCI control accuracy under a limited

amount of data.

The limited amount of available datasets from an individual has critically hindered the

establishment of a high-performance decoder for EEG signals. Compared to the fields of

image and natural language, the training size is typically in the more than 10 million

scale[13,21], with a correspondingly large parameter size and capacity of the model, as well

as the data to train it. On the other hand, the deep learning models used in EEG are

generally very small due to the small amount of data available for training, making it

difficult to capture complex representations. Thus, data-driven algorithms in EEG

decoding have attempted to improve performance by compacting parameter sizes and

regularization methods[17,18], but still have limited classification performance and

generalization capabilities[11,14]. In contrast, the present LLM-based architecture allows

researchers to implement decoding techniques and include them in top-down inference

assumptions by prompting them. We showed that by leveraging knowledge-driven

inference using an LLM, and developed a system architecture that can infer motion

intention from less than 50 trials of data. With a small amount of data and a text-based

account of decoding, the model would be beneficial for EEG decoding, where data-driven

approaches have been limited by data size.

Previous studies have attempted to augment degrees of freedom by separately using

multimodal signals such as gaze movements and EEG. The approach enables

simultaneous decoding of interaction targets and behavioral intentions based on gaze

and EEG signals, respectively. However, the separate use of these signals could hamper

the extraction of information related to movement intention from gaze signals and *vice*

versa[30–32]. Specifically, eye movements not only convey information about the object to

be manipulated but also reflect behavioral intentions, such as the user's intent to interact

with an object when fixating on it or the anticipation of the next task indicated by shifts in

gaze[33–36]. The significantly better performance of simultaneous EEG and eye movements

input than EEG alone suggests the usefulness of integrated EEG and eye movements

decoding. In addition, conventional data-driven methods have the problem that learning

information from different modalities in the same model in an integrated manner requires

a more complex model due to the no-free-lunch theorem, resulting in a larger data set

required. However, LLMs can be easily integrated if a descriptor can be constructed to

represent each modal appropriately using prior knowledge and the generic input format

of natural language, as demonstrated in the present study.

As demonstrated in the ablation analysis for the prompting for LLM (Fig. 3b), we found

that the decoding performance is improved using the few-shot prompting even when

physiological or empirical knowledge about EEG decoding is provided as input. If the

performance degradation observed with a small amount of few-shot data is mitigated by

the inclusion of empirical knowledge, it suggests that the knowledge compensates for the

useful decoding information that the LLM would otherwise extract from the few-shot data.

This implies that the empirical knowledge supplements, rather than replaces, information

essential for decoding. However, our results indicate that both few-shot prompting and

empirical knowledge independently contributed to performance improvements. This

suggests that, in addition to the physiological and empirical knowledge provided as text,

the LLM also derives useful decoding information from the few-shot data. One possible

source of such information is the subject-specific characteristics of EEG signals,

particularly in relation to ERD. Previous studies have shown that inter-subject variability

in EEG features, such as ERD intensity and variability, constrains the performance of

conventional data-driven decoding approaches. Our findings imply that the LLM

leverages these subject-specific ERD characteristics from the few-shot data input,

thereby enhancing inferential performance.

Although the present study demonstrated that the concept of performing knowledge-

driven inference of behavioral intentions, including motor intentions, from a small amount

of data using LLM, there are several limitations. First, the inter-/intra-subject

generalization of performance was limited by the ability to stably generate SMR-ERDs.

Currently, the ability of this inference system to accurately classify behavioral intentions

is restricted to evaluation in the best sessions in which subjects with SMR-ERD reactivity

above a certain level were able to adequately represent SMR-ERDs throughout. Second,

although this inference system inputs all information to the LLM in text form, there are

examples of recent LLM research, such as multimodal LLMs that support image input,

which have been used in GUI control[37–39] and medical imaging[40]. In the present study,

the evaluation was restricted to text input so that the evaluation would not be influenced

by the accuracy with which the LLM extracts features from the input UI and signal images,

but image input is beneficial as a means of efficiently inputting information in the same

data representation format as when human researchers understand data. Third, the

latency of decoding is relatively large, resulting in an approximate 1-minute delay. This

delay primarily stems from our reliance on remote LLM inference via APIs, where network

overhead and the LLM's processing time significantly contribute to the overall latency. We

posit that this issue is technically minor, as it can be resolved by running the LLM locally

to eliminate external communication overhead. In addition, ongoing improvements in

hardware and software optimizations (e.g., more efficient inference algorithms) will further

reduce the response time of LLMs, thus alleviating the current latency challenge.

In summary, we demonstrated that the knowledge-based, LLM-driven neural

decoding approach is feasible for BCI control under a limited amount of data. This

framework allows the experimenter to design an appropriate prompt as the input for

inference, making it possible to use BCI architectures other than motor imagery-based

BCIs, such as P300-based speller or steady-state visual-evoked potential BCIs. The

proposed approach, based on previous physiological knowledge, would reduce the

calibration time without affecting the accuracy, marking a promising step toward practical

applications in assistive technologies.

290
Methods

Participants

Twenty neurologically healthy adults (19 males, 1 female; mean age $\pm$ SD; 24 $\pm$ 1.4

years) were informed of the aim of the experiments and gave informed written consent.

The experiment was approved by the local ethics committee of Keio University (IRB

approval number: 2024-009) and performed in accordance with the Declaration of

Helsinki. All participants were confirmed as right-handed with the Edinburgh Handedness

Inventory[41].

Experimental setup and protocol

EEG was recorded with a 128-channel HydroCel Geodesic Sensor Net from Electrical

Geodesics Incorporated (EGI, Eugene, Oregon, USA), with a sampling rate of 1000 Hz.

The impedance level of the EEG electrodes was kept below 50 kΩ throughout

experiments. In this study, a PC-operated social media application, "X", was used." X"

allows users to view short posts, commonly known as tweets, such as informational and

news posts from celebrities and friends, and to rate the tweets by 'liking' them. A display

showing the screen of an "X" content list was placed in front of the subject. Eye

movements were recorded at a sampling rate of 1200 Hz at the bottom of the display with

a Tobii Pro Spectrum screen-based eye tracker (Tobii Technology AB, Danderyds,

Stockholm, Sweden), which was synchronized with the display to avoid measurement

errors. Each subject performed the task of liking a tweet on the "X" GUI by motor imagery

while simultaneously measuring EEG and eye movements using the behavioral intention

decoding BCI described below.

The experiment consisted of one reference session and five evaluation sessions.

After each session, participants completed the Quebec Assistive Technology Satisfaction

Evaluation (QUEST) 2.0 questionnaire[42] and a free description questionnaire on their

perception of the use of this BCI system to validate its availability. Participants were

instructed to rest, read the on-screen content, and press the Like button with the motor

image over the time lapse shown in Fig. 1. During the trial, participants were instructed to

perform the task within the same screen without scrolling. To perform the task in a different

UI arrangement each trial, scrolling was performed at the end of the trial to update the

content to be displayed. The decoder reasoned four times during the trial. The decoder

performed reasoning on five seconds of measured data. Reasonings were made twice

on "read" and twice on "push like", for a total of four inferences. The reasoning results

were displayed as a GUI during the last "blank" of the trial, and the reasoning results were

manipulated with the cursor. The "blank" time was long enough, as inference takes 20-30

seconds.

EEG Processing

EEG analysis was used to input EEG information into the decoding system. The

recorded EEG signals were subjected to digital signal processing to remove artifacts. First,

a third-order Butterworth bandstop filter (50 Hz) and a third-order Butterworth bandpass

filter (3-70 Hz) were applied[43–45]. A spatial filtering technique called spatio-spectral

decomposition (SSD) was used on this processed signal, which is capable of extracting

neuronal oscillations with spatial patterns that correspond to SM1 activity[28]. The SSD

algorithm extracted neural oscillations at the individual alpha frequency (IAF), which

reflects the physiological properties of the EEG more effectively than a uniform frequency

band[46–48]. IAF was identified using the *specparam* algorithm[49], which parametrizes and

separates the periodic and aperiodic components of the EEG signals, and allows

calculation of the frequency at which the signal magnitude in the frequency band of

interest is maximum.

The input information of EEG to the decoding system was SMR-ERD, which

putatively reflects the sensorimotor excitability[50–52]. This is defined as the magnitude of

SMR-ERD for motor excitability as follows:

343
$$ERD(f,t) = \frac{A(f,t) - R(f)}{R(f)}$$

Where A represents the signal power of the EEG signals at time t and f represents the

frequency, R and represents the mean signal power of the previous 9 s and recalculated

in every 9 s (i.e., at the beginning of relaxation and imagery periods). The power was

calculated using a short-time Fourier transform with a 90% overlap of the 1-second sliding

window.

Eye movement processing

To input eye movement information into the decoding system, we employed a fixation to

represent the position on the screen where the user is gazing[53]. Fixation was extracted

by applying an I-VT filter, which extracts gazing and saccades based on eye movement

velocity at each time point, with a velocity threshold of 30°/s[54]. Fixations were defined as

sequences of gaze points where the velocity remained below the threshold for at least

100 ms. The fixation points were mapped to predefined screen coordinates, and fixation

clusters were further quantified per tweet to determine gaze allocation across stimuli.

Decoder Architecture

EEG, eye movements, environmental information in the form of X's UI information, and

knowledge of EEG decoding and past EEG data were all integrated and fed into a large

language model to reason the user's behavioral intentions. In the signal descriptor, the

EEG, eye movements, and UI information were each processed and converted into text

data. The details of each information processing are described below. Prompts were

generated from the text data of the signal/environmental information, the EEG decoding

knowledge text, and the text data of the measured few-shot EEG in the reference session

(see below) and were input into a large language model. The large language model

performs the reasoning according to a defined format and finally outputs the operation

commands. This was used as input to the application to perform the operations.

ERD time series data for a 5-second window was calculated from the EEG using

the online EEG analysis described above. For this time series data, we selected features

within the window. As a selection method, we first calculated all the candidate feature

values: mean, median, negative 1sd, 2sd, positive 1sd, 2sd, standard deviation,

maximum amplitude, location of maximum amplitude, maximum value, minimum value,

peak distance mean, zero crossing, number of positive values, number of negative values,

and volatility. A gradient boosting model (LightGBM[29]) was then trained to classify classes

using these features for the preliminary EEG data, and then the feature importance of the

model was calculated, and the eight features that were important were selected as the

features to be used. Finally, the mean, median, 1-sd, zero crossing, maximum amplitude

value, and location of maximum amplitude, negative percentage, and volatility were

selected as features.

The eye movements were used as input by processing the information on the solid

viewpoint extracted by the online analysis described earlier. The UI information, like the

eye movements, was processed into a form that well represented the user's object of

attention by being textualized as the two-dimensional range of existence of the eye

movements on the screen and the number of solid viewpoints on each tweet, which was

calculated in combination with the UI information. The text was converted into a form that

corresponds to the coordinates of the placement of the tweets and the coordinates of the

position of the Like button of each tweet.

Moreover, to facilitate knowledge-driven reasoning, we entered knowledge useful

for EEG decoding. The knowledge required for decoding EEG included physiological

knowledge to facilitate understanding that SMR-ERD is a biomarker of SM1 excitability

during motor imagery, heuristic knowledge in EEG signals observation as to how the

signal to be observed is affected by artifacts, and finally few-shot ERD data from EEG

measured during the reference session were entered.

Decoder Evaluation

First, significant body motion noise was observed in the data of one of the 20 subjects

who performed the experiment, and the quality of the EEG could not be guaranteed, so it

was excluded from the analysis. To purely evaluate the performance of the decoder, the

remaining 19 subjects were grouped by their SMR-ERD responsiveness, and

performance was evaluated for each of these groups. First, a one-sample t-test was

conducted in the trial direction for the ERD data of the IAF during each subject's reference

session, under the null hypothesis that the mean was zero. Then, subjects whose data

for the time interval in which the motor imagery was performed took a significantly non-

zero value in the negative direction for more than 50% of the time, as the length of time

was considered the High Responder group, and those who did not were considered the

Low Responder group.

The performance of the decoder was evaluated based on the accuracy of decoding

the presence or absence of the motor intentions "Read" and "Push Like," as well as the

accuracy of decoding the target tweets that were the target of the action. The decoding

performance of the entire behavioral intention, including the target decoding of which

tweet was the target of the action, was also evaluated. For the decoding of the entire

behavioral intention, we evaluated the self-reported results of which tweets the subject

"liked" at the end of the trial as the Ground Truth. In this study, two data sets were obtained

for "Push Like" and "Read" in each trial, and since no bias was observed between classes,

we evaluated them using overall accuracy.

For data-driven benchmarking, we implemented EEGNet[17]—a compact CNN

architecture optimized for EEG-based BCI tasks. The model included three convolutional

layers with batch normalization and dropout, and was trained using the Adam optimizer

with early stopping based on validation loss. Three training conditions were compared:

(1) 10-shot training with subject-specific data, (2) 5-session training from the same subject,

and (3) pretraining on 500 trials from other subjects followed by fine-tuning on 10 trials of

the target subject. All models used ERD features as input to ensure fairness in

comparison with the LLM-based decoder.

We compared the accuracy of the LLM decoder, which includes 10 trials of data in

the prompts as few-shot data, and the EEGNet, which is trained with various amounts of

data. We prepared a model trained with 10 trials of the same subject's data, which is the

same number of trials as the LLM decoder, a model trained with 5 sessions of the same

subject's data, which is 50 trials, and a model pre-trained with 500 trials of other subjects'

data, and then fine-tuned with 10 trials of the same subject's data. For the training of both

models, we employed early stopping, conducted 200 epochs of training, and confirmed

that the training converged when the patient's experience was set to 50.

To verify whether decoding by LLM is superior to mere decision tree analysis of each

feature, we conducted a Light GBM to classify "Read" and "Push Like". The model was

constructed and evaluated under the same training data conditions as those used for

CNN. We also employed early stopping for training and confirmed that the training

converged with a boost round of 2000 and an early stopping round of 300.

Statistical Analysis

All data were subjected to parametric tests after testing their normality using the Shapiro-

Wilk test. The multilevel datasets were subjected to mixed repeated measures ANOVA

and post-hoc pairwise *t*-tests with Bonferroni correction. The sphericity was tested using

Mauchly's sphericity test, and Greenhouse–Geisser correction was applied if necessary.

Paired datasets were subjected to paired *t*-tests.

Figures

Fig. 1 Schematic of the real-time human intention inference using an LLM agent.
The neural and oculomotor signals (i.e., Eye tracker and scalp electroencephalogram
(EEG) data) and contextual information (i.e., information about PC display content) were
individually processed and converted into text data at the first stage of the processing

pipeline. In parallel, the prior information was converted to text data. The physiological knowledge used for previous EEG-decoding studies, and a few samples of the EEG dataset acquired from the participants, were used for the LLM-based inference. After the inference, the PC cursor moved automatically to the predicted location where the participant aimed.

Fig. 2 Evaluation of decoding accuracy during brain-computer interfacing.
a. Participant-wise proportion of significant SMR-ERD at the first block. A cut-off threshold of 50% accuracy was used to split participants into responder and non-responder groups. Participants included in the responder group were highlighted. **b.** Between-group comparison of overall decoding accuracy for intended action and target. **c.** Comparisons of intention decoding accuracy between trials where the target was correctly or incorrectly estimated.

Fig. 3 Multimodal signals and prior knowledge are necessary for inference.
a. Accuracy of decoding based on multimodal and single-modal data conditions. **b.** Accuracy of decoding with prior knowledge and few-shot data.

Fig. 4 Comparisons of decoding accuracy with different decoder architectures. a. Decoding accuracy comparison with convolutional neural network (CNN) models. **b.** Decoding accuracy comparison with light gradient boosting machine (GBM) models.

References

1. Edelman, B. J. *et al.* Noninvasive neuroimaging enhances continuous neural tracking for robotic device control. *Science Robotics* **4**, eaaw6844 (2019).

2. Silva, A. B., Littlejohn, K. T., Liu, J. R., Moses, D. A. & Chang, E. F. The speech neuroprosthesis. *Nat. Rev. Neurosci.* **25**, 473–492 (2024).

3. Pandarinath, C. *et al.* High performance communication by people with paralysis using an intracortical brain-computer interface. *eLife* **6**, e18554 (2017).

4. Kosnoff, J., Yu, K., Liu, C. & He, B. Transcranial focused ultrasound to V5 enhances human visual motion brain-computer interface by modulating feature-based attention. *Nat Commun* **15**, 4382 (2024).

5. Défossez, A., Caucheteux, C., Rapin, J., Kabeli, O. & King, J.-R. Decoding speech

perception from non-invasive brain recordings. *Nat Mach Intell* **5**, 1097–1107 (2023).

6. Orsborn, A. L. *et al.* Closed-loop decoder adaptation shapes neural plasticity for skillful

neuroprosthetic control. *Neuron* **82**, 1380–1393 (2014).

7. Haxby, J. V., Connolly, A. C. & Guntupalli, J. S. Decoding neural representational

spaces using multivariate pattern analysis. *Annual Review of Neuroscience* **37**, 435–

456 (2014).

8. Schirrmeister, R. T. *et al.* Deep learning with convolutional neural networks for EEG

decoding and visualization. *Human Brain Mapping* **38**, 5391–5420 (2017).

9. Lotte, F., Congedo, M., Lécuyer, A., Lamarche, F. & Arnaldi, B. A review of

classification algorithms for EEG-based brain-computer interfaces. *Journal of Neural*

Engineering vol. 4 R1–R13 (2007).

10. Lotte, F. *et al.* A review of classification algorithms for EEG-based brain-computer

interfaces: A 10 year update. *Journal of Neural Engineering* **15**, 031005 (2018).

11. Altaheri, H. *et al.* Deep learning techniques for classification of electroencephalogram

(EEG) motor imagery (MI) signals: a review. *Neural Computing and Applications* **35**,

14681–14722 (2023).

12. LeCun, Y., Bengio, Y. & Hinton, G. Deep learning. *Nature* **521**, 436–444 (2015).

13. Krizhevsky, A., Sutskever, I. & Hinton, G. E. ImageNet Classification with Deep

Convolutional Neural Networks. in *Advances in Neural Information Processing*

Systems vol. 25 (Curran Associates, Inc., 2012).

14. Craik, A., He, Y. & Contreras-Vidal, J. L. Deep learning for electroencephalogram

(EEG) classification tasks: a review. *Journal of Neural Engineering* **16**, 031001 (2019).

15. Tabar, Y. R. & Halici, U. A novel deep learning approach for classification of EEG motor

imagery signals. *Journal of Neural Engineering* **14**, 016003 (2017).

16. Zhang, X. *et al.* A survey on deep learning-based non-invasive brain signals: recent

advances and new frontiers. *Journal of Neural Engineering* **18**, 031002 (2021).

17. Lawhern, V. J. *et al.* EEGNet: A compact convolutional neural network for EEG-based

brain-computer interfaces. *Journal of Neural Engineering* **15**, 56013–56030 (2018).

18. Dai, G., Zhou, J., Huang, J. & Wang, N. HS-CNN: a CNN with hybrid convolution scale

for EEG motor imagery classification. *Journal of Neural Engineering* **17**, 016025

(2020).

19. Rajwal, S. & Aggarwal, S. Convolutional Neural Network-Based EEG Signal Analysis:

A Systematic Review. *Archives of Computational Methods in Engineering* **30**, 3585–

3615 (2023).

20. He, K., Zhang, X., Ren, S. & Sun, J. Deep Residual Learning for Image Recognition.

in 770–778 (2016).

21. Devlin, J., Chang, M.-W., Lee, K. & Toutanova, K. BERT: Pre-training of Deep

Bidirectional Transformers for Language Understanding. in *Proceedings of the 2019*

Conference of the North American Chapter of the Association for Computational

Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers) (eds.

Burstein, J., Doran, C. & Solorio, T.) 4171–4186 (Association for Computational

Linguistics, Minneapolis, Minnesota, 2019). doi:10.18653/v1/N19-1423.

22. Brown, T. *et al.* Language Models are Few-Shot Learners. in *Advances in Neural*

Information Processing Systems vol. 33 1877–1901 (Curran Associates, Inc., 2020).

23. Yang, S. *et al.* Common Sense Enhanced Knowledge-based Recommendation with

Large Language Model. (2024) doi:10.48550/arXiv.2403.18325.

24. Zhu, X. *et al.* Ghost in the Minecraft: Generally Capable Agents for Open-World

Environments via Large Language Models with Text-based Knowledge and Memory.

(2023) doi:10.48550/arXiv.2305.17144.

25. Wen, L. *et al.* DiLu: A Knowledge-Driven Approach to Autonomous Driving with Large

Language Models. (2024) doi:10.48550/arXiv.2309.16292.

26. Fu, D. *et al.* Drive Like a Human: Rethinking Autonomous Driving with Large

Language Models. (2023) doi:10.48550/arXiv.2307.07162.

27. Yao, S. *et al.* ReAct: Synergizing Reasoning and Acting in Language Models. Preprint

at https://doi.org/10.48550/arXiv.2210.03629 (2023).

28. Nikulin, V. V., Nolte, G. & Curio, G. A novel method for reliable and fast extraction of

neuronal EEG/MEG oscillations on the basis of spatio-spectral decomposition.

NeuroImage **55**, 1528–1535 (2011).

29. Ke, G. *et al.* LightGBM: A Highly Efficient Gradient Boosting Decision Tree. in

Advances in Neural Information Processing Systems vol. 30 (Curran Associates, Inc.,

2017).

30. Simola, J., Le Fevre, K., Torniainen, J. & Baccino, T. Affective processing in natural

scene viewing: Valence and arousal interactions in eye-fixation-related potentials.

NeuroImage **106**, 21–33 (2015).

31. Lee, E. C., Woo, J. C., Kim, J. H., Whang, M. & Park, K. R. A brain–computer interface

method combined with eye tracking for 3D interaction. *Journal of Neuroscience*

Methods **190**, 289–298 (2010).

32.Plöchl, M., Ossandón, J. P. & König, P. Combining EEG and eye tracking: identification,

characterization, and correction of eye movement artifacts in electroencephalographic

data. *Frontiers in Human Neuroscience* **6**, (2012).

33. Zhu, H. *et al.* Frequency-encoded eye tracking smart contact lens for human–machine

interaction. *Nature Communications* **15**, 3588 (2024).

34. Orquin, J. L. & Mueller Loose, S. Attention and choice: A review on eye movements

in decision making. *Acta Psychologica* **144**, 190–206 (2013).

35. Eckstein, M. K., Guerra-Carrillo, B., Miller Singley, A. T. & Bunge, S. A. Beyond eye

gaze: What else can eyetracking reveal about cognition and cognitive development?

Developmental Cognitive Neuroscience **25**, 69–91 (2017).

36. Skaramagkas, V. *et al.* Review of Eye Tracking Metrics Involved in Emotional and

Cognitive Processes. *IEEE Reviews in Biomedical Engineering* **16**, 260–277 (2023).

37. Wang, J. *et al.* Mobile-Agent: Autonomous Multi-Modal Mobile Device Agent with

Visual Perception. (2024) doi:10.48550/arXiv.2401.16158.

38. You, K. *et al.* Ferret-UI: Grounded Mobile UI Understanding with Multimodal LLMs.

(2024) doi:10.48550/arXiv.2404.05719.

39. Nong, S. *et al.* MobileFlow: A Multimodal LLM For Mobile GUI Agent. (2024)

doi:10.48550/arXiv.2407.04346.

40. Panagoulias, D. P., Virvou, M. & Tsihrintzis, G. A. Evaluating LLM – Generated

Multimodal Diagnosis from Medical Images and Symptom Analysis. (2024)

doi:10.48550/arXiv.2402.01730.

41. Oldfield, R. C. The assessment and analysis of handedness: The Edinburgh inventory.

Neuropsychologia **9**, 97–113 (1971).

42. Demers, L., Monette, M., Lapierre, Y., Arnold, D. L. & Wolfson, C. Reliability, validity,

and applicability of the Quebec User Evaluation of Satisfaction with assistive

Technology (QUEST 2.0) for adults with multiple sclerosis. *Disabil Rehabil* **24**, 21–30

(2002).

43. He, S., Everest-Phillips, C., Clouter, A., Brown, P. & Tan, H. Neurofeedback-linked

suppression of cortical B bursts speeds up movement initiation in healthy motor

control: A double-blind sham-controlled study. *Journal of Neuroscience* **40**, 4021–

4032 (2020).

44. Kober, S. E., Witte, M., Grinschgl, S., Neuper, C. & Wood, G. Placebo hampers ability

to self-regulate brain activity: A double-blind sham-controlled neurofeedback study.

NeuroImage **181**, 797–806 (2018).

45. Kobler, R. J., Almeida, I., Sburlea, A. I. & Müller-Putz, G. R. Using machine learning

to reveal the population vector from EEG signals. *Journal of Neural Engineering* **17**,

(2020).

46. Corsi, M. C. *et al.* Functional disconnection of associative cortical areas predicts

performance during BCI training. *NeuroImage* **209**, 116500 (2020).

47. Espenhahn, S., Berker, A. O. de, Wijk, B. C. M. van, Rossiter, H. E. & Ward, N. S.

Movement-related beta oscillations show high intra-individual reliability. *NeuroImage*

147, 175–185 (2017).

48. Iwama, S. & Ushiba, J. Rapid-IAF: Rapid Identification of Individual Alpha Frequency

in EEG Data Using Sequential Bayesian Estimation. *IEEE Transactions on Neural*

Systems and Rehabilitation Engineering **32**, 915–922 (2024).

49. Donoghue, T. *et al.* Parameterizing neural power spectra into periodic and aperiodic

components. *Nature Neuroscience* **23**, 1655–1665 (2020).

50. Ritter, P., Moosmann, M. & Villringer, A. Rolandic alpha and beta EEG rhythms'

strengths are inversely related to fMRI-BOLD signal in primary somatosensory and

motor cortex. *Human Brain Mapping* **30**, 1168–1187 (2009).

51. Takemi, M., Masakado, Y., Liu, M. & Ushiba, J. Event-related desynchronization

reflects downregulation of intracortical inhibition in human primary motor cortex.

Journal of Neurophysiology **110**, 1158–1166 (2013).

52. Zrenner, C., Desideri, D., Belardinelli, P. & Ziemann, U. Real-time EEG-defined

excitability states determine efficacy of TMS-induced plasticity in human motor cortex.

Brain Stimulation **11**, 374–389 (2018).

53. Carpenter, R. H. S. *Movements of the Eyes*. (Pion Ltd, London, 1977).

54. Munn, S. M., Stefano, L. & Pelz, J. B. Fixation-identification in dynamic scenes:

comparing an automated algorithm to manual coding. in *Proceedings of the 5th*

symposium on Applied perception in graphics and visualization 33–42 (ACM, Los

Angeles California, 2008). doi:10.1145/1394281.1394287.

612
Conflicts of Interest

J.U. is a founder and representative director of the university startup company,

LIFESCAPES Inc., involved in the research, development, and sales of rehabilitation

devices, including brain-computer interfaces. SI and He receive a salary from

LIFESCAPES Inc., and hold shares in LIFESCAPES Inc. This company does not have

any relationships with the device or setup used in the current study. The remaining

authors declare no competing interests.

Acknowledgements

This study was supported by JST, PRESTO Grant Number JPMJPR23I1, Japan, and JST

Moonshot R&D Grant Number JPMJMS2012, Japan. The authors thank Shoko Tonomoto,

Aya Kamiya, and Sayoko Ishii for their assistance.