**Human intention inference with a large language model can enhance**

**brain-computer interface control: A proof-of-concept study**

**Authors**

Shue Shiinoki[1], Seitaro Iwama[2], Junichi Ushiba[2*]

[1] Graduate School of Science and Technology, Keio University, Kanagawa, Japan

[2] Department of Biosciences and Informatics, Faculty of Science and Technology, Keio

University, Kanagawa, Japan

**\*Correspondence**

Junichi Ushiba, Ph.D.

Department of Biosciences and Informatics, Faculty of Science and Technology, Keio

University, 3-14-1 Hiyoshi, Kouhoku-ku, Yokohama, Kanagawa 223-8522, Japan.

Tel/Fax: +81-45-566-1678.

Email: ushiba@bio.keio.ac.jp

**Abstract**

Brain–computer interface (BCI) control enables direct communication between the brain and external devices. However, the accuracy of BCI control based on intentions inferred from unstable neural signals remains limited, even with data-driven approaches to tailor neural decoders. Here we propose a knowledge-driven framework for inferring human intentions, leveraging large language models (LLMs) that incorporate prior knowledge about human behavior and neural activity. We developed a neural decoder that integrates neural and oculomotor signals with contextual information using an LLM agent. Its feasibility was tested in a real-world BCI task involving interaction with a computer application. The LLM-based decoder achieved an average accuracy of 79% among participants whose neural signals were responsive (11 out of 20) in inferring the intention to select arbitrary posts in a social networking service. Ablation analyses revealed that the integration of contextual information, multimodal signals, and empirical knowledge is critical for decoding accuracy. This study demonstrates the feasibility of a neural decoding framework using an LLM, paving the way for improved performance in BCI-driven external device operation for individuals with disabilities.

**Keywords**

Brain-Computer Interface; Neural Decoding; Context Inference; Large Language Model; Motor Imagery

**Highlights**

- Large language models can infer human intent by integrating neural and oculomotor signals with screen context.

- The proposed model outperforms conventional data-driven approaches in decoding accuracy.

- Ablation analyses reveal that integrating contextual information, multimodal signals, and empirical knowledge is critical for accurate decoding.

## Introduction

A brain-computer interface (BCI) capable of bypassing human motor pathways to express user volition has long been desired for augmented alternative communication[1–5]. To achieve this, a computational model, namely a neural decoder, is employed to infer user intentions embedded in real-time neural signals[6–8]. The decoder plays a critical role in a BCI system, as the decoded outputs, which are translated into device commands, need to be accurate enough to reconstruct user intentions. The accuracy from noninvasive modalities has been significantly improved over the decades owing to advances in statistical methods and machine learning algorithms[9,10].

One representative approach to enhancing the BCI performance is deep learning, which enables data-driven representation learning from minimally preprocessed neural signals[8,11,12]. A variety of network structures, such as recurrent neural networks (RNNs) or convolutional neural networks (CNN), have been proposed to extract features from neural signals without relying on prior knowledge or assumptions about the biological model[13,14]. CNN-based models have consistently demonstrated high performance, leading to the development of derivative models aimed at improving accuracy, generalization across various tasks and subjects[8,11,14–19].

Despite remarkable achievements of deep learning in fields such as image processing and speech recognition owing to its generalization ability and high accuracy[20–22], such breakthroughs have not yet been realized in neural decoding, particularly when using low-fidelity neural measurements such as the scalp electroencephalogram (EEG) to read out of human cortical activity. This limitation likely stems from the short duration of experimental sessions, which makes it impractical to

collect datasets that sufficiently cover the vast data space required to learn

representations that generalize across datasets. These challenges highlight the need for

methods that alleviate the fully data-driven nature of existing approaches.

An alternative to fully data-driven model training is to incorporate knowledge-driven

signal observation. For instance, in a Bayesian framework, prior knowledge can be used

for initiating training from a more informative probability distribution. A more flexible

integration of such prior knowledge can be achieved by using a large language model

(LLM) as an inference module. LLMs are suitable for scenarios with limited neural training

data as they embed neurophysiological knowledge that can support decoding as a

complement to the input signals. Indeed, LLMs have demonstrated human-level

reasoning abilities in knowledge-driven applications such as recommendation systems[23],

lifelong learning[24], and autonomous driving tasks[25,26]. In autonomous driving, for instance,

LLM-based systems that mimic human-like decision-making based on common sense

and past experience have achieved highly generalized performance through causal

reasoning, surpassing conventional reinforcement learning methods[25,26].

Here, we propose a multimodal decoding system that infers motor intentions and

operational targets from EEG and eye movements, based on knowledge-driven reasoning

using an LLM. We evaluated its effectiveness in BCI control within a real-world scenario.

Participants used the BCI system while interacting with a social networking service to

assess its feasibility. The performance of the LLM-based decoder was compared against

variants with ablated inputs or knowledge, data-driven baselines, and analyses of

classification outcomes. We hypothesized that the effectiveness of the LLM-based BCI

decoder arises from the integration of multimodal signal observation, task-specific

decoding instructions, and a small amount of participant-derived training data.

**Results**

*Decoder architecture*

In this proof-of-concept study, we propose a decoder framework that integrates EEG and

oculomotor signals, contextual information, knowledge, and a small number of EEG

training samples. These inputs are all transformed into text and fed into a large language

model (LLM) agent during BCI operation (Fig. 1, Supplementary Movie). The LLM agent

is instructed to reason which content displayed on the PC screen the user intended to

select (Fig.1, Supplementary Movie). The LLM agent was instructed to reason out which

content shown in the PC display the user selected.

All input data are converted into textual representations using specialized modules,

allowing the LLM agent to interpret them in accordance with the given instructions. The

agent employs a "chain-of-thought" reasoning process for inferring human intention, a

methodology that has been successfully applied in other fields, such as autonomous

driving. In this study, we adopt the ReAct framework[25,27] to guide the reasoning process

based on the LLM's embedded common knowledge. This framework combines logical

inference with information extracted from neural signals, along with physiological and

heuristic knowledge provided as prompts. ReAct addresses the final decision-making

problem (e.g., determining user attention or intent to press a button) through iterative

steps of action selection, observation of outcomes, and reasoning based on those

outcomes.

To support this process, the system leveraged multiple information sources as

agent tools (i.e., candidate actions), including action intention references, EEG feature

extraction results, the number of visual fixations within each tweet display area, and their

spatial distribution. In addition, environmental data, such as tweet and button coordinates,

UI metadata, and physiological knowledge, are incorporated as prior information (Fig. 1b).

Prompts are generated by integrating text-based descriptions of EEG decoding

knowledge (see Supplementary Information) and a few-shot EEG dataset collected

before BCI operation. These prompts are then provided to the LLM agent, which performs

reasoning in a structured format and outputs the corresponding operation commands.

*The proposed decoder is feasible to infer the user intention*

Before the formal evaluation of decoder accuracy, the signal quality of EEG and eye gaze

signals was visually inspected. For EEG, the temporal, spatial, and spectral information

of EEG relevant to neural decoding was extracted using the spatio-spectral

decomposition[28] to visualize time-frequency representations (Supplementary Fig. 1).

Specifically, the event-related desynchronization of sensorimotor rhythm (SMR-ERD)

found during motor attempt was extracted. For the eye gaze signal, we visualized scan

path maps indicating sequences of fixations on displays.

First, we investigated whether the proposed LLM-based decoder could perform

neural decoding. Participants were stratified based on the responsiveness of their scalp

EEG signals and grouped into responders and non-responders. Responsiveness was

determined according to SMR-ERD magnitude (Fig. 2a). We evaluated decoding

accuracy for both action and target selection (i.e., the "push like" or "read" command, and

the tweet selection), as well as for action detection alone. The results showed that the

responder group outperformed the non-responder group in both overall decoding and

action decoding alone (Fig. 2b and Supplementary Fig. 2a; $t$-test, $p < 0.05$; Cohen's $d =$

2.86, 2.94), suggesting that the proposed decoding approach is feasible and its

performance is dependent on SMR-ERD responsiveness.

Next, we examined how action decoding accuracy influences target decoding

accuracy, in order to assess the interaction between the two decoding processes. To this

end, target decoding accuracy was compared between trials in which motor intention was

correctly versus incorrectly detected. We found that target decoding was significantly

more accurate when motor intention was correctly detected (Fig. 2c; paired t-test, $p <$

$0.05$; Cohen's $d = 1.88$). Furthermore, when target selection was accurate, action

decoding accuracy was also significantly higher (Supplementary Fig. 2b; paired t-test, $p$

$< 0.05$; Cohen's $d = 1.58$). These findings suggest that successful motor intention

decoding is associated with enhanced target decoding performance.

*Multimodal signal input, prior knowledge, and few-shot information are necessary for*

*effective decoding*

In the present study, multimodal data, namely neural and oculomotor movements, were

used in an integrated manner for inferring human intention. We investigated the

contribution of each modality to overall decoding performance. First, we conducted an

ablation study on input modalities (Fig. 3a), modifying the prompt to perform the same

inference task as the original model. A repeated measures analysis of variance

(rmANOVA) revealed a significant decline in decoding accuracy when either signal was

removed (main effect: $F = 3.45$, $p < 0.05$). Post-hoc pairwise $t$-tests showed that the

decoder using both EEG and gaze signals (*EEG (+), Gaze (+)*) significantly outperformed

the decoder using only EEG (*EEG (+), Gaze (−)*: $t$ = 3.3, $p$ < 0.05, Cohen's $d$ = 1.04) and

the decoder using only gaze (*EEG (−), Gaze (+)*: $t$ = 2.4, $p$ < 0.05, Cohen's $d$ = 0.77).

These results indicate that integrating both modalities significantly improves decoding

performance over using either modality alone.

Next, we examined the effects of two factors on decoding performance: empirical

knowledge of EEG decoding, provided as prior information in the prompts, and few-shot

EEG data from the initial trials, included as past decoding experience (Fig. 3b). To assess

whether prior knowledge could compensate for limited data and whether decoding

performance could be maintained with minimal examples, a two-way rmANOVA was

conducted. The independent variables were the presence of empirical knowledge and the

number of few-shot trials, while the dependent variable was decoding accuracy. The

results showed significant main effects for both factors, but not interaction. Post-hoc tests

indicated that including heuristic knowledge significantly improved performance in the 0-

shot, 1-shot, 5-shot, and 10-shot conditions (Paired $t$-test, $p$<0.05, Cohen's $d$ = 1.08, 0.98,

0.55, 0.39, Bonferroni correction for multiple comparisons). Here, the number of "shots"

refers to the number of trials provided, with each trial containing four sample data points.

Furthermore, 10-shot decoding significantly outperformed both 0-shot and 5-shot

conditions ($p$ < 0.05, paired $t$-tests with Bonferroni correction; Cohen's $d$ = 1.84, 0.60,

respectively).

*Comparison with other data-driven decoder architectures*

The decoding performance of the knowledge-driven approach was evaluated in

comparison with data-driven methods. Specifically, we compared the proposed method

with CNNs and a Light Gradient Boosting Machine (LightGBM) [29]. While the standard

input for CNN-based EEG decoding is raw data, in this study, the CNN model was also

provided with SMR-ERD features, identical to those used as input to the LLM.

We assessed decoding accuracy across multiple CNN models and the proposed

model (Fig. 4a). The LLM decoder used 10 trials of participant-specific EEG data as few-

shot prompts. We compared this with several configurations of EEGNet[17] trained under

varying data conditions: Fine-tuning (10 trials): Trained from scratch on 10 trials of

participant-specific data, matching the quantity used in the LLM decoder. Fine-tuning (50

trials): Trained on 50 trials (i.e., 5 sessions) of data from the participant. Pretraining +

Fine-tuning (pretrained + 10 trials): First pre-trained on 500 trials from other participants,

then fine-tuned using 10 trials from the same participant as in the test. The 10-shot LLM

decoder achieved significantly higher accuracy than both the CNN model trained on 5

sessions and the CNN model trained on 1 session ($p < 0.05$, paired $t$-test; Cohen's $d$ =

1.23, 1.09). These results suggest that the performance of the LLM decoder is

comparable to that of a CNN model trained with pretraining and fine-tuning.

To evaluate the effectiveness of the LLM approach compared to a decision tree-

based method, we also trained a LightGBM model using the same SMR-ERD features as

inputs. We then compared the decoding accuracy of the 10-shot LLM decoder to that of

the LightGBM model trained on 5-session and 1-session datasets (Fig. 4b). The 10-shot

LLM decoder was significantly more accurate than the 1-session LightGBM model ($p <$

0.05, paired $t$-test; Cohen's $d$ = 1.5). Collectively, these results indicate that our model

can enhance BCI control accuracy under limited user data compared to the fully data-

driven models.

**Discussion**

In the present study, we investigated the feasibility of an LLM-based neural decoder architecture for inferring human movement intentions and their corresponding targets. Through performance evaluations and ablation analyses, we demonstrate that the proposed decoder effectively infers movement intentions and target selections by integrating neural and oculomotor signals with contextual and empirical knowledge. Specifically, the decoder achieved significantly higher accuracy for responders, with successful motor intention decoding closely associated with improved target selection. Ablation analyses revealed that multimodal signal integration, empirical knowledge, and few-shot learning each contributed significantly to decoding performance, with knowledge-driven inference mitigating the limitations imposed by limited training data. These results support the feasibility of an LLM-driven approach for enhancing BCI control accuracy under a data-constrained conditions.

The limited amount of available data from individual users has critically hindered the development of high-performance EEG decoders. In contrast to fields such as computer vision and natural language processing where training datasets often exceed 10 million sample is typically in the more than 10 million scale[13,21] and model architectures are correspondingly large in both parameter count and representational capacity, EEG-based deep learning models remain relatively small due to data scarcity, making it difficult to learn complex representations. Consequently, data-driven algorithms for EEG decoding have attempted to improve performance by reducing model complexity and employing regularization techniques[17,18], but classification accuracy and generalization ability remain limited[11,14]. In contrast, the present LLM-based architecture enables researchers

to incorporate decoding techniques into top-down inference through prompt design. In

this study, we demonstrated that leveraging knowledge-driven inference via an LLM

allows for accurate inference of motor intention using fewer than 50 trials of EEG data.

With minimal training data and text-based descriptions of decoding strategies, our

approach offers a promising alternative to conventional data-driven models, which have

been constrained by limited dataset sizes in EEG decoding.

One benefit to use an LLM agent for neural decoding is to integrate information from

multiple sources. Previous studies have attempted to augment the degrees of freedom in

BCI control by independently utilizing multimodal signals such as eye gaze and EEG. This

approach enables the simultaneous decoding of interaction targets and behavioral

intentions based on gaze and EEG signals, respectively. However, treating these

modalities separately may hinder the extraction of movement-related information from

gaze signals, and vice versa[30–32]. Specifically, eye movements not only convey

information about the object to be manipulated but also reflect behavioral intentions such

as the user's intent to interact with an object when fixating on it, or anticipation of

upcoming tasks as indicated by gaze shifts[33–36]. The significantly higher decoding

performance observed when combining EEG and eye movement signals, compared to

using EEG alone, highlights the benefits of an integrated decoding approach. Moreover,

data-driven methods face a challenge: integrating heterogeneous modalities within a

single model typically requires increased model complexity, in accordance with the no-

free-lunch theorem, thereby demanding larger training datasets. In contrast, LLMs can

readily accommodate such multimodal integration when appropriate descriptors are

constructed for each modality—leveraging prior knowledge and the generic, flexible input

format of natural language, as demonstrated in the present study.

As demonstrated in the ablation analysis for LLM prompting (Fig. 3b), we found that

decoding performance improves with few-shot prompting, even when physiological or

empirical knowledge about EEG decoding is provided as input. If the performance

degradation typically observed with a small number of few-shot examples is mitigated by

the inclusion of empirical knowledge, this suggests that such knowledge compensates for

decoding-relevant information that the LLM would otherwise extract from the data. This

implies that empirical knowledge supplements but does not replaceinformation essential

for decoding. However, our results indicate that few-shot prompting and empirical

knowledge independently contribute to performance improvements. This suggests that,

in addition to the physiological and empirical knowledge provided as text, the LLM also

extracts useful decoding information from the few-shot data. One possible source of this

information is the participant-specific characteristics of EEG signals, particularly in

relation to SMR-ERD. Previous studies have shown that inter-participant variability in

EEG features such as ERD magnitude and pattern variability constrains the performance

of fully data-driven decoding approaches[37,38]. Our findings suggest that the LLM

leverages these subject-specific ERD characteristics embedded in the few-shot input to

enhance inferential performance.

Although the present study demonstrated the feasibility of performing knowledge-

driven inference of behavioral intentions including motor intentions from a small amount

of data using an LLM, several limitations remain. First, the generalization of performance

across and within participants was limited by the ability to consistently elicit SMR-ERDs.

Currently, the inference system's ability to accurately classify behavioral intentions is

restricted to evaluations conducted during the best-performing sessions specifically,

those in which participants with sufficient SMR-ERD reactivity were able to reliably

generate SMR-ERDs throughout the session.

Second, although this inference system encodes all input information in text form for

the LLM, recent advances in multimodal LLMs including models capable of processing

image inputs have shown promise in domains such as GUI control[39–41] and medical

imaging[42]. In the present study, we restricted the input modality to text in order to isolate

and evaluate the reasoning capability of the LLM without confounding effects from image-

based input parsing. However, incorporating image input may be beneficial, as it aligns

more closely with how human researchers interpret data through visual representation.

Third, the decoding latency is relatively high, with an approximate delay of one minute.

This delay primarily stems from the use of remote LLM inference via application

programming interfaces, where both network communication and the LLM's processing

time contribute significantly to overall latency. We consider this a minor technical issue

that could be resolved by deploying the LLM locally, thereby eliminating network overhead.

Furthermore, ongoing advances in hardware and inference optimization (e.g., more

efficient decoding algorithms) are expected to further reduce response times and mitigate

the current latency bottleneck.

In summary, we demonstrated that a knowledge-based, LLM-driven neural decoding

approach is feasible for BCI control under conditions of limited data availability. This

framework enables experimenters to design task-specific prompts for inference, making

it adaptable to various BCI paradigms beyond motor imagery-based BCIs. By leveraging

prior physiological knowledge, the proposed approach has the potential to reduce

calibration time without compromising decoding accuracy, representing a promising step

toward practical applications in assistive technologies.

**Methods**

*Participants*

Twenty neurologically healthy adults (19 males, 1 female; mean age ± SD: 24 ± 1.4 years)

were informed of the aim of the experiment and provided written informed consent. The

experiment was approved by the local ethics committee of Keio University (IRB approval

number: 2024-009) and was conducted in accordance with the Declaration of Helsinki.

All participants were confirmed to be right-handed using the Edinburgh Handedness

Inventory[43].

*Experimental setup and protocol*

EEG was recorded using a 128-channel HydroCel Geodesic Sensor Net from Electrical

Geodesics Incorporated (EGI, Eugene, Oregon, USA) at a sampling rate of 1000 Hz. The

impedance level of the EEG electrodes was maintained below 50 kΩ throughout the

experiment. In this study, a PC-operated social media application, "X," was used. "X"

allows users to view short posts—commonly known as tweets—such as informational and

news posts from celebrities and friends, and to rate these posts by "liking" them. A display

showing the content list screen of "X" was placed in front of the participant. Eye

movements were recorded at a sampling rate of 1200 Hz using a Tobii Pro Spectrum

screen-based eye tracker (Tobii Technology AB, Danderyd, Stockholm, Sweden)

positioned at the bottom of the display. The eye tracker was synchronized with the display

to avoid measurement errors. Each participant performed the task of liking a tweet on the

"X" GUI using motor imagery, while EEG and eye movements were simultaneously

recorded using the behavioral intention decoding BCI described below.

The experiment consisted of one reference session and five evaluation sessions.

After each session, participants completed the Quebec Assistive Technology Satisfaction

Evaluation (QUEST) 2.0 questionnaire[44] and a free-description questionnaire regarding

their impressions of the BCI system to validate its usability. Participants were instructed

to rest, read the on-screen content, and press the Like button using motor imagery during

the time window shown in Fig. 1. During each trial, they were instructed to perform the

task within the same screen without scrolling. To present a different UI layout in each trial,

scrolling was performed at the end of the trial to refresh the content displayed. The

decoder generated four inferences per trial, each based on five seconds of recorded data.

Specifically, two inferences were made during the "read" phase and two during the "push

like" phase. The inference results were presented via the GUI during the final "blank"

period of each trial, and the participant manipulated the results using a cursor. The

duration of the "blank" period was sufficient to accommodate inference processing, which

took approximately 20–30 seconds.

*EEG Processing*

EEG analysis was used to input EEG information into the decoding system. The recorded

EEG signals were subjected to digital signal processing to remove artifacts. First, a third-

order Butterworth band-stop filter (50 Hz) and a third-order Butterworth band-pass filter

(3–70 Hz) were applied[45–47]. A spatial filtering technique called spatio-spectral

decomposition (SSD) was then applied to the processed signals. SSD is capable of

extracting neuronal oscillations with spatial patterns corresponding to SM1 activity[28]. The

SSD algorithm extracted neural oscillations at the individual alpha frequency (IAF), which

more effectively reflects the physiological properties of EEG than a uniform frequency

band[48–50]. IAF was identified using the specparam algorithm[51], which parameterizes and

separates the periodic and aperiodic components of EEG signals and allows for the

calculation of the frequency at which signal magnitude in the band of interest is maximal.

The EEG input to the decoding system was the sensorimotor rhythm event-related

desynchronization (SMR-ERD), which is thought to reflect sensorimotor excitability[52–54].

SMR-ERD is defined as the relative change in power and is calculated as follows:

352
$$ERD(f,t) = \frac{A(f,t) - R(f)}{R(f)}$$

Where $A$ represents the signal power of the EEG signals at time $t$ and $f$ represents the

frequency, $R$ and represents the mean signal power of the previous 9 s and recalculated

in every 9 s (i.e., at the beginning of relaxation and imagery periods). The power was

calculated using a short-time Fourier transform with a 90% overlap of the 1-second sliding

window.

*Eye movement processing*

To input eye movement information into the decoding system, we employed fixations to

represent the positions on the screen where the user was gazing[55]. Fixations were

extracted using an I-VT (Identification by Velocity Threshold) filter, which distinguishes

between fixations and saccades based on eye movement velocity at each time point. A

velocity threshold of 30°/s was applied[56]. Fixations were defined as sequences of gaze

points in which velocity remained below this threshold for at least 100 ms. The resulting

fixation points were mapped to predefined screen coordinates, and fixation clusters were

further quantified for each tweet to determine gaze allocation across stimuli.

*Decoder Architecture*

EEG signals, eye movements, environmental information in the form of the X application's

UI, and prior knowledge including EEG decoding expertise and past EEG data were

integrated and input into an LLM to infer the user's behavioral intentions. Within the signal

descriptor, EEG, eye movement, and UI information were each preprocessed and

converted into textual data. The specific processing procedures for each type of

information are described below. Prompts were generated from the textual

representations of the signal and environmental data, domain-specific knowledge

regarding EEG decoding, and few-shot EEG data obtained during the reference session

(see below). These prompts were then input into the LLM. The LLM performed inference

based on a predefined format and ultimately output operation commands, which were

used to control the application.

SMR-ERD time series data over a 5-second window were calculated from the EEG

signals using the online EEG analysis described earlier. From this time series, candidate

features were extracted. The feature extraction included the computation of various

statistics, such as the mean, median, negative 1 SD, positive 1 SD, negative 2 SD,

positive 2 SD, standard deviation, maximum amplitude, location of maximum amplitude,

maximum and minimum values, peak-to-peak intervals, zero-crossing count, number of

positive and negative values, and signal volatility. A gradient boosting model (LightGBM)[29]

was trained using preliminary EEG data to classify behavioral intention classes based on

these features. Feature importance was then computed from the trained model, and the

eight most informative features were selected for use. These included the mean, median,

1 SD, zero-crossing count, maximum amplitude value, location of maximum amplitude,

percentage of negative values, and volatility.

Eye movement data were processed from the stable fixation points identified by

the online analysis described earlier. UI information was also processed into a textual

format that captured the user's attentional focus. This was achieved by combining the

two-dimensional spatial distribution of eye movements on the screen with the number of

stable fixations per tweet. The resulting textual data included coordinates corresponding

to the positions of tweets and the location of each tweet's Like button.

To enable knowledge-driven reasoning, relevant knowledge for EEG decoding was

also provided as input. This included physiological knowledge supporting the role of SMR-

ERD as a biomarker for SM1 excitability during motor imagery, heuristic insights into how

EEG signals are affected by artifacts, and few-shot ERD data collected during the

reference session.

*Decoder Evaluation*

One of the 20 participants exhibited significant body motion artifacts in their EEG

recordings, compromising signal quality. Therefore, this participant was excluded from the

analysis. To objectively evaluate the performance of the decoder, the remaining 19

participants were grouped according to their responsiveness to SMR-ERD, and

performance was evaluated separately for each group. First, a one-sample t-test was

performed across trials for each participant's ERD data at the individual alpha frequency

(IAF) during the reference session. The null hypothesis assumed a mean ERD value of

zero. Participants whose ERD values during the motor imagery period were significantly

less than zero (i.e., negative direction) for more than 50% of the time interval were

categorized as the responder group. Those who did not meet this criterion were

categorized as the low responder group.

The performance of the decoder was evaluated based on the accuracy of decoding

the presence or absence of the motor intentions "Read" and "Push Like," as well as the

accuracy of identifying the target tweets associated with these actions. Additionally, the

overall decoding performance of the complete behavioral intention, including identification

of the specific tweet that was the target of the action, was assessed. For the decoding of

the complete behavioral intention, the self-reported responses indicating which tweets the

participants "liked" at the end of each trial were used as the ground truth. In each trial,

two datasets were obtained corresponding to "Push Like" and "Read." Since no class

imbalance was observed between these conditions, decoding performance was

evaluated using overall accuracy.

For data-driven benchmarking, we implemented EEGNet[17], a compact convolutional

neural network (CNN) architecture optimized for EEG-based brain-computer interface

(BCI) tasks. The model consisted of three convolutional layers with batch normalization

and dropout, and was trained using the Adam optimizer with early stopping based on

validation loss. We compared three training conditions: (1) 10-shot training using subject-

specific data; (2) 5-session training using data from the same subject; and (3) pretraining

on 500 trials from other subjects followed by fine-tuning on 10 trials from the target subject.

All models used SMR-ERD features as input to ensure a fair comparison with the LLM-

based decoder.

We compared the accuracy of the LLM-based decoder, which uses 10 trials of

subject-specific data as few-shot examples within the prompt, with that of EEGNet models

trained under different data conditions. Specifically, we prepared: (1) a model trained on

10 trials of data from the same subject—equivalent in size to the LLM's few-shot input,

(2) a model trained on 5 sessions (50 trials) of data from the same subject, and (3) a

model pre-trained on 500 trials from other subjects and fine-tuned on 10 trials from the

target subject. For all models, training was conducted for up to 200 epochs with early

stopping based on validation loss. Training convergence was observed when the patience

parameter for early stopping was set to 50.

To verify whether decoding by the LLM is superior to simple decision tree-based

classification of individual features, we trained a LightGBM model to classify between the

"Read" and "Push Like" motor intentions. The model was constructed and evaluated

under the same training data conditions as those used for the CNN models. Early stopping

was also employed, with training converging using a maximum of 2000 boosting rounds

and an early stopping patience of 300 rounds.

*Statistical Analysis*

All data were analyzed using parametric tests following verification of normality with the

Shapiro–Wilk test. For multilevel datasets, a repeated-measures mixed ANOVA was

conducted, followed by post hoc pairwise t-tests with Bonferroni correction. Sphericity

was assessed using Mauchly's test, and the Greenhouse–Geisser correction was applied

when the assumption of sphericity was violated. Paired datasets were analyzed using

paired t-tests.

**Figures**

**Fig. 1. Schematic of real-time human intention inference using an LLM-based agent.**

Neural and oculomotor signals, namely, eye-tracking and scalp electroencephalogram (EEG) data—as well as contextual information (i.e., content displayed on the PC screen) were individually processed and transformed into text data at the initial stage of the processing pipeline. In parallel, prior information, including physiological knowledge from previous EEG decoding studies and a few samples of subject-specific EEG data, was also converted into text. This multimodal textual information was then input into the large language model (LLM) for inference. Based on the inference result, the PC cursor automatically moved to the location corresponding to the participant's intended action.

**Fig. 2. Evaluation of decoding accuracy during brain–computer interfacing.**
**a**. Participant-wise proportion of significant SMR-ERD in the first block. A threshold of 50% was used to categorize participants into responder and non-responder groups. Responders are highlighted. **b**. Comparison of overall decoding accuracy between responder and non-responder groups, based on intended action and target decoding. **c**.

474 Comparison of intention decoding accuracy between trials in which the target was
475 correctly versus incorrectly inferred.
476

477
478 **Fig. 3 Multimodal signals and prior knowledge are necessary for inference.**
479 **a.** Accuracy of decoding based on multimodal and single-modal data conditions. **b.**
480 Accuracy of decoding with prior knowledge and few-shot data.
481

**Fig. 4 Comparisons of decoding accuracy with different decoder architectures. a.** Decoding accuracy comparison with convolutional neural network (CNN) models. **b.** Decoding accuracy comparison with light gradient boosting machine (GBM) models.

**References**

1. Edelman, B. J. *et al.* Noninvasive neuroimaging enhances continuous neural tracking for robotic device control. *Science Robotics* **4**, eaaw6844 (2019).

2. Silva, A. B., Littlejohn, K. T., Liu, J. R., Moses, D. A. & Chang, E. F. The speech neuroprosthesis. *Nat. Rev. Neurosci.* **25**, 473–492 (2024).

3. Pandarinath, C. *et al.* High performance communication by people with paralysis using an intracortical brain-computer interface. *eLife* **6**, e18554 (2017).

4. Kosnoff, J., Yu, K., Liu, C. & He, B. Transcranial focused ultrasound to V5 enhances human visual motion brain-computer interface by modulating feature-based attention. *Nat Commun* **15**, 4382 (2024).

5. Défossez, A., Caucheteux, C., Rapin, J., Kabeli, O. & King, J.-R. Decoding speech perception from non-invasive brain recordings. *Nat Mach Intell* **5**, 1097–1107 (2023).

6. Orsborn, A. L. *et al.* Closed-loop decoder adaptation shapes neural plasticity for skillful neuroprosthetic control. *Neuron* **82**, 1380–1393 (2014).

7. Haxby, J. V., Connolly, A. C. & Guntupalli, J. S. Decoding neural representational spaces using multivariate pattern analysis. *Annual Review of Neuroscience* **37**, 435–456 (2014).

8. Schirrmeister, R. T. *et al.* Deep learning with convolutional neural networks for EEG decoding and visualization. *Human Brain Mapping* **38**, 5391–5420 (2017).

9.  Lotte, F., Congedo, M., Lécuyer, A., Lamarche, F. & Arnaldi, B. A review of

classification algorithms for EEG-based brain-computer interfaces. *Journal of Neural*

*Engineering* vol. 4 R1–R13 (2007).

10. Lotte, F. *et al.* A review of classification algorithms for EEG-based brain-computer

interfaces: A 10 year update. *Journal of Neural Engineering* **15**, 031005 (2018).

11. Altaheri, H. *et al.* Deep learning techniques for classification of

electroencephalogram (EEG) motor imagery (MI) signals: a review. *Neural*

*Computing and Applications* **35**, 14681–14722 (2023).

12. LeCun, Y., Bengio, Y. & Hinton, G. Deep learning. *Nature* **521**, 436–444 (2015).

13. Krizhevsky, A., Sutskever, I. & Hinton, G. E. ImageNet Classification with Deep

Convolutional Neural Networks. in *Advances in Neural Information Processing*

*Systems* vol. 25 (Curran Associates, Inc., 2012).

14. Craik, A., He, Y. & Contreras-Vidal, J. L. Deep learning for electroencephalogram

(EEG) classification tasks: a review. *Journal of Neural Engineering* **16**, 031001

(2019).

15. Tabar, Y. R. & Halici, U. A novel deep learning approach for classification of EEG

motor imagery signals. *Journal of Neural Engineering* **14**, 016003 (2017).

16. Zhang, X. *et al.* A survey on deep learning-based non-invasive brain signals: recent

advances and new frontiers. *Journal of Neural Engineering* **18**, 031002 (2021).

17. Lawhern, V. J. *et al.* EEGNet: A compact convolutional neural network for EEG-

based brain-computer interfaces. *Journal of Neural Engineering* **15**, 56013–56030

(2018).

18. Dai, G., Zhou, J., Huang, J. & Wang, N. HS-CNN: a CNN with hybrid convolution

scale for EEG motor imagery classification. *Journal of Neural Engineering* **17**,

016025 (2020).

19. Rajwal, S. & Aggarwal, S. Convolutional Neural Network-Based EEG Signal

Analysis: A Systematic Review. *Archives of Computational Methods in Engineering*

**30**, 3585–3615 (2023).

20. He, K., Zhang, X., Ren, S. & Sun, J. Deep Residual Learning for Image Recognition.

in 770–778 (2016).

21. Devlin, J., Chang, M.-W., Lee, K. & Toutanova, K. BERT: Pre-training of Deep

Bidirectional Transformers for Language Understanding. in *Proceedings of the 2019*

*Conference of the North American Chapter of the Association for Computational*

*Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*

(eds. Burstein, J., Doran, C. & Solorio, T.) 4171–4186 (Association for

Computational Linguistics, Minneapolis, Minnesota, 2019). doi:10.18653/v1/N19-

1423.

22. Brown, T. *et al.* Language Models are Few-Shot Learners. in *Advances in Neural*

*Information Processing Systems* vol. 33 1877–1901 (Curran Associates, Inc., 2020).

23. Yang, S. *et al.* Common Sense Enhanced Knowledge-based Recommendation with

Large Language Model. (2024) doi:10.48550/arXiv.2403.18325.

24. Zhu, X. *et al.* Ghost in the Minecraft: Generally Capable Agents for Open-World

Environments via Large Language Models with Text-based Knowledge and

Memory. (2023) doi:10.48550/arXiv.2305.17144.

25. Wen, L. *et al.* DiLu: A Knowledge-Driven Approach to Autonomous Driving with

Large Language Models. (2024) doi:10.48550/arXiv.2309.16292.

26. Fu, D. *et al.* Drive Like a Human: Rethinking Autonomous Driving with Large

Language Models. (2023) doi:10.48550/arXiv.2307.07162.

27. Yao, S. *et al.* ReAct: Synergizing Reasoning and Acting in Language Models.

Preprint at https://doi.org/10.48550/arXiv.2210.03629 (2023).

28. Nikulin, V. V., Nolte, G. & Curio, G. A novel method for reliable and fast extraction of

neuronal EEG/MEG oscillations on the basis of spatio-spectral decomposition.

*NeuroImage* **55**, 1528–1535 (2011).

29. Ke, G. *et al.* LightGBM: A Highly Efficient Gradient Boosting Decision Tree. in

*Advances in Neural Information Processing Systems* vol. 30 (Curran Associates,

Inc., 2017).

30. Simola, J., Le Fevre, K., Torniainen, J. & Baccino, T. Affective processing in natural

scene viewing: Valence and arousal interactions in eye-fixation-related potentials.

*NeuroImage* **106**, 21–33 (2015).

31. Lee, E. C., Woo, J. C., Kim, J. H., Whang, M. & Park, K. R. A brain–computer

interface method combined with eye tracking for 3D interaction. *Journal of*

*Neuroscience Methods* **190**, 289–298 (2010).

32. Plöchl, M., Ossandón, J. P. & König, P. Combining EEG and eye tracking:

identification, characterization, and correction of eye movement artifacts in

electroencephalographic data. *Frontiers in Human Neuroscience* **6**, (2012).

33. Zhu, H. *et al.* Frequency-encoded eye tracking smart contact lens for human–

machine interaction. *Nature Communications* **15**, 3588 (2024).

34. Orquin, J. L. & Mueller Loose, S. Attention and choice: A review on eye movements

in decision making. *Acta Psychologica* **144**, 190–206 (2013).

35. Eckstein, M. K., Guerra-Carrillo, B., Miller Singley, A. T. & Bunge, S. A. Beyond eye

gaze: What else can eyetracking reveal about cognition and cognitive development?

*Developmental Cognitive Neuroscience* **25**, 69–91 (2017).

36. Skaramagkas, V. *et al.* Review of Eye Tracking Metrics Involved in Emotional and

Cognitive Processes. *IEEE Reviews in Biomedical Engineering* **16**, 260–277 (2023).

37. Saha, S. & Baumert, M. Intra- and Inter-subject Variability in EEG-Based

Sensorimotor Brain Computer Interface: A Review. *Front. Comput. Neurosci.* **13**,

(2020).

38. Blankertz, B., Tomioka, R., Lemm, S., Kawanabe, M. & Muller, K. Optimizing Spatial

filters for Robust EEG Single-Trial Analysis. *IEEE Signal Processing Magazine* **25**,

41–56 (2008).

39. Wang, J. *et al.* Mobile-Agent: Autonomous Multi-Modal Mobile Device Agent with

Visual Perception. (2024) doi:10.48550/arXiv.2401.16158.

40. You, K. *et al.* Ferret-UI: Grounded Mobile UI Understanding with Multimodal LLMs.

(2024) doi:10.48550/arXiv.2404.05719.

41. Nong, S. *et al.* MobileFlow: A Multimodal LLM For Mobile GUI Agent. (2024)

doi:10.48550/arXiv.2407.04346.

42. Panagoulias, D. P., Virvou, M. & Tsihrintzis, G. A. Evaluating LLM – Generated

Multimodal Diagnosis from Medical Images and Symptom Analysis. (2024)

doi:10.48550/arXiv.2402.01730.

43. Oldfield, R. C. The assessment and analysis of handedness: The Edinburgh

inventory. *Neuropsychologia* **9**, 97–113 (1971).

44. Demers, L., Monette, M., Lapierre, Y., Arnold, D. L. & Wolfson, C. Reliability, validity,

and applicability of the Quebec User Evaluation of Satisfaction with assistive

Technology (QUEST 2.0) for adults with multiple sclerosis. *Disabil Rehabil* **24**, 21–

30 (2002).

45. He, S., Everest-Phillips, C., Clouter, A., Brown, P. & Tan, H. Neurofeedback-linked

suppression of cortical B bursts speeds up movement initiation in healthy motor

control: A double-blind sham-controlled study. *Journal of Neuroscience* **40**, 4021–

4032 (2020).

46. Kober, S. E., Witte, M., Grinschgl, S., Neuper, C. & Wood, G. Placebo hampers

ability to self-regulate brain activity: A double-blind sham-controlled neurofeedback

study. *NeuroImage* **181**, 797–806 (2018).

47. Kobler, R. J., Almeida, I., Sburlea, A. I. & Müller-Putz, G. R. Using machine learning

to reveal the population vector from EEG signals. *Journal of Neural Engineering* **17**,

(2020).

48. Corsi, M. C. *et al.* Functional disconnection of associative cortical areas predicts

performance during BCI training. *NeuroImage* **209**, 116500 (2020).

49. Espenhahn, S., Berker, A. O. de, Wijk, B. C. M. van, Rossiter, H. E. & Ward, N. S.

Movement-related beta oscillations show high intra-individual reliability. *NeuroImage*

**147**, 175–185 (2017).

50. Iwama, S. & Ushiba, J. Rapid-IAF: Rapid Identification of Individual Alpha Frequency

in EEG Data Using Sequential Bayesian Estimation. *IEEE Transactions on Neural*

*Systems and Rehabilitation Engineering* **32**, 915–922 (2024).

51. Donoghue, T. *et al.* Parameterizing neural power spectra into periodic and aperiodic

components. *Nature Neuroscience* **23**, 1655–1665 (2020).

52. Ritter, P., Moosmann, M. & Villringer, A. Rolandic alpha and beta EEG rhythms'

strengths are inversely related to fMRI-BOLD signal in primary somatosensory and

motor cortex. *Human Brain Mapping* **30**, 1168–1187 (2009).

53. Takemi, M., Masakado, Y., Liu, M. & Ushiba, J. Event-related desynchronization

reflects downregulation of intracortical inhibition in human primary motor cortex.

*Journal of Neurophysiology* **110**, 1158–1166 (2013).

54. Zrenner, C., Desideri, D., Belardinelli, P. & Ziemann, U. Real-time EEG-defined

excitability states determine efficacy of TMS-induced plasticity in human motor

cortex. *Brain Stimulation* **11**, 374–389 (2018).

55. Carpenter, R. H. S. *Movements of the Eyes*. (Pion Ltd, London, 1977).

56. Munn, S. M., Stefano, L. & Pelz, J. B. Fixation-identification in dynamic scenes:

comparing an automated algorithm to manual coding. in *Proceedings of the 5th*

*symposium on Applied perception in graphics and visualization* 33–42 (ACM, Los

Angeles California, 2008). doi:10.1145/1394281.1394287.

## Conflicts of Interest

**Conflicts of Interest**

J.U. is a founder and representative director of the university startup company,

LIFESCAPES Inc., involved in the research, development, and sales of rehabilitation

devices, including brain-computer interfaces. SI and He receive a salary from

LIFESCAPES Inc., and hold shares in LIFESCAPES Inc. This company does not have

any relationships with the device or setup used in the current study. The remaining

authors declare no competing interests.

**Acknowledgements**

This study was supported by JST, PRESTO Grant Number JPMJPR23I1, Japan, and JST

Moonshot R&D Grant Number JPMJMS2012, Japan. The authors thank Shoko Tonomoto,

Aya Kamiya, and Sayoko Ishii for their assistance.