Walking speed can be modulated on an adaptive split-belt treadmill

Rucha Kulkarni[1], Barry Bodt[2], Jill S. Higginson[1,3]

[1]Dept. of Biomedical Engineering, University of Delaware, Newark, DE 19716

[2]Biostatistics Core, Dept. of Epidemiology, College of Health Sciences, University of

Delaware, Newark, DE 19716

[3]Dept. of Mechanical Engineering, University of Delaware, Newark, DE 19716

Corresponding author:

Rucha Kulkarni

University of Delaware, 540 S. College Ave., STAR Health Sciences Complex, Suite. 201,

Newark, DE, USA

rnk@udel.edu

Keywords: Propulsion, Gait, Adaptive Treadmill, Validation

Word count: 3499

Abstract

Adaptive treadmills (ATMs) that change speed based on the users' gait mechanics can allow for healthy stride to stride variability observed during overground walking, while maintaining the benefits of traditional treadmill training for gait rehabilitation. To enable unilateral targeting of propulsion, we developed an adaptive split-belt treadmill (sATM) that updates the speed of each belt of the treadmill based on the user's propulsion and position. The present study validated the sATM against an existing tied-belt ATM that updates the speed of both belts based on the user's propulsion, step length, and position. We also determined the effect of modifying the importance of propulsion unilaterally on the sATM. To validate the sATM, fourteen young, healthy participants completed five trials at their comfortable walking speed on the tied ATM and sATM with unilateral and bilateral modifications. We hypothesized that propulsion and walking speed on the novel sATM would be equivalent to the tied ATM, and further that the sATM could be preferentially weighted to encourage higher propulsion unilaterally while maintaining walking speed. Participants maintained similar propulsion and walking speed between treadmills and belts for bilateral modifications. While a few participants increased unilateral propulsion to maintain similar walking speeds for the unilateral modification, others showed no change in propulsion with slight differences in walking speed. Our results suggest that the response to unilateral modifications was user-specific, and the sATM could be tuned individually to allow unilateral control strategies. The present study demonstrates that walking speed can be modulated on an adaptive split-belt treadmill.

1. Introduction

Walking speed is a characteristic of healthy gait (Fritz and Lusardi, 2009) and is often used as a marker of community ambulation in older adults and neurological conditions like stroke (Dickstein, 2008; Fritz and Lusardi, 2009). It is heavily influenced by propulsion (push-off), which can be defined as the positive work performed by the limb to accelerate the body forward (Awad et al., 2020; Hsiao et al., 2015). For people with post-stroke hemiparesis, the weakened muscles on one side of the body reduce the propulsion forces generated by the paretic (affected) limb, which contributes to a decreased walking speed and affects community ambulation (Patterson et al., 2007).

Treadmill training is commonly used in gait rehabilitation for stroke survivors as it enables high repetition of movement in a safe and controlled environment (Dickstein, 2008; Duncan et al., 2011). However, conventional treadmills operate at fixed speeds which limits any instantaneous changes in speed and propulsion that we might observe in overground walking. Previous rehabilitation paradigms have been limited to fixed-speed treadmills which limits stride-to-stride variability that is essential for motor learning (Stergiou and Decker, 2011). Overall, traditional treadmill training shows mixed efficacy and limited improvement in walking speed and propulsion (Gelaw et al., 2019).

Split-belt treadmills have been developed such that the walking surface is comprised of two belts with speeds set independently. Using this tool, a series of studies has been conducted with the speed of one limb set to twice the other and have shown to improve spatiotemporal gait characteristics in stroke survivors (Reisman et al., 2013, 2007). However, the speed differential is controlled by a clinician and may lead to sub-optimal rehabilitation conditions and feel dissimilar to overground walking. Furthermore, split-belt

treadmills have also been limited to fixed speeds which limits stride-to-stride variability

and cannot target specific gait kinetics like propulsion. Therefore, they also have limited

transfer of adapted gait mechanisms to overground walking (Reisman et al., 2009).

To allow for stride-to-stride variability while retaining any benefits of treadmill

training, adaptive treadmills (ATMs) that update speed based on the user gait mechanics

(user-driven) have been developed (Pariser et al., 2022; Ray et al., 2018; Sloot et al.,

2014). Early treadmill control schemes involved user position on the treadmill or

spatiotemporal gait characteristics, and did not consider the relationship between

propulsion and walking speed (Sloot et al., 2014). Recently developed ATMs update

speed based on propulsion, step length and the user's position on the treadmill relative

to the treadmill center (Pariser et al., 2022; Ray et al., 2018). Studies have shown that

healthy individuals walk on an ATM at a self-selected speed closer to overground walking

compared to fixed-speed treadmills suggesting that ATMs may be more similar to

overground walking (Donlin et al., 2022; Kempski et al., 2019; Ray et al., 2018). However,

on average, stroke survivors do not seem to increase their self-selected speed on the

ATM as compared to fixed-speed treadmills (Ray et al., 2020). To date, these ATMs

restrict both limbs to the same speed and thus do not target unilateral gait mechanics.

The purpose of this study was to develop and validate an adaptive split-belt treadmill

(sATM) to enable preferential targeting of unilateral gait mechanics. The objective of this

study was to determine the effect of an adaptive split-belt treadmill on propulsion and

walking speed in healthy young adults. We hypothesized that when the control

parameters were equal on both belts on the split-belt treadmill and equal to that of a tied-

belt treadmill developed by Pariser et al. (2022), there would be no difference in

propulsion and walking speed between treadmills. We further hypothesized that when the

control parameter for propulsion was increased equally on both belts, propulsion would

increase without an increase in walking speed. We also hypothesized that when the

propulsion control parameter was increased for just one belt on the split-belt treadmill,

propulsion on the respective belt would increase with no difference in walking speed.

2. Methods

2.1.1 SATM controller

The previous implementation of the adaptive tied-belt treadmill updates the speed of both belts based on the current speed, intermediate speeds due to the average propulsive impulse and average step length of both limbs, and the position of the person's center of mass (COM) relative to the treadmill center (Pariser et al., 2022). For application to the split-belt treadmill, the updated speed of each belt (v_{i+1}) is calculated independently based on the current speed (v_i), the intermediate speed due to propulsive impulse of the respective limb (v_{PI}), and the position of the person's center of mass relative to the treadmill center (COM_{pos}) (Fig 1A). The peak propulsive force was also calculated in real-time as the maximum anterior ground reaction force (AGRF) per stride. Peak AGRF asymmetry was then calculated as the difference of the contralateral and ipsilateral peak AGRF divided by the sum. For peak AGRF asymmetry ($AGRF_{asymm}$) greater than 5%, updated speed is decreased by the intermediate speed due to propulsive impulse averaged over both limbs around this threshold to remove this discontinuity:

$$v_{i+1} = v_i + \gamma v_{PI} - \frac{\gamma}{25} v_i + \beta * sign(COM_{pos}) * COM_{pos}^2$$

$$- \frac{\gamma}{25} * sign(AGRF_{asymm}) * AGRF_{asymm} * v_{PI,avg}$$

where $AGRF_{asymm} = \frac{Peak\ AGRF_{contralateral} - Peak\ AGRF_{ispilateral}}{Peak\ AGRF_{contralateral} + Peak\ AGRF_{ispilateral}}$

To promote healthy gait variability, for $AGRF_{asymm}$ less than 5% (Herzog et al., 1989; Lauzière et al., 2014), the updated speed was calculated using the intermediate speed due to propulsive impulse averaged over both limbs:

$$v_{i+1} = v_i + \gamma v_{PI,avg} - \frac{\gamma}{25} v_i + \beta * sign(COM_{pos}) * COM_{pos}^2$$

The updated speed was calculated between heel strike and toe-off and updated at

toe-off of each stride. To ensure smooth belt accelerations, gains (γ, β) were calculated

using exponential functions (Ray et al., 2018) where dt is the time between belt speed

updates:

$$\gamma = 1 - e^{-\frac{dt}{\tau}}$$

$$\beta = 0.5$$

The value of tau (τ) was set to either 1.5 or 0.7639 to vary gamma, described more

in section 2.1.2. Decreasing tau (τ) (increasing gamma (γ)) requires higher propulsion at

each step to maintain the user's self-selected walking speed.

2.1.2   Data Collection

Fourteen adults (24.79 ± 1.82 years, 1.70 ± 0.08 m, 75.86 ± 14.91 kg, 7 females)

participated and self-reported no known neuromuscular injuries or disorders. The

University of Delaware Institutional Review Board approved the protocol, and participants

gave written informed consent and completed a modified physical activity readiness

questionnaire. Participants first performed the 10-meter overground walking test to

determine their preferred overground walking speed. Then they performed a series of

walking trials on an instrumented split-belt treadmill (Bertec Corp; 2000 Hz) and real-time

data were collected using a motion capture data collection system (Qualisys; 100 Hz).

To validate the novel adaptive split-belt treadmill, we asked participants to walk on

the Split ATM and on a Tied ATM previously developed by Pariser et al. (2022).

Participants performed 5 walking trials for 2 minutes each – Split Normal, Tied Normal,

Tied Hard, Split Hard, and Split Uneven in a pseudo-randomized order (Fig 1B). For the

Normal and Hard conditions on the Split treadmill, the propulsive gains of both belts were

identical to the Tied Normal and Hard conditions. The Hard conditions (τ_γ = 0.7639, γ_{Hard})

had a higher propulsive gain (γ_{Hard} = 1.5*γ_{Normal}) than the Normal condition (τ_γ = 1.5,

γ_{Normal}) and required higher propulsion to maintain a comfortable speed, as observed by

Pariser et al. For the Uneven condition, one belt was defined as the preferential side and

had a higher propulsive gain (γ_{Hard}) than the other side (γ_{Normal}), such that $\gamma_{Preferential}$=

1.5 * $\gamma_{Non-Preferential}$. The preferential side (right or left belt) was randomized for all

participants (N=7 right).

Participants were given up to 10 minutes practice for each of the Normal conditions

before performing the respective Normal trial. Both Normal trials (Split and Tied) were

performed first in random order, followed by the Hard and Uneven trials in random order.

Participants were given up to 3 minutes to achieve a comfortable, steady-state speed and

the trial began when they gave verbal indication that they had achieved a comfortable

speed. The maximum speed of the treadmill was set to 2 m/s. Participants were allowed

to lightly touch the handrails for stabilization. After each trial, participants were asked to

respond to a survey to assess their perceived: (1) stability, (2) overall comfort, (3) ease of

achieving their preferred walking speed, and (4) ease of maintaining their preferred

speed. Each metric was measured on a scale of 1–7 where 1 corresponded to very

unstable, uncomfortable, or difficult and 7 represented very stable, comfortable, or easy.

Participants also performed a washout trial (1 min) of walking on a fixed speed treadmill

at 0.1 m/s less than their preferred overground walking speed after each trial.

2.1.3 Data Processing and Analysis

Kinetic and spatiotemporal data were processed using a custom-written MATLAB

2024a (Natick, MA) program. Force data were filtered using a low-pass fourth-order

Butterworth filter with a cutoff frequency of 30 Hz. Heel-strike and toe-off events were

identified using a 20 N threshold on the vertical ground reaction forces and these gait

events determined each gait cycle. We visually inspected gait events to verify event

detection and corrected if necessary. To evaluate propulsion and braking, we calculated

peak anterior (AGRF) and posterior (PGRF, Supplemental Materials) ground reaction

forces, impulses and net anterior-posterior impulse (Supplemental Materials). The speed

of each belt was recorded for each trial and averaged over the duration of each trial. We

calculated the position of participants' COM to determine their position on the treadmill.

To understand the spatiotemporal components of walking, we calculated stride length,

stride time, step length and step time using force data (Supplemental Materials). Kinetic

measures were normalized to body weight and spatial measures were normalized to

height. Each metric was averaged per limb for all gait cycles in each trial. To evaluate

symmetry between limbs, asymmetry for a metric X was calculated as $\frac{X_R - X_L}{\frac{1}{2}(X_R + X_L)} * 100\%$

(Herzog et al., 1989).

To explore the trends of the adaptive split-belt treadmill, we also ran mathematical

simulations of speed using experimental data. A mathematical model of the sATM was

applied to anterior ground reaction force (AGRF) data collected from the Normal Tied

condition for a representative participant. We varied COM position relative to the treadmill

center (0, 0.1, 0.2 m) with no changes in the AGRF data, as well as AGRF data (net

impulse + 0.001, 0.005, 0.01 BW*s) with constant COM position relative to the treadmill

center (at 0 m) to observe trends in the simulated velocity of the treadmill.

2.1.4 Statistical analysis

An a priori power analysis in RStudio 2024 (Posit, Boston, MA) for an equivalence test

for propulsive impulse (bounds = 0.05, power = 0.8, std = 0.05) indicated 10 participants.

Shapiro-Wilk tests were used to determine normality for all data.

To establish equivalence, we first looked at agreement between belts. We evaluated

only the Split treadmill for walking speed as the belt speeds are always equal on the Tied

treadmill. We evaluated the linear fit between the right and left belt. We then modeled the

difference score in terms of condition and participant. Confidence intervals (CIs) for the

difference score between trials were calculated using Tukey-HSD tests in JMP Pro (JMP®,

Version *18.0.1* SAS Institute Inc., Cary, NC).

For all other measures, we looked at both Split and Tied treadmills. We examined the

similarity between treadmills for all measures using repeated-measures two-way ANOVAs

for each belt with factors of treadmill and condition. We also evaluated limb symmetry for

all kinetic and spatiotemporal measures with repeated-measures two-way ANOVA with

factors of treadmill and condition. CIs for the symmetry scores were calculated for each

trial.

To determine differences between the belts for the Split Uneven condition, we ran

paired Wilcoxon tests for all measures. All analyses where not specified were performed

in Python (Vallat, 2018). Significance was set at 0.05 for all statistical analyses. Multiple

comparisons were corrected using Bonferroni corrections.

3. Results

Participants' self-selected walking speed was similar between Tied and Split treadmills (Table 1; Fig 2A; Right: $F_{(1,13)} = 0.347$, $p = 0.57$; Left: $F_{(1,13)} = 3.699$, $p = 0.076$). The speeds of both belts showed linear agreement on the Split treadmill (adj. $R^2 = 0.409$). The difference in belt speeds was not significantly different than zero, suggesting agreement between belts. Both belt speeds were significantly higher in the Hard condition (Right: $F_{(1,13)} = 5.569$, ; Left: $F_{(1,13)} = 35.299$ $p < 0.001$). For the Split Uneven condition, belt speed did not show a significant difference between belts ($p = 0.104$).

Average AGRF impulse on the right belt was significantly higher on the Tied treadmill (Fig 2B; $F_{(1,13)} = 12.88$, $p = 0.0033$) but showed no significant effect of condition ($F_{(1,13)} = 0.893$, $p = 0.362$). For the left belt, AGRF impulse was higher in the Hard condition ($F_{(1,13)} = 5.008$, $p = 0.043$) but had no significant effect of treadmill ($F_{(1,13)} = 3.731$, $p = 0.075$). Peak AGRF was significantly higher in the Hard condition for both belts (Right: $F_{(1,13)} = 6.839$, $p = 0.021$; Left: $F_{(1,13)} = 25.247$, $p < 0.001$) and significantly higher in the Tied treadmill for the right belt ($F_{(1,13)} = 6.557$, $p = 0.023$) but not the left belt ($F_{(1,13)} = 0.0239$, $p=0.879$). AGRF impulse symmetry showed a statistically significant effect of treadmill ($F_{(1,13)} = 15.957$, $p = 0.0015$) but not condition ($F_{(1,13)} = 0.193$, $p = 0.67$). Peak AGRF symmetry showed a significant effect of treadmill ($F_{(1,13)} = 15.581$, $p = 0.0017$) but not condition($F_{(1,13)} = 0.134$, $p = 0.719$). For the Split Uneven condition, AGRF impulse ($p=0.583$) and peak AGRF ($p=0.855$) did not show a significant difference between belts. In the few cases where the residual normality assumption for

the ANOVAs was not met, the recovery action of outlier removal did not alter which effects

were significant.

The COM position was equivalent between right and left strides (adj. R^2 = 0.99)

There was a significant interaction between treadmill and condition on COM position

$(F(1,13) = 250.184, p < 0.001)$. Participants' COM was significantly more forward in the

Hard condition for both Tied (Bonferroni-corrected p = 0.0027) and Split (Bonferroni-

corrected p = 0.027).

Survey data were compared between all five conditions (Table 2). Participants

reported that it was slightly easier to achieve and maintain speed and felt more

comfortable and stable on the tied ATM. Participants also reported that it was easier to

achieve and maintain speed and felt more comfortable and stable in the Normal condition

than the Hard condition for both treadmills as well as the Split Uneven condition.

The simulated belt speed varied with variations in COM position as well as net

anterior-posterior impulse (Fig 3). At the center of the treadmill with the original impulse

data from a representative participant, the simulated speed declined with the number of

strides. This indicates that the impulse was lower than required to maintain a speed of

1m/s at that position, and the participant was likely slightly closer to the front during the

experiment. Therefore, an increase in relative COM position corresponded to an

increased simulated belt speed. Similarly, an increase in net impulse showed an increase

in belt speed when COM position was held constant at the treadmill center.

4. Discussion

We developed and validated a novel, adaptive split-belt treadmill. We hypothesized that propulsion and walking speed on the novel sATM would be equivalent to a previously developed tied adaptive treadmill, and further that the sATM could be preferentially weighted to encourage higher propulsion unilaterally while maintaining walking speed. Our findings partially support our hypothesis – participants maintained similar propulsion and walking speed between treadmills and belts. Interestingly, while most participants maintained similar walking speeds between belts when the sATM was preferentially unilaterally weighted, there was no significant difference between belts for propulsion on average. However, a few participants increased unilateral propulsion to maintain similar walking speeds, while others showed no change in propulsion with slight differences in walking speed. These results suggest that the response to unilateral weighting was user-specific, and the sATM could be tuned to individual responses.

We found that participants maintained their walking speed between Tied and Split treadmills. Post-hoc analysis showed that differences in speed between treadmills (Split - Tied) for Normal (Right: [-0.099,0.069], Left: [-0.078,0.125]) and Hard (Right: [-0.109,0.059], Left: [-0.021,0.183]) were within 95% CIs of differences in walking speed during continuous walking ([-0.127, 0.147]) obtained from prior literature (Paterson et al., 2008).

Participants also maintained similar speeds between belts on the Split treadmill. It is possible that participants did not perceive any differences between belts during the trials. 61% (17/28) of Split trials were in the healthy gait asymmetry range ($AGRF_{asymm}$<=5%), suggesting that the sATM controller on average used a v_{PI} averaged over both limbs.

Furthermore, previous work shows that healthy participants perceive belt speed

differences during split-belt treadmill walking after a certain threshold of difference (95%

CI: [0.025, 0.105]) is achieved (Hoogkamer et al., 2015). Post-hoc analysis of the

perception threshold (absolute belt speed difference/sum of belt speeds) showed that the

confidence interval of the perception threshold for all participants in both Split Normal

([0.033, 0.093]) and Split Hard ([0.035, 0.078]) conditions were within the aforementioned

confidence intervals.

Participants had a higher self-selected speed in the Hard conditions, compared to

the Normal conditions. While participants did not increase their AGRF impulse

consistently between conditions, they were significantly closer to the front on the treadmill

in the Hard condition for both treadmills. This suggests that participants modulated their

position on the treadmill instead of AGRF impulse. Additionally, participants were

instructed to walk at a comfortable speed, not their overground speed, and may not have

sensed an "uncomfortable" change in walking speed between the Hard and Normal

conditions.

Similar to walking speeds, propulsion was also consistent between treadmills and

belts in the Normal and Hard conditions. While peak AGRF symmetry and AGRF impulse

symmetry showed a significant effect of treadmill, symmetries for each condition were

within healthy gait symmetry levels (±15.6, ±18.4 respectively) (Herzog et al., 1989).

Therefore, we believe these bilateral differences are not clinically meaningful.

Participants increased their peak AGRF for the Hard conditions on both treadmills,

suggesting that they were pushing off harder. These results indicate that by increasing

the propulsion gain, we can encourage volitional bilateral changes in propulsion on the

sATM. Peak AGRF is a good indicator of propulsion during walking in individuals post-

stroke (Hsiao et al., 2016), therefore our results demonstrate a potential tool to encourage

increased propulsion in stroke survivors.

Despite different propulsion weights, the Split Uneven condition did not show

significant differences in propulsion on the preferential limb on average. However, on an

individual level, a few participants increased their propulsion on the preferential limb and

achieved a smaller difference between belt speeds. Furthermore, net anterior-posterior

impulse was higher on the preferential limb and PGRF impulse were higher on the non-

preferential limb (higher braking) (Supplemental Materials). Therefore, participants may

have been able to maintain similar speeds on both belts by increasing their braking force

on the non-preferential limb and lowering the speed of that belt, while increasing the

preferential belt speed by increasing net impulse. Additionally, participants did not practice

the Split Uneven condition and may have struggled to accommodate to the difference

between belts. These results suggest that response to preferential weighting of unilateral

propulsion is user-specific and may need to be tuned to individual responses to

encourage a significant increase.

The simulation results demonstrate how the speed of each belt can be changed by

modulating COM position or net anterior-posterior impulse. We have verified that the

sATM controller algorithm behaves as anticipated by performing speed simulations using

data collected from a participant. These results show how participants may have

implemented different strategies to maintain comfortable walking speeds on the treadmill.

The survey results indicate that while participants perceived that achieving and

maintaining their preferred speed was easier on the tied ATM as compared to the sATM

for the Normal condition, it was equivalent between treadmills for the Hard conditions.

Additionally, the Split Normal and Uneven conditions were similar to the Hard conditions

in all survey responses. This suggests that while participants may have found it easier to

use the tied ATM, they were able to control their walking speed on all sATM conditions

with relative ease.

In the current work, users tended to modulate their position on the treadmill instead of

propulsion to control the speed of the treadmill. Previous work has suggested that

modifying the importance of position on the treadmill may result in changes in net impulse

on the tied ATM (Downer et al., 2024). While drastically reducing the importance of

position increased difficulty in achieving and maintaining walking speeds, it did not affect

the comfort and stability of use of the tied ATM. Therefore, future work should explore the

modifying the COM term in the sATM controller to reduce reliance on the modulation of

position on the treadmill while maintaining ease of use.

5. Conclusion

The present study demonstrates that walking speed can be modulated on an adaptive

split-belt treadmill. In this work, we developed and validated an sATM that allows unilateral

control strategies. Future work will explore different combinations of the propulsion gains

on the sATM in the Split Uneven condition to determine gains that promote increased

unilateral propulsion in healthy and post-stroke individuals.

6. Acknowledgements

The authors were supported by the National Institute of Health (NIH #HD111071)

and an Institutional Development Award (IDeA) from the National Institute of General

Medical Sciences of the National Institute of Health under grant number

U54-GM104941 (PI: Hicks)

7. Conflict of Interest Statement

The authors declare they have no conflicts of interest.

References

Awad, L.N., Lewek, M.D., Kesar, T.M., Franz, J.R., Bowden, M.G., 2020. These legs were made for propulsion: advancing the diagnosis and treatment of post-stroke propulsion deficits. J. NeuroEngineering Rehabil. 17, 139. https://doi.org/10.1186/s12984-020-00747-6

Dickstein, R., 2008. Rehabilitation of Gait Speed After Stroke: A Critical Review of Intervention Approaches. Neurorehabil. Neural Repair 22, 649–660. https://doi.org/10.1177/1545968308315997

Donlin, M.C., Pariser, K.M., Downer, K.E., Higginson, J.S., 2022. Adaptive treadmill walking encourages persistent propulsion. Gait Posture 93, 246–251. https://doi.org/10.1016/j.gaitpost.2022.02.017

Downer, K.E., Pariser, K.M., Donlin, M.C., Higginson, J.S., 2024. How Important is Position in Adaptive Treadmill Control? J. Biomech. Eng. 146, 011006. https://doi.org/10.1115/1.4063823

Duncan, P.W., Sullivan, K.J., Behrman, A.L., Azen, S.P., Wu, S.S., Nadeau, S.E., Dobkin, B.H., Rose, D.K., Tilson, J.K., Cen, S., Hayden, S.K., 2011. Body-Weight–Supported Treadmill Rehabilitation after Stroke. N. Engl. J. Med. 364, 2026–2036. https://doi.org/10.1056/NEJMoa1010790

Fritz, S., Lusardi, M., 2009. White Paper: "Walking Speed: the Sixth Vital Sign": J. Geriatr. Phys. Ther. 32, 2–5. https://doi.org/10.1519/00139143-200932020-00002

Gelaw, A.Y., Janakiraman, B., Teshome, A., Ravichandran, H., 2019. Effectiveness of treadmill assisted gait training in stroke survivors: A systematic review and meta-analysis. Glob. Epidemiol. 1, 100012. https://doi.org/10.1016/j.gloepi.2019.100012

Herzog, W., Nigg, B., Read, L., Olsson, E., Feb1989. Asymmetries in ground reaction force patterns in normal human gait. Med. Sci. Sports Exerc. 21, 110–114. https://doi.org/10.1249/00005768-198902000-00020

Hoogkamer, W., Bruijn, S.M., Potocanac, Z., Van Calenbergh, F., Swinnen, S.P., Duysens, J., 2015. Gait asymmetry during early split-belt walking is related to perception of belt speed difference. J. Neurophysiol. 114, 1705–1712. https://doi.org/10.1152/jn.00937.2014

Hsiao, H., Knarr, B.A., Higginson, J.S., Binder-Macleod, S.A., 2015. The relative contribution of ankle moment and trailing limb angle to propulsive force during gait. Hum. Mov. Sci. 39, 212–221. https://doi.org/10.1016/j.humov.2014.11.008

Hsiao, H., Zabielski, T.M., Palmer, J.A., Higginson, J.S., Binder-Macleod, S.A., 2016. Evaluation of measurements of propulsion used to reflect changes in walking speed in individuals poststroke. J. Biomech. 49, 4107–4112. https://doi.org/10.1016/j.jbiomech.2016.10.003

Kempski, K.M., Ray, N.T., Knarr, B.A., Higginson, J.S., 2019. Dynamic structure of variability in joint angles and center of mass position during user-driven treadmill walking. Gait Posture 71, 241–244. https://doi.org/10.1016/j.gaitpost.2019.04.031

Lauzière, S., Betschart, M., Aissaoui, R., Nadeau, S., 2014. Understanding Spatial and Temporal Gait Asymmetries in Individuals Post Stroke. Int. J. Phys. Med. Rehabil. 02. https://doi.org/10.4172/2329-9096.1000201

Pariser, K.M., Donlin, M.C., Downer, K.E., Higginson, J.S., 2022. Adaptive treadmill
control can be manipulated to increase propulsive impulse while maintaining
walking speed. J. Biomech. 133, 110971.
https://doi.org/10.1016/j.jbiomech.2022.110971
Paterson, K.L., Hill, K.D., Lythgo, N.D., Maschette, W., 2008. The Reliability of
Spatiotemporal Gait Data for Young and Older Women During Continuous
Overground Walking. Arch. Phys. Med. Rehabil. 89, 2360–2365.
https://doi.org/10.1016/j.apmr.2008.06.018
Patterson, S.L., Forrester, L.W., Rodgers, M.M., Ryan, A.S., Ivey, F.M., Sorkin, J.D.,
Macko, R.F., 2007. Determinants of Walking Function After Stroke: Differences
by Deficit Severity. Arch. Phys. Med. Rehabil. 88, 115–119.
https://doi.org/10.1016/j.apmr.2006.10.025
Ray, N.T., Knarr, B.A., Higginson, J.S., 2018. Walking speed changes in response to
novel user-driven treadmill control. J. Biomech. 78, 143–149.
https://doi.org/10.1016/j.jbiomech.2018.07.035
Ray, N.T., Reisman, D.S., Higginson, J.S., 2020. Walking speed changes in response to
user-driven treadmill control after stroke. J. Biomech. 101, 109643.
https://doi.org/10.1016/j.jbiomech.2020.109643
Reisman, D.S., McLean, H., Keller, J., Danks, K.A., Bastian, A.J., 2013. Repeated Split-
Belt Treadmill Training Improves Poststroke Step Length Asymmetry.
Neurorehabil. Neural Repair 27, 460–468.
https://doi.org/10.1177/1545968312474118
Reisman, D.S., Wityk, R., Silver, K., Bastian, A.J., 2009. Split-Belt Treadmill Adaptation
Transfers to Overground Walking in Persons Poststroke. Neurorehabil. Neural
Repair 23, 735–744. https://doi.org/10.1177/1545968309332880
Reisman, D.S., Wityk, R., Silver, K., Bastian, A.J., 2007. Locomotor adaptation on a
split-belt treadmill can improve walking symmetry post-stroke. Brain 130, 1861–
1872. https://doi.org/10.1093/brain/awm035
Sloot, L.H., Van Der Krogt, M.M., Harlaar, J., 2014. Self-paced versus fixed speed
treadmill walking. Gait Posture 39, 478–484.
https://doi.org/10.1016/j.gaitpost.2013.08.022
Stergiou, N., Decker, L.M., 2011. Human movement variability, nonlinear dynamics, and
pathology: Is there a connection? Hum. Mov. Sci. 30, 869–888.
https://doi.org/10.1016/j.humov.2011.06.002
Vallat, R., 2018. Pingouin: statistics in Python. J. Open Source Softw. 3, 1026.
https://doi.org/10.21105/joss.01026
428

Figures

432 Fig 1. (A) Experimental Set-Up. An illustrative sketch of a participant on the sATM. (B)

433 Experimental Protocol. Participants performed 5 trials on the tied ATM and sATM.

Fig 2. (A) Walking Speed (B) AGRF Impulse. Box plots represent data from all

participants for the right and left belt for each condition.

Fig 3. Simulation Results (A) Varying Position (B) Varying Net Impulse. Solid lines depict

the Split Normal condition, and dashed lines depict the Split Hard condition.

Tables

Table 1. Kinetic metrics and COM position (Mean ± SD) for all walking trials.

Treadmill	Tied		Split		Split Uneven	
	Normal	Hard	Normal	Hard	Pref Side	Non-Pref Side
SSWS (m/s)	R: 1.24±0.16 L: 1.24±0.16	R: 1.3±0.16 L: 1.3±0.16	R: 1.22±0.22 L: 1.26±0.18	R: 1.28±0.22 L: 1.38±0.18	1.28±0.23	1.41±0.21
Peak AGRF (%BW)	R: 20.91±3.81 L: 20.97±4.64	R: 22.62±4.81 L: 22.67±5.45	R: 19.61±5.33 L: 20.84±4.88	R: 20.87±5.77 L: 22.67±5.38	21.65±5.77	22.05±5.17
AGRF Impulse (%BW*s)	R: 3.20±0.49 L: 3.13±0.51	R: 3.33±0.62 L: 3.29±0.55	R: 2.91±0.69 L: 3.07±0.58	R: 2.95±0.69 L: 3.16±0.56	3.09±0.71	3.05±0.50
Center of Mass (m)	R: 0.57±0.019 L: 0.57±0.019	R: 0.79±0.009 L: 0.79±0.009	R: 0.62±0.013 L: 0.62±0.013	R: 0.65±0.046 L: 0.65±0.045	0.64±0.014	0.64±0.014

Table 2. Survey Data (Mean ± SD) for all walking trials.

Treadmill	Tied		Split		
Condition	Normal	Hard	Normal	Hard	Uneven
Achieve Speed	6.5±0.65	4.21±1.48	5.21±1.31	4.71±1.49	4.43±1.65
Maintain Speed	6.43±0.51	4.86±1.56	4.71±1.38	4.86±1.17	4.21±1.37
Stability	6.64±0.5	5.36±1.39	5.07±1.49	5.14±1.29	4.57±1.79
Comfort	6.86±0.36	5.43±1.28	4.93±1.44	5.29±1.14	4.36±1.55