Deciphering DEL Pocket Patterns through Contrastive Learning

Wenyi Zhang[1,2], Yuxing Wang[1,2], Rui Zhan[1,2], Runtong Qian[1,2], Qi Hu[1,2], Jing Huang[1,2,*].

1. Westlake AI Therapeutics Lab, Westlake Laboratory of Life Sciences and Biomedicine, 18 Shilongshan Road, Hangzhou, Zhejiang 310024, China.

2. School of Life Sciences, Westlake University, 600 Dunyu Road, Hangzhou, Zhejiang 310030, China.

*Corresponding author here

Email: huangjing@westlake.edu.cn

Keywords: DNA-Encoded Library (DEL), Pocket Representation, Contrastive Learning, Protein Property Prediction, Drug Target.

Abstract

DNA-encoded libraries (DELs) facilitate high-throughput screening of trillions of molecules against protein targets through split-pool synthesis and DNA tagging. Despite their potential, few DEL-derived compounds have advanced to clinical trials or reached the market. A better understanding of the defining characteristics of target proteins, particularly those with binding pockets suitable for DEL screening, is critical to improving success rates. However, existing approaches remain limited in assessing pocket flexibility and functional similarity. Here, we present ErePOC, a pocket representation model based on contrastive learning with ESM-2 embeddings to address these challenges. ErePOC captures both structural and functional features of binding pockets, enabling identification of shared characteristics among DEL targets. By integrating analyses of low-dimensional physicochemical properties and high-dimensional ErePOC embeddings, we provide a comprehensive view of DEL target space. With 98% precision in downstream classification tasks, ErePOC demonstrates high performance in pocket representation, which is then applied to predict human proteins suitable for DEL screening, with enrichment uncovered across 18 functional categories. This work establishes a new framework for enhancing DEL-based drug discovery through more effective target selection and pocket similarity analysis.

Main Text

1. Introduction

DNA-encoded libraries (DELs) represent a powerful screening technology for discovering small molecules with high affinity for target proteins(1, 2). Constructed through split-pool synthesis, DELs generate vast combinatorial libraries, often containing billions to trillions of compounds, each uniquely labeled with a DNA barcode. These DNA-tagged compounds are then screened based on their binding affinities to specific target proteins, facilitating high-throughput identification of potential drug candidates. DEL technology has contributed to the discovery of numerous hit compounds in target-based drug discovery, with notable successes including inhibitors for SARS-CoV-2 3CLpro(3), soluble epoxide hydrolase(4), Autotaxin(5), and receptor-interacting protein kinase 1 (RIPK1)(6).

Despite the high-throughput capabilities and economic advantages of the DEL technique, the number of DEL-derived molecules advancing to clinical trials or reaching the market remains relatively low, often attributed to the uncertainties in processing DEL data, the difficulties in optimizing DEL hits, and a general lack of understanding on target druggability with DEL molecules(7). To overcome these barriers, efforts to integrate artificial intelligence (AI) with DEL screening have emerged, with most focusing on how to select more promising hits from the highly noisy screening data(8). Notably, DEL molecules are characterized by common features constrained by solution chemistry and the structural requirements for attaching DNA tags, which may result in unique interaction patterns with target protein pockets. A perspective on the characteristics of protein pockets that bind DEL molecules could provide new insights into DEL, potentially enhancing its efficiency and success rates in drug discovery campaigns.

Protein language models (PLMs) have emerged as powerful tools in biological research, with wide applications in protein structure prediction(9), property prediction(10), function annotation(11, 12), and protein design and engineering(13). Despite these advances, large-scale language models specifically designed for binding pockets - the fundamental functional units in drug design - are still limited. Existing methods for pocket representation, such as MASIF(14), primarily rely on learning chemical and geometric features on protein surfaces. In certain machine learning (ML) models for drug-target interaction (DTI) prediction, pocket structures are explicitly encoded(15-18). For example, Uni-Mol(15) utilizes self-supervised masked atom prediction to learn the representations of pocket structures, while PocketAnchor(16) represents pockets using

anchor points sampled in space for downstream pocket detection and binding affinity prediction tasks.

In contrastive learning, ML models are trained to distinguish between similar and dissimilar pairs of data, with the aim often being to learn a generalizable feature representation. Combining such a self-supervised representation learning technique with a pre-trained large PLM such as ESM-2 enables zero-shot or few-shot learning by leveraging the evolutionary information encoded in the PLMs(19). This approach has been effectively utilized in DTI prediction by methods such as DrugLAMP(17) and PocketDTA(18). However, functional classification models for binding pockets remain largely absent.

Key challenges include the lack of comprehensive pocket databases and the inherent structural flexibility of binding pockets, which poses significant difficulties for structure-based models, limiting their effectiveness for functional annotation and classification. Research has also shown that binding pockets for the same ligand (e.g., ATP) can exhibit notable geometric differences(20), and that global structural similarity in proteins does not always correspond to local similarities in pocket structures(21). These observations underscore the limitations of current pocket representation methods, particularly in distinguishing functionally similar pockets. To address these challenges, a more tailored, function-driven approach to pocket modeling is needed to advance both the understanding of binding pockets and drug discovery.

To better represent protein pockets and assess their functional similarity, we introduce ErePOC, a pocket representation model based on contrastive learning. In this approach, ESM-2 embeddings were processed through a feedforward neural network to generate function-aware representations by minimizing a contrastive loss function that increases the similarity between pockets bound to similar ligands while maximizing the dissimilarity between those bound to dissimilar ligands. ErePOC enables the visualization of pocket feature distributions across both experimentally determined and predicted protein spaces, revealing distinct pocket patterns shared by targets binding the same class of ligand.

Building upon these capabilities, we focused on exploring the common features of DEL target pockets. We hypothesize that DEL targets exhibit unique pocket characteristics that can be utilized in drug design decision-making, such as target prioritization and hit identification. By leveraging ErePOC's ability to model these pockets, we screened the human proteome to identify targets containing pockets similar to those successfully engaged by DEL molecules, calculated

corresponding enrichment scores, and uncovered potential targets suitable for DEL screening. This work not only introduces an approach to understanding and improving DEL-based drug discovery but also enhances target identification and pocket analysis, which are crucial for biological discovery in general.

2. Results

This study aims to identify shared characteristics of protein targets suitable for DEL screening, with a particular emphasis on binding pockets as the central unit of analysis. We integrated data from several sources, including BioLiP2(22) and AlphaFill(23), which contains experimental and predicted ligand-protein complex structures, respectively. We also curated two datasets containing complex structures with ligand being either DEL molecules or FDA-approved drugs (FDA-AD). We systematically examined the binding pocket characteristics across the DEL, FDA-AD, and BioLiP2 datasets, focusing on sequence features, physicochemical properties, and binding interactions. The findings are structured as follows: We begin with a detailed analysis of DEL pocket patterns, then introduce the training and validation of the ErePOC model for representing protein pockets. This is followed by an exploration of pocket landscape clustering, where we compare experimentally determined and computationally predicted structures. Finally, we predict human protein classes most likely enriched in DEL screening and evaluate their functional roles and structural similarities at both global and local levels.

2.1 Sequence analysis on pocket datasets

We compared pocket sizes across various structures by analyzing the distribution of amino acid residues within the pockets. These structures are sourced from four categories: (i) the BioLiP2(22) database, which provides experimentally determined binding structures of natural ligands and their associated pockets; (ii) the AlphaFill dataset(23), which contains computationally predicted ligand-protein complex structures; (iii) a DEL dataset curated from ligands reported to be identified by DEL screening (Supporting Information Table S1); and (iv) an FDA-AD dataset containing FDA-approved drugs with experimentally determined complex structures (Table S2). They include 326,416, 330,434, 128, and 630 pockets, respectively. For BioLiP2, pockets were defined using experimentally annotated binding residues provided by the webserver. Meanwhile, pockets for the AlphaFill, DEL, and FDA-AD datasets were generated by including all amino acid residues within 5 Å of the bound ligand.

As shown in Fig. 1A, the average number of residues in BioLiP2, AlphaFill, DEL, and FDA-AD pockets was 9.1, 12.9, 28.1, and 17.7, respectively. DEL and FDA-AD pockets were notably larger than those in BioLiP2 and AlphaFill, likely due to differences in ligand characteristics. Drug candidates, being larger and chemically more complex than natural ligands, are specifically designed to exhibit strong binding affinity and target specificity. They often target protein pockets that are more spacious, flexible, and dynamic, accommodating a broader range of interactions. Natural ligands and their corresponding pockets have co-evolved for an optimized fit, with affinities tuned to suit biological needs rather than maximizing binding. In contrast, synthetic drugs molecules, lacking this evolutionary adaptation, may require larger, more adaptable pockets to ensure effective binding. DEL pockets were larger than FDA-AD ones, which aligns with the general understanding that DEL molecules are larger, with average molecular weights of 1298.5 Da and 218.3 Da in our datasets, respectively.

We analyzed amino acid frequencies in binding pockets across the BioLiP2, DEL, and FDA-AD datasets. To highlight compositional differences, we calculated the enrichment ratio of each amino acid relative to its abundance in the PDB. As shown in Fig. 1B, methionine, tyrosine, tryptophan, and phenylalanine were the four most significantly enriched amino acids in the DEL dataset. These four were also the most enriched in FDA-AD, appearing more than twice as frequently in drug-binding pockets compared to proteins in general. These bulky side chains potentially provide unique pocket geometries for specific molecular binding, as well as anchors for hydrophobic and aromatic interactions. Compared to BioLiP2, hydrophobic amino acids including methionine, leucine, and valine were significantly enriched in DEL and FDA-AD. In contrast, cysteine showed significantly lower enrichment in drug-binding pockets. We note that our analysis excluded covalent drug molecules, which primarily react with cysteine's thiol group. Overall, our analysis reveals that DEL and FDA-AD pockets share similar amino acid composition patterns, distinguishing them from pockets that bind natural ligands.

2.2 Analysis of pocket physicochemical properties and their interactions with ligands

We used Fpocket(24) to analyze the biochemical and biophysical properties of pockets across the DEL, FDA-AD, and BioLiP2 datasets. Six Fpocket descriptors were grouped into three clusters to compare pocket size, hydrophobicity, and polarity (Figure 2 A-F). Pocket size was assessed using volume and the number of alpha spheres. The average volumes of pockets were 3301.2 Å³ for DEL, 2723.3 Å³ for FDA-AD, and 1612.8 Å³ for BioLiP2. DEL pockets were

approximately 1.2 times larger than FDA-AD pockets, which were nearly twice the size of BioLiP2 pockets. DEL pockets also contained more alpha spheres (164.3) than FDA-AD (130.0), making them 1.26 times larger in this size metric. The average alpha sphere densities were 11.0 Å for DEL, 10.2 Å for FDA-AD, and 8.6 Å for BioLiP2, suggesting that DEL molecules generally bind to more open and exposed pockets.

DEL and FDA-AD pockets are more hydrophobic than BioLiP2 pockets, as indicated by their higher proportions of apolar alpha spheres and larger mean local hydrophobic densities. Interestingly, while DEL and FDA-AD pockets exhibit similar distributions of local hydrophobic densities, their apolar sphere proportions differ, averaging 53.8% for FDA-AD, 50.8% for DEL, and 45.3% for BioLiP2. For polar interactions, the distributions were similar. BioLiP2 had the highest proportion of polar atoms in pockets (39.0%), followed by DEL (37.3%) and FDA-AD (35.9%).

We further analyzed the interactions between pocket residues and ligands using the Arpeggio method(25) (Figure 2 a-c). Hydrophobic interactions accounted for 50.7% in DEL, 49.5% in FDA-AD, and 30.1% in BioLiP2. Hydrogen bond interactions were 3.8% for DEL, 4.8% for FDA-AD, and 9.9% for BioLiP2, while polar interactions constituted 6.0%, 7.8%, and 14.8%, respectively. Ionic interactions can be found in the DEL dataset (1.50%) but were almost absent in FDA-AD (0.15%) (Figure S1).

Overall, these results indicate that the binding of DEL hit molecules relies more on pocket shape complementarity and can be further optimized towards drug molecules. The pocket analysis is also consistent with molecular property differences obtained using MOE(26) (Figure S2). DEL molecules exhibited lower water solubility (LogS = -6.49) compared to approved drugs (-4.08) and higher hydrophobicity (cLogP = 3.42 vs. 2.54). DEL pockets possess unique features in their physicochemical properties, distinguishing them from general protein pockets. However, no single feature or simple combination is sufficient to differentiate them, possibly due to the broad variability of pocket structures.

2.3 ErePOC: an Enhanced representation of POCkets by contrastive learning

We developed ErePOC, a contrastive learning-based model trained on 326,416 pocket-ligand pairs from the BioLiP2 dataset, to generate latent space representations of binding pockets (Fig. 3). For each pair, pocket residues were embedded using 1280-dimensional feature vectors from ESM-2, and pocket-level features were obtained by average pooling of residues forming the

binding pocket. This approach ensures that the spatial profile captures structural information intrinsic to the pocket. To quantify pocket similarity, each 1280-dimensional pocket embedding was projected into a 256-dimensional latent space through a two-layer perceptron. Pocket similarity was computed as the cosine similarity between these 256-dimensional pocket representations, while ligand similarity was evaluated using the cosine similarity of their 2048-dimensional molecular fingerprints. Unlike conventional drug-target interaction models, ErePOC employs Kullback-Leibler (KL) divergence as the loss function to align ligand distributions with the pocket landscape, encouraging pockets that bind chemically similar ligands to be positioned closer in the latent space.

Ultimately, ErePOC learns a compact 256-dimensional representation for each pocket, effectively capturing both fine-grained similarities and key distinctions among binding sites. By aligning pockets according to the chemical similarity of their ligands through contrastive learning, this approach results in an enhanced, function-aware representation of binding pocket features. The resulting latent space provides deeper insights into pocket-ligand interactions, enhancing the classification and analysis of binding pockets.

We evaluated our model using zero-shot learning tasks to compare the performance of representations derived from ESM-2 embeddings and those learned by ErePOC. We considered a classification task involving seven types of pockets, each corresponding to a unique ligand type - ADP (9,531 pockets), COA (1,900), FAD (6,367), HEMe (13,312), NAD (5,354), NADP (3,997), and SAM (1,228) - totaling approximately 43,000 binding pockets curated from BioLiP2. Figures 4A and B show the clustering of these seven binding pocket types using t-SNE(27) based on ESM-2 and ErePOC representations, respectively. The results clearly demonstrate that the contrastive learning framework generates well-separated clusters for different ligand/pocket types, effectively capturing both functional and ligand-specific features of the binding pockets. In contrast, the ESM-2-based model, which lacks functional annotations specific to pockets, shows limited separation between pocket types. This comparison highlights the superior performance of contrastive learning in producing more refined and informative representations for functional pocket classification.

To assess the robustness of our model, we conducted an ablation study in which two types of binding pockets were completely excluded from the BioLiP2 training dataset prior to contrastive learning. We then evaluated the model's performance in classifying these excluded pocket types.

Figure S3 presents t-SNE visualizations for various exclusion scenarios: ADP and FAD, HEM and ADP, ADP and NAD, and HEM and SAM pockets. The results show that strong classification performance was maintained even for pockets excluded from training. The contrastive learning framework effectively distinguishes the removed ligand types, highlighting its ability to generalize and accurately classify pockets based on their functional and ligand-binding features. This robustness suggests that the model leverages annotated ligand information during training to make reliable predictions, even when specific ligand types are absent from the training set. This underscores the effectiveness of ErePOC in capturing and generalizing key binding pocket characteristics.

The approach was further validated by analyzing ATP-, FAD-, and HEM-binding pockets from both the BioLiP2 dataset (experimentally determined structures) and the AlphaFill dataset (which imputes ligands into AF2-predicted structures). t-SNE clustering based on ESM-2 features (Figure S4A) showed limited separation between pocket types. In contrast, the ErePOC representation revealed substantial overlap among pockets binding the same ligands across both datasets, demonstrating ErePOC's ability to capture structural similarities between experimental and predicted protein-ligand complexes.

Additionally, 500 randomly selected pockets from the BioLiP2 dataset were used to compute the correlation coefficient (shown in Fig. S5). Pearson correlation analysis demonstrated a robust correlation of 0.96 between ligand Tanimoto similarity and pocket cosine similarity derived from the ErePOC vector, highlighting ErePOC's aptitude for capturing meaningful pocket-ligand interactions. Furthermore, five pockets were randomly chosen from each of the seven ligand-binding types to compute pairwise cosine similarities. The heatmap in Fig. S6 compares the similarity results using the ESM-2 embeddings, ErePOC vectors, and t-SNE 2D projections following ErePOC transformation. The cosine similarity computed from ErePOC representations effectively distinguished between various pocket types, whereas ESM-2 demonstrated limited discriminatory power. Moreover, cosine similarity based on t-SNE-reduced representations also performed poorly in assessing pocket relationships. In summary, ErePOC proves highly proficient in identifying pockets that bind ligands with analogous structural features.

We designed another downstream classification task involving prediction of the seven ligand-binding pocket types using few-shot learning with ESM-2 and ErePOC representations. For independent testing, 10% of the targets were held out, ensuring a comprehensive evaluation of

the model's performance. Given the relatively straightforward nature of this classification task, all models achieved strong results. In this few-shot learning setup, we tested four models: ErePOC-NN, ErePOC-SVM, ESM2-NN, and ESM2-SVM. The ErePOC-NN and ErePOC-SVM models used pocket representations derived from contrastive learning as input features, paired with either a neural networks (NN) or a support vector machines (SVM) classifiers, respectively. Similarly, ESM2-NN and ESM2-SVM relied on direct embeddings from ESM-2, utilizing NN and SVM classifiers.

Figure S7 compares the performance of these models on the testing dataset. ESM2-NN achieved the highest overall accuracy (0.989), followed closely by ErePOC-NN (0.986) in classifying the seven ligand-bound pocket types. We note that the MaSIF-ligand model, trained using the MaSIF representation, achieved an accuracy of 0.74 for the same task, although the result was obtained on a different test set(14). Interestingly, when assessing the performance of the SVM models with an RBF kernel, ESM2-SVM's accuracy dropped significantly to 0.811, while ErePOC-SVM maintained a high accuracy of 0.985. This notable difference underscores the superiority of contrastive learning in generating robust representations for functional pocket classification. It also highlights ErePOC's capability to generalize to diverse or previously unseen pockets, whereas ESM-2's pre-trained features appear less effective for this specific task without further fine-tuning.

2.4 Clustering and characterization of DEL pockets in experimental and predicted protein landscapes

The primary goal of this study is to explore the distribution of drug-related and lead-binding pockets across the entire protein space. Using ErePOC representation, we projected the FDA-AD and DEL datasets onto the comprehensive pocket landscape generated using the BioLiP2 dataset (Figure 4C-D) and the AlphaFill dataset (Figure S8). t-SNE visualization illustrates that experimentally resolved metabolite pockets are organized into distinct localized regions (Fig. 4C), demonstrating ErePOC's ability to differentiate functional pockets. Furthermore, pockets bound to approved drug molecules (FDA-AD, shown in purple in Fig. 4D) are widely distributed throughout the protein space, rather than being confined to specific clusters, highlighting their versatility. Figure 4D also highlights the similar distribution patterns of DEL pockets (dark grey) and FDA-AD pockets, which scatter across the latent space. This spatial concordance aligns with previous Fpocket analyses, which emphasized similarities in their physicochemical properties. Together,

these results suggest that DEL screening can readily access most of the known druggable target space.

The ErePOC representation partitions the BioLiP2 pocket space into distinct patterns, offering critical insights into the global pocket landscape. For example, pockets bound to native ligands such as SAM or HEM appear less suitable as drug targets - particularly in the context of DEL screening. In contrast, pockets bound to ADP seem more flexible to accommodate designed molecule. To further explore the "DEL-able" regions of this landscape, we identified the five nearest neighbors for each DEL target in the BioLiP2 dataset based on cosine similarity (Figure S9). A total of 361 pockets in BioLiP2, referred to as DEL neighbors, exhibited cosine similarity scores greater than 0.8. The physicochemical properties of these DEL neighbors, as computed using Fpocket, are summarized in Figure S10. The average pocket volume for the DEL neighbors changed from 1612.84 to 2038.69 $Å^3$, corresponding to an approximate 26.4% increase relative to the average volume of natural pockets in the BioLiP2 dataset. The average number of alpha spheres for DEL neighbors changed from 69.35 to 92.35, reflecting a 33.2% increase and indicating higher structural complexity. Furthermore, the mean local hydrophobic density for DEL neighbors increased from 14.98 to 21.71, representing a 44.9% enhancement, emphasizing their pronounced hydrophobic nature.

In terms of interaction profiles, hydrophobic interactions in DEL neighbors changed from 30.1% to 42.0%, reflecting a 36.7% increase compared to BioLiP2 pockets. Hydrogen bond interactions, however, decreased from 9.9% to 7.0%. Polar interactions in DEL neighbors increased from 9.8% to 14.8%, showing a 51.0% rise in polarity relative to the BioLiP2 pockets. In total, these DEL neighbors exhibit larger volumes and greater spatial expansiveness than typical natural pockets in BioLiP2, with physicochemical properties that closely resemble those of both DEL and FDA-AD pockets. The similarities of DEL neighbors make them promising candidates for DEL screening. Furthermore, the ligand-pocket interaction profiles of DEL neighbors, DEL pockets, and FDA-AD pockets were found to be comparable, as illustrated in Figure S10A-C, reinforcing the similarity in their functional characteristics.

2.5 Identification and Characterization of Human Protein Pockets for DEL Screening

We screened AlphaFold2-predicted human proteins (23,391) to predict binding pockets most likely suitable for DEL screening(28). First, Fpocket was used to identify pockets in these human proteins. For each pocket, the average pLDDT of its constituent residues was calculated as the

pocket pLDDT score. Pockets with a volume smaller than 800 Å³ or a pLDDT score below 0.7 were excluded, yielding a total of 182,424 human protein pockets. These pockets were then encoded using ErePOC embeddings, and their cosine similarity to 128 known DEL pockets was computed, from which the highest similarity was assigned to each pocket. Ultimately, 4,774 pockets with a cosine similarity greater than 0.8 were identified. After removing duplicates based on UniProt ID, 2,739 unique human proteins were predicted to contain DEL-compatible pockets. The overall prediction workflow is illustrated in Fig. 5A.

Among the predicted human proteins, 17.9% were classified as transferases, 11.6% as hydrolases, and 9.4% each for DNA-binding proteins and oxidoreductases. In comparison, the 128 DEL target proteins were predominantly transferases (27.1%), followed by hydrolases (17.4%) and receptors (9.7%). As shown in Fig. 5B, the overall distribution of functional classes among predicted and known DEL targets is similar. Enrichment scores for each protein class were calculated using a hypergeometric test, and Figure 5C depicts the distribution of enrichment scores for proteins with p-values < 0.05. Notably, several classes, including **oxidoreductases, multifunctional enzymes, transferases, chromatin regulators, lyases, and isomerases,** exhibited enrichment scores ranging from 1.36 to 6.24 in both the DEL target set and the predicted human protein dataset. We note that the isomerase class is also listed, with an enrichment score of 1.35 in the predicted human protein dataset and a p-value of 0.056.

Among known DEL targets, three multifunctional enzymes—AASS (aminoadipate-semialdehyde synthase, PDB: 5L78), PSMA (proteasome subunit alpha, PDB: 1Z8L), and sEH (soluble epoxide hydrolase, PDB: 1ZD4)—resulted in the strongest enrichment. These enzymes catalyze two or more distinct biochemical reactions, which explains their dual classification in our analysis (e.g., sEH is counted as both a hydrolase and an oxidoreductase). The significant enrichment of multifunctional enzymes (p<0.05) suggests that DEL molecules may preferentially target proteins with complex structural architectures and flexible pockets that support multiple catalytic activities.

Figure S11 presents a t-SNE visualization of the distribution of DEL pockets within human proteins, alongside human protein pockets with cosine similarity > 0.8. Consistent with findings from the BioLiP2 and AlphaFill datasets, DEL pockets exhibit a broad and diverse distribution. Notably, human protein pockets closely resembling DEL pockets cluster into three distinct groups. However, a substantial number of DEL pockets lack highly similar counterparts among human

proteins. This disparity may arise from the limitations of AlphaFold2 in predicting accurate protein structures or the potential inaccuracies of Fpocket in identifying binding pockets, both of which could impact the detection of DEL-like pockets across the human proteome.

2.6 Global and local structure comparison for human DEL targets

Figure 6 presents case studies comparing global and local pocket structures for protein classes enriched in both predicted and known DEL targets. Using ErePOC embeddings, the cosine similarity scores of binding pockets within each class were calculated. Pockets with high cosine similarity and UniProt IDs assigned to the same protein class were grouped for comparative analysis of their global and local structural features. Global structural similarity was assessed using TM-align(29), which computes the TM score measuring the 3D similarity of overall protein structures, while pocket-level similarity was evaluated using PPS-align(30) , which reports the pocket similarity (PS) score measuring the 3D similarity of pockets. Both scores range from 0 to 1, with higher values indicating more similar topology. Specifically, a PS score greater than 0.46 indicates that the pocket has a similar structure(30). Illustrated in Figures 6A-D are four representative cases, each from the oxidoreductase, multifunctional enzyme, transferase, and hydrolase classes, that exhibit high similarity in latent representation space despite dissimilarity in both global protein and local pocket structures. These examples highlight how contrastive learning imparts the capacity to detect higher-level functional or physicochemical similarities that are not solely reflected by either global or local 3D structural alignment.

In contrast to above examples, we also identified instances with consistently high similarity in the latent pocket representation space and in global and local structures. Two such examples— one from the lyase class and another from the chromatin regulator class—are illustrated in Fig. 6E and 6F, exhibiting strong structural similarity at both levels, with TM scores exceeding 0.9 and PS scores above 0.5. We note that some divergence in pocket residues may arise due to the sensitivity of pocket definition, yet the latent space representation appears robust to such variation. Fig. 6G illustrates a case involving a known DEL target (FKBP) and the predicted protein target P26885 (FKBP2), which share a TM score of 0.85, indicating strong global structural similarity. However, their pocket similarity score is only 0.24, likely due to the flexible and extended nature of the binding pocket, which severely limits the effectiveness of rigid-body 3D alignment of local structures. Despite this, ErePOC identified a high cosine similarity of 0.81 in

the pocket latent space, reasonably suggesting that FKBP2 should also be a target accessible to DEL molecules.

Our analysis is not restricted to the functional classes annotated in UniProt. For example, ErePOC identified potential ligand-binding similarity between the RNA-binding protein NOP56 (UniProt: Q8TAS1) and the SAM-dependent methyltransferase TrmD (PDB: 1UA2), despite their distinct canonical biological roles. A moderate TM-score (0.75) suggests a shared Rossmann-like fold, while a moderate PS score (0.43) may arise from conserved cofactor-binding architectures (e.g., SAM/RNA interaction interfaces). This observation implies that DEL-derived chemotypes targeting TrmD's catalytic pocket could potentially engage other RNA-modifying enzymes with analogous structural features.

These findings highlight that while global and pocket-level structural similarities can indicate spatial configurations, they do not fully characterize binding pocket functionality. The inherent flexibility of binding pockets, and the conformational selection or induced fit that occurs during ligand binding, further complicates their structural representation. ErePOC's robustness stems from its integration of ESM-2 embeddings, which incorporate evolutionary information at the amino acid level to generate high-dimensional representations of physicochemical properties. Moreover, contrastive learning enhances the specific functional characterization, offering resilience to structural distortions induced by ligand binding. These underscore ErePOC's utility in providing a comprehensive and functionally relevant representation of binding pockets.

3. Conclusion and Discussion

In this study, we investigated the binding patterns of 128 targets that have been successful in DEL screening, focusing on the local structures and properties of their binding pockets. Our analyses included sequence-based evaluations and assessments of physicochemical properties, such as pocket characteristics and ligand-pocket interactions. The results revealed that DEL binding pockets possess unique structural and chemical features compared to natural ligand-binding pockets. Specifically, methionine, leucine, and valine were significantly enriched in DEL binding pockets, likely due to their flexibility, which allows the pocket to adapt its conformation to accommodate diverse ligand shapes. Furthermore, DEL pockets were found to have larger volumes and predominantly hydrophobic environments compared to natural ligand-binding pockets in the BioLiP2 dataset.

It is well established that structure determines function. However, when focusing on binding pockets - the minimal functional units relevant to drug design - their inherent flexibility presents a significant challenge. Two pockets that binds the same ligand can often display low 3D structural similarity, as reflected by PS scores below 0.4. This underscores the difficulty of assessing pocket similarity based solely on geometries. Furthermore, the functional similarity between pockets is closely tied to local physicochemical and thermodynamical properties, which are inherently complex and challenging to quantify.

As a step toward addressing this issue, we developed ErePOC, a pocket representation model that leverages contrastive learning with ESM-2 embeddings to evaluate pocket similarity. Using t-SNE visualizations of the BioLiP2 and AlphaFill datasets, we showed that ErePOC can reliably classify and distinguish pockets that bind the same ligand type. This capability was enabled by a KL divergence-based contrastive loss that aligns pocket similarity with ligand similarity, allowing functional classification of pockets even in the absence of explicit annotations. For each input protein pocket, ErePOC generates a compressed feature vector that serves as the latent representation that integrates local physicochemical properties and evolutionary constraints. Validation results demonstrated that ErePOC effectively overcomes the limitations of traditional 3D pocket structure alignment. These findings highlight ErePOC's potential as a powerful tool for pocket characterization and its applicability in advancing AI-driven drug design.

Using the cosine similarity calculated by ErePOC, we identified neighboring pockets of DEL pockets from the BioLiP2 dataset and analyzed their physicochemical properties and interaction patterns. The results demonstrated that these neighboring pockets shared highly similar property distributions with DEL pockets, further validating ErePOC's capability to effectively represent pocket features. Extending this analysis to 23,391 AlphaFold2-predicted human protein structures, we identified over 2,700 candidates with pockets closely resembling those that bind DEL molecules, suggesting that they are suitable for DEL screening. These potential targets cover a wide range of functional classes. In particular, seven protein classes were found to be highly enriched in both the DEL dataset and predicted human pockets, with transferases and hydrolases showing particularly high enrichment levels. Moreover, eleven additional human protein classes were also predicted to be suitable for DEL screening. These findings collectively demonstrate that the structural space amenable to DEL targeting is remarkably broad and diverse.

While ErePOC was developed to characterize and identify potential target proteins suitable for DEL screening, its unique representation of pocket functionality allows it to be applied to a wide range of downstream tasks, such as virtual screening(31, 32), lipid-binding pocket prediction(33), reverse screening(34), molecule generation(35), and protein design(36). In particular, when integrated with protein structure prediction frameworks such as AlphaFold3(37), ErePOC can significantly enhance the accuracy and utility of protein complex structure predictions, especially in optimizing and constraining pocket conformations. ErePOC may also facilitate the design of functional proteins with specific binding functionalities, which is a key advance in drug discovery and biomedical engineering(38, 39). The generalizability and adaptability of ErePOC underscore its potential as a versatile tool in AI-driven molecular design and target discovery.

4. Materials and Methods

4.1 Construction of ligand-pocket complexes datasets

Our study incorporates the following datasets (summarized in Table S1), which include both experimentally determined and computationally predicted structures of ligand-protein complexes, as well as datasets related to DELs and FDA-approved drugs. The first dataset consists of high-resolution experimental structures sourced from BioLiP2 (updated as of March 9, 2024), a semi-manually curated database focused on biologically relevant ligand-protein binding interactions. We extracted only regular ligands, excluding metals, peptides, DNA, and RNA, resulting in a final dataset of approximately 326,416 ligand-protein complexes. The binding sites, as defined in the BioLiP2 dataset, were used to identify the corresponding binding pockets.

Additionally, we curated predicted ligand-protein complex structures from the AlphaFill database. AlphaFill transfers ligands, cofactors, and metal ions to AlphaFold-predicted models based on sequence and structural similarities. However, due to potential clashes between the transplanted ligands and the predicted receptor structures, the quality and resolution of the predicted complexes were relatively low. Only regular ligands were retained, and pockets were defined as the amino acid residues within 5 Å of the ligand. The final AlphaFill dataset consisted of 330,434 predicted ligand-protein structures.

Our third dataset focused on FDA-approved drugs, collected from the DrugBank database. We gathered information on 2,863 FDA-approved drugs and used their SMILES representations to search the Protein Data Bank (PDB) for corresponding drug-protein complexes. In total, 5,286

potential drug-protein complex structures were identified. Ligands in these structures were marked using the 'HET' keyword, and Tanimoto similarity based on molecular fingerprints was calculated between these ligands and the FDA drug list. A ligand was considered an FDA-approved drug if its Tanimoto similarity exceeded 0.7. Pockets were defined as amino acid residues within 5 Å of these ligands, resulting in a final dataset of 630 unique crystal structures of drug-pocket complexes.

The fourth dataset was specifically developed for DEL compounds. This dataset was compiled from the DELOpen platform (https://www.delopen.org/) by WuXi AppTec, with the latest update in April 2023. We analyzed target proteins and their binding residues using public references, and corresponding structures were downloaded from the PDB. For each target protein, only the DEL hit with the best binding affinity was retained. The 3D conformation of each ligand was generated using energy minimization in the Molecular Operating Environment (MOE). Induced fit docking was then performed in MOE to predict the binding poses of the DEL hits with the target proteins. If the experimental structure of a DEL hit-target protein complex was available, it was included in the dataset instead. This dataset ultimately consisted of 128 unique DEL hit-target protein structures. Detailed information on the DEL dataset is provided in Table S2.

Finally, we downloaded 23,391 predicted human protein structures from the AlphaFold Protein Structure Database (Homo sapiens species). Each of these proteins was processed using the Fpocket tool to predict potential binding pockets. To analyze the enrichment of amino acids in our benchmark datasets, we referenced the ratios of the 20 types of amino acids that are enriched in the PDB database. These ratios were obtained from NIMBioS. (https://legacy.nimbios.org//~gross/bioed/webmodules/aminoacid.htm).

4.2 Pocket physicochemical characterization and shape similarity analysis

We used the Fpocket(24) tool to extract pocket descriptors from experimental structures in BioLiP2, FDA-AD, and the DEL datasets. These descriptors include volume, number of alpha spheres, proportion of apolar alpha spheres, mean local hydrophobic density, density of alpha spheres, and proportion of polar atoms. These properties were calculated to provide insights into the physical characteristics of the binding pockets. Specifically, volume reflects the size of the cavity, with larger values indicating larger pockets. The number of alpha spheres and the proportion of apolar alpha spheres capture the geometric and hydrophobic features of the pocket, with a higher proportion of apolar spheres suggesting a more hydrophobic environment. The

mean local hydrophobic density serves as a descriptor for the overall hydrophobicity of the pocket, with higher values indicating greater hydrophobicity. The density of alpha spheres provides an indication of the packing density of the pocket, while the proportion of polar atoms helps assess the hydrophilicity of the binding site.

4.3 Pocket-ligand interaction analysis using Arpeggio

We analyzed pocket-ligand interactions using the Arpeggio(25) tool, which identifies contacts at the pocket-ligand interface. These contacts were extracted from the '.bs_contactsfile' file generated by Arpeggio. The interaction types included in our analysis were van der Waals, hydrogen bonds, weak hydrogen bonds, halogen bonds, ionic interactions, aromatic interactions, hydrophobic interactions, carbonyl interactions, polar interactions, and weak polar interactions. For each ligand-pocket complex, we summed the number of interactions of each type between the ligand and pocket atoms. The proportion of each interaction type was calculated by dividing its count by the total number of interactions, allowing us to compare the relative contributions of different interaction types to the overall binding profile.

4.4 Evaluation of molecular properties and ligand similarity

We evaluated the molecular properties of ligands from the BioLiP2 dataset, DEL hits, and FDA-approved drugs. The properties analyzed included the number of hydrophobic atoms (a_hyd), the number of hydrogen atoms (a_nH), the log octanol/water partition coefficient (logP), the log solubility in water (logS), and the topological polar surface area (TPSA). These properties were plotted to visualize their distribution across BioLiP2 ligands, FDA-approved drugs, and DEL hits. Ligand similarity was calculated using extended connectivity fingerprints (ECFP4), generated with the RDkit package(40), to compare the molecular structures and assess their similarities across the datasets.

4.5 ErePOC model architecture

Pocket featurization. The input to the ErePOC model is the full-length amino acid sequence of the target protein. Each amino acid in the sequence is transformed into an embedding vector using the ESM-2 model. The embedding vector $E \in \mathbb{R}^{d_t}$ has a default dimension of d_t=1280 as defined by ESM-2. The binding pocket is represented by a vector $P \in \mathbb{R}^{d_t}$, which is computed as the mean of the embedding vectors for the amino acids located within the binding pocket. This mean pooling process generates a feature vector that effectively captures the overall characteristics of the binding pocket.

Mapping into a common latent space. To compare pockets in a shared latent space, we first map the pocket embeddings $P_1 \in \mathbb{R}^{d_t}$ and $P_2 \in \mathbb{R}^{d_t}$ into a common latent space. This is achieved by applying a fully connected layer with GELU (Gaussian Error Linear Unit) activation, which transforms the pocket embeddings into latent vectors $T_1^* \in \mathbb{R}^h$ and $T_2^* \in \mathbb{R}^h$. The transformation is parameterized by weight matrices $W_t \in \mathbb{R}^{h*d_t}$, and bias vectors $b_t \in \mathbb{R}^h$, described by the following equation:

$$T^* = \text{GELU}(W_t P + b_t) \text{ (1)}$$

Once we obtain the latent embeddings T_1^* and T_2^*, their cosine similarity is computed to measure the distance between the two pockets:

$$\text{CosineSimilarity}(T_1^*, T_2^*) = \frac{T_1^* \cdot T_2^*}{\|T_1^*\|_2 \cdot \|T_2^*\|_2} \text{ (2)}$$

Although the pockets themselves are not directly annotated in our dataset, each pocket is associated with a specific binding ligand. To differentiate between pockets, we use the KL divergence as the loss function. The idea is that pockets whose ligands are similar - whether in structure, function, or chemical properties - should be represented closer together in the latent space. The loss function is defined as:

$$\text{loss} = P_{ij} \log \left(\frac{P_{ij}}{Q_{ij}}\right) \text{ (3)}$$

Here, Q_{ij} represents the similarity between the ligands bound to pockets *i* and *j*, computed using the Morgan fingerprint, which encodes each molecule into a fixed-dimensional embedding $M \in \mathbb{R}^{d_m}$, where d_m =2048. This formulation ensures that the model distinguishes between pockets by leveraging the similarity of their associated ligands, while guiding the pockets to be represented closely in the latent space if their ligands are similar.

Implementation. Model training was performed using the Adam optimizer with an initial learning rate set to 0.001. Early stopping with a patience of 100 epochs was applied, saving the model with the lowest validation loss. The maximum number of epochs was set to 2000. Each training epoch consisted of 4096 batches with 128 samples per batch, while validation used 256 batches of 128 samples. The model architecture included a 2-layer neural network, with intermediate dimension $d = 512$ and output dimension $d = 256$. Each layer applied batch normalization, followed by dropout (rate = 0.1), and GELU activation. The model was

implemented in PyTorch version 2.3.1 and trained on a machine equipped with NVIDIA L40 GPUs.

Validation through binding pocket classification. To assess the performance of ErePOC, we constructed a dataset of approximately 43,000 protein binding pockets, each labeled with one of seven types of bound ligands: ADP, COA, FAD, HEM, NAD, NADP, and SAM. We then designed a downstream classification task to evaluate the ability of our model to distinguish between these different binding pockets. For a comprehensive evaluation, we compared our model against three baseline models using zero-shot learning: ErePOC-NN, ESM2-NN, ErePOC-SVM, and ESM2-SVM. In ErePOC-NN and ErePOC-SVM, the pocket representations derived from contrastive learning were used as input features, with classifiers being NN or SVM, respectively. Similarly, in ESM2-NN and ESM2-SVM, the features directly extracted from the ESM-2 model were used, with NN and SVM classifiers employed for the classification task. The dataset was split 9:1 into training and test sets. Model performance was evaluated using precision, recall, and F1-score:

$$Recall = \frac{TP}{TP+FN} \quad (4)$$

$$Precision = \frac{TP}{TP+FP} \quad (5)$$

$$F1 - score = 2 \times \frac{Precision \times Recall}{Precision + Recall} \quad (6)$$

where TP stands for True Positives, FP for False Positives, and FN for False Negatives.

4.6 Hypergeometric test for enrichment analysis

In this study, we applied a hypergeometric test(41) to assess the enrichment of human proteins whose binding pockets exhibit high cosine similarity (greater than 0.8) to pockets known to bind compounds in DNA-encoded libraries. The goal was to determine whether specific protein families or functional categories are significantly enriched within the subset of human proteins containing DEL-suitable pockets. For each human protein in the predicted dataset, we retrieved functional annotations using UniProt IDs and categorized them according to molecular functions and protein families, as defined in the UniProt database. This classification allowed us to categorize the human proteins into specific functional groups, such as enzyme families or cellular processes. We then calculated the enrichment score (ES) for each protein class, comparing its representation in the subset of DEL-suitable human proteins to its representation in the overall human proteome. Specifically, the enrichment score for a given protein class *i* was defined as:

$$Enrichment\_score(ES)_i = \frac{N(i)_M}{N(i)_{\text{total}}} / \frac{N_M}{N_{\text{total}}} \quad (7)$$

where $N(i)_M$ is the number of proteins of the *i*-th classification in the subset *M*, which includes the human proteins with pockets that exhibit cosine similarity > 0.8 to known DEL pockets. $N(i)_{total}$ is the total number of proteins of the *i*-th classification in the entire human protein dataset. N_M and N_{total} are the total numbers of proteins in subset *M* and the entire dataset, respectively. An enrichment score greater than 1 indicates that the given protein class is overrepresented in the DEL-suitable subset. To evaluate statistical significance, we computed the p-value using the hypergeometric distribution:

$$p(observed) = \frac{\binom{N(i)_{\text{total}}}{N(i)_M}\binom{N_{total}-N(i)_{total}}{N_M-N(i)_M}}{\binom{N_{\text{total}}}{N_M}} \quad (8)$$

Data and Code availability

All source codes are available at https://github.com/JingHuangLab/ErePOC, together with data files to reproduce the results in this manuscript. The BioLiP2, AlphaFill and AF2-predicted protein structure datasets were obtained from https://zhanggroup.org/BioLiP/, https://alphafill.eu/, and https://alphafold.ebi.ac.uk/download.

Acknowledgments

This work is supported by the "Pioneer" and "Leading Goose" R&D Program of Zhejiang (2023C03109, 2024SSYS0036), the National Natural Science Foundation of China (32171247), the Zhejiang Provincial Natural Science Foundation (LQ23F020011), and the Westlake Education Foundation. We thank the Westlake University Supercomputer Center for computational resources and related assistance.

References

1. P. Ma *et al.*, Evolution of chemistry and selection technology for DNA-encoded library. *Acta Pharmaceutica Sinica B* **14**, 492-516 (2024).

2. A. Gironda-Martínez, E. J. Donckele, F. Samain, D. Neri, DNA-encoded chemical libraries: a comprehensive review with succesful stories and future challenges. *ACS Pharmacology & Translational Science* **4**, 1265-1279 (2021).

3. N. Hou *et al.*, Development of highly potent noncovalent inhibitors of SARS-CoV-2 3CLpro. *ACS central science* **9**, 217-227 (2023).

4. Y. Ding *et al.*, Discovery of soluble epoxide hydrolase inhibitors through DNA-encoded library technology (ELT). *Bioorganic & Medicinal Chemistry* **41**, 116216 (2021).

5. J. W. Cuozzo *et al.*, Novel Autotaxin Inhibitor for the Treatment of Idiopathic Pulmonary Fibrosis: A Clinical Candidate Discovered Using DNA-Encoded Chemistry. *J Med Chem* **63**, 7840-7856 (2020).

6. P. A. Harris *et al.*, Discovery of a First-in-Class Receptor Interacting Protein 1 (RIP1) Kinase Specific Clinical Candidate (GSK2982772) for the Treatment of Inflammatory Diseases. *J Med Chem* **60**, 1247-1261 (2017).

7. A. A. Peterson, D. R. Liu, Small-molecule discovery through DNA-encoded libraries. *Nat Rev Drug Discov* **22**, 699-722 (2023).

8. M. Wichert, L. Guasch, R. M. Franzini, Challenges and Prospects of DNA-Encoded Library Data Interpretation. *Chem Rev* **124**, 12551-12572 (2024).

9. Z. Lin *et al.*, Evolutionary-scale prediction of atomic-level protein structure with a language model. *Science* **379**, 1123-1130 (2023).

10. J. Ouyang-Zhang, D. Diaz, A. Klivans, P. Krähenbühl. 2023. Predicting a protein's stability under a million mutations. Advances in Neural Information Processing Systems, Ernest N. Morial Convention Center in New Orleans.

11. M. Kulmanov *et al.*, Protein function prediction as approximate semantic entailment. *Nature Machine Intelligence* **6**, 220-228 (2024).

12. D. Wang *et al.*, S-PLM: Structure-Aware Protein Language Model via Contrastive Learning Between Sequence and Structure. *Adv Sci (Weinh)* 10.1002/advs.202404212, e2404212 (2024).

13. Y. He *et al.*, Protein language models-assisted optimization of a uracil-N-glycosylase variant enables programmable T-to-G and T-to-C base editing. *Mol Cell* **84**, 1257-1270 e1256 (2024).

14. P. Gainza *et al.*, Deciphering interaction fingerprints from protein molecular surfaces using geometric deep learning. *Nature Methods* **17**, 184-192 (2020).

15. G. Zhou *et al.*, Uni-mol: A universal 3d molecular representation learning framework. (2023).

16. S. Li *et al.*, PocketAnchor: Learning structure-based pocket representations for protein-ligand interaction prediction. *Cell Systems* **14**, 692-705. e696 (2023).

17. Z. Luo, W. Wu, Q. Sun, J. Wang, Accurate and transferable drug–target interaction prediction with DrugLAMP. *Bioinformatics* **40**, btae693 (2024).

18. L. Zhao, H. Wang, S. Shi, PocketDTA: an advanced multimodal architecture for enhanced prediction of drug– target affinity from 3D structural data of target binding pockets. *Bioinformatics* **40**, btae594 (2024).

19. T. Chen, S. Kornblith, M. Norouzi, G. Hinton. 2020. A simple framework for contrastive learning of visual representations. International conference on machine learning, Vienna, Austria.

20. A. Kahraman, R. J. Morris, R. A. Laskowski, J. M. Thornton, Shape variation in protein binding pockets and their ligands. *Journal of molecular biology* **368**, 283-301 (2007).

21. J. Skolnick, M. Gao, Interplay of physics and evolution in the likely origin of protein biochemical function. *Proc Natl Acad Sci U S A* **110**, 9344-9349 (2013).

22. C. Zhang, X. Zhang, P. L. Freddolino, Y. Zhang, BioLiP2: an updated structure database for biologically relevant ligand–protein interactions. *Nucleic Acids Research* **52**, D404-D412 (2024).

23. M. L. Hekkelman, I. de Vries, R. P. Joosten, A. Perrakis, AlphaFill: enriching AlphaFold models with ligands and cofactors. *Nature Methods* **20**, 205-213 (2023).

24. V. Le Guilloux, P. Schmidtke, P. Tuffery, Fpocket: an open source platform for ligand pocket detection. *BMC bioinformatics* **10**, 1-11 (2009).

25. H. C. Jubb *et al.*, Arpeggio: a web server for calculating and visualising interatomic interactions in protein structures. *Journal of molecular biology* **429**, 365-371 (2017).

26. S. Vilar, G. Cozza, S. Moro, Medicinal chemistry and the molecular operating environment (MOE): application of QSAR and molecular docking to drug discovery. *Current topics in medicinal chemistry* **8**, 1555-1572 (2008).

27. L. Van der Maaten, G. Hinton, Visualizing data using t-SNE. *Journal of machine learning research* **9** (2008).

28. M. Varadi *et al.*, AlphaFold Protein Structure Database in 2024: providing structure coverage for over 214 million protein sequences. *Nucleic Acids Res* **52**, D368-D375 (2024).

29. Y. Zhang, J. Skolnick, TM-align: a protein structure alignment algorithm based on the TM-score. *Nucleic acids research* **33**, 2302-2309 (2005).

30. J. Hu, Y. Zhang. PPS-align of the webpage. https://zhanglab.dcmb.med.umich.edu/PPS-align/. 2023.

31. W. Zhang, J. Huang, EViS: An Enhanced Virtual Screening Approach Based on Pocket–Ligand Similarity. *Journal of Chemical Information and Modeling* **62**, 498-510 (2022).

32. R. Zhan, W. Zhang, J. Huang, Scrutinization on Docking Against Individually Generated Target Pockets for Each Ligand. *bioRxiv* https://doi.org/10.1101/2025.01.01.630989 (2025).

33. T. Nishimura, K. Tsuboyama, Y. Nakagaki, E. Yamamoto, N. Mizushima, Rational engineering of lipid-binding probes via high-throughput protein-lipid interaction screening. *bioRxiv* https://doi.org/10.1101/2025.01.05.627504 (2025).

34. A. Daina, V. Zoete, Testing the predictive power of reverse screening to infer drug targets, with the help of machine learning. *Communications Chemistry* **7**, 105 (2024).

35. W. Zhang, K. Zhang, J. Huang, A Simple Way to Incorporate Target Structural Information in Molecular Generative Models. *Journal of Chemical Information and Modeling* **63**, 3719-3730 (2023).

36. J. L. Watson *et al.*, De novo design of protein structure and function with RFdiffusion. *Nature* **620**, 1089-1100 (2023).

37. J. Abramson *et al.*, Addendum: Accurate structure prediction of biomolecular interactions with AlphaFold 3. *Nature* **636**, E4 (2024).

38. G. Chen *et al.*, Rapid clearance of achiral small-molecule drugs using de novo-designed proteins and their cyclic and mirror-image variants. *Nat Biomed Eng* 10.1038/s41551-025-01404-w (2025).

39. N. F. Polizzi, W. F. DeGrado, A defined structural unit enables de novo design of small-molecule–binding proteins. *Science* **369**, 1227-1233 (2020).

40. A. P. Bento *et al.*, An open source chemical structure curation pipeline using RDKit. *J Cheminform* **12**, 51 (2020).

41. A. Subramanian *et al.*, Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proceedings of the National Academy of Sciences* **102**, 15545-15550 (2005).

Figures and Tables

Figure 1. Pocket size distribution and amino acid frequency analysis. A. Comparison of the number of pocket residues across four datasets: DEL, FAD-AD, BioLiP2, and AlphaFill. **B.** Relative frequency of the 20 amino acids in the DEL, BioLiP2, AlphaFill, and FAD-AD datasets, normalized by their corresponding frequencies in PDB.

Figure 2. Physicochemical properties of pockets and ligand-pocket interaction analysis for DEL, FDA-AD, and BioLiP2 Datasets. (A-F) The panels display the physicochemical properties of pockets computed using Fpocket, including volume, number of alpha spheres, the density of alpha sphere, the proportion of apolar alpha spheres, mean local hydrophobic density, and the proportion of polar atoms. **(a-c)** The panels illustrate the ligand-pocket interaction characteristics, focusing on hydrophobic interactions, hydrogen bonds, and polar interactions.

Figure 3. The ErePOC pipeline. A. During training, pocket residues are extracted by identifying the residues surrounding the ligand within a specific distance cutoff in the protein-ligand complex structure. **B.** The entire protein sequence is embedded using ESM-2, producing a 1280-dimensional vector for each residue. The pocket residues are then selected, and their average vector is used as the pocket's ESM-2 embedding feature. The ligand's 2048-dimensional fingerprint is computed using RDKit. **C.** represents the distribution of ligand similarity, while denotes the distribution of pocket similarity, derived from vectors learned through contrastive learning. The KL divergence is used as the loss function to align with . **D.** A 256-dimensional vector from the final latent space of the contrastive learning model is used as the ErePOC representation. The ErePOC representation model enables three important downstream applications: functional binding evaluation through cosine similarity, binding type categorization, and drug target identification.

Figure 4. t-SNE visualization of ErePOC and ESM-2 representations for BioLiP2 dataset. A-B. Visualization of the 7 types of ligand-binding pocket landscapes using ESM-2 (A) and ErePOC (B) representations, respectively. **C.** Pocket landscape using ErePOC representations. **D.** Comparison of pocket landscapes for the FDA-AD and DEL datasets against BioLiP2 using ErePOC representations.

Figure 5. Predicting human protein targets suitable for DEL screening. A. Screening pipeline: A total of 23,391 human proteins predicted by Alphafold were analyzed. Fpocket identified 182,424 pockets, which were represented using ErePOC embeddings. The cosine similarity between each DEL pocket and the human pockets was calculated, with the highest similarity score used as the final score. Human pockets with a cosine similarity > 0.8 to DEL pockets were considered suitable for DEL screening. Enrichment scores for each unique protein were determined using a hypergeometric test. **B.** Proportion of human proteins predicted to have pockets suitable for DEL screening. **C.** Distribution of enrichment scores for the predicted human proteins with p-value < 0.05.

Figure 6. Comparative analysis of global structures and local pocket structures across the enriched in DEL targets and human proteins. Subfigures A-H illustrate comparisons for each protein class. "CS" represents cosine similarity calculated using ErePOC embeddings, "TM" indicates the TM score obtained through TM-align for whole protein 3D structural comparison, and "PS" denotes pocket structure similarity assessed via PPS-align. All pockets are visualized

as cartoon and surface representation by Pymol. DEL pockets comprise residues within 5Å of bound ligands, while human protein pockets were predicted using Fpocket.