Flight trajectory modeling reveals species-specific obstacle avoidance policies in echolocating bats

Yu Teshima[1,2,✉], Shoko Genda[3], Yota Aoki[3], Masahiro Fujisawa[4,5], Shizuko Hiryu[3], and Keisuke Fujii[5,6]

[1]Project Team for System Development of Marine Environmental Impact Assessment / SIP Ocean Program, Japan Agency for Marine-Earth Science and Technology (JAMSTEC), Yokosuka 237-0061, Japan
[2]Underwater Biological Sound Analysis Unit / General Project Team for K-program, Japan Agency for Marine-Earth Science and Technology (JAMSTEC), Yokosuka 237-0061, Japan
[3]Faculty of Life and Medical Sciences, Doshisha University, Kyoto 610-0321, Japan
[4]Graduate School of Information Science and Technology, The University of Osaka, Osaka 565-0871, Japan
[5]RIKEN Center for Advanced Intelligence Project, Tokyo 103-0027, Japan
[6]Graduate School of Informatics, Nagoya University, Nagoya 464-0000, Japan

Echolocating bats routinely navigate complex wild environments with remarkable agility, yet it remains unclear whether their flight trajectories reflect reproducible internal control strategies or are merely the result of improvised reactive behavior. To address this question, we recorded flight paths and pulse emissions of *Rhinolophus nippon* and *Miniopterus fuliginosus* as they navigated seven obstacle-rich arenas in complete darkness. Using a machine learning model—a variational recurrent neural network (VRNN)—we show that bat flight is governed by a consistent internal policy. Trained on only part of each trajectory, our model accurately predicted future flight paths across arenas and individuals, preserving key features such as turning direction, obstacle-avoidance arcs, and velocity profiles. The model's ability to faithfully reproduce species-specific strategies despite differences in sonar and flight morphology supports the existence of structured internal control in bat navigation. Our approach reveals that bat flight, while appearing improvisational, is in fact guided by internal policies that can be directly inferred from trajectory data, without relying on hand-crafted assumptions. Furthermore, the data-driven model developed here enables a priori testing of flight-path reorganization by virtually imposing environmental changes and analysing the resulting predicted trajectories, providing a powerful tool for biomimetic robotic design and for forecasting ecological responses to landscape transformation.

Navigation | Sensing | Modeling | Data-Driven
Correspondence: *teshimay@jamstec.go.jp*

Introduction

The sophisticated behavioral strategies exhibited by animals provide crucial insights into how different species adapt to their environments and ensure survival. Among these, echolocation in bats is widely recognized as a highly advanced sensorimotor integration strategy (1, 2). Echolocating bats emit pulses from their mouths or nostrils and analyze the returning echoes to perceive spatiotemporal structures in their surroundings. Despite the inherent physical constraints—including relatively low pulse-emission rate (3) and narrow beam directivity (4–7)—echolocating bats are capable of navigating complex environments with remarkable precision and flexibility (8–10). A deeper understanding of this capability not only holds ecological significance in elucidating the intellectual basis of bats but also offers valuable inspiration for engineering applications that aim to replicate such sensorimotor integration, including recent advances in deep reinforcement learning (11) and bio-inspired robotics (12–15).

Numerous studies have explored the mechanisms underlying echolocation-based navigation in bats. In particular, it has been hypothesized that flight paths shaped by active acoustic sensing are governed by specific internal policies (16), and many modeling efforts have aimed to formalize such strategies. Flight control for foraging (17–20), continuous prey pursuit (21), obstacle avoidance (22, 23), and light-dependent routing (24) have all been represented through analytical models, often in the context of bio-inspired robotics. Most of these approaches, however, rely on hand-crafted heuristics grounded in human intuition, which may obscure the flexibility, context sensitivity, and inter-individual variability characteristic of real bat behavior. Thus, whether bats indeed rely on reproducible internal control strategies, rather than improvisational reflexes, remains a fundamental open question.

To address this question, we examine the hypothesis that bat flight behavior follows predictable patterns indicative of underlying flight policies. If such patterns can be identified directly from behavioral data, it would suggest that bat navigation is organized around consistent sensorimotor strategies. To investigate this, we adopt a data-driven approach that extracts patterns from behavioral data and builds predictive models of flight using machine learning. We construct a set of obstacle-rich environments and record the flight trajectories and pulse emissions of two bat species, *Rhinolophus nippon* and *Miniopterus fuliginosus*, which differ markedly in both echolocation mode and flight dynamics. The collected data exhibit temporal structure, with flight trajectories and echolocation behavior varying dynamically in response to the bat's state at each time step. These dynamics are captured using a variational recurrent neural network (VRNN) (25), a latent-variable time-series model previously shown to perform well in predicting structured movement (26–28). If the VRNN can accurately predict future trajectories from partial

Fig. 1. (A) Top view of the measurement system for flight trajectories and pulse emission timing of echolocation bats, in a 4.5 (x) m x 4.5 (y) m x 2.5 (z) m space separated from the observation room by a net. An obstacle space was constructed by hanging a 3.0 cm diameter chain as an obstacle from the ceiling. There were seven different obstacle spaces (Env 1 - 7). The bats started their flight from each of the four corners, and their flight trajectories were measured with infrared reflective markers attached to the bats' backs, with motion capture located on the ceiling of the observation room, and pulse emission timing was measured with four microphones placed in the room. (B) Flight trajectories of a single individual of *R. nippon* and *M. fuliginosus*, measured over 12 s in each obstacle space; flight trajectories of both *R. nippon* and *M. fuliginosus* tended to converge to a certain trajectory over time, but the trajectory of *M. fuliginosus* were simpler than those of *R. nippon*. (C) Top view of the flight paths of *R. nippon* and *M. fuliginosus* over 4.0 s, and the locations of the emitted pulses (circular plots). (D) Histogram of inter-pulse interval (IPI) for *R. nippon* (n=22295) and *M. fuliginosus* (n=30367) for all trials; *M. fuliginosus* usually emits only a single pulse and therefore has a single peak in the histogram *R. nippon* emits double or triple pulses in addition to single pulses, so three peaks appear. The two species therefore differ not only in their flight tendencies but also in the frequency of information updates on the obstacle environment. (E) Histogram of velocity for *R. nippon* (n=259822) and *M. fuliginosus* (n=273682) for all trials.

observations, this would provide quantitative support for the presence of internally structured, policy-like control in bat flight. We thus evaluate model accuracy by comparing predictions to actual trajectories, and interpret prediction errors as an indirect measure of how well internal control structure explains the observed behavior.

Results

Measurement set-up and behavioral overview. We measured the flight trajectories and pulse emission positions of two bat species—*Rhinolophus nippon* (*R. nippon*) and *Miniopterus fuliginosus* (*M. fuliginosus*)—in seven distinct obstacle environments (Env.1–7). These environments were constructed within an observation chamber equipped with 16 motion-capture cameras and 4 microphones, with chains suspended to form the obstacles (Fig. 1A). We recorded data from five individuals of *R. nippon* and four individuals of *M. fuliginosus*. Both species demonstrated skillful flight through the cluttered space without collisions (Fig. 1B).

To assess the frequency of spatial information acquisition, we calculated the inter-pulse interval (IPI) of echolocation. The average IPI was $1.1 \times 10^2 \pm 1.2 \times 10^2$ ms for *R. nippon* and

90 ± 90 ms for *M. fuliginosus*. Notably, in addition to single pulses, *R. nippon* frequently emitted double or triple pulses (Fig. 1C, D), indicating a distinct spatial sensing pattern compared to *M. fuliginosus*. In terms of flight speed, *R. nippon* flew at an average of 2.6 ± 0.72 m/s, whereas *M. fuliginosus* exhibited a slightly higher average speed of 3.0 ± 0.64 m/s (Fig. 1E, Table 1), often displaying relatively circular flight trajectories.

VRNN trajectory prediction. The recorded flight data were segmented into episodes of 8.0 seconds. The first 4.0 seconds of each episode were used as input to allow the model to perceive environmental information and update its internal state, while the subsequent 4.0 seconds were used for predicting flight velocities. The predicted velocities were integrated to obtain position coordinates, which were then compared to the actual measurements to evaluate prediction accuracy. Model performance was assessed using the L_2-norm-based positional error, defined as the mean Euclidean distance between predicted and observed positions.

Predicted trajectories (red curves) aligned closely with the empirical flight paths (gray dashed lines) in nearly every test arena (Fig. 2, See Appendix, Fig. S1-2). The model faithfully

Fig. 2. Top view of the 4.0 s measured flight trajectories (gray dotted lines) and sequentially predicted flight trajectories (mean: solid red lines and 2 times the standard deviation: blue) by VRNN for *R. nippon* and *M. fuliginosus* under four different obstacle environments (Env1 - 7). The input data to the model is 8.0 s, with the first 4.0 s being the burn-in period (29).

reconstructed the intricate maneuvers imposed by obstacle geometry: in *R. nippon*, arenas Env2 and Env5, and in *M. fuliginosus*, arenas Env1 and Env4, it reproduced the overall path shape, turning sense, and obstacle-avoidance arcs. Minor, localized deviations appeared only in the most cluttered setting (Env6), yet the probabilistic envelopes generated by the VRNN still encompassed the observed tracks, leaving the global trajectory architecture virtually indistinguishable from the bats' actual flights.

The average positional and velocity errors were 0.34 ± 0.27 m and 0.88 ± 0.53 m/s for *R. nippon*, and 0.40 ± 0.23 m and 0.97 ± 0.52 m/s for *M. fuliginosus*, respectively (Table 1). For both species, the model reproduced the general scale of flight speed accurately (actual vs. predicted: *R. nippon*: 2.6 m/s vs. 2.4 m/s; *M. fuliginosus*: 3.0 m/s vs. 2.6 m/s), with predicted values remaining close to the ground truth. In terms of environment-specific performance, *R. nippon* showed the smallest positional error in Env1 and Env3 (both 0.29 m), likely due to the relatively regular flight paths observed in these settings (Fig. 3). In contrast, errors were higher in Env7 (0.49 m) and Env5 (0.43 m), possibly due to the increased complexity and localized fluctuations of flight trajec-

tories. For *M. fuliginosus*, good accuracy was achieved in Env6 (0.30 m) and Env1 (0.34 m), whereas the largest positional error occurred in Env4 (0.54 m), where predicted velocities also deviated substantially from the actual values (predicted: 3.1 m/s; actual: 3.7 m/s).

Discussion

We investigated whether echolocating bats follow internally consistent flight policies by training the VRNN on flight trajectories recorded under diverse environmental conditions and environmental information calculated at pulse emission times. The model successfully reproduced species-specific flight behaviors—including turning direction, obstacle-avoidance arcs, and velocity profiles—for two bat species with distinct echolocation strategies. These results suggest that bat flight is not governed by random reactive control but instead by reproducible patterns, pointing to the presence of shared internal strategies across individuals and environments. While previous studies have inferred latent structure from recursive trajectories or implicated spatial memory cells such as place cells (30, 31), our data-driven

Fig. 3. Measurement velocity (gray dots) and predicted velocity (red dots) of *R. nippon* and *M. fuliginosus* in each obstacle environment (Env1-Env7) and violin plots for each.
Table 1. The L_2 predictions errors for the position and velocity of the *R. nippon* and *M. fuliginosus* using VRNN, and the predicted and measured velocities in each obstacle environment.

| | *R. nippon* | | | | *M. fuliginosus* | | | |
	Position error [m]	Velocity error [m/s]	Predicted velocity [m/s]	Measured velocity [m/s]	Position error [m]	Velocity error [m/s]	Predicted velocity [m/s]	Measured velocity [m/s]
All	0.34 ± 0.27	0.88 ± 0.53	2.4 ± 0.97	2.6 ± 0.76	0.40 ± 0.23	0.97 ± 0.52	2.6 ± 0.91	3.0 ± 0.61
Env1	0.29 ± 0.16	0.85 ± 0.47	2.4 ± 0.91	2.6 ± 0.59	0.34 ± 0.18	0.89 ± 0.46	2.4 ± 0.73	2.7 ± 0.25
Env2	0.39 ± 0.40	0.89 ± 0.63	2.5 ± 0.97	2.7 ± 0.88	0.44 ± 0.26	1.0 ± 0.56	2.8 ± 0.98	3.3 ± 0.70
Env3	0.29 ± 0.19	0.91 ± 0.51	2.6 ± 1.0	2.8 ± 0.73	0.42 ± 0.23	0.97 ± 0.51	2.7 ± 0.89	3.1 ± 0.54
Env4	0.35 ± 0.18	0.82 ± 0.46	2.0 ± 0.91	2.1 ± 0.61	0.54 ± 0.29	1.2 ± 0.62	3.1 ± 1.1	3.7 ± 0.86
Env5	0.43 ± 0.24	0.92 ± 0.52	2.5 ± 0.96	2.7 ± 0.77	0.45 ± 0.20	1.2 ± 0.60	3.2 ± 0.97	3.8 ± 0.27
Env6	0.38 ± 0.22	0.84 ± 0.43	2.4 ± 0.85	2.5 ± 0.52	0.30 ± 0.14	0.80 ± 0.45	2.3 ± 0.87	2.5 ± 0.60
Env7	0.49 ± 0.35	0.86 ± 0.47	2.1 ± 1.1	2.3 ± 0.92	0.34 ± 0.18	0.84 ± 0.45	2.4 ± 0.86	2.6 ± 0.51

approach directly extracted behavioral regularities from the trajectory data itself. Using machine learning as a pattern-recognition tool, we showed that seemingly improvisational flight paths can be predicted based on an underlying, consistent control policy.

The high-precision VRNN developed in this study not only corroborates the presence of internally consistent flight policies but also quantitatively predicts how bat trajectories reorganize under novel environmental conditions, including artificially designed scenarios. When trained on flight data from randomly arranged obstacle arenas (ENV 1–3) and tested on regularly arrayed arenas (ENV 4–7), the model maintained substantial predictive accuracy. The mean positional and velocity errors were 0.43 ± 0.28 m and 0.94 ± 0.57 m/s for *R. nippon*, and 0.58 ± 0.35 m and 1.1 ± 0.64 m/s for *M. fuliginosus*, respectively (See Appendix, Fig. S3–S4). This versa-

tility distinguishes our data-driven framework from heuristic rule-based simulators. It can extrapolate how bats actually adjust their flight under unfamiliar conditions, offering new potential for biomimetic applications that exploit their adaptive control strategies. Quantifying the ecological impacts of wind-power expansion and artificial lighting on bat populations has become a pressing research priority (32, 33). Our framework, by learning from current data and predicting flight paths under future landscape changes, offers an evidence-based tool for evaluating the ecological consequences of human development. Such predictions can inform mitigation measures and benefit not only bats but also other species affected by habitat transformation.

A key strength of the VRNN framework is its ability to produce approximate predictive distributions over future velocity vectors, allowing us to quantify uncertainty through

Fig. 4. (A) Measurement system for flight trajectories and pulse timing of echolocation bats. (B) Top view of seven types of obstacle space (Envs 1 - 7).

ing flight behavior.

Conclusion

Our findings demonstrate that the seemingly improvisational flights of *R. nippon* and *M. fuliginosus* are orchestrated by stable internal control policies. The VRNN, trained on only the first half of each trajectory, reproduced the remainder with sub-meter accuracy across seven cluttered arenas. The model also separated aleatoric and epistemic uncertainty, revealing where predictions remain robust and where data gaps persist. This data-driven framework not only verifies the existence of reproducible strategies in echolocating bats but also provides a practical tool for forecasting behavioral responses to novel ecological threats, such as expanding wind-turbine arrays and increasing artificial lighting. Looking ahead, coupling learned control policies with models of biosonar reception represents a promising path toward interpretable frameworks that bridge neural implementation, behavioral flexibility, and ecological resilience in sensory-guided navigation.

Materials and Methods

Behavioral Experiments.

Study Species. Two species of adult bats were included in this experiment. One is *Miniopterus fuliginosus* (*M. fuliginosus*) (one male and three females) and the other is *Rhinolophus nippon* (*R. nippon*) (five males). *M. fuliginosus* emits frequency-modulated (FM) pulses, and *R. nippon* emits a combination of constant-frequency (CF) pulses with FM pulses before and after the CF pulse. The flight characteristics of bats can be classified according to wing loading and aspect ratio. Wing loading is weight divided by wing area; the greater the weight, the faster the bat can fly. *M. fuliginosus* has high wing loading and aspect ratio, making it good for long-range fast flights, but not so good for sharp turns. *R. nippon* has low wing loading and aspect ratio, allowing it to change direction with a small turning radius and fly at low speeds. In a cave in Sabae City, Fukui Prefecture, Japan, three *M. fuliginosus* were captured on September 22, 2021, and one on September 14, 2020. One *R. nippon* was captured in the same cave on May 10, 2022, and four on May 16, 2023. All bats were housed in a dedicated colony room (4 m (L) x 6 m (W) x 2 m (H)) at Doshisha University, Kyoto. The colony room temperature was maintained at approximately 21° C and the humidity at 80% or higher. The bats could fly freely inside the colony room, consuming mealworms and water without restriction. The lighting in the room was also controlled to provide a 12 hour light / dark cycle. All necessary permits to capture and house the bats were obtained and the experiment was properly conducted under Japanese animal experimentation laws. Prior approval was obtained from the Animal Experiment Committee of Doshisha University.

Experimental Setup and Procedure. Behavioral experiments were conducted in seven different spaces with several obstacles (0.03 m diameter, plastic chains) placed in different positions in the observation room (4.5 m (L) x 4.5 m (W) x

sampling. When the training data provides sufficient constraints, the predictive distribution becomes sharp, reflecting low aleatoric uncertainty. By contrast, when the model encounters conditions outside its training distribution or faces latent influences not captured in the input data, the distribution becomes broader—an indication of epistemic uncertainty. This distinction enables us to assess the reliability of individual predictions and to identify environments or species where the model's confidence breaks down, highlighting gaps in data coverage or representational capacity.

In addition, combining our prediction model with a forward model of the bat's auditory system (34–36) could simulate how acoustic inputs guide three-dimensional trajectories. Such a hybrid approach would not only deepen our understanding of internal flight policies but also represent a broader step toward mechanistic explanations of sensory-guided navigation in echolocating animals. Exploring this direction further constitutes an important avenue for future research.

While our model supports the existence of structured flight policies, it does not reveal what those policies actually entail. Deep learning models like the VRNN are powerful for prediction but often lack interpretability. At present, it remains difficult to determine which features in the input data most influence the model's output, or how they contribute to the inferred control strategies. This limitation underscores a broader challenge in linking observed behavior to internal computation and points to the need for more interpretable modeling approaches. A promising way to tackle this challenge is to incorporate interpretable statistical frameworks that emphasize explanatory insight. Given that our study has established the existence of bat flight policies, hierarchical Bayesian models that capture species- and environment-level variation, or models that incorporate morphological traits such as body size, can simultaneously furnish interpretable structure and principled uncertainty quantification in model-

2.5 m (H)) (Fig. 4A). The obstacles in Envs. 1, 2, and 3 were randomly placed, both in position and in number. In contrast, Envs 4, 5, 6, and 7 have regularly arranged obstacles (Fig. 4B). Bats started their flight at four locations at a height of 1.5 m in the four corners of the space. In each obstacle environment, bats flew four times, one trial from each of the four flight start positions. Bat flights were tracked using a 16-camera motion-capture system (Naturalpoint, Inc. DBA OptiTrack., Motive Tracker 3.0.1, USA) until the bats perched on a wall or net and stopped flying, and 3D flight trajectories were recorded at 100 frames / s. Flights in which the bat took off and landed within eight seconds were excluded from analysis. The motion capture camera was placed at a height of 2.4 m. For tracking, a 7.8 mm diameter reflector was mounted on the bat's back. To eliminate as much as possible the influence of the experimenter on the release of bats from the starting point, flights immediately after release were excluded. Four microphones (Knowles, Fg-23329-D65) were placed at a height of 1.3 m around the observation space and recorded bat pulses emitted in flight at a sampling frequency of 500 kHz (National Instruments, PXIe-1073).

Video and Audio Analysis. The bat flight trajectories measured by the motion capture system were smoothed and saved to CSV files using the smoothing function in the Motive Tracker application. Pulse emission times were calculated in MATLAB by applying a band-pass filter (65–70 kHz for *R. nippon*; 30–85 kHz for *M. fuliginosus*), converting the filtered signal to a spectrogram via fast Fourier transform (FFT), and locating the peak sound-pressure of each pulse. The FFT window length was 16384 points (frequency resolution: 30.5 Hz), and the shift length was 8192 points (time resolution: 16.4 ms). The time was down-sampled to fs = 100 Hz to synchronize with the flight trajectory and then saved to CSV files.

Modeling flight policy by Neural Networks.

Dataset. The dataset for the obstacle avoidance model was created from flight trajectories obtained in behavioral experiments. The *R. nippon* dataset consisted of 214 training data episodes (validation data: 20 episodes) and 56 episodes of test data, while the *M. fuliginosus* dataset consisted of 246 episodes of training data (validation data: 23 episodes) and 64 test data episodes (8.0 s / 1 episode). The dataset consists of the bat's "action" and the "pulse states" of the bat when the action is taken in the two dimensions of the x-y plane. The "action" consists of the position coordinates (x, y), the flight speeds $((V_x, V_y))$, the flight turn angles (θ), and the timing of the pulses (0 (not emit the pulse) or 1 (emit the pulse)). The "pulse states" is the environmental information at the time the bat emitted the pulse. The reason why position coordinates are used as input here is that bats have place cells (37) and grid cells (38). To obtain the "pulse state", we first placed a total of 251-line segments, 5.0 m long, at 0.32° intervals over a directional range of approximately ± 40° of the *M. fuliginosus* pulse (39) in the direction of flight from the location where the bat emitted the pulse (See Appendix, Fig.

S3(A)). This interval width was set to allow the detection of obstacles (0.03 m in diameter, plastic chains) located 5.0 m away from the bat (40). The distance between the 251 line segments and the obstacle or wall was a normalized distance of 0.0 - 1.0, with 5.0 m as 1.0. Significant figures were set at three decimal places. For line segments that did not intersect an obstacle, the distance was set to 2.0. Since the directivity of *R. nippon*'s pulse is approximately ± 20° (6), the values for line segments in the + 20° to + 40° and - 20° to - 40° ranges were always set to 2.0 (See Appendix, Fig. S3(B)). Finally, the data set consisted of 800 frames per episode and 8.0 seconds per episode. For the training data to build the flight policy model under obstacle environments, 80% of the data measured in seven obstacle environments (Env 1-7) were randomly selected, and 10% of them were used as validation data. The remaining 20% was used as test data.

Structure of Neural Networks. The VRNN architecture was based on previous studies (28). The input comprised 257 dimensions ("action" + "pulse states"), with the deterministic function of the RNN, estimated using the Gated Recurrent Unit (GRU) (41). The hidden state dimension was set to 100 dimensions, and the hidden layer was configured with 64 dimensions. The model parameters were initialized using a normal distribution using the Xavier method (42). The termination criterion for model training was based on two conditions: first, when the loss observed in the validation dataset decreased to less than 1.0×10^{-4} compared to the loss update ratio from the preceding epoch, and second, when the training process extended to 500 epochs. However, all training was completed before the epoch reached 500.

Data Availability. All data supporting the conclusions of this study were deposited in an open-access repository and are accessible under the DOI doi:10.6084/m9.figshare.29209493. The analysis scripts and custom code are available on GitHub (https://github.com/tsmyu/PO-MC-DHVRNN (tag: v1.1)) and have been archived on Zenodo with versioned DOI doi:10.5281/zenodo.15638675. Together, these resources contain every file and detailed instruction required to reproduce our results. Further information is available from the corresponding author upon reasonable request.

ACKNOWLEDGEMENTS
This work was supported by JSPS KAKENHI Grant Numbers 21H05300, 21H05295, 22H01503, 25H00745, 25K21286 and JST, ACT-X Grant Number JPM-JAX23CI.

Reference

1. Donald R Griffin. *Listening in the dark: The acoustic orientation of bats and men*, volume 413. Yale University Press, New Haven, CT, 1958.

2. James A Simmons. Theories about target ranging in bat sonar. *Acoust. Today*, 13:43–51, 2017.

3. Angeles Salles, Clarice Anna Diebold, and Cynthia F Moss. Echolocating bats accumulate information from acoustic snapshots to predict auditory object motion. *Proc. Natl. Acad. Sci. U. S. A.*, 117(46):29229–29238, 17 November 2020. doi: 10.1073/pnas.2011719117.

4. H-U Schnitzler and A D Grinnell. Directional sensitivity of echolocation in the horseshoe bat, rhinolophus ferrumequinum. *J. Comp. Physiol. A Neuroethol. Sens. Neural Behav. Physiol.*, 116(1):51–61, 1977. doi: 10.1007/bf00605516.

5. Yossi Yovel, Ben Falk, Cynthia F Moss, and Nachum Ulanovsky. Optimal localization by pointing off axis. *Science*, 327(5966):701–704, 5 February 2010. doi: 10.1126/science.1183310.

6. Yasufumi Yamada, Shizuko Hiryu, and Yoshiaki Watanabe. Species-specific control of acoustic gaze by echolocating bats, rhinolophus ferrumequinum nippon and pipistrellus

abramus, during flight. *J. Comp. Physiol. A Neuroethol. Sens. Neural Behav. Physiol.*, 202 (11):791–801, November 2016. doi: 10.1007/s00359-016-1121-0.

7. Wu-Jung Lee, Benjamin Falk, Chen Chiu, Anand Krishnan, Jessica H Arbour, and Cynthia F Moss. Tongue-driven sonar beam steering by a lingual-echolocating fruit bat. *PLoS Biol.*, 15(12):e2003148, December 2017. doi: 10.1371/journal.pbio.2003148.

8. Cynthia F Moss and Annemarie Surlykke. Probing the natural scene by echolocation in bats. *Front. Behav. Neurosci.*, 4, 5 August 2010. doi: 10.3389/fnbeh.2010.00033.

9. A Surlykke and C F Moss. Echolocation behavior of big brown bats, eptesicus fuscus, in the field and the laboratory. *J. Acoust. Soc. Am.*, 108(5 Pt 1):2419–2429, November 2000. doi: 10.1121/1.1315295.

10. Kaushik Ghose and Cynthia F Moss. Steering by hearing: a bat's acoustic gaze is linked to its flight motor output by a delayed, adaptive linear law. *J. Neurosci.*, 26(6):1704–1710, 8 February 2006. doi: 10.1523/JNEUROSCI.4315-05.2006.

11. Adithya Venkatesh Mohan and Dieter Vanderelst. Training a simulated bat: Modeling sonar-based obstacle avoidance using deep-reinforcement learning. In *2020 IEEE Symposium Series on Computational Intelligence (SSCI)*, pages 2241–2249, December 2020. doi: 10.1109/SSCI47803.2020.9308555.

12. Itamar Eliakim, Zahi Cohen, Gabor Kosa, and Yossi Yovel. A fully autonomous terrestrial bat-like acoustic robot. *PLoS Comput. Biol.*, 14(9):e1006406, September 2018. doi: 10.1371/journal.pcbi.1006406.

13. Yasufumi Yamada, Kentaro Ito, Takumi Tsuji, Kohei Otani, Ryo Kobayashi, Yoshiaki Watanabe, and Shizuko Hiryu. Ultrasound navigation based on minimally designed vehicle inspired by the bio-sonar strategy of bats. *Adv. Robot.*, 33(3-4):169–182, 16 February 2019. doi: 10.1080/01691864.2019.1573470.

14. Carl Bou Mansour, Elijah Koreman, Jan Steckel, Herbert Peremans, and Dieter Vanderelst. Avoidance of non-localizable obstacles in echolocating bats: A robotic model. *PLoS Comput. Biol.*, 15(12):e1007550, December 2019. doi: 10.1371/journal.pcbi.1007550.

15. Ralph Simon, Stefan Rupitsch, Markus Baumann, Huan Wu, Herbert Peremans, and Jan Steckel. Bioinspired sonar reflectors as guiding beacons for autonomous navigation. *Proc. Natl. Acad. Sci. U. S. A.*, 117(3):1367–1374, 21 January 2020. doi: 10.1073/pnas.1909890117.

16. Cynthia F Moss, Chen Chiu, and Annemarie Surlykke. Adaptive vocal behavior drives perception by echolocation in bats. *Curr. Opin. Neurobiol.*, 21(4):645–652, August 2011. doi: 10.1016/j.conb.2011.05.028.

17. R Kuc. Sensorimotor model of bat echolocation and prey capture. *J. Acoust. Soc. Am.*, 96 (4):1965–1978, October 1994. doi: 10.1121/1.410140.

18. Kaushik Ghose, Timothy K Horiuchi, P S Krishnaprasad, and Cynthia F Moss. Echolocating bats use a nearly time-optimal strategy to intercept prey. *PLoS Biol.*, 4(5):e108, May 2006. doi: 10.1371/journal.pbio.0040108.

19. Dieter Vanderelst and Herbert Peremans. Modeling bat prey capture in echolocating bats: The feasibility of reactive pursuit. *J. Theor. Biol.*, 456:305–314, 7 November 2018. doi: 10.1016/j.jtbi.2018.07.027.

20. Nozomi Nishiumi, Emyo Fujioka, and Shizuko Hiryu. Bats integrate multiple echolocation and flight tactics to track prey. *Curr. Biol.*, 0(0), 24 June 2024. doi: 10.1016/j.cub.2024.05.062.

21. Emyo Fujioka, Ikkyu Aihara, Miwa Sumiya, Kazuyuki Aihara, and Shizuko Hiryu. Echolocating bats use future-target information for optimal foraging. *Proc. Natl. Acad. Sci. U. S. A.*, 113(17):4848–4852, 26 April 2016. doi: 10.1073/pnas.1515091113.

22. Dieter Vanderelst, Marc W Holderied, and Herbert Peremans. Sensorimotor model of obstacle avoidance in echolocating bats. *PLoS Comput. Biol.*, 11(10):e1004484, October 2015. doi: 10.1371/journal.pcbi.1004484.

23. Dieter Vanderelst and Herbert Peremans. A computational model of mapping in echolocating bats. *Anim. Behav.*, 131:73–88, 1 September 2017. doi: 10.1016/j.anbehav.2017.06.009.

24. Nadav S Bar, Sigurd Skogestad, Jose M Marçal, Nachum Ulanovsky, and Yossi Yovel. A sensory-motor control model of animal flight explains why bats fly differently in light versus dark. *PLoS Biol.*, 13(1):e1002046, 28 January 2015. doi: 10.1371/journal.pbio.1002046.

25. Junyoung Chung, Kyle Kastner, Laurent Dinh, Kratarth Goel, Aaron Courville, and Yoshua Bengio. A recurrent latent variable model for sequential data. *arXiv [cs.LG]*, 7 June 2015.

26. Eric Zhan, Stephan Zheng, Yisong Yue, Long Sha, and Patrick Lucey. Generating multi-agent trajectories using programmatic weak supervision. *arXiv [cs.LG]*, 20 March 2018.

27. Raymond A Yeh, Alexander G Schwing, Jonathan Huang, and Kevin Murphy. Diverse generation for multi-agent sports games. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 4605–4614. IEEE, June 2019. doi: 10.1109/CVPR.2019.00474.

28. Keisuke Fujii, Naoya Takeishi, Yoshinobu Kawahara, and Kazuya Takeda. Decentralized policy learning with partial observation and mechanical constraints for multiperson modeling. *Neural Netw.*, 1 December 2023. doi: 10.1016/j.neunet.2023.11.068.

29. Steven Kapturowski, Georg Ostrovski, John Quan, R Munos, and Will Dabney. Recurrent experience replay in distributed reinforcement learning. *Int Conf Learn Represent*, 27 September 2018.

30. Jonathan R Barchi, Jeffrey M Knowles, and James A Simmons. Spatial memory and stereotypy of flight paths by big brown bats in cluttered surroundings. *J. Exp. Biol.*, 216(Pt 6): 1053–1063, 15 March 2013. doi: 10.1242/jeb.073197.

31. William A Liberti, 3rd, Tobias A Schmid, Angelo Forli, Madeleine Snyder, and Michael M Yartsev. A stable hippocampal code in freely flying bats. *Nature*, 30 March 2022. doi: 10.1038/s41586-022-04560-0.

32. W F Frick, E F Baerwald, J F Pollock, R M R Barclay, J A Szymanski, T J Weller, A L Russell, S C Loeb, R A Medellin, and L P McGuire. Fatalities at wind turbines may threaten population viability of a migratory bat. *Biol. Conserv.*, 209:172–177, 1 May 2017. doi: 10.1016/j.biocon.2017.02.023.

33. Alejandro Sánchez de Miguel, Jonathan Bennie, Emma Rosenfeld, Simon Dzurjak, and Kevin J Gaston. Environmental risks from artificial nighttime lighting widespread and increasing across europe. *Sci. Adv.*, 8(37):eabl6891, 16 September 2022. doi: 10.1126/sciadv.abl6891.

34. P A Saillant, J A Simmons, S P Dear, and T A McMullen. A computational model of echo processing and acoustic imaging in frequency-modulated echolocating bats: the spectrogram correlation and transformation receiver. *J. Acoust. Soc. Am.*, 94(5):2691–2712, November 1993. doi: 10.1121/1.407353.

35. Chen Ming, Stephanie Haro, Andrea Megela Simmons, and James A Simmons. A comprehensive computational model of animal biosonar signal processing. *PLoS Comput. Biol.*, 17 (2):e1008677, February 2021. doi: 10.1371/journal.pcbi.1008677.

36. Gunpil Hwang, Seohyeon Kim, and Hyeon-Min Bae. Bat-g net: Bat-inspired high-resolution 3D image reconstruction using ultrasonic echoes. *Adv. Neural Inf. Process. Syst.*, 32, 2019.

37. Michael M Yartsev and Nachum Ulanovsky. Representation of three-dimensional space in the hippocampus of flying bats. *Science*, 340(6130):367–372, 19 April 2013. doi: 10.1126/science.1235338.

38. Michael M Yartsev, Menno P Witter, and Nachum Ulanovsky. Grid cells without theta oscillations in the entorhinal cortex of bats. *Nature*, 479(7371):103–107, 2 November 2011. doi: 10.1038/nature10583.

39. Naotaro Hirade, Emyo Fujioka, Shizuko Hiryu, Hiroshi Riquimaroux, and Yoshiaki Watanabe. A study on environmental sensing by bat bio-sonar–relationships between sonar beam direction and flight direction during obstacle avoidance. *IEICE Technical Report; IEICE Tech. Rep.*, 109(425):19–24, 2010.

40. Emyo Fujioka, Shigeki Mantani, Shizuko Hiryu, Hiroshi Riquimaroux, and Yoshiaki Watanabe. Echolocation and flight strategy of japanese house bats during natural foraging, revealed by a microphone array system. *J. Acoust. Soc. Am.*, 129(2):1081–1088, 2011.

41. Kyunghyun Cho, Bart van Merrienboer, Caglar Gulcehre, Dzmitry Bahdanau, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. Learning phrase representations using RNN encoder-decoder for statistical machine translation. *arXiv [cs.CL]*, 3 June 2014.

42. Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In Yee Whye Teh and Mike Titterington, editors, *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, volume 9 of *Proceedings of Machine Learning Research*, pages 249–256, Chia Laguna Resort, Sardinia, Italy, 2010. PMLR.

Supplementary Note 1: Supplementary Information

Fig. S1. Top view of the measured flight path of *R. nippon* over 4.0 s (gray dotted line) alongside the trajectory predicted by the VRNN (training data: *R. nippon*) (red solid line). The input data to the model is 8.0 s, with the first 4.0 s being the burn-in period.

Fig. S2. Top view of the measured flight path of *M. fuliginosus* over 4.0 s (gray dotted line) alongside the trajectory predicted by the VRNN(training data: *M. fuliginosus*) (red solid line). The input data to the model is 8.0 s, with the first 4.0 s being the burn-in period.

Fig. S3. Top view of the measured flight path of *R. nippon* over 4.0 s (gray dotted line) alongside the trajectory predicted by the VRNN (red solid line). Data collected under environmental conditions ENV 1–3 were used for training, and those from ENV 4–7 for testing. The input data to the model is 8.0 s, with the first 4.0 s being the burn-in period.

Fig. S4. Top view of the measured flight path of *M. fuliginosus* over 4.0 s (gray dotted line) alongside the trajectory predicted by the VRNN (red solid line). Data collected under environmental conditions ENV 1–3 were used for training, and those from ENV 4–7 for testing. The input data to the model is 8.0 s, with the first 4.0 s being the burn-in period.

Fig. S5. The following example illustrates the "pulse states" of *R. nippon* (A) and *M. fuliginosus* (B). The directionality of *M. fuliginosus* is ±40°, whereas that of *R. nippon* is ±20°. Consequently, the outer 20° of the *R. nippon* "pulse states" is consistently obstacle-free.