NiCLIP: Neuroimaging contrastive language-image pretraining model for predicting text from brain activation images

Julio A. Peraza[1], James D. Kent[2], Thomas E. Nichols[3], Jean-Baptiste Poline[4], Alejandro de la Vega[2], Angela R. Laird[1]

[1] Department of Physics, Florida International University, Miami, FL, USA

[2] Department of Psychology, University of Texas at Austin, Austin, TX, USA

[3] Big Data Institute, Li Ka Shing Centre for Health Information and Discovery, Nuffield Department of Population Health, University of Oxford, Oxford, UK

[4] Department of Neurology and Neurosurgery, McGill University, Montreal, QC, Canada

Abstract

Predicting cognitive processes from brain activation maps has remained an open question within the neuroscience community for many years. Meta-analytic functional decoding methods aim to tackle this issue by providing a quantitative estimation of behavioral profiles associated with specific brain regions. Existing methods face intrinsic challenges in neuroimaging meta-analysis, particularly in consolidating textual information from publications, as they rely on limited metrics that do not capture the semantic context of the text. The combination of large language models (LLMs) with advanced deep contrastive learning models (e.g., CLIP) for aligning text with images has revolutionized neuroimaging meta-analysis, potentially offering solutions to functional decoding challenges. In this work, we present NiCLIP, a contrastive language-image pretrained model that predicts cognitive tasks, concepts, and domains from brain activation patterns. We leveraged over 23,000 neuroscientific articles to train a CLIP model for text-to-brain association. We demonstrated that fine-tuned LLMs (e.g., BrainGPT models) outperform their base LLM counterparts. Evaluation of NiCLIP predictions revealed that performance is optimized when using full-text articles instead of abstracts, as well as a curated cognitive ontology with precise task-concept-domain mappings. Our results indicated that NiCLIP accurately predicts cognitive tasks from group-level activation maps provided by the Human Connectome Project across multiple domains (e.g., emotion, language, motor) and precisely characterizes the functional roles of specific brain regions, including the amygdala, hippocampus, and temporoparietal junction. However, NiCLIP showed limitations with noisy subject-level activation maps. NiCLIP represents a significant advancement in quantitative functional decoding for neuroimaging, offering researchers a powerful tool for hypothesis generation and scientific discovery.

Keywords: fMRI, meta-analysis, large language model, CLIP, functional decoding, deep learning

Corresponding Author: Dr. Angela R. Laird, Professor of Physics, Florida International University, Miami, FL, USA | Email: alaird@fiu.edu

1. Introduction

A key open question in neuroscience is whether cognitive processes can be inferred from brain activation patterns— a problem known as reverse inference (Poldrack, 2006). Large-scale meta-analysis has facilitated reverse inference through meta-analytic functional decoding, a method that offers a quantitative estimation of behavioral profiles associated with brain regions (Amft et al., 2015; Bzdok et al., 2013b, 2013a; Cieslik et al., 2013; Laird et al., 2009; Nickl-Jockschat et al., 2015; Peraza et al., 2024; Poldrack, 2011; Rottschy et al., 2013; Smith et al., 2009). However, existing functional decoding methods are fundamentally limited by the challenge of how to model unstructured text from publications to capture discrete mental states that align with established theoretical frameworks.

The release of coordinate-based meta-analytic (CBMA) databases, such as BrainMap (Fox et al., 2005; Laird et al., 2011, 2009, 2005) and Neurosynth (Yarkoni et al., 2011), along with the Cognitive Atlas ontology (Poldrack et al., 2011), has provided us with robust data to facilitate quantitative meta-analytic functional decoding in neuroimaging. The implementation of meta-analytic functional decoding methods on popular websites (e.g., Neurosynth (Yarkoni et al., 2011) and NeuroVault (Gorgolewski et al., 2015)), as well as meta-analysis software (e.g., NiMARE (Salo et al., 2023)), has boosted their popularity within the neuroimaging community. However, current methods present several limitations. For instance, the most commonly used method, correlation-type decoders, are not based on a formal model, fail to identify latent structures associated with specific cognitive processes, and lack sensitivity to unseen brain patterns (Rubin et al., 2017). The Generalized Correspondence Latent Dirichlet Allocation (GC-LDA) approach (Rubin et al., 2016, 2017) addresses some of these limitations by learning joint probabilities from latent variables in the model, allowing for predictions on unseen brain patterns. Nevertheless, GC-LDA is significantly influenced by the data, context, and assumptions established before model training, such as spatial priors, the number of topics, and other model parameters. Additionally, GC-LDA operates entirely unsupervised, suggesting that the model is not optimized for classification or prediction accuracy. Thus, other models refined to enhance prediction parameters should outperform GC-LDA (Rubin et al., 2017).

In addition, the effectiveness of functional decoding is held back by its reliance on outdated Natural Language Processing (NLP) techniques. For instance, it is quite common to analyze the text of publications using term-frequency inverse document frequency (TF-IDF) (Aizawa, 2003), a classic metric that measures a word's importance based on its frequency. While TF-IDF has proven helpful in large-scale meta-analysis (Dockès et al., 2020; Rubin et al., 2016; Salo et al., 2023; Yarkoni et al., 2011), as a "bag of words" method, it provides only a sparse view of word representation, fails to capture semantics, and overlooks relationships between words within the same conceptual family. Additionally, its vocabulary is confined to words present in the neuroscience corpora, restricting the inclusion of external terms and, more importantly, preventing the use of richer representations such as phrases, sentences, and term definitions.

The emergence of large language models (LLMs) (Liu et al., 2023; Vaswani et al., 2017) has transformed the field of NLP and is now poised to revolutionize neuroimaging meta-analysis. By capturing deep

semantic relationships, LLMs overcome the limitations of traditional NLP metrics like TF-IDF, providing rich contextual embeddings that understand relationships between related concepts and capture the full meaning of phrases and definitions (Gunasekar et al., 2023; Srivastava et al., 2023). LLMs have been applied to neuroimaging meta-analysis to enhance text encoding and synthesize results from various articles (Ngo et al., 2021). In neuroscience, BrainGPT, an LLM fine-tuned on neuroscience literature, has demonstrated domain-specific advantages by outperforming experts in predicting neuroscience findings (Luo et al., 2024). Recently, NeuroConText (Meudec et al., 2024) introduced a CLIP-based (Radford et al., 2021) framework for text-to-brain association that significantly outperformed previous approaches (i.e., NeuroQuery (Dockès et al., 2020) and Text2Brain (Ngo et al., 2021)). By using a pretrained LLM transformer (e.g., Mistral-7B-v0.1) to encode text and brain parcellation for dimensionality reduction, NeuroConText demonstrated improved flexibility in handling longer texts and better text-brain associations. While NeuroConText enables forward inference (text-to-brain), existing approaches have three critical gaps: (1) they have not been validated for reverse inference (brain-to-text) for functional decoding, (2) they have not leveraged domain-specific LLMs like BrainGPT that could capture neuroscience-specific semantics more accurately, and (3) they operate in a purely data-driven manner without incorporating structured ontologies and the semantic richness of task definitions from vocabularies like the Cognitive Atlas. Addressing these gaps is essential for achieving precise, theory-driven predictions of cognitive processes from brain activation patterns.

In this work, we present the NiCLIP (Neuroimaging Contrastive Language-Image Pre-training) model, the first LLM-powered CLIP model designed specifically for predicting cognitive tasks, concepts, and domains from brain activation patterns. NiCLIP advances beyond existing methods by: (1) implementing meta-analytic functional decoding in a CLIP framework, (2) integrating the Cognitive Atlas ontology to enable predictions using custom vocabulary by projecting task names and their definitions into CLIP's latent space, and (3) leveraging domain-specific LLMs (e.g., BrainGPT) to enhance text representation. To evaluate NiCLIP, we leveraged 23,000 neuroscientific articles with full text and reported brain activation coordinates from PubMed Central. First, we evaluated the effect of using a fine-tuned LLM on the CLIP models by comparing the two currently available BrainGPT versions (i.e., BrainGPT-7B-v0.1 and BrainGPT-7B-v0.2) with their corresponding pre-trained base LLMs (i.e., Llama-2-7b-chat-hf and Mistral-7B-v0.1, respectively), using the abstracts and the full text of the neuroimaging articles. Comparisons were carried out using Recall@k and Mix&Match (Meudec et al., 2024). Second, we assessed the functional decoding performance to predict cognitive tasks and concepts from task-fMRI group-average maps derived from the Human Connectome Project (HCP) data release (Barch et al., 2013; Smith et al., 2013; Uğurbil et al., 2013; Van Essen et al., 2013, 2012), using a vocabulary from the Cognitive Atlas database (Poldrack et al., 2011). We examined the impact that the LLM, the model-trained section of the articles, and cognitive ontology had on the final prediction of the functional decoder. Third, NiCLIP was tested on six anatomical brain regions defined by meta-analytic-based parcellations. The baseline models for evaluation included the Neurosynth correlation decoder and the GC-LDA decoder. Finally, we examined the extent to which NiCLIP's capability in predicting subject-level activation maps.

2. Results

2.1. Overview

Fig. 1 provides an overview of our general framework to train the text-to-brain model (**Fig. 1A**) and perform functional decoding of a brain activation map (**Fig. 1B**). To train the CLIP model, we required text and image data. First, we searched the PubMed Central open-source collections for fMRI articles. Second, we extracted the text and activation coordinates from the downloaded articles using Pubget (Dockès et al., 2024). Third, we identified text and brain activation embeddings for each article, along with corresponding coordinates. For the text features, we used a pre-trained LLM. Meanwhile, the brain activation features were obtained by transforming the coordinates into a modeled activation map using MKDA (Wager et al., 2007) methods and reducing the image dimensionality with a continuous brain parcellation defined by the DiFuMo 512 regions atlas (Dadi et al., 2020). Finally, we entered the normalized text and brain embeddings into the CLIP model to learn a shared latent space for the text and image encoders. To make predictions based on brain activation, we needed a cognitive ontology that consisted of fMRI tasks with their respective definitions, along with concepts associated with the tasks and their corresponding high-level domains. We first obtained a joint embedding of the task name and definition using a pre-trained LLM. The input brain activation embedding was determined using the DiFuMo 512 atlas. Then, the cognitive ontology and input activation embeddings were passed through the text and image encoders from the pre-trained CLIP model. Next, we determined the cosine similarity between the text and image embeddings in the shared latent space. This similarity was used to calculate the posterior probability of a task given an activation, given the shared latent space.

Figure 1. Overview of the framework for training the text-to-brain model and decoding brain activation maps. **(A)** The text-to-brain CLIP model was trained using text and brain activation coordinates sourced from a collection of fMRI articles downloaded from PubMed Central. Pubget was employed to download and preprocess the articles in a standardized format. Text embeddings were determined using a pre-trained LLM. Image embeddings were obtained by first calculating an MKDA-modeled activation brain map, and second applying a continuous brain parcellation defined by the DiFuMo 512 atlas. **(B)** The brain decoding model relies on a cognitive ontology to predict text from input brain activation. The embeddings of task names along with their definitions were extracted using an LLM transformer, while image features were determined using the DiFuMo brain parcellation. The text and image embeddings were processed through the pre-trained text and image

encoders from CLIP, yielding new embeddings in a shared latent space. The posterior probability representing the predicted task from the input activation was calculated based on the similarity between the text and image embeddings in the shared latent space.

2.2. CLIP model evaluation for text-to-brain association

We assessed the CLIP model's ability to match text to brain images using Recall@k and Mix&Match (Meudec et al., 2024) (see Methods section for definitions). The dataset used consisted of 23,865 articles with at least one activation coordinate, a complete abstract, and full-text information. The different models were trained and evaluated using distinct data loaders for training, validation, and testing, implementing a 23-fold cross-validation on the test set and a 22-fold nested cross-validation on the evaluation set. The fold size for the testing and evaluation was 1,000 samples, resulting in approximately 21,865 articles available for training.

Table 1

Text-to-brain association performance comparison of LLMs across article sections

CLIP model setting		Metrics		
Section	LLM	Recall@10	Recall@100	Mix&Match
Body	BrainGPT-7B-v0.2	**33.56 ± 4.12**	**71.95 ± 4.18**	**90.04 ± 1.66**
	Mistral-7B-v0.1	33.36 ± 4.05	71.78 ± 4.22	89.97 ± 1.70
	BrainGPT-7B-v0.1	32.30 ± 4.16	70.66 ± 4.81	89.65 ± 1.83
	Llama-2-7b-chat-hf	32.50 ± 4.08	71.08 ± 4.81	89.72 ± 1.84
Abstract	BrainGPT-7B-v0.2	24.01 ± 1.84	61.98 ± 4.28	85.82 ± 1.84
	Mistral-7B-v0.1	23.36 ± 2.12	61.37 ± 4.27	85.57 ± 1.88
	BrainGPT-7B-v0.1	23.51 ± 1.98	61.94 ± 4.09	85.73 ± 1.79
	Llama-2-7b-chat-hf	22.46 ± 2.07	60.69 ± 4.13	85.32 ± 1.87

Note: Values represent mean ± standard deviation across cross-validation sets. The best-performing value for each metric is highlighted in bold font.

Four different large language models (i.e., BrainGPT-7B-v0.2, Mistral-7B-v0.1, BrainGPT-7B-v0.1, and Llama-2-7b-chat-hf) were evaluated for text features extraction across two document sections (i.e., abstract and body). Training the CLIP model with the body portion of the articles and embeddings extracted with BrainGPT-7B-v0.2 demonstrated the strongest performance across all metrics (Recall@10: 33.56±4.12, Recall@100: 71.95±4.18, Mix&Match: 90.04±1.66), closely followed by its foundational LLM, Mistral-7B-v0.1 (Recall@10: 33.36±4.05, Recall@100: 71.78±4.22, Mix&Match: 89.97±1.70). BrainGPT-7B-v0.1 and Llama-2-7b-chat-hf showed comparable but slightly lower performance, with Llama-2-7b-chat-hf marginally outperforming BrainGPT-7B-v0.1 on Recall@k and Mix&Match. When using only the abstract sections to train the CLIP model, all LLMs demonstrated lower performance than when training with the full body of the articles. BrainGPT-7B-v0.2 again achieved the highest scores (Recall@10: 24.01±1.84, Recall@100: 61.98±4.28, Mix&Match: 85.82±1.84), with BrainGPT-7B-v0.1 performing slightly better than Mistral and Llama models across all three metrics. Llama-2-7b-chat-hf consistently showed the lowest performance in the abstract section evaluation. These results indicate that BrainGPT-7B-v0.2 provided the most effective text-to-brain association among the tested LLMs,

and the association performance was generally stronger with the whole body of the articles compared to the abstracts (**Table 1**). The distributions of the evaluation metrics presented in **Table 1** are available in the supplementary information (**Fig. S1**).

2.3. NiCLIP model settings evaluation

Next, we used NiCLIP, a contrastive language-image pretraining model designed for predicting tasks, concepts, and domains from brain maps. Here, a "domain" refers to a high-level concept, as defined by the concept categories in Cognitive Atlas (https://www.cognitiveatlas.org/concepts/categories/all). NiCLIP relied on a cognitive ontology that comprises a collection of fMRI tasks with their definitions, along with the collection of concepts associated with the tasks and the major domains to which the concepts belong. The prediction of the task was based exclusively on the semantic content of the task name and its definition. In contrast, the predictions for concepts and domains were determined by the task-to-concept and concept-to-domain mappings established in the ontology.

We evaluated how different combinations of parameters influence the final prediction of NiCLIP (**Table 2**), across seven major domains of high interest in the neuroscience field, drawn from the HCP task fMRI dataset. These domains included tasks such as emotion, gambling, language, motor, relational, social, and working memory. We compared the results to two baseline decoding models (i.e., Neurosynth and GC-LDA decoder). Regarding the CLIP model settings, also presented in the first analysis in **Table 1**, we examined two sections of the articles (i.e., abstract and body) and four different pre-trained LLMs (i.e., BrainGPT-7B-v0.2, Mistral-7B-v0.1, BrainGPT-7B-v0.1, and Llama-2-7b-chat-hf). Next, for the vocabulary setting of the NiCLIP model, we utilized two different ontologies based on the Cognitive Atlas. Initially, we leveraged all tasks from the Cognitive Atlas database and their concept-to-task and concept-to-domain mappings. We also tested a reduced version of the Cognitive Atlas, which contained only the most popular fMRI tasks, with a more robust mapping from concept to task and the original mapping from concept to domain. Additionally, we employed two definitions for the embedding for NiCLIP, consisting of (1) embedding calculated using only the name of the task, and (2) embedding calculated using the name of the task along with its definition. The models with different parameter combinations were compared using Recall@4 for tasks and concepts, and Recall@2 for domains. In decoding, Recall@k represents the likelihood that the model ranked a ground truth within the top k predictions.

Table 2
NiCLIP model settings evaluation and comparison against baseline models

CLIP Model settings		Vocabulary settings		Baseline Models		Our Model NiCLIP		
				Neurosynth	GC-LDA			
				Task	Task	Task	Concept	Domain
Section	LLM	Ontology	Embedding	Recall@4	Recall@4	Recall@4	Recall@4	Recall@2
Body	BrainGPT-7B-v0.2	CogAt. Reduced	Name + Def.	-	-	**62.86**	**43.57**	**90.48**
			Name	20.71	20.71	62.14	19.21	78.57
		CogAt	Name + Def.	-	-	28.57	13.97	57.14
			Name	02.86	17.14	10.71	7.62	76.19
	Mistral-7B-v0.1	CogAt. Reduced	Name + Def.	-	-	34.20	10.48	59.52
			Name	20.71	20.71	21.43	9.52	45.24
		CogAt	Name + Def.	-	-	14.29	2.86	40.48
			Name	02.86	17.14	0	0	38.10
	BrainGPT-7B-v0.1	CogAt. Reduced	Name + Def.	-	-	55.	34.29	78.57
			Name	20.71	20.71	41.43	26.43	85.71
		CogAt	Name + Def.	-	-	10.00	4.76	26.19
			Name	06.43	17.14	09.29	4.76	57.14
	Llama-2-7b-chat-hf	CogAt. Reduced	Name + Def.	-	-	49.29	26.27	47.62
			Name	20.71	20.71	13.57	15.16	28.57
		CogAt	Name + Def.	-	-	06.43	11.91	38.10
			Name	17.14	17.14	06.43	7.14	30.95
Abstract	BrainGPT-7B-v0.2	CogAt. Reduced	Name + Def.	-	-	36.43	17.14	78.57
			Name	20.71	20.71	33.57	25.24	78.57
		CogAt	Name + Def.	-	-	20.00	7.62	57.14
			Name	20.71	27.86	20.71	0	54.76
	Mistral-7B-v0.1	CogAt. Reduced	Name + Def.	-	-	37.14	20.00	59.52
			Name	20.71	27.86	20.00	15.95	42.86
		CogAt	Name + Def.	-	-	05.71	11.19	66.67
			Name	20.71	20.71	0	0	30.95
	BrainGPT-7B-v0.1	CogAt. Reduced	Name + Def.	-	-	37.86	40.16	64.29
			Name	20.71	20.71	37.14	28.33	71.43
		CogAt	Name + Def.	-	-	24.29	4.76	52.38
			Name	17.14	27.86	23.57	0	45.24
	Llama-2-7b-chat-hf	CogAt. Reduced	Name + Def.	-	-	44.29	15.95	66.67
			Name	20.71	20.71	26.43	21.67	47.62
		CogAt	Name + Def.	-	-	27.86	12.78	30.95
			Name	20.71	20.71	0	09.92	16.67

Note: The best-performing value is highlighted in bold

The strongest performance across all categories was achieved by utilizing the complete text of the articles to train CLIP, BrainGPT-7B-v0.2 with the reduced Cognitive Atlas ontology, along with their definitions and task names (Task: 62.86%, Concept: 43.57%, Domain: 90.48% at Recall@2), significantly surpassing both baseline models with over a 40% improvement in recall scores. This configuration consistently yielded superior results across all tested LLMs, with BrainGPT-7B-v0.1 achieving the second-best performance (Task: 55%, Concept: 34.29%, Process: 78.57%). The reduced and enhanced versions of Cognitive Atlas consistently outperformed the original Cognitive Atlas ontology across all models, with performance further improved when using both the task name and definition rather than the name alone. Notably, some configurations with the full Cognitive Atlas ontology exhibited minimal or zero recall, particularly with Mistral-7B-v0.1. Baseline models (Neurosynth and GC-LDA) demonstrated limited effectiveness, with maximum Recall@4 scores of 20.71% for tasks, which is substantially lower than those of our NiCLIP model implementations. For abstract sections, we

observed generally lower performance compared to body sections, but with similar patterns. BrainGPT-7B-v0.1 with CogAt reduced ontology and "name + definition" vocabulary achieved the highest concept recall (40.16%), while Llama-2-7b-chat-hf excelled in task predictions recall (44.29%) with the same configuration. The predictions of domains consistently showed higher recall rates than tasks and concepts across all models and configurations, with BrainGPT-7B-v0.2 also achieving the best performance (78.57%) when trained with the abstract section, utilizing the reduced ontology with both task name only and name plus definition.

2.4. Evaluating NiCLIP for predicting text from different brain maps

2.4.1. Group-level activation maps

Diving deeper into the previous findings, **Fig. 2** shows the top 5 predictions of NiCLIP, sorted by the magnitude of the posterior probabilities for task (P(T|A)), concept (P(C|A)), and domain (P(D|A)). The probability of P(T|A) is defined by Bayes' theorem as the normalized joint probability of P(A|T) and the prior P(T). The likelihood P(A|T) reflects the similarity in the latent space of the activation embedding to the embeddings of task names and definitions from the ontology. At the same time, the prior distribution indicates the prevalence of the tasks in the literature. The probabilities for concepts and domains are not based on their semantic content, like the task itself, but instead on the probability of the task and their connection established in the ontology using the noisy-OR model. See additional details in the methods section. For the upcoming results, we used the best-performing CLIP model from the previous analysis. Additional comparisons between the NiCLIP task predictions and baseline models are available in the supplementary information (**Fig. S2**).

We decoded seven HCP task contrasts to evaluate NiCLIP's predictions (**Fig. 2**). For the emotion processing task ("Face vs. Shape"), NiCLIP identified face identification (27.4%) as the top task, followed by a functional localizer task (19.9%). The related concepts included response selection (28.6%), visual object recognition (28.5%), and face recognition (27.4%), which map to Learning and Memory (41.6%) and Perception (36.7%) domains. The gambling task ("Reward vs. Baseline") was mainly associated with numerical working memory tasks (38.2%) and relational processing (22.1%). Key concepts involved working memory (47.0%), numerical comparison (38.3%), and mathematical reasoning (38.2%), with Executive Cognitive Control (65.0%) and Reasoning and Decision-Making (62.2%) as the top domains. For language ("Story vs. Math"), NiCLIP predicted social localizer (18.9%) and language localizer task (17.0%), with concepts including visual object recognition (27.4%), auditory sentence recognition (24.6%), and reading (20.5%). The motor task showed expected links with motor fMRI task paradigm (48.3%) and motor-related concepts (movement, motor control, motor learning; all 48.3%), mapping to Action (73.8%) and Language (56.6%) domains. The relational processing task identified the relational processing fMRI task paradigm (54.5%) with Executive Cognitive Control (72.0%) as the primary domain. Social cognition ("TOM vs. Random") predicted social localizer (39.9%) with concepts including auditory sentence recognition (58.0%) and animacy detection (39.9%). Finally, working memory ("2-Back vs. 0-Back") showed strong associations with numerical working memory

tasks (67.2%) and working memory concepts (71.0%), mapping to Reasoning and Decision-Making (89.5%) and Executive Cognitive Control (75.8%).

Figure 2. NiCLIP predicts tasks, concepts, and domains from brain activation patterns based on group-level maps. This analysis provides prediction probabilities across seven major cognitive domains from the Human

Connectome Project (HCP) task fMRI dataset. For each domain (Emotion, Gambling, Language, Motor, Relational, Social, and Working Memory), we present three types of predictions: the probability of a task given an activation pattern (P(T|A)), the probability of a concept given an activation (P(C|A)), and the probability of a domain given an activation (P(D|A)). Each prediction is illustrated with horizontal bars representing prediction strength, showcasing the top five predictions for each category.

2.4.2. Region of interest maps

Next, we present a potential application of reverse inference methods for exploring novel hypotheses and discovering tasks, concepts, and domains associated with a specific region of interest (ROI). For this experiment, we also utilized the best-performing CLIP model (i.e., BrainGPT-7B-v0.2), which was trained on the complete body of articles. The NiCLIP model relied on a reduced version of the Cognitive Atlas as its cognitive ontology. NiCLIP predictions on ROIs were tested on six popular anatomical brain regions, including the amygdala (Bzdok et al., 2013a), hippocampus (Plachti et al., 2019), insula (Chang et al., 2013), striatum (Liu et al., 2020), right temporoparietal junction (rTPJ) (Bzdok et al., 2013b), and ventromedial prefrontal cortex (vmPFC) (Chase et al., 2020). **Fig. 3** presents the results of predicting tasks, concepts, and domains across the six ROIs. Unlike the previous predictions on dense maps from **Fig. 2**, the top predicted task here resulted in a more distinct probability relative to the second-highest task. Additional comparisons between the NiCLIP task predictions and the baseline models are provided in the supplementary information (**Fig. S3**).

We analyzed NiCLIP predictions across six anatomical ROIs to demonstrate its ability to identify regional functional specialization (**Fig. 3**). The amygdala showed a strong association with emotion processing tasks (65.5%), with other tasks below 5%. Top concepts included emotion, response selection, and feature comparison (~65%), aligning with Action (68.6%), Emotion (67.6%), and Reasoning and Decision-Making (67.0%) domains. The hippocampus was linked to working memory fMRI task (25.6%), incidental encoding (17.0%), emotion processing (15.6%), and motor tasks (12.7%), with memory-related concepts (working memory, visual recognition, memory) dominating. Learning and Memory was the primary domain (47.2%), followed by Action and Executive cognitive control (31.0%). The insula exhibited pain-related functions, including pain monitoring/discrimination (34.9%) and related concepts (pain, pain sensation, pain habituation; ~38% each), with a strong mapping to the Emotion domain (76.9%). The striatum showed language specialization, connecting with semantic tasks (52.1%) and language-related concepts (52.2%), with Language (53.6%) as the dominant domain. The rTPJ displayed remarkable selectivity for social cognition/theory of mind tasks (98.5%), with related concepts (social cognition, animacy perception) mapping to Perception, Reasoning and Decision-Making, and Social Function domains (all 98.5%). Finally, the vmPFC was associated with decision-making tasks (2-stage decision: 45.7%), reward-related concepts (reward processing: 47.2%, decision-making under uncertainty: 45.9%), and the domains of Learning and Memory (63%) and Reasoning and Decision-Making (50.4%).

Figure 3. NiCLIP for predicting tasks, concepts, and domains from brain ROIs. We conducted a comprehensive analysis of prediction probabilities across six different ROIs. For each ROI (amygdala, hippocampus, insula, striatum, rTPJ, vmPFC), we display three types of predictions: the probability of a task given an activation pattern (P(T|A)), the probability of a concept given an activation (P(C|A)), and the probability of a domain given an activation (P(D|A)). Each prediction is visualized with horizontal bars indicating prediction strength, with the top five predictions shown for each category.

2.4.3. Subject-level activation maps

Following the prediction of group-level activation maps, we explored whether NiCLIP can identify the underlying tasks, concepts, and domains in subject-level images. In practice, researchers typically report activation foci from group-level images of significant findings in scientific papers. Consequently, our model is capable of producing robust predictions for population-level average activation maps, as illustrated in **Fig. 2**. In contrast, subject-level images exhibit high variability and noise, and individual subject differences are known to result in distinct brain activation patterns within the same task and condition. We anticipated that these factors could potentially interfere with NiCLIP's predictions. For this experiment, we also utilized the best-performing CLIP model. We conducted a qualitative evaluation of the NiCLIP predictions on the exact seven major domains from the HCP tasks fMRI dataset, but using the subject-level activation maps instead. These domains included tasks along with their respective contrasts of interest, including emotion, gambling, language, motor, relational, social, and working memory. In this analysis, we included 787 subjects, the distribution of the Recall@K score is presented in **Fig. S4**. **Fig. S5** illustrates the results for one particular subject with the best performance, and show the top 5 predictions sorted by the magnitude of the posterior probabilities (i.e., $P(T|A)$, $P(C|A)$, and $P(D|A)$). Overall, functional decoding on subject-level brain activation maps was less effective than the results on group-level images, with an average Recall@4 score of 38.19% for tasks, a Recall@4 score of 25.34% for concepts, and a Recall@2 score of 52.01% for the domain. Correct findings were rarely ranked among the top five predictions for most of the target brain images (**Fig. S5**). Additional comparisons between the NiCLIP task predictions and the baseline models are provided in the supplementary information (**Fig. S6**).

2.4.4. Different variations of the same activation map

Finally, we examined how sensitive the NiCLIP predictions are to the sign and activation values of the brain maps. To achieve this, we utilized the group-level activation task from the motor domain of the HCP dataset and created six distinct variations of the original map. One map included only the positively activated region, while another included only the negatively activated region. We also tested a map with the positively activated regions of the original maps, but with the sign flipped. Lastly, we evaluated the prediction on three different ROI maps, representing the top 10, 5, and 1 percentiles of the positively activated regions. **Fig. S7** shows the results of the top 5 predictions sorted by the magnitude of the posterior probabilities (i.e., $P(T|A)$, $P(C|A)$, and $P(D|A)$). Overall, the six variations produced different results. Decoding the negative tail alone, or the positive tail with the sign flipped, did not produce a motor task in the top 5 predictions. The ROI created by taking the top 10 and top 5 percentiles included the "motor fMRI task paradigm" in the top three, but the top two predicted tasks did not match the original image's prediction. The map consisting of the positive tail alone was closer to the original image's prediction. The ROI comprising the top 1 percentile of positive activation was the only variation that showed the exact prediction and selectivity as the original image, differing only in the order of the top two tasks.

3. Discussion

The topic of formal reverse inference on brain activation maps has remained an open question in the neuroscience community for many years. Although several attempts have been made to address this gap, mostly utilizing emerging meta-analytic approaches and databases, multiple limitations persist in meta-analytic methods for consolidating existing data for functional decoding. Additionally, the absence of a reliable cognitive ontology has hindered broader adoption and application. To tackle these current challenges, we present NiCLIP in this work, a contrastive language-image pretraining model designed to predict fMRI tasks, concepts, and domains from brain images. First, we compared four different LLM models and demonstrated that a fine-tuned LLM (e.g., BrainGPT-7B-v0.2) enhances text-to-brain association within the CLIP model architecture. Second, we evaluated the predictions of NiCLIP models on group-level activation maps from the HCP and found overall accurate predictions of tasks, concepts, and domains. However, when NiCLIP was applied to the same tasks on subject-level images, it produced inconsistent results, with accurate task predictions only for a few tasks, such as emotion and social, while yielding incorrect predictions for others. Third, we investigated the capabilities of the NiCLIP model for decoding regions of interest. In that experiment, we successfully predicted tasks, concepts, and domains across six different meta-analytic ROIs tested. An extensive evaluation of NiCLIP revealed that it is crucial not only to utilize a fine-tuned LLM and train the CLIP model on the full text of the articles, but also to leverage a curated cognitive ontology with precise task-to-concept and concept-to-domain mappings. Taken together, our findings situate NiCLIP not only as a precise and accurate decoding tool of brain activation maps but also as the most flexible decoding framework to date.

3.1. Situating NiCLIP within current tools for decoding brain images

NiCLIP marks a significant advancement over current solutions. Existing functional decoding methods, such as correlation-type decoders, are not based on formal models, fail to identify latent structures related to specific cognitive processes, and lack sensitivity to unseen brain patterns. Other methods, like GC-LDA, operate entirely unsupervised, indicating that these models are not optimized for classification or prediction accuracy. Generally, these methods are limited by the small number of pre-created meta-analytic maps used for predictions, rely on TF-IDF to define concepts or maps—which ignores semantic context—and operate within a limited vocabulary, thereby preventing the prediction of external or unseen concepts. As a CLIP-based decoding model, NiCLIP utilizes an image-text latent space to make predictions on unseen data. CLIP models are also self-supervised, meaning their parameters are optimized to match text to corresponding images with minimal training error, and they are fine-tuned for accurate text-image matching on unseen data. NiCLIP models are not constrained by a set of pre-computed meta-analytic maps since the model operates by finding similarities within the shared latent space. Both LLM and CLIP models enable linking the entire abstract and text body of a publication to brain activation patterns, thereby overcoming the limitations of bag-of-words and TF-IDF methods. Additionally, LLM enables the use of external terms and their

definitions to annotate publication texts, for example, concepts from established ontologies such as the Cognitive Atlas.

Although the NeuroQuery framework offers a solution to expand to external terms based on similarity (Dockès et al., 2020), such expansions remain limited to simple term combinations and do not fully capture entire ontologies or phrases. Additionally, the similarities between terms in NeuroQuery are only based on their names. In contrast, NiCLIP utilizes both the term names and their definitions, providing more precise and distinct semantic content. By employing a comprehensive ontology and leveraging semantic similarities between tasks and their descriptions from a cognitive ontology, we can also expand predictions to include concepts and domain-specific distributions, thereby providing additional context. NiCLIP also introduces a predictive framework for identifying associations with tasks that lack sufficient meta-analytic data to appear in traditional decoding results. For example, the n-back task was among the top predictions made by NiCLIP for the working memory activation maps. However, the "n-back task" was underrepresented in the literature; as a result, no meta-analytic maps were available for the Neurosynth correlation decoder to establish associations with the working memory maps, as shown in the supplementary information (**Fig. S2**).

While recent decoding approaches using NeuroVault statistical maps and Cognitive Atlas have shown improved performance over traditional CBMA-based methods (e.g., Neurosynth and GC-LDA) (Mensch et al., 2021, 2017; Menuet et al., 2022; Varoquaux et al., 2018), they face significant limitations that restrict their usefulness for comprehensive functional decoding. Despite efforts within the community, most neuroimaging studies do not share their statistical maps, resulting in NeuroVault containing only a limited set of tasks and cognitive domains with sparse coverage (Salo et al., 2023). Moreover, existing NeuroVault data suffers from inconsistent metadata annotation and frequent mislabeling of image modalities, map types, and Cognitive Atlas tasks (Peraza et al., 2025). These quality and coverage issues fundamentally restrict the generalizability of NeuroVault-based decoders. In contrast, our CBMA-based approach benefits from the extensive coverage of coordinate-based databases, which currently comprise the largest collection of neuroscience publications covering diverse fMRI tasks and cognitive domains (Oudyk et al., 2025). This broad literature coverage enables NiCLIP to decode activation patterns across a wider range of cognitive functions, including those underrepresented in NeuroVault. While whole-brain statistical maps offer richer spatial information, the balance between data richness and domain coverage makes CBMA more suitable for applications that require diverse functional decoding. Therefore, rather than a limitation, our CBMA foundation offers a strategic advantage for uncovering associations across the full spectrum of cognitive neuroscience, reducing the selection bias associated with repository-dependent decoding approaches.

3.2. The need for better ontologies

One key feature of the current framework is its ability to make predictions using external terminology, such as terms provided by an ontology. Here, NiCLIP uses a cognitive ontology to define the fMRI tasks and their connections to concepts and domains. Despite the extensive collection of tasks and concepts, the Cognitive Atlas database remains limited. As a community-driven ontology, these

mappings reflect the opinions of individual researchers and are not necessarily factual (Poldrack et al., 2011). We might find popular tasks, such as the "motor fMRI task paradigm," linked only to working memory concepts, while missing relevant terms like movement and motor, among others. The task names and descriptions are still not standardized. Some tasks may have definitions made up of two sentences, while others consist of multiple sentences, which affects the final embedding computed for prediction in the shared latent space.

We demonstrated that a reduced and curated representation of the Cognitive Atlas tasks, combined with a more robust and comprehensive mapping of concepts, outperforms the original Cognitive Atlas ontology. This highlights the importance of cognitive ontology for reverse inference tasks. Following the trend of leveraging LLMs for such challenging tasks, we believe that a data-driven ontology derived from the entire neuroscience literature has the potential to improve existing cognitive ontologies by providing more accurate and standardized task names and definitions, along with better task-to-concept mappings. We believe that developing more standardized and precise cognitive ontologies is crucial to fully harness the potential of LLM-powered functional decoders.

3.3. Recommendations, potential use cases, and applications

The results presented in this work highlight the importance of using the full text of the publication for CLIP models, as additional text offers more distinctive context for the associated brain maps. More importantly, we recommend using domain-specific LLMs through fine-tuning (i.e., BrainGPT-7B-v0.2), since they have been shown to produce better text-to-image associations than more general models. Additionally, prediction must rely on accurate and enhanced ontologies, such as the reduced and curated Cognitive Atlas ontology. The current trained model should not be used to decode images with high noise, such as subject-level activation maps, as our decoding model performs poorly on this type of data. Since the training sample consisted of activation coordinates from positively activated maps, we suggest against decoding the image with the negative signal alone. If one is interested in decoding both ends of the activation distribution in an image separately, one could flip the sign of the image to force the decoder to predict the negative tail. Alternatively, one could split the image and decode the tails separately as positively activated maps, or create an ROI for each end and decode the resultant region instead. As shown in the supplemental analysis (**Fig. S7**), decoding the same maps with inverted signs produces different results. Note that future expansion of the training data can be achieved by adding negative-only activations and images with high noise to improve the accuracy of predictions for more diverse activation maps. Further analysis is needed to support this.

Additionally, we observed that larger ROIs tend to exhibit a decrease in task selectivity, which aligns with previous findings on the relationship between selectivity and the size of brain regions. However, as noted for smaller ROIs (**Fig. 3**), some regions are indeed highly selective, but others remain low in selectivity regardless of their size relative to the whole brain. Caution is advised when interpreting the probabilities of NiCLIP predictions from this kind of predictive model. With the current training data, a high-probability target activation region for a task suggests that the semantic context of the task name and definition closely matches the semantic content of the brain region when mapped into the shared

latent space, relative to other task names from the provided ontology. However, this does not mean that directly performing a forward inference experiment—executing the predicted task in an MRI—will necessarily result in selective activation of that specific region alone.

NiCLIP not only accurately performs continuous decoding on dense activation maps but also makes predictions on sparse brain images, such as regions of interest. These promising capabilities open the door to potential new applications of reverse inference methods. In principle, researchers could explore novel hypotheses and discover the tasks, concepts, and domains associated with specific anatomical brain regions that have not been studied before. Others can leverage NiCLIP to describe functional domains of regions of interest that appear relevant to a specific population. Such predictions can also be used to contrast the functional associations linked to a region between healthy controls and clinical populations. In summary, the application of reverse inference is not limited to brain activation maps alone. In principle, one could explore the functional domain of any region in the entire brain.

In this work, NiCLIP was trained and validated to predict fMRI tasks, concepts, and domains from brain activation images using a cognitive ontology. However, the proposed framework can be applied to any image and text pairs, as long as the appropriate training data is available. For example, using data properly annotated with unstructured text by trained neuroradiologists, NiCLIP could be used with structural MRI, computed tomography scans, or other medical imaging modalities to identify names of pathologies, structural abnormalities, and other conditions. Note that the framework for the contrastive model presented here only requires embeddings from different sources as input, so, in principle, a contrastive model could be trained to also predict text related to resting state connectivity and other neuroimaging derivatives data. The network architecture and parameters may need to be adjusted for those applications.

3.4. Limitations and challenges

We note several limitations in this current work. The most significant weakness of our study pertains to the small size of the training sample. Typically, CLIP models are trained with hundreds of millions of image-text pairs (Radford et al., 2021). In contrast, our CLIP model was trained with just over 20,000 pairs, which currently is the largest sample of neuroscience papers with complete text information and reported activation coordinates. It is worth noting that (1) brain statistic images are much more constrained than naturalistic images, and (2) we employed a representation of the images based on immense quantities of training data, defined by the DiFuMO atlas. These two factors may mitigate the smaller volume of training data relative to other CLIP applications, which require multiple variations of an image's content and advanced convolutional neural networks to extract image features.

The sample size is expected to increase in the future as more articles are published. However, the scientific literature is still growing at a pace that prevents us from achieving a sample size in the millions anytime soon (Bornmann and Mutz, 2015). In principle, we can integrate NeuroVault images into the training set (Gorgolewski et al., 2015). Combining modeled activation maps from peak coordinates with statistical maps has been successfully attempted before (Meudec et al., 2022), yielding improved performance for decoding tasks. We could also incorporate subject-level labeled images from

major data consortia, such as ABIDE (Di Martino et al., 2017, 2014), ABCD (Casey et al., 2018), HCP (Barch et al., 2013; Smith et al., 2013; Uğurbil et al., 2013; Van Essen et al., 2013, 2012), ADNI (Jack Jr. et al., 2024), and ENIGMA (Thompson et al., 2014), among others. One could apply different data augmentation techniques and include various versions of the same activation brain map with added noise, or with different thresholds or smoothing parameters. Collectively, these images could expand our sample size to hundreds of thousands. However, we must consider that our CLIP model seems to perform better when the text associated with the images is large. Still, it remains uncertain whether increasing the sample size, even with less detailed text information, can overcome such limitations. More importantly, including subject-level maps and other images from online repositories, such as NeuroVault, could potentially address another issue, namely, the lack of reliability of NiCLIP in predicting individual subject activation maps. Further analyses are necessary to test these hypotheses.

Lastly, the formulation of the reverse inference problem follows Bayes' theorem, where the posterior probability of a task name given an activation is directly proportional to its prior probability. Here, we have chosen to set the prior distribution on tasks based on their prevalence in the literature. However, this assumption may be suboptimal for rare tasks, and a uniform prior could be used as an alternative. Additional work is needed to assess the actual influence and provide recommendations for selecting prior probabilities.

4. Conclusions

Taken together, this study presents NiCLIP, the first LLM-powered CLIP model for formal reverse inference of brain activation maps. We confirmed CLIP's unique ability to match article text to brain images. The results indicate that a fine-tuned LLM provides the most effective text-to-brain association, with generally stronger performance when using the full body of the articles. We validated NiCLIP as a precise decoding tool for group-level dense activation maps; however, our decoding model underperformed on individual subject images. Additionally, NiCLIP demonstrated notable performance with other image types, such as ROI maps. Lastly, we highlighted the importance of improving cognitive ontologies for reverse inference tasks. NiCLIP not only marks a major improvement over earlier methods for describing activation maps but also serves as a crucial tool for testing new hypotheses and driving scientific discovery (Poldrack, 2006).

5. Methods

5.1. Datasets

5.1.1. PubMed neuroimaging papers

We conducted an extensive search for neuroimaging articles in PubMed Central using Pubget (https://neuroquery.github.io/pubget/pubget.html), an open-access Python tool for collecting data for biomedical text mining. We performed a query and retrieved articles that included keywords such as "fMRI" or "functional MRI" in the abstracts (e.g., "(fMRI[Abstract]) OR (functional MRI[Abstract])").

Pubget extracted text, metadata, and stereotactic coordinates from the articles in a standardized format. The data was then converted into a NiMARE database object to facilitate downstream tasks such as term-based and topic-based meta-analysis for the baseline models and to generate images from the extracted activation coordinates. As of February 2025, the PubMed search for neuroimaging articles yielded more than 30,000 papers. A total of 23,865 articles included at least one activation coordinate, a complete abstract, and full-text information.

The text embeddings $M \in \mathfrak{R}^{23,865 \times 4,096}$ were derived using pre-trained LLMs. We compared four different LLM models: BrainGPT models (i.e., BrainGPT-7B-v0.1 and BrainGPT-7B-v0.2) (Luo et al., 2024), along with their corresponding foundational pre-trained LLM (i.e., Llama-2-7b-chat-hf and Mistral-7B-v0.1, respectively) (Jiang et al., 2023; Touvron et al., 2023). Due to the token size limitation of these LLMs, embeddings for long text were generated by averaging the embeddings from smaller chunks of the text. Article-specific brain images were generated from brain activation coordinates using a Multilevel Kernel Density Analysis (MKDA) (Wager et al., 2007). MKDA is a kernel-based method that convolves each activation coordinate with a binary sphere of a set radius around the peak voxel. The coordinate-specific binary maps (i.e., one map corresponding to each coordinate from the set) were combined into a single modeled activation map by taking the maximum value for each voxel. In this work, we used a sphere with a radius of 10mm. Finally, brain image embeddings $A \in \mathfrak{R}^{23,865 \times 512}$ were extracted from the modeled activation map using a continuous brain parcellation defined by the DiFuMo atlas with 512 regions (Dadi et al., 2020). Text and image embeddings were L2 normalized.

5.1.2. Cognitive Ontology

Cognitive Atlas (Poldrack et al., 2011) (https://www.cognitiveatlas.org/) is an online repository of cumulative knowledge from experienced researchers in psychology, cognitive science, and neuroscience. The repository currently offers two knowledge bases: 912 cognitive concepts and 851 tasks, complete with definitions and properties. The cognitive concepts establish relationships with other concepts and tasks, aiming to create a map between mental processes and brain functions. The task and concept metadata (i.e., names and definitions) were downloaded using the Cognitive Atlas API, while the task, concept, and domain relationships were obtained through NiMARE's 'download_cognitive_atlas' function. Here, a "domain" refers to a high-level concept, as defined by the concept categories in Cognitive Atlas (https://www.cognitiveatlas.org/concepts/categories/all). Despite the extensive collection of tasks and concepts, the mapping (i.e., which tasks measure a concept and how concepts are grouped in domains) remains limited. Additionally, as a community-based ontology, these mappings reflect the opinions of individual researchers and may not always be factual. Therefore, we utilized a simplified representation of the Cognitive Atlas task to enhance the mapping of concepts to tasks defined in (Menuet et al., 2022).

5.1.3. Task fMRI datasets

The functional decoding model was assessed using the task-fMRI group-average maps from the HCP S1200 data release (Barch et al., 2013; Smith et al., 2013; Uğurbil et al., 2013; Van Essen et al., 2013, 2012).

Specifically, we used the results in volume space reported in collection 457 in NeuroVault (https://neurovault.org/collections/457/). The HCP tasks target seven major domains that sample a diverse set of neural systems of high interest in the neuroscience field. These domains include (1) emotion processing, (2) category specific representations, (3) language processing (semantic and phonological processing), (4) visual, motion, somatosensory, and motor systems, (5) relational processing, (6) social cognition (theory of mind), (7) working memory/cognitive control systems. Additional details regarding these tasks and their available contrasts have been previously published (Barch et al., 2013). Next, the functional decoding model was evaluated using subject-level statistical images, as these data tend to have more variability and noise compared to group-level images. We used data from subject-level activation maps from 787 individuals, which contain the same tasks and contrasts as those in the HCP group-level analysis.

5.1.4. Meta-analytic regions of interest

Next, the functional decoding model was evaluated on specific regions of interest (ROI). We used six highly popular anatomical brain regions, including the amygdala (Bzdok et al., 2013a), hippocampus (Plachti et al., 2019), insula (Chang et al., 2013), striatum (Liu et al., 2020), right temporoparietal junction (rTPJ) (Bzdok et al., 2013b), and ventromedial prefrontal cortex (vmPFC) (Chase et al., 2020). Here, we defined a single ROI for each brain region by combining all the seed regions. **Fig. S8** presents the seed regions per ROI as defined by their corresponding meta-analytic-based parcellation analysis.

5.2. CLIP model for article and brain image association

The CLIP model architecture (**Fig. 4A**) adheres to the identical settings employed in the NeuroConText framework (Meudec et al., 2024). CLIP consists of both a text and an image encoder. The text encoder is characterized by a projection head and two residual heads, while the image encoder comprises three residual heads. The projection head takes the high-dimensional text embedding and projects it into a shared dimensional space to align with the image embedding dimension, which has already been reduced through brain parcellation. The projection head consists of a fully connected projection layer, followed by a GELU activation function, an identity fully connected layer, a dropout rate of 0.5 for regularization, and a normalization layer. Each residual head includes an identity fully connected layer and a GELU activation function, followed by a dropout rate of 0.5 and a normalization layer.

The model's hyperparameters for training were selected from the NeuroConText paper (Meudec et al., 2024), with the following configurations: batch size of 128, learning rate of 5e-4, weight decay of 0.1, and a total of 50 epochs. The contrastive loss function InfoNCE was employed for self-supervised learning during training, following the standard implementation of the CLIP model (Oord et al., 2019). Additionally, we incorporated an early stopping rule to prevent overfitting and avoid unnecessary computation during epochs without performance improvement. We monitored the validation loss across epochs while maintaining a patience window of 10 epochs to accommodate potential performance fluctuations. If the validation loss did not improve within the patience window, training was terminated, and the model weights corresponding to the lowest validation loss were saved. Finally, the model was trained and evaluated using distinct data loaders for training, validation, and testing,

implementing a 23-fold cross-validation on the test set and a 22-fold nested cross-validation on the evaluation set. The fold size for the testing and evaluation was 1,000 samples, resulting in approximately 21,865 articles available for training.

5.3. NiCLIP: neuroimaging CLIP model for predicting tasks, concepts, and domains from brain images

The NiCLIP architecture (**Fig. 4B**) leverages the learned shared latent space from the CLIP model to make predictions on unseen data. Given a target activation map, the goal of the NiCLIP decoder is to predict the most likely task, concept, and domain associated with the activation pattern. NiCLIP relies on a cognitive ontology to define the fMRI tasks and their definitions, as well as their associations with concepts and domains. Using Bayes' theorem, we can express the probability that a brain activation pattern (A_k) was produced by a certain fMRI task T_i as:

$$P\left(T_i|A_k\right) = \frac{P\left(A_k|T_i\right)P\left(T_i\right)}{\Sigma_j P\left(A_k|T_j\right)P\left(T_j\right)}$$

where $P\left(T_i|A_k\right)$ is the posterior probability, $P\left(A_k|T_i\right)$ is the likelihood of task T_i having an activation pattern A_k, and $P\left(T_i\right)$ is the prior probability of task T_i regardless of the activation pattern.

First, we use the pre-trained CLIP model to estimate the likelihood $P\left(A_k|T_i\right)$. To accomplish that, we use a vocabulary composed of all Cognitive Atlas tasks and their definitions. Initially, the vocabulary was encoded by the same LLM used to train CLIP, and then the embedding for each task was determined as a linear combination of the task name embedding and its definition:

$$Emb(T_i) = \alpha Emb\left(T_{i,name}\right) + (1 - \alpha)Emb\left(T_{i,description}\right)$$

where the parameter α represented the weight of the name embedding relative to its definition. Here, we considered $\alpha = 0.5$.

Next, the vocabulary embeddings were encoded by the text encoding layers from CLIP, projecting the vocabulary into the shared latent space with the images. For the target image, we extracted 512 features using the Difumo atlas (i.e., the same dimension used to train CLIP). We encoded the features with the image encoding layers, projecting the images into the same shared latent space of the vocabulary. Finally, we calculated the cosine similarity between the vocabulary embeddings and the input image embeddings and transformed the similarity into probability, resulting in the likelihood $P\left(A_k|T_i\right)$.

$$P\left(A_k|T\right) = softmax\left(Emb(T) \cdot Emb(A_k)\right)$$

The prior probability $P\left(T_i\right)$ was determined by the task representation in the neuroscience corpora used for training the CLIP model. The task representation was defined by the cosine similarity of all document task pairs DT. To obtain a measure of the global representation, we calculated the mean

across all publications, resulting in a similarity score for each task with the corpora. Finally, the prior probability resulted in

$$P(T_i) = softmax(DT)$$

Now, since we have the posterior probabilities of the task given an activation $P(T|A)$, we can use noisy-OR model to define the probability of a concept (C_j) given an activation A_k as:

$$P(C_j|A_k) = 1 - \prod_i \left(1 - P\left(T_i^j|A_k\right)\right)$$

where T_i^j represents tasks that measure the concept C_j. Similarly, we can obtain the probability of the domain D_j given an activation A_k as:

$$P(D_j|A_k) = 1 - \prod_i \left(1 - P\left(C_i^j|A_k\right)\right)$$

where C_i^j represents concepts categorized under the cognitive process D_j.

Figure 4. CLIP and NiCLIP model architecture. (A) The architecture of the CLIP model includes a text encoder and an image encoder that transform input embeddings into a shared latent space. The text encoder consists of a projection head and two residual heads, while the image encoder has three residual heads. The projection head is defined by a linear projection layer, followed by a GELU activation function, a linear layer, a dropout layer, and culminating in a normalization layer. The residual head is made up of a linear identity layer, followed by a GELU activation and a dropout layer, concluding with a normalization layer. The output from the shared latent space is utilized for downstream tasks (e.g., functional decoding), and InfoNCE loss is applied in the latent space for self-supervised learning during training. **(B)** NiCLIP takes advantage of the task name embedding and the extracted features from a target activation map. These embeddings are encoded with the pre-trained CLIP text and image encoders. Cosine similarity is assessed in the shared latent space, and a softmax function converts them to a likelihood P(A|T). Using the prior probability P(T), we compute the posterior probability of a task

given an activation P(T|A). Furthermore, the noisy-OR model is employed to determine the probability of a concept P(C|A) and domain P(D|A) given an activation.

5.4. Evaluation metrics

We assessed the CLIP model's ability to match brain images with their corresponding text using Recall@k and Mix&Match (Menuet et al., 2022; Meudec et al., 2024; Mitchell et al., 2008), which are commonly employed in contrastive learning models. Given an activation map, Recall@K quantifies the likelihood of finding its true corresponding text among the top-k ranked by similarity within the entire sample (Meudec et al., 2024). To determine the top-k maps, we first calculate the similarity matrix $S \epsilon \Re^{n \times n}$ between the image and text embeddings in the shared latent space. The identity matrix represents the true positive, as the diagonal element indicates the similarity between an image and its corresponding text. As specified in the InfoNCE loss, the model is trained so that the diagonal element of the similarity matrix approaches 1 while the nondiagonal elements decrease towards zero. The similarity matrix is sorted on a row-by-row basis, and we check whether the diagonal element (i, i) is among the top-k ranked elements. The final scores are computed by averaging across rows:

$$Recall@k = \frac{1}{n}\sum_i H(i)$$

where n represents the total number of samples (or rows), and H denotes the indicator function that yields one if the column j=i belongs to the top k sorted columns ($i \epsilon Top_{ki}$) and zero otherwise. Specifically, the best model was determined based on the highest test set Recall@10

Mix&Match measures the likelihood that a given brain map is more similar to its true corresponding text than the other text embeddings in the set (Meudec et al., 2024; Mitchell et al., 2008). In other words, this metric assesses whether the learned embeddings in the shared latent space representations are discriminative, indicating that an item is more similar to itself than to other items.

We also evaluated the sensitivity of the functional decoders, including baselines and NiCLIP, using Recall@K. In this context, the Recall@K value can be interpreted as the likelihood that a decoder ranks the true label among the top-k labels for a given brain activation map (Menuet et al., 2022). We utilized the image metadata from the HCP, which contains the corresponding Cognitive Atlas task as the ground truth.

Acknowledgments

Special thanks to the FIU Instructional & Research Computing Center (IRCC, http://ircc.fiu.edu) for providing the HPC and computing resources that contributed to the research results reported in this paper.

Ethical Statement

The Human Connectome Project provided the ethics and consent needed for the study and dissemination of HCP data. This secondary data analysis was approved by the Institutional Review Board of Florida International University.

Funding Statement

Funding for this project was provided by NIH R01-MH096906.

Data Accessibility

The functional neuroimaging data were provided by the Human Connectome Project, WU-Minn Consortium (Principal Investigators: David Van Essen and Kamil Ugurbil; U54-MH091657) funded by the 16 NIH Institutes and Centers that support the NIH Blueprint for Neuroscience Research; and by the McDonnell Center for Systems Neuroscience at Washington University. The results of group-level activation maps in volume space can be downloaded from collection 457 in NeuroVault (https://neurovault.org/collections/457/). The subject-level activation maps can be downloaded from collection 4337 in NeuroVault (https://neurovault.org/collections/4337/).

The meta-analytic parcellation images are publicly available for download at https://anima.fz-juelich.de/.

A simplified representation of the Cognitive Atlas task is available in GitHub https://github.com/Parietal-INRIA/fmri_decoding/blob/master/Data/labels/cogatlas_tasks_concepts_bertrand_mini.csv.

Code Availability

This project relied on multiple open-source Python packages, including: Jupyter (Kluyver et al., 2016), Matplotlib (Hunter, 2007), Neuromaps (Markello et al., 2022), NiBabel (Brett et al., 2020), Nilearn (Abraham et al., 2014), NiMARE (Salo et al., 2024, 2023), PyMARE (Yarkoni et al., 2024), NumPy (van der Walt et al., 2011), Pandas (McKinney, 2010), Scikit-learn (Pedregosa et al., 2011), SciPy (Virtanen et al., 2020), Seaborn (Waskom, 2021), and SurfPlot (Gale et al., 2021),. We also used the HCP software Connectome Workbench (wb_command version 1.5.0, (Marcus et al., 2011)).

All code required to reproduce the analyses and figures in this paper is available on GitHub at https://github.com/NBCLab/brain-decoder. All data and resources that resulted from this paper are openly disseminated and made available on the Open Science Framework (OSF) at https://osf.io/dsj56/, including the links to the GitHub repository and figures.

Competing Interests

The authors declare no competing interests.

Author Contributions

ARL, JAP, AdlV, JBP, TEN, and JDK conceived and designed the project. JAP, AdlV, and JDK analyzed data. JAP and JDK contributed scripts and pipelines. JAP, TEN, and ARL wrote the paper, and all authors contributed to the revisions and approved the final version.

References

Abraham, A., Pedregosa, F., Eickenberg, M., Gervais, P., Mueller, A., Kossaifi, J., Gramfort, A., Thirion, B., Varoquaux, G., 2014. Machine learning for neuroimaging with scikit-learn. Front. Neuroinform. 8. https://doi.org/10.3389/fninf.2014.00014

Aizawa, A., 2003. An information-theoretic perspective of tf–idf measures. Information Processing & Management 39, 45–65. https://doi.org/10.1016/S0306-4573(02)00021-3

Amft, M., Bzdok, D., Laird, A.R., Fox, P.T., Schilbach, L., Eickhoff, S.B., 2015. Definition and characterization of an extended social-affective default network. Brain Struct Funct 220, 1031–1049. https://doi.org/10.1007/s00429-013-0698-0

Barch, D.M., Burgess, G.C., Harms, M.P., Petersen, S.E., Schlaggar, B.L., Corbetta, M., Glasser, M.F., Curtiss, S., Dixit, S., Feldt, C., Nolan, D., Bryant, E., Hartley, T., Footer, O., Bjork, J.M., Poldrack, R., Smith, S., Johansen-Berg, H., Snyder, A.Z., Van Essen, D.C., 2013. Function in the human connectome: Task-fMRI and individual differences in behavior. NeuroImage, Mapping the Connectome 80, 169–189. https://doi.org/10.1016/j.neuroimage.2013.05.033

Bornmann, L., Mutz, R., 2015. Growth rates of modern science: A bibliometric analysis based on the number of publications and cited references. Journal of the Association for Information Science and Technology 66, 2215–2222. https://doi.org/10.1002/asi.23329

Brett, M., Markiewicz, C.J., Hanke, M., Côté, M.-A., Cipollini, B., McCarthy, P., Jarecka, D., Cheng, C.P., Halchenko, Y.O., Cottaar, M., Larson, E., Ghosh, S., Wassermann, D., Gerhard, S., Lee, G.R., Wang, H.-T., Kastman, E., Kaczmarzyk, J., Guidotti, R., Duek, O., Daniel, J., Rokem, A., Madison, C., Moloney, B., Morency, F.C., Goncalves, M., Markello, R., Riddell, C., Burns, C., Millman, J., Gramfort, A., Leppäkangas, J., Sólon, A., van den Bosch, J.J.F., Vincent, R.D., Braun, H., Subramaniam, K., Gorgolewski, K.J., Raamana, P.R., Klug, J., Nichols, B.N., Baker, E.M., Hayashi, S., Pinsard, B., Haselgrove, C., Hymers, M., Esteban, O., Koudoro, S., Pérez-García, F., Oosterhof, N.N., Amirbekian, B., Nimmo-Smith, I., Nguyen, L., Reddigari, S., St-Jean, S., Panfilov, E., Garyfallidis, E., Varoquaux, G., Legarreta, J.H., Hahn, K.S., Hinds, O.P., Fauber, B., Poline, J.-B., Stutters, J., Jordan, K., Cieslak, M., Moreno, M.E., Haenel, V., Schwartz, Y., Baratz, Z., Darwin, B.C., Thirion, B., Gauthier, C., Papadopoulos Orfanos, D., Solovey, I., Gonzalez, I., Palasubramaniam, J., Lecher, J., Leinweber, K., Raktivan, K., Calábková, M., Fischer, P., Gervais, P., Gadde, S., Ballinger, T., Roos, T., Reddam, V.R., freec84, 2020. nipy/nibabel: 3.2.1. https://doi.org/10.5281/zenodo.4295521

Bzdok, D., Laird, A.R., Zilles, K., Fox, P.T., Eickhoff, S.B., 2013a. An investigation of the structural, connectional, and functional subspecialization in the human amygdala. Hum Brain Mapp 34, 3247–3266. https://doi.org/10.1002/hbm.22138

Bzdok, D., Langner, R., Schilbach, L., Jakobs, O., Roski, C., Caspers, S., Laird, A.R., Fox, P.T., Zilles, K., Eickhoff, S.B., 2013b. Characterization of the temporo-parietal junction by combining data-driven parcellation, complementary connectivity analyses, and functional decoding. Neuroimage 81, 381–392. https://doi.org/10.1016/j.neuroimage.2013.05.046

Casey, B.J., Cannonier, T., Conley, M.I., Cohen, A.O., Barch, D.M., Heitzeg, M.M., Soules, M.E., Teslovich, T., Dellarco, D.V., Garavan, H., Orr, C.A., Wager, T.D., Banich, M.T., Speer, N.K., Sutherland, M.T., Riedel, M.C., Dick, A.S., Bjork, J.M., Thomas, K.M., Chaarani, B., Mejia, M.H., Hagler, D.J., Daniela Cornejo, M., Sicat, C.S., Harms, M.P., Dosenbach, N.U.F., Rosenberg, M., Earl, E., Bartsch, H., Watts, R., Polimeni, J.R., Kuperman, J.M., Fair, D.A., Dale, A.M., 2018. The Adolescent Brain Cognitive Development (ABCD) study: Imaging acquisition across 21 sites. Developmental Cognitive Neuroscience, The Adolescent Brain Cognitive Development (ABCD)

Consortium: Rationale, Aims, and Assessment Strategy 32, 43–54.
https://doi.org/10.1016/j.dcn.2018.03.001

Chang, L.J., Yarkoni, T., Khaw, M.W., Sanfey, A.G., 2013. Decoding the role of the insula in human
cognition: functional parcellation and large-scale reverse inference. Cereb Cortex 23, 739–749.
https://doi.org/10.1093/cercor/bhs065

Chase, H.W., Grace, A.A., Fox, P.T., Phillips, M.L., Eickhoff, S.B., 2020. Functional differentiation in the
human ventromedial frontal lobe: A data‑driven parcellation. Hum Brain Mapp 41, 3266–3283.
https://doi.org/10.1002/hbm.25014

Cieslik, E.C., Zilles, K., Caspers, S., Roski, C., Kellermann, T.S., Jakobs, O., Langner, R., Laird, A.R., Fox,
P.T., Eickhoff, S.B., 2013. Is There "One" DLPFC in Cognitive Action Control? Evidence for
Heterogeneity From Co-Activation-Based Parcellation. Cereb Cortex 23, 2677–2689.
https://doi.org/10.1093/cercor/bhs256

Dadi, K., Varoquaux, G., Machlouzarides-Shalit, A., Gorgolewski, K.J., Wassermann, D., Thirion, B.,
Mensch, A., 2020. Fine-grain atlases of functional modes for fMRI analysis. NeuroImage 221,
117126. https://doi.org/10.1016/j.neuroimage.2020.117126

Di Martino, A., O'Connor, D., Chen, B., Alaerts, K., Anderson, J.S., Assaf, M., Balsters, J.H., Baxter, L.,
Beggiato, A., Bernaerts, S., Blanken, L.M.E., Bookheimer, S.Y., Braden, B.B., Byrge, L.,
Castellanos, F.X., Dapretto, M., Delorme, R., Fair, D.A., Fishman, I., Fitzgerald, J., Gallagher, L.,
Keehn, R.J.J., Kennedy, D.P., Lainhart, J.E., Luna, B., Mostofsky, S.H., Müller, R.-A., Nebel, M.B.,
Nigg, J.T., O'Hearn, K., Solomon, M., Toro, R., Vaidya, C.J., Wenderoth, N., White, T., Craddock,
R.C., Lord, C., Leventhal, B., Milham, M.P., 2017. Enhancing studies of the connectome in autism
using the autism brain imaging data exchange II. Sci Data 4, 170010.
https://doi.org/10.1038/sdata.2017.10

Di Martino, A., Yan, C.-G., Li, Q., Denio, E., Castellanos, F.X., Alaerts, K., Anderson, J.S., Assaf, M.,
Bookheimer, S.Y., Dapretto, M., Deen, B., Delmonte, S., Dinstein, I., Ertl-Wagner, B., Fair, D.A.,
Gallagher, L., Kennedy, D.P., Keown, C.L., Keysers, C., Lainhart, J.E., Lord, C., Luna, B., Menon,
V., Minshew, N.J., Monk, C.S., Mueller, S., Müller, R.-A., Nebel, M.B., Nigg, J.T., O'Hearn, K.,
Pelphrey, K.A., Peltier, S.J., Rudie, J.D., Sunaert, S., Thioux, M., Tyszka, J.M., Uddin, L.Q.,
Verhoeven, J.S., Wenderoth, N., Wiggins, J.L., Mostofsky, S.H., Milham, M.P., 2014. The autism
brain imaging data exchange: towards a large-scale evaluation of the intrinsic brain architecture
in autism. Mol Psychiatry 19, 659–667. https://doi.org/10.1038/mp.2013.78

Dockès, J., Oudyk, K., Torabi, M., Vega, A.I. de la, Poline, J.-B., 2024. Mining the neuroimaging
literature. eLife 13. https://doi.org/10.7554/eLife.94909.1

Dockès, J., Poldrack, R.A., Primet, R., Gözükan, H., Yarkoni, T., Suchanek, F., Thirion, B., Varoquaux, G.,
2020. NeuroQuery, comprehensive meta-analysis of human brain mapping. eLife 9, e53385.
https://doi.org/10.7554/eLife.53385

Fox, P.T., Laird, A.R., Fox, S.P., Fox, P.M., Uecker, A.M., Crank, M., Koenig, S.F., Lancaster, J.L., 2005.
BrainMap taxonomy of experimental design: description and evaluation. Hum Brain Mapp 25,
185–198. https://doi.org/10.1002/hbm.20141

Gale, D.J., Vos de Wael., R., Benkarim, O., Bernhardt, B., 2021. Surfplot: Publication-ready brain surface
figures. https://doi.org/10.5281/zenodo.5567926

Gorgolewski, K.J., Varoquaux, G., Rivera, G., Schwarz, Y., Ghosh, S.S., Maumet, C., Sochat, V.V.,
Nichols, T.E., Poldrack, R.A., Poline, J.-B., Yarkoni, T., Margulies, D.S., 2015. NeuroVault.org: a
web-based repository for collecting and sharing unthresholded statistical maps of the human
brain. Frontiers in Neuroinformatics 9, 8. https://doi.org/10.3389/fninf.2015.00008

Gunasekar, S., Zhang, Y., Aneja, J., Mendes, C.C.T., Giorno, A.D., Gopi, S., Javaheripi, M., Kauffmann,

P., Rosa, G. de, Saarikivi, O., Salim, A., Shah, S., Behl, H.S., Wang, X., Bubeck, S., Eldan, R., Kalai, A.T., Lee, Y.T., Li, Y., 2023. Textbooks Are All You Need. https://doi.org/10.48550/arXiv.2306.11644

Hunter, J.D., 2007. Matplotlib: A 2D Graphics Environment. Computing in Science & Engineering 9, 90–95. https://doi.org/10.1109/MCSE.2007.55

Jack Jr., C.R., Arani, A., Borowski, B.J., Cash, D.M., Crawford, K., Das, S.R., DeCarli, C., Fletcher, E., Fox, N.C., Gunter, J.L., Ittyerah, R., Harvey, D.J., Jahanshad, N., Maillard, P., Malone, I.B., Nir, T.M., Reid, R.I., Reyes, D.A., Schwarz, C.G., Senjem, M.L., Thomas, D.L., Thompson, P.M., Tosun, D., Yushkevich, P.A., Ward, C.P., Weiner, M.W., Initiative, A.D.N., 2024. Overview of ADNI MRI. Alzheimer's & Dementia 20, 7350–7360. https://doi.org/10.1002/alz.14166

Jiang, A.Q., Sablayrolles, A., Mensch, A., Bamford, C., Chaplot, D.S., Casas, D. de las, Bressand, F., Lengyel, G., Lample, G., Saulnier, L., Lavaud, L.R., Lachaux, M.-A., Stock, P., Scao, T.L., Lavril, T., Wang, T., Lacroix, T., Sayed, W.E., 2023. Mistral 7B. https://doi.org/10.48550/arXiv.2310.06825

Kluyver, T., Ragan-Kelley, B., Pé, Rez, F., Granger, B., Bussonnier, M., Frederic, J., Kelley, K., Hamrick, J., Grout, J., Corlay, S., Ivanov, P., Avila, D., n, Abdalla, S., Willing, C., Team, J.D., 2016. Jupyter Notebooks – a publishing format for reproducible computational workflows. Positioning and Power in Academic Publishing: Players, Agents and Agendas 87–90. https://doi.org/10.3233/978-1-61499-649-1-87

Laird, A.R., Eickhoff, S.B., Fox, P.M., Uecker, A.M., Ray, K.L., Saenz, J.J., McKay, D.R., Bzdok, D., Laird, R.W., Robinson, J.L., Turner, J.A., Turkeltaub, P.E., Lancaster, J.L., Fox, P.T., 2011. The BrainMap strategy for standardization, sharing, and meta-analysis of neuroimaging data. BMC Res Notes 4, 349. https://doi.org/10.1186/1756-0500-4-349

Laird, A.R., Eickhoff, S.B., Li, K., Robin, D.A., Glahn, D.C., Fox, P.T., 2009. Investigating the Functional Heterogeneity of the Default Mode Network Using Coordinate-Based Meta-Analytic Modeling. Journal of Neuroscience 29, 14496–14505. https://doi.org/10.1523/JNEUROSCI.4004-09.2009

Laird, A.R., Fox, P.M., Price, C.J., Glahn, D.C., Uecker, A.M., Lancaster, J.L., Turkeltaub, P.E., Kochunov, P., Fox, P.T., 2005. ALE meta-analysis: Controlling the false discovery rate and performing statistical contrasts. Hum. Brain Mapp. 25, 155–164. https://doi.org/10.1002/hbm.20136

Liu, X., Eickhoff, S.B., Hoffstaedter, F., Genon, S., Caspers, S., Reetz, K., Dogan, I., Eickhoff, C.R., Chen, J., Caspers, J., Reuter, N., Mathys, C., Aleman, A., Jardri, R., Riedl, V., Sommer, I.E., Patil, K.R., 2020. Joint Multi-modal Parcellation of the Human Striatum: Functions and Clinical Relevance. Neurosci Bull 36, 1123–1136. https://doi.org/10.1007/s12264-020-00543-1

Liu, Y., Han, T., Ma, S., Zhang, J., Yang, Y., Tian, J., He, H., Li, A., He, M., Liu, Z., Wu, Z., Zhao, L., Zhu, D., Li, X., Qiang, N., Shen, D., Liu, T., Ge, B., 2023. Summary of ChatGPT-Related research and perspective towards the future of large language models. Meta-Radiology 1, 100017. https://doi.org/10.1016/j.metrad.2023.100017

Luo, X., Rechardt, A., Sun, G., Nejad, K.K., Yáñez, F., Yilmaz, B., Lee, K., Cohen, A.O., Borghesani, V., Pashkov, A., Marinazzo, D., Nicholas, J., Salatiello, A., Sucholutsky, I., Minervini, P., Razavi, S., Rocca, R., Yusifov, E., Okalova, T., Gu, N., Ferianc, M., Khona, M., Patil, K.R., Lee, P.-S., Mata, R., Myers, N.E., Bizley, J.K., Musslick, S., Bilgin, I.P., Niso, G., Ales, J.M., Gaebler, M., Ratan Murty, N.A., Loued-Khenissi, L., Behler, A., Hall, C.M., Dafflon, J., Bao, S.D., Love, B.C., 2024. Large language models surpass human experts in predicting neuroscience results. Nat Hum Behav 1–11. https://doi.org/10.1038/s41562-024-02046-9

Marcus, D., Harwell, J., Olsen, T., Hodge, M., Glasser, M., Prior, F., Jenkinson, M., Laumann, T., Curtiss, S., Van Essen, D., 2011. Informatics and Data Mining Tools and Strategies for the Human

Connectome Project. Front. Neuroinform. 5. https://doi.org/10.3389/fninf.2011.00004

Markello, R.D., Hansen, J.Y., Liu, Z.-Q., Bazinet, V., Shafiei, G., Suárez, L.E., Blostein, N., Seidlitz, J., Baillet, S., Satterthwaite, T.D., Chakravarty, M.M., Raznahan, A., Misic, B., 2022. neuromaps: structural and functional interpretation of brain maps. https://doi.org/10.1101/2022.01.06.475081

McKinney, W., 2010. Data Structures for Statistical Computing in Python. Presented at the Python in Science Conference, Austin, Texas, pp. 56–61. https://doi.org/10.25080/Majora-92bf1922-00a

Mensch, A., Mairal, J., Bzdok, D., Thirion, B., Varoquaux, G., 2017. Learning Neural Representations of Human Cognition across Many fMRI Studies, in: Advances in Neural Information Processing Systems. Curran Associates, Inc.

Mensch, A., Mairal, J., Thirion, B., Varoquaux, G., 2021. Extracting representations of cognition across neuroimaging studies improves brain decoding. PLOS Computational Biology 17, e1008795. https://doi.org/10.1371/journal.pcbi.1008795

Menuet, R., Meudec, R., Dockès, J., Varoquaux, G., Thirion, B., 2022. Comprehensive decoding mental processes from Web repositories of functional brain images. Sci Rep 12, 7050. https://doi.org/10.1038/s41598-022-10710-1

Meudec, R., Dockès, J., Wassermann, D., Thirion, B., 2022. Peaks2Image: Reconstructing fMRI Statistical Maps from Peaks.

Meudec, R., Ghayem, F., Dockès, J., Wassermann, D., Thirion, B., 2024. NeuroConText: Contrastive Text-to-Brain Mapping for Neuroscientific Literature, in: Linguraru, M.G., Dou, Q., Feragen, A., Giannarou, S., Glocker, B., Lekadir, K., Schnabel, J.A. (Eds.), Medical Image Computing and Computer Assisted Intervention – MICCAI 2024. Springer Nature Switzerland, Cham, pp. 325–335. https://doi.org/10.1007/978-3-031-72384-1_31

Mitchell, T.M., Shinkareva, S.V., Carlson, A., Chang, K.-M., Malave, V.L., Mason, R.A., Just, M.A., 2008. Predicting Human Brain Activity Associated with the Meanings of Nouns. Science 320, 1191–1195. https://doi.org/10.1126/science.1152876

Ngo, G.H., Nguyen, M., Chen, N.F., Sabuncu, M.R., 2021. Text2Brain: Synthesis of Brain Activation Maps from Free-Form Text Query, in: de Bruijne, M., Cattin, P.C., Cotin, S., Padoy, N., Speidel, S., Zheng, Y., Essert, C. (Eds.), Medical Image Computing and Computer Assisted Intervention – MICCAI 2021. Springer International Publishing, Cham, pp. 605–614. https://doi.org/10.1007/978-3-030-87234-2_57

Nickl-Jockschat, T., Rottschy, C., Thommes, J., Schneider, F., Laird, A.R., Fox, P.T., Eickhoff, S.B., 2015. Neural networks related to dysfunctional face processing in autism spectrum disorder. Brain Struct Funct 220, 2355–2371. https://doi.org/10.1007/s00429-014-0791-z

Oord, A. van den, Li, Y., Vinyals, O., 2019. Representation Learning with Contrastive Predictive Coding. https://doi.org/10.48550/arXiv.1807.03748

Oudyk, K., Dockès, J., Peraza, J., Kent, J., Torabi, M., Wang, M., McPherson, B., Mirhakimi, N., Vega, A. de la, Laird, A.R., Poline, J.B., 2025. Meta all the way down: An overview of neuroimaging meta-analyses. https://doi.org/10.1101/2025.01.21.634094

Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., 2011. Scikit-learn: Machine Learning in Python. Journal of Machine Learning Research 12, 6.

Peraza, J.A., Kent, J.D., Blair, R.W., Poline, J.-B., Nichols, T.E., Vega, A. de la, Laird, A.R., 2025. Advancing image-based meta-analysis for fMRI: A framework for leveraging NeuroVault data. https://doi.org/10.1101/2025.03.06.641922

Peraza, J.A., Salo, T., Riedel, M.C., Bottenhorn, K.L., Poline, J.-B., Dockès, J., Kent, J.D., Bartley, J.E.,

Flannery, J.S., Hill-Bowen, L.D., Lobo, R.P., Poudel, R., Ray, K.L., Robinson, J.L., Laird, R.W., Sutherland, M.T., de la Vega, A., Laird, A.R., 2024. Methods for decoding cortical gradients of functional connectivity. Imaging Neuroscience 2, 1–32. https://doi.org/10.1162/imag_a_00081

Plachti, A., Eickhoff, S.B., Hoffstaedter, F., Patil, K.R., Laird, A.R., Fox, P.T., Amunts, K., Genon, S., 2019. Multimodal Parcellations and Extensive Behavioral Profiling Tackling the Hippocampus Gradient. Cereb Cortex 29, 4595–4612. https://doi.org/10.1093/cercor/bhy336

Poldrack, R.A., 2011. Inferring mental states from neuroimaging data: from reverse inference to large-scale decoding. Neuron 72, 692–697. https://doi.org/10.1016/j.neuron.2011.11.001

Poldrack, R.A., 2006. Can cognitive processes be inferred from neuroimaging data? Trends in Cognitive Sciences 10, 59–63. https://doi.org/10.1016/j.tics.2005.12.004

Poldrack, R.A., Kittur, A., Kalar, D., Miller, E., Seppa, C., Gil, Y., Parker, D.S., Sabb, F.W., Bilder, R.M., 2011. The cognitive atlas: toward a knowledge foundation for cognitive neuroscience. Front Neuroinform 5, 17. https://doi.org/10.3389/fninf.2011.00017

Radford, A., Kim, J.W., Hallacy, C., Ramesh, A., Goh, G., Agarwal, S., Sastry, G., Askell, A., Mishkin, P., Clark, J., Krueger, G., Sutskever, I., 2021. Learning Transferable Visual Models From Natural Language Supervision. https://doi.org/10.48550/arXiv.2103.00020

Rottschy, C., Caspers, S., Roski, C., Reetz, K., Dogan, I., Schulz, J.B., Zilles, K., Laird, A.R., Fox, P.T., Eickhoff, S.B., 2013. Differentiated parietal connectivity of frontal regions for "what" and "where" memory. Brain Struct Funct 218, 1551–1567. https://doi.org/10.1007/s00429-012-0476-4

Rubin, T., Koyejo, O.O., Jones, M.N., Yarkoni, T., 2016. Generalized Correspondence-LDA Models (GC-LDA) for Identifying Functional Regions in the Brain, in: NIPS'16 Proceedings of the 30th International Conference on Neural Information Processing Systems. Presented at the 29th Conference on Neural Information Processing Systems (NIPS 2016), Barcelona, Spain, pp. 1118–1126.

Rubin, T.N., Koyejo, O., Gorgolewski, K.J., Jones, M.N., Poldrack, R.A., Yarkoni, T., 2017. Decoding brain activity using a large-scale probabilistic functional-anatomical atlas of human cognition. PLOS Computational Biology 13, e1005649. https://doi.org/10.1371/journal.pcbi.1005649

Salo, T., Yarkoni, T., Nichols, T.E., Poline, J.-B., Bilgel, M., Bottenhorn, K.L., Jarecka, D., Kent, J.D., Kimbler, A., Nielson, D.M., Oudyk, K.M., Peraza, J.A., Pérez, A., Reeders, P.C., Yanes, J.A., Laird, A.R., 2023. NiMARE: Neuroimaging Meta-Analysis Research Environment. Aperture Neuro 3, 1–32. https://doi.org/10.52294/001c.87681

Salo, T., Yarkoni, T., Nichols, T.E., Poline, J.-B., Kent, J.D., Gorgolewski, K.J., Glerean, E., Bottenhorn, K.L., Bilgel, M., Wright, J., Reeders, P., Kimbler, A., Nielson, D.N., Yanes, J.A., Pérez, A., Oudyk, K.M., Jarecka, D., Enge, A., Peraza, J.A., Eickhoff, S.B., De La Vega, A., Liu, Z.-Q., Laird, A.R., 2024. neurostuff/NiMARE: 0.4.1. https://doi.org/10.5281/zenodo.14183422

Smith, S.M., Beckmann, C.F., Andersson, J., Auerbach, E.J., Bijsterbosch, J., Douaud, G., Duff, E., Feinberg, D.A., Griffanti, L., Harms, M.P., Kelly, M., Laumann, T., Miller, K.L., Moeller, S., Petersen, S., Power, J., Salimi-Khorshidi, G., Snyder, A.Z., Vu, A.T., Woolrich, M.W., Xu, J., Yacoub, E., Uğurbil, K., Van Essen, D.C., Glasser, M.F., 2013. Resting-state fMRI in the Human Connectome Project. NeuroImage, Mapping the Connectome 80, 144–168. https://doi.org/10.1016/j.neuroimage.2013.05.039

Smith, S.M., Fox, P.T., Miller, K.L., Glahn, D.C., Fox, P.M., Mackay, C.E., Filippini, N., Watkins, K.E., Toro, R., Laird, A.R., Beckmann, C.F., 2009. Correspondence of the brain's functional architecture during activation and rest. Proc. Natl. Acad. Sci. U.S.A. 106, 13040–13045. https://doi.org/10.1073/pnas.0905267106

Srivastava, A., Rastogi, A., Rao, A., Shoeb, A.A.M., Abid, A., Fisch, A., Brown, A.R., Santoro, A., Gupta, Aditya, Garriga-Alonso, A., Kluska, A., Lewkowycz, A., Agarwal, A., Power, A., Ray, A., Warstadt, A., Kocurek, A.W., Safaya, A., Tazarv, A., Xiang, A., Parrish, A., Nie, A., Hussain, A., Askell, A., Dsouza, A., Slone, A., Rahane, A., Iyer, A.S., Andreassen, A., Madotto, A., Santilli, A., Stuhlmüller, A., Dai, A., La, A., Lampinen, A., Zou, A., Jiang, A., Chen, A., Vuong, A., Gupta, Animesh, Gottardi, A., Norelli, A., Venkatesh, A., Gholamidavoodi, A., Tabassum, A., Menezes, A., Kirubarajan, A., Mullokandov, A., Sabharwal, A., Herrick, A., Efrat, A., Erdem, A., Karakaş, A., Roberts, B.R., Loe, B.S., Zoph, B., Bojanowski, B., Özyurt, B., Hedayatnia, B., Neyshabur, B., Inden, B., Stein, B., Ekmekci, B., Lin, B.Y., Howald, B., Orinion, B., Diao, C., Dour, C., Stinson, C., Argueta, C., Ramírez, C.F., Singh, C., Rathkopf, C., Meng, C., Baral, C., Wu, C., Callison-Burch, C., Waites, C., Voigt, C., Manning, C.D., Potts, C., Ramirez, C., Rivera, C.E., Siro, C., Raffel, C., Ashcraft, C., Garbacea, C., Sileo, D., Garrette, D., Hendrycks, D., Kilman, D., Roth, D., Freeman, D., Khashabi, D., Levy, D., González, D.M., Perszyk, D., Hernandez, D., Chen, Danqi, Ippolito, D., Gilboa, D., Dohan, D., Drakard, D., Jurgens, D., Datta, D., Ganguli, D., Emelin, D., Kleyko, D., Yuret, D., Chen, Derek, Tam, D., Hupkes, D., Misra, D., Buzan, D., Mollo, D.C., Yang, D., Lee, D.-H., Schrader, D., Shutova, E., Cubuk, E.D., Segal, E., Hagerman, E., Barnes, E., Donoway, E., Pavlick, E., Rodola, E., Lam, E., Chu, E., Tang, E., Erdem, E., Chang, E., Chi, E.A., Dyer, E., Jerzak, E., Kim, E., Manyasi, E.E., Zheltonozhskii, E., Xia, F., Siar, F., Martínez-Plumed, F., Happé, F., Chollet, F., Rong, F., Mishra, G., Winata, G.I., Melo, G. de, Kruszewski, G., Parascandolo, G., Mariani, G., Wang, G., Jaimovitch-López, G., Betz, G., Gur-Ari, G., Galijasevic, H., Kim, H., Rashkin, H., Hajishirzi, H., Mehta, H., Bogar, H., Shevlin, H., Schütze, H., Yakura, H., Zhang, H., Wong, H.M., Ng, I., Noble, I., Jumelet, J., Geissinger, J., Kernion, J., Hilton, J., Lee, J., Fisac, J.F., Simon, J.B., Koppel, J., Zheng, J., Zou, J., Kocoń, J., Thompson, J., Wingfield, J., Kaplan, J., Radom, J., Sohl-Dickstein, J., Phang, J., Wei, J., Yosinski, J., Novikova, J., Bosscher, J., Marsh, J., Kim, J., Taal, J., Engel, J., Alabi, J., Xu, J., Song, J., Tang, J., Waweru, J., Burden, J., Miller, J., Balis, J.U., Batchelder, J., Berant, J., Frohberg, J., Rozen, J., Hernandez-Orallo, J., Boudeman, J., Guerr, J., Jones, J., Tenenbaum, J.B., Rule, J.S., Chua, J., Kanclerz, K., Livescu, K., Krauth, K., Gopalakrishnan, K., Ignatyeva, K., Markert, K., Dhole, K.D., Gimpel, K., Omondi, K., Mathewson, K., Chiafullo, K., Shkaruta, K., Shridhar, K., McDonell, K., Richardson, K., Reynolds, L., Gao, L., Zhang, L., Dugan, L., Qin, L., Contreras-Ochando, L., Morency, L.-P., Moschella, L., Lam, L., Noble, L., Schmidt, L., He, L., Colón, L.O., Metz, L., Şenel, L.K., Bosma, M., Sap, M., Hoeve, M. ter, Farooqi, M., Faruqui, M., Mazeika, M., Baturan, M., Marelli, M., Maru, M., Quintana, M.J.R., Tolkiehn, M., Giulianelli, M., Lewis, M., Potthast, M., Leavitt, M.L., Hagen, M., Schubert, M., Baitemirova, M.O., Arnaud, M., McElrath, M., Yee, M.A., Cohen, M., Gu, M., Ivanitskiy, M., Starritt, M., Strube, M., Swędrowski, M., Bevilacqua, M., Yasunaga, M., Kale, M., Cain, M., Xu, M., Suzgun, M., Walker, M., Tiwari, M., Bansal, M., Aminnaseri, M., Geva, M., Gheini, M., T, M.V., Peng, N., Chi, N.A., Lee, N., Krakover, N.G.-A., Cameron, N., Roberts, N., Doiron, N., Martinez, N., Nangia, N., Deckers, N., Muennighoff, N., Keskar, N.S., Iyer, N.S., Constant, N., Fiedel, N., Wen, N., Zhang, O., Agha, O., Elbaghdadi, O., Levy, O., Evans, O., Casares, P.A.M., Doshi, P., Fung, P., Liang, P.P., Vicol, P., Alipoormolabashi, P., Liao, P., Liang, P., Chang, P., Eckersley, P., Htut, P.M., Hwang, P., Miłkowski, P., Patil, P., Pezeshkpour, P., Oli, P., Mei, Q., Lyu, Q., Chen, Q., Banjade, R., Rudolph, R.E., Gabriel, R., Habacker, R., Risco, R., Millière, R., Garg, R., Barnes, R., Saurous, R.A., Arakawa, R., Raymaekers, R., Frank, R., Sikand, R., Novak, R., Sitelew, R., LeBras, R., Liu, R., Jacobs, R., Zhang, R., Salakhutdinov, R., Chi, R., Lee, R., Stovall, R., Teehan, R., Yang, R., Singh, Sahib, Mohammad, S.M., Anand, S., Dillavou, S., Shleifer, S., Wiseman, S., Gruetter, S., Bowman, S.R., Schoenholz, S.S., Han, S., Kwatra, S., Rous,

S.A., Ghazarian, S., Ghosh, S., Casey, S., Bischoff, S., Gehrmann, S., Schuster, S., Sadeghi, S., Hamdan, S., Zhou, S., Srivastava, S., Shi, S., Singh, Shikhar, Asaadi, S., Gu, S.S., Pachchigar, S., Toshniwal, S., Upadhyay, S., Shyamolima, Debnath, Shakeri, S., Thormeyer, S., Melzi, S., Reddy, S., Makini, S.P., Lee, S.-H., Torene, S., Hatwar, S., Dehaene, S., Divic, S., Ermon, S., Biderman, S., Lin, S., Prasad, S., Piantadosi, S.T., Shieber, S.M., Misherghi, S., Kiritchenko, S., Mishra, S., Linzen, T., Schuster, T., Li, T., Yu, T., Ali, T., Hashimoto, T., Wu, T.-L., Desbordes, T., Rothschild, T., Phan, T., Wang, T., Nkinyili, T., Schick, T., Kornev, T., Tunduny, T., Gerstenberg, T., Chang, T., Neeraj, T., Khot, T., Shultz, T., Shaham, U., Misra, V., Demberg, V., Nyamai, V., Raunak, V., Ramasesh, V., Prabhu, V.U., Padmakumar, V., Srikumar, V., Fedus, W., Saunders, W., Zhang, W., Vossen, W., Ren, X., Tong, X., Zhao, X., Wu, X., Shen, X., Yaghoobzadeh, Y., Lakretz, Y., Song, Y., Bahri, Y., Choi, Y., Yang, Y., Hao, Y., Chen, Y., Belinkov, Y., Hou, Yu, Hou, Yufang, Bai, Y., Seid, Z., Zhao, Z., Wang, Zijian, Wang, Z.J., Wang, Zirui, Wu, Z., 2023. Beyond the Imitation Game: Quantifying and extrapolating the capabilities of language models. https://doi.org/10.48550/arXiv.2206.04615

Thompson, P.M., Stein, J.L., Medland, S.E., Hibar, D.P., Vasquez, A.A., Renteria, M.E., Toro, R., Jahanshad, N., Schumann, G., Franke, B., Wright, M.J., Martin, N.G., Agartz, I., Alda, M., Alhusaini, S., Almasy, L., Almeida, J., Alpert, K., Andreasen, N.C., Andreassen, O.A., Apostolova, L.G., Appel, K., Armstrong, N.J., Aribisala, B., Bastin, M.E., Bauer, M., Bearden, C.E., Bergmann, O., Binder, E.B., Blangero, J., Bockholt, H.J., Bøen, E., Bois, C., Boomsma, D.I., Booth, T., Bowman, I.J., Bralten, J., Brouwer, R.M., Brunner, H.G., Brohawn, D.G., Buckner, R.L., Buitelaar, J., Bulayeva, K., Bustillo, J.R., Calhoun, V.D., Cannon, D.M., Cantor, R.M., Carless, M.A., Caseras, X., Cavalleri, G.L., Chakravarty, M.M., Chang, K.D., Ching, C.R.K., Christoforou, A., Cichon, S., Clark, V.P., Conrod, P., Coppola, G., Crespo-Facorro, B., Curran, J.E., Czisch, M., Deary, I.J., de Geus, E.J.C., den Braber, A., Delvecchio, G., Depondt, C., de Haan, L., de Zubicaray, G.I., Dima, D., Dimitrova, R., Djurovic, S., Dong, H., Donohoe, G., Duggirala, R., Dyer, T.D., Ehrlich, S., Ekman, C.J., Elvsåshagen, T., Emsell, L., Erk, S., Espeseth, T., Fagerness, J., Fears, S., Fedko, I., Fernández, G., Fisher, S.E., Foroud, T., Fox, P.T., Francks, C., Frangou, S., Frey, E.M., Frodl, T., Frouin, V., Garavan, H., Giddaluru, S., Glahn, D.C., Godlewska, B., Goldstein, R.Z., Gollub, R.L., Grabe, H.J., Grimm, O., Gruber, O., Guadalupe, T., Gur, R.E., Gur, R.C., Göring, H.H.H., Hagenaars, S., Hajek, T., Hall, G.B., Hall, J., Hardy, J., Hartman, C.A., Hass, J., Hatton, S.N., Haukvik, U.K., Hegenscheid, K., Heinz, A., Hickie, I.B., Ho, B.-C., Hoehn, D., Hoekstra, P.J., Hollinshead, M., Holmes, A.J., Homuth, G., Hoogman, M., Hong, L.E., Hosten, N., Hottenga, J.-J., Hulshoff Pol, H.E., Hwang, K.S., Jack, C.R., Jenkinson, M., Johnston, C., Jönsson, E.G., Kahn, R.S., Kasperaviciute, D., Kelly, S., Kim, S., Kochunov, P., Koenders, L., Krämer, B., Kwok, J.B.J., Lagopoulos, J., Laje, G., Landen, M., Landman, B.A., Lauriello, J., Lawrie, S.M., Lee, P.H., Le Hellard, S., Lemaître, H., Leonardo, C.D., Li, C.-S., Liberg, B., Liewald, D.C., Liu, X., Lopez, L.M., Loth, E., Lourdusamy, A., Luciano, M., Macciardi, F., Machielsen, M.W.J., Macqueen, G.M., Malt, U.F., Mandl, R., Manoach, D.S., Martinot, J.-L., Matarin, M., Mather, K.A., Mattheisen, M., Mattingsdal, M., Meyer-Lindenberg, A., McDonald, C., McIntosh, A.M., McMahon, F.J., McMahon, K.L., Meisenzahl, E., Melle, I., Milaneschi, Y., Mohnke, S., Montgomery, G.W., Morris, D.W., Moses, E.K., Mueller, B.A., Muñoz Maniega, S., Mühleisen, T.W., Müller-Myhsok, B., Mwangi, B., Nauck, M., Nho, K., Nichols, T.E., Nilsson, L.-G., Nugent, A.C., Nyberg, L., Olvera, R.L., Oosterlaan, J., Ophoff, R.A., Pandolfo, M., Papalampropoulou-Tsiridou, M., Papmeyer, M., Paus, T., Pausova, Z., Pearlson, G.D., Penninx, B.W., Peterson, C.P., Pfennig, A., Phillips, M., Pike, G.B., Poline, J.-B., Potkin, S.G., Pütz, B., Ramasamy, A., Rasmussen, J., Rietschel, M., Rijpkema, M., Risacher, S.L., Roffman, J.L.,

Roiz-Santiañez, R., Romanczuk-Seiferth, N., Rose, E.J., Royle, N.A., Rujescu, D., Ryten, M., Sachdev, P.S., Salami, A., Satterthwaite, T.D., Savitz, J., Saykin, A.J., Scanlon, C., Schmaal, L., Schnack, H.G., Schork, A.J., Schulz, S.C., Schür, R., Seidman, L., Shen, L., Shoemaker, J.M., Simmons, A., Sisodiya, S.M., Smith, C., Smoller, J.W., Soares, J.C., Sponheim, S.R., Sprooten, E., Starr, J.M., Steen, V.M., Strakowski, S., Strike, L., Sussmann, J., Sämann, P.G., Teumer, A., Toga, A.W., Tordesillas-Gutierrez, D., Trabzuni, D., Trost, S., Turner, J., Van den Heuvel, M., van der Wee, N.J., van Eijk, K., van Erp, T.G.M., van Haren, N.E.M., van 't Ent, D., van Tol, M.-J., Valdés Hernández, M.C., Veltman, D.J., Versace, A., Völzke, H., Walker, R., Walter, H., Wang, L., Wardlaw, J.M., Weale, M.E., Weiner, M.W., Wen, W., Westlye, L.T., Whalley, H.C., Whelan, C.D., White, T., Winkler, A.M., Wittfeld, K., Woldehawariat, G., Wolf, C., Zilles, D., Zwiers, M.P., Thalamuthu, A., Schofield, P.R., Freimer, N.B., Lawrence, N.S., Drevets, W., Alzheimer's Disease Neuroimaging Initiative, EPIGEN Consortium, IMAGEN Consortium, Saguenay Youth Study (SYS) Group, 2014. The ENIGMA Consortium: large-scale collaborative analyses of neuroimaging and genetic data. Brain Imaging Behav 8, 153–182. https://doi.org/10.1007/s11682-013-9269-5

Touvron, H., Martin, L., Stone, K., Albert, P., Almahairi, A., Babaei, Y., Bashlykov, N., Batra, S., Bhargava, P., Bhosale, S., Bikel, D., Blecher, L., Ferrer, C.C., Chen, M., Cucurull, G., Esiobu, D., Fernandes, J., Fu, J., Fu, W., Fuller, B., Gao, C., Goswami, V., Goyal, N., Hartshorn, A., Hosseini, S., Hou, R., Inan, H., Kardas, M., Kerkez, V., Khabsa, M., Kloumann, I., Korenev, A., Koura, P.S., Lachaux, M.-A., Lavril, T., Lee, J., Liskovich, D., Lu, Y., Mao, Y., Martinet, X., Mihaylov, T., Mishra, P., Molybog, I., Nie, Y., Poulton, A., Reizenstein, J., Rungta, R., Saladi, K., Schelten, A., Silva, R., Smith, E.M., Subramanian, R., Tan, X.E., Tang, B., Taylor, R., Williams, A., Kuan, J.X., Xu, P., Yan, Z., Zarov, I., Zhang, Y., Fan, A., Kambadur, M., Narang, S., Rodriguez, A., Stojnic, R., Edunov, S., Scialom, T., 2023. Llama 2: Open Foundation and Fine-Tuned Chat Models. https://doi.org/10.48550/arXiv.2307.09288

Uğurbil, K., Xu, J., Auerbach, E.J., Moeller, S., Vu, A.T., Duarte-Carvajalino, J.M., Lenglet, C., Wu, X., Schmitter, S., Van de Moortele, P.F., Strupp, J., Sapiro, G., De Martino, F., Wang, D., Harel, N., Garwood, M., Chen, L., Feinberg, D.A., Smith, S.M., Miller, K.L., Sotiropoulos, S.N., Jbabdi, S., Andersson, J.L.R., Behrens, T.E.J., Glasser, M.F., Van Essen, D.C., Yacoub, E., 2013. Pushing spatial and temporal resolution for functional and diffusion MRI in the Human Connectome Project. NeuroImage, Mapping the Connectome 80, 80–104. https://doi.org/10.1016/j.neuroimage.2013.05.012

van der Walt, S., Colbert, S.C., Varoquaux, G., 2011. The NumPy Array: A Structure for Efficient Numerical Computation. Computing in Science Engineering 13, 22–30. https://doi.org/10.1109/MCSE.2011.37

Van Essen, D.C., Smith, S.M., Barch, D.M., Behrens, T.E.J., Yacoub, E., Ugurbil, K., 2013. The WU-Minn Human Connectome Project: An overview. NeuroImage, Mapping the Connectome 80, 62–79. https://doi.org/10.1016/j.neuroimage.2013.05.041

Van Essen, D.C., Ugurbil, K., Auerbach, E., Barch, D., Behrens, T.E.J., Bucholz, R., Chang, A., Chen, L., Corbetta, M., Curtiss, S.W., Della Penna, S., Feinberg, D., Glasser, M.F., Harel, N., Heath, A.C., Larson-Prior, L., Marcus, D., Michalareas, G., Moeller, S., Oostenveld, R., Petersen, S.E., Prior, F., Schlaggar, B.L., Smith, S.M., Snyder, A.Z., Xu, J., Yacoub, E., 2012. The Human Connectome Project: A data acquisition perspective. NeuroImage, Connectivity 62, 2222–2231. https://doi.org/10.1016/j.neuroimage.2012.02.018

Varoquaux, G., Schwartz, Y., Poldrack, R.A., Gauthier, B., Bzdok, D., Poline, J.-B., Thirion, B., 2018. Atlases of cognition with large-scale human brain mapping. PLOS Computational Biology 14,

e1006565. https://doi.org/10.1371/journal.pcbi.1006565

Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A.N., Kaiser, Ł. ukasz, Polosukhin, I., 2017. Attention is All you Need, in: Advances in Neural Information Processing Systems. Curran Associates, Inc.

Virtanen, P., Gommers, R., Oliphant, T.E., Haberland, M., Reddy, T., Cournapeau, D., Burovski, E., Peterson, P., Weckesser, W., Bright, J., Walt, S.J. van der, Brett, M., Wilson, J., Millman, K.J., Mayorov, N., Nelson, A.R.J., Jones, E., Kern, R., Larson, E., Carey, C.J., Polat, İ., Feng, Y., Moore, E.W., VanderPlas, J., Laxalde, D., Perktold, J., Cimrman, R., Henriksen, I., Quintero, E.A., Harris, C.R., Archibald, A.M., Ribeiro, A.H., Pedregosa, F., Mulbregt, P. van, 2020. SciPy 1.0: fundamental algorithms for scientific computing in Python. Nat Methods 1–12. https://doi.org/10.1038/s41592-019-0686-2

Wager, T.D., Lindquist, M., Kaplan, L., 2007. Meta-analysis of functional neuroimaging data: current and future directions. Social Cognitive and Affective Neuroscience 2, 150–158. https://doi.org/10.1093/scan/nsm015

Waskom, M.L., 2021. seaborn: statistical data visualization. Journal of Open Source Software 6, 3021. https://doi.org/10.21105/joss.03021

Yarkoni, T., Poldrack, R.A., Nichols, T.E., Van Essen, D.C., Wager, T.D., 2011. Large-scale automated synthesis of human functional neuroimaging data. Nature Methods 8, 665–670. https://doi.org/10.1038/nmeth.1635

Yarkoni, T., Salo, T., Peraza, J.A., Nichols, T.E., 2024. neurostuff/PyMARE: 0.0.8. https://doi.org/10.5281/zenodo.13743687